

This page last changed on Jan 10, 2008 by [jjerney](#).

[edocs Home](#) > [BEA AquaLogic Data Services Platform 3.0 Documentation](#) > [Data Services Developer's Guide](#)

ALDSP 3.0 Release Notes

AquaLogic Data Services Platform provides read and write access to information in relational databases, web services, Java functions, XML files, delimited files, and other types of disparate data.

Once developed, application developers — using access technologies such as the ALDSP mediator API, JDBC, SQL, or Workshop controls — can invoke ALDSP operations as a means of providing their applications with access to integrated, updateable data from their enterprise.

Metadata, security, and cache management facilities are provided through the Data Services Platform Console (dspconsole).

**Note:**

BEA AquaLogic (R) Data Services Platform was originally named Liquid Data for WebLogic (R). Some artifacts of the original name remain in the product, path, and other artifacts.

Contents

- [Revision Policy](#)
- [Product Installation and Upgrade](#)
- [Product Support Information](#)
- [Product Limitations and Workarounds](#)

Revision Policy

AquaLogic Data Services Platform Release Notes is subject to revision between releases. The most recent version can always be found at:



<http://edocs.bea.com/aldsp/docs30/relnotes/relnotes.html>

For assistance in tracking unresolved issues please contact [BEA Customer Support](#).

What's New?



<http://edocs.bea.com/aldsp/docs30/dsp30wiki/what's%20new.html>

Product Installation and Upgrade

Product Support Information

Supported Configurations

For support information on vendor operating systems, JDK, and hardware support, see [Supported Configurations for BEA AquaLogic Data Services Platform 3.0](#).

Client Support

For this release, client applications are supported on the following JDKs:

- BEA JRockit 1.4.2 and Sun 1.4.2
- BEA JRockit 5.0 and Sun 5.0

Supported Interoperability Products

This section describes the following interoperability products that are supported for use with ALDSP 3.0:

- WebLogic Integration 9.2 (WLI to ALDSP only)
- WebLogic Portal 9.2 and 10.0 (WLP to ALDSP only)
- AquaLogic Service Bus 2.6 and higher RPs
- AquaLogic Enterprise Security 3.0
- AquaLogic Enterprise Repository 3.0.0.2

JDBC Driver Support for Reporting Tools

The following section provides information on JDBC driver support for reporting applications used with the AquaLogic Data Services Platform 3.0 JDBC driver:

Application and Version	JDBC Native	OpenLink ODBC/JDBC Lite Bridge
Crystal Reports XI	Supported	
Business Objects XI, Release 2		Supported
Hyperion BI 9+, Interactive Reporting		Supported
Microsoft Access 2000		Supported
Microsoft Excel 2000		Supported

Standards Support

The following Web services standards supported for this release:

Standards	Version
SOAP	1.1, 1.2
WSDL	1.1
JAX-RPC	1.1
SDO	2.1
XML Schema	1.0
Xquery	July 2004 Draft

Product Limitations and Workarounds

This section lists known limitations associated with the current BEA ALDSP release that users may encounter. Information regarding these limitations includes:

- A CR (change request) number for each issue.
- Applicable platform.
- Detailed description of the problem and workarounds, where applicable.
- Date, if the item is added or changed after the general availability release of the product.

Known Product Limitations and Possible Workarounds

CR357732	Unable to start the AquaLogic Data Services Platform 3.0 sample domain from the QuickStart page.
Platform	All.
Description	<p>When attempting to launch the ALDSP 3.0 sample domain by clicking the "Start AquaLogic Data Services Platform 3.0" link on the QuickStart page, a pop-up window appears displaying the following message:</p> <div> <p>The link to this application has not been implemented yet. Check this out later!</p> </div>
Workaround	Click Start -> BEA Products -> BEA AquaLogic Data Services Platform -> Examples -> Start Examples Server to start the sample domain.
CR258884	Security filter decisions are not audited.
Platform	All.
Description	Security filter decisions (XQuery functions for security) are not audited.
Workaround	None.
CR345482	Hyperion Interactive Reporting System is not supported.
Platform	All.

Description	ALDSP 3.0 does not support the Hyperion Interactive Reporting System.
Workaround	None.
CR339279	Upgrading ALDSP 2.5 projects that include multibyte characters may generate errors and produce garbled characters.
Platform	All.
Description	<p>When upgrading an ALDSP 2.5 project that includes multibyte characters to ALDSP 3.0, the following error may appear in the log view:</p> <div>'Some characters cannot be mapped'</div> <p>Similarly, when opening the updated data service file, the following error may appear:</p> <div>'Exception Message: 'Some characters cannot be mapped 'MS932'</div> <p>Garbled characters may also appear in the data service file.</p>
Workaround	The data service file was properly upgraded. Reopen the data service file to have the multibyte characters appear properly.
CR266307	Namespace URIs can become invalid when using file and folder names containing embedded spaces.
Platform	All.
Description	ALDSP does not support file and folder names containing one or more embedded spaces. This can cause namespace URIs to become invalid during certain operations such as a Refactor > Move and Refactor > Rename, among others.
Workaround	Do not create file or folder names containing embedded spaces.
CR350103	ALDSP license changes unexpectedly after installing a new version.
Platform	All.
Description	<p>ALDSP uses the first license found in the AquaLogic Data Services Platform license group (in the license.bea file). If you install multiple versions of ALDSP, your license may change unexpectedly because of the order of the licenses, as shown in the following segment:</p> <div> <pre><license-group format='1.0' product='AquaLogic Data Services Platform' release='3.0'> <license</pre> </div>

	<pre> component='Data Services Runtime' cpus='unvalued' expiration='2008-01-28' ip='any' licensee='BEA Evaluation Customer' signature='ZgOAWQ...' type='EVAL' units='5' /> <license component='Data Services Runtime' cpus='unvalued' expiration='2008-06-04' ip='any' licensee='BEA Evaluation Customer' serial='616351266349-2343532799844' signature='MC4CFQ...' type='EVAL' units='unlimited' /> </license-group> </pre>
	<p>Note that in this example, the number of "units" in the license changes from an unlimited number to five.</p>
Workaround	<p>If you have multiple versions of ALDSP installed, do the following:</p> <ol style="list-style-type: none"> 1. Verify that the most flexible license appears first in the AquaLogic Data Services Platform license group (in the license.bea file). 2. Restart the server.
CR346860	<p>ALDSP 2.5 SDOGen Web service clients need additional steps to run in backward compatibility mode.</p>
Platform	ALDSP 2.5
Description	ALDSP 2.5 Web service clients that use static SDOGen do not work out-of-the-box after the ALDSP server and the DSP Control/JWS is source upgraded.
Workaround	<p>To use static SDOGen Web service clients, do the following:</p> <ol style="list-style-type: none"> 1. In the source upgraded JWS file, modify the portName attribute of the @WLHttpTransport annotation and ensure that it matches the entry present in the 8.1 generated WSDL. 2. Generate the WSDL file for the JWS and save the file to a local disk. 3. Remove the parameterOrder attribute from the WSDL file. 4. Use the saved WSDL file in the client instead of the WSDL file dynamically available from the JWS. <p>For example, consider the following WebLogic 8.1 call:</p>

	<pre>String wsdl = 'http://acme/services/CustReadCtrlTest.jws?WSDL'weblogic. soapCtrl = new weblogic.jws.proxies.CustReadCtrlTest_Impl(wsdl).getCustR</pre> <p>Modify the statement to match the following:</p> <pre>String wsdl ='file:///local/services/CustReadCtrlTest.wsdl';weblogic soapCtrl = new weblogic.jws.proxies.CustReadCtrlTest_Impl(wsdl).getCustR</pre>
CR351310, CR351492	Missing entries in the generation log.
Platform	All.
Description	The generation log may not contain entries for target entities that cannot be updated. In this case, the update map may be incomplete.
Workaround	None.
CR337329	Running ALDSP 3.0 in the same domain as WebLogic Integration (WLI) 9.2 can cause conflicts.
Platform	ALDSP 3.0 and WebLogic Integration 9.2
Description	ALDSP 3.0 and WLI 9.2 install incompatible versions of the xquery.jar file. The software installed by ALDSP 3.0 is a newer version and is not certified for use with WLI 9.2.
Workaround	Do not create a domain that is provisioned for ALDSP 3.0 and WebLogic Integration 9.2.
CR354314	Changes made to multiple dataspace in a single session do not apply to all dataspace at runtime.
Platform	All.
Description	After acquiring a lock for a session, making changes to multiple dataspace, and committing the session, the changes are reflected only in a single dataspace. Restarting WebLogic Server causes the changes to be reflected in all modified dataspace.
Workaround	Make changes to only a single dataspace during a session. After committing the session, start a new session to make changes to another dataspace.
CR344413	Importing an AquaLogic Service Bus (ALSB) SB proxy or accessing an ALSB SB proxy physical data service requires the ALSB sbresource servlet to be available.

Platform	All.
Description	When importing web services that are routed through an ALSB SB proxy, ALDSP requests the SB proxy WSDL through the ALSB sbresource servlet. Similarly, when accessing a physical data service that was created using the ALSB SB proxy, the ALDSP runtime retrieves the SB proxy WSDL through the ALSB sbresource servlet. Both operations require that the ALSB sbresource servlet be available and running.
Workaround	Ensure that the ALSB sbresource servlet is deployed and running.
CR343216	Oracle timestamp with time zone returns an incorrect value.
Platform	Oracle 9i (using the BEA Oracle JDBC driver).
Description	The timestamp (with time zone) returned using the BEA Oracle JDBC driver may be incorrect.
Workaround	Use the native Oracle JDBC driver.
CR341851	An upgraded JWS that returns an XMLBean type will not compile.
Platform	Workshop for WebLogic Platform 9.2.2
Description	<p>All operations on an upgraded JWS that returns an XMLBean type will have a compile error similar to the following after the upgrade:</p> <div data-bbox="837 1220 1409 1294" data-label="Text"> <pre>The name 'getCustomerByIdResult' specified in javax.jws.WebResult is different to the XmlBean name of 'CUSTOMER'</pre> </div> <p>The message indicates that the return type does not match the element name defined by the XMLBean schema.</p>
Workaround	Remove the @WebResult annotation or change the name to match the schema type.
CR338622	Test View in ALDSP does not perform full XML Schema validation of the results of an operation.
Platform	All.
Description	Schema validation behavior has changed from ALDSP 2.x to ALDSP 3.0. Using ALDSP 2.x, schema validation occurs on the query return. In ALDSP 3.0, the validation is performed at the SDO structural level and does not constitute a full schema validation.
Workaround	During testing, temporarily wrap the function body using the XQuery validate construct to validate the

	<p>results of calling the function against the XML Schema, as shown in the following example:</p> <pre> validate { xquery expression } </pre>
CR342747	Crystal Reports is unable to use read functions (accepting no parameters) published as stored procedures.
Platform	Crystal Reports (using the JDBC driver).
Description	<p>Using a read function (accepting no parameters) published as a stored procedure with Crystal Reports generates an exception similar to the following:</p> <pre> java.sql.SQLException: Invalid stored procedure reference: ReportingToolCertDataServices.Xtreme.'Read at com.bea.dsp.jdbc.exceptions.DSPExceptionFactory.create(DS at com.bea.dsp.jdbc.driver.CallableDSPStatementImpl.updateWi </pre>
Workaround	Publish the read function without parameters as a table instead of a stored procedure.
CR345630	The ALDSP 2.5 server side streaming API cannot be used in ALDSP 3.0 without modification.
Platform	All.
Description	<p>In ALDSP 2.5, the streaming API is available on the server side only when used in the same ALDSP 2.5 application as a local Mediator API client. ALDSP 3.0, however, no longer uses the J2EE deployment model for dataspace deployment. As a result, a client using the ALDSP 2.5 streaming API cannot be deployed inside an ALDSP 3.0 dataspace. Doing so results in the following exception:</p> <pre> javax.naming.LinkException. </pre>
Workaround	ALDSP 3.0 supports the streaming API for all Java Mediator API clients (remote and local). Modify the streaming API client code to use the ALDSP 3.0 Java Mediator API and use the streaming facility in this API.
CR317803	Unable to display data lineage graph using the Metadata Browser with Netscape 8.1.
Platform	Microsoft Windows, Netscape 8.1
Description	When using Netscape 8.1, clicking the Data

	Lineage tab in the Metadata Browser may not display the data lineage graph nor prompt to download and install the SVG viewer.
Workaround	<p>To view data lineage graphs using Netscape 8.1, do the following:</p> <ol style="list-style-type: none"> 1. Close the Netscape browser. 2. Download and install SVG viewer plug-in. 3. Copy the NPSVG3.dll file to the <NetscapeHome>/plugins folder. 4. Restart the Netscape browser. <p>Alternatively, you can use the tabular view of the Metadata Browser to display the data lineage.</p>
CR343348	The fn:doc() and fn-bea:collection() functions cannot be accessed using the client API.
Platform	All.
Description	ALDSP 3.0 does not offer access to the fn:doc() and fn-bea:collection() functions through the client API. These functions can cause security vulnerabilities and are therefore blocked from client access. The functions are, however, available for use within data service XQuery bodies.
Workaround	None.
CR318031	The Eclipse IDE displays the following error message: "An out of memory error has occurred."
Platform	All.
Description	<p>When working with the Eclipse IDE, an "Internal Error" dialog appears displaying the following error message:</p> <p>"An out of memory error has occurred...Do you want to exit the workbench?"</p>
Workaround	<p>Do the following:</p> <ol style="list-style-type: none"> 1. Edit the configuration file. When using the Data Service Studio to launch Eclipse, edit the \$<ALDSP_HOME>/bin/aldsp.ini file. When using Eclipse independent of Data Service Studio, edit the eclipse.ini file. 2. Specify the following memory parameters for the Eclipse IDE: <pre> -vm <JDK_home>/jre/bin/java.exe -clean -vmargs -Xms256m </pre>

	<div> Xmx1024m XX:PermSize=128m </div>
CR347480	Upgrading an application to ALDSP 3.0 may produce the following error message: "This project needs to migrate WTP metadata."
Platform	All.
Description	<p>When upgrading an application from ALDSP 2.5 to ALDSP 3.0, the following error may appear under the Problems tab:</p> <div>This project needs to migrate WTP metadata</div>
Workaround	<p>This is an Eclipse error and can occur independent of ALDSP. Do the following:</p> <ol style="list-style-type: none"> 1. Using Data Services Studio, rename the project. 2. Select the project in the Project Explorer and choose Project->Build Automatically from the main menu to toggle the feature off. 3. Select the project in the Project Explorer and choose Project->Clean from the main menu. 4. Close and relaunch Data Services Studio. 5. Optionally, rename the project to the original name. 6. Select the project in the Project Explorer and choose Project->Build Automatically from the main menu to toggle the feature on.
CR347074	Changes to the database definition are not reflected in PreparedStatement calls or in the data service after updating the metadata.
Platform	All.
Description	<p>SQL queries use the PreparedStatement interface which, by default, is cached by the WebLogic Server. The default JDBC PreparedStatement cache size for is 10.</p> <p>This can result in incorrect prepared statements being used from the cache when database table or column definitions have changed between prepared statement calls.</p>
Workaround	<p>Set the PreparedStatement cache size to 0 when the database table definitions are changed. Using the WebLogic Server Administration Console, do the following:</p> <ol style="list-style-type: none"> 1. Click to expand the Services, JDBC, and Connection Pool nodes to display the list of connection pools in the current domain.

	<ol style="list-style-type: none"> Click the connection pool that you want to configure. A dialog displays in the right pane showing the tabs associated with this instance. Click the Configuration tab, then click the Connections tab. In Statement Cache Size, enter zero (0) for the number of statements to cache per connection per connection pool instance. Click Apply to save your changes.
CR297695	An "optimistic locking failure" exception can occur if Oracle checks for an empty string when the actual value is null.
Platform	Oracle
Description	<p>Oracle stores both empty strings and null strings as NULL, and both are always returned as NULL which may cause an optimistic locking error during an update operation. Consider the following mapping:</p> <pre><SomeElement>{ data(\$db_row/VARCHAR_COLUMN)}</SomeElement></pre> <p>where VARCHAR_COLUMN is a database column of VARCHAR type. In this case, the element is always created even when the column value is NULL. An SDO mapping would therefore map an empty element to the empty string value "".</p> <p>When the updated element is submitted to the database, the following exception occurs: DataServiceException: Optimistic locking failure The exception occurs because the DSP-generated SQL statements instruct Oracle to check for an empty string when the actual value is NULL.</p>
Workaround	<p>Map the column to an optional element, as shown in the following:</p> <pre><SomeElement?>{ data(\$db_row/VARCHAR_COLUMN)}</SomeElement></pre> <p>This ensures that the element is not created if the column value is NULL.</p>
CR345834	Expensive functions in LET clauses, such as calls to web services, may be invoked multiple times resulting in degraded performance.
Platform	All.
Description	XQuery 3.0 inlines LET clauses that are used only once. This can affect the number of times an expensive function, such as a web service, is called.

	<p>For example, consider the following query:</p> <pre> declare function tns:test(\$id1 as xs:string, \$id2 as xs:string){ let \$order1 := tes:getOrder(\$id1)/OrderDetail let \$order2 := for \$x in tes:getOrder(\$id2)/OrderDetail return <ORDER> <ORDER_ID>{fn:data(\$x/stns:orderId)}</ORDER_ID> </ORDER> for \$o1 in \$order1 return <ORDER> <ORDER_ID>{fn:data(\$o1/stns:orderId)}</ORDER_ID> <ORDER_DATE>{fn:data(\$o1/stns:orderDate)}</ORDER_DATE> <TOTAL_ORDER_AMOUNT> { fn:data(\$o1/stns:totalOrderAmount) }</TOTAL_ORDER_AMOUNT> <STATUS> { \$order2[\$o1/stns:orderDate = \$o1/stns:estimatedShipDate] }</STATUS> </ORDER> }; </pre> <p>In this example, ALDSP 3.0 inlines both \$order1 and \$order2 since each are used only once after being defined. This causes the system to perform repeated evaluations of the web service calls as part of the FOR clause (instead of retrieving the saved values from the variables) resulting in degraded performance.</p>
Workaround	<p>Configure ALDSP to prevent the inlining of expensive LET clauses in loops by doing the following:</p> <ol style="list-style-type: none"> 1. Set the following system property to false: <div> weblogic.xml.query.compiler.INLINE_SINGLE_EXPENSIVE_LETS_ </div> 2. Restart the WebLogic Server. By default this property is set to true (which is also the default behavior of ALDSP 2.5).
CR314392	An exception occurs when deploying an ALDSP 3.0 application generated using Workshop for WebLogic 9.2 MP1 or earlier.
Platform	ALDSP 3.0, Workshop for WebLogic 9.2 MP1 or earlier.
Description	<p>An exception can occur when deploying an ALDSP 3.0 application (using the Admin Console) using a WSDL file generated from Workshop for WebLogic 9.2 MP1 or earlier.</p> <p>ALDSP does not support WSDL files generated using Workshop for WebLogic 9.2 MP1 or earlier.</p>
Workaround	Generate the WSDL using Workshop for WebLogic

	9.2 MP2 and then rebuild and redeploy the application.
CR321293	The server is unable to locate a referenced schema file specified using the Eclipse XSD Editor.
Platform	Eclipse XSD Editor on Microsoft Windows
Description	<p>Microsoft Windows does not distinguish case in file and folder names.</p> <p>Therefore, the Eclipse XSD Editor on Microsoft Windows will not flag an error when you specify a schema file name using incorrect case. For example, the editor will not flag the following entry when the actual schema file name is ProfileView.xsd:</p> <pre><xsd:import namespace="urn:test" schemaLocation="profileView.xsd"/></pre>
Workaround	Verify the case when referencing schema file names using the Eclipse XSD Editor on Microsoft Windows.
CR327132	A schema is generated with "minOccurs=0" for all columns, not just columns that are not null.
Platform	Informix (using BEA XA and BEA Non-XA JDBC drivers).
Description	When creating a schema using an Informix database with either BEA XA or BEA Non-XA drivers, a schema is generated with "minOccurs=0" for all columns, not just columns that are not null.
Workaround	None.
CR327305	The nativeSize of data types appears as zero (0) after importing tables using Sybase drivers.
Platform	Sybase (using Sybase JDBC drivers)
Description	<p>When using Sybase drivers, the nativeSize of data types appear as zero (0) after importing tables, as shown in the following sample output:</p> <pre>xquery version "1.0" encoding "WINDOWS-1252"; (::pragma xds <x:xds xmlns:x="urn:annotations.ld.bea.com" targetType="t:sqlQuery" xmlns:t="ld:SY/datasource/TC_SQLWhereWithConstant/sqlQuery" <creationDate>yyyy-mm-ddThh:mm:ss</creationDate> <relationalDB name="datasource" providerId="Sybase-12.5.2"/> <field xpath="FIRST_NAME" type="xs:string"> <extension nativeXPath="FIRST_NAME"</pre>

	<pre> nativeType="varchar" nativeTypeCode="12" nativeSize="0" nativeFractionalDigits="0"/>\\ <properties nullable="false"/> </field> <field xpath="LAST_NAME" type="xs:string"> <extension nativeXPath="LAST_NAME" nativeType="varchar" nativeTypeCode="12" nativeSize="0" nativeFractionalDigits="0"/>\\ <properties nullable="false"/> </field> </pre>
Workaround	Use the BEA Sybase JDBC drivers.
CR327820	Certain SQL queries may generate a schema with a missing element name.
Platform	Sybase
Description	<p>When using Sybase, SELECT statements similar to the following may generate schemas with a missing element name:</p> <pre> SELECT t1.PRODUCT_ID, sum(t2.QUANTITY) FROM PRODUCT t1 JOIN CUST_ORDER_LINE_ITEM_APPL t2 on (t1.PRODUCT_ID = t2.PRODUCT_ID) GROUP by t1.PRODUCT_ID </pre>
Workaround	<p>Specify aliases for the columns in the SQL statements. For example, you could rewrite the previous SELECT statement as follows:</p> <pre> SELECT t1.PRODUCT_ID as PRODUCT_ID, sum(t2.QUANTITY) as QUANTITY FROM PRODUCT t1 JOIN CUST_ORDER_LINE_ITEM_APPL t2 on (t1.PRODUCT_ID = t2.PRODUCT_ID) GROUP by t1.PRODUCT_ID </pre>
CR328457	The Oracle JDBC driver and the BEA Oracle JDBC driver return different lengths for CHAR output parameters in stored procedures.
Platform	Oracle (using the Oracle JDBC driver and BEA Oracle JDBC driver).
Description	<p>The Oracle driver and the BEA Oracle driver may return different lengths for CHAR output parameters in stored procedures. For example:</p> <pre> CREATE OR REPLACE PROCEDURE MYPROCEDURE1(P_CHAR_OUT OUT CHAR) ...<procedure_body>... </pre> <p>In this example, P_CHAR_OUT is the output parameter returned by the stored procedure.</p>
Workaround	None.
CR328861	Ad-hoc queries in DSP controls that return XML that does not conform to the declared

	XML type generate an exception.
Platform	All.
Description	<p>When writing ad-hoc queries in a DSP control, if the ad-hoc query returns XML that does not conform to the declared XML type, the following exception is generated while marshalling the SDO data object.</p> <pre> java.lang.IllegalArgumentException: A type with this name 'ADDRESS_TYPE@urn:schemas-bea-com:ld-addr' already exists in this type system. <ComponentHandler.handleRequest:115> java.lang.IllegalArgumentException: A type with this name 'ADDRESS_TYPE@urn:schemas-bea-com:ld-addr' already exists in this type system. </pre>
Workaround	Ensure that ad-hoc queries in DSP controls conform to the XML schema for the return type.
CR331184	An exception occurs while parsing a NEIM schema.
Platform	All.
Description	<p>An XmlException exception similar to the following may occur while parsing a NEIM schema (when attempting to create a data service and associated schema, for example):</p> <pre> org.apache.xmlbeans.XmlException: D:\Eclipse Workspaces\DSPDemo\NEIM\Schema\lexs\lexs.xsd:54:5: error: Problem parsing referenced XML resource - D:\Eclipse Workspaces\DSPDemo\NEIM\Schema\lexs\lexs-digest.xsd:689:1 error: Unexpected element: CDATA at org.apache.xmlbeans.impl.schema.SchemaTypeSystemCompiler. </pre> <p>This may be caused by extra newline and whitespace characters at the end of the file.</p>
Workaround	Remove any newline or whitespace characters from the end of the NEIM schema file.
CR332755	An exception can occur when using the ALDSP 2.5 JDBC driver with ALDSP 3.0 applications.
Platform	All.
Description	<p>When attempting to get a connection using the ALDSP 2.5 JDBC driver (ldjdbc.jar) with an ALDSP 3.0 application, an IncompatibleClassChangeError exception can occur similar to the following:</p> <pre> Exception in thread "main" </pre>

	<pre> java.lang.IncompatibleClassChangeError: Implementing class at java.lang.ClassLoader.defineClass0(Native Method) at java.lang.ClassLoader.defineClass(ClassLoader.java:539) at java.security.SecureClassLoader.defineClass(SecureClassLoader </pre>
Workaround	Download the CR333047_810sp6.jar file and add the file to your client classpath.
CR333489	XQueries may return an incorrect timestamp using the BEA XA driver.
Platform	Oracle (using the BEA XA JDBC driver).
Description	<p>The BEA XA driver may return an incorrect timestamp when issued a query similar to the following:</p> <pre> <result> { for \$i in fl:DATA_TIMESTAMP_ZONE() return <row> { \$i/C_ID } { if (fn:data(\$i/C_TIMESTAMP_ZONE_3) instance of xs:dateTime) then <C_TIMESTAMP_ZONE_3> <type>TIMESTAMP_ZONE</type> <xmlltype>xs:dateTime</xmlltype> <data>{fn:data(\$i/C_TIMESTAMP_ZONE_3)}</data> </C_TIMESTAMP_ZONE_3> else <C_TIMESTAMP_ZONE_3></C_TIMESTAMP_ZONE_3> } } { if (fn:data(\$i/C_TIMESTAMP_ZONE_9) instance of xs:dateTime) then <C_TIMESTAMP_ZONE_9> <type>TIMESTAMP_ZONE</type> <xmlltype>xs:dateTime</xmlltype> <data>{fn:data(\$i/C_TIMESTAMP_ZONE_9)}</data> </C_TIMESTAMP_ZONE_9> else <C_TIMESTAMP_ZONE_9></C_TIMESTAMP_ZONE_9> } } { if (fn:data(\$i/C_TIMESTAMP_ZONE_NULL) instance of xs:dateTime) then <C_TIMESTAMP_ZONE_NULL> <type>TIMESTAMP_ZONE</type> <xmlltype>xs:dateTime</xmlltype> <data>{fn:data(\$i/C_TIMESTAMP_ZONE_NULL)}</data> </C_TIMESTAMP_ZONE_NULL> else <C_TIMESTAMP_ZONE_NULL></C_TIMESTAMP_ZONE_NULL> } } } } </result> </pre> <p>In this example, the expected return value is the following:</p> <pre> <C_TIMESTAMP_ZONE_3> <type>TIMESTAMP_ZONE</type> </pre>

	<pre> <xmltype>xs:dateTime</xmltype> <data>1999-04-15T08:00:00-07:00</data> </C_TIMESTAMP_ZONE_3> </pre>
	<p>The BEA XA driver instead returns the following:</p> <pre> <C_TIMESTAMP_ZONE_3> <type>TIMESTAMP_ZONE</type> <xmltype>xs:dateTime</xmltype> <data>1999-04-09T17:20:00+09:00</data> </C_TIMESTAMP_ZONE_3> </pre>
Workaround	Use the Oracle native XA JDBC driver.
CR333689	XQueries may return inconsistent results using the BEA XA driver.
Platform	Oracle (using the BEA XA JDBC driver).
Description	<p>The BEA XA driver may return inconsistent results when issued a query similar to the following:</p> <pre> declare namespace ns = "ld:test/RDBMS/OR-CR/DATA_NUMBER"; declare namespace ns1 = "ld:test/RDBMS/OR-CR/DATA_FLOAT"; declare namespace ns2 = "ld:test/RDBMS/OR-CR/DATA_NUMBER_N_S"; declare namespace ns3 = "ld:test/RDBMS/OR-CR/DATA_NUMBER_N"; declare variable \$ext as xs:decimal external; <result> { <column> { let \$x := for \$y in ns:DATA_NUMBER() where (\$y/C_ID mod 2) ne 0 return \$y/C_NUMBER mod \$y/C_ID return(<all> <test1>{\$x}</test1> <sql>{fn-bea:get-sql(\$x)}</sql> </all>) } </column> } { <const> { let \$x := for \$y in ns1:DATA_FLOAT() where \$y/C_ID gt (\$y/C_FLOAT mod 2) return fn:concat(xs:string(\$y/C_ID), xs:string(5 mod 4)) return(<all> <test2>{\$x}</test2> <sql>{fn-bea:get-sql(\$x)}</sql> </all>) } </const> } { <func> { let \$x := for \$y in ns2:DATA_NUMBER_N_S() </pre>

```

        where
        fn:string-length(xs:string($y/C_ID)) eq
        fn:abs( -5 mod 4)
        return fn:concat(
        xs:string($y/C_NUMBER_38_38 ), xs:string(4
        mod 5))
        return(
        <all>
        <test3>{$x}</test3>
        <sql>{fn-bea:get-sql($x)}</sql>
        </all>
        )
    }
    </func>
}
(:
{
    <param>
    {
        let $x := for $y in ns:DATA_NUMBER()
        where $y/C_NUMBER mod $ext
        return $y/C_NUMBER mod $ext
        return(
        <all>
        <test1>{$x}</test1>
        <sql>{fn-bea:get-sql($x)}</sql>
        </all>
        )
    }
    </param>
}
{
    <null>
    {
        let $x := for $y in
        ns:DATA_NUMBER()
        where $y/C_NUMBER_NULL mod $y/C_ID
        return $y/C_NUMBER_NULL mod
        $y/C_ID
        return(
        <all>
        <test1>{$x}</test1>
        <sql>{fn-bea:get-sql($x)}</sql>
        </all>
        )
    }
    </null>
}
:.)
{
    <join>
    {
        let $x:= for $y in ns:DATA_NUMBER()
        for $z in ns2:DATA_NUMBER_N_S()
        where $y/C_ID eq $z/C_ID
        return $y/C_NUMBER mod
        $z/C_NUMBER_38_38
        return(
        <all>
        <test1>{$x}</test1>
        <sql>{fn-bea:get-sql($x)}</sql>
        </all>
        )
    }
    </join>
}
{
    <orderby>
    {
        let $x:= for $y in ns:DATA_NUMBER()
        where true()
        order by $y/C_ID mod $y/C_NUMBER
        return $y/C_ID mod $y/C_NUMBER
        return(
        <all>
        <test1>{$x}</test1>

```

```

<sql>{fn-bea:get-sql($x)}</sql>
  </all>
  )
  }
  </orderby>
}
</result>

```

In this example, the expected return value is the following:

```

<result><column><all><test1>1.1E-130
2.33</test1><sql>SELECT
MOD(t1.'C_NUMBER',CAST(t1.'C_ID' AS
NUMBER)) AS c1
FROM 'CRM'.'DATA_NUMBER' t1
WHERE (MOD(t1.'C_ID',2) !=
0)</sql></all></column><const><all><test2>11
21
31</test2><sql>SELECT (TO_CHAR(t1.'C_ID')
|| '1') AS c1
FROM 'CRM'.'DATA_FLOAT' t1
WHERE (CAST(t1.'C_ID' AS NUMBER) >
MOD(t1.'C_FLOAT',2.0))</sql></all></const><func><all><tes
.1234 .14</test3><sql>SELECT
(TO_CHAR(t1.'C_NUMBER_38_38') || '4') AS c1
FROM 'CRM'.'DATA_NUMBER_N_S' t1
WHERE (NVL(LENGTH(TO_CHAR(t1.'C_ID')),0) =
1)</sql></all></func><join><all><test1>1.1E-130
-1.1E-30
0.03</test1><sql>SELECT
MOD(t1.'C_NUMBER',CAST(t2.'C_NUMBER_38_38'
AS
NUMBER)) AS c1
FROM 'CRM'.'DATA_NUMBER' t1
JOIN 'CRM'.'DATA_NUMBER_N_S' t2
ON (t1.'C_ID' =
t2.'C_ID')</sql></all></join><orderby><all><test1>-INF
9.0E-31 0.67</test1><sql>SELECT
MOD(CAST(t1.'C_ID' AS
NUMBER),t1.'C_NUMBER')
AS c1
FROM 'CRM'.'DATA_NUMBER' t1
ORDER BY MOD(CAST(t1.'C_ID' AS
NUMBER),t1.'C_NUMBER')
ASC</sql></all></orderby></result>

```

The BEA XA driver instead returns the following:

```

<result><column><all><test1>1.1E-130
2.33</test1><sql>SELECT
MOD(t1.'C_NUMBER',CAST(t1.'C_ID' AS
NUMBER)) AS c1
FROM 'CRM'.'DATA_NUMBER' t1
WHERE (MOD(t1.'C_ID',2) !=
0)</sql></all></column><const><all><test2>11
21
31</test2><sql>SELECT (TO_CHAR(t1.'C_ID')
|| '1') AS c1
FROM 'CRM'.'DATA_FLOAT' t1
WHERE (CAST(t1.'C_ID' AS NUMBER) >
MOD(t1.'C_FLOAT',2.0))</sql></all></const><func><all><tes
.1234 .14</test3><sql>SELECT
(TO_CHAR(t1.'C_NUMBER_38_38') || '4') AS c1
FROM 'CRM'.'DATA_NUMBER_N_S' t1
WHERE (NVL(LENGTH(TO_CHAR(t1.'C_ID')),0) =
1)</sql></all></func><join><all><test1>1.1E-130
-1.1E-30
0.03</test1><sql>SELECT

```

	<pre> MOD(t1.'C_NUMBER',CAST(t2.'C_NUMBER_38_38' AS NUMBER)) AS c1 FROM 'CRM'.'DATA_NUMBER' t1 JOIN 'CRM'.'DATA_NUMBER_N_S' t2 ON (t1.'C_ID' = t2.'C_ID')</sql></all></join><orderby><all><test1>0.0 9.0E-31 0.67</test1><sql>SELECT MOD(CAST(t1.'C_ID' AS NUMBER),t1.'C_NUMBER') AS c1 FROM 'CRM'.'DATA_NUMBER' t1 ORDER BY MOD(CAST(t1.'C_ID' AS NUMBER),t1.'C_NUMBER') ASC</sql></all></orderby></result> </pre>
Workaround	Use the Oracle native XA driver.
CR334116	RequestConfig.OUTPUT_FILENAME and invokeToFile() causes a DASException to occur.
Platform	All.
Description	The RequestConfig.OUTPUT_FILENAME capability has been removed from ALDSP 3.0. Similarly, the mediator function invokeToFile() is no longer available in ALDSP 3.0 Note that the RequestConfig.OUTPUT_FILENAME flag is still available to ensure backward compatibility with certain methods, however, the feature is no longer supported in ALDSP 3.0 and causes the DASException to occur if used.
Workaround	None.
CR324401	Binary string datatype parameters to DB2 stored procedures may cause an exception to occur.
Platform	DB2
Description	<p>Using binary string datatype parameters (for bit data) with DB2 stored procedures may cause an XQueryTypeException similar to the following to occur:</p> <pre> Caused by: weblogic.xml.query.exceptions.XQueryTypeException: [ad-hoc], line 3, column 39: {err}XP0004: Invalid static type: {http://www.w3.org/2001/XMLSchema}hexBinary at weblogic.xml.query.compiler.TypeMatchExpression.typeCheck() at weblogic.xml.query.compiler.Expression.typeCheck(Expression </pre>
Workaround	Do not use binary string datatype parameters with DB2 stored procedures.
CR329108	Projects are not listed when added during new server configuration.
Platform	All.

Description	<p>Projects do not appear under a configured server in the Server View when you complete the following steps:</p> <ol style="list-style-type: none"> 1. You create a new server and then delete the server (maintaining the configured runtime). 2. You create a new dataspace runtime (the target runtime is defined but not the target deployment server). 3. You add a new server using the same runtime created earlier. 4. You add the project while creating the server.
Workaround	When adding the project, click 'Finish' on the 'Add and Remove Projects' screen instead of 'Click Next and Finish.'
CR339199	SQL substitution statements do not work in applications migrated from ALDSP 2.5 to ALDSP 3.0 dataspaces.
Platform	All.
Description	SQL substitution statements created for ALDSP 2.5 may no longer work after the application is migrated to an ALDSP 3.0 dataspace. This is because the original SQL statements may have changed between ALDSP 2.5 and ALDSP 3.0.
Workaround	When migrating applications from ALDSP 2.5 to ALDSP 3.0 dataspaces, recreate and test any SQL substitution statements.
CR351305	Microsoft Visual Studio displays an error when referencing data service libraries containing functions that return item().
Platform	Microsoft Visual Studio/ADO .NET
Description	<p>ADO .NET does not support WSDL files that use xs:anyType as the return value. Since ALDSP converts functions that return item() to anyType*, Visual Studio displays an error similar to the following when attempting to reference data services containing these types of functions:</p> <div style="border: 1px solid black; padding: 10px; margin-top: 10px;"> <pre>Custom tool error: Unable to import WebService/Schema. Unable to import binding 'librarySoapBinding' from namespace 'ld:Logical/library_ws'. Unable to import operation 'XqueryNoInputOutput'. The element, XqueryNoInputOutputResponse, from namespace, ld:Logical/library_ws, was imported in two different contexts: (StructMapping, MembersMapping).</pre> </div>
Workaround	Do not .NET-enable data service functions that

	return item()).
CR349648	Unable to see an ADO DataSet when two schemas are imported in the data service.
Platform	All.
Description	<p>ADO.NET has the following requirements for supporting complex types in an ADO.NET DataSet, as described in the ADO.NET documentation:</p> <ul style="list-style-type: none"> • You need to define the entire XML type in a single schema definition file. Do not use include, import, or redefine statements. • You need to define one global element in the XML type and all other complex types as anonymous complex types within that element. Also, define one global element in the schema and define all other complex types as anonymous complex types within the element. Do not define any of the following: global attribute, global attributeGroup, or global simple type. You need to ensure that the name of an element in an anonymous complex type is unique within the entire schema definition. Note that the name of an element for simple types need not be unique unless the occurrence of the element is unbounded. Note also that ADO.NET does not support schemas with more than one type section that has the same target namespace.
Workaround	<p>Do one of the following:</p> <ul style="list-style-type: none"> • Write another create procedure that unwraps the key to the primitive return type if the key constitutes a single atomic type element in the key schema. • Associate a user-created EDS key that does not have the same namespace as the return type namespace. • Write another create procedure that does not return the key but instead drops it. • Expose EDS that do not have keys.
CR349102	XQSE procedures and functions do not support element-level security.
Platform	All.
Description	<p>Read-only library functions and non-read-only library procedures of a data service do not support element-level security. Element-level and data-driven security apply only to read and navigate functions.</p>

Workaround	As an alternative to element-level security, you can make relevant XQSE functions and procedures protected or private, and write a single-line XQuery wrapper function for functions and procedures that you need to make public.
CR348492	Eclipse-based tools are installed on Solaris and HP/UX-based systems even though they are not officially supported on these platforms.
Platform	Solaris and HP/UX.
Description	In silent/console mode, the AquaLogic Data Services Platform installer application installs Eclipse on Solaris and HP/UX-based systems and creates links to the client tools.
Workaround	Do not use the tools on Solaris and HP/UX-based systems. The ALDSP Eclipse-based IDE tools are supported on Microsoft Windows and Linux-based platforms. The tools are not supported on Solaris and HP/UX-based systems.
CR347980	Missing vertical scroll bar in the Design View when viewing a schema tree.
Platform	All.
Description	The vertical scroll bar does not appear when viewing a schema in the Design View if no functions exist. This is true even if the schema tree expands beyond the currently displayed view.
Workaround	Adding a function displays the scroll bar.
CR347865	The tree display in the Test View may not display fonts correctly on Linux-based systems.
Platform	Linux.
Description	When using AquaLogic Data Services Platform on Linux-based systems, the default Linux font size may render text in the tree display of the Test View too large, resulting in labels that are vertically clipped.
Workaround	Decrease the default Linux desktop application font size to 8 point or smaller by choosing Application > Preferences > Font > Application Font. If you do not have the Application menu on your desktop, consult the Linux document on how to set application fonts.
CR346978	Unable to specify a key for a web service-based data service.
Platform	All.
Description	When attempting to manually select the fields to

	specify the key for a web-service-based data service, the AquaLogic Data Services Platform (Eclipse ALDSP perspective) may display an "Invalid Key Specified" dialog indicating that the system cannot save the schema file.
Workaround	<p>To specify the key for a data service, the following conditions must be met:</p> <ul style="list-style-type: none"> • The key schema element must be in the same namespace as the EDS return type namespace. • The key schema element and the path selector elements must be in the same namespace as key schema element namespace.
CR346456	The ALDSP perspective does not appear in Eclipse following installation of ALDSP.
Platform	Eclipse
Description	A pre-installed version of Eclipse configured to use JDK1.4 will not be able to detect an ALDSP installation.
Workaround	When using a pre-installed version of Eclipse, configure Eclipse to use JDK 150_10 or higher.
CR339726	Deploying a dataspace using the ALDSP Console displays a 'Name not valid' error message.
Platform	All.
Description	Dataspace names are limited to 64 characters. Attempting to deploy a dataspace with a name longer than 64 characters causes a 'Name not valid' message to appear in the ALDSP Console.
Workaround	Use dataspace names with fewer than 64 characters.
CR339900	An illegal URI error message is displayed when creating a new logical data service.
Platform	All.
Description	<p>When creating a new logical data service, including preceding or embedded spaces in the schema file or folder name causes an illegal URI error message to appear, similar to the following:</p> <pre> ERROR: ld:JoinPattern/Logical/CustAddrCredit_ltoM_ltoM_Inner_Joi line 9, column 125: {err}XQ0046: 'ld:JoinPattern/Logical/schemas/ CUSTOMER_ADDRESS_CREDIT_INNER_JOIN.xsd': illegal URI UpdatePattern/JoinPattern/Logical </pre>

	CustAddrCredit_1toM_1toM_Inner_Join.ds line 9 1188433233135 3403
Workaround	Do not include preceding or embedded spaces in schema file and folder names.
CR352843	AquaLogic Data Services Platform 3.0 requires two Workshop for WebLogic 9.2 MP2 patches to be applied following installation.
Platform	Workshop for WebLogic 9.2 MP2
Description	Two required Workshop for WebLogic 9.2 MP2 patches are not automatically applied as part of the AquaLogic Data Services Platform 3.0 installation process.
Workaround	<p>After installing ALDSP 3.0, manually apply the following Workshop for WebLogic 9.2 MP2 patches using the smartupdate tool:</p> <ul style="list-style-type: none"> • RQSU • PF7M <p>The patches are in the 'downloaded' state after ALDSP 3.0 installation. You must have Workshop for WebLogic 9.2 MP2 installed to apply the patches.</p>
CR343891	Asynchronous operations do not propagate the transaction context.
Platform	All.
Description	Asynchronous web services and Java controls do not propagate the transaction context, regardless of the transaction requirements or settings (such as ReadTransaction). Asynchronous operations are likewise unable to start new transactions.
Workaround	None.
CR352226	When performing certain tasks after adding an external function, an error message may appear.
Platform	All.
Description	<p>After adding an external function, one of the following errors may appear:</p> <ul style="list-style-type: none"> • Clicking the Source tab may cause a "Resource is out of sync with the file system" error to appear. • Clicking the Source tab and modifying the code may cause the following update conflict error message to appear: "The file has been changed on the file system. Do you want to overwrite the changes?"

	<ul style="list-style-type: none"> Right-clicking to delete an existing function from the Overview page may cause the following refactoring message to appear: "The file "..." is out of sync with the underlying file system."
Workaround	Click Refresh in the Project Explorer. Alternatively, you can click "Yes" to overwrite the file.
CR338127	Unable to display data lineage graph using Solaris-based web browsers.
Platform	Firefox web browser on Solaris.
Description	The Solaris version of the Firefox web browser does not include a native SVG viewer or plug-in. Therefore, you cannot display a graphical view of the data lineage.
Workaround	Display the data lineage using the tabular view.
CR338237	Unable to display data lineage graph using HP-UX-based web browsers.
Platform	Firefox web browser on HP-UX.
Description	The HP-UX version of the Firefox web browser does not include a native SVG viewer or plug-in. Therefore, you cannot display a graphical view of the data lineage.
Workaround	Display the data lineage using the tabular view.
CR352445	Performing an Update Metadata operation may incorrectly generate the refactored source.
Platform	All.
Description	<p>The Update Metadata operation may generate incorrect refactored XML data when attribute values in the original source are enclosed in single quotes, as shown in the following example:</p> <pre><functionForDecomposition arity='0' name='t:CUSTOMER' /></pre>
Workaround	Ensure that all attribute values are enclosed in double quotes in the original source XML.
CR352805	Unable to deploy Java projects upgraded using ALDSP 3.0.
Platform	All.
Description	When upgrading Java projects (required by a data service) using ALDSP 3.0, the upgrade process adds Java 6.0 facets that makes the Java projects non-deployable in a WebLogic Server 9.2 MP2 environment.

Workaround	<p>Do the following:</p> <ol style="list-style-type: none"> 1. In the <code>\.settings\org.eclipse.wst.common.project.facet.core.xml</code> file of the upgraded Java project, change the line <code><installed facet='jst.java' version='6.0'/></code> to <code><installed facet='jst.java' version='5.0'/></code>. 2. In the <code>\.settings\org.eclipse.jdt.core.prefs</code> file of the upgraded Java project, change the value of the following properties from 1.6 to 1.5: <ul style="list-style-type: none"> • <code>org.eclipse.jdt.core.compiler.codegen.targetPlatform=</code> • <code>org.eclipse.jdt.core.compiler.compliance=1.5</code> • <code>org.eclipse.jdt.core.compiler.source=1.5</code>
CR343934	Starting to service administration requests on a deployed dataspace that is in the active state generates an error.
Platform	All.
Description	<p>When a deployed dataspace is already in the active state, clicking to start servicing administration requests causes a deployment exception to be logged and displays the following message:</p> <pre> EAR activation for dataspace '<name>' failed. Cause(s): - \[Deployer:149156\]Illegal state for operation start: 'STATE_ACTIVE' </pre>
Workaround	<p>Do not start servicing administration requests on a deployed dataspace that is in the active state. Instead, do the following:</p> <ol style="list-style-type: none"> 1. Stop the dataspace. 2. Click to start servicing administration requests
CR352634	Certain data service functions cannot be published as stored procedures.
Platform	All.
Description	<p>The following types of data service functions cannot be published as stored procedures:</p> <ul style="list-style-type: none"> • Functions with side-effects (procedures) • Functions with a simple return type
Workaround	None.
CR333331	SQL query generates an "Extra characters at the end of a datetime or interval" error.
Platform	Informix, all UNIX (using the Informix XA JDBC

	driver).
Description	<p>When using the native Informix XA driver, certain SQL queries may generate an "Error executing SQL query: Extra characters at the end of a datetime or interval" error, as shown in the following example:</p> <pre> Caused by: com.bea.ld.wrappers.rdb.exceptions.RDBWrapperException: [ad-hoc], line 10, column 1: {bea-err}RDBW0004: [ifrtl20ds]: [SELECT DISTINCT t1.cc_type AS c1 FROM rtlall_20:informix.credit_card t1, rtlall_20:informix.address t2 WHERE ((t1.customer_id = t2.customer_id) AND (t1.exp_date >= {ts '2007-01-01 00:00:00'}) AND (t2.city = 'San Jose'))]: Error executing SQL query: Extra characters at the end of a datetime or interval. at com.bea.ld.wrappers.rdb.exceptions.RDBWrapperException.cr </pre>
Workaround	Use the BEA Informix JDBC driver.
CR344349	A query produces an invalid XML character in the resulting document.
Platform	DB2 (using the native DB2 JDBC driver).
Description	When using the native DB2 driver, a query may produce an invalid XML character (Unicode: 0x0) in the resulting document.
Workaround	Use the BEA DB2 JDBC driver.
CR345306	SOAP 1.2 encoding not supported for ALDSP native web services.
Platform	All.
Description	ALDSP supports SOAP 1.1 and 1.2, and uses the version to determine the type of SOAP binding to create during WSDL generation. The default is 1.1. SOAP 1.2 encoding is not supported. Encoding is an optional feature defined by the SOAP 1.2 specification.
Workaround	Create JAX-RPC handlers to handle encoded messages.
CR355266	ALDSP 2.5 applications using JPD calls fail to work with ALDSP 3.0.
Platform	All.
Description	ALDSP 3.0 does not support applications migrated from ALDSP 2.5 to ALDSP 3.0 that use JPD call outs in update overwrites.
Workaround	This feature is not available in ALDSP 3.0. Future versions of ALDSP will support this feature.

CR294861	An exception occurs if a timestamp with time zone is fetched before LONG_RAW.
Platform	All (using the Oracle JDBC driver).
Description	When using an Oracle database, if a timestamp with a time zone is fetched before a LONG_RAW a "... Stream has already been closed" exception occurs. This is consistent with the way Oracle handles LONG_RAW fetched before blob and clob.
Workaround	Reverse the fetch order of timestamp with time zone and LONG_RAW when using Oracle.
CR286359	When importing or synchronizing metadata with an Oracle database, the native width of float elements may be incorrectly calculated.
Platform	All (using the BEA Oracle JDBC driver).
Description	When importing or synchronizing metadata with an Oracle data source, the width of float elements may be rendered incorrectly (15 instead of 6 or 9). This problem has been observed when using the WebLogic JDBC Oracle driver (version 3.0.5.0).
Workaround	Metadata synchronization using Oracle's native JDBC driver (Oracle.jdbc.driver.OracleDriver) did not exhibit this problem. Therefore, if the width of native float elements is an issue use the Oracle JDBC driver.
CR292257	Duplicate names are allow when mapping stored procedures to data services during metadata import.
Platform	All.
Description	The SQL name mapping user interface may allow more than one stored procedure with the same name to be configured under the same schema. However, if more than one stored procedure with the same name is configured, the user will see unexpected results in the JDBC metadata API and on execution of the procedures via JDBC.
Workaround	In the Publish Data Service Functions for SQL Use wizard, manually rename stored procedures so that there are no duplicate names.
CR291781	Excel Add-in will initially attempt to reuse HTTP basic authentication login credentials for all Web services hosted on the same port.
Platform	All.
Description	In cases where multiple Web services are configured in a single Excel worksheet, and these Web services are hosted by the same host machine and port number, the Excel Add-In will initially attempt to reuse the previously accepted

	<p>username/password for these services.</p> <p>If the username/password is not valid for a particular Web service, a login dialog will be displayed. Subsequent Web service invocations during the same Excel session will use the correct login information for each service.</p>
Workaround	<p>No action has to be taken, unless it is not deemed acceptable that an attempt is made to authenticate a web service call initially with incorrect credentials.</p> <p>In such cases Web services requiring different credentials should be grouped in different servers OR Web services requiring different credentials hosted on the same host/port should be used on separate Excel worksheets.</p>
CR290239	Several underlying WSDL Element definition attributes and Attribute definition attributes are not currently supported in the AquaLogic Data Services Platform Excel Add-in.
Platform	All.
Description	<p>The following Element definition attributes are currently unsupported:</p> <ul style="list-style-type: none"> • substitutionGroup • default • fixed • form • abstract • block • final <p>The following Attribute definition attributes are currently unsupported:</p> <ul style="list-style-type: none"> • default • fixed • form • abstract • block • final
Workaround	<p>Any WSDL containing the definition attributes listed above may not function as expected. If problems are encountered, remove these definition attributes from your WSDL.</p>
CR284834	When accessing data from Informix, use the Informix native JDBC driver when possible.
Platform	All using Informix database systems.
Description	<p>The WebLogic Informix JDBC driver is less performant than the native Informix JDBC driver when accessing data through AquaLogic Data Services Platform.</p>

Workaround	No workaround necessary, but for best performance with Informix data use its native JDBC driver.
CR279492	When using a data service based on a Web service at runtime, a validation error may occur if form and/or elementFormDefault do not match. This happens because redefinition of the 'Form' attribute is not supported.
Platform	All.
Description	<p>At design time, if:</p> <ul style="list-style-type: none"> • The elementFormDefault attribute in the primary schema does not match the elementFormDefault attribute in an imported or included schema, or • if the form attribute of an element does not match the elementFormDefault attribute in the primary schema then at runtime validation errors will occur when accessing Web service-based data services.
Workaround	The elementFormDefault in the primary schema and any imported or included schemas should match prior to compilation. Also, the form attribute of the element should match the elementFormDefault in the primary schema.
CR288384	The Data Lineage feature in AquaLogic Data Services Platform administration console requires the X11 graphical environment in Linux and UNIX environments.
Platform	UNIX and Linux
Description	<p>The following error:</p> <div style="border: 1px solid black; padding: 5px; margin: 10px 0;"> <pre>java.lang.NoClassDefFoundError: sun/awt/X11GraphicsEnvironment</pre> </div> <p>may occur while accessing the Data Lineage feature of AquaLogic Data Services Platform Administration Console.</p> <p>The circumstances arise when the Administration Server hosting AquaLogic Data Services Platform Administration Console is running on a Linux or UNIX host with one of the following conditions (not an exhaustive list):</p> <ul style="list-style-type: none"> • A headless environment is in use — for example, without monitor and/or X server. • With a monitor, but the user running the

	administration server is not the same user logged-in from the monitor, and therefore, does not have display permissions to the default display (:0.0).
Workaround	<p>To resolve this issue, set the following headless property to true:</p> <div>-Djava.awt.headless=true</div> <p>The property can be found in the Weblogic Server startup script (startWeblogic.sh) in the section of the script where the server is started.</p>
CR283262	Unable to add criteria to SQL when using MS Excel with EasySoft or OpenLink.
Platform	All.
Description	In Microsoft Query, adding a query criteria using the Add Criteria window, (Criteria ?Add Criteria) throws an error message when accessing AquaLogic Data Services Platform data sources.
Workaround	<p>To work around this issue:</p> <ol style="list-style-type: none"> 1. In the Microsoft Query window, select the Records menu option. If the Automatic Query option is checked, then clear this option. 2. Click View > Criteria. This will add a Criteria window to the query window into which you can enter appropriate criteria. 3. To execute query with the criteria added, click Records > Query Now.
CR264597	String comparison operations involving MS-SQL (and Sybase) may return incorrect results when the comparison operation is computed by MS-SQL.
Platform	All.
Description	See CR264597 Details
Workaround	See CR264597 Details
CR204243	When casting xs: Decimal from an xs:integer or xs:long, resulting values may not be precisely correct.
Platform	All.
Description	As above.
Workaround	To avoid the possibility of an incorrect result use a string literal instead of an xs:integer literal. For example instead of:

	<div>xs: Decimal(9223372036854775807)</div> <div>use:</div> <div>xs: Decimal("9223372036854775807")</div>
CR260587	An exception during an SDO update operation can occur if the order of elements in the client diffgram is changed and the Validate option is active.
Platform	All, using ADO.NET clients.
Description	Sometimes the order of elements in a diffgram changes, potentially leading to datagraph validation failure.
Workaround	If possible, turn off validation for the operation.
CR265950	End-point name changes do not take effect for operations in document style Web services.
Platform	All.
Description	Document style Web services use input (call parameter) types to determine the Web service operation being invoked. The operation name is not included in the SOAP request. For this reason, overwriting the operation name as part of an end point change does not work for document style Web services.
Workaround	None.
CR258884	Security decisions are not audited.
Platform	All.
Description	XQuery functions supporting security are not tracked by the audit framework.
Workaround	None.
CR257878	Use of Java keywords in schema elements and namespaces may cause name conflicts.
Platform	All.
Description	Schema elements and namespaces are converted into Java classes and packages as part of schema compilation process. This creates the potential for name conflicts with Java keywords and constructs.
Workaround	Avoid as necessary using syntax which the JVM might recognize as a reserved word or construct.
CR256214	Some DBMS systems may not properly

	handle "pushed down" constants.
Platform	Database platforms for which only generic support is provided.
Description	<p>SQL statements sent to base (not specifically supported) database platforms use a "best guess" as to the syntax for string literal. Such formulations may not work in all cases. An example of this is MySQL which requires every backslash</p> <div>[aldsp2: \]</div> <p>to be escaped with another backslash. Such cases are not handled by SQL generation code and might result in invalid SQL being generated.</p>
Workaround	<p>There are two possible workarounds for this problem:</p> <ul style="list-style-type: none"> Convert constants to parameters by using an external variable instead of a constant. For example: <div>where \$customer_id eq fn-bea:fence("CUSTOMER001")</div> Properly escape the XQuery string literal according to the rules of the underlying database.
CR248407	Metadata import wizard fails to detect in/out parameters.
Platform	All.
Description	In some situations associated with MSSQL and Sybase stored procedures, a resultset is returned which is not automatically detected.
Workaround	First, manually build a schema that is mapped to the output of the resultset. Then, when importing metadata use the wizard, add a ROWSET and link it to the previously created schema.
CR242938	Multi-dimension soap arrays are not supported in RPC mode.
Platform	All.
Description	The Web services wrapper provided by AquaLogic Data Services Platform only supports single-dimension arrays in RPC style Web services.

Workaround	None.
CR224815	The initial invocation of a Web service from an application server typically takes more time than subsequent calls. If the timeout value is less than the time required for the first call, the alternate expression (typically a timeout error) will be evaluated.
Platform	All.
Description	There is "startup overhead" the first time that a web service is invoked. The overhead can exceed the timeout threshold, leading to the specified timeout error.
Workaround	When setting timeout on expressions that have a Web service invocation, set the timeout value to be greater than the measured amount of time required for the first invocation.
CR239369	XQueries may generate invalid SQL for databases not supporting UPPER and LOWER (SQL-92). Also, empty input handling for base databases (databases not specifically support) as well as Oracle deviates from the XQuery specification when UPPER(null) or LOWER(null) is pushed down to the database level.
Platform	All platforms running base databases and Oracle databases.
Description	<p>There are two aspects to this problem:</p> <ul style="list-style-type: none"> • XQueries containing upper-case() or lower-case() functions are pushed down for database processing as UPPER and LOWER. Some databases may not support these SQL-92 keywords, however. In such cases the generated SQL will be invalid and upon execution will fail. • Similarly, input handling by base databases (as well as Oracle databases) may not match the XQuery specification. The reason for this is that the XQuery specification requires that functions <i>return an empty string</i> if input is an empty sequence. However, when these functions are pushed down, they <i>return an empty sequence</i> instead. This happens because LOWER(NULL) is NULL in SQL.
Workaround	Use the fn-bea:Fence() function to prevent pushdown of upper-case() or lower-case() functions to the database. Example:

	lower-case(fn-bea:fence(...))
CR207637	An exception appears for XQuery functions accessing metadata derived from Microsoft SQL Server stored procedures containing xs: Decimal.
Platforms	All.
Description	When importing a stored procedure from Microsoft SQL Server, the BEA JDBC driver incorrectly maps SQL decimal type to schema integer (xs:int) type.
Workaround	During stored procedure import, change the data type from xs:int to xs: Decimal. Alternatively, you can change the imported data service's metadata to specify the schema type for the affected column to be xs: Decimal.
CR203394	ROWTYPE input cursor is not supported when creating a data service from a stored procedure.
Platform	All.
Description	Stored procedure IN and INOUT cursors containing ROWIDs are not currently supported for metadata import.
Workaround	Avoid importing metadata on stored procedures which required use of IN or INOUT ROWID parameters.
CR214585	Erroneous results may occur when using fn:matches() with a regular expression containing a caret (^).
Platform	All.
Description	The match beginning-of-line operator (^) in regular expressions produces erroneous results when used with fn:matches().
Workaround	Do not use fn:matches() with a regular expression containing a caret (^).
CR215251	Identifiers within two characters of the maximum length allowed by the DBMS may result in an error.
Platform	All platforms running Sybase (and possibly other) databases.
Description	Some DBMS systems place limits on the length of identifiers (30 in the case of Sybase). AquaLogic Data Services Platform places single quotes around queries being pushed to the database, effectively reducing the maximum identifier length

	by two characters (28 in the case of Sybase).
Workaround	Possible options include renaming the table or creating a view with a shorter name.
CR226019	Access control policies associated with a data service function may disappear if the function's number of parameters is changed.
Platform	All.
Description	A data service function's signature is its QName and the number of parameters (arity) of the function. If you set security policies on a function and then change the number of parameters to the function, the function is treated as new and any previously set policies will no longer be in effect.
Workaround	If a function's arity is changed, reapply security policies to that function.
CR213916	BEA Informix JDBC driver does not return nullability information.
Platform	All platforms running Informix.
Description	The BEA Informix driver does not return information about table column nullability (that is, it is marked as unknown). During metadata import the minOccurs of the elements corresponding to the columns in the generated XML schemas is set to 0.
Workaround	Modify the imported metadata files by changing the minOccurs value for the nullable columns from 0 to 1.
CR214983, CR211701, CR201821	MSSQL VARIANT datatype has only limited support.
Platform	All.
Description	There are two limitations with this MSSQL VARIANT data type (sql_variant): <ul style="list-style-type: none"> • For SQL_VARIANT data type update will fail. • You cannot read a null value for the SQL_VARIANT data type.
Workaround	None available.
CR221015, CR319972	During metadata import the BEA Sybase JDBC driver may not display all tables to which user has authorized access.
Platform	All platforms accessing Sybase through the BEA Sybase JDBC driver.
Description	During metadata import the BEA Sybase JDBC driver may not show all tables which have been granted access to the user.

Workaround	This is a BEA Sybase driver limitation. For the import purpose, you can change to dbo user to see the full complement of available tables.
CR202963	When using BEA Oracle JDBC driver with a TIMESTAMP values, stored procedures are truncated.
Platform	All platforms running Oracle with the BEA Oracle JDBC driver.
Description	<p>When using the BEA's Oracle JDBC driver, if a stored procedure returns a TIMESTAMP value then the value gets truncated at the milliseconds level. For example, if the value was:</p> <div>1997-01-31 09:26:50.124</div> <p>then the stored procedure will return a</p> <div>1997-01-31 09:26:50.0</div> <p>value.</p>
Workaround	Use the Oracle JDBC driver stored procedures that returning TIMESTAMP values.
CR223429, CR228802	Sybase JDBC driver does not support a getBlob() call.
Platform	All platforms running Sybase with the Sybase JDBC driver.
Description	The AquaLogic Data Services Platform cache configuration does not work if using Sybase JDBC driver because the configuration implementation uses a getBlob() call on the JDBC driver. The Sybase JDBC driver does not support getBlob().
Workaround	Use the BEA JDBC driver for Sybase databases when utilizing Sybase as the AquaLogic Data Services Platform cache data source.
CR214730	SQL Server JDBC driver incorrectly renders the tinyint maximum value.
Platform	All platforms running SQL Server with the SQL Server JDBC driver.
Description	The SQL Server tinyint maximum value of 255 gets interpreted as -1 by the Microsoft SQL Server JDBC driver.
Workaround	Use the BEA JDBC driver for SQL Server.
CR223486, CR226239, CR226171	The Informix JDBC driver does not support

	standard JDBC syntax for specifying TIMESTAMP values.
Platform	All platforms running Informix with the Informix JDBC driver.
Description	<p>The Informix native driver does not support standard JDBC syntax for specifying TIMESTAMP values. For example:</p> <div>1979-03-01 00:00:00.0</div> <p>is not supported.</p>
Workaround	Use the BEA JDBC driver for Informix.
CR199675	The BEA JDBC driver for Oracle does not support UROWID column type for data retrieval.
Platform	All platforms running Oracle with the BEA JDBC driver.
Description	<p>When using BEA JDBC driver for Oracle, retrieving UROWID returns an error, identified by the following message:</p> <div>[aldsp2:BEA][aldsp2:Oracle JDBC Driver]Internal error: Net8 protocol error</div>
Workaround	Use the Oracle JDBC driver if your data contains UROWID column type.
CR212515	The Oracle stored procedure returning PL/SQL RECORD, BOOLEAN, or table with non-scalar element types is not supported.
Platform	All platforms using Oracle.
Description	<p>Oracle stored procedure limitations are detailed in the following currently-available document: http://www.stanford.edu/dept/itss/docs/oracle/9i/java.920/a966 </p>
Workaround	None available
CR202041	Metadata for SQL Server stored procedures returning CURSOR output cannot be created.
Platform	All platforms using SQL Server.
Description	When importing metadata from SQL Server, stored procedures that return CURSOR output are not supported.
Workaround	Modify the imported data service file to identify the correct data type for the cursor.
CR227440	Metadata for DB2 stored procedures returning CLOB data cannot be created.

Platform	All platforms using DB2.
Description	When importing metadata from DB2, stored procedures returning CLOB data are not supported.
Workaround	None available.
CR265965	Updating or deleting Oracle's CHAR/NCHAR with trailing blanks failed with an Optimistic locking failure message using Oracle JDBC driver.
Platform	All using Oracle's non-XA JDBC driver.
Description	With Oracle's non-XA JDBC driver, CHAR and NCHAR columns can only be updated if the number of characters is 1024 or less.
Workaround	Where possible use BEA's Oracle JDBC driver (Type 4).
CR202962	Oracle stored procedures containing CHAR or NCHAR as input may cause a Server error.
Platform	All.
Description	<p>If you have Oracle stored procedures that use an INOUT parameter, you may get an error when you run a stored procedure using AquaLogic Data Services Platform. The error is similar to:</p> <pre>java.lang.RuntimeException: ORA-01460: unimplemented or unreasonable conversion requested ORA-06512: at "WIRELESS.SP_CHAR", line 17</pre>
Workaround	Modify your stored procedure call by reducing the size of the INOUT parameter using TRIM. See aldsp2:Sample code related to CR202962, in aldsp2:Listing 1 .

Supplemental Release Note Documentation

This section contains code and other additional information related to previously described release notes.

CR264597 Details

Summary

String comparison operations involving MSSQL (and Sybase) may return incorrect results when the comparison operation is computed by MSSQL.

Description

Depending on the database and server configuration, MSSQL Server may use case-insensitive collation for string comparison operations (this is the default configuration). This is in contrast to XQuery string comparison operations, which are case-sensitive.

When generating SQL, the AquaLogic Data Services Platform currently does not take database string collation into account. This can lead to different results being produced by expressions that are "pushed down" to an MSSQL database, as compared to the results from their evaluation by the XQuery engine.

The following types of expressions are affected:

- string comparison operations
- string functions: `fn:contains()`, `starts-with()`, `ends-with()`
- order by clauses
- group by clauses.

For example, consider the following two-row, two-column table based on:

CUSTOMER(ID, FIRST_NAME)

ID	FIRST_NAME
1	John
2	john

The following XQuery might return different results depending whether it is evaluated by the database or not.

```
for $c in CUSTOMER()  
where $c/FIRST_NAME eq "john"  
return $c/ID
```

According to XQuery semantics, this query should return:

```
<ID>2</ID>
```

as only the second record matches the selection criteria.

However, when the AquaLogic Data Services Platform pushes the query to the underlying MSSQL database, the following SQL is generated:

```
SELECT t1."C_ID" AS c1  
FROM "CUSTOMER" t1  
WHERE t1."FIRST_NAME" = "john"
```

This might result in both records being returned by the MSSQL database (with case-insensitive string collation set):

```
<ID>1</ID>
<ID>2</ID>
```

Workaround

There are several workarounds to conforming with XQuery semantics for string comparisons when pushing computations down to MSSQL.

Option 1

Consider changing the collation setting that the database uses for string comparisons. See "SQL Server Collation Fundamentals" document located as of this writing at:

http://msdn.microsoft.com/library/default.asp?url=/library/en-us/architec/8_ar

Collation can change on a server, database or column level basis.

Option 2

Use the `fn-bea:fence()` function to block pushdown. In the above example, this would be rendered as:

```
for $c in CUSTOMER()
where fn-bea:fence(data($c/FIRST_NAME)) eq "john"
return $c/ID
```

Notice, however, that this approach may negatively impact performance since the AquaLogic Data Services Platform engine now must fetch and process the entire table.

To optimize performance, consider replicating the comparison operation in the query, thus allowing one copy to be evaluated by the database while keeping the second copy on the AquaLogic Data Services Platform engine. The following query illustrates such an approach:

```
for $c in CUSTOMER()
where $c/FIRST_NAME eq "john"
where fn-bea:fence(data($c/FIRST_NAME)) eq "john"
return $c/ID
```

This approach limits the number of results that the XQuery engine must process but still applies the second selection in order to obtain the correct XQuery semantics.

CR202962 Listing 1

Here is the sample code for CR202962:

```
** CREATE OR REPLACE PROCEDURE WIRELESS.SP_CHAR
(P_CHAR_IN IN CHAR,
P_CHAR_OUT OUT CHAR,
P_CHAR_INOUT IN OUT CHAR,
P_ID_OUT OUT VARCHAR2 )
IS
TEMP VARCHAR2(10);
BEGIN
SELECT C_ID INTO P_ID_OUT
FROM WIRELESS.ALL_DATATYPES
WHERE C_CHAR = P_CHAR_IN;

SELECT C_CHAR INTO P_CHAR_OUT
FROM WIRELESS.ALL_DATATYPES
WHERE C_ID = '2';

SELECT C_ID INTO TEMP
FROM WIRELESS.ALL_DATATYPES
WHERE C_CHAR = P_CHAR_INOUT;

SELECT 'WORK' INTO P_CHAR_INOUT
FROM WIRELESS.ALL_DATATYPES
WHERE C_ID = TEMP;
END;
/
to adjust the size of PCHAR_INOUT using TRIM (see highlighted code)
CREATE OR REPLACE PROCEDURE WIRELESS.SP_CHAR
(P_CHAR_IN IN CHAR,
P_CHAR_OUT OUT CHAR,
P_CHAR_INOUT IN OUT CHAR,
P_ID_OUT OUT VARCHAR2 )
IS
TEMP VARCHAR2(10);
\*ACHAR CHAR(500);

BEGIN
ACHAR := trim(P_CHAR_INOUT);
\*
SELECT C_ID INTO P_ID_OUT
FROM WIRELESS.ALL_DATATYPES
WHERE C_CHAR = P_CHAR_IN;

SELECT C_CHAR INTO P_CHAR_OUT
FROM WIRELESS.ALL_DATATYPES
WHERE C_ID = '2';

SELECT C_ID INTO TEMP
FROM WIRELESS.ALL_DATATYPES
\*WHERE C_CHAR = ACHAR; // used to fail here
\*
SELECT 'WORK' INTO P_CHAR_INOUT
FROM WIRELESS.ALL_DATATYPES
WHERE C_ID = TEMP;

END;
/
```

Version:	3.0
Document Date:	June 2005
Revision:	January 2008

[Contact BEA](#) | [Feedback](#) | [Privacy](#) | (c) [2008 BEA Systems](#)