



BEA WebLogic Java Adapter for Mainframe™

JCA Adapter Guide

Copyright

Copyright © 2002 BEA Systems, Inc. All Rights Reserved.

Restricted Rights Legend

This software and documentation is subject to and made available only pursuant to the terms of the BEA Systems License Agreement and may be used or copied only in accordance with the terms of that agreement. It is against the law to copy the software except as specifically allowed in the agreement. This document may not, in whole or in part, be copied, photocopied, reproduced, translated, or reduced to any electronic medium or machine readable form without prior consent, in writing, from BEA Systems, Inc.

Use, duplication or disclosure by the U.S. Government is subject to restrictions set forth in the BEA Systems License Agreement and in subparagraph (c)(1) of the Commercial Computer Software-Restricted Rights Clause at FAR 52.227-19; subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.227-7013, subparagraph (d) of the Commercial Computer Software--Licensing clause at NASA FAR supplement 16-52.227-86; or their equivalent.

Information in this document is subject to change without notice and does not represent a commitment on the part of BEA Systems. THE SOFTWARE AND DOCUMENTATION ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND INCLUDING WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. FURTHER, BEA Systems DOES NOT WARRANT, GUARANTEE, OR MAKE ANY REPRESENTATIONS REGARDING THE USE, OR THE RESULTS OF THE USE, OF THE SOFTWARE OR WRITTEN MATERIAL IN TERMS OF CORRECTNESS, ACCURACY, RELIABILITY, OR OTHERWISE.

Trademarks or Service Marks

BEA, WebLogic, Tuxedo, and Jolt are registered trademarks of BEA Systems, Inc. How Business Becomes E-Business, BEA WebLogic E-Business Platform, BEA Builder, BEA Manager, BEA eLink, BEA WebLogic Commerce Server, BEA WebLogic Personalization Server, BEA WebLogic Process Integrator, BEA WebLogic Collaborate, BEA WebLogic Enterprise, and BEA WebLogic Server are trademarks of BEA Systems, Inc.

All other product names may be trademarks of the respective companies with which they are associated.

BEA WebLogic JAM JCA Adapter Guide

Document Edition	Part Number	Date	Software Version
5.1	N/A	August 2002	5.1

Contents

BEA WebLogic JAM JCA Adapter Guide

Pre-requisites	1
Installation	2
Install and Define the jamjca.jar	2
For Windows Systems	2
For Unix Systems	3
Deploying the WebLogic JAM JCA Adapter via the WebLogic Console	3
Using the WebLogic JAM JCA Adapter	6
Configuring the JCA Adapter	7
Programming Client Applications	7
Example Code	8
Record Types	10
Samples	11
Container Managed Connections	11
Building the Sample	11
Running the Sample	12
Non-Managed Connections	12
Building the Sample	12
Running the Sample	13



BEA WebLogic JAM JCA Adapter Guide

The WebLogic JAM JCA Adapter is a JCA 1.0 compliant adapter which installs into the Connector Container of WebLogic Server and provides a standard API interface to WebLogic JAM services.

The WebLogic JAM JCA Adapter implements all functionality documented in the J2EE Connector Architecture Specification Version 1.0 (JSR 016) including support for:

- Local and XA transactions
- J2EE Connector Common Client Interfaces (CCI)
- Resource Adapter and Connection Metadata
- Container-managed security

In addition, the following extensions are supported:

- DataView record type allowing DataViews generated using the eGen utility to be used as input or output of a mainframe service invocation.
- XML record type allowing a properly constructed XML document to be used as input or returned as the response of a mainframe service.

Pre-requisites

WebLogic Server 7.0 must be installed prior to installing the WebLogic JAM JCA Adapter.

Installation

The WebLogic JAM JCA Adapter is delivered as part of the WebLogic JAM product from the BEA Download site or the product CD. The following files are installed:

- `jamjca.jar`

This file is installed into the `<JAM_INSTALL_DIR>/lib` directory and must be defined in the WebLogic `CLASSPATH`. This file contains the classes required to run the JCA Adapter functionality with WebLogic JAM.

- `jamjca.rar`

This file is the Resource Adapter Archive file and is installed in `<JAM_INSTALL_DIR>/lib`. This is the file that is deployed via the WebLogic Administration Console.

Install and Define the `jamjca.jar`

The `jamjca.jar` file must be defined in the WebLogic system `CLASSPATH` so that WebLogic JAM JCA clients running under the control of the WebLogic Connector Container have access to the classes which are not defined by standard J2EE JCA interfaces.

In addition, many of the features of the WebLogic JAM JCA Adapter require access to DataViews generated using the eGen utility. These DataViews describe the contents of a mainframe data record. It is recommended that a new directory be created in the `<JAM_INSTALL_DIR>` to contain these classes and that this directory be added to the system `CLASSPATH`.

For Windows Systems

To accomplish these changes edit the `startWebLogic.cmd` and make the following changes:

1. Add the following lines to the script:

```
set JAM_HOME=<Install Directory for WebLogic JAM 5.1>
set DATAVIEW_DIR=%JAM_HOME%/DataView
set JAMJCA_JAR=%JAM_HOME%/lib/jamjca.jar
```

2. Locate the following line in the script:

```
set
CLASSPATH=.;.\lib\weblogic_sp.jar;.\lib\weblogic.jar;<JAM_INSTALL
_DIR>\lib\jamjca.jar
```

Append this line of code to it.

```
set CLASSPATH=%CLASSPATH%;%JAMJCA_JAR%;%DATAVIEW_DIR%
```

For Unix Systems

To accomplish these changes edit the `startWebLogic.sh` and make the following changes:

1. Add the following lines to the script:

```
export JAM_HOME=<JAM_INSTALL_DIR>
export DATAVIEW_DIR=$JAM_HOME/DataView
export JAMJCA_JAR=$JAM_HOME/lib/jamjca.jar
```

2. Locate the following line in the script:

```
CLASSPATH=.;./lib/weblogic_sp.jar;./lib/weblogic.jar;<JAM_INSTALL
_DIR>/lib/jamjca.jar
```


Append this line of code to it.

```
CLASSPATH=$CLASSPATH:$JAMJCA_JAR:$DATAVIEW_DIR
```


Deploying the WebLogic JAM JCA Adapter via the WebLogic Console

Deployment of the WebLogic JAM JCA Adapter via the WebLogic Administration Console is accomplished as follows:

1. Select the Connectors item in the console tree and then click on Configure a new Connector Component in the right hand pane of the WebLogic Administration Console:



2. Enter the path and filename of the `jamjca.rar` file or use the Browse button to locate the file in the `<JAM_INSTALL_DIR>/lib` directory and then click on the Upload button:



3. The WebLogic JAM JCA Adapter is now deployed:

The screenshot displays the WebLogic Administration Console interface. The left-hand tree view shows the navigation structure, with 'examples' expanded to 'Resource Connectors' and 'jamjca' selected. The main content area shows the 'Deploy' tab for the 'jamjca' resource connector. The 'Deployment Status by Target' table indicates that the connector is deployed to the 'examplesserver' target. Below this, the 'Deployment Activity' table shows a successful deployment event on August 21, 2002.

Target	Target Type	Deployed	Undeploy	Redeploy
examplesserver	Server	true	Undeploy	Redeploy


Description	Status	BeginTime	EndTime
Activate application jamjca on examplesserver	Completed	Wed Aug 21 11:11:06 CDT 2002	Wed Aug 21 11:11:11 CDT 2002

Using the WebLogic JAM JCA Adapter

WebLogic JAM JCA Adapter provides a client interface using standard JCA system contracts to access WebLogic JAM services. The following sections provide guidelines for configuration and programming with the WebLogic JAM JCA Adapter.

Configuring the JCA Adapter

After installing the WebLogic JAM JCA Adapter, you may configure it using the Edit Connector Descriptor link of the WebLogic Administration Console. For more information on the Connector Container options in WebLogic Server, refer to the WebLogic Server documentation.



Programming Client Applications

Creating client applications which make use of the WebLogic JAM JCA Adapter follows the standard practices for all Connector clients. The general steps are:

1. Obtain a JAM JCA Connection Factory. In the Managed case this factory is obtained from a Pool maintained by the WebLogic Connector Container. In the Non-managed (stand-alone) case the ConnectionFactory is directly instantiated by the client.

-
2. Use the `ConnectionFactory` to obtain a `Connection` object.
 3. Using the `Connection` object, request an `Interaction` object.
 4. Instantiate an `InteractionSpec` object used to identify the mainframe service to be invoked.
 5. Create a `Record` object for the input data to the service and for the response.
 6. Use the `Interaction` object to execute the mainframe service passing the `InteractionSpec`, `Input Record`, and `Output Record`.
 7. Close the connection.

Example Code

The following listing is simple example code which outlines the previous programming steps for a non-managed (standalone) invocation:

Listing 1 Example Programming Code

```
1. import javax.resource.cci.*;
2. import com.bea.jam.jca.*;
3. String url = "t3://localhost:7001";
4. ConnectionFactory fact = new ConnectionFactoryImpl(url);
5. Connection conn = fact.getConnection();
6. Interaction action = conn.createInteraction();
7. InteractionSpecImpl actionSpec = new InteractionSpecImpl();
8. actionSpec.setFunctionName("sampleRead");
9. actionSpec.setInteractionVerb(InteractionSpec.SYNC_SEND_RECEIVE);
10. RecordFactory rfact = fact.getRecordFactory();
11. XmlRecord input = new XmlRecord("EmployeeRecord");
12. MappedRecord output = rfact.createMappedRecord("EmployeeRecord");
13. String xml = "<?xml version='1.0'?><empRecord><empName><empLastName>Smith
</empLastName></empName></empRecord>";
14. input.setData(xml);
15. action.execute(actionSpec, input, output);
16. conn.close();
```

Line Number	Description
1 and 2	Import the packages for the J2EE Connector CCI and the WebLogic JAM implementation of these interfaces.
3 and 4	Obtain a connection factory using the URL of the WebLogic Server which is hosting the WebLogic JAM Gateway.
5	Obtain a connection from the connection factory.
6	Use the connection to obtain an Interaction object.
7-9	Create an InteractionSpec object and the following properties: <ul style="list-style-type: none"> ◆ The FunctionName is the name of the mainframe service as defined in the WebLogic JAM configuration. ◆ The InteractionVerb for a synchronous send and receive of data. This is the only interaction verb supported by the WebLogic JAM JCA Adapter.
10	Obtain a record factory which can be used for the creation of Indexed and Mapped Records.
11	Create an instance of an XmlRecord. This is a WebLogic JAM JCA extension which provides support for conforming XML data. This Record object will contain data translation code to convert the XML data to mainframe data.
12	Create an instance of a MappedRecord which will be used to receive the response from the mainframe service.
13 and 14	Set the value of the input XmlRecord to the requested employee last name.
15	Invoke the mainframe service. On successful return the MappedRecord we passed in as output will contain the service response data.
16	Close the connection.

Record Types

The WebLogic JAM JCA Adapter supports four types of records for input and/or output when executing mainframe services:

Record Type	Description	Record Name Definition
IndexedRecord	This record always contains a single entry which is a byte array containing the binary data record.	An arbitrary name.
MappedRecord	<p>This record contains a Java Map of name/value pairs.</p> <ul style="list-style-type: none">◆ The name is the field name from the data record.◆ The value is the data associated with that field. <p>This Map is created using the WebLogic JAM HashtableLoader and HashtableUnloader classes.</p> <p>Note: Refer to the <i>WebLogic Java Adapter for Mainframe Programming Guide</i> for more information about these classes.</p>	Must match the name of the DataView class for the record.
DataViewRecord	This record is a wrapper around the WebLogic JAM DataView class.	Must match the name of the DataView class for the record.
XmlRecord	<p>This record converts an XML document to a binary data record using a WebLogic JAM generated DataView class.</p> <p>Note: Refer to the “Understanding How WebLogic JAM Uses XML” section in the <i>WebLogic Java Adapter for Mainframe Programming Guide</i> for more information about these classes.</p>	Must match the name of the DataView class for the record.

Samples

The WebLogic JAM JCA Adapter provides two samples: a container-managed connection sample and a non-managed connection sample. These samples are in the following locations:

- Container-Managed Connection Sample

`<JAM_INSTALL_DIR>/samples/jca/managed`

- Non-Managed Connection Sample

`<JAM_INSTALL_DIR>/samples/jca/nonmanaged`

Container Managed Connections

The Container Managed sample is a simple JSP page that accesses the `readSample` mainframe service using the `EmployeeRecord` which ships as a WebLogic JAM 5.1 sample.

Building the Sample

To build the Container Managed sample using `ant`:

1. Make sure that the WebLogic `bin` directory is in your `PATH`.
2. Enter the following command to start `ant` passing the directory where WebLogic is installed. For example:

```
ant -DWLSDIR=d:/bea/wlserver7.0
```

3. Copy the generated `EmployeeRecord` `DataView` to your `DataView` directory. For example:

```
copy EmployeeRecord*.class d:\bea\wljam5.1\DataView\.
```


4. Install the `managedjca.war` file.

Running the Sample

After installing the `managedjca.war` file, use the following HTTP URL to launch the JSP in a browser:

```
http://localhost:7001/managedjca/DisplayEmployee.jsp
```

The following page displays.



The screenshot shows a web browser window titled "JAM 5.1 JCA Sample". The form contains the following fields and controls:

- First Name:
- Middle Initial:
- Last Name:
- Street:
- City:
- State:
- Zip:
- SSN:
- Submit:

The browser's status bar at the bottom shows "Done" and "Local intranet".

Enter a name in the Last Name field and click Submit to access the mainframe and display the returned data.

Non-Managed Connections

The non-managed JCA sample is a command line application, which runs the `readSample` service and displays results in various formats.

Building the Sample

To build this sample using `ant`:

1. Make sure the WebLogic bin directory is in your PATH.
2. Enter the command to start ant passing the directory where WebLogic is installed. For example:

```
ant -DWLSDIR=d:/bea/wlserver7.0
```
3. Copy the generated EmployeeRecord DataView to your DataView directory. For example:

```
copy EmployeeRecord*.class d:\bea\wljam5.1\DataView\.
```
4. Make sure the weblogic.jar, jam.jar, and jamjca.jar files are in your CLASSPATH. Also include the current directory in the CLASSPATH.

Running the Sample

Run the sample with the following command line format:

```
java DisplayEmployee <URL of WLS> <Last Name of Employee>
```

Running this sample does the following:

1. Obtains the JAM JCA metadata classes and displays product name, version, etc.
2. Executes the readSample service returning a MappedRecord. The first and last names are displayed from this response.
3. Executes the readSample service returning an XmlRecord. The resulting XML document displays.

Listing 2 Running Non-managed Connection Sample

```
java DisplayEmployee t3://localhost:7001 Last-1

Product Name: WebLogic Java Adapter for Mainframe
Product Version: 5.1
Support for J2EE Connector Version 1.0

First Name:    New-First
Last Name:    Last-1

<?xml version="1.0"?>
<empRecord>
<empSsn>1</empSsn>
```

```
<empName>
<empNameLast>Last-1</empNameLast>
<empNameFirst>New-First</empNameFirst>
<empNameMi>M</empNameMi>
</empName>
<empAddr>
<empAddrStreet>123 Main St.</empAddrStreet>
<empAddrSt>TX</empAddrSt>
<empAddrZip>775550000</empAddrZip>
</empAddr>
</empRecord>
```
