



BEAProducts

Supported Configurations for AquaLogic Service Bus 2.6

Copyright

Copyright © 1995-2007 BEA Systems, Inc. All Rights Reserved.

Restricted Rights Legend

This software is protected by copyright, and may be protected by patent laws. No copying or other use of this software is permitted unless you have entered into a license agreement with BEA authorizing such use. This document is protected by copyright and may not be copied photocopied, reproduced, translated, or reduced to any electronic medium or machine readable form, in whole or in part, without prior consent, in writing, from BEA Systems, Inc.

Information in this document is subject to change without notice and does not represent a commitment on the part of BEA Systems. THE DOCUMENTATION IS PROVIDED “AS IS” WITHOUT WARRANTY OF ANY KIND INCLUDING WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. FURTHER, BEA SYSTEMS DOES NOT WARRANT, GUARANTEE, OR MAKE ANY REPRESENTATIONS REGARDING THE USE, OR THE RESULTS OF THE USE, OF THE DOCUMENT IN TERMS OF CORRECTNESS, ACCURACY, RELIABILITY, OR OTHERWISE.

Trademarks and Service Marks

Copyright © 1995-2007 BEA Systems, Inc. All Rights Reserved. BEA, BEA JRockit, BEA WebLogic Portal, BEA WebLogic Server, BEA WebLogic Workshop, Built on BEA, Jolt, JoltBeans, SteelThread, Top End, Tuxedo, and WebLogic are registered trademarks of BEA Systems, Inc. BEA AquaLogic, BEA AquaLogic Data Services Platform, BEA AquaLogic Enterprise Security, BEA AquaLogic Service Bus, BEA AquaLogic Service Registry, BEA Builder, BEA Campaign Manager for WebLogic, BEA eLink, BEA Liquid Data for WebLogic, BEA Manager, BEA MessageQ, BEA WebLogic Commerce Server, BEA WebLogic Communications Platform, BEA WebLogic Enterprise, BEA WebLogic Enterprise Platform, BEA WebLogic Enterprise Security, BEA WebLogic Express, BEA WebLogic Integration, BEA WebLogic Java Adapter for Mainframe, BEA WebLogic JDriver, BEA WebLogic Log Central, BEA WebLogic Network Gatekeeper, BEA WebLogic Personalization Server, BEA WebLogic Personal Messaging API, BEA WebLogic Platform, BEA WebLogic Portlets for Groupware Integration, BEA WebLogic Server Process Edition, BEA WebLogic SIP Server, BEA WebLogic WorkGroup Edition, Dev2Dev, Liquid Computing, and Think Liquid are trademarks of BEA Systems, Inc. BEA Mission Critical Support, BEA Mission Critical Support Continuum, and BEA SOA Self Assessment are service marks of BEA Systems, Inc.

All other names and marks are property of their respective owners.

Contents

1. AquaLogic Service Bus 2.6 Supported Configurations

List of Supported Operating System Configurations	1-1
Data Transformation Tools	1-4

2. Supported Browsers and Firewalls

Browsers and Plug-Ins	2-1
Browsers Supported by AquaLogic Service Bus 2.6	2-1
Firefox Browser Settings	2-1
Java Plug-In Required for Online Help	2-2
Firewalls	2-2

3. Supported Database Configurations

Database Access Requirements	3-1
Support for JDBC Drivers	3-1
JDBC Drivers Bundled with AquaLogic Service Bus	3-2
Configuring JDBC Drivers	3-2
Database Versions and Drivers Supported for AquaLogic Service Bus 2.6	3-3

4. Installation Information

5. Product Support Information

Important Support Information	5-1
AquaLogic Service Bus 2.6 Support	5-1
Supported Hardware	5-2
Support Policy for Compatible Hardware Architectures	5-2
Support for Intel 64-bit Xeon Hardware	5-2
Support for BladeFrame Architecture	5-3

Support Policy for Third-Party JVMs5-3

End-of-Life and Product Life Cycle Policy Information.5-3

AquaLogic Service Bus 2.6 Supported Configurations

The following topics provide important information about the hardware and software configurations supported by BEA for AquaLogic Service Bus 2.6:

- [List of Supported Operating System Configurations](#)
- [Data Transformation Tools](#)
- [Supported Browsers and Firewalls](#)
- [Supported Database Configurations](#)
- [Installation Information](#)
- [Product Support Information](#)

List of Supported Operating System Configurations

The following table lists the operating system and hardware configurations on which BEA supports AquaLogic Service Bus 2.6. To view detailed support information about a particular configuration, select the name of the relevant operating system.

AquaLogic Service Bus 2.6 Supported Configurations

Vendor and Operating System	Hardware
HP-UX 11i	PA-RISC
HP-UX 11i V2	• PA-RISC • Itanium
HP-UX 11i V3	Itanium
IBM AIX 5.2	pSeries
IBM AIX 5.3	pSeries
Microsoft Windows 2000 Professional	x86
Microsoft Windows 2000 Server, Advanced Server, Datacenter	x86
Microsoft Windows Server 2003 Standard, Enterprise, Datacenter	• x86 • Itanium
Microsoft Windows XP	x86
Novell SUSE Linux Enterprise Server (SLES) 9	• x86 • 64-bit AMD64 • 64-bit Xeon
Novell SUSE Linux Enterprise Server (SLES) 10	• x86 • 64-bit AMD64 • 64-bit Xeon
Red Hat Enterprise Linux 4.0: AS, ES, WS	• x86 • 64-bit AMD64 • 64-bit Xeon • Itanium
Sun Solaris 8	SPARC
Sun Solaris 9	SPARC
Sun Solaris 10	• SPARC • x86

BEA provides full support for these operating system and hardware configurations only. We are continuously working to provide support for more configurations. Please contact your sales representative for information about configurations not listed in this table.

For information about supported databases, see [“Database Versions and Drivers Supported for AquaLogic Service Bus 2.6” on page 3-3](#).

Data Transformation Tools

The following data transformation tools are installed with AquaLogic Service Bus:

- XQuery Mapper plug-in for Eclipse 3.1
- Format Builder

The BEA XQuery Mapper and Format Builder are supported only on Windows configurations.

Note: The BEA XQuery Mapper is a set of plug-ins in Eclipse. Note that the installation of Eclipse with the AquaLogic Service Bus product does not include the Java Development Tooling (JDT) plug-ins or the Plug-in Development Environment (PDE) toolkit. You can add other plug-ins to the Eclipse IDE provided with AquaLogic Service Bus. However, when you attempt to install a plug-in, any plug-ins that it depends on must already be installed. Likewise, if the plug-in you want to install depends on the JDT or the PDE, you must install these first. You can download the PDE and JDT plug-ins from <http://www.eclipse.org>.

Supported Browsers and Firewalls

This section describes AquaLogic Service Bus 2.6 support for the following configuration components:

- [Browsers and Plug-Ins](#)
- [Firewalls](#)

Browsers and Plug-Ins

The following sections provide information about browser and browser plug-in support for ProductName.

Browsers Supported by AquaLogic Service Bus 2.6

AquaLogic Service Bus 2.6 can be accessed through either of the following browsers:

- Microsoft Internet Explorer 6.0 SP1 (and higher)
- Firefox 1.0

Note: You must disable pop-up blockers when using the AquaLogic Service Bus Console.

Firefox Browser Settings

If a page is not displayed correctly in your Firefox browser (for example, if the display of the left navigation bar occupies an entire window instead of part of a window), you may have to replace the default browser settings, as described in the following procedure:

1. Go to one of the following directories: `MOZILLA_HOME/default/pref` or `MOZILLA_HOME/greprefs`.
2. Open `all.js`.
3. Find `browser.cache.check_doc_frequency` and change the value to 1.
 - The default setting is `pref("browser.cache.check_doc_frequency", 3)`.
 - The new setting is `pref("browser.cache.check_doc_frequency", 1)`.
4. Save the file.

Java Plug-In Required for Online Help

The documentation for the following is displayed in a browser-based viewer that includes a search function performed by a Java applet:

- WebLogic Server Administration Console online help
- WebLogic Server code examples
- *WebLogic Server MBean Reference*

The search applet requires a Java plug-in. If you do not have this plug-in installed on your system and you want to be able to search this documentation, you must install the plug-in.

Firewalls

AquaLogic Service Bus 2.6 supports network devices, such as firewalls, that properly support network protocols and the 7-Layer Network Model.

BEA will perform root cause analysis on interaction problems between AquaLogic Service Bus and network devices, and it will address AquaLogic Service Bus 2.6 product issues as appropriate, but it cannot address network address issues.

Supported Database Configurations

This section includes the following topics:

- [Database Access Requirements](#)
- [Support for JDBC Drivers](#)
- [Database Versions and Drivers Supported for AquaLogic Service Bus 2.6](#)

Database Access Requirements

AquaLogic Service Bus 2.6 requires the following database-specific resources:

- Access to a database server installed on the local network. When AquaLogic Service Bus is installed on your system, a local copy of the PointBase database is provided. This copy of the database is provided solely for evaluation purposes. For any other use of the PointBase Server, the user is required to obtain a separate PointBase Server license directly from DataMirror.
- If you plan to use the JMS Reporting Provider, then a database server account with privileges sufficient for creating a database with tables must be available.

Support for JDBC Drivers

This section provides:

- [JDBC Drivers Bundled with AquaLogic Service Bus](#)
- [Configuring JDBC Drivers](#)

JDBC Drivers Bundled with AquaLogic Service Bus

The following table lists the database drivers that are installed with AquaLogic Service Bus 2.6.

Table 3-1 Database Drivers Available with AquaLogic Service Bus 2.6

Type	Drivers	For more information, see . . .
WebLogic Type 4 JDBC drivers	DB2	<i>WebLogic Type 4 JDBC Drivers:</i> http://e-docs.bea.com/wls/docs92/jdbc_drivers/index.html
	Oracle	
	SQL Server	
	Sybase	
Third-party drivers supported by WebLogic Server	Oracle Thin Driver 10g	• “Using Third-Party Drivers with WebLogic Server” in <i>Programming WebLogic JDBC</i>: http://e-docs.bea.com/wls/docs92/jdbc/thirdparty.html • “Using Third-Party JDBC Drivers with WebLogic Server” in <i>Configuring and Managing WebLogic JDBC</i>: http://e-docs.bea.com/wls/docs92/jdbc_admin/third_party_drivers.html
	PointBase Type 4	

Configuring JDBC Drivers

The Configuration Wizard and the WebLogic Server Administration Console provide default configuration settings for the drivers listed in “Support for JDBC Drivers” on page 3-1, and the drivers listed in “Database Versions and Drivers Supported for AquaLogic Service Bus 2.6” on page 3-3. In some cases, support for configuring third-party drivers is provided even though the driver itself is not bundled with the product.

For more information about configuring drivers from third-party vendors, see “Using Third-Party Drivers with WebLogic Server” in *Programming WebLogic JDBC* at:
<http://e-docs.bea.com/wls/docs92/jdbc/thirdparty.html>.

Note: AquaLogic Service Bus 2.6 does not support custom configuration, through the Configuration Wizard, of all the third-party drivers supported for custom configuration by WebLogic Server. For a list of drivers supported by AquaLogic Service Bus 2.6, see

Table 3-2, “Database Types and Drivers Supported by AquaLogic Service Bus 2.6,” on page 3-3.

Database Versions and Drivers Supported for AquaLogic Service Bus 2.6

The following table lists the types and versions of databases and drivers supported for use with AquaLogic Service Bus 2.6.

Table 3-2 Database Types and Drivers Supported by AquaLogic Service Bus 2.6

Database Type	JDBC Driver	Notes
DB2 8.2 FixPak2 (equivalent to 8.1 FixPak 9) and later FixPaks	BEA WebLogic Type 4 JDBC DB2 Driver	
DB2	BEA WebLogic Type 4 JDBC DB2 XA Driver	
Oracle 9.2.0.4 and later patch sets of 9.2.x	• BEA WebLogic Type 4 JDBC Oracle Driver • BEA WebLogic Type 4 JDBC Oracle XA Driver • Oracle Driver 10g • Oracle Thin/XA Driver 10g	The Oracle Thin Driver 10g and Oracle Thin/XA Driver 10g are the default drivers for AquaLogic Service Bus 2.6.
Oracle 10.1.0.3 and later patch sets of 10.1.x (32-bit and 64-bit production editions)	• Oracle Driver 10g • Oracle Thin/XA Driver 10g	The Oracle Thin Driver 10g and Oracle Thin/XA Driver 10g are the default drivers for AquaLogic Service Bus 2.6.
Oracle 10.2 and later patch sets of 10.2 (32-bit and 64-bit production editions)	• Oracle Driver 10g • Oracle Thin/XA Driver 10g	The Oracle Thin Driver 10g and Oracle Thin/XA Driver 10g are the default drivers for AquaLogic Service Bus 2.6.

Table 3-2 Database Types and Drivers Supported by AquaLogic Service Bus 2.6

Database Type	JDBC Driver	Notes
PointBase 5.1	PointBase Type 4 Driver	PointBase Server is an all-Java DBMS product included in the WebLogic Server distribution solely for evaluation purposes, either in the form of custom trial applications or through packaged sample applications provided with WebLogic Server. Non-evaluation development or other use of the PointBase Server requires that a separate PointBase Server license be obtained by the end user directly from DataMirror.
SQL Server 2000	BEA WebLogic Type 4 JDBC SQL Server XA Driver	
SQL Server 2000 SP3+	BEA WebLogic Type 4 JDBC SQL Server Driver	
SQL Server 2005	BEA WebLogic Type 4 JDBC SQL Server Driver	
Sybase 12.5.03 and later patch levels of 12.5.x	BEA WebLogic Type 4 JDBC Sybase Driver BEA WebLogic Type 4 JDBC Sybase XA Driver	

For more information about using database drivers, see “Using Third-Party Drivers with WebLogic Server” in *Programming WebLogic JDBC* at:

<http://e-docs.bea.com/wls/docs92/jdbc/thirdparty.html>.

Installation Information

For the standard method of installing AquaLogic Service Bus, see [BEA Products Installation Guide](#). For information about distribution methods for AquaLogic Service Bus, see [Product Distribution Methods](#).

There are no special installation instructions for AquaLogic Service Bus 2.6.

Product Support Information

The following sections provide product support information about AquaLogic Service Bus 2.6:

- [Important Support Information](#)
- [End-of-Life and Product Life Cycle Policy Information](#)

Important Support Information

The following sections provides guidance about high-level support policies:

- [AquaLogic Service Bus 2.6 Support](#)
- [Supported Hardware](#)
- [Support Policy for Third-Party JVMs](#)

AquaLogic Service Bus 2.6 Support

BEA supports AquaLogic Service Bus 2.6 software on the configurations supported in this document. The supported configurations include multiple combinations of hardware, operating systems, JDKs, database systems, Web servers, and browsers that can be used with AquaLogic Service Bus 2.6 software. We are working to increase the number of configurations we support, and will update this information as new supported configurations are added.

Please contact your sales representative for information about configurations not listed in this document. Note that even using a supported configuration does not guarantee that you will never encounter operating system and JVM issues while running your application. We suggest that

customers regularly check their operating system and JVM vendor Web sites for information and patches recommended by those vendors.

Supported Hardware

This section provides information about:

- [Support Policy for Compatible Hardware Architectures](#)
- [Support for Intel 64-bit Xeon Hardware](#)
- [Support for BladeFrame Architecture](#)

Support Policy for Compatible Hardware Architectures

BEA products are certified for particular hardware chip architectures, as specified in [“List of Supported Operating System Configurations” on page 1-1](#). In some cases, a single chip architecture is provided by multiple vendors. BEA supports such implementations when they are certified for compliance by their respective owners. For example:

- Fujitsu offers a line of machines called Primepower. Because Sun has certified Primepower systems for SPARC compatibility, all Primepower computers are supported for any SPARC-based system listed in [“List of Supported Operating System Configurations” on page 1-1](#).
- The IA32-compatible (that is, x86/Xeon-compatible) architecture that is supported in the same manner by AMD.
- Virtualization software, such as VMWare, is also considered a supported compatible architecture, provided the virtualization software is supported by the operating system vendor, and the support criteria specified in the Supported Configurations documentation for WebLogic products are met. Users of Xen virtualization software should review Xen documentation to ensure that the versions of Windows and Linux supported by BEA are also supported by the Xen software. Solaris Zones is a supported compatible architecture, although certain WLS restrictions have been identified. See [Support for Sun Solaris 10 in Multi-Zone Operation](#).

Support for Intel 64-bit Xeon Hardware

Intel’s 64-bit Xeon hardware is capable of running in either of two modes: with 64-bit extended addressing or as an IA32 (x86/Xeon) machine:

- If 64-bit Xeon is explicitly listed in [“List of Supported Operating System Configurations” on page 1-1](#), this architecture will support 64-bit extended addressing.
- If 64-bit Xeon is *not* listed in [“List of Supported Operating System Configurations,”](#) this architecture will be supported only for use as an IA32 machine with the supported 32-bit operating systems and SDKs for x86-based systems listed in [“List of Supported Operating System Configurations” on page 1-1](#).

Support for BladeFrame Architecture

BEA supports BladeFrame architectures on any configuration of operating system, hardware chip architecture, and SDK that is listed in [“List of Supported Operating System Configurations” on page 1-1](#).

Support Policy for Third-Party JVMs

A Java Virtual Machine (JVM) is required for AquaLogic Service Bus to run. For your convenience, in most cases the AquaLogic installation program includes a JVM for creation of AquaLogic domain configurations and use of AquaLogic software. For details, see the installation guide for AquaLogic Service Bus.

If the JVM used in your configuration is not the BEA JRockit JVM, but a JVM provided by a third party, BEA cannot directly resolve potential issues traced to the third-party JVM. Support for a third-party JVM must be provided by the JVM vendor.

The version of any third-party JVM bundled by BEA is recommended by the JVM vendor at the time BEA releases its product. Because the versions of JVMs supported by vendors change over time, please consult with your JVM vendor and confirm the latest configurations in the documentation for your operating system before using a third-party JVM. To find the documentation for your operating system, see [“List of Supported Operating System Configurations” on page 1-1](#).

End-of-Life and Product Life Cycle Policy Information

- For notification of changes in the release life cycle for BEA products, as well as information about BEA support for third-party products reaching end-of-life, see [BEA Product End-of-Life Announcements](#).
- For BEA’s product life cycle policy, see [BEA Product Life Cycle Policy](#).

