



BEA Tuxedo

System Messages CMDGW Catalog 3300-3499

BEA Tuxedo Release 7.1
Document Edition 7.1
May 2000

Copyright

Copyright © 2000 BEA Systems, Inc. All Rights Reserved.

Restricted Rights Legend

This software and documentation is subject to and made available only pursuant to the terms of the BEA Systems License Agreement and may be used or copied only in accordance with the terms of that agreement. It is against the law to copy the software except as specifically allowed in the agreement. This document may not, in whole or in part, be copied photocopied, reproduced, translated, or reduced to any electronic medium or machine readable form without prior consent, in writing, from BEA Systems, Inc.

Use, duplication or disclosure by the U.S. Government is subject to restrictions set forth in the BEA Systems License Agreement and in subparagraph (c)(1) of the Commercial Computer Software-Restricted Rights Clause at FAR 52.227-19; subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.227-7013, subparagraph (d) of the Commercial Computer Software--Licensing clause at NASA FAR supplement 16-52.227-86; or their equivalent.

Information in this document is subject to change without notice and does not represent a commitment on the part of BEA Systems. THE SOFTWARE AND DOCUMENTATION ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND INCLUDING WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. FURTHER, BEA Systems DOES NOT WARRANT, GUARANTEE, OR MAKE ANY REPRESENTATIONS REGARDING THE USE, OR THE RESULTS OF THE USE, OF THE SOFTWARE OR WRITTEN MATERIAL IN TERMS OF CORRECTNESS, ACCURACY, RELIABILITY, OR OTHERWISE.

Trademarks or Service Marks

BEA, ObjectBroker, TOP END, and Tuxedo are registered trademarks of BEA Systems, Inc. BEA Builder, BEA Connect, BEA Manager, BEA MessageQ, BEA Jolt, M3, eSolutions, eLink, WebLogic, and WebLogic Enterprise are trademarks of BEA Systems, Inc.

All other company names may be trademarks of the respective companies with which they are associated.

BEA Tuxedo System Messages CMDGW Catalog

Document Edition	Date	Software Version
7.1	May 2000	BEA Tuxedo Release 7.1

CMDGW Messages 3300-3399

3300 ERROR: CODEPAGE not allowed for BEA TOP END LOCAL_SERVICES entries of type QSPACE

Description A DM_LOCAL_SERVICES (DM_EXPORT) entry of type QSPACE has the CODEPAGE parameter specified. This parameter is not allowed for BEA TOP END entries with a type of QSPACE.

Action Remove the CODEPAGE parameter assignment from the DM_LOCAL_SERVICES (DM_EXPORT) entry of the dmconfig file.

See Also dmconfig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3301 ERROR: ACL not allowed for BEA TOP END LOCAL_SERVICES entries of type QNAME

Description A DM_LOCAL_SERVICES (DM_EXPORT) entry of type QNAME has the ACL parameter specified. This parameter is not allowed for BEA TOP END entries with a type of QNAME.

Action Remove the ACL parameter assignment from the DM_LOCAL_SERVICES (DM_EXPORT) entry of the dmconfig file.

See Also dmconfig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3302 ERROR: RNAME not allowed for BEA TOP END LOCAL_SERVICES entries of type QNAME

Description A DM_LOCAL_SERVICES (DM_EXPORT) entry of type QNAME has the RNAME parameter specified. This parameter is not allowed for BEA TOP END entries with a type of QNAME.

Action Remove the RNAME parameter assignment from the DM_LOCAL_SERVICES (DM_EXPORT) entry of the dmconfig file.

See Also dmconfig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3303 ERROR: CONV not allowed for BEA TOP END LOCAL_SERVICES entries of type QNAME

Description A DM_LOCAL_SERVICES (DM_EXPORT) entry of type QNAME has the CONV parameter specified. This parameter is not allowed for BEA TOP END entries with a type of QNAME.

Action Remove the CONV parameter assignment from the DM_LOCAL_SERVICES (DM_EXPORT) entry of the dmconfig file.

See Also dmconfig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3304 ERROR: TE_RTQGROUP not allowed for BEA TOP END LOCAL_SERVICES entries of type QNAME

Description A DM_LOCAL_SERVICES (DM_EXPORT) entry of type QNAME has the TE_RTQGROUP parameter specified. This parameter is not allowed for BEA TOP END entries with a type of QNAME.

Action Remove the TE_RTQGROUP parameter assignment from the DM_LOCAL_SERVICES (DM_EXPORT) entry of the dmconfig file.

See Also dmconfig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3305 ERROR: TE_RTQNAME not allowed for BEA TOP END LOCAL_SERVICES entries of type QNAME

Description A DM_LOCAL_SERVICES (DM_EXPORT) entry of type QNAME has the TE_RTQNAME parameter specified. This parameter is not allowed for BEA TOP END entries with a type of QNAME.

Action Remove the TE_RTQNAME parameter assignment from the DM_LOCAL_SERVICES (DM_EXPORT) entry of the dmconfig file.

See Also dmconfig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3307 ERROR: CODEPAGE not allowed for BEA TOP END LOCAL_SERVICES entries of type QNAME

Description A DM_LOCAL_SERVICES (DM_EXPORT) entry of type QNAME has the CODEPAGE parameter specified. This parameter is not allowed for BEA TOP END entries with a type of QNAME.

Action Remove the CODEPAGE parameter assignment from the DM_LOCAL_SERVICES (DM_EXPORT) entry of the dmconfig file.

See Also dmconfig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3309 ERROR: RNAME not allowed for BEA TOP END REMOTE_SERVICES entries of type SERVICE

Description A DM_REMOTE_SERVICES (DM_IMPORT) entry of type SERVICE has the RNAME parameter specified. This parameter is not allowed for BEA TOP END entries with a type of SERVICE.

Action Remove the RNAME parameter assignment from the DM_REMOTE_SERVICES (DM_IMPORT) entry of the dmconfig file.

See Also dmconfig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3310 ERROR: TE_RTQGROUP not allowed for BEA TOP END REMOTE_SERVICES entries of type SERVICE

Description A DM_REMOTE_SERVICES (DM_IMPORT) entry of type SERVICE has the TE_RTQGROUP parameter specified. This parameter is not allowed for BEA TOP END entries with a type of SERVICE.

Action Remove the TE_RTQGROUP parameter assignment from the DM_REMOTE_SERVICES (DM_IMPORT) entry of the dmconfig file.

See Also dmconfig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3311 ERROR: TE_RTQNAME not allowed for BEA TOP END REMOTE_SERVICES entries of type SERVICE

Description A DM_REMOTE_SERVICES (DM_IMPORT) entry of type SERVICE has the TE_RTQNAME parameter specified. This parameter is not allowed for BEA TOP END entries with a type of SERVICE.

Action Remove the TE_RTQNAME parameter assignment from the DM_REMOTE_SERVICES (DM_IMPORT) entry of the dmconfig file.

See Also dmconfig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3312 ERROR: CODEPAGE not allowed for BEA TOP END REMOTE_SERVICES entries of type SERVICE

Description A DM_REMOTE_SERVICES (DM_IMPORT) entry of type SERVICE has the CODEPAGE parameter specified. This parameter is not allowed for BEA TOP END entries with a type of SERVICE.

Action Remove the CODEPAGE parameter assignment from the DM_REMOTE_SERVICES (DM_IMPORT) entry of the dmconfig file.

See Also dmconfig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3315 ERROR: RNAME not allowed for BEA TOP END REMOTE_SERVICES entries of type QSPACE

Description A DM_REMOTE_SERVICES (DM_IMPORT) entry of type QSPACE has the RNAME parameter specified. This parameter is not allowed for BEA TOP END entries with a type of QSPACE.

Action Remove the RNAME parameter assignment from the DM_REMOTE_SERVICES (DM_IMPORT) entry of the dmconfig file.

See Also dmconfig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3316 ERROR: CONV not allowed for BEA TOP END REMOTE_SERVICES entries of type QSPACE

Description A DM_REMOTE_SERVICES (DM_IMPORT) entry of type QSPACE has the CONV parameter specified. This parameter is not allowed for BEA TOP END entries with a type of QSPACE.

Action Remove the CONV parameter assignment from the DM_REMOTE_SERVICES (DM_IMPORT) entry of the dmconfig file.

See Also dmconfig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3317 ERROR: TE_PRODUCT not allowed for BEA TOP END REMOTE_SERVICES entries of type QSPACE

Description A DM_REMOTE_SERVICES (DM_IMPORT) entry of type QSPACE has the TE_PRODUCT parameter specified. This parameter is not allowed for BEA TOP END entries with a type of QSPACE.

Action Remove the TE_PRODUCT parameter assignment from the DM_REMOTE_SERVICES (DM_IMPORT) entry of the dmconfig file.

See Also dmconfig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3318 ERROR: TE_FUNCTION not allowed for BEA TOP END REMOTE_SERVICES entries of type QSPACE

- Description** A `DM_REMOTE_SERVICES (DM_IMPORT)` entry of type `QSPACE` has the `TE_FUNCTION` parameter specified. This parameter is not allowed for `BEA TOP END` entries with a type of `QSPACE`.
- Action** Remove the `TE_FUNCTION` parameter assignment from the `DM_REMOTE_SERVICES (DM_IMPORT)` entry of the `dmconfig` file.
- See Also** `dmconfig` for `GWTOPEND(5)`
Using the BEA TUXEDO TOP END Domain Gateway
- 3319 ERROR: TE_QUALIFIER not allowed for BEA TOP END REMOTE_SERVICES entries of type QSPACE**
- Description** A `DM_REMOTE_SERVICES (DM_IMPORT)` entry of type `QSPACE` has the `TE_QUALIFIER` parameter specified. This parameter is not allowed for `BEA TOP END` entries with a type of `QSPACE`.
- Action** Remove the `TE_QUALIFIER` parameter assignment from the `DM_REMOTE_SERVICES (DM_IMPORT)` entry of the `dmconfig` file.
- See Also** `dmconfig` for `GWTOPEND(5)`
Using the BEA TUXEDO TOP END Domain Gateway
- 3320 ERROR: CODEPAGE not allowed for BEA TOP END REMOTE_SERVICES entries of type QSPACE**
- Description** A `DM_REMOTE_SERVICES (DM_IMPORT)` entry of type `QSPACE` has the `CODEPAGE` parameter specified. This parameter is not allowed for `BEA TOP END` entries with a type of `QSPACE`.
- Action** Remove the `CODEPAGE` parameter assignment from the `DM_REMOTE_SERVICES (DM_IMPORT)` entry of the `dmconfig` file.
- See Also** `dmconfig` for `GWTOPEND(5)`
Using the BEA TUXEDO TOP END Domain Gateway
- 3321 ERROR: RNAME not allowed for BEA TOP END REMOTE_SERVICES entries of type QNAME**
- Description** A `DM_REMOTE_SERVICES (DM_IMPORT)` entry of type `QNAME` has the `RNAME` parameter specified. This parameter is not allowed for `BEA TOP END` entries with a type of `QNAME`.
- Action** Remove the `RNAME` parameter assignment from the `DM_REMOTE_SERVICES (DM_IMPORT)` entry of the `dmconfig` file.
- See Also** `dmconfig` for `GWTOPEND(5)`
Using the BEA TUXEDO TOP END Domain Gateway
- 3322 ERROR: CONV not allowed for BEA TOP END REMOTE_SERVICES entries of type QNAME**
- Description** A `DM_REMOTE_SERVICES (DM_IMPORT)` entry of type `QNAME` has the `CONV` parameter specified. This parameter is not allowed for `BEA TOP END` entries with a type of `QNAME`.
- Action** Remove the `CONV` parameter assignment from the `DM_REMOTE_SERVICES (DM_IMPORT)` entry of the `dmconfig` file.
- See Also** `dmconfig` for `GWTOPEND(5)`
Using the BEA TUXEDO TOP END Domain Gateway
- 3323 ERROR: TE_RTQGROUP not allowed for BEA TOP END REMOTE_SERVICES entries of type QNAME**
- Description** A `DM_REMOTE_SERVICES (DM_IMPORT)` entry of type `QNAME` has the `TE_RTQGROUP` parameter specified. This parameter is not allowed for `BEA TOP END` entries with a type of `QNAME`.
- Action** Remove the `TE_RTQGROUP` parameter assignment from the `DM_REMOTE_SERVICES (DM_IMPORT)` entry of the `dmconfig` file.
- See Also** `dmconfig` for `GWTOPEND(5)`
Using the BEA TUXEDO TOP END Domain Gateway
- 3324 ERROR: TE_RTQNAME not allowed for BEA TOP END REMOTE_SERVICES entries of type QNAME**
- Description** A `DM_REMOTE_SERVICES (DM_IMPORT)` entry of type `QNAME` has the `TE_RTQNAME` parameter specified. This parameter is not allowed for `BEA TOP END` entries with a type of `QNAME`.
- Action** Remove the `TE_RTQNAME` parameter assignment from the `DM_REMOTE_SERVICES (DM_IMPORT)` entry of the `dmconfig` file.
- See Also** `dmconfig` for `GWTOPEND(5)`
Using the BEA TUXEDO TOP END Domain Gateway
- 3325 ERROR: CODEPAGE not allowed for BEA TOP END REMOTE_SERVICES entries of type QNAME**
- Description** A `DM_REMOTE_SERVICES (DM_IMPORT)` entry of type `QNAME` has the `CODEPAGE` parameter specified. This parameter is not allowed for `BEA TOP END` entries with a type of `QNAME`.

Action Remove the CODEPAGE parameter assignment from the DM_REMOTE_SERVICES (DM_IMPORT) entry of the dmconfig file.

See Also dmconfig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3326 ERROR: Cannot add BEA TOP END entry into table

Description The GWADM server could not update shared memory to insert a new DM_TOPEND entry during dynamic configuration. Check the userlog for related errors.

Action Correct any errors and re-issue the request. Or contact your BEA TUXEDO system Technical Support.

See Also dmconfig for GWTOPEND(5), GWADM(5)

Using the BEA TUXEDO TOP END Domain Gateway

3327 ERROR: Cannot setup links from LOCAL DOMAIN entry to BEA TOP END domain

Description The GWADM administrative server received a request to add a BEA TOP END entry dynamically. The add operation succeeded but the GWADM failed to set up the links from the corresponding local domain entry to the newly added entry.

Action Contact your BEA TUXEDO system Technical Support.

See Also dmconfig for GWTOPEND(5), GWADM(5)

Using the BEA TUXEDO TOP END Domain Gateway

3328 ERROR: Cannot setup links from REMOTE DOMAIN entry to BEA TOP END domain

Description The GWADM administrative server received a request to add a BEA TOP END entry dynamically. The add operation succeeded but the GWADM failed to set up the links from the corresponding remote domain entry to the newly added entry.

Action Contact your BEA TUXEDO system Technical Support.

See Also dmconfig for GWTOPEND(5), GWADM(5)

Using the BEA TUXEDO TOP END Domain Gateway

3329 ERROR: DOMAINID - invalid characters for BEA TOP END user id.

Description While processing a local domain entry by dynamic configuration, an invalid value was detected for the DOMAINID parameter. The field contains invalid characters for a BEA TOP END user ID.

Action Remove the invalid characters and reattempt the operation.

See Also dmconfig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3330 ERROR: TP_SYSTEM - invalid characters.

Description While processing a DM_TOPEND entry by dynamic configuration, an invalid value was detected for the TP_SYSTEM parameter. The field contains invalid characters.

Action Remove the invalid characters and reattempt the operation.

See Also dmconfig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3331 ERROR: Multiple BEA TOP END RDOM addresses must have matching TP_SYSTEM values

Description While processing a DM_TOPEND entry by dynamic configuration, a validation exception was detected. For configurations in which multiple remote domain access points are specified for failover processing purposes, all TP_SYSTEM parameters must have matching values. The value of the NWADDR parameter for the entry being processed violates this rule.

Action Change the network address value to match the other DM_TOPEND entries for the remote access point (RDOM) and reattempt the operation.

See Also dmconfig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3334 ERROR: _dmcf_write failed: Can't write entry in DM_TOPEND section

Description During the processing of a dmadmin topendpasswd command, the administrative server was unable to write an updated DM_TOPEND record to the bdmconfig file.

Action Contact your BEA TUXEDO System Customer Support.

3335 ERROR: DM_TOPEND entries for remote access point rdom have differing TP_SYSTEM values

Description While processing the `dmconfig` file, a validation rule violation was detected for a remote access point `rdom` entry in the `DM_TOPEND` section. For remote access points with multiple entries in the `DM_TOPEND` section, all `TP_SYSTEM` parameters must be identical.

Action Verify that all `DM_TOPEND` entries in the `dmconfig` file for the remote access point all have the same `TP_SYSTEM` value and reattempt the `dmloadcf` operation.

See Also `dmconfig` for `GWTOPEND(5)`

Using the BEA TUXEDO TOP END Domain Gateway

3336 ERROR: Multiple entries for local access point `ldom` in `DM_TOPEND` section

Description Only a single entry may exist for a local access point within the `DM_TOPEND` section. The `dmconfig` file has multiple entries for the local access point `ldom`.

Action Modify the `dmconfig` file to remove the extra `DM_TOPEND` entries and re-execute `dmloadcf`.

See Also `dmconfig` for `GWTOPEND(5)`

Using the BEA TUXEDO TOP END Domain Gateway

3337 ERROR: Multiple local access point entries not allowed in `DM_TOPEND` section

Description Within the `DM_TOPEND` section, only a single entry may exist for a local access point. The `DM_TOPEND` record being used in dynamic configuration represents a local access point that already exists in the configuration.

Action Change the local access point and reattempt the operation, or update the values of the existing `DM_TOPEND` entry in the configuration.

See Also `dmadmin(1)`, `dmconfig` for `GWTOPEND(5)`

Using the BEA TUXEDO TOP END Domain Gateway

3338 ERROR: The `topendpasswd` command must be run from the terminal

Description The `topendpasswd` command must be run from a terminal since `dmadmin` prompts for new passwords on the terminal. The command cannot be run using other methods, such as a shell script.

Action Remove the use of the `topendpasswd` command from any non-terminal invocations of `dmadmin`.

See Also `dmadmin(1)`, `topendpasswd(1)`

3339 ERROR: Local access point (local domain) required parameter for `topendpasswd`

Description The `dmadmin topendpasswd` command was invoked without the required local access point parameter.

Action Specify the local access point name, as defined in the `DM_LOCAL_DOMAINS (DM_LOCAL)` section, on the command line.

See Also `dmadmin(1)`, `topendpasswd(1)`, `dmconfig` for `GWTOPEND(5)`

Using the BEA TUXEDO TOP END Domain Gateway

3341 ERROR: `NWADDR` - must contain hex digits

Description An error was detected while processing a dynamic reconfiguration. The `NWADDR` parameter specified in the `DM_TOPEND` section contains invalid hex digits.

Action Correct the `NWADDR` parameter in the `DM_TOPEND` section and retry the operation.

See Also `dmconfig` for `GWTOPEND(5)`

Using the BEA TUXEDO TOP END Domain Gateway

3342 ERROR: `NWADDR` - must contain an even number of hex digits

Description The domain administrative server detected an error while trying to add or update an entry in the `bdmconfig` file. The `NWADDR` parameter specified in the `DM_TOPEND` section contains an odd number of hex digits.

Action Correct the `NWADDR` parameter of the `DM_TOPEND` section and retry the operation.

See Also `dmconfig` for `GWTOPEND(5)`

Using the BEA TUXEDO TOP END Domain Gateway

3343 ERROR: `NWDEVICE` must be an absolute pathname

Description The value of `NWDEVICE` in the `DM_TOPEND` section of the `dmconfig` file must be an absolute pathname.

Action Change the value for the `NWDEVICE` to an absolute pathname and retry the operation.

See Also `dmconfig` for `GWTOPEND(5)`

Using the BEA TUXEDO TOP END Domain Gateway

3344 ERROR: TP_SYSTEM - invalid characters.

Description The value of TP_SYSTEM in the DM_TOPEND section of the dmconfig file has invalid characters.

Action Correct the value of the TP_SYSTEM parameter and retry the operation.

See Also dmconfig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3345 ERROR: _dmcf_open failed: Can't open DM_RESOURCES section

Description During a dynamic configuration attempt to add a record to the DM_TOPEND section of the bdmconfig file, an error occurred while retrieving the encryption key from the DM_RESOURCES section. The section could not be opened.

Action Make sure that the bdmconfig file still exists.

See Also dmconfig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3346 ERROR: _dmcf_seek failed: Can't seek to DM_RESOURCES section

Description During a dynamic configuration attempt to add a record to the DM_TOPEND section of the bdmconfig file, an error occurred while retrieving the encryption key from the DM_RESOURCES section. The section could not be accessed.

Action Make sure that the bdmconfig file still exists.

See Also dmconfig for GWTOPEND(5)

3347 ERROR: _dmcf_write failed: Can't write entry in DM_PASSWORDS section

Description While re-encrypting passwords in DM_PASSWORDS section of bdmconfig file, the DM_PASSWORDS section of bdmconfig file cannot be accessed for writing the new re-encrypted entries.

Action Make sure that the bdmconfig file still exists.

See Also dmconfig(5)

3348 ERROR: TE_PRODUCT and TE_FUNCTION required for entries of type TE_SERVICE or TE_QNAME

Description A dynamic configuration operation did not specify all required BEA TOP END service entry parameters in the DM_LOCAL_SERVICES (DM_EXPORT) section. Both the TE_PRODUCT and TE_FUNCTION parameters are required for BEA TOP END entries of type SERVICE.

Action Modify the entry to include both TE_PRODUCT and TE_FUNCTION values and retry the operation.

See Also dmconfig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3349 ERROR: RNAME not allowed for BEA TOP END LOCAL_SERVICES entries of type SERVICE

Description A dynamic configuration operation specified an invalid BEA TOP END service entry parameter in the DM_LOCAL_SERVICES (DM_EXPORT) section. The RNAME parameter is not allowed for BEA TOP END entries of type SERVICE.

Action Remove the RNAME parameter from the entry and retry the operation.

See Also dmconfig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3350 ERROR: TE_RTQGROUP not allowed for BEA TOP END LOCAL_SERVICES entries of type SERVICE

Description A dynamic configuration operation specified an invalid BEA TOP END service entry parameter in the DM_LOCAL_SERVICES (DM_EXPORT) section. The TE_RTQGROUP parameter is not allowed for BEA TOP END service entries.

Action Remove the TE_RTQGROUP parameter from the entry and retry the operation.

See Also dmconfig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3351 ERROR: TE_RTQNAME not allowed for BEA TOP END LOCAL_SERVICES entries of type SERVICE

Description A dynamic configuration operation specified an invalid BEA TOP END service entry parameter in the DM_LOCAL_SERVICES (DM_EXPORT) section. The TE_RTQNAME parameter is not allowed for BEA TOP END service entries.

Action Remove the TE_RTQNAME parameter from the entry and retry the operation.

See Also dmconfig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3352 ERROR: CODEPAGE not allowed for BEA TOP END LOCAL_SERVICES entries of type SERVICE

Description A dynamic configuration operation specified an invalid BEA TOP END service entry parameter in the DM_LOCAL_SERVICES (DM_EXPORT) section. The CODEPAGE parameter is not allowed for BEA TOP END service entries.

Action Remove the CODEPAGE parameter from the entry and retry the operation.

See Also dmconf ig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3353 ERROR: TE_RTQGROUP and TE_RTQNAME required for TE_QSPACE entries

Description A dynamic configuration operation did not specify all required BEA TOP END queue space entry parameters in the DM_LOCAL_SERVICES (DM_EXPORT) section. Both the TE_RTQGROUP and TE_RTQNAME parameters are required for BEA TOP END entries of type QSPACE.

Action Modify the entry to include both TE_PRODUCT and TE_FUNCTION values and retry the operation.

See Also dmconf ig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3354 ERROR: TE_QSPACE entries must not have INBUFTYPE specified

Description A dynamic configuration operation specified an invalid BEA TOP END queue space entry parameter in the DM_LOCAL_SERVICES (DM_EXPORT). The INBUFTYPE parameter is not allowed for BEA TOP END entries of type QSPACE.

Action Remove the INBUFTYPE parameter from the entry and retry the operation.

See Also dmconf ig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3355 ERROR: TE_QSPACE entries must not have OUTBUFTYPE specified

Description A dynamic configuration operation specified an invalid BEA TOP END queue space entry parameter in the DM_LOCAL_SERVICES (DM_EXPORT). The OUTBUFTYPE parameter is not allowed for BEA TOP END entries of type QSPACE.

Action Remove the OUTBUFTYPE parameter from the entry and retry the operation.

See Also dmconf ig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3356 ERROR: RNAME not allowed for BEA TOP END LOCAL_SERVICES entries of type QSPACE

Description A dynamic configuration operation specified an invalid BEA TOP END queue space entry parameter in the DM_LOCAL_SERVICES (DM_EXPORT). The RNAME parameter is not allowed for BEA TOP END entries of type QSPACE.

Action Remove the RNAME parameter from the entry and retry the operation.

See Also dmconf ig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3357 ERROR: CONV not allowed for BEA TOP END LOCAL_SERVICES entries of type QSPACE

Description A dynamic configuration operation specified an invalid BEA TOP END queue space entry parameter in the DM_LOCAL_SERVICES (DM_EXPORT) section. The CONV parameter is not allowed for BEA TOP END entries of type QSPACE.

Action Remove the CONV parameter from the entry and retry the operation.

See Also dmconf ig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3358 ERROR: TE_PRODUCT not allowed for BEA TOP END LOCAL_SERVICES entries of type QSPACE

Description A dynamic configuration operation specified an invalid BEA TOP END queue space entry parameter in the DM_LOCAL_SERVICES (DM_EXPORT) section. The TE_PRODUCT parameter is not allowed for BEA TOP END entries of type QSPACE.

Action Remove the TE_PRODUCT parameter from the entry and retry the operation.

See Also dmconf ig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3359 ERROR: TE_FUNCTION not allowed for BEA TOP END LOCAL_SERVICES entries of type QSPACE

Description A dynamic configuration operation specified an invalid BEA TOP END queue space entry parameter in the DM_LOCAL_SERVICES (DM_EXPORT) section. The TE_FUNCTION parameter is not allowed for BEA TOP END entries of type QSPACE.

Action Remove the TE_FUNCTION parameter from the entry and retry the operation.

See Also dmconf ig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3360 ERROR: TE_QUALIFIER not allowed for BEA TOP END LOCAL_SERVICES entries of type QSPACE

Description A dynamic configuration operation specified an invalid BEA TOP END queue space parameter in the DM_LOCAL_SERVICES (DM_EXPORT) section. The TE_QUALIFIER parameter is not allowed for BEA TOP END entries of type QSPACE.

Action Remove the TE_QUALIFIER parameter from the entry and retry the operation.

See Also dmconf ig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3361 ERROR: CODEPAGE not allowed for BEA TOP END LOCAL_SERVICES entries of type QSPACE

Description A dynamic configuration operation specified an invalid BEA TOP END queue space entry parameter in the DM_LOCAL_SERVICES (DM_EXPORT) section. The CODEPAGE parameter is not allowed for BEA TOP END entries of type QSPACE.

Action Remove the CODEPAGE parameter from the entry and retry the operation.

See Also dmconf ig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3362 ERROR: ACL not allowed for BEA TOP END LOCAL_SERVICES entries of type QNAME

Description A dynamic configuration operation specified an invalid BEA TOP END queue name entry parameter in the DM_LOCAL_SERVICES (DM_EXPORT) section. The ACL parameter is not allowed for BEA TOP END entries of type QNAME.

Action Remove the ACL parameter from the entry and retry the operation.

See Also dmconf ig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3363 ERROR: TE_QNAME entries must not have OUTBUFTYPE specified

Description A dynamic configuration operation specified an invalid BEA TOP END queue name entry parameter in the DM_LOCAL_SERVICES (DM_EXPORT) section. The OUTBUFTYPE parameter is not allowed for BEA TOP END entries of type QNAME.

Action Remove the OUTBUFTYPE parameter from the entry and retry the operation.

See Also dmconf ig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3364 ERROR: TE_PRODUCT and TE_FUNCTION required for entries of type TE_SERVICE or TE_QNAME

Description A dynamic configuration operation did not specify all required BEA TOP END queue name entry parameters in the DM_LOCAL_SERVICES (DM_EXPORT) section. Both the TE_PRODUCT and TE_FUNCTION parameters are required for BEA TOP END entries of type QNAME.

Action Modify the entry to include both TE_PRODUCT and TE_FUNCTION values and retry the operation.

See Also dmconf ig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3365 ERROR: RNAME not allowed for BEA TOP END LOCAL_SERVICES entries of type QNAME

Description A dynamic configuration operation specified an invalid BEA TOP END queue name entry parameter in the DM_LOCAL_SERVICES (DM_EXPORT) section. The RNAME parameter is not allowed for BEA TOP END entries of type QNAME.

Action Remove the RNAME parameter from the entry and retry the operation.

See Also dmconf ig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3366 ERROR: CONV not allowed for BEA TOP END LOCAL_SERVICES entries of type QNAME

Description A dynamic configuration operation specified an invalid BEA TOP END queue name entry parameter in the DM_LOCAL_SERVICES (DM_EXPORT) section. The CONV parameter is not allowed for BEA TOP END entries of type QNAME.

Action Remove the CONV parameter from the entry and retry the operation.

See Also dmconf ig for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

- 3367 ERROR: TE_RTQGROUP not allowed for BEA TOP END LOCAL_SERVICES entries of type QNAME**
- Description** A dynamic configuration operation specified an invalid BEA TOP END queue name entry parameter in the DM_EXPORT (DM_LOCAL_SERVICES) section. The TE_RTQGROUP parameter is not allowed for BEA TOP END entries of type QNAME.
- Action** Remove the TE_RTQGROUP parameter from the entry and retry the operation.
- See Also** dmconf ig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3368 ERROR: TE_RTQNAME not allowed for BEA TOP END LOCAL_SERVICES entries of type QNAME**
- Description** A dynamic configuration operation specified an invalid BEA TOP END queue name entry parameter in the DM_LOCAL_SERVICES (DM_EXPORT) section. The TE_RTQNAME parameter is not allowed for BEA TOP END entries of type QNAME.
- Action** Remove the TE_RTQNAME parameter from the entry and retry the operation.
- See Also** dmconf ig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3369 ERROR: CODEPAGE not allowed for BEA TOP END LOCAL_SERVICES entries of type QNAME**
- Description** A dynamic configuration operation specified an invalid BEA TOP END queue name entry parameter in the DM_LOCAL_SERVICES (DM_EXPORT) section. The CODEPAGE parameter is not allowed for BEA TOP END entries of type QNAME.
- Action** Remove the CODEPAGE parameter from the entry and retry the operation.
- See Also** dmconf ig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3371 ERROR: INBUFTYPE for BEA TOP END domains limited to FML32, CARRAY, or X_OCTET**
- Description** An invalid value for the INBUFTYPE parameter was specified in a DM_LOCAL_SERVICES (DM_EXPORT) entry during dynamic configuration. The TOP END domain gateway only supports FML32, CARRAY, and X_OCTET buffer types.
- Action** Modify the entry to assign a supported value to the INBUFTYPE parameter and retry the operation.
- See Also** dmconf ig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3372 ERROR: OUTBUFTYPE for BEA TOP END domains limited to FML32, CARRAY, or X_OCTET**
- Description** An invalid value for the OUTBUFTYPE parameter was specified in a DM_LOCAL_SERVICES (DM_EXPORT) entry during dynamic configuration. The TOP END domain gateway only supports FML32, CARRAY, and X_OCTET buffer types.
- Action** Modify the entry to assign a supported value to the OUTBUFTYPE parameter and retry the operation.
- See Also** dmconf ig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3373 ERROR: RNAME not allowed for BEA TOP END REMOTE_SERVICES entries of type SERVICE**
- Description** A dynamic configuration operation specified an invalid BEA TOP END service entry parameter in the DM_REMOTE_SERVICES (DM_IMPORT) section. The RNAME parameter is not allowed for BEA TOP END entries of type SERVICE.
- Action** Remove the RNAME parameter from the entry and retry the operation.
- See Also** dmconf ig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3374 ERROR: TE_PRODUCT and TE_FUNCTION required for entries of type TE_SERVICE or TE_QNAME**
- Description** A dynamic configuration operation did not specify all required BEA TOP END service entry parameters in the DM_LOCAL_SERVICES (DM_EXPORT) section. Both the TE_PRODUCT and TE_FUNCTION parameters are required for BEA TOP END entries of type SERVICE.
- Action** Modify the entry to include both TE_PRODUCT and TE_FUNCTION values and retry the operation.
- See Also** dmconf ig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3375 ERROR: TE_RTQGROUP not allowed for BEA TOP END REMOTE_SERVICES entries of type SERVICE**

- Description** A dynamic configuration operation specified an invalid BEA TOP END service entry parameter in the DM_REMOTE_SERVICES (DM_IMPORT) section. The TE_RTQGROUP parameter is not allowed for BEA TOP END entries of type SERVICE.
- Action** Remove the TE_RTQGROUP parameter from the entry and retry the operation.
- See Also** dmconf ig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3376 ERROR: TE_RTQNAME not allowed for BEA TOP END REMOTE_SERVICES entries of type SERVICE**
- Description** A dynamic configuration operation specified an invalid BEA TOP END service entry parameter in the DM_REMOTE_SERVICES (DM_IMPORT) section. The TE_RTQNAME parameter is not allowed for BEA TOP END entries of type SERVICE.
- Action** Remove the TE_RTQGROUP parameter from the entry and retry the operation.
- See Also** dmconf ig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3377 ERROR: CODEPAGE not allowed for BEA TOP END REMOTE_SERVICES entries of type SERVICE**
- Description** A dynamic configuration operation specified an invalid BEA TOP END service entry parameter in the DM_REMOTE_SERVICES (DM_IMPORT) section. The CODEPAGE parameter is not allowed for BEA TOP END entries of type SERVICE.
- Action** Remove the CODEPAGE parameter from the entry and retry the operation.
- See Also** dmconf ig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3378 ERROR: TE_QSPACE entries must not have INBUFTYPE specified**
- Description** A dynamic configuration operation specified an invalid BEA TOP END queue space entry parameter in the DM_REMOTE_SERVICES (DM_IMPORT) section. The INBUFTYPE parameter is not allowed for BEA TOP END entries of type QSPACE.
- Action** Remove the INBUFTYPE parameter from the entry and retry the operation.
- See Also** dmconf ig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3379 ERROR: TE_QSPACE entries must not have OUTBUFTYPE specified**
- Description** A dynamic configuration operation specified an invalid BEA TOP END queue space entry parameter in the DM_REMOTE_SERVICES (DM_IMPORT) section. The OUTBUFTYPE parameter is not allowed for BEA TOP END entries of type QSPACE.
- Action** Remove the OUTBUFTYPE parameter from the entry and retry the operation.
- See Also** dmconf ig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3380 ERROR: RNAME not allowed for BEA TOP END REMOTE_SERVICES entries of type QSPACE**
- Description** A dynamic configuration operation specified an invalid BEA TOP END queue space entry parameter in the DM_REMOTE_SERVICES (DM_IMPORT) section. The RNAME parameter is not allowed for BEA TOP END entries of type QSPACE.
- Action** Remove the RNAME parameter from the entry and retry the operation.
- See Also** dmconf ig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3381 ERROR: TE_RTQGROUP and TE_RTQNAME required for TE_QSPACE entries**
- Description** A dynamic configuration operation did not specify all required BEA TOP END queue space entry parameters in the DM_REMOTE_SERVICES (DM_IMPORT) section. Both the TE_RTQGROUP and TE_RTQNAME parameters are required for BEA TOP END entries of type QSPACE.
- Action** Modify the entry to include both TE_PRODUCT and TE_FUNCTION values and retry the operation.
- See Also** dmconf ig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3382 ERROR: CONV not allowed for BEA TOP END REMOTE_SERVICES entries of type QSPACE**
- Description** A dynamic configuration operation specified an invalid BEA TOP END queue space entry parameter in the DM_REMOTE_SERVICES (DM_IMPORT) section. The CONV parameter is not allowed for BEA TOP END entries of type QSPACE.

- Action** Remove the CONV parameter from the entry and retry the operation.
- See Also** dmconf ig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3383 ERROR: TE_PRODUCT not allowed for BEA TOP END REMOTE_SERVICES entries of type QSPACE**
- Description** A dynamic configuration operation specified an invalid BEA TOP END queue space entry parameter in the DM_REMOTE_SERVICES (DM_IMPORT) section. The TE_PRODUCT parameter is not allowed for BEA TOP END entries of type QSPACE.
- Action** Remove the TE_PRODUCT parameter from the entry and retry the operation.
- See Also** dmconf ig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3384 ERROR: TE_FUNCTION not allowed for BEA TOP END REMOTE_SERVICES entries of type QSPACE**
- Description** A dynamic configuration operation specified an invalid BEA TOP END queue space entry parameter in the DM_REMOTE_SERVICES (DM_IMPORT) section. The TE_FUNCTION parameter is not allowed for BEA TOP END entries of type QSPACE.
- Action** Remove the TE_FUNCTION parameter from the entry and retry the operation.
- See Also** dmconf ig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3385 ERROR: TE_QUALIFIER not allowed for BEA TOP END REMOTE_SERVICES entries of type QSPACE**
- Description** A dynamic configuration operation specified an invalid BEA TOP END queue space entry parameter in the DM_REMOTE_SERVICES (DM_IMPORT) section. The TE_QUALIFIER parameter is not allowed for BEA TOP END entries of type QSPACE.
- Action** Remove the TE_QUALIFIER parameter from the entry and retry the operation.
- See Also** dmconf ig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3386 ERROR: CODEPAGE not allowed for BEA TOP END REMOTE_SERVICES entries of type QSPACE**
- Description** A dynamic configuration operation specified an invalid BEA TOP END queue space entry parameter in the DM_REMOTE_SERVICES (DM_IMPORT) section. The CODEPAGE parameter is not allowed for BEA TOP END entries of type QSPACE.
- Action** Remove the CODEPAGE parameter from the entry and retry the operation.
- See Also** dmconf ig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3387 ERROR: TE_PRODUCT and TE_FUNCTION required for entries of type TE_SERVICE or TE_QNAME**
- Description** A dynamic configuration operation did not specify all required BEA TOP END queue name entry parameters in the DM_REMOTE_SERVICES (DM_IMPORT) section. Both the TE_PRODUCT and TE_FUNCTION parameters are required for BEA TOP END entries of type QNAME.
- Action** Modify the entry to include both TE_PRODUCT and TE_FUNCTION values and retry the operation.
- See Also** dmconf ig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3388 ERROR: TE_QNAME entries must not have OUTBUFTYPE specified**
- Description** A dynamic configuration operation specified an invalid BEA TOP END queue name entry parameter in the DM_REMOTE_SERVICES (DM_IMPORT) section. The OUTBUFTYPE parameter is not allowed for BEA TOP END entries of type QNAME.
- Action** Remove the OUTBUFTYPE parameter from the entry and retry the operation.
- See Also** dmconf ig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3389 ERROR: RNAME not allowed for BEA TOP END REMOTE_SERVICES entries of type QNAME**
- Description** A dynamic configuration operation specified an invalid BEA TOP END queue name entry parameter in the DM_REMOTE_SERVICES (DM_IMPORT) section. The RNAME parameter is not allowed for BEA TOP END entries of type QNAME.
- Action** Remove the RNAME parameter from the entry and retry the operation.
- See Also** dmconf ig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway

- 3390 ERROR: CONV not allowed for BEA TOP END REMOTE_SERVICES entries of type QNAME**
- Description** A dynamic configuration operation specified an invalid BEA TOP END queue name entry parameter in the DM_REMOTE_SERVICES (DM_IMPORT) section. The CONV parameter is not allowed for BEA TOP END entries of type QNAME.
- Action** Remove the CONV parameter from the entry and retry the operation.
- See Also** dmconfig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3391 ERROR: TE_RTQGROUP not allowed for BEA TOP END REMOTE_SERVICES entries of type QNAME**
- Description** A dynamic configuration operation specified an invalid BEA TOP END queue name entry parameter in the DM_REMOTE_SERVICES (DM_IMPORT) section. The TE_RTQGROUP parameter is not allowed for BEA TOP END entries of type QNAME.
- Action** Remove the TE_RTQGROUP parameter from the entry and retry the operation.
- See Also** dmconfig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3392 ERROR: TE_RTQNAME not allowed for BEA TOP END REMOTE_SERVICES entries of type QNAME**
- Description** A dynamic configuration operation specified an invalid BEA TOP END queue name entry parameter in the DM_REMOTE_SERVICES (DM_IMPORT) section. The TE_RTQNAME parameter is not allowed for BEA TOP END entries of type QNAME.
- Action** Remove the TE_RTQNAME parameter from the entry and retry the operation.
- See Also** dmconfig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3393 ERROR: CODEPAGE not allowed for BEA TOP END REMOTE_SERVICES entries of type QNAME**
- Description** A dynamic configuration operation specified an invalid BEA TOP END queue name entry parameter in the DM_REMOTE_SERVICES (DM_IMPORT) section. The CODEPAGE parameter is not allowed for BEA TOP END entries of type QNAME.
- Action** Remove the CODEPAGE parameter from the entry and retry the operation.
- See Also** dmconfig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3395 ERROR: INBUFTYPE for BEA TOP END domains limited to FML32, CARRAY, or X_OCTET**
- Description** An invalid value for the INBUFTYPE parameter was specified in a DM_REMOTE_SERVICES (DM_IMPORT) entry during dynamic configuration. The TOP END domain gateway only supports FML32, CARRAY, and X_OCTET buffer types.
- Action** Modify the entry to assign a supported value to the INBUFTYPE parameter and retry the operation.
- See Also** dmconfig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3396 ERROR: OUTBUFTYPE for BEA TOP END domains limited to FML32, CARRAY, or X_OCTET**
- Description** An invalid value for the OUTBUFTYPE parameter was specified in a DM_REMOTE_SERVICES (DM_IMPORT) entry during dynamic configuration. The TOP END domain gateway only supports FML32, CARRAY, and X_OCTET buffer types.
- Action** Modify the entry to assign a supported value to the OUTBUFTYPE parameter and retry the operation.
- See Also** dmconfig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3397 ERROR: _dmcfg_open failed: Can't open DM_TOPEND section**
- Description** During an attempt to re-encrypt BEA TOP END passwords, the DM_TOPEND section of the bdmconfig could not be opened.
- Action** Make sure that the bdmconfig file still exists.
- See Also** dmconfig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway
- 3398 ERROR: TE_PRODUCT and TE_FUNCTION required for entries of type TE_SERVICE or TE_QNAME**
- Description** A DM_LOCAL_SERVICES (DM_EXPORT) entry of type TE_QNAME in the dmconfig file did not have either a TE_PRODUCT or a TE_FUNCTION value specified. Both TE_PRODUCT and TE_FUNCTION values must be present for TE_QNAME entries.

Action Correct the entry to include both `TE_PRODUCT` and `TE_FUNCTION` values.

See Also `dmconfig` for `GWTOPEND(5)`

Using the BEA TUXEDO TOP END Domain Gateway

3399 ERROR: TE_PRODUCT and TE_FUNCTION required for entries of type TE_SERVICE or TE_QNAME

Description A `DM_REMOTE_SERVICES (DM_IMPORT)` entry of type `TE_QNAME` in the `dmconfig` file did not have either a `TE_PRODUCT` or a `TE_FUNCTION` value specified. Both `TE_PRODUCT` and `TE_FUNCTION` values must be present for `TE_QNAME` entries.

Action Correct the entry to include both `TE_PRODUCT` and `TE_FUNCTION` values.

See Also `dmconfig` for `GWTOPEND(5)`

Using the BEA TUXEDO TOP END Domain Gateway

CMDGW Messages 3400-3499

3400 ERROR: Cannot create encryption schedule

Description While processing the DM_TOPEND section of the DMCONFIG file, encryption initialization failed.

Action Please contact your BEA Customer Support.

3401 ERROR: Failed to encrypt password

Description While processing the DM_TOPEND section of the DMCONFIG file, the BEA TOP END password entry field could not be initialized.

Action Please contact your BEA Customer Support.

3403 ERROR: NWDEVICE file *nwdevice* must be an absolute pathname

Description The NWDEVICE *nwdevice* in the DM_TOPEND section of the DMCONFIG file must be an absolute pathname.

Action Change the value for the NWDEVICE to an absolute pathname in the DMCONFIG file.

See Also `dmconfig` for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3409 ERROR: Error obtaining Local Domain Password

Description The `topendpasswd` command failed because `dmadmin` could not open the terminal device (`/dev/tty`) for reading.

Action Please contact your BEA Customer Support.

3410 ERROR: Error obtaining Local Domain Password

Description The `topendpasswd` command failed because `dmadmin` could not open the terminal device (`/dev/tty`) for reading.

Action Please contact your BEA Customer Support.

3412 ERROR: Too many failed attempts

Description The `topendpasswd` command requires that a new password be entered and re-entered identically. If after three attempts this does not occur, the command fails and prints this error message.

Action Retry the `topendpasswd` command.

See Also `dmadmin(1)`, `topendpasswd(1)`, `dmconfig` for GWTOPEND(5)

Using the BEA TUXEDO TOP END Domain Gateway

3413 ERROR: Cannot create encryption key

Description The encryption key could not be created while attempting to encrypt the BEA TOP END password in the `topendpasswd` command.

Action Verify that the BDMCONFIG file exists, and make sure that the operating system parameters are set correctly for the amount of memory on the machine and the amount of memory that can be used by a process. Reduce the memory usage on the machine or increase the amount of physical memory on the machine.

See Also `dmadmin(1)`, `topendpasswd(1)`, `dmconfig` for GWTOPEND(5)

3414 ERROR: Cannot create encryption schedule

Description As part of changing the BEA TOP END domain password with the `topendpasswd` command, the new password is encrypted before writing it to the BDMCONFIG file. The two-way encryption algorithm requires that an encryption schedule be created for use by the encryption routine. This message is issued when the key used for encrypting the new password cannot be generated because memory for the key cannot be allocated dynamically from the operating system using `malloc`.

Action Make sure that the operating system parameters are set correctly for the amount of memory on the machine and the amount of memory that can be used by a process. Reduce the memory usage on the machine or increase the amount of physical memory on the machine.

3415 ERROR: Failed to encrypt password

Description As part of changing the BEA TOP END domain password with the `topendpasswd` command, the new password is encrypted before writing it to the BDMCONFIG file. This message is issued if the encryption algorithm fails.

Action Please contact your BEA Customer Support.

3418 ERROR: Cannot get sizes for TOPEND related sections of bdmconfig file

Description While determining the size of shared memory, the DMADM administrative server could not access or determine the size of the DM_TOPEND section of the BDMCONFIG file.

Action Make sure that the BDMCONFIG file still exists.

See Also DMADM(1), dmconfig for GWTOPEND(5)

3419 ERROR: Application security not enabled

Description A dynamic configuration request was specified for the DM_PASSWORD section of the BDMCONFIG file. The application is not configured for use with security so the request is not applicable.

Action Reconfigure the application to specify a security level in the UBBCONFIG file.

See Also ubbconfig(5), dmadmin(1)

3420 ERROR: FML buffer type cannot be specified for INBUFTYPE or OUTBUFTYPE when LACCESS-POINT is OSITP

Description While processing the DM_LOCAL_SERVICES (DM_EXPORT) section of the DMCONFIG file an error was detected for an OSITP entry. DM_LOCAL_SERVICES (DM_EXPORT) entries with an LACCESS-POINT (LDM) value of type OSITP must specify INBUFTYPE or OUTBUFTYPE if the ACN parameter is set to UDT. FML and FML32 buffer types are not acceptable values for INBUFTYPE or OUTBUFTYPE in this configuration.

Action Specify a supported buffer type for INBUFTYPE or OUTBUFTYPE.

See Also dmconfig(5)

3421 ERROR: Unknown SECURITY type <security_type>. Only NONE, APP_PW, DM_PW, CLEAR, SAFE and PRIVATE are recognized

Description The SECURITY parameter *security_type* in the DM_LOCAL_DOMAINS (DM_LOCAL) section of the DMCONFIG file is invalid. CLEAR, SAFE, and PRIVATE are the security parameters recognized by the TOP END Domain Gateway.

Action Specify a valid value and reload the configuration file.

See Also dmconfig(5), dmconfig for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway

3422 ERROR: FML buffer type cannot be specified for INBUFTYPE or OUTBUFTYPE when LACCESS-POINT is OSITP

Description While processing the DM_REMOTE_SERVICES (DM_IMPORT) section of the DMCONFIG file an error was detected for an OSITP entry. DM_REMOTE_SERVICES (DM_IMPORT) entries with an LACCESS-POINT (LDM) value of type OSITP must specify INBUFTYPE or OUTBUFTYPE if the ACN parameter is set to UDT. FML and FML32 buffer types are not acceptable values for INBUFTYPE or OUTBUFTYPE in this configuration.

Action Specify a supported buffer type for INBUFTYPE or OUTBUFTYPE.

See Also dmconfig(5)

3423 ERROR: Duplicate service name (service_name) occurs in *DM_LOCAL_SERVICES section

Description An error was detected while processing the DMCONFIG file. The service name *service_name* appears more than once in the DM_LOCAL_SERVICES (DM_EXPORT) section.

Action Correct the error and re-load the configuration.

See Also dmconfig(5)

3424 ERROR: Duplicate service:LDM:RDM combination exists for val in *DM_REMOTE_SERVICES section

Description An error was detected while processing the DMCONFIG file. While processing the DM_REMOTE_SERVICES (DM_IMPORT) section a duplicate entry service was found. The mapping of remote services to local access points must be unique within a configuration.

Action Correct the DMCONFIG file to contain only unique service entries in the DM_REMOTE_SERVICES (DM_IMPORT) section.

See Also dmconfig(5)

3435 ERROR: Unknown SECURITY type <val>. Only NONE, APP_PW, DM_PW and CLEAR, SAFE and PRIVATE, for TOP END Domain Gateways, are recognized

Description During dynamic configuration, the SECURITY parameter *security_type* specified in the DM_LOCAL_DOMAINS (DM_LOCAL) section is invalid.

Action Specify a valid value and reattempt the operation.

See Also `dmconfig(5)`, `dmconfig` for GWTOPEND(5)
Using the BEA TUXEDO TOP END Domain Gateway

3436 WARN: For remote service *import*, ROUTING(route) will not be used since RDOM(raccesspoint) is specified.

Description If RDOM (IMPORT) and ROUTING are specified for a DM_REMOTE_SERVICE (DM_IMPORT) entry in the DMCONFIG file, then all the requests will be sent to remote domain *raccesspoint*. For *route* to take effect, set RDOM to NULL.

Action No action required.

See Also `dmconfig(5)`

3437 ERROR: Duplicate remote service entries for *string* for same LDOM should have the same ROUTING criterion if RDOM is different

Description If entries in DM_REMOTE_SERVICES (DM_IMPORT) section of the DMCONFIG file have the same LDOM (LACCESSPOINT) value, then they should also have the same ROUTING criterion if RDOM (RACCESSPOINT) is different.

Action Correct the error and re-load the configuration.

See Also `dmconfig(5)`

3441 ERROR: Cannot have more than *num* entries in RACCESSPOINT LIST

Description The `dmloadcf(1)` utility detected an error while processing the DMCONFIG file. When using Domains-level failover, you may specify a comma-separated list for RDOM (RACCESSPOINT) in a DM_REMOTE_SERVICES (DM_IMPORT) entry. A maximum of three entries are allowed: RDOM=R1, R2, R3.

Action Change the value of the RDOM (RACCESSPOINT) parameter specifying a maximum of three values.

See Also `dmloadcf(1)`, `dmconfig(5)`

3442 ERROR: Unknown FIELDTYPE for XML routing

Description The `dmloadcf(1)` utility detected an error while processing the DMCONFIG file. The FIELDTYPE parameter in the *DM_ROUTING section is set to an invalid setting for XML routing.

Action Correct the entry in the *DM_ROUTING section and retry the operation.

See Also `dmloadcf(1)`, `dmconfig(5)`

3443 ERROR: Unknown BUFTYPE = *val*, Only STRING, X_OCTET, CARRAY, FML, FML32, VIEW, VIEW32, X_C_TYPE, X_COMMON, and XML are known

Description The `dmloadcf(1)` utility detected an error while processing the DMCONFIG file. The FIELDTYPE parameter in the *DM_ROUTING section is set to an invalid setting for XML routing.

Action Correct the entry in the *DM_ROUTING section and retry the operation.

See Also `dmloadcf(1)`, `dmconfig(5)`

3444 ERROR: Specified Local domain access point *val* not active or not configured

Description An error was detected while trying to load the `dmconfig(5)` file as a result of the `dmloadcf` command. The buffer type *type* specified is not a valid buffer type.

Action Replace the parameter specification in error with one of the valid buffer types listed above and reload the configuration.

See Also `dmconfig(5)`

3445 ERROR: Cannot access \$TUXDIR/udataobj/DMTYPE to check domain type

Description The Domain type specified in the TA_DMTYPE attribute (TDOMAIN/OSITP/...) cannot be validated because the file specified in the error message cannot be accessed.

Action The problem may be that of a missing file, or incorrect permissions to the file or to a directory in the pathname of the file. Correct the problem.

3446 ERROR: TA_DMTYPE must be specified in \$TUXDIR/udataobj/DMTYPE

Description The Domain type specified in the TA_DMTYPE does not exist in the \$TUXDIR/udataobj/DMTYPE file.

- Action** Check whether the correct domain type is specified in `TA_DMTYPE`, and also check if the software for this domain type has been installed.
- 3450 ERROR: GW_SEGSIZE must be a number, using calculated size**
- Description** The environment variable `GW_SEGSIZE` must be specified with digit. If it contains none digit GWADM will ignore this environmental variable and, create shared memory using size calculated internally.
- Action** Shutdown the affected gateway group. Correct the `GW_SEGSIZE` environmental. And then reboot the gateway group.
- See Also** `tmbboot`, `ubbconfig`
- 3451 ERROR: GW_SEGSIZE has too many digits, only 9 permitted**
- Description** The environment variable `GW_SEGSIZE` specified too large, it will be ignored by GWADM.
- Action** Shutdown the affected gateway group. Correct the `GW_SEGSIZE` environmental. And then reboot the gateway group.
- See Also** `tmbboot`, `ubbconfig`
- 3452 ERROR: GW_SEGSIZE must be greater than 0, using calculated size**
- Description** The environment variable `GW_SEGSIZE` specified can not be 0 or negative. If it is 0 or of negative value GWADM will ignore this environmental variable, and create shared memory using size calculated internally.
- Action** Shutdown the affected gateway group. Correct the `GW_SEGSIZE` environmental. And then reboot the gateway group.
- See Also** `tmbboot`, `ubbconfig`
- 3453 INFO: GW_SEGSIZE specified is smaller than calculated, use calculated size**
- Description** The environment variable `GW_SEGSIZE` specified is smaller than needed to hold the configuration in shared memroy. The Gateway Administrative server GWADM will ignore this environmental variable, and create shared memory using size calculated internally.
- Action** Shutdown the affected gateway group. Correct the `GW_SEGSIZE` environmental. And then reboot the gateway group.
- See Also** `tmbboot`, `ubbconfig`
- 3454 INFO: New segment size = *val***
- Description** The Gateway Administrative server GWADM will use the segment size specified in `GW_SEGSIZE` environmental variable to create shared memory.
- Action** Informational only, no action need to be taken.
- 3455 ERROR: Remote user mapping deleted successfully but can't delete the PRINAPPKEY entry *val***
- Description** The Domain configuration update operation successfully deleted the original local principal to remote principal mapping. But was not able to find the local principal's `APPKEY`.
- Action** This can happen if the user already deleted from the `tpusr` file, and this change already detected by GWADM and removed it.
- 3456 ERROR: Remote user mapping deleted successfully but can't find corresponding PRINAPPKEY entry to delete**
- Description** The Domain configuration update operation successfully deleted the original local principal to remote principal mapping. But was not able to find the local principal's `APPKEY`.
- Action** This can happen if the user already been removed from the `tpusr` file, and this change already detected by GWADM and removed it. Or the user has not been added to `tpusr` file yet.
- 3457 ERROR: Can't setup principal-appkey mappings**
- Description** The Domain configuration update operation successfully updated the local principal to remote principal mapping. But was not able to update the local principal's `APPKEY` information in shared memory.
- Action** This is caused by not able to expand shared memory. Shutdown the Gateway group and reboot it to grab more shared memory.
- 3460 ERROR: Failed to map request**
- Description** An invalid request buffer was passed to the Domain Admin server (`DMADM`).
- Action** Check the validity of all attributes of the request and also that the request buffer was an FML32 typed buffer. If message persists, contact BEA Customer Support.
- 3461 ERROR: Failed to map reply**
- Description** An invalid reply buffer was returned by core MIB modules, in response to the current request.

- Action** Contact BEA Customer Support.
- 3462 ERROR: Failed to map reply**
- Description** An invalid reply buffer was returned by core MIB modules, in response to the current request.
- Action** Contact BEA Customer Support.
- 3463 ERROR: MIB initialisation failed.**
- Description** An internal inconsistency has been detected during the Domains MIB initialisation.
- Action** Contact BEA Customer Support.
- 3464 ERROR: memory allocation failure**
- Description** The Domain Administrative server detected an error while trying to decode a MIB request. An error occurred while trying to allocate virtual memory.
- Action** Attempt to identify and stop any extraneous processes to free up virtual memory on your system.
- 3465 ERROR: memory allocation failure**
- Description** The Domain Administrative server detected an error while trying to decode a MIB request. An error occurred while trying to allocate virtual memory.
- Action** Attempt to identify and stop any extraneous processes to free up virtual memory on your system.
- 3466 ERROR: FML buffer inconsistency**
- Description** An internal inconsistency has been detected in the FML request buffer while decoding a Domains MIB request.
- Action** Contact BEA Customer Support.
- 3467 ERROR: internal table bad**
- Description** An inconsistency has been detected in an internal table of the DMADM server.
- Action** Shutdown and restart the DMADM server. If the condition persists, contact BEA Customer Support.
- 3468 ERROR: unable to read request buffer**
- Description** A Domains MIB request buffer is unreadable.
- Action** Correct the format of the Domains MIB request. If the condition persists, contact BEA Customer Support.
- 3469 ERROR: failed to create internal table**
- Description** The DMADM server failed to create an internal table.
- Action** Contact BEA Customer Support.
- 3470 ERROR: attribute value not defined in class class.**
- Description** *attribute* with *value* does not identify an instance of *class*.
- Action** Correct *attribute* and resubmit the MIB request.
- 3471 ERROR: Invalid LACCESSPOINT/RACCESSPOINT pair laccesspoint/raccesspoint for operation.**
- Description** One of *laccesspoint* or *raccesspoint* does not identify an existing access point, or the accesspoint is of an incompatible type for the operation.
- Action** Ensure the access points are defined and that their domain types are correct.
- 3472 ERROR: Record not found in class classname.**
- Description** No instance of the class *classname* was identified by the request.
- Action** Correct the selection attributes to identify an existing instance of the class and resubmit the request.
- 3473 ERROR: field name: String value "field value" must be <= length characters in length**
- Description** An error was detected by the Domain Administrative server while processing a MIB request. The value *field value* found for entry *field name* is too long. The value must be less than or equal to *length* characters in length.
- Action** Correct the value *field value* for the entry *field name* and retry the operation.
- 3474 ERROR: field_name: Numeric value must be <= maximum**
- Description** The Domain Administrative server detected an error while processing a MIB request. The value of field *field_name* must be less than or equal to *maximum*.
- Action** Correct the value and retry the operation.
- See Also** DMIB(5)
- 3475 ERROR: field_name: Numeric value must be >= minimum**

Description The Domain Administrative server detected an error while processing a MIB request. The value of field *field_name* must be greater than or equal to *minimum*.

Action Correct the value and retry the operation.

See Also DMIB(5)

3476 ERROR: *field_name*: Numeric value must be >= *minimum* and <= *maximum*

Description The Domain Administrative server detected an error while processing a MIB request. The value of field *field_name* must be greater than or equal to *minimum* and less than or equal to *maximum*.

Action Correct the value and retry the operation.

See Also DMIB(5)

3477 ERROR: *field_name*: Value required for operation but not provided.

Description An error was detected by the Domain Administrative server while processing a MIB request. The field *field_name* was found with no associated value. A value must be provided for this field.

Action Provide a valid value for the field *field_name* and retry the operation.

See Also DMIB(5)

3478 ERROR: *field_name*: Invalid value.

Description An error was detected by the Domain Administrative server while processing a MIB request. The field *field_name* was found to have an invalid value.

Action Provide a valid value for the field *field_name* and retry the operation.

See Also DMIB(5)

3479 ERROR: Error reading class *class_name* from BDMCONFIG

Description An error was encountered while reading the referenced class *section_name* from the Domain Configuration file (BDMCONFIG). The BDMCONFIG file is a binary file in the BEA TUXEDO VTOC format. Each DMIB class is stored as a separate table in the BDMCONFIG file. An error occurred while reading from a section of the BDMCONFIG.

Action If the BDMCONFIG file is a regular file, the file system that it is in should be checked to see if it has enough free space and if its permissions allow writing. If the BDMCONFIG VTOC is being used to hold only the BDMCONFIG tables (and not the TLOG or a BEA TUXEDO database), then the first thing to try is to recreate a new BDMCONFIG. If the BDMCONFIG is a regular file, simply remove it. If it is stored on raw disk, erase it by doing:

```
echo "" > $BDMCONFIG
```

If the error persists, check for disk-type error conditions that might cause problems writing to files. Finally, contact BEA Customer Support, making sure to have the vtoc_errno that was printed in the error message.

See Also dmconfig(5)

3480 ERROR: Operation not allowed on instance *instance_name* of class *class_name* when GWADM is booted

Description An error was detected by the Domain Administrative server while processing a DMIB request. The operation attempted on entry *instance_name* of class *class_name* can not be performed when the Gateway Administrative Server (GWADM) is active.

Action Shut down the Gateway Administrative Server (GWADM) and retry the operation.

See Also DMIB(5)

3481 ERROR: Operation not allowed on *field_name* field of entry *entry_name* of class *class_name* when GWADM is booted

Description An error was detected by the Domain Administrative server while processing a MIB request. The operation attempted on field *field_name* of instance *entry_name* of class *class_name* can not be performed when the Gateway Administrative Server (GWADM) is active.

Action Shut down the Gateway Administrative Server (GWADM) and retry the operation.

See Also DMIB(1)

3482 ERROR: Field referenced by class *class_name*.

- Description** An error was detected by the Domain Administrative server while processing a MIB request. A delete operation was attempted on either a local access point (T_DM_LOCAL class) or remote access point (T_DM_REMOTE class) while the access point was being referenced by an instance of the class *class_name*. An access point cannot be deleted while a reference to it exists.
- Action** Remove all references to the access point which you are attempting to delete and retry the operation.
- See Also** DMIB(1)
- 3483 ERROR: Attempted to add a duplicate record to class *class_name*.**
- Description** An error was detected by the Domain Administrative server while processing a MIB request. An add operation was attempted for an instance which already exists in the class *class_name*. A duplicate entry cannot be added.
- Action** Either rename the entry which you are attempting to add or delete the existing entry and retry the operation.
- See Also** DMIB(5)
- 3484 ERROR: Out of space for class *class_name* in BDMCONFIG**
- Description** An error was detected by the Domain Administrative server while processing a MIB request. An add operation was attempted for an instance of the class *class_name* without adequate space available for the expanded class.
- Action** If there are any extraneous or unused entries in the named class you may try to remove them to free the necessary space and retry the operation. Another option would be to partition the application among two or more domains; in effect, reducing the space required for the class in any single domain.
- See Also** DMIB(5)
- 3485 ERROR: GWADM server propagation - cannot convert class *class_name* request to DMADM format**
- Description** An error was detected converting the MIB request into DMADM format for propagation to relevant GWADM servers. Although the request has been applied to the BDMCONFIG file, it has not been applied to active GWADM servers.
- Action** Contact BEA Customer Support.
- 3486 ERROR: cannot propagate class *val* request to GWADM server(s)**
- Description** An error was detected propagating the MIB request to relevant GWADM servers. Although the request has been applied to the BDMCONFIG file, it has not been applied to one or more active GWADM servers.
- Action** Check that all GWADM servers are running, and restart if necessary. If a GWADM server has stopped, then it will pick up the MIB changes during initialization when it restarts.
- 3489 ERROR: Cannot access TUXCONFIG file to validate TA_DMSRVGROUP in T_DM_LOCAL class**
- Description** The Domain Administrative server was unable to access the BEA TUXEDO system configuration file TUXCONFIG
- Action** Check the surrounding messages for information to correct the problem. Correct the source of the problem and retry the operation.
- See Also** DMIB(1)
- 3490 ERROR: Cannot access \$TUXDIR/udataobj/DMTYPE to validate TA_DMTYPE**
- Description** The Domain type specified in the TA_DMTYPE attribute (TDOMAIN/OSITP/ . . .) cannot be validated because the file specified in the error message cannot be accessed.
- Action** The problem may be that of a missing file, or incorrect permissions to the file or to a directory in the pathname of the file. Correct the problem.
- 3491 ERROR: TA_DMTYPE must match one in \$TUXDIR/udataobj/DMTYPE**
- Description** The Domain type specified in the request does not exist in the \$TUXDIR/udataobj/DMTYPE file.
- Action** Check whether the correct domain type is specified in TA_DMTYPE, and also check that the software for this domain type has been installed.
- 3492 ERROR: TA_DMACCESSPOINTID - invalid characters for TOPEND user id.**
- Description** While processing a MIB request to create or update a T_DM_LOCAL class instance, an invalid value was detected for the TA_DMACCESSPOINTID field. The field contains invalid characters for a TOPEND user ID.
- Action** Remove the invalid characters and reattempt the operation.
- See Also** DMIB(5)

3495 ERROR: TA_DMACCESSPOINTID must be unique across local & remote access points

Description An error was detected by the Domain Administrative server while processing a MIB request. The TA_DMACCESSPOINTID attribute specified was found to be a duplicate of a TA_DMACCESSPOINTID attribute of an existing entry in either of the T_DM_LOCAL or T_DM_REMOTE classes.

Action Correct the value of the TA_DMACCESSPOINTID attribute and retry the operation.

See Also DMIB(5)

3496 ERROR: TA_DMTLOGDEV/TA_DMTLOGNAME must be unique across T_DM_LOCAL class instances

Description The domain administrative server detected an error while trying to process a MIB request for the T_DM_LOCAL class. The combination of the TA_DMTLOGDEV and TA_DMTLOGNAME attributes must be unique across local access points.

Action Correct the TA_DMTLOGDEV / TA_DMTLOGNAME parameter combination so that it is unique across local access points.

See Also DMIB(5)

3497 ERROR: TA_DMACCESSPOINTID must be unique across local & remote access points

Description An error was detected by the Domain Administrative server while processing a MIB request. The TA_DMACCESSPOINTID attribute specified was found to be a duplicate of a TA_DMACCESSPOINTID attribute of an existing entry in either of the T_DM_LOCAL or T_DM_REMOTE classes.

Action Correct the value of the TA_DMACCESSPOINTID attribute and retry the operation.

See Also DMIB(5)

3498 ERROR: TA_DMAUDITLOG must be an absolute pathname

Description The domain administrative server detected an error while trying to process a MIB request. The TA_DMAUDITLOG attribute specified in the T_DM_LOCAL class was found to contain an invalid path.

Action Correct the TA_DMAUDITLOG attribute and retry the operation.

See Also DMIB(5)