



BEA

WebLogic Server

Programming WebLogic JSP Tag Extensions

BEA WebLogic Server 6.0
Document Date: March 6, 2001

Copyright

Copyright © 2001 BEA Systems, Inc. All Rights Reserved.

Restricted Rights Legend

This software and documentation is subject to and made available only pursuant to the terms of the BEA Systems License Agreement and may be used or copied only in accordance with the terms of that agreement. It is against the law to copy the software except as specifically allowed in the agreement. This document may not, in whole or in part, be copied photocopied, reproduced, translated, or reduced to any electronic medium or machine readable form without prior consent, in writing, from BEA Systems, Inc.

Use, duplication or disclosure by the U.S. Government is subject to restrictions set forth in the BEA Systems License Agreement and in subparagraph (c)(1) of the Commercial Computer Software-Restricted Rights Clause at FAR 52.227-19; subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.227-7013, subparagraph (d) of the Commercial Computer Software--Licensing clause at NASA FAR supplement 16-52.227-86; or their equivalent.

Information in this document is subject to change without notice and does not represent a commitment on the part of BEA Systems. THE SOFTWARE AND DOCUMENTATION ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND INCLUDING WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. FURTHER, BEA Systems DOES NOT WARRANT, GUARANTEE, OR MAKE ANY REPRESENTATIONS REGARDING THE USE, OR THE RESULTS OF THE USE, OF THE SOFTWARE OR WRITTEN MATERIAL IN TERMS OF CORRECTNESS, ACCURACY, RELIABILITY, OR OTHERWISE.

Trademarks or Service Marks

BEA, WebLogic, Tuxedo, and Jolt are registered trademarks of BEA Systems, Inc. How Business Becomes E-Business, BEA WebLogic E-Business Platform, BEA Builder, BEA Manager, BEA eLink, BEA WebLogic Commerce Server, BEA WebLogic Personalization Server, BEA WebLogic Process Integrator, BEA WebLogic Collaborate, BEA WebLogic Enterprise, and BEA WebLogic Server are trademarks of BEA Systems, Inc.

All other product names may be trademarks of the respective companies with which they are associated.

Introduction to BEA WebLogic Server

Part Number	Document Date	Software Version
	March 6, 2001	BEA WebLogic Server Version 6.0

Contents

About This Document

Audience.....	v
e-docs Web Site.....	vi
How to Print the Document.....	vi
Related Information.....	vi
Contact Us!.....	vii
Documentation Conventions.....	vii

1. Overview of Programming JSP Tag Extensions

Overview of Custom Tag Functionality.....	1-1
Using Custom Tags in a JSP.....	1-2
Formatting Custom Tags.....	1-2
Some Example Scenarios.....	1-3
Referencing a Tag Library.....	1-4

2. Quick Start Guide

3. Creating a Tag Library Descriptor

Overview.....	3-1
Writing the Tag Library Descriptor.....	3-2
Sample Tag Library Descriptor.....	3-5

4. Implementing the Tag Handler

Tag Handler API.....	4-1
Tag Handler Life Cycle.....	4-2
Using Tag Attributes.....	4-5
Defining New Scripting Variables.....	4-6
Dynamically Named Scripting Variables.....	4-7
Writing Cooperative Nested Tags.....	4-8

5. Administration and Configuration

Configuring JSP Tag Libraries	5-1
Deploying a JSP Tag Library as a JAR File	5-2

Index

About This Document

This document describes how to write and deploy custom JavaServer Pages (JSP) tags and JSP tag libraries.

The document is organized as follows:

- Chapter 1, “Overview of Programming JSP Tag Extensions,” provides a summary of JSP tag functionality and deployment.
- Chapter 2, “Quick Start Guide,” lists the steps required to create and use custom JSP tags.
- Chapter 3, “Creating a Tag Library Descriptor,” discusses how to create a Tag Library Descriptor (TLD) file.
- Chapter 4, “Implementing the Tag Handler,” describes how to write Java classes that implement the functionality of an extended tag.
- Chapter 5, “Administration and Configuration,” contains an overview of Administration and Configuration tasks for using JSP Tag Extensions.

Audience

This document is written for application developers who want to build e-commerce applications using the Java 2 Platform, Enterprise Edition (J2EE) from Sun Microsystems. It is assumed that readers know Web technologies, object-oriented programming techniques, and the Java programming language.

e-docs Web Site

BEA product documentation is available on the BEA corporate Web site. From the BEA Home page, click on Product Documentation or go directly to the WebLogic Server Product Documentation page at <http://e-docs.bea.com/wls/docs60>.

How to Print the Document

You can print a copy of this document from a Web browser, one main topic at a time, by using the File→Print option on your Web browser.

A PDF version of this document is available on the WebLogic Server documentation Home page on the e-docs Web site (and also on the documentation CD). You can open the PDF in Adobe Acrobat Reader and print the entire document (or a portion of it) in book format. To access the PDFs, open the WebLogic Server documentation Home page, click Download Documentation, and select the document you want to print.

Adobe Acrobat Reader is available at no charge from the Adobe Web site at <http://www.adobe.com>.

Related Information

- [JSP 1.1 Specification](http://java.sun.com/products/jsp/download.html) from Sun Microsystems, available at <http://java.sun.com/products/jsp/download.html>.
- [Programming WebLogic JSP](http://e-docs.bea.com/wls/docs60/jsp/index.html) at <http://e-docs.bea.com/wls/docs60/jsp/index.html>.
- [Deploying and Configuring Web Applications](http://e-docs.bea.com/wls/docs60/adminguide/config_web_app.html) at http://e-docs.bea.com/wls/docs60/adminguide/config_web_app.html.

Contact Us!

Your feedback on BEA documentation is important to us. Send us e-mail at docsupport@bea.com if you have questions or comments. Your comments will be reviewed directly by the BEA professionals who create and update the documentation.

In your e-mail message, please indicate the software name and version your are using, as well as the title and document date of your documentation. If you have any questions about this version of BEA WebLogic Server, or if you have problems installing and running BEA WebLogic Server, contact BEA Customer Support through BEA WebSupport at <http://www.bea.com>. You can also contact Customer Support by using the contact information provided on the Customer Support Card, which is included in the product package.

When contacting Customer Support, be prepared to provide the following information:

- Your name, e-mail address, phone number, and fax number
- Your company name and company address
- Your machine type and authorization codes
- The name and version of the product you are using
- A description of the problem and the content of pertinent error messages

Documentation Conventions

The following documentation conventions are used throughout this document.

Convention	Usage
Ctrl+Tab	Keys you press simultaneously.
<i>italics</i>	Emphasis and book titles.

Convention	Usage
<code>monospace</code> <code>text</code>	Code samples, commands and their options, Java classes, data types, directories, and file names and their extensions. Monospace text also indicates text that you enter from the keyboard. <i>Examples:</i> <pre>import java.util.Enumeration; chmod u+w * config/examples/applications .java config.xml float</pre>
<code>monospace</code> <i>italic</i> <code>text</code>	Variables in code. <i>Example:</i> <pre>String CustomerName;</pre>
UPPERCASE TEXT	Device names, environment variables, and logical operators. <i>Examples:</i> <pre>LPT1 BEA_HOME OR</pre>
<code>{ }</code>	A set of choices in a syntax line.
<code>[]</code>	Optional items in a syntax line. <i>Example:</i> <pre>java utils.MulticastTest -n name -a address [-p portnumber] [-t timeout] [-s send]</pre>
<code> </code>	Separates mutually exclusive choices in a syntax line. <i>Example:</i> <pre>java weblogic.deploy [list deploy undeploy update] password {application} {source}</pre>
<code>...</code>	Indicates one of the following in a command line: <ul style="list-style-type: none"> ■ An argument can be repeated several times in the command line. ■ The statement omits additional optional arguments. ■ You can enter additional parameters, values, or other information

Convention	Usage
-------------------	--------------

- | | |
|---|--|
| . | Indicates the omission of items from a code example or from a syntax line. |
| . | |
| . | |
-



1 Overview of Programming JSP Tag Extensions

The JSP 1.1 Specification introduced the ability to create and use custom tags in JavaServer Pages (JSP). Custom tags are an excellent way to abstract the complexity of business logic from the presentation of Web pages in a way that is easy for the Web author to use and control. You can use custom JSP tag extensions in JSP pages to generate dynamic content, and you can use a variety of Web development tools to create the presentation.

The WebLogic Server fully supports the tag extension mechanism described in the [JSP 1.1 Specification](#) available at <http://java.sun.com/products/jsp/download.html>.

This topic includes the following sections:

- [Overview of Custom Tag Functionality](#)
- [Using Custom Tags in a JSP](#)

Overview of Custom Tag Functionality

You write a custom JSP tag by writing a Java class called a *tag handler*. You write the tag handler class by implementing one of two interfaces, `Tag` or `BodyTag` that define methods that are invoked during the life cycle of the tag or by extending an abstract

base class that implements one of these interfaces. Extending an abstract base class relieves the tag handler class from having to implement all methods in the interfaces and also provides other convenient functionality. The `TagSupport` and `BodyTagSupport` classes implement these interfaces and are included in the API.

One or more custom JSP tags can be included in a *Tag Library*. A tag library is defined by a Tag Library Descriptor (TLD) file. The TLD describes the syntax for each tag and ties it to the Java classes that execute its functionality.

Using Custom Tags in a JSP

Custom tags can perform the following tasks:

- Produce output. The output of the tag is sent to the surrounding scope. The scope can be one of the following:
 - If the tag is included directly in the JSP page, then the surrounding scope is the JSP page output.
 - If the tag is nested within another parent tag, then the output becomes part of the evaluated body of its parent tag.
- Define new objects that can be referenced and used as scripting variables in the JSP page. A tag can introduce fixed-named scripting variables, or can define a dynamically-named scripting variable with the `id` attribute.
- Iterate over their body content until a certain condition is met. Use iteration to create repetitive output, or to repeatedly invoke a server side action.
- Determine whether the rest of the JSP page should be processed as part of the request, or skipped.

Formatting Custom Tags

The format of a custom tag format can be empty, called an *empty tag*, or can contain a body, called a *body tag*. Both types of tags can accept a number of attributes that are passed to the Java class that implements the tag. For more details, see [Using Tag Attributes](#) on page 4-5.

An empty tag takes the following form:

```
<mytaglib:newtag attr1="aaa" attr2="bbb" ... />
```

A body tag takes the following form:

```
<mytaglib:newtag attr1="aaa" attr2="bbb" ... >
  body
</mytaglib:newtag>
```

A tag body can include more JSP syntax, and even other custom JSP tags that also have nested bodies. Tags can be nested within each other to any level. For example:

```
<mytaglib:tagA>
  <h2>This is the body of tagA</h2>
  You have seen this text <mytaglib:counter /> times!
  <p>
    <mytaglib:repeater repeat=4>
      <p>Hello World!
    </mytaglib:repeater>
  </mytaglib:tagA>
```

The preceding example uses three custom tags to illustrate the ability to nest tags within a body tag. The tags function like this:

- The body tag `<mytaglib:tagA>` only sees the HTML output from its evaluated body. That is, the nested JSP tags `<mytaglib:counter>` and `<mytaglib:repeater>` are first evaluated and their output becomes part of the evaluated body of the `<mytaglib:tagA>` tag.
- The body of a body tag is first evaluated as JSP and all tags that it contains are translated, including nested body tags, whose bodies are recursively evaluated. The result of an evaluated body can then be used directly as the output of a body tag, or the body tag can determine its output based on the content of the evaluated body.
- The output generated from the JSP of a body tag is treated as plain HTML. That is, the *output is not further interpreted as JSP*.

Some Example Scenarios

The following scenarios demonstrate what you can do with custom tags:

- An empty tag can perform server-side work based on its attributes. The action that the tag performs can determine whether the rest of the page is interpreted or some other action is taken, such as a redirect. This function is useful for checking that users are logged in before accessing a page, and redirecting them to a login page if necessary.
- An empty tag can insert content into a page based on its attributes. You can use such a tag to implement a simple page-hits counter or another template-based insertion.
- An empty tag can define a server-side object that is available in the rest of the page, based on its attributes. You can use this tag to create a reference to an EJB, which is queried for data elsewhere in the JSP page.
- A body tag has the option to process its output before the output becomes part of the HTML page sent to the browser, evaluate that output, and then determine the resulting HTML that is sent to the browser. This functionality could be used to produce “quoted HTML,” reformatted content, or used as a parameter that you pass to another function, such as an SQL query, where the output of the tag is a formatted result set.
- A body tag can repeatedly process its body until a particular condition is met.

Referencing a Tag Library

JSP tag libraries are defined in a tag library descriptor (`tld`). To use a custom tag library from a JSP page, reference its tag library descriptor with a `<%@ taglib %>` directive. For example:

```
<%@ taglib uri="myTLD" prefix="mytaglib" %>
uri
```

The JSP engine attempts to find the Tag Library Descriptor by matching the `uri` attribute to a `uri` that is defined in the Web Application deployment descriptor (`web.xml`) with the `<taglib-uri>` element. For example, `myTLD` in the above `taglib` directive would reference its tag library descriptor (`library.tld`) in the Web Application deployment descriptor like this:

```
<taglib>
```

```
<taglib-uri>myTLD</taglib-uri>  
<taglib-location>library.tld</taglib-location>  
</taglib>
```

prefix

The `prefix` attribute assigns a label to the tag library. You use this label to reference its associated tag library when writing your pages using custom JSP tags. For example, if the library (called `mytaglib`) from the example above defines a new tag called `newtag`, you would use the tag in your JSP page like this:

```
<mytaglib:newtag>
```

For more information, see [Creating a Tag Library Descriptor](#) on page 3-1.

1 *Overview of Programming JSP Tag Extensions*

2 Quick Start Guide

The following is an overview of the steps required to create and use custom JSP tags. These topics are covered in detail in this document:

1. Write a tag handler class. When you use a custom tag in your JSP, this class executes the functionality of the tag. A tag handler class implements one of two interfaces: `javax.servlet.jsp.tagtext.BodyTag` or `javax.servlet.jsp.tagtext.Tag`. Your tag handler class is implemented as part of a *tag library*. For more information, see [Implementing the Tag Handler](#) on page 4-1.
2. Reference the tag library in your JSP source using the JSP `<taglib>` directive. A tag library is a collection of JSP tags. Include this directive at the top of your JSP source. For more information, see [Referencing a Tag Library](#) on page 1-4.
3. Write the Tag Library Descriptor (TLD). The TLD defines the tag library and provides additional information about each tag, such as the name of the tag handler class, attributes, and other information about the tags. For more information, see [Creating a Tag Library Descriptor](#) on page 3-1.
4. Reference the Tag Library Descriptor in the Web Application deployment descriptor (`web.xml`). For more information, see [Writing Web Application Deployment Descriptors](#) at <http://e-docs.bea.com/wls/docs60/programming/webappdeployment.html>.
5. Use your custom tag in your JSP. For more information, see [Using Custom Tags in a JSP](#) on page 1-2.

3 Creating a Tag Library Descriptor

This section discusses how to create a Tag Library Descriptor (TLD) file. The following topics are discussed:

- [Overview](#)
- [Writing the Tag Library Descriptor](#)
- [Sample Tag Library Descriptor](#)

Overview

A tag library allows a developer to group together tags with related functionality. A tag library uses a tag library Descriptor (tld) file that describes the tag extensions and relates them to their Java classes. WebLogic Server and some authoring tools use the TLD to get information about the extensions. TLD files are written in XML notation.

The syntax for a tag library Descriptor is specified in the document type descriptor (DTD) available at: http://java.sun.com/j2ee/dtds/web-jsptaglibrary_1_1.dtd.

Writing the Tag Library Descriptor

Order the elements in the Tag Library Descriptor file as they are defined in the DTD. This ordering is used in the steps below. The XML parser will throw an exception if you incorrectly order the TLD elements.

The body of the TLD contains additional nested elements inside of the `<taglib> ... </taglib>` element. These nested elements are described in the steps below. For display in this document, nested elements are indented from their parent elements, but indenting is not required in the TLD.

A [Sample Tag Library Descriptor](#) on page 3-5 declares a new tag called `code`. The functionality of this tag is implemented by the Java class `weblogic.taglib.quote.CodeTag`.

To create a tag library descriptor:

1. Create a text file with an appropriate name and the extension `.tld`, and locate it in the `WEB-INF` directory of the Web Application containing your JSP(s). Content beneath the `WEB-INF` directory is non-public and is not served over HTTP by WebLogic Server.

2. Include the following header:

```
<!DOCTYPE taglib PUBLIC "-//Sun Microsystems, Inc.  
//DTD JSP Tag Library 1.1//EN" "web-jsptaglib_1_1.dtd">
```

3. Add the contents of the TLD, embedded in a `<taglib>` element. The contents include elements containing information about the tag library and elements that define each tag. For example:

```
<taglib>  
  ... body of taglib descriptor ...  
</taglib>
```

4. Identify the Tag Library

```
<tlibversion>version_number</tlibversion>  
(Required) The version number of the tag library.
```

```
<jspversion>version_number</jspversion>  
(Optional) The JSP version that this tag library is designed to work  
with. WebLogic supports JSP version 1.1 from this release.
```

`<shortname>TagLibraryName</shortname>`

(Required) Assigns a short name to this tag library. This element is not used by WebLogic Server.

`<uri>unique_string</uri>`

(Optional) This element is not used by WebLogic Server.

`<info>...text...</info>`

(Optional) Use this element to provide a description of the tag library. This element is not used by WebLogic Server.

5. Define a Tag

Use a separate `<tag>` element to define each new tag in the tag library. The `<tag>` element takes the following nested tags:

`<name>tag_name</name>`

(Required) Defines the name of the tag. This is used when referencing the tag in a JSP file, after the “:” symbol, For example:
`<mytaglib:tag_name>`

For more information, see [Using Custom Tags in a JSP](#) on page 1-2.

`<tagclass>package.class.name</tagclass>`

(Required) Declares the tag handler class that implements the functionality of this tag. Specify the fully qualified package name of the class.

Locate the class file under the `WEB-INF/classes` directory, in a directory structure reflecting the package name.

`<teiclass>package.class.name</teiclass>`

(Optional) Declares the subclass of `TagExtraInfo` that describes the scripting variables introduced by this tag. If your tag does not define new scripting variables, it does not use this element. Specify the fully qualified package name of the class.

Place the class files under the `WEB-INF/classes` directory of your Web Application, under a directory structure reflecting the package name.

`<bodycontent>tagdependent | JSP | empty</bodycontent>`

(Optional) Defines the content of the tag body.

`empty` means that you use the tag in the *empty tag* format in the JSP page. For example: `<taglib:tagname/>`

`JSP` means that the contents of the tag can be interpreted as JSP and that you must use the tag in the *body tag* format. For example:

3 Creating a Tag Library Descriptor

```
<taglib:tagname>...</taglib:tagname>.
```

`tagdependent` means that your tag will interpret the contents of the body as non-JSP (for instance an SQL statement).

If the `<bodycontent>` element is not defined, the default value is JSP.

```
<attribute>
```

Use a separate `<attribute>` element to define each attribute that the tag can take. Tag attributes allow the JSP author to alter the behavior of your tags.

```
<name>myAttribute</name>
```

(Required) Defines the name of the attribute as it appears in the tag element in the JSP page. For example:

```
<taglib:mytag myAttribute="myAttributeValue">
```

```
<required>true | false</required>
```

(Optional) Defines whether this attribute has optional use in the JSP page.

If not defined here, the default is `false` — that is, the attribute is optional by default.

If `true` is specified, and the attribute is not used in a JSP page, a translation-time error occurs.

```
<rtexprvalue>true | false</rtexprvalue>
```

(Optional) Defines whether this attribute can take a scriptlet expression as a value, allowing it to be dynamically calculated at request time.

If this element is not specified, the value is presumed to be `false`.

```
</attribute>
```

Sample Tag Library Descriptor

The following is a sample listing of a Taglib Descriptor.

Listing 3-1 Sample Taglib Descriptor (tld)

```
<taglib>

  <tlibversion>1.0</tlibversion>
  <jspversion>1.1</jspversion>
  <shortname>quote</shortname>
  <info>
    This tag library contains several tag extensions
    useful for formatting content for HTML.
  </info>

  <tag>
    <name>code</name>
    <tagclass>weblogic.taglib.quote.CodeTag</tagclass>
    <bodycontent>tagdependent</bodycontent>
    <attribute>
      <name>fontAttributes</name>
    </attribute>
    <attribute>
      <name>commentColor</name>
    </attribute>
    <attribute>
      <name>quoteColor</name>
    </attribute>
  </tag>

</taglib>
```

3 *Creating a Tag Library Descriptor*

4 Implementing the Tag Handler

This section describes how to write Java classes that implement the functionality of an extended tag. The following topics are discussed:

- [Tag Handler API](#)
- [Tag Handler Life Cycle](#)
- [Using Tag Attributes](#)
- [Writing Cooperative Nested Tags](#)

Tag Handler API

The JSP 1.1 API defines a set of classes and interfaces that you use to write custom tag handlers. Documentation for the `javax.servlet.jsp.tagext` API is available at <http://java.sun.com/j2ee/j2sdkee/techdocs/api/index.html>.

Your tag handler must implement one of two interfaces:

Tag

Implement the `javax.servlet.jsp.tagext.Tag` interface if your custom tag is an empty-body tag. The API also provides a convenience class `TagSupport` that implements the `Tag` interface and provides default empty methods for the methods defined in the interface.

BodyTag

Implement the `javax.servlet.jsp.tagext.BodyTag` interface if your custom tag needs to use a body. The API also provides a convenience class `BodyTagSupport` that implements the `BodyTag` interface and provides default empty methods for the methods defined in the interface. Because `BodyTag` extends `Tag` it is a super set of the interface methods.

Tag Handler Life Cycle

The methods inherited from either the `Tag` or `BodyTag` interfaces and implemented by the tag handler class are invoked by the JSP engine at specific points during the processing of the JSP page. These methods signify points in the life cycle of a tag and are executed in the following sequence:

1. When the JSP engine encounters a tag in a JSP page, a new tag handler is initialized. The `setPageContext()` and `setParent()` methods of the `javax.servlet.jsp.tagext.Tag` interface are invoked to set up the environment context for the tag handler. As a tag developer, you need not implement these methods if you extend the `TagSupport` or `BodyTagSupport` base classes.
2. The `setXXXX()` JavaBean-like methods for each tag attribute are invoked. For more details, see [Using Tag Attributes](#) on page 4-5.
3. The `doStartTag()` method is invoked. You can define this method in your tag handler class to initialize your tag handler or open connections to any resources it needs, such as a database.

At the end of the `doStartTag()` method, you can determine if the tag body should be evaluated or not by returning one of the following value constants from your tag handler class:

SKIP_BODY

Directs the JSP engine to skip the body of the tag. Return this value if the tag is an empty-body tag. The body-related parts of the tag's life cycle are skipped, and the next method invoked is `doEndTag()`.

`EVAL_BODY_INCLUDE`

Directs the JSP engine to evaluate and include the content of the tag body. The body-related parts of the tag's life cycle are skipped, and the next method invoked is `doEndTag()`.

You can only return this value for tags that implement the `Tag` interface. This allows you to write a tag that can determine whether its body is included, but is not concerned with the contents of the body. You cannot return this value if your tag implements the `BodyTag` interface (or extends the `BodyTagSupport` class).

`EVAL_BODY_TAG`

Instructs the JSP engine to evaluate the tag body, then invokes the `doInitBody()` method. You can only return this value if your tag implements the `BodyTag` interface (or extends the `BodyTagSupport` class).

4. The `setBodyContent()` method is invoked. At this point, any output from the tag is diverted into a special `JspWriter` called `BodyContent`, and is not sent to the client. All content from evaluating the body is appended to the `BodyContent` buffer. This method allows the tag handler to store a reference to the `BodyContent` buffer so it is available to the `doAfterBody()` method for post-evaluation processing.

If the tag is passing output to the JSP page (or the surrounding tag scope if it is nested), the tag must explicitly write its output to the parent-scoped `JspWriter` between this point in the tag life cycle and the end of the `doEndTag()` method. The tag handler can gain access to the enclosing output using the `getEnclosingWriter()` method.

You do not need to implement this method if you are using the `BodyTagSupport` convenience class, because the tag keeps a reference to the `BodyContent` and makes the reference available through the `getBodyContent()` method.

5. The `doInitBody()` method is invoked. This method allows you to perform some work immediately before the tag body is evaluated for the first time. You might use this opportunity to set up some scripting variables, or to push some content into the `BodyContent` before the tag body. The content you prepend here will *not* be evaluated as JSP—unlike the tag body content from the JSP page.

The significant difference between performing work in this method and performing work at the end of the `doStartTag()` method (once you know you are going to return `EVAL_BODY_TAG`) is that with this method, the scope of the

tag's output is nested and does not go directly to the JSP page (or parent tag). All output is now buffered in a special type of `JspWriter` called `BodyContent`.

6. The `doAfterBody()` method is invoked. This method is called after the body of the tag is evaluated and appended to the `BodyContent` buffer. Your tag handler should implement this method to perform some work based on the evaluated tag body. If your handler extends the convenience class `BodyTagSupport`, you can use the `getBodyContent()` method to access the evaluated body. If you are simply implementing the `BodyTag` interface, you should have defined the `setBodyContent()` method where you stored a reference to the `BodyContent` instance.

At the end of the `doAfterBody()` method, you can determine the life cycle of the tag again by returning one of the following value constants:

`SKIP_BODY`

Directs the JSP engine to continue, not evaluating the body again. The life cycle of the tag skips to the `doEndTag()` method.

`EVAL_BODY_TAG`

Directs the JSP engine to evaluate the body again. The evaluated body is appended to the `BodyContent` and the `doAfterBody()` method is invoked again.

At this point, you may want your tag handler to write output to the surrounding scope. Obtain a writer to the enclosing scope using the `BodyTagSupport.getPreviousOut()` method or the `BodyContent.getEnclosingWriter()` method. Either method obtains the same enclosing writer.

Your tag handler can write the contents of the evaluated body to the surrounding scope, or can further process the evaluated body and write some other output. Because the `BodyContent` is appended to the existing `BodyContent` upon each iteration through the body, you should only write out the entire iterated body content once you decide you are going to return `SKIP_BODY`. Otherwise, you will see the content of each subsequent iteration repeated in the output.

7. The out writer in the `pageContext` is restored to the parent `JspWriter`. This object is actually a stack that is manipulated by the JSP engine on the `pageContext` using the `pushBody()` and `popBody()` methods. Do not, however, attempt to manipulate the stack using these methods in your tag handler.

8. The `doEndTag()` method is invoked. Your tag handler can implement this method to perform post-tag, server side work, write output to the parent scope `JspWriter`, or close resources such as database connections.

Your tag handler writes output directly to the surrounding scope using the `JspWriter` obtained from `pageContext.getOut()` in the `doEndTag()` method. The previous step restored `pageContext.out` to the enclosing writer when `popBody()` was invoked on the `pageContext`.

You can control the flow for evaluation of the rest of the JSP page by returning one of the following values from the `doEngTag()` method:

`EVAL_PAGE`

Directs the JSP engine to continue processing the rest of the JSP page.

`SKIP_PAGE`

Directs the JSP engine to skip the rest of the JSP page.

9. The `release()` method is invoked. This occurs just before the tag handler instance is de-referenced and made available for garbage collection.

Using Tag Attributes

Your custom tags can define any number of attributes that can be specified from the JSP page. You can use these attributes to pass information to the tag handler and customize its behavior.

You declare each attribute name in the TLD, in the `<attribute>` element. This declares the name of the attribute and other attribute properties.

Your tag handler must implement *setter* and *getter* methods based on the attribute name, similar to the JavaBean convention. For example, if you declare an attribute named `foo`, your tag handler must define the following public methods:

```
public void setFoo(String f);
public String getFoo();
```

Note that the first letter of the attribute name is capitalized after the `set/get` prefix.

The JSP engine invokes the setter methods for each attribute appropriately after the tag handler is initialized and before the `doStartTag()` method is called. Generally, you should implement the setter methods to store the attribute value in a member variable that is accessible to the other methods of the tag handler.

Defining New Scripting Variables

Your tag handler can introduce new scripting variables that can be referenced by the JSP page at various scopes. Scripting variables can be used like implicit objects within their defined scope.

Define a new scripting variable by using the `<teiclass>` element to identify a Java class that extends `javax.servlet.jsp.tagext.TagExtraInfo`. For example:

```
<teiclass>weblogic.taglib.session.ListTagExtraInfo</teiclass>
```

Then write the `TagExtraInfo` class. For example:

```
package weblogic.taglib.session;
import javax.servlet.jsp.tagext.*;

public class ListTagExtraInfo extends TagExtraInfo {

    public VariableInfo[] getVariableInfo(TagData data) {
        return new VariableInfo[] {
            new VariableInfo("username",
                "String",
                true,
                VariableInfo.NESTED),
            new VariableInfo("dob",
                "java.util.Date",
                true,
                VariableInfo.NESTED)
        };
    }
}
```

The example above defines a single method, `getVariableInfo()`, which returns an array of `VariableInfo` elements. Each element defines a new scripting variable. The example shown above defines two scripting variables called `username` and `dob` which are of type `java.lang.String` and `java.util.Date` respectively.

The constructor for `VariableInfo()` takes four arguments.

- A `String` that defines the name of the new variable.
- A `String` that defines the Java type of the variable. Give the full package name for types in packages other than the `java.lang` package.
- A `boolean` that declares whether the variable must be instantiated before use. Set this argument to “true” unless your tag handler is written in a language other than Java.
- An `int` declaring the scope of the variable. Use a static field from `VariableInfo` shown here:

`VariableInfo.NESTED`
Available only within the start and end tags of the tag.

`VariableInfo.AT_BEGIN`
Available from the start tag until the end of the page.

`VariableInfo.AT_END`
Available from the end tag until the end of the page.

Configure your tag handler to initialize the value of the scripting variables via the page context. For example, the following Java source could be used in the `doStartTag()` method to initialize the values of the scripting variables defined above:

```
pageContext.setAttribute("name", nameStr);  
pageContext.setAttribute("dob", bday);
```

Where the first parameter names the scripting variable, and the second parameter is the value assigned. Here, the Java variable `nameStr` is of type `String` and `bday` is of type `java.util.Date`.

You can also access variables created with the `TagExtraInfo` class by referencing it the same way you access a `JavaBean` that was created with `useBean`.

Dynamically Named Scripting Variables

It is possible to define the name of a new scripting variable from a tag attribute. This definition allows you to use multiple instances of a tag that define a scripting variable at the same scope, without the scripting variables of the tag clashing. In order to

achieve this from your class that extends `TagExtraInfo`, you must get the name of the scripting variable from the `TagData` that is passed into the `getVariableInfo()` method.

From `TagData`, you can retrieve the value of the attribute that names the scripting variable using the `getAttributeString()` method. There is also the `getId()` method that returns the value of the `id` attribute, which is often used to name a new implicit object from JSP tag.

Writing Cooperative Nested Tags

You can design your tags to implicitly use properties from tags they are nested within. For example, in the code example called SQL Query (see the `samples/examples/jsp/tagext/sql` directory of your WebLogic Server installation) a `<sql:query>` tag is nested within a `<sql:connection>` tag. The query tag searches for a parent scope connection tag and uses the JDBC connection established by the parent scope.

To locate a parent scope tag, your nested tag uses the static `findAncestorWithClass()` method of the `TagSupport` class. The following is an example taken from the `QueryTag` example.

```
try {
    ConnectionTag connTag = (ConnectionTag)
        findAncestorWithClass(this,
            Class.forName("weblogic.taglib.sql.ConnectionTag"));
} catch(ClassNotFoundException cnfe) {
    throw new JspException("Query tag connection "+
        "attribute not nested "+
        "within connection tag");
}
```

This example returns the closest parent tag class whose tag handler class matched the class given. If the direct parent tag is not of this type, then it is parent is checked and so on until a matching tag is found, or a `ClassNotFoundException` is thrown.

Using this feature in your custom tags can simplify the syntax and usage of tags in the JSP page.

5 Administration and Configuration

This section contains an overview of Administration and Configuration tasks for using JSP Tag Extensions and covers the following topics:

- [Configuring JSP Tag Libraries](#)
- [Deploying a JSP Tag Library as a JAR File](#)

Configuring JSP Tag Libraries

The following steps describe how to configure and deploy a JSP tag library. You can also deploy a tag library as a `jar` file (see [Deploying a JSP Tag Library as a JAR File](#) on page 5-2).

1. Create a tag library descriptor (TLD).

For more information, see [Creating a Tag Library Descriptor](#) on page 3-1.

2. Reference this TLD in the Web Application deployment descriptor, `web.xml`.
For example:

```
<taglib>
  <taglib-uri>myTLD</taglib-uri>
  <taglib-location>WEB-INF/library.tld</taglib-location>
</taglib>
```

In this example the tag library descriptor is a file called `library.tld`. Always specify the location of the `tld` relative to the root of the Web Application.

For more information on editing the Web Application deployment descriptor, see [Taglib element](#) at

http://e-docs.bea.com/wls/docs60/programming/web_xml.html#taglib.

3. Place the tag library descriptor file in the `WEB-INF` directory of the Web Application.
4. Reference the tag library in the JSP page

In your JSP, reference the tag library with a JSP directive. For example:

```
<%@ taglib uri="myTLD" prefix="mytaglib" %>
```

For more information on WebLogic JSP, see [Programming WebLogic JSP](#) at <http://e-docs.bea.com/wls/docs60/jsp/index.html>.

5. Place the tag handler Java class files for your tags in the `WEB-INF/classes` directory of your Web Application.
6. Deploy the Web Application on WebLogic Server. For more information, see [Deploying and Configuring Web Applications](#) at http://e-docs.bea.com/wls/docs60/adminguide/config_web_app.html

Deploying a JSP Tag Library as a JAR File

In addition to the procedure described above, you can also deploy a JSP tag library as a `jar` file:

1. Create a TLD (tag library descriptor) file named `taglib.tld`.
For more information, see [Creating a Tag Library Descriptor](#) on page 3-1.
2. Create a directory containing the compiled Java tag handler class files used in your tag library.
3. Create a subdirectory of the above directory called `META-INF`.

4. Copy the `taglib.tld` file you created in step 1. into the `META-INF` directory you created in step 3.
5. Archive your compiled Java class files into a `jar` file by executing the following command from the directory you created in step 2.

```
jar cv0f myTagLibrary.jar
```

(where `myTagLibrary.jar` is a name you provide)

6. Copy the `jar` file into the `WEB-INF/lib` directory of the Web Application that uses your tag library.
7. Reference this tag library descriptor in the Web Application deployment descriptor, `web.xml`. For example:

```
<taglib>
  <taglib-uri>myjar.tld</taglib-uri>
  <taglib-location>
    /WEB-INF/lib/myTagLibrary.jar
  </taglib-location>
</taglib>
```

For more information, see [Writing Web Application Deployment Descriptors](http://e-docs.bea.com/wls/docs60/programming/webappdeployment.html) at <http://e-docs.bea.com/wls/docs60/programming/webappdeployment.html>.

8. Reference the tag library in your JSP. For example:

```
<%@ taglib uri="myjar.tld" prefix="wl" %>
```

Index

B

BodyContent 4-3

bodycontent 3-3

BodyContent.getEnclosingWriter() 4-4

BodyTagSupport.getPreviousOut() 4-4

C

classes, directories 5-2

cooperative nested tags 4-8

customer support contact information vii

D

doAfterBody() 4-4

documentation, where to find it vi

doEndTag() 4-5

doInitBody() 4-3

doStartTag() 4-2

E

EVAL_BODY_INCLUDE 4-3

EVAL_BODY_TAG 4-3, 4-4

EVAL_PAGE 4-5

G

getter method 4-5

J

jar 5-2

javax.servlet.jsp.tagext.BodyTag 4-2

javax.servlet.jsp.tagext.Tag interface 4-1

N

nested tags 4-8

O

out writer 4-4

P

printing product documentation vi

R

release() 4-5

S

scripting variables

- defining 4-6

- dynamically named 4-7

- scope 4-7

setBodyContent() 4-3

setPageContext() 4-2

setter method 4-5

SKIP_BODY 4-2, 4-4

SKIP_PAGE 4-5

support

- technical vii

T

tag attribute

- using 4-5

tag handler 1-1, 4-1

- BodyTag interface 4-2

- life cycle 4-2

- Tag interface 4-1

tag libraries

- classes 5-2

- configuration 5-1

- deploying as jar file 5-2

- overview 1-1

- referencing 1-4

- tag library descriptor 5-1

- tld 5-1

tag library descriptor 3-1

- and Web Applications 3-2

- bodycontent 3-3
- defining 3-3
- DTD 3-1
- sample 3-5
- tagclass 3-3
- tieclass 3-3
- writing 3-2
- tagclass 3-3
- TagExtraInfo 4-6
- taglib directive 1-4
 - prefix 1-5
 - uri 1-4
- tags
 - examples of use 1-3
 - nested, writing 4-8
 - using 1-2
 - writing 2-1
- tieclass 3-3
- tld 3-1, 5-1
 - and Web Application deployment descriptor 5-1
 - and Web Applications 3-2
 - body content 3-3
 - defining 3-3
 - DTD 3-1
 - sample 3-5
 - tagclass 3-3
 - tieclass 3-3
 - writing 3-2

W

- Web Application deployment descriptor 5-1