

MySQL 8.4 Error Message Reference

Abstract

This is the MySQL 8.4 Error Message Reference. It lists all error messages produced by server and client programs in MySQL 8.4. This document accompanies [Error Messages and Common Problems](#), in [MySQL 8.4 Reference Manual](#).

For help with using MySQL, please visit the [MySQL Forums](#), where you can discuss your issues with other MySQL users.

Document generated on: 2025-03-18 (revision: 81229)

Table of Contents

Preface and Legal Notices	v
1 MySQL Error Reference	1
2 Server Error Message Reference	3
3 Client Error Message Reference	431
4 Global Error Message Reference	437
Index	445

Preface and Legal Notices

This is the MySQL 8.4 Error Message Reference. It lists all error messages produced by server and client programs in MySQL 8.4.

Legal Notices

Copyright © 1997, 2025, Oracle and/or its affiliates.

License Restrictions

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

Warranty Disclaimer

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

Restricted Rights Notice

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

Hazardous Applications Notice

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Trademark Notice

Oracle, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

Third-Party Content, Products, and Services Disclaimer

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Use of This Documentation

This documentation is NOT distributed under a GPL license. Use of this documentation is subject to the following terms:

You may create a printed copy of this documentation solely for your own personal use. Conversion to other formats is allowed as long as the actual content is not altered or edited in any way. You shall not publish or distribute this documentation in any form or on any media, except if you distribute the documentation in a manner similar to how Oracle disseminates it (that is, electronically for download on a Web site with the software) or on a CD-ROM or similar medium, provided however that the documentation is disseminated together with the software on the same medium. Any other use, such as any dissemination of printed copies or use of this documentation, in whole or in part, in another publication, requires the prior written consent from an authorized representative of Oracle. Oracle and/or its affiliates reserve any and all rights to this documentation not expressly granted above.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support for Accessibility

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Chapter 1 MySQL Error Reference

This document provides a reference for the various types of error messages in MySQL:

- Error messages produced only by the server: [Chapter 2, *Server Error Message Reference*](#)

On the server side, error messages may occur during the startup and shutdown processes, as a result of issues that occur during SQL statement execution, and so forth.

- The MySQL server writes some error messages to its error log. These indicate issues of interest to database administrators or that require DBA action.
- The server sends other error messages to client programs. These indicate issues pertaining only to a particular client. The MySQL client library takes errors received from the server and makes them available to the host client program.
- Error messages that originate only from within the MySQL client library: [Chapter 3, *Client Error Message Reference*](#)

Client-side error messages are generated from within the MySQL client library, usually involving problems communicating with the server.

- Error messages that are shared between the server and the client library: [Chapter 4, *Global Error Message Reference*](#)

Some “global” error messages are shared in the sense that they can be produced by the MySQL server or by MySQL client programs.

For a description of the types of error information MySQL provides and how to obtain information about them, see [Error Messages and Common Problems](#), in [MySQL 8.4 Reference Manual](#).

Chapter 2 Server Error Message Reference

The MySQL server writes some error messages to its error log, and sends others to client programs.

Example server-side error messages written to the error log:

```
2018-10-28T13:01:32.735983Z 0 [Note] [MY-010303] [Server] Skipping
generation of SSL certificates as options related to SSL are specified.

2018-10-02T03:20:39.410387Z 768 [ERROR] [MY-010045] [Server] Event Scheduler:
[evtuser@localhost][myschema.e_daily] Unknown database 'mydb'
```

Example server-side error message sent to client programs, as displayed by the `mysql` client:

```
mysql> SELECT * FROM no_such_table;
ERROR 1146 (42S02): Table 'test.no_such_table' doesn't exist
```

Each server error message includes an error code, SQLSTATE value, and message string, as described in [Error Message Sources and Elements](#). These elements are available as described in [Error Information Interfaces](#).

In addition to the errors in the following list, the server can also produce error messages that have error codes in the range from 1 to 999. See [Chapter 4, Global Error Message Reference](#)

- Error number: [1002](#); Symbol: [ER_NO](#); SQLSTATE: [HY000](#)

Message: NO

Used in the construction of other messages.

- Error number: [1003](#); Symbol: [ER_YES](#); SQLSTATE: [HY000](#)

Message: YES

Used in the construction of other messages.

Extended [EXPLAIN](#) format generates Note messages. [ER_YES](#) is used in the [Code](#) column for these messages in subsequent [SHOW WARNINGS](#) output.

- Error number: [1004](#); Symbol: [ER_CANT_CREATE_FILE](#); SQLSTATE: [HY000](#)

Message: Can't create file '%s' (errno: %d - %s)

Occurs for failure to create or copy a file needed for some operation.

Possible causes: Permissions problem for source file; destination file already exists but is not writeable.

- Error number: [1005](#); Symbol: [ER_CANT_CREATE_TABLE](#); SQLSTATE: [HY000](#)

Message: Can't create table '%s' (errno: %d - %s)

[InnoDB](#) reports this error when a table cannot be created. If the error message refers to error 150, table creation failed because a [foreign key constraint](#) was not correctly formed. If the error message refers to error -1, table creation probably failed because the table includes a column name that matched the name of an internal [InnoDB](#) table.

- Error number: [1006](#); Symbol: [ER_CANT_CREATE_DB](#); SQLSTATE: [HY000](#)

Message: Can't create database '%s' (errno: %d - %s)

-
- Error number: [1007](#); Symbol: [ER_DB_CREATE_EXISTS](#); SQLSTATE: [HY000](#)
Message: Can't create database '%s'; database exists
An attempt to create a database failed because the database already exists.
Drop the database first if you really want to replace an existing database, or add an [IF NOT EXISTS](#) clause to the [CREATE DATABASE](#) statement if to retain an existing database without having the statement produce an error.
 - Error number: [1008](#); Symbol: [ER_DB_DROP_EXISTS](#); SQLSTATE: [HY000](#)
Message: Can't drop database '%s'; database doesn't exist
 - Error number: [1010](#); Symbol: [ER_DB_DROP_RMDIR](#); SQLSTATE: [HY000](#)
Message: Error dropping database (can't rmdir '%s', errno: %d - %s)
 - Error number: [1012](#); Symbol: [ER_CANT_FIND_SYSTEM_REC](#); SQLSTATE: [HY000](#)
Message: Can't read record in system table
Returned by [InnoDB](#) for attempts to access [InnoDB INFORMATION_SCHEMA](#) tables when [InnoDB](#) is unavailable.
 - Error number: [1013](#); Symbol: [ER_CANT_GET_STAT](#); SQLSTATE: [HY000](#)
Message: Can't get status of '%s' (errno: %d - %s)
 - Error number: [1015](#); Symbol: [ER_CANT_LOCK](#); SQLSTATE: [HY000](#)
Message: Can't lock file (errno: %d - %s)
 - Error number: [1016](#); Symbol: [ER_CANT_OPEN_FILE](#); SQLSTATE: [HY000](#)
Message: Can't open file: '%s' (errno: %d - %s)
[InnoDB](#) reports this error when the table from the [InnoDB data files](#) cannot be found.
 - Error number: [1017](#); Symbol: [ER_FILE_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: Can't find file: '%s' (errno: %d - %s)
 - Error number: [1018](#); Symbol: [ER_CANT_READ_DIR](#); SQLSTATE: [HY000](#)
Message: Can't read dir of '%s' (errno: %d - %s)
 - Error number: [1020](#); Symbol: [ER_CHECKREAD](#); SQLSTATE: [HY000](#)
Message: Record has changed since last read in table '%s'
 - Error number: [1022](#); Symbol: [ER_DUP_KEY](#); SQLSTATE: [23000](#)
Message: Can't write; duplicate key in table '%s'
 - Error number: [1024](#); Symbol: [ER_ERROR_ON_READ](#); SQLSTATE: [HY000](#)
Message: Error reading file '%s' (errno: %d - %s)
 - Error number: [1025](#); Symbol: [ER_ERROR_ON_RENAME](#); SQLSTATE: [HY000](#)

Message: Error on rename of '%s' to '%s' (errno: %d - %s)

- Error number: [1026](#); Symbol: [ER_ERROR_ON_WRITE](#); SQLSTATE: [HY000](#)

Message: Error writing file '%s' (errno: %d - %s)

- Error number: [1027](#); Symbol: [ER_FILE_USED](#); SQLSTATE: [HY000](#)

Message: '%s' is locked against change

- Error number: [1030](#); Symbol: [ER_GET_ERRNO](#); SQLSTATE: [HY000](#)

Message: Got error %d - '%s' from storage engine

Check the %d value to see what the OS error means. For example, 28 indicates that you have run out of disk space.

- Error number: [1031](#); Symbol: [ER_ILLEGAL_HA](#); SQLSTATE: [HY000](#)

Message: Table storage engine for '%s' doesn't have this option

- Error number: [1032](#); Symbol: [ER_KEY_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Can't find record in '%s'

- Error number: [1033](#); Symbol: [ER_NOT_FORM_FILE](#); SQLSTATE: [HY000](#)

Message: Incorrect information in file: '%s'

- Error number: [1034](#); Symbol: [ER_NOT_KEYFILE](#); SQLSTATE: [HY000](#)

Message: Incorrect key file for table '%s'; try to repair it

- Error number: [1035](#); Symbol: [ER_OLD_KEYFILE](#); SQLSTATE: [HY000](#)

Message: Old key file for table '%s'; repair it!

- Error number: [1036](#); Symbol: [ER_OPEN_AS_READONLY](#); SQLSTATE: [HY000](#)

Message: Table '%s' is read only

- Error number: [1037](#); Symbol: [ER_OUTOFMEMORY](#); SQLSTATE: [HY001](#)

Message: Out of memory; restart server and try again (needed %d bytes)

- Error number: [1038](#); Symbol: [ER_OUT_OF_SORTMEMORY](#); SQLSTATE: [HY001](#)

Message: Out of sort memory, consider increasing server sort buffer size

- Error number: [1040](#); Symbol: [ER_CON_COUNT_ERROR](#); SQLSTATE: [08004](#)

Message: Too many connections

- Error number: [1041](#); Symbol: [ER_OUT_OF_RESOURCES](#); SQLSTATE: [HY000](#)

Message: Out of memory; check if mysqld or some other process uses all available memory; if not, you may have to use 'ulimit' to allow mysqld to use more memory or you can add more swap space

- Error number: [1042](#); Symbol: [ER_BAD_HOST_ERROR](#); SQLSTATE: [08S01](#)

Message: Can't get hostname for your address

- Error number: 1043; Symbol: [ER_HANDSHAKE_ERROR](#); SQLSTATE: 08S01

Message: Bad handshake

- Error number: 1044; Symbol: [ER_DBACCESS_DENIED_ERROR](#); SQLSTATE: 42000

Message: Access denied for user '%s'@'%s' to database '%s'

- Error number: 1045; Symbol: [ER_ACCESS_DENIED_ERROR](#); SQLSTATE: 28000

Message: Access denied for user '%s'@'%s' (using password: %s)

- Error number: 1046; Symbol: [ER_NO_DB_ERROR](#); SQLSTATE: 3D000

Message: No database selected

- Error number: 1047; Symbol: [ER_UNKNOWN_COM_ERROR](#); SQLSTATE: 08S01

Message: Unknown command

- Error number: 1048; Symbol: [ER_BAD_NULL_ERROR](#); SQLSTATE: 23000

Message: Column '%s' cannot be null

- Error number: 1049; Symbol: [ER_BAD_DB_ERROR](#); SQLSTATE: 42000

Message: Unknown database '%s'

- Error number: 1050; Symbol: [ER_TABLE_EXISTS_ERROR](#); SQLSTATE: 42S01

Message: Table '%s' already exists

- Error number: 1051; Symbol: [ER_BAD_TABLE_ERROR](#); SQLSTATE: 42S02

Message: Unknown table '%s'

- Error number: 1052; Symbol: [ER_NON_UNIQ_ERROR](#); SQLSTATE: 23000

Message: Column '%s' in %s is ambiguous

```
%s = column name
%s = location of column (for example, "field list")
```

Likely cause: A column appears in a query without appropriate qualification, such as in a select list or ON clause.

Examples:

```
mysql> SELECT i FROM t INNER JOIN t AS t2;
ERROR 1052 (23000): Column 'i' in field list is ambiguous

mysql> SELECT * FROM t LEFT JOIN t AS t2 ON i = i;
ERROR 1052 (23000): Column 'i' in on clause is ambiguous
```

Resolution:

- Qualify the column with the appropriate table name:

```
mysql> SELECT t2.i FROM t INNER JOIN t AS t2;
```

- Modify the query to avoid the need for qualification:

```
mysql> SELECT * FROM t LEFT JOIN t AS t2 USING (i);
```

- Error number: [1053](#); Symbol: [ER_SERVER_SHUTDOWN](#); SQLSTATE: [08S01](#)
Message: Server shutdown in progress
- Error number: [1054](#); Symbol: [ER_BAD_FIELD_ERROR](#); SQLSTATE: [42S22](#)
Message: Unknown column '%s' in '%s'
- Error number: [1055](#); Symbol: [ER_WRONG_FIELD_WITH_GROUP](#); SQLSTATE: [42000](#)
Message: '%s' isn't in GROUP BY
- Error number: [1056](#); Symbol: [ER_WRONG_GROUP_FIELD](#); SQLSTATE: [42000](#)
Message: Can't group on '%s'
- Error number: [1057](#); Symbol: [ER_WRONG_SUM_SELECT](#); SQLSTATE: [42000](#)
Message: Statement has sum functions and columns in same statement
- Error number: [1058](#); Symbol: [ER_WRONG_VALUE_COUNT](#); SQLSTATE: [21S01](#)
Message: Column count doesn't match value count
- Error number: [1059](#); Symbol: [ER_TOO_LONG_IDENT](#); SQLSTATE: [42000](#)
Message: Identifier name '%s' is too long
- Error number: [1060](#); Symbol: [ER_DUP_FIELDNAME](#); SQLSTATE: [42S21](#)
Message: Duplicate column name '%s'
- Error number: [1061](#); Symbol: [ER_DUP_KEYNAME](#); SQLSTATE: [42000](#)
Message: Duplicate key name '%s'
- Error number: [1062](#); Symbol: [ER_DUP_ENTRY](#); SQLSTATE: [23000](#)
Message: Duplicate entry '%s' for key %d
The message returned with this error uses the format string for [ER_DUP_ENTRY_WITH_KEY_NAME](#).
- Error number: [1063](#); Symbol: [ER_WRONG_FIELD_SPEC](#); SQLSTATE: [42000](#)
Message: Incorrect column specifier for column '%s'
- Error number: [1064](#); Symbol: [ER_PARSE_ERROR](#); SQLSTATE: [42000](#)
Message: %s near '%s' at line %d
- Error number: [1065](#); Symbol: [ER_EMPTY_QUERY](#); SQLSTATE: [42000](#)
Message: Query was empty

-
- Error number: [1066](#); Symbol: [ER_NONUNIQ_TABLE](#); SQLSTATE: [42000](#)
Message: Not unique table/alias: '%s'
 - Error number: [1067](#); Symbol: [ER_INVALID_DEFAULT](#); SQLSTATE: [42000](#)
Message: Invalid default value for '%s'
 - Error number: [1068](#); Symbol: [ER_MULTIPLE_PRI_KEY](#); SQLSTATE: [42000](#)
Message: Multiple primary key defined
 - Error number: [1069](#); Symbol: [ER_TOO_MANY_KEYS](#); SQLSTATE: [42000](#)
Message: Too many keys specified; max %d keys allowed
 - Error number: [1070](#); Symbol: [ER_TOO_MANY_KEY_PARTS](#); SQLSTATE: [42000](#)
Message: Too many key parts specified; max %d parts allowed
 - Error number: [1071](#); Symbol: [ER_TOO_LONG_KEY](#); SQLSTATE: [42000](#)
Message: Specified key was too long; max key length is %d bytes
 - Error number: [1072](#); Symbol: [ER_KEY_COLUMN_DOES_NOT_EXIST](#); SQLSTATE: [42000](#)
Message: Key column '%s' doesn't exist in table
 - Error number: [1073](#); Symbol: [ER_BLOB_USED_AS_KEY](#); SQLSTATE: [42000](#)
Message: BLOB column '%s' can't be used in key specification with the used table type
 - Error number: [1074](#); Symbol: [ER_TOO_BIG_FIELDLENGTH](#); SQLSTATE: [42000](#)
Message: Column length too big for column '%s' (max = %lu); use BLOB or TEXT instead
 - Error number: [1075](#); Symbol: [ER_WRONG_AUTO_KEY](#); SQLSTATE: [42000](#)
Message: Incorrect table definition; there can be only one auto column and it must be defined as a key
 - Error number: [1076](#); Symbol: [ER_READY](#); SQLSTATE: [HY000](#)
Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d
 - Error number: [1079](#); Symbol: [ER_SHUTDOWN_COMPLETE](#); SQLSTATE: [HY000](#)
Message: %s: Shutdown complete
 - Error number: [1080](#); Symbol: [ER_FORCING_CLOSE](#); SQLSTATE: [08S01](#)
Message: %s: Forcing close of thread %ld user: '%s'
 - Error number: [1081](#); Symbol: [ER_IPSOCK_ERROR](#); SQLSTATE: [08S01](#)
Message: Can't create IP socket
 - Error number: [1082](#); Symbol: [ER_NO_SUCH_INDEX](#); SQLSTATE: [42S12](#)
Message: Table '%s' has no index like the one used in CREATE INDEX; recreate the table

-
- Error number: [1083](#); Symbol: [ER_WRONG_FIELD_TERMINATORS](#); SQLSTATE: [42000](#)
Message: Field separator argument is not what is expected; check the manual
 - Error number: [1084](#); Symbol: [ER_BLOBS_AND_NO_TERMINATED](#); SQLSTATE: [42000](#)
Message: You can't use fixed rowlength with BLOBs; please use 'fields terminated by'
 - Error number: [1085](#); Symbol: [ER_TEXTFILE_NOT_READABLE](#); SQLSTATE: [HY000](#)
Message: The file '%s' must be in the database directory or be readable by all
 - Error number: [1086](#); Symbol: [ER_FILE_EXISTS_ERROR](#); SQLSTATE: [HY000](#)
Message: File '%s' already exists
 - Error number: [1087](#); Symbol: [ER_LOAD_INFO](#); SQLSTATE: [HY000](#)
Message: Records: %ld Deleted: %ld Skipped: %ld Warnings: %ld
 - Error number: [1088](#); Symbol: [ER_ALTER_INFO](#); SQLSTATE: [HY000](#)
Message: Records: %ld Duplicates: %ld
 - Error number: [1089](#); Symbol: [ER_WRONG_SUB_KEY](#); SQLSTATE: [HY000](#)
Message: Incorrect prefix key; the used key part isn't a string, the used length is longer than the key part, or the storage engine doesn't support unique prefix keys
 - Error number: [1090](#); Symbol: [ER_CANT_REMOVE_ALL_FIELDS](#); SQLSTATE: [42000](#)
Message: You can't delete all columns with ALTER TABLE; use DROP TABLE instead
 - Error number: [1091](#); Symbol: [ER_CANT_DROP_FIELD_OR_KEY](#); SQLSTATE: [42000](#)
Message: Can't DROP '%s'; check that column/key exists
 - Error number: [1092](#); Symbol: [ER_INSERT_INFO](#); SQLSTATE: [HY000](#)
Message: Records: %ld Duplicates: %ld Warnings: %ld
 - Error number: [1093](#); Symbol: [ER_UPDATE_TABLE_USED](#); SQLSTATE: [HY000](#)
Message: You can't specify target table '%s' for update in FROM clause

This error occurs for attempts to select from and modify the same table within a single statement. If the select attempt occurs within a derived table, you can avoid this error by setting the [derived_merge](#) flag of the [optimizer_switch](#) system variable to force the subquery to be materialized into a temporary table, which effectively causes it to be a different table from the one modified. See [Optimizing Derived Tables, View References, and Common Table Expressions with Merging or Materialization](#).
 - Error number: [1094](#); Symbol: [ER_NO_SUCH_THREAD](#); SQLSTATE: [HY000](#)
Message: Unknown thread id: %lu
 - Error number: [1095](#); Symbol: [ER_KILL_DENIED_ERROR](#); SQLSTATE: [HY000](#)
Message: You are not owner of thread %lu
 - Error number: [1096](#); Symbol: [ER_NO_TABLES_USED](#); SQLSTATE: [HY000](#)
-

Message: No tables used

- Error number: 1097; Symbol: [ER_TOO_BIG_SET](#); SQLSTATE: HY000

Message: Too many strings for column %s and SET

- Error number: 1098; Symbol: [ER_NO_UNIQUE_LOGFILE](#); SQLSTATE: HY000

Message: Can't generate a unique log-filename %s.(1-999)

- Error number: 1099; Symbol: [ER_TABLE_NOT_LOCKED_FOR_WRITE](#); SQLSTATE: HY000

Message: Table '%s' was locked with a READ lock and can't be updated

- Error number: 1100; Symbol: [ER_TABLE_NOT_LOCKED](#); SQLSTATE: HY000

Message: Table '%s' was not locked with LOCK TABLES

- Error number: 1101; Symbol: [ER_BLOB_CANT_HAVE_DEFAULT](#); SQLSTATE: 42000

Message: BLOB, TEXT, GEOMETRY or JSON column '%s' can't have a default value

- Error number: 1102; Symbol: [ER_WRONG_DB_NAME](#); SQLSTATE: 42000

Message: Incorrect database name '%s'

- Error number: 1103; Symbol: [ER_WRONG_TABLE_NAME](#); SQLSTATE: 42000

Message: Incorrect table name '%s'

- Error number: 1104; Symbol: [ER_TOO_BIG_SELECT](#); SQLSTATE: 42000

Message: The SELECT would examine more than MAX_JOIN_SIZE rows; check your WHERE and use SET SQL_BIG_SELECTS=1 or SET MAX_JOIN_SIZE=# if the SELECT is okay

- Error number: 1105; Symbol: [ER_UNKNOWN_ERROR](#); SQLSTATE: HY000

Message: Unknown error

- Error number: 1106; Symbol: [ER_UNKNOWN_PROCEDURE](#); SQLSTATE: 42000

Message: Unknown procedure '%s'

- Error number: 1107; Symbol: [ER_WRONG_PARAMCOUNT_TO_PROCEDURE](#); SQLSTATE: 42000

Message: Incorrect parameter count to procedure '%s'

- Error number: 1108; Symbol: [ER_WRONG_PARAMETERS_TO_PROCEDURE](#); SQLSTATE: HY000

Message: Incorrect parameters to procedure '%s'

- Error number: 1109; Symbol: [ER_UNKNOWN_TABLE](#); SQLSTATE: 42S02

Message: Unknown table '%s' in %s

- Error number: 1110; Symbol: [ER_FIELD_SPECIFIED_TWICE](#); SQLSTATE: 42000

Message: Column '%s' specified twice

-
- Error number: [1111](#); Symbol: [ER_INVALID_GROUP_FUNC_USE](#); SQLSTATE: [HY000](#)
Message: Invalid use of group function
 - Error number: [1112](#); Symbol: [ER_UNSUPPORTED_EXTENSION](#); SQLSTATE: [42000](#)
Message: Table '%s' uses an extension that doesn't exist in this MySQL version
 - Error number: [1113](#); Symbol: [ER_TABLE_MUST_HAVE_COLUMNS](#); SQLSTATE: [42000](#)
Message: A table must have at least 1 column
 - Error number: [1114](#); Symbol: [ER_RECORD_FILE_FULL](#); SQLSTATE: [HY000](#)
Message: The table '%s' is full

[InnoDB](#) reports this error when the system tablespace runs out of free space. Reconfigure the system tablespace to add a new data file.
 - Error number: [1115](#); Symbol: [ER_UNKNOWN_CHARACTER_SET](#); SQLSTATE: [42000](#)
Message: Unknown character set: '%s'
 - Error number: [1116](#); Symbol: [ER_TOO_MANY_TABLES](#); SQLSTATE: [HY000](#)
Message: Too many tables; MySQL can only use %d tables in a join
 - Error number: [1117](#); Symbol: [ER_TOO_MANY_FIELDS](#); SQLSTATE: [HY000](#)
Message: Too many columns
 - Error number: [1118](#); Symbol: [ER_TOO_BIG_ROWSIZE](#); SQLSTATE: [42000](#)
Message: Row size too large. The maximum row size for the used table type, not counting BLOBs, is %ld. This includes storage overhead, check the manual. You have to change some columns to TEXT or BLOBs
 - Error number: [1119](#); Symbol: [ER_STACK_OVERRUN](#); SQLSTATE: [HY000](#)
Message: Thread stack overrun: Used: %ld of a %ld stack. Use 'mysqld --thread_stack=#' to specify a bigger stack if needed
 - Error number: [1120](#); Symbol: [ER_WRONG_OUTER_JOIN_UNUSED](#); SQLSTATE: [42000](#)
Message: Cross dependency found in OUTER JOIN; examine your ON conditions
 - Error number: [1121](#); Symbol: [ER_NULL_COLUMN_IN_INDEX](#); SQLSTATE: [42000](#)
Message: Table handler doesn't support NULL in given index. Please change column '%s' to be NOT NULL or use another handler
 - Error number: [1122](#); Symbol: [ER_CANT_FIND_UDF](#); SQLSTATE: [HY000](#)
Message: Can't load function '%s'
 - Error number: [1123](#); Symbol: [ER_CANT_INITIALIZE_UDF](#); SQLSTATE: [HY000](#)
Message: Can't initialize function '%s'; %s
 - Error number: [1124](#); Symbol: [ER_UDF_NO_PATHS](#); SQLSTATE: [HY000](#)

-
- Message: No paths allowed for shared library
- Error number: [1125](#); Symbol: [ER_UDF_EXISTS](#); SQLSTATE: [HY000](#)
Message: Function '%s' already exists
 - Error number: [1126](#); Symbol: [ER_CANT_OPEN_LIBRARY](#); SQLSTATE: [HY000](#)
Message: Can't open shared library '%s' (errno: %d %s)
 - Error number: [1127](#); Symbol: [ER_CANT_FIND_DL_ENTRY](#); SQLSTATE: [HY000](#)
Message: Can't find symbol '%s' in library
 - Error number: [1128](#); Symbol: [ER_FUNCTION_NOT_DEFINED](#); SQLSTATE: [HY000](#)
Message: Function '%s' is not defined
 - Error number: [1129](#); Symbol: [ER_HOST_IS_BLOCKED](#); SQLSTATE: [HY000](#)
Message: Host '%s' is blocked because of many connection errors; unblock with 'mysqladmin flush-hosts'
 - Error number: [1130](#); Symbol: [ER_HOST_NOT_PRIVILEGED](#); SQLSTATE: [HY000](#)
Message: Host '%s' is not allowed to connect to this MySQL server
 - Error number: [1131](#); Symbol: [ER_PASSWORD_ANONYMOUS_USER](#); SQLSTATE: [42000](#)
Message: You are using MySQL as an anonymous user and anonymous users are not allowed to change passwords
 - Error number: [1132](#); Symbol: [ER_PASSWORD_NOT_ALLOWED](#); SQLSTATE: [42000](#)
Message: You must have privileges to update tables in the mysql database to be able to change passwords for others
 - Error number: [1133](#); Symbol: [ER_PASSWORD_NO_MATCH](#); SQLSTATE: [42000](#)
Message: Can't find any matching row in the user table
 - Error number: [1134](#); Symbol: [ER_UPDATE_INFO](#); SQLSTATE: [HY000](#)
Message: Rows matched: %ld Changed: %ld Warnings: %ld
 - Error number: [1135](#); Symbol: [ER_CANT_CREATE_THREAD](#); SQLSTATE: [HY000](#)
Message: Can't create a new thread (errno %d); if you are not out of available memory, you can consult the manual for a possible OS-dependent bug
 - Error number: [1136](#); Symbol: [ER_WRONG_VALUE_COUNT_ON_ROW](#); SQLSTATE: [21S01](#)
Message: Column count doesn't match value count at row %ld
 - Error number: [1137](#); Symbol: [ER_CANT_REOPEN_TABLE](#); SQLSTATE: [HY000](#)
Message: Can't reopen table: '%s'
 - Error number: [1138](#); Symbol: [ER_INVALID_USE_OF_NULL](#); SQLSTATE: [22004](#)

Message: Invalid use of NULL value

- Error number: [1139](#); Symbol: [ER_REGEX_ERROR](#); SQLSTATE: [42000](#)

Message: Got error '%s' from regexp

- Error number: [1140](#); Symbol: [ER_MIX_OF_GROUP_FUNC_AND_FIELDS](#); SQLSTATE: [42000](#)

Message: Mixing of GROUP columns (MIN(),MAX(),COUNT(),...) with no GROUP columns is illegal if there is no GROUP BY clause

- Error number: [1141](#); Symbol: [ER_NONEXISTING_GRANT](#); SQLSTATE: [42000](#)

Message: There is no such grant defined for user '%s' on host '%s'

- Error number: [1142](#); Symbol: [ER_TABLEACCESS_DENIED_ERROR](#); SQLSTATE: [42000](#)

Message: %s command denied to user '%s'@'%s' for table '%s'

- Error number: [1143](#); Symbol: [ER_COLUMNACCESS_DENIED_ERROR](#); SQLSTATE: [42000](#)

Message: %s command denied to user '%s'@'%s' for column '%s' in table '%s'

- Error number: [1144](#); Symbol: [ER_ILLEGAL_GRANT_FOR_TABLE](#); SQLSTATE: [42000](#)

Message: Illegal GRANT/REVOKE command; please consult the manual to see which privileges can be used

- Error number: [1145](#); Symbol: [ER_GRANT_WRONG_HOST_OR_USER](#); SQLSTATE: [42000](#)

Message: The host or user argument to GRANT is too long

- Error number: [1146](#); Symbol: [ER_NO_SUCH_TABLE](#); SQLSTATE: [42S02](#)

Message: Table '%s.%s' doesn't exist

- Error number: [1147](#); Symbol: [ER_NONEXISTING_TABLE_GRANT](#); SQLSTATE: [42000](#)

Message: There is no such grant defined for user '%s' on host '%s' on table '%s'

- Error number: [1148](#); Symbol: [ER_NOT_ALLOWED_COMMAND](#); SQLSTATE: [42000](#)

Message: The used command is not allowed with this MySQL version

- Error number: [1149](#); Symbol: [ER_SYNTAX_ERROR](#); SQLSTATE: [42000](#)

Message: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use

- Error number: [1152](#); Symbol: [ER_ABORTING_CONNECTION](#); SQLSTATE: [08S01](#)

Message: Aborted connection %ld to db: '%s' user: '%s' (%s)

- Error number: [1153](#); Symbol: [ER_NET_PACKET_TOO_LARGE](#); SQLSTATE: [08S01](#)

Message: Got a packet bigger than 'max_allowed_packet' bytes

- Error number: [1154](#); Symbol: [ER_NET_READ_ERROR_FROM_PIPE](#); SQLSTATE: [08S01](#)

Message: Got a read error from the connection pipe

-
- Error number: [1155](#); Symbol: [ER_NET_FCNTL_ERROR](#); SQLSTATE: [08S01](#)
Message: Got an error from fcntl()
 - Error number: [1156](#); Symbol: [ER_NET_PACKETS_OUT_OF_ORDER](#); SQLSTATE: [08S01](#)
Message: Got packets out of order
 - Error number: [1157](#); Symbol: [ER_NET_UNCOMPRESS_ERROR](#); SQLSTATE: [08S01](#)
Message: Couldn't uncompress communication packet
 - Error number: [1158](#); Symbol: [ER_NET_READ_ERROR](#); SQLSTATE: [08S01](#)
Message: Got an error reading communication packets
 - Error number: [1159](#); Symbol: [ER_NET_READ_INTERRUPTED](#); SQLSTATE: [08S01](#)
Message: Got timeout reading communication packets
 - Error number: [1160](#); Symbol: [ER_NET_ERROR_ON_WRITE](#); SQLSTATE: [08S01](#)
Message: Got an error writing communication packets
 - Error number: [1161](#); Symbol: [ER_NET_WRITE_INTERRUPTED](#); SQLSTATE: [08S01](#)
Message: Got timeout writing communication packets
 - Error number: [1162](#); Symbol: [ER_TOO_LONG_STRING](#); SQLSTATE: [42000](#)
Message: Result string is longer than 'max_allowed_packet' bytes
 - Error number: [1163](#); Symbol: [ER_TABLE_CANT_HANDLE_BLOB](#); SQLSTATE: [42000](#)
Message: The used table type doesn't support BLOB/TEXT columns
 - Error number: [1164](#); Symbol: [ER_TABLE_CANT_HANDLE_AUTO_INCREMENT](#); SQLSTATE: [42000](#)
Message: The used table type doesn't support AUTO_INCREMENT columns
 - Error number: [1166](#); Symbol: [ER_WRONG_COLUMN_NAME](#); SQLSTATE: [42000](#)
Message: Incorrect column name '%s'
 - Error number: [1167](#); Symbol: [ER_WRONG_KEY_COLUMN](#); SQLSTATE: [42000](#)
Message: The used storage engine can't index column '%s'
 - Error number: [1168](#); Symbol: [ER_WRONG_MRG_TABLE](#); SQLSTATE: [HY000](#)
Message: Unable to open underlying table which is differently defined or of non-MyISAM type or doesn't exist
 - Error number: [1169](#); Symbol: [ER_DUP_UNIQUE](#); SQLSTATE: [23000](#)
Message: Can't write, because of unique constraint, to table '%s'
 - Error number: [1170](#); Symbol: [ER_BLOB_KEY_WITHOUT_LENGTH](#); SQLSTATE: [42000](#)
Message: BLOB/TEXT column '%s' used in key specification without a key length

-
- Error number: [1171](#); Symbol: [ER_PRIMARY_CANT_HAVE_NULL](#); SQLSTATE: [42000](#)
Message: All parts of a PRIMARY KEY must be NOT NULL; if you need NULL in a key, use UNIQUE instead
 - Error number: [1172](#); Symbol: [ER_TOO_MANY_ROWS](#); SQLSTATE: [42000](#)
Message: Result consisted of more than one row
 - Error number: [1173](#); Symbol: [ER_REQUIRES_PRIMARY_KEY](#); SQLSTATE: [42000](#)
Message: This table type requires a primary key
 - Error number: [1175](#); Symbol: [ER_UPDATE_WITHOUT_KEY_IN_SAFE_MODE](#); SQLSTATE: [HY000](#)
Message: You are using safe update mode and you tried to update a table without a WHERE that uses a KEY column. %s
 - Error number: [1176](#); Symbol: [ER_KEY_DOES_NOT_EXIST](#); SQLSTATE: [42000](#)
Message: Key '%s' doesn't exist in table '%s'
 - Error number: [1177](#); Symbol: [ER_CHECK_NO_SUCH_TABLE](#); SQLSTATE: [42000](#)
Message: Can't open table
 - Error number: [1178](#); Symbol: [ER_CHECK_NOT_IMPLEMENTED](#); SQLSTATE: [42000](#)
Message: The storage engine for the table doesn't support %s
 - Error number: [1179](#); Symbol: [ER_CANT_DO_THIS_DURING_AN_TRANSACTION](#); SQLSTATE: [25000](#)
Message: You are not allowed to execute this command in a transaction
 - Error number: [1180](#); Symbol: [ER_ERROR_DURING_COMMIT](#); SQLSTATE: [HY000](#)
Message: Got error %d - '%s' during COMMIT
 - Error number: [1181](#); Symbol: [ER_ERROR_DURING_ROLLBACK](#); SQLSTATE: [HY000](#)
Message: Got error %d - '%s' during ROLLBACK
 - Error number: [1182](#); Symbol: [ER_ERROR_DURING_FLUSH_LOGS](#); SQLSTATE: [HY000](#)
Message: Got error %d during FLUSH_LOGS
 - Error number: [1184](#); Symbol: [ER_NEW_ABORTING_CONNECTION](#); SQLSTATE: [08S01](#)
Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s)
 - Error number: [1188](#); Symbol: [ER_SOURCE](#); SQLSTATE: [HY000](#)
Message: Error from source: '%s'
 - Error number: [1189](#); Symbol: [ER_SOURCE_NET_READ](#); SQLSTATE: [08S01](#)
Message: Net error reading from source
 - Error number: [1190](#); Symbol: [ER_SOURCE_NET_WRITE](#); SQLSTATE: [08S01](#)
Message: Net error writing to source

-
- Error number: [1191](#); Symbol: [ER_FT_MATCHING_KEY_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: Can't find FULLTEXT index matching the column list
 - Error number: [1192](#); Symbol: [ER_LOCK_OR_ACTIVE_TRANSACTION](#); SQLSTATE: [HY000](#)
Message: Can't execute the given command because you have active locked tables or an active transaction
 - Error number: [1193](#); Symbol: [ER_UNKNOWN_SYSTEM_VARIABLE](#); SQLSTATE: [HY000](#)
Message: Unknown system variable '%s'
 - Error number: [1194](#); Symbol: [ER_CRASHED_ON_USAGE](#); SQLSTATE: [HY000](#)
Message: Table '%s' is marked as crashed and should be repaired
 - Error number: [1195](#); Symbol: [ER_CRASHED_ON_REPAIR](#); SQLSTATE: [HY000](#)
Message: Table '%s' is marked as crashed and last (automatic?) repair failed
 - Error number: [1196](#); Symbol: [ER_WARNING_NOT_COMPLETE_ROLLBACK](#); SQLSTATE: [HY000](#)
Message: Some non-transactional changed tables couldn't be rolled back
 - Error number: [1197](#); Symbol: [ER_TRANS_CACHE_FULL](#); SQLSTATE: [HY000](#)
Message: Multi-statement transaction required more than 'max_binlog_cache_size' bytes of storage; increase this mysqld variable and try again
 - Error number: [1199](#); Symbol: [ER_REPLICA_NOT_RUNNING](#); SQLSTATE: [HY000](#)
Message: This operation requires a running replica; configure replica and do START REPLICA
 - Error number: [1200](#); Symbol: [ER_BAD_REPLICA](#); SQLSTATE: [HY000](#)
Message: The server is not configured as replica; fix in config file or with CHANGE REPLICATION SOURCE TO
 - Error number: [1201](#); Symbol: [ER_CONNECTION_METADATA](#); SQLSTATE: [HY000](#)
Message: Could not initialize connection metadata structure; more error messages can be found in the MySQL error log
 - Error number: [1202](#); Symbol: [ER_REPLICA_THREAD](#); SQLSTATE: [HY000](#)
Message: Could not create replica thread; check system resources
 - Error number: [1203](#); Symbol: [ER_TOO_MANY_USER_CONNECTIONS](#); SQLSTATE: [42000](#)
Message: User %s already has more than 'max_user_connections' active connections
 - Error number: [1204](#); Symbol: [ER_SET_CONSTANTS_ONLY](#); SQLSTATE: [HY000](#)
Message: You may only use constant expressions with SET
 - Error number: [1205](#); Symbol: [ER_LOCK_WAIT_TIMEOUT](#); SQLSTATE: [HY000](#)
Message: Lock wait timeout exceeded; try restarting transaction

InnoDB reports this error when lock wait timeout expires. The statement that waited too long was [rolled back](#) (not the entire [transaction](#)). You can increase the value of the `innodb_lock_wait_timeout` configuration option if SQL statements should wait longer for other transactions to complete, or decrease it if too many long-running transactions are causing [locking](#) problems and reducing [concurrency](#) on a busy system.

- Error number: [1206](#); Symbol: `ER_LOCK_TABLE_FULL`; SQLSTATE: `HY000`

Message: The total number of locks exceeds the lock table size

InnoDB reports this error when the total number of locks exceeds the amount of memory devoted to managing locks. To avoid this error, increase the value of `innodb_buffer_pool_size`. Within an individual application, a workaround may be to break a large operation into smaller pieces. For example, if the error occurs for a large `INSERT`, perform several smaller `INSERT` operations.

- Error number: [1207](#); Symbol: `ER_READ_ONLY_TRANSACTION`; SQLSTATE: `25000`

Message: Update locks cannot be acquired during a READ UNCOMMITTED transaction

- Error number: [1210](#); Symbol: `ER_WRONG_ARGUMENTS`; SQLSTATE: `HY000`

Message: Incorrect arguments to %s

- Error number: [1211](#); Symbol: `ER_NO_PERMISSION_TO_CREATE_USER`; SQLSTATE: `42000`

Message: '%s'@'%s' is not allowed to create new users

- Error number: [1213](#); Symbol: `ER_LOCK_DEADLOCK`; SQLSTATE: `40001`

Message: Deadlock found when trying to get lock; try restarting transaction

InnoDB reports this error when a [transaction](#) encounters a [deadlock](#) and is automatically [rolled back](#) so that your application can take corrective action. To recover from this error, run all the operations in this transaction again. A deadlock occurs when requests for locks arrive in inconsistent order between transactions. The transaction that was rolled back released all its locks, and the other transaction can now get all the locks it requested. Thus, when you re-run the transaction that was rolled back, it might have to wait for other transactions to complete, but typically the deadlock does not recur. If you encounter frequent deadlocks, make the sequence of locking operations (`LOCK TABLES`, `SELECT ... FOR UPDATE`, and so on) consistent between the different transactions or applications that experience the issue. See [Deadlocks in InnoDB](#) for details.

- Error number: [1214](#); Symbol: `ER_TABLE_CANT_HANDLE_FT`; SQLSTATE: `HY000`

Message: The used table type doesn't support FULLTEXT indexes

- Error number: [1215](#); Symbol: `ER_CANNOT_ADD_FOREIGN`; SQLSTATE: `HY000`

Message: Cannot add foreign key constraint

- Error number: [1216](#); Symbol: `ER_NO_REFERENCED_ROW`; SQLSTATE: `23000`

Message: Cannot add or update a child row: a foreign key constraint fails

InnoDB reports this error when you try to add a row but there is no parent row, and a [foreign key constraint](#) fails. Add the parent row first.

- Error number: [1217](#); Symbol: `ER_ROW_IS_REFERENCED`; SQLSTATE: `23000`

Message: Cannot delete or update a parent row: a foreign key constraint fails

InnoDB reports this error when you try to delete a parent row that has children, and a [foreign key constraint](#) fails. Delete the children first.

- Error number: [1218](#); Symbol: [ER_CONNECT_TO_SOURCE](#); SQLSTATE: [08S01](#)
Message: Error connecting to source: %s
- Error number: [1220](#); Symbol: [ER_ERROR_WHEN_EXECUTING_COMMAND](#); SQLSTATE: [HY000](#)
Message: Error when executing command %s: %s
- Error number: [1221](#); Symbol: [ER_WRONG_USAGE](#); SQLSTATE: [HY000](#)
Message: Incorrect usage of %s and %s
- Error number: [1222](#); Symbol: [ER_WRONG_NUMBER_OF_COLUMNS_IN_SELECT](#); SQLSTATE: [21000](#)
Message: The used SELECT statements have a different number of columns
- Error number: [1223](#); Symbol: [ER_CANT_UPDATE_WITH_READLOCK](#); SQLSTATE: [HY000](#)
Message: Can't execute the query because you have a conflicting read lock
- Error number: [1224](#); Symbol: [ER_MIXING_NOT_ALLOWED](#); SQLSTATE: [HY000](#)
Message: Mixing of transactional and non-transactional tables is disabled
- Error number: [1225](#); Symbol: [ER_DUP_ARGUMENT](#); SQLSTATE: [HY000](#)
Message: Option '%s' used twice in statement
- Error number: [1226](#); Symbol: [ER_USER_LIMIT_REACHED](#); SQLSTATE: [42000](#)
Message: User '%s' has exceeded the '%s' resource (current value: %ld)
- Error number: [1227](#); Symbol: [ER_SPECIFIC_ACCESS_DENIED_ERROR](#); SQLSTATE: [42000](#)
Message: Access denied; you need (at least one of) the %s privilege(s) for this operation
- Error number: [1228](#); Symbol: [ER_LOCAL_VARIABLE](#); SQLSTATE: [HY000](#)
Message: Variable '%s' is a SESSION variable and can't be used with SET GLOBAL
- Error number: [1229](#); Symbol: [ER_GLOBAL_VARIABLE](#); SQLSTATE: [HY000](#)
Message: Variable '%s' is a GLOBAL variable and should be set with SET GLOBAL
- Error number: [1230](#); Symbol: [ER_NO_DEFAULT](#); SQLSTATE: [42000](#)
Message: Variable '%s' doesn't have a default value
- Error number: [1231](#); Symbol: [ER_WRONG_VALUE_FOR_VAR](#); SQLSTATE: [42000](#)
Message: Variable '%s' can't be set to the value of '%s'
- Error number: [1232](#); Symbol: [ER_WRONG_TYPE_FOR_VAR](#); SQLSTATE: [42000](#)
Message: Incorrect argument type to variable '%s'

-
- Error number: [1233](#); Symbol: [ER_VAR_CANT_BE_READ](#); SQLSTATE: [HY000](#)
Message: Variable '%s' can only be set, not read
 - Error number: [1234](#); Symbol: [ER_CANT_USE_OPTION_HERE](#); SQLSTATE: [42000](#)
Message: Incorrect usage/placement of '%s'
 - Error number: [1235](#); Symbol: [ER_NOT_SUPPORTED_YET](#); SQLSTATE: [42000](#)
Message: This version of MySQL doesn't yet support '%s'
 - Error number: [1236](#); Symbol: [ER_SOURCE_FATAL_ERROR_READING_BINLOG](#); SQLSTATE: [HY000](#)
Message: Got fatal error %d from source when reading data from binary log: '%s'
 - Error number: [1237](#); Symbol: [ER_REPLICA_IGNORED_TABLE](#); SQLSTATE: [HY000](#)
Message: Replica SQL thread ignored the query because of replicate-*table rules
 - Error number: [1238](#); Symbol: [ER_INCORRECT_GLOBAL_LOCAL_VAR](#); SQLSTATE: [HY000](#)
Message: Variable '%s' is a %s variable
 - Error number: [1239](#); Symbol: [ER_WRONG_FK_DEF](#); SQLSTATE: [42000](#)
Message: Incorrect foreign key definition for '%s': %s
 - Error number: [1240](#); Symbol: [ER_KEY_REF_DO_NOT_MATCH_TABLE_REF](#); SQLSTATE: [HY000](#)
Message: Key reference and table reference don't match
 - Error number: [1241](#); Symbol: [ER_OPERAND_COLUMNS](#); SQLSTATE: [21000](#)
Message: Operand should contain %d column(s)
 - Error number: [1242](#); Symbol: [ER_SUBQUERY_NO_1_ROW](#); SQLSTATE: [21000](#)
Message: Subquery returns more than 1 row
 - Error number: [1243](#); Symbol: [ER_UNKNOWN_STMT_HANDLER](#); SQLSTATE: [HY000](#)
Message: Unknown prepared statement handler (%.*s) given to %s
 - Error number: [1244](#); Symbol: [ER_CORRUPT_HELP_DB](#); SQLSTATE: [HY000](#)
Message: Help database is corrupt or does not exist
 - Error number: [1246](#); Symbol: [ER_AUTO_CONVERT](#); SQLSTATE: [HY000](#)
Message: Converting column '%s' from %s to %s
 - Error number: [1247](#); Symbol: [ER_ILLEGAL_REFERENCE](#); SQLSTATE: [42S22](#)
Message: Reference '%s' not supported (%s)
 - Error number: [1248](#); Symbol: [ER_DERIVED_MUST_HAVE_ALIAS](#); SQLSTATE: [42000](#)
Message: Every derived table must have its own alias

-
- Error number: [1249](#); Symbol: [ER_SELECT_REDUCED](#); SQLSTATE: [01000](#)
Message: Select %u was reduced during optimization
 - Error number: [1250](#); Symbol: [ER_TABLENAME_NOT_ALLOWED_HERE](#); SQLSTATE: [42000](#)
Message: Table '%s' from one of the SELECTs cannot be used in %s
 - Error number: [1251](#); Symbol: [ER_NOT_SUPPORTED_AUTH_MODE](#); SQLSTATE: [08004](#)
Message: Client does not support authentication protocol requested by server; consider upgrading MySQL client
 - Error number: [1252](#); Symbol: [ER_SPATIAL_CANT_HAVE_NULL](#); SQLSTATE: [42000](#)
Message: All parts of a SPATIAL index must be NOT NULL
 - Error number: [1253](#); Symbol: [ER_COLLATION_CHARSET_MISMATCH](#); SQLSTATE: [42000](#)
Message: COLLATION '%s' is not valid for CHARACTER SET '%s'
 - Error number: [1256](#); Symbol: [ER_TOO_BIG_FOR_UNCOMPRESS](#); SQLSTATE: [HY000](#)
Message: Uncompressed data size too large; the maximum size is %d (probably, length of uncompressed data was corrupted)
 - Error number: [1257](#); Symbol: [ER_ZLIB_Z_MEM_ERROR](#); SQLSTATE: [HY000](#)
Message: ZLIB: Not enough memory
 - Error number: [1258](#); Symbol: [ER_ZLIB_Z_BUF_ERROR](#); SQLSTATE: [HY000](#)
Message: ZLIB: Not enough room in the output buffer (probably, length of uncompressed data was corrupted)
 - Error number: [1259](#); Symbol: [ER_ZLIB_Z_DATA_ERROR](#); SQLSTATE: [HY000](#)
Message: ZLIB: Input data corrupted
 - Error number: [1260](#); Symbol: [ER_CUT_VALUE_GROUP_CONCAT](#); SQLSTATE: [HY000](#)
Message: Row %u was cut by GROUP_CONCAT()
 - Error number: [1261](#); Symbol: [ER_WARN_TOO_FEW_RECORDS](#); SQLSTATE: [01000](#)
Message: Row %ld doesn't contain data for all columns
 - Error number: [1262](#); Symbol: [ER_WARN_TOO_MANY_RECORDS](#); SQLSTATE: [01000](#)
Message: Row %ld was truncated; it contained more data than there were input columns
 - Error number: [1263](#); Symbol: [ER_WARN_NULL_TO_NOTNULL](#); SQLSTATE: [22004](#)
Message: Column set to default value; NULL supplied to NOT NULL column '%s' at row %ld
 - Error number: [1264](#); Symbol: [ER_WARN_DATA_OUT_OF_RANGE](#); SQLSTATE: [22003](#)
Message: Out of range value for column '%s' at row %ld
 - Error number: [1265](#); Symbol: [WARN_DATA_TRUNCATED](#); SQLSTATE: [01000](#)

Message: Data truncated for column '%s' at row %ld

- Error number: 1266; Symbol: ER_WARN_USING_OTHER_HANDLER; SQLSTATE: HY000

Message: Using storage engine %s for table '%s'

- Error number: 1267; Symbol: ER_CANT_AGGREGATE_2COLLATIONS; SQLSTATE: HY000

Message: Illegal mix of collations (%s,%s) and (%s,%s) for operation '%s'

- Error number: 1269; Symbol: ER_REVOKE_GRANTS; SQLSTATE: HY000

Message: Can't revoke all privileges for one or more of the requested users

- Error number: 1270; Symbol: ER_CANT_AGGREGATE_3COLLATIONS; SQLSTATE: HY000

Message: Illegal mix of collations (%s,%s), (%s,%s), (%s,%s) for operation '%s'

- Error number: 1271; Symbol: ER_CANT_AGGREGATE_NCOLLATIONS; SQLSTATE: HY000

Message: Illegal mix of collations for operation '%s'

- Error number: 1272; Symbol: ER_VARIABLE_IS_NOT_STRUCT; SQLSTATE: HY000

Message: Variable '%s' is not a variable component (can't be used as XXXX.variable_name)

- Error number: 1273; Symbol: ER_UNKNOWN_COLLATION; SQLSTATE: HY000

Message: Unknown collation: '%s'

- Error number: 1274; Symbol: ER_REPLICA_IGNORED_SSL_PARAMS; SQLSTATE: HY000

Message: SSL parameters in CHANGE REPLICATION SOURCE are ignored because this MySQL replica was compiled without SSL support; they can be used later if MySQL replica with SSL is started

- Error number: 1276; Symbol: ER_WARN_FIELD_RESOLVED; SQLSTATE: HY000

Message: Field or reference '%s%s%s%s%s%' of SELECT #%d was resolved in SELECT #%d

- Error number: 1277; Symbol: ER_BAD_REPLICA_UNTIL_COND; SQLSTATE: HY000

Message: Incorrect parameter or combination of parameters for START REPLICA UNTIL

- Error number: 1278; Symbol: ER_MISSING_SKIP_REPLICA; SQLSTATE: HY000

Message: It is recommended to use --skip-replica-start when doing step-by-step replication with START REPLICA UNTIL; otherwise, you will get problems if you get an unexpected replica's mysqld restart

- Error number: 1279; Symbol: ER_UNTIL_COND_IGNORED; SQLSTATE: HY000

Message: SQL thread is not to be started so UNTIL options are ignored

- Error number: 1280; Symbol: ER_WRONG_NAME_FOR_INDEX; SQLSTATE: 42000

Message: Incorrect index name '%s'

- Error number: 1281; Symbol: ER_WRONG_NAME_FOR_CATALOG; SQLSTATE: 42000

Message: Incorrect catalog name '%s'

-
- Error number: [1283](#); Symbol: [ER_BAD_FT_COLUMN](#); SQLSTATE: [HY000](#)
Message: Column '%s' cannot be part of FULLTEXT index
 - Error number: [1284](#); Symbol: [ER_UNKNOWN_KEY_CACHE](#); SQLSTATE: [HY000](#)
Message: Unknown key cache '%s'
 - Error number: [1285](#); Symbol: [ER_WARN_HOSTNAME_WONT_WORK](#); SQLSTATE: [HY000](#)
Message: MySQL is started in --skip-name-resolve mode; you must restart it without this switch for this grant to work
 - Error number: [1286](#); Symbol: [ER_UNKNOWN_STORAGE_ENGINE](#); SQLSTATE: [42000](#)
Message: Unknown storage engine '%s'
 - Error number: [1287](#); Symbol: [ER_WARN_DEPRECATED_SYNTAX](#); SQLSTATE: [HY000](#)
Message: '%s' is deprecated and will be removed in a future release. Please use %s instead
 - Error number: [1288](#); Symbol: [ER_NON_UPDATABLE_TABLE](#); SQLSTATE: [HY000](#)
Message: The target table %s of the %s is not updatable
 - Error number: [1289](#); Symbol: [ER_FEATURE_DISABLED](#); SQLSTATE: [HY000](#)
Message: The '%s' feature is disabled; you need MySQL built with '%s' to have it working
 - Error number: [1290](#); Symbol: [ER_OPTION_PREVENTS_STATEMENT](#); SQLSTATE: [HY000](#)
Message: The MySQL server is running with the %s option so it cannot execute this statement
 - Error number: [1291](#); Symbol: [ER_DUPLICATED_VALUE_IN_TYPE](#); SQLSTATE: [HY000](#)
Message: Column '%s' has duplicated value '%s' in %s
 - Error number: [1292](#); Symbol: [ER_TRUNCATED_WRONG_VALUE](#); SQLSTATE: [22007](#)
Message: Truncated incorrect %s value: '%s'
 - Error number: [1294](#); Symbol: [ER_INVALID_ON_UPDATE](#); SQLSTATE: [HY000](#)
Message: Invalid ON UPDATE clause for '%s' column
 - Error number: [1295](#); Symbol: [ER_UNSUPPORTED_PS](#); SQLSTATE: [HY000](#)
Message: This command is not supported in the prepared statement protocol yet
 - Error number: [1296](#); Symbol: [ER_GET_ERRMSG](#); SQLSTATE: [HY000](#)
Message: Got error %d '%s' from %s
 - Error number: [1297](#); Symbol: [ER_GET_TEMPORARY_ERRMSG](#); SQLSTATE: [HY000](#)
Message: Got temporary error %d '%s' from %s
 - Error number: [1298](#); Symbol: [ER_UNKNOWN_TIME_ZONE](#); SQLSTATE: [HY000](#)
Message: Unknown or incorrect time zone: '%s'

-
- Error number: 1299; Symbol: ER_WARN_INVALID_TIMESTAMP; SQLSTATE: HY000
Message: Invalid TIMESTAMP value in column '%s' at row %ld
 - Error number: 1300; Symbol: ER_INVALID_CHARACTER_STRING; SQLSTATE: HY000
Message: Invalid %s character string: '%s'
 - Error number: 1301; Symbol: ER_WARN_ALLOWED_PACKET_OVERFLOWED; SQLSTATE: HY000
Message: Result of %s() was larger than max_allowed_packet (%ld) - truncated
 - Error number: 1302; Symbol: ER_CONFLICTING_DECLARATIONS; SQLSTATE: HY000
Message: Conflicting declarations: '%s%s' and '%s%s'
 - Error number: 1303; Symbol: ER_SP_NO_RECURSIVE_CREATE; SQLSTATE: 2F003
Message: Can't create a %s from within another stored routine
 - Error number: 1304; Symbol: ER_SP_ALREADY_EXISTS; SQLSTATE: 42000
Message: %s %s already exists
 - Error number: 1305; Symbol: ER_SP_DOES_NOT_EXIST; SQLSTATE: 42000
Message: %s %s does not exist
 - Error number: 1306; Symbol: ER_SP_DROP_FAILED; SQLSTATE: HY000
Message: Failed to DROP %s %s
 - Error number: 1307; Symbol: ER_SP_STORE_FAILED; SQLSTATE: HY000
Message: Failed to CREATE %s %s
 - Error number: 1308; Symbol: ER_SP_LILABEL_MISMATCH; SQLSTATE: 42000
Message: %s with no matching label: %s
 - Error number: 1309; Symbol: ER_SP_LABEL_REDEFINE; SQLSTATE: 42000
Message: Redefining label %s
 - Error number: 1310; Symbol: ER_SP_LABEL_MISMATCH; SQLSTATE: 42000
Message: End-label %s without match
 - Error number: 1311; Symbol: ER_SP_UNINIT_VAR; SQLSTATE: 01000
Message: Referring to uninitialized variable %s
 - Error number: 1312; Symbol: ER_SP_BADSELECT; SQLSTATE: 0A000
Message: PROCEDURE %s can't return a result set in the given context
 - Error number: 1313; Symbol: ER_SP_BADRETURN; SQLSTATE: 42000
Message: RETURN is only allowed in a FUNCTION
 - Error number: 1314; Symbol: ER_SP_BADSTATEMENT; SQLSTATE: 0A000

Message: %s is not allowed in stored procedures

- Error number: 1315; Symbol: ER_UPDATE_LOG_DEPRECATED_IGNORED; SQLSTATE: 42000

Message: The update log is deprecated and replaced by the binary log; SET SQL_LOG_UPDATE has been ignored.

- Error number: 1316; Symbol: ER_UPDATE_LOG_DEPRECATED_TRANSLATED; SQLSTATE: 42000

Message: The update log is deprecated and replaced by the binary log; SET SQL_LOG_UPDATE has been translated to SET SQL_LOG_BIN.

- Error number: 1317; Symbol: ER_QUERY_INTERRUPTED; SQLSTATE: 70100

Message: Query execution was interrupted

- Error number: 1318; Symbol: ER_SP_WRONG_NO_OF_ARGS; SQLSTATE: 42000

Message: Incorrect number of arguments for %s %s; expected %u, got %u

- Error number: 1319; Symbol: ER_SP_COND_MISMATCH; SQLSTATE: 42000

Message: Undefined CONDITION: %s

- Error number: 1320; Symbol: ER_SP_NORETURN; SQLSTATE: 42000

Message: No RETURN found in FUNCTION %s

- Error number: 1321; Symbol: ER_SP_NORETURNEND; SQLSTATE: 2F005

Message: FUNCTION %s ended without RETURN

- Error number: 1322; Symbol: ER_SP_BAD_CURSOR_QUERY; SQLSTATE: 42000

Message: Cursor statement must be a SELECT

- Error number: 1323; Symbol: ER_SP_BAD_CURSOR_SELECT; SQLSTATE: 42000

Message: Cursor SELECT must not have INTO

- Error number: 1324; Symbol: ER_SP_CURSOR_MISMATCH; SQLSTATE: 42000

Message: Undefined CURSOR: %s

- Error number: 1325; Symbol: ER_SP_CURSOR_ALREADY_OPEN; SQLSTATE: 24000

Message: Cursor is already open

- Error number: 1326; Symbol: ER_SP_CURSOR_NOT_OPEN; SQLSTATE: 24000

Message: Cursor is not open

- Error number: 1327; Symbol: ER_SP_UNDECLARED_VAR; SQLSTATE: 42000

Message: Undeclared variable: %s

- Error number: 1328; Symbol: ER_SP_WRONG_NO_OF_FETCH_ARGS; SQLSTATE: HY000

Message: Incorrect number of FETCH variables

-
- Error number: 1329; Symbol: ER_SP_FETCH_NO_DATA; SQLSTATE: 02000
Message: No data - zero rows fetched, selected, or processed
 - Error number: 1330; Symbol: ER_SP_DUP_PARAM; SQLSTATE: 42000
Message: Duplicate parameter: %s
 - Error number: 1331; Symbol: ER_SP_DUP_VAR; SQLSTATE: 42000
Message: Duplicate variable: %s
 - Error number: 1332; Symbol: ER_SP_DUP_COND; SQLSTATE: 42000
Message: Duplicate condition: %s
 - Error number: 1333; Symbol: ER_SP_DUP_CURS; SQLSTATE: 42000
Message: Duplicate cursor: %s
 - Error number: 1334; Symbol: ER_SP_CANT_ALTER; SQLSTATE: HY000
Message: Failed to ALTER %s %s
 - Error number: 1335; Symbol: ER_SP_SUBSELECT_NYI; SQLSTATE: 0A000
Message: Subquery value not supported
 - Error number: 1336; Symbol: ER_STMT_NOT_ALLOWED_IN_SF_OR_TRG; SQLSTATE: 0A000
Message: %s is not allowed in stored function or trigger
 - Error number: 1337; Symbol: ER_SP_VARCOND_AFTER_CURSHNDLR; SQLSTATE: 42000
Message: Variable or condition declaration after cursor or handler declaration
 - Error number: 1338; Symbol: ER_SP_CURSOR_AFTER_HANDLER; SQLSTATE: 42000
Message: Cursor declaration after handler declaration
 - Error number: 1339; Symbol: ER_SP_CASE_NOT_FOUND; SQLSTATE: 20000
Message: Case not found for CASE statement
 - Error number: 1340; Symbol: ER_FPARSER_TOO_BIG_FILE; SQLSTATE: HY000
Message: Configuration file '%s' is too big
 - Error number: 1341; Symbol: ER_FPARSER_BAD_HEADER; SQLSTATE: HY000
Message: Malformed file type header in file '%s'
 - Error number: 1342; Symbol: ER_FPARSER_EOF_IN_COMMENT; SQLSTATE: HY000
Message: Unexpected end of file while parsing comment '%s'
 - Error number: 1343; Symbol: ER_FPARSER_ERROR_IN_PARAMETER; SQLSTATE: HY000
Message: Error while parsing parameter '%s' (line: '%s')
 - Error number: 1344; Symbol: ER_FPARSER_EOF_IN_UNKNOWN_PARAMETER; SQLSTATE: HY000

Message: Unexpected end of file while skipping unknown parameter '%s'

- Error number: 1345; Symbol: [ER_VIEW_NO_EXPLAIN](#); SQLSTATE: [HY000](#)

Message: EXPLAIN/SHOW can not be issued; lacking privileges for underlying table

- Error number: 1347; Symbol: [ER_WRONG_OBJECT](#); SQLSTATE: [HY000](#)

Message: '%s.%s' is not %s

The named object is incorrect for the type of operation attempted on it. It must be an object of the named type. Example: [HANDLER OPEN](#) requires a base table, not a view. It fails if attempted on an [INFORMATION_SCHEMA](#) table that is implemented as a view on data dictionary tables.

- Error number: 1348; Symbol: [ER_NONUPDATEABLE_COLUMN](#); SQLSTATE: [HY000](#)

Message: Column '%s' is not updatable

- Error number: 1350; Symbol: [ER_VIEW_SELECT_CLAUSE](#); SQLSTATE: [HY000](#)

Message: View's SELECT contains a '%s' clause

- Error number: 1351; Symbol: [ER_VIEW_SELECT_VARIABLE](#); SQLSTATE: [HY000](#)

Message: View's SELECT contains a variable or parameter

- Error number: 1352; Symbol: [ER_VIEW_SELECT_TMPTABLE](#); SQLSTATE: [HY000](#)

Message: View's SELECT refers to a temporary table '%s'

- Error number: 1353; Symbol: [ER_VIEW_WRONG_LIST](#); SQLSTATE: [HY000](#)

Message: In definition of view, derived table or common table expression, SELECT list and column names list have different column counts

- Error number: 1354; Symbol: [ER_WARN_VIEW_MERGE](#); SQLSTATE: [HY000](#)

Message: View merge algorithm can't be used here for now (assumed undefined algorithm)

- Error number: 1355; Symbol: [ER_WARN_VIEW_WITHOUT_KEY](#); SQLSTATE: [HY000](#)

Message: View being updated does not have complete key of underlying table in it

- Error number: 1356; Symbol: [ER_VIEW_INVALID](#); SQLSTATE: [HY000](#)

Message: View '%s.%s' references invalid table(s) or column(s) or function(s) or definer/invoker of view lack rights to use them

- Error number: 1357; Symbol: [ER_SP_NO_DROP_SP](#); SQLSTATE: [HY000](#)

Message: Can't drop or alter a %s from within another stored routine

- Error number: 1359; Symbol: [ER_TRG_ALREADY_EXISTS](#); SQLSTATE: [HY000](#)

Message: Trigger already exists

- Error number: 1360; Symbol: [ER_TRG_DOES_NOT_EXIST](#); SQLSTATE: [HY000](#)

Message: Trigger does not exist

-
- Error number: [1361](#); Symbol: [ER_TRG_ON_VIEW_OR_TEMP_TABLE](#); SQLSTATE: [HY000](#)
Message: Trigger's '%s' is view or temporary table
 - Error number: [1362](#); Symbol: [ER_TRG_CANT_CHANGE_ROW](#); SQLSTATE: [HY000](#)
Message: Updating of %s row is not allowed in %strigger
 - Error number: [1363](#); Symbol: [ER_TRG_NO_SUCH_ROW_IN_TRG](#); SQLSTATE: [HY000](#)
Message: There is no %s row in %s trigger
 - Error number: [1364](#); Symbol: [ER_NO_DEFAULT_FOR_FIELD](#); SQLSTATE: [HY000](#)
Message: Field '%s' doesn't have a default value
 - Error number: [1365](#); Symbol: [ER_DIVISION_BY_ZERO](#); SQLSTATE: [22012](#)
Message: Division by 0
 - Error number: [1366](#); Symbol: [ER_TRUNCATED_WRONG_VALUE_FOR_FIELD](#); SQLSTATE: [HY000](#)
Message: Incorrect %s value: '%s' for column '%s' at row %ld
 - Error number: [1367](#); Symbol: [ER_ILLEGAL_VALUE_FOR_TYPE](#); SQLSTATE: [22007](#)
Message: Illegal %s '%s' value found during parsing
 - Error number: [1368](#); Symbol: [ER_VIEW_NONUPD_CHECK](#); SQLSTATE: [HY000](#)
Message: CHECK OPTION on non-updatable view '%s.%s'
 - Error number: [1369](#); Symbol: [ER_VIEW_CHECK_FAILED](#); SQLSTATE: [HY000](#)
Message: CHECK OPTION failed '%s.%s'
 - Error number: [1370](#); Symbol: [ER_PROCACCESS_DENIED_ERROR](#); SQLSTATE: [42000](#)
Message: %s command denied to user '%s'@'%s' for routine '%s'
 - Error number: [1371](#); Symbol: [ER_RELAY_LOG_FAIL](#); SQLSTATE: [HY000](#)
Message: Failed purging old relay logs: %s
 - Error number: [1373](#); Symbol: [ER_UNKNOWN_TARGET_BINLOG](#); SQLSTATE: [HY000](#)
Message: Target log not found in binlog index
 - Error number: [1374](#); Symbol: [ER_IO_ERR_LOG_INDEX_READ](#); SQLSTATE: [HY000](#)
Message: I/O error reading log index file
 - Error number: [1375](#); Symbol: [ER_BINLOG_PURGE_PROHIBITED](#); SQLSTATE: [HY000](#)
Message: Server configuration does not permit binlog purge
 - Error number: [1376](#); Symbol: [ER_FSEEK_FAIL](#); SQLSTATE: [HY000](#)
Message: Failed on fseek()

-
- Error number: [1377](#); Symbol: [ER_BINLOG_PURGE_FATAL_ERR](#); SQLSTATE: [HY000](#)
Message: Fatal error during log purge
 - Error number: [1378](#); Symbol: [ER_LOG_IN_USE](#); SQLSTATE: [HY000](#)
Message: A purgeable log is in use, will not purge
 - Error number: [1379](#); Symbol: [ER_LOG_PURGE_UNKNOWN_ERR](#); SQLSTATE: [HY000](#)
Message: Unknown error during log purge
 - Error number: [1380](#); Symbol: [ER_RELAY_LOG_INIT](#); SQLSTATE: [HY000](#)
Message: Failed initializing relay log position: %s
 - Error number: [1381](#); Symbol: [ER_NO_BINARY_LOGGING](#); SQLSTATE: [HY000](#)
Message: You are not using binary logging
 - Error number: [1382](#); Symbol: [ER_RESERVED_SYNTAX](#); SQLSTATE: [HY000](#)
Message: The '%s' syntax is reserved for purposes internal to the MySQL server
 - Error number: [1390](#); Symbol: [ER_PS_MANY_PARAM](#); SQLSTATE: [HY000](#)
Message: Prepared statement contains too many placeholders
 - Error number: [1391](#); Symbol: [ER_KEY_PART_0](#); SQLSTATE: [HY000](#)
Message: Key part '%s' length cannot be 0
 - Error number: [1392](#); Symbol: [ER_VIEW_CHECKSUM](#); SQLSTATE: [HY000](#)
Message: View text checksum failed
 - Error number: [1393](#); Symbol: [ER_VIEW_MULTIUPDATE](#); SQLSTATE: [HY000](#)
Message: Can not modify more than one base table through a join view '%s.%s'
 - Error number: [1394](#); Symbol: [ER_VIEW_NO_INSERT_FIELD_LIST](#); SQLSTATE: [HY000](#)
Message: Can not insert into join view '%s.%s' without fields list
 - Error number: [1395](#); Symbol: [ER_VIEW_DELETE_MERGE_VIEW](#); SQLSTATE: [HY000](#)
Message: Can not delete from join view '%s.%s'
 - Error number: [1396](#); Symbol: [ER_CANNOT_USER](#); SQLSTATE: [HY000](#)
Message: Operation %s failed for %s
 - Error number: [1397](#); Symbol: [ER_XAER_NOTA](#); SQLSTATE: [XAE04](#)
Message: XAER_NOTA: Unknown XID
 - Error number: [1398](#); Symbol: [ER_XAER_INVAL](#); SQLSTATE: [XAE05](#)
Message: XAER_INVAL: Invalid arguments (or unsupported command)

-
- Error number: [1399](#); Symbol: [ER_XAER_RMFAIL](#); SQLSTATE: [XAE07](#)
Message: XAER_RMFAIL: The command cannot be executed when global transaction is in the %s state
 - Error number: [1400](#); Symbol: [ER_XAER_OUTSIDE](#); SQLSTATE: [XAE09](#)
Message: XAER_OUTSIDE: Some work is done outside global transaction
 - Error number: [1401](#); Symbol: [ER_XAER_RMERR](#); SQLSTATE: [XAE03](#)
Message: XAER_RMERR: Fatal error occurred in the transaction branch - check your data for consistency
 - Error number: [1402](#); Symbol: [ER_XA_RBROLLBACK](#); SQLSTATE: [XA100](#)
Message: XA_RBROLLBACK: Transaction branch was rolled back
 - Error number: [1403](#); Symbol: [ER_NONEXISTING_PROC_GRANT](#); SQLSTATE: [42000](#)
Message: There is no such grant defined for user '%s' on host '%s' on routine '%s'
 - Error number: [1404](#); Symbol: [ER_PROC_AUTO_GRANT_FAIL](#); SQLSTATE: [HY000](#)
Message: Failed to grant EXECUTE and ALTER ROUTINE privileges
 - Error number: [1405](#); Symbol: [ER_PROC_AUTO_REVOKE_FAIL](#); SQLSTATE: [HY000](#)
Message: Failed to revoke all privileges to dropped routine
 - Error number: [1406](#); Symbol: [ER_DATA_TOO_LONG](#); SQLSTATE: [22001](#)
Message: Data too long for column '%s' at row %ld
 - Error number: [1407](#); Symbol: [ER_SP_BAD_SQLSTATE](#); SQLSTATE: [42000](#)
Message: Bad SQLSTATE: '%s'
 - Error number: [1408](#); Symbol: [ER_STARTUP](#); SQLSTATE: [HY000](#)
Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d %s
 - Error number: [1409](#); Symbol: [ER_LOAD_FROM_FIXED_SIZE_ROWS_TO_VAR](#); SQLSTATE: [HY000](#)
Message: Can't load value from file with fixed size rows to variable
 - Error number: [1410](#); Symbol: [ER_CANT_CREATE_USER_WITH_GRANT](#); SQLSTATE: [42000](#)
Message: You are not allowed to create a user with GRANT
 - Error number: [1411](#); Symbol: [ER_WRONG_VALUE_FOR_TYPE](#); SQLSTATE: [HY000](#)
Message: Incorrect %s value: '%s' for function %s
 - Error number: [1412](#); Symbol: [ER_TABLE_DEF_CHANGED](#); SQLSTATE: [HY000](#)
Message: Table definition has changed, please retry transaction
 - Error number: [1413](#); Symbol: [ER_SP_DUP_HANDLER](#); SQLSTATE: [42000](#)
Message: Duplicate handler declared in the same block

-
- Error number: [1414](#); Symbol: [ER_SP_NOT_VAR_ARG](#); SQLSTATE: [42000](#)
Message: OUT or INOUT argument %d for routine %s is not a variable or NEW pseudo-variable in BEFORE trigger
 - Error number: [1415](#); Symbol: [ER_SP_NO_RETSET](#); SQLSTATE: [0A000](#)
Message: Not allowed to return a result set from a %s
 - Error number: [1416](#); Symbol: [ER_CANT_CREATE_GEOMETRY_OBJECT](#); SQLSTATE: [22003](#)
Message: Cannot get geometry object from data you send to the GEOMETRY field
 - Error number: [1418](#); Symbol: [ER_BINLOG_UNSAFE_ROUTINE](#); SQLSTATE: [HY000](#)
Message: This function has none of DETERMINISTIC, NO SQL, or READS SQL DATA in its declaration and binary logging is enabled (you *might* want to use the less safe log_bin_trust_function_creators variable)
 - Error number: [1419](#); Symbol: [ER_BINLOG_CREATE_ROUTINE_NEED_SUPER](#); SQLSTATE: [HY000](#)
Message: You do not have the SUPER privilege and binary logging is enabled (you *might* want to use the less safe log_bin_trust_function_creators variable)
 - Error number: [1421](#); Symbol: [ER_STMT_HAS_NO_OPEN_CURSOR](#); SQLSTATE: [HY000](#)
Message: The statement (%lu) has no open cursor.
 - Error number: [1422](#); Symbol: [ER_COMMIT_NOT_ALLOWED_IN_SF_OR_TRG](#); SQLSTATE: [HY000](#)
Message: Explicit or implicit commit is not allowed in stored function or trigger.
 - Error number: [1423](#); Symbol: [ER_NO_DEFAULT_FOR_VIEW_FIELD](#); SQLSTATE: [HY000](#)
Message: Field of view '%s.%s' underlying table doesn't have a default value
 - Error number: [1424](#); Symbol: [ER_SP_NO_RECURSION](#); SQLSTATE: [HY000](#)
Message: Recursive stored functions and triggers are not allowed.
 - Error number: [1425](#); Symbol: [ER_TOO_BIG_SCALE](#); SQLSTATE: [42000](#)
Message: Too big scale %d specified for column '%s'. Maximum is %lu.
 - Error number: [1426](#); Symbol: [ER_TOO_BIG_PRECISION](#); SQLSTATE: [42000](#)
Message: Too-big precision %d specified for '%s'. Maximum is %lu.
 - Error number: [1427](#); Symbol: [ER_M_BIGGER_THAN_D](#); SQLSTATE: [42000](#)
Message: For float(M,D), double(M,D) or decimal(M,D), M must be >= D (column '%s').
 - Error number: [1428](#); Symbol: [ER_WRONG_LOCK_OF_SYSTEM_TABLE](#); SQLSTATE: [HY000](#)
Message: You can't combine write-locking of system tables with other tables or lock types
 - Error number: [1429](#); Symbol: [ER_CONNECT_TO_FOREIGN_DATA_SOURCE](#); SQLSTATE: [HY000](#)
Message: Unable to connect to foreign data source: %s

-
- Error number: [1430](#); Symbol: [ER_QUERY_ON_FOREIGN_DATA_SOURCE](#); SQLSTATE: [HY000](#)
Message: There was a problem processing the query on the foreign data source. Data source error: %s
 - Error number: [1431](#); Symbol: [ER_FOREIGN_DATA_SOURCE_DOESNT_EXIST](#); SQLSTATE: [HY000](#)
Message: The foreign data source you are trying to reference does not exist. Data source error: %s
 - Error number: [1432](#); Symbol: [ER_FOREIGN_DATA_STRING_INVALID_CANT_CREATE](#); SQLSTATE: [HY000](#)
Message: Can't create federated table. The data source connection string '%s' is not in the correct format
 - Error number: [1433](#); Symbol: [ER_FOREIGN_DATA_STRING_INVALID](#); SQLSTATE: [HY000](#)
Message: The data source connection string '%s' is not in the correct format
 - Error number: [1435](#); Symbol: [ER_TRG_IN_WRONG_SCHEMA](#); SQLSTATE: [HY000](#)
Message: Trigger in wrong schema
 - Error number: [1436](#); Symbol: [ER_STACK_OVERRUN_NEED_MORE](#); SQLSTATE: [HY000](#)
Message: Thread stack overrun: %ld bytes used of a %ld byte stack, and %ld bytes needed. Use 'mysqld --thread_stack=#' to specify a bigger stack.
 - Error number: [1437](#); Symbol: [ER_TOO_LONG_BODY](#); SQLSTATE: [42000](#)
Message: Routine body for '%s' is too long
 - Error number: [1438](#); Symbol: [ER_WARN_CANT_DROP_DEFAULT_KEYCACHE](#); SQLSTATE: [HY000](#)
Message: Cannot drop default keycache
 - Error number: [1439](#); Symbol: [ER_TOO_BIG_DISPLAYWIDTH](#); SQLSTATE: [42000](#)
Message: Display width out of range for column '%s' (max = %lu)
 - Error number: [1440](#); Symbol: [ER_XAER_DUPID](#); SQLSTATE: [XAE08](#)
Message: XAER_DUPID: The XID already exists
 - Error number: [1441](#); Symbol: [ER_DATETIME_FUNCTION_OVERFLOW](#); SQLSTATE: [22008](#)
Message: Datetime function: %s field overflow
 - Error number: [1442](#); Symbol: [ER_CANT_UPDATE_USED_TABLE_IN_SF_OR_TRG](#); SQLSTATE: [HY000](#)
Message: Can't update table '%s' in stored function/trigger because it is already used by statement which invoked this stored function/trigger.
 - Error number: [1443](#); Symbol: [ER_VIEW_PREVENT_UPDATE](#); SQLSTATE: [HY000](#)
Message: The definition of table '%s' prevents operation %s on table '%s'.
 - Error number: [1444](#); Symbol: [ER_PS_NO_RECURSION](#); SQLSTATE: [HY000](#)
Message: The prepared statement contains a stored routine call that refers to that same statement. It's not allowed to execute a prepared statement in such a recursive manner

-
- Error number: 1445; Symbol: `ER_SP_CANT_SET_AUTOCOMMIT`; SQLSTATE: `HY000`
Message: Not allowed to set autocommit from a stored function or trigger
 - Error number: 1447; Symbol: `ER_VIEW_FRM_NO_USER`; SQLSTATE: `HY000`
Message: View '%s'.'%s' has no definer information (old table format). Current user is used as definer. Please recreate the view!
 - Error number: 1448; Symbol: `ER_VIEW_OTHER_USER`; SQLSTATE: `HY000`
Message: You need the SUPER privilege for creation view with '%s'@'%s' definer
 - Error number: 1449; Symbol: `ER_NO_SUCH_USER`; SQLSTATE: `HY000`
Message: The user specified as a definer ('%s'@'%s') does not exist
 - Error number: 1450; Symbol: `ER_FORBID_SCHEMA_CHANGE`; SQLSTATE: `HY000`
Message: Changing schema from '%s' to '%s' is not allowed.
 - Error number: 1451; Symbol: `ER_ROW_IS_REFERENCED_2`; SQLSTATE: `23000`
Message: Cannot delete or update a parent row: a foreign key constraint fails%

[InnoDB](#) reports this error when you try to delete a parent row that has children, and a [foreign key constraint](#) fails. Delete the children first.
 - Error number: 1452; Symbol: `ER_NO_REFERENCED_ROW_2`; SQLSTATE: `23000`
Message: Cannot add or update a child row: a foreign key constraint fails%

[InnoDB](#) reports this error when you try to add a row but there is no parent row, and a [foreign key constraint](#) fails. Add the parent row first.
 - Error number: 1453; Symbol: `ER_SP_BAD_VAR_SHADOW`; SQLSTATE: `42000`
Message: Variable '%s' must be quoted with `...`, or renamed
 - Error number: 1454; Symbol: `ER_TRG_NO_DEFINER`; SQLSTATE: `HY000`
Message: No definer attribute for trigger '%s'.'%s'. It's disallowed to create trigger without definer.
 - Error number: 1455; Symbol: `ER_OLD_FILE_FORMAT`; SQLSTATE: `HY000`
Message: '%s' has an old format, you should re-create the '%s' object(s)
 - Error number: 1456; Symbol: `ER_SP_RECURSION_LIMIT`; SQLSTATE: `HY000`
Message: Recursive limit %d (as set by the max_sp_recursion_depth variable) was exceeded for routine %s
 - Error number: 1458; Symbol: `ER_SP_WRONG_NAME`; SQLSTATE: `42000`
Message: Incorrect routine name '%s'
 - Error number: 1459; Symbol: `ER_TABLE_NEEDS_UPGRADE`; SQLSTATE: `HY000`
Message: Table upgrade required. Please do "REPAIR TABLE ` %s ` " or dump/reload to fix it!

-
- Error number: 1460; Symbol: [ER_SP_NO_AGGREGATE](#); SQLSTATE: 42000
Message: AGGREGATE is not supported for stored functions
 - Error number: 1461; Symbol: [ER_MAX_PREPARED_STMT_COUNT_REACHED](#); SQLSTATE: 42000
Message: Can't create more than max_prepared_stmt_count statements (current value: %lu)
 - Error number: 1462; Symbol: [ER_VIEW_RECURSIVE](#); SQLSTATE: HY000
Message: `%s`.`%s` contains view recursion
 - Error number: 1463; Symbol: [ER_NON_GROUPING_FIELD_USED](#); SQLSTATE: 42000
Message: Non-grouping field '%s' is used in %s clause
 - Error number: 1464; Symbol: [ER_TABLE_CANT_HANDLE_SPKEYS](#); SQLSTATE: HY000
Message: The used table type doesn't support SPATIAL indexes
 - Error number: 1465; Symbol: [ER_NO_TRIGGERS_ON_SYSTEM_SCHEMA](#); SQLSTATE: HY000
Message: Triggers can not be created on system tables
 - Error number: 1466; Symbol: [ER_REMOVED_SPACES](#); SQLSTATE: HY000
Message: Leading spaces are removed from name '%s'
 - Error number: 1467; Symbol: [ER_AUTOINC_READ_FAILED](#); SQLSTATE: HY000
Message: Failed to read auto-increment value from storage engine
 - Error number: 1468; Symbol: [ER_USERNAME](#); SQLSTATE: HY000
Message: user name
 - Error number: 1469; Symbol: [ER_HOSTNAME](#); SQLSTATE: HY000
Message: host name
 - Error number: 1470; Symbol: [ER_WRONG_STRING_LENGTH](#); SQLSTATE: HY000
Message: String '%s' is too long for %s (should be no longer than %d)
 - Error number: 1471; Symbol: [ER_NON_INSERTABLE_TABLE](#); SQLSTATE: HY000
Message: The target table %s of the %s is not insertable-into
 - Error number: 1472; Symbol: [ER_ADMIN_WRONG_MRG_TABLE](#); SQLSTATE: HY000
Message: Table '%s' is differently defined or of non-MyISAM type or doesn't exist
 - Error number: 1473; Symbol: [ER_TOO_HIGH_LEVEL_OF_NESTING_FOR_SELECT](#); SQLSTATE: HY000
Message: Too high level of nesting for select
 - Error number: 1474; Symbol: [ER_NAME_BECOMES_EMPTY](#); SQLSTATE: HY000
Message: Name '%s' has become "
 - Error number: 1475; Symbol: [ER_AMBIGUOUS_FIELD_TERM](#); SQLSTATE: HY000

Message: First character of the FIELDS TERMINATED string is ambiguous; please use non-optional and non-empty FIELDS ENCLOSED BY

- Error number: 1476; Symbol: ER_FOREIGN_SERVER_EXISTS; SQLSTATE: HY000

Message: The foreign server, %s, you are trying to create already exists.

- Error number: 1477; Symbol: ER_FOREIGN_SERVER_DOESNT_EXIST; SQLSTATE: HY000

Message: The foreign server name you are trying to reference does not exist. Data source error: %s

- Error number: 1478; Symbol: ER_ILLEGAL_HA_CREATE_OPTION; SQLSTATE: HY000

Message: Table storage engine '%s' does not support the create option '%s'

- Error number: 1479; Symbol: ER_PARTITION_REQUIRES_VALUES_ERROR; SQLSTATE: HY000

Message: Syntax error: %s PARTITIONING requires definition of VALUES %s for each partition

- Error number: 1480; Symbol: ER_PARTITION_WRONG_VALUES_ERROR; SQLSTATE: HY000

Message: Only %s PARTITIONING can use VALUES %s in partition definition

- Error number: 1481; Symbol: ER_PARTITION_MAXVALUE_ERROR; SQLSTATE: HY000

Message: MAXVALUE can only be used in last partition definition

- Error number: 1484; Symbol: ER_PARTITION_WRONG_NO_PART_ERROR; SQLSTATE: HY000

Message: Wrong number of partitions defined, mismatch with previous setting

- Error number: 1485; Symbol: ER_PARTITION_WRONG_NO_SUBPART_ERROR; SQLSTATE: HY000

Message: Wrong number of subpartitions defined, mismatch with previous setting

- Error number: 1486; Symbol: ER_WRONG_EXPR_IN_PARTITION_FUNC_ERROR; SQLSTATE: HY000

Message: Constant, random or timezone-dependent expressions in (sub)partitioning function are not allowed

- Error number: 1488; Symbol: ER_FIELD_NOT_FOUND_PART_ERROR; SQLSTATE: HY000

Message: Field in list of fields for partition function not found in table

- Error number: 1490; Symbol: ER_INCONSISTENT_PARTITION_INFO_ERROR; SQLSTATE: HY000

Message: The partition info in the frm file is not consistent with what can be written into the frm file

- Error number: 1491; Symbol: ER_PARTITION_FUNC_NOT_ALLOWED_ERROR; SQLSTATE: HY000

Message: The %s function returns the wrong type

- Error number: 1492; Symbol: ER_PARTITIONS_MUST_BE_DEFINED_ERROR; SQLSTATE: HY000

Message: For %s partitions each partition must be defined

- Error number: 1493; Symbol: ER_RANGE_NOT_INCREASING_ERROR; SQLSTATE: HY000

Message: VALUES LESS THAN value must be strictly increasing for each partition

-
- Error number: 1494; Symbol: `ER_INCONSISTENT_TYPE_OF_FUNCTIONS_ERROR`; SQLSTATE: HY000
Message: VALUES value must be of same type as partition function
 - Error number: 1495; Symbol: `ER_MULTIPLE_DEF_CONST_IN_LIST_PART_ERROR`; SQLSTATE: HY000
Message: Multiple definition of same constant in list partitioning
 - Error number: 1496; Symbol: `ER_PARTITION_ENTRY_ERROR`; SQLSTATE: HY000
Message: Partitioning can not be used stand-alone in query
 - Error number: 1497; Symbol: `ER_MIX_HANDLER_ERROR`; SQLSTATE: HY000
Message: The mix of handlers in the partitions is not allowed in this version of MySQL
 - Error number: 1498; Symbol: `ER_PARTITION_NOT_DEFINED_ERROR`; SQLSTATE: HY000
Message: For the partitioned engine it is necessary to define all %s
 - Error number: 1499; Symbol: `ER_TOO_MANY_PARTITIONS_ERROR`; SQLSTATE: HY000
Message: Too many partitions (including subpartitions) were defined
 - Error number: 1500; Symbol: `ER_SUBPARTITION_ERROR`; SQLSTATE: HY000
Message: It is only possible to mix RANGE/LIST partitioning with HASH/KEY partitioning for subpartitioning
 - Error number: 1501; Symbol: `ER_CANT_CREATE_HANDLER_FILE`; SQLSTATE: HY000
Message: Failed to create specific handler file
 - Error number: 1502; Symbol: `ER_BLOB_FIELD_IN_PART_FUNC_ERROR`; SQLSTATE: HY000
Message: A BLOB field is not allowed in partition function
 - Error number: 1503; Symbol: `ER_UNIQUE_KEY_NEED_ALL_FIELDS_IN_PF`; SQLSTATE: HY000
Message: A %s must include all columns in the table's partitioning function (prefixed columns are not considered).
 - Error number: 1504; Symbol: `ER_NO_PARTS_ERROR`; SQLSTATE: HY000
Message: Number of %s = 0 is not an allowed value
 - Error number: 1505; Symbol: `ER_PARTITION_MGMT_ON_NONPARTITIONED`; SQLSTATE: HY000
Message: Partition management on a not partitioned table is not possible
 - Error number: 1506; Symbol: `ER_FOREIGN_KEY_ON_PARTITIONED`; SQLSTATE: HY000
Message: Foreign keys are not yet supported in conjunction with partitioning
 - Error number: 1507; Symbol: `ER_DROP_PARTITION_NON_EXISTENT`; SQLSTATE: HY000
Message: Error in list of partitions to %s
 - Error number: 1508; Symbol: `ER_DROP_LAST_PARTITION`; SQLSTATE: HY000

Message: Cannot remove all partitions, use DROP TABLE instead

- Error number: 1509; Symbol: [ER_COALESCE_ONLY_ON_HASH_PARTITION](#); SQLSTATE: HY000

Message: COALESCE PARTITION can only be used on HASH/KEY partitions

- Error number: 1510; Symbol: [ER_REORG_HASH_ONLY_ON_SAME_NO](#); SQLSTATE: HY000

Message: REORGANIZE PARTITION can only be used to reorganize partitions not to change their numbers

- Error number: 1511; Symbol: [ER_REORG_NO_PARAM_ERROR](#); SQLSTATE: HY000

Message: REORGANIZE PARTITION without parameters can only be used on auto-partitioned tables using HASH PARTITIONS

- Error number: 1512; Symbol: [ER_ONLY_ON_RANGE_LIST_PARTITION](#); SQLSTATE: HY000

Message: %s PARTITION can only be used on RANGE/LIST partitions

- Error number: 1513; Symbol: [ER_ADD_PARTITION_SUBPART_ERROR](#); SQLSTATE: HY000

Message: Trying to Add partition(s) with wrong number of subpartitions

- Error number: 1514; Symbol: [ER_ADD_PARTITION_NO_NEW_PARTITION](#); SQLSTATE: HY000

Message: At least one partition must be added

- Error number: 1515; Symbol: [ER_COALESCE_PARTITION_NO_PARTITION](#); SQLSTATE: HY000

Message: At least one partition must be coalesced

- Error number: 1516; Symbol: [ER_REORG_PARTITION_NOT_EXIST](#); SQLSTATE: HY000

Message: More partitions to reorganize than there are partitions

- Error number: 1517; Symbol: [ER_SAME_NAME_PARTITION](#); SQLSTATE: HY000

Message: Duplicate partition name %s

- Error number: 1518; Symbol: [ER_NO_BINLOG_ERROR](#); SQLSTATE: HY000

Message: It is not allowed to shut off binlog on this command

- Error number: 1519; Symbol: [ER_CONSECUTIVE_REORG_PARTITIONS](#); SQLSTATE: HY000

Message: When reorganizing a set of partitions they must be in consecutive order

- Error number: 1520; Symbol: [ER_REORG_OUTSIDE_RANGE](#); SQLSTATE: HY000

Message: Reorganize of range partitions cannot change total ranges except for last partition where it can extend the range

- Error number: 1521; Symbol: [ER_PARTITION_FUNCTION_FAILURE](#); SQLSTATE: HY000

Message: Partition function not supported in this version for this handler

- Error number: 1523; Symbol: [ER_LIMITED_PART_RANGE](#); SQLSTATE: HY000

Message: The %s handler only supports 32 bit integers in VALUES

-
- Error number: [1524](#); Symbol: [ER_PLUGIN_IS_NOT_LOADED](#); SQLSTATE: [HY000](#)
Message: Plugin '%s' is not loaded
 - Error number: [1525](#); Symbol: [ER_WRONG_VALUE](#); SQLSTATE: [HY000](#)
Message: Incorrect %s value: '%s'
 - Error number: [1526](#); Symbol: [ER_NO_PARTITION_FOR_GIVEN_VALUE](#); SQLSTATE: [HY000](#)
Message: Table has no partition for value %s
 - Error number: [1527](#); Symbol: [ER_FILEGROUP_OPTION_ONLY_ONCE](#); SQLSTATE: [HY000](#)
Message: It is not allowed to specify %s more than once
 - Error number: [1528](#); Symbol: [ER_CREATE_FILEGROUP_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to create %s
 - Error number: [1529](#); Symbol: [ER_DROP_FILEGROUP_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to drop %s
 - Error number: [1530](#); Symbol: [ER_TABLESPACE_AUTO_EXTEND_ERROR](#); SQLSTATE: [HY000](#)
Message: The handler doesn't support autoextend of tablespaces
 - Error number: [1531](#); Symbol: [ER_WRONG_SIZE_NUMBER](#); SQLSTATE: [HY000](#)
Message: A size parameter was incorrectly specified, either number or on the form 10M
 - Error number: [1532](#); Symbol: [ER_SIZE_OVERFLOW_ERROR](#); SQLSTATE: [HY000](#)
Message: The size number was correct but we don't allow the digit part to be more than 2 billion
 - Error number: [1533](#); Symbol: [ER_ALTER_FILEGROUP_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to alter: %s
 - Error number: [1534](#); Symbol: [ER_BINLOG_ROW_LOGGING_FAILED](#); SQLSTATE: [HY000](#)
Message: Writing one row to the row-based binary log failed
 - Error number: [1537](#); Symbol: [ER_EVENT_ALREADY_EXISTS](#); SQLSTATE: [HY000](#)
Message: Event '%s' already exists
 - Error number: [1539](#); Symbol: [ER_EVENT_DOES_NOT_EXIST](#); SQLSTATE: [HY000](#)
Message: Unknown event '%s'
 - Error number: [1542](#); Symbol: [ER_EVENT_INTERVAL_NOT_POSITIVE_OR_TOO_BIG](#); SQLSTATE: [HY000](#)
Message: INTERVAL is either not positive or too big
 - Error number: [1543](#); Symbol: [ER_EVENT_ENDS_BEFORE_STARTS](#); SQLSTATE: [HY000](#)
Message: ENDS is either invalid or before STARTS

-
- Error number: 1544; Symbol: `ER_EVENT_EXEC_TIME_IN_THE_PAST`; SQLSTATE: HY000

Message: Event execution time is in the past. Event has been disabled

- Error number: 1551; Symbol: `ER_EVENT_SAME_NAME`; SQLSTATE: HY000

Message: Same old and new event name

- Error number: 1553; Symbol: `ER_DROP_INDEX_FK`; SQLSTATE: HY000

Message: Cannot drop index '%s': needed in a foreign key constraint

InnoDB reports this error when you attempt to drop the last index that can enforce a particular referential constraint.

For optimal performance with DML statements, InnoDB requires an index to exist on [foreign key](#) columns, so that `UPDATE` and `DELETE` operations on a [parent table](#) can easily check whether corresponding rows exist in the [child table](#). MySQL creates or drops such indexes automatically when needed, as a side-effect of `CREATE TABLE`, `CREATE INDEX`, and `ALTER TABLE` statements.

When you drop an index, InnoDB checks if the index is used for checking a foreign key constraint. It is still OK to drop the index if there is another index that can be used to enforce the same constraint. InnoDB prevents you from dropping the last index that can enforce a particular referential constraint.

- Error number: 1554; Symbol: `ER_WARN_DEPRECATED_SYNTAX_WITH_VER`; SQLSTATE: HY000

Message: The syntax '%s' is deprecated and will be removed in MySQL %s. Please use %s instead

- Error number: 1556; Symbol: `ER_CANT_LOCK_LOG_TABLE`; SQLSTATE: HY000

Message: You can't use locks with log tables.

- Error number: 1557; Symbol: `ER_FOREIGN_DUPLICATE_KEY_OLD_UNUSED`; SQLSTATE: 23000

Message: Upholding foreign key constraints for table '%s', entry '%s', key %d would lead to a duplicate entry

- Error number: 1558; Symbol: `ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE`; SQLSTATE: HY000

Message: The column count of mysql.%s is wrong. Expected %d, found %d. Created with MySQL %d, now running %d. Please perform the MySQL upgrade procedure.

- Error number: 1560; Symbol: `ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_FORMAT`; SQLSTATE: HY000

Message: Cannot change the binary logging format inside a stored function or trigger

- Error number: 1562; Symbol: `ER_PARTITION_NO_TEMPORARY`; SQLSTATE: HY000

Message: Cannot create temporary table with partitions

- Error number: 1563; Symbol: `ER_PARTITION_CONST_DOMAIN_ERROR`; SQLSTATE: HY000

Message: Partition constant is out of partition function domain

- Error number: 1564; Symbol: `ER_PARTITION_FUNCTION_IS_NOT_ALLOWED`; SQLSTATE: HY000

Message: This partition function is not allowed

-
- Error number: 1566; Symbol: ER_NULL_IN_VALUES_LESS_THAN; SQLSTATE: HY000
Message: Not allowed to use NULL value in VALUES LESS THAN
 - Error number: 1567; Symbol: ER_WRONG_PARTITION_NAME; SQLSTATE: HY000
Message: Incorrect partition name
 - Error number: 1568; Symbol: ER_CANT_CHANGE_TX_CHARACTERISTICS; SQLSTATE: 25001
Message: Transaction characteristics can't be changed while a transaction is in progress
 - Error number: 1569; Symbol: ER_DUP_ENTRY_AUTOINCREMENT_CASE; SQLSTATE: HY000
Message: ALTER TABLE causes auto_increment resequencing, resulting in duplicate entry '%s' for key '%s'
 - Error number: 1571; Symbol: ER_EVENT_SET_VAR_ERROR; SQLSTATE: HY000
Message: Error during starting/stopping of the scheduler. Error code %u
 - Error number: 1572; Symbol: ER_PARTITION_MERGE_ERROR; SQLSTATE: HY000
Message: Engine cannot be used in partitioned tables
 - Error number: 1575; Symbol: ER_BASE64_DECODE_ERROR; SQLSTATE: HY000
Message: Decoding of base64 string failed
 - Error number: 1576; Symbol: ER_EVENT_RECURSION_FORBIDDEN; SQLSTATE: HY000
Message: Recursion of EVENT DDL statements is forbidden when body is present
 - Error number: 1578; Symbol: ER_ONLY_INTEGERS_ALLOWED; SQLSTATE: HY000
Message: Only integers allowed as number here
 - Error number: 1579; Symbol: ER_UNSUPPORTED_LOG_ENGINE; SQLSTATE: HY000
Message: This storage engine cannot be used for log tables
 - Error number: 1580; Symbol: ER_BAD_LOG_STATEMENT; SQLSTATE: HY000
Message: You cannot '%s' a log table if logging is enabled
 - Error number: 1581; Symbol: ER_CANT_RENAME_LOG_TABLE; SQLSTATE: HY000
Message: Cannot rename '%s'. When logging enabled, rename to/from log table must rename two tables: the log table to an archive table and another table back to '%s'
 - Error number: 1582; Symbol: ER_WRONG_PARAMCOUNT_TO_NATIVE_FCT; SQLSTATE: 42000
Message: Incorrect parameter count in the call to native function '%s'
 - Error number: 1583; Symbol: ER_WRONG_PARAMETERS_TO_NATIVE_FCT; SQLSTATE: 42000
Message: Incorrect parameters in the call to native function '%s'
 - Error number: 1584; Symbol: ER_WRONG_PARAMETERS_TO_STORED_FCT; SQLSTATE: 42000
Message: Incorrect parameters in the call to stored function %s

-
- Error number: [1585](#); Symbol: [ER_NATIVE_FCT_NAME_COLLISION](#); SQLSTATE: [HY000](#)
Message: This function '%s' has the same name as a native function
 - Error number: [1586](#); Symbol: [ER_DUP_ENTRY_WITH_KEY_NAME](#); SQLSTATE: [23000](#)
Message: Duplicate entry '%s' for key '%s'
The format string for this error is also used with [ER_DUP_ENTRY](#).
 - Error number: [1587](#); Symbol: [ER_BINLOG_PURGE_EMFILE](#); SQLSTATE: [HY000](#)
Message: Too many files opened, please execute the command again
 - Error number: [1588](#); Symbol: [ER_EVENT_CANNOT_CREATE_IN_THE_PAST](#); SQLSTATE: [HY000](#)
Message: Event execution time is in the past and ON COMPLETION NOT PRESERVE is set. The event was dropped immediately after creation.
 - Error number: [1589](#); Symbol: [ER_EVENT_CANNOT_ALTER_IN_THE_PAST](#); SQLSTATE: [HY000](#)
Message: Event execution time is in the past and ON COMPLETION NOT PRESERVE is set. The event was not changed. Specify a time in the future.
 - Error number: [1591](#); Symbol: [ER_NO_PARTITION_FOR_GIVEN_VALUE_SILENT](#); SQLSTATE: [HY000](#)
Message: Table has no partition for some existing values
 - Error number: [1592](#); Symbol: [ER_BINLOG_UNSAFE_STATEMENT](#); SQLSTATE: [HY000](#)
Message: Unsafe statement written to the binary log using statement format since BINLOG_FORMAT = STATEMENT. %s
 - Error number: [1593](#); Symbol: [ER_BINLOG_FATAL_ERROR](#); SQLSTATE: [HY000](#)
Message: Fatal error: %s
 - Error number: [1598](#); Symbol: [ER_BINLOG_LOGGING_IMPOSSIBLE](#); SQLSTATE: [HY000](#)
Message: Binary logging not possible. Message: %s
 - Error number: [1599](#); Symbol: [ER_VIEW_NO_CREATION_CTX](#); SQLSTATE: [HY000](#)
Message: View `%s`.`%s` has no creation context
 - Error number: [1600](#); Symbol: [ER_VIEW_INVALID_CREATION_CTX](#); SQLSTATE: [HY000](#)
Message: Creation context of view `%s`.`%s` is invalid
 - Error number: [1602](#); Symbol: [ER_TRG_CORRUPTED_FILE](#); SQLSTATE: [HY000](#)
Message: Corrupted TRG file for table `%s`.`%s`
 - Error number: [1603](#); Symbol: [ER_TRG_NO_CREATION_CTX](#); SQLSTATE: [HY000](#)
Message: Triggers for table `%s`.`%s` have no creation context
 - Error number: [1604](#); Symbol: [ER_TRG_INVALID_CREATION_CTX](#); SQLSTATE: [HY000](#)
Message: Trigger creation context of table `%s`.`%s` is invalid

-
- Error number: 1605; Symbol: [ER_EVENT_INVALID_CREATION_CTX](#); SQLSTATE: HY000
Message: Creation context of event `%s`.`%s` is invalid
 - Error number: 1606; Symbol: [ER_TRG_CANT_OPEN_TABLE](#); SQLSTATE: HY000
Message: Cannot open table for trigger `%s`.`%s`
 - Error number: 1609; Symbol: [ER_NO_FORMAT_DESCRIPTION_EVENT_BEFORE_BINLOG_STATEMENT](#); SQLSTATE: HY000
Message: The BINLOG statement of type `%s` was not preceded by a format description BINLOG statement.
 - Error number: 1610; Symbol: [ER_REPLICA_CORRUPT_EVENT](#); SQLSTATE: HY000
Message: Corrupted replication event was detected
 - Error number: 1612; Symbol: [ER_LOG_PURGE_NO_FILE](#); SQLSTATE: HY000
Message: Being purged log %s was not found
 - Error number: 1613; Symbol: [ER_XA_RBTIMEOUT](#); SQLSTATE: XA106
Message: XA_RBTIMEOUT: Transaction branch was rolled back: took too long
 - Error number: 1614; Symbol: [ER_XA_RBDEADLOCK](#); SQLSTATE: XA102
Message: XA_RBDEADLOCK: Transaction branch was rolled back: deadlock was detected
 - Error number: 1615; Symbol: [ER_NEED_REPREPARE](#); SQLSTATE: HY000
Message: Prepared statement needs to be re-prepared
 - Error number: 1617; Symbol: [WARN_NO_CONNECTION_METADATA](#); SQLSTATE: HY000
Message: The connection metadata structure does not exist
 - Error number: 1618; Symbol: [WARN_OPTION_IGNORED](#); SQLSTATE: HY000
Message: <%s> option ignored
 - Error number: 1619; Symbol: [ER_PLUGIN_DELETE_BUILTIN](#); SQLSTATE: HY000
Message: Built-in plugins cannot be deleted
 - Error number: 1620; Symbol: [WARN_PLUGIN_BUSY](#); SQLSTATE: HY000
Message: Plugin is busy and will be uninstalled on shutdown
 - Error number: 1621; Symbol: [ER_VARIABLE_IS_READONLY](#); SQLSTATE: HY000
Message: %s variable '%s' is read-only. Use SET %s to assign the value
 - Error number: 1622; Symbol: [ER_WARN_ENGINE_TRANSACTION_ROLLBACK](#); SQLSTATE: HY000
Message: Storage engine %s does not support rollback for this statement. Transaction rolled back and must be restarted
 - Error number: 1624; Symbol: [ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE](#); SQLSTATE: HY000

Message: The requested value for the heartbeat period is either negative or exceeds the maximum allowed (%s seconds).

- Error number: [1625](#); Symbol: [ER_NDB_REPLICATION_SCHEMA_ERROR](#); SQLSTATE: [HY000](#)
Message: Bad schema for mysql.ndb_replication table. Message: %s
- Error number: [1626](#); Symbol: [ER_CONFLICT_FN_PARSE_ERROR](#); SQLSTATE: [HY000](#)
Message: Error in parsing conflict function. Message: %s
- Error number: [1627](#); Symbol: [ER_EXCEPTIONS_WRITE_ERROR](#); SQLSTATE: [HY000](#)
Message: Write to exceptions table failed. Message: %s
- Error number: [1628](#); Symbol: [ER_TOO_LONG_TABLE_COMMENT](#); SQLSTATE: [HY000](#)
Message: Comment for table '%s' is too long (max = %lu)
- Error number: [1629](#); Symbol: [ER_TOO_LONG_FIELD_COMMENT](#); SQLSTATE: [HY000](#)
Message: Comment for field '%s' is too long (max = %lu)
- Error number: [1630](#); Symbol: [ER_FUNC_INEXISTENT_NAME_COLLISION](#); SQLSTATE: [42000](#)
Message: FUNCTION %s does not exist. Check the 'Function Name Parsing and Resolution' section in the Reference Manual
- Error number: [1631](#); Symbol: [ER_DATABASE_NAME](#); SQLSTATE: [HY000](#)
Message: Database
- Error number: [1632](#); Symbol: [ER_TABLE_NAME](#); SQLSTATE: [HY000](#)
Message: Table
- Error number: [1633](#); Symbol: [ER_PARTITION_NAME](#); SQLSTATE: [HY000](#)
Message: Partition
- Error number: [1634](#); Symbol: [ER_SUBPARTITION_NAME](#); SQLSTATE: [HY000](#)
Message: Subpartition
- Error number: [1635](#); Symbol: [ER_TEMPORARY_NAME](#); SQLSTATE: [HY000](#)
Message: Temporary
- Error number: [1636](#); Symbol: [ER_RENAMED_NAME](#); SQLSTATE: [HY000](#)
Message: Renamed
- Error number: [1637](#); Symbol: [ER_TOO_MANY_CONCURRENT_TRXS](#); SQLSTATE: [HY000](#)
Message: Too many active concurrent transactions
- Error number: [1638](#); Symbol: [WARN_NON_ASCII_SEPARATOR_NOT_IMPLEMENTED](#); SQLSTATE: [HY000](#)
Message: Non-ASCII separator arguments are not fully supported

-
- Error number: [1639](#); Symbol: [ER_DEBUG_SYNC_TIMEOUT](#); SQLSTATE: [HY000](#)
Message: debug sync point wait timed out
 - Error number: [1640](#); Symbol: [ER_DEBUG_SYNC_HIT_LIMIT](#); SQLSTATE: [HY000](#)
Message: debug sync point hit limit reached
 - Error number: [1641](#); Symbol: [ER_DUP_SIGNAL_SET](#); SQLSTATE: [42000](#)
Message: Duplicate condition information item '%s'
 - Error number: [1642](#); Symbol: [ER_SIGNAL_WARN](#); SQLSTATE: [01000](#)
Message: Unhandled user-defined warning condition
 - Error number: [1643](#); Symbol: [ER_SIGNAL_NOT_FOUND](#); SQLSTATE: [02000](#)
Message: Unhandled user-defined not found condition
 - Error number: [1644](#); Symbol: [ER_SIGNAL_EXCEPTION](#); SQLSTATE: [HY000](#)
Message: Unhandled user-defined exception condition
 - Error number: [1645](#); Symbol: [ER_RESIGNAL_WITHOUT_ACTIVE_HANDLER](#); SQLSTATE: [0K000](#)
Message: RESIGNAL when handler not active
 - Error number: [1646](#); Symbol: [ER_SIGNAL_BAD_CONDITION_TYPE](#); SQLSTATE: [HY000](#)
Message: SIGNAL/RESIGNAL can only use a CONDITION defined with SQLSTATE
 - Error number: [1647](#); Symbol: [WARN_COND_ITEM_TRUNCATED](#); SQLSTATE: [HY000](#)
Message: Data truncated for condition item '%s'
 - Error number: [1648](#); Symbol: [ER_COND_ITEM_TOO_LONG](#); SQLSTATE: [HY000](#)
Message: Data too long for condition item '%s'
 - Error number: [1649](#); Symbol: [ER_UNKNOWN_LOCALE](#); SQLSTATE: [HY000](#)
Message: Unknown locale: '%s'
 - Error number: [1650](#); Symbol: [ER_REPLICA_IGNORE_SERVER_IDS](#); SQLSTATE: [HY000](#)
Message: The requested server id %d clashes with the replica startup option --replicate-same-server-id
 - Error number: [1652](#); Symbol: [ER_SAME_NAME_PARTITION_FIELD](#); SQLSTATE: [HY000](#)
Message: Duplicate partition field name '%s'
 - Error number: [1653](#); Symbol: [ER_PARTITION_COLUMN_LIST_ERROR](#); SQLSTATE: [HY000](#)
Message: Inconsistency in usage of column lists for partitioning
 - Error number: [1654](#); Symbol: [ER_WRONG_TYPE_COLUMN_VALUE_ERROR](#); SQLSTATE: [HY000](#)
Message: Partition column values of incorrect type
 - Error number: [1655](#); Symbol: [ER_TOO_MANY_PARTITION_FUNC_FIELDS_ERROR](#); SQLSTATE: [HY000](#)

Message: Too many fields in '%s'

- Error number: 1656; Symbol: [ER_MAXVALUE_IN_VALUES_IN](#); SQLSTATE: HY000

Message: Cannot use MAXVALUE as value in VALUES IN

- Error number: 1657; Symbol: [ER_TOO_MANY_VALUES_ERROR](#); SQLSTATE: HY000

Message: Cannot have more than one value for this type of %s partitioning

- Error number: 1658; Symbol: [ER_ROW_SINGLE_PARTITION_FIELD_ERROR](#); SQLSTATE: HY000

Message: Row expressions in VALUES IN only allowed for multi-field column partitioning

- Error number: 1659; Symbol: [ER_FIELD_TYPE_NOT_ALLOWED_AS_PARTITION_FIELD](#); SQLSTATE: HY000

Message: Field '%s' is of a not allowed type for this type of partitioning

- Error number: 1660; Symbol: [ER_PARTITION_FIELDS_TOO_LONG](#); SQLSTATE: HY000

Message: The total length of the partitioning fields is too large

- Error number: 1661; Symbol: [ER_BINLOG_ROW_ENGINE_AND_STMT_ENGINE](#); SQLSTATE: HY000

Message: Cannot execute statement: impossible to write to binary log since both row-incapable engines and statement-incapable engines are involved.

- Error number: 1662; Symbol: [ER_BINLOG_ROW_MODE_AND_STMT_ENGINE](#); SQLSTATE: HY000

Message: Cannot execute statement: impossible to write to binary log since BINLOG_FORMAT = ROW and at least one table uses a storage engine limited to statement-based logging.

- Error number: 1663; Symbol: [ER_BINLOG_UNSAFE_AND_STMT_ENGINE](#); SQLSTATE: HY000

Message: Cannot execute statement: impossible to write to binary log since statement is unsafe, storage engine is limited to statement-based logging, and BINLOG_FORMAT = MIXED. %s

- Error number: 1664; Symbol: [ER_BINLOG_ROW_INJECTION_AND_STMT_ENGINE](#); SQLSTATE: HY000

Message: Cannot execute statement: impossible to write to binary log since statement is in row format and at least one table uses a storage engine limited to statement-based logging.

- Error number: 1665; Symbol: [ER_BINLOG_STMT_MODE_AND_ROW_ENGINE](#); SQLSTATE: HY000

Message: Cannot execute statement: impossible to write to binary log since BINLOG_FORMAT = STATEMENT and at least one table uses a storage engine limited to row-based logging.%s

- Error number: 1666; Symbol: [ER_BINLOG_ROW_INJECTION_AND_STMT_MODE](#); SQLSTATE: HY000

Message: Cannot execute statement: impossible to write to binary log since statement is in row format and BINLOG_FORMAT = STATEMENT.

- Error number: 1667; Symbol: [ER_BINLOG_MULTIPLE_ENGINES_AND_SELF_LOGGING_ENGINE](#); SQLSTATE: HY000

Message: Cannot execute statement: impossible to write to binary log since more than one engine is involved and at least one engine is self-logging.

-
- Error number: [1668](#); Symbol: [ER_BINLOG_UNSAFE_LIMIT](#); SQLSTATE: [HY000](#)
Message: The statement is unsafe because it uses a LIMIT clause. This is unsafe because the set of rows included cannot be predicted.
 - Error number: [1670](#); Symbol: [ER_BINLOG_UNSAFE_SYSTEM_TABLE](#); SQLSTATE: [HY000](#)
Message: The statement is unsafe because it uses the general log, slow query log, or performance_schema table(s). This is unsafe because system tables may differ on replicas.
 - Error number: [1671](#); Symbol: [ER_BINLOG_UNSAFE_AUTOINC_COLUMNS](#); SQLSTATE: [HY000](#)
Message: Statement is unsafe because it invokes a trigger or a stored function that inserts into an AUTO_INCREMENT column. Inserted values cannot be logged correctly.
 - Error number: [1672](#); Symbol: [ER_BINLOG_UNSAFE_UDF](#); SQLSTATE: [HY000](#)
Message: Statement is unsafe because it uses a UDF which may not return the same value on the replica.
 - Error number: [1673](#); Symbol: [ER_BINLOG_UNSAFE_SYSTEM_VARIABLE](#); SQLSTATE: [HY000](#)
Message: Statement is unsafe because it uses a system variable that may have a different value on the replica.
 - Error number: [1674](#); Symbol: [ER_BINLOG_UNSAFE_SYSTEM_FUNCTION](#); SQLSTATE: [HY000](#)
Message: Statement is unsafe because it uses a system function that may return a different value on the replica.
 - Error number: [1675](#); Symbol: [ER_BINLOG_UNSAFE_NONTRANS_AFTER_TRANS](#); SQLSTATE: [HY000](#)
Message: Statement is unsafe because it accesses a non-transactional table after accessing a transactional table within the same transaction.
 - Error number: [1676](#); Symbol: [ER_MESSAGE_AND_STATEMENT](#); SQLSTATE: [HY000](#)
Message: %s Statement: %s
 - Error number: [1678](#); Symbol: [ER_REPLICA_CANT_CREATE_CONVERSION](#); SQLSTATE: [HY000](#)
Message: Can't create conversion table for table '%s.%s'
 - Error number: [1679](#); Symbol: [ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_FORMAT](#); SQLSTATE: [HY000](#)
Message: Cannot modify @@session.binlog_format inside a transaction
 - Error number: [1680](#); Symbol: [ER_PATH_LENGTH](#); SQLSTATE: [HY000](#)
Message: The path specified for %s is too long.
 - Error number: [1681](#); Symbol: [ER_WARN_DEPRECATED_SYNTAX_NO_REPLACEMENT](#); SQLSTATE: [HY000](#)
Message: '%s' is deprecated and will be removed in a future release.
 - Error number: [1682](#); Symbol: [ER_WRONG_NATIVE_TABLE_STRUCTURE](#); SQLSTATE: [HY000](#)
Message: Native table '%s'.'%s' has the wrong structure

-
- Error number: 1683; Symbol: [ER_WRONG_PERFSCHEMA_USAGE](#); SQLSTATE: HY000
Message: Invalid performance_schema usage.
 - Error number: 1684; Symbol: [ER_WARN_I_S_SKIPPED_TABLE](#); SQLSTATE: HY000
Message: Table '%s'. '%s' was skipped since its definition is being modified by concurrent DDL statement
 - Error number: 1685; Symbol: [ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_DIRECT](#); SQLSTATE: HY000
Message: Cannot modify @@session.binlog_direct_non_transactional_updates inside a transaction
 - Error number: 1686; Symbol: [ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_DIRECT](#); SQLSTATE: HY000
Message: Cannot change the binlog direct flag inside a stored function or trigger
 - Error number: 1687; Symbol: [ER_SPATIAL_MUST_HAVE_GEOM_COL](#); SQLSTATE: 42000
Message: A SPATIAL index may only contain a geometrical type column
 - Error number: 1688; Symbol: [ER_TOO_LONG_INDEX_COMMENT](#); SQLSTATE: HY000
Message: Comment for index '%s' is too long (max = %lu)
 - Error number: 1689; Symbol: [ER_LOCK_ABORTED](#); SQLSTATE: HY000
Message: Wait on a lock was aborted due to a pending exclusive lock
 - Error number: 1690; Symbol: [ER_DATA_OUT_OF_RANGE](#); SQLSTATE: 22003
Message: %s value is out of range in '%s'
 - Error number: 1692; Symbol: [ER_BINLOG_UNSAFE_MULTIPLE_ENGINES_AND_SELF_LOGGING_ENGINE](#); SQLSTATE: HY000
Message: Mixing self-logging and non-self-logging engines in a statement is unsafe.
 - Error number: 1693; Symbol: [ER_BINLOG_UNSAFE_MIXED_STATEMENT](#); SQLSTATE: HY000
Message: Statement accesses nontransactional table as well as transactional or temporary table, and writes to any of them.
 - Error number: 1694; Symbol: [ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_SQL_LOG_BIN](#); SQLSTATE: HY000
Message: Cannot modify @@session.sql_log_bin inside a transaction
 - Error number: 1695; Symbol: [ER_STORED_FUNCTION_PREVENTS_SWITCH_SQL_LOG_BIN](#); SQLSTATE: HY000
Message: Cannot change the sql_log_bin inside a stored function or trigger
 - Error number: 1696; Symbol: [ER_FAILED_READ_FROM_PAR_FILE](#); SQLSTATE: HY000
Message: Failed to read from the .par file
 - Error number: 1697; Symbol: [ER_VALUES_IS_NOT_INT_TYPE_ERROR](#); SQLSTATE: HY000

Message: VALUES value for partition '%s' must have type INT

- Error number: [1698](#); Symbol: [ER_ACCESS_DENIED_NO_PASSWORD_ERROR](#); SQLSTATE: [28000](#)

Message: Access denied for user '%s'@'%s'

- Error number: [1701](#); Symbol: [ER_TRUNCATE_ILLEGAL_FK](#); SQLSTATE: [42000](#)

Message: Cannot truncate a table referenced in a foreign key constraint (%s)

- Error number: [1702](#); Symbol: [ER_PLUGIN_IS_PERMANENT](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' is force_plus_permanent and can not be unloaded

- Error number: [1703](#); Symbol: [ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN](#); SQLSTATE: [HY000](#)

Message: The requested value for the heartbeat period is less than 1 millisecond. The value is reset to 0, meaning that heartbeating will effectively be disabled.

- Error number: [1704](#); Symbol: [ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX](#); SQLSTATE: [HY000](#)

Message: The requested value for the heartbeat period exceeds the value of `replica_net_timeout` seconds. A sensible value for the period should be less than the timeout.

- Error number: [1705](#); Symbol: [ER_STMT_CACHE_FULL](#); SQLSTATE: [HY000](#)

Message: Multi-row statements required more than 'max_binlog_stmt_cache_size' bytes of storage; increase this mysqld variable and try again

- Error number: [1706](#); Symbol: [ER_MULTI_UPDATE_KEY_CONFLICT](#); SQLSTATE: [HY000](#)

Message: Primary key/partition key update is not allowed since the table is updated both as '%s' and '%s'.

- Error number: [1707](#); Symbol: [ER_TABLE_NEEDS_REBUILD](#); SQLSTATE: [HY000](#)

Message: Table rebuild required. Please do "ALTER TABLE ` %s ` FORCE" or dump/reload to fix it!

- Error number: [1708](#); Symbol: [WARN_OPTION_BELOW_LIMIT](#); SQLSTATE: [HY000](#)

Message: The value of '%s' should be no less than the value of '%s'

- Error number: [1709](#); Symbol: [ER_INDEX_COLUMN_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: Index column size too large. The maximum column size is %lu bytes.

- Error number: [1710](#); Symbol: [ER_ERROR_IN_TRIGGER_BODY](#); SQLSTATE: [HY000](#)

Message: Trigger '%s' has an error in its body: '%s'

- Error number: [1711](#); Symbol: [ER_ERROR_IN_UNKNOWN_TRIGGER_BODY](#); SQLSTATE: [HY000](#)

Message: Unknown trigger has an error in its body: '%s'

- Error number: [1712](#); Symbol: [ER_INDEX_CORRUPT](#); SQLSTATE: [HY000](#)

Message: Index %s is corrupted

-
- Error number: [1713](#); Symbol: [ER_UNDO_RECORD_TOO_BIG](#); SQLSTATE: [HY000](#)
Message: Undo log record is too big.
 - Error number: [1714](#); Symbol: [ER_BINLOG_UNSAFE_INSERT_IGNORE_SELECT](#); SQLSTATE: [HY000](#)
Message: INSERT IGNORE... SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are ignored. This order cannot be predicted and may differ on source and the replica.
 - Error number: [1715](#); Symbol: [ER_BINLOG_UNSAFE_INSERT_SELECT_UPDATE](#); SQLSTATE: [HY000](#)
Message: INSERT... SELECT... ON DUPLICATE KEY UPDATE is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are updated. This order cannot be predicted and may differ on source and the replica.
 - Error number: [1716](#); Symbol: [ER_BINLOG_UNSAFE_REPLACE_SELECT](#); SQLSTATE: [HY000](#)
Message: REPLACE... SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are replaced. This order cannot be predicted and may differ on source and the replica.
 - Error number: [1717](#); Symbol: [ER_BINLOG_UNSAFE_CREATE_IGNORE_SELECT](#); SQLSTATE: [HY000](#)
Message: CREATE... IGNORE SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are ignored. This order cannot be predicted and may differ on source and the replica.
 - Error number: [1718](#); Symbol: [ER_BINLOG_UNSAFE_CREATE_REPLACE_SELECT](#); SQLSTATE: [HY000](#)
Message: CREATE... REPLACE SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are replaced. This order cannot be predicted and may differ on source and the replica.
 - Error number: [1719](#); Symbol: [ER_BINLOG_UNSAFE_UPDATE_IGNORE](#); SQLSTATE: [HY000](#)
Message: UPDATE IGNORE is unsafe because the order in which rows are updated determines which (if any) rows are ignored. This order cannot be predicted and may differ on source and the replica.
 - Error number: [1720](#); Symbol: [ER_PLUGIN_NO_UNINSTALL](#); SQLSTATE: [HY000](#)
Message: Plugin '%s' is marked as not dynamically uninstallable. You have to stop the server to uninstall it.
 - Error number: [1721](#); Symbol: [ER_PLUGIN_NO_INSTALL](#); SQLSTATE: [HY000](#)
Message: Plugin '%s' is marked as not dynamically installable. You have to stop the server to install it.
 - Error number: [1722](#); Symbol: [ER_BINLOG_UNSAFE_WRITE_AUTOINC_SELECT](#); SQLSTATE: [HY000](#)
Message: Statements writing to a table with an auto-increment column after selecting from another table are unsafe because the order in which rows are retrieved determines what (if any) rows will be written. This order cannot be predicted and may differ on source and the replica.
 - Error number: [1723](#); Symbol: [ER_BINLOG_UNSAFE_CREATE_SELECT_AUTOINC](#); SQLSTATE: [HY000](#)
Message: CREATE TABLE... SELECT... on a table with an auto-increment column is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are inserted. This order cannot be predicted and may differ on source and the replica.

-
- Error number: [1724](#); Symbol: [ER_BINLOG_UNSAFE_INSERT_TWO_KEYS](#); SQLSTATE: [HY000](#)
Message: INSERT... ON DUPLICATE KEY UPDATE on a table with more than one UNIQUE KEY is unsafe
 - Error number: [1725](#); Symbol: [ER_TABLE_IN_FK_CHECK](#); SQLSTATE: [HY000](#)
Message: Table is being used in foreign key check.
 - Error number: [1726](#); Symbol: [ER_UNSUPPORTED_ENGINE](#); SQLSTATE: [HY000](#)
Message: Storage engine '%s' does not support system tables. [%s.%s]
 - Error number: [1727](#); Symbol: [ER_BINLOG_UNSAFE_AUTOINC_NOT_FIRST](#); SQLSTATE: [HY000](#)
Message: INSERT into autoincrement field which is not the first part in the composed primary key is unsafe.
 - Error number: [1728](#); Symbol: [ER_CANNOT_LOAD_FROM_TABLE_V2](#); SQLSTATE: [HY000](#)
Message: Cannot load from %s.%s. The table is probably corrupted
 - Error number: [1729](#); Symbol: [ER_SOURCE_DELAY_VALUE_OUT_OF_RANGE](#); SQLSTATE: [HY000](#)
Message: The requested value %s for the source delay exceeds the maximum %u
 - Error number: [1730](#); Symbol: [ER_ONLY_FD_AND_RBR_EVENTS_ALLOWED_IN_BINLOG_STATEMENT](#); SQLSTATE: [HY000](#)
Message: Only Format_description_log_event and row events are allowed in BINLOG statements (but %s was provided)
 - Error number: [1731](#); Symbol: [ER_PARTITION_EXCHANGE_DIFFERENT_OPTION](#); SQLSTATE: [HY000](#)
Message: Non matching attribute '%s' between partition and table
 - Error number: [1732](#); Symbol: [ER_PARTITION_EXCHANGE_PART_TABLE](#); SQLSTATE: [HY000](#)
Message: Table to exchange with partition is partitioned: '%s'
 - Error number: [1733](#); Symbol: [ER_PARTITION_EXCHANGE_TEMP_TABLE](#); SQLSTATE: [HY000](#)
Message: Table to exchange with partition is temporary: '%s'
 - Error number: [1734](#); Symbol: [ER_PARTITION_INSTEAD_OF_SUBPARTITION](#); SQLSTATE: [HY000](#)
Message: Subpartitioned table, use subpartition instead of partition
 - Error number: [1735](#); Symbol: [ER_UNKNOWN_PARTITION](#); SQLSTATE: [HY000](#)
Message: Unknown partition '%s' in table '%s'
 - Error number: [1736](#); Symbol: [ER_TABLES_DIFFERENT_METADATA](#); SQLSTATE: [HY000](#)
Message: Tables have different definitions
 - Error number: [1737](#); Symbol: [ER_ROW_DOES_NOT_MATCH_PARTITION](#); SQLSTATE: [HY000](#)
Message: Found a row that does not match the partition

-
- Error number: 1738; Symbol: [ER_BINLOG_CACHE_SIZE_GREATER_THAN_MAX](#); SQLSTATE: HY000
Message: Option binlog_cache_size (%lu) is greater than max_binlog_cache_size (%lu); setting binlog_cache_size equal to max_binlog_cache_size.
 - Error number: 1739; Symbol: [ER_WARN_INDEX_NOT_APPLICABLE](#); SQLSTATE: HY000
Message: Cannot use %s access on index '%s' due to type or collation conversion on field '%s'
 - Error number: 1740; Symbol: [ER_PARTITION_EXCHANGE_FOREIGN_KEY](#); SQLSTATE: HY000
Message: Table to exchange with partition has foreign key references: '%s'
 - Error number: 1742; Symbol: [ER_RPL_INFO_DATA_TOO_LONG](#); SQLSTATE: HY000
Message: Data for column '%s' too long
 - Error number: 1745; Symbol: [ER_BINLOG_STMT_CACHE_SIZE_GREATER_THAN_MAX](#); SQLSTATE: HY000
Message: Option binlog_stmt_cache_size (%lu) is greater than max_binlog_stmt_cache_size (%lu); setting binlog_stmt_cache_size equal to max_binlog_stmt_cache_size.
 - Error number: 1746; Symbol: [ER_CANT_UPDATE_TABLE_IN_CREATE_TABLE_SELECT](#); SQLSTATE: HY000
Message: Can't update table '%s' while '%s' is being created.
 - Error number: 1747; Symbol: [ER_PARTITION_CLAUSE_ON_NONPARTITIONED](#); SQLSTATE: HY000
Message: PARTITION () clause on non partitioned table
 - Error number: 1748; Symbol: [ER_ROW_DOES_NOT_MATCH_GIVEN_PARTITION_SET](#); SQLSTATE: HY000
Message: Found a row not matching the given partition set
 - Error number: 1750; Symbol: [ER_CHANGE_RPL_INFO_REPOSITORY_FAILURE](#); SQLSTATE: HY000
Message: Failure while changing the type of replication repository: %s.
 - Error number: 1751; Symbol: [ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_CREATED_TEMP_TABLE](#); SQLSTATE: HY000
Message: The creation of some temporary tables could not be rolled back.
 - Error number: 1752; Symbol: [ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_DROPPED_TEMP_TABLE](#); SQLSTATE: HY000
Message: Some temporary tables were dropped, but these operations could not be rolled back.
 - Error number: 1753; Symbol: [ER_MTA_FEATURE_IS_NOT_SUPPORTED](#); SQLSTATE: HY000
Message: %s is not supported in multi-threaded replica mode. %s
 - Error number: 1754; Symbol: [ER_MTA_UPDATED_DBS_GREATER_MAX](#); SQLSTATE: HY000
Message: The number of modified databases exceeds the maximum %d; the database names will not be included in the replication event metadata.

-
- Error number: [1755](#); Symbol: [ER_MTA_CANT_PARALLEL](#); SQLSTATE: [HY000](#)
Message: Cannot execute the current event group in the parallel mode. Encountered event %s, relay-log name %s, position %s which prevents execution of this event group in parallel mode. Reason: %s.
 - Error number: [1756](#); Symbol: [ER_MTA_INCONSISTENT_DATA](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [1757](#); Symbol: [ER_FULLTEXT_NOT_SUPPORTED_WITH_PARTITIONING](#); SQLSTATE: [HY000](#)
Message: FULLTEXT index is not supported for partitioned tables.
 - Error number: [1758](#); Symbol: [ER_DA_INVALID_CONDITION_NUMBER](#); SQLSTATE: [35000](#)
Message: Invalid condition number
 - Error number: [1759](#); Symbol: [ER_INSECURE_PLAIN_TEXT](#); SQLSTATE: [HY000](#)
Message: Sending passwords in plain text without SSL/TLS is extremely insecure.
 - Error number: [1760](#); Symbol: [ER_INSECURE_CHANGE_SOURCE](#); SQLSTATE: [HY000](#)
Message: Storing MySQL user name or password information in the connection metadata repository is not secure and is therefore not recommended. Please consider using the USER and PASSWORD connection options for START REPLICA; see the 'START REPLICA Syntax' in the MySQL Manual for more information.
 - Error number: [1761](#); Symbol: [ER_FOREIGN_DUPLICATE_KEY_WITH_CHILD_INFO](#); SQLSTATE: [23000](#)
Message: Foreign key constraint for table '%s', record '%s' would lead to a duplicate entry in table '%s', key '%s'
 - Error number: [1762](#); Symbol: [ER_FOREIGN_DUPLICATE_KEY_WITHOUT_CHILD_INFO](#); SQLSTATE: [23000](#)
Message: Foreign key constraint for table '%s', record '%s' would lead to a duplicate entry in a child table
 - Error number: [1763](#); Symbol: [ER_SQLTHREAD_WITH_SECURE_REPLICA](#); SQLSTATE: [HY000](#)
Message: Setting authentication options is not possible when only the Replica SQL Thread is being started.
 - Error number: [1764](#); Symbol: [ER_TABLE_HAS_NO_FT](#); SQLSTATE: [HY000](#)
Message: The table does not have FULLTEXT index to support this query
 - Error number: [1765](#); Symbol: [ER_VARIABLE_NOT_SETTABLE_IN_SF_OR_TRIGGER](#); SQLSTATE: [HY000](#)
Message: The system variable %s cannot be set in stored functions or triggers.
 - Error number: [1766](#); Symbol: [ER_VARIABLE_NOT_SETTABLE_IN_TRANSACTION](#); SQLSTATE: [HY000](#)
Message: The system variable %s cannot be set when there is an ongoing transaction.
 - Error number: [1769](#); Symbol: [ER_SET_STATEMENT_CANNOT_INVOKE_FUNCTION](#); SQLSTATE: [HY000](#)

Message: The statement 'SET %s' cannot invoke a stored function.

- Error number: 1770; Symbol:

[ER_GTID_NEXT_CANT_BE_AUTOMATIC_IF_GTID_NEXT_LIST_IS_NON_NULL](#); SQLSTATE: HY000

Message: The system variable @@SESSION.GTID_NEXT cannot be 'AUTOMATIC' when @@SESSION.GTID_NEXT_LIST is non-NULL.

- Error number: 1772; Symbol: [ER_MALFORMED_GTID_SET_SPECIFICATION](#); SQLSTATE: HY000

Message: Malformed GTID set specification '%s'.

- Error number: 1773; Symbol: [ER_MALFORMED_GTID_SET_ENCODING](#); SQLSTATE: HY000

Message: Malformed GTID set encoding.

- Error number: 1774; Symbol: [ER_MALFORMED_GTID_SPECIFICATION](#); SQLSTATE: HY000

Message: Malformed GTID specification '%s'.

- Error number: 1775; Symbol: [ER_GNO_EXHAUSTED](#); SQLSTATE: HY000

Message: Impossible to generate GTID: the integer component reached the maximum value. Restart the server with a new server_uuid.

- Error number: 1776; Symbol: [ER_BAD_REPLICA_AUTO_POSITION](#); SQLSTATE: HY000

Message: Parameters SOURCE_LOG_FILE, SOURCE_LOG_POS, RELAY_LOG_FILE and RELAY_LOG_POS cannot be set when SOURCE_AUTO_POSITION is active.

- Error number: 1777; Symbol: [ER_AUTO_POSITION_REQUIRES_GTID_MODE_NOT_OFF](#); SQLSTATE: HY000

Message: CHANGE REPLICATION SOURCE TO SOURCE_AUTO_POSITION = 1 cannot be executed because @@GLOBAL.GTID_MODE = OFF.

- Error number: 1778; Symbol:

[ER_CANT_DO_IMPLICIT_COMMIT_IN_TRX_WHEN_GTID_NEXT_IS_SET](#); SQLSTATE: HY000

Message: Cannot execute statements with implicit commit inside a transaction when @@SESSION.GTID_NEXT == 'UUID:NUMBER'.

- Error number: 1779; Symbol: [ER_GTID_MODE_ON_REQUIRES_ENFORCE_GTID_CONSISTENCY_ON](#); SQLSTATE: HY000

Message: GTID_MODE = ON requires ENFORCE_GTID_CONSISTENCY = ON.

- Error number: 1781; Symbol: [ER_CANT_SET_GTID_NEXT_TO_GTID_WHEN_GTID_MODE_IS_OFF](#); SQLSTATE: HY000

Message: @@SESSION.GTID_NEXT cannot be set to UUID:NUMBER when @@GLOBAL.GTID_MODE = OFF.

- Error number: 1782; Symbol:

[ER_CANT_SET_GTID_NEXT_TO_ANONYMOUS_WHEN_GTID_MODE_IS_ON](#); SQLSTATE: HY000

Message: @@SESSION.GTID_NEXT cannot be set to ANONYMOUS when @@GLOBAL.GTID_MODE = ON.

-
- Error number: 1783; Symbol: [ER_CANT_SET_GTID_NEXT_LIST_TO_NON_NULL_WHEN_GTID_MODE_IS_OFF](#); SQLSTATE: HY000
Message: @@SESSION.GTID_NEXT_LIST cannot be set to a non-NULL value when @@GLOBAL.GTID_MODE = OFF.
 - Error number: 1785; Symbol: [ER_GTID_UNSAFE_NON_TRANSACTIONAL_TABLE](#); SQLSTATE: HY000
Message: Statement violates GTID consistency: Updates to non-transactional tables can only be done in either autocommitted statements or single-statement transactions, and never in the same statement as updates to transactional tables.
 - Error number: 1786; Symbol: [ER_GTID_UNSAFE_CREATE_SELECT](#); SQLSTATE: HY000
Message: Statement violates GTID consistency: CREATE TABLE ... SELECT.
 - Error number: 1788; Symbol: [ER_GTID_MODE_CAN_ONLY_CHANGE_ONE_STEP_AT_A_TIME](#); SQLSTATE: HY000
Message: The value of @@GLOBAL.GTID_MODE can only be changed one step at a time: OFF <-> OFF_PERMISSIVE <-> ON_PERMISSIVE <-> ON. Also note that this value must be stepped up or down simultaneously on all servers. See the Manual for instructions.
 - Error number: 1789; Symbol: [ER_SOURCE_HAS_PURGED_REQUIRED_GTIDS](#); SQLSTATE: HY000
Message: Cannot replicate because the source purged required binary logs. Replicate the missing transactions from elsewhere, or provision a new replica from backup. Consider increasing the source's binary log expiration period. %s
 - Error number: 1790; Symbol: [ER_CANT_SET_GTID_NEXT_WHEN_OWNING_GTID](#); SQLSTATE: HY000
Message: @@SESSION.GTID_NEXT cannot be changed by a client that owns a GTID. The client owns %s. Ownership is released on COMMIT or ROLLBACK.
 - Error number: 1791; Symbol: [ER_UNKNOWN_EXPLAIN_FORMAT](#); SQLSTATE: HY000
Message: Unknown EXPLAIN format name: '%s'
 - Error number: 1792; Symbol: [ER_CANT_EXECUTE_IN_READ_ONLY_TRANSACTION](#); SQLSTATE: 25006
Message: Cannot execute statement in a READ ONLY transaction.
 - Error number: 1793; Symbol: [ER_TOO_LONG_TABLE_PARTITION_COMMENT](#); SQLSTATE: HY000
Message: Comment for table partition '%s' is too long (max = %lu)
 - Error number: 1794; Symbol: [ER_REPLICA_CONFIGURATION](#); SQLSTATE: HY000
Message: Replica is not configured or failed to initialize properly. You must at least set --server-id to enable either a source or a replica. Additional error messages can be found in the MySQL error log.
 - Error number: 1795; Symbol: [ER_INNODB_FT_LIMIT](#); SQLSTATE: HY000
Message: InnoDB presently supports one FULLTEXT index creation at a time
 - Error number: 1796; Symbol: [ER_INNODB_NO_FT_TEMP_TABLE](#); SQLSTATE: HY000
Message: Cannot create FULLTEXT index on temporary InnoDB table

-
- Error number: [1797](#); Symbol: [ER_INNODB_FT_WRONG_DOCID_COLUMN](#); SQLSTATE: [HY000](#)
Message: Column '%s' is of wrong type for an InnoDB FULLTEXT index
 - Error number: [1798](#); Symbol: [ER_INNODB_FT_WRONG_DOCID_INDEX](#); SQLSTATE: [HY000](#)
Message: Index '%s' is of wrong type for an InnoDB FULLTEXT index
 - Error number: [1799](#); Symbol: [ER_INNODB_ONLINE_LOG_TOO_BIG](#); SQLSTATE: [HY000](#)
Message: Creating index '%s' required more than 'innodb_online_alter_log_max_size' bytes of modification log. Please try again.
 - Error number: [1800](#); Symbol: [ER_UNKNOWN_ALTER_ALGORITHM](#); SQLSTATE: [HY000](#)
Message: Unknown ALGORITHM '%s'
 - Error number: [1801](#); Symbol: [ER_UNKNOWN_ALTER_LOCK](#); SQLSTATE: [HY000](#)
Message: Unknown LOCK type '%s'
 - Error number: [1802](#); Symbol: [ER_MTA_CHANGE_SOURCE_CANT_RUN_WITH_GAPS](#); SQLSTATE: [HY000](#)
Message: CHANGE REPLICATION SOURCE cannot be executed when the replica was stopped with an error or killed in MTA mode. Consider using RESET REPLICA or START REPLICA UNTIL.
 - Error number: [1803](#); Symbol: [ER_MTA_RECOVERY_FAILURE](#); SQLSTATE: [HY000](#)
Message: Cannot recover after REPLICA errored out in parallel execution mode. Additional error messages can be found in the MySQL error log.
 - Error number: [1804](#); Symbol: [ER_MTA_RESET_WORKERS](#); SQLSTATE: [HY000](#)
Message: Cannot clean up worker info tables. Additional error messages can be found in the MySQL error log.
 - Error number: [1805](#); Symbol: [ER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2](#); SQLSTATE: [HY000](#)
Message: Column count of %s.%s is wrong. Expected %d, found %d. The table is probably corrupted
 - Error number: [1806](#); Symbol: [ER_REPLICA_SILENT_RETRY_TRANSACTION](#); SQLSTATE: [HY000](#)
Message: Replica must silently retry current transaction
 - Error number: [1807](#); Symbol: [ER_DISCARD_FK_CHECKS_RUNNING](#); SQLSTATE: [HY000](#)
Message: There is a foreign key check running on table '%s'. Cannot discard the table.
 - Error number: [1808](#); Symbol: [ER_TABLE_SCHEMA_MISMATCH](#); SQLSTATE: [HY000](#)
Message: Schema mismatch (%s)
 - Error number: [1809](#); Symbol: [ER_TABLE_IN_SYSTEM_TABLESPACE](#); SQLSTATE: [HY000](#)
Message: Table '%s' in system tablespace
 - Error number: [1810](#); Symbol: [ER_IO_READ_ERROR](#); SQLSTATE: [HY000](#)
Message: IO Read error: (%lu, %s) %s

-
- Error number: 1811; Symbol: `ER_IO_WRITE_ERROR`; SQLSTATE: `HY000`
Message: IO Write error: (%lu, %s) %s
 - Error number: 1812; Symbol: `ER_TABLESPACE_MISSING`; SQLSTATE: `HY000`
Message: Tablespace is missing for table %s.
 - Error number: 1813; Symbol: `ER_TABLESPACE_EXISTS`; SQLSTATE: `HY000`
Message: Tablespace '%s' exists.
 - Error number: 1814; Symbol: `ER_TABLESPACE_DISCARDED`; SQLSTATE: `HY000`
Message: Tablespace has been discarded for table '%s'
 - Error number: 1815; Symbol: `ER_INTERNAL_ERROR`; SQLSTATE: `HY000`
Message: Internal error: %s
 - Error number: 1816; Symbol: `ER_INNODB_IMPORT_ERROR`; SQLSTATE: `HY000`
Message: ALTER TABLE %s IMPORT TABLESPACE failed with error %lu : '%s'
 - Error number: 1817; Symbol: `ER_INNODB_INDEX_CORRUPT`; SQLSTATE: `HY000`
Message: Index corrupt: %s
 - Error number: 1818; Symbol: `ER_INVALID_YEAR_COLUMN_LENGTH`; SQLSTATE: `HY000`
Message: Invalid display width. Use YEAR instead.
 - Error number: 1819; Symbol: `ER_NOT_VALID_PASSWORD`; SQLSTATE: `HY000`
Message: Your password does not satisfy the current policy requirements
 - Error number: 1820; Symbol: `ER_MUST_CHANGE_PASSWORD`; SQLSTATE: `HY000`
Message: You must reset your password using ALTER USER statement before executing this statement.
 - Error number: 1821; Symbol: `ER_FK_NO_INDEX_CHILD`; SQLSTATE: `HY000`
Message: Failed to add the foreign key constraint. Missing index for constraint '%s' in the foreign table '%s'
 - Error number: 1822; Symbol: `ER_FK_NO_INDEX_PARENT`; SQLSTATE: `HY000`
Message: Failed to add the foreign key constraint. Missing index for constraint '%s' in the referenced table '%s'
 - Error number: 1823; Symbol: `ER_FK_FAIL_ADD_SYSTEM`; SQLSTATE: `HY000`
Message: Failed to add the foreign key constraint '%s' to system tables
 - Error number: 1824; Symbol: `ER_FK_CANNOT_OPEN_PARENT`; SQLSTATE: `HY000`
Message: Failed to open the referenced table '%s'
 - Error number: 1825; Symbol: `ER_FK_INCORRECT_OPTION`; SQLSTATE: `HY000`

Message: Failed to add the foreign key constraint on table '%s'. Incorrect options in FOREIGN KEY constraint '%s'

- Error number: [1826](#); Symbol: [ER_FK_DUP_NAME](#); SQLSTATE: [HY000](#)

Message: Duplicate foreign key constraint name '%s'

- Error number: [1827](#); Symbol: [ER_PASSWORD_FORMAT](#); SQLSTATE: [HY000](#)

Message: The password hash doesn't have the expected format.

- Error number: [1828](#); Symbol: [ER_FK_COLUMN_CANNOT_DROP](#); SQLSTATE: [HY000](#)

Message: Cannot drop column '%s': needed in a foreign key constraint '%s'

- Error number: [1829](#); Symbol: [ER_FK_COLUMN_CANNOT_DROP_CHILD](#); SQLSTATE: [HY000](#)

Message: Cannot drop column '%s': needed in a foreign key constraint '%s' of table '%s'

- Error number: [1830](#); Symbol: [ER_FK_COLUMN_NOT_NULL](#); SQLSTATE: [HY000](#)

Message: Column '%s' cannot be NOT NULL: needed in a foreign key constraint '%s' SET NULL

- Error number: [1831](#); Symbol: [ER_DUP_INDEX](#); SQLSTATE: [HY000](#)

Message: Duplicate index '%s' defined on the table '%s.%s'. This is deprecated and will be disallowed in a future release.

- Error number: [1832](#); Symbol: [ER_FK_COLUMN_CANNOT_CHANGE](#); SQLSTATE: [HY000](#)

Message: Cannot change column '%s': used in a foreign key constraint '%s'

- Error number: [1833](#); Symbol: [ER_FK_COLUMN_CANNOT_CHANGE_CHILD](#); SQLSTATE: [HY000](#)

Message: Cannot change column '%s': used in a foreign key constraint '%s' of table '%s'

- Error number: [1835](#); Symbol: [ER_MALFORMED_PACKET](#); SQLSTATE: [HY000](#)

Message: Malformed communication packet.

- Error number: [1836](#); Symbol: [ER_READ_ONLY_MODE](#); SQLSTATE: [HY000](#)

Message: Running in read-only mode

- Error number: [1837](#); Symbol: [ER_GTID_NEXT_TYPE_UNDEFINED_GTID](#); SQLSTATE: [HY000](#)

Message: When @@SESSION.GTID_NEXT is set to a GTID, you must explicitly set it to a different value after a COMMIT or ROLLBACK. Please check GTID_NEXT variable manual page for detailed explanation. Current @@SESSION.GTID_NEXT is '%s'.

- Error number: [1838](#); Symbol: [ER_VARIABLE_NOT_SETTABLE_IN_SP](#); SQLSTATE: [HY000](#)

Message: The system variable %s cannot be set in stored procedures.

- Error number: [1840](#); Symbol: [ER_CANT_SET_GTID_PURGED_WHEN_GTID_EXECUTED_IS_NOT_EMPTY](#); SQLSTATE: [HY000](#)

Message: @@GLOBAL.GTID_PURGED can only be set when @@GLOBAL.GTID_EXECUTED is empty.

-
- Error number: 1841; Symbol: ER_CANT_SET_GTID_PURGED_WHEN_OWNED_GTIDS_IS_NOT_EMPTY; SQLSTATE: HY000
Message: @@GLOBAL.GTID_PURGED can only be set when there are no ongoing transactions (not even in other clients).
 - Error number: 1842; Symbol: ER_GTID_PURGED_WAS_CHANGED; SQLSTATE: HY000
Message: @@GLOBAL.GTID_PURGED was changed from '%s' to '%s'.
 - Error number: 1843; Symbol: ER_GTID_EXECUTED_WAS_CHANGED; SQLSTATE: HY000
Message: @@GLOBAL.GTID_EXECUTED was changed from '%s' to '%s'.
 - Error number: 1844; Symbol: ER_BINLOG_STMT_MODE_AND_NO_REPL_TABLES; SQLSTATE: HY000
Message: Cannot execute statement: impossible to write to binary log since BINLOG_FORMAT = STATEMENT, and both replicated and non replicated tables are written to.
 - Error number: 1845; Symbol: ER_ALTER_OPERATION_NOT_SUPPORTED; SQLSTATE: 0A000
Message: %s is not supported for this operation. Try %s.
 - Error number: 1846; Symbol: ER_ALTER_OPERATION_NOT_SUPPORTED_REASON; SQLSTATE: 0A000
Message: %s is not supported. Reason: %s. Try %s.
 - Error number: 1847; Symbol: ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COPY; SQLSTATE: HY000
Message: COPY algorithm requires a lock
 - Error number: 1848; Symbol: ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_PARTITION; SQLSTATE: HY000
Message: Partition specific operations do not yet support LOCK/ALGORITHM
 - Error number: 1849; Symbol: ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FK_RENAME; SQLSTATE: HY000
Message: Columns participating in a foreign key are renamed
 - Error number: 1850; Symbol: ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COLUMN_TYPE; SQLSTATE: HY000
Message: Cannot change column type INPLACE
 - Error number: 1851; Symbol: ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FK_CHECK; SQLSTATE: HY000
Message: Adding foreign keys needs foreign_key_checks=OFF
 - Error number: 1853; Symbol: ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_NOPK; SQLSTATE: HY000
Message: Dropping a primary key is not allowed without also adding a new primary key
 - Error number: 1854; Symbol: ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_AUTOINC; SQLSTATE: HY000

Message: Adding an auto-increment column requires a lock

- Error number: 1855; Symbol: ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_HIDDEN_FTS; SQLSTATE: HY000

Message: Cannot replace hidden FTS_DOC_ID with a user-visible one

- Error number: 1856; Symbol: ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_CHANGE_FTS; SQLSTATE: HY000

Message: Cannot drop or rename FTS_DOC_ID

- Error number: 1857; Symbol: ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FTS; SQLSTATE: HY000

Message: Fulltext index creation requires a lock

- Error number: 1859; Symbol: ER_DUP_UNKNOWN_IN_INDEX; SQLSTATE: 23000

Message: Duplicate entry for key '%s'

- Error number: 1860; Symbol: ER_IDENT_CAUSES_TOO_LONG_PATH; SQLSTATE: HY000

Message: Long database name and identifier for object resulted in path length exceeding %d characters. Path: '%s'.

- Error number: 1861; Symbol: ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_NOT_NULL; SQLSTATE: HY000

Message: cannot silently convert NULL values, as required in this SQL_MODE

- Error number: 1862; Symbol: ER_MUST_CHANGE_PASSWORD_LOGIN; SQLSTATE: HY000

Message: Your password has expired. To log in you must change it using a client that supports expired passwords.

- Error number: 1863; Symbol: ER_ROW_IN_WRONG_PARTITION; SQLSTATE: HY000

Message: Found a row in wrong partition %s

- Error number: 1864; Symbol: ER_MTA_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX; SQLSTATE: HY000

Message: Cannot schedule event %s, relay-log name %s, position %s to Worker thread because its size %lu exceeds %lu of replica_pending_jobs_size_max.

- Error number: 1866; Symbol: ER_BINLOG_LOGICAL_CORRUPTION; SQLSTATE: HY000

Message: The binary log file '%s' is logically corrupted: %s

- Error number: 1867; Symbol: ER_WARN_PURGE_LOG_IN_USE; SQLSTATE: HY000

Message: file %s was not purged because it was being read by %d thread(s), purged only %d out of %d files.

- Error number: 1868; Symbol: ER_WARN_PURGE_LOG_IS_ACTIVE; SQLSTATE: HY000

Message: file %s was not purged because it is the active log file.

-
- Error number: [1869](#); Symbol: [ER_AUTO_INCREMENT_CONFLICT](#); SQLSTATE: [HY000](#)
Message: Auto-increment value in UPDATE conflicts with internally generated values
 - Error number: [1870](#); Symbol: [WARN_ON_BLOCKHOLE_IN_RBR](#); SQLSTATE: [HY000](#)
Message: Row events are not logged for %s statements that modify BLACKHOLE tables in row format. Table(s): '%s'
 - Error number: [1871](#); Symbol: [ER_REPLICA_CM_INIT_REPOSITORY](#); SQLSTATE: [HY000](#)
Message: Replica failed to initialize connection metadata structure from the repository
 - Error number: [1872](#); Symbol: [ER_REPLICA_AM_INIT_REPOSITORY](#); SQLSTATE: [HY000](#)
Message: Replica failed to initialize applier metadata structure from the repository
 - Error number: [1873](#); Symbol: [ER_ACCESS_DENIED_CHANGE_USER_ERROR](#); SQLSTATE: [28000](#)
Message: Access denied trying to change to user '%s'@'%s' (using password: %s). Disconnecting.
 - Error number: [1874](#); Symbol: [ER_INNO_DB_READ_ONLY](#); SQLSTATE: [HY000](#)
Message: InnoDB is in read only mode.
 - Error number: [1875](#); Symbol: [ER_STOP_REPLICA_SQL_THREAD_TIMEOUT](#); SQLSTATE: [HY000](#)
Message: STOP REPLICA command execution is incomplete: Replica SQL thread got the stop signal, thread is busy, SQL thread will stop once the current task is complete.
 - Error number: [1876](#); Symbol: [ER_STOP_REPLICA_IO_THREAD_TIMEOUT](#); SQLSTATE: [HY000](#)
Message: STOP REPLICA command execution is incomplete: Replica IO thread got the stop signal, thread is busy, IO thread will stop once the current task is complete.
 - Error number: [1877](#); Symbol: [ER_TABLE_CORRUPT](#); SQLSTATE: [HY000](#)
Message: Operation cannot be performed. The table '%s.%s' is missing, corrupt or contains bad data.
 - Error number: [1878](#); Symbol: [ER_TEMP_FILE_WRITE_FAILURE](#); SQLSTATE: [HY000](#)
Message: Temporary file write failure.
 - Error number: [1879](#); Symbol: [ER_INNO_DB_FT_AUX_NOT_HEX_ID](#); SQLSTATE: [HY000](#)
Message: Upgrade index name failed, please use create index(alter table) algorithm copy to rebuild index.
 - Error number: [1880](#); Symbol: [ER_OLD_TEMPORALS_UPGRADED](#); SQLSTATE: [HY000](#)
Message: TIME/TIMESTAMP/DATETIME columns of old format have been upgraded to the new format.
 - Error number: [1881](#); Symbol: [ER_INNO_DB_FORCED_RECOVERY](#); SQLSTATE: [HY000](#)
Message: Operation not allowed when innodb_force_recovery > 0.
 - Error number: [1882](#); Symbol: [ER_AES_INVALID_IV](#); SQLSTATE: [HY000](#)
Message: The initialization vector supplied to %s is too short. Must be at least %d bytes long

-
- Error number: 1883; Symbol: [ER_PLUGIN_CANNOT_BE_UNINSTALLED](#); SQLSTATE: HY000
Message: Plugin '%s' cannot be uninstalled now. %s
 - Error number: 1884; Symbol: [ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_ASSIGNED_GTID](#); SQLSTATE: HY000
Message: Cannot execute statement because it needs to be written to the binary log as multiple statements, and this is not allowed when @@SESSION.GTID_NEXT == 'UUID:NUMBER'.
 - Error number: 1885; Symbol: [ER_REPLICA_HAS_MORE_GTIDS_THAN_SOURCE](#); SQLSTATE: HY000
Message: Replica has more GTIDs than the source has, using the source's SERVER_UUID. This may indicate that the the last binary log file was truncated or lost, e.g., after a power failure when sync_binlog != 1. The source may have rolled back transactions that were already replicated to the replica. Replicate any transactions that source has rolled back from replica to source, and/or commit empty transactions on source to account for transactions that have been committed on source but are not included in GTID_EXECUTED.
 - Error number: 1886; Symbol: [ER_MISSING_KEY](#); SQLSTATE: HY000
Message: The table '%s.%s' does not have the necessary key(s) defined on it. Please check the table definition and create index(s) accordingly.
 - Error number: 1887; Symbol: [WARN_NAMED_PIPE_ACCESS_EVERYONE](#); SQLSTATE: HY000
Message: Setting named_pipe_full_access_group='%s' is insecure. Consider using a Windows group with fewer members.
 - Error number: 3000; Symbol: [ER_FILE_CORRUPT](#); SQLSTATE: HY000
Message: File %s is corrupted
 - Error number: 3001; Symbol: [ER_ERROR_ON_SOURCE](#); SQLSTATE: HY000
Message: Query partially completed on the source (error on source: %d) and was aborted. There is a chance that your source is inconsistent at this point. If you are sure that your source is ok, run this query manually on the replica and then restart the replica with SET GLOBAL SQL_REPLICA_SKIP_COUNTER=1; START REPLICA;. Query:'%s'
 - Error number: 3003; Symbol: [ER_STORAGE_ENGINE_NOT_LOADED](#); SQLSTATE: HY000
Message: Storage engine for table '%s'.'%s' is not loaded.
 - Error number: 3004; Symbol: [ER_GET_STACKED_DA_WITHOUT_ACTIVE_HANDLER](#); SQLSTATE: 0Z002
Message: GET STACKED DIAGNOSTICS when handler not active
 - Error number: 3005; Symbol: [ER_WARN_LEGACY_SYNTAX_CONVERTED](#); SQLSTATE: HY000
Message: %s is no longer supported. The statement was converted to %s.
 - Error number: 3006; Symbol: [ER_BINLOG_UNSAFE_FULLTEXT_PLUGIN](#); SQLSTATE: HY000
Message: Statement is unsafe because it uses a fulltext parser plugin which may not return the same value on the replica.
 - Error number: 3007; Symbol: [ER_CANNOT_DISCARD_TEMPORARY_TABLE](#); SQLSTATE: HY000

Message: Cannot DISCARD/IMPORT tablespace associated with temporary table

- Error number: 3008; Symbol: ER_FK_DEPTH_EXCEEDED; SQLSTATE: HY000

Message: Foreign key cascade delete/update exceeds max depth of %d.

- Error number: 3009; Symbol: ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V2; SQLSTATE: HY000

Message: The column count of %s.%s is wrong. Expected %d, found %d. Created with MySQL %d, now running %d. Please perform the MySQL upgrade procedure.

- Error number: 3010; Symbol: ER_WARN_TRIGGER_DOESNT_HAVE_CREATED; SQLSTATE: HY000

Message: Trigger %s.%s.%s does not have CREATED attribute.

- Error number: 3011; Symbol: ER_REFERENCED_TRG_DOES_NOT_EXIST; SQLSTATE: HY000

Message: Referenced trigger '%s' for the given action time and event type does not exist.

- Error number: 3012; Symbol: ER_EXPLAIN_NOT_SUPPORTED; SQLSTATE: HY000

Message: EXPLAIN FOR CONNECTION command is supported only for SELECT/UPDATE/INSERT/DELETE/REPLACE

- Error number: 3013; Symbol: ER_INVALID_FIELD_SIZE; SQLSTATE: HY000

Message: Invalid size for column '%s'.

- Error number: 3014; Symbol: ER_MISSING_HA_CREATE_OPTION; SQLSTATE: HY000

Message: Table storage engine '%s' found required create option missing

- Error number: 3015; Symbol: ER_ENGINE_OUT_OF_MEMORY; SQLSTATE: HY000

Message: Out of memory in storage engine '%s'.

- Error number: 3016; Symbol: ER_PASSWORD_EXPIRE_ANONYMOUS_USER; SQLSTATE: HY000

Message: The password for anonymous user cannot be expired.

- Error number: 3017; Symbol: ER_REPLICA_SQL_THREAD_MUST_STOP; SQLSTATE: HY000

Message: This operation cannot be performed with a running replica sql thread; run STOP REPLICA SQL_THREAD first

- Error number: 3018; Symbol: ER_NO_FT_MATERIALIZED_SUBQUERY; SQLSTATE: HY000

Message: Cannot create FULLTEXT index on materialized subquery

- Error number: 3019; Symbol: ER_INNODB_UNDO_LOG_FULL; SQLSTATE: HY000

Message: Undo Log error: %s

- Error number: 3020; Symbol: ER_INVALID_ARGUMENT_FOR_LOGARITHM; SQLSTATE: 2201E

Message: Invalid argument for logarithm

- Error number: 3021; Symbol: ER_REPLICA_CHANNEL_IO_THREAD_MUST_STOP; SQLSTATE: HY000

Message: This operation cannot be performed with a running replica io thread; run STOP REPLICATION IO_THREAD FOR CHANNEL '%s' first.

- Error number: 3022; Symbol: ER_WARN_OPEN_TEMP_TABLES_MUST_BE_ZERO; SQLSTATE: HY000

Message: This operation may not be safe when the replica has temporary tables. The tables will be kept open until the server restarts or until the tables are deleted by any replicated DROP statement. Suggest to wait until replica_open_temp_tables = 0.

- Error number: 3023; Symbol: ER_WARN_ONLY_SOURCE_LOG_FILE_NO_POS; SQLSTATE: HY000

Message: CHANGE REPLICATION SOURCE TO with a SOURCE_LOG_FILE clause but no SOURCE_LOG_POS clause may not be safe. The old position value may not be valid for the new binary log file.

- Error number: 3024; Symbol: ER_QUERY_TIMEOUT; SQLSTATE: HY000

Message: Query execution was interrupted, maximum statement execution time exceeded

- Error number: 3025; Symbol: ER_NON_RO_SELECT_DISABLE_TIMER; SQLSTATE: HY000

Message: Select is not a read only statement, disabling timer

- Error number: 3026; Symbol: ER_DUP_LIST_ENTRY; SQLSTATE: HY000

Message: Duplicate entry '%s'.

- Error number: 3028; Symbol: ERAggregate_ORDER_FOR_UNION; SQLSTATE: HY000

Message: Expression #%u of ORDER BY contains aggregate function and applies to a UNION, EXCEPT or INTERSECT

- Error number: 3029; Symbol: ERAggregate_ORDER_NON_AGG_QUERY; SQLSTATE: HY000

Message: Expression #%u of ORDER BY contains aggregate function and applies to the result of a non-aggregated query

- Error number: 3030; Symbol: ER_REPLICA_WORKER_STOPPED_PREVIOUS_THD_ERROR; SQLSTATE: HY000

Message: Replica worker has stopped after at least one previous worker encountered an error when replica-preserve-commit-order was enabled. To preserve commit order, the last transaction executed by this thread has not been committed. When restarting the replica after fixing any failed threads, you should fix this worker as well.

- Error number: 3031; Symbol: ER_DONT_SUPPORT_REPLICA_PRESERVE_COMMIT_ORDER; SQLSTATE: HY000

Message: replica_preserve_commit_order is not supported %s.

- Error number: 3032; Symbol: ER_SERVER_OFFLINE_MODE; SQLSTATE: HY000

Message: The server is currently in offline mode

- Error number: 3033; Symbol: ER_GIS_DIFFERENT_SRIDS; SQLSTATE: HY000

Message: Binary geometry function %s given two geometries of different srids: %u and %u, which should have been identical.

Geometry values passed as arguments to spatial functions must have the same SRID value.

- Error number: 3034; Symbol: `ER_GIS_UNSUPPORTED_ARGUMENT`; SQLSTATE: `HY000`
Message: Calling geometry function %s with unsupported types of arguments.
A spatial function was called with a combination of argument types that the function does not support.
- Error number: 3035; Symbol: `ER_GIS_UNKNOWN_ERROR`; SQLSTATE: `HY000`
Message: Unknown GIS error occurred in function %s.
- Error number: 3036; Symbol: `ER_GIS_UNKNOWN_EXCEPTION`; SQLSTATE: `HY000`
Message: Unknown exception caught in GIS function %s.
- Error number: 3037; Symbol: `ER_GIS_INVALID_DATA`; SQLSTATE: `22023`
Message: Invalid GIS data provided to function %s.
A spatial function was called with an argument not recognized as a valid geometry value.
- Error number: 3038; Symbol: `ER_BOOST_GEOMETRY_EMPTY_INPUT_EXCEPTION`; SQLSTATE: `HY000`
Message: The geometry has no data in function %s.
- Error number: 3039; Symbol: `ER_BOOST_GEOMETRY_CENTROID_EXCEPTION`; SQLSTATE: `HY000`
Message: Unable to calculate centroid because geometry is empty in function %s.
- Error number: 3040; Symbol: `ER_BOOST_GEOMETRY_OVERLAY_INVALID_INPUT_EXCEPTION`; SQLSTATE: `HY000`
Message: Geometry overlay calculation error: geometry data is invalid in function %s.
- Error number: 3041; Symbol: `ER_BOOST_GEOMETRY_TURN_INFO_EXCEPTION`; SQLSTATE: `HY000`
Message: Geometry turn info calculation error: geometry data is invalid in function %s.
- Error number: 3042; Symbol: `ER_BOOST_GEOMETRY_SELF_INTERSECTION_POINT_EXCEPTION`; SQLSTATE: `HY000`
Message: Analysis procedures of intersection points interrupted unexpectedly in function %s.
- Error number: 3043; Symbol: `ER_BOOST_GEOMETRY_UNKNOWN_EXCEPTION`; SQLSTATE: `HY000`
Message: Unknown exception thrown in function %s.
- Error number: 3044; Symbol: `ER_STD_BAD_ALLOC_ERROR`; SQLSTATE: `HY000`
Message: Memory allocation error: %s in function %s.
- Error number: 3045; Symbol: `ER_STD_DOMAIN_ERROR`; SQLSTATE: `HY000`
Message: Domain error: %s in function %s.
- Error number: 3046; Symbol: `ER_STD_LENGTH_ERROR`; SQLSTATE: `HY000`
Message: Length error: %s in function %s.

-
- Error number: [3047](#); Symbol: [ER_STD_INVALID_ARGUMENT](#); SQLSTATE: [HY000](#)
Message: Invalid argument error: %s in function %s.
 - Error number: [3048](#); Symbol: [ER_STD_OUT_OF_RANGE_ERROR](#); SQLSTATE: [HY000](#)
Message: Out of range error: %s in function %s.
 - Error number: [3049](#); Symbol: [ER_STD_OVERFLOW_ERROR](#); SQLSTATE: [HY000](#)
Message: Overflow error: %s in function %s.
 - Error number: [3050](#); Symbol: [ER_STD_RANGE_ERROR](#); SQLSTATE: [HY000](#)
Message: Range error: %s in function %s.
 - Error number: [3051](#); Symbol: [ER_STD_UNDERFLOW_ERROR](#); SQLSTATE: [HY000](#)
Message: Underflow error: %s in function %s.
 - Error number: [3052](#); Symbol: [ER_STD_LOGIC_ERROR](#); SQLSTATE: [HY000](#)
Message: Logic error: %s in function %s.
 - Error number: [3053](#); Symbol: [ER_STD_RUNTIME_ERROR](#); SQLSTATE: [HY000](#)
Message: Runtime error: %s in function %s.
 - Error number: [3054](#); Symbol: [ER_STD_UNKNOWN_EXCEPTION](#); SQLSTATE: [HY000](#)
Message: Unknown exception: %s in function %s.
 - Error number: [3055](#); Symbol: [ER_GIS_DATA_WRONG_ENDIANNESS](#); SQLSTATE: [HY000](#)
Message: Geometry byte string must be little endian.
 - Error number: [3056](#); Symbol: [ER_CHANGE_SOURCE_PASSWORD_LENGTH](#); SQLSTATE: [HY000](#)
Message: The password provided for the replication user exceeds the maximum length of 32 characters
 - Error number: [3057](#); Symbol: [ER_USER_LOCK_WRONG_NAME](#); SQLSTATE: [42000](#)
Message: Incorrect user-level lock name '%s!'. The name is empty, NULL, or can not be expressed in the current character-set.
 - Error number: [3058](#); Symbol: [ER_USER_LOCK_DEADLOCK](#); SQLSTATE: [HY000](#)
Message: Deadlock found when trying to get user-level lock; try rolling back transaction/releasing locks and restarting lock acquisition.

This error is returned when the metadata locking subsystem detects a deadlock for an attempt to acquire a named lock with [GET_LOCK](#).
 - Error number: [3059](#); Symbol: [ER_REPLACE_INACCESSIBLE_ROWS](#); SQLSTATE: [HY000](#)
Message: REPLACE cannot be executed as it requires deleting rows that are not in the view
 - Error number: [3060](#); Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_GIS](#); SQLSTATE: [HY000](#)

Message: Do not support online operation on table with GIS index

- Error number: 3061; Symbol: ER_ILLEGAL_USER_VAR; SQLSTATE: 42000

Message: User variable name '%s' is illegal

- Error number: 3062; Symbol: ER_GTID_MODE_OFF; SQLSTATE: HY000

Message: Cannot %s when GTID_MODE = OFF.

- Error number: 3064; Symbol: ER_INCORRECT_TYPE; SQLSTATE: HY000

Message: Incorrect type for argument %s in function %s.

- Error number: 3065; Symbol: ER_FIELD_IN_ORDER_NOT_SELECT; SQLSTATE: HY000

Message: Expression #%u of ORDER BY clause is not in SELECT list, references column '%s' which is not in SELECT list; this is incompatible with %s

- Error number: 3066; Symbol: ER_AGGREGATE_IN_ORDER_NOT_SELECT; SQLSTATE: HY000

Message: Expression #%u of ORDER BY clause is not in SELECT list, contains aggregate function; this is incompatible with %s

- Error number: 3067; Symbol: ER_INVALID_RPL_WILD_TABLE_FILTER_PATTERN; SQLSTATE: HY000

Message: Supplied filter list contains a value which is not in the required format 'db_pattern.table_pattern'

- Error number: 3068; Symbol: ER_NET_OK_PACKET_TOO_LARGE; SQLSTATE: 08S01

Message: OK packet too large

- Error number: 3069; Symbol: ER_INVALID_JSON_DATA; SQLSTATE: HY000

Message: Invalid JSON data provided to function %s: %s

- Error number: 3070; Symbol: ER_INVALID_GEOJSON_MISSING_MEMBER; SQLSTATE: HY000

Message: Invalid GeoJSON data provided to function %s: Missing required member '%s'

- Error number: 3071; Symbol: ER_INVALID_GEOJSON_WRONG_TYPE; SQLSTATE: HY000

Message: Invalid GeoJSON data provided to function %s: Member '%s' must be of type '%s'

- Error number: 3072; Symbol: ER_INVALID_GEOJSON_UNSPECIFIED; SQLSTATE: HY000

Message: Invalid GeoJSON data provided to function %s

- Error number: 3073; Symbol: ER_DIMENSION_UNSUPPORTED; SQLSTATE: HY000

Message: Unsupported number of coordinate dimensions in function %s: Found %u, expected %u

- Error number: 3074; Symbol: ER_REPLICA_CHANNEL_DOES_NOT_EXIST; SQLSTATE: HY000

Message: Replica channel '%s' does not exist.

- Error number: 3076; Symbol: ER_REPLICA_CHANNEL_NAME_INVALID_OR_TOO_LONG; SQLSTATE: HY000

Message: Couldn't create channel: Channel name is either invalid or too long.

- Error number: 3077; Symbol: [ER_REPLICA_NEW_CHANNEL_WRONG_REPOSITORY](#); SQLSTATE: HY000

Message: To have multiple channels, repository cannot be of type FILE; Please check the repository configuration and convert them to TABLE.

- Error number: 3079; Symbol: [ER_REPLICA_MULTIPLE_CHANNELS_CMD](#); SQLSTATE: HY000

Message: Multiple channels exist on the replica. Please provide channel name as an argument.

- Error number: 3080; Symbol: [ER_REPLICA_MAX_CHANNELS_EXCEEDED](#); SQLSTATE: HY000

Message: Maximum number of replication channels allowed exceeded.

- Error number: 3081; Symbol: [ER_REPLICA_CHANNEL_MUST_STOP](#); SQLSTATE: HY000

Message: This operation cannot be performed with running replication threads; run STOP REPLICA FOR CHANNEL '%s' first

- Error number: 3082; Symbol: [ER_REPLICA_CHANNEL_NOT_RUNNING](#); SQLSTATE: HY000

Message: This operation requires running replication threads; configure replica and run START REPLICA FOR CHANNEL '%s'

- Error number: 3083; Symbol: [ER_REPLICA_CHANNEL_WAS_RUNNING](#); SQLSTATE: HY000

Message: Replication thread(s) for channel '%s' are already running.

- Error number: 3084; Symbol: [ER_REPLICA_CHANNEL_WAS_NOT_RUNNING](#); SQLSTATE: HY000

Message: Replication thread(s) for channel '%s' are already stopped.

- Error number: 3085; Symbol: [ER_REPLICA_CHANNEL_SQL_THREAD_MUST_STOP](#); SQLSTATE: HY000

Message: This operation cannot be performed with a running replica sql thread; run STOP REPLICA SQL_THREAD FOR CHANNEL '%s' first.

- Error number: 3086; Symbol: [ER_REPLICA_CHANNEL_SQL_SKIP_COUNTER](#); SQLSTATE: HY000

Message: When sql_replica_skip_counter > 0, it is not allowed to start more than one SQL thread by using 'START REPLICA [SQL_THREAD]'. Value of sql_replica_skip_counter can only be used by one SQL thread at a time. Please use 'START REPLICA [SQL_THREAD] FOR CHANNEL' to start the SQL thread which will use the value of sql_replica_skip_counter.

- Error number: 3087; Symbol: [ER_WRONG_FIELD_WITH_GROUP_V2](#); SQLSTATE: HY000

Message: Expression #%u of %s is not in GROUP BY clause and contains nonaggregated column '%s' which is not functionally dependent on columns in GROUP BY clause; this is incompatible with sql_mode=only_full_group_by

- Error number: 3088; Symbol: [ER_MIX_OF_GROUP_FUNC_AND_FIELDS_V2](#); SQLSTATE: HY000

Message: In aggregated query without GROUP BY, expression #%u of %s contains nonaggregated column '%s'; this is incompatible with sql_mode=only_full_group_by

- Error number: 3089; Symbol: [ER_WARN_DEPRECATED_SYSVAR_UPDATE](#); SQLSTATE: HY000

Message: Updating '%s' is deprecated. It will be made read-only in a future release.

- Error number: 3090; Symbol: `ER_WARN_DEPRECATED_SQLMODE`; SQLSTATE: `HY000`

Message: Changing sql mode '%s' is deprecated. It will be removed in a future release.

- Error number: 3091; Symbol: `ER_CANNOT_LOG_PARTIAL_DROP_DATABASE_WITH_GTID`; SQLSTATE: `HY000`

Message: DROP DATABASE failed; some tables may have been dropped but the database directory remains. The GTID has not been added to GTID_EXECUTED and the statement was not written to the binary log. Fix this as follows: (1) remove all files from the database directory %s; (2) SET GTID_NEXT='%s'; (3) DROP DATABASE ` %s`.

- Error number: 3092; Symbol: `ER_GROUP_REPLICATION_CONFIGURATION`; SQLSTATE: `HY000`

Message: The server is not configured properly to be an active member of the group. Please see more details on error log.

- Error number: 3093; Symbol: `ER_GROUP_REPLICATION_RUNNING`; SQLSTATE: `HY000`

Message: The START GROUP_REPLICATION command failed since the group is already running.

- Error number: 3094; Symbol: `ER_GROUP_REPLICATION_APPLIER_INIT_ERROR`; SQLSTATE: `HY000`

Message: The START GROUP_REPLICATION command failed as the applier module failed to start.

- Error number: 3095; Symbol: `ER_GROUP_REPLICATION_STOP_APPLIER_THREAD_TIMEOUT`; SQLSTATE: `HY000`

Message: The STOP GROUP_REPLICATION command execution is incomplete: The applier thread got the stop signal while it was busy. The applier thread will stop once the current task is complete.

- Error number: 3096; Symbol: `ER_GROUP_REPLICATION_COMMUNICATION_LAYER_SESSION_ERROR`; SQLSTATE: `HY000`

Message: The START GROUP_REPLICATION command failed as there was an error when initializing the group communication layer.

- Error number: 3097; Symbol: `ER_GROUP_REPLICATION_COMMUNICATION_LAYER_JOIN_ERROR`; SQLSTATE: `HY000`

Message: The START GROUP_REPLICATION command failed as there was an error when joining the communication group.

- Error number: 3098; Symbol: `ER_BEFORE_DML_VALIDATION_ERROR`; SQLSTATE: `HY000`

Message: The table does not comply with the requirements by an external plugin.

- Error number: 3099; Symbol: `ER_PREVENTS_VARIABLE_WITHOUT_RBR`; SQLSTATE: `HY000`

Message: Cannot change the value of variable %s without binary log format as ROW.

- Error number: 3100; Symbol: `ER_RUN_HOOK_ERROR`; SQLSTATE: `HY000`

Message: Error on observer while running replication hook '%s'.

- Error number: 3101; Symbol: `ER_TRANSACTION_ROLLBACK_DURING_COMMIT`; SQLSTATE: `40000`

Message: Plugin instructed the server to rollback the current transaction.

When using Group Replication, this means that a transaction failed the group certification process, due to one or more members detecting a potential conflict, and was thus rolled back. See [Group Replication](#).

- Error number: 3102; Symbol: [ER_GENERATED_COLUMN_FUNCTION_IS_NOT_ALLOWED](#); SQLSTATE: [HY000](#)

Message: Expression of generated column '%s' contains a disallowed function.

- Error number: 3103; Symbol: [ER_UNSUPPORTED_ALTER_INPLACE_ON_VIRTUAL_COLUMN](#); SQLSTATE: [HY000](#)

Message: INPLACE ADD or DROP of virtual columns cannot be combined with other ALTER TABLE actions

- Error number: 3104; Symbol: [ER_WRONG_FK_OPTION_FOR_GENERATED_COLUMN](#); SQLSTATE: [HY000](#)

Message: Cannot define foreign key with %s clause on a generated column.

- Error number: 3105; Symbol: [ER_NON_DEFAULT_VALUE_FOR_GENERATED_COLUMN](#); SQLSTATE: [HY000](#)

Message: The value specified for generated column '%s' in table '%s' is not allowed.

- Error number: 3106; Symbol: [ER_UNSUPPORTED_ACTION_ON_GENERATED_COLUMN](#); SQLSTATE: [HY000](#)

Message: '%s' is not supported for generated columns.

- Error number: 3107; Symbol: [ER_GENERATED_COLUMN_NON_PRIOR](#); SQLSTATE: [HY000](#)

Message: Generated column can refer only to generated columns defined prior to it.

To address this issue, change the table definition to define each generated column later than any generated columns to which it refers.

- Error number: 3108; Symbol: [ER_DEPENDENT_BY_GENERATED_COLUMN](#); SQLSTATE: [HY000](#)

Message: Column '%s' has a generated column dependency.

You cannot drop or rename a generated column if another column refers to it. You must either drop those columns as well, or redefine them not to refer to the generated column.

- Error number: 3109; Symbol: [ER_GENERATED_COLUMN_REF_AUTO_INC](#); SQLSTATE: [HY000](#)

Message: Generated column '%s' cannot refer to auto-increment column.

- Error number: 3110; Symbol: [ER_FEATURE_NOT_AVAILABLE](#); SQLSTATE: [HY000](#)

Message: The '%s' feature is not available; you need to remove '%s' or use MySQL built with '%s'

- Error number: 3111; Symbol: [ER_CANT_SET_GTID_MODE](#); SQLSTATE: [HY000](#)

Message: SET @@GLOBAL.GTID_MODE = %s is not allowed because %s.

- Error number: 3112; Symbol: [ER_CANT_USE_AUTO_POSITION_WITH_GTID_MODE_OFF](#); SQLSTATE: [HY000](#)

Message: The replication receiver thread%s cannot start in AUTO_POSITION mode: this server uses @@GLOBAL.GTID_MODE = OFF.

- Error number: 3116; Symbol: ER_CANT_ENFORCE_GTID_CONSISTENCY_WITH_ONGOING_GTID_VIOLATING_TX; SQLSTATE: HY000

Message: Cannot set ENFORCE_GTID_CONSISTENCY = ON because there are ongoing transactions that violate GTID consistency.

ER_CANT_SET_ENFORCE_GTID_CONSISTENCY_ON_WITH_ONGOING_GTID_VIOLATING_TRANSACTIONS was renamed to ER_CANT_ENFORCE_GTID_CONSISTENCY_WITH_ONGOING_GTID_VIOLATING_TX.

- Error number: 3117; Symbol: ER_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING_GTID_VIOLATING_TX; SQLSTATE: HY000

Message: There are ongoing transactions that violate GTID consistency.

ER_SET_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING_GTID_VIOLATING_TRANSACTIONS was renamed to ER_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING_GTID_VIOLATING_TX.

- Error number: 3118; Symbol: ER_ACCOUNT_HAS_BEEN_LOCKED; SQLSTATE: HY000

Message: Access denied for user '%s'@'%s'. Account is locked.

The account was locked with CREATE USER ... ACCOUNT LOCK or ALTER USER ... ACCOUNT LOCK. An administrator can unlock it with ALTER USER ... ACCOUNT UNLOCK.

- Error number: 3119; Symbol: ER_WRONG_TABLESPACE_NAME; SQLSTATE: 42000

Message: Incorrect tablespace name `%s`

- Error number: 3120; Symbol: ER_TABLESPACE_IS_NOT_EMPTY; SQLSTATE: HY000

Message: Tablespace `%s` is not empty.

- Error number: 3121; Symbol: ER_WRONG_FILE_NAME; SQLSTATE: HY000

Message: Incorrect File Name '%s'.

- Error number: 3122; Symbol: ER_BOOST_GEOMETRY_INCONSISTENT_TURNS_EXCEPTION; SQLSTATE: HY000

Message: Inconsistent intersection points.

- Error number: 3123; Symbol: ER_WARN_OPTIMIZER_HINT_SYNTAX_ERROR; SQLSTATE: HY000

Message: Optimizer hint syntax error

- Error number: 3124; Symbol: ER_WARN_BAD_MAX_EXECUTION_TIME; SQLSTATE: HY000

Message: Unsupported MAX_EXECUTION_TIME

- Error number: 3125; Symbol: ER_WARN_UNSUPPORTED_MAX_EXECUTION_TIME; SQLSTATE: HY000

Message: MAX_EXECUTION_TIME hint is supported by top-level standalone SELECT statements only

The `MAX_EXECUTION_TIME` optimizer hint is supported only for `SELECT` statements.

- Error number: 3126; Symbol: `ER_WARN_CONFLICTING_HINT`; SQLSTATE: `HY000`

Message: Hint %s is ignored as conflicting/duplicated

- Error number: 3127; Symbol: `ER_WARN_UNKNOWN_QB_NAME`; SQLSTATE: `HY000`

Message: Query block name %s is not found for %s hint

- Error number: 3128; Symbol: `ER_UNRESOLVED_HINT_NAME`; SQLSTATE: `HY000`

Message: Unresolved name %s for %s hint

- Error number: 3129; Symbol: `ER_WARN_ON_MODIFYING_GTID_EXECUTED_TABLE`; SQLSTATE: `HY000`

Message: Please do not modify the %s table. This is a mysql internal system table to store GTIDs for committed transactions. Modifying it can lead to an inconsistent GTID state.

- Error number: 3130; Symbol: `ER_PLUGGABLE_PROTOCOL_COMMAND_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: Command not supported by pluggable protocols

- Error number: 3131; Symbol: `ER_LOCKING_SERVICE_WRONG_NAME`; SQLSTATE: `42000`

Message: Incorrect locking service lock name '%s'.

A locking service name was specified as `NULL`, the empty string, or a string longer than 64 characters. Namespace and lock names must be non-`NULL`, nonempty, and no more than 64 characters long.

- Error number: 3132; Symbol: `ER_LOCKING_SERVICE_DEADLOCK`; SQLSTATE: `HY000`

Message: Deadlock found when trying to get locking service lock; try releasing locks and restarting lock acquisition.

- Error number: 3133; Symbol: `ER_LOCKING_SERVICE_TIMEOUT`; SQLSTATE: `HY000`

Message: Service lock wait timeout exceeded.

- Error number: 3134; Symbol: `ER_GIS_MAX_POINTS_IN_GEOMETRY_OVERFLOWED`; SQLSTATE: `HY000`

Message: Parameter %s exceeds the maximum number of points in a geometry (%lu) in function %s.

- Error number: 3135; Symbol: `ER_SQL_MODE_MERGED`; SQLSTATE: `HY000`

Message: 'NO_ZERO_DATE', 'NO_ZERO_IN_DATE' and 'ERROR_FOR_DIVISION_BY_ZERO' sql modes should be used with strict mode. They will be merged with strict mode in a future release.

- Error number: 3136; Symbol: `ER_VTOKEN_PLUGIN_TOKEN_MISMATCH`; SQLSTATE: `HY000`

Message: Version token mismatch for %.*s. Correct value %.*s

The client has set its `version_tokens_session` system variable to the list of tokens it requires the server to match, but the server token list has at least one matching token name that has a value different from what the client requires. See [Version Tokens](#).

-
- Error number: [3137](#); Symbol: [ER_VTOKEN_PLUGIN_TOKEN_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: Version token %.*s not found.
The client has set its [version_tokens_session](#) system variable to the list of tokens it requires the server to match, but the server token list is missing at least one of those tokens. See [Version Tokens](#).
 - Error number: [3138](#); Symbol: [ER_CANT_SET_VARIABLE_WHEN_OWNING_GTID](#); SQLSTATE: [HY000](#)
Message: Variable %s cannot be changed by a client that owns a GTID. The client owns %s. Ownership is released on COMMIT or ROLLBACK.
 - Error number: [3139](#); Symbol: [ER_REPLICA_CHANNEL_OPERATION_NOT_ALLOWED](#); SQLSTATE: [HY000](#)
Message: %s cannot be performed on channel '%s'.
 - Error number: [3140](#); Symbol: [ER_INVALID_JSON_TEXT](#); SQLSTATE: [22032](#)
Message: Invalid JSON text: "%s" at position %u in value for column '%s'.
 - Error number: [3141](#); Symbol: [ER_INVALID_JSON_TEXT_IN_PARAM](#); SQLSTATE: [22032](#)
Message: Invalid JSON text in argument %u to function %s: "%s" at position %u.%s
 - Error number: [3142](#); Symbol: [ER_INVALID_JSON_BINARY_DATA](#); SQLSTATE: [HY000](#)
Message: The JSON binary value contains invalid data.
 - Error number: [3143](#); Symbol: [ER_INVALID_JSON_PATH](#); SQLSTATE: [42000](#)
Message: Invalid JSON path expression. The error is around character position %u.%s
 - Error number: [3144](#); Symbol: [ER_INVALID_JSON_CHARSET](#); SQLSTATE: [22032](#)
Message: Cannot create a JSON value from a string with CHARACTER SET '%s'.
 - Error number: [3145](#); Symbol: [ER_INVALID_JSON_CHARSET_IN_FUNCTION](#); SQLSTATE: [22032](#)
Message: Invalid JSON character data provided to function %s: '%s'; utf8 is required.
 - Error number: [3146](#); Symbol: [ER_INVALID_TYPE_FOR_JSON](#); SQLSTATE: [22032](#)
Message: Invalid data type for JSON data in argument %u to function %s; a JSON string or JSON type is required.
 - Error number: [3147](#); Symbol: [ER_INVALID_CAST_TO_JSON](#); SQLSTATE: [22032](#)
Message: Cannot CAST value to JSON.
 - Error number: [3148](#); Symbol: [ER_INVALID_JSON_PATH_CHARSET](#); SQLSTATE: [42000](#)
Message: A path expression must be encoded in the utf8 character set. The path expression '%s' is encoded in character set '%s'.
 - Error number: [3149](#); Symbol: [ER_INVALID_JSON_PATH_WILDCARD](#); SQLSTATE: [42000](#)
Message: In this situation, path expressions may not contain the * and ** tokens or an array range.
 - Error number: [3150](#); Symbol: [ER_JSON_VALUE_TOO_BIG](#); SQLSTATE: [22032](#)

Message: The JSON value is too big to be stored in a JSON column.

- Error number: 3151; Symbol: [ER_JSON_KEY_TOO_BIG](#); SQLSTATE: 22032

Message: The JSON object contains a key name that is too long.

- Error number: 3152; Symbol: [ER_JSON_USED_AS_KEY](#); SQLSTATE: 42000

Message: JSON column '%s' supports indexing only via generated columns on a specified JSON path.

- Error number: 3153; Symbol: [ER_JSON_VACUOUS_PATH](#); SQLSTATE: 42000

Message: The path expression '\$' is not allowed in this context.

- Error number: 3154; Symbol: [ER_JSON_BAD_ONE_OR_ALL_ARG](#); SQLSTATE: 42000

Message: The oneOrAll argument to %s may take these values: 'one' or 'all'.

- Error number: 3155; Symbol: [ER_NUMERIC_JSON_VALUE_OUT_OF_RANGE](#); SQLSTATE: 22003

Message: Out of range JSON value for CAST to %s%s from column %s at row %ld

- Error number: 3156; Symbol: [ER_INVALID_JSON_VALUE_FOR_CAST](#); SQLSTATE: 22018

Message: Invalid JSON value for CAST to %s%s from column %s at row %ld

- Error number: 3157; Symbol: [ER_JSON_DOCUMENT_TOO_DEEP](#); SQLSTATE: 22032

Message: The JSON document exceeds the maximum depth.

- Error number: 3158; Symbol: [ER_JSON_DOCUMENT_NULL_KEY](#); SQLSTATE: 22032

Message: JSON documents may not contain NULL member names.

- Error number: 3159; Symbol: [ER_SECURE_TRANSPORT_REQUIRED](#); SQLSTATE: HY000

Message: Connections using insecure transport are prohibited while --require_secure_transport=ON.

With the [require_secure_transport](#) system variable, clients can connect only using secure transports. Qualifying connections are those using SSL, a Unix socket file, or shared memory.

- Error number: 3160; Symbol: [ER_NO_SECURE_TRANSPORTS_CONFIGURED](#); SQLSTATE: HY000

Message: No secure transports (SSL or Shared Memory) are configured, unable to set --require_secure_transport=ON.

The [require_secure_transport](#) system variable cannot be enabled if the server does not support at least one secure transport. Configure the server with the required SSL keys/certificates to enable SSL connections, or enable the [shared_memory](#) system variable to enable shared-memory connections.

- Error number: 3161; Symbol: [ER_DISABLED_STORAGE_ENGINE](#); SQLSTATE: HY000

Message: Storage engine %s is disabled (Table creation is disallowed).

An attempt was made to create a table or tablespace using a storage engine listed in the value of the [disabled_storage_engines](#) system variable, or to change an existing table or tablespace to such an engine. Choose a different storage engine.

- Error number: 3162; Symbol: [ER_USER_DOES_NOT_EXIST](#); SQLSTATE: HY000

Message: Authorization ID %s does not exist.

- Error number: 3163; Symbol: ER_USER_ALREADY_EXISTS; SQLSTATE: HY000

Message: Authorization ID %s already exists.

- Error number: 3164; Symbol: ER_AUDIT_API_ABORT; SQLSTATE: HY000

Message: Aborted by Audit API ('%s';%d).

This error indicates that an audit plugin terminated execution of an event. The message typically indicates the event subclass name and a numeric status value.

- Error number: 3165; Symbol: ER_INVALID_JSON_PATH_ARRAY_CELL; SQLSTATE: 42000

Message: A path expression is not a path to a cell in an array.

- Error number: 3166; Symbol: ER_BUFPOOL_RESIZE_INPROGRESS; SQLSTATE: HY000

Message: Another buffer pool resize is already in progress.

- Error number: 3167; Symbol: ER_FEATURE_DISABLED_SEE_DOC; SQLSTATE: HY000

Message: The '%s' feature is disabled; see the documentation for '%s'

- Error number: 3168; Symbol: ER_SERVER_ISNT_AVAILABLE; SQLSTATE: HY000

Message: Server isn't available

- Error number: 3169; Symbol: ER_SESSION_WAS_KILLED; SQLSTATE: HY000

Message: Session was killed

- Error number: 3170; Symbol: ER_CAPACITY_EXCEEDED; SQLSTATE: HY000

Message: Memory capacity of %llu bytes for '%s' exceeded. %s

- Error number: 3171; Symbol: ER_CAPACITY_EXCEEDED_IN_RANGE_OPTIMIZER; SQLSTATE: HY000

Message: Range optimization was not done for this query.

- Error number: 3173; Symbol: ER_CANT_WAIT_FOR_EXECUTED_GTID_SET_WHILE_OWNING_A_GTID; SQLSTATE: HY000

Message: The client holds ownership of the GTID %s. Therefore, WAIT_FOR_EXECUTED_GTID_SET cannot wait for this GTID.

- Error number: 3174; Symbol: ER_CANNOT_ADD_FOREIGN_BASE_COL_VIRTUAL; SQLSTATE: HY000

Message: Cannot add foreign key on the base column of indexed virtual column.

- Error number: 3175; Symbol: ER_CANNOT_CREATE_VIRTUAL_INDEX_CONSTRAINT; SQLSTATE: HY000

Message: Cannot create index on virtual column whose base column has foreign constraint.

- Error number: 3176; Symbol: ER_ERROR_ON_MODIFYING_GTID_EXECUTED_TABLE; SQLSTATE: HY000

Message: Please do not modify the %s table with an XA transaction. This is an internal system table used to store GTIDs for committed transactions. Although modifying it can lead to an inconsistent GTID state, if necessary you can modify it with a non-XA transaction.

- Error number: 3177; Symbol: `ER_LOCK_REFUSED_BY_ENGINE`; SQLSTATE: `HY000`

Message: Lock acquisition refused by storage engine.

- Error number: 3178; Symbol: `ER_UNSUPPORTED_ALTER_ONLINE_ON_VIRTUAL_COLUMN`; SQLSTATE: `HY000`

Message: ADD COLUMN col...VIRTUAL, ADD INDEX(col)

- Error number: 3179; Symbol: `ER_MASTER_KEY_ROTATION_NOT_SUPPORTED_BY_SE`; SQLSTATE: `HY000`

Message: Master key rotation is not supported by storage engine.

- Error number: 3181; Symbol: `ER_MASTER_KEY_ROTATION_BINLOG_FAILED`; SQLSTATE: `HY000`

Message: Write to binlog failed. However, master key rotation has been completed successfully.

- Error number: 3182; Symbol: `ER_MASTER_KEY_ROTATION_SE_UNAVAILABLE`; SQLSTATE: `HY000`

Message: Storage engine is not available.

- Error number: 3183; Symbol: `ER_TABLESPACE_CANNOT_ENCRYPT`; SQLSTATE: `HY000`

Message: This tablespace can't be encrypted.

- Error number: 3184; Symbol: `ER_INVALID_ENCRYPTION_OPTION`; SQLSTATE: `HY000`

Message: Invalid encryption option.

- Error number: 3185; Symbol: `ER_CANNOT_FIND_KEY_IN_KEYRING`; SQLSTATE: `HY000`

Message: Can't find master key from keyring, please check in the server log if a keyring is loaded and initialized successfully.

- Error number: 3186; Symbol: `ER_CAPACITY_EXCEEDED_IN_PARSER`; SQLSTATE: `HY000`

Message: Parser bailed out for this query.

- Error number: 3187; Symbol: `ER_UNSUPPORTED_ALTER_ENCRYPTION_INPLACE`; SQLSTATE: `HY000`

Message: Cannot alter encryption attribute by inplace algorithm.

- Error number: 3188; Symbol: `ER_KEYRING_UDF_KEYRING_SERVICE_ERROR`; SQLSTATE: `HY000`

Message: Function '%s' failed because underlying keyring service returned an error. Please check if a keyring is installed and that provided arguments are valid for the keyring you are using.

- Error number: 3189; Symbol: `ER_USER_COLUMN_OLD_LENGTH`; SQLSTATE: `HY000`

Message: It seems that your db schema is old. The %s column is 77 characters long and should be 93 characters long. Please perform the MySQL upgrade procedure.

- Error number: 3190; Symbol: `ER_CANT_RESET_SOURCE`; SQLSTATE: `HY000`

Message: RESET BINARY LOGS AND GTIDS is not allowed because %s.

- Error number: 3191; Symbol: `ER_GROUP_REPLICATION_MAX_GROUP_SIZE`; SQLSTATE: HY000

Message: The START GROUP_REPLICATION command failed since the group already has 9 members.

- Error number: 3192; Symbol: `ER_CANNOT_ADD_FOREIGN_BASE_COL_STORED`; SQLSTATE: HY000

Message: Cannot add foreign key on the base column of stored column.

- Error number: 3193; Symbol: `ER_TABLE_REFERENCED`; SQLSTATE: HY000

Message: Cannot complete the operation because table is referenced by another connection.

- Error number: 3197; Symbol: `ER_XA_RETRY`; SQLSTATE: HY000

Message: The resource manager is not able to commit the transaction branch at this time. Please retry later.

- Error number: 3198; Symbol: `ER_KEYRING_AWS_UDF_AWS_KMS_ERROR`; SQLSTATE: HY000

Message: Function %s failed due to: %s.

- Error number: 3199; Symbol: `ER_BINLOG_UNSAFE_XA`; SQLSTATE: HY000

Message: Statement is unsafe because it is being used inside a XA transaction. Concurrent XA transactions may deadlock on replicas when replicated using statements.

- Error number: 3200; Symbol: `ER_UDF_ERROR`; SQLSTATE: HY000

Message: %s UDF failed; %s

- Error number: 3201; Symbol: `ER_KEYRING_MIGRATION_FAILURE`; SQLSTATE: HY000

Message: Can not perform keyring migration : %s

- Error number: 3202; Symbol: `ER_KEYRING_ACCESS_DENIED_ERROR`; SQLSTATE: 42000

Message: Access denied; you need %s privileges for this operation

- Error number: 3203; Symbol: `ER_KEYRING_MIGRATION_STATUS`; SQLSTATE: HY000

Message: Keyring migration %s.

- Error number: 3218; Symbol: `ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH_ARG_VALUE`; SQLSTATE: HY000

Message: Invalid "max_array_length" argument value.

- Error number: 3231; Symbol: `ER_WRITE_SET_EXCEEDS_LIMIT`; SQLSTATE: HY000

Message: The size of writeset data for the current transaction exceeds a limit imposed by an external component. If using Group Replication check 'group_replication_transaction_size_limit'.

- Error number: 3235; Symbol: `ER_AES_INVALID_KDF_NAME`; SQLSTATE: HY000

Message: KDF method name is not valid. Please use hkdf or pbkdf2_hmac method name

-
- Error number: [3236](#); Symbol: [ER_AES_INVALID_KDF_ITERATIONS](#); SQLSTATE: [HY000](#)
Message: For KDF method pbkdf2_hmac iterations value less than 1000 or more than 65535 is not allowed due to security reasons. Please provide iterations >= 1000 and iterations < 65535
 - Error number: [3237](#); Symbol: [WARN_AES_KEY_SIZE](#); SQLSTATE: [HY000](#)
Message: AES key size should be %d bytes length or secure KDF methods hkdf or pbkdf2_hmac should be used, please provide exact AES key size or use KDF methods for better security.
 - Error number: [3238](#); Symbol: [ER_AES_INVALID_KDF_OPTION_SIZE](#); SQLSTATE: [HY000](#)
Message: KDF option size is invalid, please provide valid size < %d bytes and not NULL
 - Error number: [3500](#); Symbol: [ER_UNSUPPORT_COMPRESSED_TEMPORARY_TABLE](#); SQLSTATE: [HY000](#)
Message: CREATE TEMPORARY TABLE is not allowed with ROW_FORMAT=COMPRESSED or KEY_BLOCK_SIZE.
 - Error number: [3501](#); Symbol: [ER_ACL_OPERATION_FAILED](#); SQLSTATE: [HY000](#)
Message: The ACL operation failed due to the following error from SE: errcode %d - %s
 - Error number: [3502](#); Symbol: [ER_UNSUPPORTED_INDEX_ALGORITHM](#); SQLSTATE: [HY000](#)
Message: This storage engine does not support the %s index algorithm, storage engine default was used instead.
 - Error number: [3503](#); Symbol: [ER_NO_SUCH_DB](#); SQLSTATE: [42Y07](#)
Message: Database '%s' doesn't exist
 - Error number: [3504](#); Symbol: [ER_TOO_BIG_ENUM](#); SQLSTATE: [HY000](#)
Message: Too many enumeration values for column %s.
 - Error number: [3505](#); Symbol: [ER_TOO_LONG_SET_ENUM_VALUE](#); SQLSTATE: [HY000](#)
Message: Too long enumeration/set value for column %s.
 - Error number: [3506](#); Symbol: [ER_INVALID_DD_OBJECT](#); SQLSTATE: [HY000](#)
Message: %s dictionary object is invalid. (%s)
 - Error number: [3507](#); Symbol: [ER_UPDATING_DD_TABLE](#); SQLSTATE: [HY000](#)
Message: Failed to update %s dictionary object.
 - Error number: [3508](#); Symbol: [ER_INVALID_DD_OBJECT_ID](#); SQLSTATE: [HY000](#)
Message: Dictionary object id (%lu) does not exist.
 - Error number: [3509](#); Symbol: [ER_INVALID_DD_OBJECT_NAME](#); SQLSTATE: [HY000](#)
Message: Dictionary object name '%s' is invalid. (%s)
 - Error number: [3510](#); Symbol: [ER_TABLESPACE_MISSING_WITH_NAME](#); SQLSTATE: [HY000](#)
Message: Tablespace %s doesn't exist.

-
- Error number: 3511; Symbol: ER_TOO_LONG_ROUTINE_COMMENT; SQLSTATE: HY000
Message: Comment for routine '%s' is too long (max = %lu)
 - Error number: 3512; Symbol: ER_SP_LOAD_FAILED; SQLSTATE: HY000
Message: Failed to load routine '%s'.
 - Error number: 3513; Symbol: ER_INVALID_BITWISE_OPERANDS_SIZE; SQLSTATE: HY000
Message: Binary operands of bitwise operators must be of equal length
 - Error number: 3514; Symbol: ER_INVALID_BITWISE_AGGREGATE_OPERANDS_SIZE; SQLSTATE: HY000
Message: Aggregate bitwise functions cannot accept arguments longer than 511 bytes; consider using the SUBSTRING() function
 - Error number: 3515; Symbol: ER_WARN_UNSUPPORTED_HINT; SQLSTATE: HY000
Message: Hints aren't supported in %s
 - Error number: 3516; Symbol: ER_UNEXPECTED_GEOMETRY_TYPE; SQLSTATE: 22S01
Message: %s value is a geometry of unexpected type %s in %s.
 - Error number: 3517; Symbol: ER_SRS_PARSE_ERROR; SQLSTATE: SR002
Message: Can't parse the spatial reference system definition of SRID %u.
 - Error number: 3518; Symbol: ER_SRS_PROJ_PARAMETER_MISSING; SQLSTATE: SR003
Message: The spatial reference system definition for SRID %u does not specify the mandatory %s (EPSG %u) projection parameter.
 - Error number: 3519; Symbol: ER_WARN_SRS_NOT_FOUND; SQLSTATE: 01000
Message: There's no spatial reference system with SRID %u.
 - Error number: 3520; Symbol: ER_SRS_NOT_CARTESIAN; SQLSTATE: 22S00
Message: Function %s is only defined for Cartesian spatial reference systems, but one of its arguments is in SRID %u, which is not Cartesian.
 - Error number: 3521; Symbol: ER_SRS_NOT_CARTESIAN_UNDEFINED; SQLSTATE: SR001
Message: Function %s is only defined for Cartesian spatial reference systems, but one of its arguments is in SRID %u, which has not been defined.
 - Error number: 3522; Symbol: ER_PK_INDEX_CANT_BE_INVISIBLE; SQLSTATE: HY000
Message: A primary key index cannot be invisible
 - Error number: 3523; Symbol: ER_UNKNOWN_AUTHID; SQLSTATE: HY000
Message: Unknown authorization ID `%s` @ `%s`
 - Error number: 3524; Symbol: ER_FAILED_ROLE_GRANT; SQLSTATE: HY000
Message: Failed to grant %s` to %s

-
- Error number: [3525](#); Symbol: [ER_OPEN_ROLE_TABLES](#); SQLSTATE: [HY000](#)
Message: Failed to open the security system tables
 - Error number: [3526](#); Symbol: [ER_FAILED_DEFAULT_ROLES](#); SQLSTATE: [HY000](#)
Message: Failed to set default roles
 - Error number: [3527](#); Symbol: [ER_COMPONENTS_NO_SCHEME](#); SQLSTATE: [HY000](#)
Message: Cannot find schema in specified URN: '%s'.
 - Error number: [3528](#); Symbol: [ER_COMPONENTS_NO_SCHEME_SERVICE](#); SQLSTATE: [HY000](#)
Message: Cannot acquire scheme load service implementation for schema '%s' in specified URN: '%s'.
 - Error number: [3529](#); Symbol: [ER_COMPONENTS_CANT_LOAD](#); SQLSTATE: [HY000](#)
Message: Cannot load component from specified URN: '%s'.
 - Error number: [3530](#); Symbol: [ER_ROLE_NOT_GRANTED](#); SQLSTATE: [HY000](#)
Message: '%s`@`%s`' is not granted to '%s`@`%s`'
 - Error number: [3531](#); Symbol: [ER_FAILED_REVOKE_ROLE](#); SQLSTATE: [HY000](#)
Message: Could not revoke role from '%s`@`%s`'
 - Error number: [3532](#); Symbol: [ER_RENAME_ROLE](#); SQLSTATE: [HY000](#)
Message: Renaming of a role identifier is forbidden
 - Error number: [3533](#); Symbol: [ER_COMPONENTS_CANT_ACQUIRE_SERVICE_IMPLEMENTATION](#); SQLSTATE: [HY000](#)
Message: Cannot acquire specified service implementation: '%s'.
 - Error number: [3534](#); Symbol: [ER_COMPONENTS_CANT_SATISFY_DEPENDENCY](#); SQLSTATE: [HY000](#)
Message: Cannot satisfy dependency for service '%s' required by component '%s'.
 - Error number: [3535](#); Symbol: [ER_COMPONENTS_LOAD_CANT_REGISTER_SERVICE_IMPLEMENTATION](#); SQLSTATE: [HY000](#)
Message: Cannot register service implementation '%s' provided by component '%s'.
 - Error number: [3536](#); Symbol: [ER_COMPONENTS_LOAD_CANT_INITIALIZE](#); SQLSTATE: [HY000](#)
Message: Initialization method provided by component '%s' failed.
 - Error number: [3537](#); Symbol: [ER_COMPONENTS_UNLOAD_NOT_LOADED](#); SQLSTATE: [HY000](#)
Message: Component specified by URN '%s' to unload has not been loaded before.
 - Error number: [3538](#); Symbol: [ER_COMPONENTS_UNLOAD_CANT_DEINITIALIZE](#); SQLSTATE: [HY000](#)
Message: De-initialization method provided by component '%s' failed.
 - Error number: [3539](#); Symbol: [ER_COMPONENTS_CANT_RELEASE_SERVICE](#); SQLSTATE: [HY000](#)
Message: Release of previously acquired service implementation failed.

-
- Error number: 3540; Symbol: `ER_COMPONENTS_UNLOAD_CANT_UNREGISTER_SERVICE`; SQLSTATE: HY000
Message: Unregistration of service implementation '%s' provided by component '%s' failed during unloading of the component.
 - Error number: 3541; Symbol: `ER_COMPONENTS_CANT_UNLOAD`; SQLSTATE: HY000
Message: Cannot unload component from specified URN: '%s'.
 - Error number: 3542; Symbol: `ER_WARN_UNLOAD_THE_NOT_PERSISTED`; SQLSTATE: HY000
Message: The Persistent Dynamic Loader was used to unload a component '%s', but it was not used to load that component before.
 - Error number: 3543; Symbol: `ER_COMPONENT_TABLE_INCORRECT`; SQLSTATE: HY000
Message: The mysql.component table is missing or has an incorrect definition.
 - Error number: 3544; Symbol: `ER_COMPONENT_MANIPULATE_ROW_FAILED`; SQLSTATE: HY000
Message: Failed to manipulate component '%s' persistence data. Error code %d from storage engine.
 - Error number: 3545; Symbol: `ER_COMPONENTS_UNLOAD_DUPLICATE_IN_GROUP`; SQLSTATE: HY000
Message: The component with specified URN: '%s' was specified in group more than once.
 - Error number: 3546; Symbol: `ER_CANT_SET_GTID_PURGED_DUE_SETS_CONSTRAINTS`; SQLSTATE: HY000
Message: @@GLOBAL.GTID_PURGED cannot be changed: %s
 - Error number: 3547; Symbol: `ER_CANNOT_LOCK_USER_MANAGEMENT_CACHES`; SQLSTATE: HY000
Message: Can not lock user management caches for processing.
 - Error number: 3548; Symbol: `ER_SRS_NOT_FOUND`; SQLSTATE: SR001
Message: There's no spatial reference system with SRID %u.
 - Error number: 3549; Symbol: `ER_VARIABLE_NOT_PERSISTED`; SQLSTATE: HY000
Message: Variables cannot be persisted. Please retry.
 - Error number: 3550; Symbol: `ER_IS_QUERY_INVALID_CLAUSE`; SQLSTATE: HY000
Message: Information schema queries do not support the '%s' clause.
 - Error number: 3551; Symbol: `ER_UNABLE_TO_STORE_STATISTICS`; SQLSTATE: HY000
Message: Unable to store dynamic %s statistics into data dictionary.
 - Error number: 3552; Symbol: `ER_NO_SYSTEM_SCHEMA_ACCESS`; SQLSTATE: HY000
Message: Access to system schema '%s' is rejected.
 - Error number: 3553; Symbol: `ER_NO_SYSTEM_TABLESPACE_ACCESS`; SQLSTATE: HY000
Message: Access to system tablespace '%s' is rejected.
 - Error number: 3554; Symbol: `ER_NO_SYSTEM_TABLE_ACCESS`; SQLSTATE: HY000

Message: Access to %s '%s.%s' is rejected.

- Error number: 3555; Symbol: [ER_NO_SYSTEM_TABLE_ACCESS_FOR_DICTIONARY_TABLE](#); SQLSTATE: [HY000](#)

Message: data dictionary table

- Error number: 3556; Symbol: [ER_NO_SYSTEM_TABLE_ACCESS_FOR_SYSTEM_TABLE](#); SQLSTATE: [HY000](#)

Message: system table

- Error number: 3557; Symbol: [ER_NO_SYSTEM_TABLE_ACCESS_FOR_TABLE](#); SQLSTATE: [HY000](#)

Message: table

- Error number: 3558; Symbol: [ER_INVALID_OPTION_KEY](#); SQLSTATE: [22023](#)

Message: Invalid option key '%s' in function %s.

- Error number: 3559; Symbol: [ER_INVALID_OPTION_VALUE](#); SQLSTATE: [22023](#)

Message: Invalid value '%s' for option '%s' in function '%s'.

- Error number: 3560; Symbol: [ER_INVALID_OPTION_KEY_VALUE_PAIR](#); SQLSTATE: [22023](#)

Message: The string '%s' is not a valid key %c value pair in function %s.

- Error number: 3561; Symbol: [ER_INVALID_OPTION_START_CHARACTER](#); SQLSTATE: [22023](#)

Message: The options argument in function %s starts with the invalid character '%c'.

- Error number: 3562; Symbol: [ER_INVALID_OPTION_END_CHARACTER](#); SQLSTATE: [22023](#)

Message: The options argument in function %s ends with the invalid character '%c'.

- Error number: 3563; Symbol: [ER_INVALID_OPTION_CHARACTERS](#); SQLSTATE: [22023](#)

Message: The options argument in function %s contains the invalid character sequence '%s'.

- Error number: 3564; Symbol: [ER_DUPLICATE_OPTION_KEY](#); SQLSTATE: [22023](#)

Message: Duplicate option key '%s' in function '%s'.

- Error number: 3565; Symbol: [ER_WARN_SRS_NOT_FOUND_AXIS_ORDER](#); SQLSTATE: [01000](#)

Message: There's no spatial reference system with SRID %u. The axis order is unknown.

- Error number: 3566; Symbol: [ER_NO_ACCESS_TO_NATIVE_FCT](#); SQLSTATE: [HY000](#)

Message: Access to native function '%s' is rejected.

- Error number: 3567; Symbol: [ER_RESET_SOURCE_TO_VALUE_OUT_OF_RANGE](#); SQLSTATE: [HY000](#)

Message: The requested value '%llu' for the next binary log index is out of range. Please use a value between '1' and '%lu'.

- Error number: 3568; Symbol: [ER_UNRESOLVED_TABLE_LOCK](#); SQLSTATE: [HY000](#)

Message: Unresolved table name %s in locking clause.

-
- Error number: [3569](#); Symbol: [ER_DUPLICATE_TABLE_LOCK](#); SQLSTATE: [HY000](#)
Message: Table %s appears in multiple locking clauses.
 - Error number: [3570](#); Symbol: [ER_BINLOG_UNSAFE_SKIP_LOCKED](#); SQLSTATE: [HY000](#)
Message: Statement is unsafe because it uses SKIP LOCKED. The set of inserted values is non-deterministic.
 - Error number: [3571](#); Symbol: [ER_BINLOG_UNSAFE_NOWAIT](#); SQLSTATE: [HY000](#)
Message: Statement is unsafe because it uses NOWAIT. Whether the command will succeed or fail is not deterministic.
 - Error number: [3572](#); Symbol: [ER_LOCK_NOWAIT](#); SQLSTATE: [HY000](#)
Message: Statement aborted because lock(s) could not be acquired immediately and NOWAIT is set.
 - Error number: [3573](#); Symbol: [ER_CTE_RECURSIVE_REQUIRES_UNION](#); SQLSTATE: [HY000](#)
Message: Recursive Common Table Expression '%s' should contain a UNION
 - Error number: [3574](#); Symbol: [ER_CTE_RECURSIVE_REQUIRES_NONRECURSIVE_FIRST](#); SQLSTATE: [HY000](#)
Message: Recursive Common Table Expression '%s' should have one or more non-recursive query blocks followed by one or more recursive ones
 - Error number: [3575](#); Symbol: [ER_CTE_RECURSIVE_FORBIDS_AGGREGATION](#); SQLSTATE: [HY000](#)
Message: Recursive Common Table Expression '%s' can contain neither aggregation nor window functions in recursive query block
 - Error number: [3576](#); Symbol: [ER_CTE_RECURSIVE_FORBIDDEN_JOIN_ORDER](#); SQLSTATE: [HY000](#)
Message: In recursive query block of Recursive Common Table Expression '%s', the recursive table must neither be in the right argument of a LEFT JOIN, nor be forced to be non-first with join order hints
 - Error number: [3577](#); Symbol: [ER_CTE_RECURSIVE_REQUIRES_SINGLE_REFERENCE](#); SQLSTATE: [HY000](#)
Message: In recursive query block of Recursive Common Table Expression '%s', the recursive table must be referenced only once, and not in any subquery
 - Error number: [3578](#); Symbol: [ER_SWITCH_TMP_ENGINE](#); SQLSTATE: [HY000](#)
Message: '%s' requires @@internal_tmp_disk_storage_engine=InnoDB
 - Error number: [3579](#); Symbol: [ER_WINDOW_NO_SUCH_WINDOW](#); SQLSTATE: [HY000](#)
Message: Window name '%s' is not defined.
 - Error number: [3580](#); Symbol: [ER_WINDOW_CIRCULARITY_IN_WINDOW_GRAPH](#); SQLSTATE: [HY000](#)
Message: There is a circularity in the window dependency graph.
 - Error number: [3581](#); Symbol: [ER_WINDOW_NO_CHILD_PARTITIONING](#); SQLSTATE: [HY000](#)
Message: A window which depends on another cannot define partitioning.

-
- Error number: 3582; Symbol: [ER_WINDOW_NO_INHERIT_FRAME](#); SQLSTATE: HY000
Message: Window '%s' has a frame definition, so cannot be referenced by another window.
 - Error number: 3583; Symbol: [ER_WINDOW_NO_REDEFINE_ORDER_BY](#); SQLSTATE: HY000
Message: Window '%s' cannot inherit '%s' since both contain an ORDER BY clause.
 - Error number: 3584; Symbol: [ER_WINDOW_FRAME_START_ILLEGAL](#); SQLSTATE: HY000
Message: Window '%s': frame start cannot be UNBOUNDED FOLLOWING.
 - Error number: 3585; Symbol: [ER_WINDOW_FRAME_END_ILLEGAL](#); SQLSTATE: HY000
Message: Window '%s': frame end cannot be UNBOUNDED PRECEDING.
 - Error number: 3586; Symbol: [ER_WINDOW_FRAME_ILLEGAL](#); SQLSTATE: HY000
Message: Window '%s': frame start or end is negative, NULL or of non-integral type
 - Error number: 3587; Symbol: [ER_WINDOW_RANGE_FRAME_ORDER_TYPE](#); SQLSTATE: HY000
Message: Window '%s' with RANGE N PRECEDING/FOLLOWING frame requires exactly one ORDER BY expression, of numeric or temporal type
 - Error number: 3588; Symbol: [ER_WINDOW_RANGE_FRAME_TEMPORAL_TYPE](#); SQLSTATE: HY000
Message: Window '%s' with RANGE frame has ORDER BY expression of datetime type. Only INTERVAL bound value allowed.
 - Error number: 3589; Symbol: [ER_WINDOW_RANGE_FRAME_NUMERIC_TYPE](#); SQLSTATE: HY000
Message: Window '%s' with RANGE frame has ORDER BY expression of numeric type, INTERVAL bound value not allowed.
 - Error number: 3590; Symbol: [ER_WINDOW_RANGE_BOUND_NOT_CONSTANT](#); SQLSTATE: HY000
Message: Window '%s' has a non-constant frame bound.
 - Error number: 3591; Symbol: [ER_WINDOW_DUPLICATE_NAME](#); SQLSTATE: HY000
Message: Window '%s' is defined twice.
 - Error number: 3592; Symbol: [ER_WINDOW_ILLEGAL_ORDER_BY](#); SQLSTATE: HY000
Message: Window '%s': ORDER BY or PARTITION BY uses legacy position indication which is not supported, use expression.
 - Error number: 3593; Symbol: [ER_WINDOW_INVALID_WINDOW_FUNC_USE](#); SQLSTATE: HY000
Message: You cannot use the window function '%s' in this context.'
 - Error number: 3594; Symbol: [ER_WINDOW_INVALID_WINDOW_FUNC_ALIAS_USE](#); SQLSTATE: HY000
Message: You cannot use the alias '%s' of an expression containing a window function in this context.'
 - Error number: 3595; Symbol: [ER_WINDOW_NESTED_WINDOW_FUNC_USE_IN_WINDOW_SPEC](#); SQLSTATE: HY000
Message: You cannot nest a window function in the specification of window '%s'.

-
- Error number: [3596](#); Symbol: [ER_WINDOW_ROWS_INTERVAL_USE](#); SQLSTATE: [HY000](#)
Message: Window '%s': INTERVAL can only be used with RANGE frames.
 - Error number: [3597](#); Symbol: [ER_WINDOW_NO_GROUP_ORDER_UNUSED](#); SQLSTATE: [HY000](#)
Message: ASC or DESC with GROUP BY isn't allowed with window functions; put ASC or DESC in ORDER BY
 - Error number: [3598](#); Symbol: [ER_WINDOW_EXPLAIN_JSON](#); SQLSTATE: [HY000](#)
Message: To get information about window functions use EXPLAIN FORMAT=JSON
 - Error number: [3599](#); Symbol: [ER_WINDOW_FUNCTION_IGNORES_FRAME](#); SQLSTATE: [HY000](#)
Message: Window function '%s' ignores the frame clause of window '%s' and aggregates over the whole partition
 - Error number: [3600](#); Symbol: [ER_WL9236_NOW_UNUSED](#); SQLSTATE: [HY000](#)
Message: Windowing requires @@internal_tmp_mem_storage_engine=TempTable.
 - Error number: [3601](#); Symbol: [ER_INVALID_NO_OF_ARGS](#); SQLSTATE: [HY000](#)
Message: Too many arguments for function %s: %lu; maximum allowed is %s.
 - Error number: [3602](#); Symbol: [ER_FIELD_IN_GROUPING_NOT_GROUP_BY](#); SQLSTATE: [HY000](#)
Message: Argument #%u of GROUPING function is not in GROUP BY
 - Error number: [3603](#); Symbol: [ER_TOO_LONG_TABLESPACE_COMMENT](#); SQLSTATE: [HY000](#)
Message: Comment for tablespace '%s' is too long (max = %lu)
 - Error number: [3604](#); Symbol: [ER_ENGINE_CANT_DROP_TABLE](#); SQLSTATE: [HY000](#)
Message: Storage engine can't drop table '%s'
 - Error number: [3605](#); Symbol: [ER_ENGINE_CANT_DROP_MISSING_TABLE](#); SQLSTATE: [HY000](#)
Message: Storage engine can't drop table '%s' because it is missing. Use DROP TABLE IF EXISTS to remove it from data-dictionary.
 - Error number: [3606](#); Symbol: [ER_TABLESPACE_DUP_FILENAME](#); SQLSTATE: [HY000](#)
Message: Duplicate file name for tablespace '%s'
 - Error number: [3607](#); Symbol: [ER_DB_DROP_RMDIR2](#); SQLSTATE: [HY000](#)
Message: Problem while dropping database. Can't remove database directory (%s). Please remove it manually.
 - Error number: [3608](#); Symbol: [ER_IMP_NO_FILES_MATCHED](#); SQLSTATE: [HY000](#)
Message: No SDI files matched the pattern '%s'
 - Error number: [3609](#); Symbol: [ER_IMP_SCHEMA_DOES_NOT_EXIST](#); SQLSTATE: [HY000](#)
Message: Schema '%s', referenced in SDI, does not exist.
-

-
- Error number: 3610; Symbol: [ER_IMP_TABLE_ALREADY_EXISTS](#); SQLSTATE: HY000
Message: Table '%s.%s', referenced in SDI, already exists.
 - Error number: 3611; Symbol: [ER_IMP_INCOMPATIBLE_MYSQLD_VERSION](#); SQLSTATE: HY000
Message: Imported mysqld_version (%llu) is not compatible with current (%llu)
 - Error number: 3612; Symbol: [ER_IMP_INCOMPATIBLE_DD_VERSION](#); SQLSTATE: HY000
Message: Imported dd version (%u) is not compatible with current (%u)
 - Error number: 3613; Symbol: [ER_IMP_INCOMPATIBLE_SDI_VERSION](#); SQLSTATE: HY000
Message: Imported sdi version (%llu) is not compatible with current (%llu)
 - Error number: 3614; Symbol: [ER_WARN_INVALID_HINT](#); SQLSTATE: HY000
Message: Invalid number of arguments for hint %s
 - Error number: 3615; Symbol: [ER_VAR_DOES_NOT_EXIST](#); SQLSTATE: HY000
Message: Variable %s does not exist in persisted config file
 - Error number: 3616; Symbol: [ER_LONGITUDE_OUT_OF_RANGE](#); SQLSTATE: 22S02
Message: Longitude %f is out of range in function %s. It must be within (%f, %f].
 - Error number: 3617; Symbol: [ER_LATITUDE_OUT_OF_RANGE](#); SQLSTATE: 22S03
Message: Latitude %f is out of range in function %s. It must be within [%f, %f].
 - Error number: 3618; Symbol: [ER_NOT_IMPLEMENTED_FOR_GEOGRAPHIC_SRS](#); SQLSTATE: 22S00
Message: %s(%s) has not been implemented for geographic spatial reference systems.
 - Error number: 3619; Symbol: [ER_ILLEGAL_PRIVILEGE_LEVEL](#); SQLSTATE: HY000
Message: Illegal privilege level specified for %s
 - Error number: 3620; Symbol: [ER_NO_SYSTEM_VIEW_ACCESS](#); SQLSTATE: HY000
Message: Access to system view INFORMATION_SCHEMA.'%s' is rejected.
 - Error number: 3621; Symbol: [ER_COMPONENT_FILTER_FLABBERGASTED](#); SQLSTATE: HY000
Message: The log-filter component "%s" got confused at "%s" ...
 - Error number: 3622; Symbol: [ER_PART_EXPR_TOO_LONG](#); SQLSTATE: HY000
Message: Partitioning expression is too long.
 - Error number: 3623; Symbol: [ER_UDF_DROP_DYNAMICALLY_REGISTERED](#); SQLSTATE: HY000
Message: DROP FUNCTION can't drop a dynamically registered user defined function
 - Error number: 3624; Symbol: [ER_UNABLE_TO_STORE_COLUMN_STATISTICS](#); SQLSTATE: HY000
Message: Unable to store column statistics for column '%s' in table '%s'.'%s'
 - Error number: 3625; Symbol: [ER_UNABLE_TO_UPDATE_COLUMN_STATISTICS](#); SQLSTATE: HY000

Message: Unable to update column statistics for column '%s' in table '%s'. '%s'

- Error number: [3626](#); Symbol: [ER_UNABLE_TO_DROP_COLUMN_STATISTICS](#); SQLSTATE: [HY000](#)

Message: Unable to remove column statistics for column '%s' in table '%s'. '%s'

- Error number: [3627](#); Symbol: [ER_UNABLE_TO_BUILD_HISTOGRAM](#); SQLSTATE: [HY000](#)

Message: Unable to build histogram statistics for column '%s' in table '%s'. '%s'

- Error number: [3628](#); Symbol: [ER_MANDATORY_ROLE](#); SQLSTATE: [HY000](#)

Message: The role %s is a mandatory role and can't be revoked or dropped. The restriction can be lifted by excluding the role identifier from the global variable mandatory_roles.

- Error number: [3629](#); Symbol: [ER_MISSING_TABLESPACE_FILE](#); SQLSTATE: [HY000](#)

Message: Tablespace '%s' does not have a file named '%s'

- Error number: [3630](#); Symbol: [ER_PERSIST_ONLY_ACCESS_DENIED_ERROR](#); SQLSTATE: [42000](#)

Message: Access denied; you need %s privileges for this operation

- Error number: [3631](#); Symbol: [ER_CMD_NEED_SUPER](#); SQLSTATE: [HY000](#)

Message: You need the SUPER privilege for command '%s'

- Error number: [3632](#); Symbol: [ER_PATH_IN_DATADIR](#); SQLSTATE: [HY000](#)

Message: Path is within the current data directory '%s'

- Error number: [3633](#); Symbol: [ER_CLONE_DDL_IN_PROGRESS](#); SQLSTATE: [HY000](#)

Message: Concurrent DDL is performed during clone operation. Please try again.

- Error number: [3634](#); Symbol: [ER_CLONE_TOO_MANY_CONCURRENT_CLONES](#); SQLSTATE: [HY000](#)

Message: Too many concurrent clone operations. Maximum allowed - %d.

- Error number: [3635](#); Symbol: [ER_APPLIER_LOG_EVENT_VALIDATION_ERROR](#); SQLSTATE: [HY000](#)

Message: The table in transaction %s does not comply with the requirements by an external plugin.

- Error number: [3636](#); Symbol: [ER_CTE_MAX_RECURSION_DEPTH](#); SQLSTATE: [HY000](#)

Message: Recursive query aborted after %u iterations. Try increasing @@cte_max_recursion_depth to a larger value.

- Error number: [3637](#); Symbol: [ER_NOT_HINT_UPDATABLE_VARIABLE](#); SQLSTATE: [HY000](#)

Message: Variable %s cannot be set using SET_VAR hint.

- Error number: [3638](#); Symbol: [ER_CREDENTIALS_CONTRADICT_TO_HISTORY](#); SQLSTATE: [HY000](#)

Message: Cannot use these credentials for '%.*s@%.*s' because they contradict the password history policy

- Error number: [3639](#); Symbol: [ER_WARNING_PASSWORD_HISTORY_CLAUSES_VOID](#); SQLSTATE: [HY000](#)

Message: Non-zero password history clauses ignored for user '%s'@'%s' as its authentication plugin %s does not support password history

- Error number: 3640; Symbol: [ER_CLIENT_DOES_NOT_SUPPORT](#); SQLSTATE: HY000

Message: The client doesn't support %s

- Error number: 3641; Symbol: [ER_I_S_SKIPPED_TABLESPACE](#); SQLSTATE: HY000

Message: Tablespace '%s' was skipped since its definition is being modified by concurrent DDL statement

- Error number: 3642; Symbol: [ER_TABLESPACE_ENGINE_MISMATCH](#); SQLSTATE: HY000

Message: Engine '%s' does not match stored engine '%s' for tablespace '%s'

- Error number: 3643; Symbol: [ER_WRONG_SRID_FOR_COLUMN](#); SQLSTATE: HY000

Message: The SRID of the geometry does not match the SRID of the column '%s'. The SRID of the geometry is %lu, but the SRID of the column is %lu. Consider changing the SRID of the geometry or the SRID property of the column.

- Error number: 3644; Symbol: [ER_CANNOT_ALTER_SRID_DUE_TO_INDEX](#); SQLSTATE: HY000

Message: The SRID specification on the column '%s' cannot be changed because there is a spatial index on the column. Please remove the spatial index before altering the SRID specification.

- Error number: 3645; Symbol: [ER_WARN_BINLOG_PARTIAL_UPDATES_DISABLED](#); SQLSTATE: HY000

Message: When %s, the option binlog_row_value_options=%s will be ignored and updates will be written in full format to binary log.

- Error number: 3647; Symbol: [ER_WARN_BINLOG_PARTIAL_UPDATES_SUGGESTS_PARTIAL_IMAGES](#); SQLSTATE: HY000

Message: When %s, the option binlog_row_value_options=%s will be used only for the after-image. Full values will be written in the before-image, so the saving in disk space due to binlog_row_value_options is limited to less than 50%%.

- Error number: 3648; Symbol: [ER_COULD_NOT_APPLY_JSON_DIFF](#); SQLSTATE: HY000

Message: Could not apply JSON diff in table %.*s, column %s.

- Error number: 3649; Symbol: [ER_CORRUPTED_JSON_DIFF](#); SQLSTATE: HY000

Message: Corrupted JSON diff for table %.*s, column %s.

- Error number: 3650; Symbol: [ER_RESOURCE_GROUP_EXISTS](#); SQLSTATE: HY000

Message: Resource Group '%s' exists

- Error number: 3651; Symbol: [ER_RESOURCE_GROUP_NOT_EXISTS](#); SQLSTATE: HY000

Message: Resource Group '%s' does not exist.

- Error number: 3652; Symbol: [ER_INVALID_VCPU_ID](#); SQLSTATE: HY000

Message: Invalid cpu id %u

-
- Error number: 3653; Symbol: [ER_INVALID_VCPU_RANGE](#); SQLSTATE: HY000
Message: Invalid VCPU range %u-%u
 - Error number: 3654; Symbol: [ER_INVALID_THREAD_PRIORITY](#); SQLSTATE: HY000
Message: Invalid thread priority value %d for %s resource group %s. Allowed range is [%d, %d].
 - Error number: 3655; Symbol: [ER_DISALLOWED_OPERATION](#); SQLSTATE: HY000
Message: %s operation is disallowed on %s
 - Error number: 3656; Symbol: [ER_RESOURCE_GROUP_BUSY](#); SQLSTATE: HY000
Message: Resource group %s is busy.
 - Error number: 3657; Symbol: [ER_RESOURCE_GROUP_DISABLED](#); SQLSTATE: HY000
Message: Resource group %s is disabled.
 - Error number: 3658; Symbol: [ER_FEATURE_UNSUPPORTED](#); SQLSTATE: HY000
Message: Feature %s is unsupported (%s).
 - Error number: 3659; Symbol: [ER_ATTRIBUTE_IGNORED](#); SQLSTATE: HY000
Message: Attribute %s is ignored (%s).
 - Error number: 3660; Symbol: [ER_INVALID_THREAD_ID](#); SQLSTATE: HY000
Message: Invalid thread id (%llu).
 - Error number: 3661; Symbol: [ER_RESOURCE_GROUP_BIND_FAILED](#); SQLSTATE: HY000
Message: Unable to bind resource group %s with thread id (%llu).(%s).
 - Error number: 3662; Symbol: [ER_INVALID_USE_OF_FORCE_OPTION](#); SQLSTATE: HY000
Message: Option FORCE invalid as DISABLE option is not specified.
 - Error number: 3663; Symbol: [ER_GROUP_REPLICATION_COMMAND_FAILURE](#); SQLSTATE: HY000
Message: The %s command encountered a failure. %s
 - Error number: 3664; Symbol: [ER_SDI_OPERATION_FAILED](#); SQLSTATE: HY000
Message: Failed to %s SDI '%s.%s' in tablespace '%s'.
 - Error number: 3665; Symbol: [ER_MISSING_JSON_TABLE_VALUE](#); SQLSTATE: 22035
Message: Missing value for JSON_TABLE column '%s'
 - Error number: 3666; Symbol: [ER_WRONG_JSON_TABLE_VALUE](#); SQLSTATE: 2203F
Message: Can't store an array or an object in the scalar JSON_TABLE column '%s'
 - Error number: 3667; Symbol: [ER_TF_MUST_HAVE_ALIAS](#); SQLSTATE: 42000
Message: Every table function must have an alias

-
- Error number: 3668; Symbol: [ER_TF_FORBIDDEN_JOIN_TYPE](#); SQLSTATE: HY000
Message: INNER or LEFT JOIN must be used for LATERAL references made by '%s'
 - Error number: 3669; Symbol: [ER_JT_VALUE_OUT_OF_RANGE](#); SQLSTATE: 22003
Message: Value is out of range for JSON_TABLE's column '%s'
 - Error number: 3670; Symbol: [ER_JT_MAX_NESTED_PATH](#); SQLSTATE: 42000
Message: More than supported %u NESTED PATHs were found in JSON_TABLE '%s'
 - Error number: 3671; Symbol: [ER_PASSWORD_EXPIRATION_NOT_SUPPORTED_BY_AUTH_METHOD](#); SQLSTATE: HY000
Message: The selected authentication method %.*s does not support password expiration
 - Error number: 3672; Symbol: [ER_INVALID_GEOJSON CRS NOT TOP LEVEL](#); SQLSTATE: HY000
Message: Invalid GeoJSON data provided to function %s: Member 'crs' must be specified in the top level object.
 - Error number: 3673; Symbol: [ER_BAD_NULL_ERROR_NOT_IGNORED](#); SQLSTATE: 23000
Message: Column '%s' cannot be null
 - Error number: 3674; Symbol: [WARN_USELESS_SPATIAL_INDEX](#); SQLSTATE: HY000
Message: The spatial index on column '%s' will not be used by the query optimizer since the column does not have an SRID attribute. Consider adding an SRID attribute to the column.
 - Error number: 3675; Symbol: [ER_DISK_FULL_NOWAIT](#); SQLSTATE: HY000
Message: Create table/tablespace '%s' failed, as disk is full
 - Error number: 3676; Symbol: [ER_PARSE_ERROR_IN_DIGEST_FN](#); SQLSTATE: HY000
Message: Could not parse argument to digest function: "%s".
 - Error number: 3677; Symbol: [ER_UNDISCLOSED_PARSE_ERROR_IN_DIGEST_FN](#); SQLSTATE: HY000
Message: Could not parse argument to digest function.
 - Error number: 3678; Symbol: [ER_SCHEMA_DIR_EXISTS](#); SQLSTATE: HY000
Message: Schema directory '%s' already exists. This must be resolved manually (e.g. by moving the schema directory to another location).
 - Error number: 3679; Symbol: [ER_SCHEMA_DIR_MISSING](#); SQLSTATE: HY000
Message: Schema directory '%s' does not exist
 - Error number: 3680; Symbol: [ER_SCHEMA_DIR_CREATE_FAILED](#); SQLSTATE: HY000
Message: Failed to create schema directory '%s' (errno: %d - %s)
 - Error number: 3681; Symbol: [ER_SCHEMA_DIR_UNKNOWN](#); SQLSTATE: HY000
Message: Schema '%s' does not exist, but schema directory '%s' was found. This must be resolved manually (e.g. by moving the schema directory to another location).

-
- Error number: 3682; Symbol: [ER_ONLY_IMPLEMENTED_FOR_SRID_0_AND_4326](#); SQLSTATE: 22S00
Message: Function %s is only defined for SRID 0 and SRID 4326.
 - Error number: 3684; Symbol: [ER_REGEX_BUFFER_OVERFLOW](#); SQLSTATE: HY000
Message: The result string is larger than the result buffer.
 - Error number: 3685; Symbol: [ER_REGEX_ILLEGAL_ARGUMENT](#); SQLSTATE: HY000
Message: Illegal argument to a regular expression.
 - Error number: 3686; Symbol: [ER_REGEX_INDEX_OUTOFBOUNDS_ERROR](#); SQLSTATE: HY000
Message: Index out of bounds in regular expression search.
 - Error number: 3687; Symbol: [ER_REGEX_INTERNAL_ERROR](#); SQLSTATE: HY000
Message: Internal error in the regular expression library.
 - Error number: 3688; Symbol: [ER_REGEX_RULE_SYNTAX](#); SQLSTATE: HY000
Message: Syntax error in regular expression on line %u, character %u.
 - Error number: 3689; Symbol: [ER_REGEX_BAD_ESCAPE_SEQUENCE](#); SQLSTATE: HY000
Message: Unrecognized escape sequence in regular expression.
 - Error number: 3690; Symbol: [ER_REGEX_UNIMPLEMENTED](#); SQLSTATE: HY000
Message: The regular expression contains a feature that is not implemented in this library version.
 - Error number: 3691; Symbol: [ER_REGEX_MISMATCHED_PAREN](#); SQLSTATE: HY000
Message: Mismatched parenthesis in regular expression.
 - Error number: 3692; Symbol: [ER_REGEX_BAD_INTERVAL](#); SQLSTATE: HY000
Message: Incorrect description of a {min,max} interval.
 - Error number: 3693; Symbol: [ER_REGEX_MAX_LT_MIN](#); SQLSTATE: HY000
Message: The maximum is less than the minimum in a {min,max} interval.
 - Error number: 3694; Symbol: [ER_REGEX_INVALID_BACK_REF](#); SQLSTATE: HY000
Message: Invalid back-reference in regular expression.
 - Error number: 3695; Symbol: [ER_REGEX_LOOK_BEHIND_LIMIT](#); SQLSTATE: HY000
Message: The look-behind assertion exceeds the limit in regular expression.
 - Error number: 3696; Symbol: [ER_REGEX_MISSING_CLOSE_BRACKET](#); SQLSTATE: HY000
Message: The regular expression contains an unclosed bracket expression.
 - Error number: 3697; Symbol: [ER_REGEX_INVALID_RANGE](#); SQLSTATE: HY000
Message: The regular expression contains an [x-y] character range where x comes after y.
 - Error number: 3698; Symbol: [ER_REGEX_STACK_OVERFLOW](#); SQLSTATE: HY000

Message: Overflow in the regular expression backtrack stack.

- Error number: 3699; Symbol: ER_REGEXPTIME_OUT; SQLSTATE: HY000

Message: Timeout exceeded in regular expression match.

- Error number: 3700; Symbol: ER_REGEXPTOOPATTERN_TOO_BIG; SQLSTATE: HY000

Message: The regular expression pattern exceeds limits on size or complexity.

- Error number: 3701; Symbol: ER_CANTSETERRORLOGSERVICE; SQLSTATE: HY000

Message: Value for %s got confusing at or around "%s". Syntax may be wrong, component may not be INSTALLED, or a component that does not support instances may be listed more than once.

- Error number: 3702; Symbol: ER_EMPTY_PIPELINE_FOR_ERROR_LOG_SERVICE; SQLSTATE: HY000

Message: Setting an empty %s pipeline disables error logging!

- Error number: 3703; Symbol: ER_COMPONENT_FILTER_DIAGNOSTICS; SQLSTATE: HY000

Message: filter %s: %s

- Error number: 3704; Symbol: ER_NOT_IMPLEMENTED_FOR_CARTESIAN_SRS; SQLSTATE: 22S00

Message: %s(%s) has not been implemented for Cartesian spatial reference systems.

- Error number: 3705; Symbol: ER_NOT_IMPLEMENTED_FOR_PROJECTED_SRS; SQLSTATE: 22S00

Message: %s(%s) has not been implemented for projected spatial reference systems.

- Error number: 3706; Symbol: ER_NONPOSITIVE_RADIUS; SQLSTATE: 22003

Message: Invalid radius provided to function %s: Radius must be greater than zero.

- Error number: 3707; Symbol: ER_RESTART_SERVER_FAILED; SQLSTATE: HY000

Message: Restart server failed (%s).

- Error number: 3708; Symbol: ER_SRS_MISSING_MANDATORY_ATTRIBUTE; SQLSTATE: SR006

Message: Missing mandatory attribute %s.

- Error number: 3709; Symbol: ER_SRS_MULTIPLE_ATTRIBUTE_DEFINITIONS; SQLSTATE: SR006

Message: Multiple definitions of attribute %s.

- Error number: 3710; Symbol: ER_SRS_NAME_CANT_BE_EMPTY_OR_WHITESPACE; SQLSTATE: SR006

Message: The spatial reference system name can't be an empty string or start or end with whitespace.

- Error number: 3711; Symbol: ER_SRS_ORGANIZATION_CANT_BE_EMPTY_OR_WHITESPACE; SQLSTATE: SR006

Message: The organization name can't be an empty string or start or end with whitespace.

- Error number: 3712; Symbol: ER_SRS_ID_ALREADY_EXISTS; SQLSTATE: SR004

Message: There is already a spatial reference system with SRID %u.

-
- Error number: [3713](#); Symbol: [ER_WARN_SRS_ID_ALREADY_EXISTS](#); SQLSTATE: [01S00](#)
Message: There is already a spatial reference system with SRID %u.
 - Error number: [3714](#); Symbol: [ER_CANT_MODIFY_SRID_0](#); SQLSTATE: [SR000](#)
Message: SRID 0 is not modifiable.
 - Error number: [3715](#); Symbol: [ER_WARN_RESERVED_SRID_RANGE](#); SQLSTATE: [01S01](#)
Message: The SRID range [%u, %u] has been reserved for system use. SRSs in this range may be added, modified or removed without warning during upgrade.
 - Error number: [3716](#); Symbol: [ER_CANT_MODIFY_SRS_USED_BY_COLUMN](#); SQLSTATE: [SR005](#)
Message: Can't modify SRID %u. There is at least one column depending on it.
 - Error number: [3717](#); Symbol: [ER_SRS_INVALID_CHARACTER_IN_ATTRIBUTE](#); SQLSTATE: [SR006](#)
Message: Invalid character in attribute %s.
 - Error number: [3718](#); Symbol: [ER_SRS_ATTRIBUTE_STRING_TOO_LONG](#); SQLSTATE: [SR006](#)
Message: Attribute %s is too long. The maximum length is %u characters.
 - Error number: [3719](#); Symbol: [ER_DEPRECATED_UTF8_ALIAS](#); SQLSTATE: [HY000](#)
Message: 'utf8' is currently an alias for the character set UTF8MB3, but will be an alias for UTF8MB4 in a future release. Please consider using UTF8MB4 in order to be unambiguous.
 - Error number: [3720](#); Symbol: [ER_DEPRECATED_NATIONAL](#); SQLSTATE: [HY000](#)
Message: NATIONAL/NCHAR/NVARCHAR implies the character set UTF8MB3, which will be replaced by UTF8MB4 in a future release. Please consider using CHAR(x) CHARACTER SET UTF8MB4 in order to be unambiguous.
 - Error number: [3721](#); Symbol: [ER_INVALID_DEFAULT_UTF8MB4_COLLATION](#); SQLSTATE: [HY000](#)
Message: Invalid default collation %s: utf8mb4_0900_ai_ci or utf8mb4_general_ci expected
 - Error number: [3722](#); Symbol: [ER_UNABLE_TO_COLLECT_LOG_STATUS](#); SQLSTATE: [HY000](#)
Message: Unable to collect information for column '%s': %s.
 - Error number: [3723](#); Symbol: [ER_RESERVED_TABLESPACE_NAME](#); SQLSTATE: [HY000](#)
Message: The table '%s' may not be created in the reserved tablespace '%s'.
 - Error number: [3724](#); Symbol: [ER_UNABLE_TO_SET_OPTION](#); SQLSTATE: [HY000](#)
Message: This option cannot be set %s.
 - Error number: [3725](#); Symbol: [ER_REPLICA_POSSIBLY_DIVERGED_AFTER_DDL](#); SQLSTATE: [HY000](#)
Message: A commit for an atomic DDL statement was unsuccessful on the source and the replica. The replica supports atomic DDL statements but the source does not, so the action taken by the replica and source might differ. Check that their states have not diverged before proceeding.
 - Error number: [3726](#); Symbol: [ER_SRS_NOT_GEOGRAPHIC](#); SQLSTATE: [22S00](#)

Message: Function %s is only defined for geographic spatial reference systems, but one of its arguments is in SRID %u, which is not geographic.

- Error number: [3727](#); Symbol: [ER_POLYGON_TOO_LARGE](#); SQLSTATE: [22023](#)

Message: Function %s encountered a polygon that was too large. Polygons must cover less than half the planet.

- Error number: [3728](#); Symbol: [ER_SPATIAL_UNIQUE_INDEX](#); SQLSTATE: [HY000](#)

Message: Spatial indexes can't be primary or unique indexes.

- Error number: [3729](#); Symbol: [ER_INDEX_TYPE_NOT_SUPPORTED_FOR_SPATIAL_INDEX](#); SQLSTATE: [HY000](#)

Message: The index type %s is not supported for spatial indexes.

- Error number: [3730](#); Symbol: [ER_FK_CANNOT_DROP_PARENT](#); SQLSTATE: [HY000](#)

Message: Cannot drop table '%s' referenced by a foreign key constraint '%s' on table '%s'.

- Error number: [3731](#); Symbol: [ER_GEOMETRY_PARAM_LONGITUDE_OUT_OF_RANGE](#); SQLSTATE: [22S02](#)

Message: A parameter of function %s contains a geometry with longitude %f, which is out of range. It must be within [%f, %f].

- Error number: [3732](#); Symbol: [ER_GEOMETRY_PARAM_LATITUDE_OUT_OF_RANGE](#); SQLSTATE: [22S03](#)

Message: A parameter of function %s contains a geometry with latitude %f, which is out of range. It must be within [%f, %f].

- Error number: [3733](#); Symbol: [ER_FK_CANNOT_USE_VIRTUAL_COLUMN](#); SQLSTATE: [HY000](#)

Message: Foreign key '%s' uses virtual column '%s' which is not supported.

- Error number: [3734](#); Symbol: [ER_FK_NO_COLUMN_PARENT](#); SQLSTATE: [HY000](#)

Message: Failed to add the foreign key constraint. Missing column '%s' for constraint '%s' in the referenced table '%s'

- Error number: [3735](#); Symbol: [ER_CANT_SET_ERROR_SUPPRESSION_LIST](#); SQLSTATE: [HY000](#)

Message: %s: Could not add suppression rule for code "%s". Rule-set may be full, or code may not correspond to an error-log message.

- Error number: [3736](#); Symbol: [ER_SRS_GEOGCS_INVALID_AXES](#); SQLSTATE: [SR002](#)

Message: The spatial reference system definition for SRID %u specifies invalid geographic axes '%s' and '%s'. One axis must be NORTH or SOUTH and the other must be EAST or WEST.

- Error number: [3737](#); Symbol: [ER_SRS_INVALID_SEMI_MAJOR_AXIS](#); SQLSTATE: [SR002](#)

Message: The length of the semi-major axis must be a positive number.

- Error number: [3738](#); Symbol: [ER_SRS_INVALID_INVERSE_FLATTENING](#); SQLSTATE: [SR002](#)

Message: The inverse flattening must be larger than 1.0, or 0.0 if the ellipsoid is a sphere.

-
- Error number: 3739; Symbol: `ER_SRS_INVALID_ANGULAR_UNIT`; SQLSTATE: `SR002`
Message: The angular unit conversion factor must be a positive number.
 - Error number: 3740; Symbol: `ER_SRS_INVALID_PRIME_MERIDIAN`; SQLSTATE: `SR002`
Message: The prime meridian must be within (-180, 180] degrees, specified in the SRS angular unit.
 - Error number: 3741; Symbol: `ER_TRANSFORM_SOURCE_SRS_NOT_SUPPORTED`; SQLSTATE: `22S00`
Message: Transformation from SRID %u is not supported.
 - Error number: 3742; Symbol: `ER_TRANSFORM_TARGET_SRS_NOT_SUPPORTED`; SQLSTATE: `22S00`
Message: Transformation to SRID %u is not supported.
 - Error number: 3743; Symbol: `ER_TRANSFORM_SOURCE_SRS_MISSING_TOWGS84`; SQLSTATE: `22S00`
Message: Transformation from SRID %u is not supported. The spatial reference system has no TOWGS84 clause.
 - Error number: 3744; Symbol: `ER_TRANSFORM_TARGET_SRS_MISSING_TOWGS84`; SQLSTATE: `22S00`
Message: Transformation to SRID %u is not supported. The spatial reference system has no TOWGS84 clause.
 - Error number: 3745; Symbol: `ER_TEMP_TABLE_PREVENTS_SWITCH_SESSION_BINLOG_FORMAT`; SQLSTATE: `HY000`
Message: Changing @@session.binlog_format is disallowed when the session has open temporary table(s). You could wait until these temporary table(s) are dropped and try again.
 - Error number: 3746; Symbol: `ER_TEMP_TABLE_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT`; SQLSTATE: `HY000`
Message: Changing @@global.binlog_format or @@persist.binlog_format is disallowed when any replication channel has open temporary table(s). You could wait until Replica_open_temp_tables = 0 and try again
 - Error number: 3747; Symbol: `ER_RUNNING_APPLIER_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT`; SQLSTATE: `HY000`
Message: Changing @@global.binlog_format or @@persist.binlog_format is disallowed when any replication channel applier thread is running. You could execute STOP REPLICA SQL_THREAD and try again.
 - Error number: 3748; Symbol: `ER_CLIENT_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN_TRX_IN_SBR`; SQLSTATE: `HY000`
Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE are not allowed inside a transaction or inside a procedure in a transactional context when @@session.binlog_format=STATEMENT.
 - Error number: 3750; Symbol: `ER_TABLE_WITHOUT_PK`; SQLSTATE: `HY000`
Message: Unable to create or change a table without a primary key, when the system variable 'sql_require_primary_key' is set. Add a primary key to the table or unset this variable to avoid this message. Note that tables without a primary key can cause performance problems in row-based replication, so please consult your DBA before changing this setting.

-
- Error number: 3751; Symbol: [ER_WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX](#); SQLSTATE: 01000
Message: Data truncated for functional index '%s' at row %ld
 - Error number: 3752; Symbol: [ER_WARN_DATA_OUT_OF_RANGE_FUNCTIONAL_INDEX](#); SQLSTATE: 22003
Message: Value is out of range for functional index '%s' at row %ld
 - Error number: 3753; Symbol: [ER_FUNCTIONAL_INDEX_ON_JSON_OR_GEOMETRY_FUNCTION](#); SQLSTATE: 42000
Message: Cannot create a functional index on a function that returns a JSON or GEOMETRY value.
 - Error number: 3754; Symbol: [ER_FUNCTIONAL_INDEX_REF_AUTO_INCREMENT](#); SQLSTATE: HY000
Message: Functional index '%s' cannot refer to an auto-increment column.
 - Error number: 3755; Symbol: [ER_CANNOT_DROP_COLUMN_FUNCTIONAL_INDEX](#); SQLSTATE: HY000
Message: Cannot drop column '%s' because it is used by a functional index. In order to drop the column, you must remove the functional index.
 - Error number: 3756; Symbol: [ER_FUNCTIONAL_INDEX_PRIMARY_KEY](#); SQLSTATE: HY000
Message: The primary key cannot be a functional index
 - Error number: 3757; Symbol: [ER_FUNCTIONAL_INDEX_ON_LOB](#); SQLSTATE: HY000
Message: Cannot create a functional index on an expression that returns a BLOB or TEXT. Please consider using CAST.
 - Error number: 3758; Symbol: [ER_FUNCTIONAL_INDEX_FUNCTION_IS_NOT_ALLOWED](#); SQLSTATE: HY000
Message: Expression of functional index '%s' contains a disallowed function.
 - Error number: 3759; Symbol: [ER_FULLTEXT_FUNCTIONAL_INDEX](#); SQLSTATE: HY000
Message: Fulltext functional index is not supported.
 - Error number: 3760; Symbol: [ER_SPATIAL_FUNCTIONAL_INDEX](#); SQLSTATE: HY000
Message: Spatial functional index is not supported.
 - Error number: 3761; Symbol: [ER_WRONG_KEY_COLUMN_FUNCTIONAL_INDEX](#); SQLSTATE: HY000
Message: The used storage engine cannot index the expression '%s'.
 - Error number: 3762; Symbol: [ER_FUNCTIONAL_INDEX_ON_FIELD](#); SQLSTATE: HY000
Message: Functional index on a column is not supported. Consider using a regular index instead.
 - Error number: 3763; Symbol: [ER_GENERATED_COLUMN_NAMED_FUNCTION_IS_NOT_ALLOWED](#); SQLSTATE: HY000
Message: Expression of generated column '%s' contains a disallowed function: %s.
 - Error number: 3764; Symbol: [ER_GENERATED_COLUMN_ROW_VALUE](#); SQLSTATE: HY000

Message: Expression of generated column '%s' cannot refer to a row value.

- Error number: 3765; Symbol: [ER_GENERATED_COLUMN_VARIABLES](#); SQLSTATE: HY000

Message: Expression of generated column '%s' cannot refer user or system variables.

- Error number: 3766; Symbol: [ER_DEPENDENT_BY_DEFAULT_GENERATED_VALUE](#); SQLSTATE: HY000

Message: Column '%s' of table '%s' has a default value expression dependency and cannot be dropped or renamed.

- Error number: 3767; Symbol: [ER_DEFAULT_VAL_GENERATED_NON_PRIOR](#); SQLSTATE: HY000

Message: Default value expression of column '%s' cannot refer to a column defined after it if that column is a generated column or has an expression as default value.

- Error number: 3768; Symbol: [ER_DEFAULT_VAL_GENERATED_REF_AUTO_INC](#); SQLSTATE: HY000

Message: Default value expression of column '%s' cannot refer to an auto-increment column.

- Error number: 3769; Symbol: [ER_DEFAULT_VAL_GENERATED_FUNCTION_IS_NOT_ALLOWED](#); SQLSTATE: HY000

Message: Default value expression of column '%s' contains a disallowed function.

- Error number: 3770; Symbol: [ER_DEFAULT_VAL_GENERATED_NAMED_FUNCTION_IS_NOT_ALLOWED](#); SQLSTATE: HY000

Message: Default value expression of column '%s' contains a disallowed function: %s.

- Error number: 3771; Symbol: [ER_DEFAULT_VAL_GENERATED_ROW_VALUE](#); SQLSTATE: HY000

Message: Default value expression of column '%s' cannot refer to a row value.

- Error number: 3772; Symbol: [ER_DEFAULT_VAL_GENERATED_VARIABLES](#); SQLSTATE: HY000

Message: Default value expression of column '%s' cannot refer user or system variables.

- Error number: 3773; Symbol: [ER_DEFAULT_AS_VAL_GENERATED](#); SQLSTATE: HY000

Message: DEFAULT function cannot be used with default value expressions

- Error number: 3774; Symbol: [ER_UNSUPPORTED_ACTION_ON_DEFAULT_VAL_GENERATED](#); SQLSTATE: HY000

Message: '%s' is not supported for default value expressions.

- Error number: 3775; Symbol: [ER_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION](#); SQLSTATE: HY000

Message: Statement violates GTID consistency: ALTER TABLE ... ADD COLUMN .. with expression as DEFAULT.

- Error number: 3776; Symbol: [ER_FK_CANNOT_CHANGE_ENGINE](#); SQLSTATE: HY000

Message: Cannot change table's storage engine because the table participates in a foreign key constraint.

- Error number: 3777; Symbol: [ER_WARN_DEPRECATED_USER_SET_EXPR](#); SQLSTATE: HY000

Message: Setting user variables within expressions is deprecated and will be removed in a future release. Consider alternatives: 'SET variable=expression, ...', or 'SELECT expression(s) INTO variables(s)'.

- Error number: 3778; Symbol: [ER_WARN_DEPRECATED_UTF8MB3_COLLATION](#); SQLSTATE: [HY000](#)

Message: '%s' is a collation of the deprecated character set UTF8MB3. Please consider using UTF8MB4 with an appropriate collation instead.

- Error number: 3779; Symbol: [ER_WARN_DEPRECATED_NESTED_COMMENT_SYNTAX](#); SQLSTATE: [HY000](#)

Message: Nested comment syntax is deprecated and will be removed in a future release.

- Error number: 3780; Symbol: [ER_FK_INCOMPATIBLE_COLUMNS](#); SQLSTATE: [HY000](#)

Message: Referencing column '%s' and referenced column '%s' in foreign key constraint '%s' are incompatible.

- Error number: 3781; Symbol: [ER_GR_HOLD_WAIT_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: Timeout exceeded for held statement while new Group Replication primary member is applying backlog.

- Error number: 3782; Symbol: [ER_GR_HOLD_KILLED](#); SQLSTATE: [HY000](#)

Message: Held statement aborted because Group Replication plugin got shut down or thread was killed while new primary member was applying backlog.

- Error number: 3783; Symbol: [ER_GR_HOLD_MEMBER_STATUS_ERROR](#); SQLSTATE: [HY000](#)

Message: Held statement was aborted due to member being in error state, while backlog is being applied during Group Replication primary election.

- Error number: 3784; Symbol: [ER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY](#); SQLSTATE: [HY000](#)

Message: Failed to fetch key from keyring, please check if keyring is loaded.

- Error number: 3785; Symbol: [ER_RPL_ENCRYPTION_KEY_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Can't find key from keyring, please check in the server log if a keyring is loaded and initialized successfully.

- Error number: 3786; Symbol: [ER_RPL_ENCRYPTION_KEYRING_INVALID_KEY](#); SQLSTATE: [HY000](#)

Message: Fetched an invalid key from keyring.

- Error number: 3787; Symbol: [ER_RPL_ENCRYPTION_HEADER_ERROR](#); SQLSTATE: [HY000](#)

Message: Error reading a replication log encryption header: %s.

- Error number: 3788; Symbol: [ER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS](#); SQLSTATE: [HY000](#)

Message: Failed to rotate some logs after changing binlog encryption settings. Please fix the problem and rotate the logs manually.

- Error number: 3789; Symbol: [ER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED](#); SQLSTATE: [HY000](#)

Message: Key %s exists unexpected.

- Error number: 3790; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY`; SQLSTATE: HY000

Message: Failed to generate key, please check if keyring is loaded.

- Error number: 3791; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY`; SQLSTATE: HY000

Message: Failed to store key, please check if keyring is loaded.

- Error number: 3792; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY`; SQLSTATE: HY000

Message: Failed to remove key, please check if keyring is loaded.

- Error number: 3793; Symbol: `ER_RPL_ENCRYPTION_UNABLE_TO_CHANGE_OPTION`; SQLSTATE: HY000

Message: Failed to change binlog_encryption value. %s.

- Error number: 3794; Symbol: `ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED`; SQLSTATE: HY000

Message: Unable to recover binlog encryption master key, please check if keyring is loaded.

- Error number: 3795; Symbol: `ER_SLOW_LOG_MODE_IGNORED_WHEN_NOT_LOGGING_TO_FILE`; SQLSTATE: HY000

Message: slow query log file format changed as requested, but setting will have no effect when not actually logging to a file.

- Error number: 3796; Symbol: `ER_GRP_TRX_CONSISTENCY_NOT_ALLOWED`; SQLSTATE: HY000

Message: The option group_replication_consistency cannot be used on the current member state.

- Error number: 3797; Symbol: `ER_GRP_TRX_CONSISTENCY_BEFORE`; SQLSTATE: HY000

Message: Error while waiting for group transactions commit on group_replication_consistency='BEFORE'.

- Error number: 3798; Symbol: `ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN`; SQLSTATE: HY000

Message: Error while waiting for transactions with group_replication_consistency='AFTER' to commit.

- Error number: 3799; Symbol: `ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED`; SQLSTATE: HY000

Message: The Group Replication plugin is stopping, therefore new transactions are not allowed to start.

- Error number: 3800; Symbol: `ER_FUNCTIONAL_INDEX_ROW_VALUE_IS_NOT_ALLOWED`; SQLSTATE: HY000

Message: Expression of functional index '%s' cannot refer to a row value.

- Error number: 3801; Symbol: `ER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT`; SQLSTATE: HY000

Message: Failed to encrypt content to write into binlog file: %s.

-
- Error number: 3802; Symbol: `ER_PAGE_TRACKING_NOT_STARTED`; SQLSTATE: `HY000`
Message: Page Tracking is not started yet.
 - Error number: 3803; Symbol: `ER_PAGE_TRACKING_RANGE_NOT_TRACKED`; SQLSTATE: `HY000`
Message: Tracking was not enabled for the LSN range specified
 - Error number: 3804; Symbol: `ER_PAGE_TRACKING_CANNOT_PURGE`; SQLSTATE: `HY000`
Message: Cannot purge data when concurrent clone is in progress. Try later.
 - Error number: 3805; Symbol: `ER_RPL_ENCRYPTION_CANNOT_ROTATE_BINLOG_MASTER_KEY`; SQLSTATE: `HY000`
Message: Cannot rotate binary log master key when 'binlog-encryption' is off.
 - Error number: 3806; Symbol: `ER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION`; SQLSTATE: `HY000`
Message: Unable to recover binary log master key, the combination of new_master_key_seqno=%u, master_key_seqno=%u and old_master_key_seqno=%u are wrong.
 - Error number: 3807; Symbol: `ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_OPERATE_KEY`; SQLSTATE: `HY000`
Message: Failed to operate binary log master key on keyring, please check if keyring is loaded. The statement had no effect: the old binary log master key is still in use, the keyring, binary and relay log files are unchanged, and the server could not start using a new binary log master key for encrypting new binary and relay log files.
 - Error number: 3808; Symbol: `ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_ROTATE_LOGS`; SQLSTATE: `HY000`
Message: Failed to rotate one or more binary or relay log files. A new binary log master key was generated and will be used to encrypt new binary and relay log files. There may still exist binary or relay log files using the previous binary log master key.
 - Error number: 3809; Symbol: `ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_REENCRYPT_LOG`; SQLSTATE: `HY000`
Message: %s. A new binary log master key was generated and will be used to encrypt new binary and relay log files. There may still exist binary or relay log files using the previous binary log master key.
 - Error number: 3810; Symbol: `ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_UNUSED_KEYS`; SQLSTATE: `HY000`
Message: Failed to remove unused binary log encryption keys from the keyring, please check if keyring is loaded. The unused binary log encryption keys may still exist in the keyring, and they will be removed upon server restart or next 'ALTER INSTANCE ROTATE BINLOG MASTER KEY' execution.
 - Error number: 3811; Symbol: `ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_AUX_KEY`; SQLSTATE: `HY000`
Message: Failed to remove auxiliary binary log encryption key from keyring, please check if keyring is loaded. The cleanup of the binary log master key rotation process did not finish as expected and the cleanup will take place upon server restart or next 'ALTER INSTANCE ROTATE BINLOG MASTER KEY' execution.

-
- Error number: 3812; Symbol: `ER_NON_BOOLEAN_EXPR_FOR_CHECK_CONSTRAINT`; SQLSTATE: `HY000`
Message: An expression of non-boolean type specified to a check constraint '%s'.
 - Error number: 3813; Symbol: `ER_COLUMN_CHECK_CONSTRAINT_REFERENCES_OTHER_COLUMN`; SQLSTATE: `HY000`
Message: Column check constraint '%s' references other column.
 - Error number: 3814; Symbol: `ER_CHECK_CONSTRAINT_NAMED_FUNCTION_IS_NOT_ALLOWED`; SQLSTATE: `HY000`
Message: An expression of a check constraint '%s' contains disallowed function: %s.
 - Error number: 3815; Symbol: `ER_CHECK_CONSTRAINT_FUNCTION_IS_NOT_ALLOWED`; SQLSTATE: `HY000`
Message: An expression of a check constraint '%s' contains disallowed function.
 - Error number: 3816; Symbol: `ER_CHECK_CONSTRAINT_VARIABLES`; SQLSTATE: `HY000`
Message: An expression of a check constraint '%s' cannot refer to a user or system variable.
 - Error number: 3817; Symbol: `ER_CHECK_CONSTRAINT_ROW_VALUE`; SQLSTATE: `HY000`
Message: Check constraint '%s' cannot refer to a row value.
 - Error number: 3818; Symbol: `ER_CHECK_CONSTRAINT_REFERS_AUTO_INCREMENT_COLUMN`; SQLSTATE: `HY000`
Message: Check constraint '%s' cannot refer to an auto-increment column.
 - Error number: 3819; Symbol: `ER_CHECK_CONSTRAINT_VIOLATED`; SQLSTATE: `HY000`
Message: Check constraint '%s' is violated.
 - Error number: 3820; Symbol: `ER_CHECK_CONSTRAINT_REFERS_UNKNOWN_COLUMN`; SQLSTATE: `HY000`
Message: Check constraint '%s' refers to non-existing column '%s'.
 - Error number: 3821; Symbol: `ER_CHECK_CONSTRAINT_NOT_FOUND`; SQLSTATE: `HY000`
Message: Check constraint '%s' is not found in the table.
 - Error number: 3822; Symbol: `ER_CHECK_CONSTRAINT_DUP_NAME`; SQLSTATE: `HY000`
Message: Duplicate check constraint name '%s'.
 - Error number: 3823; Symbol: `ER_CHECK_CONSTRAINT_CLAUSE_USING_FK_REFER_ACTION_COLUMN`; SQLSTATE: `HY000`
Message: Column '%s' cannot be used in a check constraint '%s': needed in a foreign key constraint '%s' referential action.
 - Error number: 3824; Symbol: `WARN_UNENCRYPTED_TABLE_IN_ENCRYPTED_DB`; SQLSTATE: `HY000`
Message: Creating an unencrypted table in a database with default encryption enabled.

-
- Error number: 3825; Symbol: `ER_INVALID_ENCRYPTION_REQUEST`; SQLSTATE: `HY000`
Message: Request to create %s table while using an %s tablespace.
 - Error number: 3826; Symbol: `ER_CANNOT_SET_TABLE_ENCRYPTION`; SQLSTATE: `HY000`
Message: Table encryption differ from its database default encryption, and user doesn't have enough privilege.
 - Error number: 3827; Symbol: `ER_CANNOT_SET_DATABASE_ENCRYPTION`; SQLSTATE: `HY000`
Message: Database default encryption differ from 'default_table_encryption' setting, and user doesn't have enough privilege.
 - Error number: 3828; Symbol: `ER_CANNOT_SET_TABLESPACE_ENCRYPTION`; SQLSTATE: `HY000`
Message: Tablespace encryption differ from 'default_table_encryption' setting, and user doesn't have enough privilege.
 - Error number: 3829; Symbol: `ER_TABLESPACE_CANNOT_BE_ENCRYPTED`; SQLSTATE: `HY000`
Message: This tablespace can't be encrypted, because one of table's schema has default encryption OFF and user doesn't have enough privilege.
 - Error number: 3830; Symbol: `ER_TABLESPACE_CANNOT_BE_DECRYPTED`; SQLSTATE: `HY000`
Message: This tablespace can't be decrypted, because one of table's schema has default encryption ON and user doesn't have enough privilege.
 - Error number: 3831; Symbol: `ER_TABLESPACE_TYPE_UNKNOWN`; SQLSTATE: `HY000`
Message: Cannot determine the type of the tablespace named '%s'.
 - Error number: 3832; Symbol: `ER_TARGET_TABLESPACE_UNENCRYPTED`; SQLSTATE: `HY000`
Message: Source tablespace is encrypted but target tablespace is not.
 - Error number: 3833; Symbol: `ER_CANNOT_USE_ENCRYPTION_CLAUSE`; SQLSTATE: `HY000`
Message: ENCRYPTION clause is not valid for %s tablespace.
 - Error number: 3834; Symbol: `ER_INVALID_MULTIPLE_CLAUSES`; SQLSTATE: `HY000`
Message: Multiple %s clauses
 - Error number: 3835; Symbol: `ER_UNSUPPORTED_USE_OF_GRANT_AS`; SQLSTATE: `HY000`
Message: GRANT ... AS is currently supported only for global privileges.
 - Error number: 3836; Symbol: `ER_UNKNOWN_AUTH_ID_OR_ACCESS_DENIED_FOR_GRANT_AS`; SQLSTATE: `HY000`
Message: Either some of the authorization IDs in the AS clause are invalid or the current user lacks privileges to execute the statement.
 - Error number: 3837; Symbol: `ER_DEPENDENT_BY_FUNCTIONAL_INDEX`; SQLSTATE: `HY000`
Message: Column '%s' has a functional index dependency and cannot be dropped or renamed.
 - Error number: 3838; Symbol: `ER_PLUGIN_NOT_EARLY`; SQLSTATE: `HY000`

Message: Plugin '%s' is not to be used as an "early" plugin. Don't add it to --early-plugin-load, keyring migration etc.

- Error number: 3839; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_START_SUBDIR_PATH`; SQLSTATE: `HY000`

Message: Redo log archiving start prohibits path name in 'subdir' argument

- Error number: 3840; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_START_TIMEOUT`; SQLSTATE: `HY000`

Message: Redo log archiving start timed out

- Error number: 3841; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_DIRS_INVALID`; SQLSTATE: `HY000`

Message: Server variable 'innodb_redo_log_archive_dirs' is NULL or empty

- Error number: 3842; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_LABEL_NOT_FOUND`; SQLSTATE: `HY000`

Message: Label '%s' not found in server variable 'innodb_redo_log_archive_dirs'

- Error number: 3843; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_DIR_EMPTY`; SQLSTATE: `HY000`

Message: Directory is empty after label '%s' in server variable 'innodb_redo_log_archive_dirs'

- Error number: 3844; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_NO_SUCH_DIR`; SQLSTATE: `HY000`

Message: Redo log archive directory '%s' does not exist or is not a directory

- Error number: 3845; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_DIR_CLASH`; SQLSTATE: `HY000`

Message: Redo log archive directory '%s' is in, under, or over server directory '%s' - '%s'

- Error number: 3846; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_DIR_PERMISSIONS`; SQLSTATE: `HY000`

Message: Redo log archive directory '%s' is accessible to all OS users

- Error number: 3847; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_FILE_CREATE`; SQLSTATE: `HY000`

Message: Cannot create redo log archive file '%s' (OS errno: %d - %s)

- Error number: 3848; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_ACTIVE`; SQLSTATE: `HY000`

Message: Redo log archiving has been started on '%s' - Call `innodb_redo_log_archive_stop()` first

- Error number: 3849; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_INACTIVE`; SQLSTATE: `HY000`

Message: Redo log archiving is not active

- Error number: 3850; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_FAILED`; SQLSTATE: `HY000`

Message: Redo log archiving failed: %s

- Error number: 3851; Symbol: `ER_INNODB_REDO_LOG_ARCHIVE_SESSION`; SQLSTATE: `HY000`

Message: Redo log archiving has not been started by this session

-
- Error number: 3852; Symbol: [ER_STD_REGEX_ERROR](#); SQLSTATE: HY000
Message: Regex error: %s in function %s.
 - Error number: 3853; Symbol: [ER_INVALID_JSON_TYPE](#); SQLSTATE: 22032
Message: Invalid JSON type in argument %u to function %s; an %s is required.
 - Error number: 3854; Symbol: [ER_CANNOT_CONVERT_STRING](#); SQLSTATE: HY000
Message: Cannot convert string '%s' from %s to %s
 - Error number: 3855; Symbol: [ER_DEPENDENT_BY_PARTITION_FUNC](#); SQLSTATE: HY000
Message: Column '%s' has a partitioning function dependency and cannot be dropped or renamed.
 - Error number: 3856; Symbol: [ER_WARN_DEPRECATED_FLOAT_AUTO_INCREMENT](#); SQLSTATE: HY000
Message: AUTO_INCREMENT support for FLOAT/DOUBLE columns is deprecated and will be removed in a future release. Consider removing AUTO_INCREMENT from column '%s'.
 - Error number: 3857; Symbol: [ER_RPL_CANT_STOP_REPLICA_WHILE_LOCKED_BACKUP](#); SQLSTATE: HY000
Message: Cannot stop the replica SQL thread while the instance is locked for backup. Try running `UNLOCK INSTANCE` first.
 - Error number: 3858; Symbol: [ER_WARN_DEPRECATED_FLOAT_DIGITS](#); SQLSTATE: HY000
Message: Specifying number of digits for floating point data types is deprecated and will be removed in a future release.
 - Error number: 3859; Symbol: [ER_WARN_DEPRECATED_FLOAT_UNSIGNED](#); SQLSTATE: HY000
Message: UNSIGNED for decimal and floating point data types is deprecated and support for it will be removed in a future release.
 - Error number: 3860; Symbol: [ER_WARN_DEPRECATED_INTEGER_DISPLAY_WIDTH](#); SQLSTATE: HY000
Message: Integer display width is deprecated and will be removed in a future release.
 - Error number: 3861; Symbol: [ER_WARN_DEPRECATED_ZEROFILL](#); SQLSTATE: HY000
Message: The ZEROFILL attribute is deprecated and will be removed in a future release. Use the LPAD function to zero-pad numbers, or store the formatted numbers in a CHAR column.
 - Error number: 3862; Symbol: [ER_CLONE_DONOR](#); SQLSTATE: HY000
Message: Clone Donor Error: %s.
 - Error number: 3863; Symbol: [ER_CLONE_PROTOCOL](#); SQLSTATE: HY000
Message: Clone received unexpected response from Donor : %s.
 - Error number: 3864; Symbol: [ER_CLONE_DONOR_VERSION](#); SQLSTATE: HY000
Message: Clone Donor MySQL version: %s is different from Recipient MySQL version %s.
 - Error number: 3865; Symbol: [ER_CLONE_OS](#); SQLSTATE: HY000

Message: Clone Donor OS: %s is different from Recipient OS: %s.

- Error number: 3866; Symbol: ER_CLONE_PLATFORM; SQLSTATE: HY000

Message: Clone Donor platform: %s is different from Recipient platform: %s.

- Error number: 3867; Symbol: ER_CLONE_CHARSET; SQLSTATE: HY000

Message: Clone Donor collation: %s is unavailable in Recipient.

- Error number: 3868; Symbol: ER_CLONE_CONFIG; SQLSTATE: HY000

Message: Clone Configuration %s: Donor value: %s is different from Recipient value: %s.

- Error number: 3869; Symbol: ER_CLONE_SYS_CONFIG; SQLSTATE: HY000

Message: Clone system configuration: %s

- Error number: 3870; Symbol: ER_CLONE_PLUGIN_MATCH; SQLSTATE: HY000

Message: Clone Donor plugin %s is not active in Recipient.

- Error number: 3871; Symbol: ER_CLONE_LOOPBACK; SQLSTATE: HY000

Message: Clone cannot use loop back connection while cloning into current data directory.

- Error number: 3872; Symbol: ER_CLONE_ENCRYPTION; SQLSTATE: HY000

Message: Clone needs SSL connection for encrypted table.

- Error number: 3873; Symbol: ER_CLONE_DISK_SPACE; SQLSTATE: HY000

Message: Clone estimated database size is %s. Available space %s is not enough.

- Error number: 3874; Symbol: ER_CLONE_IN_PROGRESS; SQLSTATE: HY000

Message: Concurrent clone in progress. Please try after clone is complete.

- Error number: 3875; Symbol: ER_CLONE_DISALLOWED; SQLSTATE: HY000

Message: The clone operation cannot be executed when %s.

- Error number: 3876; Symbol: ER_CANNOT_GRANT_ROLES_TO_ANONYMOUS_USER; SQLSTATE: HY000

Message: Cannot grant roles to an anonymous user.

- Error number: 3877; Symbol: ER_SECONDARY_ENGINE_PLUGIN; SQLSTATE: HY000

Message: %s

- Error number: 3878; Symbol: ER_SECOND_PASSWORD_CANNOT_BE_EMPTY; SQLSTATE: HY000

Message: Empty password can not be retained as second password for user '%s'@'%s'.

- Error number: 3879; Symbol: ER_DB_ACCESS_DENIED; SQLSTATE: HY000

Message: Access denied for AuthId `%s`@`%s` to database '%s'.

- Error number: 3880; Symbol: ER_DA_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLES; SQLSTATE: HY000

-
- Message: Cannot set mandatory_roles: AuthId `'%s'`@`'%s'` has '%s' privilege.
- Error number: 3881; Symbol: [ER_DA_RPL_GTID_TABLE_CANNOT_OPEN](#); SQLSTATE: HY000
Message: Gtid table is not ready to be used. Table '%s.%s' cannot be opened.
 - Error number: 3882; Symbol: [ER_GEOMETRY_IN_UNKNOWN_LENGTH_UNIT](#); SQLSTATE: SU001
Message: The geometry passed to function %s is in SRID 0, which doesn't specify a length unit. Can't convert to '%s'.
 - Error number: 3883; Symbol: [ER_DA_PLUGIN_INSTALL_ERROR](#); SQLSTATE: HY000
Message: Error installing plugin '%s': %s
 - Error number: 3884; Symbol: [ER_NO_SESSION_TEMP](#); SQLSTATE: HY000
Message: Storage engine could not allocate temporary tablespace for this session.
 - Error number: 3885; Symbol: [ER_DA_UNKNOWN_ERROR_NUMBER](#); SQLSTATE: HY000
Message: Got unknown error: %d
 - Error number: 3886; Symbol: [ER_COLUMN_CHANGE_SIZE](#); SQLSTATE: HY000
Message: Could not change column '%s' of table '%s'. The resulting size of index '%s' would exceed the max key length of %d bytes.
 - Error number: 3887; Symbol: [ER_REGEX_INVALID_CAPTURE_GROUP_NAME](#); SQLSTATE: HY000
Message: A capture group has an invalid name.
 - Error number: 3888; Symbol: [ER_DA_SSL_LIBRARY_ERROR](#); SQLSTATE: HY000
Message: Failed to set up SSL because of the following SSL library error: %s
 - Error number: 3889; Symbol: [ER_SECONDARY_ENGINE](#); SQLSTATE: HY000
Message: Secondary engine operation failed. %s.
 - Error number: 3890; Symbol: [ER_SECONDARY_ENGINE_DDL](#); SQLSTATE: HY000
Message: DDLs on a table with a secondary engine defined are not allowed.
 - Error number: 3891; Symbol: [ER_INCORRECT_CURRENT_PASSWORD](#); SQLSTATE: HY000
Message: Incorrect current password. Specify the correct password which has to be replaced.
 - Error number: 3892; Symbol: [ER_MISSING_CURRENT_PASSWORD](#); SQLSTATE: HY000
Message: Current password needs to be specified in the REPLACE clause in order to change it.
 - Error number: 3893; Symbol: [ER_CURRENT_PASSWORD_NOT_REQUIRED](#); SQLSTATE: HY000
Message: Do not specify the current password while changing it for other users.
 - Error number: 3894; Symbol: [ER_PASSWORD_CANNOT_BE_RETAINED_ON_PLUGIN_CHANGE](#); SQLSTATE: HY000

Message: Current password can not be retained for user '%s'@'%s' because authentication plugin is being changed.

- Error number: 3895; Symbol: [ER_CURRENT_PASSWORD_CANNOT_BE_RETAINED](#); SQLSTATE: HY000

Message: Current password can not be retained for user '%s'@'%s' because new password is empty.

- Error number: 3896; Symbol: [ER_PARTIAL_REVOKES_EXIST](#); SQLSTATE: HY000

Message: At least one partial revoke exists on a database. The system variable '@@partial_revokes' must be set to ON.

- Error number: 3897; Symbol: [ER_CANNOT_GRANT_SYSTEM_PRIV_TO_MANDATORY_ROLE](#); SQLSTATE: HY000

Message: AuthId '%s'@'%s' is set as mandatory_roles. Cannot grant the '%s' privilege.

- Error number: 3898; Symbol: [ER_XA_REPLICATION_FILTERS](#); SQLSTATE: HY000

Message: The use of replication filters with XA transactions is not supported, and can lead to an undefined state in the replica.

- Error number: 3899; Symbol: [ER_UNSUPPORTED_SQL_MODE](#); SQLSTATE: HY000

Message: sql_mode=0x%08x is not supported.

- Error number: 3900; Symbol: [ER_REGEX_INVALID_FLAG](#); SQLSTATE: HY000

Message: Invalid match mode flag in regular expression.

- Error number: 3901; Symbol: [ER_PARTIAL_REVOKE_AND_DB_GRANT_BOTH_EXISTS](#); SQLSTATE: HY000

Message: '%s' privilege for database '%s' exists both as partial revoke and mysql.db simultaneously. It could mean that the 'mysql' schema is corrupted.

- Error number: 3902; Symbol: [ER_UNIT_NOT_FOUND](#); SQLSTATE: SU001

Message: There's no unit of measure named '%s'.

- Error number: 3903; Symbol: [ER_INVALID_JSON_VALUE_FOR_FUNC_INDEX](#); SQLSTATE: 22018

Message: Invalid JSON value for CAST for functional index '%s'.

- Error number: 3904; Symbol: [ER_JSON_VALUE_OUT_OF_RANGE_FOR_FUNC_INDEX](#); SQLSTATE: 22003

Message: Out of range JSON value for CAST for functional index '%s'.

- Error number: 3905; Symbol: [ER_EXCEEDED_MV_KEYS_NUM](#); SQLSTATE: HY000

Message: Exceeded max number of values per record for multi-valued index '%s' by %u value(s).

- Error number: 3906; Symbol: [ER_EXCEEDED_MV_KEYS_SPACE](#); SQLSTATE: HY000

Message: Exceeded max total length of values per record for multi-valued index '%s' by %u bytes.

- Error number: 3907; Symbol: [ER_FUNCTIONAL_INDEX_DATA_IS_TOO_LONG](#); SQLSTATE: 22001

-
- Message: Data too long for functional index '%s'.
- Error number: 3908; Symbol: ER_WRONG_MVI_VALUE; SQLSTATE: HY000
Message: Cannot store an array or an object in a scalar key part of the index '%s'.
 - Error number: 3909; Symbol: ER_WARN_FUNC_INDEX_NOT_APPLICABLE; SQLSTATE: HY000
Message: Cannot use functional index '%s' due to type or collation conversion.
 - Error number: 3910; Symbol: ER_GRP_RPL_UDF_ERROR; SQLSTATE: HY000
Message: The function '%s' failed. %s
 - Error number: 3911; Symbol: ER_UPDATE_GTID_PURGED_WITH_GR; SQLSTATE: HY000
Message: Cannot update GTID_PURGED with the Group Replication plugin running
 - Error number: 3912; Symbol: ER_GROUPING_ON_TIMESTAMP_IN_DST; SQLSTATE: HY000
Message: Grouping on temporal is non-deterministic for timezones having DST. Please consider switching to UTC for this query.
 - Error number: 3913; Symbol: ER_TABLE_NAME_CAUSES_TOO_LONG_PATH; SQLSTATE: HY000
Message: Long database name and identifier for object resulted in a path length too long for table '%s'. Please check the path limit for your OS.
 - Error number: 3914; Symbol: ER_AUDIT_LOG_INSUFFICIENT_PRIVILEGE; SQLSTATE: HY000
Message: Request ignored for '%s'@'%s'. Role needed to perform operation: '%s'
 - Error number: 3916; Symbol: ER_DA_GRP_RPL_STARTED_AUTO_REJOIN; SQLSTATE: HY000
Message: Started auto-rejoin procedure attempt %lu of %lu
 - Error number: 3917; Symbol: ER_SYSVAR_CHANGE_DURING_QUERY; SQLSTATE: HY000
Message: A plugin was loaded or unloaded during a query, a system variable table was changed.
 - Error number: 3918; Symbol: ER_GLOBSTAT_CHANGE_DURING_QUERY; SQLSTATE: HY000
Message: A plugin was loaded or unloaded during a query, a global status variable was changed.
 - Error number: 3919; Symbol: ER_GRP_RPL_MESSAGE_SERVICE_INIT_FAILURE; SQLSTATE: HY000
Message: The START GROUP_REPLICATION command failed to start its message service.
 - Error number: 3920; Symbol: ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM_CLIENT; SQLSTATE: HY000
Message: Invalid SOURCE_COMPRESSION_ALGORITHMS '%s' for channel '%s'.
 - Error number: 3921; Symbol: ER_CHANGE_SOURCE_WRONG_COMPRESSION_LEVEL_CLIENT; SQLSTATE: HY000
Message: Invalid SOURCE_ZSTD_COMPRESSION_LEVEL %u for channel '%s'.
 - Error number: 3922; Symbol: ER_WRONG_COMPRESSION_ALGORITHM_CLIENT; SQLSTATE: HY000

Message: Invalid compression algorithm '%s'.

- Error number: 3923; Symbol: [ER_WRONG_COMPRESSION_LEVEL_CLIENT](#); SQLSTATE: HY000

Message: Invalid zstd compression level for algorithm '%s'.

- Error number: 3924; Symbol: [ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM_LIST_CLIENT](#); SQLSTATE: HY000

Message: Specified compression algorithm list '%s' exceeds total count of 3 for channel '%s'.

- Error number: 3925; Symbol: [ER_CLIENT_PRIVILEGE_CHECKS_USER_CANNOT_BE_ANONYMOUS](#); SQLSTATE: HY000

Message: PRIVILEGE_CHECKS_USER for replication channel '%s' was set to ``@`%s`, but anonymous users are disallowed for PRIVILEGE_CHECKS_USER.

- Error number: 3926; Symbol: [ER_CLIENT_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST](#); SQLSTATE: HY000

Message: PRIVILEGE_CHECKS_USER for replication channel '%s' was set to `%s`@`%s`, but this is not an existing user.

- Error number: 3927; Symbol: [ER_CLIENT_PRIVILEGE_CHECKS_USER_CORRUPT](#); SQLSTATE: HY000

Message: Invalid, corrupted PRIVILEGE_CHECKS_USER was found in the replication configuration repository for channel '%s'. Use CHANGE REPLICATION SOURCE TO PRIVILEGE_CHECKS_USER to correct the configuration.

- Error number: 3928; Symbol: [ER_CLIENT_PRIVILEGE_CHECKS_USER_NEEDS_RPL_APPLIER_PRIV](#); SQLSTATE: HY000

Message: PRIVILEGE_CHECKS_USER for replication channel '%s' was set to `%s`@`%s`, but this user does not have REPLICATION_APPLIER privilege.

- Error number: 3929; Symbol: [ER_WARN_DA_PRIVILEGE_NOT_REGISTERED](#); SQLSTATE: HY000

Message: Dynamic privilege '%s' is not registered with the server.

- Error number: 3930; Symbol: [ER_CLIENT_KEYRING_UDF_KEY_INVALID](#); SQLSTATE: HY000

Message: Function '%s' failed because key is invalid.

- Error number: 3931; Symbol: [ER_CLIENT_KEYRING_UDF_KEY_TYPE_INVALID](#); SQLSTATE: HY000

Message: Function '%s' failed because key type is invalid.

- Error number: 3932; Symbol: [ER_CLIENT_KEYRING_UDF_KEY_TOO_LONG](#); SQLSTATE: HY000

Message: Function '%s' failed because key length is too long.

- Error number: 3933; Symbol: [ER_CLIENT_KEYRING_UDF_KEY_TYPE_TOO_LONG](#); SQLSTATE: HY000

Message: Function '%s' failed because key type is too long.

- Error number: 3934; Symbol: [ER_JSON_SCHEMA_VALIDATION_ERROR_WITH_DETAILED_REPORT](#); SQLSTATE: HY000

Message: %s.

- Error number: [3935](#); Symbol: [ER_DA_UDF_INVALID_CHARSET_SPECIFIED](#); SQLSTATE: [HY000](#)

Message: Invalid character set '%s' was specified. It must be either character set name or collation name as supported by server.

- Error number: [3936](#); Symbol: [ER_DA_UDF_INVALID_CHARSET](#); SQLSTATE: [HY000](#)

Message: Invalid character set '%s' was specified. It must be a character set name as supported by server.

- Error number: [3937](#); Symbol: [ER_DA_UDF_INVALID_COLLATION](#); SQLSTATE: [HY000](#)

Message: Invalid collation '%s' was specified. It must be a collation name as supported by server.

- Error number: [3938](#); Symbol: [ER_DA_UDF_INVALID_EXTENSION_ARGUMENT_TYPE](#); SQLSTATE: [HY000](#)

Message: Invalid extension argument type '%s' was specified. Refer the MySQL manual for the valid UDF extension arguments type.

- Error number: [3939](#); Symbol: [ER_MULTIPLE_CONSTRAINTS_WITH_SAME_NAME](#); SQLSTATE: [HY000](#)

Message: Table has multiple constraints with the name '%s'. Please use constraint specific '%s' clause.

- Error number: [3940](#); Symbol: [ER_CONSTRAINT_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Constraint '%s' does not exist.

- Error number: [3941](#); Symbol: [ER_ALTER_CONSTRAINT_ENFORCEMENT_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: Altering constraint enforcement is not supported for the constraint '%s'. Enforcement state alter is not supported for the PRIMARY, UNIQUE and FOREIGN KEY type constraints.

- Error number: [3942](#); Symbol: [ER_TABLE_VALUE_CONSTRUCTOR_MUST_HAVE_COLUMNS](#); SQLSTATE: [HY000](#)

Message: Each row of a VALUES clause must have at least one column, unless when used as source in an INSERT statement.

- Error number: [3943](#); Symbol: [ER_TABLE_VALUE_CONSTRUCTOR_CANNOT_HAVE_DEFAULT](#); SQLSTATE: [HY000](#)

Message: A VALUES clause cannot use DEFAULT values, unless used as a source in an INSERT statement.

- Error number: [3944](#); Symbol: [ER_CLIENT_QUERY_FAILURE_INVALID_NON_ROW_FORMAT](#); SQLSTATE: [HY000](#)

Message: The query does not comply with variable `require_row_format` restrictions.

- Error number: [3945](#); Symbol: [ER_REQUIRE_ROW_FORMAT_INVALID_VALUE](#); SQLSTATE: [HY000](#)

Message: The requested value %s is invalid for `REQUIRE_ROW_FORMAT`, must be either 0 or 1.

- Error number: [3946](#); Symbol: [ER_FAILED_TO_DETERMINE_IF_ROLE_IS_MANDATORY](#); SQLSTATE: [HY000](#)

Message: Failed to acquire lock on user management service, unable to determine if role `'%s'@'%s'` is mandatory

- Error number: 3947; Symbol: [ER_FAILED_TO_FETCH_MANDATORY_ROLE_LIST](#); SQLSTATE: HY000

Message: Failed to acquire lock on user management service, unable to fetch mandatory role list

- Error number: 3948; Symbol: [ER_CLIENT_LOCAL_FILES_DISABLED](#); SQLSTATE: 42000

Message: Loading local data is disabled; this must be enabled on both the client and server sides

- Error number: 3949; Symbol: [ER_IMP_INCOMPATIBLE_CFG_VERSION](#); SQLSTATE: HY000

Message: Failed to import %s because the CFG file version (%u) is not compatible with the current version (%u)

- Error number: 3950; Symbol: [ER_DA_OOM](#); SQLSTATE: HY000

Message: Out of memory

- Error number: 3951; Symbol: [ER_DA_UDF_INVALID_ARGUMENT_TO_SET_CHARSET](#); SQLSTATE: HY000

Message: Character set can be set only for the UDF argument type STRING.

- Error number: 3952; Symbol: [ER_DA_UDF_INVALID_RETURN_TYPE_TO_SET_CHARSET](#); SQLSTATE: HY000

Message: Character set can be set only for the UDF RETURN type STRING.

- Error number: 3953; Symbol: [ER_MULTIPLE_INTO_CLAUSES](#); SQLSTATE: HY000

Message: Multiple INTO clauses in one query block.

- Error number: 3954; Symbol: [ER_MISPLACED_INTO](#); SQLSTATE: HY000

Message: Misplaced INTO clause, INTO is not allowed inside subqueries, and must be placed at end of UNION clauses.

- Error number: 3955; Symbol: [ER_USER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED_BY_PASSWORD_LOCK](#); SQLSTATE: HY000

Message: Access denied for user '%s'@'%s'. Account is blocked for %s day(s) (%s day(s) remaining) due to %u consecutive failed logins.

- Error number: 3956; Symbol: [ER_WARN_DEPRECATED_YEAR_UNSIGNED](#); SQLSTATE: HY000

Message: UNSIGNED for the YEAR data type is deprecated and support for it will be removed in a future release.

- Error number: 3957; Symbol: [ER_CLONE_NETWORK_PACKET](#); SQLSTATE: HY000

Message: Clone needs max_allowed_packet value to be %u or more. Current value is %u

- Error number: 3958; Symbol: [ER_SDI_OPERATION_FAILED_MISSING_RECORD](#); SQLSTATE: HY000

Message: Failed to %s sdi for %s.%s in %s due to missing record.

-
- Error number: [3959](#); Symbol: [ER_DEPENDENT_BY_CHECK_CONSTRAINT](#); SQLSTATE: [HY000](#)
Message: Check constraint '%s' uses column '%s', hence column cannot be dropped or renamed.
 - Error number: [3960](#); Symbol: [ER_GRP_OPERATION_NOT_ALLOWED_GR_MUST_STOP](#); SQLSTATE: [HY000](#)
Message: This operation cannot be performed while Group Replication is running; run STOP GROUP_REPLICATION first
 - Error number: [3961](#); Symbol: [ER_WARN_DEPRECATED_JSON_TABLE_ON_ERROR_ON_EMPTY](#); SQLSTATE: [HY000](#)
Message: Specifying an ON EMPTY clause after the ON ERROR clause in a JSON_TABLE column definition is deprecated syntax and will be removed in a future release. Specify ON EMPTY before ON ERROR instead.
 - Error number: [3962](#); Symbol: [ER_WARN_DEPRECATED_INNER_INTO](#); SQLSTATE: [HY000](#)
Message: The INTO clause is deprecated inside query blocks of query expressions and will be removed in a future release. Please move the INTO clause to the end of statement instead.
 - Error number: [3963](#); Symbol: [ER_WARN_DEPRECATED_VALUES_FUNCTION_ALWAYS_NULL](#); SQLSTATE: [HY000](#)
Message: The VALUES function is deprecated and will be removed in a future release. It always returns NULL in this context. If you meant to access a value from the VALUES clause of the INSERT statement, consider using an alias (INSERT INTO ... VALUES (...) AS alias) and reference alias.col instead of VALUES(col) in the ON DUPLICATE KEY UPDATE clause.
 - Error number: [3964](#); Symbol: [ER_WARN_DEPRECATED_SQL_CALC_FOUND_ROWS](#); SQLSTATE: [HY000](#)
Message: SQL_CALC_FOUND_ROWS is deprecated and will be removed in a future release. Consider using two separate queries instead.
 - Error number: [3965](#); Symbol: [ER_WARN_DEPRECATED_FOUND_ROWS](#); SQLSTATE: [HY000](#)
Message: FOUND_ROWS() is deprecated and will be removed in a future release. Consider using COUNT(*) instead.
 - Error number: [3966](#); Symbol: [ER_MISSING_JSON_VALUE](#); SQLSTATE: [22035](#)
Message: No value was found by '%s' on the specified path.
 - Error number: [3967](#); Symbol: [ER_MULTIPLE_JSON_VALUES](#); SQLSTATE: [22034](#)
Message: More than one value was found by '%s' on the specified path.
 - Error number: [3968](#); Symbol: [ER_HOSTNAME_TOO_LONG](#); SQLSTATE: [HY000](#)
Message: Hostname cannot be longer than %d characters.
 - Error number: [3970](#); Symbol: [ER_GROUP_REPLICATION_USER_EMPTY_MSG](#); SQLSTATE: [HY000](#)
Message: The START GROUP_REPLICATION command failed since the username provided for recovery channel is empty.
 - Error number: [3971](#); Symbol: [ER_GROUP_REPLICATION_USER_MANDATORY_MSG](#); SQLSTATE: [HY000](#)

Message: The START GROUP_REPLICATION command failed since the USER option was not provided with PASSWORD for recovery channel.

- Error number: 3972; Symbol: ER_GROUP_REPLICATION_PASSWORD_LENGTH; SQLSTATE: HY000

Message: The START GROUP_REPLICATION command failed since the password provided for the recovery channel exceeds the maximum length of 32 characters.

- Error number: 3973; Symbol: ER_SUBQUERY_TRANSFORM_REJECTED; SQLSTATE: HY000

Message: Statement requires a transform of a subquery to a non-SET operation (like IN2EXISTS, or subquery-to-LATERAL-derived-table). This is not allowed with optimizer switch 'subquery_to_derived' on.

- Error number: 3974; Symbol: ER_DA_GRP_RPL_RECOVERY_ENDPOINT_FORMAT; SQLSTATE: HY000

Message: Invalid input value for recovery socket endpoints '%s'. Please, provide a valid, comma separated, list of endpoints (IP:port).

- Error number: 3975; Symbol: ER_DA_GRP_RPL_RECOVERY_ENDPOINT_INVALID; SQLSTATE: HY000

Message: The server is not listening on endpoint '%s'. Only endpoints that the server is listening on are valid recovery endpoints.

- Error number: 3976; Symbol: ER_WRONG_VALUE_FOR_VAR_PLUS_ACTIONABLE_PART; SQLSTATE: HY000

Message: Variable '%s' cannot be set to the value of '%s'. %s

- Error number: 3977; Symbol: ER_STATEMENT_NOT_ALLOWED_AFTER_START_TRANSACTION; SQLSTATE: HY000

Message: Only BINLOG INSERT, COMMIT and ROLLBACK statements are allowed after CREATE TABLE with START TRANSACTION statement.

- Error number: 3978; Symbol: ER_FOREIGN_KEY_WITH_ATOMIC_CREATE_SELECT; SQLSTATE: HY000

Message: Foreign key creation is not allowed with CREATE TABLE as SELECT and CREATE TABLE with START TRANSACTION statement.

- Error number: 3979; Symbol: ER_NOT_ALLOWED_WITH_START_TRANSACTION; SQLSTATE: HY000

Message: START TRANSACTION clause cannot be used %s

- Error number: 3980; Symbol: ER_INVALID_JSON_ATTRIBUTE; SQLSTATE: HY000

Message: Invalid json attribute, error: "%s" at pos %u: '%s'

- Error number: 3981; Symbol: ER_ENGINE_ATTRIBUTE_NOT_SUPPORTED; SQLSTATE: HY000

Message: Storage engine '%s' does not support ENGINE_ATTRIBUTE.

- Error number: 3982; Symbol: ER_INVALID_USER_ATTRIBUTE_JSON; SQLSTATE: HY000

Message: The user attribute must be a valid JSON object

- Error number: 3983; Symbol: ER_INNOODB_REDO_DISABLED; SQLSTATE: HY000

Message: Cannot perform operation as InnoDB redo logging is disabled. Please retry after enabling redo log with ALTER INSTANCE

- Error number: 3984; Symbol: ER_INNODB_REDO_ARCHIVING_ENABLED; SQLSTATE: HY000

Message: Cannot perform operation as InnoDB is archiving redo log. Please retry after stopping redo archive by invoking innodb_redo_log_archive_stop()

- Error number: 3985; Symbol: ER_MDL_OUT_OF_RESOURCES; SQLSTATE: HY000

Message: Not enough resources to complete lock request.

- Error number: 3986; Symbol: ER_IMPLICIT_COMPARISON_FOR_JSON; SQLSTATE: HY000

Message: Evaluating a JSON value in SQL boolean context does an implicit comparison against JSON integer 0; if this is not what you want, consider converting JSON to a SQL numeric type with JSON_VALUE RETURNING

- Error number: 3987; Symbol: ER_FUNCTION_DOES_NOT_SUPPORT_CHARACTER_SET; SQLSTATE: HY000

Message: The function %s does not support the character set '%s'.

- Error number: 3988; Symbol: ER_IMPOSSIBLE_STRING_CONVERSION; SQLSTATE: HY000

Message: Conversion from collation %s into %s impossible for %s

- Error number: 3989; Symbol: ER_SCHEMA_READ_ONLY; SQLSTATE: HY000

Message: Schema '%s' is in read only mode.

- Error number: 3990; Symbol: ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF; SQLSTATE: HY000

Message: Failed to enable Asynchronous Replication Connection Failover feature. The CHANGE REPLICATION SOURCE TO SOURCE_CONNECTION_AUTO_FAILOVER = 1 can only be set when @@GLOBAL.GTID_MODE = ON.

- Error number: 3991; Symbol: ER_RPL_ASYNC_RECONNECT_AUTO_POSITION_OFF; SQLSTATE: HY000

Message: Failed to enable Asynchronous Replication Connection Failover feature. The CHANGE REPLICATION SOURCE TO SOURCE_CONNECTION_AUTO_FAILOVER = 1 can only be set when SOURCE_AUTO_POSITION option of CHANGE REPLICATION SOURCE TO is enabled.

- Error number: 3992; Symbol: ER_DISABLE_GTID_MODE_REQUIRES_ASYNC_RECONNECT_OFF; SQLSTATE: HY000

Message: The @@GLOBAL.GTID_MODE = %s cannot be executed because Asynchronous Replication Connection Failover is enabled i.e. CHANGE REPLICATION SOURCE TO SOURCE_CONNECTION_AUTO_FAILOVER = 1.

- Error number: 3993; Symbol: ER_DISABLE_AUTO_POSITION_REQUIRES_ASYNC_RECONNECT_OFF; SQLSTATE: HY000

Message: CHANGE REPLICATION SOURCE TO SOURCE_AUTO_POSITION = 0 cannot be executed because Asynchronous Replication Connection Failover is enabled i.e. CHANGE REPLICATION SOURCE TO SOURCE_CONNECTION_AUTO_FAILOVER = 1.

-
- Error number: [3994](#); Symbol: [ER_INVALID_PARAMETER_USE](#); SQLSTATE: [HY000](#)
Message: Invalid use of parameters in '%s'
 - Error number: [3995](#); Symbol: [ER_CHARACTER_SET_MISMATCH](#); SQLSTATE: [HY000](#)
Message: Character set '%s' cannot be used in conjunction with '%s' in call to %s.
 - Error number: [3996](#); Symbol: [ER_WARN_VAR_VALUE_CHANGE_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)
Message: Changing %s not supported on this platform. Falling back to the default.
 - Error number: [3997](#); Symbol: [ER_INVALID_TIME_ZONE_INTERVAL](#); SQLSTATE: [HY000](#)
Message: Invalid time zone interval: '%s'
 - Error number: [3998](#); Symbol: [ER_INVALID_CAST](#); SQLSTATE: [HY000](#)
Message: Cannot cast value to %s.
 - Error number: [3999](#); Symbol: [ER_HYPERGRAPH_NOT_SUPPORTED_YET](#); SQLSTATE: [42000](#)
Message: The hypergraph optimizer does not yet support '%s'
 - Error number: [4000](#); Symbol: [ER_WARN_HYPERGRAPH_EXPERIMENTAL](#); SQLSTATE: [HY000](#)
Message: The hypergraph optimizer is highly experimental and is meant for testing only. Do not enable it unless you are a MySQL developer.
 - Error number: [4001](#); Symbol: [ER_DA_NO_ERROR_LOG_PARSER_CONFIGURED](#); SQLSTATE: [HY000](#)
Message: None of the log-sinks selected with --log-error-services=... provides a log-parser. The server will not be able to make the previous runs' error-logs available in performance_schema.error_log.
 - Error number: [4002](#); Symbol: [ER_DA_ERROR_LOG_TABLE_DISABLED](#); SQLSTATE: [HY000](#)
Message: None of the log-sinks selected in @@global.log_error_services supports writing to the performance schema. The server will not be able to make the current runs' error events available in performance_schema.error_log. To change this, add a log-sink that supports the performance schema to @@global.log_error_services.
 - Error number: [4003](#); Symbol: [ER_DA_ERROR_LOG_MULTIPLE_FILTERS](#); SQLSTATE: [HY000](#)
Message: @@global.log_error_services lists more than one log-filter service. This is discouraged as it will make it hard to understand which rule in which filter affected a log-event.
 - Error number: [4004](#); Symbol: [ER_DA_CANT_OPEN_ERROR_LOG](#); SQLSTATE: [HY000](#)
Message: Could not open file '%s' for error logging%s%s
 - Error number: [4005](#); Symbol: [ER_USER_REFERENCED_AS_DEFINER](#); SQLSTATE: [HY000](#)
Message: User %s is referenced as a definer account in %s.
 - Error number: [4006](#); Symbol: [ER_CANNOT_USER_REFERENCED_AS_DEFINER](#); SQLSTATE: [HY000](#)
Message: Operation %s failed for %s as it is referenced as a definer account in %s.
 - Error number: [4007](#); Symbol: [ER_REGEX_NUMBER_TOO_BIG](#); SQLSTATE: [HY000](#)

Message: Decimal number in regular expression is too large.

- Error number: 4008; Symbol: `ER_SPVAR_NONINTEGER_TYPE`; SQLSTATE: `HY000`

Message: The variable "%s" has a non-integer based type

- Error number: 4009; Symbol: `WARN_UNSUPPORTED_ACL_TABLES_READ`; SQLSTATE: `HY000`

Message: Reads with serializable isolation/SELECT FOR SHARE are not supported for ACL tables.

- Error number: 4010; Symbol: `ER_BINLOG_UNSAFE_ACL_TABLE_READ_IN_DML_DDL`; SQLSTATE: `HY000`

Message: The statement is unsafe because it updates a table depending on ACL table read operation. As storage engine row locks are skipped for ACL table, it may not have same effect on source and replica.

- Error number: 4011; Symbol: `ER_STOP_REPLICA_MONITOR_IO_THREAD_TIMEOUT`; SQLSTATE: `HY000`

Message: STOP REPLICA command execution is incomplete: Replica Monitor thread got the stop signal, thread is busy, Monitor thread will stop once the current task is complete.

- Error number: 4012; Symbol: `ER_STARTING_REPLICA_MONITOR_IO_THREAD`; SQLSTATE: `HY000`

Message: The Replica Monitor thread failed to start.

- Error number: 4013; Symbol: `ER_CANT_USE_ANONYMOUS_TO_GTID_WITH_GTID_MODE_NOT_ON`; SQLSTATE: `HY000`

Message: Replication cannot start%s with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>` as this server uses `@@GLOBAL.GTID_MODE <> ON`.

- Error number: 4014; Symbol: `ER_CANT_COMBINE_ANONYMOUS_TO_GTID_AND_AUTOPOSITION`; SQLSTATE: `HY000`

Message: The options `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>` and `SOURCE_AUTO_POSITION = 1` cannot be used together.

- Error number: 4015; Symbol: `ER_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_REQUIRES_GTID_MODE_ON`; SQLSTATE: `HY000`

Message: CHANGE REPLICATION SOURCE TO `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>` cannot be executed because `@@GLOBAL.GTID_MODE <> ON`.

- Error number: 4016; Symbol: `ER_SQL_REPLICA_SKIP_COUNTER_USED_WITH_GTID_MODE_ON`; SQLSTATE: `HY000`

Message: The value of `sql_replica_skip_counter` will only take effect for channels running with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS <> OFF`.

-
- Error number: 4017; Symbol: [ER_USING_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_AS_LOCAL_OR_UUID](#); SQLSTATE: HY000

Message: Using ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS creates limitations on the replication topology - you cannot fail over between downstream and upstream servers. Only use this option if it is not possible to enable GTIDs on the source, for instance, because of lack of permissions. If possible, use the procedure for enabling GTID transactions online instead, as described in the documentation.
 - Error number: 4019; Symbol: [ER_CANT_SET_SQL_AFTER_OR_BEFORE_GTIDS_WITH_ANONYMOUS_TO_GTID](#); SQLSTATE: HY000

Message: The SQL_AFTER_GTIDS or SQL_BEFORE_GTIDS clauses for START REPLICA cannot be used when the replication channel is configured with ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>.
 - Error number: 4020; Symbol: [ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NAME](#); SQLSTATE: HY000

Message: Replication '%s' is configured with ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = <UUID> where the UUID value is equal to the group_replication_group_name
 - Error number: 4021; Symbol: [ER_CANT_USE_SAME_UUID_AS_GROUP_NAME](#); SQLSTATE: HY000

Message: CHANGE REPLICATION SOURCE TO ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = <UUID> cannot be executed because the UUID value is equal to the group_replication_group_name.
 - Error number: 4022; Symbol: [ER_GRP_RPL_RECOVERY_CHANNEL_STILL_RUNNING](#); SQLSTATE: HY000

Message: The group_replication_recovery channel is still running, most likely it is waiting for a database/table lock, which is preventing the channel from stopping. Please check database/table locks, including the ones created by backup tools.
 - Error number: 4023; Symbol: [ER_INNOODB_INVALID_AUTOEXTEND_SIZE_VALUE](#); SQLSTATE: HY000

Message: AUTOEXTEND_SIZE should be a multiple of %uM
 - Error number: 4024; Symbol: [ER_INNOODB_INCOMPATIBLE_WITH_TABLESPACE](#); SQLSTATE: HY000

Message: InnoDB: "%s" not allowed with general tablespaces
 - Error number: 4025; Symbol: [ER_INNOODB_AUTOEXTEND_SIZE_OUT_OF_RANGE](#); SQLSTATE: HY000

Message: AUTOEXTEND_SIZE value should be between %uM and %uM
 - Error number: 4026; Symbol: [ER_CANNOT_USE_AUTOEXTEND_SIZE_CLAUSE](#); SQLSTATE: HY000

Message: AUTOEXTEND_SIZE clause is not valid for %s tablespace.
 - Error number: 4027; Symbol: [ER_ROLE_GRANTED_TO_ITSELF](#); SQLSTATE: HY000

Message: User account %s is directly or indirectly granted to the role %s. The GRANT would create a loop
 - Error number: 4028; Symbol: [ER_TABLE_MUST_HAVE_A_VISIBLE_COLUMN](#); SQLSTATE: HY000

Message: A table must have at least one visible column.

- Error number: 4029; Symbol: [ER_INNODB_COMPRESSION_FAILURE](#); SQLSTATE: HY000

Message: Compression failed with the following error : %s

- Error number: 4030; Symbol: [ER_WARN_ASYNC_CONN_FAILOVER_NETWORK_NAMESPACE](#); SQLSTATE: HY000

Message: The parameter network_namespace is reserved for future use. Please use the CHANGE REPLICATION SOURCE command to set channel network_namespace parameter.

- Error number: 4031; Symbol: [ER_CLIENT_INTERACTION_TIMEOUT](#); SQLSTATE: HY000

Message: The client was disconnected by the server because of inactivity. See wait_timeout and interactive_timeout for configuring this behavior.

- Error number: 4032; Symbol: [ER_INVALID_CAST_TO_GEOMETRY](#); SQLSTATE: 22S01

Message: Invalid cast from %s to %s.

- Error number: 4033; Symbol: [ER_INVALID_CAST_POLYGON_RING_DIRECTION](#); SQLSTATE: 22S04

Message: Invalid cast from %s to %s. A polygon ring is in the wrong direction.

- Error number: 4034; Symbol: [ER_GIS_DIFFERENT_SRIDS_AGGREGATION](#); SQLSTATE: 22S05

Message: Arguments to function %s contains geometries with different SRIDs: %u and %u. All geometries must have the same SRID.

- Error number: 4035; Symbol: [ER_RELOAD_KEYRING_FAILURE](#); SQLSTATE: HY000

Message: Keyring reload failed. Please check error log for more details.

- Error number: 4036; Symbol: [ER_SDI_GET_KEYS_INVALID_TABLESPACE](#); SQLSTATE: HY000

Message: Tablespace '%s' is invalid for SDI operations.

- Error number: 4037; Symbol: [ER_CHANGE_RPL_SRC_WRONG_COMPRESSION_ALGORITHM_SIZE](#); SQLSTATE: HY000

Message: Value too long setting SOURCE_COMPRESSION_ALGORITHMS option to a %d chars long string for channel '%s'.

- Error number: 4039; Symbol: [ER_CANT_USE_SAME_UUID_AS_VIEW_CHANGE_UUID](#); SQLSTATE: HY000

Message: CHANGE REPLICATION SOURCE TO ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = <UUID> cannot be executed because the UUID value is equal to the group_replication_view_change_uuid.

- Error number: 4040; Symbol: [ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_VIEW_CHANGE_UUID](#); SQLSTATE: HY000

Message: Replication '%s' is configured with ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = <UUID> where the UUID value is equal to the group_replication_view_change_uuid

- Error number: 4041; Symbol: [ER_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE](#); SQLSTATE: HY000

Message: Unable to retrieve group_replication_view_change_uuid variable during server checks on replication operations.

- Error number: 4042; Symbol: ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS; SQLSTATE: HY000

Message: Both audit_log_max_size and audit_log_prune_seconds are set to non-zero. audit_log_max_size takes precedence and audit_log_prune_seconds is ignored

- Error number: 4043; Symbol: ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE_ON_SIZE; SQLSTATE: HY000

Message: audit_log_rotate_on_size is not granular enough for the value of audit_log_max_size supplied. Should be at least %d times smaller.

- Error number: 4044; Symbol: ER_KERBEROS_CREATE_USER; SQLSTATE: HY000

Message: Create/Alter user has failed, Configured user realm as authentication string is empty, Please make sure to configure authentication string as user realm.

- Error number: 4045; Symbol: ER_INSTALL_PLUGIN_CONFLICT_CLIENT; SQLSTATE: HY000

Message: Cannot install the %s plugin when the %s plugin is installed.

- Error number: 4046; Symbol: ER_DA_ERROR_LOG_COMPONENT_FLUSH_FAILED; SQLSTATE: HY000

Message: %d error logging component(s) failed to flush. For file-based logs this can happen when the path or permissions of the log-file have changed. Failure to flush file-based logs may affect log-rotation.

- Error number: 4047; Symbol: ER_WARN_SQL_AFTER_MTS_GAPS_GAP_NOT_CALCULATED; SQLSTATE: HY000

Message: The until clause SQL_AFTER_MTS_GAPS is being used for channel '%s' when GTID_MODE = ON and SOURCE_AUTO_POSITION=1 meaning the server did not compute internally what gaps may exist in the relay log transaction execution. To close any execution gaps use either the SQL_BEFORE_GTIDS or SQL_AFTER_GTIDS until clause.

- Error number: 4048; Symbol: ER_INVALID_ASSIGNMENT_TARGET; SQLSTATE: 42000

Message: Invalid target for assignment in INSERT or UPDATE statement '%s'.

- Error number: 4049; Symbol: ER_OPERATION_NOT_ALLOWED_ON_GR_SECONDARY; SQLSTATE: HY000

Message: This operation cannot be performed on a Group Replication secondary member, it must be done on the group primary.

- Error number: 4050; Symbol: ER_GRP_RPL_FAILOVER_CHANNEL_STATUS_PROPAGATION; SQLSTATE: HY000

Message: Unable to propagate the SOURCE_CONNECTION_AUTO_FAILOVER value for channel '%s' to group replication members. Please retry the operation.

- Error number: 4051; Symbol: ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_ONLY_WHEN_JSON; SQLSTATE: HY000

Message: audit_log_format_unix_timestamp is applicable only when audit_log_format = JSON.

-
- Error number: 4052; Symbol: `ER_INVALID_MFA_PLUGIN_SPECIFIED`; SQLSTATE: `HY000`
Message: Invalid plugin "%s" specified as %d factor during "%s".
 - Error number: 4053; Symbol: `ER_IDENTIFIED_BY_UNSUPPORTED`; SQLSTATE: `HY000`
Message: IDENTIFIED BY clause during "%s" not supported for plugin "%s".
 - Error number: 4054; Symbol: `ER_INVALID_PLUGIN_FOR_REGISTRATION`; SQLSTATE: `HY000`
Message: This operation is not supported for plugin "%s".
 - Error number: 4055; Symbol: `ER_PLUGIN_REQUIRES_REGISTRATION`; SQLSTATE: `HY000`
Message: Authentication plugin requires registration. Please refer ALTER USER syntax or set --register-factor command line option to do registration.
 - Error number: 4056; Symbol: `ER_MFA_METHOD_EXISTS`; SQLSTATE: `HY000`
Message: %d factor authentication method exists. Please do ALTER USER... DROP %d factor before doing this operation OR do ALTER USER... MODIFY %d factor... to modify existing %d factor authentication method.
 - Error number: 4057; Symbol: `ER_MFA_METHOD_NOT_EXISTS`; SQLSTATE: `HY000`
Message: %d factor authentication method doesn't exist. Please do ALTER USER... ADD %d factor... before doing this operation.
 - Error number: 4058; Symbol: `ER_AUTHENTICATION_POLICY_MISMATCH`; SQLSTATE: `HY000`
Message: %d factor authentication method does not match against authentication policy. Please refer @@authentication_policy system variable.
 - Error number: 4059; Symbol: `ER_PLUGIN_REGISTRATION_DONE`; SQLSTATE: `HY000`
Message: The registration for %d factor authentication method is already completed. You cannot perform registration multiple times.
 - Error number: 4060; Symbol: `ER_INVALID_USER_FOR_REGISTRATION`; SQLSTATE: `HY000`
Message: The registration operation is not allowed for user '%s'@'%s'. The operation can only be performed in user's own session.
 - Error number: 4061; Symbol: `ER_USER_REGISTRATION_FAILED`; SQLSTATE: `HY000`
Message: Authentication plugin's registration failed.
 - Error number: 4062; Symbol: `ER_MFA_METHODS_INVALID_ORDER`; SQLSTATE: `HY000`
Message: %d factor authentication method should be added before %d factor authentication method.
 - Error number: 4063; Symbol: `ER_MFA_METHODS_IDENTICAL`; SQLSTATE: `HY000`
Message: Authentication factor should be different.
 - Error number: 4064; Symbol: `ER_INVALID_MFA_OPERATIONS_FOR_PASSWORDLESS_USER`; SQLSTATE: `HY000`
Message: The operation "%s" cannot be performed for user '%s'@'%s' configured to connect without a password.

-
- Error number: 4065; Symbol: `ER_CHANGE_REPLICATION_SOURCE_NO_OPTIONS_FOR_GTID_ONLY`; SQLSTATE: `HY000`

Message: `GTID_ONLY` cannot be enabled for replication channel '%s'. You need `GTID_MODE = ON`, `SOURCE_AUTO_POSITION = 1` and `REQUIRE_ROW_FORMAT = 1`.
 - Error number: 4066; Symbol: `ER_CHANGE_REP_SOURCE_CANT_DISABLE_REQ_ROW_FORMAT_WITH_GTID_ONLY`; SQLSTATE: `HY000`

Message: `REQUIRE_ROW_FORMAT` cannot be disabled for replication channel '%s' when `GTID_ONLY=1`.
 - Error number: 4067; Symbol: `ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POSITION_WITH_GTID_ONLY`; SQLSTATE: `HY000`

Message: `SOURCE_AUTO_POSITION` cannot be disabled for replication channel '%s' when `GTID_ONLY=1`.
 - Error number: 4068; Symbol: `ER_CHANGE_REP_SOURCE_CANT_DISABLE_GTID_ONLY_WITHOUT_POSITIONS`; SQLSTATE: `HY000`

Message: When disabling `GTID_ONLY` and `SOURCE_AUTO_POSITION` FOR CHANNEL '%s' you must provide `SOURCE_LOG_FILE` and `SOURCE_LOG_POS` as source positions are invalid.
 - Error number: 4069; Symbol: `ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POS_WITHOUT_POSITIONS`; SQLSTATE: `HY000`

Message: When disabling `SOURCE_AUTO_POSITION` FOR CHANNEL '%s' you must provide `SOURCE_LOG_FILE` and `SOURCE_LOG_POS` as source positions are invalid.
 - Error number: 4070; Symbol: `ER_CHANGE_REP_SOURCE_GR_CHANNEL_WITH_GTID_MODE_NOT_ON`; SQLSTATE: `HY000`

Message: When configuring a group replication channel you must do it when `GTID_MODE = ON`.
 - Error number: 4071; Symbol: `ER_CANT_USE_GTID_ONLY_WITH_GTID_MODE_NOT_ON`; SQLSTATE: `HY000`

Message: Replication cannot start%s with `GTID_ONLY = 1` as this server uses `@@GLOBAL.GTID_MODE <> ON`.
 - Error number: 4072; Symbol: `ER_WARN_C_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO_POS_INVALID_POS`; SQLSTATE: `HY000`

Message: The replication positions relative to the source may be out-of-date on channel '%s', due to the use of `GTID_ONLY=1`. The out-of-date positions can still be used in some cases so, in order to update them, we suggest that you start the replication to receive and apply at least one transaction, which will set the positions to valid values.
 - Error number: 4073; Symbol: `ER_DA_SSL_FIPS_MODE_ERROR`; SQLSTATE: `HY000`

Message: SSL fips mode error: %s
 - Error number: 4074; Symbol: `ER_VALUE_OUT_OF_RANGE`; SQLSTATE: `HY000`

Message: %s=%llu is outside the valid range [%llu,%llu]. %llu will be used.
-

-
- Error number: 4075; Symbol: [ER_FULLTEXT_WITH_ROLLUP](#); SQLSTATE: HY000
Message: MATCH does not support ROLLUP columns.
 - Error number: 4076; Symbol: [ER_REGEXP_MISSING_RESOURCE](#); SQLSTATE: HY000
Message: Missing locale resource in regular expression library.
 - Error number: 4077; Symbol: [ER_WARN_REGEXP_USING_DEFAULT](#); SQLSTATE: HY000
Message: Regular expression library used default (root) locale.
 - Error number: 4078; Symbol: [ER_REGEXP_MISSING_FILE](#); SQLSTATE: HY000
Message: Missing data file in regular expression library.
 - Error number: 4079; Symbol: [ER_WARN_DEPRECATED_COLLATION](#); SQLSTATE: HY000
Message: '%s' is a collation of the deprecated character set %s. Please consider using %s with an appropriate collation instead.
 - Error number: 4080; Symbol: [ER_CONCURRENT_PROCEDURE_USAGE](#); SQLSTATE: HY000
Message: The %s was called when there was already another concurrent call to this procedure. No action was taken. Wait for other calls to %s to finish before retrying.
 - Error number: 4081; Symbol: [ER_DA_GLOBAL_CONN_LIMIT](#); SQLSTATE: HY000
Message: Connection closed. Global connection memory limit %llu bytes exceeded. Consumed %llu bytes.
 - Error number: 4082; Symbol: [ER_DA_CONN_LIMIT](#); SQLSTATE: HY000
Message: Connection closed. Connection memory limit %llu bytes exceeded. Consumed %llu bytes.
 - Error number: 4083; Symbol: [ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_COLUMN_TYPE_INSTANT](#); SQLSTATE: HY000
Message: Need to rebuild the table to change column type
 - Error number: 4084; Symbol: [ER_WARN_SF_UDF_NAME_COLLISION](#); SQLSTATE: HY000
Message: This function '%s' has the same name as a loadable function (UDF). To invoke the stored function, it is necessary to qualify it with the schema name.
 - Error number: 4085; Symbol: [ER_CANNOT_PURGE_BINLOG_WITH_BACKUP_LOCK](#); SQLSTATE: HY000
Message: Could not purge binary logs since another session is executing LOCK INSTANCE FOR BACKUP. Wait for that session to release the lock.
 - Error number: 4086; Symbol: [ER_TOO_MANY_WINDOWS](#); SQLSTATE: HY000
Message: Too many windows in SELECT: %d. Maximum allowed is %d. Use named windows to share windows between window functions.
 - Error number: 4087; Symbol: [ER_MYSQLBACKUP_CLIENT_MSG](#); SQLSTATE: HY000
Message: %s
 - Error number: 4088; Symbol: [ER_COMMENT_CONTAINS_INVALID_STRING](#); SQLSTATE: HY000

Message: Comment for %s '%s' contains an invalid %s character string: '%s'.

- Error number: 4089; Symbol: [ER_DEFINITION_CONTAINS_INVALID_STRING](#); SQLSTATE: HY000

Message: Definition of %s '%s.%s' contains an invalid %s character string: '%s'.

- Error number: 4090; Symbol: [ER_CANT_EXECUTE_COMMAND_WITH_ASSIGNED_GTID_NEXT](#); SQLSTATE: HY000

Message: Can't execute the given command when @@SESSION.GTID_NEXT == 'UUID:NUMBER'.

- Error number: 4091; Symbol: [ER_XA_TEMP_TABLE](#); SQLSTATE: HY000

Message: XA: Temporary tables cannot be accessed inside XA transactions when xa_detach_on_prepare=ON

- Error number: 4092; Symbol: [ER_INNOODB_MAX_ROW_VERSION](#); SQLSTATE: HY000

Message: Maximum row versions reached for table %s. No more columns can be added or dropped instantly. Please use COPY/INPLACE.

- Error number: 4094; Symbol: [ER_OPERATION_NOT_ALLOWED_WHILE_PRIMARY_CHANGE_IS_RUNNING](#); SQLSTATE: HY000

Message: All queries have been blocked while function 'group_replication_set_as_primary()' is executing. Please refer timeout parameter of function 'group_replication_set_as_primary()'.

- Error number: 4095; Symbol: [ER_WARN_DEPRECATED_DATETIME_DELIMITER](#); SQLSTATE: HY000

Message: Delimiter '%s' in position %d in datetime value '%s' at row %d is deprecated. Prefer the standard '%c'.

- Error number: 4096; Symbol: [ER_WARN_DEPRECATED_SUPERFLUOUS_DELIMITER](#); SQLSTATE: HY000

Message: Delimiter '%s' in position %d in datetime value '%s' at row %d is superfluous and is deprecated. Please remove.

- Error number: 4097; Symbol: [ER_CANNOT_PERSIST_SENSITIVE_VARIABLES](#); SQLSTATE: HY000

Message: Cannot persist SENSITIVE system variable '%s' because keyring component support is unavailable.

- Error number: 4098; Symbol: [ER_WARN_CANNOT_SECURELY_PERSIST_SENSITIVE_VARIABLES](#); SQLSTATE: HY000

Message: SENSITIVE system variable '%s' was persisted without encryption. Consider restarting server with keyring component support to persist SENSITIVE variables securely.

- Error number: 4099; Symbol: [ER_WARN_TRG_ALREADY_EXISTS](#); SQLSTATE: HY000

Message: Trigger '%s' already exists on the table '%s'. '%s'.

- Error number: 4100; Symbol: [ER_IF_NOT_EXISTS_UNSUPPORTED_TRG_EXISTS_ON_DIFFERENT_TABLE](#); SQLSTATE: HY000

Message: Trigger '%s'. '%s' already exists on a different table. The 'IF NOT EXISTS' clause is only supported for triggers associated with the same table.

-
- Error number: 4101; Symbol: `ER_IF_NOT_EXISTS_UNSUPPORTED_UDF_NATIVE_FCT_NAME_COLLISION`; SQLSTATE: HY000
Message: This function '%s' has the same name as a native function. The 'IF NOT EXISTS' clause is not supported while creating a loadable function with the same name as a native function.
 - Error number: 4102; Symbol: `ER_SET_PASSWORD_AUTH_PLUGIN_ERROR`; SQLSTATE: HY000
Message: SET PASSWORD has no significance for user '%s'@'%s' as the authentication method used doesn't store authentication data in the MySQL server. Please consider using ALTER USER instead if you want to change authentication parameters.
 - Error number: 4105; Symbol: `ER_SRS_INVALID_LATITUDE_OF_ORIGIN`; SQLSTATE: SR002
Message: Latitude of origin must be within [-90, 90] degrees, specified in the SRS angular unit.
 - Error number: 4106; Symbol: `ER_SRS_INVALID_LONGITUDE_OF_ORIGIN`; SQLSTATE: SR002
Message: Longitude of origin must be within (-180, 180] degrees, specified in the SRS angular unit.
 - Error number: 4107; Symbol: `ER_SRS_UNUSED_PROJ_PARAMETER_PRESENT`; SQLSTATE: SR002
Message: The spatial reference system definition for SRID %u contains unused projection parameter "%s".
 - Error number: 4108; Symbol: `ER_GIPK_COLUMN_EXISTS`; SQLSTATE: HY000
Message: Failed to generate invisible primary key. Column 'my_row_id' already exists.
 - Error number: 4109; Symbol: `ER_GIPK_FAILED_AUTOINC_COLUMN_EXISTS`; SQLSTATE: HY000
Message: Failed to generate invisible primary key. Auto-increment column already exists.
 - Error number: 4110; Symbol: `ER_GIPK_COLUMN_ALTER_NOT_ALLOWED`; SQLSTATE: HY000
Message: Altering generated invisible primary key column 'my_row_id' is not allowed.
 - Error number: 4111; Symbol: `ER_DROP_PK_COLUMN_TO_DROP_GIPK`; SQLSTATE: HY000
Message: Please drop primary key column to be able to drop generated invisible primary key.
 - Error number: 4112; Symbol: `ER_CREATE_SELECT_WITH_GIPK_DISALLOWED_IN_SBR`; SQLSTATE: HY000
Message: Generating an invisible primary key for a table created using CREATE TABLE ... SELECT ... is disallowed when binlog_format=STATEMENT. It cannot be guaranteed that the SELECT retrieves rows in the same order on source and replica. Therefore, it cannot be guaranteed that the value generated for the generated implicit primary key column will be the same on source and replica for all rows. Use binlog_format=ROW or MIXED to execute this statement.
 - Error number: 4114; Symbol: `ER_CTE_RECURSIVE_NOT_UNION`; SQLSTATE: HY000
Message: Recursive table reference in EXCEPT or INTERSECT operand is not allowed.
 - Error number: 4115; Symbol: `ER_COMMAND_BACKEND_FAILED_TO_FETCH_SECURITY_CTX`; SQLSTATE: HY000
Message: Error when trying to fetch information from security context object, when trying to connect the server.

-
- Error number: [4116](#); Symbol: [ER_COMMAND_SERVICE_BACKEND_FAILED](#); SQLSTATE: [HY000](#)
Message: Error in command service backend interface, because of : "%s"
 - Error number: [4117](#); Symbol: [ER_CLIENT_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS](#); SQLSTATE: [HY000](#)
Message: The PRIVILEGE_CHECKS_USER for channel '%s' would need FILE privilege to execute a LOAD DATA INFILE statement replicated in statement format. Consider using binlog_format=ROW on source. If the replicated events are trusted, recover from the failure by temporarily granting FILE to the PRIVILEGE_CHECKS_USER.
 - Error number: [4118](#); Symbol: [ER_GROUP_REPLICATION_FORCE_MEMBERS_COMMAND_FAILURE](#); SQLSTATE: [HY000](#)
Message: The 'SET GLOBAL group_replication_force_members=%s' command encountered a failure. %s
 - Error number: [4119](#); Symbol: [ER_WARN_DEPRECATED_IDENT](#); SQLSTATE: [HY000](#)
Message: Using %s as unquoted identifier is deprecated, please use quotes or rename the identifier.
 - Error number: [4120](#); Symbol: [ER_INTERSECT_ALL_MAX_DUPLICATES_EXCEEDED](#); SQLSTATE: [HY000](#)
Message: Max number of duplicate rows in INTERSECT ALL exceeded.
 - Error number: [4121](#); Symbol: [ER_TP_QUERY_THRS_PER_GRP_EXCEEDS_TXN_THR_LIMIT](#); SQLSTATE: [HY000](#)
Message: Query threads count(%u) exceeds transaction threads limit(%u) per group. Please use query threads count per group smaller or equal to max transaction threads limit per group
 - Error number: [4122](#); Symbol: [ER_BAD_TIMESTAMP_FORMAT](#); SQLSTATE: [HY000](#)
Message: Invalid timestamp format in %s udf
 - Error number: [4123](#); Symbol: [ER_SHAPE_PREDICTION_UDF](#); SQLSTATE: [HY000](#)
Message: SHAPE_PREDICTION UDF %s got error because of %s.
 - Error number: [4124](#); Symbol: [ER_SRS_INVALID_HEIGHT](#); SQLSTATE: [SR002](#)
Message: Height parameter must be non negative.
 - Error number: [4125](#); Symbol: [ER_SRS_INVALID_SCALING](#); SQLSTATE: [SR002](#)
Message: Scaling parameter must be non negative.
 - Error number: [4126](#); Symbol: [ER_SRS_INVALID_ZONE_WIDTH](#); SQLSTATE: [SR002](#)
Message: Zone width parameter must be an integer between 1-60.
 - Error number: [4127](#); Symbol: [ER_SRS_INVALID_LATITUDE_POLAR_STERE_VAR_A](#); SQLSTATE: [SR002](#)
Message: Latitude of origin must be +-90 degrees, specified in the SRS angular unit, in Polar Stereographic (variant A) projection method (EPSG:9810).

-
- Error number: [4128](#); Symbol: [ER_WARN_DEPRECATED_CLIENT_NO_SCHEMA_OPTION](#); SQLSTATE: [HY000](#)
Message: The client is using a deprecated CLIENT_NO_SCHEMA client option. CLIENT_NO_SCHEMA will be removed in a future release.
 - Error number: [4129](#); Symbol: [ER_TABLE_NOT_EMPTY](#); SQLSTATE: [HY000](#)
Message: Table '%s' is not empty.
 - Error number: [4130](#); Symbol: [ER_TABLE_NO_PRIMARY_KEY](#); SQLSTATE: [HY000](#)
Message: Table '%s' has no primary key.
 - Error number: [4131](#); Symbol: [ER_TABLE_IN_SHARED_TABLESPACE](#); SQLSTATE: [HY000](#)
Message: Table '%s' is in a shared tablespace.
 - Error number: [4132](#); Symbol: [ER_INDEX_OTHER_THAN_PK](#); SQLSTATE: [HY000](#)
Message: Table '%s' has indexes other than primary key.
 - Error number: [4133](#); Symbol: [ER_LOAD_BULK_DATA_UNSORTED](#); SQLSTATE: [HY000](#)
Message: [IN PRIMARY KEY ORDER] specified but data not sorted: '%s'
 - Error number: [4134](#); Symbol: [ER_BULK_EXECUTOR_ERROR](#); SQLSTATE: [HY000](#)
Message: Bulk executor error: %s
 - Error number: [4135](#); Symbol: [ER_BULK_READER_LIBCURL_INIT_FAILED](#); SQLSTATE: [HY000](#)
Message: Bulk reader failed to initialize libcurl
 - Error number: [4136](#); Symbol: [ER_BULK_READER_LIBCURL_ERROR](#); SQLSTATE: [HY000](#)
Message: Bulk reader got libcurl error: %s
 - Error number: [4137](#); Symbol: [ER_BULK_READER_SERVER_ERROR](#); SQLSTATE: [HY000](#)
Message: Bulk reader got error response from server: %ld
 - Error number: [4138](#); Symbol: [ER_BULK_READER_COMMUNICATION_ERROR](#); SQLSTATE: [HY000](#)
Message: Bulk reader got error in communication with source server, check the error log for additional details.
 - Error number: [4139](#); Symbol: [ER_BULK_LOAD_DATA_FAILED](#); SQLSTATE: [HY000](#)
Message: Bulk loader failed in Innodb storage engine, check the error log for additional details.
 - Error number: [4140](#); Symbol: [ER_BULK_LOADER_COLUMN_TOO_BIG_FOR_LEFTOVER_BUFFER](#); SQLSTATE: [HY000](#)
Message: CSV column too big for leftover buffer.
 - Error number: [4141](#); Symbol: [ER_BULK_LOADER_COMPONENT_ERROR](#); SQLSTATE: [HY000](#)
Message: Bulk loader component error: %s

-
- Error number: 4142; Symbol: [ER_BULK_LOADER_FILE_CONTAINS_LESS_LINES_THAN_IGNORE_CLAUSE](#); SQLSTATE: HY000
Message: The first file being loaded contained less lines than the ignore clause
 - Error number: 4143; Symbol: [ER_BULK_PARSER_MISSING_ENCLOSED_BY](#); SQLSTATE: HY000
Message: Missing ENCLOSED BY character at row %ld in file '%s'. Add OPTIONALLY to the ENCLOSED BY clause to allow this input.
 - Error number: 4144; Symbol: [ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS_EXCEEDED](#); SQLSTATE: HY000
Message: The number of input columns that need to be buffered for parsing exceeded predefined buffer max size for file '%s'.
 - Error number: 4145; Symbol: [ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED](#); SQLSTATE: HY000
Message: The column data that needed to be copied due to escaped characters exceeded the size of the internal copy buffer for file '%s'.
 - Error number: 4146; Symbol: [ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT](#); SQLSTATE: HY000
Message: Unexpected end of input found at row %ld in file '%s'. Data for some columns is missing.
 - Error number: 4147; Symbol: [ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR](#); SQLSTATE: HY000
Message: Unexpected row terminator found at row %ld in file '%s'. Data for some columns is missing.
 - Error number: 4148; Symbol: [ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENDING_ENCLOSED_BY](#); SQLSTATE: HY000
Message: Unexpected characters after ending ENCLOSED BY character found at row %ld in file '%s'.
 - Error number: 4149; Symbol: [ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE](#); SQLSTATE: HY000
Message: Unexpected characters after NULL escape (\N) found at row %ld in file '%s'.
 - Error number: 4150; Symbol: [ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_TERMINATOR](#); SQLSTATE: HY000
Message: Unexpected characters after column terminator found at row %ld in file '%s'.
 - Error number: 4151; Symbol: [ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE](#); SQLSTATE: HY000
Message: Unexpected end of input found at row %ld in file '%s' resulting in incomplete escape sequence.
 - Error number: 4152; Symbol: [ER_LOAD_BULK_DATA_FAILED](#); SQLSTATE: HY000
Message: LOAD BULK DATA into table '%s' failed: %s
 - Error number: 4153; Symbol: [ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD](#); SQLSTATE: HY000
Message: Incorrect %s value: '%s' for column '%s' at row %ld in file '%s'
-

-
- Error number: [4154](#); Symbol: [ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL](#); SQLSTATE: [HY000](#)
Message: NULL supplied to NOT NULL column '%s' at row %ld in file '%s'
 - Error number: [4155](#); Symbol: [ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATE_WITH_GR](#); SQLSTATE: [HY000](#)
Message: On a Group Replication channel, setting REQUIRE_TABLE_PRIMARY_KEY_CHECK to 'GENERATE' is not allowed.
 - Error number: [4156](#); Symbol: [ER_CANT_CHANGE_SYS_VAR_IN_READ_ONLY_MODE](#); SQLSTATE: [HY000](#)
Message: Cannot change the '%s' system variable in read-only mode.
 - Error number: [4157](#); Symbol: [ER_INNODB_INSTANT_ADD_DROP_NOT_SUPPORTEDED_MAX_SIZE](#); SQLSTATE: [HY000](#)
Message: Column can't be added or dropped with ALGORITHM=INSTANT as either max possible row size already crosses max permissible row size or may cross it after add. Try ALGORITHM=INPLACE/COPY.
 - Error number: [4158](#); Symbol: [ER_INNODB_INSTANT_ADD_NOT_SUPPORTEDED_MAX_FIELDS](#); SQLSTATE: [HY000](#)
Message: Column can't be added to '%s' with ALGORITHM=INSTANT anymore. Please try ALGORITHM=INPLACE/COPY.
 - Error number: [4159](#); Symbol: [ER_CANT_SET_PERSISTED](#); SQLSTATE: [HY000](#)
Message: Failed to set persisted options.
 - Error number: [4160](#); Symbol: [ER_INSTALL_COMPONENT_SET_NULL_VALUE](#); SQLSTATE: [HY000](#)
Message: The value supplied for %s in the SET list cannot be null
 - Error number: [4161](#); Symbol: [ER_INSTALL_COMPONENT_SET_UNUSED_VALUE](#); SQLSTATE: [HY000](#)
Message: The assignment of %s in SET doesn't match any of the variables registered by the component(s)
 - Error number: [4162](#); Symbol: [ER_WARN_DEPRECATED_USER_DEFINED_COLLATIONS](#); SQLSTATE: [HY000](#)
Message: '%s' is a user defined collation. User defined collations are deprecated and will be removed in a future release. Consider using a compiled collation instead.
 - Error number: [4163](#); Symbol: [ER_USER_LOCK_OVERLONG_NAME](#); SQLSTATE: [42000](#)
Message: User-level lock name '%s' should not exceed %d characters.
 - Error number: [4164](#); Symbol: [ER_WARN_NO_SPACE_VERSION_COMMENT](#); SQLSTATE: [HY000](#)
Message: Immediately starting the version comment after the version number is deprecated and may change behavior in a future release. Please insert a white-space character after the version number.
 - Error number: [4165](#); Symbol: [ER_VALIDATE_PASSWORD_INSUFFICIENT_CHANGED_CHARACTERS](#); SQLSTATE: [HY000](#)

Message: The new password must have at least '%u' characters that are different from the old password. It has only '%u' character(s) different. For this comparison, uppercase letters and lowercase letters are considered to be equal.

- Error number: 4166; Symbol: [ER_WARN_DEPRECATED_WITH_NOTE](#); SQLSTATE: [HY000](#)

Message: '%s' is deprecated and will be removed in a future release. %s

- Error number: 4167; Symbol: [ER_CANT_RUN_COMMAND_SERVICES_RECURSIVELY](#); SQLSTATE: [HY000](#)

Message: Running recursive calls to SQL execution service is not supported

[ER_CANT_RUN_COMMAND_SERVICES_RECURSIVELY](#) was added in 8.4.6.

- Error number: 6000; Symbol: [ER_LANGUAGE_COMPONENT](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: 6001; Symbol: [ER_LANGUAGE_COMPONENT_NOT_AVAILABLE](#); SQLSTATE: [HY000](#)

Message: Language component: Not available.

- Error number: 6002; Symbol: [ER_LANGUAGE_COMPONENT_UNSUPPORTED_LANGUAGE](#); SQLSTATE: [HY000](#)

Message: Language component: Unsupported language '%s'

- Error number: 6003; Symbol: [ER_LANGUAGE_COMPONENT_CANNOT_UNINSTALL](#); SQLSTATE: [HY000](#)

Message: Language component: Cannot uninstall due to connected sessions. Please disconnect all sessions and try again.

- Error number: 6004; Symbol: [ER_SP_NO_ALTER_LANGUAGE](#); SQLSTATE: [HY000](#)

Message: Altering the language of an existing routine is not possible.

- Error number: 6005; Symbol: [ER_EXPLAIN_INTO_ANALYZE_NOT_SUPPORTED](#); SQLSTATE: [0A000](#)

Message: EXPLAIN ANALYZE does not support the INTO clause.

- Error number: 6006; Symbol: [ER_EXPLAIN_INTO_IMPLICIT_FORMAT_NOT_SUPPORTED](#); SQLSTATE: [0A000](#)

Message: EXPLAIN INTO does not support implicit FORMAT.

- Error number: 6007; Symbol: [ER_EXPLAIN_INTO_FORMAT_NOT_SUPPORTED](#); SQLSTATE: [0A000](#)

Message: EXPLAIN INTO does not support FORMAT=%s.

- Error number: 6008; Symbol: [ER_NULL_CANT_BE_PERSISTED_FOR_READONLY](#); SQLSTATE: [HY000](#)

Message: Trying to persist a NULL into a variable '%s' that's settable only on command line is not supported

- Error number: 6009; Symbol: [ER_EXPLAIN_INTO_FOR_CONNECTION_NOT_SUPPORTED](#); SQLSTATE: [0A000](#)

Message: EXPLAIN FOR CONNECTION does not support the INTO clause.

-
- Error number: 6010; Symbol: `ER_INNODB_IMPORT_WRONG_DROPPED_ENUM_LENGTH`; SQLSTATE: `HY000`
Message: Enum element name length %lu, is invalid for column %s
 - Error number: 6011; Symbol: `ER_INNODB_IMPORT_WRONG_NUMBER_OF_INDEXES_ZERO`; SQLSTATE: `HY000`
Message: Number of indexes in meta-data file is 0
 - Error number: 6012; Symbol: `ER_INNODB_IMPORT_WRONG_NUMBER_OF_INDEXES_TOO_HIGH`; SQLSTATE: `HY000`
Message: Number of indexes in meta-data file is too high: %llu
 - Error number: 6013; Symbol: `ER_INNODB_IMPORT_DROP_COL_METADATA_MISMATCH`; SQLSTATE: `HY000`
Message: DD metadata for INSTANT DROP column %s in target table doesn't match with CFG.
 - Error number: 6014; Symbol: `ER_INNODB_IMPORT_ENUM_NULL_TERMINATOR_MISSING`; SQLSTATE: `HY000`
Message: Enum/Set element name missing null terminator for column '%s'
 - Error number: 6015; Symbol: `ER_SIMULATED_INJECTION_ERROR`; SQLSTATE: `HY000`
Message: %s %s %zu.
 - Error number: 6016; Symbol: `ER_WARN_DEPRECATED_DYNAMIC_PRIV_IN_GRANT`; SQLSTATE: `HY000`
Message: The privilege '%s' is deprecated.
 - Error number: 6017; Symbol: `ER_BULK_MULTI_READER_OPEN_FILE_FAILED`; SQLSTATE: `HY000`
Message: Bulk Multi Reader: Failed to open file
 - Error number: 6018; Symbol: `ER_BULK_MULTI_READER_READ_FILE_FAILED`; SQLSTATE: `HY000`
Message: Bulk Multi Reader: Failed to read file
 - Error number: 6019; Symbol: `ER_BULK_MERGE_INVALID_CHUNK`; SQLSTATE: `HY000`
Message: Bulk Merge Loader: Invalid Chunk
 - Error number: 6020; Symbol: `ER_BULK_MERGE_NOT_ALL_CHUNKS_CONSUMED`; SQLSTATE: `HY000`
Message: Bulk Merge Loader: Not all chunks consumed
 - Error number: 6021; Symbol: `ER_BULK_WRITER_LIBCURL_INIT_FAILED`; SQLSTATE: `HY000`
Message: Bulk writer failed to initialize libcurl
 - Error number: 6022; Symbol: `ER_BULK_WRITER_LIBCURL_ERROR`; SQLSTATE: `HY000`
Message: Bulk writer got libcurl error: %s
 - Error number: 6023; Symbol: `ER_BULK_SORTING_LOADER_WRITE`; SQLSTATE: `HY000`

Message: Bulk Sorting Loader: Failed to write data to temporary file

- Error number: 6024; Symbol: ER_BULK_SORTING_LOADER_WAIT; SQLSTATE: HY000

Message: Bulk Sorting Loader: Interrupted while waiting

- Error number: 6025; Symbol: ER_BULK_READER_OPEN_FILE_FAILED; SQLSTATE: HY000

Message: Bulk Reader: Failed to access file %s

- Error number: 6026; Symbol: ER_BULK_LOAD_TABLE_HAS_INSTANT_COLS; SQLSTATE: HY000

Message: Bulk Loader: Table '%s' has instantly added/dropped columns. Please TRUNCATE TABLE and retry.

- Error number: 6027; Symbol: ER_BULK_LOAD_RESOURCE; SQLSTATE: HY000

Message: Bulk Loader: Not enough memory available. Memory needed for loading %s data: %s for %u threads, %s with minimal configuration. Total configured memory is %s, Available memory is %s.

- Error number: 6028; Symbol: ER_BULK_LOAD_SECONDARY_ENGINE; SQLSTATE: HY000

Message: LOAD DATA with BULK Algorithm is not supported on a table with secondary engine.

- Error number: 6029; Symbol: ER_BULK_READER_ERROR; SQLSTATE: HY000

Message: Bulk reader error: %s

- Error number: 6030; Symbol: ER_BULK_READER_FILE_DOESNT_EXIST; SQLSTATE: HY000

Message: File not found, check whether it exists: %s

- Error number: 6031; Symbol: ER_BULK_READER_COULDNT_RESOLVE_HOST; SQLSTATE: HY000

Message: Couldn't resolve host: %s

- Error number: 6032; Symbol: ER_START_REPLICA_CHANNEL_INVALID_CONFIGURATION; SQLSTATE: HY000

Message: Cannot start replication channel '%s' because %s.

- Error number: 6033; Symbol: ER_CANNOT_EXECUTE_IN_PRIMARY; SQLSTATE: HY000

Message: '%s' is not supported

- Error number: 6034; Symbol: ER_TOO_MANY_GROUP_BY_MODIFIER_BRANCHES; SQLSTATE: HY000

Message: '%s' is supported with maximum %d elements in the GROUP BY list

- Error number: 6035; Symbol: ER_WARN_DEPRECATED_ENGINE_SYNTAX_NO_REPLACEMENT; SQLSTATE: HY000

Message: '%s' for '%s' storage engine is deprecated and will be removed in a future release.

- Error number: 6036; Symbol: ER_QUALIFY_WITHOUT_WINDOW_FUNCTION; SQLSTATE: HY000

Message: QUALIFY clause cannot be used without a window function.

- Error number: 6037; Symbol: ER_SUPPORTED_ONLY_WITH_HYPERGRAPH; SQLSTATE: HY000

Message: '%s' can be used only if the hypergraph optimizer is enabled.

- Error number: 6038; Symbol: [ER_SPECIFIC_ACCESS_DENIED](#); SQLSTATE: HY000

Message: Access denied; you need %s privilege(s) for this operation

- Error number: 6039; Symbol: [ER_CANT_SET_GTID_NEXT_TO_AUTOMATIC_TAGGED_WHEN_GTID_MODE_IS_OFF](#); SQLSTATE: HY000

Message: @@SESSION.GTID_NEXT cannot be set to AUTOMATIC:<TAG> when @@GLOBAL.GTID_MODE = OFF or OFF_PERMISSIVE

- Error number: 6040; Symbol: [ER_GTID_NEXT_TAG_GTID_MODE_OFF](#); SQLSTATE: HY000

Message: @@SESSION.GTID_NEXT cannot be set to UUID:TAG:NUMBER when @@GLOBAL.GTID_MODE = OFF.

- Error number: 6041; Symbol: [ER_LH_COL_NOT_NULLABLE](#); SQLSTATE: HY000

Message: Column %d of %s : Column contains null but it is not nullable.

- Error number: 6042; Symbol: [ER_LH_WARN_COL_MISSING_NOT_NULLABLE](#); SQLSTATE: HY000

Message: Column %d of %s : Column is missing, but it is not nullable and no explicit default value is provided.

- Error number: 6043; Symbol: [ER_LH_COL_IS_EMPTY](#); SQLSTATE: HY000

Message: Column %d of %s : Column is empty.

- Error number: 6044; Symbol: [ER_LH_COL_IS_EMPTY_WARN](#); SQLSTATE: HY000

Message: Column %d of %s : Column is empty, setting default value.

- Error number: 6045; Symbol: [ER_LH_BAD_VALUE](#); SQLSTATE: HY000

Message: Column %d of %s : Invalid %s value.

- Error number: 6046; Symbol: [ER_LH_DECIMAL_UNKNOWN_ERR](#); SQLSTATE: HY000

Message: Column %d of %s : Unknown error while parsing decimal.

- Error number: 6047; Symbol: [ER_LH_DECIMAL_OOM_ERR](#); SQLSTATE: HY000

Message: Column %d of %s : Out of memory loading decimal.

- Error number: 6048; Symbol: [ER_LH_WARN_DECIMAL_ROUNDING](#); SQLSTATE: HY000

Message: Column %d of %s : Fraction exceeds schema, rounding value.

- Error number: 6049; Symbol: [ER_LH_DECIMAL_PRECISION_EXCEEDS_SCHEMA](#); SQLSTATE: HY000

Message: Column %d of %s : decimal precision exceeds schema.

- Error number: 6050; Symbol: [ER_LH_EXCEEDS_MIN](#); SQLSTATE: HY000

Message: Column %d of %s : %s exceeds min.

-
- Error number: [6051](#); Symbol: [ER_LH_EXCEEDS_MAX](#); SQLSTATE: [HY000](#)
Message: Column %d of %s : %s exceeds max.
 - Error number: [6052](#); Symbol: [ER_LH_WARN_EXCEEDS_MIN_TRUNCATING](#); SQLSTATE: [HY000](#)
Message: Column %d of %s : %s exceeds min, setting to min value possible.
 - Error number: [6053](#); Symbol: [ER_LH_WARN_EXCEEDS_MAX_TRUNCATING](#); SQLSTATE: [HY000](#)
Message: Column %d of %s : %s exceeds max, setting to max value possible.
 - Error number: [6054](#); Symbol: [ER_LH_REAL_IS_NAN](#); SQLSTATE: [HY000](#)
Message: Column %d of %s : Real value is NaN.
 - Error number: [6055](#); Symbol: [ER_LH_OUT_OF_RANGE](#); SQLSTATE: [HY000](#)
Message: Column %d of %s : %s value is out of range.
 - Error number: [6056](#); Symbol: [ER_LH_DATETIME_FORMAT](#); SQLSTATE: [HY000](#)
Message: Column %d of %s : Error while applying %s format.
 - Error number: [6057](#); Symbol: [ER_LH_WARN_TRUNCATED](#); SQLSTATE: [HY000](#)
Message: Column %d of %s : %s value was truncated.
 - Error number: [6058](#); Symbol: [ER_LH_CANNOT_CONVERT_STRING](#); SQLSTATE: [HY000](#)
Message: Column %d of %s : Cannot convert string %s.
 - Error number: [6059](#); Symbol: [ER_LH_RESOURCE_PRINCIPAL_ERR](#); SQLSTATE: [HY000](#)
Message: Resource principal error.
 - Error number: [6060](#); Symbol: [ER_LH_AWS_AUTH_ERR](#); SQLSTATE: [HY000](#)
Message: AWS authentication error.
 - Error number: [6061](#); Symbol: [ER_LH_CSV_PARSING_ERR](#); SQLSTATE: [HY000](#)
Message: %s:%lu: Parsing error found. %s.
 - Error number: [6062](#); Symbol: [ER_LH_COLUMN_MISMATCH_ERR](#); SQLSTATE: [HY000](#)
Message: %s: Mismatch in the number of columns. Expected %u, found %u.
 - Error number: [6063](#); Symbol: [ER_LH_COLUMN_MAX_ERR](#); SQLSTATE: [HY000](#)
Message: %s: More than %u column(s) found.
 - Error number: [6064](#); Symbol: [ER_LH_CHARSET_UNSUPPORTED](#); SQLSTATE: [HY000](#)
Message: Column %d in %s: Charset is not supported.
 - Error number: [6065](#); Symbol: [ER_LH_PARQUET_DECIMAL_CONVERSION_ERR](#); SQLSTATE: [HY000](#)
Message: Column %d in %s: Decimal conversion error.
 - Error number: [6066](#); Symbol: [ER_LH_STRING_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: Column %d in %s: String is too long.

- Error number: 6067; Symbol: ER_LH_RESOURCE_PRINCIPAL_BUCKET_ERR; SQLSTATE: HY000

Message: Resource Principal endpoint is not configured. Cannot access following buckets: %s.

- Error number: 6068; Symbol: ER_LH_NO_FILES_FOUND; SQLSTATE: HY000

Message: No files found corresponding to the following data locations: %s.

- Error number: 6069; Symbol: ER_LH_EMPTY_FILE; SQLSTATE: HY000

Message: File %s is empty.

- Error number: 6070; Symbol: ER_LH_DUPLICATE_FILE; SQLSTATE: HY000

Message: File %s was not processed (duplicate).

- Error number: 6071; Symbol: ER_LH_AVRO_SCHEMA_DEPTH_EXCEEDS_MAX; SQLSTATE: HY000

Message: File %s: Avro schema depth exceeds max allowed depth.

- Error number: 6072; Symbol: ER_LH_AVRO_HEADER_MISMATCH; SQLSTATE: HY000

Message: File %s: Header does not match other files.

- Error number: 6073; Symbol: ER_LH_AVRO_ENUM_CANNOT_CONVERT_CHARSET; SQLSTATE: HY000

Message: File %s: Enum symbol can't convert to column charset.

- Error number: 6074; Symbol: ER_LH_AVRO_ENUM_MISMATCH; SQLSTATE: HY000

Message: File %s: Enum symbols are not the same, or are not in the same order.

- Error number: 6075; Symbol: ER_LH_AVRO_TYPE_CANNOT_CONVERT; SQLSTATE: HY000

Message: Column %d in %s: Avro value of physical type %.*s logical type %.*s cannot be converted to mysql type %s.

- Error number: 6076; Symbol: ER_LH_AVRO_FILE_ENDS_UNEXPECTEDLY; SQLSTATE: HY000

Message: File %.*s: Ends unexpectedly.

- Error number: 6077; Symbol: ER_LH_AVRO_FILE_DATA_CORRUPT; SQLSTATE: HY000

Message: File %.*s: File data might be corrupt.

- Error number: 6078; Symbol: ER_LH_AVRO_INVALID_UNION; SQLSTATE: HY000

Message: Column %d in %s: Invalid union encountered. Unions are only supported to represent nullable columns. One of the two types of the union must be null.

- Error number: 6079; Symbol: ER_LH_AVRO_INVALID_BLOCK_SIZE; SQLSTATE: HY000

Message: File %.*s: Invalid avro block size.

- Error number: 6080; Symbol: ER_LH_AVRO_INVALID_BLOCK_RECORD_COUNT; SQLSTATE: HY000

Message: File %.*s: Invalid Avro block record count.

-
- Error number: [6081](#); Symbol: [ER_LH_FORMAT_HEADER_NO_MAGIC_BYTES](#); SQLSTATE: [HY000](#)
Message: File %.*s: Cannot locate %s specific metadata. Either the file is corrupted or this is not an %s file.
 - Error number: [6082](#); Symbol: [ER_LH_AVRO_HEADER_METADATA_ERR](#); SQLSTATE: [HY000](#)
Message: File %.*s: Could not process Avro header metadata. The metadata is corrupted or invalid.
 - Error number: [6083](#); Symbol: [ER_LH_AVRO_HEADER_NO_SCHEMA](#); SQLSTATE: [HY000](#)
Message: File %.*s: No schema in Avro header metadata.
 - Error number: [6084](#); Symbol: [ER_LH_AVRO_NO_CODEC_IN_HEADER](#); SQLSTATE: [HY000](#)
Message: File %.*s: No codec in Avro header metadata.
 - Error number: [6085](#); Symbol: [ER_LH_AVRO_INVALID_NAME_IN_SCHEMA](#); SQLSTATE: [HY000](#)
Message: File %.*s: Invalid name in Avro schema.
 - Error number: [6086](#); Symbol: [ER_LH_AVRO_DECODING_ERR](#); SQLSTATE: [HY000](#)
Message: File %.*s: Error decoding Avro %.*s. %s
 - Error number: [6087](#); Symbol: [ER_LH_PARQUET_NON_UTF8_FILE_ENC](#); SQLSTATE: [HY000](#)
Message: Column %d in %s: String with non-utf8 file encoding.
 - Error number: [6088](#); Symbol: [ER_LH_PARQUET_SCHEMA_MISMATCH](#); SQLSTATE: [HY000](#)
Message: Difference in schema among Parquet files.
 - Error number: [6089](#); Symbol: [ER_LH_PARQUET_ROW_GROUP_SIZE_EXCEEDS_MAX](#); SQLSTATE: [HY000](#)
Message: File %s: Size of row group %ld is larger than maximum allowed size (%d).
 - Error number: [6090](#); Symbol: [ER_LH_PARQUET_CANNOT_LOCATE_OFFSET](#); SQLSTATE: [HY000](#)
Message: File %s: Cannot locate offset of row group %ld in metadata.
 - Error number: [6091](#); Symbol: [ER_LH_PARQUET_TYPE_CANNOT_CONVERT](#); SQLSTATE: [HY000](#)
Message: Column %d in parquet table cannot be converted to mysql format.
 - Error number: [6092](#); Symbol: [ER_LH_PARQUET_CANNOT_LOCATE_SCHEMA](#); SQLSTATE: [HY000](#)
Message: Cannot locate schema in %s.
 - Error number: [6093](#); Symbol: [ER_LH_INFER_SCHEMA_MISMATCH](#); SQLSTATE: [HY000](#)
Message: Found files with mismatched schemas.
 - Error number: [6094](#); Symbol: [ER_LH_OOM](#); SQLSTATE: [HY000](#)
Message: Insufficient memory.
 - Error number: [6095](#); Symbol: [ER_LH_WARN_INFER_SKIPPED_LINES](#); SQLSTATE: [HY000](#)
Message: Skipped %lu line(s) due to mismatched num of cols.

-
- Error number: 6096; Symbol: `ER_LH_WARN_INFER_SKIPPED_FILES`; SQLSTATE: HY000
Message: Skipped %lu file(s) due to mismatched num of cols.
 - Error number: 6097; Symbol: `ER_LH_INFER_FILE_HAS_NO_DATA`; SQLSTATE: HY000
Message: File %s is skipped because it has no valid data. File is either empty or all rows are skipped.
 - Error number: 6098; Symbol: `ER_LH_INFER_NO_DATA`; SQLSTATE: HY000
Message: No valid data found for processing.
 - Error number: 6099; Symbol: `ER_LH_INFER_NO_FILES`; SQLSTATE: HY000
Message: No valid files found for processing.
 - Error number: 6100; Symbol: `ER_LH_WARN_INFER_USE_DEFAULT_COL_NAMES`; SQLSTATE: HY000
Message: Used default column names for column index(s) %s as they are %s.
 - Error number: 6101; Symbol: `ER_LH_PARQUET_CANNOT_READ_HEADER`; SQLSTATE: HY000
Message: File %s: Unable to read Parquet header.
 - Error number: 6102; Symbol: `ER_LH_INFER_WARN_GOT_EXCEPTION`; SQLSTATE: HY000
Message: Got an exception while trying to process file task.
 - Error number: 6103; Symbol: `ER_LH_AVRO_CANNOT_PARSE_HEADER`; SQLSTATE: HY000
Message: File %.*s: Could not parse avro header. Probably corrupted avro file.
 - Error number: 6104; Symbol: `ER_LH_PARQUET_CANT_OPEN_FILE`; SQLSTATE: HY000
Message: Parquet reader cannot open %s. %s
 - Error number: 6105; Symbol: `ER_LH_TOO_LARGE_VALUE_ERR`; SQLSTATE: HY000
Message: File %.*s: %s
 - Error number: 6106; Symbol: `ER_LH_TOO_LARGE_ROW_ERR`; SQLSTATE: HY000
Message: File %.*s: %s
 - Error number: 6107; Symbol: `ER_TABLESAMPLE_PERCENTAGE`; SQLSTATE: 2202H
Message: Tablesample percentage should range between 0 and 100.
 - Error number: 6108; Symbol: `ER_TABLESAMPLE_ONLY_ON_BASE_TABLES`; SQLSTATE: HY000
Message: Tablesample can be applied only on base tables.
 - Error number: 6110; Symbol: `ER_RESULT_SIZE_LIMIT_EXCEEDED`; SQLSTATE: HY000
Message: Result size limit exceeded.
 - Error number: 6111; Symbol: `ER_LANGUAGE_COMPONENT_INTERNAL`; SQLSTATE: HY000
Message: Language component: Internal error.
 - Error number: 6112; Symbol: `ER_LANGUAGE_COMPONENT_CONCURRENCY_LIMIT`; SQLSTATE: HY000

Message: Language component: Concurrency limit (%s) has been reached.

- Error number: 6113; Symbol: ER_LANGUAGE_COMPONENT_RUNTIME; SQLSTATE: HY000

Message: %s> %s

- Error number: 6114; Symbol: ER_LANGUAGE_COMPONENT_TIMEZONE; SQLSTATE: HY000

Message: %s> Time zone %s is not supported.

- Error number: 6115; Symbol: ER_LANGUAGE_COMPONENT_KEYWORD; SQLSTATE: HY000

Message: %s> The identifier '%s' is a reserved word.

- Error number: 6116; Symbol: ER_LANGUAGE_COMPONENT_SET_SYSTEM_VARIABLE; SQLSTATE: HY000

Message: Language component: System variable '%s' cannot be configured when component is active.

- Error number: 6117; Symbol: ER_LANGUAGE_COMPONENT_UNSUPPORTED_TYPE; SQLSTATE: HY000

Message: %s> %s

- Error number: 6118; Symbol: ER_LANGUAGE_COMPONENT_CONVERSION; SQLSTATE: HY000

Message: %s> %s

- Error number: 6119; Symbol: ER_WARN_SP_STATEMENT_PARTIALLY_EXECUTED; SQLSTATE: HY000

Message: Stored program statement is partially completed. Result set might not contain all the rows.

- Error number: 6120; Symbol: ER_STMT_EXECUTION_NOT_ALLOWED_WITHIN_SP_OR_TRG_OR_UDF; SQLSTATE: HY000

Message: Executing SQL statement using %s Statement Handle Interface is not allowed within stored function, trigger or loadable function (UDF).

- Error number: 6121; Symbol: ER_LH_JSON_PARSING; SQLSTATE: HY000

Message: Column %d of %s : %s

- Error number: 6122; Symbol: ER_ENGINE_CANNOT_BE_DEFAULT; SQLSTATE: HY000

Message: Engine %s cannot be set as default_storage_engine.

- Error number: 6123; Symbol: ER_PARTITION_PREFIX_KEY_NOT_SUPPORTED; SQLSTATE: HY000

Message: Column '%s.%s.%s' having prefix key part '%s(%u)' in the PARTITION BY KEY() clause is not supported.

- Error number: 6124; Symbol: ER_WARN_DEPRECATED_NON_STANDARD_KEY; SQLSTATE: HY000

Message: Foreign key '%s' refers to non-unique key or partial key. This is deprecated and will be removed in a future release.

- Error number: 6125; Symbol: ER_FK_NO_UNIQUE_INDEX_PARENT; SQLSTATE: HY000

Message: Failed to add the foreign key constraint. Missing unique key for constraint '%s' in the referenced table '%s'

-
- Error number: [6126](#); Symbol: [ER_ACCESS_DENIED_NO_PROXY_GRANT](#); SQLSTATE: [HY000](#)
Message: Access denied for user '%s'@'%s', missing proxy privilege.
 - Error number: [6127](#); Symbol: [ER_ACCESS_DENIED_NO_PROXY](#); SQLSTATE: [HY000](#)
Message: Access denied for user '%s'@'%s', proxied user doesn't exist.
 - Error number: [6128](#); Symbol: [ER_LH_USER_DATA_ACCESS_FAILED](#); SQLSTATE: [HY000](#)
Message: Unable to access the following data locations: %s
 - Error number: [6129](#); Symbol: [ER_BULK_READER_ZSTD_ERROR](#); SQLSTATE: [HY000](#)
Message: ZSTD decompression failed: %s
 - Error number: [6130](#); Symbol: [ER_BULK_PARSER_ERROR](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [6131](#); Symbol: [ER_LH_INVALID_JSON_FILE_FORMAT_SCHEMA](#); SQLSTATE: [HY000](#)
Message: Invalid json file format schema: %s
 - Error number: [6132](#); Symbol: [ER_LH_INFER_JSON_INVALID_SCHEMA](#); SQLSTATE: [HY000](#)
Message: Inferred invalid schema. A single column with JSON type is the only valid schema for JSON file format.
 - Error number: [6133](#); Symbol: [ER_LH_JSON_FILE_FORMAT_WARN_INFER_SCHEMA](#); SQLSTATE: [HY000](#)
Message: Altered the inferred schema to a single JSON column.
 - Error number: [6134](#); Symbol: [ER_NON_SCALAR_USED_AS_KEY](#); SQLSTATE: [HY000](#)
Message: Non-scalar (e.g., vector) column '%s' cannot be used as key.
 - Error number: [6135](#); Symbol: [ER_INCOMPATIBLE_TYPE_AGG](#); SQLSTATE: [HY000](#)
Message: Columns aggregated with incompatible types: '%s', '%s'.
 - Error number: [6136](#); Symbol: [ER_DATA_INCOMPATIBLE_WITH_VECTOR](#); SQLSTATE: [HY000](#)
Message: Value of type '%s, size: %zu' cannot be converted to 'vector' type.
 - Error number: [6137](#); Symbol: [ER_EXCEEDS_VECTOR_MAX_DIMENSIONS](#); SQLSTATE: [HY000](#)
Message: Data size (%zu Bytes, %u dimensions) exceeds VECTOR max (%zu Bytes, %u dimensions) for column: '%s'
 - Error number: [6138](#); Symbol: [ER_TO_VECTOR_CONVERSION](#); SQLSTATE: [HY000](#)
Message: Data cannot be converted to a valid vector: '%.*s'
 - Error number: [6139](#); Symbol: [ER_EXTERNAL_UNSUPPORTED_INDEX_ALGORITHM](#); SQLSTATE: [HY000](#)
Message: This storage engine ignores the %s index algorithm.
 - Error number: [6140](#); Symbol: [ER_TP_CANNOT_DISABLE_MTL_WITH_DL](#); SQLSTATE: [HY000](#)

Message: The variable `thread_pool_max_transactions_limit` cannot be set to 0 when `thread_pool_dedicated_listeners` is ON.

`ER_TP_CANNOT_DISABLE_MTL_WITH_DL` was added in 8.4.1.

- Error number: `MY-010000`; Symbol: `ER_PARSER_TRACE`; SQLSTATE: `XX999`
Message: Parser saw: %s
- Error number: `MY-010001`; Symbol: `ER_BOOTSTRAP_CANT_THREAD`; SQLSTATE: `HY000`
Message: Can't create thread to handle bootstrap (errno: %d)
- Error number: `MY-010002`; Symbol: `ER_TRIGGER_INVALID_VALUE`; SQLSTATE: `HY000`
Message: Trigger for table '%s'. '%s': invalid %s value (%s).
- Error number: `MY-010003`; Symbol: `ER_OPT_WRONG_TREE`; SQLSTATE: `HY000`
Message: Wrong tree: %s
- Error number: `MY-010004`; Symbol: `ER_DD_FAILSAFE`; SQLSTATE: `HY000`
Message: Error: Invalid %s
- Error number: `MY-010005`; Symbol: `ER_DD_NO_WRITES_NO_REPOPULATION`; SQLSTATE: `HY000`
Message: Skip re-populating collations and character sets tables in %s%read-only mode.
- Error number: `MY-010006`; Symbol: `ER_DD_VERSION_FOUND`; SQLSTATE: `HY000`
Message: Using data dictionary with version '%d'.
- Error number: `MY-010007`; Symbol: `ER_DD_VERSION_INSTALLED`; SQLSTATE: `HY000`
Message: Installed data dictionary with version %d
- Error number: `MY-010008`; Symbol: `ER_DD_VERSION_UNSUPPORTED`; SQLSTATE: `HY000`
Message: Data Dictionary version '%d' not supported.
- Error number: `MY-010010`; Symbol: `ER_LOG_SYSLOG_CANNOT_OPEN`; SQLSTATE: `HY000`
Message: Cannot open %s; check privileges, or remove syseventlog from --log-error-services!
- Error number: `MY-010011`; Symbol: `ER_LOG_SLOW_CANNOT_OPEN`; SQLSTATE: `HY000`
Message: either restart the query logging by using "SET GLOBAL SLOW_QUERY_LOG=ON" or
- Error number: `MY-010012`; Symbol: `ER_LOG_GENERAL_CANNOT_OPEN`; SQLSTATE: `HY000`
Message: either restart the query logging by using "SET GLOBAL GENERAL_LOG=ON" or
- Error number: `MY-010013`; Symbol: `ER_LOG_CANNOT_WRITE`; SQLSTATE: `HY000`
Message: Failed to write to %s: %s
- Error number: `MY-010014`; Symbol: `ER_RPL_ZOMBIE_ENCOUNTERED`; SQLSTATE: `HY000`

Message: While initializing dump thread for replica with %s <%s>, found a zombie dump thread with the same %s. Source is killing the zombie dump thread(%u).

[ER_RPL_ZOMBIE_ENCOUNTERED](#) was removed after 8.4.3.

- Error number: [MY-010015](#); Symbol: [ER_RPL_GTID_TABLE_CANNOT_OPEN](#); SQLSTATE: [HY000](#)
Message: Gtid table is not ready to be used. Table '%s.%s' cannot be opened.
- Error number: [MY-010016](#); Symbol: [ER_SYSTEM_SCHEMA_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: System schema directory does not exist.
- Error number: [MY-010017](#); Symbol: [ER_DD_INIT_UPGRADE_FAILED](#); SQLSTATE: [HY000](#)
Message: Error in initializing dictionary, upgrade will do a cleanup and exit
- Error number: [MY-010018](#); Symbol: [ER_VIEW_UNKNOWN_CHARSET_OR_COLLATION](#); SQLSTATE: [HY000](#)
Message: View '%s'.'%s': unknown charset name and/or collation name (client: '%s'; connection: '%s').
- Error number: [MY-010019](#); Symbol: [ER_DD_VIEW_CANT_ALLOC_CHARSET](#); SQLSTATE: [HY000](#)
Message: Error in allocating memory for character set name for view %s.%s.
- Error number: [MY-010020](#); Symbol: [ER_DD_INIT_FAILED](#); SQLSTATE: [HY000](#)
Message: Data Dictionary initialization failed.
- Error number: [MY-010021](#); Symbol: [ER_DD_UPDATING_PLUGIN_MD_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to update plugin metadata in dictionary tables.
- Error number: [MY-010023](#); Symbol: [ER_DD_VIEW_CANT_CREATE](#); SQLSTATE: [HY000](#)
Message: Error in Creating View %s.%s
- Error number: [MY-010024](#); Symbol: [ER_DD_METADATA_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: Unable to start server. Cannot find the meta data for data dictionary table '%s'.
- Error number: [MY-010025](#); Symbol: [ER_DD_CACHE_NOT_EMPTY_AT_SHUTDOWN](#); SQLSTATE: [HY000](#)
Message: Dictionary cache not empty at shutdown.
- Error number: [MY-010026](#); Symbol: [ER_DD_OBJECT_REMAINS](#); SQLSTATE: [HY000](#)
Message: Dictionary objects used but not released.
- Error number: [MY-010027](#); Symbol: [ER_DD_OBJECT_REMAINS_IN_RELEASER](#); SQLSTATE: [HY000](#)
Message: Dictionary objects left in default releaser.
- Error number: [MY-010028](#); Symbol: [ER_DD_OBJECT_RELEASER_REMAINS](#); SQLSTATE: [HY000](#)
Message: Dictionary object auto releaser not deleted
- Error number: [MY-010029](#); Symbol: [ER_DD_CANT_GET_OBJECT_KEY](#); SQLSTATE: [HY000](#)

Message: Error: Unable to create primary object key

- Error number: [MY-010030](#); Symbol: [ER_DD_CANT_CREATE_OBJECT_KEY](#); SQLSTATE: [HY000](#)

Message: Error: Unable to create object key

- Error number: [MY-010031](#); Symbol: [ER_CANT_CREATE_HANDLE_MGR_THREAD](#); SQLSTATE: [HY000](#)

Message: Can't create handle_manager thread (errno= %d)

- Error number: [MY-010032](#); Symbol: [ER_RPL_REPO_HAS_GAPS](#); SQLSTATE: [HY000](#)

Message: It is not possible to change the type of the relay log's repository because there are workers' repositories with gaps. Please, fix the gaps first before doing such change.

- Error number: [MY-010033](#); Symbol: [ER_INVALID_VALUE_FOR_ENFORCE_GTID_CONSISTENCY](#); SQLSTATE: [HY000](#)

Message: option 'enforce-gtid-consistency': value '%s' was not recognized. Setting enforce-gtid-consistency to OFF.

- Error number: [MY-010034](#); Symbol: [ER_CHANGED_ENFORCE_GTID_CONSISTENCY](#); SQLSTATE: [HY000](#)

Message: Changed ENFORCE_GTID_CONSISTENCY from %s to %s.

- Error number: [MY-010035](#); Symbol: [ER_CHANGED_GTID_MODE](#); SQLSTATE: [HY000](#)

Message: Changed GTID_MODE from %s to %s.

- Error number: [MY-010036](#); Symbol: [ER_DISABLED_STORAGE_ENGINE_AS_DEFAULT](#); SQLSTATE: [HY000](#)

Message: %s is set to a disabled storage engine %s.

- Error number: [MY-010037](#); Symbol: [ER_DEBUG_SYNC_HIT](#); SQLSTATE: [HY000](#)

Message: Debug sync points hit: %s

- Error number: [MY-010038](#); Symbol: [ER_DEBUG_SYNC_EXECUTED](#); SQLSTATE: [HY000](#)

Message: Debug sync points executed: %s

- Error number: [MY-010039](#); Symbol: [ER_DEBUG_SYNC_THREAD_MAX](#); SQLSTATE: [HY000](#)

Message: Debug sync points max active per thread: %s

- Error number: [MY-010040](#); Symbol: [ER_DEBUG_SYNC_OOM](#); SQLSTATE: [HY000](#)

Message: Debug Sync Facility disabled due to lack of memory.

- Error number: [MY-010041](#); Symbol: [ER_CANT_INIT_TC_LOG](#); SQLSTATE: [HY000](#)

Message: Can't init tc log

- Error number: [MY-010042](#); Symbol: [ER_EVENT_CANT_INIT_QUEUE](#); SQLSTATE: [HY000](#)

Message: Event Scheduler: Can't initialize the execution queue

-
- Error number: `MY-010043`; Symbol: `ER_EVENT_PURGING_QUEUE`; SQLSTATE: `HY000`
Message: Event Scheduler: Purging the queue. %u events
 - Error number: `MY-010044`; Symbol: `ER_EVENT_LAST_EXECUTION`; SQLSTATE: `HY000`
Message: Event Scheduler: Last execution of %s.%s. %s
 - Error number: `MY-010045`; Symbol: `ER_EVENT_MESSAGE_STACK`; SQLSTATE: `HY000`
Message: %*s
 - Error number: `MY-010046`; Symbol: `ER_EVENT_EXECUTION_FAILED`; SQLSTATE: `HY000`
Message: Event Scheduler: [%s].[%s.%s] event execution failed.
 - Error number: `MY-010047`; Symbol: `ER_CANT_INIT_SCHEDULER_THREAD`; SQLSTATE: `HY000`
Message: Event Scheduler: Cannot initialize the scheduler thread
 - Error number: `MY-010048`; Symbol: `ER_SCHEDULER_STOPPED`; SQLSTATE: `HY000`
Message: Event Scheduler: Stopped
 - Error number: `MY-010049`; Symbol: `ER_CANT_CREATE_SCHEDULER_THREAD`; SQLSTATE: `HY000`
Message: Event scheduler: Failed to start scheduler, Can not create thread for event scheduler (errno=%d)
 - Error number: `MY-010050`; Symbol: `ER_SCHEDULER_WAITING`; SQLSTATE: `HY000`
Message: Event Scheduler: Waiting for the scheduler thread to reply
 - Error number: `MY-010051`; Symbol: `ER_SCHEDULER_STARTED`; SQLSTATE: `HY000`
Message: Event Scheduler: scheduler thread started with id %u
 - Error number: `MY-010052`; Symbol: `ER_SCHEDULER_STOPPING_FAILED_TO_GET_EVENT`; SQLSTATE: `HY000`
Message: Event Scheduler: Serious error during getting next event to execute. Stopping
 - Error number: `MY-010053`; Symbol: `ER_SCHEDULER_STOPPING_FAILED_TO_CREATE_WORKER`; SQLSTATE: `HY000`
Message: Event_scheduler::execute_top: Can not create event worker thread (errno=%d). Stopping event scheduler
 - Error number: `MY-010054`; Symbol: `ER_SCHEDULER_KILLING`; SQLSTATE: `HY000`
Message: Event Scheduler: Killing the scheduler thread, thread id %u
 - Error number: `MY-010055`; Symbol: `ER_UNABLE_TO_RESOLVE_IP`; SQLSTATE: `HY000`
Message: IP address '%s' could not be resolved: %s
 - Error number: `MY-010056`; Symbol: `ER_UNABLE_TO_RESOLVE_HOSTNAME`; SQLSTATE: `HY000`
Message: Host name '%s' could not be resolved: %s

-
- Error number: [MY-010057](#); Symbol: [ER_HOSTNAME_RESEMBLES_IPV4](#); SQLSTATE: [HY000](#)
Message: IP address '%s' has been resolved to the host name '%s', which resembles IPv4-address itself.
 - Error number: [MY-010058](#); Symbol: [ER_HOSTNAME_DOESNT_RESOLVE_TO](#); SQLSTATE: [HY000](#)
Message: Hostname '%s' does not resolve to '%s'.
 - Error number: [MY-010059](#); Symbol: [ER_ADDRESSES_FOR_HOSTNAME_HEADER](#); SQLSTATE: [HY000](#)
Message: Hostname '%s' has the following IP addresses:
 - Error number: [MY-010060](#); Symbol: [ER_ADDRESSES_FOR_HOSTNAME_LIST_ITEM](#); SQLSTATE: [HY000](#)
Message: - %s
 - Error number: [MY-010061](#); Symbol: [ER_TRG_WITHOUT_DEFINER](#); SQLSTATE: [HY000](#)
Message: Definer clause is missing in Trigger of Table %s. Rebuild Trigger to fix definer.
 - Error number: [MY-010062](#); Symbol: [ER_TRG_NO_CLIENT_CHARSET](#); SQLSTATE: [HY000](#)
Message: Client character set is missing for trigger of table %s. Using default character set.
 - Error number: [MY-010063](#); Symbol: [ER_PARSING_VIEW](#); SQLSTATE: [HY000](#)
Message: Error in parsing view %s.%s
 - Error number: [MY-010064](#); Symbol: [ER_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP](#); SQLSTATE: [HY000](#)
Message: Failed to bootstrap components infrastructure.
 - Error number: [MY-010065](#); Symbol: [ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN](#); SQLSTATE: [HY000](#)
Message: Failed to shutdown components infrastructure.
 - Error number: [MY-010066](#); Symbol: [ER_COMPONENTS_PERSIST_LOADER_BOOTSTRAP](#); SQLSTATE: [HY000](#)
Message: Failed to bootstrap persistent components loader.
 - Error number: [MY-010067](#); Symbol: [ER_DEPART_WITH_GRACE](#); SQLSTATE: [HY000](#)
Message: Giving %d client threads a chance to die gracefully
 - Error number: [MY-010068](#); Symbol: [ER_CA_SELF_SIGNED](#); SQLSTATE: [HY000](#)
Message: CA certificate %s is self signed.
 - Error number: [MY-010069](#); Symbol: [ER_SSL_LIBRARY_ERROR](#); SQLSTATE: [HY000](#)
Message: Failed to set up SSL because of the following SSL library error: %s
 - Error number: [MY-010070](#); Symbol: [ER_NO_THD_NO_UUID](#); SQLSTATE: [HY000](#)
Message: Failed to generate a server UUID because it is failed to allocate the THD.

-
- Error number: `MY-010071`; Symbol: `ER_UUID_SALT`; SQLSTATE: `HY000`
Message: Salting uuid generator variables, current_pid: %lu, server_start_time: %lu, bytes_sent: %llu,
 - Error number: `MY-010072`; Symbol: `ER_UUID_IS`; SQLSTATE: `HY000`
Message: Generated uuid: '%s', server_start_time: %lu, bytes_sent: %llu
 - Error number: `MY-010073`; Symbol: `ER_UUID_INVALID`; SQLSTATE: `HY000`
Message: The server_uuid stored in auto.cnf file is not a valid UUID.
 - Error number: `MY-010074`; Symbol: `ER_UUID_SCRUB`; SQLSTATE: `HY000`
Message: Garbage characters found at the end of the server_uuid value in auto.cnf file. It should be of length '%d' (UUID_LENGTH). Clear it and restart the server.
 - Error number: `MY-010075`; Symbol: `ER_CREATING_NEW_UUID`; SQLSTATE: `HY000`
Message: No existing UUID has been found, so we assume that this is the first time that this server has been started. Generating a new UUID: %s.
 - Error number: `MY-010076`; Symbol: `ER_CANT_CREATE_UUID`; SQLSTATE: `HY000`
Message: Initialization of the server's UUID failed because it could not be read from the auto.cnf file. If this is a new server, the initialization failed because it was not possible to generate a new UUID.
 - Error number: `MY-010077`; Symbol: `ER_UNKNOWN_UNSUPPORTED_STORAGE_ENGINE`; SQLSTATE: `HY000`
Message: Unknown/unsupported storage engine: %s
 - Error number: `MY-010078`; Symbol: `ER_SECURE_AUTH_VALUE_UNSUPPORTED`; SQLSTATE: `HY000`
Message: Unsupported value 0 for secure-auth
 - Error number: `MY-010079`; Symbol: `ER_INVALID_INSTRUMENT`; SQLSTATE: `HY000`
Message: Invalid instrument name or value for performance_schema_instrument '%s'.
 - Error number: `MY-010080`; Symbol: `ER_INNOQB_MANDATORY`; SQLSTATE: `HY000`
Message: The use of InnoDB is mandatory since MySQL 5.7. The former options like '--innodb=0/1/OFF/ON' or '--skip-innodb' are ignored.
 - Error number: `MY-010083`; Symbol: `ER_VERBOSE_REQUIRES_HELP`; SQLSTATE: `HY000`
Message: --verbose is for use with --help; did you mean --log-error-verbosity?
 - Error number: `MY-010084`; Symbol: `ER_POINTLESS_WITHOUT_SLOWLOG`; SQLSTATE: `HY000`
Message: options --log-slow-admin-statements, --log-queries-not-using-indexes and --log-slow-replica-statements have no effect if --slow-query-log is not set
 - Error number: `MY-010085`; Symbol: `ER_WASTEFUL_NET_BUFFER_SIZE`; SQLSTATE: `HY000`
Message: net_buffer_length (%lu) is set to be larger than max_allowed_packet (%lu). Please rectify.
 - Error number: `MY-010086`; Symbol: `ER_DEPRECATED_TIMESTAMP_IMPLICIT_DEFAULTS`; SQLSTATE: `HY000`

Message: TIMESTAMP with implicit DEFAULT value is deprecated. Please use --explicit_defaults_for_timestamp server option (see documentation for more details).

- Error number: `MY-010087`; Symbol: `ER_FT_BOOL_SYNTAX_INVALID`; SQLSTATE: `HY000`

Message: Invalid ft-boolean-syntax string: %s

- Error number: `MY-010088`; Symbol: `ER_CREDENTIALLESS_AUTO_USER_BAD`; SQLSTATE: `HY000`

Message: 'NO_AUTO_CREATE_USER' sql mode was not set.

- Error number: `MY-010089`; Symbol: `ER_CONNECTION_HANDLING_OOM`; SQLSTATE: `HY000`

Message: Could not allocate memory for connection handling

- Error number: `MY-010090`; Symbol: `ER_THREAD_HANDLING_OOM`; SQLSTATE: `HY000`

Message: Could not allocate memory for thread handling

- Error number: `MY-010091`; Symbol: `ER_CANT_CREATE_TEST_FILE`; SQLSTATE: `HY000`

Message: Can't create test file %s

- Error number: `MY-010092`; Symbol: `ER_CANT_CREATE_PID_FILE`; SQLSTATE: `HY000`

Message: Can't start server: can't create PID file: %s

- Error number: `MY-010093`; Symbol: `ER_CANT_REMOVE_PID_FILE`; SQLSTATE: `HY000`

Message: Unable to delete pid file: %s

- Error number: `MY-010094`; Symbol: `ER_CANT_CREATE_SHUTDOWN_THREAD`; SQLSTATE: `HY000`

Message: Can't create thread to handle shutdown requests (errno= %d)

- Error number: `MY-010095`; Symbol: `ER_SEC_FILE_PRIV_CANT_ACCESS_DIR`; SQLSTATE: `HY000`

Message: Failed to access directory for --secure-file-priv. Please make sure that directory exists and is accessible by MySQL Server. Supplied value : %s

- Error number: `MY-010096`; Symbol: `ER_SEC_FILE_PRIV_IGNORED`; SQLSTATE: `HY000`

Message: Ignoring --secure-file-priv value as server is running with --initialize(-insecure).

- Error number: `MY-010097`; Symbol: `ER_SEC_FILE_PRIV_EMPTY`; SQLSTATE: `HY000`

Message: Insecure configuration for --secure-file-priv: Current value does not restrict location of generated files. Consider setting it to a valid, non-empty path.

- Error number: `MY-010098`; Symbol: `ER_SEC_FILE_PRIV_NULL`; SQLSTATE: `HY000`

Message: --secure-file-priv is set to NULL. Operations related to importing and exporting data are disabled

- Error number: `MY-010099`; Symbol: `ER_SEC_FILE_PRIV_DIRECTORY_INSECURE`; SQLSTATE: `HY000`

Message: Insecure configuration for --secure-file-priv: %s is accessible through --secure-file-priv. Consider choosing a different directory.

-
- Error number: `MY-010100`; Symbol: `ER_SEC_FILE_PRIV_CANT_STAT`; SQLSTATE: `HY000`
Message: Failed to get stat for directory pointed out by --secure-file-priv
 - Error number: `MY-010101`; Symbol: `ER_SEC_FILE_PRIV_DIRECTORY_PERMISSIONS`; SQLSTATE: `HY000`
Message: Insecure configuration for --secure-file-priv: Location is accessible to all OS users. Consider choosing a different directory.
 - Error number: `MY-010102`; Symbol: `ER_SEC_FILE_PRIV_ARGUMENT_TOO_LONG`; SQLSTATE: `HY000`
Message: Value for --secure-file-priv is longer than maximum limit of %d
 - Error number: `MY-010103`; Symbol: `ER_CANT_CREATE_NAMED_PIPES_THREAD`; SQLSTATE: `HY000`
Message: Can't create thread to handle named pipes (errno= %d)
 - Error number: `MY-010104`; Symbol: `ER_CANT_CREATE_TCPIP_THREAD`; SQLSTATE: `HY000`
Message: Can't create thread to handle TCP/IP (errno= %d)
 - Error number: `MY-010105`; Symbol: `ER_CANT_CREATE_SHM_THREAD`; SQLSTATE: `HY000`
Message: Can't create thread to handle shared memory (errno= %d)
 - Error number: `MY-010106`; Symbol: `ER_CANT_CREATE_INTERRUPT_THREAD`; SQLSTATE: `HY000`
Message: Can't create interrupt-thread (error %d, errno: %d)
 - Error number: `MY-010107`; Symbol: `ER_WRITABLE_CONFIG_REMOVED`; SQLSTATE: `HY000`
Message: World-writable config file '%s' has been removed.
 - Error number: `MY-010108`; Symbol: `ER_CORE_VALUES`; SQLSTATE: `HY000`
Message: setrlimit could not change the size of core files to 'infinity'; We may not be able to generate a core file on signals
 - Error number: `MY-010109`; Symbol: `ER_WRONG_DATETIME_SPEC`; SQLSTATE: `HY000`
Message: Wrong date/time format specifier: %s
 - Error number: `MY-010110`; Symbol: `ER_RPL_BINLOG_FILTERS_OOM`; SQLSTATE: `HY000`
Message: Could not allocate replication and binlog filters: %s
 - Error number: `MY-010111`; Symbol: `ER_KEYCACHE_OOM`; SQLSTATE: `HY000`
Message: Cannot allocate the keycache
 - Error number: `MY-010112`; Symbol: `ER_CONFIRMING_THE_FUTURE`; SQLSTATE: `HY000`
Message: Current time has got past year 2038. Validating current time with %d iterations before initiating the normal server shutdown process.
 - Error number: `MY-010113`; Symbol: `ER_BACK_IN_TIME`; SQLSTATE: `HY000`
Message: Iteration %d: Obtained valid current time from system

-
- Error number: [MY-010114](#); Symbol: [ER_FUTURE_DATE](#); SQLSTATE: [HY000](#)
Message: Iteration %d: Current time obtained from system is greater than 2038
 - Error number: [MY-010115](#); Symbol: [ER_UNSUPPORTED_DATE](#); SQLSTATE: [HY000](#)
Message: This MySQL server doesn't support dates later than 2038
 - Error number: [MY-010116](#); Symbol: [ER_STARTING_AS](#); SQLSTATE: [HY000](#)
Message: %s (mysqld %s) starting as process %lu
 - Error number: [MY-010117](#); Symbol: [ER_SHUTTING_DOWN_REPLICA_THREADS](#); SQLSTATE: [HY000](#)
Message: Shutting down replica threads
 - Error number: [MY-010118](#); Symbol: [ER_DISCONNECTING_REMAINING_CLIENTS](#); SQLSTATE: [HY000](#)
Message: Forcefully disconnecting %d remaining clients
 - Error number: [MY-010119](#); Symbol: [ER_ABORTING](#); SQLSTATE: [HY000](#)
Message: Aborting
 - Error number: [MY-010120](#); Symbol: [ER_BINLOG_END](#); SQLSTATE: [HY000](#)
Message: Binlog end
 - Error number: [MY-010121](#); Symbol: [ER_CALL_ME_LOCALHOST](#); SQLSTATE: [HY000](#)
Message: gethostname failed, using '%s' as hostname
 - Error number: [MY-010122](#); Symbol: [ER_USER_REQUIRES_ROOT](#); SQLSTATE: [HY000](#)
Message: One can only use the --user switch if running as root
 - Error number: [MY-010123](#); Symbol: [ER_REALLY_RUN_AS_ROOT](#); SQLSTATE: [HY000](#)
Message: Fatal error: Please read "Security" section of the manual to find out how to run mysqld as root!
 - Error number: [MY-010124](#); Symbol: [ER_USER_WHAT_USER](#); SQLSTATE: [HY000](#)
Message: Fatal error: Can't change to run as user '%s' ; Please check that the user exists!
 - Error number: [MY-010125](#); Symbol: [ER_TRANSPORTS_WHAT_TRANSPORTS](#); SQLSTATE: [HY000](#)
Message: Server is started with --require-secure-transport=ON but no secure transports (SSL or Shared Memory) are configured.
 - Error number: [MY-010126](#); Symbol: [ER_FAIL_SETGID](#); SQLSTATE: [HY000](#)
Message: setgid: %s
 - Error number: [MY-010127](#); Symbol: [ER_FAIL_SETUID](#); SQLSTATE: [HY000](#)
Message: setuid: %s
 - Error number: [MY-010128](#); Symbol: [ER_FAIL_SETREGID](#); SQLSTATE: [HY000](#)
Message: setregid: %s

-
- Error number: [MY-010129](#); Symbol: [ER_FAIL_SETREUID](#); SQLSTATE: [HY000](#)
Message: setreuid: %s
 - Error number: [MY-010130](#); Symbol: [ER_FAIL_CHROOT](#); SQLSTATE: [HY000](#)
Message: chroot: %s
 - Error number: [MY-010131](#); Symbol: [ER_WIN_LISTEN_BUT_HOW](#); SQLSTATE: [HY000](#)
Message: TCP/IP, --shared-memory, or --named-pipe should be configured on NT OS
 - Error number: [MY-010132](#); Symbol: [ER_NOT_RIGHT_NOW](#); SQLSTATE: [HY000](#)
Message: CTRL-C ignored during startup
 - Error number: [MY-010133](#); Symbol: [ER_FIXING_CLIENT_CHARSET](#); SQLSTATE: [HY000](#)
Message: '%s' can not be used as client character set. '%s' will be used as default client character set.
 - Error number: [MY-010134](#); Symbol: [ER_OOM](#); SQLSTATE: [HY000](#)
Message: Out of memory
 - Error number: [MY-010135](#); Symbol: [ER_FAILED_TO_LOCK_MEM](#); SQLSTATE: [HY000](#)
Message: Failed to lock memory. Errno: %d
 - Error number: [MY-010136](#); Symbol: [ER_MYINIT_FAILED](#); SQLSTATE: [HY000](#)
Message: my_init() failed.
 - Error number: [MY-010137](#); Symbol: [ER_BEG_INITFILE](#); SQLSTATE: [HY000](#)
Message: Execution of init_file '%s' started.
 - Error number: [MY-010138](#); Symbol: [ER_END_INITFILE](#); SQLSTATE: [HY000](#)
Message: Execution of init_file '%s' ended.
 - Error number: [MY-010139](#); Symbol: [ER_CHANGED_MAX_OPEN_FILES](#); SQLSTATE: [HY000](#)
Message: Changed limits: max_open_files: %lu (requested %lu)
 - Error number: [MY-010140](#); Symbol: [ER_CANT_INCREASE_MAX_OPEN_FILES](#); SQLSTATE: [HY000](#)
Message: Could not increase number of max_open_files to more than %lu (request: %lu)
 - Error number: [MY-010141](#); Symbol: [ER_CHANGED_MAX_CONNECTIONS](#); SQLSTATE: [HY000](#)
Message: Changed limits: max_connections: %lu (requested %lu)
 - Error number: [MY-010142](#); Symbol: [ER_CHANGED_TABLE_OPEN_CACHE](#); SQLSTATE: [HY000](#)
Message: Changed limits: table_open_cache: %lu (requested %lu)
 - Error number: [MY-010143](#); Symbol: [ER_THE_USER_ABIDES](#); SQLSTATE: [HY000](#)
Message: Ignoring user change to '%s' because the user was set to '%s' earlier on the command line
 - Error number: [MY-010144](#); Symbol: [ER_RPL_CANT_ADD_DO_TABLE](#); SQLSTATE: [HY000](#)

Message: Could not add do table rule '%s'!

- Error number: [MY-010145](#); Symbol: [ER_RPL_CANT_ADD_IGNORE_TABLE](#); SQLSTATE: [HY000](#)

Message: Could not add ignore table rule '%s'!

- Error number: [MY-010146](#); Symbol: [ER_TRACK_VARIABLES_BOGUS](#); SQLSTATE: [HY000](#)

Message: The variable session_track_system_variables either has duplicate values or invalid values.

- Error number: [MY-010147](#); Symbol: [ER_EXCESS_ARGUMENTS](#); SQLSTATE: [HY000](#)

Message: Too many arguments (first extra is '%s').

- Error number: [MY-010148](#); Symbol: [ER_VERBOSE_HINT](#); SQLSTATE: [HY000](#)

Message: Use --verbose --help to get a list of available options!

- Error number: [MY-010149](#); Symbol: [ER_CANT_READ_ERRMSG](#); SQLSTATE: [HY000](#)

Message: Unable to read errmsg.sys file

- Error number: [MY-010150](#); Symbol: [ER_CANT_INIT_DBS](#); SQLSTATE: [HY000](#)

Message: Can't init databases

- Error number: [MY-010151](#); Symbol: [ER_LOG_OUTPUT_CONTRADICTORY](#); SQLSTATE: [HY000](#)

Message: There were other values specified to log-output besides NONE. Disabling slow and general logs anyway.

- Error number: [MY-010152](#); Symbol: [ER_NO_CSV_NO_LOG_TABLES](#); SQLSTATE: [HY000](#)

Message: CSV engine is not present, falling back to the log files

- Error number: [MY-010153](#); Symbol: [ER_RPL_REWRITEDB_MISSING_ARROW](#); SQLSTATE: [HY000](#)

Message: Bad syntax in replicate-rewrite-db - missing '->'!

- Error number: [MY-010154](#); Symbol: [ER_RPL_REWRITEDB_EMPTY_FROM](#); SQLSTATE: [HY000](#)

Message: Bad syntax in replicate-rewrite-db - empty FROM db!

- Error number: [MY-010155](#); Symbol: [ER_RPL_REWRITEDB_EMPTY_TO](#); SQLSTATE: [HY000](#)

Message: Bad syntax in replicate-rewrite-db - empty TO db!

- Error number: [MY-010156](#); Symbol: [ER_LOG_FILES_GIVEN_LOG_OUTPUT_IS_TABLE](#); SQLSTATE: [HY000](#)

Message: Although a path was specified for the %s, log tables are used. To enable logging to files use the --log-output=file option.

- Error number: [MY-010157](#); Symbol: [ER_LOG_FILE_INVALID](#); SQLSTATE: [HY000](#)

Message: Invalid value for %s: %s

- Error number: [MY-010158](#); Symbol: [ER_LOWER_CASE_TABLE_NAMES_CS_DD_ON_CI_FS_UNSUPPORTED](#); SQLSTATE: [HY000](#)

Message: The server option 'lower_case_table_names' is configured to use case sensitive table names but the data directory is on a case-insensitive file system which is an unsupported combination. Please consider either using a case sensitive file system for your data directory or switching to a case-insensitive table name mode.

- Error number: [MY-010159](#); Symbol: [ER_LOWER_CASE_TABLE_NAMES_USING_2](#); SQLSTATE: [HY000](#)

Message: Setting lower_case_table_names=2 because file system for %s is case insensitive

- Error number: [MY-010160](#); Symbol: [ER_LOWER_CASE_TABLE_NAMES_USING_0](#); SQLSTATE: [HY000](#)

Message: lower_case_table_names was set to 2, even though your the file system '%s' is case sensitive. Now setting lower_case_table_names to 0 to avoid future problems.

- Error number: [MY-010161](#); Symbol: [ER_NEED_LOG_BIN](#); SQLSTATE: [HY000](#)

Message: You need to use --log-bin to make %s work.

- Error number: [MY-010162](#); Symbol: [ER_NEED_FILE_INSTEAD_OF_DIR](#); SQLSTATE: [HY000](#)

Message: Path '%s' is a directory name, please specify a file name for %s option

- Error number: [MY-010163](#); Symbol: [ER_LOG_BIN_BETTER_WITH_NAME](#); SQLSTATE: [HY000](#)

Message: No argument was provided to --log-bin, and --log-bin-index was not used; so replication may break when this MySQL server acts as a source and has his hostname changed!! Please use '--log-bin=%s' to avoid this problem.

- Error number: [MY-010164](#); Symbol: [ER_BINLOG_NEEDS_SERVERID](#); SQLSTATE: [HY000](#)

Message: You have enabled the binary log, but you haven't provided the mandatory server-id. Please refer to the proper server start-up parameters documentation

- Error number: [MY-010165](#); Symbol: [ER_RPL_CANT_MAKE_PATHS](#); SQLSTATE: [HY000](#)

Message: Unable to create replication path names: out of memory or path names too long (path name exceeds %d or file name exceeds %d).

- Error number: [MY-010166](#); Symbol: [ER_CANT_INITIALIZE_GTID](#); SQLSTATE: [HY000](#)

Message: Failed to initialize GTID structures.

- Error number: [MY-010167](#); Symbol: [ER_CANT_INITIALIZE_EARLY_PLUGINS](#); SQLSTATE: [HY000](#)

Message: Failed to initialize early plugins.

- Error number: [MY-010168](#); Symbol: [ER_CANT_INITIALIZE_BUILTIN_PLUGINS](#); SQLSTATE: [HY000](#)

Message: Failed to initialize builtin plugins.

- Error number: [MY-010169](#); Symbol: [ER_CANT_INITIALIZE_DYNAMIC_PLUGINS](#); SQLSTATE: [HY000](#)

Message: Failed to initialize dynamic plugins.

- Error number: [MY-010170](#); Symbol: [ER_PERFSHEMA_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Performance schema disabled (reason: init failed).

- Error number: [MY-010171](#); Symbol: [ER_STACKSIZE_UNEXPECTED](#); SQLSTATE: [HY000](#)

Message: Asked for %lu thread stack, but got %ld

- Error number: [MY-010173](#); Symbol: [ER_CANT_STAT_DATADIR](#); SQLSTATE: [HY000](#)

Message: Can't read data directory's stats (%d): %s. Assuming that it's not owned by the same user/group

- Error number: [MY-010174](#); Symbol: [ER_CANT_CHOWN_DATADIR](#); SQLSTATE: [HY000](#)

Message: Can't change data directory owner to %s

- Error number: [MY-010175](#); Symbol: [ER_CANT_SET_UP_PERSISTED_VALUES](#); SQLSTATE: [HY000](#)

Message: Setting persistent options failed.

- Error number: [MY-010176](#); Symbol: [ER_CANT_SAVE_GTIDS](#); SQLSTATE: [HY000](#)

Message: Failed to save the set of Global Transaction Identifiers of the last binary log into the mysql.gtid_executed table while the server was shutting down. The next server restart will make another attempt to save Global Transaction Identifiers into the table.

- Error number: [MY-010178](#); Symbol: [ER_CANT_JOIN_SHUTDOWN_THREAD](#); SQLSTATE: [HY000](#)

Message: Could not join %sthread. error:%d

- Error number: [MY-010179](#); Symbol: [ER_CANT_HASH_DO_AND_IGNORE_RULES](#); SQLSTATE: [HY000](#)

Message: An error occurred while building do_table and ignore_table rules to hashes for global replication filter.

- Error number: [MY-010180](#); Symbol: [ER_CANT_OPEN_CA](#); SQLSTATE: [HY000](#)

Message: Error opening CA certificate file

- Error number: [MY-010181](#); Symbol: [ER_CANT_ACCESS_CAPATH](#); SQLSTATE: [HY000](#)

Message: Error accessing directory pointed by --ssl-capath

- Error number: [MY-010182](#); Symbol: [ER_SSL_TRYING_DATADIR_DEFAULTS](#); SQLSTATE: [HY000](#)

Message: Found %s, %s and %s in data directory. Trying to enable SSL support using them.

- Error number: [MY-010183](#); Symbol: [ER_AUTO_OPTIONS_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to create %s(file: '%s', errno %d)

- Error number: [MY-010184](#); Symbol: [ER_CANT_INIT_TIMER](#); SQLSTATE: [HY000](#)

Message: Failed to initialize timer component (errno %d).

- Error number: [MY-010185](#); Symbol: [ER_SERVERID_TOO_LARGE](#); SQLSTATE: [HY000](#)

Message: server-id configured is too large to represent with server-id-bits configured.

- Error number: [MY-010186](#); Symbol: [ER_DEFAULT_SE_UNAVAILABLE](#); SQLSTATE: [HY000](#)

Message: Default%s storage engine (%s) is not available

- Error number: [MY-010187](#); Symbol: [ER_CANT_OPEN_ERROR_LOG](#); SQLSTATE: [HY000](#)

Message: Could not open file '%s' for error logging%s%s

- Error number: [MY-010188](#); Symbol: [ER_INVALID_ERROR_LOG_NAME](#); SQLSTATE: [HY000](#)

Message: Invalid log file name after expanding symlinks: '%s'

- Error number: [MY-010189](#); Symbol: [ER_RPL_INFINITY_DENIED](#); SQLSTATE: [HY000](#)

Message: using --replicate-same-server-id in conjunction with --log-replica-updates is impossible, it would lead to infinite loops in this server.

- Error number: [MY-010190](#); Symbol: [ER_RPL_INFINITY_IGNORED](#); SQLSTATE: [HY000](#)

Message: using --replicate-same-server-id in conjunction with --log-replica-updates would lead to infinite loops in this server. However this will be ignored as the --log-bin option is not defined or your server is running with global transaction identifiers enabled.

- Error number: [MY-010192](#); Symbol: [ER_TABLE_CHECK_INTACT](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-010193](#); Symbol: [ER_DD_TABLESPACE_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Unable to start server. The data dictionary tablespace '%s' does not exist.

- Error number: [MY-010194](#); Symbol: [ER_DD_TRG_CONNECTION_COLLATION_MISSING](#); SQLSTATE: [HY000](#)

Message: Connection collation is missing for trigger of table %s. Using default connection collation.

- Error number: [MY-010195](#); Symbol: [ER_DD_TRG_DB_COLLATION_MISSING](#); SQLSTATE: [HY000](#)

Message: Database collation is missing for trigger of table %s. Using Default character set.

- Error number: [MY-010196](#); Symbol: [ER_DD_TRG_DEFINER_OOM](#); SQLSTATE: [HY000](#)

Message: Error in Memory allocation for Definer %s for Trigger.

- Error number: [MY-010197](#); Symbol: [ER_DD_TRG_FILE_UNREADABLE](#); SQLSTATE: [HY000](#)

Message: Error in reading %s.TRG file.

- Error number: [MY-010198](#); Symbol: [ER_TRG_CANT_PARSE](#); SQLSTATE: [HY000](#)

Message: Error in parsing Triggers from %s.TRG file.

- Error number: [MY-010199](#); Symbol: [ER_DD_TRG_CANT_ADD](#); SQLSTATE: [HY000](#)

Message: Error in creating DD entry for Trigger %s.%s

- Error number: [MY-010200](#); Symbol: [ER_DD_CANT_RESOLVE_VIEW](#); SQLSTATE: [HY000](#)

Message: Resolving dependency for the view '%s.%s' failed. View is no more valid to use

- Error number: [MY-010201](#); Symbol: [ER_DD_VIEW_WITHOUT_DEFINER](#); SQLSTATE: [HY000](#)

Message: %s.%s has no definer (as per an old view format). Current user is used as definer. Please recreate the view.

-
- Error number: `MY-010202`; Symbol: `ER_PLUGIN_INIT_FAILED`; SQLSTATE: `HY000`
Message: Plugin '%s' init function returned error.
 - Error number: `MY-010203`; Symbol: `ER_RPL_TRX_DELEGATES_INIT_FAILED`; SQLSTATE: `HY000`
Message: Initialization of transaction delegates failed. Please report a bug.
 - Error number: `MY-010204`; Symbol: `ER_RPL_BINLOG_STORAGE_DELEGATES_INIT_FAILED`; SQLSTATE: `HY000`
Message: Initialization binlog storage delegates failed. Please report a bug.
 - Error number: `MY-010205`; Symbol: `ER_RPL_BINLOG_TRANSMIT_DELEGATES_INIT_FAILED`; SQLSTATE: `HY000`
Message: Initialization of binlog transmit delegates failed. Please report a bug.
 - Error number: `MY-010206`; Symbol: `ER_RPL_BINLOG_RELAY_DELEGATES_INIT_FAILED`; SQLSTATE: `HY000`
Message: Initialization binlog relay IO delegates failed. Please report a bug.
 - Error number: `MY-010207`; Symbol: `ER_RPL_PLUGIN_FUNCTION_FAILED`; SQLSTATE: `HY000`
Message: Run function '...' in plugin '%s' failed
 - Error number: `MY-010208`; Symbol: `ER_SQL_HA_READ_FAILED`; SQLSTATE: `HY000`
Message: mysql_ha_read: Got error %d when reading table '%s'
 - Error number: `MY-010209`; Symbol: `ER_SR_BOGUS_VALUE`; SQLSTATE: `HY000`
Message: Stored routine '%s'.%s': invalid value in column %s.
 - Error number: `MY-010210`; Symbol: `ER_SR_INVALID_CONTEXT`; SQLSTATE: `HY000`
Message: Invalid creation context '%s.%s'.
 - Error number: `MY-010211`; Symbol: `ER_READING_TABLE_FAILED`; SQLSTATE: `HY000`
Message: Got error %d when reading table '%s'
 - Error number: `MY-010212`; Symbol: `ER_DES_FILE_WRONG_KEY`; SQLSTATE: `HY000`
Message: load_des_file: Found wrong key_number: %c
 - Error number: `MY-010214`; Symbol: `ER_JSON_PARSE_ERROR`; SQLSTATE: `HY000`
Message: Persisted config file is corrupt. Please ensure mysqld-auto.cnf file is valid JSON.
 - Error number: `MY-010215`; Symbol: `ER_CONFIG_OPTION_WITHOUT_GROUP`; SQLSTATE: `HY000`
Message: Found option without preceding group in config file
 - Error number: `MY-010216`; Symbol: `ER_VALGRIND_DO_QUICK_LEAK_CHECK`; SQLSTATE: `HY000`
Message: VALGRIND_DO_QUICK_LEAK_CHECK
 - Error number: `MY-010217`; Symbol: `ER_VALGRIND_COUNT_LEAKS`; SQLSTATE: `HY000`

Message: VALGRIND_COUNT_LEAKS reports %lu leaked bytes for query '%.*s'

- Error number: [MY-010218](#); Symbol: [ER_LOAD_DATA_INFILE_FAILED_IN_UNEXPECTED_WAY](#); SQLSTATE: [HY000](#)

Message: LOAD DATA INFILE in the replica SQL Thread can only read from --replica-load-tmpdir. Please, report a bug.

- Error number: [MY-010219](#); Symbol: [ER_UNKNOWN_ERROR_NUMBER](#); SQLSTATE: [HY000](#)

Message: Got unknown error: %d

- Error number: [MY-010220](#); Symbol: [ER_UDF_CANT_ALLOC_FOR_STRUCTURES](#); SQLSTATE: [HY000](#)

Message: Can't allocate memory for udf structures

- Error number: [MY-010221](#); Symbol: [ER_UDF_CANT_ALLOC_FOR_FUNCTION](#); SQLSTATE: [HY000](#)

Message: Can't alloc memory for udf function: '%s'

- Error number: [MY-010222](#); Symbol: [ER_UDF_INVALID_ROW_IN_FUNCTION_TABLE](#); SQLSTATE: [HY000](#)

Message: Invalid row in mysql.func table for function '%s'

- Error number: [MY-010223](#); Symbol: [ER_UDF_CANT_OPEN_FUNCTION_TABLE](#); SQLSTATE: [HY000](#)

Message: Could not open the mysql.func table. Please perform the MySQL upgrade procedure.

- Error number: [MY-010224](#); Symbol: [ER_XA_RECOVER_FOUND_TRX_IN_SE](#); SQLSTATE: [HY000](#)

Message: Found %d prepared transaction(s) in %s

- Error number: [MY-010225](#); Symbol: [ER_XA_RECOVER_FOUND_XA_TRX](#); SQLSTATE: [HY000](#)

Message: Found %d prepared XA transactions

- Error number: [MY-010229](#); Symbol: [ER_XA_STARTING_RECOVERY](#); SQLSTATE: [HY000](#)

Message: Starting XA crash recovery...

- Error number: [MY-010230](#); Symbol: [ER_XA_NO_MULTI_2PC_HEURISTIC_RECOVER](#); SQLSTATE: [HY000](#)

Message: --tc-heuristic-recover rollback strategy is not safe on systems with more than one 2-phase-commit-capable storage engine. Aborting crash recovery.

- Error number: [MY-010231](#); Symbol: [ER_XA_RECOVER_EXPLANATION](#); SQLSTATE: [HY000](#)

Message: Found %d prepared transactions! It means that mysqld was not shut down properly last time and critical recovery information (last binlog or %s file) was manually deleted after a crash. You have to start mysqld with --tc-heuristic-recover switch to commit or rollback pending transactions.

- Error number: [MY-010232](#); Symbol: [ER_XA_RECOVERY_DONE](#); SQLSTATE: [HY000](#)

Message: XA crash recovery finished.

- Error number: [MY-010233](#); Symbol: [ER_TRX_GTID_COLLECT_REJECT](#); SQLSTATE: [HY000](#)

Message: Failed to collect GTID to send in the response packet!

- Error number: [MY-010234](#); Symbol: [ER_SQL_AUTHOR_DEFAULT_ROLES_FAIL](#); SQLSTATE: [HY000](#)

Message: MYSQL.DEFAULT_ROLES couldn't be updated for authorization identifier %s

- Error number: [MY-010235](#); Symbol: [ER_SQL_USER_TABLE_CREATE_WARNING](#); SQLSTATE: [HY000](#)

Message: Following users were specified in CREATE USER IF NOT EXISTS but they already exist. Corresponding entry in binary log used default authentication plugin '%s' to rewrite authentication information (if any) for them: %s

- Error number: [MY-010236](#); Symbol: [ER_SQL_USER_TABLE_ALTER_WARNING](#); SQLSTATE: [HY000](#)

Message: Following users were specified in ALTER USER IF EXISTS but they do not exist. Corresponding entry in binary log used default authentication plugin '%s' to rewrite authentication information (if any) for them: %s

- Error number: [MY-010237](#); Symbol: [ER_ROW_IN_WRONG_PARTITION_PLEASE_REPAIR](#); SQLSTATE: [HY000](#)

Message: Table '%s' corrupted: row in wrong partition: %s -- Please REPAIR the table!

- Error number: [MY-010238](#); Symbol: [ER_MYISAM_CRASHED_ERROR_IN_THREAD](#); SQLSTATE: [HY000](#)

Message: Got an error from thread_id=%u, %s:%d

- Error number: [MY-010239](#); Symbol: [ER_MYISAM_CRASHED_ERROR_IN](#); SQLSTATE: [HY000](#)

Message: Got an error from unknown thread, %s:%d

- Error number: [MY-010240](#); Symbol: [ER_TOO_MANY_STORAGE_ENGINES](#); SQLSTATE: [HY000](#)

Message: Too many storage engines!

- Error number: [MY-010241](#); Symbol: [ER_SE_TYPECODE_CONFLICT](#); SQLSTATE: [HY000](#)

Message: Storage engine '%s' has conflicting typecode. Assigning value %d.

- Error number: [MY-010242](#); Symbol: [ER_TRX_WRITE_SET_OOM](#); SQLSTATE: [HY000](#)

Message: Out of memory on transaction write set extraction

- Error number: [MY-010243](#); Symbol: [ER_HANDLER_TON_OOM](#); SQLSTATE: [HY000](#)

Message: Unable to allocate memory for plugin '%s' handlerton.

- Error number: [MY-010244](#); Symbol: [ER_CONN_SHM_LISTENER](#); SQLSTATE: [HY000](#)

Message: Shared memory setting up listener

- Error number: [MY-010245](#); Symbol: [ER_CONN_SHM_CANT_CREATE_SERVICE](#); SQLSTATE: [HY000](#)

Message: Can't create shared memory service: %s. : %s

- Error number: [MY-010246](#); Symbol: [ER_CONN_SHM_CANT_CREATE_CONNECTION](#); SQLSTATE: [HY000](#)

Message: Can't create shared memory connection: %s. : %s

-
- Error number: `MY-010247`; Symbol: `ER_CONN_PIP_CANT_CREATE_EVENT`; SQLSTATE: `HY000`
Message: Can't create event, last error=%u
 - Error number: `MY-010248`; Symbol: `ER_CONN_PIP_CANT_CREATE_PIPE`; SQLSTATE: `HY000`
Message: Can't create new named pipe!: %s
 - Error number: `MY-010249`; Symbol: `ER_CONN_PER_THREAD_NO_THREAD`; SQLSTATE: `HY000`
Message: Can't create thread to handle new connection(errno= %d)
 - Error number: `MY-010250`; Symbol: `ER_CONN_TCP_NO_SOCKET`; SQLSTATE: `HY000`
Message: Failed to create a socket for %s '%s': errno: %d.
 - Error number: `MY-010251`; Symbol: `ER_CONN_TCP_CREATED`; SQLSTATE: `HY000`
Message: Server socket created on IP: '%s'.
 - Error number: `MY-010252`; Symbol: `ER_CONN_TCP_ADDRESS`; SQLSTATE: `HY000`
Message: Server hostname (bind-address): '%s'; port: %d
 - Error number: `MY-010253`; Symbol: `ER_CONN_TCP_IPV6_AVAILABLE`; SQLSTATE: `HY000`
Message: IPv6 is available.
 - Error number: `MY-010254`; Symbol: `ER_CONN_TCP_IPV6_UNAVAILABLE`; SQLSTATE: `HY000`
Message: IPv6 is not available.
 - Error number: `MY-010255`; Symbol: `ER_CONN_TCP_ERROR_WITH_STRERROR`; SQLSTATE: `HY000`
Message: Can't create IP socket: %s
 - Error number: `MY-010256`; Symbol: `ER_CONN_TCP_CANT_RESOLVE_HOSTNAME`; SQLSTATE: `HY000`
Message: Can't start server: cannot resolve hostname!
 - Error number: `MY-010257`; Symbol: `ER_CONN_TCP_IS_THERE_ANOTHER_USING_PORT`; SQLSTATE: `HY000`
Message: Do you already have another mysqld server running on port: %d ?
 - Error number: `MY-010258`; Symbol: `ER_CONN_UNIX_IS_THERE_ANOTHER_USING_SOCKET`; SQLSTATE: `HY000`
Message: Do you already have another mysqld server running on socket: %s ?
 - Error number: `MY-010259`; Symbol: `ER_CONN_UNIX_PID_CLAIMED_SOCKET_FILE`; SQLSTATE: `HY000`
Message: Another process with pid %d is using unix socket file.
 - Error number: `MY-010260`; Symbol: `ER_CONN_TCP_CANT_RESET_V6ONLY`; SQLSTATE: `HY000`
Message: Failed to reset IPV6_V6ONLY flag (error: %d). The server will listen to IPv6 addresses only.
 - Error number: `MY-010261`; Symbol: `ER_CONN_TCP_BIND_RETRY`; SQLSTATE: `HY000`

Message: Retrying bind on TCP/IP port %u

- Error number: [MY-010262](#); Symbol: [ER_CONN_TCP_BIND_FAIL](#); SQLSTATE: [HY000](#)

Message: Can't start server: Bind on TCP/IP port: %s

- Error number: [MY-010263](#); Symbol: [ER_CONN_TCP_IP_NOT_LOGGED](#); SQLSTATE: [HY000](#)

Message: Fails to print out IP-address.

- Error number: [MY-010264](#); Symbol: [ER_CONN_TCP_RESOLVE_INFO](#); SQLSTATE: [HY000](#)

Message: - '%s' resolves to '%s';

- Error number: [MY-010265](#); Symbol: [ER_CONN_TCP_START_FAIL](#); SQLSTATE: [HY000](#)

Message: Can't start server: listen() on TCP/IP port: %s

- Error number: [MY-010266](#); Symbol: [ER_CONN_TCP_LISTEN_FAIL](#); SQLSTATE: [HY000](#)

Message: listen() on TCP/IP failed with error %d

- Error number: [MY-010267](#); Symbol: [ER_CONN_UNIX_PATH_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: The socket file path is too long (> %u): %s

- Error number: [MY-010268](#); Symbol: [ER_CONN_UNIX_LOCK_FILE_FAIL](#); SQLSTATE: [HY000](#)

Message: Unable to setup unix socket lock file.

- Error number: [MY-010269](#); Symbol: [ER_CONN_UNIX_NO_FD](#); SQLSTATE: [HY000](#)

Message: Can't start server: UNIX Socket : %s

- Error number: [MY-010270](#); Symbol: [ER_CONN_UNIX_NO_BIND_NO_START](#); SQLSTATE: [HY000](#)

Message: Can't start server : Bind on unix socket: %s

- Error number: [MY-010271](#); Symbol: [ER_CONN_UNIX_LISTEN_FAILED](#); SQLSTATE: [HY000](#)

Message: listen() on Unix socket failed with error %d

- Error number: [MY-010272](#); Symbol: [ER_CONN_UNIX_LOCK_FILE_GIVING_UP](#); SQLSTATE: [HY000](#)

Message: Unable to create unix socket lock file %s after retries.

- Error number: [MY-010273](#); Symbol: [ER_CONN_UNIX_LOCK_FILE_CANT_CREATE](#); SQLSTATE: [HY000](#)

Message: Could not create unix socket lock file %s.

- Error number: [MY-010274](#); Symbol: [ER_CONN_UNIX_LOCK_FILE_CANT_OPEN](#); SQLSTATE: [HY000](#)

Message: Could not open unix socket lock file %s.

- Error number: [MY-010275](#); Symbol: [ER_CONN_UNIX_LOCK_FILE_CANT_READ](#); SQLSTATE: [HY000](#)

Message: Could not read unix socket lock file %s.

- Error number: [MY-010276](#); Symbol: [ER_CONN_UNIX_LOCK_FILE_EMPTY](#); SQLSTATE: [HY000](#)

-
- Message: Unix socket lock file is empty %s.
- Error number: `MY-010277`; Symbol: `ER_CONN_UNIX_LOCK_FILE_PIDLESS`; SQLSTATE: `HY000`
Message: Invalid pid in unix socket lock file %s.
 - Error number: `MY-010278`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_WRITE`; SQLSTATE: `HY000`
Message: Could not write unix socket lock file %s errno %d.
 - Error number: `MY-010279`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_DELETE`; SQLSTATE: `HY000`
Message: Could not remove unix socket lock file %s errno %d.
 - Error number: `MY-010280`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_SYNC`; SQLSTATE: `HY000`
Message: Could not sync unix socket lock file %s errno %d.
 - Error number: `MY-010281`; Symbol: `ER_CONN_UNIX_LOCK_FILE_CANT_CLOSE`; SQLSTATE: `HY000`
Message: Could not close unix socket lock file %s errno %d.
 - Error number: `MY-010282`; Symbol: `ER_CONN_SOCKET_SELECT_FAILED`; SQLSTATE: `HY000`
Message: mysqld: Got error %d from select
 - Error number: `MY-010283`; Symbol: `ER_CONN_SOCKET_ACCEPT_FAILED`; SQLSTATE: `HY000`
Message: Error in accept: %s
 - Error number: `MY-010284`; Symbol: `ER_AUTH_RSA_CANT_FIND`; SQLSTATE: `HY000`
Message: RSA %s key file not found: %s. Some authentication plugins will not work.
 - Error number: `MY-010285`; Symbol: `ER_AUTH_RSA_CANT_PARSE`; SQLSTATE: `HY000`
Message: Failure to parse RSA %s key (file exists): %s: %s
 - Error number: `MY-010286`; Symbol: `ER_AUTH_RSA_CANT_READ`; SQLSTATE: `HY000`
Message: Failure to read key file: %s
 - Error number: `MY-010287`; Symbol: `ER_AUTH_RSA_FILES_NOT_FOUND`; SQLSTATE: `HY000`
Message: RSA key files not found. Some authentication plugins will not work.
 - Error number: `MY-010288`; Symbol: `ER_CONN_ATTR_TRUNCATED`; SQLSTATE: `HY000`
Message: Connection attributes of length %lu were truncated (%d bytes lost) for connection %llu, user %s@%s (as %s), auth: %s
 - Error number: `MY-010289`; Symbol: `ER_X509_CIPHERS_MISMATCH`; SQLSTATE: `HY000`
Message: X.509 ciphers mismatch: should be '%s' but is '%s'
 - Error number: `MY-010290`; Symbol: `ER_X509_ISSUER_MISMATCH`; SQLSTATE: `HY000`
Message: X.509 issuer mismatch: should be '%s' but is '%s'
 - Error number: `MY-010291`; Symbol: `ER_X509_SUBJECT_MISMATCH`; SQLSTATE: `HY000`

Message: X.509 subject mismatch: should be '%s' but is '%s'

- Error number: [MY-010292](#); Symbol: [ER_AUTH_CANT_ACTIVATE_ROLE](#); SQLSTATE: [HY000](#)

Message: Failed to activate default role %s for %s

- Error number: [MY-010293](#); Symbol: [ER_X509_NEEDS_RSA_PRIVKEY](#); SQLSTATE: [HY000](#)

Message: Could not generate RSA private key required for X.509 certificate.

- Error number: [MY-010294](#); Symbol: [ER_X509_CANT_WRITE_KEY](#); SQLSTATE: [HY000](#)

Message: Could not write key file: %s

- Error number: [MY-010295](#); Symbol: [ER_X509_CANT_CHMOD_KEY](#); SQLSTATE: [HY000](#)

Message: Could not set file permission for %s

- Error number: [MY-010296](#); Symbol: [ER_X509_CANT_READ_CA_KEY](#); SQLSTATE: [HY000](#)

Message: Could not read CA key file: %s

- Error number: [MY-010297](#); Symbol: [ER_X509_CANT_READ_CA_CERT](#); SQLSTATE: [HY000](#)

Message: Could not read CA certificate file: %s

- Error number: [MY-010298](#); Symbol: [ER_X509_CANT_CREATE_CERT](#); SQLSTATE: [HY000](#)

Message: Could not generate X.509 certificate.

- Error number: [MY-010299](#); Symbol: [ER_X509_CANT_WRITE_CERT](#); SQLSTATE: [HY000](#)

Message: Could not write certificate file: %s

- Error number: [MY-010300](#); Symbol: [ER_AUTH_CANT_CREATE_RSA_PAIR](#); SQLSTATE: [HY000](#)

Message: Could not generate RSA Private/Public key pair

- Error number: [MY-010301](#); Symbol: [ER_AUTH_CANT_WRITE_PRIVKEY](#); SQLSTATE: [HY000](#)

Message: Could not write private key file: %s

- Error number: [MY-010302](#); Symbol: [ER_AUTH_CANT_WRITE_PUBKEY](#); SQLSTATE: [HY000](#)

Message: Could not write public key file: %s

- Error number: [MY-010303](#); Symbol: [ER_AUTH_SSL_CONF_PREVENTS_CERT_GENERATION](#); SQLSTATE: [HY000](#)

Message: Skipping generation of SSL certificates as options related to SSL are specified.

- Error number: [MY-010304](#); Symbol: [ER_AUTH_USING_EXISTING_CERTS](#); SQLSTATE: [HY000](#)

Message: Skipping generation of SSL certificates as certificate files are present in data directory.

- Error number: [MY-010305](#); Symbol: [ER_AUTH_CERTS_SAVED_TO_DATADIR](#); SQLSTATE: [HY000](#)

Message: Auto generated SSL certificates are placed in data directory.

- Error number: [MY-010306](#); Symbol: [ER_AUTH_CERT_GENERATION_DISABLED](#); SQLSTATE: [HY000](#)

-
- Message: Skipping generation of SSL certificates as --auto_generate_certs is set to OFF.
- Error number: [MY-010307](#); Symbol: [ER_AUTH_RSA_CONF_PREVENTS_KEY_GENERATION](#); SQLSTATE: [HY000](#)
Message: Skipping generation of RSA key pair through %s as options related to RSA keys are specified.
 - Error number: [MY-010308](#); Symbol: [ER_AUTH_KEY_GENERATION_SKIPPED_PAIR_PRESENT](#); SQLSTATE: [HY000](#)
Message: Skipping generation of RSA key pair through %s as key files are present in data directory.
 - Error number: [MY-010309](#); Symbol: [ER_AUTH_KEYS_SAVED_TO_DATADIR](#); SQLSTATE: [HY000](#)
Message: Auto generated RSA key files through %s are placed in data directory.
 - Error number: [MY-010310](#); Symbol: [ER_AUTH_KEY_GENERATION_DISABLED](#); SQLSTATE: [HY000](#)
Message: Skipping generation of RSA key pair as %s is set to OFF.
 - Error number: [MY-010311](#); Symbol: [ER_AUTHCACHE_PROXIES_PRIV_SKIPPED_NEEDS_RESOLVE](#); SQLSTATE: [HY000](#)
Message: 'proxies_priv' entry '%s@%s %s@%s' ignored in --skip-name-resolve mode.
 - Error number: [MY-010312](#); Symbol: [ER_AUTHCACHE_PLUGIN_MISSING](#); SQLSTATE: [HY000](#)
Message: The plugin '%.*s' used to authenticate user '%s'@'%.*s' is not loaded. Nobody can currently login using this account.
 - Error number: [MY-010313](#); Symbol: [ER_AUTHCACHE_PLUGIN_CONFIG](#); SQLSTATE: [HY000](#)
Message: The plugin '%s' is used to authenticate user '%s'@'%.*s', %s configured. Nobody can currently login using this account.
 - Error number: [MY-010315](#); Symbol: [ER_AUTHCACHE_USER_SKIPPED_NEEDS_RESOLVE](#); SQLSTATE: [HY000](#)
Message: 'user' entry '%s@%s' ignored in --skip-name-resolve mode.
 - Error number: [MY-010316](#); Symbol: [ER_AUTHCACHE_USER_TABLE_DODGY](#); SQLSTATE: [HY000](#)
Message: Fatal error: Could not read the column 'authentication_string' from table 'mysql.user'. Please perform the MySQL upgrade procedure.
 - Error number: [MY-010317](#); Symbol: [ER_AUTHCACHE_USER_IGNORED_DEPRECATED_PASSWORD](#); SQLSTATE: [HY000](#)
Message: User entry '%s'@'%s' has a deprecated pre-4.1 password. The user will be ignored and no one can login with this user anymore.
 - Error number: [MY-010318](#); Symbol: [ER_AUTHCACHE_USER_IGNORED_NEEDS_PLUGIN](#); SQLSTATE: [HY000](#)
Message: User entry '%s'@'%s' has an empty plugin value. The user will be ignored and no one can login with this user anymore.
 - Error number: [MY-010319](#); Symbol: [ER_AUTHCACHE_USER_IGNORED_INVALID_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Found invalid password for user: '%s@%s'; Ignoring user

- Error number: [MY-010320](#); Symbol: [ER_AUTHCACHE_EXPIRED_PASSWORD_UNSUPPORTED](#); SQLSTATE: [HY000](#)

Message: 'user' entry '%s@%s' has the password ignore flag raised, but its authentication plugin doesn't support password expiration. The user id will be ignored.

- Error number: [MY-010321](#); Symbol: [ER_NO_SUPER_WITHOUT_USER_PLUGIN](#); SQLSTATE: [HY000](#)

Message: Some of the user accounts with SUPER privileges were disabled because of empty mysql.user.plugin value. If you are upgrading from MySQL 5.6 to MySQL 5.7 it means that substitution for the empty plugin column was not possible. Probably because of pre 4.1 password hash. If your account is disabled you will need to perform the MySQL upgrade procedure. For complete instructions on how to upgrade MySQL to a new version please see the 'Upgrading MySQL' section from the MySQL manual.

- Error number: [MY-010322](#); Symbol: [ER_AUTHCACHE_DB_IGNORED_EMPTY_NAME](#); SQLSTATE: [HY000](#)

Message: Found an entry in the 'db' table with empty database name; Skipped

- Error number: [MY-010323](#); Symbol: [ER_AUTHCACHE_DB_SKIPPED_NEEDS_RESOLVE](#); SQLSTATE: [HY000](#)

Message: 'db' entry '%s %s@%s' ignored in --skip-name-resolve mode.

- Error number: [MY-010324](#); Symbol: [ER_AUTHCACHE_DB_ENTRY_LOWERCASED_REVOKE_WILL_FAIL](#); SQLSTATE: [HY000](#)

Message: 'db' entry '%s %s@%s' had database in mixed case that has been forced to lowercase because lower_case_table_names is set. It will not be possible to remove this privilege using REVOKE.

- Error number: [MY-010325](#); Symbol: [ER_AUTHCACHE_TABLE_PROXIES_PRIV_MISSING](#); SQLSTATE: [HY000](#)

Message: The system table mysql.proxies_priv is missing. Please perform the MySQL upgrade procedure.

- Error number: [MY-010326](#); Symbol: [ER_AUTHCACHE_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES](#); SQLSTATE: [HY000](#)

Message: Fatal error: Can't open and lock privilege tables: %s

- Error number: [MY-010327](#); Symbol: [ER_AUTHCACHE_CANT_INIT_GRANT_SUBSYSTEM](#); SQLSTATE: [HY000](#)

Message: Fatal: can't initialize grant subsystem - '%s'

- Error number: [MY-010328](#); Symbol: [ER_AUTHCACHE_PROCS_PRIV_SKIPPED_NEEDS_RESOLVE](#); SQLSTATE: [HY000](#)

Message: 'procs_priv' entry '%s %s@%s' ignored in --skip-name-resolve mode.

- Error number: [MY-010329](#); Symbol: [ER_AUTHCACHE_PROCS_PRIV_ENTRY_IGNORED_BAD_ROUTINE_TYPE](#); SQLSTATE: [HY000](#)

Message: 'procs_priv' entry '%s' ignored, bad routine type

-
- Error number: `MY-010330`; Symbol: `ER_AUTHCACHE_TABLES_PRIV_SKIPPED_NEEDS_RESOLVE`; SQLSTATE: `HY000`
Message: 'tables_priv' entry '%s %s@%s' ignored in --skip-name-resolve mode.
 - Error number: `MY-010331`; Symbol: `ER_USER_NOT_IN_EXTRA_USERS_BINLOG_POSSIBLY_INCOMPLETE`; SQLSTATE: `HY000`
Message: Failed to add %s in extra_users. Binary log entry may miss some of the users.
 - Error number: `MY-010332`; Symbol: `ER_DD_SCHEMA_NOT_FOUND`; SQLSTATE: `HY000`
Message: Unable to start server. The data dictionary schema '%s' does not exist.
 - Error number: `MY-010333`; Symbol: `ER_DD_TABLE_NOT_FOUND`; SQLSTATE: `HY000`
Message: Unable to start server. The data dictionary table '%s' does not exist.
 - Error number: `MY-010334`; Symbol: `ER_DD_SE_INIT_FAILED`; SQLSTATE: `HY000`
Message: Failed to initialize DD Storage Engine
 - Error number: `MY-010335`; Symbol: `ER_DD_ABORTING_PARTIAL_UPGRADE`; SQLSTATE: `HY000`
Message: Found partially upgraded DD. Aborting upgrade and deleting all DD tables. Start the upgrade process again.
 - Error number: `MY-010336`; Symbol: `ER_DD_FRM_EXISTS_FOR_TABLE`; SQLSTATE: `HY000`
Message: Found .frm file with same name as one of the Dictionary Tables.
 - Error number: `MY-010337`; Symbol: `ER_DD_CREATED_FOR_UPGRADE`; SQLSTATE: `HY000`
Message: Created Data Dictionary for upgrade
 - Error number: `MY-010338`; Symbol: `ER_ERRMSG_CANT_FIND_FILE`; SQLSTATE: `HY000`
Message: Can't find error-message file '%s'. Check error-message file location and 'lc-messages-dir' configuration directive.
 - Error number: `MY-010340`; Symbol: `ER_ERRMSG_MISSING_IN_FILE`; SQLSTATE: `HY000`
Message: Error message file '%s' had only %d error messages, but it should contain at least %d error messages. Check that the above file is the right version for this program!
 - Error number: `MY-010341`; Symbol: `ER_ERRMSG_OOM`; SQLSTATE: `HY000`
Message: Not enough memory for messagefile '%s'
 - Error number: `MY-010342`; Symbol: `ER_ERRMSG_CANT_READ`; SQLSTATE: `HY000`
Message: Can't read from messagefile '%s'
 - Error number: `MY-010343`; Symbol: `ER_TABLE_INCOMPATIBLE_DECIMAL_FIELD`; SQLSTATE: `HY000`
Message: Found incompatible DECIMAL field '%s' in %s; Please do "ALTER TABLE `'%s` FORCE" to fix it!
 - Error number: `MY-010344`; Symbol: `ER_TABLE_INCOMPATIBLE_YEAR_FIELD`; SQLSTATE: `HY000`

Message: Found incompatible YEAR(x) field '%s' in %s; Please do "ALTER TABLE `'%s` FORCE" to fix it!

- Error number: [MY-010345](#); Symbol: [ER_INVALID_CHARSET_AND_DEFAULT_IS_MB](#); SQLSTATE: [HY000](#)

Message: '%s' had no or invalid character set, and default character set is multi-byte, so character column sizes may have changed

- Error number: [MY-010346](#); Symbol: [ER_TABLE_WRONG_KEY_DEFINITION](#); SQLSTATE: [HY000](#)

Message: Found wrong key definition in %s; Please do "ALTER TABLE `'%s` FORCE " to fix it!

- Error number: [MY-010347](#); Symbol: [ER_CANT_OPEN_FRM_FILE](#); SQLSTATE: [HY000](#)

Message: Unable to open file %s

- Error number: [MY-010348](#); Symbol: [ER_CANT_READ_FRM_FILE](#); SQLSTATE: [HY000](#)

Message: Error in reading file %s

- Error number: [MY-010349](#); Symbol: [ER_TABLE_CREATED_WITH_DIFFERENT_VERSION](#); SQLSTATE: [HY000](#)

Message: Table '%s' was created with a different version of MySQL and cannot be read

- Error number: [MY-010350](#); Symbol: [ER_VIEW_UNPARSABLE](#); SQLSTATE: [HY000](#)

Message: Unable to read view %s

- Error number: [MY-010351](#); Symbol: [ER_FILE_TYPE_UNKNOWN](#); SQLSTATE: [HY000](#)

Message: File %s has unknown type in its header.

- Error number: [MY-010352](#); Symbol: [ER_INVALID_INFO_IN_FRM](#); SQLSTATE: [HY000](#)

Message: Incorrect information in file %s

- Error number: [MY-010353](#); Symbol: [ER_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES](#); SQLSTATE: [HY000](#)

Message: Can't open and lock privilege tables: %s

- Error number: [MY-010354](#); Symbol: [ER_AUDIT_PLUGIN_DOES_NOT_SUPPORT_AUDIT_AUTH_EVENTS](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' cannot subscribe to MYSQL_AUDIT_AUTHORIZATION events. Currently not supported.

- Error number: [MY-010355](#); Symbol: [ER_AUDIT_PLUGIN_HAS_INVALID_DATA](#); SQLSTATE: [HY000](#)

Message: Plugin '%s' has invalid data.

- Error number: [MY-010356](#); Symbol: [ER_TZ_OOM_INITIALIZING_TIME_ZONES](#); SQLSTATE: [HY000](#)

Message: Fatal error: OOM while initializing time zones

- Error number: [MY-010357](#); Symbol: [ER_TZ_CANT_OPEN_AND_LOCK_TIME_ZONE_TABLE](#); SQLSTATE: [HY000](#)

Message: Can't open and lock time zone table: %s trying to live without them

- Error number: `MY-010358`; Symbol: `ER_TZ_OOM_LOADING_LEAP_SECOND_TABLE`; SQLSTATE: `HY000`

Message: Fatal error: Out of memory while loading mysql.time_zone_leap_second table

- Error number: `MY-010359`; Symbol: `ER_TZ_TOO_MANY_LEAPS_IN_LEAP_SECOND_TABLE`; SQLSTATE: `HY000`

Message: Fatal error: While loading mysql.time_zone_leap_second table: too much leaps

- Error number: `MY-010360`; Symbol: `ER_TZ_ERROR_LOADING_LEAP_SECOND_TABLE`; SQLSTATE: `HY000`

Message: Fatal error: Error while loading mysql.time_zone_leap_second table

- Error number: `MY-010361`; Symbol: `ER_TZ_UNKNOWN_OR_ILLEGAL_DEFAULT_TIME_ZONE`; SQLSTATE: `HY000`

Message: Fatal error: Illegal or unknown default time zone '%s'

- Error number: `MY-010362`; Symbol: `ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE`; SQLSTATE: `HY000`

Message: Can't find description of time zone '%.*s'

- Error number: `MY-010363`; Symbol: `ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE_ID`; SQLSTATE: `HY000`

Message: Can't find description of time zone '%u'

- Error number: `MY-010364`; Symbol: `ER_TZ_TRANSITION_TYPE_TABLE_TYPE_TOO_LARGE`; SQLSTATE: `HY000`

Message: Error while loading time zone description from mysql.time_zone_transition_type table: too big transition type id

- Error number: `MY-010365`; Symbol: `ER_TZ_TRANSITION_TYPE_TABLE_ABBREVIATIONS_EXCEED_SPACE`; SQLSTATE: `HY000`

Message: Error while loading time zone description from mysql.time_zone_transition_type table: not enough room for abbreviations

- Error number: `MY-010366`; Symbol: `ER_TZ_TRANSITION_TYPE_TABLE_LOAD_ERROR`; SQLSTATE: `HY000`

Message: Error while loading time zone description from mysql.time_zone_transition_type table

- Error number: `MY-010367`; Symbol: `ER_TZ_TRANSITION_TABLE_TOO_MANY_TRANSITIONS`; SQLSTATE: `HY000`

Message: Error while loading time zone description from mysql.time_zone_transition table: too much transitions

- Error number: `MY-010368`; Symbol: `ER_TZ_TRANSITION_TABLE_BAD_TRANSITION_TYPE`; SQLSTATE: `HY000`

Message: Error while loading time zone description from mysql.time_zone_transition table: bad transition type id

- Error number: [MY-010369](#); Symbol: [ER_TZ_TRANSITION_TABLE_LOAD_ERROR](#); SQLSTATE: [HY000](#)

Message: Error while loading time zone description from mysql.time_zone_transition table

- Error number: [MY-010370](#); Symbol: [ER_TZ_NO_TRANSITION_TYPES_IN_TIME_ZONE](#); SQLSTATE: [HY000](#)

Message: loading time zone without transition types

- Error number: [MY-010371](#); Symbol: [ER_TZ_OOM_LOADING_TIME_ZONE_DESCRIPTION](#); SQLSTATE: [HY000](#)

Message: Out of memory while loading time zone description

- Error number: [MY-010372](#); Symbol: [ER_TZ_CANT_BUILD_MKTIME_MAP](#); SQLSTATE: [HY000](#)

Message: Unable to build mktime map for time zone

- Error number: [MY-010373](#); Symbol: [ER_TZ_OOM_WHILE_LOADING_TIME_ZONE](#); SQLSTATE: [HY000](#)

Message: Out of memory while loading time zone

- Error number: [MY-010374](#); Symbol: [ER_TZ_OOM_WHILE_SETTING_TIME_ZONE](#); SQLSTATE: [HY000](#)

Message: Fatal error: Out of memory while setting new time zone

- Error number: [MY-010375](#); Symbol: [ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_CONDITION_BAD](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread is stopped because UNTIL condition is bad(%s:%llu).

- Error number: [MY-010376](#); Symbol: [ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_POSITION_REACHED](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread stopped because it reached its UNTIL position %llu

- Error number: [MY-010377](#); Symbol: [ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS_ALREADY_APPLIED](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread stopped because UNTIL SQL_BEFORE_GTIDS %s is already applied

- Error number: [MY-010378](#); Symbol: [ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS_REACHED](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread stopped because it reached UNTIL SQL_BEFORE_GTIDS %s

- Error number: [MY-010379](#); Symbol: [ER_REPLICA_SQL_THREAD_STOPPED_AFTER_GTIDS_REACHED](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread stopped because it reached UNTIL SQL_AFTER_GTIDS %s

- Error number: [MY-010380](#); Symbol: [ER_REPLICA_SQL_THREAD_STOPPED_GAP_TRX_PROCESSED](#); SQLSTATE: [HY000](#)

Message: Replica SQL thread stopped according to UNTIL SQL_AFTER_MTS_GAPS as it has processed all gap transactions left from the previous replica session.

-
- Error number: `MY-010381`; Symbol: `ER_GROUP_REPLICATION_PLUGIN_NOT_INSTALLED`; SQLSTATE: `HY000`
Message: Group Replication plugin is not installed.
 - Error number: `MY-010382`; Symbol: `ER_GTID_ALREADY_ADDED_BY_USER`; SQLSTATE: `HY000`
Message: The transaction owned GTID is already in the %s table, which is caused by an explicit modifying from user client.
 - Error number: `MY-010383`; Symbol: `ER_FAILED_TO_DELETE_FROM_GTID_EXECUTED_TABLE`; SQLSTATE: `HY000`
Message: Failed to delete the row: '%s' from the gtid_executed table.
 - Error number: `MY-010384`; Symbol: `ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE`; SQLSTATE: `HY000`
Message: Failed to compress the gtid_executed table.
 - Error number: `MY-010385`; Symbol: `ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE_OOM`; SQLSTATE: `HY000`
Message: Failed to compress the gtid_executed table, because it is failed to allocate the THD.
 - Error number: `MY-010386`; Symbol: `ER_FAILED_TO_INIT_THREAD_ATTR_FOR_GTID_TABLE_COMPRESSION`; SQLSTATE: `HY000`
Message: Failed to initialize thread attribute when creating compression thread.
 - Error number: `MY-010387`; Symbol: `ER_FAILED_TO_CREATE_GTID_TABLE_COMPRESSION_THREAD`; SQLSTATE: `HY000`
Message: Can not create thread to compress gtid_executed table (errno= %d)
 - Error number: `MY-010388`; Symbol: `ER_FAILED_TO_JOIN_GTID_TABLE_COMPRESSION_THREAD`; SQLSTATE: `HY000`
Message: Could not join gtid_executed table compression thread. error:%d
 - Error number: `MY-010389`; Symbol: `ER_NPIPE_FAILED_TO_INIT_SECURITY_DESCRIPTOR`; SQLSTATE: `HY000`
Message: Can't start server : Initialize security descriptor: %s
 - Error number: `MY-010390`; Symbol: `ER_NPIPE_FAILED_TO_SET_SECURITY_DESCRIPTOR`; SQLSTATE: `HY000`
Message: Can't start server : Set security descriptor: %s
 - Error number: `MY-010391`; Symbol: `ER_NPIPE_PIPE_ALREADY_IN_USE`; SQLSTATE: `HY000`
Message: Can't start server : Named Pipe "%s" already in use.
 - Error number: `MY-010405`; Symbol: `ER_RPL_CANT_OPEN_INFO_TABLE`; SQLSTATE: `HY000`
Message: Info table is not ready to be used. Table '%s.%s' cannot be opened.
 - Error number: `MY-010406`; Symbol: `ER_RPL_CANT_SCAN_INFO_TABLE`; SQLSTATE: `HY000`

Message: Info table is not ready to be used. Table '%s.%s' cannot be scanned.

- Error number: [MY-010407](#); Symbol: [ER_RPL_CORRUPTED_INFO_TABLE](#); SQLSTATE: [HY000](#)

Message: Corrupted table %s.%s. Check out table definition.

- Error number: [MY-010408](#); Symbol: [ER_RPL_CORRUPTED_KEYS_IN_INFO_TABLE](#); SQLSTATE: [HY000](#)

Message: Info table has a problem with its key field(s). Table '%s.%s' expected field #%u to be '%s' but found '%s' instead.

- Error number: [MY-010409](#); Symbol: [ER_RPL_WORKER_ID_IS](#); SQLSTATE: [HY000](#)

Message: Choosing worker id %lu, the following is going to be %lu

- Error number: [MY-010410](#); Symbol: [ER_RPL_INCONSISTENT_TIMESTAMPS_IN_TRX](#); SQLSTATE: [HY000](#)

Message: Transaction is tagged with inconsistent logical timestamps: sequence_number (%lld) <= last_committed (%lld)

- Error number: [MY-010411](#); Symbol: [ER_RPL_INCONSISTENT_SEQUENCE_NO_IN_TRX](#); SQLSTATE: [HY000](#)

Message: Transaction's sequence number is inconsistent with that of a preceding one: sequence_number (%lld) <= previous sequence_number (%lld)

- Error number: [MY-010413](#); Symbol: [ER_RPL_CHANNELS_REQUIRE_NON_ZERO_SERVER_ID](#); SQLSTATE: [HY000](#)

Message: For the creation of replication channels the server id must be different from 0

- Error number: [MY-010415](#); Symbol: [ER_RPL_ERROR_CREATING_CONNECTION_METADATA](#); SQLSTATE: [HY000](#)

Message: Error creating connection metadata: %s.

- Error number: [MY-010418](#); Symbol: [ER_RPL_ERROR_CREATING_APPLIER_METADATA](#); SQLSTATE: [HY000](#)

Message: Error creating applier metadata: %s.

- Error number: [MY-010420](#); Symbol: [ER_RPL_FAILED_TO_DELETE_FROM_REPLICA_WORKERS_INFO_REPOSITORY](#); SQLSTATE: [HY000](#)

Message: Could not delete from Replica Workers info repository.

- Error number: [MY-010421](#); Symbol: [ER_RPL_FAILED_TO_RESET_STATE_IN_REPLICA_INFO_REPOSITORY](#); SQLSTATE: [HY000](#)

Message: Could not store the reset Replica Worker state into the replica info repository.

- Error number: [MY-010423](#); Symbol: [ER_RPL_REPLICA_GENERIC_MESSAGE](#); SQLSTATE: [HY000](#)

Message: Replica: %s

- Error number: [MY-010424](#); Symbol: [ER_RPL_REPLICA_COULD_NOT_CREATE_CHANNEL_LIST](#); SQLSTATE: [HY000](#)

Message: Replica: Could not create channel list

- Error number: `MY-010425`; Symbol: `ER_RPL_MULTISOURCE_REQUIRES_TABLE_TYPE_REPOSITORIES`; SQLSTATE: `HY000`

Message: Replica: This replica was a multisourced replica previously which is supported only by both TABLE based connection metadata and applier metadata repositories. Found one or both of the info repos to be type FILE. Set both repos to type TABLE.

- Error number: `MY-010426`; Symbol: `ER_RPL_REPLICA_FAILED_TO_INIT_A_CONNECTION_METADATA_STRUCTURE`; SQLSTATE: `HY000`

Message: Replica: Failed to initialize the connection metadata structure for channel '%s'; its record may still be present in the applier metadata repository, consider deleting it.

- Error number: `MY-010427`; Symbol: `ER_RPL_REPLICA_FAILED_TO_INIT_CONNECTION_METADATA_STRUCTURE`; SQLSTATE: `HY000`

Message: Failed to initialize the connection metadata structure%s

- Error number: `MY-010428`; Symbol: `ER_RPL_REPLICA_FAILED_TO_CREATE_CHANNEL_FROM_CONNECTION_METADATA`; SQLSTATE: `HY000`

Message: Replica: Failed to create a channel from connection metadata repository.

- Error number: `MY-010429`; Symbol: `ER_RPL_FAILED_TO_CREATE_NEW_INFO_FILE`; SQLSTATE: `HY000`

Message: Failed to create a new info file (file '%s', errno %d)

- Error number: `MY-010430`; Symbol: `ER_RPL_FAILED_TO_CREATE_CACHE_FOR_INFO_FILE`; SQLSTATE: `HY000`

Message: Failed to create a cache on info file (file '%s')

- Error number: `MY-010431`; Symbol: `ER_RPL_FAILED_TO_OPEN_INFO_FILE`; SQLSTATE: `HY000`

Message: Failed to open the existing info file (file '%s', errno %d)

- Error number: `MY-010432`; Symbol: `ER_RPL_GTID_MEMORY_FINALY_AVAILABLE`; SQLSTATE: `HY000`

Message: Server overcomes the temporary 'out of memory' in '%d' tries while allocating a new chunk of intervals for storing GTIDs.

- Error number: `MY-010433`; Symbol: `ER_SERVER_COST_UNKNOWN_COST_CONSTANT`; SQLSTATE: `HY000`

Message: Unknown cost constant "%s" in mysql.server_cost table

- Error number: `MY-010434`; Symbol: `ER_SERVER_COST_INVALID_COST_CONSTANT`; SQLSTATE: `HY000`

Message: Invalid value for cost constant "%s" in mysql.server_cost table: %.1f

- Error number: `MY-010435`; Symbol: `ER_ENGINE_COST_UNKNOWN_COST_CONSTANT`; SQLSTATE: `HY000`

Message: Unknown cost constant "%s" in mysql.engine_cost table

- Error number: [MY-010436](#); Symbol: [ER_ENGINE_COST_UNKNOWN_STORAGE_ENGINE](#); SQLSTATE: [HY000](#)

Message: Unknown storage engine "%s" in mysql.engine_cost table

- Error number: [MY-010437](#); Symbol: [ER_ENGINE_COST_INVALID_DEVICE_TYPE_FOR_SE](#); SQLSTATE: [HY000](#)

Message: Invalid device type %d for "%s" storage engine for cost constant "%s" in mysql.engine_cost table

- Error number: [MY-010438](#); Symbol: [ER_ENGINE_COST_INVALID_CONST_CONSTANT_FOR_SE_AND_DEVICE](#); SQLSTATE: [HY000](#)

Message: Invalid value for cost constant "%s" for "%s" storage engine and device type %d in mysql.engine_cost table: %.1f

- Error number: [MY-010439](#); Symbol: [ER_SERVER_COST_FAILED_TO_READ](#); SQLSTATE: [HY000](#)

Message: Error while reading from mysql.server_cost table.

- Error number: [MY-010440](#); Symbol: [ER_ENGINE_COST_FAILED_TO_READ](#); SQLSTATE: [HY000](#)

Message: Error while reading from mysql.engine_cost table.

- Error number: [MY-010441](#); Symbol: [ER_FAILED_TO_OPEN_COST_CONSTANT_TABLES](#); SQLSTATE: [HY000](#)

Message: Failed to open optimizer cost constant tables

- Error number: [MY-010442](#); Symbol: [ER_RPL_UNSUPPORTED_UNIGNORABLE_EVENT_IN_STREAM](#); SQLSTATE: [HY000](#)

Message: Unsupported non-ignorable event fed into the event stream.

- Error number: [MY-010443](#); Symbol: [ER_RPL_GTID_LOG_EVENT_IN_STREAM](#); SQLSTATE: [HY000](#)

Message: GTID_LOG_EVENT, GTID_TAGGED_LOG_EVENT or ANONYMOUS_GTID_LOG_EVENT is not expected in an event stream %s.

- Error number: [MY-010444](#); Symbol: [ER_RPL_UNEXPECTED_BEGIN_IN_STREAM](#); SQLSTATE: [HY000](#)

Message: QUERY(BEGIN) is not expected in an event stream in the middle of a %s.

- Error number: [MY-010445](#); Symbol: [ER_RPL_UNEXPECTED_COMMIT_ROLLBACK_OR_XID_LOG_EVENT_IN_STREAM](#); SQLSTATE: [HY000](#)

Message: QUERY(COMMIT or ROLLBACK) or XID_LOG_EVENT is not expected in an event stream %s.

- Error number: [MY-010446](#); Symbol: [ER_RPL_UNEXPECTED_XA_ROLLBACK_IN_STREAM](#); SQLSTATE: [HY000](#)

Message: QUERY(XA ROLLBACK) is not expected in an event stream %s.

- Error number: [MY-010447](#); Symbol: [ER_EVENT_EXECUTION_FAILED_CANT_AUTHENTICATE_USER](#); SQLSTATE: [HY000](#)

-
- Message: Event Scheduler: [%s].[%s.%s] execution failed, failed to authenticate the user.
- Error number: `MY-010448`; Symbol: `ER_EVENT_EXECUTION_FAILED_USER_LOST_EVENT_PRIVILEGE`; `SQLSTATE: HY000`
Message: Event Scheduler: [%s].[%s.%s] execution failed, user no longer has EVENT privilege.
 - Error number: `MY-010449`; Symbol: `ER_EVENT_ERROR_DURING_COMPILATION`; `SQLSTATE: HY000`
Message: Event Scheduler: %serror during compilation of %s.%s
 - Error number: `MY-010450`; Symbol: `ER_EVENT_DROPPING`; `SQLSTATE: HY000`
Message: Event Scheduler: Dropping %s.%s
 - Error number: `MY-010452`; Symbol: `ER_RPL_INCOMPATIBLE_DECIMAL_IN_RBR`; `SQLSTATE: HY000`
Message: In RBR mode, Replica received incompatible DECIMAL field (old-style decimal field) from Source while creating conversion table. Please consider changing datatype on Source to new style decimal by executing ALTER command for column Name: %s.%s.%s.
 - Error number: `MY-010453`; Symbol: `ER_INIT_ROOT_WITHOUT_PASSWORD`; `SQLSTATE: HY000`
Message: root@localhost is created with an empty password ! Please consider switching off the --initialize-insecure option.
 - Error number: `MY-010454`; Symbol: `ER_INIT_GENERATING_TEMP_PASSWORD_FOR_ROOT`; `SQLSTATE: HY000`
Message: A temporary password is generated for root@localhost: %s
 - Error number: `MY-010455`; Symbol: `ER_INIT_CANT_OPEN_BOOTSTRAP_FILE`; `SQLSTATE: HY000`
Message: Failed to open the bootstrap file %s
 - Error number: `MY-010456`; Symbol: `ER_INIT_BOOTSTRAP_COMPLETE`; `SQLSTATE: HY000`
Message: Bootstrapping complete
 - Error number: `MY-010457`; Symbol: `ER_INIT_DATADIR_NOT_EMPTY_WONT_INITIALIZE`; `SQLSTATE: HY000`
Message: --initialize specified but the data directory has files in it. Aborting.
 - Error number: `MY-010458`; Symbol: `ER_INIT_DATADIR_EXISTS_WONT_INITIALIZE`; `SQLSTATE: HY000`
Message: --initialize specified on an existing data directory.
 - Error number: `MY-010459`; Symbol: `ER_INIT_DATADIR_EXISTS_AND_PATH_TOO_LONG_WONT_INITIALIZE`; `SQLSTATE: HY000`
Message: --initialize specified but the data directory exists and the path is too long. Aborting.
 - Error number: `MY-010460`; Symbol: `ER_INIT_DATADIR_EXISTS_AND_NOT_WRITABLE_WONT_INITIALIZE`; `SQLSTATE: HY000`
Message: --initialize specified but the data directory exists and is not writable. Aborting.

-
- Error number: [MY-010461](#); Symbol: [ER_INIT_CREATING_DD](#); SQLSTATE: [HY000](#)
Message: Creating the data directory %s
 - Error number: [MY-010462](#); Symbol: [ER_RPL_BINLOG_STARTING_DUMP](#); SQLSTATE: [HY000](#)
Message: Start binlog_dump to source_thread_id(%u) replica_server(%u), pos(%s, %llu)
 - Error number: [MY-010463](#); Symbol: [ER_RPL_BINLOG_SOURCE_SENDS_HEARTBEAT](#); SQLSTATE: [HY000](#)
Message: source sends heartbeat message
 - Error number: [MY-010464](#); Symbol: [ER_RPL_BINLOG_SKIPPING_REMAINING_HEARTBEAT_INFO](#); SQLSTATE: [HY000](#)
Message: the rest of heartbeat info skipped ...
 - Error number: [MY-010465](#); Symbol: [ER_RPL_BINLOG_SOURCE_USES_CHECKSUM_AND_REPLICA_CANT](#); SQLSTATE: [HY000](#)
Message: Source is configured to log replication events with checksum, but will not send such events to replicas that cannot process them
 - Error number: [MY-010467](#); Symbol: [ER_KILLING_THREAD](#); SQLSTATE: [HY000](#)
Message: Killing thread %lu
 - Error number: [MY-010468](#); Symbol: [ER_DETACHING_SESSION_LEFT_BY_PLUGIN](#); SQLSTATE: [HY000](#)
Message: Plugin %s is deinitializing a thread but left a session attached. Detaching it forcefully.
 - Error number: [MY-010469](#); Symbol: [ER_CANT_DETACH_SESSION_LEFT_BY_PLUGIN](#); SQLSTATE: [HY000](#)
Message: Failed to detach the session.
 - Error number: [MY-010470](#); Symbol: [ER_DETACHED_SESSIONS_LEFT_BY_PLUGIN](#); SQLSTATE: [HY000](#)
Message: Closed forcefully %u session%s left opened by plugin %s
 - Error number: [MY-010471](#); Symbol: [ER_FAILED_TO_DECREMENT_NUMBER_OF_THREADS](#); SQLSTATE: [HY000](#)
Message: Failed to decrement the number of threads
 - Error number: [MY-010472](#); Symbol: [ER_PLUGIN_DID_NOT_DEINITIALIZE_THREADS](#); SQLSTATE: [HY000](#)
Message: Plugin %s did not deinitialize %u threads
 - Error number: [MY-010473](#); Symbol: [ER_KILLED_THREADS_OF_PLUGIN](#); SQLSTATE: [HY000](#)
Message: Killed %u threads of plugin %s
 - Error number: [MY-010517](#); Symbol: [ER_DEBUG_CHECK_SHARES_OPEN](#); SQLSTATE: [HY000](#)
-

-
- Message: `debug_check_shares` open:
- Error number: `MY-010518`; Symbol: `ER_DEBUG_CHECK_SHARES_INFO`; SQLSTATE: `HY000`
Message: `%s.%s: state: %s(%u) use_count: %u`
 - Error number: `MY-010519`; Symbol: `ER_DEBUG_CHECK_SHARES_DROPPED`; SQLSTATE: `HY000`
Message: `debug_check_shares` dropped:
 - Error number: `MY-010520`; Symbol: `ER_INVALID_OR_OLD_TABLE_OR_DB_NAME`; SQLSTATE: `HY000`
Message: Invalid (old?) table or database name '`%s`'
 - Error number: `MY-010521`; Symbol: `ER_TC_RECOVERING_AFTER_CRASH_USING`; SQLSTATE: `HY000`
Message: Recovering after a crash using `%s`
 - Error number: `MY-010522`; Symbol: `ER_TC_CANT_AUTO_RECOVER_WITH_TC_HEURISTIC_RECOVER`; SQLSTATE: `HY000`
Message: Cannot perform automatic crash recovery when `--tc-heuristic-recover` is used
 - Error number: `MY-010523`; Symbol: `ER_TC_BAD_MAGIC_IN_TC_LOG`; SQLSTATE: `HY000`
Message: Bad magic header in tc log
 - Error number: `MY-010524`; Symbol: `ER_TC_NEED_N_SE_SUPPORTING_2PC_FOR_RECOVERY`; SQLSTATE: `HY000`
Message: Recovery failed! You must enable exactly `%d` storage engines that support two-phase commit protocol
 - Error number: `MY-010525`; Symbol: `ER_TC_RECOVERY_FAILED_THESE_ARE_YOUR_OPTIONS`; SQLSTATE: `HY000`
Message: Crash recovery failed. Either correct the problem (if it's, for example, out of memory error) and restart, or delete tc log and start `mysqld` with `--tc-heuristic-recover={commit|rollback}`
 - Error number: `MY-010526`; Symbol: `ER_TC_HEURISTIC_RECOVERY_MODE`; SQLSTATE: `HY000`
Message: Heuristic crash recovery mode
 - Error number: `MY-010527`; Symbol: `ER_TC_HEURISTIC_RECOVERY_FAILED`; SQLSTATE: `HY000`
Message: Heuristic crash recovery failed
 - Error number: `MY-010528`; Symbol: `ER_TC_RESTART_WITHOUT_TC_HEURISTIC_RECOVER`; SQLSTATE: `HY000`
Message: Please restart `mysqld` without `--tc-heuristic-recover`
 - Error number: `MY-010529`; Symbol: `ER_RPL_REPLICA_FAILED_TO_CREATE_OR_RECOVER_INFO_REPOSITORIES`; SQLSTATE: `HY000`
Message: Failed to create or recover replication info repositories.
 - Error number: `MY-010530`; Symbol: `ER_RPL_REPLICA_AUTO_POSITION_IS_1_AND_GTID_MODE_IS_OFF`; SQLSTATE: `HY000`

Message: Detected misconfiguration: replication channel '%s' was configured with AUTO_POSITION = 1, but the server was started with --gtid-mode=off. Either reconfigure replication using CHANGE REPLICATION SOURCE TO SOURCE_AUTO_POSITION = 0 FOR CHANNEL '%s', or change GTID_MODE to some value other than OFF, before starting the replica receiver thread.

- Error number: [MY-010531](#); Symbol: [ER_RPL_REPLICA_CANT_START_REPLICA_FOR_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Replica: Could not start replica for channel '%s'. operation discontinued

- Error number: [MY-010532](#); Symbol: [ER_RPL_REPLICA_CANT_STOP_REPLICA_FOR_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Replica: Could not stop replica for channel '%s' operation discontinued

- Error number: [MY-010533](#); Symbol: [ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SOURCE](#); SQLSTATE: [HY000](#)

Message: Error during --relay-log-recovery: Could not locate rotate event from the source.

- Error number: [MY-010534](#); Symbol: [ER_RPL_RECOVERY_ERROR_READ_RELAY_LOG](#); SQLSTATE: [HY000](#)

Message: Error during --relay-log-recovery: Error reading events from relay log: %d

- Error number: [MY-010536](#); Symbol: [ER_RPL_RECOVERY_SKIPPED_GROUP_REPLICATION_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Relay log recovery skipped for group replication channel.

- Error number: [MY-010537](#); Symbol: [ER_RPL_RECOVERY_ERROR](#); SQLSTATE: [HY000](#)

Message: Error during --relay-log-recovery: %s

- Error number: [MY-010538](#); Symbol: [ER_RPL_RECOVERY_IO_ERROR_READING_RELAY_LOG_INDEX](#); SQLSTATE: [HY000](#)

Message: Error during --relay-log-recovery: Could not read relay log index file due to an IO error.

- Error number: [MY-010539](#); Symbol: [ER_RPL_RECOVERY_FILE_SOURCE_POS_INFO](#); SQLSTATE: [HY000](#)

Message: Recovery from source pos %ld and file %s%. Previous relay log pos and relay log file had been set to %lld, %s respectively.

- Error number: [MY-010540](#); Symbol: [ER_RPL_RECOVERY_REPLICATE_SAME_SERVER_ID_REQUIRES_POSITION](#); SQLSTATE: [HY000](#)

Message: Error during --relay-log-recovery: replicate_same_server_id is in use and sql thread's positions are not initialized, hence relay log recovery cannot happen.

- Error number: [MY-010541](#); Symbol: [ER_RPL_MTA_RECOVERY_STARTING_COORDINATOR](#); SQLSTATE: [HY000](#)

Message: MTA recovery: starting coordinator thread to fill MTA gaps.

- Error number: [MY-010542](#); Symbol: [ER_RPL_MTA_RECOVERY_FAILED_TO_START_COORDINATOR](#); SQLSTATE: [HY000](#)

Message: MTA recovery: failed to start the coordinator thread. Check the error log for additional details.

- Error number: [MY-010543](#); Symbol: [ER_RPL_MTA_AUTOMATIC_RECOVERY_FAILED](#); SQLSTATE: [HY000](#)

Message: MTA recovery: automatic recovery failed. Either the replica server had stopped due to an error during an earlier session or relay logs are corrupted. Fix the cause of the replica side error and restart the replica server or consider using RESET REPLICA.

- Error number: [MY-010544](#); Symbol: [ER_RPL_MTA_RECOVERY_CANT_OPEN_RELAY_LOG](#); SQLSTATE: [HY000](#)

Message: Failed to open the relay log '%s' (relay_log_pos %s).

- Error number: [MY-010545](#); Symbol: [ER_RPL_MTA_RECOVERY_SUCCESSFUL](#); SQLSTATE: [HY000](#)

Message: MTA recovery: completed successfully.

- Error number: [MY-010546](#); Symbol: [ER_RPL_SERVER_ID_MISSING](#); SQLSTATE: [HY000](#)

Message: Server id not set, will not start replica%s

- Error number: [MY-010547](#); Symbol: [ER_RPL_CANT_CREATE_REPLICA_THREAD](#); SQLSTATE: [HY000](#)

Message: Can't create replica thread%s.

- Error number: [MY-010548](#); Symbol: [ER_RPL_REPLICA_IO_THREAD_WAS_KILLED](#); SQLSTATE: [HY000](#)

Message: The replica IO thread%s was killed while executing initialization query '%s'

- Error number: [MY-010550](#); Symbol: [ER_RPL_REPLICA_USES_CHECKSUM_AND_SOURCE_PRE_50](#); SQLSTATE: [HY000](#)

Message: Found a source with MySQL server version older than 5.0. With checksums enabled on the replica, replication might not work correctly. To ensure correct replication, restart the replica server with --replica_sql_verify_checksum=0.

- Error number: [MY-010551](#); Symbol: [ER_RPL_REPLICA_SECONDS_BEHIND_SOURCE_DUBIOUS](#); SQLSTATE: [HY000](#)

Message: "SELECT UNIX_TIMESTAMP()" failed on source, do not trust column Seconds_Behind_Source of SHOW REPLICA STATUS. Error: %s (%d)

- Error number: [MY-010552](#); Symbol: [ER_RPL_REPLICA_CANT_FLUSH_CONNECTION_METADATA_REPOS](#); SQLSTATE: [HY000](#)

Message: Failed to flush connection metadata repository.

- Error number: [MY-010553](#); Symbol: [ER_RPL_REPLICA_REPORT_HOST_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: The length of report_host is %zu. It is larger than the max length(%d), so this replica cannot be registered to the source%s.

- Error number: [MY-010554](#); Symbol: [ER_RPL_REPLICA_REPORT_USER_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: The length of report_user is %zu. It is larger than the max length(%d), so this replica cannot be registered to the source%s.

- Error number: MY-010555; Symbol: ER_RPL_REPLICA_REPORT_PASSWORD_TOO_LONG; SQLSTATE: HY000

Message: The length of report_password is %zu. It is larger than the max length(%d), so this replica cannot be registered to the source%s.

- Error number: MY-010556; Symbol: ER_RPL_REPLICA_ERROR_RETRYING; SQLSTATE: HY000

Message: Error on %s: %d %s, will retry in %d secs

- Error number: MY-010557; Symbol: ER_RPL_REPLICA_ERROR_READING_FROM_SERVER; SQLSTATE: HY000

Message: Error reading packet from server%s: %s (server_errno=%d)

- Error number: MY-010558; Symbol: ER_RPL_REPLICA_DUMP_THREAD_KILLED_BY_SOURCE; SQLSTATE: HY000

Message: Replica%s: received end packet from server due to dump thread being killed on source. Dump threads are killed for example during source shutdown, explicitly by a user, or when the source receives a binlog send request from a duplicate server UUID <%s> : Error %s

- Error number: MY-010559; Symbol: ER_RPL_MTA_STATISTICS; SQLSTATE: HY000

Message: Multi-threaded replica statistics%s: seconds elapsed = %lu; events assigned = %lu; worker queues filled over overrun level = %lu; waited due a Worker queue full = %lu; waited due the total size = %lu; waited at clock conflicts = %llu waited (count) when Workers occupied = %lu waited when Workers occupied = %llu

- Error number: MY-010560; Symbol: ER_RPL_MTA_RECOVERY_COMPLETE; SQLSTATE: HY000

Message: Replica%s: MTA Recovery has completed at relay log %s, position %llu source log %s, position %llu.

- Error number: MY-010561; Symbol: ER_RPL_REPLICA_CANT_INIT_RELAY_LOG_POSITION; SQLSTATE: HY000

Message: Error initializing relay log position%s: %s

- Error number: MY-010563; Symbol: ER_RPL_REPLICA_IO_THREAD_KILLED; SQLSTATE: HY000

Message: Replica I/O thread%s killed while connecting to source

- Error number: MY-010564; Symbol: ER_RPL_REPLICA_IO_THREAD_CANT_REGISTER_ON_SOURCE; SQLSTATE: HY000

Message: Replica I/O thread couldn't register on source

- Error number: MY-010565; Symbol: ER_RPL_REPLICA_FORCING_TO_RECONNECT_IO_THREAD; SQLSTATE: HY000

Message: Forcing to reconnect replica I/O thread%s

- Error number: MY-010566; Symbol: ER_RPL_REPLICA_ERROR_REQUESTING_BINLOG_DUMP; SQLSTATE: HY000

Message: Failed on request_dump() %s

- Error number: MY-010567; Symbol: ER_RPL_LOG_ENTRY_EXCEEDS_REPLICA_MAX_ALLOWED_PACKET; SQLSTATE: HY000

Message: Log entry on source is longer than replica_max_allowed_packet (%lu) on replica. If the entry is correct, restart the server with a higher value of replica_max_allowed_packet

- Error number: MY-010568; Symbol: ER_RPL_REPLICA_STOPPING_AS_SOURCE_OOM; SQLSTATE: HY000

Message: Stopping replica I/O thread due to out-of-memory error from source

- Error number: MY-010569; Symbol: ER_RPL_REPLICA_IO_THREAD_ABORTED_WAITING_FOR_RELAY_LOG_SPACE; SQLSTATE: HY000

Message: Replica I/O thread aborted while waiting for relay log space

- Error number: MY-010570; Symbol: ER_RPL_REPLICA_IO_THREAD_EXITING; SQLSTATE: HY000

Message: Replica I/O thread exiting %s, read up to log '%s', position %s

- Error number: MY-010571; Symbol: ER_RPL_REPLICA_CANT_INITIALIZE_REPLICA_WORKER; SQLSTATE: HY000

Message: Failed during replica worker initialization %s

- Error number: MY-010572; Symbol: ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA_FOR_WORKER; SQLSTATE: HY000

Message: Replica: MTA group recovery applier metadata based on Worker-Id %lu, group_relay_log_name %s, group_relay_log_pos %llu group_source_log_name %s, group_source_log_pos %llu

- Error number: MY-010573; Symbol: ER_RPL_ERROR_LOOKING_FOR_LOG; SQLSTATE: HY000

Message: Error looking for %s.

- Error number: MY-010574; Symbol: ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA; SQLSTATE: HY000

Message: Replica: MTA group recovery applier metadata group_source_log_name %s, event_source_log_pos %llu.

- Error number: MY-010575; Symbol: ER_RPL_CANT_FIND_FOLLOWUP_FILE; SQLSTATE: HY000

Message: Error looking for file after %s.

- Error number: MY-010576; Symbol: ER_RPL_MTA_CHECKPOINT_PERIOD_DIFFERS_FROM_CNT; SQLSTATE: HY000

Message: This an error cnt != mta_checkpoint_period

- Error number: MY-010577; Symbol: ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED; SQLSTATE: HY000

Message: Failed during replica worker thread creation %s

-
- Error number: [MY-010578](#); Symbol: [ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED_WITH_ERRNO](#); SQLSTATE: [HY000](#)
Message: Failed during replica worker thread creation%s (errno= %d)
 - Error number: [MY-010579](#); Symbol: [ER_RPL_REPLICA_FAILED_TO_INIT_PARTITIONS_HASH](#); SQLSTATE: [HY000](#)
Message: Failed to init partitions hash
 - Error number: [MY-010581](#); Symbol: [ER_RPL_REPLICA_SQL_THREAD_STARTING](#); SQLSTATE: [HY000](#)
Message: Replica SQL thread%s initialized, starting replication in log '%s' at position %s, relay log '%s' position: %s
 - Error number: [MY-010582](#); Symbol: [ER_RPL_REPLICA_SKIP_COUNTER_EXECUTED](#); SQLSTATE: [HY000](#)
Message: 'SQL_REPLICA_SKIP_COUNTER=%ld' executed at relay_log_file='%s', relay_log_pos='%ld', source_log_name='%s', source_log_pos='%ld' and new position at relay_log_file='%s', relay_log_pos='%ld', source_log_name='%s', source_log_pos='%ld'
 - Error number: [MY-010583](#); Symbol: [ER_RPL_REPLICA_ADDITIONAL_ERROR_INFO_FROM_DA](#); SQLSTATE: [HY000](#)
Message: Replica (additional info): %s Error_code: MY-%06d
 - Error number: [MY-010584](#); Symbol: [ER_RPL_REPLICA_ERROR_INFO_FROM_DA](#); SQLSTATE: [HY000](#)
Message: Replica: %s Error_code: MY-%06d
 - Error number: [MY-010585](#); Symbol: [ER_RPL_REPLICA_ERROR_LOADING_USER_DEFINED_LIBRARY](#); SQLSTATE: [HY000](#)
Message: Error loading user-defined library, replica SQL thread aborted. Install the missing library, and restart the replica SQL thread with "START REPLICA". We stopped at log '%s' position %s
 - Error number: [MY-010586](#); Symbol: [ER_RPL_REPLICA_ERROR_RUNNING_QUERY](#); SQLSTATE: [HY000](#)
Message: Error running query, replica SQL thread aborted. Fix the problem, and restart the replica SQL thread with "START REPLICA". We stopped at log '%s' position %s
 - Error number: [MY-010587](#); Symbol: [ER_RPL_REPLICA_SQL_THREAD_EXITING](#); SQLSTATE: [HY000](#)
Message: Replica SQL thread%s exiting, replication stopped in log '%s' at position %s
 - Error number: [MY-010588](#); Symbol: [ER_RPL_REPLICA_READ_INVALID_EVENT_FROM_SOURCE](#); SQLSTATE: [HY000](#)
Message: Read invalid event from source: '%s', source could be corrupt but a more likely cause of this is a bug
 - Error number: [MY-010589](#); Symbol: [ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_CONFIGURATION](#); SQLSTATE: [HY000](#)
Message: The queue event failed for channel '%s' as its configuration is invalid.
 - Error number: [MY-010590](#); Symbol: [ER_RPL_REPLICA_IO_THREAD_DETECTED_UNEXPECTED_EVENT_SEQUENCE](#); SQLSTATE: [HY000](#)
-

Message: An unexpected event sequence was detected by the IO thread while queuing the event received from source '%s' binary log file, at position %llu.

- Error number: `MY-010591`; Symbol: `ER_RPL_REPLICA_CANT_USE_CHARSET`; SQLSTATE: `HY000`

Message: '%s' can not be used as client character set. '%s' will be used as default client character set while connecting to source.

- Error number: `MY-010592`; Symbol: `ER_RPL_REPLICA_CONNECTED_TO_SOURCE_REPLICATION_RESUMED`; SQLSTATE: `HY000`

Message: Replica%s: connected to source '%s@%s:%d', replication resumed in log '%s' at position %s

- Error number: `MY-010593`; Symbol: `ER_RPL_REPLICA_NEXT_LOG_IS_ACTIVE`; SQLSTATE: `HY000`

Message: next log '%s' is active

- Error number: `MY-010594`; Symbol: `ER_RPL_REPLICA_NEXT_LOG_IS_INACTIVE`; SQLSTATE: `HY000`

Message: next log '%s' is not active

- Error number: `MY-010595`; Symbol: `ER_RPL_REPLICA_SQL_THREAD_IO_ERROR_READING_EVENT`; SQLSTATE: `HY000`

Message: Replica SQL thread%s: I/O error reading event (errno: %d cur_log->error: %d)

- Error number: `MY-010596`; Symbol: `ER_RPL_REPLICA_ERROR_READING_RELAY_LOG_EVENTS`; SQLSTATE: `HY000`

Message: Error reading relay log event%s: %s

- Error number: `MY-010597`; Symbol: `ER_REPLICA_CHANGE_SOURCE_TO_EXECUTED`; SQLSTATE: `HY000`

Message: 'CHANGE REPLICATION SOURCE TO%s executed'. Previous state source_host='%s', source_port= %u, source_log_file='%s', source_log_pos= %ld, source_bind='%s'. New state source_host='%s', source_port= %u, source_log_file='%s', source_log_pos= %ld, source_bind='%s'.

- Error number: `MY-010598`; Symbol: `ER_RPL_REPLICA_NEW_C_M_NEEDS_REPOS_TYPE_OTHER_THAN_FILE`; SQLSTATE: `HY000`

Message: Replica: Cannot create new connection metadata structure when repositories are of type FILE. Convert replica repositories to TABLE to replicate from multiple sources.

- Error number: `MY-010599`; Symbol: `ER_RPL_FAILED_TO_STAT_LOG_IN_INDEX`; SQLSTATE: `HY000`

Message: log %s listed in the index, but failed to stat.

- Error number: `MY-010600`; Symbol: `ER_RPL_LOG_NOT_FOUND_WHILE_COUNTING_RELAY_LOG_SPACE`; SQLSTATE: `HY000`

Message: Could not find first log while counting relay log space.

- Error number: `MY-010601`; Symbol: `ER_REPLICA_CANT_USE_TEMPDIR`; SQLSTATE: `HY000`

Message: Unable to use replica's temporary directory '%s'.

-
- Error number: `MY-010602`; Symbol: `ER_RPL_RELAY_LOG_NEEDS_FILE_NOT_DIRECTORY`; SQLSTATE: `HY000`
Message: Path '%s' is a directory name, please specify a file name for --relay-log option.
 - Error number: `MY-010603`; Symbol: `ER_RPL_RELAY_LOG_INDEX_NEEDS_FILE_NOT_DIRECTORY`; SQLSTATE: `HY000`
Message: Path '%s' is a directory name, please specify a file name for --relay-log-index option.
 - Error number: `MY-010604`; Symbol: `ER_RPL_PLEASE_USE_OPTION_RELAY_LOG`; SQLSTATE: `HY000`
Message: Neither --relay-log nor --relay-log-index were used; so replication may break when this MySQL server acts as a replica and has his hostname changed!! Please use '--relay-log=%s' to avoid this problem.
 - Error number: `MY-010605`; Symbol: `ER_RPL_OPEN_INDEX_FILE_FAILED`; SQLSTATE: `HY000`
Message: Failed in open_index_file() called from Relay_log_info::rli_init_info().
 - Error number: `MY-010606`; Symbol: `ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_AM_INIT_INFO`; SQLSTATE: `HY000`
Message: Failed in init_gtid_sets() called from Relay_log_info::rli_init_info().
 - Error number: `MY-010607`; Symbol: `ER_RPL_CANT_OPEN_LOG_IN_AM_INIT_INFO`; SQLSTATE: `HY000`
Message: Failed in open_log() called from Relay_log_info::rli_init_info().
 - Error number: `MY-010608`; Symbol: `ER_RPL_ERROR_WRITING_RELAY_LOG_CONFIGURATION`; SQLSTATE: `HY000`
Message: Error writing relay log configuration.
 - Error number: `MY-010709`; Symbol: `ER_TREE_CORRUPT_PARENT_SHOULD_POINT_AT_PARENT`; SQLSTATE: `HY000`
Message: Wrong tree: Parent doesn't point at parent
 - Error number: `MY-010710`; Symbol: `ER_TREE_CORRUPT_ROOT_SHOULD_BE_BLACK`; SQLSTATE: `HY000`
Message: Wrong tree: Root should be black
 - Error number: `MY-010711`; Symbol: `ER_TREE_CORRUPT_2_CONSECUTIVE_REDS`; SQLSTATE: `HY000`
Message: Wrong tree: Found two red in a row
 - Error number: `MY-010712`; Symbol: `ER_TREE_CORRUPT_RIGHT_IS_LEFT`; SQLSTATE: `HY000`
Message: Wrong tree: Found right == left
 - Error number: `MY-010713`; Symbol: `ER_TREE_CORRUPT_INCORRECT_BLACK_COUNT`; SQLSTATE: `HY000`
Message: Wrong tree: Incorrect black-count: %d - %d
 - Error number: `MY-010714`; Symbol: `ER_WRONG_COUNT_FOR_ORIGIN`; SQLSTATE: `HY000`
-

-
- Message: Use_count: Wrong count %lu for origin %p
- Error number: [MY-010715](#); Symbol: [ER_WRONG_COUNT_FOR_KEY](#); SQLSTATE: [HY000](#)
Message: Use_count: Wrong count for key at %p, %lu should be %lu
 - Error number: [MY-010716](#); Symbol: [ER_WRONG_COUNT_OF_ELEMENTS](#); SQLSTATE: [HY000](#)
Message: Wrong number of elements: %u (should be %u) for tree at %p
 - Error number: [MY-010717](#); Symbol: [ER_RPL_ERROR_READING_REPLICA_WORKER_CONFIGURATION](#); SQLSTATE: [HY000](#)
Message: Error reading replica worker configuration
 - Error number: [MY-010719](#); Symbol: [ER_RPL_FAILED_TO_OPEN_RELAY_LOG](#); SQLSTATE: [HY000](#)
Message: Failed to open relay log %s, error: %s
 - Error number: [MY-010720](#); Symbol: [ER_RPL_WORKER_CANT_READ_RELAY_LOG](#); SQLSTATE: [HY000](#)
Message: Error when worker read relay log events, relay log name %s, position %llu
 - Error number: [MY-010721](#); Symbol: [ER_RPL_WORKER_CANT_FIND_NEXT_RELAY_LOG](#); SQLSTATE: [HY000](#)
Message: Failed to find next relay log when retrying the transaction, current relay log is %s
 - Error number: [MY-010722](#); Symbol: [ER_RPL_MTA_REPLICA_COORDINATOR_HAS_WAITED](#); SQLSTATE: [HY000](#)
Message: Multi-threaded replica: Coordinator has waited %lu times hitting replica_pending_jobs_size_max; current event size = %zu.
 - Error number: [MY-010723](#); Symbol: [ER_BINLOG_FAILED_TO_WRITE_DROP_FOR_TEMP_TABLES](#); SQLSTATE: [HY000](#)
Message: Failed to write the DROP statement for temporary tables to binary log
 - Error number: [MY-010724](#); Symbol: [ER_BINLOG_OOM_WRITING_DELETE_WHILE_OPENING_HEAP_TABLE](#); SQLSTATE: [HY000](#)
Message: When opening HEAP table, could not allocate memory to write 'DELETE FROM `%s`.`%s`' to the binary log
 - Error number: [MY-010725](#); Symbol: [ER_FAILED_TO_REPAIR_TABLE](#); SQLSTATE: [HY000](#)
Message: Couldn't repair table: %s.%s
 - Error number: [MY-010726](#); Symbol: [ER_FAILED_TO_REMOVE_TEMP_TABLE](#); SQLSTATE: [HY000](#)
Message: Could not remove temporary table: '%s', error: %d
 - Error number: [MY-010727](#); Symbol: [ER_SYSTEM_TABLE_NOT_TRANSACTIONAL](#); SQLSTATE: [HY000](#)
Message: System table '%.*s' is expected to be transactional.
 - Error number: [MY-010728](#); Symbol: [ER_RPL_ERROR_WRITING_SOURCE_CONFIGURATION](#); SQLSTATE: [HY000](#)

Message: Error writing source configuration.

- Error number: `MY-010729`; Symbol: `ER_RPL_ERROR_READING_SOURCE_CONFIGURATION`; SQLSTATE: `HY000`

Message: Error reading source configuration.

- Error number: `MY-010730`; Symbol: `ER_RPL_SSL_INFO_IN_CONNECTION_METADATA_IGNORED`; SQLSTATE: `HY000`

Message: SSL information in the connection metadata repository are ignored because this MySQL replica was compiled without SSL support.

- Error number: `MY-010731`; Symbol: `ER_PLUGIN_FAILED_DEINITIALIZATION`; SQLSTATE: `HY000`

Message: Plugin '%s' of type %s failed deinitialization

- Error number: `MY-010732`; Symbol: `ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_DEINITIALIZATION`; SQLSTATE: `HY000`

Message: Plugin '%s' has ref_count=%d after deinitialization.

- Error number: `MY-010733`; Symbol: `ER_PLUGIN_SHUTTING_DOWN_PLUGIN`; SQLSTATE: `HY000`

Message: Shutting down plugin '%s'

- Error number: `MY-010734`; Symbol: `ER_PLUGIN_REGISTRATION_FAILED`; SQLSTATE: `HY000`

Message: Plugin '%s' registration as a %s failed.

- Error number: `MY-010735`; Symbol: `ER_PLUGIN_CANT_OPEN_PLUGIN_TABLE`; SQLSTATE: `HY000`

Message: Could not open the mysql.plugin table. Please perform the MySQL upgrade procedure.

- Error number: `MY-010736`; Symbol: `ER_PLUGIN_CANT_LOAD`; SQLSTATE: `HY000`

Message: Couldn't load plugin named '%s' with soname '%s'.

- Error number: `MY-010737`; Symbol: `ER_PLUGIN_LOAD_PARAMETER_TOO_LONG`; SQLSTATE: `HY000`

Message: plugin-load parameter too long

- Error number: `MY-010738`; Symbol: `ER_PLUGIN_FORCING_SHUTDOWN`; SQLSTATE: `HY000`

Message: Plugin '%s' will be forced to shutdown

- Error number: `MY-010739`; Symbol: `ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_SHUTDOWN`; SQLSTATE: `HY000`

Message: Plugin '%s' has ref_count=%d after shutdown.

- Error number: `MY-010740`; Symbol: `ER_PLUGIN_UNKNOWN_VARIABLE_TYPE`; SQLSTATE: `HY000`

Message: Unknown variable type code 0x%x in plugin '%s'.

- Error number: `MY-010741`; Symbol: `ER_PLUGIN_VARIABLE_SET_READ_ONLY`; SQLSTATE: `HY000`

Message: Server variable %s of plugin %s was forced to be read-only: string variable without update_func and PLUGIN_VAR_MEMALLOC flag

-
- Error number: [MY-010742](#); Symbol: [ER_PLUGIN_VARIABLE_MISSING_NAME](#); SQLSTATE: [HY000](#)
Message: Missing variable name in plugin '%s'.
 - Error number: [MY-010743](#); Symbol: [ER_PLUGIN_VARIABLE_NOT_ALLOCATED_THREAD_LOCAL](#); SQLSTATE: [HY000](#)
Message: Thread local variable '%s' not allocated in plugin '%s'.
 - Error number: [MY-010744](#); Symbol: [ER_PLUGIN_OOM](#); SQLSTATE: [HY000](#)
Message: Out of memory for plugin '%s'.
 - Error number: [MY-010745](#); Symbol: [ER_PLUGIN_BAD_OPTIONS](#); SQLSTATE: [HY000](#)
Message: Bad options for plugin '%s'.
 - Error number: [MY-010746](#); Symbol: [ER_PLUGIN_PARSING_OPTIONS_FAILED](#); SQLSTATE: [HY000](#)
Message: Parsing options for plugin '%s' failed.
 - Error number: [MY-010747](#); Symbol: [ER_PLUGIN_DISABLED](#); SQLSTATE: [HY000](#)
Message: Plugin '%s' is disabled.
 - Error number: [MY-010748](#); Symbol: [ER_PLUGIN_HAS_CONFLICTING_SYSTEM_VARIABLES](#); SQLSTATE: [HY000](#)
Message: Plugin '%s' has conflicting system variables
 - Error number: [MY-010749](#); Symbol: [ER_PLUGIN_CANT_SET_PERSISTENT_OPTIONS](#); SQLSTATE: [HY000](#)
Message: Setting persistent options for plugin '%s' failed.
 - Error number: [MY-010750](#); Symbol: [ER_MY_NET_WRITE_FAILED_FALLING_BACK_ON_STDERR](#); SQLSTATE: [HY000](#)
Message: Failed on my_net_write, writing to stderr instead: %s
 - Error number: [MY-010751](#); Symbol: [ER_RETRYING_REPAIR_WITHOUT_QUICK](#); SQLSTATE: [HY000](#)
Message: Retrying repair of: '%s' without quick
 - Error number: [MY-010752](#); Symbol: [ER_RETRYING_REPAIR_WITH_KEYCACHE](#); SQLSTATE: [HY000](#)
Message: Retrying repair of: '%s' with keycache
 - Error number: [MY-010753](#); Symbol: [ER_FOUND_ROWS_WHILE_REPAIRING](#); SQLSTATE: [HY000](#)
Message: Found %s of %s rows when repairing '%s'
 - Error number: [MY-010754](#); Symbol: [ER_ERROR_DURING_OPTIMIZE_TABLE](#); SQLSTATE: [HY000](#)
Message: Warning: Optimize table got errno %d on %s.%s, retrying
 - Error number: [MY-010755](#); Symbol: [ER_ERROR_ENABLING_KEYS](#); SQLSTATE: [HY000](#)
Message: Warning: Enabling keys got errno %d on %s.%s, retrying

-
- Error number: [MY-010756](#); Symbol: [ER_CHECKING_TABLE](#); SQLSTATE: [HY000](#)
Message: Checking table: '%s'
 - Error number: [MY-010757](#); Symbol: [ER_RECOVERING_TABLE](#); SQLSTATE: [HY000](#)
Message: Recovering table: '%s'
 - Error number: [MY-010758](#); Symbol: [ER_CANT_CREATE_TABLE_SHARE_FROM_FRM](#); SQLSTATE: [HY000](#)
Message: Error in creating TABLE_SHARE from %s.frm file.
 - Error number: [MY-010759](#); Symbol: [ER_CANT_LOCK_TABLE](#); SQLSTATE: [HY000](#)
Message: Unable to acquire lock on %s.%s
 - Error number: [MY-010760](#); Symbol: [ER_CANT_ALLOC_TABLE_OBJECT](#); SQLSTATE: [HY000](#)
Message: Error in allocation memory for TABLE object.
 - Error number: [MY-010761](#); Symbol: [ER_CANT_CREATE_HANDLER_OBJECT_FOR_TABLE](#); SQLSTATE: [HY000](#)
Message: Error in creating handler object for table %s.%s
 - Error number: [MY-010762](#); Symbol: [ER_CANT_SET_HANDLER_REFERENCE_FOR_TABLE](#); SQLSTATE: [HY000](#)
Message: Error in setting handler reference for table %s.%s
 - Error number: [MY-010763](#); Symbol: [ER_CANT_LOCK_TABLESPACE](#); SQLSTATE: [HY000](#)
Message: Unable to acquire lock on tablespace name %s
 - Error number: [MY-010764](#); Symbol: [ER_CANT_UPGRADE_GENERATED_COLUMNS_TO_DD](#); SQLSTATE: [HY000](#)
Message: Error in processing generated columns for table %s.%s
 - Error number: [MY-010765](#); Symbol: [ER_DD_ERROR_CREATING_ENTRY](#); SQLSTATE: [HY000](#)
Message: Error in Creating DD entry for %s.%s
 - Error number: [MY-010766](#); Symbol: [ER_DD_CANT_FETCH_TABLE_DATA](#); SQLSTATE: [HY000](#)
Message: Error in fetching %s.%s table data from dictionary
 - Error number: [MY-010767](#); Symbol: [ER_DD_CANT_FIX_SE_DATA](#); SQLSTATE: [HY000](#)
Message: Error in fixing SE data for %s.%s
 - Error number: [MY-010768](#); Symbol: [ER_DD_CANT_CREATE_SP](#); SQLSTATE: [HY000](#)
Message: Error in creating stored program '%s.%s'
 - Error number: [MY-010769](#); Symbol: [ER_CANT_OPEN_DB_OPT_USING_DEFAULT_CHARSET](#); SQLSTATE: [HY000](#)
Message: Unable to open db.opt file %s. Using default Character set.
-

-
- Error number: [MY-010770](#); Symbol: [ER_CANT_CREATE_CACHE_FOR_DB_OPT](#); SQLSTATE: [HY000](#)
Message: Unable to initialize IO cache to open db.opt file %s.
 - Error number: [MY-010771](#); Symbol: [ER_CANT_IDENTIFY_CHARSET_USING_DEFAULT](#); SQLSTATE: [HY000](#)
Message: Unable to identify the charset in %s. Using default character set.
 - Error number: [MY-010772](#); Symbol: [ER_DB_OPT_NOT_FOUND_USING_DEFAULT_CHARSET](#); SQLSTATE: [HY000](#)
Message: db.opt file not found for %s database. Using default Character set.
 - Error number: [MY-010773](#); Symbol: [ER_EVENT_CANT_GET_TIMEZONE_FROM_FIELD](#); SQLSTATE: [HY000](#)
Message: Event '%s'. '%s': invalid value in column mysql.event.time_zone.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.
 - Error number: [MY-010774](#); Symbol: [ER_EVENT_CANT_FIND_TIMEZONE](#); SQLSTATE: [HY000](#)
Message: Event '%s'. '%s': has invalid time zone value

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.
 - Error number: [MY-010775](#); Symbol: [ER_EVENT_CANT_GET_CHARSET](#); SQLSTATE: [HY000](#)
Message: Event '%s'. '%s': invalid value in column mysql.event.character_set_client.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.
 - Error number: [MY-010776](#); Symbol: [ER_EVENT_CANT_GET_COLLATION](#); SQLSTATE: [HY000](#)
Message: Event '%s'. '%s': invalid value in column mysql.event.collation_connection.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.
 - Error number: [MY-010777](#); Symbol: [ER_EVENT_CANT_OPEN_TABLE_MYSQL_EVENT](#); SQLSTATE: [HY000](#)
Message: Failed to open mysql.event Table.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.event` system table and migrates its contents to the internal data dictionary.
 - Error number: [MY-010778](#); Symbol: [ER_CANT_PARSE_STORED_ROUTINE_BODY](#); SQLSTATE: [HY000](#)
Message: Parsing '%s.%s' routine body failed.%s
 - Error number: [MY-010779](#); Symbol: [ER_CANT_OPEN_TABLE_MYSQL_PROC](#); SQLSTATE: [HY000](#)
Message: Failed to open mysql.proc Table.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.proc` system table and migrates its contents to the internal data dictionary.

- Error number: `MY-010780`; Symbol: `ER_CANT_READ_TABLE_MYSQL_PROC`; SQLSTATE: `HY000`

Message: Failed to read mysql.proc table.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the `mysql.proc` system table and migrates its contents to the internal data dictionary.

- Error number: `MY-010781`; Symbol: `ER_FILE_EXISTS_DURING_UPGRADE`; SQLSTATE: `HY000`

Message: Found %s file in mysql schema. DD will create .ibd file with same name. Please rename table and start upgrade process again.

- Error number: `MY-010782`; Symbol: `ER_CANT_OPEN_DATADIR_AFTER_UPGRADE_FAILURE`; SQLSTATE: `HY000`

Message: Unable to open the data directory %s during clean up after upgrade failed

- Error number: `MY-010783`; Symbol: `ER_CANT_SET_PATH_FOR`; SQLSTATE: `HY000`

Message: Failed to set path %s

- Error number: `MY-010784`; Symbol: `ER_CANT_OPEN_DIR`; SQLSTATE: `HY000`

Message: Failed to open dir %s

- Error number: `MY-010801`; Symbol: `ER_EVENT_ERROR_CREATING_QUERY_TO_WRITE_TO_BINLOG`; SQLSTATE: `HY000`

Message: Event Error: An error occurred while creating query string, before writing it into binary log.

- Error number: `MY-010802`; Symbol: `ER_EVENT_SCHEDULER_ERROR_LOADING_FROM_DB`; SQLSTATE: `HY000`

Message: Event Scheduler: Error while loading from disk.

- Error number: `MY-010803`; Symbol: `ER_EVENT_SCHEDULER_ERROR_GETTING_EVENT_OBJECT`; SQLSTATE: `HY000`

Message: Event Scheduler: Error getting event object.

- Error number: `MY-010804`; Symbol: `ER_EVENT_SCHEDULER_GOT_BAD_DATA_FROM_TABLE`; SQLSTATE: `HY000`

Message: Event Scheduler: Error while loading events from mysql.events. The table probably contains bad data or is corrupted

- Error number: `MY-010805`; Symbol: `ER_EVENT_CANT_GET_LOCK_FOR_DROPPING_EVENT`; SQLSTATE: `HY000`

Message: Unable to obtain lock for dropping event %s from schema %s

- Error number: `MY-010806`; Symbol: `ER_EVENT_UNABLE_TO_DROP_EVENT`; SQLSTATE: `HY000`

Message: Unable to drop event %s from schema %s

- Error number: `MY-010808`; Symbol: `ER_BINLOG_CANT_RESIZE_CACHE`; SQLSTATE: `HY000`

Message: Unable to resize binlog IOCACHE auxiliary file

- Error number: `MY-010809`; Symbol: `ER_BINLOG_FILE_BEING_READ_NOT_PURGED`; SQLSTATE: `HY000`

Message: file %s was not purged because it was being read by thread number %u

- Error number: `MY-010810`; Symbol: `ER_BINLOG_IO_ERROR_READING_HEADER`; SQLSTATE: `HY000`

Message: I/O error reading the header from the binary log, errno=%d, io cache code=%d

- Error number: `MY-010813`; Symbol: `ER_BINLOG_FILE_EXTENSION_NUMBER_EXHAUSTED`; SQLSTATE: `HY000`

Message: Log filename extension number exhausted: %06lu. Please fix this by archiving old logs and updating the index files.

- Error number: `MY-010814`; Symbol: `ER_BINLOG_FILE_NAME_TOO_LONG`; SQLSTATE: `HY000`

Message: Log filename too large: %s%s (%zu). Please fix this by archiving old logs and updating the index files.

- Error number: `MY-010815`; Symbol: `ER_BINLOG_FILE_EXTENSION_NUMBER_RUNNING_LOW`; SQLSTATE: `HY000`

Message: Next log extension: %lu. Remaining log filename extensions: %lu. Please consider archiving some logs.

- Error number: `MY-010816`; Symbol: `ER_BINLOG_CANT_OPEN_FOR_LOGGING`; SQLSTATE: `HY000`

Message: Could not open %s for logging (error %d). Turning logging off for the whole duration of the MySQL server process. To turn it on again: fix the cause, shutdown the MySQL server and restart it.

- Error number: `MY-010817`; Symbol: `ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE`; SQLSTATE: `HY000`

Message: MYSQL_BIN_LOG::open_index_file failed to sync the index file.

- Error number: `MY-010818`; Symbol: `ER_BINLOG_ERROR_READING_GTIDS_FROM_RELAY_LOG`; SQLSTATE: `HY000`

Message: Error reading GTIDs from relaylog: %d

- Error number: `MY-010819`; Symbol: `ER_BINLOG_EVENTS_READ_FROM_APPLIER_METADATA`; SQLSTATE: `HY000`

Message: %lu events read in relaylog file '%s' for updating Retrieved_Gtid_Set and/or IO thread transaction parser state.

- Error number: `MY-010820`; Symbol: `ER_BINLOG_ERROR_READING_GTIDS_FROM_BINARY_LOG`; SQLSTATE: `HY000`

Message: Error reading GTIDs from binary log: %d

- Error number: `MY-010821`; Symbol: `ER_BINLOG_EVENTS_READ_FROM_BINLOG_INFO`; SQLSTATE: `HY000`

Message: Read %lu events from binary log file '%s' to determine the GTIDs purged from binary logs.

-
- Error number: `MY-010822`; Symbol: `ER_BINLOG_CANT_GENERATE_NEW_FILE_NAME`; SQLSTATE: `HY000`
Message: `MYSQL_BIN_LOG::open` failed to generate new file name.
 - Error number: `MY-010823`; Symbol: `ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE_IN_OPEN`; SQLSTATE: `HY000`
Message: `MYSQL_BIN_LOG::open` failed to sync the index file.
 - Error number: `MY-010824`; Symbol: `ER_BINLOG_CANT_USE_FOR_LOGGING`; SQLSTATE: `HY000`
Message: Could not use %s for logging (error %d). Turning logging off for the whole duration of the MySQL server process. To turn it on again: fix the cause, shutdown the MySQL server and restart it.
 - Error number: `MY-010825`; Symbol: `ER_BINLOG_FAILED_TO_CLOSE_INDEX_FILE_WHILE_REBUILDING`; SQLSTATE: `HY000`
Message: While rebuilding index file %s: Failed to close the index file.
 - Error number: `MY-010826`; Symbol: `ER_BINLOG_FAILED_TO_DELETE_INDEX_FILE_WHILE_REBUILDING`; SQLSTATE: `HY000`
Message: While rebuilding index file %s: Failed to delete the existing index file. It could be that file is being used by some other process.
 - Error number: `MY-010827`; Symbol: `ER_BINLOG_FAILED_TO_RENAME_INDEX_FILE_WHILE_REBUILDING`; SQLSTATE: `HY000`
Message: While rebuilding index file %s: Failed to rename the new index file to the existing index file.
 - Error number: `MY-010828`; Symbol: `ER_BINLOG_FAILED_TO_OPEN_INDEX_FILE_AFTER_REBUILDING`; SQLSTATE: `HY000`
Message: After rebuilding the index file %s: Failed to open the index file.
 - Error number: `MY-010829`; Symbol: `ER_BINLOG_CANT_APPEND_LOG_TO_TMP_INDEX`; SQLSTATE: `HY000`
Message: `MYSQL_BIN_LOG::add_log_to_index` failed to append log file name: %s, to crash safe index file.
 - Error number: `MY-010830`; Symbol: `ER_BINLOG_CANT_LOCATE_OLD_BINLOG_OR_RELAY_LOG_FILES`; SQLSTATE: `HY000`
Message: Failed to locate old binlog or relay log files
 - Error number: `MY-010831`; Symbol: `ER_BINLOG_CANT_DELETE_FILE`; SQLSTATE: `HY000`
Message: Failed to delete file '%s'
 - Error number: `MY-010832`; Symbol: `ER_BINLOG_CANT_SET_TMP_INDEX_NAME`; SQLSTATE: `HY000`
Message: `MYSQL_BIN_LOG::set_crash_safe_index_file_name` failed to set file name.
 - Error number: `MY-010833`; Symbol: `ER_BINLOG_FAILED_TO_OPEN_TEMPORARY_INDEX_FILE`; SQLSTATE: `HY000`
Message: `MYSQL_BIN_LOG::open_crash_safe_index_file` failed to open temporary index file.
-

-
- Error number: `MY-010835`; Symbol: `ER_BINLOG_CANT_OPEN_TMP_INDEX`; SQLSTATE: `HY000`
Message: %s failed to open the crash safe index file.
 - Error number: `MY-010836`; Symbol: `ER_BINLOG_CANT_COPY_INDEX_TO_TMP`; SQLSTATE: `HY000`
Message: %s failed to copy index file to crash safe index file.
 - Error number: `MY-010837`; Symbol: `ER_BINLOG_CANT_CLOSE_TMP_INDEX`; SQLSTATE: `HY000`
Message: %s failed to close the crash safe index file.
 - Error number: `MY-010838`; Symbol: `ER_BINLOG_CANT_MOVE_TMP_TO_INDEX`; SQLSTATE: `HY000`
Message: %s failed to move crash safe index file to index file.
 - Error number: `MY-010839`; Symbol: `ER_BINLOG_PURGE_LOGS_CALLED_WITH_FILE_NOT_IN_INDEX`; SQLSTATE: `HY000`
Message: `MYSQL_BIN_LOG::purge_logs` was called with file %s not listed in the index.
 - Error number: `MY-010840`; Symbol: `ER_BINLOG_PURGE_LOGS_CANT_SYNC_INDEX_FILE`; SQLSTATE: `HY000`
Message: `MYSQL_BIN_LOG::purge_logs` failed to sync the index file.
 - Error number: `MY-010841`; Symbol: `ER_BINLOG_PURGE_LOGS_CANT_COPY_TO_REGISTER_FILE`; SQLSTATE: `HY000`
Message: `MYSQL_BIN_LOG::purge_logs` failed to copy %s to register file.
 - Error number: `MY-010842`; Symbol: `ER_BINLOG_PURGE_LOGS_CANT_FLUSH_REGISTER_FILE`; SQLSTATE: `HY000`
Message: `MYSQL_BIN_LOG::purge_logs` failed to flush register file.
 - Error number: `MY-010843`; Symbol: `ER_BINLOG_PURGE_LOGS_CANT_UPDATE_INDEX_FILE`; SQLSTATE: `HY000`
Message: `MYSQL_BIN_LOG::purge_logs` failed to update the index file
 - Error number: `MY-010844`; Symbol: `ER_BINLOG_PURGE_LOGS_FAILED_TO_PURGE_LOG`; SQLSTATE: `HY000`
Message: `MYSQL_BIN_LOG::purge_logs` failed to process registered files that would be purged.
 - Error number: `MY-010845`; Symbol: `ER_BINLOG_FAILED_TO_SET_PURGE_INDEX_FILE_NAME`; SQLSTATE: `HY000`
Message: `MYSQL_BIN_LOG::set_purge_index_file_name` failed to set file name.
 - Error number: `MY-010846`; Symbol: `ER_BINLOG_FAILED_TO_OPEN_REGISTER_FILE`; SQLSTATE: `HY000`
Message: `MYSQL_BIN_LOG::open_purge_index_file` failed to open register file.
 - Error number: `MY-010847`; Symbol: `ER_BINLOG_FAILED_TO_REINIT_REGISTER_FILE`; SQLSTATE: `HY000`
Message: `MYSQL_BIN_LOG::purge_index_entry` failed to reinit register file for read

-
- Error number: `MY-010848`; Symbol: `ER_BINLOG_FAILED_TO_READ_REGISTER_FILE`; SQLSTATE: `HY000`
Message: `MYSQL_BIN_LOG::purge_index_entry` error %d reading from register file.
 - Error number: `MY-010849`; Symbol: `ER_CANT_STAT_FILE`; SQLSTATE: `HY000`
Message: Failed to execute `mysql_file_stat` on file '%s'
 - Error number: `MY-010850`; Symbol: `ER_BINLOG_CANT_DELETE_LOG_FILE_DOES_INDEX_MATCH_FILES`; SQLSTATE: `HY000`
Message: Failed to delete log file '%s'; consider examining correspondence of your binlog index file to the actual binlog files
 - Error number: `MY-010851`; Symbol: `ER_BINLOG_CANT_DELETE_FILE_AND_READ_BINLOG_INDEX`; SQLSTATE: `HY000`
Message: Failed to delete file '%s' and read the binlog index file
 - Error number: `MY-010852`; Symbol: `ER_BINLOG_FAILED_TO_DELETE_LOG_FILE`; SQLSTATE: `HY000`
Message: Failed to delete log file '%s'
 - Error number: `MY-010853`; Symbol: `ER_BINLOG_LOGGING_INCIDENT_TO_STOP_REPLICAS`; SQLSTATE: `HY000`
Message: %s An incident event has been written to the binary log which will stop the replicas.
 - Error number: `MY-010854`; Symbol: `ER_BINLOG_CANT_FIND_LOG_IN_INDEX`; SQLSTATE: `HY000`
Message: `find_log_pos()` failed (error: %d)
 - Error number: `MY-010855`; Symbol: `ER_BINLOG_RECOVERING_AFTER_CRASH_USING`; SQLSTATE: `HY000`
Message: Recovering after a crash using %s
 - Error number: `MY-010856`; Symbol: `ER_BINLOG_CANT_OPEN_CRASHED_BINLOG`; SQLSTATE: `HY000`
Message: Failed to open the crashed binlog file when source server is recovering it.
 - Error number: `MY-010857`; Symbol: `ER_BINLOG_CANT_TRIM_CRASHED_BINLOG`; SQLSTATE: `HY000`
Message: Failed to trim the crashed binlog file when source server is recovering it.
 - Error number: `MY-010858`; Symbol: `ER_BINLOG_CRASHED_BINLOG_TRIMMED`; SQLSTATE: `HY000`
Message: Crashed binlog file %s size is %llu, but recovered up to %llu. Binlog trimmed to %llu bytes.
 - Error number: `MY-010859`; Symbol: `ER_BINLOG_CANT_CLEAR_IN_USE_FLAG_FOR_CRASHED_BINLOG`; SQLSTATE: `HY000`
Message: Failed to clear `LOG_EVENT_BINLOG_IN_USE_F` for the crashed binlog file when source server is recovering it.
 - Error number: `MY-010860`; Symbol: `ER_BINLOG_FAILED_TO_RUN_AFTER_SYNC_HOOK`; SQLSTATE: `HY000`
-

Message: Failed to run 'after_sync' hooks

- Error number: `MY-010861`; Symbol: `ER_TURNING_LOGGING_OFF_FOR_THE_DURATION`; SQLSTATE: `HY000`

Message: %s Hence turning logging off for the whole duration of the MySQL server process. To turn it on again: fix the cause, shutdown the MySQL server and restart it.

- Error number: `MY-010862`; Symbol: `ER_BINLOG_FAILED_TO_RUN_AFTER_FLUSH_HOOK`; SQLSTATE: `HY000`

Message: Failed to run 'after_flush' hooks

- Error number: `MY-010864`; Symbol: `ER_BINLOG_WARNING_SUPPRESSED`; SQLSTATE: `HY000`

Message: The following warning was suppressed %d times during the last %d seconds in the error log

- Error number: `MY-010865`; Symbol: `ER_NDB_LOG_ENTRY`; SQLSTATE: `HY000`

Message: NDB: %s

- Error number: `MY-010866`; Symbol: `ER_NDB_LOG_ENTRY_WITH_PREFIX`; SQLSTATE: `HY000`

Message: NDB %s: %s

- Error number: `MY-010868`; Symbol: `ER_INNODB_UNKNOWN_COLLATION`; SQLSTATE: `HY000`

Message: Unknown collation #%lu.

- Error number: `MY-010869`; Symbol: `ER_INNODB_INVALID_LOG_GROUP_HOME_DIR`; SQLSTATE: `HY000`

Message: syntax error in innodb_log_group_home_dir

- Error number: `MY-010870`; Symbol: `ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY`; SQLSTATE: `HY000`

Message: syntax error in innodb_undo_directory

- Error number: `MY-010871`; Symbol: `ER_INNODB_ILLEGAL_COLON_IN_POOL`; SQLSTATE: `HY000`

Message: InnoDB: innodb_buffer_pool_filename cannot have colon (:) in the file name.

- Error number: `MY-010872`; Symbol: `ER_INNODB_INVALID_PAGE_SIZE`; SQLSTATE: `HY000`

Message: InnoDB: Invalid page size=%lu.

- Error number: `MY-010873`; Symbol: `ER_INNODB_DIRTY_WATER_MARK_NOT_LOW`; SQLSTATE: `HY000`

Message: InnoDB: innodb_max_dirty_pages_pct_lwm cannot be set higher than innodb_max_dirty_pages_pct. Setting innodb_max_dirty_pages_pct_lwm to %lf

- Error number: `MY-010874`; Symbol: `ER_INNODB_IO_CAPACITY_EXCEEDS_MAX`; SQLSTATE: `HY000`

Message: InnoDB: innodb_io_capacity cannot be set higher than innodb_io_capacity_max. Setting innodb_io_capacity to %lu

- Error number: `MY-010875`; Symbol: `ER_INNODB_FILES_SAME`; SQLSTATE: `HY000`

Message: %s and %s file names seem to be the same.

- Error number: [MY-010876](#); Symbol: [ER_INNODB_UNREGISTERED_TRX_ACTIVE](#); SQLSTATE: [HY000](#)

Message: Transaction not registered for MySQL 2PC, but transaction is active

- Error number: [MY-010877](#); Symbol: [ER_INNODB_CLOSING_CONNECTION_ROLLS_BACK](#); SQLSTATE: [HY000](#)

Message: MySQL is closing a connection that has an active InnoDB transaction. %llu row modifications will roll back.

- Error number: [MY-010878](#); Symbol: [ER_INNODB_TRX_XLATION_TABLE_OOM](#); SQLSTATE: [HY000](#)

Message: InnoDB: fail to allocate memory for index translation table. Number of Index:%lu, array size: %lu

- Error number: [MY-010879](#); Symbol: [ER_INNODB_CANT_FIND_INDEX_IN_INNODB_DD](#); SQLSTATE: [HY000](#)

Message: Cannot find index %s in InnoDB index dictionary.

- Error number: [MY-010880](#); Symbol: [ER_INNODB_INDEX_COLUMN_INFO_UNLIKE_MYSQLS](#); SQLSTATE: [HY000](#)

Message: Found index %s whose column info does not match that of MySQL.

- Error number: [MY-010882](#); Symbol: [ER_INNODB_CANT_BUILD_INDEX_XLATION_TABLE_FOR](#); SQLSTATE: [HY000](#)

Message: Build InnoDB index translation table for Table %s failed

- Error number: [MY-010883](#); Symbol: [ER_INNODB_PK_NOT_IN_MYSQL](#); SQLSTATE: [HY000](#)

Message: Table %s has a primary key in InnoDB data dictionary, but not in MySQL!

- Error number: [MY-010884](#); Symbol: [ER_INNODB_PK_ONLY_IN_MYSQL](#); SQLSTATE: [HY000](#)

Message: Table %s has no primary key in InnoDB data dictionary, but has one in MySQL! If you created the table with a MySQL version < 3.23.54 and did not define a primary key, but defined a unique key with all non-NULL columns, then MySQL internally treats that key as the primary key. You can fix this error by dump + DROP + CREATE + reimport of the table.

- Error number: [MY-010885](#); Symbol: [ER_INNODB_CLUSTERED_INDEX_PRIVATE](#); SQLSTATE: [HY000](#)

Message: Table %s key_used_on_scan is %lu even though there is no primary key inside InnoDB.

- Error number: [MY-010887](#); Symbol: [ER_ERRMSG_REPLACEMENT_DODGY](#); SQLSTATE: [HY000](#)

Message: Cannot replace error message (%s,%s,%s) "%s" with "%s"; wrong number or type of %% substitutions.

- Error number: [MY-010888](#); Symbol: [ER_ERRMSG_REPLACEMENTS_FAILED](#); SQLSTATE: [HY000](#)

Message: Table for error message replacements could not be found or read, or one or more replacements could not be applied.

- Error number: [MY-010889](#); Symbol: [ER_NPIPE_CANT_CREATE](#); SQLSTATE: [HY000](#)

Message: %s: %s

- Error number: [MY-010890](#); Symbol:

[ER_PARTITION_MOVE_CREATED_DUPLICATE_ROW_PLEASE_FIX](#); SQLSTATE: [HY000](#)

Message: Table '%s': Delete from part %d failed with error %d. But it was already inserted into part %d, when moving the misplaced row! Please manually fix the duplicate row: %s

- Error number: [MY-010891](#); Symbol: [ER_AUDIT_CANT_ABORT_COMMAND](#); SQLSTATE: [HY000](#)

Message: Command '%s' cannot be aborted. The trigger error was (%d) [%s]: %s

- Error number: [MY-010892](#); Symbol: [ER_AUDIT_CANT_ABORT_EVENT](#); SQLSTATE: [HY000](#)

Message: Event '%s' cannot be aborted. The trigger error was (%d) [%s]: %s

- Error number: [MY-010893](#); Symbol: [ER_AUDIT_WARNING](#); SQLSTATE: [HY000](#)

Message: %s. The trigger error was (%d) [%s]: %s

- Error number: [MY-010897](#); Symbol: [ER_RPL_REPLICA_INSECURE_CHANGE_SOURCE](#); SQLSTATE: [HY000](#)

Message: Storing MySQL user name or password information in the connection metadata repository is not secure and is therefore not recommended. Please consider using the USER and PASSWORD connection options for START REPLICA; see the 'START REPLICA Syntax' in the MySQL Manual for more information.

- Error number: [MY-010899](#); Symbol: [ER_RPL_REPLICA_INCORRECT_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Replica channel '%s' does not exist.

- Error number: [MY-010900](#); Symbol: [ER_FAILED_TO_FIND_DL_ENTRY](#); SQLSTATE: [HY000](#)

Message: Can't find symbol '%s' in library.

- Error number: [MY-010901](#); Symbol: [ER_FAILED_TO_OPEN_SHARED_LIBRARY](#); SQLSTATE: [HY000](#)

Message: Can't open shared library '%s' (errno: %d %s).

- Error number: [MY-010902](#); Symbol: [ER_THREAD_PRIORITY_IGNORED](#); SQLSTATE: [HY000](#)

Message: Thread priority attribute setting in Resource Group SQL shall be ignored due to unsupported platform or insufficient privilege.

- Error number: [MY-010903](#); Symbol: [ER_BINLOG_CACHE_SIZE_TOO_LARGE](#); SQLSTATE: [HY000](#)

Message: Option binlog_cache_size (%lu) is greater than max_binlog_cache_size (%lu); setting binlog_cache_size equal to max_binlog_cache_size.

- Error number: [MY-010904](#); Symbol: [ER_BINLOG_STMT_CACHE_SIZE_TOO_LARGE](#); SQLSTATE: [HY000](#)

Message: Option binlog_stmt_cache_size (%lu) is greater than max_binlog_stmt_cache_size (%lu); setting binlog_stmt_cache_size equal to max_binlog_stmt_cache_size.

- Error number: [MY-010905](#); Symbol: [ER_FAILED_TO_GENERATE_UNIQUE_LOGFILE](#); SQLSTATE: [HY000](#)

Message: Can't generate a unique log-filename %s.(1-999).

- Error number: [MY-010906](#); Symbol: [ER_FAILED_TO_READ_FILE](#); SQLSTATE: [HY000](#)

Message: Error reading file '%s' (errno: %d - %s)

- Error number: [MY-010907](#); Symbol: [ER_FAILED_TO_WRITE_TO_FILE](#); SQLSTATE: [HY000](#)

Message: Error writing file '%s' (errno: %d - %s)

- Error number: [MY-010908](#); Symbol: [ER_BINLOG_UNSAFE_MESSAGE_AND_STATEMENT](#); SQLSTATE: [HY000](#)

Message: %s Statement: %s

- Error number: [MY-010909](#); Symbol: [ER_FORCE_CLOSE_THREAD](#); SQLSTATE: [HY000](#)

Message: %s: Forcing close of thread %ld user: '%s'.

- Error number: [MY-010910](#); Symbol: [ER_SERVER_SHUTDOWN_COMPLETE](#); SQLSTATE: [HY000](#)

Message: %s: Shutdown complete (mysqld %s) %s.

- Error number: [MY-010911](#); Symbol: [ER_RPL_CANT_HAVE_SAME_BASENAME](#); SQLSTATE: [HY000](#)

Message: Cannot have same base name '%s' for both binary and relay logs. Please check %s (default '%s' if --log-bin option is not used, default '%s' if --log-bin option is used without argument) and %s (default '%s') options to ensure they do not conflict.

- Error number: [MY-010912](#); Symbol: [ER_RPL_GTID_MODE_REQUIRES_ENFORCE_GTID_CONSISTENCY_ON](#); SQLSTATE: [HY000](#)

Message: GTID_MODE = ON requires ENFORCE_GTID_CONSISTENCY = ON.

- Error number: [MY-010913](#); Symbol: [ER_WARN_NO_SERVERID_SPECIFIED](#); SQLSTATE: [HY000](#)

Message: You have not provided a mandatory server-id. Servers in a replication topology must have unique server-ids. Please refer to the proper server start-up parameters documentation.

- Error number: [MY-010914](#); Symbol: [ER_ABORTING_USER_CONNECTION](#); SQLSTATE: [HY000](#)

Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s).

- Error number: [MY-010915](#); Symbol: [ER_SQL_MODE_MERGED_WITH_STRICT_MODE](#); SQLSTATE: [HY000](#)

Message: 'NO_ZERO_DATE', 'NO_ZERO_IN_DATE' and 'ERROR_FOR_DIVISION_BY_ZERO' sql modes should be used with strict mode. They will be merged with strict mode in a future release.

- Error number: [MY-010916](#); Symbol: [ER_GTID_PURGED_WAS_UPDATED](#); SQLSTATE: [HY000](#)

Message: @@GLOBAL.GTID_PURGED was changed from '%s' to '%s'.

- Error number: [MY-010917](#); Symbol: [ER_GTID_EXECUTED_WAS_UPDATED](#); SQLSTATE: [HY000](#)

Message: @@GLOBAL.GTID_EXECUTED was changed from '%s' to '%s'.

- Error number: [MY-010918](#); Symbol: [ER_DEPRECATED_MSG_WITH_REPLACEMENT](#); SQLSTATE: [HY000](#)

Message: '%s' is deprecated and will be removed in a future release. Please use %s instead.

- Error number: [MY-010919](#); Symbol: [ER_TRG_CREATION_CTX_NOT_SET](#); SQLSTATE: [HY000](#)

Message: Triggers for table ` %s `.` %s ` have no creation context

- Error number: [MY-010920](#); Symbol: [ER_FILE_HAS_OLD_FORMAT](#); SQLSTATE: [HY000](#)

Message: '%s' has an old format, you should re-create the '%s' object(s)

- Error number: [MY-010921](#); Symbol: [ER_VIEW_CREATION_CTX_NOT_SET](#); SQLSTATE: [HY000](#)

Message: View ` %s `.` %s ` has no creation context

- Error number: [MY-010923](#); Symbol: [ER_TABLE_UPGRADE_REQUIRED](#); SQLSTATE: [HY000](#)

Message: Table upgrade required. Please do "REPAIR TABLE ` %s `" or dump/reload to fix it!

- Error number: [MY-010924](#); Symbol: [ER_GET_ERRNO_FROM_STORAGE_ENGINE](#); SQLSTATE: [HY000](#)

Message: Got error %d - '%s' from storage engine.

- Error number: [MY-010925](#); Symbol: [ER_ACCESS_DENIED_ERROR_WITHOUT_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Access denied for user '%s'@'%s'

- Error number: [MY-010926](#); Symbol: [ER_ACCESS_DENIED_ERROR_WITH_PASSWORD](#); SQLSTATE: [HY000](#)

Message: Access denied for user '%s'@'%s' (using password: %s)

- Error number: [MY-010927](#); Symbol: [ER_ACCESS_DENIED_FOR_USER_ACCOUNT_LOCKED](#); SQLSTATE: [HY000](#)

Message: Access denied for user '%s'@'%s'. Account is locked.

- Error number: [MY-010929](#); Symbol: [ER_SYSTEM_TABLES_NOT_SUPPORTED_BY_STORAGE_ENGINE](#); SQLSTATE: [HY000](#)

Message: Storage engine '%s' does not support system tables. [%s.%s].

- Error number: [MY-010931](#); Symbol: [ER_SERVER_STARTUP_MSG](#); SQLSTATE: [HY000](#)

Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d %s.

- Error number: [MY-010932](#); Symbol: [ER_FAILED_TO_FIND_LOCALE_NAME](#); SQLSTATE: [HY000](#)

Message: Unknown locale: '%s'.

- Error number: [MY-010933](#); Symbol: [ER_FAILED_TO_FIND_COLLATION_NAME](#); SQLSTATE: [HY000](#)

Message: Unknown collation: '%s'.

- Error number: [MY-010934](#); Symbol: [ER_SERVER_OUT_OF_RESOURCES](#); SQLSTATE: [HY000](#)

Message: Out of memory; check if mysqld or some other process uses all available memory; if not, you may have to use 'ulimit' to allow mysqld to use more memory or you can add more swap space

-
- Error number: [MY-010935](#); Symbol: [ER_SERVER_OUTOFMEMORY](#); SQLSTATE: [HY000](#)
Message: Out of memory; restart server and try again (needed %d bytes)
 - Error number: [MY-010936](#); Symbol: [ER_INVALID_COLLATION_FOR_CHARSET](#); SQLSTATE: [HY000](#)
Message: COLLATION '%s' is not valid for CHARACTER SET '%s'
 - Error number: [MY-010937](#); Symbol: [ER_CANT_START_ERROR_LOG_SERVICE](#); SQLSTATE: [HY000](#)
Message: Failed to set %s at or around "%s" -- service is valid, but can not be initialized; please check its configuration and make sure it can read its input(s) and write to its output(s).
 - Error number: [MY-010938](#); Symbol: [ER_CREATING_NEW_UUID_FIRST_START](#); SQLSTATE: [HY000](#)
Message: Generating a new UUID: %s.
 - Error number: [MY-010939](#); Symbol: [ER_FAILED_TO_GET_ABSOLUTE_PATH](#); SQLSTATE: [HY000](#)
Message: Failed to get absolute path of program executable %s
 - Error number: [MY-010940](#); Symbol: [ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP](#); SQLSTATE: [HY000](#)
Message: Failed to bootstrap performance schema components infrastructure.
 - Error number: [MY-010941](#); Symbol: [ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_SHUTDOWN](#); SQLSTATE: [HY000](#)
Message: Failed to deinit performance schema components infrastructure.
 - Error number: [MY-010942](#); Symbol: [ER_DUP_FD_OPEN_FAILED](#); SQLSTATE: [HY000](#)
Message: Could not open duplicate fd for %s: %s.
 - Error number: [MY-010943](#); Symbol: [ER_SYSTEM_VIEW_INIT_FAILED](#); SQLSTATE: [HY000](#)
Message: System views initialization failed.
 - Error number: [MY-010944](#); Symbol: [ER_RESOURCE_GROUP_POST_INIT_FAILED](#); SQLSTATE: [HY000](#)
Message: Resource group post initialization failed.
 - Error number: [MY-010945](#); Symbol: [ER_RESOURCE_GROUP_SUBSYSTEM_INIT_FAILED](#); SQLSTATE: [HY000](#)
Message: Resource Group subsystem initialization failed.
 - Error number: [MY-010946](#); Symbol: [ER_FAILED_START_MYSQLD_DAEMON](#); SQLSTATE: [HY000](#)
Message: Failed to start mysqld daemon. Check mysqld error log.
 - Error number: [MY-010947](#); Symbol: [ER_CANNOT_CHANGE_TO_ROOT_DIR](#); SQLSTATE: [HY000](#)
Message: Cannot change to root directory: %s.
 - Error number: [MY-010948](#); Symbol: [ER_PERSISTENT_PRIVILEGES_BOOTSTRAP](#); SQLSTATE: [HY000](#)
Message: Failed to bootstrap persistent privileges.

-
- Error number: [MY-010949](#); Symbol: [ER_BASEDIR_SET_TO](#); SQLSTATE: [HY000](#)
Message: Basedir set to %s.
 - Error number: [MY-010950](#); Symbol: [ER_RPL_FILTER_ADD_WILD_DO_TABLE_FAILED](#); SQLSTATE: [HY000](#)
Message: Could not add wild do table rule '%s'!
 - Error number: [MY-010951](#); Symbol: [ER_RPL_FILTER_ADD_WILD_IGNORE_TABLE_FAILED](#); SQLSTATE: [HY000](#)
Message: Could not add wild ignore table rule '%s'!
 - Error number: [MY-010952](#); Symbol: [ER_PRIVILEGE_SYSTEM_INIT_FAILED](#); SQLSTATE: [HY000](#)
Message: The privilege system failed to initialize correctly. For complete instructions on how to upgrade MySQL to a new version please see the 'Upgrading MySQL' section from the MySQL manual.
 - Error number: [MY-010953](#); Symbol: [ER_CANNOT_SET_LOG_ERROR_SERVICES](#); SQLSTATE: [HY000](#)
Message: Cannot set services "%s" requested in --log-error-services, using defaults.
 - Error number: [MY-010954](#); Symbol: [ER_PERFSHEMA_TABLES_INIT_FAILED](#); SQLSTATE: [HY000](#)
Message: Performance schema tables initialization failed.
 - Error number: [MY-010958](#); Symbol: [ER_BINLOG_FILE_OPEN_FAILED](#); SQLSTATE: [HY000](#)
Message: %s.
 - Error number: [MY-010959](#); Symbol: [ER_BINLOG_EVENT_WRITE_TO_STMT_CACHE_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to write an incident event into stmt_cache.
 - Error number: [MY-010960](#); Symbol: [ER_REPLICA_RELAY_LOG_TRUNCATE_INFO](#); SQLSTATE: [HY000](#)
Message: Relaylog file %s size was %llu, but was truncated at %llu.
 - Error number: [MY-010961](#); Symbol: [ER_REPLICA_RELAY_LOG_PURGE_FAILED](#); SQLSTATE: [HY000](#)
Message: Unable to purge relay log files. %s:%s.
 - Error number: [MY-010962](#); Symbol: [ER_RPL_REPLICA_FILTER_CREATE_FAILED](#); SQLSTATE: [HY000](#)
Message: Replica: failed in creating filter for channel '%s'.
 - Error number: [MY-010963](#); Symbol: [ER_RPL_REPLICA_GLOBAL_FILTERS_COPY_FAILED](#); SQLSTATE: [HY000](#)
Message: Replica: failed in copying the global filters to its own per-channel filters on configuration for channel '%s'.
 - Error number: [MY-010964](#); Symbol: [ER_RPL_REPLICA_RESET_FILTER_OPTIONS](#); SQLSTATE: [HY000](#)
Message: There are per-channel replication filter(s) configured for channel '%s' which does not exist. The filter(s) have been discarded.

-
- Error number: [MY-010965](#); Symbol: [ER_MISSING_GRANT_SYSTEM_TABLE](#); SQLSTATE: [HY000](#)
Message: The system table mysql.global_grants is missing. Please perform the MySQL upgrade procedure.
 - Error number: [MY-010966](#); Symbol: [ER_MISSING_ACL_SYSTEM_TABLE](#); SQLSTATE: [HY000](#)
Message: ACL table mysql.%.*s missing. Some operations may fail.
 - Error number: [MY-010967](#); Symbol: [ER_ANONYMOUS_AUTH_ID_NOT_ALLOWED_IN_MANDATORY_ROLES](#); SQLSTATE: [HY000](#)
Message: Can't set mandatory_role %s@%s: Anonymous authorization IDs are not allowed as roles.
 - Error number: [MY-010968](#); Symbol: [ER_UNKNOWN_AUTH_ID_IN_MANDATORY_ROLE](#); SQLSTATE: [HY000](#)
Message: Can't set mandatory_role: There's no such authorization ID %s@%s.
 - Error number: [MY-010969](#); Symbol: [ER_WRITE_ROW_TO_PARTITION_FAILED](#); SQLSTATE: [HY000](#)
Message: Table '%s' failed to move/insert a row from part %d into part %d: %s.
 - Error number: [MY-010970](#); Symbol: [ER_RESOURCE_GROUP_METADATA_UPDATE_SKIPPED](#); SQLSTATE: [HY000](#)
Message: Skipped updating resource group metadata in InnoDB read only mode.
 - Error number: [MY-010971](#); Symbol: [ER_FAILED_TO_PERSIST_RESOURCE_GROUP_METADATA](#); SQLSTATE: [HY000](#)
Message: Failed to persist resource group %s to Data Dictionary.
 - Error number: [MY-010972](#); Symbol: [ER_FAILED_TO_DESERIALIZE_RESOURCE_GROUP](#); SQLSTATE: [HY000](#)
Message: Failed to deserialize resource group %s.
 - Error number: [MY-010973](#); Symbol: [ER_FAILED_TO_UPDATE_RESOURCE_GROUP](#); SQLSTATE: [HY000](#)
Message: Update of resource group %s failed.
 - Error number: [MY-010974](#); Symbol: [ER_RESOURCE_GROUP_VALIDATION_FAILED](#); SQLSTATE: [HY000](#)
Message: Validation of resource group %s failed. Resource group is disabled.
 - Error number: [MY-010975](#); Symbol: [ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP](#); SQLSTATE: [HY000](#)
Message: Unable to allocate memory for Resource Group %s.
 - Error number: [MY-010976](#); Symbol: [ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP_HASH](#); SQLSTATE: [HY000](#)
Message: Failed to allocate memory for resource group hash.
 - Error number: [MY-010977](#); Symbol: [ER_FAILED_TO_ADD_RESOURCE_GROUP_TO_MAP](#); SQLSTATE: [HY000](#)

Message: Failed to add resource group %s to resource group map.

- Error number: `MY-010978`; Symbol: `ER_RESOURCE_GROUP_IS_DISABLED`; SQLSTATE: `HY000`

Message: Resource group feature is disabled. (Server is compiled with `DISABLE_PSI_THREAD`).

- Error number: `MY-010979`; Symbol: `ER_FAILED_TO_APPLY_RESOURCE_GROUP_CONTROLLER`; SQLSTATE: `HY000`

Message: Unable to apply resource group controller %s.

- Error number: `MY-010980`; Symbol: `ER_FAILED_TO_ACQUIRE_LOCK_ON_RESOURCE_GROUP`; SQLSTATE: `HY000`

Message: Unable to acquire lock on the resource group %s. Hint to switch resource group shall be ignored.

- Error number: `MY-010981`; Symbol: `ER_PFS_NOTIFICATION_FUNCTION_REGISTER_FAILED`; SQLSTATE: `HY000`

Message: PFS %s notification function registration failed.

- Error number: `MY-010982`; Symbol: `ER_RES_GRP_SET_THR_AFFINITY_FAILED`; SQLSTATE: `HY000`

Message: Unable to bind thread id %llu to cpu id %u (error code %d - %s).

- Error number: `MY-010983`; Symbol: `ER_RES_GRP_SET_THR_AFFINITY_TO_CPUS_FAILED`; SQLSTATE: `HY000`

Message: Unable to bind thread id %llu to cpu ids (error code %d - %s).

- Error number: `MY-010984`; Symbol: `ER_RES_GRP_THD_UNBIND_FROM_CPU_FAILED`; SQLSTATE: `HY000`

Message: Unbind thread id %llu failed. (error code %d - %s).

- Error number: `MY-010985`; Symbol: `ER_RES_GRP_SET_THREAD_PRIORITY_FAILED`; SQLSTATE: `HY000`

Message: Setting thread priority %d to thread id %llu failed. (error code %d - %s).

- Error number: `MY-010986`; Symbol: `ER_RES_GRP_FAILED_TO_DETERMINE_NICE_CAPABILITY`; SQLSTATE: `HY000`

Message: Unable to determine `CAP_SYS_NICE` capability.

- Error number: `MY-010987`; Symbol: `ER_RES_GRP_FAILED_TO_GET_THREAD_HANDLE`; SQLSTATE: `HY000`

Message: %s failed: Failed to get handle for thread %llu.

- Error number: `MY-010988`; Symbol: `ER_RES_GRP_GET_THREAD_PRIO_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: Retrieval of thread priority unsupported on %s.

- Error number: `MY-010989`; Symbol: `ER_RES_GRP_FAILED_DETERMINE_CPU_COUNT`; SQLSTATE: `HY000`

Message: Unable to determine the number of CPUs.

- Error number: `MY-010990`; Symbol: `ER_RES_GRP_FEATURE_NOT_AVAILABLE`; SQLSTATE: `HY000`

Message: Resource group feature shall not be available. Incompatible thread handling option.

- Error number: `MY-010991`; Symbol: `ER_RES_GRP_INVALID_THREAD_PRIORITY`; SQLSTATE: `HY000`

Message: Invalid thread priority %d for a %s resource group. Allowed range is [%d, %d].

- Error number: `MY-010992`; Symbol: `ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_CPUID_FAILED`; SQLSTATE: `HY000`

Message: bind_to_cpu failed: processor_bind for cpuid %u failed (error code %d - %s).

- Error number: `MY-010993`; Symbol: `ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_THREAD_FAILED`; SQLSTATE: `HY000`

Message: bind_to_cpu failed: processor_bind for thread %l with cpu id %u (error code %d - %s).

- Error number: `MY-010994`; Symbol: `ER_RES_GRP_SOLARIS_PROCESSOR_AFFINITY_FAILED`; SQLSTATE: `HY000`

Message: %s failed: processor_affinity failed (error code %d - %s).

- Error number: `MY-010995`; Symbol: `ER_DD_UPGRADE_RENAME_IDX_STATS_FILE_FAILED`; SQLSTATE: `HY000`

Message: Error in renaming mysql_index_stats.ibd.

- Error number: `MY-010996`; Symbol: `ER_DD_UPGRADE_DD_OPEN_FAILED`; SQLSTATE: `HY000`

Message: Error in opening data directory %s.

- Error number: `MY-010997`; Symbol: `ER_DD_UPGRADE_FAILED_TO_FETCH_TABLESPACES`; SQLSTATE: `HY000`

Message: Error in fetching list of tablespaces.

- Error number: `MY-010998`; Symbol: `ER_DD_UPGRADE_FAILED_TO_ACQUIRE_TABLESPACE`; SQLSTATE: `HY000`

Message: Error in acquiring Tablespace for SDI insertion %s.

- Error number: `MY-010999`; Symbol: `ER_DD_UPGRADE_FAILED_TO_RESOLVE_TABLESPACE_ENGINE`; SQLSTATE: `HY000`

Message: Error in resolving Engine name for tablespace %s with engine %s.

- Error number: `MY-011000`; Symbol: `ER_FAILED_TO_CREATE_SDI_FOR_TABLESPACE`; SQLSTATE: `HY000`

Message: Error in creating SDI for %s tablespace.

- Error number: `MY-011001`; Symbol: `ER_FAILED_TO_STORE_SDI_FOR_TABLESPACE`; SQLSTATE: `HY000`

Message: Error in storing SDI for %s tablespace.

-
- Error number: `MY-011002`; Symbol: `ER_DD_UPGRADE_FAILED_TO_FETCH_TABLES`; SQLSTATE: `HY000`
Message: Error in fetching list of tables.
 - Error number: `MY-011003`; Symbol: `ER_DD_UPGRADE_DD_POPULATED`; SQLSTATE: `HY000`
Message: Finished populating Data Dictionary tables with data.
 - Error number: `MY-011004`; Symbol: `ER_DD_UPGRADE_INFO_FILE_OPEN_FAILED`; SQLSTATE: `HY000`
Message: Could not open the upgrade info file '%s' in the MySQL servers datadir, errno: %d.
 - Error number: `MY-011005`; Symbol: `ER_DD_UPGRADE_INFO_FILE_CLOSE_FAILED`; SQLSTATE: `HY000`
Message: Could not close the upgrade info file '%s' in the MySQL servers datadir, errno: %d.
 - Error number: `MY-011006`; Symbol: `ER_DD_UPGRADE_TABLESPACE_MIGRATION_FAILED`; SQLSTATE: `HY000`
Message: Got error %d from SE while migrating tablespaces.
 - Error number: `MY-011007`; Symbol: `ER_DD_UPGRADE_FAILED_TO_CREATE_TABLE_STATS`; SQLSTATE: `HY000`
Message: Error in creating TABLE statistics entry. Fix statistics data by using ANALYZE command.
 - Error number: `MY-011008`; Symbol: `ER_DD_UPGRADE_TABLE_STATS_MIGRATE_COMPLETED`; SQLSTATE: `HY000`
Message: Finished migrating TABLE statistics data.
 - Error number: `MY-011009`; Symbol: `ER_DD_UPGRADE_FAILED_TO_CREATE_INDEX_STATS`; SQLSTATE: `HY000`
Message: Error in creating Index statistics entry. Fix statistics data by using ANALYZE command.
 - Error number: `MY-011010`; Symbol: `ER_DD_UPGRADE_INDEX_STATS_MIGRATE_COMPLETED`; SQLSTATE: `HY000`
Message: Finished migrating INDEX statistics data.
 - Error number: `MY-011011`; Symbol: `ER_DD_UPGRADE_FAILED_FIND_VALID_DATA_DIR`; SQLSTATE: `HY000`
Message: Failed to find valid data directory.
 - Error number: `MY-011012`; Symbol: `ER_DD_UPGRADE_START`; SQLSTATE: `HY000`
Message: Starting upgrade of data directory.
 - Error number: `MY-011013`; Symbol: `ER_DD_UPGRADE_FAILED_INIT_DD_SE`; SQLSTATE: `HY000`
Message: Failed to initialize DD Storage Engine.
 - Error number: `MY-011014`; Symbol: `ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD_ABORT`; SQLSTATE: `HY000`

Message: Found partially upgraded DD. Aborting upgrade and deleting all DD tables. Start the upgrade process again.

- Error number: `MY-011015`; Symbol: `ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD_CONTINUE`; SQLSTATE: `HY000`

Message: Found partially upgraded DD. Upgrade will continue and start the server.

- Error number: `MY-011016`; Symbol: `ER_DD_UPGRADE_SE_LOGS_FAILED`; SQLSTATE: `HY000`

Message: Error in upgrading engine logs.

- Error number: `MY-011017`; Symbol: `ER_DD_UPGRADE_SDI_INFO_UPDATE_FAILED`; SQLSTATE: `HY000`

Message: Error in updating SDI information.

- Error number: `MY-011018`; Symbol: `ER_SKIP_UPDATING_METADATA_IN_SE_RO_MODE`; SQLSTATE: `HY000`

Message: Skip updating %s metadata in InnoDB read-only mode.

- Error number: `MY-011019`; Symbol: `ER_CREATED_SYSTEM_WITH_VERSION`; SQLSTATE: `HY000`

Message: Created system views with I_S version %d.

- Error number: `MY-011020`; Symbol: `ER_UNKNOWN_ERROR_DETECTED_IN_SE`; SQLSTATE: `HY000`

Message: Unknown error detected %d in handler.

- Error number: `MY-011021`; Symbol: `ER_READ_LOG_EVENT_FAILED`; SQLSTATE: `HY000`

Message: Error in Log_event::read_log_event(): '%s', data_len: %lu, event_type: %d.

- Error number: `MY-011022`; Symbol: `ER_ROW_DATA_TOO_BIG_TO_WRITE_IN_BINLOG`; SQLSTATE: `HY000`

Message: The row data is greater than 4GB, which is too big to write to the binary log.

- Error number: `MY-011023`; Symbol: `ER_FAILED_TO_CONSTRUCT_DROP_EVENT_QUERY`; SQLSTATE: `HY000`

Message: Unable to construct DROP EVENT SQL query string.

- Error number: `MY-011024`; Symbol: `ER_FAILED_TO_BINLOG_DROP_EVENT`; SQLSTATE: `HY000`

Message: Unable to binlog drop event %s.%s.

- Error number: `MY-011025`; Symbol: `ER_FAILED_TO_START_REPLICA_THREAD`; SQLSTATE: `HY000`

Message: Failed to start replica threads for channel '%s'.

- Error number: `MY-011026`; Symbol: `ER_RPL_IO_THREAD_KILLED`; SQLSTATE: `HY000`

Message: %s%s.

- Error number: `MY-011027`; Symbol: `ER_REPLICA_RECONNECT_FAILED`; SQLSTATE: `HY000`

Message: Failed registering on source, reconnecting to try again, log '%s' at position %s. %s.

-
- Error number: [MY-011028](#); Symbol: [ER_REPLICA_KILLED_AFTER_RECONNECT](#); SQLSTATE: [HY000](#)
Message: Replica I/O thread killed during or after reconnect.
 - Error number: [MY-011029](#); Symbol: [ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS](#); SQLSTATE: [HY000](#)
Message: Some of the channels are not created/initialized properly. Check for additional messages above. You will not be able to start replication on those channels until the issue is resolved and the server restarted.
 - Error number: [MY-011030](#); Symbol: [ER_FAILED_TO_ADD_RPL_FILTER](#); SQLSTATE: [HY000](#)
Message: Failed to add a replication filter into filter map for channel '%s'.
 - Error number: [MY-011031](#); Symbol: [ER_PER_CHANNEL_RPL_FILTER_CONF_FOR_GRP_RPL](#); SQLSTATE: [HY000](#)
Message: There are per-channel replication filter(s) configured for group replication channel '%s' which is disallowed. The filter(s) have been discarded.
 - Error number: [MY-011032](#); Symbol: [ER_RPL_FILTERS_NOT_ATTACHED_TO_CHANNEL](#); SQLSTATE: [HY000](#)
Message: There are per-channel replication filter(s) configured for channel '%s' which does not exist. The filter(s) have been discarded.
 - Error number: [MY-011033](#); Symbol: [ER_FAILED_TO_BUILD_DO_AND_IGNORE_TABLE_HASHES](#); SQLSTATE: [HY000](#)
Message: An error occurred while building do_table and ignore_table rules to hashes for per-channel filter.
 - Error number: [MY-011034](#); Symbol: [ER_CLONE_PLUGIN_NOT_LOADED_TRACE](#); SQLSTATE: [HY000](#)
Message: Clone plugin cannot be loaded.
 - Error number: [MY-011035](#); Symbol: [ER_CLONE_HANDLER_EXIST_TRACE](#); SQLSTATE: [HY000](#)
Message: Clone Handler exists.
 - Error number: [MY-011036](#); Symbol: [ER_CLONE_CREATE_HANDLER_FAIL_TRACE](#); SQLSTATE: [HY000](#)
Message: Could not create Clone Handler.
 - Error number: [MY-011037](#); Symbol: [ER_CYCLE_TIMER_IS_NOT_AVAILABLE](#); SQLSTATE: [HY000](#)
Message: The CYCLE timer is not available. WAIT events in the performance_schema will not be timed.
 - Error number: [MY-011038](#); Symbol: [ER_NANOSECOND_TIMER_IS_NOT_AVAILABLE](#); SQLSTATE: [HY000](#)
Message: The NANOSECOND timer is not available. IDLE/STAGE/STATEMENT/TRANSACTION events in the performance_schema will not be timed.

-
- Error number: [MY-011039](#); Symbol: [ER_MICROSECOND_TIMER_IS_NOT_AVAILABLE](#); SQLSTATE: [HY000](#)
Message: The MICROSECOND timer is not available. IDLE/STAGE/STATEMENT/TRANSACTION events in the performance_schema will not be timed.
 - Error number: [MY-011040](#); Symbol: [ER_PFS_MALLOC_ARRAY_OVERFLOW](#); SQLSTATE: [HY000](#)
Message: Failed to allocate memory for %zu chunks each of size %zu for buffer '%s' due to overflow.
 - Error number: [MY-011041](#); Symbol: [ER_PFS_MALLOC_ARRAY_OOM](#); SQLSTATE: [HY000](#)
Message: Failed to allocate %zu bytes for buffer '%s' due to out-of-memory.
 - Error number: [MY-011042](#); Symbol: [ER_INNOODB_FAILED_TO_FIND_IDX_WITH_KEY_NO](#); SQLSTATE: [HY000](#)
Message: InnoDB could not find index %s key no %u for table %s through its index translation table.
 - Error number: [MY-011043](#); Symbol: [ER_INNOODB_FAILED_TO_FIND_IDX](#); SQLSTATE: [HY000](#)
Message: Cannot find index %s in InnoDB index translation table.
 - Error number: [MY-011044](#); Symbol: [ER_INNOODB_FAILED_TO_FIND_IDX_FROM_DICT_CACHE](#); SQLSTATE: [HY000](#)
Message: InnoDB could not find key no %u with name %s from dict cache for table %s.
 - Error number: [MY-011045](#); Symbol: [ER_INNOODB_ACTIVE_INDEX_CHANGE_FAILED](#); SQLSTATE: [HY000](#)
Message: InnoDB: change_active_index(%u) failed.
 - Error number: [MY-011046](#); Symbol: [ER_INNOODB_DIFF_IN_REF_LEN](#); SQLSTATE: [HY000](#)
Message: Stored ref len is %lu, but table ref len is %lu.
 - Error number: [MY-011047](#); Symbol: [ER_WRONG_TYPE_FOR_COLUMN_PREFIX_IDX_FLD](#); SQLSTATE: [HY000](#)
Message: MySQL is trying to create a column prefix index field, on an inappropriate data type. Table name %s, column name %s.
 - Error number: [MY-011048](#); Symbol: [ER_INNOODB_CANNOT_CREATE_TABLE](#); SQLSTATE: [HY000](#)
Message: Cannot create table %s.
 - Error number: [MY-011049](#); Symbol: [ER_INNOODB_INTERNAL_INDEX](#); SQLSTATE: [HY000](#)
Message: Found index %s in InnoDB index list but not its MySQL index number. It could be an InnoDB internal index.
 - Error number: [MY-011050](#); Symbol: [ER_INNOODB_IDX_CNT_MORE_THAN_DEFINED_IN_MYSQL](#); SQLSTATE: [HY000](#)
Message: InnoDB: Table %s contains %lu indexes inside InnoDB, which is different from the number of indexes %u defined in MySQL.
 - Error number: [MY-011051](#); Symbol: [ER_INNOODB_IDX_CNT_FEWER_THAN_DEFINED_IN_MYSQL](#); SQLSTATE: [HY000](#)

Message: Table %s contains fewer indexes inside InnoDB than are defined in the MySQL. Have you mixed up with data dictionary from different installation?

- Error number: `MY-011052`; Symbol: `ER_INNODB_IDX_COLUMN_CNT_DIFF`; SQLSTATE: `HY000`

Message: Index %s of %s has %lu columns unique inside InnoDB, but MySQL is asking statistics for %lu columns. Have you mixed data dictionary from different installation?

- Error number: `MY-011053`; Symbol: `ER_INNODB_USE_MONITOR_GROUP_NAME`; SQLSTATE: `HY000`

Message: Monitor counter '%s' cannot be turned on/off individually. Please use its module name to turn on/off the counters in the module as a group.

- Error number: `MY-011054`; Symbol: `ER_INNODB_MONITOR_DEFAULT_VALUE_NOT_DEFINED`; SQLSTATE: `HY000`

Message: Default value is not defined for this set option. Please specify correct counter or module name.

- Error number: `MY-011055`; Symbol: `ER_INNODB_MONITOR_IS_ENABLED`; SQLSTATE: `HY000`

Message: InnoDB: Monitor %s is already enabled.

- Error number: `MY-011056`; Symbol: `ER_INNODB_INVALID_MONITOR_COUNTER_NAME`; SQLSTATE: `HY000`

Message: Invalid monitor counter : %s.

- Error number: `MY-011057`; Symbol: `ER_WIN_LOAD_LIBRARY_FAILED`; SQLSTATE: `HY000`

Message: LoadLibrary("%s") failed: GetLastError returns %lu.

- Error number: `MY-011058`; Symbol: `ER_PARTITION_HANDLER_ADMIN_MSG`; SQLSTATE: `HY000`

Message: %s.

- Error number: `MY-011059`; Symbol: `ER_RPL_AM_INIT_INFO_MSG`; SQLSTATE: `HY000`

Message: %s.

- Error number: `MY-011060`; Symbol: `ER_DD_UPGRADE_TABLE_INTACT_ERROR`; SQLSTATE: `HY000`

Message: %s.

- Error number: `MY-011061`; Symbol: `ER_SERVER_INIT_COMPILED_IN_COMMANDS`; SQLSTATE: `HY000`

Message: %s.

- Error number: `MY-011062`; Symbol: `ER_MYISAM_CHECK_METHOD_ERROR`; SQLSTATE: `HY000`

Message: %s.

- Error number: `MY-011063`; Symbol: `ER_MYISAM_CRASHED_ERROR`; SQLSTATE: `HY000`

Message: %s.

- Error number: `MY-011064`; Symbol: `ER_WAITPID_FAILED`; SQLSTATE: `HY000`

Message: Unable to wait for process %lld.

-
- Error number: [MY-011065](#); Symbol: [ER_FAILED_TO_FIND_MYSQLD_STATUS](#); SQLSTATE: [HY000](#)
Message: Unable to determine if daemon is running: %s (rc=%d).
 - Error number: [MY-011066](#); Symbol: [ER_INNODB_ERROR_LOGGER_MSG](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011067](#); Symbol: [ER_INNODB_ERROR_LOGGER_FATAL_MSG](#); SQLSTATE: [HY000](#)
Message: [FATAL] InnoDB: %s
 - Error number: [MY-011068](#); Symbol: [ER_DEPRECATED_SYNTAX_WITH_REPLACEMENT](#); SQLSTATE: [HY000](#)
Message: The syntax '%s' is deprecated and will be removed in a future release. Please use %s instead.
 - Error number: [MY-011069](#); Symbol: [ER_DEPRECATED_SYNTAX_NO_REPLACEMENT](#); SQLSTATE: [HY000](#)
Message: The syntax '%s' is deprecated and will be removed in a future release.
 - Error number: [MY-011070](#); Symbol: [ER_DEPRECATED_MSG_NO_REPLACEMENT](#); SQLSTATE: [HY000](#)
Message: '%s' is deprecated and will be removed in a future release.
 - Error number: [MY-011071](#); Symbol: [ER_LOG_PRINTF_MSG](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011072](#); Symbol: [ER_BINLOG_LOGGING_NOT_POSSIBLE](#); SQLSTATE: [HY000](#)
Message: Binary logging not possible. Message: %s.
 - Error number: [MY-011073](#); Symbol: [ER_FAILED_TO_SET_PERSISTED_OPTIONS](#); SQLSTATE: [HY000](#)
Message: Failed to set persisted options.
 - Error number: [MY-011074](#); Symbol: [ER_COMPONENTS_FAILED_TO_ACQUIRE_SERVICE_IMPLEMENTATION](#); SQLSTATE: [HY000](#)
Message: Cannot acquire specified service implementation: '%s'.
 - Error number: [MY-011075](#); Symbol: [ER_RES_GRP_INVALID_VCPU_RANGE](#); SQLSTATE: [HY000](#)
Message: Invalid VCPU range %u-%u.
 - Error number: [MY-011076](#); Symbol: [ER_RES_GRP_INVALID_VCPU_ID](#); SQLSTATE: [HY000](#)
Message: Invalid cpu id %u.
 - Error number: [MY-011077](#); Symbol: [ER_ERROR_DURING_FLUSH_LOG_COMMIT_PHASE](#); SQLSTATE: [HY000](#)
Message: Got error %d during FLUSH_LOGS.

-
- Error number: [MY-011078](#); Symbol: [ER_DROP_DATABASE_FAILED_RMDIR_MANUALLY](#); SQLSTATE: [HY000](#)
Message: Problem while dropping database. Can't remove database directory (%s). Please remove it manually.
 - Error number: [MY-011080](#); Symbol: [ER_BINLOG_MALFORMED_OR_OLD_RELAY_LOG](#); SQLSTATE: [HY000](#)
Message: malformed or very old relay log which does not have FormatDescriptor.
 - Error number: [MY-011081](#); Symbol: [ER_DD_UPGRADE_VIEW_COLUMN_NAME_TOO_LONG](#); SQLSTATE: [HY000](#)
Message: Upgrade of view '%s.%s' failed. Re-create the view with the explicit column name lesser than 64 characters.
 - Error number: [MY-011082](#); Symbol: [ER_TABLE_NEEDS_DUMP_UPGRADE](#); SQLSTATE: [HY000](#)
Message: Table upgrade required for `%s`.`%s`. Please dump/reload table to fix it!
 - Error number: [MY-011083](#); Symbol: [ER_DD_UPGRADE_FAILED_TO_UPDATE_VER_NO_IN_TABLESPACE](#); SQLSTATE: [HY000](#)
Message: Error in updating version number in %s tablespace.
 - Error number: [MY-011084](#); Symbol: [ER_KEYRING_MIGRATION_FAILED](#); SQLSTATE: [HY000](#)
Message: Keyring migration failed.
 - Error number: [MY-011085](#); Symbol: [ER_KEYRING_MIGRATION_SUCCESSFUL](#); SQLSTATE: [HY000](#)
Message: Keyring migration successful.
 - Error number: [MY-011086](#); Symbol: [ER_RESTART_RECEIVED_INFO](#); SQLSTATE: [HY000](#)
Message: Received RESTART from user %s. Restarting mysqld (Version: %s).
 - Error number: [MY-011087](#); Symbol: [ER_LCTN_CHANGED](#); SQLSTATE: [HY000](#)
Message: Different lower_case_table_names settings for server ('%u') and data dictionary ('%u').
 - Error number: [MY-011088](#); Symbol: [ER_DD_INITIALIZE](#); SQLSTATE: [HY000](#)
Message: Data dictionary initializing version '%u'.
 - Error number: [MY-011089](#); Symbol: [ER_DD_RESTART](#); SQLSTATE: [HY000](#)
Message: Data dictionary restarting version '%u'.
 - Error number: [MY-011090](#); Symbol: [ER_DD_UPGRADE](#); SQLSTATE: [HY000](#)
Message: Data dictionary upgrading from version '%u' to '%u'.
 - Error number: [MY-011091](#); Symbol: [ER_DD_UPGRADE_OFF](#); SQLSTATE: [HY000](#)
Message: Data dictionary upgrade prohibited by the command line option '--no_dd_upgrade'.
 - Error number: [MY-011092](#); Symbol: [ER_DD_UPGRADE_VERSION_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: Upgrading the data dictionary from dictionary version '%u' is not supported.

- Error number: `MY-011093`; Symbol: `ER_DD_UPGRADE_SCHEMA_UNAVAILABLE`; SQLSTATE: `HY000`

Message: Upgrading the data dictionary failed, temporary schema name '%s' not available.

- Error number: `MY-011094`; Symbol: `ER_DD_MINOR_DOWNGRADE`; SQLSTATE: `HY000`

Message: Data dictionary minor downgrade from version '%u' to '%u'.

- Error number: `MY-011095`; Symbol: `ER_DD_MINOR_DOWNGRADE_VERSION_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: Minor downgrade of the Data dictionary from dictionary version '%u' is not supported.

- Error number: `MY-011096`; Symbol: `ER_DD_NO_VERSION_FOUND`; SQLSTATE: `HY000`

Message: No data dictionary version number found.

- Error number: `MY-011097`; Symbol: `ER_THREAD_POOL_NOT_SUPPORTED_ON_PLATFORM`; SQLSTATE: `HY000`

Message: Thread pool not supported, requires a minimum of %s.

- Error number: `MY-011098`; Symbol: `ER_THREAD_POOL_SIZE_TOO_LOW`; SQLSTATE: `HY000`

Message: thread_pool_size=0 means thread pool disabled, Allowed range of thread_pool_size is %d-%d.

- Error number: `MY-011099`; Symbol: `ER_THREAD_POOL_SIZE_TOO_HIGH`; SQLSTATE: `HY000`

Message: thread_pool_size=%lu is too high, %d is maximum, thread pool is disabled. Allowed range of thread_pool_size is %d-%d.

- Error number: `MY-011100`; Symbol: `ER_THREAD_POOL_ALGORITHM_INVALID`; SQLSTATE: `HY000`

Message: thread_pool_algorithm can be set to 0 and 1, 0 indicates the default low concurrency algorithm, 1 means a high concurrency algorithm.

- Error number: `MY-011101`; Symbol: `ER_THREAD_POOL_INVALID_STALL_LIMIT`; SQLSTATE: `HY000`

Message: thread_pool_stall_limit can be %d at minimum and %d at maximum, smaller values would render the thread pool fairly useless and higher values could make it possible to have undetected deadlock issues in the MySQL Server.

- Error number: `MY-011102`; Symbol: `ER_THREAD_POOL_INVALID_PRIO_KICKUP_TIMER`; SQLSTATE: `HY000`

Message: Invalid value of thread_pool_prio_kickup_timer specified. Value of thread_pool_prio_kickup_timer should be in range 0-4294967294.

- Error number: `MY-011103`; Symbol: `ER_THREAD_POOL_MAX_UNUSED_THREADS_INVALID`; SQLSTATE: `HY000`

Message: thread_pool_max_unused_threads cannot be set higher than %d.

- Error number: `MY-011104`; Symbol: `ER_THREAD_POOL_CON_HANDLER_INIT_FAILED`; SQLSTATE: `HY000`

Message: Failed to instantiate the connection handler object.

- Error number: `MY-011105`; Symbol: `ER_THREAD_POOL_INIT_FAILED`; SQLSTATE: `HY000`

Message: Failed to initialize thread pool plugin.

- Error number: `MY-011107`; Symbol: `ER_THREAD_POOL_CANNOT_SET_THREAD_SPECIFIC_DATA`; SQLSTATE: `HY000`

Message: Can't setup connection teardown thread-specific data.

- Error number: `MY-011108`; Symbol: `ER_THREAD_POOL_FAILED_TO_CREATE_CONNECT_HANDLER_THD`; SQLSTATE: `HY000`

Message: Creation of connect handler thread failed.

- Error number: `MY-011109`; Symbol: `ER_THREAD_POOL_FAILED_TO_CREATE_THD_AND_AUTH_CONN`; SQLSTATE: `HY000`

Message: Failed to create thd and authenticate connection.

- Error number: `MY-011110`; Symbol: `ER_THREAD_POOL_FAILED_PROCESS_CONNECT_EVENT`; SQLSTATE: `HY000`

Message: Failed to process connection event.

- Error number: `MY-011111`; Symbol: `ER_THREAD_POOL_FAILED_TO_CREATE_POOL`; SQLSTATE: `HY000`

Message: Can't create pool thread (error %d, errno: %d).

- Error number: `MY-011112`; Symbol: `ER_THREAD_POOL_RATE_LIMITED_ERROR_MSGS`; SQLSTATE: `HY000`

Message: %.*s.

- Error number: `MY-011113`; Symbol: `ER_THREAD_POOL_LOW_LEVEL_INIT_FAILED`; SQLSTATE: `HY000`

Message: `tp_group_low_level_init()` failed.

- Error number: `MY-011114`; Symbol: `ER_THREAD_POOL_LOW_LEVEL_REARM_FAILED`; SQLSTATE: `HY000`

Message: Rearm failed even after 30 seconds, can't continue without notify socket.

- Error number: `MY-011115`; Symbol: `ER_THREAD_POOL_BUFFER_TOO_SMALL`; SQLSTATE: `HY000`

Message: %s: %s buffer is too small

- Error number: `MY-011116`; Symbol: `ER_MECAB_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: Mecab v%s is not supported, the lowest version supported is v%s.

- Error number: `MY-011117`; Symbol: `ER_MECAB_NOT_VERIFIED`; SQLSTATE: `HY000`

Message: Mecab v%s is not verified, the highest version supported is v%s.

- Error number: `MY-011118`; Symbol: `ER_MECAB_CREATING_MODEL`; SQLSTATE: `HY000`

Message: Mecab: Trying createModel(%s).

- Error number: [MY-011119](#); Symbol: [ER_MECAB_FAILED_TO_CREATE_MODEL](#); SQLSTATE: [HY000](#)

Message: Mecab: createModel() failed: %s.

- Error number: [MY-011120](#); Symbol: [ER_MECAB_FAILED_TO_CREATE_TRIGGER](#); SQLSTATE: [HY000](#)

Message: Mecab: createTagger() failed: %s.

- Error number: [MY-011121](#); Symbol: [ER_MECAB_UNSUPPORTED_CHARSET](#); SQLSTATE: [HY000](#)

Message: Mecab: Unsupported dictionary charset %s.

- Error number: [MY-011122](#); Symbol: [ER_MECAB_CHARSET_LOADED](#); SQLSTATE: [HY000](#)

Message: Mecab: Loaded dictionary charset is %s.

- Error number: [MY-011123](#); Symbol: [ER_MECAB_PARSE_FAILED](#); SQLSTATE: [HY000](#)

Message: Mecab: parse() failed: %s.

- Error number: [MY-011124](#); Symbol: [ER_MECAB_OOM_WHILE_PARSING_TEXT](#); SQLSTATE: [HY000](#)

Message: Mecab: parse() failed: out of memory.

- Error number: [MY-011125](#); Symbol: [ER_MECAB_CREATE_LATTICE_FAILED](#); SQLSTATE: [HY000](#)

Message: Mecab: createLattice() failed: %s.

- Error number: [MY-011126](#); Symbol: [ER_SEMISYNC_TRACE_ENTER_FUNC](#); SQLSTATE: [HY000](#)

Message: ---> %s enter.

- Error number: [MY-011127](#); Symbol: [ER_SEMISYNC_TRACE_EXIT_WITH_INT_EXIT_CODE](#); SQLSTATE: [HY000](#)

Message: <--- %s exit (%d).

- Error number: [MY-011128](#); Symbol: [ER_SEMISYNC_TRACE_EXIT_WITH_BOOL_EXIT_CODE](#); SQLSTATE: [HY000](#)

Message: <--- %s exit (%s).

- Error number: [MY-011129](#); Symbol: [ER_SEMISYNC_TRACE_EXIT](#); SQLSTATE: [HY000](#)

Message: <--- %s exit.

- Error number: [MY-011130](#); Symbol: [ER_SEMISYNC_RPL_INIT_FOR_TRX](#); SQLSTATE: [HY000](#)

Message: Semi-sync replication initialized for transactions.

- Error number: [MY-011131](#); Symbol: [ER_SEMISYNC_FAILED_TO_ALLOCATE_TRX_NODE](#); SQLSTATE: [HY000](#)

Message: %s: transaction node allocation failed for: (%s, %lu).

- Error number: [MY-011132](#); Symbol: [ER_SEMISYNC_BINLOG_WRITE_OUT_OF_ORDER](#); SQLSTATE: [HY000](#)

-
- Message: %s: binlog write out-of-order, tail (%s, %lu), new node (%s, %lu).
- Error number: `MY-011133`; Symbol: `ER_SEMISYNC_INSERT_LOG_INFO_IN_ENTRY`; SQLSTATE: `HY000`
Message: %s: insert (%s, %lu) in entry(%u).
 - Error number: `MY-011134`; Symbol: `ER_SEMISYNC_PROBE_LOG_INFO_IN_ENTRY`; SQLSTATE: `HY000`
Message: %s: probe (%s, %lu) in entry(%u).
 - Error number: `MY-011135`; Symbol: `ER_SEMISYNC_CLEARED_ALL_ACTIVE_TRANSACTION_NODES`; SQLSTATE: `HY000`
Message: %s: cleared all nodes.
 - Error number: `MY-011136`; Symbol: `ER_SEMISYNC_CLEARED_ACTIVE_TRANSACTION_TILL_POS`; SQLSTATE: `HY000`
Message: %s: cleared %d nodes back until pos (%s, %lu).
 - Error number: `MY-011137`; Symbol: `ER_SEMISYNC_REPLY_MAGIC_NO_ERROR`; SQLSTATE: `HY000`
Message: Read semi-sync reply magic number error.
 - Error number: `MY-011138`; Symbol: `ER_SEMISYNC_REPLY_PKT_LENGTH_TOO_SMALL`; SQLSTATE: `HY000`
Message: Read semi-sync reply length error: packet is too small.
 - Error number: `MY-011139`; Symbol: `ER_SEMISYNC_REPLY_BINLOG_FILE_TOO_LARGE`; SQLSTATE: `HY000`
Message: Read semi-sync reply binlog file length too large.
 - Error number: `MY-011140`; Symbol: `ER_SEMISYNC_SERVER_REPLY`; SQLSTATE: `HY000`
Message: %s: Got reply(%s, %lu) from server %u.
 - Error number: `MY-011141`; Symbol: `ER_SEMISYNC_FUNCTION_CALLED_TWICE`; SQLSTATE: `HY000`
Message: %s called twice.
 - Error number: `MY-011142`; Symbol: `ER_SEMISYNC_RPL_ENABLED_ON_SOURCE`; SQLSTATE: `HY000`
Message: Semi-sync replication enabled on the source.
 - Error number: `MY-011143`; Symbol: `ER_SEMISYNC_SOURCE_OOM`; SQLSTATE: `HY000`
Message: Cannot allocate memory to enable semi-sync on the source.
 - Error number: `MY-011144`; Symbol: `ER_SEMISYNC_DISABLED_ON_SOURCE`; SQLSTATE: `HY000`
Message: Semi-sync replication disabled on the source.
 - Error number: `MY-011145`; Symbol: `ER_SEMISYNC_FORCED_SHUTDOWN`; SQLSTATE: `HY000`
Message: SEMISYNC: Forced shutdown. Some updates might not be replicated.

-
- Error number: `MY-011146`; Symbol: `ER_SEMISYNC_SOURCE_GOT_REPLY_AT_POS`; SQLSTATE: `HY000`
Message: %s: Got reply at (%s, %lu).
 - Error number: `MY-011147`; Symbol: `ER_SEMISYNC_SOURCE_SIGNAL_ALL_WAITING_THREADS`; SQLSTATE: `HY000`
Message: %s: signal all waiting threads.
 - Error number: `MY-011148`; Symbol: `ER_SEMISYNC_SOURCE_TRX_WAIT_POS`; SQLSTATE: `HY000`
Message: %s: wait pos (%s, %lu), repl(%d).
 - Error number: `MY-011149`; Symbol: `ER_SEMISYNC_BINLOG_REPLY_IS_AHEAD`; SQLSTATE: `HY000`
Message: %s: Binlog reply is ahead (%s, %lu).
 - Error number: `MY-011150`; Symbol: `ER_SEMISYNC_MOVE_BACK_WAIT_POS`; SQLSTATE: `HY000`
Message: %s: move back wait position (%s, %lu).
 - Error number: `MY-011151`; Symbol: `ER_SEMISYNC_INIT_WAIT_POS`; SQLSTATE: `HY000`
Message: %s: init wait position (%s, %lu).
 - Error number: `MY-011152`; Symbol: `ER_SEMISYNC_WAIT_TIME_FOR_BINLOG_SENT`; SQLSTATE: `HY000`
Message: %s: wait %lu ms for binlog sent (%s, %lu).
 - Error number: `MY-011153`; Symbol: `ER_SEMISYNC_WAIT_FOR_BINLOG_TIMEOUT`; SQLSTATE: `HY000`
Message: Timeout waiting for reply of binlog (file: %s, pos: %lu), semi-sync up to file %s, position %lu.
 - Error number: `MY-011154`; Symbol: `ER_SEMISYNC_WAIT_TIME_ASSESSMENT_FOR_COMMIT_TRX_FAILED`; SQLSTATE: `HY000`
Message: Assessment of waiting time for commitTrx failed at wait position (%s, %lu).
 - Error number: `MY-011155`; Symbol: `ER_SEMISYNC_RPL_SWITCHED_OFF`; SQLSTATE: `HY000`
Message: Semi-sync replication switched OFF.
 - Error number: `MY-011156`; Symbol: `ER_SEMISYNC_RPL_SWITCHED_ON`; SQLSTATE: `HY000`
Message: Semi-sync replication switched ON at (%s, %lu).
 - Error number: `MY-011157`; Symbol: `ER_SEMISYNC_NO_SPACE_IN_THE_PKT`; SQLSTATE: `HY000`
Message: No enough space in the packet for semi-sync extra header, semi-sync replication disabled.
 - Error number: `MY-011158`; Symbol: `ER_SEMISYNC_SYNC_HEADER_UPDATE_INFO`; SQLSTATE: `HY000`
Message: %s: server(%d), (%s, %lu) sync(%d), repl(%d).
 - Error number: `MY-011159`; Symbol: `ER_SEMISYNC_FAILED_TO_INSERT_TRX_NODE`; SQLSTATE: `HY000`

-
- Message: Semi-sync failed to insert tranx_node for binlog file: %s, position: %lu.
- Error number: `MY-011160`; Symbol: `ER_SEMISYNC_TRX_SKIPPED_AT_POS`; SQLSTATE: `HY000`
Message: %s: Transaction skipped at (%s, %lu).
 - Error number: `MY-011161`; Symbol: `ER_SEMISYNC_SOURCE_FAILED_ON_NET_FLUSH`; SQLSTATE: `HY000`
Message: Semi-sync source failed on net_flush() before waiting for replica reply.
 - Error number: `MY-011162`; Symbol: `ER_SEMISYNC_RECEIVED_ACK_IS_SMALLER`; SQLSTATE: `HY000`
Message: The received ack is smaller than m_greatest_ack.
 - Error number: `MY-011163`; Symbol: `ER_SEMISYNC_ADD_ACK_TO_SLOT`; SQLSTATE: `HY000`
Message: Add the ack into slot %u.
 - Error number: `MY-011164`; Symbol: `ER_SEMISYNC_UPDATE_EXISTING_REPLICA_ACK`; SQLSTATE: `HY000`
Message: Update an existing ack in slot %u.
 - Error number: `MY-011165`; Symbol: `ER_SEMISYNC_FAILED_TO_START_ACK_RECEIVER_THD`; SQLSTATE: `HY000`
Message: Failed to start semi-sync ACK receiver thread, could not create thread(errno=%d).
 - Error number: `MY-011166`; Symbol: `ER_SEMISYNC_STARTING_ACK_RECEIVER_THD`; SQLSTATE: `HY000`
Message: Starting ack receiver thread.
 - Error number: `MY-011167`; Symbol: `ER_SEMISYNC_FAILED_TO_WAIT_ON_DUMP_SOCKET`; SQLSTATE: `HY000`
Message: Failed to wait on semi-sync dump sockets, error: errno=%d.
 - Error number: `MY-011168`; Symbol: `ER_SEMISYNC_STOPPING_ACK_RECEIVER_THREAD`; SQLSTATE: `HY000`
Message: Stopping ack receiver thread.
 - Error number: `MY-011169`; Symbol: `ER_SEMISYNC_FAILED_REGISTER_REPLICA_TO_RECEIVER`; SQLSTATE: `HY000`
Message: Failed to register replica to semi-sync ACK receiver thread.
 - Error number: `MY-011170`; Symbol: `ER_SEMISYNC_START_BINLOG_DUMP_TO_REPLICA`; SQLSTATE: `HY000`
Message: Start %s binlog_dump to replica (server_id: %d), pos(%s, %lu).
 - Error number: `MY-011171`; Symbol: `ER_SEMISYNC_STOP_BINLOG_DUMP_TO_REPLICA`; SQLSTATE: `HY000`

Message: Stop %s binlog_dump to replica (server_id: %d).

- Error number: [MY-011172](#); Symbol: [ER_SEMISYNC_UNREGISTER_TRX_OBSERVER_FAILED](#); SQLSTATE: [HY000](#)

Message: unregister_trans_observer failed.

- Error number: [MY-011173](#); Symbol: [ER_SEMISYNC_UNREGISTER_BINLOG_STORAGE_OBSERVER_FAILED](#); SQLSTATE: [HY000](#)

Message: unregister_binlog_storage_observer failed.

- Error number: [MY-011174](#); Symbol: [ER_SEMISYNC_UNREGISTER_BINLOG_TRANSMIT_OBSERVER_FAILED](#); SQLSTATE: [HY000](#)

Message: unregister_binlog_transmit_observer failed.

- Error number: [MY-011175](#); Symbol: [ER_SEMISYNC_UNREGISTERED_REPLICATOR](#); SQLSTATE: [HY000](#)

Message: unregister_replicator OK.

- Error number: [MY-011176](#); Symbol: [ER_SEMISYNC_SOCKET_FD_TOO_LARGE](#); SQLSTATE: [HY000](#)

Message: Semisync replica socket fd is %u. select() cannot handle if the socket fd is bigger than %u (FD_SETSIZE).

- Error number: [MY-011177](#); Symbol: [ER_SEMISYNC_REPLICA_REPLY](#); SQLSTATE: [HY000](#)

Message: %s: reply - %d.

- Error number: [MY-011178](#); Symbol: [ER_SEMISYNC_MISSING_MAGIC_NO_FOR_SEMISYNC_PKT](#); SQLSTATE: [HY000](#)

Message: Missing magic number for semi-sync packet, packet len: %lu.

- Error number: [MY-011179](#); Symbol: [ER_SEMISYNC_REPLICA_START](#); SQLSTATE: [HY000](#)

Message: Replica I/O thread: Start %s replication to source '%s@%s:%d' in log '%s' at position %lu.

- Error number: [MY-011180](#); Symbol: [ER_SEMISYNC_REPLICA_REPLY_WITH_BINLOG_INFO](#); SQLSTATE: [HY000](#)

Message: %s: reply (%s, %lu).

- Error number: [MY-011181](#); Symbol: [ER_SEMISYNC_REPLICA_NET_FLUSH_REPLY_FAILED](#); SQLSTATE: [HY000](#)

Message: Semi-sync replica net_flush() reply failed.

- Error number: [MY-011182](#); Symbol: [ER_SEMISYNC_REPLICA_SEND_REPLY_FAILED](#); SQLSTATE: [HY000](#)

Message: Semi-sync replica send reply failed: %s (%d).

- Error number: [MY-011183](#); Symbol: [ER_SEMISYNC_EXECUTION_FAILED_ON_SOURCE](#); SQLSTATE: [HY000](#)

Message: Execution failed on source: %s; error %d

- Error number: MY-011184; Symbol: ER_SEMISYNC_NOT_SUPPORTED_BY_SOURCE; SQLSTATE: HY000

Message: Source server does not support semi-sync, fallback to asynchronous replication

- Error number: MY-011185; Symbol: ER_SEMISYNC_REPLICA_SET_FAILED; SQLSTATE: HY000

Message: Set 'rpl_semi_sync_replica=1' on source failed

- Error number: MY-011186; Symbol: ER_SEMISYNC_FAILED_TO_STOP_ACK_RECEIVER_THD; SQLSTATE: HY000

Message: Failed to stop ack receiver thread on my_thread_join, errno(%d).

- Error number: MY-011187; Symbol: ER_FIREWALL_FAILED_TO_READ_FIREWALL_TABLES; SQLSTATE: HY000

Message: Failed to read the firewall tables

- Error number: MY-011188; Symbol: ER_FIREWALL_FAILED_TO_REG_DYNAMIC_PRIVILEGES; SQLSTATE: HY000

Message: Failed to register dynamic privileges

- Error number: MY-011189; Symbol: ER_FIREWALL_RECORDING_STMT_WAS_TRUNCATED; SQLSTATE: HY000

Message: Statement was truncated and not recorded: %s

- Error number: MY-011190; Symbol: ER_FIREWALL_RECORDING_STMT_WITHOUT_TEXT; SQLSTATE: HY000

Message: Statement with no text was not recorded

- Error number: MY-011191; Symbol: ER_FIREWALL_SUSPICIOUS_STMT; SQLSTATE: HY000

Message: SUSPICIOUS STATEMENT from '%s'. Reason: %s Statement: %s

- Error number: MY-011192; Symbol: ER_FIREWALL_ACCESS_DENIED; SQLSTATE: HY000

Message: ACCESS DENIED for '%s'. Reason: %s Statement: %s

- Error number: MY-011193; Symbol: ER_FIREWALL_SKIPPED_UNKNOWN_USER_MODE; SQLSTATE: HY000

Message: Skipped unknown user mode '%s'

- Error number: MY-011194; Symbol: ER_FIREWALL_RELOADING_CACHE; SQLSTATE: HY000

Message: Reloading cache from disk

- Error number: MY-011195; Symbol: ER_FIREWALL_RESET_FOR_USER; SQLSTATE: HY000

Message: FIREWALL RESET for '%s'

- Error number: MY-011196; Symbol: ER_FIREWALL_STATUS_FLUSHED; SQLSTATE: HY000

Message: Counters are reset to zero

- Error number: `MY-011197`; Symbol: `ER_KEYRING_LOGGER_ERROR_MSG`; SQLSTATE: `HY000`

Message: %s

- Error number: `MY-011198`; Symbol: `ER_AUDIT_LOG_FILTER_IS_NOT_INSTALLED`; SQLSTATE: `HY000`

Message: Audit Log plugin supports filtering mode, which has not been installed yet. Audit Log plugin will run in the legacy mode, which will be removed in the next release.

- Error number: `MY-011199`; Symbol: `ER_AUDIT_LOG_SWITCHING_TO_INCLUDE_LIST`; SQLSTATE: `HY000`

Message: Previously exclude list is used, now we start using include list, exclude list is set to NULL.

- Error number: `MY-011200`; Symbol: `ER_AUDIT_LOG_CANNOT_SET_LOG_POLICY_WITH_OTHER_POLICIES`; SQLSTATE: `HY000`

Message: Cannot set `audit_log_policy` simultaneously with either `audit_log_connection_policy` or `audit_log_statement_policy`, setting `audit_log_connection_policy` and `audit_log_statement_policy` based on `audit_log_policy`.

- Error number: `MY-011201`; Symbol: `ER_AUDIT_LOG_ONLY_INCLUDE_LIST_USED`; SQLSTATE: `HY000`

Message: Both include and exclude lists provided, include list is preferred, exclude list is set to NULL.

- Error number: `MY-011202`; Symbol: `ER_AUDIT_LOG_INDEX_MAP_CANNOT_ACCESS_DIR`; SQLSTATE: `HY000`

Message: Could not access '%s' directory.

- Error number: `MY-011203`; Symbol: `ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED`; SQLSTATE: `HY000`

Message: Could not rename file from '%s' to '%s'.

- Error number: `MY-011204`; Symbol: `ER_AUDIT_LOG_WRITER_DEST_FILE_ALREADY_EXISTS`; SQLSTATE: `HY000`

Message: File '%s' should not exist. It may be incomplete. The server crashed.

- Error number: `MY-011205`; Symbol: `ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED_REMOVE_FILE_MANUALLY`; SQLSTATE: `HY000`

Message: Could not rename file from '%s' to '%s'. Remove the file manually.

- Error number: `MY-011206`; Symbol: `ER_AUDIT_LOG_WRITER_INCOMPLETE_FILE_RENAMED`; SQLSTATE: `HY000`

Message: Incomplete file renamed from '%s' to '%s'.

- Error number: `MY-011207`; Symbol: `ER_AUDIT_LOG_WRITER_FAILED_TO_WRITE_TO_FILE`; SQLSTATE: `HY000`

Message: Error writing file '%s' (errno: %d - %s).

-
- Error number: `MY-011208`; Symbol: `ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_ENCRYPTION`; SQLSTATE: `HY000`
Message: Could not initialize audit log file encryption.
 - Error number: `MY-011209`; Symbol: `ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_COMPRESSION`; SQLSTATE: `HY000`
Message: Could not initialize audit log file compression.
 - Error number: `MY-011210`; Symbol: `ER_AUDIT_LOG_EC_WRITER_FAILED_TO_CREATE_FILE`; SQLSTATE: `HY000`
Message: Could not create '%s' file for audit logging.
 - Error number: `MY-011211`; Symbol: `ER_AUDIT_LOG_RENAME_LOG_FILE_BEFORE_FLUSH`; SQLSTATE: `HY000`
Message: Audit log file (%s) must be manually renamed before `audit_log_flush` is set to true.
 - Error number: `MY-011212`; Symbol: `ER_AUDIT_LOG_FILTER_RESULT_MSG`; SQLSTATE: `HY000`
Message: %s
 - Error number: `MY-011213`; Symbol: `ER_AUDIT_LOG_JSON_READER_FAILED_TO_PARSE`; SQLSTATE: `HY000`
Message: Error parsing JSON event. Event not accessible.
 - Error number: `MY-011214`; Symbol: `ER_AUDIT_LOG_JSON_READER_BUF_TOO_SMALL`; SQLSTATE: `HY000`
Message: Buffer is too small to hold JSON event. Number of events skipped: %zu.
 - Error number: `MY-011215`; Symbol: `ER_AUDIT_LOG_JSON_READER_FAILED_TO_OPEN_FILE`; SQLSTATE: `HY000`
Message: Could not open JSON file for reading. Reading next file if exists.
 - Error number: `MY-011216`; Symbol: `ER_AUDIT_LOG_JSON_READER_FILE_PARSING_ERROR`; SQLSTATE: `HY000`
Message: JSON file parsing error. Reading next file if exists
 - Error number: `MY-011219`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_STORE_TABLE_FLDS`; SQLSTATE: `HY000`
Message: Could not store field of the %s table.
 - Error number: `MY-011220`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_UPDATE_TABLE`; SQLSTATE: `HY000`
Message: Could not update %s table.
 - Error number: `MY-011221`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_INSERT_INTO_TABLE`; SQLSTATE: `HY000`
Message: Could not insert into %s table.

-
- Error number: `MY-011222`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_DELETE_FROM_TABLE`; SQLSTATE: `HY000`
Message: Could not delete from %s table.
 - Error number: `MY-011223`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_INIT_TABLE_FOR_READ`; SQLSTATE: `HY000`
Message: Could not initialize %s table for reading.
 - Error number: `MY-011224`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_READ_TABLE`; SQLSTATE: `HY000`
Message: Could not read %s table.
 - Error number: `MY-011225`; Symbol: `ER_AUDIT_LOG_FILTER_FAILED_TO_CLOSE_TABLE_AFTER_READING`; SQLSTATE: `HY000`
Message: Could not close %s table reading.
 - Error number: `MY-011226`; Symbol: `ER_AUDIT_LOG_FILTER_USER_AND_HOST_CANNOT_BE_EMPTY`; SQLSTATE: `HY000`
Message: Both user and host columns of %s table cannot be empty.
 - Error number: `MY-011227`; Symbol: `ER_AUDIT_LOG_FILTER_FLD_FILTERNAME_CANNOT_BE_EMPTY`; SQLSTATE: `HY000`
Message: Filtername column of %s table cannot be empty.
 - Error number: `MY-011228`; Symbol: `ER_VALIDATE_PWD_DICT_FILE_NOT_SPECIFIED`; SQLSTATE: `HY000`
Message: Dictionary file not specified
 - Error number: `MY-011229`; Symbol: `ER_VALIDATE_PWD_DICT_FILE_NOT_LOADED`; SQLSTATE: `HY000`
Message: Dictionary file not loaded
 - Error number: `MY-011230`; Symbol: `ER_VALIDATE_PWD_DICT_FILE_TOO_BIG`; SQLSTATE: `HY000`
Message: Dictionary file size exceeded `MAX_DICTIONARY_FILE_LENGTH`, not loaded
 - Error number: `MY-011231`; Symbol: `ER_VALIDATE_PWD_FAILED_TO_READ_DICT_FILE`; SQLSTATE: `HY000`
Message: Exception while reading the dictionary file
 - Error number: `MY-011232`; Symbol: `ER_VALIDATE_PWD_FAILED_TO_GET_FLD_FROM_SECURITY_CTX`; SQLSTATE: `HY000`
Message: Can't retrieve the %s from the security context
 - Error number: `MY-011233`; Symbol: `ER_VALIDATE_PWD_FAILED_TO_GET_SECURITY_CTX`; SQLSTATE: `HY000`
Message: Can't retrieve the security context
-

-
- Error number: [MY-011234](#); Symbol: [ER_VALIDATE_PWD_LENGTH_CHANGED](#); SQLSTATE: [HY000](#)
Message: Effective value of validate_password_length is changed. New value is %d
 - Error number: [MY-011235](#); Symbol: [ER_REWRITER_QUERY_ERROR_MSG](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011236](#); Symbol: [ER_REWRITER_QUERY_FAILED](#); SQLSTATE: [HY000](#)
Message: Rewritten query failed to parse:%s
 - Error number: [MY-011237](#); Symbol: [ER_XPLUGIN_STARTUP_FAILED](#); SQLSTATE: [HY000](#)
Message: Startup failed with error "%s"
 - Error number: [MY-011240](#); Symbol: [ER_XPLUGIN_USING_SSL_CONF_FROM_SERVER](#); SQLSTATE: [HY000](#)
Message: Using SSL configuration from MySQL Server
 - Error number: [MY-011241](#); Symbol: [ER_XPLUGIN_USING_SSL_CONF_FROM_MYSQLX](#); SQLSTATE: [HY000](#)
Message: Using SSL configuration from Mysqlx Plugin
 - Error number: [MY-011242](#); Symbol: [ER_XPLUGIN_FAILED_TO_USE_SSL_CONF](#); SQLSTATE: [HY000](#)
Message: Neither MySQL Server nor Mysqlx Plugin has valid SSL configuration
 - Error number: [MY-011243](#); Symbol: [ER_XPLUGIN_USING_SSL_FOR_TLS_CONNECTION](#); SQLSTATE: [HY000](#)
Message: Using %s for TLS connections
 - Error number: [MY-011244](#); Symbol: [ER_XPLUGIN_REFERENCE_TO_SECURE_CONN_WITH_XPLUGIN](#); SQLSTATE: [HY000](#)
Message: For more information, please see the Using Secure Connections with X Plugin section in the MySQL documentation
 - Error number: [MY-011245](#); Symbol: [ER_XPLUGIN_ERROR_MSG](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011246](#); Symbol: [ER_SHA_PWD_FAILED_TO_PARSE_AUTH_STRING](#); SQLSTATE: [HY000](#)
Message: Failed to parse stored authentication string for %s. Please check if mysql.user table not corrupted
 - Error number: [MY-011247](#); Symbol: [ER_SHA_PWD_FAILED_TO_GENERATE_MULTI_ROUND_HASH](#); SQLSTATE: [HY000](#)
Message: Error in generating multi-round hash for %s. Plugin can not perform authentication without it. This may be a transient problem
 - Error number: [MY-011248](#); Symbol: [ER_SHA_PWD_AUTH_REQUIRES_RSA_OR_SSL](#); SQLSTATE: [HY000](#)

Message: Authentication requires either RSA keys or SSL encryption

- Error number: `MY-011249`; Symbol: `ER_SHA_PWD_RSA_KEY_TOO_LONG`; SQLSTATE: `HY000`

Message: RSA key cipher length of %u is too long. Max value is %u

- Error number: `MY-011250`; Symbol: `ER_PLUGIN_COMMON_FAILED_TO_OPEN_FILTER_TABLES`; SQLSTATE: `HY000`

Message: Failed to open the %s filter tables

- Error number: `MY-011251`; Symbol: `ER_PLUGIN_COMMON_FAILED_TO_OPEN_TABLE`; SQLSTATE: `HY000`

Message: Failed to open '%s.%s' %s table

- Error number: `MY-011252`; Symbol: `ER_AUTH_LDAP_ERROR_LOGGER_ERROR_MSG`; SQLSTATE: `HY000`

Message: %s

- Error number: `MY-011253`; Symbol: `ER_CONN_CONTROL_ERROR_MSG`; SQLSTATE: `HY000`

Message: %s

- Error number: `MY-011254`; Symbol: `ER_GRP_RPL_ERROR_MSG`; SQLSTATE: `HY000`

Message: %s

- Error number: `MY-011255`; Symbol: `ER_SHA_PWD_SALT_FOR_USER_CORRUPT`; SQLSTATE: `HY000`

Message: Password salt for user '%s' is corrupt

- Error number: `MY-011256`; Symbol: `ER_SYS_VAR_COMPONENT_OOM`; SQLSTATE: `HY000`

Message: Out of memory for component system variable '%s'.

- Error number: `MY-011257`; Symbol: `ER_SYS_VAR_COMPONENT_VARIABLE_SET_READ_ONLY`; SQLSTATE: `HY000`

Message: variable %s of component %s was forced to be read-only: string variable without update_func and PLUGIN_VAR_MEMALLOC flag.

- Error number: `MY-011258`; Symbol: `ER_SYS_VAR_COMPONENT_UNKNOWN_VARIABLE_TYPE`; SQLSTATE: `HY000`

Message: Unknown variable type code 0x%x in component '%s'.

- Error number: `MY-011259`; Symbol: `ER_SYS_VAR_COMPONENT_FAILED_TO_PARSE_VARIABLE_OPTIONS`; SQLSTATE: `HY000`

Message: Parsing options for variable '%s' failed.

- Error number: `MY-011260`; Symbol: `ER_SYS_VAR_COMPONENT_FAILED_TO_MAKE_VARIABLE_PERSISTENT`; SQLSTATE: `HY000`

Message: Setting persistent options for component variable '%s' failed.

- Error number: `MY-011261`; Symbol: `ER_COMPONENT_FILTER_CONFUSED`; SQLSTATE: `HY000`

Message: The log-filter component "%s" got confused at "%s" (state: %s) ...

- Error number: [MY-011262](#); Symbol: [ER_STOP_REPLICA_IO_THREAD_DISK_SPACE](#); SQLSTATE: [HY000](#)

Message: Waiting until I/O thread for channel '%s' finish writing to disk before stopping. Free some disk space or use 'KILL' to abort I/O thread operation. Notice that aborting the I/O thread while rotating the relay log might corrupt the relay logs, requiring a server restart to fix it.

- Error number: [MY-011263](#); Symbol: [ER_LOG_FILE_CANNOT_OPEN](#); SQLSTATE: [HY000](#)

Message: Could not use %s for logging (error %d - %s). Turning logging off for the server process. To turn it on again: fix the cause, then %s restart the MySQL server.

- Error number: [MY-011268](#); Symbol: [ER_PERSIST_OPTION_STATUS](#); SQLSTATE: [HY000](#)

Message: Configuring persisted options failed: "%s".

- Error number: [MY-011269](#); Symbol: [ER_NOT_IMPLEMENTED_GET_TABLESPACE_STATISTICS](#); SQLSTATE: [HY000](#)

Message: The storage engine '%s' does not provide dynamic table statistics

- Error number: [MY-011272](#); Symbol: [ER_SSL_FIPS_MODE_ERROR](#); SQLSTATE: [HY000](#)

Message: SSL fips mode error: %s

- Error number: [MY-011273](#); Symbol: [ER_CONN_INIT_CONNECT_IGNORED](#); SQLSTATE: [HY000](#)

Message: init_connect variable is ignored for user: %s host: %s due to expired password.

- Error number: [MY-011275](#); Symbol: [ER_REWRITER_OOM](#); SQLSTATE: [HY000](#)

Message: Out of memory.

- Error number: [MY-011276](#); Symbol: [ER_REWRITER_TABLE_MALFORMED_ERROR](#); SQLSTATE: [HY000](#)

Message: Wrong column count or names when loading rules.

- Error number: [MY-011277](#); Symbol: [ER_REWRITER_LOAD_FAILED](#); SQLSTATE: [HY000](#)

Message: Some rules failed to load.

- Error number: [MY-011278](#); Symbol: [ER_REWRITER_READ_FAILED](#); SQLSTATE: [HY000](#)

Message: Got error from storage engine while refreshing rewrite rules.

- Error number: [MY-011279](#); Symbol: [ER_CONN_CONTROL_EVENT_COORDINATOR_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to initialize Connection_event_coordinator

- Error number: [MY-011280](#); Symbol: [ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_UPDATE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to update connection delay triggered stats

- Error number: [MY-011281](#); Symbol: [ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_RESET_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to reset connection delay triggered stats

- Error number: [MY-011282](#); Symbol: [ER_CONN_CONTROL_INVALID_CONN_DELAY_TYPE](#); SQLSTATE: [HY000](#)

Message: Unexpected option type for connection delay.

- Error number: [MY-011283](#); Symbol: [ER_CONN_CONTROL_DELAY_ACTION_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to initialize Connection_delay_action

- Error number: [MY-011284](#); Symbol: [ER_CONN_CONTROL_FAILED_TO_SET_CONN_DELAY](#); SQLSTATE: [HY000](#)

Message: Could not set %s delay for connection delay.

- Error number: [MY-011285](#); Symbol: [ER_CONN_CONTROL_FAILED_TO_UPDATE_CONN_DELAY_HASH](#); SQLSTATE: [HY000](#)

Message: Failed to update connection delay hash for account : %s

- Error number: [MY-011286](#); Symbol: [ER_XPLUGIN_FORCE_STOP_CLIENT](#); SQLSTATE: [HY000](#)

Message: %s: Force stopping client because exception occurred: %s

- Error number: [MY-011287](#); Symbol: [ER_XPLUGIN_MAX_AUTH_ATTEMPTS_REACHED](#); SQLSTATE: [HY000](#)

Message: %s.%u: Maximum number of authentication attempts reached, login failed.

- Error number: [MY-011288](#); Symbol: [ER_XPLUGIN_BUFFER_PAGE_ALLOC_FAILED](#); SQLSTATE: [HY000](#)

Message: Error allocating Buffer_page: %s

- Error number: [MY-011289](#); Symbol: [ER_XPLUGIN_DETECTED_HANGING_CLIENTS](#); SQLSTATE: [HY000](#)

Message: Detected %u hanging client(s)

- Error number: [MY-011290](#); Symbol: [ER_XPLUGIN_FAILED_TO_ACCEPT_CLIENT](#); SQLSTATE: [HY000](#)

Message: Error accepting client

- Error number: [MY-011291](#); Symbol: [ER_XPLUGIN_FAILED_TO_SCHEDULE_CLIENT](#); SQLSTATE: [HY000](#)

Message: Internal error scheduling client for execution

- Error number: [MY-011292](#); Symbol: [ER_XPLUGIN_FAILED_TO_PREPARE_IO_INTERFACES](#); SQLSTATE: [HY000](#)

Message: Preparation of I/O interfaces failed, X Protocol won't be accessible

- Error number: [MY-011293](#); Symbol: [ER_XPLUGIN_SRV_SESSION_INIT_THREAD_FAILED](#); SQLSTATE: [HY000](#)

Message: srv_session_init_thread returned error

-
- Error number: [MY-011294](#); Symbol: [ER_XPLUGIN_UNABLE_TO_USE_USER_SESSION_ACCOUNT](#); SQLSTATE: [HY000](#)
Message: Unable to use user mysql.session account when connecting the server for internal plugin requests.
 - Error number: [MY-011295](#); Symbol: [ER_XPLUGIN_REFERENCE_TO_USER_ACCOUNT_DOC_SECTION](#); SQLSTATE: [HY000](#)
Message: For more information, please see the X Plugin User Account section in the MySQL documentation
 - Error number: [MY-011296](#); Symbol: [ER_XPLUGIN_UNEXPECTED_EXCEPTION_DISPATCHING_CMD](#); SQLSTATE: [HY000](#)
Message: %s: Unexpected exception dispatching command: %s
 - Error number: [MY-011297](#); Symbol: [ER_XPLUGIN_EXCEPTION_IN_TASK_SCHEDULER](#); SQLSTATE: [HY000](#)
Message: Exception in post: %s
 - Error number: [MY-011298](#); Symbol: [ER_XPLUGIN_TASK_SCHEDULING_FAILED](#); SQLSTATE: [HY000](#)
Message: Internal error scheduling task
 - Error number: [MY-011299](#); Symbol: [ER_XPLUGIN_EXCEPTION_IN_EVENT_LOOP](#); SQLSTATE: [HY000](#)
Message: Exception in event loop: "%s": %s
 - Error number: [MY-011300](#); Symbol: [ER_XPLUGIN_LISTENER_SETUP_FAILED](#); SQLSTATE: [HY000](#)
Message: Setup of %s failed, %s
 - Error number: [MY-011301](#); Symbol: [ER_XPLUING_NET_STARTUP_FAILED](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011302](#); Symbol: [ER_XPLUGIN_FAILED_AT_SSL_CONF](#); SQLSTATE: [HY000](#)
Message: Failed at SSL configuration: "%s"
 - Error number: [MY-011305](#); Symbol: [ER_XPLUGIN_FAILED_TO_CREATE_SESSION_FOR_CONN](#); SQLSTATE: [HY000](#)
Message: %s: Error creating session for connection from %s
 - Error number: [MY-011306](#); Symbol: [ER_XPLUGIN_FAILED_TO_INITIALIZE_SESSION](#); SQLSTATE: [HY000](#)
Message: %s: Error initializing session for connection: %s
 - Error number: [MY-011307](#); Symbol: [ER_XPLUGIN_MESSAGE_TOO_LONG](#); SQLSTATE: [HY000](#)
Message: %s: Message of size %u received, exceeding the limit of %i
 - Error number: [MY-011308](#); Symbol: [ER_XPLUGIN_UNINITIALIZED_MESSAGE](#); SQLSTATE: [HY000](#)
Message: Message is not properly initialized: %s

-
- Error number: [MY-011309](#); Symbol: [ER_XPLUGIN_FAILED_TO_SET_MIN_NUMBER_OF_WORKERS](#); SQLSTATE: [HY000](#)
Message: Unable to set minimal number of workers to %u; actual value is %i
 - Error number: [MY-011310](#); Symbol: [ER_XPLUGIN_UNABLE_TO_ACCEPT_CONNECTION](#); SQLSTATE: [HY000](#)
Message: Unable to accept connection, disconnecting client
 - Error number: [MY-011311](#); Symbol: [ER_XPLUGIN_ALL_IO_INTERFACES_DISABLED](#); SQLSTATE: [HY000](#)
Message: All I/O interfaces are disabled, X Protocol won't be accessible
 - Error number: [MY-011314](#); Symbol: [ER_XPLUGIN_ERROR_READING_SOCKET](#); SQLSTATE: [HY000](#)
Message: %s: Error reading from socket %s (%i)
 - Error number: [MY-011315](#); Symbol: [ER_XPLUGIN_PEER_DISCONNECTED_WHILE_READING_MSG_BODY](#); SQLSTATE: [HY000](#)
Message: %s: peer disconnected while reading message body
 - Error number: [MY-011316](#); Symbol: [ER_XPLUGIN_READ_FAILED_CLOSING_CONNECTION](#); SQLSTATE: [HY000](#)
Message: client_id:%s - %s while reading from socket, closing connection
 - Error number: [MY-011322](#); Symbol: [ER_XPLUGIN_LISTENER_SYS_VARIABLE_ERROR](#); SQLSTATE: [HY000](#)
Message: Please see the MySQL documentation for '%s' system variables to fix the error
 - Error number: [MY-011323](#); Symbol: [ER_XPLUGIN_LISTENER_STATUS_MSG](#); SQLSTATE: [HY000](#)
Message: X Plugin ready for connections. %s
 - Error number: [MY-011324](#); Symbol: [ER_XPLUGIN_RETRYING_BIND_ON_PORT](#); SQLSTATE: [HY000](#)
Message: Retrying `bind()` on TCP/IP port %i
 - Error number: [MY-011327](#); Symbol: [ER_XPLUGIN_EXISTING_USER_ACCOUNT_WITH_INCOMPLETE_GRANTS](#); SQLSTATE: [HY000](#)
Message: Using existing %s account for authentication. Incomplete grants will be fixed
 - Error number: [MY-011332](#); Symbol: [ER_XPLUGIN_IPv6_AVAILABLE](#); SQLSTATE: [HY000](#)
Message: IPv6 is available
 - Error number: [MY-011334](#); Symbol: [ER_XPLUGIN_CLIENT_KILL_MSG](#); SQLSTATE: [HY000](#)
Message: Kill client: %i %s
 - Error number: [MY-011335](#); Symbol: [ER_XPLUGIN_FAILED_TO_GET_SECURITY_CTX](#); SQLSTATE: [HY000](#)
Message: Could not get security context for session

-
- Error number: [MY-011337](#); Symbol: [ER_XPLUGIN_FAILED_TO_CLOSE_SQL_SESSION](#); SQLSTATE: [HY000](#)
Message: Error closing SQL session
 - Error number: [MY-011338](#); Symbol: [ER_XPLUGIN_FAILED_TO_EXECUTE_ADMIN_CMD](#); SQLSTATE: [HY000](#)
Message: Error executing admin command %s: %s
 - Error number: [MY-011339](#); Symbol: [ER_XPLUGIN_EMPTY_ADMIN_CMD](#); SQLSTATE: [HY000](#)
Message: Error executing empty admin command
 - Error number: [MY-011340](#); Symbol: [ER_XPLUGIN_FAILED_TO_GET_SYS_VAR](#); SQLSTATE: [HY000](#)
Message: Unable to retrieve system variable '%s'
 - Error number: [MY-011341](#); Symbol: [ER_XPLUGIN_FAILED_TO_GET_CREATION_STMT](#); SQLSTATE: [HY000](#)
Message: Unable to get creation stmt for collection '%s'; query result size: %lu
 - Error number: [MY-011342](#); Symbol: [ER_XPLUGIN_FAILED_TO_GET_ENGINE_INFO](#); SQLSTATE: [HY000](#)
Message: Unable to get engine info for collection '%s'; creation stmt: %s
 - Error number: [MY-011345](#); Symbol: [ER_XPLUGIN_FAILED_TO_SET_SO_REUSEADDR_FLAG](#); SQLSTATE: [HY000](#)
Message: Failed to set SO_REUSEADDR flag (error: %d).
 - Error number: [MY-011346](#); Symbol: [ER_XPLUGIN_FAILED_TO_OPEN_INTERNAL_SESSION](#); SQLSTATE: [HY000](#)
Message: Could not open internal MySQL session
 - Error number: [MY-011347](#); Symbol: [ER_XPLUGIN_FAILED_TO_SWITCH_CONTEXT](#); SQLSTATE: [HY000](#)
Message: Unable to switch context to user %s
 - Error number: [MY-011348](#); Symbol: [ER_XPLUGIN_FAILED_TO_UNREGISTER_UDF](#); SQLSTATE: [HY000](#)
Message: Can't unregister '%s' user defined function
 - Error number: [MY-011351](#); Symbol: [ER_XPLUGIN_FAILED_TO_RESET_IPV6_V6ONLY_FLAG](#); SQLSTATE: [HY000](#)
Message: Failed to reset IPV6_V6ONLY flag (error: %d). The server will listen to IPv6 addresses only.
 - Error number: [MY-011352](#); Symbol: [ER_KEYRING_INVALID_KEY_TYPE](#); SQLSTATE: [HY000](#)
Message: Invalid key type
 - Error number: [MY-011353](#); Symbol: [ER_KEYRING_INVALID_KEY_LENGTH](#); SQLSTATE: [HY000](#)
Message: Invalid key length for given block cipher

-
- Error number: [MY-011358](#); Symbol: [ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_INVALID_KEY](#); SQLSTATE: [HY000](#)
Message: Error while %s key: invalid key_type
 - Error number: [MY-011359](#); Symbol: [ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_EMPTY_KEY_ID](#); SQLSTATE: [HY000](#)
Message: Error while %s key: key_id cannot be empty
 - Error number: [MY-011360](#); Symbol: [ER_KEYRING_OPERATION_FAILED_DUE_TO_INTERNAL_ERROR](#); SQLSTATE: [HY000](#)
Message: Failed to %s due to internal exception inside %s plugin
 - Error number: [MY-011361](#); Symbol: [ER_KEYRING_INCORRECT_FILE](#); SQLSTATE: [HY000](#)
Message: Incorrect Keyring file
 - Error number: [MY-011362](#); Symbol: [ER_KEYRING_FOUND_MALFORMED_BACKUP_FILE](#); SQLSTATE: [HY000](#)
Message: Found malformed keyring backup file - removing it
 - Error number: [MY-011363](#); Symbol: [ER_KEYRING_FAILED_TO_RESTORE_FROM_BACKUP_FILE](#); SQLSTATE: [HY000](#)
Message: Error while restoring keyring from backup file cannot overwrite keyring with backup
 - Error number: [MY-011364](#); Symbol: [ER_KEYRING_FAILED_TO_FLUSH_KEYRING_TO_FILE](#); SQLSTATE: [HY000](#)
Message: Error while flushing in-memory keyring into keyring file
 - Error number: [MY-011365](#); Symbol: [ER_KEYRING_FAILED_TO_GET_FILE_STAT](#); SQLSTATE: [HY000](#)
Message: Error while reading stat for %s. Please check if file %s was not removed. OS returned this error: %s
 - Error number: [MY-011366](#); Symbol: [ER_KEYRING_FAILED_TO_REMOVE_FILE](#); SQLSTATE: [HY000](#)
Message: Could not remove file %s OS returned this error: %s
 - Error number: [MY-011367](#); Symbol: [ER_KEYRING_FAILED_TO_TRUNCATE_FILE](#); SQLSTATE: [HY000](#)
Message: Could not truncate file %s. OS returned this error: %s
 - Error number: [MY-011368](#); Symbol: [ER_KEYRING_UNKNOWN_ERROR](#); SQLSTATE: [HY000](#)
Message: Unknown error %d
 - Error number: [MY-011370](#); Symbol: [ER_KEYRING_FILE_IO_ERROR](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011371](#); Symbol: [ER_KEYRING_FAILED_TO_LOAD_KEYRING_CONTENT](#); SQLSTATE: [HY000](#)
Message: Error while loading keyring content. The keyring might be malformed

-
- Error number: `MY-011372`; Symbol: `ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING`; SQLSTATE: `HY000`
Message: Could not flush keys to keyring
 - Error number: `MY-011373`; Symbol: `ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING_BACKUP`; SQLSTATE: `HY000`
Message: Could not flush keys to keyring's backup
 - Error number: `MY-011374`; Symbol: `ER_KEYRING_KEY_FETCH_FAILED_DUE_TO_EMPTY_KEY_ID`; SQLSTATE: `HY000`
Message: Error while fetching key: key_id cannot be empty
 - Error number: `MY-011375`; Symbol: `ER_KEYRING_FAILED_TO_REMOVE_KEY_DUE_TO_EMPTY_ID`; SQLSTATE: `HY000`
Message: Error while removing key: key_id cannot be empty
 - Error number: `MY-011376`; Symbol: `ER_KEYRING_OKV_INCORRECT_KEY_VAULT_CONFIGURED`; SQLSTATE: `HY000`
Message: For keyring_okv to be initialized, please point keyring_okv_conf_dir variable to a directory with Oracle Key Vault configuration file and ssl materials
 - Error number: `MY-011377`; Symbol: `ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INCORRECT_CONF`; SQLSTATE: `HY000`
Message: keyring_okv initialization failure. Please check that the keyring_okv_conf_dir points to a readable directory and that the directory contains Oracle Key Vault configuration file and ssl materials. Please also check that Oracle Key Vault is up and running.
 - Error number: `MY-011378`; Symbol: `ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INTERNAL_ERROR`; SQLSTATE: `HY000`
Message: keyring_okv initialization failure due to internal exception inside the plugin
 - Error number: `MY-011379`; Symbol: `ER_KEYRING_OKV_INVALID_KEY_TYPE`; SQLSTATE: `HY000`
Message: Invalid key type
 - Error number: `MY-011380`; Symbol: `ER_KEYRING_OKV_INVALID_KEY_LENGTH_FOR_CIPHER`; SQLSTATE: `HY000`
Message: Invalid key length for given block cipher
 - Error number: `MY-011381`; Symbol: `ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR`; SQLSTATE: `HY000`
Message: Failed to generate a key due to internal exception inside keyring_okv plugin
 - Error number: `MY-011382`; Symbol: `ER_KEYRING_OKV_FAILED_TO_FIND_SERVER_ENTRY`; SQLSTATE: `HY000`
Message: Could not find entry for server in configuration file %s
 - Error number: `MY-011383`; Symbol: `ER_KEYRING_OKV_FAILED_TO_FIND_STANDBY_SERVER_ENTRY`; SQLSTATE: `HY000`

Message: Could not find entry for standby server in configuration file %s

- Error number: MY-011384; Symbol: ER_KEYRING_OKV_FAILED_TO_PARSE_CONF_FILE; SQLSTATE: HY000

Message: Could not parse the %s file provided

- Error number: MY-011385; Symbol: ER_KEYRING_OKV_FAILED_TO_LOAD_KEY_UID; SQLSTATE: HY000

Message: Could not load keys' uids from the OKV server

- Error number: MY-011386; Symbol: ER_KEYRING_OKV_FAILED_TO_INIT_SSL_LAYER; SQLSTATE: HY000

Message: Could not initialize ssl layer

- Error number: MY-011387; Symbol: ER_KEYRING_OKV_FAILED_TO_INIT_CLIENT; SQLSTATE: HY000

Message: Could not initialize OKV client

- Error number: MY-011388; Symbol: ER_KEYRING_OKV_CONNECTION_TO_SERVER_FAILED; SQLSTATE: HY000

Message: Could not connect to the OKV server

- Error number: MY-011389; Symbol: ER_KEYRING_OKV_FAILED_TO_REMOVE_KEY; SQLSTATE: HY000

Message: Could not remove the key

- Error number: MY-011390; Symbol: ER_KEYRING_OKV_FAILED_TO_ADD_ATTRIBUTE; SQLSTATE: HY000

Message: Could not add attribute, attribute_name=%s attribute value=%s

- Error number: MY-011391; Symbol: ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY; SQLSTATE: HY000

Message: Could not generate the key.

- Error number: MY-011392; Symbol: ER_KEYRING_OKV_FAILED_TO_STORE_KEY; SQLSTATE: HY000

Message: Could not store the key.

- Error number: MY-011393; Symbol: ER_KEYRING_OKV_FAILED_TO_ACTIVATE_KEYS; SQLSTATE: HY000

Message: Could not activate the key.

- Error number: MY-011394; Symbol: ER_KEYRING_OKV_FAILED_TO_FETCH_KEY; SQLSTATE: HY000

Message: Could not fetch generated key

- Error number: MY-011395; Symbol: ER_KEYRING_OKV_FAILED_TO_STORE_OR_GENERATE_KEY; SQLSTATE: HY000

Message: Could not store/generate the key - failed to set key attribute x-key-ready

-
- Error number: `MY-011396`; Symbol: `ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY_SIGNATURE`; SQLSTATE: `HY000`

Message: Could not retrieve key signature from custom attributes

- Error number: `MY-011397`; Symbol: `ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY`; SQLSTATE: `HY000`

Message: Could not retrieve key from OKV

- Error number: `MY-011398`; Symbol: `ER_KEYRING_OKV_FAILED_TO_LOAD_SSL_TRUST_STORE`; SQLSTATE: `HY000`

Message: Error loading trust store

- Error number: `MY-011399`; Symbol: `ER_KEYRING_OKV_FAILED_TO_SET_CERTIFICATE_FILE`; SQLSTATE: `HY000`

Message: Error setting the certificate file.

- Error number: `MY-011400`; Symbol: `ER_KEYRING_OKV_FAILED_TO_SET_KEY_FILE`; SQLSTATE: `HY000`

Message: Error setting the key file.

- Error number: `MY-011401`; Symbol: `ER_KEYRING_OKV_KEY_MISMATCH`; SQLSTATE: `HY000`

Message: Private key does not match the certificate public key

- Error number: `MY-011415`; Symbol: `ER_KEYRING_AWS_FAILED_TO_SET_CMK_ID`; SQLSTATE: `HY000`

Message: `keyring_aws_cmk_id` cannot be set to the new value as AWS KMS seems to not understand the id provided. Please check that CMK id provided is correct.

- Error number: `MY-011416`; Symbol: `ER_KEYRING_AWS_FAILED_TO_SET_REGION`; SQLSTATE: `HY000`

Message: `keyring_aws_region` cannot be set to the new value as AWS KMS seems to not understand the region provided. Please check that region provided is correct.

- Error number: `MY-011417`; Symbol: `ER_KEYRING_AWS_FAILED_TO_OPEN_CONF_FILE`; SQLSTATE: `HY000`

Message: Could not open `keyring_aws` configuration file: %s. OS returned this error: %s

- Error number: `MY-011418`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_ID_FROM_CONF_FILE`; SQLSTATE: `HY000`

Message: Could not read AWS access key id from `keyring_aws` configuration file: %s. OS returned this error: %s

- Error number: `MY-011419`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_FROM_CONF_FILE`; SQLSTATE: `HY000`

Message: Could not read AWS access key from `keyring_aws` configuration file: %s. OS returned this error: %s

-
- Error number: `MY-011420`; Symbol: `ER_KEYRING_AWS_INVALID_CONF_FILE_PATH`; SQLSTATE: `HY000`
Message: Path to keyring aws configuration file cannot be empty
 - Error number: `MY-011421`; Symbol: `ER_KEYRING_AWS_INVALID_DATA_FILE_PATH`; SQLSTATE: `HY000`
Message: Path to keyring_aws storage file cannot be empty.
 - Error number: `MY-011422`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DIR`; SQLSTATE: `HY000`
Message: Unable to create/access keyring directory.
 - Error number: `MY-011423`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYRING_DATA_FILE`; SQLSTATE: `HY000`
Message: Unable to create/access keyring_aws storage file. Please check if keyring_aws_data_file points to location where keyring file can be created/accessed. Please also make sure that MySQL server's user has high enough privileges to access this location.
 - Error number: `MY-011424`; Symbol: `ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_INTERNAL_ERROR`; SQLSTATE: `HY000`
Message: keyring_aws initialization failed due to internal error when initializing synchronization primitive - %s. OS returned this error: %s:
 - Error number: `MY-011425`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ACCESS_DATA_FILE`; SQLSTATE: `HY000`
Message: Could not access keyring_aws storage file in the path provided. Please check if the keyring_aws directory can be accessed by MySQL Server
 - Error number: `MY-011426`; Symbol: `ER_KEYRING_AWS_CMK_ID_NOT_SET`; SQLSTATE: `HY000`
Message: keyring_aws_cmk_id has to be set
 - Error number: `MY-011427`; Symbol: `ER_KEYRING_AWS_FAILED_TO_GET_KMS_CREDENTIAL_FROM_CONF_FILE`; SQLSTATE: `HY000`
Message: Could not get AWS KMS credentials from the configuration file
 - Error number: `MY-011428`; Symbol: `ER_KEYRING_AWS_INIT_FAILURE`; SQLSTATE: `HY000`
Message: keyring_aws initialization failure.
 - Error number: `MY-011429`; Symbol: `ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_PLUGIN_INTERNAL_ERROR`; SQLSTATE: `HY000`
Message: keyring_aws initialization failure due to internal exception inside the plugin
 - Error number: `MY-011430`; Symbol: `ER_KEYRING_AWS_INVALID_KEY_LENGTH_FOR_CIPHER`; SQLSTATE: `HY000`
Message: Invalid key length for given block cipher
 - Error number: `MY-011431`; Symbol: `ER_KEYRING_AWS_FAILED_TO_GENERATE_KEY_DUE_TO_INTERNAL_ERROR`; SQLSTATE: `HY000`

Message: Failed to generate a key due to internal exception inside keyring_file plugin

- Error number: `MY-011432`; Symbol: `ER_KEYRING_AWS_INCORRECT_FILE`; SQLSTATE: `HY000`

Message: Incorrect Keyring file

- Error number: `MY-011433`; Symbol: `ER_KEYRING_AWS_FOUND_MALFORMED_BACKUP_FILE`; SQLSTATE: `HY000`

Message: Found malformed keyring backup file - removing it

- Error number: `MY-011434`; Symbol: `ER_KEYRING_AWS_FAILED_TO_RESTORE_FROM_BACKUP_FILE`; SQLSTATE: `HY000`

Message: Error while restoring keyring from backup file cannot overwrite keyring with backup

- Error number: `MY-011435`; Symbol: `ER_KEYRING_AWS_FAILED_TO_FLUSH_KEYRING_TO_FILE`; SQLSTATE: `HY000`

Message: Error while flushing in-memory keyring into keyring file

- Error number: `MY-011436`; Symbol: `ER_KEYRING_AWS_INCORRECT_REGION`; SQLSTATE: `HY000`

Message: Wrong region

- Error number: `MY-011437`; Symbol: `ER_KEYRING_AWS_FAILED_TO_CONNECT_KMS`; SQLSTATE: `HY000`

Message: Could not connect to AWS KMS with the credentials provided. Please make sure they are correct. AWS KMS returned this error: %s

- Error number: `MY-011438`; Symbol: `ER_KEYRING_AWS_FAILED_TO_GENERATE_NEW_KEY`; SQLSTATE: `HY000`

Message: Could not generate a new key. AWS KMS returned this error: %s

- Error number: `MY-011439`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ENCRYPT_KEY`; SQLSTATE: `HY000`

Message: Could not encrypt key. AWS KMS returned this error: %s

- Error number: `MY-011440`; Symbol: `ER_KEYRING_AWS_FAILED_TO_RE_ENCRYPT_KEY`; SQLSTATE: `HY000`

Message: Could not re-encrypt key. AWS KMS returned this error: %s

- Error number: `MY-011441`; Symbol: `ER_KEYRING_AWS_FAILED_TO_DECRYPT_KEY`; SQLSTATE: `HY000`

Message: Could not decrypt key. AWS KMS returned this error: %s

- Error number: `MY-011442`; Symbol: `ER_KEYRING_AWS_FAILED_TO_ROTATE_CMK`; SQLSTATE: `HY000`

Message: Could not rotate the CMK. AWS KMS returned this error: %s

- Error number: `MY-011443`; Symbol: `ER_GRP_RPL_GTID_ALREADY_USED`; SQLSTATE: `HY000`

Message: The requested GTID '%s:%lld' was already used, the transaction will rollback.

- Error number: [MY-011444](#); Symbol: [ER_GRP_RPL_APPLIER_THD_KILLED](#); SQLSTATE: [HY000](#)

Message: The group replication applier thread was killed.

- Error number: [MY-011445](#); Symbol: [ER_GRP_RPL_EVENT_HANDLING_ERROR](#); SQLSTATE: [HY000](#)

Message: Error at event handling! Got error: %d.

- Error number: [MY-011446](#); Symbol: [ER_GRP_RPL_ERROR_GTID_EXECUTION_INFO](#); SQLSTATE: [HY000](#)

Message: Error when extracting group GTID execution information, some recovery operations may face future issues.

- Error number: [MY-011448](#); Symbol: [ER_GRP_RPL_CREATE_APPLIER_CACHE_ERROR](#); SQLSTATE: [HY000](#)

Message: Failed to create group replication pipeline applier cache!

- Error number: [MY-011449](#); Symbol: [ER_GRP_RPL_UNBLOCK_WAITING_THD](#); SQLSTATE: [HY000](#)

Message: Unblocking the group replication thread waiting for applier to start, as the start group replication was killed.

- Error number: [MY-011450](#); Symbol: [ER_GRP_RPL_APPLIER_PIPELINE_NOT_DISPOSED](#); SQLSTATE: [HY000](#)

Message: The group replication applier pipeline was not properly disposed. Check the error log for further info.

- Error number: [MY-011451](#); Symbol: [ER_GRP_RPL_APPLIER_THD_EXECUTION_ABORTED](#); SQLSTATE: [HY000](#)

Message: The applier thread execution was aborted. Unable to process more transactions, this member will now leave the group.

- Error number: [MY-011452](#); Symbol: [ER_GRP_RPL_APPLIER_EXECUTION_FATAL_ERROR](#); SQLSTATE: [HY000](#)

Message: Fatal error during execution on the Applier process of Group Replication. The server will now leave the group.

- Error number: [MY-011453](#); Symbol: [ER_GRP_RPL_ERROR_STOPPING_CHANNELS](#); SQLSTATE: [HY000](#)

Message: Error stopping all replication channels while server was leaving the group. %s

- Error number: [MY-011454](#); Symbol: [ER_GRP_RPL_ERROR_SENDING_SINGLE_PRIMARY_MSSG](#); SQLSTATE: [HY000](#)

Message: Error sending single primary message informing that primary did apply relay logs.

- Error number: [MY-011457](#); Symbol: [ER_GRP_RPL_BROADCAST_COMMIT_TRANS_MSSG_FAILED](#); SQLSTATE: [HY000](#)

Message: Broadcast of committed transactions message failed.

-
- Error number: [MY-011458](#); Symbol: [ER_GRP_RPL_GROUP_NAME_PARSE_ERROR](#); SQLSTATE: [HY000](#)
Message: Unable to parse the group_replication_group_name during the Certification module initialization.
 - Error number: [MY-011459](#); Symbol: [ER_GRP_RPL_ADD_GRPSID_TO_GRPGTIDSID_MAP_ERROR](#); SQLSTATE: [HY000](#)
Message: Unable to add the group_sid in the group_gtid_sid_map during the Certification module initialization.
 - Error number: [MY-011460](#); Symbol: [ER_GRP_RPL_UPDATE_GRPGTID_EXECUTED_ERROR](#); SQLSTATE: [HY000](#)
Message: Error updating group_gtid_executed GTID set during the Certification module initialization.
 - Error number: [MY-011461](#); Symbol: [ER_GRP_RPL_DONOR_TRANS_INFO_ERROR](#); SQLSTATE: [HY000](#)
Message: Unable to handle the donor's transaction information when initializing the conflict detection component. Possible out of memory error.
 - Error number: [MY-011462](#); Symbol: [ER_GRP_RPL_SERVER_CONN_ERROR](#); SQLSTATE: [HY000](#)
Message: Error when establishing a server connection during the Certification module initialization.
 - Error number: [MY-011463](#); Symbol: [ER_GRP_RPL_ERROR_FETCHING_GTID_EXECUTED_SET](#); SQLSTATE: [HY000](#)
Message: Error when extracting this member GTID executed set. Certification module can't be properly initialized.
 - Error number: [MY-011464](#); Symbol: [ER_GRP_RPL_ADD_GTID_TO_GRPGTID_EXECUTED_ERROR](#); SQLSTATE: [HY000](#)
Message: Error while adding the server GTID EXECUTED set to the group_gtid_execute during the Certification module initialization.
 - Error number: [MY-011465](#); Symbol: [ER_GRP_RPL_ERROR_FETCHING_GTID_SET](#); SQLSTATE: [HY000](#)
Message: Error when extracting this member retrieved set for its applier. Certification module can't be properly initialized.
 - Error number: [MY-011466](#); Symbol: [ER_GRP_RPL_ADD_RETRIEVED_SET_TO_GRP_GTID_EXECUTED_ERROR](#); SQLSTATE: [HY000](#)
Message: Error while adding the member retrieved set to the group_gtid_executed during the Certification module initialization.
 - Error number: [MY-011467](#); Symbol: [ER_GRP_RPL_CERTIFICATION_INITIALIZATION_FAILURE](#); SQLSTATE: [HY000](#)
Message: Error during Certification module initialization.
 - Error number: [MY-011468](#); Symbol: [ER_GRP_RPL_UPDATE_LAST_CONFLICT_FREE_TRANS_ERROR](#); SQLSTATE: [HY000](#)
Message: Unable to update last conflict free transaction, this transaction will not be tracked on performance_schema.replication_group_member_stats.last_conflict_free_transaction.

-
- Error number: [MY-011469](#); Symbol: [ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_REF_VER_ERROR](#); SQLSTATE: [HY000](#)
Message: Error updating transaction snapshot version reference for internal storage.
 - Error number: [MY-011472](#); Symbol: [ER_GRP_RPL_CANT_GENERATE_GTID](#); SQLSTATE: [HY000](#)
Message: Impossible to generate Global Transaction Identifier: the integer component reached the maximal value. Restart the group with a new group_replication_group_name.
 - Error number: [MY-011473](#); Symbol: [ER_GRP_RPL_INVALID_GTID_SET](#); SQLSTATE: [HY000](#)
Message: Invalid stable transactions set.
 - Error number: [MY-011474](#); Symbol: [ER_GRP_RPL_UPDATE_GTID_SET_ERROR](#); SQLSTATE: [HY000](#)
Message: Error updating stable transactions set.
 - Error number: [MY-011475](#); Symbol: [ER_GRP_RPL_RECEIVED_SET_MISSING_GTIDS](#); SQLSTATE: [HY000](#)
Message: There was an error when filling the missing GTIDs on the applier channel received set. Despite not critical, on the long run this may cause performance issues.
 - Error number: [MY-011477](#); Symbol: [ER_GRP_RPL_NULL_PACKET](#); SQLSTATE: [HY000](#)
Message: Null packet on certifier's queue.
 - Error number: [MY-011478](#); Symbol: [ER_GRP_RPL_CANT_READ_GTID](#); SQLSTATE: [HY000](#)
Message: Error reading GTIDs from the message.
 - Error number: [MY-011479](#); Symbol: [ER_GRP_RPL_PROCESS_GTID_SET_ERROR](#); SQLSTATE: [HY000](#)
Message: Error processing stable transactions set.
 - Error number: [MY-011480](#); Symbol: [ER_GRP_RPL_PROCESS_INTERSECTION_GTID_SET_ERROR](#); SQLSTATE: [HY000](#)
Message: Error processing intersection of stable transactions set.
 - Error number: [MY-011481](#); Symbol: [ER_GRP_RPL_SET_STABLE_TRANS_ERROR](#); SQLSTATE: [HY000](#)
Message: Error setting stable transactions set.
 - Error number: [MY-011482](#); Symbol: [ER_GRP_RPL_CANT_READ_GRP_GTID_EXTRACTED](#); SQLSTATE: [HY000](#)
Message: Error reading group_gtid_extracted from the View_change_log_event.
 - Error number: [MY-011483](#); Symbol: [ER_GRP_RPL_CANT_READ_WRITE_SET_ITEM](#); SQLSTATE: [HY000](#)
Message: Error reading the write set item '%s' from the View_change_log_event.
 - Error number: [MY-011484](#); Symbol: [ER_GRP_RPL_INIT_CERTIFICATION_INFO_FAILURE](#); SQLSTATE: [HY000](#)
Message: Error during certification_info initialization.

-
- Error number: [MY-011485](#); Symbol: [ER_GRP_RPL_CONFLICT_DETECTION_DISABLED](#); SQLSTATE: [HY000](#)
Message: Primary had applied all relay logs, disabled conflict detection.
 - Error number: [MY-011486](#); Symbol: [ER_GRP_RPL_MSG_DISCARDED](#); SQLSTATE: [HY000](#)
Message: Message received while the plugin is not ready, message discarded.
 - Error number: [MY-011487](#); Symbol: [ER_GRP_RPL_MISSING_GRP_RPL_APPLIER](#); SQLSTATE: [HY000](#)
Message: Message received without a proper group replication applier.
 - Error number: [MY-011488](#); Symbol: [ER_GRP_RPL_CERTIFIER_MSSG_PROCESS_ERROR](#); SQLSTATE: [HY000](#)
Message: Error processing message in Certifier.
 - Error number: [MY-011489](#); Symbol: [ER_GRP_RPL_SRV_NOT_ONLINE](#); SQLSTATE: [HY000](#)
Message: This server was not declared online since it is on status %s.
 - Error number: [MY-011490](#); Symbol: [ER_GRP_RPL_SRV_ONLINE](#); SQLSTATE: [HY000](#)
Message: This server was declared online within the replication group.
 - Error number: [MY-011491](#); Symbol: [ER_GRP_RPL_DISABLE_SRV_READ_MODE_RESTRICTED](#); SQLSTATE: [HY000](#)
Message: When declaring the plugin online it was not possible to disable the server read mode settings. Try to disable it manually.
 - Error number: [MY-011492](#); Symbol: [ER_GRP_RPL_MEM_ONLINE](#); SQLSTATE: [HY000](#)
Message: The member with address %s:%u was declared online within the replication group.
 - Error number: [MY-011493](#); Symbol: [ER_GRP_RPL_MEM_UNREACHABLE](#); SQLSTATE: [HY000](#)
Message: Member with address %s:%u has become unreachable.
 - Error number: [MY-011494](#); Symbol: [ER_GRP_RPL_MEM_REACHABLE](#); SQLSTATE: [HY000](#)
Message: Member with address %s:%u is reachable again.
 - Error number: [MY-011495](#); Symbol: [ER_GRP_RPL_SRV_BLOCKED](#); SQLSTATE: [HY000](#)
Message: This server is not able to reach a majority of members in the group. This server will now block all updates. The server will remain blocked until contact with the majority is restored. It is possible to use `group_replication_force_members` to force a new group membership.
 - Error number: [MY-011496](#); Symbol: [ER_GRP_RPL_SRV_BLOCKED_FOR_SECS](#); SQLSTATE: [HY000](#)
Message: This server is not able to reach a majority of members in the group. This server will now block all updates. The server will remain blocked for the next %lu seconds. Unless contact with the majority is restored, after this time the member will error out and leave the group. It is possible to use `group_replication_force_members` to force a new group membership.
 - Error number: [MY-011497](#); Symbol: [ER_GRP_RPL_CHANGE_GRP_MEM_NOT_PROCESSED](#); SQLSTATE: [HY000](#)

Message: A group membership change was received but the plugin is already leaving due to the configured timeout on group_replication_unreachable_majority_timeout option.

- Error number: [MY-011498](#); Symbol: [ER_GRP_RPL_MEMBER_CONTACT_RESTORED](#); SQLSTATE: [HY000](#)

Message: The member has resumed contact with a majority of the members in the group. Regular operation is restored and transactions are unblocked.

- Error number: [MY-011499](#); Symbol: [ER_GRP_RPL_MEMBER_REMOVED](#); SQLSTATE: [HY000](#)

Message: Members removed from the group: %s

- Error number: [MY-011500](#); Symbol: [ER_GRP_RPL_PRIMARY_MEMBER_LEFT_GRP](#); SQLSTATE: [HY000](#)

Message: Primary server with address %s left the group. Electing new Primary.

- Error number: [MY-011501](#); Symbol: [ER_GRP_RPL_MEMBER_ADDED](#); SQLSTATE: [HY000](#)

Message: Members joined the group: %s

- Error number: [MY-011502](#); Symbol: [ER_GRP_RPL_MEMBER_EXIT_PLUGIN_ERROR](#); SQLSTATE: [HY000](#)

Message: There was a previous plugin error while the member joined the group. The member will now exit the group.

- Error number: [MY-011503](#); Symbol: [ER_GRP_RPL_MEMBER_CHANGE](#); SQLSTATE: [HY000](#)

Message: Group membership changed to %s on view %s.

- Error number: [MY-011504](#); Symbol: [ER_GRP_RPL_MEMBER_LEFT_GRP](#); SQLSTATE: [HY000](#)

Message: Group membership changed: This member has left the group.

- Error number: [MY-011505](#); Symbol: [ER_GRP_RPL_MEMBER_EXPELLED](#); SQLSTATE: [HY000](#)

Message: Member was expelled from the group due to network failures, changing member status to ERROR.

- Error number: [MY-011506](#); Symbol: [ER_GRP_RPL_SESSION_OPEN_FAILED](#); SQLSTATE: [HY000](#)

Message: Unable to open session to (re)set read only mode. Skipping.

- Error number: [MY-011507](#); Symbol: [ER_GRP_RPL_NEW_PRIMARY_ELECTED](#); SQLSTATE: [HY000](#)

Message: A new primary with address %s:%u was elected. %s

- Error number: [MY-011508](#); Symbol: [ER_GRP_RPL_DISABLE_READ_ONLY_FAILED](#); SQLSTATE: [HY000](#)

Message: Unable to disable super read only flag. Try to disable it manually

- Error number: [MY-011509](#); Symbol: [ER_GRP_RPL_ENABLE_READ_ONLY_FAILED](#); SQLSTATE: [HY000](#)

Message: Unable to set super read only flag. Try to set it manually.

- Error number: [MY-011510](#); Symbol: [ER_GRP_RPL_SRV_PRIMARY_MEM](#); SQLSTATE: [HY000](#)

Message: This server is working as primary member.

-
- Error number: [MY-011511](#); Symbol: [ER_GRP_RPL_SRV_SECONDARY_MEM](#); SQLSTATE: [HY000](#)
Message: This server is working as secondary member with primary member address %s:%u.
 - Error number: [MY-011512](#); Symbol: [ER_GRP_RPL_NO_SUITABLE_PRIMARY_MEM](#); SQLSTATE: [HY000](#)
Message: Unable to set any member as primary. No suitable candidate.
 - Error number: [MY-011513](#); Symbol: [ER_GRP_RPL_SUPER_READ_ONLY_ACTIVATE_ERROR](#); SQLSTATE: [HY000](#)
Message: Error when activating super_read_only mode on start. The member will now exit the group.
 - Error number: [MY-011514](#); Symbol: [ER_GRP_RPL_EXCEEDS_AUTO_INC_VALUE](#); SQLSTATE: [HY000](#)
Message: Group contains %lu members which is greater than group_replication_auto_increment_increment value of %lu. This can lead to a higher transactional abort rate.
 - Error number: [MY-011515](#); Symbol: [ER_GRP_RPL_DATA_NOT_PROVIDED_BY_MEM](#); SQLSTATE: [HY000](#)
Message: Member with address '%s:%u' didn't provide any data during the last group change. Group information can be outdated and lead to errors on recovery.
 - Error number: [MY-011516](#); Symbol: [ER_GRP_RPL_MEMBER_ALREADY_EXISTS](#); SQLSTATE: [HY000](#)
Message: There is already a member with server_uuid %s. The member will now exit the group.
 - Error number: [MY-011518](#); Symbol: [ER_GRP_RPL_GTID_EXECUTED_EXTRACT_ERROR](#); SQLSTATE: [HY000](#)
Message: Error when extracting this member GTID executed set. Operations and checks made to group joiners may be incomplete.
 - Error number: [MY-011519](#); Symbol: [ER_GRP_RPL_GTID_SET_EXTRACT_ERROR](#); SQLSTATE: [HY000](#)
Message: Error when extracting this member retrieved set for its applier. Operations and checks made to group joiners may be incomplete.
 - Error number: [MY-011520](#); Symbol: [ER_GRP_RPL_START_FAILED](#); SQLSTATE: [HY000](#)
Message: The START GROUP_REPLICATION command failed since the group already has 9 members.
 - Error number: [MY-011521](#); Symbol: [ER_GRP_RPL_MEMBER_VER_INCOMPATIBLE](#); SQLSTATE: [HY000](#)
Message: Member version is incompatible with the group.
 - Error number: [MY-011522](#); Symbol: [ER_GRP_RPL_TRANS_NOT_PRESENT_IN_GRP](#); SQLSTATE: [HY000](#)
Message: The member contains transactions not present in the group. The member will now exit the group.
 - Error number: [MY-011523](#); Symbol: [ER_GRP_RPL_TRANS_GREATER_THAN_GRP](#); SQLSTATE: [HY000](#)
Message: It was not possible to assess if the member has more transactions than the group. The member will now exit the group.

-
- Error number: [MY-011524](#); Symbol: [ER_GRP_RPL_MEMBER_VERSION_LOWER_THAN_GRP](#); SQLSTATE: [HY000](#)

Message: Member version is lower than some group member, but since option 'group_replication_allow_local_lower_version_join' is enabled, member will be allowed to join.
 - Error number: [MY-011525](#); Symbol: [ER_GRP_RPL_LOCAL_GTID_SETS_PROCESS_ERROR](#); SQLSTATE: [HY000](#)

Message: Error processing local GTID sets when comparing this member transactions against the group.
 - Error number: [MY-011526](#); Symbol: [ER_GRP_RPL_MEMBER_TRANS_GREATER_THAN_GRP](#); SQLSTATE: [HY000](#)

Message: This member has more executed transactions than those present in the group. Local transactions: %s > Group transactions: %s
 - Error number: [MY-011527](#); Symbol: [ER_GRP_RPL_BLOCK_SIZE_DIFF_FROM_GRP](#); SQLSTATE: [HY000](#)

Message: The member is configured with a group_replication_gtid_assignment_block_size option value '%llu' different from the group '%llu'. The member will now exit the group.
 - Error number: [MY-011528](#); Symbol: [ER_GRP_RPL_TRANS_WRITE_SET_EXTRACT_DIFF_FROM_GRP](#); SQLSTATE: [HY000](#)

Message: The member is configured with a transaction-write-set-extraction option value '%s' different from the group '%s'. The member will now exit the group.
 - Error number: [MY-011529](#); Symbol: [ER_GRP_RPL_MEMBER_CFG_INCOMPATIBLE_WITH_GRP_CFG](#); SQLSTATE: [HY000](#)

Message: The member configuration is not compatible with the group configuration. Variables such as group_replication_single_primary_mode or group_replication_enforce_update_everywhere_checks must have the same value on every server in the group. (member configuration option: [%s], group configuration option: [%s]).
 - Error number: [MY-011530](#); Symbol: [ER_GRP_RPL_MEMBER_STOP_RPL_CHANNELS_ERROR](#); SQLSTATE: [HY000](#)

Message: Error stopping all replication channels while server was leaving the group. %s
 - Error number: [MY-011531](#); Symbol: [ER_GRP_RPL_PURGE_APPLIERS_LOGS](#); SQLSTATE: [HY000](#)

Message: Detected previous RESET BINARY LOGS AND GTIDS invocation or an issue exists in the group replication applier relay log. Purging existing applier logs.
 - Error number: [MY-011532](#); Symbol: [ER_GRP_RPL_RESET_APPLIERS_MODULE_LOGS_ERROR](#); SQLSTATE: [HY000](#)

Message: Unknown error occurred while resetting applier's module logs.
 - Error number: [MY-011533](#); Symbol: [ER_GRP_RPL_APPLIERS_THD_SETUP_ERROR](#); SQLSTATE: [HY000](#)

Message: Failed to setup the group replication applier thread.
 - Error number: [MY-011534](#); Symbol: [ER_GRP_RPL_APPLIERS_THD_START_ERROR](#); SQLSTATE: [HY000](#)

Message: Error while starting the group replication applier thread

- Error number: [MY-011535](#); Symbol: [ER_GRP_RPL_APPLIER_THD_STOP_ERROR](#); SQLSTATE: [HY000](#)

Message: Failed to stop the group replication applier thread.

- Error number: [MY-011536](#); Symbol: [ER_GRP_RPL_FETCH_TRANS_DATA_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to fetch transaction data containing required transaction info for applier

- Error number: [MY-011537](#); Symbol: [ER_GRP_RPL_REPLICA_IO_THD_PRIMARY_UNKNOWN](#); SQLSTATE: [HY000](#)

Message: Can't start replica IO THREAD of channel '%s' when group replication is running with single-primary mode and the primary member is not known.

- Error number: [MY-011538](#); Symbol: [ER_GRP_RPL_SALVE_IO_THD_ON_SECONDARY_MEMBER](#); SQLSTATE: [HY000](#)

Message: Can't start replica IO THREAD of channel '%s' when group replication is running with single-primary mode on a secondary member.

- Error number: [MY-011539](#); Symbol: [ER_GRP_RPL_REPLICA_SQL_THD_PRIMARY_UNKNOWN](#); SQLSTATE: [HY000](#)

Message: Can't start replica SQL THREAD of channel '%s' when group replication is running with single-primary mode and the primary member is not known.

- Error number: [MY-011540](#); Symbol: [ER_GRP_RPL_REPLICA_SQL_THD_ON_SECONDARY_MEMBER](#); SQLSTATE: [HY000](#)

Message: Can't start replica SQL THREAD of channel '%s' when group replication is running with single-primary mode on a secondary member.

- Error number: [MY-011541](#); Symbol: [ER_GRP_RPL_NEEDS_INNO_DB_TABLE](#); SQLSTATE: [HY000](#)

Message: Table %s does not use the InnoDB storage engine. This is not compatible with Group Replication.

- Error number: [MY-011542](#); Symbol: [ER_GRP_RPL_PRIMARY_KEY_NOT_DEFINED](#); SQLSTATE: [HY000](#)

Message: Table %s does not have any PRIMARY KEY. This is not compatible with Group Replication.

- Error number: [MY-011543](#); Symbol: [ER_GRP_RPL_FK_WITH_CASCADE_UNSUPPORTED](#); SQLSTATE: [HY000](#)

Message: Table %s has a foreign key with 'CASCADE', 'SET NULL' or 'SET DEFAULT' clause. This is not compatible with Group Replication.

- Error number: [MY-011544](#); Symbol: [ER_GRP_RPL_AUTO_INC_RESET](#); SQLSTATE: [HY000](#)

Message: group_replication_auto_increment_increment is reset to %lu

- Error number: [MY-011545](#); Symbol: [ER_GRP_RPL_AUTO_INC_OFFSET_RESET](#); SQLSTATE: [HY000](#)

Message: auto_increment_offset is reset to %lu

- Error number: [MY-011546](#); Symbol: [ER_GRP_RPL_AUTO_INC_SET](#); SQLSTATE: [HY000](#)

Message: group_replication_auto_increment_increment is set to %lu

- Error number: `MY-011547`; Symbol: `ER_GRP_RPL_AUTO_INC_OFFSET_SET`; SQLSTATE: `HY000`

Message: auto_increment_offset is set to %lu

- Error number: `MY-011548`; Symbol: `ER_GRP_RPL_FETCH_TRANS_CONTEXT_FAILED`; SQLSTATE: `HY000`

Message: Failed to fetch transaction context containing required transaction info for certification

- Error number: `MY-011549`; Symbol: `ER_GRP_RPL_FETCH_FORMAT_DESC_LOG_EVENT_FAILED`; SQLSTATE: `HY000`

Message: Failed to fetch Format_description_log_event containing required server info for applier

- Error number: `MY-011550`; Symbol: `ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FAILED`; SQLSTATE: `HY000`

Message: Failed to fetch Transaction_context_log_event containing required transaction info for certification

- Error number: `MY-011551`; Symbol: `ER_GRP_RPL_FETCH_SNAPSHOT_VERSION_FAILED`; SQLSTATE: `HY000`

Message: Failed to read snapshot version from transaction context event required for certification

- Error number: `MY-011552`; Symbol: `ER_GRP_RPL_FETCH_GTID_LOG_EVENT_FAILED`; SQLSTATE: `HY000`

Message: Failed to fetch Gtid_log_event containing required transaction info for certification

- Error number: `MY-011553`; Symbol: `ER_GRP_RPL_UPDATE_SERV_CERTIFICATE_FAILED`; SQLSTATE: `HY000`

Message: Unable to update certification result on server side, thread_id: %lu

- Error number: `MY-011554`; Symbol: `ER_GRP_RPL_ADD_GTID_INFO_WITH_LOCAL_GTID_FAILED`; SQLSTATE: `HY000`

Message: Unable to add gtid information to the group_gtid_executed set when gtid was provided for local transactions

- Error number: `MY-011555`; Symbol: `ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_LOCAL_GTID_FAILED`; SQLSTATE: `HY000`

Message: Unable to add gtid information to the group_gtid_executed set when no gtid was provided for local transactions

- Error number: `MY-011556`; Symbol: `ER_GRP_RPL_NOTIFY_CERTIFICATION_OUTCOME_FAILED`; SQLSTATE: `HY000`

Message: Failed to notify certification outcome

-
- Error number: [MY-011557](#); Symbol: [ER_GRP_RPL_ADD_GTID_INFO_WITH_REMOTE_GTID_FAILED](#); SQLSTATE: [HY000](#)
Message: Unable to add gtid information to the group_gtid_executed set when gtid was provided for remote transactions
 - Error number: [MY-011558](#); Symbol: [ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_REMOTE_GTID_FAILED](#); SQLSTATE: [HY000](#)
Message: Unable to add gtid information to the group_gtid_executed set when gtid was not provided for remote transactions
 - Error number: [MY-011559](#); Symbol: [ER_GRP_RPL_FETCH_VIEW_CHANGE_LOG_EVENT_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to fetch View_change_log_event containing required info for certification
 - Error number: [MY-011562](#); Symbol: [ER_GRP_RPL_FETCH_LOG_EVENT_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to fetch Log_event containing required server info for applier
 - Error number: [MY-011563](#); Symbol: [ER_GRP_RPL_START_GRP_RPL_FAILED](#); SQLSTATE: [HY000](#)
Message: Unable to start Group Replication. Replication applier infrastructure is not initialized since the server was started with --initialize, --initialize-insecure or --upgrade=MINIMAL on a server upgrade.
 - Error number: [MY-011564](#); Symbol: [ER_GRP_RPL_CONN_INTERNAL_PLUGIN_FAIL](#); SQLSTATE: [HY000](#)
Message: Failed to establish an internal server connection to execute plugin operations
 - Error number: [MY-011565](#); Symbol: [ER_GRP_RPL_SUPER_READ_ON](#); SQLSTATE: [HY000](#)
Message: Setting super_read_only=ON.
 - Error number: [MY-011566](#); Symbol: [ER_GRP_RPL_SUPER_READ_OFF](#); SQLSTATE: [HY000](#)
Message: Setting super_read_only=OFF.
 - Error number: [MY-011567](#); Symbol: [ER_GRP_RPL_KILLED_SESSION_ID](#); SQLSTATE: [HY000](#)
Message: killed session id: %d status: %d
 - Error number: [MY-011568](#); Symbol: [ER_GRP_RPL_KILLED_FAILED_ID](#); SQLSTATE: [HY000](#)
Message: killed failed id: %d failed: %d
 - Error number: [MY-011569](#); Symbol: [ER_GRP_RPL_INTERNAL_QUERY](#); SQLSTATE: [HY000](#)
Message: Internal query: %s result in error. Error number: %ld
 - Error number: [MY-011570](#); Symbol: [ER_GRP_RPL_COPY_FROM_EMPTY_STRING](#); SQLSTATE: [HY000](#)
Message: Error copying from empty string
 - Error number: [MY-011571](#); Symbol: [ER_GRP_RPL_QUERY_FAIL](#); SQLSTATE: [HY000](#)
Message: Query execution resulted in failure. errno: %d
 - Error number: [MY-011572](#); Symbol: [ER_GRP_RPL_CREATE_SESSION_UNABLE](#); SQLSTATE: [HY000](#)

Message: Unable to create a session for executing the queries on the server

- Error number: `MY-011573`; Symbol: `ER_GRP_RPL_MEMBER_NOT_FOUND`; SQLSTATE: `HY000`

Message: The member with address %s:%u has unexpectedly disappeared, killing the current group replication recovery connection

- Error number: `MY-011574`; Symbol: `ER_GRP_RPL_MAXIMUM_CONNECTION_RETRIES_REACHED`; SQLSTATE: `HY000`

Message: Maximum number of retries when trying to connect to a donor reached. Aborting group replication incremental recovery.

- Error number: `MY-011575`; Symbol: `ER_GRP_RPL_ALL_DONORS_LEFT_ABORT_RECOVERY`; SQLSTATE: `HY000`

Message: All donors left. Aborting group replication incremental recovery.

- Error number: `MY-011576`; Symbol: `ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_DONOR`; SQLSTATE: `HY000`

Message: Establishing group recovery connection with a possible donor. Attempt %d/%d

- Error number: `MY-011577`; Symbol: `ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_ANOTHER_DONOR`; SQLSTATE: `HY000`

Message: Retrying group recovery connection with another donor. Attempt %d/%d

- Error number: `MY-011578`; Symbol: `ER_GRP_RPL_NO_VALID_DONOR`; SQLSTATE: `HY000`

Message: No valid donors exist in the group, retrying

- Error number: `MY-011579`; Symbol: `ER_GRP_RPL_CONFIG_RECOVERY`; SQLSTATE: `HY000`

Message: Error when configuring the asynchronous recovery channel connection to the donor.

- Error number: `MY-011580`; Symbol: `ER_GRP_RPL_ESTABLISHING_CONN_GRP_REC_DONOR`; SQLSTATE: `HY000`

Message: Establishing connection to a group replication recovery donor %s at %s port: %d.

- Error number: `MY-011581`; Symbol: `ER_GRP_RPL_CREATE_GRP_RPL_REC_CHANNEL`; SQLSTATE: `HY000`

Message: Error while creating the group replication recovery channel with donor %s at %s port: %d.

- Error number: `MY-011582`; Symbol: `ER_GRP_RPL_DONOR_SERVER_CONN`; SQLSTATE: `HY000`

Message: There was an error when connecting to the donor server. Please check that `group_replication_recovery` channel credentials and all `MEMBER_HOST` column values of `performance_schema.replication_group_members` table are correct and DNS resolvable.

- Error number: `MY-011583`; Symbol: `ER_GRP_RPL_CHECK_STATUS_TABLE`; SQLSTATE: `HY000`

Message: For details please check `performance_schema.replication_connection_status` table and error log messages of Replica I/O for channel `group_replication_recovery`.

- Error number: `MY-011584`; Symbol: `ER_GRP_RPL_STARTING_GRP_REC`; SQLSTATE: `HY000`

Message: Error while starting the group replication incremental recovery receiver/applier threads

- Error number: [MY-011585](#); Symbol: [ER_GRP_RPL_DONOR_CONN_TERMINATION](#); SQLSTATE: [HY000](#)

Message: Terminating existing group replication donor connection and purging the corresponding logs.

- Error number: [MY-011586](#); Symbol: [ER_GRP_RPL_STOPPING_GRP_REC](#); SQLSTATE: [HY000](#)

Message: Error when stopping the group replication incremental recovery's donor connection

- Error number: [MY-011587](#); Symbol: [ER_GRP_RPL_PURGE_REC](#); SQLSTATE: [HY000](#)

Message: Error when purging the group replication recovery's relay logs

- Error number: [MY-011588](#); Symbol: [ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_APPLIER](#); SQLSTATE: [HY000](#)

Message: Unable to kill the current group replication recovery donor connection after an applier error. Incremental recovery will shutdown.

- Error number: [MY-011589](#); Symbol: [ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_FAILOVER](#); SQLSTATE: [HY000](#)

Message: Unable to kill the current group replication recovery donor connection during failover. Incremental recovery will shutdown.

- Error number: [MY-011590](#); Symbol: [ER_GRP_RPL_FAILED_TO_NOTIFY_GRP_MEMBERSHIP_EVENT](#); SQLSTATE: [HY000](#)

Message: Unexpected error when notifying an internal component named %s regarding a group membership event.

- Error number: [MY-011591](#); Symbol: [ER_GRP_RPL_FAILED_TO_BROADCAST_GRP_MEMBERSHIP_NOTIFICATION](#); SQLSTATE: [HY000](#)

Message: An undefined error was found while broadcasting an internal group membership notification! This is likely to happen if your components or plugins are not properly loaded or are malfunctioning!

- Error number: [MY-011592](#); Symbol: [ER_GRP_RPL_FAILED_TO_BROADCAST_MEMBER_STATUS_NOTIFICATION](#); SQLSTATE: [HY000](#)

Message: An undefined error was found while broadcasting an internal group member status notification! This is likely to happen if your components or plugins are not properly loaded or are malfunctioning!

- Error number: [MY-011593](#); Symbol: [ER_GRP_RPL_OOM_FAILED_TO_GENERATE_IDENTIFICATION_HASH](#); SQLSTATE: [HY000](#)

Message: No memory to generate write identification hash

- Error number: [MY-011594](#); Symbol: [ER_GRP_RPL_WRITE_IDENT_HASH_BASE64_ENCODING_FAILED](#); SQLSTATE: [HY000](#)

Message: Base 64 encoding of the write identification hash failed

- Error number: [MY-011595](#); Symbol: [ER_GRP_RPL_INVALID_BINLOG_FORMAT](#); SQLSTATE: [HY000](#)

Message: Binlog format should be ROW for Group Replication

-
- Error number: [MY-011598](#); Symbol: [ER_GRP_RPL_UNSUPPORTED_TRANS_ISOLATION](#); SQLSTATE: [HY000](#)

Message: Transaction isolation level (tx_isolation) is set to SERIALIZABLE, which is not compatible with Group Replication
 - Error number: [MY-011599](#); Symbol: [ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_STOPPING](#); SQLSTATE: [HY000](#)

Message: Transaction cannot be executed while Group Replication is stopping.
 - Error number: [MY-011600](#); Symbol: [ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_RECOVERING](#); SQLSTATE: [HY000](#)

Message: Transaction cannot be executed while Group Replication is recovering. Try again when the server is ONLINE.
 - Error number: [MY-011601](#); Symbol: [ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_ERROR_STATE](#); SQLSTATE: [HY000](#)

Message: Transaction cannot be executed while Group Replication is on ERROR state. Check for errors and restart the plugin
 - Error number: [MY-011602](#); Symbol: [ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_OFFLINE_MODE](#); SQLSTATE: [HY000](#)

Message: Transaction cannot be executed while Group Replication is OFFLINE. Check for errors and restart the plugin
 - Error number: [MY-011603](#); Symbol: [ER_GRP_RPL_MULTIPLE_CACHE_TYPE_NOT_SUPPORTED_FOR_SESSION](#); SQLSTATE: [HY000](#)

Message: We can only use one cache type at a time on session %u
 - Error number: [MY-011604](#); Symbol: [ER_GRP_RPL_FAILED_TO_REINIT_BINLOG_CACHE_FOR_READ](#); SQLSTATE: [HY000](#)

Message: Failed to reinit binlog cache log for read on session %u
 - Error number: [MY-011605](#); Symbol: [ER_GRP_RPL_FAILED_TO_CREATE_TRANS_CONTEXT](#); SQLSTATE: [HY000](#)

Message: Failed to create the context of the current transaction on session %u
 - Error number: [MY-011606](#); Symbol: [ER_GRP_RPL_FAILED_TO_EXTRACT_TRANS_WRITE_SET](#); SQLSTATE: [HY000](#)

Message: Failed to extract the set of items written during the execution of the current transaction on session %u
 - Error number: [MY-011607](#); Symbol: [ER_GRP_RPL_FAILED_TO_GATHER_TRANS_WRITE_SET](#); SQLSTATE: [HY000](#)

Message: Failed to gather the set of items written during the execution of the current transaction on session %u
 - Error number: [MY-011608](#); Symbol: [ER_GRP_RPL_TRANS_SIZE_EXCEEDS_LIMIT](#); SQLSTATE: [HY000](#)
-

Message: Error on session %u. Transaction of size %llu exceeds specified limit %lu. To increase the limit please adjust group_replication_transaction_size_limit option.

- Error number: MY-011611; Symbol: ER_GRP_RPL_WRITE_TO_TRANSACTION_MESSAGE_FAILED; SQLSTATE: HY000

Message: Error while writing to transaction message on session %u

- Error number: MY-011612; Symbol: ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_OUTCOME_NOTIFICATION; SQLSTATE: HY000

Message: Unable to register for getting notifications regarding the outcome of the transaction on session %u

- Error number: MY-011613; Symbol: ER_GRP_RPL_MSG_TOO_LONG_BROADCASTING_TRANS_FAILED; SQLSTATE: HY000

Message: Error broadcasting transaction to the group on session %u. Message is too big.

- Error number: MY-011614; Symbol: ER_GRP_RPL_BROADCASTING_TRANS_TO_GRP_FAILED; SQLSTATE: HY000

Message: Error while broadcasting the transaction to the group on session %u

- Error number: MY-011615; Symbol: ER_GRP_RPL_ERROR_WHILE_WAITING_FOR_CONFLICT_DETECTION; SQLSTATE: HY000

Message: Error while waiting for conflict detection procedure to finish on session %u

- Error number: MY-011620; Symbol: ER_GRP_RPL_FATAL_REC_PROCESS; SQLSTATE: HY000

Message: Fatal error during the incremental recovery process of Group Replication. The server will leave the group.

- Error number: MY-011622; Symbol: ER_GRP_RPL_UNABLE_TO_EVALUATE_APPLIER_STATUS; SQLSTATE: HY000

Message: Unable to evaluate the group replication applier execution status. Group replication recovery will shutdown to avoid data corruption.

- Error number: MY-011623; Symbol: ER_GRP_RPL_ONLY_ONE_SERVER_ALIVE; SQLSTATE: HY000

Message: Only one server alive. Declaring this server as online within the replication group

- Error number: MY-011624; Symbol: ER_GRP_RPL_CERTIFICATION_REC_PROCESS; SQLSTATE: HY000

Message: Error when processing certification information in the incremental recovery process

- Error number: MY-011625; Symbol: ER_GRP_RPL_UNABLE_TO_ENSURE_EXECUTION_REC; SQLSTATE: HY000

Message: Unable to ensure the execution of group transactions received during recovery.

- Error number: MY-011626; Symbol: ER_GRP_RPL_WHILE_SENDING_MSG_REC; SQLSTATE: HY000

Message: Error while sending message in the group replication incremental recovery process.

-
- Error number: [MY-011628](#); Symbol: [ER_GRP_RPL_READ_UNABLE_FOR_READ_ONLY_SUPER_READ_ONLY](#); SQLSTATE: [HY000](#)
Message: Unable to read the server values for the read_only and super_read_only variables.
 - Error number: [MY-011629](#); Symbol: [ER_GRP_RPL_UNABLE_TO_RESET_SERVER_READ_MODE](#); SQLSTATE: [HY000](#)
Message: Unable to reset the server read mode settings. Try to reset them manually.
 - Error number: [MY-011630](#); Symbol: [ER_GRP_RPL_UNABLE_TO_CERTIFY_PLUGIN_TRANS](#); SQLSTATE: [HY000](#)
Message: Due to a plugin error, some transactions were unable to be certified and will now rollback.
 - Error number: [MY-011631](#); Symbol: [ER_GRP_RPL_UNBLOCK_CERTIFIED_TRANS](#); SQLSTATE: [HY000](#)
Message: Error when trying to unblock non certified or consistent transactions. Check for consistency errors when restarting the service
 - Error number: [MY-011633](#); Symbol: [ER_GRP_RPL_FAILED_TO_START_WITH_INVALID_SERVER_ID](#); SQLSTATE: [HY000](#)
Message: Unable to start Group Replication. Replication applier infrastructure is not initialized since the server was started with server_id=0. Please, restart the server with server_id larger than 0.
 - Error number: [MY-011634](#); Symbol: [ER_GRP_RPL_FORCE_MEMBERS_MUST_BE_EMPTY](#); SQLSTATE: [HY000](#)
Message: group_replication_force_members must be empty on group start. Current value: '%s'
 - Error number: [MY-011635](#); Symbol: [ER_GRP_RPL_PLUGIN_STRUCT_INIT_NOT_POSSIBLE_ON_SERVER_START](#); SQLSTATE: [HY000](#)
Message: It was not possible to guarantee the initialization of plugin structures on server start
 - Error number: [MY-011636](#); Symbol: [ER_GRP_RPL_FAILED_TO_ENABLE_SUPER_READ_ONLY_MODE](#); SQLSTATE: [HY000](#)
Message: Could not enable the server read only mode and guarantee a safe recovery execution
 - Error number: [MY-011637](#); Symbol: [ER_GRP_RPL_FAILED_TO_INIT_COMMUNICATION_ENGINE](#); SQLSTATE: [HY000](#)
Message: Error on group communication engine initialization
 - Error number: [MY-011638](#); Symbol: [ER_GRP_RPL_FAILED_TO_START_ON_SECONDARY_WITH_ASYNC_CHANNELS](#); SQLSTATE: [HY000](#)
Message: Can't start group replication on secondary member with single-primary mode while asynchronous replication channels are running.
 - Error number: [MY-011639](#); Symbol: [ER_GRP_RPL_FAILED_TO_START_COMMUNICATION_ENGINE](#); SQLSTATE: [HY000](#)
Message: Error on group communication engine start
 - Error number: [MY-011640](#); Symbol: [ER_GRP_RPL_TIMEOUT_ON_VIEW_AFTER_JOINING_GRP](#); SQLSTATE: [HY000](#)

Message: Timeout on wait for view after joining group

- Error number: MY-011641; Symbol: ER_GRP_RPL_FAILED_TO_CALL_GRP_COMMUNICATION_INTERFACE; SQLSTATE: HY000

Message: Error calling group communication interfaces

- Error number: MY-011642; Symbol: ER_GRP_RPL_MEMBER_SERVER_UUID_IS_INCOMPATIBLE_WITH_GRP; SQLSTATE: HY000

Message: Member server_uuid is incompatible with the group. Server_uuid %s matches group_replication_group_name %s.

- Error number: MY-011643; Symbol: ER_GRP_RPL_MEMBER_CONF_INFO; SQLSTATE: HY000

Message: Member configuration: member_id: %lu; member_uuid: "%s"; single-primary mode: "%s"; group_replication_auto_increment_increment: %lu; group_replication_view_change_uuid: "%s";

- Error number: MY-011644; Symbol: ER_GRP_RPL_FAILED_TO_CONFIRM_IF_SERVER_LEFT_GRP; SQLSTATE: HY000

Message: Unable to confirm whether the server has left the group or not. Check performance_schema.replication_group_members to check group membership information.

- Error number: MY-011645; Symbol: ER_GRP_RPL_SERVER_IS_ALREADY_LEAVING; SQLSTATE: HY000

Message: Skipping leave operation: concurrent attempt to leave the group is on-going.

- Error number: MY-011646; Symbol: ER_GRP_RPL_SERVER_ALREADY_LEFT; SQLSTATE: HY000

Message: Skipping leave operation: member already left the group.

- Error number: MY-011647; Symbol: ER_GRP_RPL_WAITING_FOR_VIEW_UPDATE; SQLSTATE: HY000

Message: Going to wait for view modification

- Error number: MY-011648; Symbol: ER_GRP_RPL_TIMEOUT_RECEIVING_VIEW_CHANGE_ON_SHUTDOWN; SQLSTATE: HY000

Message: While leaving the group due to a stop, shutdown or failure there was a timeout receiving a view change. This can lead to a possible inconsistent state. Check the log for more details

- Error number: MY-011649; Symbol: ER_GRP_RPL_REQUESTING_NON_MEMBER_SERVER_TO_LEAVE; SQLSTATE: HY000

Message: Requesting to leave the group despite of not being a member

- Error number: MY-011650; Symbol: ER_GRP_RPL_IS_STOPPING; SQLSTATE: HY000

Message: Plugin 'group_replication' is stopping.

- Error number: MY-011651; Symbol: ER_GRP_RPL_IS_STOPPED; SQLSTATE: HY000

Message: Plugin 'group_replication' has been stopped.

- Error number: MY-011652; Symbol: ER_GRP_RPL_FAILED_TO_ENABLE_READ_ONLY_MODE_ON_SHUTDOWN; SQLSTATE: HY000

Message: On plugin shutdown it was not possible to enable the server read only mode. Local transactions will be accepted and committed.

- Error number: [MY-011653](#); Symbol: [ER_GRP_RPL_RECOVERY_MODULE_TERMINATION_TIMED_OUT_ON_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: On shutdown there was a timeout on the Group Replication recovery module termination. Check the log for more details

- Error number: [MY-011654](#); Symbol: [ER_GRP_RPL_APPLIER_TERMINATION_TIMED_OUT_ON_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: On shutdown there was a timeout on the Group Replication applier termination.

- Error number: [MY-011655](#); Symbol: [ER_GRP_RPL_FAILED_TO_SHUTDOWN_REGISTRY_MODULE](#); SQLSTATE: [HY000](#)

Message: Unexpected failure while shutting down registry module!

- Error number: [MY-011656](#); Symbol: [ER_GRP_RPL_FAILED_TO_INIT_HANDLER](#); SQLSTATE: [HY000](#)

Message: Failure during Group Replication handler initialization

- Error number: [MY-011657](#); Symbol: [ER_GRP_RPL_FAILED_TO_REGISTER_SERVER_STATE_OBSERVER](#); SQLSTATE: [HY000](#)

Message: Failure when registering the server state observers

- Error number: [MY-011658](#); Symbol: [ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OBSERVER](#); SQLSTATE: [HY000](#)

Message: Failure when registering the transactions state observers

- Error number: [MY-011659](#); Symbol: [ER_GRP_RPL_FAILED_TO_REGISTER_BINLOG_STATE_OBSERVER](#); SQLSTATE: [HY000](#)

Message: Failure when registering the binlog state observers

- Error number: [MY-011660](#); Symbol: [ER_GRP_RPL_FAILED_TO_START_ON_BOOT](#); SQLSTATE: [HY000](#)

Message: Unable to start Group Replication on boot

- Error number: [MY-011661](#); Symbol: [ER_GRP_RPL_FAILED_TO_STOP_ON_PLUGIN_UNINSTALL](#); SQLSTATE: [HY000](#)

Message: Failure when stopping Group Replication on plugin uninstall

- Error number: [MY-011662](#); Symbol: [ER_GRP_RPL_FAILED_TO_UNREGISTER_SERVER_STATE_OBSERVER](#); SQLSTATE: [HY000](#)

Message: Failure when unregistering the server state observers

- Error number: [MY-011663](#); Symbol: [ER_GRP_RPL_FAILED_TO_UNREGISTER_TRANS_STATE_OBSERVER](#); SQLSTATE: [HY000](#)

Message: Failure when unregistering the transactions state observers

- Error number: [MY-011664](#); Symbol: [ER_GRP_RPL_FAILED_TO_UNREGISTER_BINLOG_STATE_OBSERVER](#); SQLSTATE: [HY000](#)

Message: Failure when unregistering the binlog state observers

- Error number: `MY-011665`; Symbol: `ER_GRP_RPL_ALL_OBSERVERS_UNREGISTERED`; SQLSTATE: `HY000`

Message: All Group Replication server observers have been successfully unregistered

- Error number: `MY-011666`; Symbol: `ER_GRP_RPL_FAILED_TO_PARSE_THE_GRP_NAME`; SQLSTATE: `HY000`

Message: Unable to parse the `group_replication_group_name`.

- Error number: `MY-011667`; Symbol: `ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_GRP`; SQLSTATE: `HY000`

Message: Unable to parse the `group_replication_group_name`.

- Error number: `MY-011668`; Symbol: `ER_GRP_RPL_APPLIER_NOT_STARTED_DUE_TO_RUNNING_PREV_SHUTDOWN`; SQLSTATE: `HY000`

Message: Cannot start the Group Replication applier as a previous shutdown is still running: The thread will stop once its task is complete.

- Error number: `MY-011669`; Symbol: `ER_GRP_RPL_FAILED_TO_INIT_APPLIER_MODULE`; SQLSTATE: `HY000`

Message: Unable to initialize the Group Replication applier module.

- Error number: `MY-011670`; Symbol: `ER_GRP_RPL_APPLIER_INITIALIZED`; SQLSTATE: `HY000`

Message: Group Replication applier module successfully initialized!

- Error number: `MY-011671`; Symbol: `ER_GRP_RPL_COMMUNICATION_SSL_CONF_INFO`; SQLSTATE: `HY000`

Message: Group communication SSL configuration: `group_replication_ssl_mode: "%s"`; `server_key_file: "%s"`; `server_cert_file: "%s"`; `client_key_file: "%s"`; `client_cert_file: "%s"`; `ca_file: "%s"`; `ca_path: "%s"`; `cipher: "%s"`; `tls_version: "%s"`; `tls_ciphersuites: "%s"`; `crl_file: "%s"`; `crl_path: "%s"`; `ssl_fips_mode: "%s"`

- Error number: `MY-011672`; Symbol: `ER_GRP_RPL_ABORTS_AS_SSL_NOT_SUPPORTED_BY_MYSQLD`; SQLSTATE: `HY000`

Message: MySQL server does not have SSL support and `group_replication_ssl_mode` is "`%s`", `START GROUP_REPLICATION` will abort

- Error number: `MY-011673`; Symbol: `ER_GRP_RPL_SSL_DISABLED`; SQLSTATE: `HY000`

Message: Group communication SSL configuration: `group_replication_ssl_mode: "%s"`

- Error number: `MY-011674`; Symbol: `ER_GRP_RPL_UNABLE_TO_INIT_COMMUNICATION_ENGINE`; SQLSTATE: `HY000`

Message: Unable to initialize the group communication engine

- Error number: `MY-011675`; Symbol: `ER_GRP_RPL_BINLOG_DISABLED`; SQLSTATE: `HY000`

Message: Binlog must be enabled for Group Replication

-
- Error number: [MY-011676](#); Symbol: [ER_GRP_RPL_GTID_MODE_OFF](#); SQLSTATE: [HY000](#)
Message: Gtid mode should be ON for Group Replication
 - Error number: [MY-011677](#); Symbol: [ER_GRP_RPL_LOG_REPLICA_UPDATES_NOT_SET](#); SQLSTATE: [HY000](#)
Message: LOG_REPLICA_UPDATES should be ON for Group Replication
 - Error number: [MY-011679](#); Symbol: [ER_GRP_RPL_APPLIER_METADATA_REPO_MUST_BE_TABLE](#); SQLSTATE: [HY000](#)
Message: Applier metadata repository must be set to TABLE
 - Error number: [MY-011680](#); Symbol: [ER_GRP_RPL_CONNECTION_METADATA_REPO_MUST_BE_TABLE](#); SQLSTATE: [HY000](#)
Message: Connection metadata repository must be set to TABLE.
 - Error number: [MY-011681](#); Symbol: [ER_GRP_RPL_INCORRECT_TYPE_SET_FOR_PARALLEL_APPLIER](#); SQLSTATE: [HY000](#)
Message: In order to use parallel applier on Group Replication, parameter replica-parallel-type must be set to 'LOGICAL_CLOCK'.
 - Error number: [MY-011682](#); Symbol: [ER_GRP_RPL_REPLICA_PRESERVE_COMMIT_ORDER_NOT_SET](#); SQLSTATE: [HY000](#)
Message: Group Replication requires replica-preserve-commit-order to be set to ON when using more than 1 applier threads.
 - Error number: [MY-011683](#); Symbol: [ER_GRP_RPL_SINGLE_PRIM_MODE_NOT_ALLOWED_WITH_UPDATE_EVERYWHERE](#); SQLSTATE: [HY000](#)
Message: It is not allowed to run single primary mode with 'group_replication_enforce_update_everywhere_checks' enabled.
 - Error number: [MY-011684](#); Symbol: [ER_GRP_RPL_MODULE_TERMINATE_ERROR](#); SQLSTATE: [HY000](#)
Message: error_message: %s
 - Error number: [MY-011685](#); Symbol: [ER_GRP_RPL_GRP_NAME_OPTION_MANDATORY](#); SQLSTATE: [HY000](#)
Message: The group_replication_group_name option is mandatory
 - Error number: [MY-011686](#); Symbol: [ER_GRP_RPL_GRP_NAME_IS_TOO_LONG](#); SQLSTATE: [HY000](#)
Message: The group_replication_group_name '%s' is not a valid UUID, its length is too big
 - Error number: [MY-011687](#); Symbol: [ER_GRP_RPL_GRP_NAME_IS_NOT_VALID_UUID](#); SQLSTATE: [HY000](#)
Message: The group_replication_group_name '%s' is not a valid UUID
 - Error number: [MY-011688](#); Symbol: [ER_GRP_RPL_FLOW_CTRL_MIN_QUOTA_GREATER_THAN_MAX_QUOTA](#); SQLSTATE: [HY000](#)
-

Message: group_replication_flow_control_min_quota cannot be larger than group_replication_flow_control_max_quota

- Error number: [MY-011689](#); Symbol: [ER_GRP_RPL_FLOW_CTRL_MIN_RECOVERY_QUOTA_GREATER_THAN_MAX_QUOTA](#); SQLSTATE: HY000

Message: group_replication_flow_control_min_recovery_quota cannot be larger than group_replication_flow_control_max_quota

- Error number: [MY-011690](#); Symbol: [ER_GRP_RPL_FLOW_CTRL_MAX_QUOTA_SMALLER_THAN_MIN_QUOTAS](#); SQLSTATE: HY000

Message: group_replication_flow_control_max_quota cannot be smaller than group_replication_flow_control_min_quota or group_replication_flow_control_min_recovery_quota

- Error number: [MY-011691](#); Symbol: [ER_GRP_RPL_INVALID_SSL_RECOVERY_STRING](#); SQLSTATE: HY000

Message: The given value for recovery ssl option 'group_replication_%' is invalid as its length is beyond the limit

- Error number: [MY-011694](#); Symbol: [ER_GRP_RPL_GRP_COMMUNICATION_INIT_WITH_CONF](#); SQLSTATE: HY000

Message: Initialized group communication with configuration: group_replication_group_name: '%s'; group_replication_local_address: '%s'; group_replication_group_seeds: '%s'; group_replication_bootstrap_group: '%s'; group_replication_poll_spin_loops: %lu; group_replication_compression_threshold: %lu; group_replication_ip_allowlist: '%s'; group_replication_communication_debug_options: '%s'; group_replication_member_expel_timeout: '%lu'; group_replication_communication_max_message_size: %lu; group_replication_message_cache_size: '%luu'; group_replication_communication_stack: '%lu'

- Error number: [MY-011695](#); Symbol: [ER_GRP_RPL_UNKNOWN_GRP_RPL_APPLIER_PIPELINE_REQUESTED](#); SQLSTATE: HY000

Message: Unknown group replication applier pipeline requested

- Error number: [MY-011696](#); Symbol: [ER_GRP_RPL_FAILED_TO_BOOTSTRAP_EVENT_HANDLING_INFRASTRUCTURE](#); SQLSTATE: HY000

Message: Unable to bootstrap group replication event handling infrastructure. Unknown handler type: %d

- Error number: [MY-011697](#); Symbol: [ER_GRP_RPL_APPLIER_HANDLER_NOT_INITIALIZED](#); SQLSTATE: HY000

Message: One of the group replication applier handlers is null due to an initialization error

- Error number: [MY-011698](#); Symbol: [ER_GRP_RPL_APPLIER_HANDLER_IS_IN_USE](#); SQLSTATE: HY000

Message: A group replication applier handler, marked as unique, is already in use.

- Error number: [MY-011699](#); Symbol: [ER_GRP_RPL_APPLIER_HANDLER_ROLE_IS_IN_USE](#); SQLSTATE: HY000

Message: A group replication applier handler role, that was marked as unique, is already in use.

- Error number: `MY-011700`; Symbol: `ER_GRP_RPL_FAILED_TO_INIT_APPLIER_HANDLER`; SQLSTATE: `HY000`

Message: Error on group replication applier handler initialization

- Error number: `MY-011701`; Symbol: `ER_GRP_RPL_SQL_SERVICE_FAILED_TO_INIT_SESSION_THREAD`; SQLSTATE: `HY000`

Message: Error when initializing a session thread for internal server connection.

- Error number: `MY-011702`; Symbol: `ER_GRP_RPL_SQL_SERVICE_COMM_SESSION_NOT_INITIALIZED`; SQLSTATE: `HY000`

Message: Error running internal SQL query: %s. The internal server communication session is not initialized

- Error number: `MY-011703`; Symbol: `ER_GRP_RPL_SQL_SERVICE_SERVER_SESSION_KILLED`; SQLSTATE: `HY000`

Message: Error running internal SQL query: %s. The internal server session was killed or server is shutting down.

- Error number: `MY-011704`; Symbol: `ER_GRP_RPL_SQL_SERVICE_FAILED_TO_RUN_SQL_QUERY`; SQLSTATE: `HY000`

Message: Error running internal SQL query: %s. Got internal SQL error: %s(%d)

- Error number: `MY-011705`; Symbol: `ER_GRP_RPL_SQL_SERVICE_SERVER_INTERNAL_FAILURE`; SQLSTATE: `HY000`

Message: Error running internal SQL query: %s. Internal failure.

- Error number: `MY-011706`; Symbol: `ER_GRP_RPL_SQL_SERVICE_RETRIES_EXCEEDED_ON_SESSION_STATE`; SQLSTATE: `HY000`

Message: Error, maximum number of retries exceeded when waiting for the internal server session state to be operating

- Error number: `MY-011707`; Symbol: `ER_GRP_RPL_SQL_SERVICE_FAILED_TO_FETCH_SECURITY_CTX`; SQLSTATE: `HY000`

Message: Error when trying to fetch security context when contacting the server for internal plugin requests.

- Error number: `MY-011708`; Symbol: `ER_GRP_RPL_SQL_SERVICE_SERVER_ACCESS_DENIED_FOR_USER`; SQLSTATE: `HY000`

Message: There was an error when trying to access the server with user: %s. Make sure the user is present in the server and that the MySQL upgrade procedure was run correctly.

- Error number: `MY-011709`; Symbol: `ER_GRP_RPL_SQL_SERVICE_MAX_CONN_ERROR_FROM_SERVER`; SQLSTATE: `HY000`

Message: Failed to establish an internal server connection to execute plugin operations since the server does not have available connections, please increase @@GLOBAL.MAX_CONNECTIONS. Server error: %i.

-
- Error number: `MY-011710`; Symbol: `ER_GRP_RPL_SQL_SERVICE_SERVER_ERROR_ON_CONN`; SQLSTATE: `HY000`
Message: Failed to establish an internal server connection to execute plugin operations. Server error: %i. Server error message: %s
 - Error number: `MY-011711`; Symbol: `ER_GRP_RPL_UNREACHABLE_MAJORITY_TIMEOUT_FOR_MEMBER`; SQLSTATE: `HY000`
Message: This member could not reach a majority of the members for more than %ld seconds. The member will now leave the group as instructed by the group_replication_unreachable_majority_timeout option.
 - Error number: `MY-011712`; Symbol: `ER_GRP_RPL_SERVER_SET_TO_READ_ONLY_DUE_TO_ERRORS`; SQLSTATE: `HY000`
Message: The server was automatically set into read only mode after an error was detected.
 - Error number: `MY-011713`; Symbol: `ER_GRP_RPL_GMS_LISTENER_FAILED_TO_LOG_NOTIFICATION`; SQLSTATE: `HY000`
Message: Unable to log notification to table (errno: %lu) (res: %d)! Message: %s
 - Error number: `MY-011714`; Symbol: `ER_GRP_RPL_GRP_COMMUNICATION_ENG_INIT_FAILED`; SQLSTATE: `HY000`
Message: Failure in group communication engine '%s' initialization
 - Error number: `MY-011715`; Symbol: `ER_GRP_RPL_SET_GRP_COMMUNICATION_ENG_LOGGER_FAILED`; SQLSTATE: `HY000`
Message: Unable to set the group communication engine logger
 - Error number: `MY-011716`; Symbol: `ER_GRP_RPL_DEBUG_OPTIONS`; SQLSTATE: `HY000`
Message: Current debug options are: '%s'.
 - Error number: `MY-011717`; Symbol: `ER_GRP_RPL_INVALID_DEBUG_OPTIONS`; SQLSTATE: `HY000`
Message: Some debug options in '%s' are not valid.
 - Error number: `MY-011718`; Symbol: `ER_GRP_RPL_EXIT_GRP_GCS_ERROR`; SQLSTATE: `HY000`
Message: Error calling group communication interfaces while trying to leave the group
 - Error number: `MY-011719`; Symbol: `ER_GRP_RPL_GRP_MEMBER_OFFLINE`; SQLSTATE: `HY000`
Message: Member is not ONLINE, it is not possible to force a new group membership
 - Error number: `MY-011720`; Symbol: `ER_GRP_RPL_GCS_INTERFACE_ERROR`; SQLSTATE: `HY000`
Message: Error calling group communication interfaces
 - Error number: `MY-011721`; Symbol: `ER_GRP_RPL_FORCE_MEMBER_VALUE_SET_ERROR`; SQLSTATE: `HY000`
Message: Error setting group_replication_force_members value '%s' on group communication interfaces
 - Error number: `MY-011722`; Symbol: `ER_GRP_RPL_FORCE_MEMBER_VALUE_SET`; SQLSTATE: `HY000`

Message: The group_replication_force_members value '%s' was set in the group communication interfaces

- Error number: [MY-011723](#); Symbol: [ER_GRP_RPL_FORCE_MEMBER_VALUE_TIME_OUT](#); SQLSTATE: [HY000](#)

Message: Timeout on wait for view after setting group_replication_force_members value '%s' into group communication interfaces

- Error number: [MY-011724](#); Symbol: [ER_GRP_RPL_BROADCAST_COMMIT_MSSG_TOO_BIG](#); SQLSTATE: [HY000](#)

Message: Broadcast of committed transactions message failed. Message is too big.

- Error number: [MY-011725](#); Symbol: [ER_GRP_RPL_SEND_STATS_ERROR](#); SQLSTATE: [HY000](#)

Message: Error while sending stats message

- Error number: [MY-011726](#); Symbol: [ER_GRP_RPL_MEMBER_STATS_INFO](#); SQLSTATE: [HY000](#)

Message: Flow control - update member stats: %s stats certifier_queue %d, applier_queue %d certified %ld (%ld), applied %ld (%ld), local %ld (%ld), quota %ld (%ld) mode=%d

- Error number: [MY-011727](#); Symbol: [ER_GRP_RPL_FLOW_CONTROL_STATS](#); SQLSTATE: [HY000](#)

Message: Flow control: throttling to %ld commits per %ld sec, with %d writing and %d non-recovering members, min capacity %ld, lim throttle %ld

- Error number: [MY-011728](#); Symbol: [ER_GRP_RPL_UNABLE_TO_CONVERT_PACKET_TO_EVENT](#); SQLSTATE: [HY000](#)

Message: Unable to convert a packet into an event on the applier. Error: %s

- Error number: [MY-011729](#); Symbol: [ER_GRP_RPL_PIPELINE_CREATE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to create group replication pipeline cache.

- Error number: [MY-011730](#); Symbol: [ER_GRP_RPL_PIPELINE_REINIT_FAILED_WRITE](#); SQLSTATE: [HY000](#)

Message: Failed to reinit group replication pipeline cache for write.

- Error number: [MY-011731](#); Symbol: [ER_GRP_RPL_UNABLE_TO_CONVERT_EVENT_TO_PACKET](#); SQLSTATE: [HY000](#)

Message: Unable to convert the event into a packet on the applier. Error: %s

- Error number: [MY-011732](#); Symbol: [ER_GRP_RPL_PIPELINE_FLUSH_FAIL](#); SQLSTATE: [HY000](#)

Message: Failed to flush group replication pipeline cache.

- Error number: [MY-011733](#); Symbol: [ER_GRP_RPL_PIPELINE_REINIT_FAILED_READ](#); SQLSTATE: [HY000](#)

Message: Failed to reinit group replication pipeline cache for read.

- Error number: [MY-011735](#); Symbol: [ER_GRP_RPL_GCS_GR_ERROR_MSG](#); SQLSTATE: [HY000](#)

Message: %s

-
- Error number: [MY-011736](#); Symbol: [ER_GRP_RPL_REPLICA_IO_THREAD_UNBLOCKED](#); SQLSTATE: [HY000](#)
Message: The replica IO thread of channel '%s' is unblocked as the member is declared ONLINE now.
 - Error number: [MY-011737](#); Symbol: [ER_GRP_RPL_REPLICA_IO_THREAD_ERROR_OUT](#); SQLSTATE: [HY000](#)
Message: The replica IO thread of channel '%s' will error out as the member failed to come ONLINE.
 - Error number: [MY-011738](#); Symbol: [ER_GRP_RPL_REPLICA_APPLIER_THREAD_UNBLOCKED](#); SQLSTATE: [HY000](#)
Message: The replica applier thread of channel '%s' is unblocked as the member is declared ONLINE now.
 - Error number: [MY-011739](#); Symbol: [ER_GRP_RPL_REPLICA_APPLIER_THREAD_ERROR_OUT](#); SQLSTATE: [HY000](#)
Message: The replica applier thread of channel '%s' will error out as the member failed to come ONLINE.
 - Error number: [MY-011740](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_CREATE_OR_GET_CONNECTION](#); SQLSTATE: [HY000](#)
Message: LDAP authentication initialize: failed to create/ get connection from the pool.
 - Error number: [MY-011741](#); Symbol: [ER_LDAP_AUTH_DEINIT_FAILED](#); SQLSTATE: [HY000](#)
Message: LDAP authentication de_initialize Failed
 - Error number: [MY-011742](#); Symbol: [ER_LDAP_AUTH_SKIPPING_USER_GROUP_SEARCH](#); SQLSTATE: [HY000](#)
Message: Skipping group search, No group attribute mentioned
 - Error number: [MY-011743](#); Symbol: [ER_LDAP_AUTH_POOL_DISABLE_MAX_SIZE_ZERO](#); SQLSTATE: [HY000](#)
Message: Pool max size is 0, connection pool is disabled
 - Error number: [MY-011744](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT_CREATOR](#); SQLSTATE: [HY000](#)
Message: Connection pool initialization, failed to create LDAP object creator
 - Error number: [MY-011745](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT](#); SQLSTATE: [HY000](#)
Message: Connection pool initialization, failed to create LDAP object
 - Error number: [MY-011746](#); Symbol: [ER_LDAP_AUTH_TLS_CONF](#); SQLSTATE: [HY000](#)
Message: LDAP TLS configuration
 - Error number: [MY-011747](#); Symbol: [ER_LDAP_AUTH_TLS_CONNECTION](#); SQLSTATE: [HY000](#)
Message: LDAP TLS connection
 - Error number: [MY-011748](#); Symbol: [ER_LDAP_AUTH_CONN_POOL_NOT_CREATED](#); SQLSTATE: [HY000](#)

Message: LDAP pool is not created.

- Error number: [MY-011749](#); Symbol: [ER_LDAP_AUTH_CONN_POOL_INITIALIZING](#); SQLSTATE: [HY000](#)

Message: LDAP pool is initializing

- Error number: [MY-011750](#); Symbol: [ER_LDAP_AUTH_CONN_POOL_DEINITIALIZING](#); SQLSTATE: [HY000](#)

Message: LDAP pool is de-initializing

- Error number: [MY-011751](#); Symbol: [ER_LDAP_AUTH_ZERO_MAX_POOL_SIZE_UNCHANGED](#); SQLSTATE: [HY000](#)

Message: Pool max size old and new values are 0

- Error number: [MY-011752](#); Symbol: [ER_LDAP_AUTH_POOL_REINITIALIZING](#); SQLSTATE: [HY000](#)

Message: LDAP pool is re-initializing

- Error number: [MY-011753](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_WRITE_PACKET](#); SQLSTATE: [HY000](#)

Message: Plug-in has failed to write the packet.

- Error number: [MY-011754](#); Symbol: [ER_LDAP_AUTH_SETTING_USERNAME](#); SQLSTATE: [HY000](#)

Message: Setting LDAP user name as : %s

- Error number: [MY-011755](#); Symbol: [ER_LDAP_AUTH_USER_AUTH_DATA](#); SQLSTATE: [HY000](#)

Message: User authentication data: %s size: %lu

- Error number: [MY-011756](#); Symbol: [ER_LDAP_AUTH_INFO_FOR_USER](#); SQLSTATE: [HY000](#)

Message: User is authenticated as: %s external user: %s

[ER_LDAP_AUTH_INFO_FOR_USER](#) was removed after 8.4.0.

- Error number: [MY-011757](#); Symbol: [ER_LDAP_AUTH_USER_GROUP_SEARCH_INFO](#); SQLSTATE: [HY000](#)

Message: Group search information base DN: %s scope: %d filter: %s attribute: %s

- Error number: [MY-011758](#); Symbol: [ER_LDAP_AUTH_GRP_SEARCH_SPECIAL_HDL](#); SQLSTATE: [HY000](#)

Message: Special handling for group search, {GA} found

- Error number: [MY-011759](#); Symbol: [ER_LDAP_AUTH_GRP_IS_FULL_DN](#); SQLSTATE: [HY000](#)

Message: Group search special handling, group full DN found.

- Error number: [MY-011760](#); Symbol: [ER_LDAP_AUTH_USER_NOT_FOUND_IN_ANY_GRP](#); SQLSTATE: [HY000](#)

Message: User %s is not member of any group.

-
- Error number: [MY-011761](#); Symbol: [ER_LDAP_AUTH_USER_FOUND_IN_MANY_GRP_S](#); SQLSTATE: [HY000](#)
Message: User %s is member of more than one group
 - Error number: [MY-011762](#); Symbol: [ER_LDAP_AUTH_USER_HAS_MULTIPLE_GRP_NAMES](#); SQLSTATE: [HY000](#)
Message: For user %s has multiple user group names. Please check if group attribute name is correct
 - Error number: [MY-011763](#); Symbol: [ER_LDAP_AUTH_SEARCHED_USER_GRP_NAME](#); SQLSTATE: [HY000](#)
Message: Searched group name: %s
 - Error number: [MY-011764](#); Symbol: [ER_LDAP_AUTH_OBJECT_CREATE_TIMESTAMP](#); SQLSTATE: [HY000](#)
Message: LDAP authentication object creation time_stamp: %s dn: %s
 - Error number: [MY-011765](#); Symbol: [ER_LDAP_AUTH_CERTIFICATE_NAME](#); SQLSTATE: [HY000](#)
Message: Certificate name: %s
 - Error number: [MY-011766](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_POOL_DEINIT](#); SQLSTATE: [HY000](#)
Message: Failed to pool de-initialized: pool is already reconstructing
 - Error number: [MY-011767](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_RECONSTRUCTING](#); SQLSTATE: [HY000](#)
Message: Pool initialization failed: pool is already initialized
 - Error number: [MY-011768](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_INIT_STATE](#); SQLSTATE: [HY000](#)
Message: Pool initialization failed: pool is initializing
 - Error number: [MY-011769](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_DEINIT_STATE](#); SQLSTATE: [HY000](#)
Message: Pool initialization failed: pool is de-initializing
 - Error number: [MY-011770](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_POOL_IN_RECONSTRUCT_STATE](#); SQLSTATE: [HY000](#)
Message: Failed to pool deinitialized: pool is already reconstructing
 - Error number: [MY-011771](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_NOT_READY_POOL](#); SQLSTATE: [HY000](#)
Message: Failed to pool deinitialized : pool is not ready
 - Error number: [MY-011772](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_GET_CONNECTION_AS_PLUGIN_NOT_READY](#); SQLSTATE: [HY000](#)
Message: Ldap_connection_pool::get: Failed to return connection as plug-in is not ready/initializing/de-initializing

-
- Error number: [MY-011773](#); Symbol: [ER_LDAP_AUTH_CONNECTION_POOL_INIT_FAILED](#); SQLSTATE: [HY000](#)
Message: Connection pool has failed to initialized
 - Error number: [MY-011774](#); Symbol: [ER_LDAP_AUTH_MAX_ALLOWED_CONNECTION_LIMIT_HIT](#); SQLSTATE: [HY000](#)
Message: Ldap_connection_pool::get LDAP maximum connection allowed size is reached. Increase the maximum limit.
 - Error number: [MY-011775](#); Symbol: [ER_LDAP_AUTH_MAX_POOL_SIZE_SET_FAILED](#); SQLSTATE: [HY000](#)
Message: Set max pool size failed.
 - Error number: [MY-011776](#); Symbol: [ER_LDAP_AUTH_PLUGIN_FAILED_TO_READ_PACKET](#); SQLSTATE: [HY000](#)
Message: Plug-in has failed to read the packet from client
 - Error number: [MY-011777](#); Symbol: [ER_LDAP_AUTH_CREATING_LDAP_CONNECTION](#); SQLSTATE: [HY000](#)
Message: Ldap_authentication::initialize: creating new LDAP connection.
 - Error number: [MY-011778](#); Symbol: [ER_LDAP_AUTH_GETTING_CONNECTION_FROM_POOL](#); SQLSTATE: [HY000](#)
Message: Ldap_authentication::initialize: getting connection from pool.
 - Error number: [MY-011779](#); Symbol: [ER_LDAP_AUTH_RETURNING_CONNECTION_TO_POOL](#); SQLSTATE: [HY000](#)
Message: Ldap_authentication::de_initialize putting back connection in the pool
 - Error number: [MY-011780](#); Symbol: [ER_LDAP_AUTH_SEARCH_USER_GROUP_ATTR_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: Ldap_authentication::search_user_group no group attribute found
 - Error number: [MY-011781](#); Symbol: [ER_LDAP_AUTH_LDAP_INFO_NULL](#); SQLSTATE: [HY000](#)
Message: Ldap_connection_pool::put ldap info null
 - Error number: [MY-011782](#); Symbol: [ER_LDAP_AUTH_FREEING_CONNECTION](#); SQLSTATE: [HY000](#)
Message: Ldap_connection_pool::put connection is freeing.
 - Error number: [MY-011783](#); Symbol: [ER_LDAP_AUTH_CONNECTION_PUSHED_TO_POOL](#); SQLSTATE: [HY000](#)
Message: Ldap_connection_pool::put connection in pushed in the pool
 - Error number: [MY-011784](#); Symbol: [ER_LDAP_AUTH_CONNECTION_CREATOR_ENTER](#); SQLSTATE: [HY000](#)
Message: Ldap_connection_creator::Ldap_connection_creator
-

-
- Error number: [MY-011785](#); Symbol: [ER_LDAP_AUTH_STARTING_TLS](#); SQLSTATE: [HY000](#)
Message: starting TLS
 - Error number: [MY-011786](#); Symbol: [ER_LDAP_AUTH_CONNECTION_GET_LDAP_INFO_NULL](#); SQLSTATE: [HY000](#)
Message: Ldap_connection_pool::get: (ldap_info == NULL)|| (*ldap_info)
 - Error number: [MY-011787](#); Symbol: [ER_LDAP_AUTH_DELETING_CONNECTION_KEY](#); SQLSTATE: [HY000](#)
Message: Ldap_connection_pool::deinit: deleting connection key %s
 - Error number: [MY-011788](#); Symbol: [ER_LDAP_AUTH_POOLED_CONNECTION_KEY](#); SQLSTATE: [HY000](#)
Message: Ldap_connection_pool::get pooled connection key: %s
 - Error number: [MY-011789](#); Symbol: [ER_LDAP_AUTH_CREATE_CONNECTION_KEY](#); SQLSTATE: [HY000](#)
Message: Ldap_connection_pool::get create connection key: %s
 - Error number: [MY-011790](#); Symbol: [ER_LDAP_AUTH_COMMUNICATION_HOST_INFO](#); SQLSTATE: [HY000](#)
Message: LDAP communication host %s port %u
 - Error number: [MY-011791](#); Symbol: [ER_LDAP_AUTH_METHOD_TO_CLIENT](#); SQLSTATE: [HY000](#)
Message: Sending authentication method to client : %s
 - Error number: [MY-011792](#); Symbol: [ER_LDAP_AUTH_SASL_REQUEST_FROM_CLIENT](#); SQLSTATE: [HY000](#)
Message: SASL request received from mysql client: %s
 - Error number: [MY-011793](#); Symbol: [ER_LDAP_AUTH_SASL_PROCESS_SASL](#); SQLSTATE: [HY000](#)
Message: Ldap_sasl_authentication::process_sasl rc: %s
 - Error number: [MY-011794](#); Symbol: [ER_LDAP_AUTH_SASL_BIND_SUCCESS_INFO](#); SQLSTATE: [HY000](#)
Message: Ldap_sasl_authentication::process_sasl sasl bind succeed. dn: %s method: %s server credential: %s
 - Error number: [MY-011795](#); Symbol: [ER_LDAP_AUTH_STARTED_FOR_USER](#); SQLSTATE: [HY000](#)
Message: LDAP authentication started for user name: %s
 - Error number: [MY-011796](#); Symbol: [ER_LDAP_AUTH_DISTINGUISHED_NAME](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011797](#); Symbol: [ER_LDAP_AUTH_INIT_FAILED](#); SQLSTATE: [HY000](#)
Message: LDAP authentication initialize is failed with: %s
 - Error number: [MY-011798](#); Symbol: [ER_LDAP_AUTH_OR_GROUP_RETRIEVAL_FAILED](#); SQLSTATE: [HY000](#)

Message: LDAP authentication failed or group retrieval failed: %s

- Error number: [MY-011799](#); Symbol: [ER_LDAP_AUTH_USER_GROUP_SEARCH_FAILED](#); SQLSTATE: [HY000](#)

Message: Search user group has failed: %s

- Error number: [MY-011800](#); Symbol: [ER_LDAP_AUTH_USER_BIND_FAILED](#); SQLSTATE: [HY000](#)

Message: LDAP user bind has failed: %s

- Error number: [MY-011801](#); Symbol: [ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION](#); SQLSTATE: [HY000](#)

Message: Connection pool get: Failed to create LDAP connection. %s

- Error number: [MY-011802](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_CONNECTION](#); SQLSTATE: [HY000](#)

Message: Failed to create new LDAP connection: %s

- Error number: [MY-011803](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNECTION](#); SQLSTATE: [HY000](#)

Message: Failed to establish TLS connection: %s

- Error number: [MY-011804](#); Symbol: [ER_LDAP_AUTH_FAILED_TO_SEARCH_DN](#); SQLSTATE: [HY000](#)

Message: Failed to search user full dn: %s

- Error number: [MY-011805](#); Symbol: [ER_LDAP_AUTH_CONNECTION_POOL_REINIT_ENTER](#); SQLSTATE: [HY000](#)

Message: Ldap_connection_pool::reinit

- Error number: [MY-011806](#); Symbol: [ER_SYSTEMD_NOTIFY_PATH_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: The path '%s', from the NOTIFY_SOCKET environment variable, is too long. At %u bytes it exceeds the limit of %u bytes for an AF_UNIX socket.

- Error number: [MY-011807](#); Symbol: [ER_SYSTEMD_NOTIFY_CONNECT_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to connect to systemd notification socket named %s. Error: '%s'

- Error number: [MY-011808](#); Symbol: [ER_SYSTEMD_NOTIFY_WRITE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to write '%s' to systemd notification. Error: '%s'

- Error number: [MY-011809](#); Symbol: [ER_FOUND_MISSING_GTIDS](#); SQLSTATE: [HY000](#)

Message: Cannot replicate to server with server_uuid='%s' because the present server has purged required binary logs. The connecting server needs to replicate the missing transactions from elsewhere, or be replaced by a new server created from a more recent backup. To prevent this error in the future, consider increasing the binary log expiration period on the present server. %s.

- Error number: [MY-011810](#); Symbol: [ER_PID_FILE_PRIV_DIRECTORY_INSECURE](#); SQLSTATE: [HY000](#)

Message: Insecure configuration for --pid-file: Location '%s' in the path is accessible to all OS users. Consider choosing a different directory.

- Error number: MY-011811; Symbol: ER_CANT_CHECK_PID_PATH; SQLSTATE: HY000

Message: Can't start server: can't check PID filepath: %s

- Error number: MY-011812; Symbol: ER_VALIDATE_PWD_STATUS_VAR_REGISTRATION_FAILED; SQLSTATE: HY000

Message: validate_password status variables registration failed.

- Error number: MY-011813; Symbol: ER_VALIDATE_PWD_STATUS_VAR_UNREGISTRATION_FAILED; SQLSTATE: HY000

Message: validate_password status variables unregistration failed.

- Error number: MY-011814; Symbol: ER_VALIDATE_PWD_DICT_FILE_OPEN_FAILED; SQLSTATE: HY000

Message: Dictionary file open failed

- Error number: MY-011815; Symbol: ER_VALIDATE_PWD_COULD_BE_NULL; SQLSTATE: HY000

Message: given password string could be null

- Error number: MY-011816; Symbol: ER_VALIDATE_PWD_STRING_CONV_TO_LOWERCASE_FAILED; SQLSTATE: HY000

Message: failed to convert the password string to lower case

- Error number: MY-011817; Symbol: ER_VALIDATE_PWD_STRING_CONV_TO_BUFFER_FAILED; SQLSTATE: HY000

Message: failed to convert the password string into a buffer

- Error number: MY-011818; Symbol: ER_VALIDATE_PWD_STRING_HANDLER_MEM_ALLOCATION_FAILED; SQLSTATE: HY000

Message: memory allocation failed for string handler

- Error number: MY-011819; Symbol: ER_VALIDATE_PWD_STRONG_POLICY_DICT_FILE_UNSPECIFIED; SQLSTATE: HY000

Message: Since the validate_password_policy is mentioned as Strong, dictionary file must be specified

- Error number: MY-011820; Symbol: ER_VALIDATE_PWD_CONVERT_TO_BUFFER_FAILED; SQLSTATE: HY000

Message: convert_to_buffer service failed

- Error number: MY-011821; Symbol: ER_VALIDATE_PWD_VARIABLE_REGISTRATION_FAILED; SQLSTATE: HY000

Message: %s variable registration failed.

- Error number: MY-011822; Symbol: ER_VALIDATE_PWD_VARIABLE_UNREGISTRATION_FAILED; SQLSTATE: HY000

Message: %s variable unregistration failed.

- Error number: [MY-011823](#); Symbol: [ER_KEYRING_MIGRATION_EXTRA_OPTIONS](#); SQLSTATE: [HY000](#)

Message: Please specify options specific to keyring migration. Any additional options can be ignored.
NOTE: Although some options are valid, migration tool can still report error example: plugin variables for which plugin is not loaded yet.

- Error number: [MY-011825](#); Symbol: [ER_IB_MSG_0](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011826](#); Symbol: [ER_IB_MSG_1](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011827](#); Symbol: [ER_IB_MSG_2](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011828](#); Symbol: [ER_IB_MSG_3](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011829](#); Symbol: [ER_IB_MSG_4](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011830](#); Symbol: [ER_IB_MSG_5](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011831](#); Symbol: [ER_IB_MSG_6](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011832](#); Symbol: [ER_IB_MSG_7](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011833](#); Symbol: [ER_IB_MSG_8](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011834](#); Symbol: [ER_IB_MSG_9](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011835](#); Symbol: [ER_IB_MSG_10](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011836](#); Symbol: [ER_IB_MSG_11](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-011837](#); Symbol: [ER_IB_MSG_12](#); SQLSTATE: [HY000](#)

Message: %s

-
- Error number: [MY-011838](#); Symbol: [ER_IB_MSG_13](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011839](#); Symbol: [ER_IB_MSG_14](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011840](#); Symbol: [ER_IB_MSG_15](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011841](#); Symbol: [ER_IB_MSG_16](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011842](#); Symbol: [ER_IB_MSG_17](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011843](#); Symbol: [ER_IB_MSG_18](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011844](#); Symbol: [ER_IB_MSG_19](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011845](#); Symbol: [ER_IB_MSG_20](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011846](#); Symbol: [ER_IB_MSG_21](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011847](#); Symbol: [ER_IB_MSG_22](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011848](#); Symbol: [ER_IB_MSG_23](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011849](#); Symbol: [ER_IB_MSG_24](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011850](#); Symbol: [ER_IB_MSG_25](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011851](#); Symbol: [ER_IB_MSG_26](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011852](#); Symbol: [ER_IB_MSG_27](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-011853](#); Symbol: [ER_IB_MSG_28](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011854](#); Symbol: [ER_IB_MSG_29](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011855](#); Symbol: [ER_IB_MSG_30](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011857](#); Symbol: [ER_IB_MSG_32](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011858](#); Symbol: [ER_IB_MSG_33](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011859](#); Symbol: [ER_IB_MSG_34](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011860](#); Symbol: [ER_IB_MSG_35](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011861](#); Symbol: [ER_IB_MSG_36](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011862](#); Symbol: [ER_IB_MSG_37](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011863](#); Symbol: [ER_IB_MSG_38](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011864](#); Symbol: [ER_IB_MSG_39](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011865](#); Symbol: [ER_IB_MSG_40](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011866](#); Symbol: [ER_IB_MSG_41](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011867](#); Symbol: [ER_IB_MSG_42](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011868](#); Symbol: [ER_IB_MSG_43](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-011869](#); Symbol: [ER_IB_MSG_44](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011870](#); Symbol: [ER_IB_MSG_45](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011871](#); Symbol: [ER_IB_MSG_46](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011872](#); Symbol: [ER_IB_MSG_47](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011873](#); Symbol: [ER_IB_MSG_48](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011874](#); Symbol: [ER_IB_MSG_49](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011875](#); Symbol: [ER_IB_MSG_50](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011876](#); Symbol: [ER_IB_MSG_51](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011877](#); Symbol: [ER_IB_MSG_52](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011878](#); Symbol: [ER_IB_MSG_53](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011879](#); Symbol: [ER_IB_MSG_54](#); SQLSTATE: [HY000](#)
Message: Failed to set NUMA memory policy of buffer pool page frames with mbind(%p,%zu,%s,,,,,, %s) failed with %s
 - Error number: [MY-011880](#); Symbol: [ER_IB_MSG_55](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011881](#); Symbol: [ER_IB_MSG_56](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011882](#); Symbol: [ER_IB_MSG_57](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011883](#); Symbol: [ER_IB_MSG_58](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-011884](#); Symbol: [ER_IB_MSG_59](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011885](#); Symbol: [ER_IB_MSG_60](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011886](#); Symbol: [ER_IB_MSG_61](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011887](#); Symbol: [ER_IB_MSG_62](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011888](#); Symbol: [ER_IB_MSG_63](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011889](#); Symbol: [ER_IB_MSG_64](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011890](#); Symbol: [ER_IB_MSG_65](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011891](#); Symbol: [ER_IB_MSG_66](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011892](#); Symbol: [ER_IB_MSG_67](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011893](#); Symbol: [ER_IB_MSG_68](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011894](#); Symbol: [ER_IB_MSG_69](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011895](#); Symbol: [ER_IB_MSG_70](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011896](#); Symbol: [ER_IB_MSG_71](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011897](#); Symbol: [ER_IB_MSG_72](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011898](#); Symbol: [ER_IB_MSG_73](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-011899](#); Symbol: [ER_IB_MSG_74](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011900](#); Symbol: [ER_IB_MSG_75](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011901](#); Symbol: [ER_IB_MSG_76](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011902](#); Symbol: [ER_IB_MSG_77](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011903](#); Symbol: [ER_IB_MSG_78](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011904](#); Symbol: [ER_IB_MSG_79](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011905](#); Symbol: [ER_IB_MSG_80](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011906](#); Symbol: [ER_IB_MSG_81](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011907](#); Symbol: [ER_IB_MSG_82](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011908](#); Symbol: [ER_IB_MSG_83](#); SQLSTATE: [HY000](#)
Message: %s
[ER_IB_MSG_83](#) was removed after 8.4.4.
 - Error number: [MY-011908](#); Symbol: [ER_IB_ERR_PAGE_DIRTY_AT_SHUTDOWN](#); SQLSTATE: [HY000](#)
Message: Page still fixed or dirty at shutdown. %s
[ER_IB_ERR_PAGE_DIRTY_AT_SHUTDOWN](#) was added in 8.4.5.
 - Error number: [MY-011909](#); Symbol: [ER_IB_MSG_84](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011910](#); Symbol: [ER_IB_MSG_85](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011911](#); Symbol: [ER_IB_MSG_86](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-011920](#); Symbol: [ER_IB_MSG_95](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011921](#); Symbol: [ER_IB_MSG_96](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011922](#); Symbol: [ER_IB_MSG_97](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011923](#); Symbol: [ER_IB_MSG_98](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011924](#); Symbol: [ER_IB_MSG_99](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011925](#); Symbol: [ER_IB_MSG_100](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011926](#); Symbol: [ER_IB_MSG_101](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011927](#); Symbol: [ER_IB_MSG_102](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011928](#); Symbol: [ER_IB_MSG_103](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011929](#); Symbol: [ER_IB_MSG_104](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011930](#); Symbol: [ER_IB_MSG_105](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011931](#); Symbol: [ER_IB_MSG_106](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011932](#); Symbol: [ER_IB_MSG_107](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011933](#); Symbol: [ER_IB_MSG_108](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011934](#); Symbol: [ER_IB_MSG_109](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-011935](#); Symbol: [ER_IB_MSG_110](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011936](#); Symbol: [ER_IB_MSG_111](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011937](#); Symbol: [ER_IB_MSG_112](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011944](#); Symbol: [ER_IB_MSG_119](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011945](#); Symbol: [ER_IB_MSG_120](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011946](#); Symbol: [ER_IB_MSG_121](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011947](#); Symbol: [ER_IB_MSG_122](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011948](#); Symbol: [ER_IB_MSG_123](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011949](#); Symbol: [ER_IB_MSG_124](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011950](#); Symbol: [ER_IB_MSG_125](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011951](#); Symbol: [ER_IB_MSG_126](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011952](#); Symbol: [ER_IB_MSG_127](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011953](#); Symbol: [ER_IB_MSG_128](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011954](#); Symbol: [ER_IB_MSG_129](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011955](#); Symbol: [ER_IB_MSG_130](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-011956](#); Symbol: [ER_IB_MSG_131](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011957](#); Symbol: [ER_IB_MSG_132](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011958](#); Symbol: [ER_IB_MSG_133](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011959](#); Symbol: [ER_IB_MSG_134](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011960](#); Symbol: [ER_IB_MSG_135](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011961](#); Symbol: [ER_IB_MSG_136](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011962](#); Symbol: [ER_IB_MSG_137](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011963](#); Symbol: [ER_IB_MSG_138](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011964](#); Symbol: [ER_IB_MSG_139](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011965](#); Symbol: [ER_IB_MSG_140](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011966](#); Symbol: [ER_IB_MSG_141](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011967](#); Symbol: [ER_IB_MSG_142](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011968](#); Symbol: [ER_IB_MSG_143](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011969](#); Symbol: [ER_IB_MSG_144](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011970](#); Symbol: [ER_IB_MSG_145](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-011971](#); Symbol: [ER_IB_MSG_146](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011972](#); Symbol: [ER_IB_MSG_147](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011973](#); Symbol: [ER_IB_MSG_148](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011974](#); Symbol: [ER_IB_CLONE_INTERNAL](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011975](#); Symbol: [ER_IB_CLONE_TIMEOUT](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011976](#); Symbol: [ER_IB_CLONE_STATUS_FILE](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011977](#); Symbol: [ER_IB_CLONE_SQL](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011978](#); Symbol: [ER_IB_CLONE_VALIDATE](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011979](#); Symbol: [ER_IB_CLONE_PUNCH_HOLE](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011980](#); Symbol: [ER_IB_CLONE_GTID_PERSIST](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011981](#); Symbol: [ER_IB_MSG_156](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011982](#); Symbol: [ER_IB_MSG_157](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011983](#); Symbol: [ER_IB_MSG_158](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011984](#); Symbol: [ER_IB_MSG_159](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011985](#); Symbol: [ER_IB_MSG_160](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-011986](#); Symbol: [ER_IB_MSG_161](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011987](#); Symbol: [ER_IB_MSG_162](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011988](#); Symbol: [ER_IB_MSG_163](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011989](#); Symbol: [ER_IB_MSG_164](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011990](#); Symbol: [ER_IB_MSG_165](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011991](#); Symbol: [ER_IB_MSG_166](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011992](#); Symbol: [ER_IB_MSG_167](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011993](#); Symbol: [ER_IB_MSG_168](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011994](#); Symbol: [ER_IB_MSG_169](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011995](#); Symbol: [ER_IB_MSG_170](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011996](#); Symbol: [ER_IB_MSG_171](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011997](#); Symbol: [ER_IB_MSG_172](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011998](#); Symbol: [ER_IB_MSG_173](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-011999](#); Symbol: [ER_IB_MSG_174](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012000](#); Symbol: [ER_IB_MSG_175](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012001](#); Symbol: [ER_IB_MSG_176](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012002](#); Symbol: [ER_IB_MSG_177](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012003](#); Symbol: [ER_IB_MSG_178](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012004](#); Symbol: [ER_IB_MSG_179](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012005](#); Symbol: [ER_IB_MSG_180](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012006](#); Symbol: [ER_IB_LONG_AHI_DISABLE_WAIT](#); SQLSTATE: [HY000](#)
Message: Waited for %u secs for hash index ref_count (%zu) to drop to 0. index: "%s" table: "%s"
 - Error number: [MY-012007](#); Symbol: [ER_IB_MSG_182](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012008](#); Symbol: [ER_IB_MSG_183](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012009](#); Symbol: [ER_IB_MSG_184](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012012](#); Symbol: [ER_IB_MSG_187](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012013](#); Symbol: [ER_IB_MSG_188](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012014](#); Symbol: [ER_IB_MSG_189](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012015](#); Symbol: [ER_IB_MSG_190](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012016](#); Symbol: [ER_IB_MSG_191](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012017](#); Symbol: [ER_IB_MSG_192](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012018](#); Symbol: [ER_IB_MSG_193](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012019](#); Symbol: [ER_IB_MSG_194](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012020](#); Symbol: [ER_IB_MSG_195](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012021](#); Symbol: [ER_IB_MSG_196](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012022](#); Symbol: [ER_IB_MSG_197](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012023](#); Symbol: [ER_IB_MSG_198](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012024](#); Symbol: [ER_IB_MSG_199](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012025](#); Symbol: [ER_IB_MSG_200](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012026](#); Symbol: [ER_IB_MSG_201](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012027](#); Symbol: [ER_IB_MSG_202](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012028](#); Symbol: [ER_IB_MSG_203](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012029](#); Symbol: [ER_IB_MSG_204](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012030](#); Symbol: [ER_IB_MSG_205](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012031](#); Symbol: [ER_IB_MSG_206](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012032](#); Symbol: [ER_IB_MSG_207](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012033](#); Symbol: [ER_IB_MSG_208](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012034](#); Symbol: [ER_IB_MSG_209](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012035](#); Symbol: [ER_IB_MSG_210](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012036](#); Symbol: [ER_IB_MSG_211](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012037](#); Symbol: [ER_IB_MSG_212](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012038](#); Symbol: [ER_IB_MSG_213](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012039](#); Symbol: [ER_IB_MSG_214](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012040](#); Symbol: [ER_IB_MSG_215](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012041](#); Symbol: [ER_IB_MSG_216](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012042](#); Symbol: [ER_IB_MSG_217](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012043](#); Symbol: [ER_IB_MSG_218](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012044](#); Symbol: [ER_IB_MSG_219](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012045](#); Symbol: [ER_IB_MSG_220](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012046](#); Symbol: [ER_IB_MSG_221](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012047](#); Symbol: [ER_IB_MSG_222](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012048](#); Symbol: [ER_IB_MSG_223](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012049](#); Symbol: [ER_IB_MSG_224](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012050](#); Symbol: [ER_IB_MSG_225](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012051](#); Symbol: [ER_IB_MSG_226](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012054](#); Symbol: [ER_IB_MSG_229](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012055](#); Symbol: [ER_IB_MSG_230](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012056](#); Symbol: [ER_IB_MSG_231](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012057](#); Symbol: [ER_IB_MSG_232](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012058](#); Symbol: [ER_IB_MSG_233](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012059](#); Symbol: [ER_IB_MSG_234](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012060](#); Symbol: [ER_IB_MSG_235](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012061](#); Symbol: [ER_IB_MSG_236](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012062](#); Symbol: [ER_IB_MSG_237](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012063](#); Symbol: [ER_IB_MSG_238](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012064](#); Symbol: [ER_IB_MSG_239](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012065](#); Symbol: [ER_IB_MSG_240](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012066](#); Symbol: [ER_IB_MSG_241](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012067](#); Symbol: [ER_IB_MSG_242](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012068](#); Symbol: [ER_IB_MSG_243](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012069](#); Symbol: [ER_IB_MSG_244](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012070](#); Symbol: [ER_IB_MSG_245](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012071](#); Symbol: [ER_IB_MSG_246](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012072](#); Symbol: [ER_IB_MSG_247](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012073](#); Symbol: [ER_IB_MSG_248](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012074](#); Symbol: [ER_IB_MSG_249](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012075](#); Symbol: [ER_IB_MSG_250](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012076](#); Symbol: [ER_IB_MSG_251](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012077](#); Symbol: [ER_IB_MSG_252](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012078](#); Symbol: [ER_IB_MSG_253](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012079](#); Symbol: [ER_IB_MSG_254](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012080](#); Symbol: [ER_IB_MSG_255](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012081](#); Symbol: [ER_IB_MSG_256](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012082](#); Symbol: [ER_IB_MSG_257](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012083](#); Symbol: [ER_IB_MSG_258](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012084](#); Symbol: [ER_IB_MSG_259](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012085](#); Symbol: [ER_IB_MSG_260](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012086](#); Symbol: [ER_IB_MSG_261](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012087](#); Symbol: [ER_IB_MSG_262](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012088](#); Symbol: [ER_IB_MSG_263](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012089](#); Symbol: [ER_IB_MSG_264](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012090](#); Symbol: [ER_IB_MSG_265](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012091](#); Symbol: [ER_IB_MSG_266](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012092](#); Symbol: [ER_IB_MSG_267](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012093](#); Symbol: [ER_IB_MSG_268](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012094](#); Symbol: [ER_IB_MSG_269](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012095](#); Symbol: [ER_IB_MSG_270](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012096](#); Symbol: [ER_IB_MSG_271](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012097](#); Symbol: [ER_IB_MSG_272](#); SQLSTATE: [HY000](#)
Message: Table flags are 0x%lx in the data dictionary but the flags in file %s are 0x%llx!
 - Error number: [MY-012098](#); Symbol: [ER_IB_MSG_273](#); SQLSTATE: [HY000](#)
Message: Can't read encryption key from file %s!
 - Error number: [MY-012103](#); Symbol: [ER_IB_MSG_278](#); SQLSTATE: [HY000](#)
Message: Tablespace %s, waiting for IO to stop for %lld seconds
 - Error number: [MY-012105](#); Symbol: [ER_IB_MSG_280](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012106](#); Symbol: [ER_IB_MSG_281](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012107](#); Symbol: [ER_IB_MSG_282](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012108](#); Symbol: [ER_IB_MSG_283](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012109](#); Symbol: [ER_IB_MSG_284](#); SQLSTATE: [HY000](#)
Message: You must raise the value of innodb_open_files in my.cnf! Remember that InnoDB keeps all redo log files and all system tablespace files open for the whole time mysqld is running, and needs to open also some .ibd files if the file-per-table storage model is used. Current open files %zu, max allowed open files %zu.
 - Error number: [MY-012110](#); Symbol: [ER_IB_MSG_285](#); SQLSTATE: [HY000](#)
Message: Max tablespace id is too high, %lu
 - Error number: [MY-012111](#); Symbol: [ER_IB_WARN_ACCESSING_NONEXISTINC_SPACE](#); SQLSTATE: [HY000](#)
Message: Trying to access missing tablespace %lu
 - Error number: [MY-012112](#); Symbol: [ER_IB_MSG_287](#); SQLSTATE: [HY000](#)
Message: Trying to close/delete tablespace '%s' but there are %lu pending operations on it.
 - Error number: [MY-012113](#); Symbol: [ER_IB_MSG_288](#); SQLSTATE: [HY000](#)
Message: Trying to delete/close tablespace '%s' but there are %lu flushes and %zu pending I/O's on it.

-
- Error number: [MY-012114](#); Symbol: [ER_IB_MSG_289](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012116](#); Symbol: [ER_IB_MSG_291](#); SQLSTATE: [HY000](#)
Message: While deleting tablespace %lu in DISCARD TABLESPACE. File rename/delete failed: %s
 - Error number: [MY-012117](#); Symbol: [ER_IB_MSG_292](#); SQLSTATE: [HY000](#)
Message: Cannot delete tablespace %lu in DISCARD TABLESPACE: %s
 - Error number: [MY-012118](#); Symbol: [ER_IB_MSG_293](#); SQLSTATE: [HY000](#)
Message: Cannot rename '%s' to '%s' for space ID %lu because the source file does not exist.
 - Error number: [MY-012119](#); Symbol: [ER_IB_MSG_294](#); SQLSTATE: [HY000](#)
Message: Cannot rename '%s' to '%s' for space ID %lu because the target file exists. Remove the target file and try again.
 - Error number: [MY-012120](#); Symbol: [ER_IB_MSG_295](#); SQLSTATE: [HY000](#)
Message: Cannot rename file '%s' (space id %lu) retried %llu times. There are either pending IOs or flushes or the file is being extended.
 - Error number: [MY-012121](#); Symbol: [ER_IB_MSG_296](#); SQLSTATE: [HY000](#)
Message: Cannot find space id %lu in the tablespace memory cache, though the file '%s' in a rename operation should have that ID.
 - Error number: [MY-012122](#); Symbol: [ER_IB_MSG_297](#); SQLSTATE: [HY000](#)
Message: Rename waiting for IO to resume
 - Error number: [MY-012123](#); Symbol: [ER_IB_MSG_298](#); SQLSTATE: [HY000](#)
Message: Cannot find tablespace for '%s' in the tablespace memory cache
 - Error number: [MY-012124](#); Symbol: [ER_IB_MSG_299](#); SQLSTATE: [HY000](#)
Message: Cannot find tablespace for '%s' in the tablespace memory cache
 - Error number: [MY-012125](#); Symbol: [ER_IB_MSG_300](#); SQLSTATE: [HY000](#)
Message: Tablespace '%s' is already in the tablespace memory cache
 - Error number: [MY-012126](#); Symbol: [ER_IB_MSG_301](#); SQLSTATE: [HY000](#)
Message: Cannot create file '%s'
 - Error number: [MY-012127](#); Symbol: [ER_IB_MSG_UNEXPECTED_FILE_EXISTS](#); SQLSTATE: [HY000](#)
Message: The file '%s' already exists though the corresponding table did not exist. Have you moved InnoDB .ibd files around without using the SQL commands DISCARD TABLESPACE and IMPORT TABLESPACE, or did mysqld crash in the middle of CREATE TABLE? You can resolve the problem by removing the file '%s' under the 'datadir' of MySQL.
 - Error number: [MY-012128](#); Symbol: [ER_IB_MSG_303](#); SQLSTATE: [HY000](#)

Message: posix_fallocate(): Failed to preallocate data for file %s, desired size %llu Operating system error number %d - %s. Check that the disk is not full or a disk quota exceeded. Make sure the file system supports this function. Refer to your operating system documentation for operating system error code information.

- Error number: [MY-012129](#); Symbol: [ER_IB_MSG_304](#); SQLSTATE: [HY000](#)

Message: Could not write the first page to tablespace '%s'

- Error number: [MY-012130](#); Symbol: [ER_IB_MSG_305](#); SQLSTATE: [HY000](#)

Message: File flush of tablespace '%s' failed

- Error number: [MY-012131](#); Symbol: [ER_IB_MSG_306](#); SQLSTATE: [HY000](#)

Message: Could not find a valid tablespace file for `%s`. %s

- Error number: [MY-012132](#); Symbol: [ER_IB_MSG_307](#); SQLSTATE: [HY000](#)

Message: Ignoring data file '%s' with space ID %lu. Another data file called '%s' exists with the same space ID

- Error number: [MY-012133](#); Symbol: [ER_IB_MSG_308](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012134](#); Symbol: [ER_IB_MSG_309](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012135](#); Symbol: [ER_IB_MSG_310](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012136](#); Symbol: [ER_IB_MSG_311](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012137](#); Symbol: [ER_IB_MSG_312](#); SQLSTATE: [HY000](#)

Message: Can't set encryption information for tablespace %s!

- Error number: [MY-012138](#); Symbol: [ER_IB_MSG_313](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012139](#); Symbol: [ER_IB_MSG_314](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012140](#); Symbol: [ER_IB_MSG_315](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012141](#); Symbol: [ER_IB_MSG_316](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012142](#); Symbol: [ER_IB_MSG_317](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012143](#); Symbol: [ER_IB_MSG_318](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012144](#); Symbol: [ER_IB_MSG_319](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012145](#); Symbol: [ER_IB_MSG_320](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012146](#); Symbol: [ER_IB_MSG_321](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012147](#); Symbol: [ER_IB_MSG_322](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012148](#); Symbol: [ER_IB_MSG_323](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012149](#); Symbol: [ER_IB_MSG_324](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012150](#); Symbol: [ER_IB_MSG_325](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012151](#); Symbol: [ER_IB_MSG_326](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012153](#); Symbol: [ER_IB_MSG_328](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012154](#); Symbol: [ER_IB_MSG_329](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012155](#); Symbol: [ER_IB_MSG_330](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012156](#); Symbol: [ER_IB_MSG_331](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012157](#); Symbol: [ER_IB_MSG_332](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012158](#); Symbol: [ER_IB_MSG_333](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012159](#); Symbol: [ER_IB_MSG_334](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012160](#); Symbol: [ER_IB_MSG_335](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012161](#); Symbol: [ER_IB_MSG_336](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012162](#); Symbol: [ER_IB_MSG_337](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012163](#); Symbol: [ER_IB_MSG_338](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012164](#); Symbol: [ER_IB_MSG_339](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012165](#); Symbol: [ER_IB_MSG_340](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012166](#); Symbol: [ER_IB_MSG_341](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012167](#); Symbol: [ER_IB_MSG_342](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012168](#); Symbol: [ER_IB_MSG_343](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012169](#); Symbol: [ER_IB_MSG_344](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012170](#); Symbol: [ER_IB_MSG_345](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012171](#); Symbol: [ER_IB_MSG_346](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012172](#); Symbol: [ER_IB_MSG_347](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012173](#); Symbol: [ER_IB_MSG_348](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012174](#); Symbol: [ER_IB_MSG_349](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012175](#); Symbol: [ER_IB_MSG_350](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012177](#); Symbol: [ER_IB_MSG_UNPROTECTED_LOCATION_ALLOWED](#); SQLSTATE: [HY000](#)

Message: The datafile '%s' for tablespace %s is in an unprotected location. This file cannot be recovered after a crash until this location is added to innodb_directories.

- Error number: [MY-012179](#); Symbol: [ER_IB_MSG_354](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012180](#); Symbol: [ER_IB_MSG_355](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012181](#); Symbol: [ER_IB_MSG_356](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012182](#); Symbol: [ER_IB_MSG_357](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012183](#); Symbol: [ER_IB_MSG_358](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012184](#); Symbol: [ER_IB_MSG_359](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012185](#); Symbol: [ER_IB_MSG_360](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012186](#); Symbol: [ER_IB_MSG_361](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012187](#); Symbol: [ER_IB_MSG_362](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012189](#); Symbol: [ER_IB_MSG_364](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012190](#); Symbol: [ER_IB_MSG_365](#); SQLSTATE: [HY000](#)

Message: %s

-
- Error number: [MY-012191](#); Symbol: [ER_IB_MSG_IGNORE_SCAN_PATH](#); SQLSTATE: [HY000](#)
Message: Scan path '%s' is ignored because %s
 - Error number: [MY-012192](#); Symbol: [ER_IB_MSG_367](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012193](#); Symbol: [ER_IB_MSG_368](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012194](#); Symbol: [ER_IB_MSG_369](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012195](#); Symbol: [ER_IB_MSG_370](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012196](#); Symbol: [ER_IB_MSG_371](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012197](#); Symbol: [ER_IB_MSG_372](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012198](#); Symbol: [ER_IB_MSG_373](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012199](#); Symbol: [ER_IB_MSG_374](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012200](#); Symbol: [ER_IB_MSG_375](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012201](#); Symbol: [ER_IB_MSG_376](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012202](#); Symbol: [ER_IB_MSG_377](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012203](#); Symbol: [ER_IB_MSG_378](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012204](#); Symbol: [ER_IB_MSG_379](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012205](#); Symbol: [ER_IB_MSG_380](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012206](#); Symbol: [ER_IB_MSG_381](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012207](#); Symbol: [ER_IB_MSG_382](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012208](#); Symbol: [ER_IB_MSG_383](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012209](#); Symbol: [ER_IB_MSG_384](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012210](#); Symbol: [ER_IB_MSG_385](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012211](#); Symbol: [ER_IB_MSG_386](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012212](#); Symbol: [ER_IB_MSG_387](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012213](#); Symbol: [ER_IB_MSG_GENERAL_TABLESPACE_UNDER_DATADIR](#); SQLSTATE: [HY000](#)

Message: A general tablespace cannot be located under the datadir. Cannot open file '%s'.

- Error number: [MY-012214](#); Symbol: [ER_IB_MSG_IMPLICIT_TABLESPACE_IN_DATADIR](#); SQLSTATE: [HY000](#)

Message: A file-per-table tablespace cannot be located in the datadir. Cannot open file '%s'.

- Error number: [MY-012215](#); Symbol: [ER_IB_MSG_390](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012216](#); Symbol: [ER_IB_MSG_391](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012217](#); Symbol: [ER_IB_MSG_392](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012218](#); Symbol: [ER_IB_MSG_393](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012219](#); Symbol: [ER_IB_MSG_394](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012220](#); Symbol: [ER_IB_MSG_395](#); SQLSTATE: [HY000](#)

Message: %s

-
- Error number: [MY-012221](#); Symbol: [ER_IB_MSG_396](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012222](#); Symbol: [ER_IB_MSG_397](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012223](#); Symbol: [ER_IB_MSG_398](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012224](#); Symbol: [ER_IB_MSG_399](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012226](#); Symbol: [ER_IB_MSG_401](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012227](#); Symbol: [ER_IB_MSG_402](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012228](#); Symbol: [ER_IB_MSG_403](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012229](#); Symbol: [ER_IB_MSG_404](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012230](#); Symbol: [ER_IB_MSG_405](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012231](#); Symbol: [ER_IB_MSG_406](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012232](#); Symbol: [ER_IB_MSG_407](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012233](#); Symbol: [ER_IB_MSG_408](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012234](#); Symbol: [ER_IB_MSG_409](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012235](#); Symbol: [ER_IB_MSG_410](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012236](#); Symbol: [ER_IB_MSG_411](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012237](#); Symbol: [ER_IB_MSG_412](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012238](#); Symbol: [ER_IB_MSG_413](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012239](#); Symbol: [ER_IB_MSG_414](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012240](#); Symbol: [ER_IB_MSG_415](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012241](#); Symbol: [ER_IB_MSG_416](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012242](#); Symbol: [ER_IB_MSG_417](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012243](#); Symbol: [ER_IB_MSG_418](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012244](#); Symbol: [ER_IB_MSG_419](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012245](#); Symbol: [ER_IB_MSG_420](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012246](#); Symbol: [ER_IB_MSG_421](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012247](#); Symbol: [ER_IB_MSG_422](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012248](#); Symbol: [ER_IB_MSG_423](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012249](#); Symbol: [ER_IB_MSG_424](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012250](#); Symbol: [ER_IB_MSG_425](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012251](#); Symbol: [ER_IB_MSG_426](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012252](#); Symbol: [ER_IB_MSG_427](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012253](#); Symbol: [ER_IB_MSG_428](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012254](#); Symbol: [ER_IB_MSG_429](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012255](#); Symbol: [ER_IB_MSG_430](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012256](#); Symbol: [ER_IB_MSG_431](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012257](#); Symbol: [ER_IB_MSG_432](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012258](#); Symbol: [ER_IB_MSG_433](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012259](#); Symbol: [ER_IB_MSG_434](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012260](#); Symbol: [ER_IB_MSG_435](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012261](#); Symbol: [ER_IB_MSG_436](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012262](#); Symbol: [ER_IB_MSG_437](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012263](#); Symbol: [ER_IB_MSG_438](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012264](#); Symbol: [ER_IB_MSG_439](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012265](#); Symbol: [ER_IB_MSG_440](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012266](#); Symbol: [ER_IB_MSG_441](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012267](#); Symbol: [ER_IB_MSG_442](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012268](#); Symbol: [ER_IB_MSG_443](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012270](#); Symbol: [ER_IB_MSG_445](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012271](#); Symbol: [ER_IB_MSG_446](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012272](#); Symbol: [ER_IB_MSG_447](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012273](#); Symbol: [ER_IB_MSG_448](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012274](#); Symbol: [ER_IB_MSG_449](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012275](#); Symbol: [ER_IB_MSG_450](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012276](#); Symbol: [ER_IB_MSG_451](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012277](#); Symbol: [ER_IB_MSG_452](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012278](#); Symbol: [ER_IB_MSG_453](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012279](#); Symbol: [ER_IB_MSG_454](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012280](#); Symbol: [ER_IB_MSG_455](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012281](#); Symbol: [ER_IB_MSG_456](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012282](#); Symbol: [ER_IB_MSG_457](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012283](#); Symbol: [ER_IB_MSG_458](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012284](#); Symbol: [ER_IB_MSG_459](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012285](#); Symbol: [ER_IB_MSG_460](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012286](#); Symbol: [ER_IB_MSG_461](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012287](#); Symbol: [ER_IB_MSG_462](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012288](#); Symbol: [ER_IB_MSG_463](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012289](#); Symbol: [ER_IB_MSG_464](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012290](#); Symbol: [ER_IB_MSG_465](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012291](#); Symbol: [ER_IB_MSG_466](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012292](#); Symbol: [ER_IB_MSG_467](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012293](#); Symbol: [ER_IB_MSG_468](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012294](#); Symbol: [ER_IB_MSG_469](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012295](#); Symbol: [ER_IB_MSG_470](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012296](#); Symbol: [ER_IB_MSG_471](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012297](#); Symbol: [ER_IB_MSG_472](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012298](#); Symbol: [ER_IB_MSG_473](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012299](#); Symbol: [ER_IB_MSG_474](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012300](#); Symbol: [ER_IB_MSG_475](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012301](#); Symbol: [ER_IB_MSG_476](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012302](#); Symbol: [ER_IB_MSG_477](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012303](#); Symbol: [ER_IB_MSG_478](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012304](#); Symbol: [ER_IB_MSG_479](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012305](#); Symbol: [ER_IB_MSG_480](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012306](#); Symbol: [ER_IB_MSG_481](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012307](#); Symbol: [ER_IB_MSG_482](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012308](#); Symbol: [ER_IB_MSG_483](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012309](#); Symbol: [ER_IB_MSG_484](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012310](#); Symbol: [ER_IB_MSG_485](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012311](#); Symbol: [ER_IB_MSG_486](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012312](#); Symbol: [ER_IB_MSG_487](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012313](#); Symbol: [ER_IB_MSG_488](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012314](#); Symbol: [ER_IB_MSG_489](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012315](#); Symbol: [ER_IB_MSG_490](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012316](#); Symbol: [ER_IB_MSG_491](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012317](#); Symbol: [ER_IB_MSG_492](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012318](#); Symbol: [ER_IB_MSG_493](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012319](#); Symbol: [ER_IB_MSG_494](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012320](#); Symbol: [ER_IB_MSG_495](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012321](#); Symbol: [ER_IB_MSG_496](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012322](#); Symbol: [ER_IB_MSG_497](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012323](#); Symbol: [ER_IB_MSG_498](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012324](#); Symbol: [ER_IB_MSG_499](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012325](#); Symbol: [ER_IB_MSG_500](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012326](#); Symbol: [ER_IB_MSG_501](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012327](#); Symbol: [ER_IB_MSG_502](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012328](#); Symbol: [ER_IB_MSG_503](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012329](#); Symbol: [ER_IB_MSG_504](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012330](#); Symbol: [ER_IB_MSG_505](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012331](#); Symbol: [ER_IB_MSG_506](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012332](#); Symbol: [ER_IB_MSG_507](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012333](#); Symbol: [ER_IB_MSG_508](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012334](#); Symbol: [ER_IB_MSG_509](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012335](#); Symbol: [ER_IB_MSG_510](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012336](#); Symbol: [ER_IB_MSG_511](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012337](#); Symbol: [ER_IB_MSG_512](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012338](#); Symbol: [ER_IB_MSG_513](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012339](#); Symbol: [ER_IB_MSG_514](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012340](#); Symbol: [ER_IB_MSG_515](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012341](#); Symbol: [ER_IB_MSG_516](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012342](#); Symbol: [ER_IB_MSG_517](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012343](#); Symbol: [ER_IB_MSG_518](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012344](#); Symbol: [ER_IB_MSG_519](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012345](#); Symbol: [ER_IB_MSG_520](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012346](#); Symbol: [ER_IB_MSG_521](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012347](#); Symbol: [ER_IB_MSG_522](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012348](#); Symbol: [ER_IB_MSG_523](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012349](#); Symbol: [ER_IB_MSG_524](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012350](#); Symbol: [ER_IB_MSG_525](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012351](#); Symbol: [ER_IB_MSG_526](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012352](#); Symbol: [ER_IB_MSG_527](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012355](#); Symbol: [ER_IB_MSG_530](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012356](#); Symbol: [ER_IB_MSG_531](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012357](#); Symbol: [ER_IB_MSG_532](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012358](#); Symbol: [ER_IB_MSG_533](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012359](#); Symbol: [ER_IB_MSG_534](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012362](#); Symbol: [ER_IB_MSG_537](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012363](#); Symbol: [ER_IB_MSG_538](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012364](#); Symbol: [ER_IB_MSG_539](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012365](#); Symbol: [ER_IB_MSG_540](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012366](#); Symbol: [ER_IB_MSG_541](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012368](#); Symbol: [ER_IB_MSG_543](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012369](#); Symbol: [ER_IB_MSG_544](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012370](#); Symbol: [ER_IB_MSG_545](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012371](#); Symbol: [ER_IB_MSG_546](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012372](#); Symbol: [ER_IB_MSG_547](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012373](#); Symbol: [ER_IB_MSG_548](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012374](#); Symbol: [ER_IB_MSG_549](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012375](#); Symbol: [ER_IB_MSG_550](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012376](#); Symbol: [ER_IB_MSG_551](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012377](#); Symbol: [ER_IB_MSG_552](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012378](#); Symbol: [ER_IB_MSG_553](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012379](#); Symbol: [ER_IB_MSG_554](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012380](#); Symbol: [ER_IB_MSG_555](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012381](#); Symbol: [ER_IB_MSG_556](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012382](#); Symbol: [ER_IB_MSG_557](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012383](#); Symbol: [ER_IB_MSG_558](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012384](#); Symbol: [ER_IB_MSG_559](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012385](#); Symbol: [ER_IB_MSG_560](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012386](#); Symbol: [ER_IB_MSG_561](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012387](#); Symbol: [ER_IB_MSG_562](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012388](#); Symbol: [ER_IB_MSG_563](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012389](#); Symbol: [ER_IB_MSG_564](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012390](#); Symbol: [ER_IB_MSG_INVALID_LOCATION_FOR_TABLE](#); SQLSTATE: [HY000](#)
Message: Cannot create a tablespace for table %s because the directory is not a valid location. %s
 - Error number: [MY-012391](#); Symbol: [ER_IB_MSG_566](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012392](#); Symbol: [ER_IB_MSG_567](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012393](#); Symbol: [ER_IB_MSG_568](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012394](#); Symbol: [ER_IB_MSG_569](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012395](#); Symbol: [ER_IB_MSG_570](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012396](#); Symbol: [ER_IB_MSG_571](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012398](#); Symbol: [ER_IB_MSG_573](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012399](#); Symbol: [ER_IB_MSG_574](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012403](#); Symbol: [ER_IB_MSG_578](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012404](#); Symbol: [ER_IB_MSG_579](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012405](#); Symbol: [ER_IB_MSG_580](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012406](#); Symbol: [ER_IB_MSG_581](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012407](#); Symbol: [ER_IB_MSG_582](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012408](#); Symbol: [ER_IB_MSG_583](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012409](#); Symbol: [ER_IB_MSG_584](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012410](#); Symbol: [ER_IB_MSG_585](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012411](#); Symbol: [ER_IB_MSG_586](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012412](#); Symbol: [ER_IB_MSG_587](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012413](#); Symbol: [ER_IB_MSG_588](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012414](#); Symbol: [ER_IB_MSG_589](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012415](#); Symbol: [ER_IB_MSG_590](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012416](#); Symbol: [ER_IB_MSG_591](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012417](#); Symbol: [ER_IB_MSG_592](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012418](#); Symbol: [ER_IB_MSG_593](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012419](#); Symbol: [ER_IB_MSG_594](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012420](#); Symbol: [ER_IB_MSG_595](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012421](#); Symbol: [ER_IB_MSG_596](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012422](#); Symbol: [ER_IB_MSG_597](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012423](#); Symbol: [ER_IB_MSG_598](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012424](#); Symbol: [ER_IB_MSG_599](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012425](#); Symbol: [ER_IB_MSG_600](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012426](#); Symbol: [ER_IB_MSG_601](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012427](#); Symbol: [ER_IB_MSG_602](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012428](#); Symbol: [ER_IB_MSG_603](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012429](#); Symbol: [ER_IB_MSG_604](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012430](#); Symbol: [ER_IB_MSG_605](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012431](#); Symbol: [ER_IB_MSG_606](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012432](#); Symbol: [ER_IB_MSG_607](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012433](#); Symbol: [ER_IB_MSG_608](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012434](#); Symbol: [ER_IB_MSG_609](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012436](#); Symbol: [ER_IB_MSG_611](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012437](#); Symbol: [ER_IB_MSG_612](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012438](#); Symbol: [ER_IB_MSG_613](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012439](#); Symbol: [ER_IB_MSG_614](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012440](#); Symbol: [ER_IB_MSG_615](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012441](#); Symbol: [ER_IB_MSG_616](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012442](#); Symbol: [ER_IB_MSG_617](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012444](#); Symbol: [ER_IB_MSG_619](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012445](#); Symbol: [ER_IB_MSG_IBUF_CURSOR_RESTORATION_FAILED](#); SQLSTATE: [HY000](#)
Message: ibuf cursor restoration fails!. ibuf record inserted to page %s:%s
 - Error number: [MY-012447](#); Symbol: [ER_IB_MSG_IBUF_FAILED_TO_RESTORE_POSITION](#); SQLSTATE: [HY000](#)
Message: Failed to restore ibuf position.
 - Error number: [MY-012448](#); Symbol: [ER_IB_MSG_623](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012449](#); Symbol: [ER_IB_MSG_624](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012451](#); Symbol: [ER_IB_MSG_626](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012452](#); Symbol: [ER_IB_MSG_627](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012453](#); Symbol: [ER_IB_MSG_628](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012454](#); Symbol: [ER_IB_MSG_629](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012455](#); Symbol: [ER_IB_MSG_630](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012456](#); Symbol: [ER_IB_MSG_631](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012457](#); Symbol: [ER_IB_MSG_632](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012458](#); Symbol: [ER_IB_MSG_633](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012459](#); Symbol: [ER_IB_MSG_634](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012460](#); Symbol: [ER_IB_MSG_635](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012461](#); Symbol: [ER_IB_MSG_636](#); SQLSTATE: [HY000](#)

Message: Blocked High Priority Transaction (ID %llu, Thread ID %s) forces rollback of the blocking transaction (ID %llu - %s).

- Error number: [MY-012462](#); Symbol: [ER_IB_MSG_637](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012463](#); Symbol: [ER_IB_MSG_638](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012464](#); Symbol: [ER_IB_MSG_639](#); SQLSTATE: [HY000](#)

Message: Blocked High Priority Transaction (Thread ID %s) waking up the blocking transaction (ID %llu) by pretending it's a deadlock victim.

- Error number: [MY-012467](#); Symbol: [ER_IB_MSG_642](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012468](#); Symbol: [ER_IB_MSG_643](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012469](#); Symbol: [ER_IB_MSG_644](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012470](#); Symbol: [ER_IB_MSG_645](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012471](#); Symbol: [ER_IB_MSG_646](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012472](#); Symbol: [ER_IB_MSG_647](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012473](#); Symbol: [ER_IB_MSG_648](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012474](#); Symbol: [ER_IB_MSG_649](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012475](#); Symbol: [ER_IB_MSG_650](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012476](#); Symbol: [ER_IB_MSG_651](#); SQLSTATE: [HY000](#)

Message: %s

-
- Error number: [MY-012477](#); Symbol: [ER_IB_MSG_652](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012478](#); Symbol: [ER_IB_MSG_DDL_LOG_DELETE_BY_ID_OK](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012479](#); Symbol: [ER_IB_MSG_654](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012480](#); Symbol: [ER_IB_MSG_655](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012481](#); Symbol: [ER_IB_MSG_656](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012482](#); Symbol: [ER_IB_MSG_657](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012483](#); Symbol: [ER_IB_MSG_658](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012484](#); Symbol: [ER_IB_MSG_659](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012485](#); Symbol: [ER_IB_MSG_660](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012486](#); Symbol: [ER_IB_MSG_661](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012487](#); Symbol: [ER_IB_MSG_662](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012488](#); Symbol: [ER_IB_MSG_663](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012519](#); Symbol: [ER_IB_MSG_694](#); SQLSTATE: [HY000](#)
Message: ##### CORRUPT LOG RECORD FOUND #####
 - Error number: [MY-012520](#); Symbol: [ER_IB_MSG_695](#); SQLSTATE: [HY000](#)
Message: Log record type %d, page %lu:%lu. Log parsing proceeded successfully up to %llu. Previous log record type %d, is multi %llu Recv offset %zd, prev %llu
 - Error number: [MY-012521](#); Symbol: [ER_IB_MSG_696](#); SQLSTATE: [HY000](#)
Message: Hex dump starting %llu bytes before and ending %llu bytes after the corrupted record:

-
- Error number: [MY-012522](#); Symbol: [ER_IB_MSG_697](#); SQLSTATE: [HY000](#)
Message: Set innodb_force_recovery to ignore this error.
 - Error number: [MY-012523](#); Symbol: [ER_IB_MSG_LOG_CORRUPT](#); SQLSTATE: [HY000](#)
Message: The redo log file may have been corrupt and it is possible that the log scan did not proceed far enough in recovery! Please run CHECK TABLE on your InnoDB tables to check that they are ok! If mysqld crashes after this recovery; %s
 - Error number: [MY-012524](#); Symbol: [ER_IB_MSG_699](#); SQLSTATE: [HY000](#)
Message: %llu pages with log records were left unprocessed!
 - Error number: [MY-012525](#); Symbol: [ER_IB_MSG_LOG_FORMAT_OLD_AND_LOG_CORRUPTED](#); SQLSTATE: [HY000](#)
Message: Upgrade after a crash is not supported. This redo log was created with %s, and it appears corrupted. Please follow the instructions at %s
 - Error number: [MY-012526](#); Symbol: [ER_IB_MSG_LOG_FORMAT_OLD_AND_NO_CLEAN_SHUTDOWN](#); SQLSTATE: [HY000](#)
Message: Upgrade is not supported after a crash or shutdown with innodb_fast_shutdown = 2. This redo log was created with %s, and it appears logically non empty. Please follow the instructions at %s
 - Error number: [MY-012529](#); Symbol: [ER_IB_MSG_LOG_FORMAT_BEFORE_8_0_30](#); SQLSTATE: [HY000](#)
Message: Redo log format is v%lu. The redo log was created before MySQL 8.0.30.
 - Error number: [MY-012530](#); Symbol: [ER_IB_MSG_LOG_FILE_FORMAT_UNKNOWN](#); SQLSTATE: [HY000](#)
Message: Unknown redo log format (v%lu) in file %s. Please follow the instructions at %s
 - Error number: [MY-012531](#); Symbol: [ER_IB_MSG_RECOVERY_CHECKPOINT_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: No valid checkpoint found (corrupted redo log). You can try --innodb-force-recovery=6 as a last resort.
 - Error number: [MY-012532](#); Symbol: [ER_IB_MSG_707](#); SQLSTATE: [HY000](#)
Message: Applying a batch of %llu redo log records ...
 - Error number: [MY-012533](#); Symbol: [ER_IB_MSG_708](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012534](#); Symbol: [ER_IB_MSG_709](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012535](#); Symbol: [ER_IB_MSG_710](#); SQLSTATE: [HY000](#)
Message: Apply batch completed!
 - Error number: [MY-012536](#); Symbol: [ER_IB_MSG_711](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012537](#); Symbol: [ER_IB_MSG_712](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012538](#); Symbol: [ER_IB_MSG_713](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012539](#); Symbol: [ER_IB_MSG_714](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012540](#); Symbol: [ER_IB_MSG_715](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012541](#); Symbol: [ER_IB_MSG_716](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012543](#); Symbol: [ER_IB_MSG_718](#); SQLSTATE: [HY000](#)
Message: Extending tablespace : %lu space name: %s to new size: %lu pages during recovery.
 - Error number: [MY-012544](#); Symbol: [ER_IB_MSG_719](#); SQLSTATE: [HY000](#)
Message: Could not extend tablespace: %lu space name: %s to new size: %lu pages during recovery.
 - Error number: [MY-012545](#); Symbol: [ER_IB_MSG_720](#); SQLSTATE: [HY000](#)
Message: Log block %lu at lsn %llu has valid header, but checksum field contains %lu, should be %lu.
 - Error number: [MY-012546](#); Symbol: [ER_IB_MSG_RECOVERY_SKIPPED_IN_READ_ONLY_MODE](#); SQLSTATE: [HY000](#)
Message: Skipped necessary redo log applying, --innodb-read-only set!
 - Error number: [MY-012547](#); Symbol: [ER_IB_MSG_722](#); SQLSTATE: [HY000](#)
Message: Log scan progressed past the checkpoint LSN %llu.
 - Error number: [MY-012548](#); Symbol: [ER_IB_MSG_723](#); SQLSTATE: [HY000](#)
Message: Log parsing buffer overflow. Recovery may have failed! Please set log_buffer_size to a value higher than %lu.
 - Error number: [MY-012549](#); Symbol: [ER_IB_MSG_724](#); SQLSTATE: [HY000](#)
Message: Set innodb_force_recovery to ignore this error.
 - Error number: [MY-012550](#); Symbol: [ER_IB_MSG_725](#); SQLSTATE: [HY000](#)
Message: Doing recovery: scanned up to log sequence number %llu
 - Error number: [MY-012551](#); Symbol: [ER_IB_MSG_726](#); SQLSTATE: [HY000](#)
Message: Database was not shutdown normally!
 - Error number: [MY-012552](#); Symbol: [ER_IB_MSG_727](#); SQLSTATE: [HY000](#)

Message: Starting crash recovery.

- Error number: `MY-012553`; Symbol: `ER_IB_MSG_728`; SQLSTATE: `HY000`

Message: The user has set `SRV_FORCE_NO_LOG_REDO` on, skipping log redo

- Error number: `MY-012554`; Symbol: `ER_IB_MSG_LOG_FILES_CREATED_BY_MEB_AND_READ_ONLY_MODE`; SQLSTATE: `HY000`

Message: Cannot restore from mysqlbackup, InnoDB running in read-only mode!

- Error number: `MY-012555`; Symbol: `ER_IB_MSG_LOG_FILES_CREATED_BY_MEB`; SQLSTATE: `HY000`

Message: The redo log file was created by mysqlbackup --apply-log at %s. The following crash recovery is part of a normal restore.

- Error number: `MY-012556`; Symbol: `ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE`; SQLSTATE: `HY000`

Message: Opening cloned database

- Error number: `MY-012557`; Symbol: `ER_IB_MSG_LOG_FORMAT_OLD`; SQLSTATE: `HY000`

Message: Redo log is from an earlier version, v%lu.

- Error number: `MY-012559`; Symbol: `ER_IB_MSG_RECOVERY_CHECKPOINT_FROM_BEFORE_CLEAN_SHUTDOWN`; SQLSTATE: `HY000`

Message: Are you sure you are using the right redo log files to start up the database? Log sequence number in the redo log files is %llu, less than the log sequence number in the first system tablespace file header, %llu.

- Error number: `MY-012560`; Symbol: `ER_IB_MSG_RECOVERY_IS_NEEDED`; SQLSTATE: `HY000`

Message: The log sequence number %llu in the system tablespace does not match the log sequence number %llu in the redo log files!

- Error number: `MY-012561`; Symbol: `ER_IB_MSG_RECOVERY_IN_READ_ONLY`; SQLSTATE: `HY000`

Message: Can't initiate database recovery, running in read-only-mode.

- Error number: `MY-012562`; Symbol: `ER_IB_MSG_737`; SQLSTATE: `HY000`

Message: We scanned the log up to %llu. A checkpoint was at %llu and the maximum LSN on a database page was %llu. It is possible that the database is now corrupt!

- Error number: `MY-012563`; Symbol: `ER_IB_MSG_738`; SQLSTATE: `HY000`

Message: Waiting for `recv_writer` to finish flushing of buffer pool

- Error number: `MY-012564`; Symbol: `ER_IB_MSG_739`; SQLSTATE: `HY000`

Message: Recovery parsing buffer extended to %zu.

- Error number: `MY-012565`; Symbol: `ER_IB_MSG_740`; SQLSTATE: `HY000`

Message: Out of memory while resizing recovery parsing buffer.

- Error number: `MY-012566`; Symbol: `ER_IB_MSG_741`; SQLSTATE: `HY000`

Message: %s

- Error number: [MY-012567](#); Symbol: [ER_IB_MSG_742](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012568](#); Symbol: [ER_IB_MSG_743](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012569](#); Symbol: [ER_IB_MSG_744](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012570](#); Symbol: [ER_IB_MSG_745](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012571](#); Symbol: [ER_IB_MSG_746](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012572](#); Symbol: [ER_IB_MSG_747](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012573](#); Symbol: [ER_IB_MSG_748](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012574](#); Symbol: [ER_IB_MSG_749](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012575](#); Symbol: [ER_IB_MSG_750](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012576](#); Symbol: [ER_IB_MSG_751](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012577](#); Symbol: [ER_IB_MSG_752](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012578](#); Symbol: [ER_IB_MSG_753](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012579](#); Symbol: [ER_IB_MSG_754](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012580](#); Symbol: [ER_IB_MSG_755](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012581](#); Symbol: [ER_IB_MSG_756](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012582](#); Symbol: [ER_IB_MSG_757](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012583](#); Symbol: [ER_IB_MSG_758](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012584](#); Symbol: [ER_IB_MSG_759](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012585](#); Symbol: [ER_IB_MSG_760](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012586](#); Symbol: [ER_IB_MSG_761](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012587](#); Symbol: [ER_IB_MSG_762](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012588](#); Symbol: [ER_IB_MSG_763](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012589](#); Symbol: [ER_IB_MSG_764](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012590](#); Symbol: [ER_IB_MSG_765](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012591](#); Symbol: [ER_IB_MSG_766](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012592](#); Symbol: [ER_IB_MSG_767](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012593](#); Symbol: [ER_IB_MSG_768](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012594](#); Symbol: [ER_IB_MSG_769](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012595](#); Symbol: [ER_IB_MSG_770](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012596](#); Symbol: [ER_IB_MSG_771](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012597](#); Symbol: [ER_IB_MSG_772](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012598](#); Symbol: [ER_IB_MSG_773](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012599](#); Symbol: [ER_IB_MSG_774](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012600](#); Symbol: [ER_IB_MSG_775](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012601](#); Symbol: [ER_IB_MSG_776](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012602](#); Symbol: [ER_IB_MSG_777](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012603](#); Symbol: [ER_IB_MSG_778](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012604](#); Symbol: [ER_IB_MSG_779](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012605](#); Symbol: [ER_IB_MSG_780](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012606](#); Symbol: [ER_IB_MSG_781](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012607](#); Symbol: [ER_IB_MSG_782](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012608](#); Symbol: [ER_IB_MSG_783](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012609](#); Symbol: [ER_IB_MSG_784](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012610](#); Symbol: [ER_IB_MSG_785](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012611](#); Symbol: [ER_IB_MSG_786](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012612](#); Symbol: [ER_IB_MSG_787](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012613](#); Symbol: [ER_IB_MSG_788](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012614](#); Symbol: [ER_IB_MSG_789](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012615](#); Symbol: [ER_IB_MSG_790](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012616](#); Symbol: [ER_IB_MSG_791](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012617](#); Symbol: [ER_IB_MSG_792](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012618](#); Symbol: [ER_IB_MSG_793](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012619](#); Symbol: [ER_IB_MSG_794](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012620](#); Symbol: [ER_IB_MSG_795](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012621](#); Symbol: [ER_IB_MSG_796](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012622](#); Symbol: [ER_IB_MSG_797](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012623](#); Symbol: [ER_IB_MSG_798](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012624](#); Symbol: [ER_IB_MSG_799](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012625](#); Symbol: [ER_IB_MSG_800](#); SQLSTATE: [HY000](#)

Message: %s

[ER_IB_MSG_800](#) was removed after 8.4.2.

-
- Error number: [MY-012626](#); Symbol: [ER_IB_MSG_801](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012627](#); Symbol: [ER_IB_MSG_802](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012628](#); Symbol: [ER_IB_MSG_803](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012629](#); Symbol: [ER_IB_MSG_804](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012630](#); Symbol: [ER_IB_MSG_805](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012631](#); Symbol: [ER_IB_MSG_806](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012632](#); Symbol: [ER_IB_MSG_807](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012633](#); Symbol: [ER_IB_MSG_808](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012634](#); Symbol: [ER_IB_MSG_809](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012635](#); Symbol: [ER_IB_MSG_810](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012636](#); Symbol: [ER_IB_MSG_811](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012637](#); Symbol: [ER_IB_MSG_812](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012638](#); Symbol: [ER_IB_MSG_813](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012639](#); Symbol: [ER_IB_MSG_814](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012640](#); Symbol: [ER_IB_MSG_815](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012641](#); Symbol: [ER_IB_MSG_816](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012642](#); Symbol: [ER_IB_MSG_817](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012643](#); Symbol: [ER_IB_MSG_818](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012644](#); Symbol: [ER_IB_MSG_819](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012645](#); Symbol: [ER_IB_MSG_820](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012646](#); Symbol: [ER_IB_MSG_821](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012647](#); Symbol: [ER_IB_MSG_822](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012648](#); Symbol: [ER_IB_MSG_823](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012649](#); Symbol: [ER_IB_MSG_824](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012650](#); Symbol: [ER_IB_MSG_825](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012651](#); Symbol: [ER_IB_MSG_826](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012652](#); Symbol: [ER_IB_MSG_827](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012653](#); Symbol: [ER_IB_MSG_828](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012654](#); Symbol: [ER_IB_MSG_829](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012655](#); Symbol: [ER_IB_MSG_830](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012656](#); Symbol: [ER_IB_MSG_831](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012657](#); Symbol: [ER_IB_MSG_832](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012658](#); Symbol: [ER_IB_MSG_833](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012659](#); Symbol: [ER_IB_MSG_834](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012660](#); Symbol: [ER_IB_MSG_835](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012661](#); Symbol: [ER_IB_MSG_836](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012662](#); Symbol: [ER_IB_MSG_837](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012663](#); Symbol: [ER_IB_MSG_838](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012664](#); Symbol: [ER_IB_MSG_839](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012665](#); Symbol: [ER_IB_MSG_840](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012666](#); Symbol: [ER_IB_MSG_841](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012667](#); Symbol: [ER_IB_MSG_842](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012668](#); Symbol: [ER_IB_MSG_CANT_ENCRYPT_REDO_LOG_DATA](#); SQLSTATE: [HY000](#)
Message: Can't encrypt data of redo log
 - Error number: [MY-012669](#); Symbol: [ER_IB_MSG_844](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012670](#); Symbol: [ER_IB_MSG_845](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012671](#); Symbol: [ER_IB_MSG_CANT_DECRYPT_REDO_LOG](#); SQLSTATE: [HY000](#)
Message: Decryption of redo log block at offset %llu in file %s failed because there's no keyring configured
 - Error number: [MY-012672](#); Symbol: [ER_IB_MSG_847](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012673](#); Symbol: [ER_IB_MSG_848](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012674](#); Symbol: [ER_IB_MSG_849](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012675](#); Symbol: [ER_IB_MSG_850](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012676](#); Symbol: [ER_IB_MSG_851](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012677](#); Symbol: [ER_IB_MSG_852](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012678](#); Symbol: [ER_IB_MSG_853](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012679](#); Symbol: [ER_IB_MSG_854](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012680](#); Symbol: [ER_IB_MSG_855](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012681](#); Symbol: [ER_IB_MSG_856](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012682](#); Symbol: [ER_IB_MSG_857](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012683](#); Symbol: [ER_IB_MSG_858](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012684](#); Symbol: [ER_IB_MSG_859](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012685](#); Symbol: [ER_IB_MSG_860](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012686](#); Symbol: [ER_IB_MSG_861](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012687](#); Symbol: [ER_IB_MSG_862](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012688](#); Symbol: [ER_IB_MSG_863](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012689](#); Symbol: [ER_IB_MSG_864](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012690](#); Symbol: [ER_IB_MSG_865](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012691](#); Symbol: [ER_IB_MSG_866](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012692](#); Symbol: [ER_IB_MSG_867](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012693](#); Symbol: [ER_IB_MSG_868](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012694](#); Symbol: [ER_IB_MSG_869](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012695](#); Symbol: [ER_IB_MSG_870](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012696](#); Symbol: [ER_IB_MSG_871](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012697](#); Symbol: [ER_IB_MSG_872](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012698](#); Symbol: [ER_IB_MSG_873](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012699](#); Symbol: [ER_IB_MSG_874](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012700](#); Symbol: [ER_IB_MSG_875](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012701](#); Symbol: [ER_IB_MSG_876](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012702](#); Symbol: [ER_IB_MSG_877](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012703](#); Symbol: [ER_IB_MSG_878](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012704](#); Symbol: [ER_IB_MSG_879](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012705](#); Symbol: [ER_IB_MSG_880](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012706](#); Symbol: [ER_IB_MSG_881](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012707](#); Symbol: [ER_IB_MSG_882](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012708](#); Symbol: [ER_IB_MSG_883](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012709](#); Symbol: [ER_IB_MSG_884](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012710](#); Symbol: [ER_IB_MSG_885](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012711](#); Symbol: [ER_IB_MSG_886](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012712](#); Symbol: [ER_IB_MSG_887](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012713](#); Symbol: [ER_IB_MSG_888](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012714](#); Symbol: [ER_IB_MSG_889](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012715](#); Symbol: [ER_IB_MSG_890](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012716](#); Symbol: [ER_IB_MSG_891](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012717](#); Symbol: [ER_IB_MSG_892](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012718](#); Symbol: [ER_IB_MSG_893](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012719](#); Symbol: [ER_IB_MSG_894](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012720](#); Symbol: [ER_IB_MSG_895](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012721](#); Symbol: [ER_IB_MSG_896](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012722](#); Symbol: [ER_IB_MSG_897](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012723](#); Symbol: [ER_IB_MSG_898](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012724](#); Symbol: [ER_IB_MSG_899](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012725](#); Symbol: [ER_IB_MSG_900](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012726](#); Symbol: [ER_IB_MSG_901](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012727](#); Symbol: [ER_IB_MSG_902](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012728](#); Symbol: [ER_IB_MSG_903](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012729](#); Symbol: [ER_IB_MSG_904](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012730](#); Symbol: [ER_IB_MSG_905](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012731](#); Symbol: [ER_IB_MSG_906](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012732](#); Symbol: [ER_IB_MSG_907](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012733](#); Symbol: [ER_IB_MSG_908](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012734](#); Symbol: [ER_IB_MSG_909](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012735](#); Symbol: [ER_IB_MSG_910](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012736](#); Symbol: [ER_IB_MSG_911](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012737](#); Symbol: [ER_IB_MSG_912](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012738](#); Symbol: [ER_IB_MSG_913](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012739](#); Symbol: [ER_IB_MSG_914](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012740](#); Symbol: [ER_IB_MSG_915](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012741](#); Symbol: [ER_IB_MSG_916](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012742](#); Symbol: [ER_IB_MSG_917](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012743](#); Symbol: [ER_IB_MSG_918](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012744](#); Symbol: [ER_IB_MSG_919](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012745](#); Symbol: [ER_IB_MSG_920](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012746](#); Symbol: [ER_IB_MSG_921](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012747](#); Symbol: [ER_IB_MSG_922](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012748](#); Symbol: [ER_IB_MSG_923](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012749](#); Symbol: [ER_IB_MSG_924](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012750](#); Symbol: [ER_IB_MSG_925](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012751](#); Symbol: [ER_IB_MSG_926](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012752](#); Symbol: [ER_IB_MSG_927](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012753](#); Symbol: [ER_IB_MSG_928](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012754](#); Symbol: [ER_IB_MSG_929](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012755](#); Symbol: [ER_IB_MSG_930](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012756](#); Symbol: [ER_IB_MSG_931](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012757](#); Symbol: [ER_IB_MSG_932](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012758](#); Symbol: [ER_IB_MSG_933](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012759](#); Symbol: [ER_IB_MSG_934](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012760](#); Symbol: [ER_IB_MSG_935](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012761](#); Symbol: [ER_IB_MSG_936](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012762](#); Symbol: [ER_IB_MSG_937](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012763](#); Symbol: [ER_IB_MSG_938](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012764](#); Symbol: [ER_IB_MSG_939](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012765](#); Symbol: [ER_IB_MSG_940](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012766](#); Symbol: [ER_IB_MSG_941](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012767](#); Symbol: [ER_IB_MSG_942](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012768](#); Symbol: [ER_IB_MSG_943](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012769](#); Symbol: [ER_IB_MSG_944](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012770](#); Symbol: [ER_IB_MSG_945](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012771](#); Symbol: [ER_IB_MSG_946](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012772](#); Symbol: [ER_IB_IMPORT_INDEX_METADATA_READ_FAILED](#); SQLSTATE: [HY000](#)
Message: IO Error: %s
 - Error number: [MY-012773](#); Symbol: [ER_IB_MSG_948](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012774](#); Symbol: [ER_IB_MSG_949](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012775](#); Symbol: [ER_IB_MSG_950](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012776](#); Symbol: [ER_IB_MSG_951](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012777](#); Symbol: [ER_IB_MSG_952](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012778](#); Symbol: [ER_IB_MSG_953](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012779](#); Symbol: [ER_IB_MSG_954](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012780](#); Symbol: [ER_IB_MSG_955](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012781](#); Symbol: [ER_IB_MSG_956](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012782](#); Symbol: [ER_IB_MSG_957](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012783](#); Symbol: [ER_IB_MSG_958](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012784](#); Symbol: [ER_IB_MSG_959](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012785](#); Symbol: [ER_IB_MSG_960](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012786](#); Symbol: [ER_IB_MSG_961](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012787](#); Symbol: [ER_IB_MSG_962](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012788](#); Symbol: [ER_IB_MSG_963](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012789](#); Symbol: [ER_IB_MSG_964](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012790](#); Symbol: [ER_IB_MSG_965](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012791](#); Symbol: [ER_IB_MSG_966](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012792](#); Symbol: [ER_IB_MSG_967](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012793](#); Symbol: [ER_IB_MSG_968](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012794](#); Symbol: [ER_IB_MSG_969](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012795](#); Symbol: [ER_IB_MSG_970](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012796](#); Symbol: [ER_IB_MSG_971](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012797](#); Symbol: [ER_IB_MSG_972](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012798](#); Symbol: [ER_IB_MSG_973](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012799](#); Symbol: [ER_IB_MSG_974](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012800](#); Symbol: [ER_IB_MSG_975](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012801](#); Symbol: [ER_IB_MSG_976](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012802](#); Symbol: [ER_IB_MSG_977](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012803](#); Symbol: [ER_IB_MSG_978](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012804](#); Symbol: [ER_IB_MSG_979](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012805](#); Symbol: [ER_IB_MSG_980](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012806](#); Symbol: [ER_IB_MSG_981](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012807](#); Symbol: [ER_IB_MSG_982](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012808](#); Symbol: [ER_IB_MSG_983](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012809](#); Symbol: [ER_IB_MSG_984](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012810](#); Symbol: [ER_IB_MSG_985](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012811](#); Symbol: [ER_IB_MSG_986](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012812](#); Symbol: [ER_IB_MSG_987](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012813](#); Symbol: [ER_IB_MSG_988](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012814](#); Symbol: [ER_IB_MSG_989](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012815](#); Symbol: [ER_IB_MSG_990](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012816](#); Symbol: [ER_IB_MSG_991](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012817](#); Symbol: [ER_IB_MSG_992](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012818](#); Symbol: [ER_IB_MSG_993](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012819](#); Symbol: [ER_IB_MSG_994](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012820](#); Symbol: [ER_IB_MSG_995](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012821](#); Symbol: [ER_IB_MSG_996](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012822](#); Symbol: [ER_IB_MSG_997](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012823](#); Symbol: [ER_IB_MSG_998](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012824](#); Symbol: [ER_IB_MSG_999](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012825](#); Symbol: [ER_IB_MSG_1000](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012826](#); Symbol: [ER_IB_MSG_1001](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012827](#); Symbol: [ER_IB_MSG_1002](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012828](#); Symbol: [ER_IB_MSG_1003](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012829](#); Symbol: [ER_IB_MSG_1004](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012830](#); Symbol: [ER_IB_MSG_1005](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012831](#); Symbol: [ER_IB_MSG_1006](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012832](#); Symbol: [ER_IB_MSG_1007](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012833](#); Symbol: [ER_IB_MSG_1008](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012834](#); Symbol: [ER_IB_MSG_1009](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012835](#); Symbol: [ER_IB_MSG_1010](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012836](#); Symbol: [ER_IB_MSG_1011](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012837](#); Symbol: [ER_IB_MSG_1012](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012838](#); Symbol: [ER_IB_MSG_1013](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012839](#); Symbol: [ER_IB_IMPORT_START_CFG_NAME](#); SQLSTATE: [HY000](#)
Message: Writing table metadata to '%s'
 - Error number: [MY-012840](#); Symbol: [ER_IB_MSG_1015](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012841](#); Symbol: [ER_IB_MSG_1016](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012842](#); Symbol: [ER_IB_MSG_1017](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012843](#); Symbol: [ER_IB_MSG_1018](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012844](#); Symbol: [ER_IB_MSG_1019](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012845](#); Symbol: [ER_IB_MSG_1020](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012846](#); Symbol: [ER_IB_MSG_1021](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012847](#); Symbol: [ER_IB_MSG_1022](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012848](#); Symbol: [ER_IB_MSG_1023](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012849](#); Symbol: [ER_IB_MSG_1024](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012850](#); Symbol: [ER_IB_MSG_1025](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-012851](#); Symbol: [ER_IB_MSG_1026](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012852](#); Symbol: [ER_IB_MSG_1027](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012853](#); Symbol: [ER_IB_MSG_1028](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012854](#); Symbol: [ER_IB_MSG_1029](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012855](#); Symbol: [ER_IB_MSG_1030](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012856](#); Symbol: [ER_IB_MSG_1031](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012857](#); Symbol: [ER_IB_MSG_1032](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012858](#); Symbol: [ER_IB_MSG_1033](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012859](#); Symbol: [ER_IB_MSG_1034](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012860](#); Symbol: [ER_IB_MSG_1035](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012861](#); Symbol: [ER_IB_MSG_1036](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012862](#); Symbol: [ER_IB_MSG_1037](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012863](#); Symbol: [ER_IB_MSG_1038](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012864](#); Symbol: [ER_IB_MSG_1039](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012865](#); Symbol: [ER_IB_MSG_1040](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012866](#); Symbol: [ER_IB_MSG_1041](#); SQLSTATE: [HY000](#)

-
- Message: %s
- Error number: [MY-012867](#); Symbol: [ER_IB_MSG_1042](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012868](#); Symbol: [ER_IB_MSG_1043](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012869](#); Symbol: [ER_IB_MSG_1044](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012870](#); Symbol: [ER_IB_MSG_1045](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012871](#); Symbol: [ER_IB_MSG_1046](#); SQLSTATE: [HY000](#)
Message: Old log sequence number %llu was greater than the new log sequence number %llu. Please submit a bug report to <http://bugs.mysql.com>
 - Error number: [MY-012872](#); Symbol: [ER_IB_MSG_1047](#); SQLSTATE: [HY000](#)
Message: Semaphore wait has lasted > %llu seconds. We intentionally crash the server because it appears to be hung.
 - Error number: [MY-012873](#); Symbol: [ER_IB_MSG_1048](#); SQLSTATE: [HY000](#)
Message: Waiting for %llu table(s) to be dropped
 - Error number: [MY-012874](#); Symbol: [ER_IB_MSG_1049](#); SQLSTATE: [HY000](#)
Message: Waiting for change buffer merge to complete number of bytes of change buffer just merged: %llu
 - Error number: [MY-012876](#); Symbol: [ER_IB_MSG_1051](#); SQLSTATE: [HY000](#)
Message: Can't set undo tablespace(s) to be encrypted in read-only-mode.
 - Error number: [MY-012877](#); Symbol: [ER_IB_MSG_1052](#); SQLSTATE: [HY000](#)
Message: Can't set undo tablespace '%s' to be encrypted.
 - Error number: [MY-012878](#); Symbol: [ER_IB_MSG_1053](#); SQLSTATE: [HY000](#)
Message: Can't set undo tablespace '%s' to be encrypted. Failed to write header page.
 - Error number: [MY-012879](#); Symbol: [ER_IB_MSG_1054](#); SQLSTATE: [HY000](#)
Message: Can't set undo tablespace '%s' to be encrypted. Error %d - %s
 - Error number: [MY-012880](#); Symbol: [ER_IB_MSG_1055](#); SQLSTATE: [HY000](#)
Message: Encryption is enabled for undo tablespace '%s'.
 - Error number: [MY-012881](#); Symbol: [ER_IB_MSG_1056](#); SQLSTATE: [HY000](#)
Message: Can't rotate encryption on undo tablespace '%s'.

-
- Error number: [MY-012882](#); Symbol: [ER_IB_MSG_1057](#); SQLSTATE: [HY000](#)
Message: Encryption is enabled for undo tablespace '%s'.
 - Error number: [MY-012883](#); Symbol: [ER_IB_MSG_1058](#); SQLSTATE: [HY000](#)
Message: os_file_get_status() failed on '%s'. Can't determine file permissions.
 - Error number: [MY-012884](#); Symbol: [ER_IB_MSG_1059](#); SQLSTATE: [HY000](#)
Message: %s can't be opened in %s mode.
 - Error number: [MY-012885](#); Symbol: [ER_IB_MSG_1060](#); SQLSTATE: [HY000](#)
Message: '%s' not a regular file.
 - Error number: [MY-012886](#); Symbol: [ER_IB_MSG_LOG_FILE_OS_CREATE_FAILED](#); SQLSTATE: [HY000](#)
Message: Cannot create %s
 - Error number: [MY-012887](#); Symbol: [ER_IB_MSG_FILE_RESIZE](#); SQLSTATE: [HY000](#)
Message: Setting file %s size to %llu MB. Progress : %u%%
 - Error number: [MY-012888](#); Symbol: [ER_IB_MSG_LOG_FILE_RESIZE_FAILED](#); SQLSTATE: [HY000](#)
Message: Cannot resize redo log file %s to %llu MB (%s)
 - Error number: [MY-012889](#); Symbol: [ER_IB_MSG_LOG_FILES_CREATE_AND_READ_ONLY_MODE](#); SQLSTATE: [HY000](#)
Message: Cannot create redo log files in read-only mode (--innodb-read-only).
 - Error number: [MY-012890](#); Symbol: [ER_IB_MSG_1065](#); SQLSTATE: [HY000](#)
Message: Redo log encryption is enabled, but the keyring is not loaded.
 - Error number: [MY-012891](#); Symbol: [ER_IB_MSG_LOG_FILE_PREPARE_ON_CREATE_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to create redo log file %s (error: %d) for start LSN %llu
 - Error number: [MY-012893](#); Symbol: [ER_IB_MSG_LOG_FILES_INITIALIZED](#); SQLSTATE: [HY000](#)
Message: New redo log files created, LSN=%llu
 - Error number: [MY-012894](#); Symbol: [ER_IB_MSG_LOG_FILE_OPEN_FAILED](#); SQLSTATE: [HY000](#)
Message: Unable to open '%s' (error: %d).
 - Error number: [MY-012895](#); Symbol: [ER_IB_MSG_1070](#); SQLSTATE: [HY000](#)
Message: Cannot create construction log file '%s' for undo tablespace '%s'.
 - Error number: [MY-012896](#); Symbol: [ER_IB_MSG_1071](#); SQLSTATE: [HY000](#)
Message: Creating UNDO Tablespace %s
 - Error number: [MY-012897](#); Symbol: [ER_IB_MSG_1072](#); SQLSTATE: [HY000](#)

-
- Message: Setting file %s size to %llu MB
- Error number: [MY-012898](#); Symbol: [ER_IB_MSG_1073](#); SQLSTATE: [HY000](#)
Message: Physically writing the file full
 - Error number: [MY-012899](#); Symbol: [ER_IB_MSG_1074](#); SQLSTATE: [HY000](#)
Message: Error in creating %s: probably out of disk space
 - Error number: [MY-012900](#); Symbol: [ER_IB_MSG_1075](#); SQLSTATE: [HY000](#)
Message: Can't set encryption metadata for space %s
 - Error number: [MY-012901](#); Symbol: [ER_IB_MSG_1076](#); SQLSTATE: [HY000](#)
Message: Cannot read first page of '%s' - %s
 - Error number: [MY-012902](#); Symbol: [ER_IB_MSG_1077](#); SQLSTATE: [HY000](#)
Message: Undo tablespace number %lu was being truncated when mysqld quit.
 - Error number: [MY-012903](#); Symbol: [ER_IB_MSG_1078](#); SQLSTATE: [HY000](#)
Message: Cannot recover a truncated undo tablespace in read-only mode
 - Error number: [MY-012904](#); Symbol: [ER_IB_MSG_1079](#); SQLSTATE: [HY000](#)
Message: Reconstructing undo tablespace number %lu.
 - Error number: [MY-012905](#); Symbol: [ER_IB_MSG_1080](#); SQLSTATE: [HY000](#)
Message: Cannot create %s because %s already uses Space ID=%lu! Did you change innodb_undo_directory?
 - Error number: [MY-012906](#); Symbol: [ER_IB_MSG_1081](#); SQLSTATE: [HY000](#)
Message: UNDO tablespace %s must be %s
 - Error number: [MY-012907](#); Symbol: [ER_IB_MSG_1082](#); SQLSTATE: [HY000](#)
Message: Error creating file for %s
 - Error number: [MY-012908](#); Symbol: [ER_IB_MSG_1083](#); SQLSTATE: [HY000](#)
Message: Error reading encryption for %s
 - Error number: [MY-012909](#); Symbol: [ER_IB_MSG_CANNOT_OPEN_57_UNDO](#); SQLSTATE: [HY000](#)
Message: Unable to open undo tablespace number %lu
 - Error number: [MY-012910](#); Symbol: [ER_IB_MSG_1085](#); SQLSTATE: [HY000](#)
Message: Opened %llu existing undo tablespaces.
 - Error number: [MY-012911](#); Symbol: [ER_IB_MSG_1086](#); SQLSTATE: [HY000](#)
Message: Cannot create undo tablespaces since innodb_%s has been set. Using %llu existing undo tablespaces.

-
- Error number: [MY-012912](#); Symbol: [ER_IB_MSG_1087](#); SQLSTATE: [HY000](#)
Message: Cannot continue InnoDB startup in %s mode because there are no existing undo tablespaces found.
 - Error number: [MY-012913](#); Symbol: [ER_IB_MSG_1088](#); SQLSTATE: [HY000](#)
Message: Could not create undo tablespace '%s'.
 - Error number: [MY-012914](#); Symbol: [ER_IB_MSG_1089](#); SQLSTATE: [HY000](#)
Message: Error %d - %s - opening newly created undo tablespace '%s'.
 - Error number: [MY-012915](#); Symbol: [ER_IB_MSG_1090](#); SQLSTATE: [HY000](#)
Message: Created %llu undo tablespaces.
 - Error number: [MY-012916](#); Symbol: [ER_IB_MSG_1091](#); SQLSTATE: [HY000](#)
Message: Unable to create encrypted undo tablespace number %lu. please check if the keyring is initialized correctly
 - Error number: [MY-012917](#); Symbol: [ER_IB_MSG_1092](#); SQLSTATE: [HY000](#)
Message: Encryption is enabled for undo tablespace number %lu.
 - Error number: [MY-012918](#); Symbol: [ER_IB_MSG_1093](#); SQLSTATE: [HY000](#)
Message: Unable to initialize the header page in undo tablespace number %lu.
 - Error number: [MY-012919](#); Symbol: [ER_IB_MSG_1094](#); SQLSTATE: [HY000](#)
Message: Cannot delete old undo tablespaces because they contain undo logs for XA PREPARED transactions.
 - Error number: [MY-012920](#); Symbol: [ER_IB_MSG_1095](#); SQLSTATE: [HY000](#)
Message: Upgrading %zu existing undo tablespaces that were tracked in the system tablespace to %lu new independent undo tablespaces.
 - Error number: [MY-012921](#); Symbol: [ER_IB_MSG_1096](#); SQLSTATE: [HY000](#)
Message: Deleting %llu new independent undo tablespaces that we just created.
 - Error number: [MY-012922](#); Symbol: [ER_IB_MSG_1097](#); SQLSTATE: [HY000](#)
Message: Waiting for purge to start
 - Error number: [MY-012923](#); Symbol: [ER_IB_MSG_1098](#); SQLSTATE: [HY000](#)
Message: Creating shared tablespace for temporary tables
 - Error number: [MY-012924](#); Symbol: [ER_IB_MSG_1099](#); SQLSTATE: [HY000](#)
Message: The %s data file must be writable!
 - Error number: [MY-012925](#); Symbol: [ER_IB_MSG_1100](#); SQLSTATE: [HY000](#)
Message: Could not create the shared %s.

-
- Error number: [MY-012926](#); Symbol: [ER_IB_MSG_1101](#); SQLSTATE: [HY000](#)
Message: Unable to create the shared %s.
 - Error number: [MY-012927](#); Symbol: [ER_IB_MSG_1102](#); SQLSTATE: [HY000](#)
Message: The %s data file cannot be re-opened after check_file_spec() succeeded!
 - Error number: [MY-012928](#); Symbol: [ER_IB_MSG_1103](#); SQLSTATE: [HY000](#)
Message: %d threads created by InnoDB had not exited at shutdown!
 - Error number: [MY-012929](#); Symbol: [ER_IB_MSG_1104](#); SQLSTATE: [HY000](#)
Message: InnoDB Database creation was aborted %swith error %s. You may need to delete the ibdata1 file before trying to start up again.
 - Error number: [MY-012930](#); Symbol: [ER_IB_MSG_1105](#); SQLSTATE: [HY000](#)
Message: Plugin initialization aborted %swith error %s.
 - Error number: [MY-012931](#); Symbol: [ER_IB_MSG_BUF_PENDING_IO](#); SQLSTATE: [HY000](#)
Message: Waiting for %zu buffer page I/Os to complete.
 - Error number: [MY-012932](#); Symbol: [ER_IB_MSG_1107](#); SQLSTATE: [HY000](#)
Message: PUNCH HOLE support available
 - Error number: [MY-012933](#); Symbol: [ER_IB_MSG_1108](#); SQLSTATE: [HY000](#)
Message: PUNCH HOLE support not available
 - Error number: [MY-012934](#); Symbol: [ER_IB_MSG_1109](#); SQLSTATE: [HY000](#)
Message: Size of InnoDB's ulint is %zu but size of void* is %zu. The sizes should be the same so that on a 64-bit platforms you can allocate more than 4 GB of memory.
 - Error number: [MY-012935](#); Symbol: [ER_IB_MSG_1110](#); SQLSTATE: [HY000](#)
Message: Database upgrade cannot be accomplished in read-only mode.
 - Error number: [MY-012936](#); Symbol: [ER_IB_MSG_1111](#); SQLSTATE: [HY000](#)
Message: Database upgrade cannot be accomplished with innodb_force_recovery > 0
 - Error number: [MY-012937](#); Symbol: [ER_IB_MSG_1112](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012938](#); Symbol: [ER_IB_MSG_1113](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012939](#); Symbol: [ER_IB_MSG_1114](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012940](#); Symbol: [ER_IB_MSG_1115](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012941](#); Symbol: [ER_IB_MSG_1116](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012942](#); Symbol: [ER_IB_MSG_1117](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012944](#); Symbol: [ER_IB_MSG_1119](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012945](#); Symbol: [ER_IB_MSG_1120](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012946](#); Symbol: [ER_IB_MSG_1121](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012947](#); Symbol: [ER_IB_MSG_1122](#); SQLSTATE: [HY000](#)

Message: MySQL was built without a memory barrier capability on this architecture, which might allow a mutex/rw_lock violation under high thread concurrency. This may cause a hang.

- Error number: [MY-012948](#); Symbol: [ER_IB_MSG_1123](#); SQLSTATE: [HY000](#)

Message: Compressed tables use zlib %s

- Error number: [MY-012949](#); Symbol: [ER_IB_MSG_1124](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012950](#); Symbol: [ER_IB_MSG_1125](#); SQLSTATE: [HY000](#)

Message: Startup called second time during the process lifetime. In the MySQL Embedded Server Library you cannot call `server_init()` more than once during the process lifetime.

- Error number: [MY-012951](#); Symbol: [ER_IB_MSG_1126](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-012952](#); Symbol: [ER_IB_MSG_1127](#); SQLSTATE: [HY000](#)

Message: Unable to create monitor file %s: %s

- Error number: [MY-012953](#); Symbol: [ER_IB_MSG_1128](#); SQLSTATE: [HY000](#)

Message: Disabling background ibuf IO read threads.

- Error number: [MY-012954](#); Symbol: [ER_IB_MSG_1129](#); SQLSTATE: [HY000](#)

Message: Cannot initialize AIO sub-system

- Error number: [MY-012955](#); Symbol: [ER_IB_MSG_1130](#); SQLSTATE: [HY000](#)

Message: Initializing buffer pool, total size = %lf%c, instances = %lu, chunk size =%lf%c

-
- Error number: [MY-012956](#); Symbol: [ER_IB_MSG_1131](#); SQLSTATE: [HY000](#)
Message: Cannot allocate memory for the buffer pool
 - Error number: [MY-012957](#); Symbol: [ER_IB_MSG_1132](#); SQLSTATE: [HY000](#)
Message: Completed initialization of buffer pool
 - Error number: [MY-012958](#); Symbol: [ER_IB_MSG_1133](#); SQLSTATE: [HY000](#)
Message: Small buffer pool size (%lluM), the flst_validate() debug function can cause a deadlock if the buffer pool fills up.
 - Error number: [MY-012959](#); Symbol: [ER_IB_MSG_1134](#); SQLSTATE: [HY000](#)
Message: Could not open or create the system tablespace. If you tried to add new data files to the system tablespace, and it failed here, you should now edit innodb_data_file_path in my.cnf back to what it was, and remove the new ibdata files InnoDB created in this failed attempt. InnoDB only wrote those files full of zeros, but did not yet use them in any way. But be careful: do not remove old data files which contain your precious data!
 - Error number: [MY-012960](#); Symbol: [ER_IB_MSG_DATA_DIRECTORY_NOT_INITIALIZED_OR_CORRUPTED](#); SQLSTATE: [HY000](#)
Message: Cannot create redo log files because data files are corrupt or the database was not shut down cleanly after creating the data files.
 - Error number: [MY-012961](#); Symbol: [ER_IB_MSG_LOG_FILES_INVALID_SET](#); SQLSTATE: [HY000](#)
Message: Only one redo log file found
 - Error number: [MY-012962](#); Symbol: [ER_IB_MSG_LOG_FILE_SIZE_INVALID](#); SQLSTATE: [HY000](#)
Message: The redo log file %s size %llu is not a multiple of innodb_page_size
 - Error number: [MY-012963](#); Symbol: [ER_IB_MSG_LOG_FILES_DIFFERENT_SIZES](#); SQLSTATE: [HY000](#)
Message: The redo log file %s is of different size %llu bytes than other log files %llu bytes!
 - Error number: [MY-012964](#); Symbol: [ER_IB_MSG_1139](#); SQLSTATE: [HY000](#)
Message: Use --innodb-directories to find the tablespace files. If that fails then use --innodb-force-recovery=1 to ignore this and to permanently lose all changes to the missing tablespace(s)
 - Error number: [MY-012965](#); Symbol: [ER_IB_MSG_RECOVERY_CORRUPT](#); SQLSTATE: [HY000](#)
Message: The redo log file may have been corrupt and it is possible that the log scan or parsing did not proceed far enough in recovery. Please run CHECK TABLE on your InnoDB tables to check that they are ok! It may be safest to recover your InnoDB database from a backup!
 - Error number: [MY-012967](#); Symbol: [ER_IB_MSG_1142](#); SQLSTATE: [HY000](#)
Message: Cannot open DD tablespace.
 - Error number: [MY-012968](#); Symbol: [ER_IB_MSG_LOG_FILES_REWRITING](#); SQLSTATE: [HY000](#)
Message: Starting to delete and rewrite redo log files.

-
- Error number: [MY-012969](#); Symbol: [ER_IB_MSG_1144](#); SQLSTATE: [HY000](#)
Message: Undo from 5.7 found. It will be purged
 - Error number: [MY-012970](#); Symbol: [ER_IB_MSG_1145](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012971](#); Symbol: [ER_IB_MSG_1146](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012972](#); Symbol: [ER_IB_MSG_1147](#); SQLSTATE: [HY000](#)
Message: Tablespace size stored in header is %lu pages, but the sum of data file sizes is %lu pages
 - Error number: [MY-012973](#); Symbol: [ER_IB_MSG_1148](#); SQLSTATE: [HY000](#)
Message: Cannot start InnoDB. The tail of the system tablespace is missing. Have you edited `innodb_data_file_path` in `my.cnf` in an inappropriate way, removing `ibdata` files from there? You can set `innodb_force_recovery=1` in `my.cnf` to force a startup if you are trying to recover a badly corrupt database.
 - Error number: [MY-012974](#); Symbol: [ER_IB_MSG_1149](#); SQLSTATE: [HY000](#)
Message: Tablespace size stored in header is %lu pages, but the sum of data file sizes is only %lu pages
 - Error number: [MY-012975](#); Symbol: [ER_IB_MSG_1150](#); SQLSTATE: [HY000](#)
Message: Cannot start InnoDB. The tail of the system tablespace is missing. Have you edited `innodb_data_file_path` in `my.cnf` in an InnoDB: inappropriate way, removing `ibdata` files from there? You can set `innodb_force_recovery=1` in `my.cnf` to force InnoDB: a startup if you are trying to recover a badly corrupt database.
 - Error number: [MY-012976](#); Symbol: [ER_IB_MSG_1151](#); SQLSTATE: [HY000](#)
Message: %s started; log sequence number %llu
 - Error number: [MY-012977](#); Symbol: [ER_IB_MSG_1152](#); SQLSTATE: [HY000](#)
Message: Waiting for purge to complete
 - Error number: [MY-012979](#); Symbol: [ER_IB_MSG_1154](#); SQLSTATE: [HY000](#)
Message: Query counter shows %lld queries still inside InnoDB at shutdown
 - Error number: [MY-012980](#); Symbol: [ER_IB_MSG_1155](#); SQLSTATE: [HY000](#)
Message: Shutdown completed; log sequence number %llu
 - Error number: [MY-012981](#); Symbol: [ER_IB_MSG_1156](#); SQLSTATE: [HY000](#)
Message: Cannot continue operation.
 - Error number: [MY-012982](#); Symbol: [ER_IB_MSG_1157](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012983](#); Symbol: [ER_IB_MSG_1158](#); SQLSTATE: [HY000](#)

-
- Message: %s
- Error number: [MY-012984](#); Symbol: [ER_IB_MSG_1159](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012985](#); Symbol: [ER_IB_MSG_1160](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012986](#); Symbol: [ER_IB_MSG_1161](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012987](#); Symbol: [ER_IB_MSG_1162](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012988](#); Symbol: [ER_IB_MSG_1163](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012989](#); Symbol: [ER_IB_MSG_1164](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012990](#); Symbol: [ER_IB_MSG_1165](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-012991](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_FAIL_TO_READ_LOG_FILE](#); SQLSTATE: [HY000](#)
Message: Unable to read the existing undo truncate log file '%s'. The error is %s
 - Error number: [MY-012992](#); Symbol: [ER_IB_MSG_UNDO_MARKED_FOR_TRUNCATE](#); SQLSTATE: [HY000](#)
Message: Undo tablespace %s is marked for truncate
 - Error number: [MY-012994](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_START](#); SQLSTATE: [HY000](#)
Message: Truncating UNDO tablespace %s
 - Error number: [MY-012996](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_LOG_CREATE](#); SQLSTATE: [HY000](#)
Message: Cannot create truncate log for undo tablespace '%s'.
 - Error number: [MY-012998](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_FAILURE](#); SQLSTATE: [HY000](#)
Message: Failed to truncate undo tablespace '%s'.
 - Error number: [MY-013000](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_COMPLETE](#); SQLSTATE: [HY000](#)
Message: Completed truncate of undo tablespace %s.
 - Error number: [MY-013002](#); Symbol: [ER_IB_MSG_1177](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: `MY-013003`; Symbol: `ER_IB_MSG_1178`; SQLSTATE: `HY000`
Message: %s
 - Error number: `MY-013004`; Symbol: `ER_IB_MSG_1179`; SQLSTATE: `HY000`
Message: %s
 - Error number: `MY-013005`; Symbol: `ER_IB_MSG_1180`; SQLSTATE: `HY000`
Message: %s
 - Error number: `MY-013006`; Symbol: `ER_IB_MSG_1181`; SQLSTATE: `HY000`
Message: %s
 - Error number: `MY-013007`; Symbol: `ER_IB_MSG_1182`; SQLSTATE: `HY000`
Message: %s
 - Error number: `MY-013008`; Symbol: `ER_IB_MSG_1183`; SQLSTATE: `HY000`
Message: %s
 - Error number: `MY-013009`; Symbol: `ER_IB_ERR_ACCESSING_OUT_OF_BOUND_FIELD_IN_INDEX`; SQLSTATE: `HY000`
Message: Trying to access update undo rec field %llu in index %s of table %s but index has only %llu fields. %s. Run also CHECK TABLE %s. n_fields = %llu, i = %llu, ptr = %p.
 - Error number: `MY-013010`; Symbol: `ER_IB_MSG_1185`; SQLSTATE: `HY000`
Message: %s
 - Error number: `MY-013011`; Symbol: `ER_IB_MSG_1186`; SQLSTATE: `HY000`
Message: %s
 - Error number: `MY-013012`; Symbol: `ER_IB_MSG_1187`; SQLSTATE: `HY000`
Message: %s
 - Error number: `MY-013013`; Symbol: `ER_IB_MSG_1188`; SQLSTATE: `HY000`
Message: %s
 - Error number: `MY-013014`; Symbol: `ER_IB_MSG_1189`; SQLSTATE: `HY000`
Message: %s
 - Error number: `MY-013015`; Symbol: `ER_IB_MSG_TRX_RECOVERY_ROLLBACK_COMPLETED`; SQLSTATE: `HY000`
Message: Rollback of non-prepared transactions completed
 - Error number: `MY-013016`; Symbol: `ER_IB_MSG_1191`; SQLSTATE: `HY000`
Message: %s
 - Error number: `MY-013017`; Symbol: `ER_IB_MSG_1192`; SQLSTATE: `HY000`

Message: %s

- Error number: [MY-013018](#); Symbol: [ER_IB_MSG_1193](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013019](#); Symbol: [ER_IB_MSG_1194](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013020](#); Symbol: [ER_IB_MSG_1195](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013021](#); Symbol: [ER_IB_MSG_1196](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013022](#); Symbol: [ER_IB_MSG_1197](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013023](#); Symbol: [ER_IB_MSG_1198](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013024](#); Symbol: [ER_IB_MSG_1199](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013025](#); Symbol: [ER_IB_MSG_1200](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013026](#); Symbol: [ER_IB_MSG_1201](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013027](#); Symbol: [ER_IB_MSG_1202](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013028](#); Symbol: [ER_IB_MSG_1203](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013029](#); Symbol: [ER_IB_MSG_1204](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013030](#); Symbol: [ER_IB_MSG_1205](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013031](#); Symbol: [ER_IB_MSG_1206](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013032](#); Symbol: [ER_IB_MSG_1207](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013033](#); Symbol: [ER_IB_MSG_1208](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013034](#); Symbol: [ER_IB_MSG_1209](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013035](#); Symbol: [ER_IB_MSG_1210](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013036](#); Symbol: [ER_IB_MSG_1211](#); SQLSTATE: [HY000](#)

Message: Blocked High Priority Transaction (ID %llu, Thread ID %s) killed the blocking transaction (ID %llu - %s) by rolling it back.

- Error number: [MY-013037](#); Symbol: [ER_IB_MSG_1212](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013038](#); Symbol: [ER_IB_MSG_1213](#); SQLSTATE: [HY000](#)

Message: gettimeofday() failed: %s

- Error number: [MY-013039](#); Symbol: [ER_IB_MSG_1214](#); SQLSTATE: [HY000](#)

Message: Can't create UNDO tablespace %s %s

- Error number: [MY-013040](#); Symbol: [ER_IB_MSG_1215](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013041](#); Symbol: [ER_IB_MSG_LOG_FILES_RESIZE_ON_START](#); SQLSTATE: [HY000](#)

Message: Resizing redo log from %lluM to %lluM (LSN=%llu) synchronously. If this takes too long, consider starting the server with large --innodb_redo_log_capacity, and resizing the redo log online using SET.

- Error number: [MY-013042](#); Symbol: [ER_IB_MSG_1217](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013043](#); Symbol: [ER_IB_MSG_1218](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013044](#); Symbol: [ER_IB_MSG_1219](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013045](#); Symbol: [ER_IB_MSG_1220](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013046](#); Symbol: [ER_IB_MSG_1221](#); SQLSTATE: [HY000](#)

-
- Message: %s
- Error number: [MY-013047](#); Symbol: [ER_IB_MSG_1222](#); SQLSTATE: [HY000](#)
- Message: %s
- Error number: [MY-013048](#); Symbol: [ER_IB_MSG_1223](#); SQLSTATE: [HY000](#)
- Message: %s
- Error number: [MY-013049](#); Symbol: [ER_IB_MSG_1224](#); SQLSTATE: [HY000](#)
- Message: %s
- Error number: [MY-013050](#); Symbol: [ER_IB_MSG_1225](#); SQLSTATE: [HY000](#)
- Message: %s
- Error number: [MY-013051](#); Symbol: [ER_IB_MSG_1226](#); SQLSTATE: [HY000](#)
- Message: %s
- Error number: [MY-013052](#); Symbol: [ER_IB_MSG_1227](#); SQLSTATE: [HY000](#)
- Message: %s
- Error number: [MY-013053](#); Symbol: [ER_IB_MSG_1228](#); SQLSTATE: [HY000](#)
- Message: %s
- Error number: [MY-013054](#); Symbol: [ER_IB_MSG_1229](#); SQLSTATE: [HY000](#)
- Message: %s
- Error number: [MY-013056](#); Symbol: [ER_IB_MSG_1231](#); SQLSTATE: [HY000](#)
- Message: %s
- Error number: [MY-013058](#); Symbol: [ER_IB_MSG_1233](#); SQLSTATE: [HY000](#)
- Message: %s
- Error number: [MY-013059](#); Symbol: [ER_IB_MSG_LOG_WRITER_OUT_OF_SPACE](#); SQLSTATE: [HY000](#)
- Message: Out of space in the redo log. Checkpoint LSN: %llu. Consider increasing innodb_redo_log_capacity.
- Error number: [MY-013060](#); Symbol: [ER_IB_MSG_1235](#); SQLSTATE: [HY000](#)
- Message: %s
- Error number: [MY-013061](#); Symbol: [ER_IB_MSG_LOG_WRITER_ABORTS_LOG_ARCHIVER](#); SQLSTATE: [HY000](#)
- Message: Log writer waited too long for redo-archiver to advance (1 second). There are unarchived: %llu bytes. Archiver LSN: %llu. Aborted the redo-archiver. Consider increasing innodb_redo_log_capacity.
- Error number: [MY-013062](#); Symbol: [ER_IB_MSG_LOG_WRITER_WAITING_FOR_ARCHIVER](#); SQLSTATE: [HY000](#)

Message: Log writer is waiting for redo-archiver to catch up unarchived: %llu bytes. Archiver LSN: %llu. Consider increasing innodb_redo_log_capacity.

- Error number: [MY-013063](#); Symbol: [ER_IB_MSG_1238](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013064](#); Symbol: [ER_IB_MSG_1239](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013066](#); Symbol: [ER_IB_MSG_1241](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013067](#); Symbol: [ER_IB_MSG_LOG_FILES_CANNOT_ENCRYPT_IN_READ_ONLY](#); SQLSTATE: [HY000](#)

Message: Can't set redo log files to be encrypted in read-only mode.

- Error number: [MY-013068](#); Symbol: [ER_IB_MSG_LOG_FILES_ENCRYPTION_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Can't set redo log files to be encrypted.

- Error number: [MY-013070](#); Symbol: [ER_IB_MSG_1245](#); SQLSTATE: [HY000](#)

Message: Redo log encryption is enabled.

- Error number: [MY-013071](#); Symbol: [ER_IB_MSG_1246](#); SQLSTATE: [HY000](#)

Message: Waiting for archiver to finish archiving page and log

- Error number: [MY-013072](#); Symbol: [ER_IB_MSG_1247](#); SQLSTATE: [HY000](#)

Message: Starting shutdown...

- Error number: [MY-013073](#); Symbol: [ER_IB_MSG_1248](#); SQLSTATE: [HY000](#)

Message: Waiting for %s to exit.

- Error number: [MY-013074](#); Symbol: [ER_IB_MSG_1249](#); SQLSTATE: [HY000](#)

Message: Waiting for rollback of %zu recovered transactions, before shutdown.

- Error number: [MY-013075](#); Symbol: [ER_IB_MSG_1250](#); SQLSTATE: [HY000](#)

Message: Waiting for master thread to be suspended.

- Error number: [MY-013076](#); Symbol: [ER_IB_MSG_1251](#); SQLSTATE: [HY000](#)

Message: Waiting for page_cleaner to finish flushing of buffer pool.

- Error number: [MY-013077](#); Symbol: [ER_IB_MSG_BUF_PENDING_IO_ON_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: Shutdown is waiting for %zu buffer page I/Os to complete.

- Error number: [MY-013078](#); Symbol: [ER_IB_MSG_1253](#); SQLSTATE: [HY000](#)

Message: MySQL has requested a very fast shutdown without flushing the InnoDB buffer pool to data files. At the next mysqld startup InnoDB will do a crash recovery!

- Error number: [MY-013080](#); Symbol: [ER_IB_MSG_1255](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013081](#); Symbol: [ER_IB_MSG_1256](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013082](#); Symbol: [ER_IB_MSG_1257](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013083](#); Symbol: [ER_IB_MSG_1258](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013084](#); Symbol: [ER_IB_MSG_1259](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013085](#); Symbol: [ER_IB_MSG_1260](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013086](#); Symbol: [ER_IB_MSG_1261](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013087](#); Symbol: [ER_IB_MSG_1262](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013088](#); Symbol: [ER_IB_MSG_1263](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013089](#); Symbol: [ER_IB_MSG_LOG_FILE_HEADER_INVALID_CHECKSUM](#); SQLSTATE: [HY000](#)

Message: Invalid redo log header checksum.

- Error number: [MY-013090](#); Symbol: [ER_IB_MSG_LOG_FORMAT_BEFORE_5_7_9](#); SQLSTATE: [HY000](#)

Message: Unsupported redo log format (v%lu). The redo log was created before MySQL 5.7.9

- Error number: [MY-013091](#); Symbol: [ER_IB_MSG_1266](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013092](#); Symbol: [ER_IB_MSG_LOG_PARAMS_CONCURRENCY_MARGIN_UNSAFE](#); SQLSTATE: [HY000](#)

Message: Cannot continue operation. The innodb_redo_log_capacity=%lluM is too small for the innodb_thread_concurrency=%lu. The capacity of redo should be >= %lluM. To get mysqld running, set innodb_thread_concurrency to a smaller value or increase innodb_redo_log_capacity. %s

- Error number: [MY-013093](#); Symbol: [ER_IB_MSG_1268](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013094](#); Symbol: [ER_IB_MSG_1269](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013095](#); Symbol: [ER_IB_MSG_THREAD_CONCURRENCY_CHANGED](#); SQLSTATE: [HY000](#)

Message: User has set innodb_thread_concurrency to %lu.

- Error number: [MY-013096](#); Symbol: [ER_RPL_REPLICA_SQL_THREAD_STOP_CMD_EXEC_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: STOP REPLICA command execution is incomplete: Replica SQL thread got the stop signal, thread is busy, SQL thread will stop once the current task is complete.

- Error number: [MY-013097](#); Symbol: [ER_RPL_REPLICA_IO_THREAD_STOP_CMD_EXEC_TIMEOUT](#); SQLSTATE: [HY000](#)

Message: STOP REPLICA command execution is incomplete: Replica IO thread got the stop signal, thread is busy, IO thread will stop once the current task is complete.

- Error number: [MY-013098](#); Symbol: [ER_RPL_GTID_UNSAFE_STMT_ON_NON_TRANS_TABLE](#); SQLSTATE: [HY000](#)

Message: Statement violates GTID consistency: Updates to non-transactional tables can only be done in either autocommitted statements or single-statement transactions, and never in the same statement as updates to transactional tables.

- Error number: [MY-013099](#); Symbol: [ER_RPL_GTID_UNSAFE_STMT_CREATE_SELECT](#); SQLSTATE: [HY000](#)

Message: Statement violates GTID consistency: CREATE TABLE ... SELECT.

- Error number: [MY-013101](#); Symbol: [ER_BINLOG_ROW_VALUE_OPTION_IGNORED](#); SQLSTATE: [HY000](#)

Message: When %s, the option binlog_row_value_options=%s will be ignored and updates will be written in full format to binary log.

- Error number: [MY-013103](#); Symbol: [ER_BINLOG_ROW_VALUE_OPTION_USED_ONLY_FOR_AFTER_IMAGES](#); SQLSTATE: [HY000](#)

Message: When %s, the option binlog_row_value_options=%s will be used only for the after-image. Full values will be written in the before-image, so the saving in disk space due to binlog_row_value_options is limited to less than 50%%.

- Error number: [MY-013104](#); Symbol: [ER_CONNECTION_ABORTED](#); SQLSTATE: [HY000](#)

Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s).

- Error number: [MY-013105](#); Symbol: [ER_NORMAL_SERVER_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: %s: Normal shutdown.

- Error number: [MY-013106](#); Symbol: [ER_KEYRING_MIGRATE_FAILED](#); SQLSTATE: [HY000](#)

Message: Can not perform keyring migration : %s.

-
- Error number: [MY-013107](#); Symbol: [ER_GRP_RPL_LOWER_CASE_TABLE_NAMES_DIFF_FROM_GRP](#); SQLSTATE: [HY000](#)
Message: The member is configured with a `lower_case_table_names` option value '%u' different from the group '%u'. The member will now exit the group. If there is existing data on member, it may be incompatible with group if it was created with a `lower_case_table_names` value different from the group.
 - Error number: [MY-013108](#); Symbol: [ER_OOM_SAVE_GTIDS](#); SQLSTATE: [HY000](#)
Message: An out-of-memory error occurred while saving the set of GTIDs from the last binary log into the `mysql.gtid_executed` table
 - Error number: [MY-013109](#); Symbol: [ER_LCTN_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: The `lower_case_table_names` setting for the data dictionary was not found. Starting the server using `lower_case_table_names = '%u'`.
 - Error number: [MY-013111](#); Symbol: [ER_COMPONENT_FILTER_WRONG_VALUE](#); SQLSTATE: [HY000](#)
Message: Variable '%s' can't be set to the value of '%s'
 - Error number: [MY-013112](#); Symbol: [ER_XPLUGIN_FAILED_TO_STOP_SERVICES](#); SQLSTATE: [HY000](#)
Message: Stopping services failed with error "%s"
 - Error number: [MY-013113](#); Symbol: [ER_INCONSISTENT_ERROR](#); SQLSTATE: [HY000](#)
Message: Query caused different errors on source and replica. Error on source: message (format)='%s' error code=%d; Error on replica:actual message='%s', error code=%d. Default database:'%s'. Query:'%s'
 - Error number: [MY-013114](#); Symbol: [ER_SERVER_SOURCE_FATAL_ERROR_READING_BINLOG](#); SQLSTATE: [HY000](#)
Message: Got fatal error %d from source when reading data from binary log: '%s'
 - Error number: [MY-013115](#); Symbol: [ER_NETWORK_READ_EVENT_CHECKSUM_FAILURE](#); SQLSTATE: [HY000](#)
Message: Replication event checksum verification failed while reading from network.
 - Error number: [MY-013116](#); Symbol: [ER_REPLICA_CREATE_EVENT_FAILURE](#); SQLSTATE: [HY000](#)
Message: Failed to create %s
 - Error number: [MY-013117](#); Symbol: [ER_REPLICA_FATAL_ERROR](#); SQLSTATE: [HY000](#)
Message: Fatal error: %s
 - Error number: [MY-013118](#); Symbol: [ER_REPLICA_HEARTBEAT_FAILURE](#); SQLSTATE: [HY000](#)
Message: Unexpected source's heartbeat data: %s
 - Error number: [MY-013119](#); Symbol: [ER_REPLICA_INCIDENT](#); SQLSTATE: [HY000](#)
Message: The incident %s occurred on the source. Message: %s
 - Error number: [MY-013120](#); Symbol: [ER_REPLICA_SOURCE_COM_FAILURE](#); SQLSTATE: [HY000](#)
Message: Source command %s failed: %s

-
- Error number: [MY-013121](#); Symbol: [ER_REPLICA_RELAY_LOG_READ_FAILURE](#); SQLSTATE: [HY000](#)
Message: Relay log read failure: %s
 - Error number: [MY-013122](#); Symbol: [ER_REPLICA_RELAY_LOG_WRITE_FAILURE](#); SQLSTATE: [HY000](#)
Message: Relay log write failure: %s
 - Error number: [MY-013123](#); Symbol: [ER_SERVER_REPLICA_CM_INIT_REPOSITORY](#); SQLSTATE: [HY000](#)
Message: Replica failed to initialize connection metadata structure from the repository
 - Error number: [MY-013124](#); Symbol: [ER_SERVER_REPLICA_AM_INIT_REPOSITORY](#); SQLSTATE: [HY000](#)
Message: Replica failed to initialize applier metadata structure from the repository
 - Error number: [MY-013125](#); Symbol: [ER_SERVER_NET_PACKET_TOO_LARGE](#); SQLSTATE: [HY000](#)
Message: Got a packet bigger than 'max_allowed_packet' bytes
 - Error number: [MY-013126](#); Symbol: [ER_SERVER_NO_SYSTEM_TABLE_ACCESS](#); SQLSTATE: [HY000](#)
Message: Access to %s '%s.%s' is rejected.
 - Error number: [MY-013128](#); Symbol: [ER_SERVER_UNKNOWN_SYSTEM_VARIABLE](#); SQLSTATE: [HY000](#)
Message: Unknown system variable '%s'
 - Error number: [MY-013129](#); Symbol: [ER_SERVER_NO_SESSION_TO_SEND_TO](#); SQLSTATE: [HY000](#)
Message: A message intended for a client cannot be sent there as no client-session is attached. Therefore, we're sending the information to the error-log instead: MY-%06d - %s
 - Error number: [MY-013130](#); Symbol: [ER_SERVER_NEW_ABORTING_CONNECTION](#); SQLSTATE: [08S01](#)
Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s; diagnostics area: MY-%06d - %s)
 - Error number: [MY-013131](#); Symbol: [ER_SERVER_OUT_OF_SORTMEMORY](#); SQLSTATE: [HY000](#)
Message: Out of sort memory, consider increasing server sort buffer size!
 - Error number: [MY-013132](#); Symbol: [ER_SERVER_RECORD_FILE_FULL](#); SQLSTATE: [HY000](#)
Message: The table '%s' is full!
 - Error number: [MY-013133](#); Symbol: [ER_SERVER_DISK_FULL_NOWAIT](#); SQLSTATE: [HY000](#)
Message: Create table/tablespace '%s' failed, as disk is full.
 - Error number: [MY-013134](#); Symbol: [ER_SERVER_HANDLER_ERROR](#); SQLSTATE: [HY000](#)
Message: Handler reported error %d - %s
 - Error number: [MY-013135](#); Symbol: [ER_SERVER_NOT_FORM_FILE](#); SQLSTATE: [HY000](#)
Message: Incorrect information in file: '%s'
 - Error number: [MY-013136](#); Symbol: [ER_SERVER_CANT_OPEN_FILE](#); SQLSTATE: [HY000](#)

-
- Message: Can't open file: '%s' (OS errno: %d - %s)
- Error number: [MY-013137](#); Symbol: [ER_SERVER_FILE_NOT_FOUND](#); SQLSTATE: [HY000](#)
- Message: Can't find file: '%s' (OS errno: %d - %s)
- Error number: [MY-013138](#); Symbol: [ER_SERVER_FILE_USED](#); SQLSTATE: [HY000](#)
- Message: '%s' is locked against change (OS errno: %d - %s)
- Error number: [MY-013139](#); Symbol: [ER_SERVER_CANNOT_LOAD_FROM_TABLE_V2](#); SQLSTATE: [HY000](#)
- Message: Cannot load from %s.%s. The table is probably corrupted!
- Error number: [MY-013140](#); Symbol: [ER_ERROR_INFO_FROM_DA](#); SQLSTATE: [HY000](#)
- Message: Error in diagnostics area: MY-%06d - %s
- Error number: [MY-013141](#); Symbol: [ER_SERVER_TABLE_CHECK_FAILED](#); SQLSTATE: [HY000](#)
- Message: Incorrect definition of table %s.%s: expected column '%s' at position %d, found '%s'.
- Error number: [MY-013142](#); Symbol: [ER_SERVER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V2](#); SQLSTATE: [HY000](#)
- Message: The column count of %s.%s is wrong. Expected %d, found %d. Created with MySQL %d, now running %d. Please perform the MySQL upgrade procedure.
- Error number: [MY-013143](#); Symbol: [ER_SERVER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2](#); SQLSTATE: [HY000](#)
- Message: Column count of %s.%s is wrong. Expected %d, found %d. The table is probably corrupted.
- Error number: [MY-013144](#); Symbol: [ER_SERVER_ACL_TABLE_ERROR](#); SQLSTATE: [HY000](#)
- Message:
- Error number: [MY-013145](#); Symbol: [ER_SERVER_REPLICA_INIT_QUERY_FAILED](#); SQLSTATE: [HY000](#)
- Message: Replica SQL thread aborted. Can't execute init_replica query, MY-%06d - '%s'
- Error number: [MY-013146](#); Symbol: [ER_SERVER_REPLICA_CONVERSION_FAILED](#); SQLSTATE: [HY000](#)
- Message: Column %d of table '%s.%s' cannot be converted from type '%s' to type '%s'
- Error number: [MY-013147](#); Symbol: [ER_SERVER_REPLICA_IGNORED_TABLE](#); SQLSTATE: [HY000](#)
- Message: Replica SQL thread ignored the query because of replicate-*-*table rules
- Error number: [MY-013148](#); Symbol: [ER_CANT_REPLICATE_ANONYMOUS_WITH_AUTO_POSITION](#); SQLSTATE: [HY000](#)
- Message: Cannot replicate anonymous transaction when AUTO_POSITION = 1, at file %s, position %lld.
- Error number: [MY-013149](#); Symbol: [ER_CANT_REPLICATE_ANONYMOUS_WITH_GTID_MODE_ON](#); SQLSTATE: [HY000](#)

Message: Cannot replicate anonymous transaction when @@GLOBAL.GTID_MODE = ON, at file %s, position %lld.

- Error number: [MY-013150](#); Symbol: [ER_CANT_REPLICATE_GTID_WITH_GTID_MODE_OFF](#); SQLSTATE: [HY000](#)

Message: Cannot replicate GTID-transaction when @@GLOBAL.GTID_MODE = OFF, at file %s, position %lld.

- Error number: [MY-013151](#); Symbol: [ER_SERVER_TEST_MESSAGE](#); SQLSTATE: [HY000](#)

Message: Simulated error

- Error number: [MY-013152](#); Symbol: [ER_AUDIT_LOG_JSON_FILTER_PARSING_ERROR](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013153](#); Symbol: [ER_AUDIT_LOG_JSON_FILTERING_NOT_ENABLED](#); SQLSTATE: [HY000](#)

Message: Audit Log filtering has not been installed.

- Error number: [MY-013154](#); Symbol: [ER_PLUGIN_FAILED_TO_OPEN_TABLES](#); SQLSTATE: [HY000](#)

Message: Failed to open the %s filter tables.

- Error number: [MY-013155](#); Symbol: [ER_PLUGIN_FAILED_TO_OPEN_TABLE](#); SQLSTATE: [HY000](#)

Message: Failed to open '%s.%s' %s table.

- Error number: [MY-013156](#); Symbol: [ER_AUDIT_LOG_JSON_FILTER_NAME_CANNOT_BE_EMPTY](#); SQLSTATE: [HY000](#)

Message: Filter name cannot be empty.

- Error number: [MY-013157](#); Symbol: [ER_AUDIT_LOG_USER_NAME_INVALID_CHARACTER](#); SQLSTATE: [HY000](#)

Message: Invalid character in the user name.

- Error number: [MY-013158](#); Symbol: [ER_AUDIT_LOG_UDF_INSUFFICIENT_PRIVILEGE](#); SQLSTATE: [HY000](#)

Message: Request ignored for '%s'@'%s'. SUPER or AUDIT_ADMIN needed to perform operation

- Error number: [MY-013159](#); Symbol: [ER_AUDIT_LOG_NO_KEYRING_PLUGIN_INSTALLED](#); SQLSTATE: [HY000](#)

Message: No keyring installed.

- Error number: [MY-013160](#); Symbol: [ER_AUDIT_LOG_HOST_NAME_INVALID_CHARACTER](#); SQLSTATE: [HY000](#)

Message: Invalid character in the host name.

- Error number: [MY-013161](#); Symbol: [ER_AUDIT_LOG_ENCRYPTION_PASSWORD_HAS_NOT_BEEN_SET](#); SQLSTATE: [HY000](#)

Message: Audit log encryption password has not been set; it will be generated automatically. Use `audit_log_encryption_password_get` to obtain the password or `audit_log_encryption_password_set` to set a new one.

- Error number: `MY-013162`; Symbol: `ER_AUDIT_LOG_COULD_NOT_CREATE_AES_KEY`; SQLSTATE: `HY000`

Message: Could not create AES key. OpenSSL's `EVP_BytesToKey` function failed.

- Error number: `MY-013163`; Symbol: `ER_AUDIT_LOG_ENCRYPTION_PASSWORD_CANNOT_BE_FETCHED`; SQLSTATE: `HY000`

Message: Audit log encryption password cannot be fetched from the keyring. Password used so far is used for encryption.

- Error number: `MY-013164`; Symbol: `ER_COULD_NOT_REINITIALIZE_AUDIT_LOG_FILTERS`; SQLSTATE: `HY000`

Message: Could not reinitialize audit log filters.

- Error number: `MY-013165`; Symbol: `ER_AUDIT_LOG_JSON_USER_NAME_CANNOT_BE_EMPTY`; SQLSTATE: `HY000`

Message: User cannot be empty.

- Error number: `MY-013166`; Symbol: `ER_AUDIT_LOG_USER_FIRST_CHARACTER_MUST_BE_ALPHANUMERIC`; SQLSTATE: `HY000`

Message: First character of the user name must be alphanumeric.

- Error number: `MY-013167`; Symbol: `ER_AUDIT_LOG_JSON_FILTER_DOES_NOT_EXIST`; SQLSTATE: `HY000`

Message: Specified filter has not been found.

- Error number: `MY-013169`; Symbol: `ER_STARTING_INIT`; SQLSTATE: `HY000`

Message: %s (mysqld %s) initializing of server in progress as process %lu

- Error number: `MY-013170`; Symbol: `ER_ENDING_INIT`; SQLSTATE: `HY000`

Message: %s (mysqld %s) initializing of server has completed

- Error number: `MY-013171`; Symbol: `ER_IB_MSG_1272`; SQLSTATE: `HY000`

Message: Cannot boot server version %lu on data directory built by version %llu. Downgrade is not supported

- Error number: `MY-013172`; Symbol: `ER_SERVER_SHUTDOWN_INFO`; SQLSTATE: `HY000`

Message: Received SHUTDOWN from user %s. Shutting down mysqld (Version: %s).

- Error number: `MY-013173`; Symbol: `ER_GRP_RPL_PLUGIN_ABORT`; SQLSTATE: `HY000`

Message: The plugin encountered a critical error and will abort: %s

- Error number: `MY-013177`; Symbol: `ER_AUDIT_LOG_TABLE_DEFINITION_NOT_UPDATED`; SQLSTATE: `HY000`

Message: '%s.%s' table definition has not been upgraded; Please perform the MySQL upgrade procedure.

- Error number: [MY-013178](#); Symbol: [ER_DD_INITIALIZE_SQL_ERROR](#); SQLSTATE: [HY000](#)

Message: Execution of server-side SQL statement '%s' failed with error code = %d, error message = '%s'.

- Error number: [MY-013179](#); Symbol: [ER_NO_PATH_FOR_SHARED_LIBRARY](#); SQLSTATE: [HY000](#)

Message: No paths allowed for shared library.

- Error number: [MY-013180](#); Symbol: [ER_UDF_ALREADY_EXISTS](#); SQLSTATE: [HY000](#)

Message: Function '%s' already exists.

- Error number: [MY-013181](#); Symbol: [ER_SET_EVENT_FAILED](#); SQLSTATE: [HY000](#)

Message: Got Error: %ld from SetEvent.

- Error number: [MY-013182](#); Symbol: [ER_FAILED_TO_ALLOCATE_SSL_BIO](#); SQLSTATE: [HY000](#)

Message: Error allocating SSL BIO.

- Error number: [MY-013183](#); Symbol: [ER_IB_MSG_1273](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013184](#); Symbol: [ER_PID_FILEPATH_LOCATIONS_INACCESSIBLE](#); SQLSTATE: [HY000](#)

Message: One or several locations were inaccessible while checking PID filepath.

- Error number: [MY-013185](#); Symbol: [ER_UNKNOWN_VARIABLE_IN_PERSISTED_CONFIG_FILE](#); SQLSTATE: [HY000](#)

Message: Currently unknown variable '%s' was read from the persisted config file.

- Error number: [MY-013186](#); Symbol: [ER_FAILED_TO_HANDLE_DEFAULTS_FILE](#); SQLSTATE: [HY000](#)

Message: Fatal error in defaults handling. Program aborted!

- Error number: [MY-013187](#); Symbol: [ER_DUPLICATE_SYS_VAR](#); SQLSTATE: [HY000](#)

Message: Duplicate variable name '%s'.

- Error number: [MY-013188](#); Symbol: [ER_FAILED_TO_INIT_SYS_VAR](#); SQLSTATE: [HY000](#)

Message: Failed to initialize system variables.

- Error number: [MY-013189](#); Symbol: [ER_SYS_VAR_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Variable name '%s' not found.

- Error number: [MY-013190](#); Symbol: [ER_IB_MSG_1274](#); SQLSTATE: [HY000](#)

Message: Some (%d) threads are still active

- Error number: [MY-013191](#); Symbol: [ER_IB_MSG_1275](#); SQLSTATE: [HY000](#)

-
- Message: %s
- Error number: [MY-013193](#); Symbol: [ER_IB_MSG_WAIT_FOR_ENCRYPT_THREAD](#); SQLSTATE: [HY000](#)
Message: Waiting for tablespace_alter_encrypt_thread to exit
 - Error number: [MY-013194](#); Symbol: [ER_IB_MSG_1277](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013195](#); Symbol: [ER_IB_MSG_NO_ENCRYPT_PROGRESS_FOUND](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013196](#); Symbol: [ER_IB_MSG_RESUME_OP_FOR_SPACE](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013197](#); Symbol: [ER_IB_MSG_1280](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013198](#); Symbol: [ER_IB_MSG_1281](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013199](#); Symbol: [ER_IB_MSG_1282](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013200](#); Symbol: [ER_IB_MSG_1283](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013201](#); Symbol: [ER_IB_MSG_1284](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013202](#); Symbol: [ER_CANT_SET_ERROR_SUPPRESSION_LIST_FROM_COMMAND_LINE](#); SQLSTATE: [HY000](#)
Message: %s: Could not add suppression rule for code "%s". Rule-set may be full, or code may not correspond to an error-log message.
 - Error number: [MY-013203](#); Symbol: [ER_INVALID_VALUE_OF_BIND_ADDRESSES](#); SQLSTATE: [HY000](#)
Message: Invalid value for command line option bind-addresses: '%s'
 - Error number: [MY-013204](#); Symbol: [ER_RELAY_LOG_SPACE_LIMIT_DISABLED](#); SQLSTATE: [HY000](#)
Message: Ignoring the @@global.relay_log_space_limit option because @@global.relay_log_purge is disabled.
 - Error number: [MY-013205](#); Symbol: [ER_GRP_RPL_ERROR_GTID_SET_EXTRACTION](#); SQLSTATE: [HY000](#)
Message: Error when extracting GTID execution information: %s

-
- Error number: `MY-013206`; Symbol: `ER_GRP_RPL_MISSING_GRP_RPL_ACTION_COORDINATOR`; SQLSTATE: `HY000`
Message: Message received without a proper group coordinator module.
 - Error number: `MY-013207`; Symbol: `ER_GRP_RPL_JOIN_WHEN_GROUP_ACTION_RUNNING`; SQLSTATE: `HY000`
Message: A member cannot join the group while a group configuration operation '%s' is running initiated by '%s'.
 - Error number: `MY-013208`; Symbol: `ER_GRP_RPL_JOINER_EXIT_WHEN_GROUP_ACTION_RUNNING`; SQLSTATE: `HY000`
Message: A member is joining the group while a group configuration operation '%s' is running initiated by '%s'. The member will now leave the group.
 - Error number: `MY-013209`; Symbol: `ER_GRP_RPL_CHANNEL_THREAD_WHEN_GROUP_ACTION_RUNNING`; SQLSTATE: `HY000`
Message: Can't start %s for channel '%s' when group replication is running a group configuration operation '%s' initiated by '%s'.
 - Error number: `MY-013210`; Symbol: `ER_GRP_RPL_APPOINTED_PRIMARY_NOT_PRESENT`; SQLSTATE: `HY000`
Message: A primary election was invoked but the requested primary member is not in the group. Request ignored.
 - Error number: `MY-013211`; Symbol: `ER_GRP_RPL_ERROR_ON_MESSAGE_SENDING`; SQLSTATE: `HY000`
Message: Error while sending message. Context: %s
 - Error number: `MY-013212`; Symbol: `ER_GRP_RPL_CONFIGURATION_ACTION_ERROR`; SQLSTATE: `HY000`
Message: Error while executing a group configuration operation: %s
 - Error number: `MY-013213`; Symbol: `ER_GRP_RPL_CONFIGURATION_ACTION_LOCAL_TERMINATION`; SQLSTATE: `HY000`
Message: Configuration operation '%s' terminated. %s
 - Error number: `MY-013214`; Symbol: `ER_GRP_RPL_CONFIGURATION_ACTION_START`; SQLSTATE: `HY000`
Message: Starting group operation local execution: %s
 - Error number: `MY-013215`; Symbol: `ER_GRP_RPL_CONFIGURATION_ACTION_END`; SQLSTATE: `HY000`
Message: Termination of group operation local execution: %s
 - Error number: `MY-013216`; Symbol: `ER_GRP_RPL_CONFIGURATION_ACTION_KILLED_ERROR`; SQLSTATE: `HY000`
Message: A configuration change was killed in this member. The member will now leave the group as its configuration may have diverged.

-
- Error number: [MY-013217](#); Symbol: [ER_GRP_RPL_PRIMARY_ELECTION_PROCESS_ERROR](#); SQLSTATE: [HY000](#)
Message: There was an issue on the primary election process: %s The member will now leave the group.
 - Error number: [MY-013218](#); Symbol: [ER_GRP_RPL_PRIMARY_ELECTION_STOP_ERROR](#); SQLSTATE: [HY000](#)
Message: There was an issue when stopping a previous election process: %s
 - Error number: [MY-013219](#); Symbol: [ER_GRP_RPL_NO_STAGE_SERVICE](#); SQLSTATE: [HY000](#)
Message: It was not possible to initialize stage logging for this task. The operation will still run without stage tracking.
 - Error number: [MY-013220](#); Symbol: [ER_GRP_RPL_UDF_REGISTER_ERROR](#); SQLSTATE: [HY000](#)
Message: Could not execute the installation of Group Replication UDF function: %s. Check if the function is already present, if so, try to remove it
 - Error number: [MY-013221](#); Symbol: [ER_GRP_RPL_UDF_UNREGISTER_ERROR](#); SQLSTATE: [HY000](#)
Message: Could not uninstall Group Replication UDF functions. Try to remove them manually if present.
 - Error number: [MY-013222](#); Symbol: [ER_GRP_RPL_UDF_REGISTER_SERVICE_ERROR](#); SQLSTATE: [HY000](#)
Message: Could not execute the installation of Group Replication UDF functions. Check for other errors in the log and try to reinstall the plugin
 - Error number: [MY-013223](#); Symbol: [ER_GRP_RPL_SERVER_UDF_ERROR](#); SQLSTATE: [HY000](#)
Message: The function '%s' failed. %s
 - Error number: [MY-013227](#); Symbol: [ER_SERVER_WRONG_VALUE_FOR_VAR](#); SQLSTATE: [HY000](#)
Message: Variable '%s' can't be set to the value of '%s'
 - Error number: [MY-013228](#); Symbol: [ER_COULD_NOT_CREATE_WINDOWS_REGISTRY_KEY](#); SQLSTATE: [HY000](#)
Message: %s was unable to create a new Windows registry key %s for %s; continuing to use the previous ident.
 - Error number: [MY-013229](#); Symbol: [ER_SERVER_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN_TRX_IN_SBR](#); SQLSTATE: [HY000](#)
Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE are not allowed inside a transaction or inside a procedure in a transactional context when @@session.binlog_format=STATEMENT.
 - Error number: [MY-013233](#); Symbol: [ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX](#); SQLSTATE: [HY000](#)
Message: Unable to switch security context to user: %s
 - Error number: [MY-013234](#); Symbol: [ER_RPL_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION](#); SQLSTATE: [HY000](#)

Message: Statement violates GTID consistency: ALTER TABLE ... ADD COLUMN .. with expression as DEFAULT.

- Error number: [MY-013235](#); Symbol: [ER_UPGRADE_PARSE_ERROR](#); SQLSTATE: [HY000](#)

Message: Error in parsing %s '%s'.'%s' during upgrade. %s

- Error number: [MY-013236](#); Symbol: [ER_DATA_DIRECTORY_UNUSABLE](#); SQLSTATE: [HY000](#)

Message: The designated data directory %s is unusable. You can remove all files that the server added to it.

- Error number: [MY-013237](#); Symbol: [ER_LDAP_AUTH_USER_GROUP_SEARCH_ROOT_BIND](#); SQLSTATE: [HY000](#)

Message: Group search rebinding via root DN: %s

- Error number: [MY-013238](#); Symbol: [ER_PLUGIN_INSTALL_ERROR](#); SQLSTATE: [HY000](#)

Message: Error installing plugin '%s': %s

- Error number: [MY-013239](#); Symbol: [ER_PLUGIN_UNINSTALL_ERROR](#); SQLSTATE: [HY000](#)

Message: Error uninstalling plugin '%s': %s

- Error number: [MY-013240](#); Symbol: [ER_SHARED_TABLESPACE_USED_BY_PARTITIONED_TABLE](#); SQLSTATE: [HY000](#)

Message: Partitioned table '%s' is not allowed to use shared tablespace '%s'. Please move all partitions to file-per-table tablespaces before upgrade.

- Error number: [MY-013241](#); Symbol: [ER_UNKNOWN_TABLESPACE_TYPE](#); SQLSTATE: [HY000](#)

Message: Cannot determine the type of the tablespace named '%s'.

- Error number: [MY-013242](#); Symbol: [ER_WARN_DEPRECATED_UTF8_ALIAS_OPTION](#); SQLSTATE: [HY000](#)

Message: %s: 'utf8' is currently an alias for the character set UTF8MB3, but will be an alias for UTF8MB4 in a future release. Please consider using UTF8MB4 in order to be unambiguous.

- Error number: [MY-013243](#); Symbol: [ER_WARN_DEPRECATED_UTF8MB3_CHARSET_OPTION](#); SQLSTATE: [HY000](#)

Message: %s: The character set UTF8MB3 is deprecated and will be removed in a future release. Please consider using UTF8MB4 instead.

- Error number: [MY-013244](#); Symbol: [ER_WARN_DEPRECATED_UTF8MB3_COLLATION_OPTION](#); SQLSTATE: [HY000](#)

Message: %s: '%s' is a collation of the deprecated character set UTF8MB3. Please consider using UTF8MB4 with an appropriate collation instead.

- Error number: [MY-013245](#); Symbol: [ER_SSL_MEMORY_INSTRUMENTATION_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: The SSL library function %s failed. This is typically caused by the SSL library already being used. As a result the SSL memory allocation will not be instrumented.

-
- Error number: [MY-013246](#); Symbol: [ER_IB_MSG_MADV_DONTDUMP_UNSUPPORTED](#); SQLSTATE: [HY000](#)
Message: Disabling @@core_file because @@innodb_buffer_pool_in_core_file is disabled, yet MADV_DONTDUMP is not supported on this platform
 - Error number: [MY-013247](#); Symbol: [ER_IB_MSG_MADVISE_FAILED](#); SQLSTATE: [HY000](#)
Message: Disabling @@core_file because @@innodb_buffer_pool_in_core_file is disabled, yet madvise(%p,%zu,%s) failed with %s
 - Error number: [MY-013249](#); Symbol: [ER_WARN_REMOVED_SQL_MODE](#); SQLSTATE: [HY000](#)
Message: sql_mode=0x%08x has been removed and will be ignored
 - Error number: [MY-013250](#); Symbol: [ER_IB_MSG_FAILED_TO_ALLOCATE_WAIT](#); SQLSTATE: [HY000](#)
Message: Failed to allocate memory for a pool of size %zu bytes. Will wait for %zu seconds for a thread to free a resource.
 - Error number: [MY-013252](#); Symbol: [ER_IB_MSG_USING_UNDO_SPACE](#); SQLSTATE: [HY000](#)
Message: Using undo tablespace '%s'.
 - Error number: [MY-013253](#); Symbol: [ER_IB_MSG_FAIL_TO_SAVE_SPACE_STATE](#); SQLSTATE: [HY000](#)
Message: %s Unable to save the current state of tablespace '%s' to the data dictionary
 - Error number: [MY-013254](#); Symbol: [ER_IB_MSG_MAX_UNDO_SPACES_REACHED](#); SQLSTATE: [HY000](#)
Message: Cannot create undo tablespace %s at %s because %d undo tablespaces already exist.
 - Error number: [MY-013255](#); Symbol: [ER_IB_MSG_ERROR_OPENING_NEW_UNDO_SPACE](#); SQLSTATE: [HY000](#)
Message: Error %d opening newly created undo tablespace %s.
 - Error number: [MY-013256](#); Symbol: [ER_IB_MSG_FAILED_SDI_Z_BUF_ERROR](#); SQLSTATE: [HY000](#)
Message: SDI Compression failed, Z_BUF_ERROR
 - Error number: [MY-013257](#); Symbol: [ER_IB_MSG_FAILED_SDI_Z_MEM_ERROR](#); SQLSTATE: [HY000](#)
Message: SDI Compression failed, Z_MEM_ERROR
 - Error number: [MY-013258](#); Symbol: [ER_IB_MSG_SDI_Z_STREAM_ERROR](#); SQLSTATE: [HY000](#)
Message: SDI Compression failed, Z_STREAM_ERROR
 - Error number: [MY-013259](#); Symbol: [ER_IB_MSG_SDI_Z_UNKNOWN_ERROR](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013260](#); Symbol: [ER_IB_MSG_FOUND_WRONG_UNDO_SPACE](#); SQLSTATE: [HY000](#)
Message: Expected to find undo tablespace '%s' for Space ID=%lu, but found '%s' instead! Did you change innodb_undo_directory?
 - Error number: [MY-013261](#); Symbol: [ER_IB_MSG_NOT_END_WITH_IBU](#); SQLSTATE: [HY000](#)

Message: Cannot use %s as an undo tablespace because it does not end with '.ibu'.

- Error number: [MY-013266](#); Symbol: [ER_IB_MSG_FAILED_TO_FINISH_TRUNCATE](#); SQLSTATE: [HY000](#)

Message: %s Failed to finish truncating Undo Tablespace '%s'

- Error number: [MY-013267](#); Symbol: [ER_IB_MSG_DEPRECATED_INNODB_UNDO_TABLESPACES](#); SQLSTATE: [HY000](#)

Message: The setting INNODB_UNDO_TABLESPACES is deprecated and is no longer used. InnoDB always creates 2 undo tablespaces to start with. If you need more, please use CREATE UNDO TABLESPACE.

- Error number: [MY-013268](#); Symbol: [ER_IB_MSG_WRONG_TABLESPACE_DIR](#); SQLSTATE: [HY000](#)

Message: The directory for tablespace %s does not exist or is incorrect.

- Error number: [MY-013269](#); Symbol: [ER_IB_MSG_LOCK_FREE_HASH_USAGE_STATS](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013270](#); Symbol: [ER_CLONE_DONOR_TRACE](#); SQLSTATE: [HY000](#)

Message: Clone donor reported : %s.

- Error number: [MY-013271](#); Symbol: [ER_CLONE_PROTOCOL_TRACE](#); SQLSTATE: [HY000](#)

Message: Clone received unexpected response from donor : %s.

- Error number: [MY-013272](#); Symbol: [ER_CLONE_CLIENT_TRACE](#); SQLSTATE: [HY000](#)

Message: Client: %s.

- Error number: [MY-013273](#); Symbol: [ER_CLONE_SERVER_TRACE](#); SQLSTATE: [HY000](#)

Message: Server: %s.

- Error number: [MY-013274](#); Symbol: [ER_THREAD_POOL_PFS_TABLES_INIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to initialize the performance schema tables service.

- Error number: [MY-013275](#); Symbol: [ER_THREAD_POOL_PFS_TABLES_ADD_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to add thread pool performance schema tables.

- Error number: [MY-013276](#); Symbol: [ER_CANT_SET_DATA_DIR](#); SQLSTATE: [HY000](#)

Message: Failed to set datadir to '%s\' (OS errno: %d - %s)

- Error number: [MY-013277](#); Symbol: [ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY_LOCATION](#); SQLSTATE: [HY000](#)

Message: The innodb_undo_directory is not allowed to be an ancestor of the datadir.

-
- Error number: `MY-013278`; Symbol: `ER_SERVER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY`; SQLSTATE: `HY000`

Message: Failed to fetch key from keyring, please check if keyring is loaded.

- Error number: `MY-013279`; Symbol: `ER_SERVER_RPL_ENCRYPTION_KEY_NOT_FOUND`; SQLSTATE: `HY000`

Message: Can't find key from keyring, please check in the server log if a keyring is loaded and initialized successfully.

- Error number: `MY-013280`; Symbol: `ER_SERVER_RPL_ENCRYPTION_KEYRING_INVALID_KEY`; SQLSTATE: `HY000`

Message: Fetched an invalid key from keyring.

- Error number: `MY-013281`; Symbol: `ER_SERVER_RPL_ENCRYPTION_HEADER_ERROR`; SQLSTATE: `HY000`

Message: Error reading a replication log encryption header: %s.

- Error number: `MY-013282`; Symbol: `ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS`; SQLSTATE: `HY000`

Message: Failed to rotate some logs after changing binlog encryption settings. Please fix the problem and rotate the logs manually.

- Error number: `MY-013283`; Symbol: `ER_SERVER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED`; SQLSTATE: `HY000`

Message: Key %s exists unexpected.

- Error number: `MY-013284`; Symbol: `ER_SERVER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY`; SQLSTATE: `HY000`

Message: Failed to generate key, please check if keyring is loaded.

- Error number: `MY-013285`; Symbol: `ER_SERVER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY`; SQLSTATE: `HY000`

Message: Failed to store key, please check if keyring is loaded.

- Error number: `MY-013286`; Symbol: `ER_SERVER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY`; SQLSTATE: `HY000`

Message: Failed to remove key, please check if keyring is loaded.

- Error number: `MY-013287`; Symbol: `ER_SERVER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED`; SQLSTATE: `HY000`

Message: Unable to recover binlog encryption master key, please check if keyring is loaded.

- Error number: `MY-013288`; Symbol: `ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_INITIALIZE`; SQLSTATE: `HY000`

Message: Failed to initialize binlog encryption, please check if keyring is loaded.

-
- Error number: `MY-013289`; Symbol: `ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_ROTATE_MASTER_KEY_AT_STARTUP`; SQLSTATE: `HY000`
Message: Failed to rotate binlog encryption master key at startup, please check if keyring is loaded.
 - Error number: `MY-013290`; Symbol: `ER_SERVER_RPL_ENCRYPTION_IGNORE_ROTATE_MASTER_KEY_AT_STARTUP`; SQLSTATE: `HY000`
Message: Ignoring binlog_rotate_encryption_master_key_at_startup because binlog_encryption option is disabled.
 - Error number: `MY-013291`; Symbol: `ER_INVALID_ADMIN_ADDRESS`; SQLSTATE: `HY000`
Message: Invalid value for command line option admin-address: '%s'
 - Error number: `MY-013292`; Symbol: `ER_SERVER_STARTUP_ADMIN_INTERFACE`; SQLSTATE: `HY000`
Message: Admin interface ready for connections, address: '%s' port: %d
 - Error number: `MY-013293`; Symbol: `ER_CANT_CREATE_ADMIN_THREAD`; SQLSTATE: `HY000`
Message: Can't create thread to handle admin connections (errno= %d)
 - Error number: `MY-013294`; Symbol: `ER_WARNING_RETAIN_CURRENT_PASSWORD_CLAUSE_VOID`; SQLSTATE: `HY000`
Message: RETAIN CURRENT PASSWORD ignored for user '%s'@'%s' as its authentication plugin %s does not support multiple passwords.
 - Error number: `MY-013295`; Symbol: `ER_WARNING_DISCARD_OLD_PASSWORD_CLAUSE_VOID`; SQLSTATE: `HY000`
Message: DISCARD OLD PASSWORD ignored for user '%s'@'%s' as its authentication plugin %s does not support multiple passwords.
 - Error number: `MY-013299`; Symbol: `ER_WARNING_AUTHCACHE_INVALID_USER_ATTRIBUTES`; SQLSTATE: `HY000`
Message: Can not read and process value of User_attributes column from mysql.user table for user: '%s@%s'; Ignoring user.
 - Error number: `MY-013300`; Symbol: `ER_MYSQL_NATIVE_PASSWORD_SECOND_PASSWORD_USED_INFORMATION`; SQLSTATE: `HY000`
Message: Second password was used for login by user: '%s'@'%s'.
 - Error number: `MY-013301`; Symbol: `ER_SHA256_PASSWORD_SECOND_PASSWORD_USED_INFORMATION`; SQLSTATE: `HY000`
Message: Second password was used for login by user: '%s'@'%s'.
 - Error number: `MY-013302`; Symbol: `ER_CACHING_SHA2_PASSWORD_SECOND_PASSWORD_USED_INFORMATION`; SQLSTATE: `HY000`
Message: Second password was used for login by user: '%s'@'%s'.
 - Error number: `MY-013303`; Symbol: `ER_GRP_RPL_SEND_TRX_PREPARED_MESSAGE_FAILED`; SQLSTATE: `HY000`
-

Message: Error sending transaction '%s:%lld' prepared message from session '%u'.

- Error number: MY-013304; Symbol:
ER_GRP_RPL_RELEASE_COMMIT_AFTER_GROUP_PREPARE_FAILED; SQLSTATE: HY000

Message: Error releasing transaction '%s:%lld' for commit on session '%u' after being prepared on all group members.

- Error number: MY-013305; Symbol:
ER_GRP_RPL_TRX_ALREADY_EXISTS_ON_TCM_ON_AFTER_CERTIFICATION; SQLSTATE: HY000

Message: Transaction '%s:%lld' already exists on Group Replication consistency manager while being registered after conflict detection.

- Error number: MY-013306; Symbol:
ER_GRP_RPL_FAILED_TO_INSERT_TRX_ON_TCM_ON_AFTER_CERTIFICATION; SQLSTATE: HY000

Message: Error registering transaction '%s:%lld' on Group Replication consistency manager after conflict detection.

- Error number: MY-013307; Symbol:
ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_GROUP_PREPARE_FAILED; SQLSTATE: HY000

Message: Error registering transaction '%s:%lld' from session '%u' to wait for being prepared on all group members.

- Error number: MY-013308; Symbol: ER_GRP_RPL_TRX_WAIT_FOR_GROUP_PREPARE_FAILED;
SQLSTATE: HY000

Message: Error on transaction '%s:%lld' from session '%u' while waiting for being prepared on all group members.

- Error number: MY-013309; Symbol:
ER_GRP_RPL_TRX_DOES_NOT_EXIST_ON_TCM_ON_HANDLE_REMOTE_PREPARE; SQLSTATE: HY000

Message: Transaction '%s:%lld' does not exist on Group Replication consistency manager while receiving remote transaction prepare.

- Error number: MY-013310; Symbol:
ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_DEPENDENCIES_COMMIT_FAILED; SQLSTATE: HY000

Message: Error releasing transaction '%s:%lld' for execution on session '%u' after its dependencies did complete commit.

- Error number: MY-013311; Symbol:
ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_DEPENDENCIES_FAILED; SQLSTATE: HY000

Message: Error registering transaction from session '%u' to wait for its dependencies to complete commit.

- Error number: MY-013312; Symbol: ER_GRP_RPL_WAIT_FOR_DEPENDENCIES_FAILED; SQLSTATE:
HY000

Message: Error on session '%u' while waiting for its dependencies to complete commit.

- Error number: MY-013313; Symbol:
ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_SYNC_BEFORE_EXECUTION_FAILED; SQLSTATE:
HY000

Message: Error registering transaction from session '%u' to wait for sync before execution.

- Error number: `MY-013314`; Symbol: `ER_GRP_RPL_SEND_TRX_SYNC_BEFORE_EXECUTION_FAILED`; SQLSTATE: `HY000`

Message: Error sending sync before execution message from session '%u'.

- Error number: `MY-013315`; Symbol: `ER_GRP_RPL_TRX_WAIT_FOR_SYNC_BEFORE_EXECUTION_FAILED`; SQLSTATE: `HY000`

Message: Error on transaction from session '%u' while waiting for sync before execution.

- Error number: `MY-013316`; Symbol: `ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_WAIT_FOR_SYNC_BEFORE_EXEC`; SQLSTATE: `HY000`

Message: Error releasing transaction for execution on session '%u' after wait for sync before execution.

- Error number: `MY-013317`; Symbol: `ER_GRP_RPL_TRX_WAIT_FOR_GROUP_GTID_EXECUTED`; SQLSTATE: `HY000`

Message: Error waiting for group executed transactions commit on session '%u'.

- Error number: `MY-013320`; Symbol: `ER_WARN_PROPERTY_STRING_PARSE_FAILED`; SQLSTATE: `HY000`

Message: Could not parse key-value pairs in property string '%s'

- Error number: `MY-013321`; Symbol: `ER_INVALID_PROPERTY_KEY`; SQLSTATE: `HY000`

Message: Property key '%s' is invalid.

- Error number: `MY-013322`; Symbol: `ER_GRP_RPL_GTID_SET_EXTRACT_ERROR_DURING_RECOVERY`; SQLSTATE: `HY000`

Message: Error when extracting the group_replication_applier channel received transactions set. Unable to ensure the execution of group transactions received during recovery.

- Error number: `MY-013323`; Symbol: `ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT`; SQLSTATE: `HY000`

Message: Failed to encrypt content to write into binlog file: %s.

- Error number: `MY-013324`; Symbol: `ER_CANNOT_GET_SERVER_VERSION_FROM_TABLESPACE_HEADER`; SQLSTATE: `HY000`

Message: Cannot get the server version number from the dictionary tablespace header.

- Error number: `MY-013325`; Symbol: `ER_CANNOT_SET_SERVER_VERSION_IN_TABLESPACE_HEADER`; SQLSTATE: `HY000`

Message: Cannot set the server version number in the dictionary tablespace header.

- Error number: `MY-013326`; Symbol: `ER_SERVER_UPGRADE_VERSION_NOT_SUPPORTED`; SQLSTATE: `HY000`

Message: Upgrading the server from server version '%u' is not supported.

- Error number: `MY-013327`; Symbol: `ER_SERVER_UPGRADE_FROM_VERSION`; SQLSTATE: `HY000`

Message: MySQL server upgrading from version '%u' to '%u'.

- Error number: `MY-013328`; Symbol: `ER_GRP_RPL_ERROR_ON_CERT_DB_INSTALL`; SQLSTATE: `HY000`

Message: The certification information could not be set in this server: '%s'

- Error number: `MY-013329`; Symbol: `ER_GRP_RPL_FORCE_MEMBERS_WHEN_LEAVING`; SQLSTATE: `HY000`

Message: A request to force a new group membership was issued when the member is leaving the group.

- Error number: `MY-013330`; Symbol: `ER_TRG_WRONG_ORDER`; SQLSTATE: `HY000`

Message: Trigger %s.%s for table %s.%s is listed in wrong order. Please drop and recreate all triggers for the table.

- Error number: `MY-013332`; Symbol: `ER_LDAP_AUTH_GRP_SEARCH_NOT_SPECIAL_HDL`; SQLSTATE: `HY000`

Message: Special handling for group search, {GA} not found

- Error number: `MY-013333`; Symbol: `ER_LDAP_AUTH_GRP_USER_OBJECT_HAS_GROUP_INFO`; SQLSTATE: `HY000`

Message: User group retrieval: User object has group information

- Error number: `MY-013334`; Symbol: `ER_LDAP_AUTH_GRP_INFO_FOUND_IN_MANY_OBJECTS`; SQLSTATE: `HY000`

Message: Group information found in multiple user objects. Search filter configuration is incorrect.

- Error number: `MY-013335`; Symbol: `ER_LDAP_AUTH_GRP_INCORRECT_ATTRIBUTE`; SQLSTATE: `HY000`

Message: User group retrieval: no group attribute found. Incorrect group search attribute.

- Error number: `MY-013336`; Symbol: `ER_LDAP_AUTH_GRP_NULL_ATTRIBUTE_VALUE`; SQLSTATE: `HY000`

Message: User group retrieval: Group attribute values is NULL.

- Error number: `MY-013337`; Symbol: `ER_LDAP_AUTH_GRP_DN_PARSING_FAILED`; SQLSTATE: `HY000`

Message: User group retrieval: parsing DN failed.

- Error number: `MY-013338`; Symbol: `ER_LDAP_AUTH_GRP_OBJECT_HAS_USER_INFO`; SQLSTATE: `HY000`

Message: User group retrieval: Group object has user information

- Error number: `MY-013339`; Symbol: `ER_LDAP_AUTH_LDAPS`; SQLSTATE: `HY000`

Message: Reserved port for ldaps using ldaps

- Error number: `MY-013340`; Symbol: `ER_LDAP_MAPPING_GET_USER_PROXY`; SQLSTATE: `HY000`

Message: Get user proxy

-
- Error number: [MY-013341](#); Symbol: [ER_LDAP_MAPPING_USER_DONT_BELONG_GROUP](#); SQLSTATE: [HY000](#)
Message: Get user proxy: User doesn't belongs to any group, user name will be treated as authenticated user.
 - Error number: [MY-013342](#); Symbol: [ER_LDAP_MAPPING_INFO](#); SQLSTATE: [HY000](#)
Message: Get user proxy: configured mapping info: %s
 - Error number: [MY-013343](#); Symbol: [ER_LDAP_MAPPING_EMPTY_MAPPING](#); SQLSTATE: [HY000](#)
Message: Get user proxy: User doesn't have group mapping information, First LDAP group will be treated as authenticated user.
 - Error number: [MY-013344](#); Symbol: [ER_LDAP_MAPPING_PROCESS_MAPPING](#); SQLSTATE: [HY000](#)
Message: Process group proxy mapping
 - Error number: [MY-013345](#); Symbol: [ER_LDAP_MAPPING_CHECK_DELIMI_QUOTE](#); SQLSTATE: [HY000](#)
Message: Check delimiter after quote
 - Error number: [MY-013346](#); Symbol: [ER_LDAP_MAPPING_PROCESS_DELIMITER](#); SQLSTATE: [HY000](#)
Message: Processing delimiter
 - Error number: [MY-013347](#); Symbol: [ER_LDAP_MAPPING_PROCESS_DELIMITER_EQUAL_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: Processing delimiter, separator = not found, resetting position
 - Error number: [MY-013348](#); Symbol: [ER_LDAP_MAPPING_PROCESS_DELIMITER_TRY_COMMA](#); SQLSTATE: [HY000](#)
Message: Processing delimiter, failed to get data for = separator try for separator ,.
 - Error number: [MY-013349](#); Symbol: [ER_LDAP_MAPPING_PROCESS_DELIMITER_COMMA_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: Processing delimiter, separator , not found, resetting position
 - Error number: [MY-013350](#); Symbol: [ER_LDAP_MAPPING_NO_SEPEARATOR_END_OF_GROUP](#); SQLSTATE: [HY000](#)
Message: Processing delimiter: No mapping separator is found, end of group information
 - Error number: [MY-013351](#); Symbol: [ER_LDAP_MAPPING_GETTING_NEXT_MAPPING](#); SQLSTATE: [HY000](#)
Message: Getting next mapping information
 - Error number: [MY-013352](#); Symbol: [ER_LDAP_MAPPING_PARSING_CURRENT_STATE](#); SQLSTATE: [HY000](#)
Message: Parsing mapping, current state: %d delimiter char: %c
 - Error number: [MY-013353](#); Symbol: [ER_LDAP_MAPPING_PARSING_MAPPING_INFO](#); SQLSTATE: [HY000](#)

-
- Message: Parsing mapping info, LDAP group: %s MySQL proxy: %s
- Error number: [MY-013354](#); Symbol: [ER_LDAP_MAPPING_PARSING_ERROR](#); SQLSTATE: [HY000](#)
Message: Mapping parsing error
 - Error number: [MY-013355](#); Symbol: [ER_LDAP_MAPPING_TRIMMING_SPACES](#); SQLSTATE: [HY000](#)
Message: Trimming left spaces
 - Error number: [MY-013356](#); Symbol: [ER_LDAP_MAPPING_IS_QUOTE](#); SQLSTATE: [HY000](#)
Message: Checking if current characters is quote
 - Error number: [MY-013357](#); Symbol: [ER_LDAP_MAPPING_NON_DESIRED_STATE](#); SQLSTATE: [HY000](#)
Message: Not desired state or un-defined states.
 - Error number: [MY-013358](#); Symbol: [ER_INVALID_NAMED_PIPE_FULL_ACCESS_GROUP](#); SQLSTATE: [HY000](#)
Message: Invalid value for named_pipe_full_access_group.
 - Error number: [MY-013359](#); Symbol: [ER_PREPARE_FOR_SECONDARY_ENGINE](#); SQLSTATE: [HY000](#)
Message: Retry the statement using a secondary storage engine.
 - Error number: [MY-013360](#); Symbol: [ER_SERVER_WARN_DEPRECATED](#); SQLSTATE: [HY000](#)
Message: '%s' is deprecated and will be removed in a future release. Please use %s instead
 - Error number: [MY-013361](#); Symbol: [ER_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLES](#); SQLSTATE: [HY000](#)
Message: Cannot set mandatory_roles: AuthId `%s`@`%s` has '%s' privilege.
 - Error number: [MY-013362](#); Symbol: [ER_SERVER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION](#); SQLSTATE: [HY000](#)
Message: Unable to recover binary log master key, the combination of new_master_key_seqno=%u, master_key_seqno=%u and old_master_key_seqno=%u are wrong.
 - Error number: [MY-013363](#); Symbol: [ER_SERVER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_AUX_KEY](#); SQLSTATE: [HY000](#)
Message: Failed to remove auxiliary binary log encryption key from keyring, please check if keyring is loaded. The cleanup of the binary log master key rotation process did not finish as expected and the cleanup will take place upon server restart or next 'ALTER INSTANCE ROTATE BINLOG MASTER KEY' execution.
 - Error number: [MY-013368](#); Symbol: [ER_TURNING_ON_PARTIAL_REVOKES](#); SQLSTATE: [HY000](#)
Message: At least one partial revoke exists on a database. Turning ON the system variable '@@partial_revokes'.
 - Error number: [MY-013369](#); Symbol: [ER_WARN_PARTIAL_REVOKE_AND_DB_GRANT](#); SQLSTATE: [HY000](#)

Message: For user '%s'@'%s', one or more privileges granted through mysql.db for database '%s', conflict with partial revoke. It could mean 'mysql' schema is corrupted.

- Error number: [MY-013370](#); Symbol: [ER_WARN_INCORRECT_PRIVILEGE_FOR_DB_RESTRICTIONS](#); SQLSTATE: [HY000](#)

Message: For user %s, ignored restrictions for privilege(s) '%s' for database '%s' as these are not valid database privileges.

- Error number: [MY-013371](#); Symbol: [ER_WARN_INVALID_DB_RESTRICTIONS](#); SQLSTATE: [HY000](#)

Message: For user %s, ignored restrictions for privilege(s) '%s' for database '%s' as corresponding global privilege(s) are not granted.

- Error number: [MY-013372](#); Symbol: [ER_GRP_RPL_INVALID_COMMUNICATION_PROTOCOL](#); SQLSTATE: [HY000](#)

Message: '%s' is an invalid value for group_replication_communication_protocol_join, please use a MySQL version between 5.7.14 and this server's version

- Error number: [MY-013373](#); Symbol: [ER_GRP_RPL_STARTED_AUTO_REJOIN](#); SQLSTATE: [HY000](#)

Message: Started auto-rejoin procedure attempt %lu of %lu

- Error number: [MY-013374](#); Symbol: [ER_GRP_RPL_TIMEOUT_RECEIVED_VC_ON_REJOIN](#); SQLSTATE: [HY000](#)

Message: Timeout while waiting for a view change event during the auto-rejoin procedure

- Error number: [MY-013375](#); Symbol: [ER_GRP_RPL_FINISHED_AUTO_REJOIN](#); SQLSTATE: [HY000](#)

Message: Auto-rejoin procedure attempt %lu of %lu finished. Member was %s able to join the group.

- Error number: [MY-013376](#); Symbol: [ER_GRP_RPL_DEFAULT_TABLE_ENCRYPTION_DIFF_FROM_GRP](#); SQLSTATE: [HY000](#)

Message: The member is configured with a default_table_encryption option value '%d' different from the group '%d'. The member will now exit the group.

- Error number: [MY-013377](#); Symbol: [ER_SERVER_UPGRADE_OFF](#); SQLSTATE: [HY000](#)

Message: Server shutting down because upgrade is required, yet prohibited by the command line option '--upgrade=NONE'.

- Error number: [MY-013378](#); Symbol: [ER_SERVER_UPGRADE_SKIP](#); SQLSTATE: [HY000](#)

Message: Server upgrade is required, but skipped by command line option '--upgrade=MINIMAL'.

- Error number: [MY-013379](#); Symbol: [ER_SERVER_UPGRADE_PENDING](#); SQLSTATE: [HY000](#)

Message: Server upgrade started with version %d, but server upgrade of version %d is still pending.

- Error number: [MY-013380](#); Symbol: [ER_SERVER_UPGRADE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to upgrade server.

- Error number: [MY-013381](#); Symbol: [ER_SERVER_UPGRADE_STATUS](#); SQLSTATE: [HY000](#)

Message: Server upgrade from '%d' to '%d' %s.

-
- Error number: [MY-013382](#); Symbol: [ER_SERVER_UPGRADE_REPAIR_REQUIRED](#); SQLSTATE: [HY000](#)
Message: Table '%s' requires repair.
 - Error number: [MY-013383](#); Symbol: [ER_SERVER_UPGRADE_REPAIR_STATUS](#); SQLSTATE: [HY000](#)
Message: Table '%s' repair %s.
 - Error number: [MY-013384](#); Symbol: [ER_SERVER_UPGRADE_INFO_FILE](#); SQLSTATE: [HY000](#)
Message: Could not open server upgrade info file '%s' for writing. Please make sure the file is writable.
 - Error number: [MY-013385](#); Symbol: [ER_SERVER_UPGRADE_SYS_SCHEMA](#); SQLSTATE: [HY000](#)
Message: Upgrading the sys schema.
 - Error number: [MY-013386](#); Symbol: [ER_SERVER_UPGRADE_MYSQL_TABLES](#); SQLSTATE: [HY000](#)
Message: Running queries to upgrade MySQL server.
 - Error number: [MY-013387](#); Symbol: [ER_SERVER_UPGRADE_SYSTEM_TABLES](#); SQLSTATE: [HY000](#)
Message: Upgrading system table data.
 - Error number: [MY-013388](#); Symbol: [ER_SERVER_UPGRADE_EMPTY_SYS](#); SQLSTATE: [HY000](#)
Message: Found empty sys database. Installing the sys schema.
 - Error number: [MY-013389](#); Symbol: [ER_SERVER_UPGRADE_NO_SYS_VERSION](#); SQLSTATE: [HY000](#)
Message: A sys schema exists with no sys.version view. If you have a user created sys schema, this must be renamed for the upgrade to succeed.
 - Error number: [MY-013390](#); Symbol: [ER_SERVER_UPGRADE_SYS_VERSION_EMPTY](#); SQLSTATE: [HY000](#)
Message: A sys schema exists with a sys.version view, but it returns no results.
 - Error number: [MY-013391](#); Symbol: [ER_SERVER_UPGRADE_SYS_SCHEMA_OUTDATED](#); SQLSTATE: [HY000](#)
Message: Found outdated sys schema version %s.
 - Error number: [MY-013392](#); Symbol: [ER_SERVER_UPGRADE_SYS_SCHEMA_UP_TO_DATE](#); SQLSTATE: [HY000](#)
Message: The sys schema is already up to date (version %s).
 - Error number: [MY-013393](#); Symbol: [ER_SERVER_UPGRADE_SYS_SCHEMA_OBJECT_COUNT](#); SQLSTATE: [HY000](#)
Message: Found %d sys %s, but expected %d. Re-installing the sys schema.
 - Error number: [MY-013394](#); Symbol: [ER_SERVER_UPGRADE_CHECKING_DB](#); SQLSTATE: [HY000](#)
Message: Checking '%s' schema.
 - Error number: [MY-013395](#); Symbol: [ER_IB_MSG_DDL_LOG_DELETE_BY_ID_TMCT](#); SQLSTATE: [HY000](#)

Message: Too many concurrent transactions while clearing the DDL Log. Please increase the number of Rollback Segments.

- Error number: [MY-013396](#); Symbol: [ER_IB_MSG_POST_RECOVER_DDL_LOG_RECOVER](#); SQLSTATE: [HY000](#)

Message: Error in DDL Log recovery during Post-Recovery processing.

- Error number: [MY-013397](#); Symbol: [ER_IB_MSG_POST_RECOVER_POST_TS_ENCRYPT](#); SQLSTATE: [HY000](#)

Message: Error in Post-Tablespace-Encryption during Post-Recovery processing.

- Error number: [MY-013398](#); Symbol: [ER_IB_MSG_DDL_LOG_FAIL_POST_DDL](#); SQLSTATE: [HY000](#)

Message: Error in DLL Log cleanup during Post-DDL processing.

- Error number: [MY-013399](#); Symbol: [ER_SERVER_BINLOG_UNSAFE_SYSTEM_FUNCTION](#); SQLSTATE: [HY000](#)

Message: '%s' statement is unsafe because it uses a system function that may return a different value on the replica.

- Error number: [MY-013400](#); Symbol: [ER_SERVER_UPGRADE_HELP_TABLE_STATUS](#); SQLSTATE: [HY000](#)

Message: Upgrade of help tables %s.

- Error number: [MY-013404](#); Symbol: [ER_BINLOG_UNABLE_TO_ROTATE_GTID_TABLE_READONLY](#); SQLSTATE: [HY000](#)

Message: Unable to create a new binlog file: Table `mysql.gtid_executed` couldn't be opened. %s

- Error number: [MY-013405](#); Symbol: [ER_NETWORK_NAMESPACES_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)

Message: Network Namespaces is not supported on this platform

- Error number: [MY-013406](#); Symbol: [ER_UNKNOWN_NETWORK_NAMESPACE](#); SQLSTATE: [HY000](#)

Message: Unknown network namespace '%s'

- Error number: [MY-013407](#); Symbol: [ER_NETWORK_NAMESPACE_NOT_ALLOWED_FOR_WILDCARD_ADDRESS](#); SQLSTATE: [HY000](#)

Message: Network namespace not allowed for wildcard interface address

- Error number: [MY-013408](#); Symbol: [ER_SETNS_FAILED](#); SQLSTATE: [HY000](#)

Message: setns() failed with error '%s'

- Error number: [MY-013409](#); Symbol: [ER_WILDCARD_NOT_ALLOWED_FOR_MULTIADDRESS_BIND](#); SQLSTATE: [HY000](#)

Message: Wildcard address value not allowed for multivalued bind address

- Error number: [MY-013410](#); Symbol: [ER_NETWORK_NAMESPACE_FILE_PATH_TOO_LONG](#); SQLSTATE: [HY000](#)

-
- Message: The path to a special network namespace file is too long. (got %u > max %u)
- Error number: [MY-013411](#); Symbol: [ER_IB_MSG_TOO_LONG_PATH](#); SQLSTATE: [HY000](#)
Message: Cannot create tablespace '%s'. The filepath is too long for this OS.
 - Error number: [MY-013412](#); Symbol: [ER_IB_RECV_FIRST_REC_GROUP_INVALID](#); SQLSTATE: [HY000](#)
Message: The last block of redo had corrupted first_rec_group and became fixed (%u -> %u).
 - Error number: [MY-013413](#); Symbol: [ER_DD_UPGRADE_COMPLETED](#); SQLSTATE: [HY000](#)
Message: Data dictionary upgrade from version '%u' to '%u' completed.
 - Error number: [MY-013415](#); Symbol: [ER_PERSIST_OPTION_USER_TRUNCATED](#); SQLSTATE: [HY000](#)
Message: Truncated a user name for %s that was too long while reading the persisted variables file
 - Error number: [MY-013416](#); Symbol: [ER_PERSIST_OPTION_HOST_TRUNCATED](#); SQLSTATE: [HY000](#)
Message: Truncated a host name for %s that was too long while reading the persisted variables file
 - Error number: [MY-013417](#); Symbol: [ER_NET_WAIT_ERROR](#); SQLSTATE: [HY000](#)
Message: The wait_timeout period was exceeded, the idle time since last command was too long.
 - Error number: [MY-013418](#); Symbol: [ER_IB_MSG_1285](#); SQLSTATE: [HY000](#)
Message: '%s' found not encrypted while '%s' is ON. Trying to encrypt it now.
 - Error number: [MY-013419](#); Symbol: [ER_IB_MSG_CLOCK_MONOTONIC_UNSUPPORTED](#); SQLSTATE: [HY000](#)
Message: CLOCK_MONOTONIC is unsupported, so do not change the system time when MySQL is running !
 - Error number: [MY-013420](#); Symbol: [ER_IB_MSG_CLOCK_GETTIME_FAILED](#); SQLSTATE: [HY000](#)
Message: clock_gettime() failed: %s
 - Error number: [MY-013421](#); Symbol: [ER_PLUGIN_NOT_EARLY_DUP](#); SQLSTATE: [HY000](#)
Message: Plugin '%s' is not to be used as an "early" plugin. Don't add it to --early-plugin-load, keyring migration etc.
 - Error number: [MY-013422](#); Symbol: [ER_PLUGIN_NO_INSTALL_DUP](#); SQLSTATE: [HY000](#)
Message: Plugin '%s' is marked as not dynamically installable. You have to stop the server to install it.
 - Error number: [MY-013425](#); Symbol: [ER_BINLOG_UNSAFE_DEFAULT_EXPRESSION_IN_SUBSTATEMENT](#); SQLSTATE: [HY000](#)
Message: The statement is unsafe because it invokes a trigger or a stored function that modifies a table that has a column with a DEFAULT expression that may return a different value on the replica.
 - Error number: [MY-013426](#); Symbol: [ER_GRP_RPL_MEMBER_VER_READ_COMPATIBLE](#); SQLSTATE: [HY000](#)
Message: Member version is read compatible with the group.

-
- Error number: [MY-013427](#); Symbol: [ER_LOCK_ORDER_INIT_FAILED](#); SQLSTATE: [HY000](#)
Message: Lock order disabled (reason: init failed).
 - Error number: [MY-013428](#); Symbol: [ER_AUDIT_LOG_KEYRING_ID_TIMESTAMP_VALUE_IS_INVALID](#); SQLSTATE: [HY000](#)
Message: Keyring ID timestamp value is invalid: '%s'
 - Error number: [MY-013429](#); Symbol: [ER_AUDIT_LOG_FILE_NAME_TIMESTAMP_VALUE_IS_MISSING_OR_INVALID](#); SQLSTATE: [HY000](#)
Message: Cannot process audit log file. File name timestamp value is missing or invalid: '%s'
 - Error number: [MY-013430](#); Symbol: [ER_AUDIT_LOG_FILE_NAME_DOES_NOT_HAVE_REQUIRED_FORMAT](#); SQLSTATE: [HY000](#)
Message: Cannot process audit log file. File name does not have required format: '%s'
 - Error number: [MY-013431](#); Symbol: [ER_AUDIT_LOG_FILE_NAME_KEYRING_ID_VALUE_IS_MISSING](#); SQLSTATE: [HY000](#)
Message: Cannot process audit log file. File name keyring ID value is missing: '%s'
 - Error number: [MY-013432](#); Symbol: [ER_AUDIT_LOG_FILE_HAS_BEEN_SUCCESSFULLY_PROCESSED](#); SQLSTATE: [HY000](#)
Message: Audit log file has been successfully processed: '%s'
 - Error number: [MY-013433](#); Symbol: [ER_AUDIT_LOG_COULD_NOT_OPEN_FILE_FOR_READING](#); SQLSTATE: [HY000](#)
Message: Could not open audit log file for reading: '%s'
 - Error number: [MY-013434](#); Symbol: [ER_AUDIT_LOG_INVALID_FILE_CONTENT](#); SQLSTATE: [HY000](#)
Message: Invalid audit log file content: '%s'
 - Error number: [MY-013435](#); Symbol: [ER_AUDIT_LOG_CANNOT_READ_PASSWORD](#); SQLSTATE: [HY000](#)
Message: Cannot read password: '%s'.
 - Error number: [MY-013436](#); Symbol: [ER_AUDIT_LOG_CANNOT_STORE_PASSWORD](#); SQLSTATE: [HY000](#)
Message: Cannot store password: '%s'.
 - Error number: [MY-013437](#); Symbol: [ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD](#); SQLSTATE: [HY000](#)
Message: Cannot remove password: '%s'.
 - Error number: [MY-013438](#); Symbol: [ER_AUDIT_LOG_PASSWORD_HAS_BEEN_COPIED](#); SQLSTATE: [HY000](#)
Message: 'audit_log' password has been copied into '%s' and will be removed with first purged password.
 - Error number: [MY-013447](#); Symbol: [ER_LDAP_EMPTY_USERDN_PASSWORD](#); SQLSTATE: [HY000](#)
-

Message: Empty user dn or password is not allowed, not attempting LDAP bind.

- Error number: `MY-013449`; Symbol: `ER_ACL_WRONG_OR_MISSING_ACL_TABLES_LOG`; SQLSTATE: `HY000`

Message: The current layout of the ACL tables does not conform to the server's expected layout. They're either altered, missing or not upgraded from a previous version. However a best effort attempt to read data from these tables will still be made.

- Error number: `MY-013450`; Symbol: `ER_LOCK_ORDER_FAILED_WRITE_FILE`; SQLSTATE: `HY000`

Message: LOCK_ORDER: Failed to write to file <%s>.

- Error number: `MY-013451`; Symbol: `ER_LOCK_ORDER_FAILED_READ_FILE`; SQLSTATE: `HY000`

Message: LOCK_ORDER: Failed to read from file <%s>.

- Error number: `MY-013452`; Symbol: `ER_LOCK_ORDER_MESSAGE`; SQLSTATE: `HY000`

Message: LOCK_ORDER message: %s

- Error number: `MY-013453`; Symbol: `ER_LOCK_ORDER_DEPENDENCIES_SYNTAX`; SQLSTATE: `HY000`

Message: Lock order dependencies file <%s> (%d:%d) - (%d:%d) : %s

- Error number: `MY-013454`; Symbol: `ER_LOCK_ORDER_SCANNER_SYNTAX`; SQLSTATE: `HY000`

Message: Lock order scanner: (%d:%d) - (%d:%d) : %s

- Error number: `MY-013455`; Symbol: `ER_DATA_DIRECTORY_UNUSABLE_DELETABLE`; SQLSTATE: `HY000`

Message: The newly created data directory %s by --initialize is unusable. You can remove it.

- Error number: `MY-013456`; Symbol: `ER_IB_MSG_BTREE_LEVEL_LIMIT_EXCEEDED`; SQLSTATE: `HY000`

Message: No. of B-tree level created for index %s has crossed the permissible limit. If debug option `innodb_limit_optimistic_insert_debug` is being used try tweaking it to include more records in a page.

- Error number: `MY-013457`; Symbol: `ER_IB_CLONE_START_STOP`; SQLSTATE: `HY000`

Message: %s

- Error number: `MY-013458`; Symbol: `ER_IB_CLONE_OPERATION`; SQLSTATE: `HY000`

Message: %s

- Error number: `MY-013459`; Symbol: `ER_IB_CLONE_RESTART`; SQLSTATE: `HY000`

Message: %s

- Error number: `MY-013460`; Symbol: `ER_IB_CLONE_USER_DATA`; SQLSTATE: `HY000`

Message: Clone removing all user data for provisioning: %s

- Error number: `MY-013461`; Symbol: `ER_IB_CLONE_NON_INNO_DB_TABLE`; SQLSTATE: `HY000`

Message: Non innodb table: %s.%s is not cloned and is empty.

-
- Error number: [MY-013462](#); Symbol: [ER_CLONE_SHUTDOWN_TRACE](#); SQLSTATE: [HY000](#)
Message: Clone shutting down server as RESTART failed. Please start server to complete clone operation.
 - Error number: [MY-013463](#); Symbol: [ER_GRP_RPL_GTID_PURGED_EXTRACT_ERROR](#); SQLSTATE: [HY000](#)
Message: Error when extracting this member GTID purged set. Operations and checks made to group joiners may be incomplete.
 - Error number: [MY-013464](#); Symbol: [ER_GRP_RPL_CLONE_PROCESS_PREPARE_ERROR](#); SQLSTATE: [HY000](#)
Message: There was an issue when configuring the remote cloning process: %s
 - Error number: [MY-013465](#); Symbol: [ER_GRP_RPL_CLONE_PROCESS_EXEC_ERROR](#); SQLSTATE: [HY000](#)
Message: There was an issue when cloning from another server: %s
 - Error number: [MY-013466](#); Symbol: [ER_GRP_RPL_RECOVERY_EVAL_ERROR](#); SQLSTATE: [HY000](#)
Message: There was an issue when trying to evaluate the best distributed recovery strategy while joining.%s
 - Error number: [MY-013467](#); Symbol: [ER_GRP_RPL_NO_POSSIBLE_RECOVERY](#); SQLSTATE: [HY000](#)
Message: No valid or ONLINE members exist to get the missing data from the group. For cloning check if donors of the same version and with clone plugin installed exist. For incremental recovery check if you have donors where the required data was not purged from the binary logs.
 - Error number: [MY-013468](#); Symbol: [ER_GRP_RPL_CANT_KILL_THREAD](#); SQLSTATE: [HY000](#)
Message: The group replication plugin could not kill the plugin routine for %s. %s
 - Error number: [MY-013469](#); Symbol: [ER_GRP_RPL_RECOVERY_STRAT_CLONE_THRESHOLD](#); SQLSTATE: [HY000](#)
Message: This member will start distributed recovery using clone. It is due to the number of missing transactions being higher than the configured threshold of %llu.
 - Error number: [MY-013470](#); Symbol: [ER_GRP_RPL_RECOVERY_STRAT_CLONE_PURGED](#); SQLSTATE: [HY000](#)
Message: This member will start distributed recovery using clone. It is due to no ONLINE member has the missing data for recovering in its binary logs.
 - Error number: [MY-013471](#); Symbol: [ER_GRP_RPL_RECOVERY_STRAT_CHOICE](#); SQLSTATE: [HY000](#)
Message: Distributed recovery will transfer data using: %s
 - Error number: [MY-013472](#); Symbol: [ER_GRP_RPL_RECOVERY_STRAT_FALLBACK](#); SQLSTATE: [HY000](#)
Message: Due to some issue on the previous step distributed recovery is now executing: %s
 - Error number: [MY-013473](#); Symbol: [ER_GRP_RPL_RECOVERY_STRAT_NO_FALLBACK](#); SQLSTATE: [HY000](#)

Message: Due to a critical cloning error or lack of donors, distributed recovery cannot be executed. The member will now leave the group.

- Error number: [MY-013474](#); Symbol: [ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_CLONE](#); SQLSTATE: [HY000](#)

Message: The '%s' thread of channel '%s' will error out as the server will attempt to clone another server

- Error number: [MY-013475](#); Symbol: [ER_UNKNOWN_TABLE_IN_UPGRADE](#); SQLSTATE: [HY000](#)

Message: Unknown table '%s'

- Error number: [MY-013476](#); Symbol: [ER_IDENT_CAUSES_TOO_LONG_PATH_IN_UPGRADE](#); SQLSTATE: [HY000](#)

Message: Long database name and identifier for object resulted in path length exceeding %d characters. Path: '%s'.

- Error number: [MY-013477](#); Symbol: [ER_XA_CANT_CREATE_MDL_BACKUP](#); SQLSTATE: [HY000](#)

Message: XA: Failed to take MDL Lock backup of PREPARED XA transaction during client disconnect.

- Error number: [MY-013478](#); Symbol: [ER_AUDIT_LOG_SUPER_PRIVILEGE_REQUIRED](#); SQLSTATE: [HY000](#)

Message: SUPER privilege or AUDIT_ADMIN role required for '%s'@'%s' user.

- Error number: [MY-013479](#); Symbol: [ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_TYPE](#); SQLSTATE: [HY000](#)

Message: Invalid argument type

- Error number: [MY-013480](#); Symbol: [ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_COUNT](#); SQLSTATE: [HY000](#)

Message: Invalid argument count

- Error number: [MY-013481](#); Symbol: [ER_AUDIT_LOG_HAS_NOT_BEEN_INSTALLED](#); SQLSTATE: [HY000](#)

Message: audit_log plugin has not been installed using INSTALL PLUGIN syntax.

- Error number: [MY-013482](#); Symbol: [ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH_ARG_TYPE](#); SQLSTATE: [HY000](#)

Message: Invalid "max_array_length" argument type.

- Error number: [MY-013483](#); Symbol: [ER_LOG_CANNOT_WRITE_EXTENDED](#); SQLSTATE: [HY000](#)

Message: Failed to write to %s: %s (%s)

- Error number: [MY-013485](#); Symbol: [ER_KEYRING_AWS_INCORRECT_PROXY](#); SQLSTATE: [HY000](#)

Message: Incorrect environment variable %s, invalid port: %s

- Error number: [MY-013486](#); Symbol: [ER_GRP_RPL_SERVER_SET_TO_OFFLINE_MODE_DUE_TO_ERRORS](#); SQLSTATE: [HY000](#)

Message: The server was automatically set into offline mode after an error was detected.

- Error number: `MY-013487`; Symbol: `ER_GRP_RPL_MESSAGE_SERVICE_FATAL_ERROR`; SQLSTATE: `HY000`

Message: A message sent through the Group Replication message deliver service was not delivered successfully. The server will now leave the group. Try to add the server back to the group and check if the problem persists, or check previous messages in the log for hints of what could be the problem.

- Error number: `MY-013488`; Symbol: `ER_WARN_WRONG_COMPRESSION_ALGORITHM_LOG`; SQLSTATE: `HY000`

Message: Invalid `SOURCE_COMPRESSION_ALGORITHMS` '%s' found in repository for channel '%s'. Resetting to 'uncompressed' (no compression).

- Error number: `MY-013489`; Symbol: `ER_WARN_WRONG_COMPRESSION_LEVEL_LOG`; SQLSTATE: `HY000`

Message: Invalid `SOURCE_ZSTD_COMPRESSION_LEVEL` found in repository for channel '%s'. Resetting to %u.

- Error number: `MY-013490`; Symbol: `ER_PROTOCOL_COMPRESSION_RESET_LOG`; SQLSTATE: `HY000`

Message: Option `--protocol-compression-algorithms` is reset to default value.

- Error number: `MY-013491`; Symbol: `ER_XPLUGIN_COMPRESSION_ERROR`; SQLSTATE: `HY000`

Message: Fatal error while compressing outgoing data - %s

- Error number: `MY-013492`; Symbol: `ER_MYSQLBACKUP_MSG`; SQLSTATE: `HY000`

Message: %s

- Error number: `MY-013493`; Symbol: `ER_WARN_UNKNOWN_KEYRING_AWS_REGION`; SQLSTATE: `HY000`

Message: Unknown keyring_aws_region '%s'. Connection to AWS KMS may fail.

- Error number: `MY-013494`; Symbol: `ER_WARN_LOG_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST`; SQLSTATE: `HY000`

Message: `PRIVILEGE_CHECKS_USER` for replication channel '%s' was set to ``%s`@`%s``, but this is not an existing user. Correct this before starting replication threads.

- Error number: `MY-013495`; Symbol: `ER_WARN_LOG_PRIVILEGE_CHECKS_USER_CORRUPT`; SQLSTATE: `HY000`

Message: Invalid, corrupted `PRIVILEGE_CHECKS_USER` was found in the replication configuration repository for channel '%s'. Use `CHANGE REPLICATION SOURCE TO PRIVILEGE_CHECKS_USER` to correct the configuration.

- Error number: `MY-013496`; Symbol: `ER_WARN_LOG_PRIVILEGE_CHECKS_USER_NEEDS_RPL_APPLIER_PRIV`; SQLSTATE: `HY000`

Message: `PRIVILEGE_CHECKS_USER` for replication channel '%s' was set to ``%s`@`%s``, but this user does not have `REPLICATION_APPLIER` privilege. Correct this before starting the replication threads.

- Error number: `MY-013497`; Symbol: `ER_OBSOLETE_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS`; SQLSTATE: `HY000`

Message: The PRIVILEGE_CHECKS_USER for channel '%s' would need FILE privilege to execute a LOAD DATA INFILE statement replicated in statement format. Consider using binlog_format=ROW on source. If the replicated events are trusted, recover from the failure by temporarily granting FILE to the PRIVILEGE_CHECKS_USER.

- Error number: MY-013498; Symbol:

[ER_RPL_REPLICA_SQL_THREAD_STARTING_WITH_PRIVILEGE_CHECKS](#); SQLSTATE: HY000

Message: Replica SQL thread%s initialized, starting replication in log '%s' at position %s, relay log '%s' position: %s, user: '%s'@'%s', roles: %s

- Error number: MY-013499; Symbol: [ER_AUDIT_LOG_CANNOT_GENERATE_PASSWORD](#); SQLSTATE: HY000

Message: Cannot generate password: '%s'

- Error number: MY-013500; Symbol: [ER_INIT_FAILED_TO_GENERATE_ROOT_PASSWORD](#); SQLSTATE: HY000

Message: Failed to generate a random password for root. Probabably not enough entrophy.

- Error number: MY-013501; Symbol: [ER_PLUGIN_LOAD_OPTIONS_IGNORED](#); SQLSTATE: HY000

Message: Ignoring --plugin-load[_add] list as the server is running with --initialize(-insecure).

- Error number: MY-013502; Symbol:

[ER_WARN_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLES](#); SQLSTATE: HY000

Message: Cannot set mandatory_roles: AuthId `'%s'`@`'%s'` has '%s' privilege. AuthId(s) set in the mandatory_roles are ignored.

- Error number: MY-013503; Symbol: [ER_IB_MSG_SKIP_HIDDEN_DIR](#); SQLSTATE: HY000

Message: Directory '%s' will not be scanned because it is a hidden directory.

- Error number: MY-013504; Symbol:

[ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SOURCE_EOF](#); SQLSTATE: HY000

Message: Server was not able to find a rotate event from source server to initialize relay log recovery for channel '%s'. Skipping relay log recovery for the channel.

- Error number: MY-013505; Symbol: [ER_IB_LOB_ROLLBACK_INDEX_LEN](#); SQLSTATE: HY000

Message: Rolling back LOB for transaction %llu undo number %llu : current index length %llu. (iteration %llu)

- Error number: MY-013506; Symbol:

[ER_CANT_PROCESS_EXPRESSION_FOR_GENERATED_COLUMN_TO_DD](#); SQLSTATE: HY000

Message: Error in processing (possibly deprecated) expression or function '%s' for generated column %s.%s.%s

- Error number: MY-013507; Symbol:

[ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_NON_ROW_FORMAT](#); SQLSTATE: HY000

Message: The queue event failed for channel '%s' as an invalid event according to REQUIRE_ROW_FORMAT was found.

-
- Error number: [MY-013508](#); Symbol: [ER_OBSOLETE_REQUIRE_ROW_FORMAT_VIOLATION](#); SQLSTATE: [HY000](#)

Message: The application of relay events failed for channel '%s' as an invalid event according to REQUIRE_ROW_FORMAT was found.
 - Error number: [MY-013509](#); Symbol: [ER_LOG_PRIV_CHECKS_REQUIRE_ROW_FORMAT_NOT_SET](#); SQLSTATE: [HY000](#)

Message: PRIVILEGE_CHECKS_USER for replication channel '%s' can't be set to `%s`@`%s` unless REQUIRE_ROW_FORMAT is also set to %d.
 - Error number: [MY-013510](#); Symbol: [ER_RPL_REPLICA_SQL_THREAD_DETECTED_UNEXPECTED_EVENT_SEQUENCE](#); SQLSTATE: [HY000](#)

Message: An unexpected event sequence was detected by the SQL thread while applying an event.
 - Error number: [MY-013511](#); Symbol: [ER_IB_MSG_UPGRADE_PARTITION_FILE](#); SQLSTATE: [HY000](#)

Message: Updating partition file name '%s' to '%s' and all other partition files during upgrade
 - Error number: [MY-013512](#); Symbol: [ER_IB_MSG_DOWNGRADE_PARTITION_FILE](#); SQLSTATE: [HY000](#)

Message: Updating partition file name '%s' to '%s' and all other partition files during downgrade
 - Error number: [MY-013513](#); Symbol: [ER_IB_MSG_UPGRADE_PARTITION_FILE_IMPORT](#); SQLSTATE: [HY000](#)

Message: Updating partition file name '%s' to '%s' for import
 - Error number: [MY-013514](#); Symbol: [ER_IB_WARN_OPEN_PARTITION_FILE](#); SQLSTATE: [HY000](#)

Message: Unable to open partition file with new name '%s'. Please check if innodb_directories is set to include all external file paths
 - Error number: [MY-013515](#); Symbol: [ER_IB_MSG_FIL_STATE_MOVED_CORRECTED](#); SQLSTATE: [HY000](#)

Message: %s DD ID: %llu - Partition tablespace %u, name '%s' is corrected to '%s'
 - Error number: [MY-013516](#); Symbol: [ER_IB_MSG_FIL_STATE_MOVED_CHANGED_PATH](#); SQLSTATE: [HY000](#)

Message: %s DD ID: %llu - Tablespace %u, name '%s', '%s' is moved to '%s'
 - Error number: [MY-013517](#); Symbol: [ER_IB_MSG_FIL_STATE_MOVED_CHANGED_NAME](#); SQLSTATE: [HY000](#)

Message: %s DD ID: %llu - Partition tablespace %u, name '%s', '%s' is updated to '%s'
 - Error number: [MY-013518](#); Symbol: [ER_IB_MSG_FIL_STATE_MOVED_TOO_MANY](#); SQLSTATE: [HY000](#)

Message: %s Too many files have been moved, disabling logging of detailed messages
 - Error number: [MY-013519](#); Symbol: [ER_GR_ELECTED_PRIMARY_GTID_INFORMATION](#); SQLSTATE: [HY000](#)

Message: Elected primary member %s: %s
-

-
- Error number: [MY-013520](#); Symbol: [ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED](#); SQLSTATE: [HY000](#)
Message: Schema name '%s' containing upper case characters is not allowed with lower_case_table_names = 1.
 - Error number: [MY-013521](#); Symbol: [ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED](#); SQLSTATE: [HY000](#)
Message: Table name '%s.%s' containing upper case characters is not allowed with lower_case_table_names = 1.
 - Error number: [MY-013522](#); Symbol: [ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_FK](#); SQLSTATE: [HY000](#)
Message: Schema name '%s' containing upper case characters, used by foreign key '%s' in table '%s.%s', is not allowed with lower_case_table_names = 1.
 - Error number: [MY-013523](#); Symbol: [ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_FK](#); SQLSTATE: [HY000](#)
Message: Table name '%s.%s' containing upper case characters, used by foreign key '%s' in table '%s.%s', is not allowed with lower_case_table_names = 1.
 - Error number: [MY-013524](#); Symbol: [ER_IB_MSG_DICT_PARTITION_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: Table Partition: %s is not found in InnoDB dictionary
 - Error number: [MY-013525](#); Symbol: [ER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED_BY_PASSWORD_LOCK](#); SQLSTATE: [HY000](#)
Message: Access denied for user '%s'@'%s'. Account is blocked for %s day(s) (%s day(s) remaining) due to %u consecutive failed logins. Use FLUSH PRIVILEGES or ALTER USER to reset.
 - Error number: [MY-013526](#); Symbol: [ER_INNO_DB_OUT_OF_RESOURCES](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013528](#); Symbol: [ER_MIGRATE_TABLE_TO_DD_OOM](#); SQLSTATE: [HY000](#)
Message: Could not allocate memory for key_info when migrating table %s.%s
 - Error number: [MY-013529](#); Symbol: [ER_RPL_RELAY_LOG_RECOVERY_INFO_AFTER_CLONE](#); SQLSTATE: [HY000](#)
Message: Applier metadata information for channel '%s' was found after a clone operation. Relay log recovery will be executed to adjust positions and file information for this new server. Should that automatic procedure fail please adjust the positions through 'CHANGE REPLICATION SOURCE TO'
 - Error number: [MY-013530](#); Symbol: [ER_IB_MSG_57_UNDO_SPACE_DELETE_FAIL](#); SQLSTATE: [HY000](#)
Message: Failed to delete 5.7 undo tablespace: %s during upgrade
 - Error number: [MY-013531](#); Symbol: [ER_IB_MSG_DBLWR_1285](#); SQLSTATE: [HY000](#)
Message: Empty doublewrite file: %s
 - Error number: [MY-013532](#); Symbol: [ER_IB_MSG_DBLWR_1286](#); SQLSTATE: [HY000](#)

Message: Using '%s' for doublewrite

- Error number: [MY-013533](#); Symbol: [ER_IB_MSG_DBLWR_1287](#); SQLSTATE: [HY000](#)

Message: Error reading doublewrite buffer from the system tablespace

- Error number: [MY-013534](#); Symbol: [ER_IB_MSG_DBLWR_1288](#); SQLSTATE: [HY000](#)

Message: Cannot create doublewrite buffer: you must increase your buffer pool size. Cannot continue operation.

- Error number: [MY-013535](#); Symbol: [ER_IB_MSG_DBLWR_1290](#); SQLSTATE: [HY000](#)

Message: The page in the doublewrite file is corrupt. Cannot continue operation. You can try to recover the database with innodb_force_recovery=6

- Error number: [MY-013536](#); Symbol: [ER_IB_MSG_BAD_DBLWR_FILE_NAME](#); SQLSTATE: [HY000](#)

Message: The doublewrite filename '%s' is incorrect.

- Error number: [MY-013538](#); Symbol: [ER_IB_MSG_DBLWR_1293](#); SQLSTATE: [HY000](#)

Message: Doublewrite file create failed: %s

- Error number: [MY-013539](#); Symbol: [ER_IB_MSG_DBLWR_1294](#); SQLSTATE: [HY000](#)

Message: DBLWRThread: pthread_setaffinity() failed!

- Error number: [MY-013540](#); Symbol: [ER_IB_MSG_DBLWR_1295](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013541](#); Symbol: [ER_IB_MSG_DBLWR_1296](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013542](#); Symbol: [ER_IB_MSG_DBLWR_1297](#); SQLSTATE: [HY000](#)

Message: Doublewrite file read failed: %s

- Error number: [MY-013543](#); Symbol: [ER_IB_MSG_DBLWR_1298](#); SQLSTATE: [HY000](#)

Message: Dump of the data file page:

- Error number: [MY-013544](#); Symbol: [ER_IB_MSG_DBLWR_1300](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013545](#); Symbol: [ER_IB_MSG_DBLWR_1301](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013546](#); Symbol: [ER_IB_MSG_DBLWR_1304](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013547](#); Symbol: [ER_IB_MSG_DBLWR_1305](#); SQLSTATE: [HY000](#)

Message: %s

-
- Error number: [MY-013548](#); Symbol: [ER_IB_MSG_DBLWR_1306](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013549](#); Symbol: [ER_IB_MSG_DBLWR_1307](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013550](#); Symbol: [ER_IB_MSG_DBLWR_1308](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013551](#); Symbol: [ER_IB_MSG_DBLWR_1309](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013552](#); Symbol: [ER_IB_MSG_DBLWR_1310](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013553](#); Symbol: [ER_IB_MSG_DBLWR_1311](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013554](#); Symbol: [ER_IB_MSG_DBLWR_1312](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013555](#); Symbol: [ER_IB_MSG_DBLWR_1313](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013556](#); Symbol: [ER_IB_MSG_DBLWR_1314](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013557](#); Symbol: [ER_IB_MSG_DBLWR_1315](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013558](#); Symbol: [ER_IB_MSG_DBLWR_1316](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013559](#); Symbol: [ER_IB_MSG_DBLWR_1317](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013560](#); Symbol: [ER_IB_MSG_DBLWR_1318](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013561](#); Symbol: [ER_IB_MSG_DBLWR_LOAD_WRONG_SIZE](#); SQLSTATE: [HY000](#)
Message: Doublewrite load file %s size %llu is not a multiple of the configured page size %zu
 - Error number: [MY-013562](#); Symbol: [ER_IB_MSG_DBLWR_1320](#); SQLSTATE: [HY000](#)
Message: Doublewrite file %s truncate failed
 - Error number: [MY-013563](#); Symbol: [ER_IB_MSG_DBLWR_1321](#); SQLSTATE: [HY000](#)

Message: Doublewrite file %s failed to writ zeros

- Error number: [MY-013564](#); Symbol: [ER_IB_MSG_DBLWR_OPEN_OR_CREATE_WRONG_SIZE](#); SQLSTATE: [HY000](#)

Message: Doublewrite open or create file %s size %llu is not a multiple of the configured page size %zu

- Error number: [MY-013565](#); Symbol: [ER_IB_MSG_DBLWR_1323](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013566](#); Symbol: [ER_IB_MSG_DBLWR_1324](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013567](#); Symbol: [ER_IB_MSG_DBLWR_1325](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013568](#); Symbol: [ER_IB_MSG_DBLWR_1326](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013569](#); Symbol: [ER_IB_MSG_DBLWR_1327](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013570](#); Symbol: [ER_IB_MSG_GTID_FLUSH_AT_SHUTDOWN](#); SQLSTATE: [HY000](#)

Message: Could not flush all GTIDs during slow shutdown. Will recover GTIDs when server restarts.

- Error number: [MY-013571](#); Symbol: [ER_IB_MSG_57_STAT_SPACE_DELETE_FAIL](#); SQLSTATE: [HY000](#)

Message: Failed to delete 5.7 stat tablespace: %s during upgrade

- Error number: [MY-013572](#); Symbol: [ER_NDBINFO_UPGRADING_SCHEMA](#); SQLSTATE: [HY000](#)

Message: Installing ndbinfo schema version %s

- Error number: [MY-013573](#); Symbol: [ER_NDBINFO_NOT_UPGRADING_SCHEMA](#); SQLSTATE: [HY000](#)

Message: Installed ndbinfo schema is current. Not upgrading.

- Error number: [MY-013574](#); Symbol: [ER_NDBINFO_UPGRADING_SCHEMA_FAIL](#); SQLSTATE: [HY000](#)

Message: Failed to upgrade ndbinfo schema.

- Error number: [MY-013576](#); Symbol: [ER_IB_MSG_INNODB_START_INITIALIZE](#); SQLSTATE: [HY000](#)

Message: InnoDB initialization has started.

- Error number: [MY-013577](#); Symbol: [ER_IB_MSG_INNODB_END_INITIALIZE](#); SQLSTATE: [HY000](#)

Message: InnoDB initialization has ended.

- Error number: [MY-013578](#); Symbol: [ER_IB_MSG_PAGE_ARCH_NO_RESET_POINTS](#); SQLSTATE: [HY000](#)

Message: Could not find appropriate reset points.

-
- Error number: [MY-013579](#); Symbol: [ER_IB_WRN_PAGE_ARCH_FLUSH_DATA](#); SQLSTATE: [HY000](#)
Message: Unable to flush. Page archiving data may be corrupt in case of a crash.
 - Error number: [MY-013580](#); Symbol: [ER_IB_ERR_PAGE_ARCH_INVALID_DOUBLE_WRITE_BUF](#); SQLSTATE: [HY000](#)
Message: Page archiver's doublewrite buffer for %ld is not valid.
 - Error number: [MY-013581](#); Symbol: [ER_IB_ERR_PAGE_ARCH_RECOVERY_FAILED](#); SQLSTATE: [HY000](#)
Message: Page archiver system's recovery failed.
 - Error number: [MY-013582](#); Symbol: [ER_IB_ERR_PAGE_ARCH_INVALID_FORMAT](#); SQLSTATE: [HY000](#)
Message: Invalid archived file name format. The archived file is supposed to have the format %s + [0-9]*.
 - Error number: [MY-013583](#); Symbol: [ER_INVALID_XPLUGIN_SOCKET_SAME_AS_SERVER](#); SQLSTATE: [HY000](#)
Message: X Plugins UNIX socket must use different file than MySQL server. X Plugin won't be accessible through UNIX socket
 - Error number: [MY-013584](#); Symbol: [ER_INNOODB_UNABLE_TO_ACQUIRE_DD_OBJECT](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013586](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_TOO_OFTEN](#); SQLSTATE: [HY000](#)
Message: Undo Truncation is occurring too often. Consider increasing --innodb-max-undo-log-size.
 - Error number: [MY-013587](#); Symbol: [ER_GRP_RPL_IS_STARTING](#); SQLSTATE: [HY000](#)
Message: Plugin 'group_replication' is starting.
 - Error number: [MY-013588](#); Symbol: [ER_IB_MSG_INVALID_LOCATION_FOR_TABLESPACE](#); SQLSTATE: [HY000](#)
Message: Cannot create tablespace %s because the directory is not a valid location. %s
 - Error number: [MY-013589](#); Symbol: [ER_IB_MSG_INVALID_LOCATION_WRONG_DB](#); SQLSTATE: [HY000](#)
Message: Scanned file '%s' for tablespace %s cannot be opened because it is not in a sub-directory named for the schema.
 - Error number: [MY-013590](#); Symbol: [ER_IB_MSG_CANNOT_FIND_DD_UNDO_SPACE](#); SQLSTATE: [HY000](#)
Message: Cannot find undo tablespace %s with filename '%s' as indicated by the Data Dictionary. Did you move or delete this tablespace? Any undo logs in it cannot be used.
 - Error number: [MY-013591](#); Symbol: [ER_GRP_RPL_RECOVERY_ENDPOINT_FORMAT](#); SQLSTATE: [HY000](#)
Message: Invalid input value for recovery socket endpoints '%s'. Please, provide a valid, comma separated, list of endpoints (IP:port).

-
- Error number: [MY-013592](#); Symbol: [ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID](#); SQLSTATE: [HY000](#)

Message: The server is not listening on endpoint '%s'. Only endpoints that the server is listening on are valid recovery endpoints.
 - Error number: [MY-013593](#); Symbol: [ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID_DONOR_ENDPOINT](#); SQLSTATE: [HY000](#)

Message: Received invalid recovery endpoints configuration from donor. This member is not a valid donor for recovery, so it will be skipped.
 - Error number: [MY-013594](#); Symbol: [ER_GRP_RPL_RECOVERY_ENDPOINT_INTERFACES_IPS](#); SQLSTATE: [HY000](#)

Message: Failed to retrieve IP addresses from enabled host network interfaces.
 - Error number: [MY-013595](#); Symbol: [ER_WARN_TLS_CHANNEL_INITIALIZATION_ERROR](#); SQLSTATE: [HY000](#)

Message: Failed to initialize TLS for channel: %s. See below for the description of exact issue.
 - Error number: [MY-013596](#); Symbol: [ER_XPLUGIN_FAILED_TO_VALIDATE_ADDRESS](#); SQLSTATE: [HY000](#)

Message: Validation of value '%s' set to `Mysqlx_bind_address` failed: %s. Skipping this value.
 - Error number: [MY-013597](#); Symbol: [ER_XPLUGIN_FAILED_TO_BIND_INTERFACE_ADDRESS](#); SQLSTATE: [HY000](#)

Message: Value '%s' set to `Mysqlx_bind_address`, X Plugin can't bind to it. Skipping this value.
 - Error number: [MY-013598](#); Symbol: [ER_IB_ERR_RECOVERY_REDO_DISABLED](#); SQLSTATE: [HY000](#)

Message: Server was killed when InnoDB redo logging was disabled. Data files could be corrupt. You can try to restart the database with `innodb_force_recovery=6`
 - Error number: [MY-013599](#); Symbol: [ER_IB_WRN_FAST_SHUTDOWN_REDO_DISABLED](#); SQLSTATE: [HY000](#)

Message: InnoDB cannot do cold shutdown 'innodb_fast_shutdown = 2' and is forcing 'innodb_fast_shutdown = 1' as redo logging is disabled. InnoDB would flush all dirty pages to ensure physical data consistency.
 - Error number: [MY-013600](#); Symbol: [ER_IB_WRN_REDO_DISABLED](#); SQLSTATE: [HY000](#)

Message: InnoDB redo logging is disabled. All data could be lost in case of a server crash.
 - Error number: [MY-013601](#); Symbol: [ER_IB_WRN_REDO_ENABLED](#); SQLSTATE: [HY000](#)

Message: InnoDB redo logging is enabled. Data is now safe and can be recovered in case of a server crash.
 - Error number: [MY-013602](#); Symbol: [ER_TLS_CONFIGURED_FOR_CHANNEL](#); SQLSTATE: [HY000](#)

Message: Channel %s configured to support TLS. Encrypted connections are now supported for this channel.
 - Error number: [MY-013603](#); Symbol: [ER_TLS_CONFIGURATION_REUSED](#); SQLSTATE: [HY000](#)

Message: No TLS configuration was given for channel %s; re-using TLS configuration of channel %s.

- Error number: `MY-013604`; Symbol: `ER_IB_TABLESPACE_PATH_VALIDATION_SKIPPED`; SQLSTATE: `HY000`

Message: Skipping InnoDB tablespace path validation. Manually moved tablespace files will not be detected!

- Error number: `MY-013605`; Symbol: `ER_IB_CANNOT_UPGRADE_WITH_DISCARDED_TABLESPACES`; SQLSTATE: `HY000`

Message: Upgrade failed because database contains discarded tablespaces.

- Error number: `MY-013606`; Symbol: `ER_USERNAME_TRUNCATED`; SQLSTATE: `HY000`

Message: The user name '%s' exceeds the maximum number of allowed characters %d and is truncated.

- Error number: `MY-013607`; Symbol: `ER_HOSTNAME_TRUNCATED`; SQLSTATE: `HY000`

Message: The host name '%s' exceeds the maximum number of allowed characters %d and is truncated.

- Error number: `MY-013608`; Symbol: `ER_IB_MSG_TRX_RECOVERY_ROLLBACK_NOT_COMPLETED`; SQLSTATE: `HY000`

Message: Rollback of non-prepared transactions not completed, due to fast shutdown

- Error number: `MY-013609`; Symbol: `ER_AUTHCACHE_ROLE_EDGES_IGNORED_EMPTY_NAME`; SQLSTATE: `HY000`

Message: Found an entry in the 'role_edges' table with empty authorization ID; Skipped

- Error number: `MY-013610`; Symbol: `ER_AUTHCACHE_ROLE_EDGES_UNKNOWN_AUTHORIZATION_ID`; SQLSTATE: `HY000`

Message: Found an entry in the 'role_edges' table with unknown authorization ID '%s'; Skipped

- Error number: `MY-013611`; Symbol: `ER_AUTHCACHE_DEFAULT_ROLES_IGNORED_EMPTY_NAME`; SQLSTATE: `HY000`

Message: Found an entry in the 'default_roles' table with empty authorization ID; Skipped

- Error number: `MY-013612`; Symbol: `ER_AUTHCACHE_DEFAULT_ROLES_UNKNOWN_AUTHORIZATION_ID`; SQLSTATE: `HY000`

Message: Found an entry in the 'default_roles' table with unknown authorization ID '%s'; Skipped

- Error number: `MY-013613`; Symbol: `ER_IB_ERR_DDL_LOG_INSERT_FAILURE`; SQLSTATE: `HY000`

Message: Couldn't insert entry in ddl log for ddl.

- Error number: `MY-013614`; Symbol: `ER_IB_LOCK_VALIDATE_LATCH_ORDER_VIOLATION`; SQLSTATE: `HY000`

Message: %s

- Error number: `MY-013615`; Symbol: `ER_IB_RELOCK_LATCH_ORDER_VIOLATION`; SQLSTATE: `HY000`

Message: %s

- Error number: `MY-013621`; Symbol: `ER_IB_MSG_1357`; SQLSTATE: `HY000`

Message: %s

- Error number: `MY-013622`; Symbol: `ER_IB_MSG_1358`; SQLSTATE: `HY000`

Message: %s

- Error number: `MY-013623`; Symbol: `ER_IB_MSG_1359`; SQLSTATE: `HY000`

Message: %s

- Error number: `MY-013624`; Symbol: `ER_IB_FAILED_TO_DELETE_TABLESPACE_FILE`; SQLSTATE: `HY000`

Message: %s

- Error number: `MY-013625`; Symbol: `ER_IB_UNABLE_TO_EXPAND_TEMPORARY_TABLESPACE_POOL`; SQLSTATE: `HY000`

Message: %s

- Error number: `MY-013626`; Symbol: `ER_IB_TMP_TABLESPACE_CANNOT_CREATE_DIRECTORY`; SQLSTATE: `HY000`

Message: %s

- Error number: `MY-013627`; Symbol: `ER_IB_MSG_SCANNING_TEMP_TABLESPACE_DIR`; SQLSTATE: `HY000`

Message: %s

- Error number: `MY-013628`; Symbol: `ER_IB_ERR_TEMP_TABLESPACE_DIR_DOESNT_EXIST`; SQLSTATE: `HY000`

Message: %s

- Error number: `MY-013629`; Symbol: `ER_IB_ERR_TEMP_TABLESPACE_DIR_EMPTY`; SQLSTATE: `HY000`

Message: %s

- Error number: `MY-013630`; Symbol: `ER_IB_ERR_TEMP_TABLESPACE_DIR_CONTAINS_SEMICOLON`; SQLSTATE: `HY000`

Message: %s

- Error number: `MY-013631`; Symbol: `ER_IB_ERR_TEMP_TABLESPACE_DIR_SUBDIR_OF_DATADIR`; SQLSTATE: `HY000`

Message: %s

- Error number: `MY-013632`; Symbol: `ER_IB_ERR_SCHED_SETAFFINITY_FAILED`; SQLSTATE: `HY000`

Message: %s

-
- Error number: `MY-013633`; Symbol: `ER_IB_ERR_UNKNOWN_PAGE_FETCH_MODE`; `SQLSTATE: HY000`
Message: %s
 - Error number: `MY-013634`; Symbol: `ER_IB_ERR_LOG_PARSING_BUFFER_OVERFLOW`; `SQLSTATE: HY000`
Message: %s
 - Error number: `MY-013635`; Symbol: `ER_IB_ERR_NOT_ENOUGH_MEMORY_FOR_PARSE_BUFFER`; `SQLSTATE: HY000`
Message: %s
 - Error number: `MY-013636`; Symbol: `ER_IB_MSG_1372`; `SQLSTATE: HY000`
Message: %s
 - Error number: `MY-013637`; Symbol: `ER_IB_MSG_1373`; `SQLSTATE: HY000`
Message: %s
 - Error number: `MY-013638`; Symbol: `ER_IB_MSG_1374`; `SQLSTATE: HY000`
Message: %s
 - Error number: `MY-013639`; Symbol: `ER_IB_MSG_1375`; `SQLSTATE: HY000`
Message: %s
 - Error number: `MY-013640`; Symbol: `ER_IB_ERR_ZLIB_UNCOMPRESS_FAILED`; `SQLSTATE: HY000`
Message: %s
 - Error number: `MY-013641`; Symbol: `ER_IB_ERR_ZLIB_BUF_ERROR`; `SQLSTATE: HY000`
Message: %s
 - Error number: `MY-013642`; Symbol: `ER_IB_ERR_ZLIB_MEM_ERROR`; `SQLSTATE: HY000`
Message: %s
 - Error number: `MY-013643`; Symbol: `ER_IB_ERR_ZLIB_DATA_ERROR`; `SQLSTATE: HY000`
Message: %s
 - Error number: `MY-013644`; Symbol: `ER_IB_ERR_ZLIB_UNKNOWN_ERROR`; `SQLSTATE: HY000`
Message: %s
 - Error number: `MY-013645`; Symbol: `ER_IB_MSG_1381`; `SQLSTATE: HY000`
Message: %s
 - Error number: `MY-013646`; Symbol: `ER_IB_ERR_INDEX_RECORDS_WRONG_ORDER`; `SQLSTATE: HY000`
Message: %s
 - Error number: `MY-013647`; Symbol: `ER_IB_ERR_INDEX_DUPLICATE_KEY`; `SQLSTATE: HY000`

Message: %s

- Error number: [MY-013648](#); Symbol: [ER_IB_ERR_FOUND_N_DUPLICATE_KEYS](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013649](#); Symbol: [ER_IB_ERR_FOUND_N_RECORDS_WRONG_ORDER](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013650](#); Symbol: [ER_IB_ERR_PARALLEL_READ_OOM](#); SQLSTATE: [HY000](#)

Message: %s

- Error number: [MY-013651](#); Symbol: [ER_IB_MSG_UNDO_MARKED_ACTIVE](#); SQLSTATE: [HY000](#)

Message: The state of undo tablespace %s is set to active implicitly.

- Error number: [MY-013652](#); Symbol: [ER_IB_MSG_UNDO_ALTERED_ACTIVE](#); SQLSTATE: [HY000](#)

Message: The state of undo tablespace %s is set to 'active' by ALTER TABLESPACE.

- Error number: [MY-013653](#); Symbol: [ER_IB_MSG_UNDO_ALTERED_INACTIVE](#); SQLSTATE: [HY000](#)

Message: The state of undo tablespace %s is set to 'inactive' by ALTER TABLESPACE.

- Error number: [MY-013654](#); Symbol: [ER_IB_MSG_UNDO_MARKED_EMPTY](#); SQLSTATE: [HY000](#)

Message: The state of undo tablespace %s is set to 'empty'.

- Error number: [MY-013655](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_CLONE](#); SQLSTATE: [HY000](#)

Message: Delaying truncate of undo tablespace %s due to clone activity.

- Error number: [MY-013656](#); Symbol: [ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_MDL](#); SQLSTATE: [HY000](#)

Message: Delaying truncate of undo tablespace %s due to a metadata lock.

- Error number: [MY-013657](#); Symbol: [ER_IB_MSG_INJECT_CRASH](#); SQLSTATE: [HY000](#)

Message: Injected debug crash point: %s

- Error number: [MY-013658](#); Symbol: [ER_IB_MSG_INJECT_FAILURE](#); SQLSTATE: [HY000](#)

Message: Injected debug failure point: %s

- Error number: [MY-013659](#); Symbol: [ER_GRP_RPL_TIMEOUT_RECEIVED_VC_LEAVE_ON_REJOIN](#); SQLSTATE: [HY000](#)

Message: Timeout while waiting for a view change event during the leave step before a auto-rejoin attempt.

-
- Error number: `MY-013660`; Symbol: `ER_RPL_ASYNC_RECONNECT_FAIL_NO_SOURCE`; SQLSTATE: `HY000`
Message: Failed to automatically re-connect to a different source, for channel '%s', because %s. To fix this %s.
 - Error number: `MY-013661`; Symbol: `ER_UDF_REGISTER_SERVICE_ERROR`; SQLSTATE: `HY000`
Message: Could not execute the installation of UDF functions. Check for other errors in the log
 - Error number: `MY-013662`; Symbol: `ER_UDF_REGISTER_ERROR`; SQLSTATE: `HY000`
Message: Could not execute the installation of UDF function: %s. Check if the function is already present, if so, try to remove it.
 - Error number: `MY-013663`; Symbol: `ER_UDF_UNREGISTER_ERROR`; SQLSTATE: `HY000`
Message: Could not uninstall UDF functions. Try to remove them manually if present.
 - Error number: `MY-013664`; Symbol: `ER_EMPTY_PRIVILEGE_NAME_IGNORED`; SQLSTATE: `HY000`
Message: An empty or illegal privilege identifier was ignored when global privileges were read from disk.
 - Error number: `MY-013665`; Symbol: `ER_IB_MSG_INCORRECT_SIZE`; SQLSTATE: `HY000`
Message: %s
 - Error number: `MY-013666`; Symbol: `ER_TMPDIR_PATH_TOO_LONG`; SQLSTATE: `HY000`
Message: A tmpdir temporary path "%s" is too long (> %zu) for this OS. This would not leave enough space for a temporary filename of length %zu within it.
 - Error number: `MY-013667`; Symbol: `ER_ERROR_LOG_DESTINATION_NOT_A_FILE`; SQLSTATE: `HY000`
Message: Error-log destination "%s" is not a file. Can not restore error log messages from previous run.
 - Error number: `MY-013668`; Symbol: `ER_NO_ERROR_LOG_PARSER_CONFIGURED`; SQLSTATE: `HY000`
Message: None of the log-sinks selected with --log-error-services=... provides a log-parser. The server will not be able to make the previous runs' error-logs available in performance_schema.error_log.
 - Error number: `MY-013669`; Symbol: `ER_UPGRADE_NONEXISTENT_SCHEMA`; SQLSTATE: `HY000`
Message: The schema "%s" referenced by %s "%s" does not exist. Please clean up any orphan %s before upgrading.
 - Error number: `MY-013670`; Symbol: `ER_IB_MSG_CREATED_UNDO_SPACE`; SQLSTATE: `HY000`
Message: Created undo tablespace '%s'.
 - Error number: `MY-013671`; Symbol: `ER_IB_MSG_DROPPED_UNDO_SPACE`; SQLSTATE: `HY000`
Message: Dropped undo tablespace '%s'.
 - Error number: `MY-013672`; Symbol: `ER_IB_MSG_MASTER_KEY_ROTATED`; SQLSTATE: `HY000`
Message: The InnoDB Encryption Master Key has been rotated in %d tablespaces.
 - Error number: `MY-013673`; Symbol: `ER_IB_DBLWR_DECOMPRESS_FAILED`; SQLSTATE: `HY000`

Message: Failed to decompress a DBLWR page (err=%d). The original size is %d. Reporting the dblwr page as corrupted.

- Error number: [MY-013674](#); Symbol: [ER_IB_DBLWR_DECRYPT_FAILED](#); SQLSTATE: [HY000](#)

Message: Decrypting a page in doublewrite file failed: %s.

- Error number: [MY-013675](#); Symbol: [ER_IB_DBLWR_KEY_MISSING](#); SQLSTATE: [HY000](#)

Message: Encryption key missing: %s.

- Error number: [MY-013676](#); Symbol: [ER_INNOQB_IO_WRITE_ERROR_RETRYING](#); SQLSTATE: [HY000](#)

Message: I/O error while writing to file: %s. Retrying ...

- Error number: [MY-013677](#); Symbol: [ER_INNOQB_IO_WRITE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to write data to file: %s

- Error number: [MY-013678](#); Symbol: [ER_LOG_COMPONENT_CANNOT_INIT](#); SQLSTATE: [HY000](#)

Message: Log component %s failed to initialize.

- Error number: [MY-013679](#); Symbol: [ER_RPL_ASYNC_CHANNEL_CANT_CONNECT](#); SQLSTATE: [HY000](#)

Message: The Monitor IO thread failed to connect to the source (host:%s port:%u network_namespace:%s) for channel '%s', thence it will try to connect to another source.

- Error number: [MY-013680](#); Symbol: [ER_RPL_ASYNC_SENDER_ADDED](#); SQLSTATE: [HY000](#)

Message: The source (host:%s port:%u network_namespace:%s) for channel '%s' has joined the group (group_name: %s), and so added its entry into replication_asynchronous_connection_failover table.

- Error number: [MY-013681](#); Symbol: [ER_RPL_ASYNC_SENDER_REMOVED](#); SQLSTATE: [HY000](#)

Message: The source (host:%s port:%u network_namespace:%s) for channel '%s' has left the group (group_name: %s), and so removed its entry from replication_asynchronous_connection_failover table.

- Error number: [MY-013682](#); Symbol: [ER_RPL_ASYNC_CHANNEL_STOPPED_QUORUM_LOST](#); SQLSTATE: [HY000](#)

Message: The Monitor IO thread detected that the source (host:%s port:%u network_namespace:%s) does not belong to the group majority, thence the channel '%s' will try to connect to another source.

- Error number: [MY-013683](#); Symbol: [ER_RPL_ASYNC_CHANNEL_CANT_CONNECT_NO_QUORUM](#); SQLSTATE: [HY000](#)

Message: The IO thread detected that the source (host:%s port:%u network_namespace:%s) does not belong to the group majority, thence the channel '%s' will try to connect to another source.

- Error number: [MY-013685](#); Symbol: [ER_RPL_REPLICA_MONITOR_IO_THREAD_EXITING](#); SQLSTATE: [HY000](#)

Message: Replica Monitor IO thread exiting.

-
- Error number: [MY-013686](#); Symbol: [ER_RPL_ASYNC_MANAGED_NAME_REMOVED](#); SQLSTATE: [HY000](#)
Message: The group (group_name: %s) for the channel '%s' has been removed, and so removed its entry from replication_asynchronous_connection_failover_managed and all the group members from replication_asynchronous_connection_failover table.
 - Error number: [MY-013687](#); Symbol: [ER_RPL_ASYNC_MANAGED_NAME_ADDED](#); SQLSTATE: [HY000](#)
Message: The group (group_name: %s) for the channel '%s' has been added, and so added its entry in replication_asynchronous_connection_failover_managed and source to replication_asynchronous_connection_failover table.
 - Error number: [MY-013688](#); Symbol: [ER_RPL_ASYNC_READ_FAILOVER_TABLE](#); SQLSTATE: [HY000](#)
Message: Error reading failover sources for channel '%s' from replication_asynchronous_connection_failover table.
 - Error number: [MY-013689](#); Symbol: [ER_RPL_REPLICA_MONITOR_IO_THREAD_RECONNECT_CHANNEL](#); SQLSTATE: [HY000](#)
Message: Error %s the channel '%s', the operation will be automatically retried.
 - Error number: [MY-013690](#); Symbol: [ER_REPLICA_ANON_TO_GTID_IS_LOCAL_OR_UUID_AND_GTID_MODE_NOT_ON](#); SQLSTATE: [HY000](#)
Message: Replication channel '%s' is configured with ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS='%s', which is invalid when GTID_MODE <> ON. If you intend to use GTID_MODE = ON everywhere, change to ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = OFF and use the procedure for enabling GTIDs online (see the documentation). If you intend to use GTIDs on this replica and cannot enable GTIDs on the source, enable GTID_MODE = ON and leave ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>. If you intend to not use GTIDs at all in the replication topology, change to ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS=OFF and leave GTID_MODE = '%s'.
 - Error number: [MY-013691](#); Symbol: [ER_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NAME](#); SQLSTATE: [HY000](#)
Message: Replication channel '%s' is configured with ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS='%s' which is equal to group_replication_group_name. To fix this issue, either change the group_replication_group_name or use a different value for ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS.
 - Error number: [MY-013692](#); Symbol: [ER_GRP_RPL_GRP_NAME_IS_SAME_AS_ANONYMOUS_TO_GTID_UUID](#); SQLSTATE: [HY000](#)
Message: The group_replication_group_name '%s' is the same as the UUID value for ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS in a server channel
 - Error number: [MY-013693](#); Symbol: [ER_WARN_GTID_THRESHOLD_BREACH](#); SQLSTATE: [HY000](#)
Message: The integer component of the GTID number is high. Suggest restarting the server with a new server_uuid to prevent it from reaching the maximum number 2^63-1, which will make it impossible to write the binary log and invoke the behavior specified by binlog_error_action.
 - Error number: [MY-013694](#); Symbol: [ER_HEALTH_INFO](#); SQLSTATE: [HY000](#)
Message: %s

-
- Error number: [MY-013695](#); Symbol: [ER_HEALTH_WARNING](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013696](#); Symbol: [ER_HEALTH_ERROR](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013697](#); Symbol: [ER_HEALTH_WARNING_DISK_USAGE_LEVEL_1](#); SQLSTATE: [HY000](#)
Message: %s: Warning Level 1 (%llu MiB): mount point = '%s', available = %llu MiB, total = %llu MiB, used = %.2f%%, low limit = %llu MiB, critical level = %llu MiB
 - Error number: [MY-013698](#); Symbol: [ER_HEALTH_WARNING_DISK_USAGE_LEVEL_2](#); SQLSTATE: [HY000](#)
Message: %s: Warning Level 2 (%llu MiB): mount point = '%s', available = %llu MiB, total = %llu MiB, used = %.2f%%, low limit = %llu MiB, critical level = %llu MiB
 - Error number: [MY-013699](#); Symbol: [ER_HEALTH_WARNING_DISK_USAGE_LEVEL_3](#); SQLSTATE: [HY000](#)
Message: %s: Warning Level 3 (%llu MiB): mount point = '%s', available = %llu MiB, total = %llu MiB, used = %.2f%%, low limit = %llu MiB, critical level = %llu MiB
 - Error number: [MY-013700](#); Symbol: [ER_IB_INNODB_TBSP_OUT_OF_SPACE](#); SQLSTATE: [HY000](#)
Message: InnoDB: Size of tablespace %s is more than the maximum size allowed.
 - Error number: [MY-013701](#); Symbol: [ER_GRP_RPL_APPLIER_CHANNEL_STILL_RUNNING](#); SQLSTATE: [HY000](#)
Message: The group_replication_applier channel is still running, most likely it is waiting for a database/table lock, which is preventing the channel from stopping. Please check database/table locks, including the ones created by backup tools.
 - Error number: [MY-013702](#); Symbol: [ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF_CHANNEL](#); SQLSTATE: [HY000](#)
Message: Detected misconfiguration: replication channel '%s' was configured with SOURCE_CONNECTION_AUTO_FAILOVER = 1, but the server was started with a value other than --gtid-mode = ON. Either reconfigure replication using CHANGE REPLICATION SOURCE TO SOURCE_CONNECTION_AUTO_FAILOVER = 0 FOR CHANNEL '%s', or change GTID_MODE to value ON, before starting the replica receiver thread.
 - Error number: [MY-013703](#); Symbol: [ER_FIREWALL_SERVICES_NOT_ACQUIRED](#); SQLSTATE: [HY000](#)
Message: Could not acquire required component services.
 - Error number: [MY-013704](#); Symbol: [ER_FIREWALL_UDF_REGISTER_FAILED](#); SQLSTATE: [HY000](#)
Message: Automatic registration of function(s) failed.
 - Error number: [MY-013705](#); Symbol: [ER_FIREWALL_PFS_TABLE_REGISTER_FAILED](#); SQLSTATE: [HY000](#)
Message: Automatic registration of Performance schema table(s) failed.
-

-
- Error number: [MY-013706](#); Symbol: [ER_IB_MSG_STATS_SAMPLING_TOO_LARGE](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013707](#); Symbol: [ER_AUDIT_LOG_FILE_PRUNE_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to auto-prune file '%s', Error (%d): %s
 - Error number: [MY-013708](#); Symbol: [ER_AUDIT_LOG_FILE_AUTO_PRUNED](#); SQLSTATE: [HY000](#)
Message: File '%s' auto-pruned
 - Error number: [MY-013709](#); Symbol: [ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_INIT](#); SQLSTATE: [HY000](#)
Message: Received an error while processing components from manifest file: %s
 - Error number: [MY-013710](#); Symbol: [ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_DEINIT](#); SQLSTATE: [HY000](#)
Message: Received an error while unloading components read from manifest file: %s
 - Error number: [MY-013711](#); Symbol: [ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_NOT_RO](#); SQLSTATE: [HY000](#)
Message: Manifest file '%s' is not read-only. For better security, please make sure that the file is read-only.
 - Error number: [MY-013712](#); Symbol: [ER_WARN_NO_KEYRING_COMPONENT_SERVICE_FOUND](#); SQLSTATE: [HY000](#)
Message: No suitable '%s' service implementation found to fulfill the request.
 - Error number: [MY-013713](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_INITIALIZED](#); SQLSTATE: [HY000](#)
Message: Keyring component initialized successfully.
 - Error number: [MY-013714](#); Symbol: [ER_KEYRING_COMPONENT_NOT_INITIALIZED](#); SQLSTATE: [HY000](#)
Message: The component is not initialized properly. Error: %s. Make sure that configuration is proper and use ALTER INSTANCE RELOAD KEYRING to reinitialize the component.
 - Error number: [MY-013715](#); Symbol: [ER_KEYRING_COMPONENT_EXCEPTION](#); SQLSTATE: [HY000](#)
Message: Keyring component encountered an exception while executing : '%s' API of service: '%s'
 - Error number: [MY-013716](#); Symbol: [ER_KEYRING_COMPONENT_MEMORY_ALLOCATION_ERROR](#); SQLSTATE: [HY000](#)
Message: Failed to allocated memory for '%s' while executing: '%s' API of service: '%s'
 - Error number: [MY-013717](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_AES_INVALID_MODE_BLOCK_SIZE](#); SQLSTATE: [HY000](#)
Message: Empty or 0 values for AES encryption mode and/or block size are not permitted.
 - Error number: [MY-013718](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_AES_DATA_IDENTIFIER_EMPTY](#); SQLSTATE: [HY000](#)

Message: A valid data identifier is required in order to fetch the key required for the AES operation.

- Error number: [MY-013719](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_AES_INVALID_KEY](#); SQLSTATE: [HY000](#)

Message: Key identified by Data ID: '%s' and Auth ID: '%s' is not of type AES.

- Error number: [MY-013720](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_AES_OPERATION_ERROR](#); SQLSTATE: [HY000](#)

Message: Encountered error: '%s' while executing '%s' API of keyring_aes service. Key details are Data ID: '%s' and Auth ID: '%s'.

- Error number: [MY-013721](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_READ_DATA_NOT_FOUND](#); SQLSTATE: [HY000](#)

Message: Could not find the data corresponding to Data ID: '%s', Auth ID: '%s'.

- Error number: [MY-013722](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_WRITE_MAXIMUM_DATA_LENGTH](#); SQLSTATE: [HY000](#)

Message: Maximum permissible size of data is '%zu' bits

- Error number: [MY-013723](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_STORE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error writing data for Data ID: '%s', Auth ID: '%s'. Either data already exists with same identifier or keyring backend encountered an error.

- Error number: [MY-013724](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_REMOVE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error removing data for Data ID: '%s', Auth ID: '%s'. Either data does not exist with same identifier or keyring backend encountered an error.

- Error number: [MY-013725](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_GENERATE_FAILED](#); SQLSTATE: [HY000](#)

Message: Error generating data for Data ID: '%s', Auth ID: '%s'. Either data already exists with same identifier or keyring backend encountered an error.

- Error number: [MY-013726](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ITERATOR_FETCH_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to get metadata from current keys metadata iterator position.

- Error number: [MY-013727](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_METADATA_ITERATOR_INVALID_OUT_PARAM](#); SQLSTATE: [HY000](#)

Message: Key and value length parameters must not be null.

- Error number: [MY-013728](#); Symbol: [ER_IB_WRN_FAILED_TO_ACQUIRE_SERVICE](#); SQLSTATE: [HY000](#)

Message: Innodb could not acquire service : %s

- Error number: [MY-013729](#); Symbol: [ER_IB_WRN_OLD_GEOMETRY_TYPE](#); SQLSTATE: [HY000](#)

Message: Column %s of type GEOMETRY is in old (5.6) format which could be deprecated in the future. To change the format to latest, please consider rebuilding the table after the upgrade.

- Error number: `MY-013730`; Symbol: `ER_NET_WAIT_ERROR2`; SQLSTATE: `HY000`

Message: 'wait_timeout' period of %s seconds was exceeded for %s. The idle time since last command was too long.

- Error number: `MY-013731`; Symbol: `ER_GRP_RPL_MEMBER_ACTION_TRIGGERED`; SQLSTATE: `HY000`

Message: The member action "%s" for event "%s" with priority "%u" will be run.

- Error number: `MY-013732`; Symbol: `ER_GRP_RPL_MEMBER_ACTION_FAILURE_IGNORE`; SQLSTATE: `HY000`

Message: The member action "%s" for event "%s" with priority "%u" failed, this error is ignored as instructed. Please check previous messages in the error log for hints about what could have caused this failure.

- Error number: `MY-013733`; Symbol: `ER_GRP_RPL_MEMBER_ACTION_FAILURE`; SQLSTATE: `HY000`

Message: The member action "%s" for event "%s" with priority "%u" failed. Please check previous messages in the error log for hints about what could have caused this failure.

- Error number: `MY-013734`; Symbol: `ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_RECEIVE`; SQLSTATE: `HY000`

Message: Unable to parse the member actions configuration sent by the primary.

- Error number: `MY-013735`; Symbol: `ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS`; SQLSTATE: `HY000`

Message: Unable to update the member actions configuration with the one sent by the primary. Please check the tables 'mysql.replication_group_member_actions' and 'mysql.replication_group_configuration_version'.

- Error number: `MY-013736`; Symbol: `ER_GRP_RPL_MEMBER_ACTION_GET_EXCHANGEABLE_DATA`; SQLSTATE: `HY000`

Message: Unable to read the member actions configuration during group membership change. Please check the tables 'mysql.replication_group_member_actions' and 'mysql.replication_group_configuration_version'.

- Error number: `MY-013737`; Symbol: `ER_GRP_RPL_MEMBER_ACTION_DEFAULT_CONFIGURATION`; SQLSTATE: `HY000`

Message: This member joined a group on which all members do not support member actions, as such it did reset its member configuration to the default one.

- Error number: `MY-013738`; Symbol: `ER_GRP_RPL_MEMBER_ACTION_UNABLE_TO_SET_DEFAULT_CONFIGURATION`; SQLSTATE: `HY000`

Message: Unable to reset to member actions default configuration on member join. Please check the tables 'mysql.replication_group_member_actions' and 'mysql.replication_group_configuration_version'.

- Error number: `MY-013739`; Symbol: `ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_MEMBER_JOIN`; SQLSTATE: `HY000`

Message: Unable to parse the member actions configuration sent by the group on member join.

- Error number: [MY-013740](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS_ON_MEMBER_JOIN](#); SQLSTATE: [HY000](#)

Message: Unable to update the member actions configuration on member join. Please check the tables 'mysql.replication_group_member_actions' and 'mysql.replication_group_configuration_version'.

- Error number: [MY-013741](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_INVALID_ACTIONS_ON_MEMBER_JOIN](#); SQLSTATE: [HY000](#)

Message: The group members were unable to send their member actions configuration. Please check the tables 'mysql.replication_group_member_actions' and 'mysql.replication_group_configuration_version' on all members.

- Error number: [MY-013742](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_ENABLED](#); SQLSTATE: [HY000](#)

Message: Member action enabled: "%s", type: "%s", event: "%s", priority: "%u", error_handling: "%s".

- Error number: [MY-013743](#); Symbol: [ER_GRP_RPL_MEMBER_ACTION_DISABLED](#); SQLSTATE: [HY000](#)

Message: Member action disabled: "%s", type: "%s", event: "%s", priority: "%u", error_handling: "%s".

- Error number: [MY-013744](#); Symbol: [ER_GRP_RPL_MEMBER_ACTIONS_RESET](#); SQLSTATE: [HY000](#)

Message: Member actions configuration was reset.

- Error number: [MY-013747](#); Symbol: [ER_FIREWALL_DEPRECATED_USER_PROFILE](#); SQLSTATE: [HY000](#)

Message: User profile '\%s\' loaded. Firewall user profiles are deprecated, consider migrating to group profiles.

- Error number: [MY-013748](#); Symbol: [ER_GRP_RPL_VIEW_CHANGE_UUID_INVALID](#); SQLSTATE: [HY000](#)

Message: Invalid input value for group_replication_view_change_uuid '%s'. Please, provide a valid UUID.

- Error number: [MY-013749](#); Symbol: [ER_GRP_RPL_VIEW_CHANGE_UUID_SAME_AS_GROUP_NAME](#); SQLSTATE: [HY000](#)

Message: Variable 'group_replication_view_change_uuid' cannot be set to the value of '%s'. If you want to use the UUID of 'group_replication_group_name' for the UUID of View_change_log_events, please set 'group_replication_view_change_uuid' to AUTOMATIC.

- Error number: [MY-013750](#); Symbol: [ER_GRP_RPL_GROUP_NAME_SAME_AS_VIEW_CHANGE_UUID](#); SQLSTATE: [HY000](#)

Message: group_replication_group_name '%s', which is the same as group_replication_view_change_uuid. Please change group_replication_view_change_uuid to AUTOMATIC

- Error number: [MY-013751](#); Symbol: [ER_GRP_RPL_VIEW_CHANGE_UUID_IS_SAME_AS_ANONYMOUS_TO_GTID_UUID](#); SQLSTATE: [HY000](#)

Message: The group_replication_view_change_uuid '%s' is the same as the UUID value for ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS in a server channel

-
- Error number: `MY-013752`; Symbol: `ER_GRP_RPL_GRP_VIEW_CHANGE_UUID_IS_INCOMPATIBLE_WITH_SERVER_UUID`; SQLSTATE: `HY000`

Message: group_replication_view_change_uuid is incompatible with group.
group_replication_view_change_uuid %s matches server_uuid %s.
 - Error number: `MY-013753`; Symbol: `ER_GRP_RPL_VIEW_CHANGE_UUID_DIFF_FROM_GRP`; SQLSTATE: `HY000`

Message: The member is configured with a group_replication_view_change_uuid option value '%s' different from the group '%s'. The member will now exit the group.
 - Error number: `MY-013754`; Symbol: `ER_WARN_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_VIEW_CHANGE_UUID`; SQLSTATE: `HY000`

Message: Replication channel '%s' is configured with `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS='%s'` which is equal to group_replication_view_change_uuid. To fix this issue, either change the group_replication_view_change_uuid or use a different value for `ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS`.
 - Error number: `MY-013755`; Symbol: `ER_GRP_RPL_FAILED_TO_PARSE_THE_VIEW_CHANGE_UUID`; SQLSTATE: `HY000`

Message: Unable to parse the group_replication_view_change_uuid.
 - Error number: `MY-013756`; Symbol: `ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_VIEW_CHANGE_UUID`; SQLSTATE: `HY000`

Message: Unable to generate sidno for group_replication_view_change_uuid.
 - Error number: `MY-013757`; Symbol: `ER_GRP_RPL_VIEW_CHANGE_UUID_PARSE_ERROR`; SQLSTATE: `HY000`

Message: Unable to parse the group_replication_view_change_uuid during the Certification module initialization.
 - Error number: `MY-013758`; Symbol: `ER_GRP_RPL_UPDATE_GRPGTID_VIEW_CHANGE_UUID_EXECUTED_ERROR`; SQLSTATE: `HY000`

Message: Error updating group_gtid_executed GTID set with view change uuid during the Certification module initialization.
 - Error number: `MY-013759`; Symbol: `ER_GRP_RPL_ADD_VIEW_CHANGE_UUID_TO_GRP_SID_MAP_ERROR`; SQLSTATE: `HY000`

Message: Unable to add the group_replication_view_change_uuid sidno in the group_gtid_sid_map during the Certification module initialization.
 - Error number: `MY-013760`; Symbol: `ER_GRP_RPL_DONOR_VIEW_CHANGE_UUID_TRANS_INFO_ERROR`; SQLSTATE: `HY000`

Message: Unable to handle the donor's view change uuid transaction information when initializing the conflict detection component. Possible out of memory error.

-
- Error number: [MY-013761](#); Symbol: [ER_WARN_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE](#); SQLSTATE: [HY000](#)
Message: Unable to retrieve group_replication_view_change_uuid during server checks on replication operations.
 - Error number: [MY-013762](#); Symbol: [ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS_LOG](#); SQLSTATE: [HY000](#)
Message: Both audit_log_max_size and audit_log_prune_seconds are set to non-zero. audit_log_max_size takes precedence and audit_log_prune_seconds is ignored
 - Error number: [MY-013763](#); Symbol: [ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE_ON_SIZE_LOG](#); SQLSTATE: [HY000](#)
Message: audit_log_rotate_on_size is not granular enough for the value of audit_log_max_size supplied. Should be at least %d times smaller.
 - Error number: [MY-013764](#); Symbol: [ER_PLUGIN_INVALID_TABLE_DEFINITION](#); SQLSTATE: [HY000](#)
Message: Invalid table definition for '%s.%s'.
 - Error number: [MY-013765](#); Symbol: [ER_AUTH_KERBEROS_LOGGER_GENERIC_MSG](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013766](#); Symbol: [ER_INSTALL_PLUGIN_CONFLICT_LOG](#); SQLSTATE: [HY000](#)
Message: Cannot install the %s plugin when the %s plugin is installed.
 - Error number: [MY-013767](#); Symbol: [ER_DEPRECATED_PERSISTED_VARIABLE_WITH_ALIAS](#); SQLSTATE: [HY000](#)
Message: The variable %s has been renamed to %s, and the old name deprecated. Only the old name was found in the persisted variable file. Next time the file is saved, both names will be stored. Issue any SET PERSIST command to save the file, get rid of this warning, and prepare the persisted configuration for when the variable is removed in a future version.
 - Error number: [MY-013768](#); Symbol: [ER_LOG_COMPONENT_FLUSH_FAILED](#); SQLSTATE: [HY000](#)
Message: %d error logging component(s) failed to flush. For file-based logs this can happen when the path or permissions of the log-file have changed. Failure to flush file-based logs may affect log-rotation.
 - Error number: [MY-013769](#); Symbol: [ER_IB_MSG_REENCRYPTED_TABLESPACE_KEY](#); SQLSTATE: [HY000](#)
Message: Tablespace key for %s has been re-encrypted using the latest InnoDB master key. However, we recommend that you rebuild the table for better security.
 - Error number: [MY-013770](#); Symbol: [ER_IB_MSG_REENCRYPTED_GENERAL_TABLESPACE_KEY](#); SQLSTATE: [HY000](#)
Message: Tablespace key for %s has been re-encrypted using the latest InnoDB master key. However, we recommend that you reencrypt the tablespace for better security.
 - Error number: [MY-013771](#); Symbol: [ER_IB_ERR_PAGE_ARCH_DBLWR_INIT_FAILED](#); SQLSTATE: [HY000](#)
-

Message: Page Archiver's doublewrite buffer initialisation failed. Page tracking is at risk of losing tracked information.

- Error number: `MY-013772`; Symbol: `ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG__SKIP_IBUF_MERGES`; SQLSTATE: `HY000`

Message: There is not enough free space in the redo log during recovery to perform pending ibuf merges. Please retry starting MySQL with `--innodb-force-recovery=4`.

- Error number: `MY-013773`; Symbol: `ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG__UNEXPECTED`; SQLSTATE: `HY000`

Message: There is not enough free space in the redo log during recovery, restore from backup (or retry with `--innodb-force-recovery=6`).

- Error number: `MY-013774`; Symbol: `ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_ONLY_WHEN_JSON_LOG`; SQLSTATE: `HY000`

Message: `audit_log_format_unix_timestamp` is applicable only when `audit_log_format = JSON`.

- Error number: `MY-013775`; Symbol: `ER_PREPARE_FOR_PRIMARY_ENGINE`; SQLSTATE: `HY000`

Message: Retry the statement using the primary storage engine.

- Error number: `MY-013776`; Symbol: `ER_IB_MSG_PAR_RSEG_INIT_COMPLETE_MSG`; SQLSTATE: `HY000`

Message: Parallel initialization of rseg complete

- Error number: `MY-013777`; Symbol: `ER_IB_MSG_PAR_RSEG_INIT_TIME_MSG`; SQLSTATE: `HY000`

Message: Time taken to initialize rseg using %u thread: %u ms.

- Error number: `MY-013778`; Symbol: `ER_DDL_MSG_1`; SQLSTATE: `HY000`

Message: DDL failed to create a thread to load an index, fall back to single thread

- Error number: `MY-013779`; Symbol: `ER_MTR_MSG_1`; SQLSTATE: `HY000`

Message: `Debug_check_no_latching` failed, slot->type=%d

- Error number: `MY-013780`; Symbol: `ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ERROR_CONN_ERR`; SQLSTATE: `HY000`

Message: Failed to establish MySQL client connection in Group Replication. Error establishing connection. Please refer to the manual to make sure that you configured Group Replication properly to work with MySQL Protocol connections.

- Error number: `MY-013781`; Symbol: `ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ERROR_COMMAND_ERR`; SQLSTATE: `HY000`

Message: Failed to establish MySQL client connection in Group Replication. Error sending connection delegation command. Please refer to the manual to make sure that you configured Group Replication properly to work with MySQL Protocol connections.

- Error number: `MY-013782`; Symbol: `ER_GRP_RPL_FAILOVER_CONF_GET_EXCHANGEABLE_DATA`; SQLSTATE: `HY000`

Message: Unable to read the replication failover channels configuration during group membership change. Please check the tables 'mysql.replication_asynchronous_connection_failover', 'mysql.replication_asynchronous_connection_failover_managed' and 'mysql.replication_group_configuration_version'.

- Error number: `MY-013783`; Symbol: `ER_GRP_RPL_FAILOVER_CONF_DEFAULT_CONFIGURATION`; SQLSTATE: `HY000`

Message: This member joined a group on which all members do not support replication failover channels integration on Group Replication, as such it did reset its replication failover channels configuration to the default one.

- Error number: `MY-013784`; Symbol: `ER_GRP_RPL_FAILOVER_CONF_UNABLE_TO_SET_DEFAULT_CONFIGURATION`; SQLSTATE: `HY000`

Message: Unable to reset to replication failover channels default configuration on member join. Please check the tables 'mysql.replication_asynchronous_connection_failover', 'mysql.replication_asynchronous_connection_failover_managed' and 'mysql.replication_group_configuration_version'.

- Error number: `MY-013785`; Symbol: `ER_GRP_RPL_FAILOVER_CONF_PARSE_ON_MEMBER_JOIN`; SQLSTATE: `HY000`

Message: Unable to parse the replication failover channels configuration sent by the group on member join.

- Error number: `MY-013786`; Symbol: `ER_GRP_RPL_FAILOVER_CONF_CHANNEL_DOES_NOT_EXIST`; SQLSTATE: `HY000`

Message: Unable to set `SOURCE_CONNECTION_AUTO_FAILOVER` on a non-existent or misconfigured replication channel '%s', please create the channel and rejoin the server to the group.

- Error number: `MY-013787`; Symbol: `ER_GRP_RPL_FAILOVER_REGISTER_MESSAGE_LISTENER_SERVICE`; SQLSTATE: `HY000`

Message: Unable to register the listener 'replication_asynchronous_connection_failover_configuration' to the service 'group_replication_message_service_rcv'.

- Error number: `MY-013788`; Symbol: `ER_GRP_RPL_FAILOVER_PRIMARY_WITHOUT_MAJORITY`; SQLSTATE: `HY000`

Message: This server is not able to reach a majority of members in the group. This server will skip the replication failover channels handling until this server is back to the group majority.

- Error number: `MY-013789`; Symbol: `ER_GRP_RPL_FAILOVER_PRIMARY_BACK_TO_MAJORITY`; SQLSTATE: `HY000`

Message: This server is back to the group majority. Replication failover channels handling is resumed.

- Error number: `MY-013790`; Symbol: `ER_RPL_INCREMENTING_MEMBER_ACTION_VERSION`; SQLSTATE: `HY000`

Message: Error incrementing member action configuration version for %s.%s table.

- Error number: `MY-013791`; Symbol: `ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_SECONDARY_MEMBER`; SQLSTATE: `HY000`

-
- Message: The '%s' thread of channel '%s' will error out as this server is a group secondary.
- Error number: [MY-013792](#); Symbol: [ER_IB_MSG_CLONE_DDL_NTFN](#); SQLSTATE: [HY000](#)
Message: Clone DDL Notification: %s
 - Error number: [MY-013793](#); Symbol: [ER_IB_MSG_CLONE_DDL_APPLY](#); SQLSTATE: [HY000](#)
Message: Clone DDL APPLY: %s
 - Error number: [MY-013794](#); Symbol: [ER_IB_MSG_CLONE_DDL_INVALIDATE](#); SQLSTATE: [HY000](#)
Message: Clone DDL Invalidate : %s
 - Error number: [MY-013795](#); Symbol: [ER_IB_MSG_UNDO_ENCRYPTION_INFO_LOADED](#); SQLSTATE: [HY000](#)
Message: Encryption key is loaded for undo tablespace '%s'.
 - Error number: [MY-013796](#); Symbol: [ER_IB_WRN_ENCRYPTION_INFO_SIZE_MISMATCH](#); SQLSTATE: [HY000](#)
Message: Ignoring encryption INFO size in redo log: %zu, expected: %zu
 - Error number: [MY-013797](#); Symbol: [ER_INVALID_AUTHENTICATION_POLICY](#); SQLSTATE: [HY000](#)
Message: Option --authentication-policy is set to an invalid value. Please check if the specified authentication plugins are valid.
 - Error number: [MY-013798](#); Symbol: [ER_AUTHENTICATION_PLUGIN_REGISTRATION_FAILED](#); SQLSTATE: [HY000](#)
Message: Signature verification failed during registration.
 - Error number: [MY-013799](#); Symbol: [ER_AUTHENTICATION_PLUGIN_REGISTRATION_INSUFFICIENT_BUFFER](#); SQLSTATE: [HY000](#)
Message: Buffer too small to hold registration challenge response.
 - Error number: [MY-013800](#); Symbol: [ER_AUTHENTICATION_PLUGIN_AUTH_DATA_CORRUPT](#); SQLSTATE: [HY000](#)
Message: FIDO device authenticator data corrupt.
 - Error number: [MY-013801](#); Symbol: [ER_AUTHENTICATION_PLUGIN_SIGNATURE_CORRUPT](#); SQLSTATE: [HY000](#)
Message: FIDO device signature corrupt.
 - Error number: [MY-013802](#); Symbol: [ER_AUTHENTICATION_PLUGIN_VERIFY_SIGNATURE_FAILED](#); SQLSTATE: [HY000](#)
Message: Signature verification failed during authentication.
 - Error number: [MY-013803](#); Symbol: [ER_AUTHENTICATION_PLUGIN_OOM](#); SQLSTATE: [HY000](#)
Message: Out of memory.
 - Error number: [MY-013804](#); Symbol: [ER_AUTHENTICATION_PLUGIN_LOG](#); SQLSTATE: [HY000](#)

Message: Can't initialize logging service.

- Error number: [MY-013805](#); Symbol: [ER_WARN_REPLICA_GTID_ONLY_AND_GTID_MODE_NOT_ON](#); SQLSTATE: [HY000](#)

Message: Replication channel '%s' is configured with GTID_ONLY=1, which is invalid when GTID_MODE <> ON. If you intend to disable GTIDs in the replication topology, change GTID_ONLY to 0.

- Error number: [MY-013806](#); Symbol: [ER_WARN_L_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO_POS_INVALID_POS](#); SQLSTATE: [HY000](#)

Message: The replication positions relative to the source may be out-of-date on channel '%s', due to the use of GTID_ONLY=1. The out-of-date positions can still be used in some cases so, in order to update them, we suggest that you start the replication to receive and apply at least one transaction, which will set the positions to valid values.

- Error number: [MY-013807](#); Symbol: [ER_RPL_CANNOT_OPEN_RELAY_LOG](#); SQLSTATE: [HY000](#)

Message: Could not open relay log: %s

- Error number: [MY-013808](#); Symbol: [ER_AUTHENTICATION_OCI_PLUGIN_NOT_INITIALIZED](#); SQLSTATE: [HY000](#)

Message: Authentication plugin not initialized.

- Error number: [MY-013809](#); Symbol: [ER_AUTHENTICATION_OCI_PRIVATE_KEY_ERROR](#); SQLSTATE: [HY000](#)

Message: Cannot use the generated private key file.

- Error number: [MY-013810](#); Symbol: [ER_AUTHENTICATION_OCI_DOWNLOAD_PUBLIC_KEY](#); SQLSTATE: [HY000](#)

Message: Unavailable public key with fingerprint %s for user %s in tenancy %s .

- Error number: [MY-013811](#); Symbol: [ER_AUTHENTICATION_OCI_IMDS](#); SQLSTATE: [HY000](#)

Message: Cannot obtain the OCI configuration from the IMDS service.

- Error number: [MY-013812](#); Symbol: [ER_AUTHENTICATION_OCI_IAM](#); SQLSTATE: [HY000](#)

Message: Cannot initialize the IAM service.

- Error number: [MY-013813](#); Symbol: [ER_AUTHENTICATION_OCI_INVALID_AUTHENTICATION_STRING](#); SQLSTATE: [HY000](#)

Message: Invalid authentication string details for user: `%s`@`%s`.

- Error number: [MY-013814](#); Symbol: [ER_AUTHENTICATION_OCI_NO_MATCHING_GROUPS](#); SQLSTATE: [HY000](#)

Message: None of the groups returned by IAM matches any of the entries from authentication string.

- Error number: [MY-013815](#); Symbol: [ER_AUTHENTICATION_OCI_NO_GROUPS_FOUND](#); SQLSTATE: [HY000](#)

Message: User is not part of any groups. However, account is configured to use group mapping.

-
- Error number: [MY-013816](#); Symbol: [ER_AUTHENTICATION_OCI_NONCE](#); SQLSTATE: [HY000](#)
Message: Received OpenSSL error: %s while authenticating user %s with fingerprint %s in tenancy %s .
 - Error number: [MY-013817](#); Symbol: [ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_1](#); SQLSTATE: [HY000](#)
Message: %s: Warning Level 1 (%llu MiB): available=%llu MiB, total=%llu MiB, used=%.2f%%, mysqlid=%llu MiB
 - Error number: [MY-013818](#); Symbol: [ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_2](#); SQLSTATE: [HY000](#)
Message: %s: Warning Level 2 (%llu MiB): available=%llu MiB, total=%llu MiB, used=%.2f%%, mysqlid=%llu MiB
 - Error number: [MY-013819](#); Symbol: [ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_3](#); SQLSTATE: [HY000](#)
Message: %s: Warning Level 3 (%llu MiB): available=%llu MiB, total=%llu MiB, used=%.2f%%, mysqlid=%llu MiB
 - Error number: [MY-013820](#); Symbol: [ER_GRP_RPL_SET_SINGLE_CONSENSUS_LEADER](#); SQLSTATE: [HY000](#)
Message: The member %s:%u, with UUID: %s, was set as the single preferred consensus leader.
 - Error number: [MY-013821](#); Symbol: [ER_GRP_RPL_ERROR_SET_SINGLE_CONSENSUS_LEADER](#); SQLSTATE: [HY000](#)
Message: Something went wrong trying to set the member %s:%u, with UUID: %s, as the single preferred consensus leader. Please query the `performance_schema.replication_group_communication_information` table to see whether the operation took effect, i.e. whether the preferred consensus leader matches the current primary. If not, consider electing a different primary to try again. Please check the error log and `GCS_DEBUG_TRACE` for more information that may help understanding what went wrong.
 - Error number: [MY-013822](#); Symbol: [ER_GRP_RPL_SET_MULTI_CONSENSUS_LEADER](#); SQLSTATE: [HY000](#)
Message: All members were set as consensus leaders.
 - Error number: [MY-013823](#); Symbol: [ER_GRP_RPL_ERROR_SET_MULTI_CONSENSUS_LEADER](#); SQLSTATE: [HY000](#)
Message: Something went wrong trying to set all members as consensus leaders. Please query the `performance_schema.replication_group_communication_information` table to see whether the operation took effect, i.e. whether the consensus leaders match all members. If not, consider resetting the group communication protocol to a version < 8.0.22, or switch to single-primary mode and back again to multi-primary mode, to try again. Please check the error log and `GCS_DEBUG_TRACE` for more information that may help understanding what went wrong.
 - Error number: [MY-013824](#); Symbol: [ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_GRP](#); SQLSTATE: [HY000](#)
Message: This member is configured with a `group_replication_paxos_single_leader` option value of '%d' that is different from the group's value ('%d'). This member will now exit the group.

-
- Error number: [MY-013825](#); Symbol: [ER_MFA_USER_ATTRIBUTES_CORRUPT](#); SQLSTATE: [HY000](#)
Message: Invalid and/or corrupted multi factor authentication methods in User_attributes column in mysql.user table. "%s".
 - Error number: [MY-013826](#); Symbol: [ER_MFA_PLUGIN_NOT_LOADED](#); SQLSTATE: [HY000](#)
Message: Plugin '%s' is not loaded; Ignoring user
 - Error number: [MY-013827](#); Symbol: [ER_WARN_DEPRECATED_CHARSET_OPTION](#); SQLSTATE: [HY000](#)
Message: %s: The character set %s is deprecated and will be removed in a future release. Please consider using %s instead.
 - Error number: [MY-013828](#); Symbol: [ER_WARN_DEPRECATED_COLLATION_OPTION](#); SQLSTATE: [HY000](#)
Message: %s: '%s' is a collation of the deprecated character set %s. Please consider using %s with an appropriate collation instead.
 - Error number: [MY-013829](#); Symbol: [ER_REGEX_MISSING_ICU_DATADIR](#); SQLSTATE: [HY000](#)
Message: Missing data directory for ICU regular expressions: %s.
 - Error number: [MY-013830](#); Symbol: [ER_IB_WARN_MANY_NON_LRU_FILES_OPENED](#); SQLSTATE: [HY000](#)
Message: More than 90%% of files opened out of the innodb_open_files limit are files that are not easy to close. The performance of system may degrade. Consider increasing value of the innodb_open_files system variable. There are %zu such files opened out of the total limit for all files opened of %zu.
 - Error number: [MY-013831](#); Symbol: [ER_IB_MSG_TRYING_TO_OPEN_FILE_FOR_LONG_TIME](#); SQLSTATE: [HY000](#)
Message: Trying to open a file for %lld seconds. Configuration only allows for %zu open files. Consider setting innobase_open_files higher.
 - Error number: [MY-013832](#); Symbol: [ER_GLOBAL_CONN_LIMIT](#); SQLSTATE: [HY000](#)
Message: Connection closed. Global connection memory limit %llu bytes exceeded. Consumed %llu bytes.
 - Error number: [MY-013833](#); Symbol: [ER_CONN_LIMIT](#); SQLSTATE: [HY000](#)
Message: Connection closed. Connection memory limit %llu bytes exceeded. Consumed %llu bytes.
 - Error number: [MY-013834](#); Symbol: [ER_WARN_AUDIT_LOG_DISABLED](#); SQLSTATE: [HY000](#)
Message: Audit Log is disabled. Enable it with audit_log_disable = false.
 - Error number: [MY-013835](#); Symbol: [ER_INVALID_TLS_VERSION](#); SQLSTATE: [HY000](#)
Message: Option --tls-version or --admin-tls-version is set to an invalid value %s.
 - Error number: [MY-013836](#); Symbol: [ER_RPL_RELAY_LOG_RECOVERY_GTID_ONLY](#); SQLSTATE: [HY000](#)
Message: Relay log recovery on channel with GTID_ONLY=1. The channel will switch to a new relay log and the GTID protocol will be used to replicate unapplied transactions.
-

-
- Error number: [MY-013837](#); Symbol: [ER_KEYRING_OKV_STANDBY_SERVER_COUNT_EXCEEDED](#); SQLSTATE: [HY000](#)
Message: Number of STANDBY_SERVER values exceeded maximum limit of 64.
 - Error number: [MY-013838](#); Symbol: [ER_WARN_MIGRATION_EMPTY_SOURCE_KEYRING](#); SQLSTATE: [HY000](#)
Message: Source keyring does not have any keys to migrate.
 - Error number: [MY-013839](#); Symbol: [ER_WARN_CANNOT_PERSIST_SENSITIVE_VARIABLES](#); SQLSTATE: [HY000](#)
Message: Cannot persist SENSITIVE system variables because keyring component support is unavailable and persist_sensitive_variables_in_plaintext is set to OFF. Please make sure that keyring services are active and required keys are available.
 - Error number: [MY-013840](#); Symbol: [ER_CANNOT_INTERPRET_PERSISTED_SENSITIVE_VARIABLES](#); SQLSTATE: [HY000](#)
Message: Cannot interpret persisted SENSITIVE system variables. Please make sure that keyring services are active and required keys are available.
 - Error number: [MY-013841](#); Symbol: [ER_PERSISTED_VARIABLES_KEYRING_SUPPORT_REQUIRED](#); SQLSTATE: [HY000](#)
Message: Keyring has to be loaded through manifest file in order to support secure storage for persisted variables
 - Error number: [MY-013842](#); Symbol: [ER_PERSISTED_VARIABLES_MASTER_KEY_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: Could not find master key %s in keyring
 - Error number: [MY-013843](#); Symbol: [ER_PERSISTED_VARIABLES_MASTER_KEY_CANNOT_BE_GENERATED](#); SQLSTATE: [HY000](#)
Message: A new master key %s could not be generated
 - Error number: [MY-013844](#); Symbol: [ER_PERSISTED_VARIABLES_ENCRYPTION_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to encrypt %s using %s
 - Error number: [MY-013845](#); Symbol: [ER_PERSISTED_VARIABLES_DECRYPTION_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to decrypt %s using %s
 - Error number: [MY-013846](#); Symbol: [ER_PERSISTED_VARIABLES_LACK_KEYRING_SUPPORT](#); SQLSTATE: [HY000](#)
Message: Persisting SENSITIVE variables in encrypted form requires keyring component loaded through manifest file.
 - Error number: [MY-013847](#); Symbol: [ER_MY_MALLOC_USING_JEMALLOC](#); SQLSTATE: [HY000](#)
Message: Using jemalloc.dll for my_malloc and ut::malloc etc.

-
- Error number: [MY-013848](#); Symbol: [ER_MY_MALLOC_USING_STD_MALLOC](#); SQLSTATE: [HY000](#)
Message: %s.
 - Error number: [MY-013849](#); Symbol: [ER_MY_MALLOC_LOADLIBRARY_FAILED](#); SQLSTATE: [HY000](#)
Message: %s.
 - Error number: [MY-013850](#); Symbol: [ER_MY_MALLOC_GETPROCADDRESS_FAILED](#); SQLSTATE: [HY000](#)
Message: %s.
 - Error number: [MY-013851](#); Symbol: [ER_ACCOUNT_WITH_EXPIRED_PASSWORD](#); SQLSTATE: [HY000](#)
Message: Password for the account '%s'@'%s' has expired. To log in, either change it using a client that supports expired passwords or send the change request to an administrator.
 - Error number: [MY-013852](#); Symbol: [ER_THREAD_POOL_PLUGIN_STARTED](#); SQLSTATE: [HY000](#)
Message: Thread pool plugin started successfully with parameters: %s
 - Error number: [MY-013853](#); Symbol: [ER_THREAD_POOL_DEDICATED_LISTENERS_INVALID](#); SQLSTATE: [HY000](#)
Message: thread_pool_dedicated_listeners cannot be set unless thread_pool_max_transactions_limit > 0
 - Error number: [MY-013854](#); Symbol: [ER_IB_DBLWR_BYTES_INFO](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013855](#); Symbol: [ER_IB_RDBLWR_BYTES_INFO](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013856](#); Symbol: [ER_IB_MSG_LOG_FILE_IS_EMPTY](#); SQLSTATE: [HY000](#)
Message: The redo log file %s is empty, which indicates it was not generated by InnoDB or become corrupted. Please restore the correct file or try recovering without the redo files, in read-only mode, by providing --innodb-force-recovery=6.
 - Error number: [MY-013857](#); Symbol: [ER_IB_MSG_LOG_FILE_TOO_SMALL](#); SQLSTATE: [HY000](#)
Message: The redo log file %s is smaller than %llu bytes, which indicates it was not generated by InnoDB or become corrupted. Please restore the correct file.
 - Error number: [MY-013858](#); Symbol: [ER_IB_MSG_LOG_FILE_TOO_BIG](#); SQLSTATE: [HY000](#)
Message: The redo log file %s is larger than %llu bytes, which indicates it was not generated by InnoDB or become corrupted. Please restore the correct file.
 - Error number: [MY-013859](#); Symbol: [ER_IB_MSG_LOG_FILE_HEADER_READ_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to read header of the redo log file %s
 - Error number: [MY-013860](#); Symbol: [ER_IB_MSG_LOG_INIT_DIR_NOT_EMPTY_WONT_INITIALIZE](#); SQLSTATE: [HY000](#)

-
- Message: --initialize specified but the redo log directory %s has redo log files inside. Aborting.
- Error number: `MY-013861`; Symbol: `ER_IB_MSG_LOG_INIT_DIR_LIST_FAILED`; SQLSTATE: `HY000`
Message: Failed to list redo log files in the redo log directory %s
 - Error number: `MY-013862`; Symbol: `ER_IB_MSG_LOG_INIT_DIR_MISSING_SUBDIR`; SQLSTATE: `HY000`
Message: Neither found %s subdirectory, nor %s* files in %s
 - Error number: `MY-013863`; Symbol: `ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE_AND_READ_ONLY_MODE`; SQLSTATE: `HY000`
Message: Cannot restore cloned data directory, InnoDB running in read-only mode!
 - Error number: `MY-013864`; Symbol: `ER_IB_MSG_LOG_WRITER_WRITE_FAILED`; SQLSTATE: `HY000`
Message: Error %d encountered when writing to the redo log file: %s.
 - Error number: `MY-013865`; Symbol: `ER_IB_MSG_LOG_WRITER_WAIT_ON_NEW_LOG_FILE`; SQLSTATE: `HY000`
Message: Redo log writer is waiting for a new redo log file. Consider increasing `innodb_redo_log_capacity`.
 - Error number: `MY-013866`; Symbol: `ER_IB_MSG_RECOVERY_CHECKPOINT_OUTSIDE_LOG_FILE`; SQLSTATE: `HY000`
Message: Found checkpoint LSN %llu in a redo log file %s, but the file represents range of LSN values [%llu, %llu), so the file is corrupted.
 - Error number: `MY-013867`; Symbol: `ER_IB_MSG_LOG_WRITER_ENTERED_EXTRA_MARGIN`; SQLSTATE: `HY000`
Message: Redo log is running out of free space, pausing user threads... Consider increasing `innodb_redo_log_capacity`.
 - Error number: `MY-013868`; Symbol: `ER_IB_MSG_LOG_WRITER_EXITED_EXTRA_MARGIN`; SQLSTATE: `HY000`
Message: Redo log reclaimed some free space, resuming user threads.
 - Error number: `MY-013869`; Symbol: `ER_IB_MSG_LOG_PARAMS_FILE_SIZE_UNUSED`; SQLSTATE: `HY000`
Message: Ignored deprecated configuration parameter `innodb_log_file_size`. Used `innodb_redo_log_capacity` instead.
 - Error number: `MY-013870`; Symbol: `ER_IB_MSG_LOG_PARAMS_N_FILES_UNUSED`; SQLSTATE: `HY000`
Message: Ignored deprecated configuration parameter `innodb_log_files_in_group`. Used `innodb_redo_log_capacity` instead.
 - Error number: `MY-013871`; Symbol: `ER_IB_MSG_LOG_UPGRADE_FORCED_RECV`; SQLSTATE: `HY000`
Message: Cannot upgrade format (v%lu) of redo log files when `innodb-force-recovery > 0`.

-
- Error number: [MY-013872](#); Symbol: [ER_IB_MSG_LOG_UPGRADE_IN_READ_ONLY_MODE](#); SQLSTATE: [HY000](#)
Message: Cannot upgrade format (v%lu) of redo log files in read-only mode (--innodb-read-only).
 - Error number: [MY-013873](#); Symbol: [ER_IB_MSG_LOG_UPGRADE_CLONED_DB](#); SQLSTATE: [HY000](#)
Message: Cannot upgrade format (v%lu) of redo log files on cloned data directory. Please use an older version of MySQL - recover and shutdown (with innodb-fast-shutdown < 2).
 - Error number: [MY-013874](#); Symbol: [ER_IB_MSG_LOG_UPGRADE_UNINITIALIZED_FILES](#); SQLSTATE: [HY000](#)
Message: Cannot upgrade format (v%lu) of redo log files because they are marked as uninitialized. Please use an older version of MySQL - recover and shutdown (with innodb-fast-shutdown < 2).
 - Error number: [MY-013875](#); Symbol: [ER_IB_MSG_LOG_UPGRADE_CORRUPTION__UNEXPECTED](#); SQLSTATE: [HY000](#)
Message: Cannot upgrade format (v%lu) of redo log files when the redo log is corrupted. Please use an older version of MySQL - recover and shutdown (with innodb-fast-shutdown < 2).
 - Error number: [MY-013879](#); Symbol: [ER_IB_MSG_LOG_FILE_FOREIGN_UUID](#); SQLSTATE: [HY000](#)
Message: The redo log file %s comes from other data directory than redo log file %s.
 - Error number: [MY-013880](#); Symbol: [ER_IB_MSG_LOG_FILE_INVALID_START_LSN](#); SQLSTATE: [HY000](#)
Message: The redo log file %s has invalid start_lsn %llu.
 - Error number: [MY-013881](#); Symbol: [ER_IB_MSG_LOG_FILE_INVALID_LSN_RANGES](#); SQLSTATE: [HY000](#)
Message: The redo log file %s has start_lsn %llu but expected %llu (end_lsn of the previous redo log file).
 - Error number: [MY-013882](#); Symbol: [ER_IB_MSG_LOG_FILE_MISSING_FOR_ID](#); SQLSTATE: [HY000](#)
Message: Missing redo log file %s (with start_lsn = %llu).
 - Error number: [MY-013883](#); Symbol: [ER_IB_MSG_LOG_CHECKPOINT_FOUND](#); SQLSTATE: [HY000](#)
Message: The latest found checkpoint is at lsn = %llu in redo log file %s.
 - Error number: [MY-013884](#); Symbol: [ER_IB_MSG_LOG_FILES_CAPACITY_CHANGED](#); SQLSTATE: [HY000](#)
Message: User has set innodb_redo_log_capacity to %lluM.
 - Error number: [MY-013885](#); Symbol: [ER_IB_MSG_LOG_FILES_RESIZE_REQUESTED](#); SQLSTATE: [HY000](#)
Message: Redo log has been requested to resize from %lluM to %lluM.
 - Error number: [MY-013886](#); Symbol: [ER_IB_MSG_LOG_FILES_RESIZE_CANCELLED](#); SQLSTATE: [HY000](#)
Message: Redo log resize has been cancelled.
-

-
- Error number: `MY-013887`; Symbol: `ER_IB_MSG_LOG_FILES_RESIZE_FINISHED`; SQLSTATE: `HY000`
Message: Redo log has been resized to %lluM.
 - Error number: `MY-013888`; Symbol: `ER_IB_MSG_LOG_FILES_UPGRADE`; SQLSTATE: `HY000`
Message: Upgrading redo log: %lluM, LSN=%llu.
 - Error number: `MY-013889`; Symbol: `ER_IB_MSG_LOG_FILE_MARK_CURRENT_AS_INCOMPLETE`; SQLSTATE: `HY000`
Message: Marked the current redo log file %s as incomplete.
 - Error number: `MY-013890`; Symbol: `ER_IB_MSG_LOG_FILE_REMOVE_FAILED`; SQLSTATE: `HY000`
Message: Failed to remove redo log file %s.
 - Error number: `MY-013891`; Symbol: `ER_IB_MSG_LOG_FILE_RENAME_ON_CREATE_FAILED`; SQLSTATE: `HY000`
Message: Failed to rename %s when creating redo log file %s (error: %d)
 - Error number: `MY-013892`; Symbol: `ER_IB_MSG_LOG_FILES_CREATED_BY_UNKNOWN_CREATOR`; SQLSTATE: `HY000`
Message: Redo log files created by unknown creator %s.
 - Error number: `MY-013893`; Symbol: `ER_IB_MSG_LOG_FILES_FOUND_MISSING`; SQLSTATE: `HY000`
Message: Found existing redo log files, but at least one is missing. It is unknown if recovery could reach physically consistent state. Please consider restoring from backup or providing `--innodb-force-recovery > 0`.
 - Error number: `MY-013894`; Symbol: `ER_IB_MSG_LOG_FILE_FORMAT_TOO_NEW`; SQLSTATE: `HY000`
Message: Found redo log file %s which has format (v%lu) and is stored outside #innodb_redo.
 - Error number: `MY-013895`; Symbol: `ER_IB_MSG_LOG_FILE_FORMAT_TOO_OLD`; SQLSTATE: `HY000`
Message: Found redo log file %s which has format (v%lu) and is stored inside #innodb_redo.
 - Error number: `MY-013896`; Symbol: `ER_IB_MSG_LOG_FILE_DIFFERENT_FORMATS`; SQLSTATE: `HY000`
Message: Found redo log files with different formats: %s has format v%lu, %s has format v%lu.
 - Error number: `MY-013897`; Symbol: `ER_IB_MSG_LOG_PRE_8_0_30_MISSING_FILE0`; SQLSTATE: `HY000`
Message: Missing ib_logfile0 in the directory %s.
 - Error number: `MY-013898`; Symbol: `ER_IB_MSG_LOG_PFS_ACQUIRE_SERVICES_FAILED`; SQLSTATE: `HY000`
Message: Failed to initialize services required to handle redo log PFS tables.
 - Error number: `MY-013899`; Symbol: `ER_IB_MSG_LOG_PFS_CREATE_TABLES_FAILED`; SQLSTATE: `HY000`

Message: Failed to create redo log PFS tables.

- Error number: [MY-013900](#); Symbol: [ER_IB_MSG_LOG_FILE_TRUNCATE](#); SQLSTATE: [HY000](#)

Message: Truncating redo log file %s...

- Error number: [MY-013901](#); Symbol: [ER_IB_MSG_LOG_FILE_UNUSED_RESIZE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to resize unused redo log file %s to %llu MB (%s).

- Error number: [MY-013902](#); Symbol: [ER_IB_MSG_LOG_FILE_UNUSED_REMOVE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to remove unused redo log file %s.

- Error number: [MY-013903](#); Symbol: [ER_IB_MSG_LOG_FILE_UNUSED_RENAME_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to rename unused redo log file %s to %s.

- Error number: [MY-013904](#); Symbol: [ER_IB_MSG_LOG_FILE_UNUSED_MARK_AS_IN_USE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to mark unused redo log file %s as in use (by renaming to %s).

- Error number: [MY-013905](#); Symbol: [ER_IB_MSG_LOG_FILE_MARK_AS_UNUSED_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to mark redo log file %s as unused (by renaming to %s).

- Error number: [MY-013906](#); Symbol: [ER_IB_MSG_LOG_PARAMS_DEDICATED_SERVER_IGNORED](#); SQLSTATE: [HY000](#)

Message: Option `innodb_dedicated_server` is ignored for `innodb_redo_log_capacity`, because `innodb_redo_log_capacity`, `innodb_log_file_size` or `innodb_log_files_in_group` is specified explicitly. Redo log capacity: %lluM.

- Error number: [MY-013907](#); Symbol: [ER_IB_MSG_LOG_PARAMS_LEGACY_USAGE](#); SQLSTATE: [HY000](#)

Message: Deprecated configuration parameters `innodb_log_file_size` and/or `innodb_log_files_in_group` have been used to compute `innodb_redo_log_capacity=%llu`. Please use `innodb_redo_log_capacity` instead.

- Error number: [MY-013908](#); Symbol: [ER_GRP_RPL_FAILED_TO_LOG_VIEW_CHANGE](#); SQLSTATE: [HY000](#)

Message: This member was unable to log the `View_change_log_event` into the binary log, hence it will leave the group. Please check that there is available disk space and add the member back to the group.

- Error number: [MY-013909](#); Symbol: [ER_BINLOG_CRASH_RECOVERY_MALFORMED_LOG](#); SQLSTATE: [HY000](#)

Message: Found invalid event sequence while recovering from binary log file '%s', between positions %llu and %llu: %s. The recovery process was stopped early and no transaction was recovered. Side effects may be transactions in an inconsistent state between the binary log and the storage engines, or transactions kept by storage engines in a prepared state (possibly holding locks). Either fix the issues

with the binary log or, to release possibly acquired locks, disable the binary log during server recovery. Note that disabling the binary log may lead to loss of transactions that were already acknowledged as successful to client connections and may have been replicated to other servers in the topology.

- Error number: [MY-013910](#); Symbol: [ER_BINLOG_CRASH_RECOVERY_ERROR_RETURNED_SE](#); SQLSTATE: [HY000](#)

Message: Storage engines failed to recover one or more transactions. The recovery process was stopped early, check previous messages for the details on failed transactions. Side effects may be transactions in an inconsistent state between the binary log and the storage engines, or transactions kept by storage engines in a prepared state (possibly holding locks). Either fix the issues with the storage engine (out-of-memory, no disk space, etc) or, to release possibly acquired locks held by XA transactions, disable the binary log during server recovery and check consistency between storage engines and binary log files.

- Error number: [MY-013911](#); Symbol: [ER_BINLOG_CRASH_RECOVERY_ENGINE_RESULTS](#); SQLSTATE: [HY000](#)

Message: Crash recovery finished in %s engine. %s

- Error number: [MY-013912](#); Symbol: [ER_BINLOG_CRASH_RECOVERY_COMMIT_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to commit %s in %s, with failure code %s.

- Error number: [MY-013913](#); Symbol: [ER_BINLOG_CRASH_RECOVERY_ROLLBACK_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to rollback %s in %s, with failure code %s.

- Error number: [MY-013914](#); Symbol: [ER_BINLOG_CRASH_RECOVERY_PREPARE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to prepare %s in %s, with failure code %s.

- Error number: [MY-013915](#); Symbol: [ER_COMPONENT_EE_SYS_VAR_REGISTRATION_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot register variable '%s'. Please check if it is not already registered by another component.

- Error number: [MY-013916](#); Symbol: [ER_COMPONENT_EE_SYS_VAR_DEREGISTRATION_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot unregister variable '%s'. Please check if it was registered properly in the first place.

- Error number: [MY-013917](#); Symbol: [ER_COMPONENT_EE_FUNCTION_REGISTRATION_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot register function '%s'. Please check if it is not already registered.

- Error number: [MY-013918](#); Symbol: [ER_COMPONENT_EE_FUNCTION_DEREGISTRATION_FAILURE](#); SQLSTATE: [HY000](#)

Message: Cannot unregister function '%s'. Please check if it was registered properly in the first place.

- Error number: [MY-013919](#); Symbol: [ER_COMPONENT_EE_FUNCTION_INVALID_ARGUMENTS](#); SQLSTATE: [HY000](#)

Message: Invalid arguments to function '%s'. Expected values: %s.

- Error number: [MY-013920](#); Symbol: [ER_COMPONENT_EE_FUNCTION_INVALID_ALGORITHM](#); SQLSTATE: [HY000](#)

Message: Invalid algorithm value '%s' in function %s.

- Error number: [MY-013921](#); Symbol: [ER_COMPONENT_EE_FUNCTION_KEY_LENGTH_OUT_OF_RANGE](#); SQLSTATE: [HY000](#)

Message: Invalid key length '%d' for function '%s' with algorithm '%s'. Please provide a value between [%d, %d].

- Error number: [MY-013922](#); Symbol: [ER_COMPONENT_EE_FUNCTION_PRIVATE_KEY_GENERATION_FAILURE](#); SQLSTATE: [HY000](#)

Message: Failed to generate private key of length '%d' with algorithm '%s' in function '%s'. More details about the error would have been logged before this message.

- Error number: [MY-013923](#); Symbol: [ER_COMPONENT_EE_FUNCTION_PUBLIC_KEY_GENERATION_FAILURE](#); SQLSTATE: [HY000](#)

Message: Failed to generate public key with algorithm '%s' for given private key in function '%s'. More details about the error would have been logged before this message.

- Error number: [MY-013924](#); Symbol: [ER_COMPONENT_EE_DATA_LENGTH_OUT_OF_RANGE](#); SQLSTATE: [HY000](#)

Message: Invalid data length '%d' (in bytes) for function '%s' with algorithm '%s'. The maximum support data length for given private key is %d (in bytes).

- Error number: [MY-013925](#); Symbol: [ER_COMPONENT_EE_DATA_ENCRYPTION_ERROR](#); SQLSTATE: [HY000](#)

Message: Could not encrypt data in function '%s' using algorithm '%s'. Data length was '%d' bytes. More details about the error would have been logged before this message.

- Error number: [MY-013926](#); Symbol: [ER_COMPONENT_EE_DATA_DECRYPTION_ERROR](#); SQLSTATE: [HY000](#)

Message: Could not decrypt data in function '%s' using algorithm '%s'. Data length was '%d' bytes. More details about the error would have been logged before this message.

- Error number: [MY-013927](#); Symbol: [ER_COMPONENT_EE_DATA_SIGN_ERROR](#); SQLSTATE: [HY000](#)

Message: Could not sign data in function '%s' using algorithm '%s' and digest type '%s'. More details about the error would have been logged before this message.

- Error number: [MY-013928](#); Symbol: [ER_COMPONENT_EE_OPENSSL_ERROR](#); SQLSTATE: [HY000](#)

Message: Received OpenSSL error in function '%s' for algorithm '%s': '%s'

- Error number: [MY-013929](#); Symbol: [ER_COMPONENT_EE_INSUFFICIENT_LENGTH](#); SQLSTATE: [HY000](#)

Message: In function '%s' with algorithm '%s': insufficient output buffer length '%zu'. Required length '%zu'.

-
- Error number: [MY-013930](#); Symbol: [ER_SYSTEMD_NOTIFY_DEBUG](#); SQLSTATE: [HY000](#)
Message: %s%s
 - Error number: [MY-013931](#); Symbol: [ER_TMP_SESSION_FOR_VAR](#); SQLSTATE: [HY000](#)
Message: Setting session values for system variables only makes sense in a user session (failed to set '%s').
 - Error number: [MY-013932](#); Symbol: [ER_BUILD_ID](#); SQLSTATE: [HY000](#)
Message: BuildID[sha1]=%s
 - Error number: [MY-013933](#); Symbol: [ER_THREAD_POOL_CANNOT_REGISTER_DYNAMIC_PRIVILEGE](#); SQLSTATE: [HY000](#)
Message: Failed to register dynamic privilege %s.
 - Error number: [MY-013934](#); Symbol: [ER_IB_MSG_LOG_WRITER_WAIT_ON_CONSUMER](#); SQLSTATE: [HY000](#)
Message: Redo log writer is waiting for %s redo log consumer which is currently reading LSN=%llu preventing reclamation of subsequent portion of the redo log. Consider increasing innodb_redo_log_capacity.
 - Error number: [MY-013935](#); Symbol: [ER_CONDITIONAL_DEBUG](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-013936](#); Symbol: [ER_IB_MSG_PARSE_OLD_REDO_INDEX_VERSION](#); SQLSTATE: [HY000](#)
Message: Recovery: Generating index information for INSTANT DDL Table in 8.0.29 format
 - Error number: [MY-013941](#); Symbol: [ER_IB_MSG_CLEAR_INSTANT_DROP_COLUMN_METADATA](#); SQLSTATE: [HY000](#)
Message: Failed to clear instant drop column metadata for table %s
 - Error number: [MY-013942](#); Symbol: [ER_COMPONENT_KEYRING_OCI_OPEN_KEY_FILE](#); SQLSTATE: [HY000](#)
Message: Cannot open signing key file %s.
 - Error number: [MY-013943](#); Symbol: [ER_COMPONENT_KEYRING_OCI_CREATE_PRIVATE_KEY](#); SQLSTATE: [HY000](#)
Message: Out of memory! Cannot create private key.
 - Error number: [MY-013944](#); Symbol: [ER_COMPONENT_KEYRING_OCI_READ_KEY_FILE](#); SQLSTATE: [HY000](#)
Message: Cannot read signing key file %s.
 - Error number: [MY-013945](#); Symbol: [ER_NOTE_COMPONENT_KEYRING_OCI_MISSING_NAME_OR_TYPE](#); SQLSTATE: [HY000](#)
Message: Incomplete key: missing Name/Type for the Key: %s.

-
- Error number: [MY-013946](#); Symbol: [ER_WARN_COMPONENT_KEYRING_OCI_DUPLICATE_KEY](#); SQLSTATE: [HY000](#)
 Message: Duplicate key found in keyring with Name: %s and Owner: %s.
 - Error number: [MY-013947](#); Symbol: [ER_KEYRING_OCI_PARSE_JSON](#); SQLSTATE: [HY000](#)
 Message: Error parsing JSON response %s.
 - Error number: [MY-013948](#); Symbol: [ER_KEYRING_OCI_INVALID_JSON](#); SQLSTATE: [HY000](#)
 Message: Invalid JSON response!
 - Error number: [MY-013949](#); Symbol: [ER_KEYRING_OCI_HTTP_REQUEST](#); SQLSTATE: [HY000](#)
 Message: HTTP request failed with error: '%s'
 - Error number: [MY-013950](#); Symbol: [ER_THREAD_POOL_SYSVAR_CHANGE](#); SQLSTATE: [HY000](#)
 Message: Variable thread_pool.%s was updated: %s
 - Error number: [MY-013951](#); Symbol: [ER_STACK_BACKTRACE](#); SQLSTATE: [HY000](#)
 Message: %s
 - Error number: [MY-013952](#); Symbol: [ER_IB_MSG_BUF_POOL_RESIZE_COMPLETE_CUR_CODE](#); SQLSTATE: [HY000](#)
 Message: Status code %u: Completed
 - Error number: [MY-013953](#); Symbol: [ER_IB_MSG_BUF_POOL_RESIZE_PROGRESS_UPDATE](#); SQLSTATE: [HY000](#)
 Message: Status code %u: %u%% complete
 - Error number: [MY-013954](#); Symbol: [ER_IB_MSG_BUF_POOL_RESIZE_CODE_STATUS](#); SQLSTATE: [HY000](#)
 Message: Status code %u: %s
 - Error number: [MY-013955](#); Symbol: [ER_THREAD_POOL_QUERY_THREADS_PER_GROUP_INVALID](#); SQLSTATE: [HY000](#)
 Message: Invalid value set to thread_pool_query_threads_per_group. Valid value range is %u - %u.
 - Error number: [MY-013956](#); Symbol: [ER_THREAD_POOL_QUERY_THRS_PER_GRP_EXCEEDS_TXN_THR_LIMIT](#); SQLSTATE: [HY000](#)
 Message: Query threads count(%u) exceeds transaction threads limit(%u) per group. Please use query threads count per group smaller or equal to max transaction threads limit per group
 - Error number: [MY-013957](#); Symbol: [ER_IB_MSG_INVALID_PAGE_TYPE](#); SQLSTATE: [HY000](#)
 Message: Found page type mismatch. Expected %u, found %u, in page: space_id=%lu page_no= %lu
 - Error number: [MY-013958](#); Symbol: [ER_IB_PARALLEL_READER_WORKER_INFO](#); SQLSTATE: [HY000](#)
 Message: preader: thread_id=%zu, n_threads=%zu, n_ctx=%zu, one_range_per_thread=%s, n_index=%zu, index_list=%s, err=%zu
-

-
- Error number: [MY-013959](#); Symbol: [ER_IB_BULK_LOAD_SUBTREE_INFO](#); SQLSTATE: [HY000](#)
Message: bulkload: space_id=%zu, table=%s, index=%s, height=%zu, n_extents=%zu, n_pages=%zu
 - Error number: [MY-013960](#); Symbol: [ER_IB_BULK_FLUSHER_INFO](#); SQLSTATE: [HY000](#)
Message: bulkflusher: sleep_count=%zu, sleep_duration=%zu milliseconds, total_sleep=%zu milliseconds, pages_flushed=%zu
 - Error number: [MY-013961](#); Symbol: [ER_IB_BUFFER_POOL_OVERUSE](#); SQLSTATE: [HY000](#)
Message: %s: Over 67 percent of the buffer pool (curr_size=%zu MB) is occupied by lock heaps or the adaptive hash index or BUF_BLOCK_MEMORY pages. Check that your transactions do not set too many row locks. Maybe you should make the buffer pool bigger?. Starting the InnoDB Monitor to print diagnostics.
 - Error number: [MY-013962](#); Symbol: [ER_IB_BUFFER_POOL_FULL](#); SQLSTATE: [HY000](#)
Message: %s: Over 95 percent of the buffer pool (curr_size=%zu MB) is occupied by lock heaps or the adaptive hash index or BUF_BLOCK_MEMORY pages. Check that your transactions do not set too many row locks. Maybe you should make the buffer pool bigger?. We intentionally generate a seg fault to print a stack trace on Linux!
 - Error number: [MY-013963](#); Symbol: [ER_IB_DUPLICATE_KEY](#); SQLSTATE: [HY000](#)
Message: %s: table=%s, index=%s, n_uniq=%zu, n_fields=%zu, lhs=(%s), rhs=(%s)
 - Error number: [MY-013964](#); Symbol: [ER_REPLICATION_INCOMPATIBLE_TABLE_WITH_GIPK](#); SQLSTATE: [HY000](#)
Message: Failed to apply row event with %d columns, originating from a server of version %s on table '%s.%s', which has %d columns, one of which is a generated implicit primary key. Replication is unsupported when the source server is older than 8.0.30, the replica table has a generated implicit primary key, and there is a difference in column count, not counting the replica's generated implicit primary key. Align the table schemas on source and replica, and restart replication.
 - Error number: [MY-013965](#); Symbol: [ER_BULK_EXECUTOR_INFO](#); SQLSTATE: [HY000](#)
Message: Bulk executor: %s
 - Error number: [MY-013966](#); Symbol: [ER_BULK_LOADER_INFO](#); SQLSTATE: [HY000](#)
Message: Bulk loader: %s
 - Error number: [MY-013967](#); Symbol: [ER_BULK_LOADER_FILE_CONTAINS_LESS_LINES_THAN_IGNORE_CLAUSE_LOG](#); SQLSTATE: [HY000](#)
Message: The first file being loaded contained less lines than the ignore clause
 - Error number: [MY-013968](#); Symbol: [ER_BULK_READER_INFO](#); SQLSTATE: [HY000](#)
Message: Bulk reader: %s
 - Error number: [MY-013969](#); Symbol: [ER_BULK_READER_LIBCURL_INIT_FAILED_LOG](#); SQLSTATE: [HY000](#)
Message: Bulk reader failed to initialize libcurl

-
- Error number: [MY-013970](#); Symbol: [ER_BULK_READER_LIBCURL_ERROR_LOG](#); SQLSTATE: [HY000](#)
Message: Bulk reader got libcurl error: %s
 - Error number: [MY-013971](#); Symbol: [ER_BULK_READER_SERVER_ERROR_LOG](#); SQLSTATE: [HY000](#)
Message: Bulk reader got error response from server: %ld
 - Error number: [MY-013972](#); Symbol: [ER_BULK_READER_COMMUNICATION_ERROR_LOG](#); SQLSTATE: [HY000](#)
Message: Bulk reader got error in communication with source server, check the error log for additional details
 - Error number: [MY-013973](#); Symbol: [ER_BULK_PARSER_MISSING_ENCLOSED_BY_LOG](#); SQLSTATE: [HY000](#)
Message: Missing ENCLOSED BY character at row %ld in file %s. Add OPTIONALLY to the ENCLOSED BY clause to allow this input.
 - Error number: [MY-013974](#); Symbol: [ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS_EXCEEDED_LOG](#); SQLSTATE: [HY000](#)
Message: The number of input columns that need to be buffered for parsing exceeded predefined buffer max size for file '%s'.
 - Error number: [MY-013975](#); Symbol: [ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED_LOG](#); SQLSTATE: [HY000](#)
Message: The column data that needed to be copied due to escaped characters exceeded the size of the internal copy buffer for file '%s'.
 - Error number: [MY-013976](#); Symbol: [ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT_LOG](#); SQLSTATE: [HY000](#)
Message: Unexpected end of input found at row %ld in file '%s'. Data for some columns is missing.
 - Error number: [MY-013977](#); Symbol: [ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR_LOG](#); SQLSTATE: [HY000](#)
Message: Unexpected row terminator found at row %ld in file '%s'. Data for some columns is missing.
 - Error number: [MY-013978](#); Symbol: [ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENDING_ENCLOSED_BY_LOG](#); SQLSTATE: [HY000](#)
Message: Unexpected characters after ending ENCLOSED BY character found at row %ld in file '%s'.
 - Error number: [MY-013979](#); Symbol: [ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE_LOG](#); SQLSTATE: [HY000](#)
Message: Unexpected characters after NULL escape (\\N) found at row %ld in file '%s'.
 - Error number: [MY-013980](#); Symbol: [ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_TERMINATOR_LOG](#); SQLSTATE: [HY000](#)
Message: Unexpected characters after column terminator found at row %ld in file '%s'.
 - Error number: [MY-013981](#); Symbol: [ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE_LOG](#); SQLSTATE: [HY000](#)

Message: Unexpected end of input found at row %ld in file '%s' resulting in incomplete escape sequence.

- Error number: [MY-013982](#); Symbol: [ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD_LOG](#); SQLSTATE: [HY000](#)

Message: Incorrect %s value: '%s' for column '%s' at row %ld in file '%s'

- Error number: [MY-013983](#); Symbol: [ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL_LOG](#); SQLSTATE: [HY000](#)

Message: NULL supplied to NOT NULL column '%s' at row %ld in file '%s'

- Error number: [MY-013984](#); Symbol: [ER_IB_BULK_LOAD_THREAD_FAIL](#); SQLSTATE: [HY000](#)

Message: %s: LOAD BULK DATA thread failure (err=%lu), table=%s, index=%s

- Error number: [MY-013985](#); Symbol: [ER_IB_BULK_LOAD_MERGE_FAIL](#); SQLSTATE: [HY000](#)

Message: %s: Failed to merge sub-trees in LOAD BULK DATA, table=%s, index=%s, details=%s

- Error number: [MY-013986](#); Symbol: [ER_IB_LOAD_BULK_CONCURRENCY_REDUCED](#); SQLSTATE: [HY000](#)

Message: LOAD BULK DATA: Buffer pool size is %zu. Reducing concurrency from %zu to %zu. table=%s.

- Error number: [MY-013987](#); Symbol: [ER_PLUGIN_EXCEPTION_OPERATION_FAILED](#); SQLSTATE: [HY000](#)

Message: C++ Exception caught while %s the %s plugin: [%s]

- Error number: [MY-013988](#); Symbol: [ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATE_WITH_GR_IN_REPO](#); SQLSTATE: [HY000](#)

Message: Replication configuration appears to be corrupted. On Group Replication channel '%s', setting REQUIRE_TABLE_PRIMARY_KEY_CHECK to 'GENERATE' is not allowed. Run RESET REPLICA ALL to reset it.

- Error number: [MY-013989](#); Symbol: [ER_CHECK_TABLE_INSTANT_VERSION_BIT_SET](#); SQLSTATE: [HY000](#)

Message: Record has both instant and version bit set.

- Error number: [MY-013990](#); Symbol: [ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_OLD_GRP](#); SQLSTATE: [HY000](#)

Message: This member is configured with a group_replication_paxos_single_leader option value of 1 and it is trying to join a group with Communication Protocol Version below 8.0.27. In order to join this group, group_replication_paxos_single_leader value must be configured to the value 0. This member will now exit the group.

- Error number: [MY-013991](#); Symbol: [ER_IB_WRN_IGNORE_REDO_LOG_CAPACITY](#); SQLSTATE: [HY000](#)

Message: Ignored the innodb-redo-log-capacity option in the Innodb read-only mode. Server is using active redo log files.

- Error number: [MY-013992](#); Symbol: [ER_IB_PRIMARY_KEY_IS_INSTANT](#); SQLSTATE: [HY000](#)

Message: Unexpected INSTANTLY Added / Dropped column: '%s' at position %lu for Table '%s', Index '%s' while getting Primary Key for row logging

- Error number: [MY-013993](#); Symbol: [ER_THREAD_POOL_IDLE_CONNECTION_CLOSED](#); SQLSTATE: [HY000](#)
Message: %s
- Error number: [MY-013994](#); Symbol: [ER_IB_HIDDEN_NAME_CONFLICT](#); SQLSTATE: [HY000](#)
Message: Column name %s and internally generated INSTANT DROP column name %s is causing a conflict.
- Error number: [MY-013995](#); Symbol: [ER_IB_DICT_INVALID_COLUMN_POSITION](#); SQLSTATE: [HY000](#)
Message: Field number: %llu too large, Total fields in Record: %zu.
- Error number: [MY-013996](#); Symbol: [ER_IB_DICT_LOG_TABLE_INFO](#); SQLSTATE: [HY000](#)
Message: %s
- Error number: [MY-013997](#); Symbol: [ER_RPL_ASYNC_NEXT_FAILOVER_CHANNEL_SELECTED](#); SQLSTATE: [HY000](#)
Message: The connection has timed out after %lu retries connecting to '%s@%s:%d'%s, and therefore the MySQL server is going to attempt an asynchronous replication connection failover, to '%s@%s:%d'
- Error number: [MY-013998](#); Symbol: [ER_RPL_REPLICA_SOURCE_UUID_HAS_NOT_CHANGED](#); SQLSTATE: [HY000](#)
Message: The Replica which was connected to source '%s:%d', is now connected to new source '%s:%d', but still has the same server_uuid %s.
- Error number: [MY-013999](#); Symbol: [ER_RPL_REPLICA_SOURCE_UUID_HAS_CHANGED_HOST_PORT_UNCHANGED](#); SQLSTATE: [HY000](#)
Message: The server_uuid for source server '%s:%d' has changed from %s to %s. This should not happen unless you have changed it manually.
- Error number: [MY-014000](#); Symbol: [ER_RPL_REPLICA_SOURCE_UUID_HOST_PORT_HAS_CHANGED](#); SQLSTATE: [HY000](#)
Message: The source server has changed from '%s:%d' with server_uuid %s, to '%s:%d' with server_uuid %s.
- Error number: [MY-014001](#); Symbol: [ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_STARTED_FILE_BASED](#); SQLSTATE: [HY000](#)
Message: Replica receiver thread%s: connected to source '%s@%s:%d' with server_uuid=%s, server_id=%d. Starting replication from file '%s', position '%s'.
- Error number: [MY-014002](#); Symbol: [ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_STARTED_GTID_BASED](#); SQLSTATE: [HY000](#)
Message: Replica receiver thread%s: connected to source '%s@%s:%d' with server_uuid=%s, server_id=%d. Starting GTID-based replication.
- Error number: [MY-014003](#); Symbol: [ER_IB_INDEX_LOADER_DONE](#); SQLSTATE: [HY000](#)

Message: Loader::build_all(): Completed building %zu indexes for old_table=%s, new_table=%s, err=%zu.

- Error number: `MY-014004`; Symbol: `ER_IB_INDEX_BUILDER_DONE`; SQLSTATE: `HY000`

Message: Builder::finish(): Completed building index=%s of table=%s, err=%zu.

- Error number: `MY-014005`; Symbol: `ER_WARN_DEPRECATED_USER_DEFINED_COLLATIONS_OPTION`; SQLSTATE: `HY000`

Message: %s: '%s' is a user defined collation. User defined collations are deprecated and will be removed in a future release. Consider using a compiled collation instead.

- Error number: `MY-014006`; Symbol: `ER_IB_INDEX_BUILDER_INIT`; SQLSTATE: `HY000`

Message: Builder::init(): Initialize for building index=%s of table=%s, n_threads=%zu, sort buffer size=%zu bytes, i/o buffer size=%zu bytes.

- Error number: `MY-014007`; Symbol: `ER_IB_SELECT_COUNT_STAR`; SQLSTATE: `HY000`

Message: SELECT COUNT(*) FROM table=%s, n_threads=%zu, n_partitions=%zu.

- Error number: `MY-014008`; Symbol: `ER_IB_INDEX_LOG_VERSION_MISMATCH`; SQLSTATE: `HY000`

Message: Index log version %u did not match. Max index version is %u. Recovery can't continue. Please make sure server is not starting up with the datadir generated in future version.

- Error number: `MY-014009`; Symbol: `ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_MULTIPLE_KEYRING`; SQLSTATE: `HY000`

Message: Multiple keyring component URNs '%s' found in manifest file '%s'. Only one keyring component can be loaded at a time.

- Error number: `MY-014010`; Symbol: `ER_GRP_RPL_HAS_STARTED`; SQLSTATE: `HY000`

Message: Plugin 'group_replication' has been started.

- Error number: `MY-014011`; Symbol: `ER_CHECK_TABLE_MIN_REC_FLAG_SET`; SQLSTATE: `HY000`

Message: Minimum record flag is wrongly set to rec on page '%lu' at level '%lu' for index '%s' of table '%s'.

- Error number: `MY-014012`; Symbol: `ER_CHECK_TABLE_MIN_REC_FLAG_NOT_SET`; SQLSTATE: `HY000`

Message: Minimum record flag is not set to first rec on page '%lu' at level '%lu' for index '%s' of table '%s'.

- Error number: `MY-014013`; Symbol: `ER_NOTE_COMPONENT_SLOT_REGISTRATION_SUCCESS`; SQLSTATE: `HY000`

Message: Successfully registered slot '%d' for component '%s'.

- Error number: `MY-014014`; Symbol: `ER_NOTE_COMPONENT_SLOT_DEREGISTRATION_SUCCESS`; SQLSTATE: `HY000`

Message: Successfully de-registered slot '%d' from component '%s'.

-
- Error number: `MY-014015`; Symbol: `ER_WARN_CANNOT_FREE_COMPONENT_DATA_DEALLOCATION_FAILED`; SQLSTATE: `HY000`
Message: Cannot free resources stored by component '%s' in thread with ID: '%d'. Component failed to free required resources.
 - Error number: `MY-014016`; Symbol: `ER_IB_RESURRECT_TRX_INSERT`; SQLSTATE: `HY000`
Message: Transaction ID: %lu found for resurrecting inserts
 - Error number: `MY-014017`; Symbol: `ER_IB_RESURRECT_TRX_UPDATE`; SQLSTATE: `HY000`
Message: Transaction ID: %lu found for resurrecting updates
 - Error number: `MY-014018`; Symbol: `ER_IB_RESURRECT_IDENTIFY_TABLE_TO_LOCK`; SQLSTATE: `HY000`
Message: Identified table ID: %lu to acquire lock
 - Error number: `MY-014019`; Symbol: `ER_IB_RESURRECT_ACQUIRE_TABLE_LOCK`; SQLSTATE: `HY000`
Message: Acquired lock on table ID: %lu, name: %s
 - Error number: `MY-014020`; Symbol: `ER_IB_RESURRECT_RECORD_PROGRESS`; SQLSTATE: `HY000`
Message: Records read: %lu - Pages read: %lu
 - Error number: `MY-014021`; Symbol: `ER_IB_RESURRECT_RECORD_COMPLETE`; SQLSTATE: `HY000`
Message: Total records resurrected: %lu - Total pages read: %lu - Total tables acquired: %lu
 - Error number: `MY-014022`; Symbol: `ER_IB_RESURRECT_TRX_INSERT_COMPLETE`; SQLSTATE: `HY000`
Message: Resurrected %lu transactions doing inserts.
 - Error number: `MY-014023`; Symbol: `ER_IB_RESURRECT_TRX_UPDATE_COMPLETE`; SQLSTATE: `HY000`
Message: Resurrected %lu transactions doing updates.
 - Error number: `MY-014024`; Symbol: `ER_AUTHENTICATION_OCI_INVALID_TOKEN`; SQLSTATE: `HY000`
Message: Invalid security token provided by '%s' for '%s'@'%s': %s.
 - Error number: `MY-014025`; Symbol: `ER_AUTHENTICATION_OCI_TOKEN_DETAILS_MISMATCH`; SQLSTATE: `HY000`
Message: Unknown user/tenancy (user: %s tenancy: %s) found in security token provided by '%s' for '%s'@'%s'.
 - Error number: `MY-014026`; Symbol: `ER_AUTHENTICATION_OCI_TOKEN_NOT_VERIFIED`; SQLSTATE: `HY000`
Message: Verification failed for security token provided by '%s' for '%s'@'%s' : %s.
 - Error number: `MY-014027`; Symbol: `ER_AUTHENTICATION_OCI_DOWNLOAD_IDDP_PUBLIC_KEY`; SQLSTATE: `HY000`
-

Message: Could not download IDDP Public key. Please check if security token provided by '%s' for '%s'@'%s' is valid.

- Error number: [MY-014029](#); Symbol: [ER_SYS_VAR_REGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot register variable '%s'. Please check if it is not already registered by another component.

- Error number: [MY-014030](#); Symbol: [ER_SYS_VAR_DEREGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot unregister variable '%s'. Please check if it was registered properly in the first place.

- Error number: [MY-014031](#); Symbol: [ER_UDF_REGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot register function '%s'. Please check if it is not already registered by another component.

- Error number: [MY-014032](#); Symbol: [ER_UDF_DEREGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot unregister function '%s'. Please check if it was registered properly in the first place.

- Error number: [MY-014033](#); Symbol: [ER_PRIVILEGE_REGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot register privilege '%s'. Please check if it is not already registered.

- Error number: [MY-014034](#); Symbol: [ER_PRIVILEGE_DEREGISTRATION](#); SQLSTATE: [HY000](#)

Message: Cannot unregister privilege '%s'. Please check if it was registered properly in the first place.

- Error number: [MY-014035](#); Symbol: [ER_UDF_EXEC_FAILURE](#); SQLSTATE: [HY000](#)

Message: Error while executing UDF %s.

- Error number: [MY-014036](#); Symbol: [ER_UDF_EXEC_FAILURE_REASON](#); SQLSTATE: [HY000](#)

Message: Error while executing UDF %s: %s.

- Error number: [MY-014037](#); Symbol: [ER_COMPONENT_SERVICE_CALL](#); SQLSTATE: [HY000](#)

Message: %s failed.

- Error number: [MY-014038](#); Symbol: [ER_COMPONENT_SERVICE_CALL_RESULT](#); SQLSTATE: [HY000](#)

Message: %s failed with %u.

- Error number: [MY-014039](#); Symbol: [ER_COMPONENT_LOCK](#); SQLSTATE: [HY000](#)

Message: Lock failed at %s : %u.

- Error number: [MY-014040](#); Symbol: [ER_COMPONENT_UNLOCK](#); SQLSTATE: [HY000](#)

Message: Lock from %s : %u failed to unlock.

- Error number: [MY-014041](#); Symbol: [ER_COMPONENT_MASKING_OTHER_ERROR](#); SQLSTATE: [HY000](#)

Message: Masking component error: '%s'.

- Error number: [MY-014042](#); Symbol: [ER_COMPONENT_MASKING_ABI](#); SQLSTATE: [HY000](#)

Message: %s failed.

-
- Error number: [MY-014043](#); Symbol: [ER_COMPONENT_MASKING_ABI_REASON](#); SQLSTATE: [HY000](#)
Message: %s failed because %s.
 - Error number: [MY-014044](#); Symbol: [ER_COMPONENT_MASKING_RANDOM_CREATE](#); SQLSTATE: [HY000](#)
Message: Creation of random context failed.
 - Error number: [MY-014045](#); Symbol: [ER_COMPONENT_MASKING_RANDOM_CREATE_REASON](#); SQLSTATE: [HY000](#)
Message: Creation of random context failed because %s.
 - Error number: [MY-014046](#); Symbol: [ER_COMPONENT_MASKING_CANNOT_ACCESS_TABLE](#); SQLSTATE: [HY000](#)
Message: Cannot access %s.%s table.
 - Error number: [MY-014047](#); Symbol: [ER_REDUCED_DBLWR_FILE_CORRUPTED](#); SQLSTATE: [HY000](#)
Message: Cannot recover from detect_only doublewrite buffer as page %u from batch doublewrite file is corrupted.
 - Error number: [MY-014048](#); Symbol: [ER_REDUCED_DBLWR_PAGE_FOUND](#); SQLSTATE: [HY000](#)
Message: Database page corruption of tablespace %s space_id: %u page_num: %u. Cannot recover it from the doublewrite buffer because it was written in detect_only-doublewrite mode.
 - Error number: [MY-014049](#); Symbol: [ER_CONN_INIT_CONNECT_IGNORED_MFA](#); SQLSTATE: [HY000](#)
Message: init_connect variable is ignored for user: %s host: %s due to multi-factor registration required sandboxing
 - Error number: [MY-014050](#); Symbol: [ER_SECONDARY_ENGINE_DDL_FAILED](#); SQLSTATE: [HY000](#)
Message: Execution of alter table %s %s failed because %s.
 - Error number: [MY-014051](#); Symbol: [ER_THREAD_POOL_CONNECTION_REPORT](#); SQLSTATE: [HY000](#)
Message: TP conn (port: managed(delta), active, opened, closed, added, dropped): %s
 - Error number: [MY-014052](#); Symbol: [ER_WARN_SCHEDULED_TASK_RUN_FAILED](#); SQLSTATE: [HY000](#)
Message: Scheduled run of task %s failed
 - Error number: [MY-014053](#); Symbol: [ER_AUDIT_LOG_INVALID_FLUSH_INTERVAL_VALUE](#); SQLSTATE: [HY000](#)
Message: Invalid flush interval specified: %lu. Valid values are 0 (off) or greater than or equal to %d. Adjusting to %d
 - Error number: [MY-014054](#); Symbol: [ER_LOG_CANNOT_PURGE_BINLOG_WITH_BACKUP_LOCK](#); SQLSTATE: [HY000](#)
Message: Could not purge binary logs since another session is executing LOCK INSTANCE FOR BACKUP. Wait for that session to release the lock.
 - Error number: [MY-014055](#); Symbol: [ER_CONVERT_MULTI_VALUE](#); SQLSTATE: [HY000](#)
Message: Multi-values cannot be converted to MySQL format: %s

-
- Error number: [MY-014056](#); Symbol: [ER_IB_DDL_CONVERT_HEAP_NOT_FOUND](#); SQLSTATE: [HY000](#)
Message: Heap required to convert columns is not present.
 - Error number: [MY-014057](#); Symbol: [ER_SERVER_DOWNGRADE_FROM_VERSION](#); SQLSTATE: [HY000](#)
Message: MySQL server downgrading from version '%u' to '%u'.
 - Error number: [MY-014058](#); Symbol: [ER_BEYOND_SERVER_DOWNGRADE_THRESHOLD](#); SQLSTATE: [HY000](#)
Message: Invalid MySQL server downgrade: Cannot downgrade from %u to %u. Target MySQL server version is lower than the server downgrade threshold %u.
 - Error number: [MY-014059](#); Symbol: [ER_BEYOND_SERVER_UPGRADE_THRESHOLD](#); SQLSTATE: [HY000](#)
Message: Invalid MySQL server upgrade: Cannot upgrade from %u to %u. Target MySQL server version is lower than the server upgrade threshold %u.
 - Error number: [MY-014060](#); Symbol: [ER_INVALID_SERVER_UPGRADE_NOT_LTS](#); SQLSTATE: [HY000](#)
Message: Invalid MySQL server upgrade: Cannot upgrade from %u to %u. Upgrade to next major version is only allowed from the last LTS release, which version %u is not.
 - Error number: [MY-014061](#); Symbol: [ER_INVALID_SERVER_DOWNGRADE_NOT_PATCH](#); SQLSTATE: [HY000](#)
Message: Invalid MySQL server downgrade: Cannot downgrade from %u to %u. Downgrade is only permitted between patch releases.
 - Error number: [MY-014062](#); Symbol: [ER_FAILED_GET_DD_PROPERTY](#); SQLSTATE: [HY000](#)
Message: Failed to get the data dictionary property %s.
 - Error number: [MY-014063](#); Symbol: [ER_FAILED_SET_DD_PROPERTY](#); SQLSTATE: [HY000](#)
Message: Failed to set the data dictionary property %s.
 - Error number: [MY-014064](#); Symbol: [ER_SERVER_DOWNGRADE_STATUS](#); SQLSTATE: [HY000](#)
Message: Server downgrade from '%d' to '%d' %s.
 - Error number: [MY-014065](#); Symbol: [ER_INFORMATION_SCHEMA_VERSION_CHANGE](#); SQLSTATE: [HY000](#)
Message: %s information schema from version %u to %u.
 - Error number: [MY-014066](#); Symbol: [ER_PERFORMANCE_SCHEMA_VERSION_CHANGE](#); SQLSTATE: [HY000](#)
Message: %s performance schema from version %u to %u.
 - Error number: [MY-014067](#); Symbol: [ER_WARN_DEPRECATED_OR_BLOCKED_CIPHER](#); SQLSTATE: [HY000](#)
Message: Value for option '%s' contains cipher '%s' that is either blocked or deprecated (and will be removed in a future release). Please refer to the documentation for more details.
 - Error number: [MY-014068](#); Symbol: [ER_IB_MSG_DDL_FAIL_NO_BUILDER](#); SQLSTATE: [HY000](#)

Message: DDL failed as Builder is already freed. Builder: state=%u, error_state=%u. Index: id=%zu, name='%s', space_id=%u, page=%u. Table: old_name='%s', new_name='%s'.

- Error number: [MY-014069](#); Symbol: [ER_GRP_RPL_MEMBER_INFO_DOES_NOT_EXIST](#); SQLSTATE: [HY000](#)

Message: Member identified %s: '%s' does not exist on Group Replication membership during %s.

- Error number: [MY-014070](#); Symbol: [ER_USAGE_DEPRECATION_COUNTER](#); SQLSTATE: [HY000](#)

Message: Deprecated '%s' used %s times, last time used '%s'.

- Error number: [MY-014071](#); Symbol: [ER_WAITING_FOR_NO_CONNECTIONS](#); SQLSTATE: [HY000](#)

Message: Waiting for %u connections to be closed.

- Error number: [MY-014072](#); Symbol: [ER_WAITING_FOR_NO_THDS](#); SQLSTATE: [HY000](#)

Message: Waiting for THDs in partition %u to be closed, %u still left. %u THDs left in total for all partitions.

- Error number: [MY-014073](#); Symbol: [ER_IB_INDEX_PART_TOO_LONG](#); SQLSTATE: [HY000](#)

Message: Index %s of %s.%s exceeds limit of %lu bytes per column.

[ER_IB_INDEX_PART_TOO_LONG](#) was added in 8.4.1.

- Error number: [MY-014078](#); Symbol: [ER_CHECK_TABLE_FUNCTIONS](#); SQLSTATE: [HY000](#)

Message: Can not open table `%s`.`%s`; functions in constraints, partitions, or virtual columns may have failed.

[ER_CHECK_TABLE_FUNCTIONS](#) was added in 8.4.5.

- Error number: [MY-014079](#); Symbol: [ER_CHECK_TABLE_FUNCTIONS_DETAIL](#); SQLSTATE: [HY000](#)

Message: %s

[ER_CHECK_TABLE_FUNCTIONS_DETAIL](#) was added in 8.4.5.

- Error number: [MY-014080](#); Symbol: [ER_GRP_RPL_CERT_BROADCAST_THREAD_CREATE_FAILED](#); SQLSTATE: [HY000](#)

Message: Failed to create the Group Replication certifier broadcast thread (THD_certifier_broadcast).

[ER_GRP_RPL_CERT_BROADCAST_THREAD_CREATE_FAILED](#) was added in 8.4.5.

- Error number: [MY-014081](#); Symbol: [ER_GRP_RPL_CERT_BROADCAST_THREAD_STARTED](#); SQLSTATE: [HY000](#)

Message: The Group Replication certifier broadcast thread (THD_certifier_broadcast) started.

[ER_GRP_RPL_CERT_BROADCAST_THREAD_STARTED](#) was added in 8.4.5.

- Error number: [MY-014082](#); Symbol: [ER_GRP_RPL_CERT_BROADCAST_THREAD_STOPPED](#); SQLSTATE: [HY000](#)

Message: The Group Replication certifier broadcast thread (THD_certifier_broadcast) stopped.

`ER_GRP_RPL_CERT_BROADCAST_THREAD_STOPPED` was added in 8.4.5.

- Error number: `MY-015000`; Symbol: `ER_LANGUAGE_COMPONENT_INFO`; SQLSTATE: `HY000`
Message: %s
- Error number: `MY-015001`; Symbol: `ER_LANGUAGE_COMPONENT_WARNING`; SQLSTATE: `HY000`
Message: %s
- Error number: `MY-015002`; Symbol: `ER_LANGUAGE_COMPONENT_ERROR`; SQLSTATE: `HY000`
Message: %s
- Error number: `MY-015003`; Symbol: `ER_IB_BULK_FLUSHER_PUNCH_HOLE`; SQLSTATE: `HY000`
Message: bulkflusher: Failed to punch hole: table=%s, index=%s, space_id=%zu, page_no=%zu, disk_page_size=%zu, hole_size=%zu, file=%s, err=%zu
- Error number: `MY-015004`; Symbol: `ER_GRP_RPL_CONN_KILLED`; SQLSTATE: `HY000`
Message: %s as the client session was killed.
- Error number: `MY-015005`; Symbol: `ER_WARN_CANT_OPEN_CERTIFICATE`; SQLSTATE: `HY000`
Message: Cannot open certificate %s. Please check the certificate
- Error number: `MY-015006`; Symbol: `ER_FAILED_TO_VALIDATE_CERTIFICATES_SERVER_EXIT`; SQLSTATE: `HY000`
Message: Certificate validation has failed. Stopping the server as tls-certificates-enforced-validation is enabled
- Error number: `MY-015007`; Symbol: `ER_WARN_CA_CERT_VERIFY_FAILED`; SQLSTATE: `HY000`
Message: CA certificate/certificates is invalid. Please check logs for more details.
- Error number: `MY-015008`; Symbol: `ER_WARN_FAILED_TO_SETUP_TLS`; SQLSTATE: `HY000`
Message: Internal TLS error %s:%s:%d:%s
- Error number: `MY-015009`; Symbol: `ER_TLS_LIBRARY_ERROR_INTERNAL`; SQLSTATE: `HY000`
Message: Failed to set up TLS. Check logs for details
- Error number: `MY-015010`; Symbol: `ER_SERVER_CERT_VERIFY_FAILED`; SQLSTATE: `HY000`
Message: Server certificate %s verification has failed. Check logs for more details
- Error number: `MY-015011`; Symbol: `ER_WARN_CERTIFICATE_ERROR_STRING`; SQLSTATE: `HY000`
Message: Failed to validate certificate %s because %s
- Error number: `MY-015012`; Symbol: `ER_TELEMETRY_INFO`; SQLSTATE: `HY000`
Message: %s
- Error number: `MY-015013`; Symbol: `ER_TELEMETRY_WARNING`; SQLSTATE: `HY000`
Message: %s

-
- Error number: [MY-015014](#); Symbol: [ER_TELEMETRY_ERROR](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-015015](#); Symbol: [ER_SRV_START](#); SQLSTATE: [HY000](#)
Message: MySQL Server - start.
 - Error number: [MY-015016](#); Symbol: [ER_SRV_END](#); SQLSTATE: [HY000](#)
Message: MySQL Server - end.
 - Error number: [MY-015017](#); Symbol: [ER_SRV_INIT_START](#); SQLSTATE: [HY000](#)
Message: MySQL Server Initialization - start.
 - Error number: [MY-015018](#); Symbol: [ER_SRV_INIT_END](#); SQLSTATE: [HY000](#)
Message: MySQL Server Initialization - end.
 - Error number: [MY-015019](#); Symbol: [ER_PLUGINS_SHUTDOWN_START](#); SQLSTATE: [HY000](#)
Message: MySQL Server: Plugins Shutdown - start.
 - Error number: [MY-015020](#); Symbol: [ER_PLUGINS_SHUTDOWN_END](#); SQLSTATE: [HY000](#)
Message: MySQL Server: Plugins Shutdown - end.
 - Error number: [MY-015021](#); Symbol: [ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN_START](#); SQLSTATE: [HY000](#)
Message: MySQL Server: Components Shutdown - start.
 - Error number: [MY-015022](#); Symbol: [ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN_END](#); SQLSTATE: [HY000](#)
Message: MySQL Server: Components Shutdown - end (with return value = %d).
 - Error number: [MY-015023](#); Symbol: [ER_CONNECTIONS_SHUTDOWN_START](#); SQLSTATE: [HY000](#)
Message: MySQL Server: Closing Connections - start.
 - Error number: [MY-015024](#); Symbol: [ER_CONNECTIONS_SHUTDOWN_END](#); SQLSTATE: [HY000](#)
Message: MySQL Server: Closing Connections - end.
 - Error number: [MY-015025](#); Symbol: [ER_THREAD_STILL_ALIVE](#); SQLSTATE: [HY000](#)
Message: Waiting for forceful disconnection of Thread (ID %ld) to end.
 - Error number: [MY-015026](#); Symbol: [ER_NUM_THREADS_STILL_ALIVE](#); SQLSTATE: [HY000](#)
Message: Waiting for forceful disconnection of %ld thread(s) to end.
 - Error number: [MY-015027](#); Symbol: [ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_SERVER_ERROR_COMMAND_ERR](#); SQLSTATE: [HY000](#)
Message: Failed to accept a MySQL connection for Group Replication. %s. Please retry.
 - Error number: [MY-015028](#); Symbol: [ER_COMPONENT_KEYRING_OCI_INVALID_CONFIG_VAR](#); SQLSTATE: [HY000](#)

Message: Invalid value of argument %s (%s).

- Error number: [MY-015029](#); Symbol: [ER_WARN_OPTION_RESET_AND_IGNORED_DURING_INITIALIZE](#); SQLSTATE: [HY000](#)

Message: Ignoring a non-default value for %s during --initialize.

- Error number: [MY-015030](#); Symbol: [ER_FIREWALL_SCHEDULER_REGISTER_FAILED](#); SQLSTATE: [HY000](#)

Message: Automatic registration of the scheduler failed.

- Error number: [MY-015031](#); Symbol: [ER_FIREWALL_INVALID_RELOAD_INTERVAL_VALUE](#); SQLSTATE: [HY000](#)

Message: Invalid reload interval specified: %lu. Valid values are 0 (off) or greater than or equal to %d. Adjusting to %d.

- Error number: [MY-015032](#); Symbol: [ER_WARN_DEPRECATED_DYNAMIC_PRIV_FOR_USER](#); SQLSTATE: [HY000](#)

Message: '%s' (granted to '%s@%s') is deprecated and will be removed in a future release.

- Error number: [MY-015033](#); Symbol: [ER_BULK_MULTI_READER_INFO](#); SQLSTATE: [HY000](#)

Message: Bulk Multi Reader: %s

- Error number: [MY-015034](#); Symbol: [ER_BULK_MERGE_LOADER_INFO](#); SQLSTATE: [HY000](#)

Message: Bulk Merge Loader: %s

- Error number: [MY-015035](#); Symbol: [ER_BULK_SORTING_LOADER_INFO](#); SQLSTATE: [HY000](#)

Message: Bulk Sorting Loader: %s

- Error number: [MY-015036](#); Symbol: [ER_BULK_WRITER_INFO](#); SQLSTATE: [HY000](#)

Message: Bulk Writer: %s

- Error number: [MY-015037](#); Symbol: [ER_BULK_WRITER_LIBCURL_INIT_FAILED_LOG](#); SQLSTATE: [HY000](#)

Message: Bulk writer failed to initialize libcurl

- Error number: [MY-015038](#); Symbol: [ER_BULK_WRITER_LIBCURL_ERROR_LOG](#); SQLSTATE: [HY000](#)

Message: Bulk writer got libcurl error: %s

- Error number: [MY-015039](#); Symbol: [ER_IB_WRONG_PAGE_ID](#); SQLSTATE: [HY000](#)

Message: Detected wrong page_id: buf_block_t[space_id=%zu, page_no=%zu], buf_frame_t[space_id=%zu, page_no=%zu], file=%s

- Error number: [MY-015040](#); Symbol: [ER_IB_FIXED_PAGE_ID](#); SQLSTATE: [HY000](#)

Message: Fixed wrong page_id with sync read: buf_block_t[space_id=%zu, page_no=%zu], buf_frame_t[space_id=%zu, page_no=%zu], file=%s, retry=%zu

- Error number: [MY-015041](#); Symbol: [ER_IB_WRONG_PAGEID_AFTER_SYNC_READ](#); SQLSTATE: [HY000](#)

Message: Wrong page_id after sync read: buf_block_t[space_id=%zu, page_no=%zu],
buf_frame_t[space_id=%zu, page_no=%zu], file=%s, retry=%zu

- Error number: [MY-015042](#); Symbol: [ER_IB_SYNC_READ_FAILED](#); SQLSTATE: [HY000](#)

Message: Sync read to fix wrong page_id failed: buf_block_t[space_id=%zu, page_no=%zu], file=%s,
err=%zu, retry=%zu

- Error number: [MY-015043](#); Symbol: [ER_START_REPLICA_CHANNEL_INVALID_CONFIGURATION_LOG](#); SQLSTATE: [HY000](#)

Message: Cannot start replication channel '%s' because %s.

- Error number: [MY-015044](#); Symbol: [ER_GROUP_REPLICATION_CERTIFIER_MESSAGE_LARGE](#); SQLSTATE: [HY000](#)

Message: The certification information, part of the required information to the new member join the group, is too big and cannot be send. Please wait until the value of the column COUNT_TRANSACTIONS_ROWS_VALIDATING of the table performance_schema.replication_group_member_stats decreases and try to join the new member again.

- Error number: [MY-015045](#); Symbol: [ER_GROUP_REPLICATION_METADATA_SENDER_IS_REMOTE](#); SQLSTATE: [HY000](#)

Message: The member %s:%u will be the one sending the recovery metadata message.

- Error number: [MY-015046](#); Symbol: [ER_GROUP_REPLICATION_METADATA_SENDER](#); SQLSTATE: [HY000](#)

Message: This member %s:%u will be the one sending the recovery metadata message.

- Error number: [MY-015047](#); Symbol: [ER_GROUP_REPLICATION_ERROR_COMPRESS_INITIALIZE](#); SQLSTATE: [HY000](#)

Message: Error initializing the %s compression context. Data cannot be compressed.

- Error number: [MY-015048](#); Symbol: [ER_GROUP_REPLICATION_COMPRESS_PROCESS](#); SQLSTATE: [HY000](#)

Message: Error while compressing data using %s compression. Data cannot be decompressed.

- Error number: [MY-015049](#); Symbol: [ER_GROUP_REPLICATION_UNKOWN_COMPRESSION_TYPE](#); SQLSTATE: [HY000](#)

Message: Error unknown Compression Library requested.

- Error number: [MY-015050](#); Symbol: [ER_GROUP_REPLICATION_COMPRESS_EXCEEDS_MAX_SIZE](#); SQLSTATE: [HY000](#)

Message: Error while compressing data using %s compression. The operation could not be performed as buffer size exceeded configured maximum size. Please wait until the value of the column COUNT_TRANSACTIONS_ROWS_VALIDATING of the table performance_schema.replication_group_member_stats decreases and try to join the new member again.

- Error number: [MY-015051](#); Symbol: [ER_GROUP_REPLICATION_COMPRESS_OUT_OF_MEMORY](#); SQLSTATE: [HY000](#)

Message: Error while compressing data using %s compression. The operation could not be performed as memory allocation failed.

- Error number: [MY-015052](#); Symbol: [ER_GROUP_REPLICATION_ERROR_DECOMPRESS_INITIALIZE](#); SQLSTATE: [HY000](#)

Message: Error initializing the %s decompression context. Data cannot be decompressed.

- Error number: [MY-015053](#); Symbol: [ER_GROUP_REPLICATION_DECOMPRESS_EXCEEDS_MAX_SIZE](#); SQLSTATE: [HY000](#)

Message: Error while decompressing data using %s compression. The operation could not be performed as buffer size exceeded configured maximum size. Please wait until the value of the column `COUNT_TRANSACTIONS_ROWS_VALIDATING` of the table `performance_schema.replication_group_member_stats` decreases and try to join the new member again.

- Error number: [MY-015054](#); Symbol: [ER_GROUP_REPLICATION_DECOMPRESS_OUT_OF_MEMORY](#); SQLSTATE: [HY000](#)

Message: Error while decompressing data using %s compression. The operation could not be performed as memory allocation failed.

- Error number: [MY-015055](#); Symbol: [ER_GROUP_REPLICATION_DECOMPRESS_TRUNCATED](#); SQLSTATE: [HY000](#)

Message: Error while decompressing data using %s compression. The operation could not be performed as all the input provided to decompress is consumed, but the decompressed output produced is less than required.

- Error number: [MY-015056](#); Symbol: [ER_GROUP_REPLICATION_DECOMPRESS_CORRUPTED](#); SQLSTATE: [HY000](#)

Message: Error while decompressing data using %s compression. The operation could not be performed as the compression library reported an error.

- Error number: [MY-015057](#); Symbol: [ER_GROUP_REPLICATION_DECOMPRESS_END](#); SQLSTATE: [HY000](#)

Message: Error while decompressing data using %s compression. The operation could not be performed as no more input bytes remaining to decompress. The decompressed output has not been changed.

- Error number: [MY-015058](#); Symbol: [ER_GROUP_REPLICATION_DECOMPRESS_PROCESS](#); SQLSTATE: [HY000](#)

Message: Error while decompressing data using %s compression. Data cannot be decompressed.

- Error number: [MY-015059](#); Symbol: [ER_GRP_RPL_VCLE_NOT_BEING_LOGGED](#); SQLSTATE: [HY000](#)

Message: `View_change_log_event` will not be logged further on the binary log, as all members of the group are 8.3.0 or greater.

- Error number: [MY-015060](#); Symbol: [ER_GROUP_REPLICATION_METADATA_PROTOBUF_PARSING](#); SQLSTATE: [HY000](#)

Message: Error while parsing serialized `Certification_info` from received Recovery Metadata to Protobuf format using Protobuf library.

-
- Error number: `MY-015061`; Symbol: `ER_GROUP_REPLICATION_PROTOBUF_SERIALIZING_ERROR`; SQLSTATE: `HY000`

Message: Error while serializing % data using Protobuf library.
 - Error number: `MY-015062`; Symbol: `ER_GROUP_REPLICATION_ERROR_RECEIVED_WAITING_METADATA`; SQLSTATE: `HY000`

Message: Error received while the Recovery thread was waiting for the Recovery Metadata. The Recovery will be terminated.
 - Error number: `MY-015063`; Symbol: `ER_GROUP_REPLICATION_TIMEOUT_ERROR_FETCHING_METADATA`; SQLSTATE: `HY000`

Message: Error fetching AFTER_GTIDS from Recovery Metadata by Recovery thread. The Recovery thread timeout after waiting for %d seconds. The Recovery will be terminated.
 - Error number: `MY-015064`; Symbol: `ER_GROUP_REPLICATION_METADATA_PAYLOAD_EMPTY`; SQLSTATE: `HY000`

Message: Error while decoding the received Recovery Metadata Message. The received payload is empty which could be due to error in decoding of received Recovery Metadata Message. The joining member will leave the group.
 - Error number: `MY-015065`; Symbol: `ER_GROUP_REPLICATION_METADATA_MESSAGE_PAYLOAD_EMPTY`; SQLSTATE: `HY000`

Message: The %s payload type of the received Recovery Metadata Message is empty.
 - Error number: `MY-015066`; Symbol: `ER_GROUP_REPLICATION_METADATA_READ_GTID_EXECUTED`; SQLSTATE: `HY000`

Message: Error reading gtid_executed from the received Recovery Metadata Message.
 - Error number: `MY-015067`; Symbol: `ER_GROUP_REPLICATION_METADATA_PAYLOAD_DECODING`; SQLSTATE: `HY000`

Message: Error while decoding the received Recovery Metadata Message.
 - Error number: `MY-015068`; Symbol: `ER_GROUP_REPLICATION_METADATA_SEND_ERROR`; SQLSTATE: `HY000`

Message: The group was unable to send the Recovery Metadata to a joining member.
 - Error number: `MY-015069`; Symbol: `ER_GROUP_REPLICATION_METADATA_SAVE_RECOVERY_COPY`; SQLSTATE: `HY000`

Message: Error while saving copy of Recovery Metadata Message.
 - Error number: `MY-015070`; Symbol: `ER_GROUP_REPLICATION_METADATA_CERT_INFO_ERROR_PROCESSING`; SQLSTATE: `HY000`

Message: Error while processing received Certification Information from the Recovery Metadata Message.
-

-
- Error number: `MY-015071`; Symbol: `ER_GROUP_REPLICATION_METADATA_CERT_INFO_PACKET_EMPTY`; SQLSTATE: `HY000`
Message: Error Certification Information packet from the received Recovery Metadata Message is empty.
 - Error number: `MY-015072`; Symbol: `ER_GROUP_REPLICATION_METADATA_ERROR_ON_SEND_ERROR_MESSAGE`; SQLSTATE: `HY000`
Message: Error while sending Recovery metadata error message. If this is a temporary failure of send message and member itself hasn't left the group, then joiner will timeout waiting for Recovery metadata message. If this is a permanent failure, the member will leave the group and another member will send the Recovery metadata message.
 - Error number: `MY-015073`; Symbol: `ER_GROUP_REPLICATION_METADATA_SET_IN_RECOVERY_FAILED`; SQLSTATE: `HY000`
Message: Error when transferring Recovery Metadata Message to Recovery. The joining member will leave the group.
 - Error number: `MY-015074`; Symbol: `ER_GROUP_REPLICATION_CERTIFICATION_MODULE_FAILURE`; SQLSTATE: `HY000`
Message: Error Certification module wasn't properly initialized.
 - Error number: `MY-015075`; Symbol: `ER_GROUP_REPLICATION_METADATA_INITIALIZATION_FAILURE`; SQLSTATE: `HY000`
Message: Error Recovery Metadata Message module wasn't properly initialized.
 - Error number: `MY-015076`; Symbol: `ER_GROUP_REPLICATION_METADATA_MEMORY_ALLOC`; SQLSTATE: `HY000`
Message: Error while %s. The operation could not be performed as memory allocation failed.
 - Error number: `MY-015077`; Symbol: `ER_GROUP_REPLICATION_RECOVERY_SKIPPED_GTID_PRESENT`; SQLSTATE: `HY000`
Message: The group replication recovery is skipped as the joiner's gtid executed set %s already has all the transactions of the donor's gtid set %s.
 - Error number: `MY-015078`; Symbol: `ER_GROUP_REPLICATION_RECOVERY_FETCHING_GTID_EXECUTED_SET`; SQLSTATE: `HY000`
Message: Error in Group Replication Recovery while getting member's global GTID executed set.
 - Error number: `MY-015079`; Symbol: `ER_GROUP_REPLICATION_RECOVERY_ERROR_ADD_GTID_EXECUTED`; SQLSTATE: `HY000`
Message: Error in Group Replication Recovery while adding GTIDs in string format to Gtid_set.
 - Error number: `MY-015080`; Symbol: `ER_GROUP_REPLICATION_RECOVERY_METADATA_SENDER_NOT_FOUND`; SQLSTATE: `HY000`
Message: Error computing the current Recovery metadata sender. Check if this MEMBER is not leaving the group and the joiner is able to successfully fetch the recovery metadata or not.
 - Error number: `MY-015081`; Symbol: `ER_GROUP_REPLICATION_METADATA_CERT_INFO_PACKET_COUNT_ERROR`; SQLSTATE: `HY000`

Message: Error in the received Recovery Metadata Message the number of compressed Certification Information packet count mismatch with the number of sent compressed Certification Information packets.

- Error number: `MY-015082`; Symbol: `ER_GROUP_REPLICATION_METADATA_CERT_INFO_ENCODING_ERROR`; SQLSTATE: `HY000`

Message: Error while encoding Certification Information for the Recovery Metadata Message.

- Error number: `MY-015083`; Symbol: `ER_GROUP_REPLICATION_METADATA_NO_VALID_DONOR`; SQLSTATE: `HY000`

Message: There are no valid recovery metadata donors. The joining member will leave the group.

- Error number: `MY-015084`; Symbol: `ER_GROUP_REPLICATION_NO_CERTIFICATION_DONOR_AVAILABLE`; SQLSTATE: `HY000`

Message: No donor available to provide the certification information, part of the required information to the new member join the group. Please wait until there are ONLINE members on the group and try to join the new member again.

- Error number: `MY-015085`; Symbol: `ER_GROUP_REPLICATION_RECOVERY_STOPPED_GTID_PRESENT`; SQLSTATE: `HY000`

Message: The group replication recovery is complete, joiner gtid executed set has all the transactions of the donor's gtid set %s.

- Error number: `MY-015086`; Symbol: `ER_RPL_ASYNC_CHECK_CONNECTION_ERROR`; SQLSTATE: `HY000`

Message: The Monitor IO thread encountered an error while executing the query to check connection to the source server. Error: %s. The query failed to execute on the source (host:%s port:%u network_namespace:%s) for channel '%s'.

- Error number: `MY-015087`; Symbol: `ER_RPL_ASYNC_MONITOR_IO_THD_FETCH_GROUP_MAJORITY_ERROR`; SQLSTATE: `HY000`

Message: The Monitor IO thread failed to detect if the source belongs to the group majority. Error: %s. The query failed to execute on the source (host:%s port:%u network_namespace:%s) for channel '%s'.

- Error number: `MY-015088`; Symbol: `ER_RPL_ASYNC_REPLICA_IO_THD_FETCH_GROUP_MAJORITY_ERROR`; SQLSTATE: `HY000`

Message: The replica IO thread failed to detect if the source belongs to the group majority. Error: %s. The query failed to execute on the source (host:%s port:%u network_namespace:%s) for channel '%s'.

- Error number: `MY-015089`; Symbol: `ER_RPL_ASYNC_GET_GROUP_MEMBERSHIP_DETAILS_ERROR`; SQLSTATE: `HY000`

Message: The Monitor IO thread failed to get group membership details. Error: %s. The query failed to execute on the source (host:%s port:%u network_namespace:%s) for channel '%s'.

- Error number: `MY-015090`; Symbol: `ER_IB_ERR_CORRUPT_TABLESPACE_UNRECOVERABLE`; SQLSTATE: `HY000`

Message: Tablespace '%u' mentioned in the redo log is corrupted in a way it is unrecoverable by double-write buffer, so further redo log recovery is not possible!

-
- Error number: [MY-015091](#); Symbol: [ER_IB_BULK_LOAD_STATS_WARN](#); SQLSTATE: [HY000](#)
Message: %s: Failed to save statistics for table=%s err=%zu
 - Error number: [MY-015092](#); Symbol: [ER_COMPONENT_MASKING_INVALID_FLUSH_INTERVAL_VALUE](#); SQLSTATE: [HY000](#)
Message: Invalid flush interval specified: %lu. Valid values are 0 (off) or greater than or equal to %d. Adjusting to %d.
 - Error number: [MY-015093](#); Symbol: [ER_COMPONENT_MASKING_VAR_REGISTRATION_FAILURE](#); SQLSTATE: [HY000](#)
Message: Cannot register variable '%s'.'%s'.
 - Error number: [MY-015094](#); Symbol: [ER_COMPONENT_MASKING_NOTIFICATION_REGISTRATION_FAILURE](#); SQLSTATE: [HY000](#)
Message: Masking component failed to register notification service. Periodical masking dictionaries flush will not work.
 - Error number: [MY-015095](#); Symbol: [ER_GRP_RPL_MSG_DECODING_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to decode Group Replication message: %s. Reason : %s
 - Error number: [MY-015096](#); Symbol: [ER_GRP_RPL_APPLIER_ERROR_PACKET_RECEIVED](#); SQLSTATE: [HY000](#)
Message: The Applier process of Group Replication found an error and was requested to stop: %s
 - Error number: [MY-015097](#); Symbol: [ER_LANGUAGE_COMPONENT_INSTALL_ERROR](#); SQLSTATE: [HY000](#)
Message: Cannot install the component.
 - Error number: [MY-015098](#); Symbol: [ER_WARN_LANGUAGE_COMPONENT_CANNOT_UNINSTALL](#); SQLSTATE: [HY000](#)
Message: Cannot uninstall the language component: %s.
 - Error number: [MY-015099](#); Symbol: [ER_LANGUAGE_COMPONENT_SERVER_ERROR](#); SQLSTATE: [HY000](#)
Message: Calling component service: %s.
 - Error number: [MY-015100](#); Symbol: [ER_LANGUAGE_COMPONENT_INTERNAL_ERROR](#); SQLSTATE: [HY000](#)
Message: Internal error while %s.
 - Error number: [MY-015101](#); Symbol: [ER_LANGUAGE_COMPONENT_VM_API_FUNCTION_ERROR](#); SQLSTATE: [HY000](#)
Message: Internal VM API function failed: %s.
 - Error number: [MY-015102](#); Symbol: [ER_LANGUAGE_COMPONENT_VM_INTERNAL_ERROR](#); SQLSTATE: [HY000](#)
Message: Internal VM error while %s.

-
- Error number: [MY-015103](#); Symbol: [ER_WARN_LANGUAGE_COMPONENT_RESOURCE_LIMIT](#); SQLSTATE: [HY000](#)
Message: The resource limit has been exceeded. Details: %s.
 - Error number: [MY-015104](#); Symbol: [ER_BLOCKED_CIPHER](#); SQLSTATE: [HY000](#)
Message: Value for option '%s' contains cipher '%s' that is blocked. Please refer to the documentation for allowed ciphers.
 - Error number: [MY-015105](#); Symbol: [ER_KEYRING_COMPONENT_KEYRING_FILE_NAME_EMPTY](#); SQLSTATE: [HY000](#)
Message: Keyring file path is empty in configuration file.
 - Error number: [MY-015106](#); Symbol: [ER_KEYRING_COMPONENT_KEYRING_FILE_READ_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to read keyring file: %s.
 - Error number: [MY-015107](#); Symbol: [ER_KEYRING_COMPONENT_KEYRING_FILE_DECRYPT_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to decrypt keyring file: %s.
 - Error number: [MY-015108](#); Symbol: [ER_KEYRING_COMPONENT_KEYRING_FILE_INVALID_FORMAT](#); SQLSTATE: [HY000](#)
Message: The keyring file content is not in a valid JSON format.
 - Error number: [MY-015109](#); Symbol: [ER_KEYRING_COMPONENT_KEYRING_FILE_JSON_EXTRACT_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to extract a valid JSON data from keyring file.
 - Error number: [MY-015110](#); Symbol: [ER_KEYRING_COMPONENT_KEYRING_FILE_KEY_EXTRACT_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to extract key from keyring file JSON data.
 - Error number: [MY-015111](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_NOT_INITIALIZED](#); SQLSTATE: [HY000](#)
Message: Keyring component is not initialized.
 - Error number: [MY-015112](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_EMPTY_DATA_ID](#); SQLSTATE: [HY000](#)
Message: Provided Data ID is empty.
 - Error number: [MY-015113](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ITERATOR_INIT_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to initialize metadata iterator.
 - Error number: [MY-015114](#); Symbol: [ER_NOTE_KEYRING_COMPONENT_KEY_READ_ITERATOR_INIT_FAILED](#); SQLSTATE: [HY000](#)
Message: Failed to initialize key reader iterator.

-
- Error number: `MY-015115`; Symbol: `ER_NOTE_KEYRING_COMPONENT_KEY_READ_ITERATOR_FETCH_FAILED`; SQLSTATE: `HY000`
Message: Failed to read key from key reader iterator.
 - Error number: `MY-015116`; Symbol: `ER_BACKGROUND_HISTOGRAM_UPDATE`; SQLSTATE: `HY000`
Message: %*s
 - Error number: `MY-015117`; Symbol: `ER_IB_MSG_SUBMIT_DETAILED_BUG_REPORT`; SQLSTATE: `HY000`
Message: Submit a detailed bug report to <http://bugs.mysql.com>
 - Error number: `MY-015118`; Symbol: `ER_AUTO_INCREMENT_NOT_SUPPORTED_FOR_FLOAT_DOUBLE`; SQLSTATE: `HY000`
Message: AUTO_INCREMENT is not supported with DOUBLE/FLOAT field. Please consider fixing (Schema:%s, Table:%s, Column:%s).
 - Error number: `MY-015119`; Symbol: `ER_SERVER_DOWNGRADE_SYS_SCHEMA`; SQLSTATE: `HY000`
Message: Downgrading the sys schema.
 - Error number: `MY-015120`; Symbol: `ER_SERVER_DOWNGRADE_HELP_TABLE_STATUS`; SQLSTATE: `HY000`
Message: Downgrade of help tables %s.
 - Error number: `MY-015121`; Symbol: `ER_KEYRING_MIGRATE_SKIPPED_KEY`; SQLSTATE: `HY000`
Message: Could not find data pointed by data_id: %s, auth_id: %s. Skipping.
 - Error number: `MY-015122`; Symbol: `ER_KEYRING_MIGRATE_MEMORY_DEALLOCATION_FAILED`; SQLSTATE: `HY000`
Message: Failed to deallocate reader_object.
 - Error number: `MY-015123`; Symbol: `ER_LOG_CLIENT_INTERACTION_TIMEOUT`; SQLSTATE: `HY000`
Message: A connection from %s was closed by the server due to a timeout in the communication layer (vio:%d, packet:%d) %ld seconds after the last command started. Currently configured wait_timeout is %ld seconds.
 - Error number: `MY-015124`; Symbol: `ER_GRP_RPL_PREEMPTIVE_GARBAGE_COLLECTION_DIFF_FROM_GRP`; SQLSTATE: `HY000`
Message: The member is configured with a group_replication_preemptive_garbage_collection option value '%d' different from the group '%d'. The member will now exit the group.
 - Error number: `MY-015125`; Symbol: `ER_IB_LONG_ROLLBACK_FULL`; SQLSTATE: `HY000`
Message: Still rolling back transaction %llu; %llu undo records rolled back out of %llu total (%lu%% complete). Transaction info: last state: %s
 - Error number: `MY-015126`; Symbol: `ER_IB_LONG_ROLLBACK`; SQLSTATE: `HY000`
Message: Still rolling back transaction %llu; %llu undo records rolled back out of %llu total (%lu%% complete).

-
- Error number: [MY-015127](#); Symbol: [ER_INVALID_FILE_FORMAT](#); SQLSTATE: [HY000](#)
Message: Invalid format of file '%s'.
 - Error number: [MY-015128](#); Symbol: [ER_LOG_SANITIZATION](#); SQLSTATE: [HY000](#)
Message: Relay log sanitization: %s
 - Error number: [MY-015129](#); Symbol: [ER_WARN_LOG_DEPRECATED_NON_STANDARD_KEY](#); SQLSTATE: [HY000](#)
Message: Foreign key '%s' on table '%s'.'%s' refers to non-unique key or partial key. This is deprecated and will be removed in a future release.
 - Error number: [MY-015130](#); Symbol: [ER_THREAD_POOL_MTL_DISABLE](#); SQLSTATE: [HY000](#)
Message: Disabling MTL in thread group %u since it has %u (=MTL per group) long running transactions.
 - Error number: [MY-015131](#); Symbol: [ER_THREAD_POOL_MTL_REENABLE](#); SQLSTATE: [HY000](#)
Message: Re-enabling MTL in thread group %u since it is down to %u long running transactions.
 - Error number: [MY-015132](#); Symbol: [ER_LOG_PARTITION_PREFIX_KEY_NOT_SUPPORTED](#); SQLSTATE: [HY000](#)
Message: Column '%s.%s.%s' having prefix key part '%s(%u)' in the PARTITION BY KEY() clause is not supported.
 - Error number: [MY-015133](#); Symbol: [ER_LDAP_AUTH_INFO_USER_MAP](#); SQLSTATE: [HY000](#)
Message: Login user: %s@%s (external: %s) authenticated as: %s
 - Error number: [MY-015134](#); Symbol: [ER_ACCESS_DENIED_NO_PROXY_GRANT_WITH_NAME](#); SQLSTATE: [HY000](#)
Message: Access denied for user '%s'@'%s', missing proxy privilege to '%s'.
 - Error number: [MY-015135](#); Symbol: [ER_ACCESS_DENIED_NO_PROXY_WITH_NAME](#); SQLSTATE: [HY000](#)
Message: Access denied for user '%s'@'%s', proxied user '%s' doesn't exist.
 - Error number: [MY-015136](#); Symbol: [ER_GRP_RPL_RECOVERY_WAIT_APPLIER_BACKLOG_START](#); SQLSTATE: [HY000](#)
Message: Distributed recovery will wait until the transactions '%s' contained on the 'group_replication_applier' channel are applied.
 - Error number: [MY-015137](#); Symbol: [ER_GRP_RPL_RECOVERY_WAIT_APPLIER_BACKLOG_FINISH](#); SQLSTATE: [HY000](#)
Message: Distributed recovery finished applying the transactions '%s' contained on the 'group_replication_applier' channel.
 - Error number: [MY-015138](#); Symbol: [ER_BULK_READER_ZSTD_ERROR_LOG](#); SQLSTATE: [HY000](#)
Message: ZSTD decompression failed: %s

-
- Error number: [MY-015139](#); Symbol: [ER_SECONDARY_ENGINE_DDL_TRACK_PROGRESS](#); SQLSTATE: [HY000](#)
Message: %s
 - Error number: [MY-015140](#); Symbol: [ER_IB_MSG_INNODB_FLUSH_METHOD](#); SQLSTATE: [HY000](#)
Message: Using innodb_flush_method=%s
 - Error number: [MY-015141](#); Symbol: [ER_BULK_SCANNER_INFO](#); SQLSTATE: [HY000](#)
Message: Bulk Scanner: %s
[ER_BULK_SCANNER_INFO](#) was added in 8.4.1.
 - Error number: [MY-015142](#); Symbol: [ER_LOG_DEPRECATED_NON_COMPOSABLE_MULTIPLE_ENGINE](#); SQLSTATE: [HY000](#)
Message: Combining the storage engines %s and %s is deprecated, but the statement or transaction updates both the %s table %s.%s and the %s table %s.%s.
[ER_LOG_DEPRECATED_NON_COMPOSABLE_MULTIPLE_ENGINE](#) was added in 8.4.1.
 - Error number: [MY-015143](#); Symbol: [ER_DD_UPDATE_DATADIR_FLAG_FAIL](#); SQLSTATE: [HY000](#)
Message: Failed to update data directory flag for dd table with tablespace id '%llu' when ibd file for '%s' is moved to new location '%s' during server shutdown
[ER_DD_UPDATE_DATADIR_FLAG_FAIL](#) was added in 8.4.1.
 - Error number: [MY-015144](#); Symbol: [ER_IB_MSG_FIL_STATE_MOVED_PREV](#); SQLSTATE: [HY000](#)
Message: %s DD ID: %llu - Tablespace %u, name '%s', found at '%s' outside default data directory, but DD misses info about DATA DIRECTORY
[ER_IB_MSG_FIL_STATE_MOVED_PREV](#) was added in 8.4.1.
 - Error number: [MY-015144](#); Symbol: [ER_IB_MSG_FIL_STATE_MOVED_PREV_OR_HAS_DATADIR](#); SQLSTATE: [HY000](#)
Message: %s DD ID: %llu - Tablespace %u, name '%s', found at '%s' outside default data directory. It is either moved or is created with 'DATA DIRECTORY'
[ER_IB_MSG_FIL_STATE_MOVED_PREV_OR_HAS_DATADIR](#) was added in 8.4.2, removed after 8.4.3.
 - Error number: [MY-015145](#); Symbol: [ER_RPL_KILL_OLD_DUMP_THREAD_ENCOUNTERED](#); SQLSTATE: [HY000](#)
Message: Upon reconnection with the replica, while initializing the dump thread for %s <%s>, an existing dump thread with the same %s was detected. The source is terminating the previous dump thread (%u), which is normal and expected.
[ER_RPL_KILL_OLD_DUMP_THREAD_ENCOUNTERED](#) was added in 8.4.4.
 - Error number: [MY-015146](#); Symbol: [ER_RPL_MTA_ALLOW_COMMIT_OUT_OF_ORDER](#); SQLSTATE: [HY000](#)
Message: The transaction '%s' will commit out of order with respect to its source to follow the group global order.

`ER_RPL_MTA_ALLOW_COMMIT_OUT_OF_ORDER` was added in 8.4.4.

Chapter 3 Client Error Message Reference

Client error messages originate from within the MySQL client library. Here is an example client error message, as displayed by the `mysql` client:

```
$> mysql -h no-such-host
ERROR 2005 (HY000): Unknown MySQL server host 'no-such-host' (0)
```

Each client error message includes an error code, SQLSTATE value, and message string, as described in [Error Message Sources and Elements](#). These elements are available as described in [Error Information Interfaces](#). For client errors, the SQLSTATE value is always 'HY000' (general error), so it is not meaningful for distinguishing one client error from another.

The client library also makes available to host client programs any errors that originate on the server side and are received by the client from the server. For a list of server-side errors, see [Chapter 2, Server Error Message Reference](#).

In addition to the errors in the following list, the client library can also produce error messages that have error codes in the range from 1 to 999. See [Chapter 4, Global Error Message Reference](#)

- Error number: 2000; Symbol: `CR_UNKNOWN_ERROR`;
Message: Unknown MySQL error
- Error number: 2001; Symbol: `CR_SOCKET_CREATE_ERROR`;
Message: Can't create UNIX socket (%d)
- Error number: 2002; Symbol: `CR_CONNECTION_ERROR`;
Message: Can't connect to local MySQL server through socket '%s' (%d)
- Error number: 2003; Symbol: `CR_CONN_HOST_ERROR`;
Message: Can't connect to MySQL server on '%s:%u' (%d)
- Error number: 2004; Symbol: `CR_IPSOCK_ERROR`;
Message: Can't create TCP/IP socket (%d)
- Error number: 2005; Symbol: `CR_UNKNOWN_HOST`;
Message: Unknown MySQL server host '%s' (%d)
- Error number: 2006; Symbol: `CR_SERVER_GONE_ERROR`;
Message: MySQL server has gone away
- Error number: 2007; Symbol: `CR_VERSION_ERROR`;
Message: Protocol mismatch; server version = %d, client version = %d
- Error number: 2008; Symbol: `CR_OUT_OF_MEMORY`;
Message: MySQL client ran out of memory
- Error number: 2009; Symbol: `CR_WRONG_HOST_INFO`;
Message: Wrong host info

-
- Error number: [2010](#); Symbol: [CR_LOCALHOST_CONNECTION](#);

Message: Localhost via UNIX socket

- Error number: [2011](#); Symbol: [CR_TCP_CONNECTION](#);

Message: %s via TCP/IP

- Error number: [2012](#); Symbol: [CR_SERVER_HANDSHAKE_ERR](#);

Message: Error in server handshake

- Error number: [2013](#); Symbol: [CR_SERVER_LOST](#);

Message: Lost connection to MySQL server during query

- Error number: [2014](#); Symbol: [CR_COMMANDS_OUT_OF_SYNC](#);

Message: Commands out of sync; you can't run this command now

Commands were executed in an improper order. This error occurs when a function is called that is not appropriate for the current state of the connection. For example, if `mysql_stmt_fetch()` is not called enough times to read an entire result set (that is, enough times to return `MYSQL_NO_DATA`), this error may occur for the following C API call.

- Error number: [2015](#); Symbol: [CR_NAMEDPIPE_CONNECTION](#);

Message: Named pipe: %s

- Error number: [2016](#); Symbol: [CR_NAMEDPIPEWAIT_ERROR](#);

Message: Can't wait for named pipe to host: %s pipe: %s (%lu)

- Error number: [2017](#); Symbol: [CR_NAMEDPIPEOPEN_ERROR](#);

Message: Can't open named pipe to host: %s pipe: %s (%lu)

- Error number: [2018](#); Symbol: [CR_NAMEDPIPESETSTATE_ERROR](#);

Message: Can't set state of named pipe to host: %s pipe: %s (%lu)

- Error number: [2019](#); Symbol: [CR_CANT_READ_CHARSET](#);

Message: Can't initialize character set %s (path: %s)

- Error number: [2020](#); Symbol: [CR_NET_PACKET_TOO_LARGE](#);

Message: Got packet bigger than 'max_allowed_packet' bytes

- Error number: [2021](#); Symbol: [CR_EMBEDDED_CONNECTION](#);

Message: Embedded server

- Error number: [2022](#); Symbol: [CR_PROBE_REPLICA_STATUS](#);

Message: Error on SHOW REPLICA STATUS:

- Error number: [2023](#); Symbol: [CR_PROBE_REPLICA_HOSTS](#);

Message: Error on SHOW REPLICA HOSTS:

-
- Error number: [2024](#); Symbol: [CR_PROBE_REPLICA_CONNECT](#);
Message: Error connecting to replica:
 - Error number: [2025](#); Symbol: [CR_PROBE_SOURCE_CONNECT](#);
Message: Error connecting to source:
 - Error number: [2026](#); Symbol: [CR_SSL_CONNECTION_ERROR](#);
Message: SSL connection error: %s
 - Error number: [2027](#); Symbol: [CR_MALFORMED_PACKET](#);
Message: Malformed packet
 - Error number: [2028](#); Symbol: [CR_WRONG_LICENSE](#);
Message: This client library is licensed only for use with MySQL servers having '%s' license
 - Error number: [2029](#); Symbol: [CR_NULL_POINTER](#);
Message: Invalid use of null pointer
 - Error number: [2030](#); Symbol: [CR_NO_PREPARE_STMT](#);
Message: Statement not prepared
 - Error number: [2031](#); Symbol: [CR_PARAMS_NOT_BOUND](#);
Message: No data supplied for parameters in prepared statement
 - Error number: [2032](#); Symbol: [CR_DATA_TRUNCATED](#);
Message: Data truncated
 - Error number: [2033](#); Symbol: [CR_NO_PARAMETERS_EXISTS](#);
Message: No parameters exist in the statement
 - Error number: [2034](#); Symbol: [CR_INVALID_PARAMETER_NO](#);
Message: Invalid parameter number

The column number for `mysql_stmt_fetch_column()` was invalid.

The parameter number for `mysql_stmt_send_long_data()` was invalid.

A key name was empty or the amount of connection attribute data for `mysql_options4()` exceeds the 64KB limit.
 - Error number: [2035](#); Symbol: [CR_INVALID_BUFFER_USE](#);
Message: Can't send long data for non-string/non-binary data types (parameter: %d)
 - Error number: [2036](#); Symbol: [CR_UNSUPPORTED_PARAM_TYPE](#);
Message: Using unsupported buffer type: %d (parameter: %d)
 - Error number: [2037](#); Symbol: [CR_SHARED_MEMORY_CONNECTION](#);

-
- Message: Shared memory: %s
- Error number: 2038; Symbol: [CR_SHARED_MEMORY_CONNECT_REQUEST_ERROR](#);
Message: Can't open shared memory; client could not create request event (%lu)
 - Error number: 2039; Symbol: [CR_SHARED_MEMORY_CONNECT_ANSWER_ERROR](#);
Message: Can't open shared memory; no answer event received from server (%lu)
 - Error number: 2040; Symbol: [CR_SHARED_MEMORY_CONNECT_FILE_MAP_ERROR](#);
Message: Can't open shared memory; server could not allocate file mapping (%lu)
 - Error number: 2041; Symbol: [CR_SHARED_MEMORY_CONNECT_MAP_ERROR](#);
Message: Can't open shared memory; server could not get pointer to file mapping (%lu)
 - Error number: 2042; Symbol: [CR_SHARED_MEMORY_FILE_MAP_ERROR](#);
Message: Can't open shared memory; client could not allocate file mapping (%lu)
 - Error number: 2043; Symbol: [CR_SHARED_MEMORY_MAP_ERROR](#);
Message: Can't open shared memory; client could not get pointer to file mapping (%lu)
 - Error number: 2044; Symbol: [CR_SHARED_MEMORY_EVENT_ERROR](#);
Message: Can't open shared memory; client could not create %s event (%lu)
 - Error number: 2045; Symbol: [CR_SHARED_MEMORY_CONNECT_ABANDONED_ERROR](#);
Message: Can't open shared memory; no answer from server (%lu)
 - Error number: 2046; Symbol: [CR_SHARED_MEMORY_CONNECT_SET_ERROR](#);
Message: Can't open shared memory; cannot send request event to server (%lu)
 - Error number: 2047; Symbol: [CR_CONN_UNKNOW_PROTOCOL](#);
Message: Wrong or unknown protocol
 - Error number: 2048; Symbol: [CR_INVALID_CONN_HANDLE](#);
Message: Invalid connection handle
 - Error number: 2049; Symbol: [CR_UNUSED_1](#);
Message: Connection using old (pre-4.1.1) authentication protocol refused (client option 'secure_auth' enabled)
 - Error number: 2050; Symbol: [CR_FETCH_CANCELED](#);
Message: Row retrieval was canceled by mysql_stmt_close() call
 - Error number: 2051; Symbol: [CR_NO_DATA](#);
Message: Attempt to read column without prior row fetch

-
- Error number: [2052](#); Symbol: [CR_NO_STMT_METADATA](#);
Message: Prepared statement contains no metadata
 - Error number: [2053](#); Symbol: [CR_NO_RESULT_SET](#);
Message: Attempt to read a row while there is no result set associated with the statement
 - Error number: [2054](#); Symbol: [CR_NOT_IMPLEMENTED](#);
Message: This feature is not implemented yet
 - Error number: [2055](#); Symbol: [CR_SERVER_LOST_EXTENDED](#);
Message: Lost connection to MySQL server at '%s', system error: %d
 - Error number: [2056](#); Symbol: [CR_STMT_CLOSED](#);
Message: Statement closed indirectly because of a preceding %s() call
 - Error number: [2057](#); Symbol: [CR_NEW_STMT_METADATA](#);
Message: The number of columns in the result set differs from the number of bound buffers. You must reset the statement, rebind the result set columns, and execute the statement again
 - Error number: [2058](#); Symbol: [CR_ALREADY_CONNECTED](#);
Message: This handle is already connected. Use a separate handle for each connection.
 - Error number: [2059](#); Symbol: [CR_AUTH_PLUGIN_CANNOT_LOAD](#);
Message: Authentication plugin '%s' cannot be loaded: %s
 - Error number: [2060](#); Symbol: [CR_DUPLICATE_CONNECTION_ATTR](#);
Message: There is an attribute with the same name already
A duplicate connection attribute name was specified for `mysql_options4()`.
 - Error number: [2061](#); Symbol: [CR_AUTH_PLUGIN_ERR](#);
Message: Authentication plugin '%s' reported error: %s
 - Error number: [2062](#); Symbol: [CR_INSECURE_API_ERR](#);
Message: Insecure API function call: '%s' Use instead: '%s'
An insecure function call was detected. Modify the application to use the suggested alternative function instead.
 - Error number: [2063](#); Symbol: [CR_FILE_NAME_TOO_LONG](#);
Message: File name is too long
 - Error number: [2064](#); Symbol: [CR_SSL_FIPS_MODE_ERR](#);
Message: Set FIPS mode ON/STRICT failed
 - Error number: [2065](#); Symbol: [CR_DEPRECATED_COMPRESSION_NOT_SUPPORTED](#);

-
- Message: Compression protocol not supported with asynchronous protocol
 - Error number: 2066; Symbol: CR_COMPRESSION_WRONGLY_CONFIGURED;
Message: Connection failed due to wrongly configured compression algorithm
 - Error number: 2067; Symbol: CR_KERBEROS_USER_NOT_FOUND;
Message: SSO user not found, Please perform SSO authentication using kerberos.
 - Error number: 2068; Symbol: CR_LOAD_DATA_LOCAL_INFILE_REJECTED;
Message: LOAD DATA LOCAL INFILE file request rejected due to restrictions on access.
 - Error number: 2069; Symbol: CR_LOAD_DATA_LOCAL_INFILE_REALPATH_FAIL;
Message: Determining the real path for '%s' failed with error (%d): %s
 - Error number: 2070; Symbol: CR_DNS_SRV_LOOKUP_FAILED;
Message: DNS SRV lookup failed with error : %d
 - Error number: 2071; Symbol: CR_MANDATORY_TRACKER_NOT_FOUND;
Message: Client does not recognise tracker type %d marked as mandatory by server.
 - Error number: 2072; Symbol: CR_INVALID_FACTOR_NO;
Message: Invalid first argument for MYSQL_OPT_USER_PASSWORD option. Valid value should be between 1 and 3 inclusive.
 - Error number: 2073; Symbol: CR_CANT_GET_SESSION_DATA;
Message: Can't get session data: %s
 - Error number: 2074; Symbol: CR_INVALID_CLIENT_CHARSET;
Message: '%s' character set is having more than 1 byte minimum character length, which cannot be used as a client character set. Please use any of the single byte minimum ones, e.g. utf8mb4, latin1 etc.
 - Error number: 2075; Symbol: CR_TLS_SERVER_NOT_FOUND;
Message: Server rejected the ssl handshake for specified sni servername, sslerror: %s

Chapter 4 Global Error Message Reference

This document lists “global” error messages that are shared in the sense that they can be produced by the MySQL server or by MySQL client programs. These errors have error codes in the range from 1 to 999.

Each global error message includes an error code, SQLSTATE value, and message string, as described in [Error Message Sources and Elements](#). These elements are available as described in [Error Information Interfaces](#). For global errors, the SQLSTATE value is always 'HY000' (general error), so it is not meaningful for distinguishing one client error from another.

If the server writes a message to the error log that has a global error code, it pads the error code with leading zeros to six digits and adds a prefix of `MY-` (example: `MY-000022`). The following list displays error codes in that format.

If a client returns a message with a global error code, it adds no zero-padding or prefix to the error code.

- Error number: 1; Symbol: `EE_CANTCREATEFILE`;
Message: Can't create/write to file '%s' (OS errno %d - %s)
- Error number: 2; Symbol: `EE_READ`;
Message: Error reading file '%s' (OS errno %d - %s)
- Error number: 3; Symbol: `EE_WRITE`;
Message: Error writing file '%s' (OS errno %d - %s)
- Error number: 4; Symbol: `EE_BADCLOSE`;
Message: Error on close of '%s' (OS errno %d - %s)
- Error number: 5; Symbol: `EE_OUTOFMEMORY`;
Message: Out of memory (Needed %u bytes)
- Error number: 6; Symbol: `EE_DELETE`;
Message: Error on delete of '%s' (OS errno %d - %s)
- Error number: 7; Symbol: `EE_LINK`;
Message: Error on rename of '%s' to '%s' (OS errno %d - %s)
- Error number: 9; Symbol: `EE_EOFERR`;
Message: Unexpected EOF found when reading file '%s' (OS errno %d - %s)
- Error number: 10; Symbol: `EE_CANTLOCK`;
Message: Can't lock file (OS errno %d - %s)
- Error number: 11; Symbol: `EE_CANTUNLOCK`;
Message: Can't unlock file (OS errno %d - %s)
- Error number: 12; Symbol: `EE_DIR`;

-
- Message: Can't read dir of '%s' (OS errno %d - %s)
 - Error number: [13](#); Symbol: [EE_STAT](#);
Message: Can't get stat of '%s' (OS errno %d - %s)
 - Error number: [14](#); Symbol: [EE_CANT_CHSIZE](#);
Message: Can't change size of file (OS errno %d - %s)
 - Error number: [15](#); Symbol: [EE_CANT_OPEN_STREAM](#);
Message: Can't open stream from handle (OS errno %d - %s)
 - Error number: [16](#); Symbol: [EE_GETWD](#);
Message: Can't get working directory (OS errno %d - %s)
 - Error number: [17](#); Symbol: [EE_SETWD](#);
Message: Can't change dir to '%s' (OS errno %d - %s)
 - Error number: [18](#); Symbol: [EE_LINK_WARNING](#);
Message: Warning: '%s' had %d links
 - Error number: [19](#); Symbol: [EE_OPEN_WARNING](#);
Message: Warning: %d files and %d streams are left open
 - Error number: [20](#); Symbol: [EE_DISK_FULL](#);
Message: Disk is full writing '%s' (OS errno %d - %s). Waiting for someone to free space...
 - Error number: [21](#); Symbol: [EE_CANT_MKDIR](#);
Message: Can't create directory '%s' (OS errno %d - %s)
 - Error number: [22](#); Symbol: [EE_UNKNOWN_CHARSET](#);
Message: Character set '%s' is not a compiled character set and is not specified in the '%s' file
 - Error number: [23](#); Symbol: [EE_OUT_OF_FILERESOURCES](#);
Message: Out of resources when opening file '%s' (OS errno %d - %s)
 - Error number: [24](#); Symbol: [EE_CANT_READLINK](#);
Message: Can't read value for symlink '%s' (Error %d - %s)
 - Error number: [25](#); Symbol: [EE_CANT_SYMLINK](#);
Message: Can't create symlink '%s' pointing at '%s' (Error %d - %s)
 - Error number: [26](#); Symbol: [EE_REALPATH](#);
Message: Error on realpath() on '%s' (Error %d - %s)
 - Error number: [27](#); Symbol: [EE_SYNC](#);

Message: Can't sync file '%s' to disk (OS errno %d - %s)

- Error number: 28; Symbol: `EE_UNKNOWN_COLLATION`;

Message: Collation '%s' is not a compiled collation and is not specified in the '%s' file

- Error number: 29; Symbol: `EE_FILENOTFOUND`;

Message: File '%s' not found (OS errno %d - %s)

- Error number: 30; Symbol: `EE_FILE_NOT_CLOSED`;

Message: File '%s' (fileno: %d) was not closed

- Error number: 31; Symbol: `EE_CHANGE_OWNERSHIP`;

Message: Cannot change ownership of the file '%s' (OS errno %d - %s)

- Error number: 32; Symbol: `EE_CHANGE_PERMISSIONS`;

Message: Cannot change permissions of the file '%s' (OS errno %d - %s)

- Error number: 33; Symbol: `EE_CANT_SEEK`;

Message: Cannot seek in file '%s' (OS errno %d - %s)

- Error number: 34; Symbol: `EE_CAPACITY_EXCEEDED`;

Message: Memory capacity exceeded (capacity %llu bytes)

- Error number: 35; Symbol: `EE_DISK_FULL_WITH_RETRY_MSG`;

Message: Disk is full writing '%s' (OS errno %d - %s). Waiting for someone to free space... Retry in %d secs. Message reprinted in %d secs.

- Error number: 36; Symbol: `EE_FAILED_TO_CREATE_TIMER`;

Message: Failed to create timer (OS errno %d).

- Error number: 37; Symbol: `EE_FAILED_TO_DELETE_TIMER`;

Message: Failed to delete timer (OS errno %d).

- Error number: 38; Symbol: `EE_FAILED_TO_CREATE_TIMER_QUEUE`;

Message: Failed to create timer queue (OS errno %d).

- Error number: 39; Symbol: `EE_FAILED_TO_START_TIMER_NOTIFY_THREAD`;

Message: Failed to start timer notify thread.

- Error number: 40; Symbol: `EE_FAILED_TO_CREATE_TIMER_NOTIFY_THREAD_INTERRUPT_EVENT`;

Message: Failed to create event to interrupt timer notifier thread (OS errno %d).

- Error number: 41; Symbol: `EE_EXITING_TIMER_NOTIFY_THREAD`;

Message: Failed to register timer event with queue (OS errno %d), exiting timer notifier thread.

-
- Error number: 42; Symbol: `EE_WIN_LIBRARY_LOAD_FAILED`;
Message: LoadLibrary("kernel32.dll") failed: GetLastError returns %lu.
 - Error number: 43; Symbol: `EE_WIN_RUN_TIME_ERROR_CHECK`;
Message: %s.
 - Error number: 44; Symbol: `EE_FAILED_TO_DETERMINE_LARGE_PAGE_SIZE`;
Message: Failed to determine large page size.
 - Error number: 45; Symbol: `EE_FAILED_TO_KILL_ALL_THREADS`;
Message: Error in my_thread_global_end(): %d thread(s) did not exit.
 - Error number: 46; Symbol: `EE_FAILED_TO_CREATE_IO_COMPLETION_PORT`;
Message: Failed to create IO completion port (OS errno %d).
 - Error number: 47; Symbol: `EE_FAILED_TO_OPEN_DEFAULTS_FILE`;
Message: Failed to open required defaults file: %s
 - Error number: 48; Symbol: `EE_FAILED_TO_HANDLE_DEFAULTS_FILE`;
Message: Fatal error in defaults handling. Program aborted!
 - Error number: 49; Symbol: `EE_WRONG_DIRECTIVE_IN_CONFIG_FILE`;
Message: Wrong '%s' directive in config file %s at line %d.
 - Error number: 50; Symbol: `EE_SKIPPING_DIRECTIVE_DUE_TO_MAX_INCLUDE_RECURSION`;
Message: Skipping '%s' directive as maximum include recursion level was reached in file %s at line %d.
 - Error number: 51; Symbol: `EE_INCORRECT_GRP_DEFINITION_IN_CONFIG_FILE`;
Message: Wrong group definition in config file %s at line %d.
 - Error number: 52; Symbol: `EE_OPTION_WITHOUT_GRP_IN_CONFIG_FILE`;
Message: Found option without preceding group in config file %s at line %d.
 - Error number: 53; Symbol: `EE_CONFIG_FILE_PERMISSION_ERROR`;
Message: %s should be readable/writable only by current user.
 - Error number: 54; Symbol: `EE_IGNORE_WORLD_WRITABLE_CONFIG_FILE`;
Message: World-writable config file '%s' is ignored.
 - Error number: 55; Symbol: `EE_USING_DISABLED_OPTION`;
Message: %s: Option '%s' was used, but is disabled.
 - Error number: 56; Symbol: `EE_USING_DISABLED_SHORT_OPTION`;
Message: %s: Option '-%c' was used, but is disabled.

-
- Error number: [57](#); Symbol: [EE_USING_PASSWORD_ON_CLI_IS_INSECURE](#);
Message: Using a password on the command line interface can be insecure.
 - Error number: [58](#); Symbol: [EE_UNKNOWN_SUFFIX_FOR_VARIABLE](#);
Message: Unknown suffix '%c' used for variable '%s' (value '%s').
 - Error number: [59](#); Symbol: [EE_SSL_ERROR_FROM_FILE](#);
Message: SSL error: %s from '%s'.
 - Error number: [60](#); Symbol: [EE_SSL_ERROR](#);
Message: SSL error: %s.
 - Error number: [61](#); Symbol: [EE_NET_SEND_ERROR_IN_BOOTSTRAP](#);
Message: %d %s.
 - Error number: [62](#); Symbol: [EE_PACKETS_OUT_OF_ORDER](#);
Message: Packets out of order (found %u, expected %u).
 - Error number: [63](#); Symbol: [EE_UNKNOWN_PROTOCOL_OPTION](#);
Message: Unknown option to protocol: %s.
 - Error number: [64](#); Symbol: [EE_FAILED_TO_LOCATE_SERVER_PUBLIC_KEY](#);
Message: Failed to locate server public key '%s'.
 - Error number: [65](#); Symbol: [EE_PUBLIC_KEY_NOT_IN_PEM_FORMAT](#);
Message: Public key is not in Privacy Enhanced Mail format: '%s'.
 - Error number: [66](#); Symbol: [EE_DEBUG_INFO](#);
Message: %s.
 - Error number: [67](#); Symbol: [EE_UNKNOWN_VARIABLE](#);
Message: unknown variable '%s'.
 - Error number: [68](#); Symbol: [EE_UNKNOWN_OPTION](#);
Message: unknown option '--%s'.
 - Error number: [69](#); Symbol: [EE_UNKNOWN_SHORT_OPTION](#);
Message: %s: unknown option '-%c'.
 - Error number: [70](#); Symbol: [EE_OPTION_WITHOUT_ARGUMENT](#);
Message: %s: option '--%s' cannot take an argument.
 - Error number: [71](#); Symbol: [EE_OPTION_REQUIRES_ARGUMENT](#);
Message: %s: option '--%s' requires an argument.

-
- Error number: 72; Symbol: `EE_SHORT_OPTION_REQUIRES_ARGUMENT`;
Message: %s: option '-%c' requires an argument.
 - Error number: 73; Symbol: `EE_OPTION_IGNORED_DUE_TO_INVALID_VALUE`;
Message: %s: ignoring option '--%s' due to invalid value '%s'.
 - Error number: 74; Symbol: `EE_OPTION_WITH_EMPTY_VALUE`;
Message: %s: Empty value for '%s' specified.
 - Error number: 75; Symbol: `EE_FAILED_TO_ASSIGN_MAX_VALUE_TO_OPTION`;
Message: %s: Maximum value of '%s' cannot be set.
 - Error number: 76; Symbol: `EE_INCORRECT_BOOLEAN_VALUE_FOR_OPTION`;
Message: option '%s': boolean value '%s' was not recognized. Set to OFF.
 - Error number: 77; Symbol: `EE_FAILED_TO_SET_OPTION_VALUE`;
Message: %s: Error while setting value '%s' to '%s'.
 - Error number: 78; Symbol: `EE_INCORRECT_INT_VALUE_FOR_OPTION`;
Message: Incorrect integer value: '%s'.
 - Error number: 79; Symbol: `EE_INCORRECT_UINT_VALUE_FOR_OPTION`;
Message: Incorrect unsigned integer value: '%s'.
 - Error number: 80; Symbol: `EE_ADJUSTED_SIGNED_VALUE_FOR_OPTION`;
Message: option '%s': signed value %s adjusted to %s.
 - Error number: 81; Symbol: `EE_ADJUSTED_UNSIGNED_VALUE_FOR_OPTION`;
Message: option '%s': unsigned value %s adjusted to %s.
 - Error number: 82; Symbol: `EE_ADJUSTED_ULONGLONG_VALUE_FOR_OPTION`;
Message: option '%s': value %s adjusted to %s.
 - Error number: 83; Symbol: `EE_ADJUSTED_DOUBLE_VALUE_FOR_OPTION`;
Message: option '%s': value %g adjusted to %g.
 - Error number: 84; Symbol: `EE_INVALID_DECIMAL_VALUE_FOR_OPTION`;
Message: Invalid decimal value for option '%s'.
 - Error number: 85; Symbol: `EE_COLLATION_PARSER_ERROR`;
Message: %s.
 - Error number: 86; Symbol: `EE_FAILED_TO_RESET_BEFORE_PRIMARY_IGNOREABLE_CHAR`;
Message: Failed to reset before a primary ignorable character %s.

-
- Error number: 87; Symbol: `EE_FAILED_TO_RESET_BEFORE_TERTIARY_IGNOREABLE_CHAR`;
Message: Failed to reset before a tertiary ignorable character %s.
 - Error number: 88; Symbol: `EE_SHIFT_CHAR_OUT_OF_RANGE`;
Message: Shift character out of range: %s.
 - Error number: 89; Symbol: `EE_RESET_CHAR_OUT_OF_RANGE`;
Message: Reset character out of range: %s.
 - Error number: 90; Symbol: `EE_UNKNOWN_LDML_TAG`;
Message: Unknown LDML tag: '%.*s'.
 - Error number: 91; Symbol: `EE_FAILED_TO_RESET_BEFORE_SECONDARY_IGNOREABLE_CHAR`;
Message: Failed to reset before a secondary ignorable character %s.
 - Error number: 92; Symbol: `EE_FAILED_PROCESSING_DIRECTIVE`;
Message: Stopped processing the '%s' directive in file %s at line %d.
 - Error number: 93; Symbol: `EE_PTHREAD_KILL_FAILED`;
Message: pthread_kill(thread_id:%lu, signal:%s) returned '%s'.

Index

C

- CR_ALREADY_CONNECTED error code, 435
- CR_AUTH_PLUGIN_CANNOT_LOAD error code, 435
- CR_AUTH_PLUGIN_ERR error code, 435
- CR_CANT_GET_SESSION_DATA error code, 436
- CR_CANT_READ_CHARSET error code, 432
- CR_COMMANDS_OUT_OF_SYNC error code, 432
- CR_COMPRESSION_WRONGLY_CONFIGURED error code, 436
- CR_CONNECTION_ERROR error code, 431
- CR_CONN_HOST_ERROR error code, 431
- CR_CONN_UNKNOW_PROTOCOL error code, 434
- CR_DATA_TRUNCATED error code, 433
- CR_DEPRECATED_COMPRESSION_NOT_SUPPORTED error code, 436
- CR_DNS_SRV_LOOKUP_FAILED error code, 436
- CR_DUPLICATE_CONNECTION_ATTR error code, 435
- CR_EMBEDDED_CONNECTION error code, 432
- CR_FETCH_CANCELED error code, 434
- CR_FILE_NAME_TOO_LONG error code, 435
- CR_INSECURE_API_ERR error code, 435
- CR_INVALID_BUFFER_USE error code, 433
- CR_INVALID_CLIENT_CHARSET error code, 436
- CR_INVALID_CONN_HANDLE error code, 434
- CR_INVALID_FACTOR_NO error code, 436
- CR_INVALID_PARAMETER_NO error code, 433
- CR_IPSOCK_ERROR error code, 431
- CR_KERBEROS_USER_NOT_FOUND error code, 436
- CR_LOAD_DATA_LOCAL_INFILE_REALPATH_FAIL error code, 436
- CR_LOAD_DATA_LOCAL_INFILE_REJECTED error code, 436
- CR_LOCALHOST_CONNECTION error code, 432
- CR_MALFORMED_PACKET error code, 433
- CR_MANDATORY_TRACKER_NOT_FOUND error code, 436
- CR_NAMEDPIPEOPEN_ERROR error code, 432
- CR_NAMEDPIPESETSTATE_ERROR error code, 432
- CR_NAMEDPIPEWAIT_ERROR error code, 432
- CR_NAMEDPIPE_CONNECTION error code, 432
- CR_NET_PACKET_TOO_LARGE error code, 432
- CR_NEW_STMT_METADATA error code, 435
- CR_NOT_IMPLEMENTED error code, 435
- CR_NO_DATA error code, 434
- CR_NO_PARAMETERS_EXISTS error code, 433
- CR_NO_PREPARE_STMT error code, 433
- CR_NO_RESULT_SET error code, 435
- CR_NO_STMT_METADATA error code, 435
- CR_NULL_POINTER error code, 433
- CR_OUT_OF_MEMORY error code, 431
- CR_PARAMS_NOT_BOUND error code, 433
- CR_PROBE_REPLICA_CONNECT error code, 433
- CR_PROBE_REPLICA_HOSTS error code, 432
- CR_PROBE_REPLICA_STATUS error code, 432
- CR_PROBE_SOURCE_CONNECT error code, 433
- CR_SERVER_GONE_ERROR error code, 431
- CR_SERVER_HANDSHAKE_ERR error code, 432
- CR_SERVER_LOST error code, 432
- CR_SERVER_LOST_EXTENDED error code, 435
- CR_SHARED_MEMORY_CONNECTION error code, 434
- CR_SHARED_MEMORY_CONNECT_ABANDONED_ERROR error code, 434
- CR_SHARED_MEMORY_CONNECT_ANSWER_ERROR error code, 434
- CR_SHARED_MEMORY_CONNECT_FILE_MAP_ERROR error code, 434
- CR_SHARED_MEMORY_CONNECT_MAP_ERROR error code, 434
- CR_SHARED_MEMORY_CONNECT_REQUEST_ERROR error code, 434
- CR_SHARED_MEMORY_CONNECT_SET_ERROR error code, 434
- CR_SHARED_MEMORY_EVENT_ERROR error code, 434
- CR_SHARED_MEMORY_FILE_MAP_ERROR error code, 434
- CR_SHARED_MEMORY_MAP_ERROR error code, 434
- CR_SOCKET_CREATE_ERROR error code, 431
- CR_SSL_CONNECTION_ERROR error code, 433
- CR_SSL_FIPS_MODE_ERR error code, 435
- CR_STMT_CLOSED error code, 435
- CR_TCP_CONNECTION error code, 432
- CR_TLS_SERVER_NOT_FOUND error code, 436
- CR_UNKNOWN_ERROR error code, 431
- CR_UNKNOWN_HOST error code, 431
- CR_UNSUPPORTED_PARAM_TYPE error code, 433
- CR_UNUSED_1 error code, 434
- CR_VERSION_ERROR error code, 431
- CR_WRONG_HOST_INFO error code, 431
- CR_WRONG_LICENSE error code, 433

E

- EE_ADJUSTED_DOUBLE_VALUE_FOR_OPTION error code, 442
- EE_ADJUSTED_SIGNED_VALUE_FOR_OPTION error code, 442
- EE_ADJUSTED_ULONGLONG_VALUE_FOR_OPTION error code, 442
- EE_ADJUSTED_UNSIGNED_VALUE_FOR_OPTION error code, 442
- EE_BADCLOSE error code, 437
- EE_CANTCREATEFILE error code, 437
- EE_CANTLOCK error code, 437

EE_CANTUNLOCK error code, 437
 EE_CANT_CHSIZE error code, 438
 EE_CANT_MKDIR error code, 438
 EE_CANT_OPEN_STREAM error code, 438
 EE_CANT_READLINK error code, 438
 EE_CANT_SEEK error code, 439
 EE_CANT_SYMLINK error code, 438
 EE_CAPACITY_EXCEEDED error code, 439
 EE_CHANGE_OWNERSHIP error code, 439
 EE_CHANGE_PERMISSIONS error code, 439
 EE_COLLATION_PARSER_ERROR error code, 442
 EE_CONFIG_FILE_PERMISSION_ERROR error code, 440
 EE_DEBUG_INFO error code, 441
 EE_DELETE error code, 437
 EE_DIR error code, 438
 EE_DISK_FULL error code, 438
 EE_DISK_FULL_WITH_RETRY_MSG error code, 439
 EE_EOFERR error code, 437
 EE_EXITING_TIMER_NOTIFY_THREAD error code, 439
 EE_FAILED_PROCESSING_DIRECTIVE error code, 443
 EE_FAILED_TO_ASSIGN_MAX_VALUE_TO_OPTION error code, 442
 EE_FAILED_TO_CREATE_IO_COMPLETION_PORT error code, 440
 EE_FAILED_TO_CREATE_TIMER error code, 439
 EE_FAILED_TO_CREATE_TIMER_NOTIFY_THREAD_INTERRUPTIBLE error code, 439
 EE_FAILED_TO_CREATE_TIMER_QUEUE error code, 439
 EE_FAILED_TO_DELETE_TIMER error code, 439
 EE_FAILED_TO_DETERMINE_LARGE_PAGE_SIZE error code, 440
 EE_FAILED_TO_HANDLE_DEFAULTS_FILE error code, 440
 EE_FAILED_TO_KILL_ALL_THREADS error code, 440
 EE_FAILED_TO_LOCATE_SERVER_PUBLIC_KEY error code, 441
 EE_FAILED_TO_OPEN_DEFAULTS_FILE error code, 440
 EE_FAILED_TO_RESET_BEFORE_PRIMARY_IGNOREABLE error code, 442
 EE_FAILED_TO_RESET_BEFORE_SECONDARY_IGNOREABLE error code, 443
 EE_FAILED_TO_RESET_BEFORE_TERTIARY_IGNOREABLE error code, 443
 EE_FAILED_TO_SET_OPTION_VALUE error code, 442
 EE_FAILED_TO_START_TIMER_NOTIFY_THREAD error code, 439
 EE_FILENOTFOUND error code, 439
 EE_FILE_NOT_CLOSED error code, 439
 EE_GETWD error code, 438
 EE_IGNORE_WORLD_WRITABLE_CONFIG_FILE error code, 440
 EE_INCORRECT_BOOLEAN_VALUE_FOR_OPTION error code, 442
 EE_INCORRECT_GRP_DEFINITION_IN_CONFIG_FILE error code, 440
 EE_INCORRECT_INT_VALUE_FOR_OPTION error code, 442
 EE_INCORRECT_UINT_VALUE_FOR_OPTION error code, 442
 EE_INVALID_DECIMAL_VALUE_FOR_OPTION error code, 442
 EE_LINK error code, 437
 EE_LINK_WARNING error code, 438
 EE_NET_SEND_ERROR_IN_BOOTSTRAP error code, 441
 EE_OPEN_WARNING error code, 438
 EE_OPTION_IGNORED_DUE_TO_INVALID_VALUE error code, 442
 EE_OPTION_REQUIRES_ARGUMENT error code, 441
 EE_OPTION_WITHOUT_ARGUMENT error code, 441
 EE_OPTION_WITHOUT_GRP_IN_CONFIG_FILE error code, 440
 EE_OPTION_WITH_EMPTY_VALUE error code, 442
 EE_OUTOFMEMORY error code, 437
 EE_OUT_OF_FILERESOURCES error code, 438
 EE_PACKETS_OUT_OF_ORDER error code, 441
 EE_PTHREAD_KILL_FAILED error code, 443
 EE_PUBLIC_KEY_NOT_IN_PEM_FORMAT error code, 441
 EE_READ error code, 437
 EE_REALPATH error code, 438
 EE_RESET_CHAR_OUT_OF_RANGE error code, 443
 EE_SETWD error code, 438
 EE_SHIFT_CHAR_OUT_OF_RANGE error code, 443
 EE_SHORT_OPTION_REQUIRES_ARGUMENT error code, 442
 EE_SKIPPING_DIRECTIVE_DUE_TO_MAX_INCLUDE_RECURSION error code, 440
 EE_SSL_ERROR error code, 441
 EE_SSL_ERROR_FROM_FILE error code, 441
 EE_STAT error code, 438
 EE_SYMLINK error code, 439
 EE_UNKNOWN_CHARSET error code, 438
 EE_UNKNOWN_COLLATION error code, 439
 EE_UNKNOWN_LDML_TAG error code, 443
 EE_UNKNOWN_OPTION error code, 441
 EE_UNKNOWN_PROTOCOL_OPTION error code, 441
 EE_UNKNOWN_SHORT_OPTION error code, 441
 EE_UNKNOWN_SUFFIX_FOR_VARIABLE error code, 441
 EE_UNKNOWN_VARIABLE error code, 441
 EE_USING_DISABLED_OPTION error code, 440

EE_USING_DISABLED_SHORT_OPTION error code, 440
 EE_USING_PASSWORD_ON_CLI_IS_INSECURE error code, 441
 EE_WIN_LIBRARY_LOAD_FAILED error code, 440
 EE_WIN_RUN_TIME_ERROR_CHECK error code, 440
 EE_WRITE error code, 437
 EE_WRONG_DIRECTIVE_IN_CONFIG_FILE error code, 440
 error code
 CR_ALREADY_CONNECTED, 435
 CR_AUTH_PLUGIN_CANNOT_LOAD, 435
 CR_AUTH_PLUGIN_ERR, 435
 CR_CANT_GET_SESSION_DATA, 436
 CR_CANT_READ_CHARSET, 432
 CR_COMMANDS_OUT_OF_SYNC, 432
 CR_COMPRESSION_WRONGLY_CONFIGURED, 436
 CR_CONNECTION_ERROR, 431
 CR_CONN_HOST_ERROR, 431
 CR_CONN_UNKNOW_PROTOCOL, 434
 CR_DATA_TRUNCATED, 433
 CR_DEPRECATED_COMPRESSION_NOT_SUPPORTED, 436
 CR_DNS_SRV_LOOKUP_FAILED, 436
 CR_DUPLICATE_CONNECTION_ATTR, 435
 CR_EMBEDDED_CONNECTION, 432
 CR_FETCH_CANCELED, 434
 CR_FILE_NAME_TOO_LONG, 435
 CR_INSECURE_API_ERR, 435
 CR_INVALID_BUFFER_USE, 433
 CR_INVALID_CLIENT_CHARSET, 436
 CR_INVALID_CONN_HANDLE, 434
 CR_INVALID_FACTOR_NO, 436
 CR_INVALID_PARAMETER_NO, 433
 CR_IPSOCK_ERROR, 431
 CR_KERBEROS_USER_NOT_FOUND, 436
 CR_LOAD_DATA_LOCAL_INFILE_REALPATH_FAIL, 436
 CR_LOAD_DATA_LOCAL_INFILE_REJECTED, 436
 CR_LOCALHOST_CONNECTION, 432
 CR_MALFORMED_PACKET, 433
 CR_MANDATORY_TRACKER_NOT_FOUND, 436
 CR_NAMEDPIPEOPEN_ERROR, 432
 CR_NAMEDPIPESETSTATE_ERROR, 432
 CR_NAMEDPIPEWAIT_ERROR, 432
 CR_NAMEDPIPE_CONNECTION, 432
 CR_NET_PACKET_TOO_LARGE, 432
 CR_NEW_STMT_METADATA, 435
 CR_NOT_IMPLEMENTED, 435
 CR_NO_DATA, 434
 CR_NO_PARAMETERS_EXISTS, 433
 CR_NO_PREPARE_STMT, 433
 CR_NO_RESULT_SET, 435
 CR_NO_STMT_METADATA, 435
 CR_NULL_POINTER, 433
 CR_OUT_OF_MEMORY, 431
 CR_PARAMS_NOT_BOUND, 433
 CR_PROBE_REPLICA_CONNECT, 433
 CR_PROBE_REPLICA_HOSTS, 432
 CR_PROBE_REPLICA_STATUS, 432
 CR_PROBE_SOURCE_CONNECT, 433
 CR_SERVER_GONE_ERROR, 431
 CR_SERVER_HANDSHAKE_ERR, 432
 CR_SERVER_LOST, 432
 CR_SERVER_LOST_EXTENDED, 435
 CR_SHARED_MEMORY_CONNECTION, 434
 CR_SHARED_MEMORY_CONNECT_ABANDONED_ERROR, 434
 CR_SHARED_MEMORY_CONNECT_ANSWER_ERROR, 434
 CR_SHARED_MEMORY_CONNECT_FILE_MAP_ERROR, 434
 CR_SHARED_MEMORY_CONNECT_MAP_ERROR, 434
 CR_SHARED_MEMORY_CONNECT_REQUEST_ERROR, 434
 CR_SHARED_MEMORY_CONNECT_SET_ERROR, 434
 CR_SHARED_MEMORY_EVENT_ERROR, 434
 CR_SHARED_MEMORY_FILE_MAP_ERROR, 434
 CR_SHARED_MEMORY_MAP_ERROR, 434
 CR_SOCKET_CREATE_ERROR, 431
 CR_SSL_CONNECTION_ERROR, 433
 CR_SSL_FIPS_MODE_ERR, 435
 CR_STMT_CLOSED, 435
 CR_TCP_CONNECTION, 432
 CR_TLS_SERVER_NOT_FOUND, 436
 CR_UNKNOWN_ERROR, 431
 CR_UNKNOWN_HOST, 431
 CR_UNSUPPORTED_PARAM_TYPE, 433
 CR_UNUSED_1, 434
 CR_VERSION_ERROR, 431
 CR_WRONG_HOST_INFO, 431
 CR_WRONG_LICENSE, 433
 EE_ADJUSTED_DOUBLE_VALUE_FOR_OPTION, 442
 EE_ADJUSTED_SIGNED_VALUE_FOR_OPTION, 442
 EE_ADJUSTED_ULONGLONG_VALUE_FOR_OPTION, 442
 EE_ADJUSTED_UNSIGNED_VALUE_FOR_OPTION, 442
 EE_BADCLOSE, 437
 EE_CANTCREATEFILE, 437
 EE_CANTLOCK, 437
 EE_CANTUNLOCK, 437
 EE_CANT_CHSIZE, 438

EE_CANT_MKDIR, 438
 EE_CANT_OPEN_STREAM, 438
 EE_CANT_READLINK, 438
 EE_CANT_SEEK, 439
 EE_CANT_SYMLINK, 438
 EE_CAPACITY_EXCEEDED, 439
 EE_CHANGE_OWNERSHIP, 439
 EE_CHANGE_PERMISSIONS, 439
 EE_COLLATION_PARSER_ERROR, 442
 EE_CONFIG_FILE_PERMISSION_ERROR, 440
 EE_DEBUG_INFO, 441
 EE_DELETE, 437
 EE_DIR, 438
 EE_DISK_FULL, 438
 EE_DISK_FULL_WITH_RETRY_MSG, 439
 EE_EOFERR, 437
 EE_EXITING_TIMER_NOTIFY_THREAD, 439
 EE_FAILED_PROCESSING_DIRECTIVE, 443
 EE_FAILED_TO_ASSIGN_MAX_VALUE_TO_OPTION, 442
 EE_FAILED_TO_CREATE_IO_COMPLETION_PORT, 440
 EE_FAILED_TO_CREATE_TIMER, 439
 EE_FAILED_TO_CREATE_TIMER_NOTIFY_THREAD_INTERRUPTIBLE, 439
 EE_FAILED_TO_CREATE_TIMER_QUEUE, 439
 EE_FAILED_TO_DELETE_TIMER, 439
 EE_FAILED_TO_DETERMINE_LARGE_PAGE_SIZE, 440
 EE_FAILED_TO_HANDLE_DEFAULTS_FILE, 440
 EE_FAILED_TO_KILL_ALL_THREADS, 440
 EE_FAILED_TO_LOCATE_SERVER_PUBLIC_KEY, 441
 EE_FAILED_TO_OPEN_DEFAULTS_FILE, 440
 EE_FAILED_TO_RESET_BEFORE_PRIMARY_IGNOREABLE_DIRECTIVE, 442
 EE_FAILED_TO_RESET_BEFORE_SECONDARY_IGNOREABLE_DIRECTIVE, 443
 EE_FAILED_TO_RESET_BEFORE_TERTIARY_IGNOREABLE_DIRECTIVE, 443
 EE_FAILED_TO_SET_OPTION_VALUE, 442
 EE_FAILED_TO_START_TIMER_NOTIFY_THREAD, 439
 EE_FILENOTFOUND, 439
 EE_FILE_NOT_CLOSED, 439
 EE_GETWD, 438
 EE_IGNORE_WORLD_WRITABLE_CONFIG_FILE, 440
 EE_INCORRECT_BOOLEAN_VALUE_FOR_OPTION, 442
 EE_INCORRECT_GRP_DEFINITION_IN_CONFIG_FILE, 440
 EE_INCORRECT_INT_VALUE_FOR_OPTION, 442
 EE_INCORRECT_UINT_VALUE_FOR_OPTION, 442
 EE_INVALID_DECIMAL_VALUE_FOR_OPTION, 442
 EE_LINK, 437
 EE_LINK_WARNING, 438
 EE_NET_SEND_ERROR_IN_BOOTSTRAP, 441
 EE_OPEN_WARNING, 438
 EE_OPTION_IGNORED_DUE_TO_INVALID_VALUE, 442
 EE_OPTION_REQUIRES_ARGUMENT, 441
 EE_OPTION_WITHOUT_ARGUMENT, 441
 EE_OPTION_WITHOUT_GRP_IN_CONFIG_FILE, 440
 EE_OPTION_WITH_EMPTY_VALUE, 442
 EE_OUTOFMEMORY, 437
 EE_OUT_OF_FILERESOURCES, 438
 EE_PACKETS_OUT_OF_ORDER, 441
 EE_PTHREAD_KILL_FAILED, 443
 EE_PUBLIC_KEY_NOT_IN_PEM_FORMAT, 441
 EE_READ, 437
 EE_REALPATH, 438
 EE_RESET_CHAR_OUT_OF_RANGE, 443
 EE_SETWD, 438
 EE_SHIFT_CHAR_OUT_OF_RANGE, 443
 EE_SHORT_OPTION_REQUIRES_ARGUMENT, 442
 EE_SKIP_FILE_DIRECTIVE_DUE_TO_MAX_INCLUDE_RECURSION, 440
 EE_SSL_ERROR, 441
 EE_SSL_ERROR_FROM_FILE, 441
 EE_STAT, 438
 EE_SYNC, 439
 EE_UNKNOWN_CHARSET, 438
 EE_UNKNOWN_COLLATION, 439
 EE_UNKNOWN_LDML_TAG, 443
 EE_UNKNOWN_OPTION, 441
 EE_UNKNOWN_PROTOCOL_OPTION, 441
 EE_UNKNOWN_SHORT_OPTION, 441
 EE_UNKNOWN_SUFFIX_FOR_VARIABLE, 441
 EE_UNKNOWN_VARIABLE, 441
 EE_USING_DISABLED_OPTION, 440
 EE_USING_DISABLED_SHORT_OPTION, 440
 EE_USING_PASSWORD_ON_CLI_IS_INSECURE, 441
 EE_WIN_LIBRARY_LOAD_FAILED, 440
 EE_WIN_RUN_TIME_ERROR_CHECK, 440
 EE_WRITE, 437
 EE_WRONG_DIRECTIVE_IN_CONFIG_FILE, 440
 ER_ABORTING, 145
 ER_ABORTING_CONNECTION, 13
 ER_ABORTING_USER_CONNECTION, 191
 ER_ACCESS_DENIED_CHANGE_USER_ERROR, 59
 ER_ACCESS_DENIED_ERROR, 6
 ER_ACCESS_DENIED_ERROR_WITHOUT_PASSWORD, 192

ER_ACCESS_DENIED_ERROR_WITH_PASSWORD, 192	ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_FT 58
ER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED, 370	ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_GIS 65
ER_ACCESS_DENIED_FOR_USER_ACCOUNT_LOCKED, 192	ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_HID 58
ER_ACCESS_DENIED_NO_PASSWORD_ERROR, 47	ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_NO 57
ER_ACCESS_DENIED_NO_PROXY, 136	ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_NO 58
ER_ACCESS_DENIED_NO_PROXY_GRANT, 136	ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_PA 57
ER_ACCESS_DENIED_NO_PROXY_GRANT_WITH_NAME, 427	ER_ambiguous_field_term, 34
ER_ACCESS_DENIED_NO_PROXY_WITH_NAME, 427	ER_ANONYMOUS_AUTH_ID_NOT_ALLOWED_IN_MANDAT 195
ER_ACCOUNT_HAS_BEEN_LOCKED, 69	ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NA 115
ER_ACCOUNT_WITH_EXPIRED_PASSWORD, 397	ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_VIEW_CHAN 116
ER_ACL_OPERATION_FAILED, 76	ER_APPLIER_LOG_EVENT_VALIDATION_ERROR, 85
ER_ACL_WRONG_OR_MISSING_ACL_TABLES_LOG, 364	ER_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_R 114
ER_ADDRESSES_FOR_HOSTNAME_HEADER, 141	ER_ATTRIBUTE_IGNORED, 87
ER_ADDRESSES_FOR_HOSTNAME_LIST_ITEM, 141	ER_AUDIT_API_ABORT, 73
ER_ADD_PARTITION_NO_NEW_PARTITION, 36	ER_AUDIT_CANT_ABORT_COMMAND, 190
ER_ADD_PARTITION_SUBPART_ERROR, 36	ER_AUDIT_CANT_ABORT_EVENT, 190
ER_ADMIN_WRONG_MRG_TABLE, 33	ER_AUDIT_LOG_CANNOT_GENERATE_PASSWORD, 368
ER_AES_INVALID_IV, 59	ER_AUDIT_LOG_CANNOT_READ_PASSWORD, 363
ER_AES_INVALID_KDF_ITERATIONS, 76	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_AES_INVALID_KDF_NAME, 75	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_AES_INVALID_KDF_OPTION_SIZE, 76	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_AGGREGATE_IN_ORDER_NOT_SELECT, 65	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_AGGREGATE_ORDER_FOR_UNION, 62	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_AGGREGATE_ORDER_NON_AGG_QUERY, 62	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_CONSTRAINT_ENFORCEMENT_NOT_SUPPORT 108	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_FILEGROUP_FAILED, 37	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_INFO, 9	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED, 57	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON, 57	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_A 58	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_C 58	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_D 57	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_E 120	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_F 57	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_G 57	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_H 57	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_I 57	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_J 57	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_K 57	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_L 57	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_M 57	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_N 57	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_O 57	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_P 57	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_Q 57	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_R 57	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_S 57	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_T 57	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_U 57	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_V 57	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_W 57	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_X 57	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_Y 57	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON_Z 57	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD, 363

ER_AUDIT_LOG_FILE_NAME_DOES_NOT_HAVE_REQUIRED_FORMAT, 363	ER_AUDIT_LOG_JSON_USER_NAME_CANNOT_BE_EMPTY, 344
ER_AUDIT_LOG_FILE_NAME_KEYRING_ID_VALUE_IS_MISSING, 363	ER_AUDIT_LOG_KEYRING_ID_TIMESTAMP_VALUE_IS_INVALID, 363
ER_AUDIT_LOG_FILE_NAME_TIMESTAMP_VALUE_IS_MISSING_OR_INVALID, 363	KEYRING_PLUGIN_INSTALLED, 343
ER_AUDIT_LOG_FILE_PRUNE_FAILED, 384	ER_AUDIT_LOG_ONLY_INCLUDE_LIST_USED, 213
ER_AUDIT_LOG_FILTER_FAILED_TO_CLOSE_TABLE_AFTER_READING, 215	PASSWORD_HAS_BEEN_COPIED, 363
ER_AUDIT_LOG_FILTER_FAILED_TO_DELETE_FROM_TABLE, 215	ER_AUDIT_LOG_RENAME_LOG_FILE_BEFORE_FLUSH, 214
ER_AUDIT_LOG_FILTER_FAILED_TO_INIT_TABLE_FOR_READ, 215	ER_AUDIT_LOG_SUPER_PRIVILEGE_REQUIRED, 366
ER_AUDIT_LOG_FILTER_FAILED_TO_INSERT_INTO_TABLE, 214	ER_AUDIT_LOG_SWITCHING_TO_INCLUDE_LIST, 213
ER_AUDIT_LOG_FILTER_FAILED_TO_READ_TABLE, 215	ER_AUDIT_LOG_TABLE_DEFINITION_NOT_UPDATED, 345
ER_AUDIT_LOG_FILTER_FAILED_TO_STORE_TABLE_FILTERS, 214	ER_AUDIT_LOG_UDF_INSUFFICIENT_PRIVILEGE, 343
ER_AUDIT_LOG_FILTER_FAILED_TO_UPDATE_TABLE, 214	ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_COUNT, 366
ER_AUDIT_LOG_FILTER_FLD_FILTERNAME_CANNOT_BE_EMPTY, 215	ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_TYPE, 366
ER_AUDIT_LOG_FILTER_IS_NOT_INSTALLED, 213	ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH, 366
ER_AUDIT_LOG_FILTER_RESULT_MSG, 214	366
ER_AUDIT_LOG_FILTER_USER_AND_HOST_CANNOT_BE_EMPTY, 215	ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH, 75
ER_AUDIT_LOG_HAS_NOT_BEEN_INSTALLED, 366	ER_AUDIT_LOG_USER_FIRST_CHARACTER_MUST_BE_ALPHA, 344
ER_AUDIT_LOG_HOST_NAME_INVALID_CHARACTER, 343	ER_AUDIT_LOG_USER_NAME_INVALID_CHARACTER, 343
ER_AUDIT_LOG_INDEX_MAP_CANNOT_ACCESS_DIR, 213	ER_AUDIT_LOG_WRITER_DEST_FILE_ALREADY_EXISTS, 213
ER_AUDIT_LOG_INSUFFICIENT_PRIVILEGE, 106	ER_AUDIT_LOG_WRITER_FAILED_TO_WRITE_TO_FILE, 213
ER_AUDIT_LOG_INVALID_FILE_CONTENT, 363	ER_AUDIT_LOG_WRITER_INCOMPLETE_FILE_RENAMED, 213
ER_AUDIT_LOG_INVALID_FLUSH_INTERVAL_VALUE, 413	ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED, 213
ER_AUDIT_LOG_JSON_FILTERING_NOT_ENABLED, 343	ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED_REMOVE_F, 213
ER_AUDIT_LOG_JSON_FILTER_DOES_NOT_EXIST, 344	ER_AUDIT_PLUGIN_DOES_NOT_SUPPORT_AUDIT_AUTH_EVENTS, 161
ER_AUDIT_LOG_JSON_FILTER_NAME_CANNOT_BE_EMPTY, 343	ER_AUDIT_PLUGIN_HAS_INVALID_DATA, 161
ER_AUDIT_LOG_JSON_FILTER_PARSING_ERROR, 343	ER_AUDIT_WARNING, 190
ER_AUDIT_LOG_JSON_READER_BUF_TOO_SMALL, 214	ER_AUTHCACHE_CANT_INIT_GRANT_SUBSYSTEM, 159
ER_AUDIT_LOG_JSON_READER_FAILED_TO_OPEN_FILE, 214	ER_AUTHCACHE_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLE, 159
ER_AUDIT_LOG_JSON_READER_FAILED_TO_PARSE, 214	ER_AUTHCACHE_DB_ENTRY_LOWERCASED_REVOKE_WILL_FAIL, 159
ER_AUDIT_LOG_JSON_READER_FILE_PARSING_ERROR, 214	ER_AUTHCACHE_DB_IGNORED_EMPTY_NAME, 159

ER_AUTHCACHE_DB_SKIPPED_NEEDS_RESOLVE, 159	ER_AUTHENTICATION_OCI_TOKEN_NOT_VERIFIED, 411
ER_AUTHCACHE_DEFAULT_ROLES_IGNORED_EMPTY_NAME, 376	ER_AUTHENTICATION_PLUGIN_AUTH_DATA_CORRUPT, 392
ER_AUTHCACHE_DEFAULT_ROLES_UNKNOWN_AUTHORIZATION, 376	ER_AUTHENTICATION_PLUGIN_LOG, 393
ER_AUTHCACHE_EXPIRED_PASSWORD_UNSUPPORTED, 159	ER_AUTHENTICATION_PLUGIN_OOM, 392
ER_AUTHCACHE_PLUGIN_CONFIG, 158	ER_AUTHENTICATION_PLUGIN_REGISTRATION_FAILED, 392
ER_AUTHCACHE_PLUGIN_MISSING, 158	ER_AUTHENTICATION_PLUGIN_REGISTRATION_INSUFFICIENT, 392
ER_AUTHCACHE_PROCS_PRIV_ENTRY_IGNORED_BAD_ROUTINE, 159	ER_AUTHENTICATION_PLUGIN_SIGNATURE_CORRUPT, 392
ER_AUTHCACHE_PROCS_PRIV_SKIPPED_NEEDS_RESOLVE, 159	ER_AUTHENTICATION_PLUGIN_VERIFY_SIGNATURE_FAILED, 392
ER_AUTHCACHE_PROXIES_PRIV_SKIPPED_NEEDS_RESOLVE, 158	ER_AUTHENTICATION_POLICY_MISMATCH, 118
ER_AUTHCACHE_ROLE_EDGES_IGNORED_EMPTY_NAME, 376	ER_AUTH_CANT_ACTIVATE_ROLE, 157
ER_AUTHCACHE_ROLE_EDGES_UNKNOWN_AUTHORIZATION, 376	ER_AUTH_CANT_CREATE_RSA_PAIR, 157
ER_AUTHCACHE_TABLES_PRIV_SKIPPED_NEEDS_RESOLVE, 160	ER_AUTH_CANT_WRITE_PRIVKEY, 157
ER_AUTHCACHE_TABLE_PROXIES_PRIV_MISSING, 159	ER_AUTH_CANT_WRITE_PUBKEY, 157
ER_AUTHCACHE_USER_IGNORED_DEPRECATED_PASSWORD, 158	ER_AUTH_CERTS_SAVED_TO_DATADIR, 157
ER_AUTHCACHE_USER_IGNORED_INVALID_PASSWORD, 159	ER_AUTH_CERT_GENERATION_DISABLED, 158
ER_AUTHCACHE_USER_IGNORED_NEEDS_PLUGIN, 158	ER_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY, 358
ER_AUTHCACHE_USER_SKIPPED_NEEDS_RESOLVE, 158	ER_AUTH_KERBEROS_LOGGER_GENERIC_MSG, 389
ER_AUTHCACHE_USER_TABLE_DODGY, 158	ER_AUTH_KEYS_SAVED_TO_DATADIR, 158
ER_AUTHENTICATION_OCI_DOWNLOAD_IDDP_PUBLIC_KEY, 412	ER_AUTH_KEY_GENERATION_DISABLED, 158
ER_AUTHENTICATION_OCI_DOWNLOAD_PUBLIC_KEY, 393	ER_AUTH_KEY_GENERATION_SKIPPED_PAIR_PRESENT, 158
ER_AUTHENTICATION_OCI_IAM, 393	ER_AUTH_LDAP_ERROR_LOGGER_ERROR_MSG, 217
ER_AUTHENTICATION_OCI_IMDS, 393	ER_AUTH_RSA_CANT_FIND, 156
ER_AUTHENTICATION_OCI_INVALID_AUTHENTICATION_STRING, 393	ER_AUTH_RSA_CANT_PARSE, 156
ER_AUTHENTICATION_OCI_INVALID_TOKEN, 411	ER_AUTH_RSA_CANT_READ, 156
ER_AUTHENTICATION_OCI_NONCE, 394	ER_AUTH_RSA_CONF_PREVENTS_KEY_GENERATION, 158
ER_AUTHENTICATION_OCI_NO_GROUPS_FOUND, 393	ER_AUTH_RSA_FILES_NOT_FOUND, 156
ER_AUTHENTICATION_OCI_NO_MATCHING_GROUPS, 393	ER_AUTH_SSL_CONF_PREVENTS_CERT_GENERATION, 157
ER_AUTHENTICATION_OCI_PLUGIN_NOT_INITIALIZED, 393	ER_AUTH_USING_EXISTING_CERTS, 157
ER_AUTHENTICATION_OCI_PRIVATE_KEY_ERROR, 393	ER_AUTOINC_READ_FAILED, 33
ER_AUTHENTICATION_OCI_TOKEN_DETAILS_MISMATCH, 411	ER_AUTO_CONVERT, 19
	ER_AUTO_INCREMENT_CONFLICT, 59
	ER_AUTO_INCREMENT_NOT_SUPPORTED_FOR_FLOAT, 426
	ER_AUTO_OPTIONS_FAILED, 149
	ER_AUTO_POSITION_REQUIRES_GTID_MODE_NOT_OFF, 52
	ER_BACKGROUND_HISTOGRAM_UPDATE, 426
	ER_BACK_IN_TIME, 144
	ER_BAD_DB_ERROR, 6
	ER_BAD_FIELD_ERROR, 7
	ER_BAD_FT_COLUMN, 22
	ER_BAD_HOST_ERROR, 6

ER_BAD_LOG_STATEMENT, 39	ER_BINLOG_CRASH_RECOVERY_PREPARE_FAILED, 402
ER_BAD_NULL_ERROR, 6	ER_BINLOG_CRASH_RECOVERY_ROLLBACK_FAILED, 402
ER_BAD_NULL_ERROR_NOT_IGNORED, 88	ER_BINLOG_CREATE_ROUTINE_NEED_SUPER, 30
ER_BAD_REPLICA, 16	ER_BINLOG_END, 145
ER_BAD_REPLICA_AUTO_POSITION, 52	ER_BINLOG_ERROR_READING_GTIDS_FROM_BINARY_LOG, 184
ER_BAD_REPLICA_UNTIL_COND, 21	ER_BINLOG_ERROR_READING_GTIDS_FROM_RELAY_LOG, 184
ER_BAD_TABLE_ERROR, 6	ER_BINLOG_EVENTS_READ_FROM_APPLIER_METADATA, 184
ER_BAD_TIMESTAMP_FORMAT, 123	ER_BINLOG_EVENTS_READ_FROM_BINLOG_INFO, 184
ER_BASE64_DECODE_ERROR, 39	ER_BINLOG_EVENT_WRITE_TO_STMT_CACHE_FAILED, 194
ER_BASEDIR_SET_TO, 194	ER_BINLOG_FAILED_TO_CLOSE_INDEX_FILE_WHILE_REBUILDING_BINLOG, 185
ER_BEFORE_DML_VALIDATION_ERROR, 67	ER_BINLOG_FAILED_TO_DELETE_INDEX_FILE_WHILE_REBUILDING_BINLOG, 185
ER_BEG_INITFILE, 146	ER_BINLOG_FAILED_TO_DELETE_LOG_FILE, 187
ER_BEYOND_SERVER_DOWNGRADE_THRESHOLD, 414	ER_BINLOG_FAILED_TO_OPEN_INDEX_FILE_AFTER_REBUILDING_BINLOG, 185
ER_BEYOND_SERVER_UPGRADE_THRESHOLD, 414	ER_BINLOG_FAILED_TO_OPEN_REGISTER_FILE, 186
ER_BINLOG_CACHE_SIZE_GREATER_THAN_MAX, 50	ER_BINLOG_FAILED_TO_OPEN_TEMPORARY_INDEX_FILE, 185
ER_BINLOG_CACHE_SIZE_TOO_LARGE, 190	ER_BINLOG_FAILED_TO_READ_REGISTER_FILE, 187
ER_BINLOG_CANT_APPEND_LOG_TO_TMP_INDEX, 185	ER_BINLOG_FAILED_TO_REINIT_REGISTER_FILE, 186
ER_BINLOG_CANT_CLEAR_IN_USE_FLAG_FOR_CRASHED_BINLOG, 187	ER_BINLOG_FAILED_TO_RENAME_INDEX_FILE_WHILE_REBUILDING_BINLOG_FILES, 185
ER_BINLOG_CANT_CLOSE_TMP_INDEX, 186	ER_BINLOG_FAILED_TO_RUN_AFTER_FLUSH_HOOK, 188
ER_BINLOG_CANT_COPY_INDEX_TO_TMP, 186	ER_BINLOG_FAILED_TO_RUN_AFTER_SYNC_HOOK, 188
ER_BINLOG_CANT_DELETE_FILE, 185	ER_BINLOG_FAILED_TO_SET_PURGE_INDEX_FILE_NAME, 186
ER_BINLOG_CANT_DELETE_FILE_AND_READ_BINLOG_INDEX, 187	ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE, 184
ER_BINLOG_CANT_DELETE_LOG_FILE_DOES_INDEX_MATCH_BINLOG, 187	ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE_IN_OPEN, 185
ER_BINLOG_CANT_FIND_LOG_IN_INDEX, 187	ER_BINLOG_FAILED_TO_WRITE_DROP_FOR_TEMP_TABLES, 178
ER_BINLOG_CANT_GENERATE_NEW_FILE_NAME, 185	ER_BINLOG_FATAL_ERROR, 40
ER_BINLOG_CANT_LOCATE_OLD_BINLOG_OR_RELAY_LOG, 185	ER_BINLOG_FILE_BEING_READ_NOT_PURGED, 184
ER_BINLOG_CANT_MOVE_TMP_TO_INDEX, 186	ER_BINLOG_FILE_EXTENSION_NUMBER_EXHAUSTED, 184
ER_BINLOG_CANT_OPEN_CRASHED_BINLOG, 187	ER_BINLOG_FILE_EXTENSION_NUMBER_RUNNING_LOW, 184
ER_BINLOG_CANT_OPEN_FOR_LOGGING, 184	ER_BINLOG_FILE_NAME_TOO_LONG, 184
ER_BINLOG_CANT_OPEN_TMP_INDEX, 186	ER_BINLOG_FILE_OPEN_FAILED, 194
ER_BINLOG_CANT_RESIZE_CACHE, 184	
ER_BINLOG_CANT_SET_TMP_INDEX_NAME, 185	
ER_BINLOG_CANT_TRIM_CRASHED_BINLOG, 187	
ER_BINLOG_CANT_USE_FOR_LOGGING, 185	
ER_BINLOG_CRASHED_BINLOG_TRIMMED, 187	
ER_BINLOG_CRASH_RECOVERY_COMMIT_FAILED, 402	
ER_BINLOG_CRASH_RECOVERY_ENGINE_RESULTS, 402	
ER_BINLOG_CRASH_RECOVERY_ERROR_RETURNED, 402	
ER_BINLOG_CRASH_RECOVERY_MALFORMED_LOG, 402	

ER_BINLOG_IO_ERROR_READING_HEADER, 184	ER_BINLOG_STMT_CACHE_SIZE_GREATER_THAN_MAX, 50
ER_BINLOG_LOGGING_IMPOSSIBLE, 40	ER_BINLOG_STMT_CACHE_SIZE_TOO_LARGE, 190
ER_BINLOG_LOGGING_INCIDENT_TO_STOP_REPLICAS, 187	ER_BINLOG_STMT_MODE_AND_NO_REPL_TABLES, 57
ER_BINLOG_LOGGING_NOT_POSSIBLE, 203	ER_BINLOG_STMT_MODE_AND_ROW_ENGINE, 44
ER_BINLOG_LOGICAL_CORRUPTION, 58	ER_BINLOG_UNABLE_TO_ROTATE_GTID_TABLE_READON COMBINATION, 57
ER_BINLOG_MALFORMED_OR_OLD_RELAY_LOG, 204	ER_BINLOG_UNSAFE_ACL_TABLE_READ_IN_DML_DDL, 44
ER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION, 98	ER_BINLOG_UNSAFE_CREATE_IGNORE_SELECT, 48
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_AUX_KEY, 98	ER_BINLOG_UNSAFE_CREATE_REPLACE_SELECT, 48
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_UNUSED_KEYS, 98	ER_BINLOG_UNSAFE_CREATE_SELECT_AUTOINC, 48
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_OPERATE, 98	ER_BINLOG_UNSAFE_DEFAULT_EXPRESSION_IN_SUBST, 362
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_REENCRYPT_BINLOG, 98	ER_BINLOG_UNSAFE_FULLTEXT_PLUGIN, 60
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_ROTATE_LOGS, 98	ER_BINLOG_UNSAFE_INSERT_IGNORE_SELECT, 48
ER_BINLOG_MULTIPLE_ENGINES_AND_SELF_LOGGING_ENGINE, 44	ER_BINLOG_UNSAFE_INSERT_SELECT_UPDATE, 48
ER_BINLOG_NEEDS_SERVERID, 148	ER_BINLOG_UNSAFE_INSERT_TWO_KEYS, 49
ER_BINLOG_OOM_WRITING_DELETE_WHILE_OPENING_RELAY_LOG, 178	ER_BINLOG_UNSAFE_LIMIT, 45
ER_BINLOG_PURGE_EMFILE, 40	ER_BINLOG_UNSAFE_MESSAGE_AND_STATEMENT, 191
ER_BINLOG_PURGE_FATAL_ERR, 28	ER_BINLOG_UNSAFE_MIXED_STATEMENT, 46
ER_BINLOG_PURGE_LOGS_CALLED_WITH_FILE_NOT_REGISTERED, 186	ER_BINLOG_UNSAFE_MULTIPLE_ENGINES_AND_SELF_L, 46
ER_BINLOG_PURGE_LOGS_CANT_COPY_TO_REGISTERED_FILE, 186	ER_BINLOG_UNSAFE_NONTRANS_AFTER_TRANS, 45
ER_BINLOG_PURGE_LOGS_CANT_FLUSH_REGISTERED_FILE, 186	ER_BINLOG_UNSAFE_NOWAIT, 81
ER_BINLOG_PURGE_LOGS_CANT_SYNC_INDEX_FILE, 186	ER_BINLOG_UNSAFE_REPLACE_SELECT, 48
ER_BINLOG_PURGE_LOGS_CANT_UPDATE_INDEX_FILE, 186	ER_BINLOG_UNSAFE_ROUTINE, 30
ER_BINLOG_PURGE_LOGS_FAILED_TO_PURGE_LOG, 186	ER_BINLOG_UNSAFE_SKIP_LOCKED, 81
ER_BINLOG_PURGE_PROHIBITED, 27	ER_BINLOG_UNSAFE_STATEMENT, 40
ER_BINLOG_RECOVERING_AFTER_CRASH_USING, 187	ER_BINLOG_UNSAFE_SYSTEM_FUNCTION, 45
ER_BINLOG_ROW_ENGINE_AND_STMT_ENGINE, 44	ER_BINLOG_UNSAFE_SYSTEM_TABLE, 45
ER_BINLOG_ROW_INJECTION_AND_STMT_ENGINE, 44	ER_BINLOG_UNSAFE_SYSTEM_VARIABLE, 45
ER_BINLOG_ROW_INJECTION_AND_STMT_MODE, 44	ER_BINLOG_UNSAFE_UDF, 45
ER_BINLOG_ROW_LOGGING_FAILED, 37	ER_BINLOG_UNSAFE_UPDATE_IGNORE, 48
ER_BINLOG_ROW_MODE_AND_STMT_ENGINE, 44	ER_BINLOG_UNSAFE_WRITE_AUTOINC_SELECT, 48
ER_BINLOG_ROW_VALUE_OPTION_IGNORED, 339	ER_BINLOG_UNSAFE_XA, 75
ER_BINLOG_ROW_VALUE_OPTION_USED_ONLY_FOR_ARTBROBAGLES, 339	ER_BINLOG_WARNING_SUPPRESSED, 188
	ER_BLOBS_AND_NO_TERMINATED, 9
	ER_BLOB_CANT_HAVE_DEFAULT, 10
	ER_BLOB_KEY_IN_PART_FUNC_ERROR, 35
	ER_BLOB_KEY_WITHOUT_LENGTH, 14

ER_BLOB_USED_AS_KEY, 8	ER_BULK_PARSER_MISSING_ENCLOSED_BY_LOG,
ER_BLOCKED_CIPHER, 425	407
ER_BOOST_GEOMETRY_CENTROID_EXCEPTION,	ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS_EXCE
63	125
ER_BOOST_GEOMETRY_EMPTY_INPUT_EXCEPTION,	ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS_EXCE
63	407
ER_BOOST_GEOMETRY_INCONSISTENT_TURNS_EXCEPTION,	ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_T
69	125
ER_BOOST_GEOMETRY_OVERLAY_INVALID_INPUT_EXCEPTION,	ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_T
63	407
ER_BOOST_GEOMETRY_SELF_INTERSECTION_POINT_EXCEPTION,	ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENDING_EI
63	125
ER_BOOST_GEOMETRY_TURN_INFO_EXCEPTION,	ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENDING_EI
63	407
ER_BOOST_GEOMETRY_UNKNOWN_EXCEPTION,	ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESC,
63	125
ER_BOOTSTRAP_CANT_THREAD, 137	ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESC,
ER_BUFPOOL_RESIZE_INPROGRESS, 73	407
ER_BUILD_ID, 404	ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT,
ER_BULK_EXECUTOR_ERROR, 124	125
ER_BULK_EXECUTOR_INFO, 406	ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT_LOG,
ER_BULK_LOADER_COLUMN_TOO_BIG_FOR_LEFTOVER,	407
124	ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR,
ER_BULK_LOADER_COMPONENT_ERROR, 124	125
ER_BULK_LOADER_FILE_CONTAINS_LESS_LINES_THAN_EXPECTED,	ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR_LOG,
125	407
ER_BULK_LOADER_FILE_CONTAINS_LESS_LINES_THAN_EXPECTED_SECOND,	ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR_LOG,
406	407
ER_BULK_LOADER_INFO, 406	ER_BULK_READER_COMMUNICATION_ERROR,
ER_BULK_LOAD_DATA_FAILED, 124	124
ER_BULK_LOAD_RESOURCE, 129	ER_BULK_READER_COMMUNICATION_ERROR_LOG,
ER_BULK_LOAD_SECONDARY_ENGINE, 129	407
ER_BULK_LOAD_TABLE_HAS_INSTANT_COLS,	ER_BULK_READER_COULDNT_RESOLVE_HOST,
129	129
ER_BULK_MERGE_INVALID_CHUNK, 128	ER_BULK_READER_ERROR, 129
ER_BULK_MERGE_LOADER_INFO, 418	ER_BULK_READER_FILE_DOESNT_EXIST, 129
ER_BULK_MERGE_NOT_ALL_CHUNKS_CONSUMED,	ER_BULK_READER_INFO, 406
128	ER_BULK_READER_LIBCURL_ERROR, 124
ER_BULK_MULTI_READER_INFO, 418	ER_BULK_READER_LIBCURL_ERROR_LOG, 407
ER_BULK_MULTI_READER_OPEN_FILE_FAILED,	ER_BULK_READER_LIBCURL_INIT_FAILED, 124
128	ER_BULK_READER_LIBCURL_INIT_FAILED_LOG,
ER_BULK_MULTI_READER_READ_FILE_FAILED,	406
128	ER_BULK_READER_OPEN_FILE_FAILED, 129
ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED,	ER_BULK_READER_SERVER_ERROR, 124
125	ER_BULK_READER_SERVER_ERROR_LOG, 407
ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED_LOG,	ER_BULK_READER_ZSTD_ERROR, 136
407	ER_BULK_READER_ZSTD_ERROR_LOG, 427
ER_BULK_PARSER_ERROR, 136	ER_BULK_SCANNER_INFO, 428
ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE,	ER_BULK_SORTING_LOADER_INFO, 418
125	ER_BULK_SORTING_LOADER_WAIT, 129
ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE_LOG,	ER_BULK_SORTING_LOADER_WRITE, 129
408	ER_BULK_WRITER_INFO, 418
ER_BULK_PARSER_MISSING_ENCLOSED_BY, 125	ER_BULK_WRITER_LIBCURL_ERROR, 128
	ER_BULK_WRITER_LIBCURL_ERROR_LOG, 418
	ER_BULK_WRITER_LIBCURL_INIT_FAILED, 128

ER_BULK_WRITER_LIBCURL_INIT_FAILED_LOG, 418	ER_CANT_ALLOC_TABLE_OBJECT, 181
ER_CACHING_SHA2_PASSWORD_SECOND_PASSWORD, 353	ER_CANT_CHANGE_SYS_VAR_IN_READ_ONLY_MODE, 26
ER_CALL_ME_LOCALHOST, 145	USED_INFORMATION,
ER_CANNOT_ADD_FOREIGN, 17	ER_CANT_CHANGE_TX_CHARACTERISTICS, 39
ER_CANNOT_ADD_FOREIGN_BASE_COL_STORED, 75	ER_CANT_CHECK_PID_PATH, 258
ER_CANNOT_ADD_FOREIGN_BASE_COL_VIRTUAL, 73	ER_CANT_CHOWN_DATADIR, 149
ER_CANNOT_ALTER_SRID_DUE_TO_INDEX, 86	ER_CANT_COMBINE_ANONYMOUS_TO_GTID_AND_AUTO 114
ER_CANNOT_CHANGE_TO_ROOT_DIR, 193	ER_CANT_CREATE_ADMIN_THREAD, 353
ER_CANNOT_CONVERT_STRING, 102	ER_CANT_CREATE_CACHE_FOR_DB_OPT, 182
ER_CANNOT_CREATE_VIRTUAL_INDEX_CONSTRAINT, 73	ER_CANT_CREATE_DB, 3
ER_CANNOT_DISCARD_TEMPORARY_TABLE, 61	ER_CANT_CREATE_FILE, 3
ER_CANNOT_DROP_COLUMN_FUNCTIONAL_INDEX, 94	ER_CANT_CREATE_GEOMETRY_OBJECT, 30
ER_CANNOT_EXECUTE_IN_PRIMARY, 129	ER_CANT_CREATE_HANDLER_FILE, 35
ER_CANNOT_FIND_KEY_IN_KEYRING, 74	ER_CANT_CREATE_HANDLER_OBJECT_FOR_TABLE, 181
ER_CANNOT_GET_SERVER_VERSION_FROM_TABLESPACE, 355	ER_CANT_CREATE_HANDLE_MGR_THREAD, 139
ER_CANNOT_GRANT_ROLES_TO_ANONYMOUS_USER, 103	ER_CANT_CREATE_INTERRUPT_THREAD, 144
ER_CANNOT_GRANT_SYSTEM_PRIV_TO_MANDATORY_ROLE, 105	ER_CANT_CREATE_NAMED_PIPES_THREAD, 144
ER_CANNOT_INTERPRET_PERSISTED_SENSITIVE_VARIABLES, 396	ER_CANT_CREATE_PID_FILE, 143
ER_CANNOT_LOAD_FROM_TABLE_V2, 49	ER_CANT_CREATE_SCHEDULER_THREAD, 140
ER_CANNOT_LOCK_USER_MANAGEMENT_CACHES, 79	ER_CANT_CREATE_SHM_THREAD, 144
ER_CANNOT_LOG_PARTIAL_DROP_DATABASE_WITH_GRID, 67	ER_CANT_CREATE_SHUTDOWN_THREAD, 143
ER_CANNOT_PERSIST_SENSITIVE_VARIABLES, 121	ER_CANT_CREATE_TABLE, 3
ER_CANNOT_PURGE_BINLOG_WITH_BACKUP_LOCK, 120	ER_CANT_CREATE_TABLE_SHARE_FROM_FRM, 181
ER_CANNOT_SET_DATABASE_ENCRYPTION, 100	ER_CANT_CREATE_TCPIP_THREAD, 144
ER_CANNOT_SET_LOG_ERROR_SERVICES, 194	ER_CANT_CREATE_TEST_FILE, 143
ER_CANNOT_SET_SERVER_VERSION_IN_TABLESPACE, 355	ER_CANT_CREATE_THREAD, 12
ER_CANNOT_SET_TABLESPACE_ENCRYPTION, 100	ER_CANT_CREATE_USER_WITH_GRANT, 29
ER_CANNOT_SET_TABLE_ENCRYPTION, 100	ER_CANT_CREATE_UUID, 142
ER_CANNOT_USER, 28	ER_CANT_DETACH_SESSION_LEFT_BY_PLUGIN, 169
ER_CANNOT_USER_REFERENCED_AS_DEFINER, 113	ER_CANT_DO_IMPLICIT_COMMIT_IN_TRX_WHEN_GTID_N 52
ER_CANNOT_USE_AUTOEXTEND_SIZE_CLAUSE, 115	ER_CANT_DO_THIS_DURING_AN_TRANSACTION, 15
ER_CANNOT_USE_ENCRYPTION_CLAUSE, 100	ER_CANT_DROP_FIELD_OR_KEY, 9
ER_CANT_ACCESS_CAPATH, 149	ER_CANT_ENFORCE_GTID_CONSISTENCY_WITH_ONGOI 69
ER_CANT_AGGREGATE_2COLLATIONS, 21	HEADER,
ER_CANT_AGGREGATE_3COLLATIONS, 21	ER_CANT_EXECUTE_COMMAND_WITH_ASSIGNED_GTID 121
ER_CANT_AGGREGATE_NCOLLATIONS, 21	ER_CANT_EXECUTE_IN_READ_ONLY_TRANSACTION, 53
	ER_CANT_FIND_DL_ENTRY, 12
	ER_CANT_FIND_SYSTEM_REC, 4
	ER_CANT_FIND_UDF, 11
	ER_CANT_GET_STAT, 4
	ER_CANT_HASH_DO_AND_IGNORE_RULES, 149
	ER_CANT_IDENTIFY_CHARSET_USING_DEFAULT, 182
	ER_CANT_INCREASE_MAX_OPEN_FILES, 146
	ER_CANT_INITIALIZE_BUILTIN_PLUGINS, 148
	ER_CANT_INITIALIZE_DYNAMIC_PLUGINS, 148

ER_CANT_INITIALIZE_EARLY_PLUGINS, 148
ER_CANT_INITIALIZE_GTID, 148
ER_CANT_INITIALIZE_UDF, 11
ER_CANT_INIT_DB, 147
ER_CANT_INIT_SCHEDULER_THREAD, 140
ER_CANT_INIT_TC_LOG, 139
ER_CANT_INIT_TIMER, 149
ER_CANT_JOIN_SHUTDOWN_THREAD, 149
ER_CANT_LOCK, 4
ER_CANT_LOCK_LOG_TABLE, 38
ER_CANT_LOCK_TABLE, 181
ER_CANT_LOCK_TABLESPACE, 181
ER_CANT_MODIFY_SRID_0, 91
ER_CANT_MODIFY_SRS_USED_BY_COLUMN, 91
ER_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES, 161
ER_CANT_OPEN_CA, 149
ER_CANT_OPEN_DATADIR_AFTER_UPGRADE_FAILURE, 183
ER_CANT_OPEN_DB_OPT_USING_DEFAULT_CHARSET, 181
ER_CANT_OPEN_DIR, 183
ER_CANT_OPEN_ERROR_LOG, 150
ER_CANT_OPEN_FILE, 4
ER_CANT_OPEN_FRM_FILE, 161
ER_CANT_OPEN_LIBRARY, 12
ER_CANT_OPEN_TABLE_MYSQL_PROC, 183
ER_CANT_PARSE_STORED_ROUTINE_BODY, 182
ER_CANT_PROCESS_EXPRESSION_FOR_GENERATED_COLUMNS, 368
ER_CANT_READ_DIR, 4
ER_CANT_READ_ERRMSG, 147
ER_CANT_READ_FRM_FILE, 161
ER_CANT_READ_TABLE_MYSQL_PROC, 183
ER_CANT_REMOVE_ALL_FIELDS, 9
ER_CANT_REMOVE_PID_FILE, 143
ER_CANT_RENAME_LOG_TABLE, 39
ER_CANT_REOPEN_TABLE, 12
ER_CANT_REPLICATE_ANONYMOUS_WITH_AUTO_POSITION, 342
ER_CANT_REPLICATE_ANONYMOUS_WITH_GTID_MODE_ON, 343
ER_CANT_REPLICATE_GTID_WITH_GTID_MODE_OFF, 343
ER_CANT_RESET_SOURCE, 75
ER_CANT_RUN_COMMAND_SERVICES_RECURSIVELY, 127
ER_CANT_SAVE_GTIDS, 149
ER_CANT_SET_DATA_DIR, 351
ER_CANT_SET_ERROR_LOG_SERVICE, 90
ER_CANT_SET_ERROR_SUPPRESSION_LIST, 92
ER_CANT_SET_ERROR_SUPPRESSION_LIST_FROM_COMMAND_LINE, 346
ER_CANT_SET_GTID_MODE, 68
ER_CANT_SET_GTID_NEXT_LIST_TO_NON_NULL_WHEN_GTID_MODE_ON, 53
ER_CANT_SET_GTID_NEXT_TO_ANONYMOUS_WHEN_GTID_MODE_ON, 52
ER_CANT_SET_GTID_NEXT_TO_AUTOMATIC_TAGGED_WHEN_GTID_MODE_ON, 130
ER_CANT_SET_GTID_NEXT_TO_GTID_WHEN_GTID_MODE_ON, 52
ER_CANT_SET_GTID_NEXT_WHEN_OWNING_GTID, 53
ER_CANT_SET_GTID_PURGED_DUE_SETS_CONSTRAINTS, 79
ER_CANT_SET_GTID_PURGED_WHEN_GTID_EXECUTED_IS_NULL, 56
ER_CANT_SET_GTID_PURGED_WHEN_OWNED_GTIDS_IS_NULL, 57
ER_CANT_SET_HANDLER_REFERENCE_FOR_TABLE, 181
ER_CANT_SET_PATH_FOR, 183
ER_CANT_SET_PERSISTED, 126
ER_CANT_SET_SQL_AFTER_OR_BEFORE_GTIDS_WITH_ANONYMOUS, 115
ER_CANT_SET_UP_PERSISTED_VALUES, 149
ER_CANT_SET_VARIABLE_WHEN_OWNING_GTID, 71
ER_CANT_START_ERROR_LOG_SERVICE, 193
ER_CANT_STAT_DATADIR, 149
ER_CANT_STAT_FILE, 187
ER_CANT_UPDATE_COLUMN_UPDATE_TABLE_IN_CREATE_TABLE_SELECT, 50
ER_CANT_UPDATE_USED_TABLE_IN_SF_OR_TRG, 31
ER_CANT_UPDATE_WITH_READLOCK, 18
ER_CANT_UPGRADE_GENERATED_COLUMNS_TO_DD, 181
ER_CANT_USE_ANONYMOUS_TO_GTID_WITH_GTID_MODE_ON, 114
ER_CANT_USE_AUTO_POSITION_WITH_GTID_MODE_OFF, 51
ER_CANT_USE_GTID_ONLY_WITH_GTID_MODE_NOT_ON, 51
ER_CANT_USE_OPTION_HERE, 19
ER_CANT_USE_SAME_UUID_AS_GROUP_NAME, 115
ER_CANT_USE_SAME_UUID_AS_VIEW_CHANGE_UUID, 116
ER_CANT_WAIT_FOR_EXECUTED_GTID_SET_WHILE_OWNING_GTID, 73
ER_CAPACITY_EXCEEDED, 73
ER_CAPACITY_EXCEEDED_IN_PARSER, 74
ER_CAPACITY_EXCEEDED_IN_RANGE_OPTIMIZER, 74
ER_CA_SELF_SIGNED, 141

ER_CHANGED_ENFORCE_GTID_CONSISTENCY, 139	ER_CHECK_TABLE_MIN_REC_FLAG_NOT_SET, 410
ER_CHANGED_GTID_MODE, 139	ER_CHECK_TABLE_MIN_REC_FLAG_SET, 410
ER_CHANGED_MAX_CONNECTIONS, 146	ER_CLIENT_DOES_NOT_SUPPORT, 86
ER_CHANGED_MAX_OPEN_FILES, 146	ER_CLIENT_FILE_PRIVILEGE_FOR_REPLICATION_CHECK, 123
ER_CHANGED_TABLE_OPEN_CACHE, 146	ER_CLIENT_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE, 93
ER_CHANGE_REPLICATION_SOURCE_NO_OPTIONS_FOR_GTID_ONLY, 119	ER_CLIENT_INTERACTION_TIMEOUT, 116
ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POSITIONS, 119	ER_CLIENT_KEYRING_UDF_KEY_INVALID, 107
ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POSITIONS_WITHOUT_POSITIONS, 119	ER_CLIENT_KEYRING_UDF_KEY_TOO_LONG, 107
ER_CHANGE_REP_SOURCE_CANT_DISABLE_GTID_ONLY_WITHOUT_POSITIONS, 119	ER_CLIENT_KEYRING_UDF_KEY_TYPE_INVALID, 107
ER_CHANGE_REP_SOURCE_CANT_DISABLE_REQ_ROW_FORMAT_WITH_GTID_ONLY, 119	ER_CLIENT_KEYRING_UDF_KEY_TYPE_TOO_LONG, 107
ER_CHANGE_REP_SOURCE_GR_CHANNEL_WITH_GTID_MODE_NOT_ALLOWED, 119	ER_CLIENT_LOCAL_FILES_DISABLED, 109
ER_CHANGE_RPL_INFO_REPOSITORY_FAILURE, 50	ER_CLIENT_PRIVILEGE_CHECKS_USER_CANNOT_BE_ADMIN, 107
ER_CHANGE_RPL_SRC_WRONG_COMPRESSION_ALGORITHM_SIZE, 116	ER_CLIENT_PRIVILEGE_CHECKS_USER_CORRUPT, 107
ER_CHANGE_SOURCE_PASSWORD_LENGTH, 64	ER_CLIENT_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST, 107
ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM_CLIENT, 106	ER_CLIENT_PRIVILEGE_CHECKS_USER_NEEDS_RPL_APPLIC, 107
ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM_LIST_CLIENT, 107	ER_CLIENT_QUERY_FAILURE_INVALID_NON_ROW_FORMAT, 107
ER_CHANGE_SOURCE_WRONG_COMPRESSION_LEVEL_CLIENT, 106	ER_CLONE_CHARSET, 103
ER_CHARACTER_SET_MISMATCH, 113	ER_CLONE_CLIENT_TRACE, 351
ER_CHECKING_TABLE, 181	ER_CLONE_CONFIG, 103
ER_CHECKREAD, 4	ER_CLONE_CREATE_HANDLER_FAIL_TRACE, 200
ER_CHECK_CONSTRAINT_CLAUSE_USING_FK_REFERENCED_COLUMNS, 99	ER_CLONE_DDL_IN_PROGRESS, 85
ER_CHECK_CONSTRAINT_DUP_NAME, 99	ER_CLONE_DISALLOWED, 103
ER_CHECK_CONSTRAINT_FUNCTION_IS_NOT_ALLOWED, 99	ER_CLONE_DISKSPACE, 103
ER_CHECK_CONSTRAINT_NAMED_FUNCTION_IS_NOT_ALLOWED, 99	ER_CLONE_DONOR, 102
ER_CHECK_CONSTRAINT_NOT_FOUND, 99	ER_CLONE_DONOR_TRACE, 351
ER_CHECK_CONSTRAINT_REFERS_AUTO_INCREMENTED_COLUMN, 99	ER_CLONE_DONOR_VERSION, 102
ER_CHECK_CONSTRAINT_REFERS_UNKNOWN_COLUMN, 99	ER_CLONE_ENCRYPTION, 103
ER_CHECK_CONSTRAINT_ROW_VALUE, 99	ER_CLONE_HANDLER_EXIST_TRACE, 200
ER_CHECK_CONSTRAINT_VARIABLES, 99	ER_CLONE_IN_PROGRESS, 103
ER_CHECK_CONSTRAINT_VIOLATED, 99	ER_CLONE_LOOPBACK, 103
ER_CHECK_NOT_IMPLEMENTED, 15	ER_CLONE_NETWORK_PACKET, 109
ER_CHECK_NO_SUCH_TABLE, 15	ER_CLONE_OS, 103
ER_CHECK_TABLE_FUNCTIONS, 415	ER_CLONE_PLATFORM, 103
ER_CHECK_TABLE_FUNCTIONS_DETAIL, 415	ER_CLONE_PLUGIN_MATCH, 103
ER_CHECK_TABLE_INSTANT_VERSION_BIT_SET, 408	ER_CLONE_PLUGIN_NOT_LOADED_TRACE, 200
	ER_CLONE_PROTOCOL, 102
	ER_CLONE_PROTOCOL_TRACE, 351
	ER_CLONE_SERVER_TRACE, 351
	ER_CLONE_SHUTDOWN_TRACE, 365
	ER_CLONE_SYS_CONFIG, 103
	ER_CLONE_TOO_MANY_CONCURRENT_CLONES, 85
	ER_CMD_NEED_SUPER, 85
	ER_COALESCE_ONLY_ON_HASH_PARTITION, 36

ER_COALESCE_PARTITION_NO_PARTITION, 36	ER_COMPONENT_EE_DATA_ENCRYPTION_ERROR, 403
ER_COLLATION_CHARSET_MISMATCH, 20	ER_COMPONENT_EE_DATA_LENGTH_OUT_OF_RANGE, 403
ER_COLUMNACCESS_DENIED_ERROR, 13	ER_COMPONENT_EE_DATA_SIGN_ERROR, 403
ER_COLUMN_CHANGE_SIZE, 104	ER_COMPONENT_EE_FUNCTION_DEREGISTRATION_FAILURE, 402
ER_COLUMN_CHECK_CONSTRAINT_REFERENCES_OTHER_COLUMNS, 99	ER_COMPONENT_EE_FUNCTION_INVALID_ALGORITHM, 403
ER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2, 54	ER_COMPONENT_EE_FUNCTION_INVALID_ARGUMENTS, 403
ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE, 38	ER_COMPONENT_EE_FUNCTION_KEY_LENGTH_OUT_OF_RANGE, 403
ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V2, 61	ER_COMPONENT_EE_FUNCTION_PRIVATE_KEY_GENERATION_ERROR, 403
ER_COMMAND_BACKEND_FAILED_TO_FETCH_SECURITY_CTX, 122	ER_COMPONENT_EE_FUNCTION_PUBLIC_KEY_GENERATION_ERROR, 403
ER_COMMAND_SERVICE_BACKEND_FAILED, 123	ER_COMPONENT_EE_FUNCTION_REGISTRATION_FAILURE, 402
ER_COMMENT_CONTAINS_INVALID_STRING, 121	ER_COMPONENT_EE_INSUFFICIENT_LENGTH, 403
ER_COMMIT_NOT_ALLOWED_IN_SF_OR_TRG, 30	ER_COMPONENT_EE_OPENSSL_ERROR, 403
ER_COMPONENTS_CANT_ACQUIRE_SERVICE_IMPLEMENTATION, 78	ER_COMPONENT_EE_SYS_VAR_DEREGISTRATION_FAILURE, 402
ER_COMPONENTS_CANT_LOAD, 78	ER_COMPONENT_EE_SYS_VAR_REGISTRATION_FAILURE, 402
ER_COMPONENTS_CANT_RELEASE_SERVICE, 78	ER_COMPONENT_FILTER_CONFUSED, 218
ER_COMPONENTS_CANT_SATISFY_DEPENDENCY, 78	ER_COMPONENT_FILTER_DIAGNOSTICS, 90
ER_COMPONENTS_CANT_UNLOAD, 79	ER_COMPONENT_FILTER_FLABBERGASTED, 84
ER_COMPONENTS_FAILED_TO_ACQUIRE_SERVICE_IMPLEMENTATION, 203	ER_COMPONENT_FILTER_WRONG_VALUE, 340
ER_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP, 141	ER_COMPONENT_KEYRING_OCI_CREATE_PRIVATE_KEY, 404
ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_DEINIT, 384	ER_COMPONENT_KEYRING_OCI_INVALID_CONFIG_VAR, 418
ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_INIT, 384	ER_COMPONENT_KEYRING_OCI_OPEN_KEY_FILE, 404
ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN, 141	ER_COMPONENT_KEYRING_OCI_READ_KEY_FILE, 404
ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN_END, 417	ER_COMPONENT_LOCK, 412
ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN_START, 417	ER_COMPONENT_MANIPULATE_ROW_FAILED, 79
ER_COMPONENTS_LOAD_CANT_INITIALIZE, 78	ER_COMPONENT_MASKING_ABI, 412
ER_COMPONENTS_LOAD_CANT_REGISTER_SERVICE_IMPLEMENTATION, 78	ER_COMPONENT_MASKING_ABI_REASON, 413
ER_COMPONENTS_NO_SCHEME, 78	ER_COMPONENT_MASKING_CANNOT_ACCESS_TABLE, 413
ER_COMPONENTS_NO_SCHEME_SERVICE, 78	ER_COMPONENT_MASKING_INVALID_FLUSH_INTERVAL_VALUE, 424
ER_COMPONENTS_PERSIST_LOADER_BOOTSTRAP, 141	ER_COMPONENT_MASKING_NOTIFICATION_REGISTRATION_FAILURE, 402
ER_COMPONENTS_UNLOAD_CANT_DEINITIALIZE, 78	ER_COMPONENT_MASKING_OTHER_ERROR, 412
ER_COMPONENTS_UNLOAD_CANT_UNREGISTER_SERVICE, 79	ER_COMPONENT_MASKING_RANDOM_CREATE, 413
ER_COMPONENTS_UNLOAD_DUPLICATE_IN_GROUP, 79	ER_COMPONENT_MASKING_RANDOM_CREATE_REASON, 413
ER_COMPONENTS_UNLOAD_NOT_LOADED, 78	
ER_COMPONENT_EE_DATA_DECRYPTION_ERROR, 403	

ER_COMPONENT_MASKING_VAR_REGISTRATION_FAILED, 424
 ER_COMPONENT_SERVICE_CALL, 412
 ER_COMPONENT_SERVICE_CALL_RESULT, 412
 ER_COMPONENT_TABLE_INCORRECT, 79
 ER_COMPONENT_UNLOCK, 412
 ER_CONCURRENT_PROCEDURE_USAGE, 120
 ER_CONDITIONAL_DEBUG, 404
 ER_COND_ITEM_TOO_LONG, 43
 ER_CONFIG_OPTION_WITHOUT_GROUP, 151
 ER_CONFIRMING_THE_FUTURE, 144
 ER_CONFLICTING_DECLARATIONS, 23
 ER_CONFLICT_FN_PARSE_ERROR, 42
 ER_CONNECTIONS_SHUTDOWN_END, 417
 ER_CONNECTIONS_SHUTDOWN_START, 417
 ER_CONNECTION_ABORTED, 339
 ER_CONNECTION_HANDLING_OOM, 143
 ER_CONNECTION_METADATA, 16
 ER_CONNECT_TO_FOREIGN_DATA_SOURCE, 30
 ER_CONNECT_TO_SOURCE, 18
 ER_CONN_ATTR_TRUNCATED, 156
 ER_CONN_CONTROL_DELAY_ACTION_INIT_FAILED, 219
 ER_CONN_CONTROL_ERROR_MSG, 217
 ER_CONN_CONTROL_EVENT_COORDINATOR_INIT_FAILED, 218
 ER_CONN_CONTROL_FAILED_TO_SET_CONN_DELAY, 219
 ER_CONN_CONTROL_FAILED_TO_UPDATE_CONN_DELAY, 219
 ER_CONN_CONTROL_INVALID_CONN_DELAY_TYPE, 219
 ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED, 219
 ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_BY_UPDATE_VALUES, 218
 ER_CONN_INIT_CONNECT_IGNORED, 218
 ER_CONN_INIT_CONNECT_IGNORED_MFA, 413
 ER_CONN_LIMIT, 395
 ER_CONN_PER_THREAD_NO_THREAD, 154
 ER_CONN_PIP_CANT_CREATE_EVENT, 154
 ER_CONN_PIP_CANT_CREATE_PIPE, 154
 ER_CONN_SHM_CANT_CREATE_CONNECTION, 153
 ER_CONN_SHM_CANT_CREATE_SERVICE, 153
 ER_CONN_SHM_LISTENER, 153
 ER_CONN_SOCKET_ACCEPT_FAILED, 156
 ER_CONN_SOCKET_SELECT_FAILED, 156
 ER_CONN_TCP_ADDRESS, 154
 ER_CONN_TCP_BIND_FAIL, 155
 ER_CONN_TCP_BIND_RETRY, 155
 ER_CONN_TCP_CANT_RESET_V6ONLY, 154
 ER_CONN_TCP_CANT_RESOLVE_HOSTNAME, 154
 ER_CONN_TCP_CREATED, 154
 ER_CONN_TCP_ERROR_WITH_STRError, 154
 ER_CONN_TCP_IPV6_AVAILABLE, 154
 ER_CONN_TCP_IPV6_UNAVAILABLE, 154
 ER_CONN_TCP_IP_NOT_LOGGED, 155
 ER_CONN_TCP_IS_THERE_ANOTHER_USING_PORT, 154
 ER_CONN_TCP_LISTEN_FAIL, 155
 ER_CONN_TCP_NO_SOCKET, 154
 ER_CONN_TCP_RESOLVE_INFO, 155
 ER_CONN_TCP_START_FAIL, 155
 ER_CONN_UNIX_IS_THERE_ANOTHER_USING_SOCKET, 154
 ER_CONN_UNIX_LISTEN_FAILED, 155
 ER_CONN_UNIX_LOCK_FILE_CANT_CLOSE, 156
 ER_CONN_UNIX_LOCK_FILE_CANT_CREATE, 155
 ER_CONN_UNIX_LOCK_FILE_CANT_DELETE, 156
 ER_CONN_UNIX_LOCK_FILE_CANT_OPEN, 155
 ER_CONN_UNIX_LOCK_FILE_CANT_READ, 155
 ER_CONN_UNIX_LOCK_FILE_CANT_SYNC, 156
 ER_CONN_UNIX_LOCK_FILE_CANT_WRITE, 156
 ER_CONN_UNIX_LOCK_FILE_EMPTY, 156
 ER_CONN_UNIX_LOCK_FILE_FAIL, 155
 ER_CONN_UNIX_LOCK_FILE_GIVING_UP, 155
 ER_CONN_UNIX_LOCK_FILE_PIDLESS, 156
 ER_CONN_UNIX_NO_BIND_NO_START, 155
 ER_CONN_UNIX_NO_FD, 155
 ER_CONN_UNIX_PATH_TOO_LONG, 155
 ER_CONN_UNIX_PID_CLAIMED_SOCKET_FILE, 154
 ER_CONSECUTIVE_REORG_PARTITIONS, 36
 ER_CONSTRAINT_NOT_FOUND, 108
 ER_CREATE_FAILED_MULTI_VALUE, 413
 ER_CREATE_FAILED_UPDATE_VALUES, 144
 ER_CORRUPTED_JSON_DIFF, 86
 ER_CORRUPT_HELP_DB, 19
 ER_COULD_NOT_APPLY_JSON_DIFF, 86
 ER_COULD_NOT_CREATE_WINDOWS_REGISTRY_KEY, 348
 ER_COULD_NOT_REINITIALIZE_AUDIT_LOG_FILTERS, 344
 ER_CRASHED_ON_REPAIR, 16
 ER_CRASHED_ON_USAGE, 16
 ER_CREATED_SYSTEM_WITH_VERSION, 199
 ER_CREATE_FILEGROUP_FAILED, 37
 ER_CREATE_SELECT_WITH_GIPK_DISALLOWED_IN_SBR, 122
 ER_CREATING_NEW_UUID, 142
 ER_CREATING_NEW_UUID_FIRST_START, 193
 ER_CREDENTIALLESS_AUTO_USER_BAD, 143
 ER_CREDENTIALS_CONTRADICT_TO_HISTORY, 85
 ER_CTE_MAX_RECURSION_DEPTH, 85

ER_CTE_RECURSIVE_FORBIDDEN_JOIN_ORDER, 81
ER_CTE_RECURSIVE_FORBIDS_AGGREGATION, 81
ER_CTE_RECURSIVE_NOT_UNION, 122
ER_CTE_RECURSIVE_REQUIRES_NONRECURSIVE_FIRST, 81
ER_CTE_RECURSIVE_REQUIRES_SINGLE_REFERENCE, 81
ER_CTE_RECURSIVE_REQUIRES_UNION, 81
ER_CURRENT_PASSWORD_CANNOT_BE_RETAINED, 105
ER_CURRENT_PASSWORD_NOT_REQUIRED, 104
ER_CUT_VALUE_GROUP_CONCAT, 20
ER_CYCLE_TIMER_IS_NOT_AVAILABLE, 200
ER_DATABASE_NAME, 42
ER_DATA_DIRECTORY_UNUSABLE, 349
ER_DATA_DIRECTORY_UNUSABLE_DELETABLE, 364
ER_DATA_INCOMPATIBLE_WITH_VECTOR, 136
ER_DATA_OUT_OF_RANGE, 46
ER_DATA_TOO_LONG, 29
ER_DATETIME_FUNCTION_OVERFLOW, 31
ER_DA_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANAGED_OBJECTS, 104
ER_DA_CANT_OPEN_ERROR_LOG, 113
ER_DA_CONN_LIMIT, 120
ER_DA_ERROR_LOG_COMPONENT_FLUSH_FAILED, 117
ER_DA_ERROR_LOG_MULTIPLE_FILTERS, 113
ER_DA_ERROR_LOG_TABLE_DISABLED, 113
ER_DA_GLOBAL_CONN_LIMIT, 120
ER_DA_GRP_RPL_RECOVERY_ENDPOINT_FORMAT, 111
ER_DA_GRP_RPL_RECOVERY_ENDPOINT_INVALID, 111
ER_DA_GRP_RPL_STARTED_AUTO_REJOIN, 106
ER_DA_INVALID_CONDITION_NUMBER, 51
ER_DA_NO_ERROR_LOG_PARSER_CONFIGURED, 113
ER_DA_OOM, 109
ER_DA_PLUGIN_INSTALL_ERROR, 104
ER_DA_RPL_GTID_TABLE_CANNOT_OPEN, 104
ER_DA_SSL_FIPS_MODE_ERROR, 119
ER_DA_SSL_LIBRARY_ERROR, 104
ER_DA_UDF_INVALID_ARGUMENT_TO_SET_CHARSET, 109
ER_DA_UDF_INVALID_CHARSET, 108
ER_DA_UDF_INVALID_CHARSET_SPECIFIED, 108
ER_DA_UDF_INVALID_COLLATION, 108
ER_DA_UDF_INVALID_EXTENSION_ARGUMENT_TYPE, 108
ER_DA_UDF_INVALID_RETURN_TYPE_TO_SET_CHARSET, 109
ER_DA_UNKNOWN_ERROR_NUMBER, 104
ER_DBACCESS_DENIED_ERROR, 6
ER_DEBUG_CHECK_SHARES_DROPPED, 170
ER_DEBUG_CHECK_SHARES_INFO, 170
ER_DEBUG_CHECK_SHARES_OPEN, 170
ER_DB_ACCESS_DENIED, 103
ER_DB_CREATE_EXISTS, 4
ER_DB_DROP_EXISTS, 4
ER_DB_DROP_RMDIR, 4
ER_DB_DROP_RMDIR2, 83
ER_DB_OPT_NOT_FOUND_USING_DEFAULT_CHARSET, 182
ER_DDL_MSG_1, 390
ER_DD_ABORTING_PARTIAL_UPGRADE, 160
ER_DD_CACHE_NOT_EMPTY_AT_SHUTDOWN, 138
ER_DD_CANT_CREATE_OBJECT_KEY, 139
ER_DD_CANT_CREATE_SP, 181
ER_DD_CANT_FETCH_TABLE_DATA, 181
ER_DD_CANT_FIX_SE_DATA, 181
ER_DD_CANT_GET_OBJECT_KEY, 139
ER_DD_CANT_RESOLVE_VIEW, 150
ER_DD_CREATED_FOR_UPGRADE, 160
ER_DD_CREATE_FAILED, 181
ER_DD_FAILSAFE, 137
ER_DD_FRM_EXISTS_FOR_TABLE, 160
ER_DD_INITIALIZE, 204
ER_DD_INITIALIZE_SQL_ERROR, 345
ER_DD_INIT_FAILED, 138
ER_DD_INIT_UPGRADE_FAILED, 138
ER_DD_METADATA_NOT_FOUND, 138
ER_DD_MINOR_DOWNGRADE, 205
ER_DD_MINOR_DOWNGRADE_VERSION_NOT_SUPPORTED, 205
ER_DD_NO_VERSION_FOUND, 205
ER_DD_NO_WRITES_NO_REPOPULATION, 137
ER_DD_OBJECT_RELEASER_REMAINS, 138
ER_DD_OBJECT_REMAINS, 138
ER_DD_OBJECT_REMAINS_IN_RELEASER, 138
ER_DD_RESTART, 204
ER_DD_SCHEMA_NOT_FOUND, 160
ER_DD_SE_INIT_FAILED, 160
ER_DD_TABLESPACE_NOT_FOUND, 150
ER_DD_TABLE_NOT_FOUND, 160
ER_DD_TRG_CANT_ADD, 150
ER_DD_TRG_CONNECTION_COLLATION_MISSING, 150
ER_DD_TRG_DB_COLLATION_MISSING, 150
ER_DD_TRG_DEFINER_OOM, 150
ER_DD_TRG_FILE_UNREADABLE, 150
ER_DD_UPDATE_DATADIR_FLAG_FAIL, 428
ER_DD_UPDATING_PLUGIN_MD_FAILED, 138
ER_DD_UPGRADE, 204
ER_DD_UPGRADE_COMPLETED, 362

ER_DD_UPGRADE_DD_OPEN_FAILED, 197	ER_DEBUG_SYNC_OOM, 139
ER_DD_UPGRADE_DD_POPULATED, 198	ER_DEBUG_SYNC_THREAD_MAX, 139
ER_DD_UPGRADE_FAILED_FIND_VALID_DATA_DIR, 198	ER_DEBUG_SYNC_TIMEOUT, 43
ER_DD_UPGRADE_FAILED_INIT_DD_SE, 198	ER_DEFAULT_AS_VAL_GENERATED, 95
ER_DD_UPGRADE_FAILED_TO_ACQUIRE_TABLESPACE, 197	ER_DEFAULT_SE_UNAVAILABLE, 149
ER_DD_UPGRADE_FAILED_TO_CREATE_INDEX_STATS, 198	ER_DEFAULT_VAL_GENERATED_FUNCTION_IS_NOT_ALL, 95
ER_DD_UPGRADE_FAILED_TO_CREATE_TABLE_STATS, 198	ER_DEFAULT_VAL_GENERATED_NAMED_FUNCTION_IS_I, 95
ER_DD_UPGRADE_FAILED_TO_FETCH_TABLES, 198	ER_DEFAULT_VAL_GENERATED_NON_PRIOR, 95
ER_DD_UPGRADE_FAILED_TO_FETCH_TABLESPACES, 197	ER_DEFAULT_VAL_GENERATED_REF_AUTO_INC, 95
ER_DD_UPGRADE_FAILED_TO_RESOLVE_TABLESPACE, 197	ER_DEFAULT_VAL_GENERATED_ROW_VALUE, 95
ER_DD_UPGRADE_FAILED_TO_UPDATE_VER_NO_IN_TABLESPACE, 204	ER_DEFAULT_VAL_GENERATED_VARIABLES, 95
ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD, 199	ER_DEFINITION_CONTAINS_INVALID_STRING, ENGINE,
ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD, 199	ER_DEPART_WITH_GRACE, 141
ER_DD_UPGRADE_INDEX_STATS_MIGRATE_COMPLETED, 198	ER_DEPENDENT_BY_CHECK_CONSTRAINT, 110
ER_DD_UPGRADE_INFO_FILE_CLOSE_FAILED, 198	ER_DEPENDENT_BY_DEFAULT_GENERATED_VALUE, 95
ER_DD_UPGRADE_INFO_FILE_OPEN_FAILED, 198	ER_ABORT,
ER_DD_UPGRADE_OFF, 204	ER_DEPENDENT_BY_FUNCTIONAL_INDEX, 100
ER_DD_UPGRADE_RENAME_IDX_STATS_FILE_FAILED, 197	ER_DEPENDENT_BY_GENERATED_COLUMN, 68
ER_DD_UPGRADE_SCHEMA_UNAVAILABLE, 205	ER_DEPENDENT_BY_PARTITION_FUNC, 102
ER_DD_UPGRADE_SDI_INFO_UPDATE_FAILED, 199	ER_DEPRECATED_NATIONAL, 91
ER_DD_UPGRADE_SE_LOGS_FAILED, 199	ER_DEPRECATED_PERSISTED_VARIABLE_WITH_ALIAS, 389
ER_DD_UPGRADE_START, 198	ER_DEPRECATED_SYNTAX_NO_REPLACEMENT, 203
ER_DD_UPGRADE_TABLESPACE_MIGRATION_FAILED, 198	ER_DEPRECATED_SYNTAX_WITH_REPLACEMENT, 203
ER_DD_UPGRADE_TABLE_INTACT_ERROR, 202	ER_DEPRECATED_TIMESTAMP_IMPLICIT_DEFAULTS, 143
ER_DD_UPGRADE_TABLE_STATS_MIGRATE_COMPLETED, 198	ER_DEPRECATED_UTF8_ALIAS, 91
ER_DD_UPGRADE_VERSION_NOT_SUPPORTED, 205	ER_DEPRECATE_MSG_NO_REPLACEMENT, 203
ER_DD_UPGRADE_VIEW_COLUMN_NAME_TOO_LONG, 204	ER_DEPRECATE_MSG_WITH_REPLACEMENT, 192
ER_DD_VERSION_FOUND, 137	ER_DERIVED_MUST_HAVE_ALIAS, 19
ER_DD_VERSION_INSTALLED, 137	ER_DERIVED_MUST_HAVE_ALIAS, 19
ER_DD_VERSION_UNSUPPORTED, 137	ER_DES_FILE_WRONG_KEY, 151
ER_DD_VIEW_CANT_ALLOC_CHARSET, 138	ER_DETACHED_SESSIONS_LEFT_BY_PLUGIN, 169
ER_DD_VIEW_CANT_CREATE, 138	ER_DETACHING_SESSION_LEFT_BY_PLUGIN, 169
ER_DD_VIEW_WITHOUT_DEFINER, 150	ER_DIMENSION_UNSUPPORTED, 65
ER_DEBUG_SYNC_EXECUTED, 139	ER_DISABLED_STORAGE_ENGINE, 72
ER_DEBUG_SYNC_HIT, 139	ER_DISABLED_STORAGE_ENGINE_AS_DEFAULT, 139
ER_DEBUG_SYNC_HIT_LIMIT, 43	ER_DISABLE_AUTO_POSITION_REQUIRES_ASYNC_REC, 112
	ER_DISABLE_GTID_MODE_REQUIRES_ASYNC_RECONNE, 112
	ER_DISALLOWED_OPERATION, 87
	ER_DISCARD_FK_CHECKS_RUNNING, 54
	ER_DISCONNECTING_REMAINING_CLIENTS, 145
	ER_DISK_FULL_NOWAIT, 88
	ER_DIVISION_BY_ZERO, 27

ER_DONT_SUPPORT_REPLICA_PRESERVE_COMMIT_ORDER, 15
62
ER_DROP_DATABASE_FAILED_RMDIR_MANUALLY, 204
ER_DROP_FILEGROUP_FAILED, 37
ER_DROP_INDEX_FK, 38
ER_DROP_LAST_PARTITION, 36
ER_DROP_PARTITION_NON_EXISTENT, 35
ER_DROP_PK_COLUMN_TO_DROP_GIPK, 122
ER_DUPLICATED_VALUE_IN_TYPE, 22
ER_DUPLICATE_OPTION_KEY, 80
ER_DUPLICATE_SYS_VAR, 345
ER_DUPLICATE_TABLE_LOCK, 81
ER_DUP_ARGUMENT, 18
ER_DUP_ENTRY, 7
ER_DUP_ENTRY_AUTOINCREMENT_CASE, 39
ER_DUP_ENTRY_WITH_KEY_NAME, 40
ER_DUP_FD_OPEN_FAILED, 193
ER_DUP_FIELDNAME, 7
ER_DUP_INDEX, 56
ER_DUP_KEY, 4
ER_DUP_KEYNAME, 7
ER_DUP_LIST_ENTRY, 62
ER_DUP_SIGNAL_SET, 43
ER_DUP_UNIQUE, 14
ER_DUP_UNKNOWN_IN_INDEX, 58
ER_EMPTY_PIPELINE_FOR_ERROR_LOG_SERVICE, 90
ER_EMPTY_PRIVILEGE_NAME_IGNORED, 380
ER_EMPTY_QUERY, 7
ER_ENDING_INIT, 344
ER_END_INITFILE, 146
ER_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONLINE_DROPING, 69
ER_ENGINE_ATTRIBUTE_NOT_SUPPORTED, 111
ER_ENGINE_CANNOT_BE_DEFAULT, 135
ER_ENGINE_CANT_DROP_MISSING_TABLE, 83
ER_ENGINE_CANT_DROP_TABLE, 83
ER_ENGINE_COST_FAILED_TO_READ, 167
ER_ENGINE_COST_INVALID_CONST_CONSTANT_FOR_SE, 167
ER_ENGINE_COST_INVALID_DEVICE_TYPE_FOR_SE, 167
ER_ENGINE_COST_UNKNOWN_COST_CONSTANT, 167
ER_ENGINE_COST_UNKNOWN_STORAGE_ENGINE, 167
ER_ENGINE_OUT_OF_MEMORY, 61
ER_ERRMSG_CANT_FIND_FILE, 160
ER_ERRMSG_CANT_READ, 160
ER_ERRMSG_MISSING_IN_FILE, 160
ER_ERRMSG_OOM, 160
ER_ERRMSG_REPLACEMENTS_FAILED, 189
ER_ERRMSG_REPLACEMENT_DODGY, 189
ER_ERROR_DURING_COMMIT, 15
ER_ERROR_DURING_FLUSH_LOGS, 15
ER_ERROR_DURING_FLUSH_LOG_COMMIT_PHASE, 203
ER_ERROR_DURING_OPTIMIZE_TABLE, 180
ER_ERROR_DURING_ROLLBACK, 15
ER_ERROR_ENABLING_KEYS, 180
ER_ERROR_INFO_FROM_DA, 342
ER_ERROR_IN_TRIGGER_BODY, 47
ER_ERROR_IN_UNKNOWN_TRIGGER_BODY, 47
ER_ERROR_LOG_DESTINATION_NOT_A_FILE, 380
ER_ERROR_ON_MODIFYING_GTID_EXECUTED_TABLE, 74
ER_ERROR_ON_READ, 4
ER_ERROR_ON_RENAME, 5
ER_ERROR_ON_SOURCE, 60
ER_ERROR_ON_WRITE, 5
ER_ERROR_WHEN_EXECUTING_COMMAND, 18
ER_EVENT_ALREADY_EXISTS, 37
ER_EVENT_CANNOT ALTER_IN_THE_PAST, 40
ER_EVENT_CANNOT_CREATE_IN_THE_PAST, 40
ER_EVENT_CANT_FIND_TIMEZONE, 182
ER_EVENT_CANT_GET_CHARSET, 182
ER_EVENT_CANT_GET_COLLATION, 182
ER_EVENT_CANT_GET_LOCK_FOR_DROPPING_EVENT, 183
ER_EVENT_CANT_GET_TIMEZONE_FROM_FIELD, 182
ER_EVENT_CANT_INIT_QUEUE, 139
ER_EVENT_CANT_OPEN_TABLE_MYSQL_EVENT, 182
ER_EVENT_DOES_NOT_EXIST, 37
ER_EVENT_DROPING, 168
ER_EVENT_ENDS_BEFORE_STARTS, 37
ER_EVENT_ERROR_CREATING_QUERY_TO_WRITE_TO_BINLOG, 183
ER_EVENT_ERROR_DURING_COMPILATION, 168
ER_EVENT_EXECUTION_FAILED, 140
ER_EVENT_EXECUTION_FAILED_CANT_AUTHENTICATE_USER_AND_DEVICE, 168
ER_EVENT_EXECUTION_FAILED_USER_LOST_EVEN_PRIVILEGE, 168
ER_EVENT_EXEC_TIME_IN_THE_PAST, 38
ER_EVENT_INTERVAL_NOT_POSITIVE_OR_TOO_BIG, 37
ER_EVENT_INVALID_CREATION_CTX, 41
ER_EVENT_LAST_EXECUTION, 140
ER_EVENT_MESSAGE_STACK, 140
ER_EVENT_PURGING_QUEUE, 140
ER_EVENT_RECURSION_FORBIDDEN, 39
ER_EVENT_SAME_NAME, 38
ER_EVENT_SCHEDULER_ERROR_GETTING_EVENT_OBJECT, 183

ER_EVENT_SCHEDULER_ERROR_LOADING_FROM_DB, 183
ER_EVENT_SCHEDULER_GOT_BAD_DATA_FROM_TABLE, 183
ER_EVENT_SET_VAR_ERROR, 39
ER_EVENT_UNABLE_TO_DROP_EVENT, 183
ER_EXCEEDED_MV_KEYS_NUM, 105
ER_EXCEEDED_MV_KEYS_SPACE, 105
ER_EXCEEDS_VECTOR_MAX_DIMENSIONS, 136
ER_EXCEPTIONS_WRITE_ERROR, 42
ER_EXCESS_ARGUMENTS, 147
ER_EXPLAIN_INT0_ANALYZE_NOT_SUPPORTED, 127
ER_EXPLAIN_INT0_FORMAT_NOT_SUPPORTED, 127
ER_EXPLAIN_INT0_FOR_CONNECTION_NOT_SUPPORTED, 127
ER_EXPLAIN_INT0_IMPLICIT_FORMAT_NOT_SUPPORTED, 127
ER_EXPLAIN_NOT_SUPPORTED, 61
ER_EXTERNAL_UNSUPPORTED_INDEX_ALGORITHM, 136
ER_FAILED_DEFAULT_ROLES, 78
ER_FAILED_GET_DD_PROPERTY, 414
ER_FAILED_READ_FROM_PAR_FILE, 46
ER_FAILED_REVOKE_ROLE, 78
ER_FAILED_ROLE_GRANT, 77
ER_FAILED_SET_DD_PROPERTY, 414
ER_FAILED_START_MYSQLD_DAEMON, 193
ER_FAILED_TO_ACQUIRE_LOCK_ON_RESOURCE_GROUP, 196
ER_FAILED_TO_ADD_RESOURCE_GROUP_TO_MAP, 196
ER_FAILED_TO_ADD_RPL_FILTER, 200
ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP, 195
ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP_HASH, 195
ER_FAILED_TO_ALLOCATE_SSL_BIO, 345
ER_FAILED_TO_APPLY_RESOURCE_GROUP_CONTROL, 196
ER_FAILED_TO_BINLOG_DROP_EVENT, 199
ER_FAILED_TO_BUILD_DO_AND_IGNORE_TABLE_HASHES, 200
ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE, 164
ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE_FROM, 164
ER_FAILED_TO_CONSTRUCT_DROP_EVENT_QUERY, 199
ER_FAILED_TO_CREATE_GTID_TABLE_COMPRESSION_THREAD, 164
ER_FAILED_TO_CREATE_SDI_FOR_TABLESPACE, 197
ER_FAILED_TO_DECREMENT_NUMBER_OF_THREADS, 169
ER_FAILED_TO_DELETE_FROM_GTID_EXECUTED_TABLE, 164
ER_FAILED_TO_DESERIALIZE_RESOURCE_GROUP, 195
ER_FAILED_TO_DETERMINE_IF_ROLE_IS_MANDATORY, 109
ER_FAILED_TO_FETCH_MANDATORY_ROLE_LIST, 109
ER_FAILED_TO_FIND_COLLATION_NAME, 192
ER_FAILED_TO_FIND_DL_ENTRY, 190
ER_FAILED_TO_FIND_LOCALE_NAME, 192
ER_FAILED_TO_FIND_MYSQLD_STATUS, 203
ER_FAILED_TO_GENERATE_UNIQUE_LOGFILE, 190
ER_FAILED_TO_GET_ABSOLUTE_PATH, 193
ER_FAILED_TO_HANDLE_DEFAULTS_FILE, 345
ER_FAILED_TO_INIT_SYS_VAR, 345
ER_FAILED_TO_INIT_THREAD_ATTR_FOR_GTID_TABLE_COMPRESSION_THREAD, 164
ER_FAILED_TO_JOIN_GTID_TABLE_COMPRESSION_THREADS, 164
ER_FAILED_TO_LOCK_MEM, 146
ER_FAILED_TO_OPEN_COST_CONSTANT_TABLES, 167
ER_FAILED_TO_OPEN_SHARED_LIBRARY, 190
ER_FAILED_TO_PERSIST_RESOURCE_GROUP_METADATA, 195
ER_FAILED_TO_READ_FILE, 191
ER_FAILED_TO_REMOVE_TEMP_TABLE, 178
ER_FAILED_TO_REPAIR_TABLE, 178
ER_FAILED_TO_SET_PERSISTED_OPTIONS, 203
ER_FAILED_TO_START_REPLICA_THREAD, 199
ER_FAILED_TO_STORE_SDI_FOR_TABLESPACE, 197
ER_FAILED_TO_UPDATE_RESOURCE_GROUP, 195
ER_FAILED_TO_VALIDATE_CERTIFICATES_SERVER_EXIT, 168
ER_FAILED_TO_WRITE_TO_FILE, 191
ER_FAIL_CHROOT, 146
ER_FAIL_SETGID, 145
ER_FAIL_SETREGID, 145
ER_FAIL_SETREUID, 146
ER_FAIL_SETTUID, 145
ER_FEATURE_DISABLED, 22
ER_FEATURE_DISABLED_SEE_DOC, 73
ER_FEATURE_NOT_AVAILABLE, 68
ER_FEATURE_UNSUPPORTED, 87
ER_THREAD_IN_GROUPING_NOT_GROUP_BY, 83
ER_FIELD_IN_ORDER_NOT_SELECT, 65
ER_FIELD_NOT_FOUND_PART_ERROR, 34
ER_FIELD_SPECIFIED_TWICE, 10

ER_FIELD_TYPE_NOT_ALLOWED_AS_PARTITION_FIELD, 44
 ER_FILEGROUP_OPTION_ONLY_ONCE, 37
 ER_FILE_CORRUPT, 60
 ER_FILE_EXISTS_DURING_UPGRADE, 183
 ER_FILE_EXISTS_ERROR, 9
 ER_FILE_HAS_OLD_FORMAT, 192
 ER_FILE_NOT_FOUND, 4
 ER_FILE_TYPE_UNKNOWN, 161
 ER_FILE_USED, 5
 ER_FIREWALL_ACCESS_DENIED, 212
 ER_FIREWALL_DEPRECATED_USER_PROFILE, 387
 ER_FIREWALL_FAILED_TO_READ_FIREWALL_TABLES, 212
 ER_FIREWALL_FAILED_TO_REG_DYNAMIC_PRIVILEGES, 212
 ER_FIREWALL_INVALID_RELOAD_INTERVAL_VALUE, 418
 ER_FIREWALL_PFS_TABLE_REGISTER_FAILED, 383
 ER_FIREWALL_RECORDING_STMT_WAS_TRUNCATED, 212
 ER_FIREWALL_RECORDING_STMT_WITHOUT_TEXT, 212
 ER_FIREWALL_RELOADING_CACHE, 212
 ER_FIREWALL_RESET_FOR_USER, 212
 ER_FIREWALL_SCHEDULER_REGISTER_FAILED, 418
 ER_FIREWALL_SERVICES_NOT_ACQUIRED, 383
 ER_FIREWALL_SKIPPED_UNKNOWN_USER_MODE, 212
 ER_FIREWALL_STATUS_FLUSHED, 213
 ER_FIREWALL_SUSPICIOUS_STMT, 212
 ER_FIREWALL_UDF_REGISTER_FAILED, 383
 ER_FIXING_CLIENT_CHARSET, 146
 ER_FK_CANNOT_CHANGE_ENGINE, 95
 ER_FK_CANNOT_DROP_PARENT, 92
 ER_FK_CANNOT_OPEN_PARENT, 55
 ER_FK_CANNOT_USE_VIRTUAL_COLUMN, 92
 ER_FK_COLUMN_CANNOT_CHANGE, 56
 ER_FK_COLUMN_CANNOT_CHANGE_CHILD, 56
 ER_FK_COLUMN_CANNOT_DROP, 56
 ER_FK_COLUMN_CANNOT_DROP_CHILD, 56
 ER_FK_COLUMN_NOT_NULL, 56
 ER_FK_DEPTH_EXCEEDED, 61
 ER_FK_DUP_NAME, 56
 ER_FK_FAIL_ADD_SYSTEM, 55
 ER_FK_INCOMPATIBLE_COLUMNS, 96
 ER_FK_INCORRECT_OPTION, 56
 ER_FK_NO_COLUMN_PARENT, 92
 ER_FK_NO_INDEX_CHILD, 55
 ER_FK_NO_INDEX_PARENT, 55
 ER_FK_NO_UNIQUE_INDEX_PARENT, 135
 ER_FORBID_SCHEMA_CHANGE, 32
 ER_FORCE_CLOSE_THREAD, 191
 ER_FORCING_CLOSE, 8
 ER_FOREIGN_DATA_SOURCE_DOESNT_EXIST, 31
 ER_FOREIGN_DATA_STRING_INVALID, 31
 ER_FOREIGN_DATA_STRING_INVALID_CANT_CREATE, 31
 ER_FOREIGN_DUPLICATE_KEY_OLD_UNUSED, 38
 ER_FOREIGN_DUPLICATE_KEY_WITHOUT_CHILD_INFO, 51
 ER_FOREIGN_DUPLICATE_KEY_WITH_CHILD_INFO, 51
 ER_FOREIGN_KEY_ON_PARTITIONED, 35
 ER_FOREIGN_KEY_WITH_ATOMIC_CREATE_SELECT, 31
 ER_FOREIGN_SERVER_DOESNT_EXIST, 34
 ER_FOREIGN_SERVER_EXISTS, 34
 ER_FOUND_MISSING_GTIDS, 257
 ER_FOUND_ROWS_WHILE_REPAIRING, 180
 ER_FPARSER_BAD_HEADER, 25
 ER_FPARSER_EOF_IN_COMMENT, 25
 ER_FPARSER_EOF_IN_UNKNOWN_PARAMETER, 26
 ER_FPARSER_ERROR_IN_PARAMETER, 25
 ER_FPARSER_TOO_BIG_FILE, 25
 ER_FSEEK_FAIL, 27
 ER_FT_BOOL_SYNTAX_INVALID, 143
 ER_FT_MATCHING_KEY_NOT_FOUND, 16
 ER_FULLTEXT_FUNCTIONAL_INDEX, 94
 ER_FULLTEXT_NOT_SUPPORTED_WITH_PARTITIONING, 51
 ER_FULLTEXT_WITH_ROLLUP, 120
 ER_FUNCTIONAL_INDEX_DATA_IS_TOO_LONG, 106
 ER_FUNCTIONAL_INDEX_FUNCTION_IS_NOT_ALLOWED, 94
 ER_FUNCTIONAL_INDEX_ON_FIELD, 94
 ER_FUNCTIONAL_INDEX_ON_JSON_OR_GEOMETRY_FUNCTIONS, 94
 ER_FUNCTIONAL_INDEX_ON_LOB, 94
 ER_FUNCTIONAL_INDEX_PRIMARY_KEY, 94
 ER_FUNCTIONAL_INDEX_REF_AUTO_INCREMENT, 94
 ER_FUNCTIONAL_INDEX_ROW_VALUE_IS_NOT_ALLOWED, 97
 ER_FUNCTION_DOES_NOT_SUPPORT_CHARACTER_SET, 112
 ER_FUNCTION_NOT_DEFINED, 12
 ER_FUNC_INEXISTENT_NAME_COLLISION, 42
 ER_FUTURE_DATE, 145
 ER_GENERATED_COLUMN_FUNCTION_IS_NOT_ALLOWED, 68

ER_GENERATED_COLUMN_NAMED_FUNCTION_IS_NOT_ALLOWED, 94	ER_GROUP_REPLICATION_COMPRESS_PROCESS, 419
ER_GENERATED_COLUMN_NON_PRIOR, 68	ER_GROUP_REPLICATION_CONFIGURATION, 67
ER_GENERATED_COLUMN_REF_AUTO_INC, 68	ER_GROUP_REPLICATION_DECOMPRESS_CORRUPTED, 420
ER_GENERATED_COLUMN_ROW_VALUE, 95	ER_GROUP_REPLICATION_DECOMPRESS_END, 420
ER_GENERATED_COLUMN_VARIABLES, 95	ER_GROUP_REPLICATION_DECOMPRESS_EXCEEDS_MAX_SIZE, 420
ER_GEOMETRY_IN_UNKNOWN_LENGTH_UNIT, 104	ER_GROUP_REPLICATION_DECOMPRESS_OUT_OF_MEMORY, 420
ER_GEOMETRY_PARAM_LATITUDE_OUT_OF_RANGE, 92	ER_GROUP_REPLICATION_DECOMPRESS_PROCESS, 420
ER_GEOMETRY_PARAM_LONGITUDE_OUT_OF_RANGE, 92	ER_GROUP_REPLICATION_DECOMPRESS_TRUNCATED, 420
ER_GET_ERRMSG, 22	ER_GROUP_REPLICATION_ERROR_COMPRESS_INITIALIZATION_FAILED, 419
ER_GET_ERRNO, 5	ER_GROUP_REPLICATION_ERROR_DECOMPRESS_INITIALIZATION_FAILED, 420
ER_GET_ERRNO_FROM_STORAGE_ENGINE, 192	ER_GROUP_REPLICATION_ERROR_RECEIVED_WAITING_FOR_SLAVE, 421
ER_GET_STACKED_DATA_WITHOUT_ACTIVE_HANDLER, 60	ER_GROUP_REPLICATION_FORCE_MEMBERS_COMMAND_FAILED, 123
ER_GET_TEMPORARY_ERRMSG, 22	ER_GROUP_REPLICATION_MAX_GROUP_SIZE, 75
ER_GIPK_COLUMN_ALTER_NOT_ALLOWED, 122	ER_GROUP_REPLICATION_METADATA_CERT_INFO_ENCRYPTION_FAILED, 423
ER_GIPK_COLUMN_EXISTS, 122	ER_GROUP_REPLICATION_METADATA_CERT_INFO_ERROR, 421
ER_GIPK_FAILED_AUTOINC_COLUMN_EXISTS, 122	ER_GROUP_REPLICATION_METADATA_CERT_INFO_PACKET_TOO_LARGE, 423
ER_GIS_DATA_WRONG_ENDIANNESS, 64	ER_GROUP_REPLICATION_METADATA_CERT_INFO_PACKET_TOO_SMALL, 422
ER_GIS_DIFFERENT_SRIDS, 63	ER_GROUP_REPLICATION_METADATA_ERROR_ON_SENDING_PACKET, 422
ER_GIS_DIFFERENT_SRIDS_AGGREGATION, 116	ER_GROUP_REPLICATION_METADATA_INITIALIZATION_FAILED, 422
ER_GIS_INVALID_DATA, 63	ER_GROUP_REPLICATION_METADATA_MEMORY_ALLOCATION_FAILED, 422
ER_GIS_MAX_POINTS_IN_GEOMETRY_OVERFLOWED, 70	ER_GROUP_REPLICATION_METADATA_MESSAGE_PAYLOAD_TOO_LARGE, 421
ER_GIS_UNKNOWN_ERROR, 63	ER_GROUP_REPLICATION_METADATA_NO_VALID_DONOR_SLAVE, 421
ER_GIS_UNKNOWN_EXCEPTION, 63	ER_GROUP_REPLICATION_METADATA_PAYLOAD_DECODING_FAILED, 421
ER_GIS_UNSUPPORTED_ARGUMENT, 63	ER_GROUP_REPLICATION_METADATA_PAYLOAD_EMPTY, 421
ER_GLOBAL_CONN_LIMIT, 395	ER_GROUP_REPLICATION_METADATA_PROTOBUF_PARSING_FAILED, 421
ER_GLOBAL_VARIABLE, 18	ER_GROUP_REPLICATION_METADATA_READ_GTID_EXECLOG_FAILED, 421
ER_GLOBSTAT_CHANGE_DURING_QUERY, 106	ER_GROUP_REPLICATION_METADATA_SAVE_RECOVERY_LOG_FAILED, 421
ER_GNO_EXHAUSTED, 52	ER_GROUP_REPLICATION_METADATA_SENDER, 419
ER_GRANT_WRONG_HOST_OR_USER, 13	
ER_GROUPING_ON_TIMESTAMP_IN_DST, 106	
ER_GROUP_REPLICATION_APPLIER_INIT_ERROR, 67	
ER_GROUP_REPLICATION_CERTIFICATION_MODULE_FAILURE, 422	
ER_GROUP_REPLICATION_CERTIFIER_MESSAGE_TOO_LARGE, 419	
ER_GROUP_REPLICATION_COMMAND_FAILURE, 87	
ER_GROUP_REPLICATION_COMMUNICATION_LAYER_JOIN_ERROR, 67	
ER_GROUP_REPLICATION_COMMUNICATION_LAYER_SESSION_ERROR, 67	
ER_GROUP_REPLICATION_COMPRESS_EXCEEDS_MAX_SIZE, 419	
ER_GROUP_REPLICATION_COMPRESS_OUT_OF_MEMORY, 420	

ER_GROUP_REPLICATION_METADATA_SENDER_IS_REMOTE,	ER_GRP_RPL_ADD_VIEW_CHANGE_UUID_TO_GRP_SID_MAP,
419	388
ER_GROUP_REPLICATION_METADATA_SEND_ERROR,	ER_GRP_RPL_ALL_DONORS_LEFT_ABORT_RECOVERY,
421	239
ER_GROUP_REPLICATION_METADATA_SET_IN_RECOVERY_FAILED,	ER_GRP_RPL_ALL_OBSERVERS_UNREGISTERED,
422	246
ER_GROUP_REPLICATION_NO_CERTIFICATION_DONOR_AVAILABLE,	ER_GRP_RPL_APPLIER_CHANNEL_STILL_RUNNING,
423	383
ER_GROUP_REPLICATION_PASSWORD_LENGTH,	ER_GRP_RPL_APPLIER_ERROR_PACKET_RECEIVED,
111	424
ER_GROUP_REPLICATION_PLUGIN_NOT_INSTALLED,	ER_GRP_RPL_APPLIER_EXECUTION_FATAL_ERROR,
164	229
ER_GROUP_REPLICATION_PROTOBUF_SERIALIZING_ERROR,	ER_GRP_RPL_APPLIER_HANDLER_IS_IN_USE,
421	248
ER_GROUP_REPLICATION_RECOVERY_ERROR_ADD_GTID_EXECUTED,	ER_GRP_RPL_APPLIER_HANDLER_NOT_INITIALIZED,
422	248
ER_GROUP_REPLICATION_RECOVERY_FETCHING_GTID_EXECUTED_SET,	ER_GRP_RPL_APPLIER_HANDLER_ROLE_IS_IN_USE,
422	249
ER_GROUP_REPLICATION_RECOVERY_METADATA_SENDER_NOTIFICATION,	ER_GRP_RPL_APPLIER_INITIALIZED,
422	246
ER_GROUP_REPLICATION_RECOVERY_SKIPPED_GTID_PRESENT,	ER_GRP_RPL_APPLIER_METADATA_REPO_MUST_BE_TABLE,
422	247
ER_GROUP_REPLICATION_RECOVERY_STOPPED_GTID_PRESENT,	ER_GRP_RPL_APPLIER_NOT_STARTED_DUE_TO_RUNNING,
423	246
ER_GROUP_REPLICATION_RUNNING,	ER_GRP_RPL_APPLIER_PIPELINE_NOT_DISPOSED,
67	229
ER_GROUP_REPLICATION_STOP_APPLIER_THREAD_TIMEOUT,	ER_GRP_RPL_APPLIER_TERMINATION_TIMED_OUT_ON_SHUTDOWN,
67	245
ER_GROUP_REPLICATION_TIMEOUT_ERROR_FETCHING_METADATA,	ER_GRP_RPL_APPLIER_THD_EXECUTION_ABORTED,
421	229
ER_GROUP_REPLICATION_UNKOWN_COMPRESSION_TYPE,	ER_GRP_RPL_APPLIER_THD_KILLED,
419	229
ER_GROUP_REPLICATION_USER_EMPTY_MSG,	ER_GRP_RPL_APPLIER_THD_SETUP_ERROR,
110	235
ER_GROUP_REPLICATION_USER_MANDATORY_MSG,	ER_GRP_RPL_APPLIER_THD_START_ERROR,
111	236
	ER_GRP_RPL_APPLIER_THD_STOP_ERROR,
	236
ER_GRP_OPERATION_NOT_ALLOWED_GRP_MUST_STOP,	ER_GRP_RPL_APPOINTED_PRIMARY_NOT_PRESENT,
110	347
	ER_GRP_RPL_AUTO_INC_OFFSET_RESET,
	236
ER_GRP_RPL_ABORTS_AS_SSL_NOT_SUPPORTED_BY_MYSQLD,	ER_GRP_RPL_AUTO_INC_OFFSET_SET,
246	237
	ER_GRP_RPL_AUTO_INC_RESET,
	236
ER_GRP_RPL_ADD_GRP_SID_TO_GRP_GTIDSID_MAP_ERROR,	ER_GRP_RPL_AUTO_INC_SET,
230	237
	ER_GRP_RPL_BINLOG_DISABLED,
	246
ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_LOCAL_GTID_FAILED,	ER_GRP_RPL_BLOCK_SIZE_DIFF_FROM_GRP,
237	235
	ER_GRP_RPL_BROADCASTING_TRANS_TO_GRP_FAILED,
	242
ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_REMOTE_GTID_FAILED,	ER_GRP_RPL_BROADCAST_COMMIT_MSSG_TOO_BIG,
238	242
	ER_GRP_RPL_BROADCAST_COMMIT_TRANS_MSSG_FAILED,
	251
ER_GRP_RPL_ADD_GTID_INFO_WITH_LOCAL_GTID_FAILED,	ER_GRP_RPL_BROADCAST_COMMIT_TRANS_MSSG_FAILED,
237	242
	ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_ERROR_STATE,
	240
ER_GRP_RPL_ADD_GTID_INFO_WITH_REMOTE_GTID_FAILED,	ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_OFFLINE_MODE,
238	240
	ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_RECOVERING,
	240
ER_GRP_RPL_ADD_GTID_TO_GRP_GTID_EXECUTED_ERROR,	ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_RECOVERING,
230	241
	241
ER_GRP_RPL_ADD_RETRIEVED_SET_TO_GRP_GTID_EXECUTED_ERROR,	
230	

ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_STOPPING, 241	ER_GRP_RPL_CREATE_GRP_RPL_REC_CHANNEL, 239
ER_GRP_RPL_CANT_GENERATE_GTID, 231	ER_GRP_RPL_CREATE_SESSION_UNABLE, 239
ER_GRP_RPL_CANT_KILL_THREAD, 365	ER_GRP_RPL_DATA_NOT_PROVIDED_BY_MEM, 234
ER_GRP_RPL_CANT_READ_GRP_GTID_EXTRACTED, 231	ER_GRP_RPL_DEBUG_OPTIONS, 250
ER_GRP_RPL_CANT_READ_GTID, 231	ER_GRP_RPL_DEFAULT_TABLE_ENCRYPTION_DIFF_FRO 359
ER_GRP_RPL_CANT_READ_WRITE_SET_ITEM, 231	ER_GRP_RPL_DISABLE_READ_ONLY_FAILED, 233
ER_GRP_RPL_CERTIFICATION_INITIALIZATION_FAILURE, 230	ER_GRP_RPL_DISABLE_SRV_READ_MODE_RESTRICTED, 232
ER_GRP_RPL_CERTIFICATION_REC_PROCESS, 242	ER_GRP_RPL_DONOR_CONN_TERMINATION, 240
ER_GRP_RPL_CERTIFIER_MSSG_PROCESS_ERROR, 232	ER_GRP_RPL_DONOR_SERVER_CONN, 239
ER_GRP_RPL_CERT_BROADCAST_THREAD_CREATE_FAILED, 415	ER_GRP_RPL_DONOR_TRANS_INFO_ERROR, 230
ER_GRP_RPL_CERT_BROADCAST_THREAD_STARTED, 415	ER_GRP_RPL_DONOR_VIEW_CHANGE_UUID_TRANS_INF 230
ER_GRP_RPL_CERT_BROADCAST_THREAD_STOPPED, 416	ER_GRP_RPL_ENABLE_READ_ONLY_FAILED, 233
ER_GRP_RPL_CHANGE_GRP_MEM_NOT_PROCESSED, 233	ER_GRP_RPL_ERROR_FETCHING_GTID_EXECUTED_SET, 230
ER_GRP_RPL_CHANNEL_THREAD_WHEN_GROUP_ACTION_RUNNING, 347	ER_GRP_RPL_ERROR_FETCHING_GTID_SET, 230
ER_GRP_RPL_CHECK_STATUS_TABLE, 239	ER_GRP_RPL_ERROR_GTID_EXECUTION_INFO, 229
ER_GRP_RPL_CLONE_PROCESS_EXEC_ERROR, 365	ER_GRP_RPL_ERROR_GTID_SET_EXTRACTION, 306
ER_GRP_RPL_CLONE_PROCESS_PREPARE_ERROR, 365	ER_GRP_RPL_ERROR_MSG, 217
ER_GRP_RPL_COMMUNICATION_SSL_CONF_INFO, 246	ER_GRP_RPL_ERROR_ON_CERT_DB_INSTALL, 356
ER_GRP_RPL_CONFIGURATION_ACTION_END, 347	ER_GRP_RPL_ERROR_ON_MESSAGE_SENDING, 347
ER_GRP_RPL_CONFIGURATION_ACTION_ERROR, 347	ER_GRP_RPL_ERROR_SENDING_SINGLE_PRIMARY_MSS 229
ER_GRP_RPL_CONFIGURATION_ACTION_KILLED_ERROR, 347	ER_GRP_RPL_ERROR_SET_MULTI_CONSENSUS_LEADER, 394
ER_GRP_RPL_CONFIGURATION_ACTION_LOCAL_TERMINATION, 347	ER_GRP_RPL_ERROR_SET_SINGLE_CONSENSUS_LEADER, 394
ER_GRP_RPL_CONFIGURATION_ACTION_START, 347	ER_GRP_RPL_ERROR_STOPPING_CHANNELS, 229
ER_GRP_RPL_CONFIG_RECOVERY, 239	ER_GRP_RPL_ERROR_WHILE_WAITING_FOR_CONFLICT 242
ER_GRP_RPL_CONFLICT_DETECTION_DISABLED, 232	ER_GRP_RPL_ESTABLISHING_CONN_GRP_REC_DONOR, 239
ER_GRP_RPL_CONNECTION_METADATA_REPO_MUST_BE_ENABLED, 247	ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_ANOTHER, 239
ER_GRP_RPL_CONN_INTERNAL_PLUGIN_FAIL, 238	ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_DONOR, 239
ER_GRP_RPL_CONN_KILLED, 416	ER_GRP_RPL_EVENT_HANDLING_ERROR, 229
ER_GRP_RPL_COPY_FROM_EMPTY_STRING, 238	ER_GRP_RPL_EXCEEDS_AUTO_INC_VALUE, 234
ER_GRP_RPL_CREATE_APPLIER_CACHE_ERROR, 229	ER_GRP_RPL_EXIT_GRP_GCS_ERROR, 250
	ER_GRP_RPL_FAILED_TO_BOOTSTRAP_EVENT_HANDLIN 248
	ER_GRP_RPL_FAILED_TO_BROADCAST_GRP_MEMBERSHI 240
	ER_GRP_RPL_FAILED_TO_BROADCAST_MEMBER_STATU 240

ER_GRP_RPL_FAILED_TO_CALL_GRP_COMMUNICATION_ENGINE_PLUGIN, 244
ER_GRP_RPL_FAILED_TO_CONFIRM_IF_SERVER_LEFT_GRP, 244
ER_GRP_RPL_FAILED_TO_CREATE_TRANS_CONTEXT, 241
ER_GRP_RPL_FAILED_TO_ENABLE_READ_ONLY_MODE_ON_SERVER, 245
ER_GRP_RPL_FAILED_TO_ENABLE_SUPER_READ_ONLY_MODE, 243
ER_GRP_RPL_FAILED_TO_EXTRACT_TRANS_WRITE_SET, 241
ER_GRP_RPL_FAILED_TO_GATHER_TRANS_WRITE_SET, 241
ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_GRP, 246
ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_VIEW_CHANGE, 388
ER_GRP_RPL_FAILED_TO_INIT_APPLIER_HANDLER, 249
ER_GRP_RPL_FAILED_TO_INIT_APPLIER_MODULE, 246
ER_GRP_RPL_FAILED_TO_INIT_COMMUNICATION_ENGINE, 243
ER_GRP_RPL_FAILED_TO_INIT_HANDLER, 245
ER_GRP_RPL_FAILED_TO_INSERT_TRX_ON_TCM_ON_SERVER, 354
ER_GRP_RPL_FAILED_TO_LOG_VIEW_CHANGE, 401
ER_GRP_RPL_FAILED_TO_NOTIFY_GRP_MEMBERSHIP_EVENT, 240
ER_GRP_RPL_FAILED_TO_PARSE_THE_GRP_NAME, 246
ER_GRP_RPL_FAILED_TO_PARSE_THE_VIEW_CHANGE, 388
ER_GRP_RPL_FAILED_TO_REGISTER_BINLOG_STATE_OBSERVER, 245
ER_GRP_RPL_FAILED_TO_REGISTER_SERVER_STATE_OBSERVER, 245
ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_OUTCOME_NOTIFICATION, 242
ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OBSERVER, 245
ER_GRP_RPL_FAILED_TO_REINIT_BINLOG_CACHE_FOR_READ, 241
ER_GRP_RPL_FAILED_TO_SHUTDOWN_REGISTRY_MODULE, 245
ER_GRP_RPL_FAILED_TO_START_COMMUNICATION_ENGINE, 243
ER_GRP_RPL_FAILED_TO_START_ON_BOOT, 245
ER_GRP_RPL_FAILED_TO_START_ON_SECONDARY_WRITE, 243
ER_GRP_RPL_FAILED_TO_START_WITH_INVALID_SERVER_ID, 243
ER_GRP_RPL_FAILED_TO_STOP_ON_PLUGIN_UNINSTALL, 245
ER_GRP_RPL_FAILED_TO_UNREGISTER_BINLOG_STATE_OBSERVER, 246
ER_GRP_RPL_FAILED_TO_UNREGISTER_SERVER_STATE_OBSERVER, 245
ER_GRP_RPL_FAILED_TO_UNREGISTER_TRANS_STATE_OBSERVER, 245
ER_GRP_RPL_FAILOVER_CHANNEL_STATUS_PROPAGATION, 117
ER_GRP_RPL_FAILOVER_CONF_CHANNEL_DOES_NOT_EXIST, 391
ER_GRP_RPL_FAILOVER_CONF_DEFAULT_CONFIGURATION, 391
ER_GRP_RPL_FAILOVER_CONF_GET_EXCHANGEABLE_DATA, 391
ER_GRP_RPL_FAILOVER_CONF_PARSE_ON_MEMBER_JOIN, 391
ER_GRP_RPL_FAILOVER_CONF_UNABLE_TO_SET_DEFAULT, 391
ER_GRP_RPL_FAILOVER_PRIMARY_BACK_TO_MAJORITY, 391
ER_GRP_RPL_FAILOVER_PRIMARY_WITHOUT_MAJORITY, 391
ER_GRP_RPL_FAILOVER_REGISTER_MESSAGE_LISTENER_AFTER_CERTIFICATION, 241
ER_GRP_RPL_FATAL_REC_PROCESS, 242
ER_GRP_RPL_FETCH_FORMAT_DESC_LOG_EVENT_FAILED, 237
ER_GRP_RPL_FETCH_GTID_LOG_EVENT_FAILED, 237
ER_GRP_RPL_FETCH_LOG_EVENT_FAILED, 238
ER_GRP_RPL_FETCH_SNAPSHOT_VERSION_FAILED, 237
ER_GRP_RPL_FETCH_TRANS_CONTEXT_FAILED, 237
ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FAILED, 237
ER_GRP_RPL_FETCH_TRANS_DATA_FAILED, 236
ER_GRP_RPL_FETCH_VIEW_CHANGE_LOG_EVENT_FAILED, 238
ER_GRP_RPL_FINISHED_AUTO_REJOIN, 359
ER_GRP_RPL_FK_WITH_CASCADE_UNSUPPORTED, 236
ER_GRP_RPL_FLOW_CONTROL_STATS, 251
ER_GRP_RPL_FLOW_CTRL_MAX_QUOTA_SMALLER_THAN_MIN, 248
ER_GRP_RPL_FLOW_CTRL_MIN_QUOTA_GREATER_THAN_MAX, 248
ER_GRP_RPL_FLOW_CTRL_MIN_RECOVERY_QUOTA_GREATER_THAN_MAX, 248
ER_GRP_RPL_ASYNC_CHANNELS, 241
ER_GRP_RPL_FORCE_MEMBERS_MUST_BE_EMPTY, 241

ER_GRP_RPL_FORCE_MEMBERS_WHEN_LEAVING, 356	ER_GRP_RPL_JOINER_EXIT_WHEN_GROUP_ACTION_RUNNING, 347
ER_GRP_RPL_FORCE_MEMBER_VALUE_SET, 251	ER_GRP_RPL_JOIN_WHEN_GROUP_ACTION_RUNNING, 347
ER_GRP_RPL_FORCE_MEMBER_VALUE_SET_ERROR, 250	ER_GRP_RPL_KILLED_FAILED_ID, 238
ER_GRP_RPL_FORCE_MEMBER_VALUE_TIME_OUT, 251	ER_GRP_RPL_KILLED_SESSION_ID, 238
ER_GRP_RPL_GCS_GR_ERROR_MSG, 251	ER_GRP_RPL_LOCAL_GTID_SETS_PROCESS_ERROR, 235
ER_GRP_RPL_GCS_INTERFACE_ERROR, 250	ER_GRP_RPL_LOG_REPLICA_UPDATES_NOT_SET, 247
ER_GRP_RPL_GMS_LISTENER_FAILED_TO_LOG_NOTIFICATION, 250	ER_GRP_RPL_LOWER_CASE_TABLE_NAMES_DIFF_FROM 340
ER_GRP_RPL_GROUP_NAME_PARSE_ERROR, 230	ER_GRP_RPL_MAXIMUM_CONNECTION_RETRIES_REACHED, 239
ER_GRP_RPL_GROUP_NAME_SAME_AS_VIEW_CHANGE_UUID, 387	ER_GRP_RPL_MEMBER_ACTIONS_RESET, 387
ER_GRP_RPL_GRP_COMMUNICATION_ENG_INIT_FAILURE, 250	ER_GRP_RPL_MEMBER_ACTION_DEFAULT_CONFIGURATION, 386
ER_GRP_RPL_GRP_COMMUNICATION_INIT_WITH_CONFLICT, 248	ER_GRP_RPL_MEMBER_ACTION_DISABLED, 387
ER_GRP_RPL_GRP_MEMBER_OFFLINE, 250	ER_GRP_RPL_MEMBER_ACTION_ENABLED, 387
ER_GRP_RPL_GRP_NAME_IS_NOT_VALID_UUID, 247	ER_GRP_RPL_MEMBER_ACTION_FAILURE, 386
ER_GRP_RPL_GRP_NAME_IS_SAME_AS_ANONYMOUS_GROUP_UUID, 382	ER_GRP_RPL_MEMBER_ACTION_FAILURE_IGNORE, 386
ER_GRP_RPL_GRP_NAME_IS_TOO_LONG, 247	ER_GRP_RPL_MEMBER_ACTION_GET_EXCHANGEABLE, 386
ER_GRP_RPL_GRP_NAME_OPTION_MANDATORY, 247	ER_GRP_RPL_MEMBER_ACTION_INVALID_ACTIONS_ON_JOIN, 387
ER_GRP_RPL_GRP_VIEW_CHANGE_UUID_IS_INCOMPATIBLE_WITH_SERVER_UUID, 388	ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_MEMBER_JOIN, 386
ER_GRP_RPL_GTID_ALREADY_USED, 229	ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_RECEIVE, 386
ER_GRP_RPL_GTID_EXECUTED_EXTRACT_ERROR, 234	ER_GRP_RPL_MEMBER_ACTION_TRIGGERED, 386
ER_GRP_RPL_GTID_MODE_OFF, 247	ER_GRP_RPL_MEMBER_ACTION_UNABLE_TO_SET_DEFAULT, 386
ER_GRP_RPL_GTID_PURGED_EXTRACT_ERROR, 365	ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS, 386
ER_GRP_RPL_GTID_SET_EXTRACT_ERROR, 234	ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS_ON_JOIN, 387
ER_GRP_RPL_GTID_SET_EXTRACT_ERROR_DURING_RECOVERY, 355	ER_GRP_RPL_MEMBER_ADDED, 233
ER_GRP_RPL_HAS_STARTED, 410	ER_GRP_RPL_MEMBER_ALREADY_EXISTS, 234
ER_GRP_RPL_INCORRECT_TYPE_SET_FOR_PARALLEL_EXECUTION, 247	ER_GRP_RPL_MEMBER_CFG_INCOMPATIBLE_WITH_GRP, 235
ER_GRP_RPL_INIT_CERTIFICATION_INFO_FAILURE, 231	ER_GRP_RPL_MEMBER_CHANGE, 233
ER_GRP_RPL_INTERNAL_QUERY, 238	ER_GRP_RPL_MEMBER_CONF_INFO, 244
ER_GRP_RPL_INVALID_BINLOG_FORMAT, 240	ER_GRP_RPL_MEMBER_CONTACT_RESTORED, 233
ER_GRP_RPL_INVALID_COMMUNICATION_PROTOCOL, 359	ER_GRP_RPL_MEMBER_EXIT_PLUGIN_ERROR, 233
ER_GRP_RPL_INVALID_DEBUG_OPTIONS, 250	ER_GRP_RPL_MEMBER_EXPELLED, 233
ER_GRP_RPL_INVALID_GTID_SET, 231	ER_GRP_RPL_MEMBER_INFO_DOES_NOT_EXIST, 415
ER_GRP_RPL_INVALID_SSL_RECOVERY_STRING, 248	ER_GRP_RPL_MEMBER_LEFT_GRP, 233
ER_GRP_RPL_IS_STARTING, 374	ER_GRP_RPL_MEMBER_NOT_FOUND, 239
ER_GRP_RPL_IS_STOPPED, 244	ER_GRP_RPL_MEMBER_REMOVED, 233
ER_GRP_RPL_IS_STOPPING, 244	

ER_GRP_RPL_MEMBER_SERVER_UUID_IS_INCOMPATIBLE_WITH_GRP,	244	ER_GRP_RPL_PIPELINE_REINIT_FAILED_READ,	251
ER_GRP_RPL_MEMBER_STATS_INFO,	251	ER_GRP_RPL_PIPELINE_REINIT_FAILED_WRITE,	251
ER_GRP_RPL_MEMBER_STOP_RPL_CHANNELS_ERROR,	235	ER_GRP_RPL_PLUGIN_ABORT,	344
ER_GRP_RPL_MEMBER_TRANS_GREATER_THAN_GRP,	235	ER_GRP_RPL_PLUGIN_STRUCT_INIT_NOT_POSSIBLE_ON_SECONDARY,	243
ER_GRP_RPL_MEMBER_VERSION_LOWER_THAN_GRP,	235	ER_GRP_RPL_PREEMPTIVE_GARBAGE_COLLECTION_DIFFERENTIAL,	426
ER_GRP_RPL_MEMBER_VER_INCOMPATIBLE,	234	ER_GRP_RPL_PRIMARY_ELECTION_PROCESS_ERROR,	348
ER_GRP_RPL_MEMBER_VER_READ_COMPATIBLE,	362	ER_GRP_RPL_PRIMARY_ELECTION_STOP_ERROR,	348
ER_GRP_RPL_MEM_ONLINE,	232	ER_GRP_RPL_PRIMARY_KEY_NOT_DEFINED,	236
ER_GRP_RPL_MEM_REACHABLE,	232	ER_GRP_RPL_PRIMARY_MEMBER_LEFT_GRP,	233
ER_GRP_RPL_MEM_UNREACHABLE,	232	ER_GRP_RPL_PROCESS_GTID_SET_ERROR,	231
ER_GRP_RPL_MESSAGE_SERVICE_FATAL_ERROR,	367	ER_GRP_RPL_PROCESS_INTERSECTION_GTID_SET_ERROR,	231
ER_GRP_RPL_MESSAGE_SERVICE_INIT_FAILURE,	106	ER_GRP_RPL_PURGE_APPLIER_LOGS,	235
ER_GRP_RPL_MISSING_GRP_RPL_ACTION_COORDINATOR,	347	ER_GRP_RPL_PURGE_REC,	240
ER_GRP_RPL_MISSING_GRP_RPL_APPLIER,	232	ER_GRP_RPL_QUERY_FAIL,	238
ER_GRP_RPL_MODULE_TERMINATE_ERROR,	247	ER_GRP_RPL_READ_UNABLE_FOR_READ_ONLY_SUPER_REPLICATION,	243
ER_GRP_RPL_MSG_DECODING_FAILED,	424	ER_GRP_RPL_RECEIVED_SET_MISSING_GTIDS,	231
ER_GRP_RPL_MSG_DISCARDED,	232	ER_GRP_RPL_RECOVERY_CHANNEL_STILL_RUNNING,	115
ER_GRP_RPL_MSG_TOO_LONG_BROADCASTING_TRANSACTION,	242	ER_GRP_RPL_RECOVERY_ENDPOINT_FORMAT,	374
ER_GRP_RPL_MULTIPLE_CACHE_TYPE_NOT_SUPPORTED,	241	ER_GRP_RPL_RECOVERY_ENDPOINT_INTERFACES_IPS,	375
ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ERROR_COMMAND,	390	ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID,	375
ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ERROR_CONNECTION,	390	ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID_DONOR_ENDPOINT,	375
ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_SERVER_ERROR_COMMAND,	417	ER_GRP_RPL_RECOVERY_EVAL_ERROR,	365
ER_GRP_RPL_NEEDS_INNODB_TABLE,	236	ER_GRP_RPL_RECOVERY_MODULE_TERMINATION_TIMED_OUT,	243
ER_GRP_RPL_NEW_PRIMARY_ELECTED,	233	ER_GRP_RPL_RECOVERY_STRAT_CHOICE,	365
ER_GRP_RPL_NOTIFY_CERTIFICATION_OUTCOME_FAILED,	237	ER_GRP_RPL_RECOVERY_STRAT_CLONE_PURGED,	365
ER_GRP_RPL_NO_POSSIBLE_RECOVERY,	365	ER_GRP_RPL_RECOVERY_STRAT_CLONE_THRESHOLD,	365
ER_GRP_RPL_NO_STAGE_SERVICE,	348	ER_GRP_RPL_RECOVERY_STRAT_FALLBACK,	365
ER_GRP_RPL_NO_SUITABLE_PRIMARY_MEM,	234	ER_GRP_RPL_RECOVERY_STRAT_NO_FALLBACK,	366
ER_GRP_RPL_NO_VALID_DONOR,	239	ER_GRP_RPL_RECOVERY_WAIT_APPLIER_BACKLOG_FINISH,	427
ER_GRP_RPL_NULL_PACKET,	231	ER_GRP_RPL_RECOVERY_WAIT_APPLIER_BACKLOG_START,	427
ER_GRP_RPL_ONLY_ONE_SERVER_ALIVE,	242	ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_DEPENDENCIES,	354
ER_GRP_RPL_OOM_FAILED_TO_GENERATE_IDENTIFICATION_HASH,	240		
ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_OLD_GRP,	394		
ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_OLD_GRP,	408		
ER_GRP_RPL_PIPELINE_CREATE_FAILED,	251		
ER_GRP_RPL_PIPELINE_FLUSH_FAIL,	251		

ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_GROUPER	ERR_GRP_RPL_ALREADY_MULTIPLE, 394
354	ERR_GRP_RPL_ALREADY_MULTIPLE, 394
ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_SYNC	ERR_GRP_EXCLUSIVE_SINGLE, 394
355	ERR_GRP_EXCLUSIVE_SINGLE, 394
ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_DEPENDEN	ERR_GRP_COMMIT_FAILED_TRANS_ERROR, 231
354	ERR_GRP_COMMIT_FAILED_TRANS_ERROR, 231
ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_WAIT_FOR	ERR_GRP_SINGLE_PRIM_MODE_NOT_ALLOWED_WIT
355	ERR_GRP_SINGLE_PRIM_MODE_NOT_ALLOWED_WIT
ER_GRP_RPL_RELEASE_COMMIT_AFTER_GROUP_PRO	ERR_GRP_SYNC_BEFORE_EXEC, 249
354	ERR_GRP_SYNC_BEFORE_EXEC, 249
ER_GRP_RPL_REPLICA_APPLIER_THREAD_ERROR_OUT	ERR_GRP_SQL_SERVICE_COMM_SESSION_NOT_INIT
252	ERR_GRP_SQL_SERVICE_COMM_SESSION_NOT_INIT
ER_GRP_RPL_REPLICA_APPLIER_THREAD_UNBLOCKED	ERR_GRP_SQL_SERVICE_FAILED, 249
252	ERR_GRP_SQL_SERVICE_FAILED, 249
ER_GRP_RPL_REPLICA_IO_THD_PRIMARY_UNKNOWN	ERR_GRP_SQL_SERVICE_FAILED_TO_FETCH_SECUR
236	ERR_GRP_SQL_SERVICE_FAILED_TO_FETCH_SECUR
ER_GRP_RPL_REPLICA_IO_THREAD_ERROR_OUT,	ERR_GRP_SQL_SERVICE_FAILED_TO_INIT_SESSION,
252	ERR_GRP_SQL_SERVICE_FAILED_TO_INIT_SESSION,
ER_GRP_RPL_REPLICA_IO_THREAD_UNBLOCKED,	ERR_GRP_SQL_SERVICE_FAILED_TO_RUN_SQL_QUE
252	ERR_GRP_SQL_SERVICE_FAILED_TO_RUN_SQL_QUE
ER_GRP_RPL_REPLICA_PRESERVE_COMMIT_ORDER	ERR_GRP_SQL_SERVICE_MAX_CONN_ERROR_FROM
247	ERR_GRP_SQL_SERVICE_MAX_CONN_ERROR_FROM
ER_GRP_RPL_REPLICA_SQL_THD_ON_SECONDARY_M	ERR_GRP_SQL_SERVICE_RETRIES_EXCEEDED_ON_S
236	ERR_GRP_SQL_SERVICE_RETRIES_EXCEEDED_ON_S
ER_GRP_RPL_REPLICA_SQL_THD_PRIMARY_UNKNOWN	ERR_GRP_SQL_SERVICE_SERVER_ACCESS_DENIED,
236	ERR_GRP_SQL_SERVICE_SERVER_ACCESS_DENIED,
ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_CLONE,	ERR_GRP_SQL_SERVICE_SERVER_ERROR_ON_CON
366	ERR_GRP_SQL_SERVICE_SERVER_ERROR_ON_CON
ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_SECOND	ERR_GRP_SQL_SERVICE_SERVER_INTERNAL_FAILUR
392	ERR_GRP_SQL_SERVICE_SERVER_INTERNAL_FAILUR
ER_GRP_RPL_REQUESTING_NON_MEMBER_SERVER	ERR_GRP_SQL_SERVICE_SERVER_SESSION_KILLED,
244	ERR_GRP_SQL_SERVICE_SERVER_SESSION_KILLED,
ER_GRP_RPL_RESET_APPLIER_MODULE_LOGS_ERROR	ERR_GRP_SRV_BLOCKED, 232
235	ERR_GRP_SRV_BLOCKED, 232
ER_GRP_RPL_SALVE_IO_THD_ON_SECONDARY_MEMB	ERR_GRP_SRV_BLOCKED_FOR_SECS, 232
236	ERR_GRP_SRV_BLOCKED_FOR_SECS, 232
ER_GRP_RPL_SEND_STATS_ERROR,	ERR_GRP_SRV_NOT_ONLINE, 232
251	ERR_GRP_SRV_NOT_ONLINE, 232
ER_GRP_RPL_SEND_TRX_PREPARED_MESSAGE_FAIL	ERR_GRP_SRV_PRIMARY_MEM, 233
354	ERR_GRP_SRV_PRIMARY_MEM, 233
ER_GRP_RPL_SEND_TRX_SYNC_BEFORE_EXECUTION	ERR_GRP_SRV_SECONDARY_MEM, 234
355	ERR_GRP_SRV_SECONDARY_MEM, 234
ER_GRP_RPL_SERVER_ALREADY_LEFT,	ERR_GRP_SSL_DISABLED, 246
244	ERR_GRP_SSL_DISABLED, 246
ER_GRP_RPL_SERVER_CONN_ERROR,	ERR_GRP_STARTED_AUTO_REJOIN, 359
230	ERR_GRP_STARTED_AUTO_REJOIN, 359
ER_GRP_RPL_SERVER_IS_ALREADY_LEAVING,	ERR_GRP_STARTING_GRP_REC, 240
244	ERR_GRP_STARTING_GRP_REC, 240
ER_GRP_RPL_SERVER_SET_TO_OFFLINE_MODE_DUE	ERR_GRP_START_FAILED, 234
367	ERR_GRP_START_FAILED, 234
ER_GRP_RPL_SERVER_SET_TO_READ_ONLY_DUE_TO	ERR_GRP_START_GRP_RPL_FAILED, 238
250	ERR_GRP_START_GRP_RPL_FAILED, 238
ER_GRP_RPL_SERVER_UDF_ERROR,	ERR_GRP_STOPPING_GRP_REC, 240
348	ERR_GRP_STOPPING_GRP_REC, 240
ER_GRP_RPL_SESSION_OPEN_FAILED,	ERR_GRP_SUPER_READ_OFF, 238
233	ERR_GRP_SUPER_READ_OFF, 238
ER_GRP_RPL_SET_GRP_COMMUNICATION_ENG_LOG	ERR_GRP_SUPER_READ_ON, 238
250	ERR_GRP_SUPER_READ_ON, 238
	ERR_GRP_SUPER_READ_ONLY_ACTIVATE_ERROR,
	ERR_GRP_SUPER_READ_ONLY_ACTIVATE_ERROR,
	ERR_GRP_TIMEOUT_ON_VIEW_AFTER_JOINING_GRP
	ERR_GRP_TIMEOUT_ON_VIEW_AFTER_JOINING_GRP
	ERR_GRP_TIMEOUT_RECEIVED_VC_LEAVE_ON_REJO
	ERR_GRP_TIMEOUT_RECEIVED_VC_LEAVE_ON_REJO
	ERR_GRP_TIMEOUT_RECEIVED_VC_ON_REJOIN,
	ERR_GRP_TIMEOUT_RECEIVED_VC_ON_REJOIN,
	ERR_GRP_TIMEOUT_RECEIVING_VIEW_CHANGE_ON,
	ERR_GRP_TIMEOUT_RECEIVING_VIEW_CHANGE_ON,
	ERR_GRP_TRANS_GREATER_THAN_GRP, 234
	ERR_GRP_TRANS_GREATER_THAN_GRP, 234
	ERR_GRP_TRANS_NOT_PRESENT_IN_GRP,
	ERR_GRP_TRANS_NOT_PRESENT_IN_GRP,

ER_GRP_RPL_TRANS_SIZE_EXCEEDS_LIMIT, 242	ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_REF_VER_ERROR, 231
ER_GRP_RPL_TRANS_WRITE_SET_EXTRACT_DIFF_FROM_GRP, 235	ER_GRP_RPL_VCLE_NOT_BEING_LOGGED, 420
ER_GRP_RPL_TRX_ALREADY_EXISTS_ON_TCM_ON_APLIERS_FOR_VIEW_CHANGE_UUID_DIFF_FROM_GRP, 354	ER_GRP_RPL_VIEW_CHANGE_UUID_INVALID, 387
ER_GRP_RPL_TRX_DOES_NOT_EXIST_ON_TCM_ON_HANDLER_PROMOTE_TO_PREPARE, 354	ER_GRP_RPL_VIEW_CHANGE_UUID_IS_SAME_AS_ANONYMOUS, 387
ER_GRP_RPL_TRX_WAIT_FOR_GROUP_GTID_EXECUTED, 355	ER_GRP_RPL_VIEW_CHANGE_UUID_PARSE_ERROR, 380
ER_GRP_RPL_TRX_WAIT_FOR_GROUP_PREPARE_FAILED, 354	ER_GRP_RPL_VIEW_CHANGE_UUID_SAME_AS_GROUP_NAME, 387
ER_GRP_RPL_TRX_WAIT_FOR_SYNC_BEFORE_EXECUTION_FAILED, 355	ER_GRP_RPL_WAITING_FOR_VIEW_UPDATE, 244
ER_GRP_RPL_UDF_ERROR, 106	ER_GRP_RPL_WAIT_FOR_DEPENDENCIES_FAILED, 354
ER_GRP_RPL_UDF_REGISTER_ERROR, 348	ER_GRP_RPL_WHILE_SENDING_MSG_REC, 242
ER_GRP_RPL_UDF_REGISTER_SERVICE_ERROR, 348	ER_GRP_RPL_WRITE_IDENT_HASH_BASE64_ENCODING_FAILED, 240
ER_GRP_RPL_UDF_UNREGISTER_ERROR, 348	ER_GRP_RPL_WRITE_TO_TRANSACTION_MESSAGE_FAILED, 242
ER_GRP_RPL_UNABLE_TO_CERTIFY_PLUGIN_TRANS, 243	ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN, 97
ER_GRP_RPL_UNABLE_TO_CONVERT_EVENT_TO_PACKET, 251	ER_GRP_TRX_CONSISTENCY_BEFORE, 97
ER_GRP_RPL_UNABLE_TO_CONVERT_PACKET_TO_EVENT, 251	ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED, 97
ER_GRP_RPL_UNABLE_TO_ENSURE_EXECUTION_RECORDS, 242	ER_GRP_TRX_CONSISTENCY_NOT_ALLOWED, 97
ER_GRP_RPL_UNABLE_TO_EVALUATE_APPLIER_STATUS, 242	ER_GRP_ELECTED_PRIMARY_GTID_INFORMATION, 369
ER_GRP_RPL_UNABLE_TO_INIT_COMMUNICATION_ENGINES, 246	ER_GRP_HOLD_KILLED, 96
ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_APPLIER, 240	ER_GRP_HOLD_MEMBER_STATUS_ERROR, 96
ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_APPLIER, 240	ER_GRP_HOLD_WAIT_TIMEOUT, 96
ER_GRP_RPL_UNABLE_TO_RESET_SERVER_READ_MODE, 243	ER_GTID_ALREADY_ADDED_BY_USER, 164
ER_GRP_RPL_UNBLOCK_CERTIFIED_TRANS, 243	ER_GTID_EXECUTED_WAS_CHANGED, 57
ER_GRP_RPL_UNBLOCK_WAITING_THD, 229	ER_GTID_EXECUTED_WAS_UPDATED, 191
ER_GRP_RPL_UNKNOWN_GRP_RPL_APPLIER_PIPELINE_ERROR_CODE, 248	ER_GTID_MODE_CAN_ONLY_CHANGE_ONE_STEP_AT_A_TIME, 53
ER_GRP_RPL_UNREACHABLE_MAJORITY_TIMEOUT_FOR_MEMBER, 250	ER_GTID_MODE_ON_REQUIRES_ENFORCE_GTID_CONSISTENCY, 65
ER_GRP_RPL_UNSUPPORTED_TRANS_ISOLATION, 241	ER_GTID_NEXT_CANT_BE_AUTOMATIC_IF_GTID_NEXT_LIST_IS_EMPTY, 52
ER_GRP_RPL_UPDATE_GRPGTID_EXECUTED_ERROR, 230	ER_GTID_NEXT_TAG_GTID_MODE_OFF, 130
ER_GRP_RPL_UPDATE_GRPGTID_VIEW_CHANGE_UUID_EXECUTION_ERROR, 388	ER_GTID_NEXT_TYPE_UNDEFINED_GTID, 56
ER_GRP_RPL_UPDATE_GTID_SET_ERROR, 231	ER_GTID_PURGED_WAS_CHANGED, 57
ER_GRP_RPL_UPDATE_LAST_CONFLICT_FREE_TRANSACTION_ERROR, 230	ER_GTID_PURGED_WAS_UPDATED, 191
ER_GRP_RPL_UPDATE_SERV_CERTIFICATE_FAILED, 237	ER_GTID_UNSAFE ALTER ADD COL WITH DEFAULT EXPRESSION, 60
	ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_TRANSACTION, 60
	ER_GTID_UNSAFE_CREATE_SELECT, 53
	ER_GTID_UNSAFE_NON_TRANSACTIONAL_TABLE, 53

ER_HANDLERTON_OOM, 153
 ER_HANDSHAKE_ERROR, 6
 ER_HEALTH_ERROR, 383
 ER_HEALTH_INFO, 382
 ER_HEALTH_WARNING, 383
 ER_HEALTH_WARNING_DISK_USAGE_LEVEL_1, 383
 ER_HEALTH_WARNING_DISK_USAGE_LEVEL_2, 383
 ER_HEALTH_WARNING_DISK_USAGE_LEVEL_3, 383
 ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_1, 394
 ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_2, 394
 ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_3, 394
 ER_HOSTNAME, 33
 ER_HOSTNAME_DOESNT_RESOLVE_TO, 141
 ER_HOSTNAME_RESEMBLES_IPV4, 141
 ER_HOSTNAME_TOO_LONG, 110
 ER_HOSTNAME_TRUNCATED, 376
 ER_HOST_IS_BLOCKED, 12
 ER_HOST_NOT_PRIVILEGED, 12
 ER_HYPERGRAPH_NOT_SUPPORTED_YET, 113
 ER_IB_BUFFER_POOL_FULL, 406
 ER_IB_BUFFER_POOL_OVERUSE, 406
 ER_IB_BULK_FLUSHER_INFO, 406
 ER_IB_BULK_FLUSHER_PUNCH_HOLE, 416
 ER_IB_BULK_LOAD_MERGE_FAIL, 408
 ER_IB_BULK_LOAD_STATS_WARN, 424
 ER_IB_BULK_LOAD_SUBTREE_INFO, 406
 ER_IB_BULK_LOAD_THREAD_FAIL, 408
 ER_IB_CANNOT_UPGRADE_WITH_DISCARDED_TABLESPACE, 376
 ER_IB_CLONE_GTID_PERSIST, 268
 ER_IB_CLONE_INTERNAL, 268
 ER_IB_CLONE_NON_INNODB_TABLE, 364
 ER_IB_CLONE_OPERATION, 364
 ER_IB_CLONE_PUNCH_HOLE, 268
 ER_IB_CLONE_RESTART, 364
 ER_IB_CLONE_SQL, 268
 ER_IB_CLONE_START_STOP, 364
 ER_IB_CLONE_STATUS_FILE, 268
 ER_IB_CLONE_TIMEOUT, 268
 ER_IB_CLONE_USER_DATA, 364
 ER_IB_CLONE_VALIDATE, 268
 ER_IB_DBLWR_BYTES_INFO, 397
 ER_IB_DBLWR_DECOMPRESS_FAILED, 381
 ER_IB_DBLWR_DECRYPT_FAILED, 381
 ER_IB_DBLWR_KEY_MISSING, 381
 ER_IB_DDL_CONVERT_HEAP_NOT_FOUND, 414
 ER_IB_DICT_INVALID_COLUMN_POSITION, 409
 ER_IB_DICT_LOG_TABLE_INFO, 409
 ER_IB_DUPLICATE_KEY, 406
 ER_IB_ERR_ACCESSING_OUT_OF_BOUND_FIELD_IN_INDEX, 333
 ER_IB_ERR_CORRUPT_TABLESPACE_UNRECOVERABLE, 423
 ER_IB_ERR_DDL_LOG_INSERT_FAILURE, 376
 ER_IB_ERR_FOUND_N_DUPLICATE_KEYS, 379
 ER_IB_ERR_FOUND_N_RECORDS_WRONG_ORDER, 379
 ER_IB_ERR_INDEX_DUPLICATE_KEY, 379
 ER_IB_ERR_INDEX_RECORDS_WRONG_ORDER, 378
 ER_IB_ERR_LOG_PARSING_BUFFER_OVERFLOW, 378
 ER_IB_ERR_NOT_ENOUGH_MEMORY_FOR_PARSE_BUFFER, 378
 ER_IB_ERR_PAGE_ARCH_DBLWR_INIT_FAILED, 390
 ER_IB_ERR_PAGE_ARCH_INVALID_DOUBLE_WRITE_BUFFER, 374
 ER_IB_ERR_PAGE_ARCH_INVALID_FORMAT, 374
 ER_IB_ERR_PAGE_ARCH_RECOVERY_FAILED, 374
 ER_IB_ERR_PAGE_DIRTY_AT_SHUTDOWN, 264
 ER_IB_ERR_PARALLEL_READ_OOM, 379
 ER_IB_ERR_RECOVERY_REDO_DISABLED, 375
 ER_IB_ERR_SCHED_SETAFFINITY_FAILED, 377
 ER_IB_ERR_TEMP_TABLESPACE_DIR_CONTAINS_SEMICOLON, 377
 ER_IB_ERR_TEMP_TABLESPACE_DIR_DOESNT_EXIST, 377
 ER_IB_ERR_TEMP_TABLESPACE_DIR_EMPTY, 377
 ER_IB_ERR_TEMP_TABLESPACE_DIR_SUBDIR_OF_DATAFILESPACE, 377
 ER_IB_ERR_UNKNOWN_PAGE_FETCH_MODE, 378
 ER_IB_ERR_ZLIB_BUF_ERROR, 378
 ER_IB_ERR_ZLIB_DATA_ERROR, 378
 ER_IB_ERR_ZLIB_MEM_ERROR, 378
 ER_IB_ERR_ZLIB_UNCOMPRESS_FAILED, 378
 ER_IB_ERR_ZLIB_UNKNOWN_ERROR, 378
 ER_IB_FAILED_TO_DELETE_TABLESPACE_FILE, 377
 ER_IB_FIXED_PAGE_ID, 418
 ER_IB_HIDDEN_NAME_CONFLICT, 409
 ER_IB_IMPORT_INDEX_METADATA_READ_FAILED, 317
 ER_IB_IMPORT_START_CFG_NAME, 322
 ER_IB_INDEX_BUILDER_DONE, 410
 ER_IB_INDEX_BUILDER_INIT, 410
 ER_IB_INDEX_LOADER_DONE, 410
 ER_IB_INDEX_LOG_VERSION_MISMATCH, 410
 ER_IB_INDEX_PART_TOO_LONG, 415

ER_IB_INNOODB_TBSP_OUT_OF_SPACE, 383	ER_IB_MSG_1039, 323
ER_IB_LOAD_BULK_CONCURRENCY_REDUCED, 408	ER_IB_MSG_104, 265
ER_IB_LOB_ROLLBACK_INDEX_LEN, 368	ER_IB_MSG_1040, 323
ER_IB_LOCK_VALIDATE_LATCH_ORDER_VIOLATION, 376	ER_IB_MSG_1041, 324
ER_IB_LONG_AHI_DISABLE_WAIT, 270	ER_IB_MSG_1042, 324
ER_IB_LONG_ROLLBACK, 426	ER_IB_MSG_1043, 324
ER_IB_LONG_ROLLBACK_FULL, 426	ER_IB_MSG_1044, 324
ER_IB_MSG_0, 259	ER_IB_MSG_1045, 324
ER_IB_MSG_1, 259	ER_IB_MSG_1046, 324
ER_IB_MSG_10, 259	ER_IB_MSG_1047, 324
ER_IB_MSG_100, 265	ER_IB_MSG_1048, 324
ER_IB_MSG_1000, 321	ER_IB_MSG_1049, 324
ER_IB_MSG_1001, 321	ER_IB_MSG_105, 265
ER_IB_MSG_1002, 321	ER_IB_MSG_1051, 324
ER_IB_MSG_1003, 321	ER_IB_MSG_1052, 324
ER_IB_MSG_1004, 321	ER_IB_MSG_1053, 324
ER_IB_MSG_1005, 321	ER_IB_MSG_1054, 324
ER_IB_MSG_1006, 321	ER_IB_MSG_1055, 324
ER_IB_MSG_1007, 321	ER_IB_MSG_1056, 324
ER_IB_MSG_1008, 321	ER_IB_MSG_1057, 325
ER_IB_MSG_1009, 321	ER_IB_MSG_1058, 325
ER_IB_MSG_101, 265	ER_IB_MSG_1059, 325
ER_IB_MSG_1010, 321	ER_IB_MSG_106, 265
ER_IB_MSG_1011, 322	ER_IB_MSG_1060, 325
ER_IB_MSG_1012, 322	ER_IB_MSG_1065, 325
ER_IB_MSG_1013, 322	ER_IB_MSG_107, 265
ER_IB_MSG_1015, 322	ER_IB_MSG_1070, 325
ER_IB_MSG_1016, 322	ER_IB_MSG_1071, 325
ER_IB_MSG_1017, 322	ER_IB_MSG_1072, 326
ER_IB_MSG_1018, 322	ER_IB_MSG_1073, 326
ER_IB_MSG_1019, 322	ER_IB_MSG_1074, 326
ER_IB_MSG_102, 265	ER_IB_MSG_1075, 326
ER_IB_MSG_1020, 322	ER_IB_MSG_1076, 326
ER_IB_MSG_1021, 322	ER_IB_MSG_1077, 326
ER_IB_MSG_1022, 322	ER_IB_MSG_1078, 326
ER_IB_MSG_1023, 322	ER_IB_MSG_1079, 326
ER_IB_MSG_1024, 322	ER_IB_MSG_108, 265
ER_IB_MSG_1025, 322	ER_IB_MSG_1080, 326
ER_IB_MSG_1026, 323	ER_IB_MSG_1081, 326
ER_IB_MSG_1027, 323	ER_IB_MSG_1082, 326
ER_IB_MSG_1028, 323	ER_IB_MSG_1083, 326
ER_IB_MSG_1029, 323	ER_IB_MSG_1085, 326
ER_IB_MSG_103, 265	ER_IB_MSG_1086, 326
ER_IB_MSG_1030, 323	ER_IB_MSG_1087, 327
ER_IB_MSG_1031, 323	ER_IB_MSG_1088, 327
ER_IB_MSG_1032, 323	ER_IB_MSG_1089, 327
ER_IB_MSG_1033, 323	ER_IB_MSG_109, 265
ER_IB_MSG_1034, 323	ER_IB_MSG_1090, 327
ER_IB_MSG_1035, 323	ER_IB_MSG_1091, 327
ER_IB_MSG_1036, 323	ER_IB_MSG_1092, 327
ER_IB_MSG_1037, 323	ER_IB_MSG_1093, 327
ER_IB_MSG_1038, 323	ER_IB_MSG_1094, 327
	ER_IB_MSG_1095, 327
	ER_IB_MSG_1096, 327

ER_IB_MSG_1097, 327	ER_IB_MSG_1157, 331
ER_IB_MSG_1098, 327	ER_IB_MSG_1158, 332
ER_IB_MSG_1099, 327	ER_IB_MSG_1159, 332
ER_IB_MSG_11, 259	ER_IB_MSG_1160, 332
ER_IB_MSG_110, 266	ER_IB_MSG_1161, 332
ER_IB_MSG_1100, 327	ER_IB_MSG_1162, 332
ER_IB_MSG_1101, 328	ER_IB_MSG_1163, 332
ER_IB_MSG_1102, 328	ER_IB_MSG_1164, 332
ER_IB_MSG_1103, 328	ER_IB_MSG_1165, 332
ER_IB_MSG_1104, 328	ER_IB_MSG_1177, 332
ER_IB_MSG_1105, 328	ER_IB_MSG_1178, 333
ER_IB_MSG_1107, 328	ER_IB_MSG_1179, 333
ER_IB_MSG_1108, 328	ER_IB_MSG_1180, 333
ER_IB_MSG_1109, 328	ER_IB_MSG_1181, 333
ER_IB_MSG_111, 266	ER_IB_MSG_1182, 333
ER_IB_MSG_1110, 328	ER_IB_MSG_1183, 333
ER_IB_MSG_1111, 328	ER_IB_MSG_1185, 333
ER_IB_MSG_1112, 328	ER_IB_MSG_1186, 333
ER_IB_MSG_1113, 328	ER_IB_MSG_1187, 333
ER_IB_MSG_1114, 328	ER_IB_MSG_1188, 333
ER_IB_MSG_1115, 329	ER_IB_MSG_1189, 333
ER_IB_MSG_1116, 329	ER_IB_MSG_119, 266
ER_IB_MSG_1117, 329	ER_IB_MSG_1191, 333
ER_IB_MSG_1119, 329	ER_IB_MSG_1192, 334
ER_IB_MSG_112, 266	ER_IB_MSG_1193, 334
ER_IB_MSG_1120, 329	ER_IB_MSG_1194, 334
ER_IB_MSG_1121, 329	ER_IB_MSG_1195, 334
ER_IB_MSG_1122, 329	ER_IB_MSG_1196, 334
ER_IB_MSG_1123, 329	ER_IB_MSG_1197, 334
ER_IB_MSG_1124, 329	ER_IB_MSG_1198, 334
ER_IB_MSG_1125, 329	ER_IB_MSG_1199, 334
ER_IB_MSG_1126, 329	ER_IB_MSG_12, 259
ER_IB_MSG_1127, 329	ER_IB_MSG_120, 266
ER_IB_MSG_1128, 329	ER_IB_MSG_1200, 334
ER_IB_MSG_1129, 329	ER_IB_MSG_1201, 334
ER_IB_MSG_1130, 329	ER_IB_MSG_1202, 334
ER_IB_MSG_1131, 330	ER_IB_MSG_1203, 334
ER_IB_MSG_1132, 330	ER_IB_MSG_1204, 334
ER_IB_MSG_1133, 330	ER_IB_MSG_1205, 334
ER_IB_MSG_1134, 330	ER_IB_MSG_1206, 334
ER_IB_MSG_1139, 330	ER_IB_MSG_1207, 335
ER_IB_MSG_1142, 330	ER_IB_MSG_1208, 335
ER_IB_MSG_1144, 331	ER_IB_MSG_1209, 335
ER_IB_MSG_1145, 331	ER_IB_MSG_121, 266
ER_IB_MSG_1146, 331	ER_IB_MSG_1210, 335
ER_IB_MSG_1147, 331	ER_IB_MSG_1211, 335
ER_IB_MSG_1148, 331	ER_IB_MSG_1212, 335
ER_IB_MSG_1149, 331	ER_IB_MSG_1213, 335
ER_IB_MSG_1150, 331	ER_IB_MSG_1214, 335
ER_IB_MSG_1151, 331	ER_IB_MSG_1215, 335
ER_IB_MSG_1152, 331	ER_IB_MSG_1217, 335
ER_IB_MSG_1154, 331	ER_IB_MSG_1218, 335
ER_IB_MSG_1155, 331	ER_IB_MSG_1219, 335
ER_IB_MSG_1156, 331	ER_IB_MSG_122, 266

ER_IB_MSG_1220, 335
ER_IB_MSG_1221, 336
ER_IB_MSG_1222, 336
ER_IB_MSG_1223, 336
ER_IB_MSG_1224, 336
ER_IB_MSG_1225, 336
ER_IB_MSG_1226, 336
ER_IB_MSG_1227, 336
ER_IB_MSG_1228, 336
ER_IB_MSG_1229, 336
ER_IB_MSG_123, 266
ER_IB_MSG_1231, 336
ER_IB_MSG_1233, 336
ER_IB_MSG_1235, 336
ER_IB_MSG_1238, 337
ER_IB_MSG_1239, 337
ER_IB_MSG_124, 266
ER_IB_MSG_1241, 337
ER_IB_MSG_1245, 337
ER_IB_MSG_1246, 337
ER_IB_MSG_1247, 337
ER_IB_MSG_1248, 337
ER_IB_MSG_1249, 337
ER_IB_MSG_125, 266
ER_IB_MSG_1250, 337
ER_IB_MSG_1251, 337
ER_IB_MSG_1253, 338
ER_IB_MSG_1255, 338
ER_IB_MSG_1256, 338
ER_IB_MSG_1257, 338
ER_IB_MSG_1258, 338
ER_IB_MSG_1259, 338
ER_IB_MSG_126, 266
ER_IB_MSG_1260, 338
ER_IB_MSG_1261, 338
ER_IB_MSG_1262, 338
ER_IB_MSG_1263, 338
ER_IB_MSG_1266, 338
ER_IB_MSG_1268, 339
ER_IB_MSG_1269, 339
ER_IB_MSG_127, 266
ER_IB_MSG_1272, 344
ER_IB_MSG_1273, 345
ER_IB_MSG_1274, 345
ER_IB_MSG_1275, 346
ER_IB_MSG_1277, 346
ER_IB_MSG_128, 266
ER_IB_MSG_1280, 346
ER_IB_MSG_1281, 346
ER_IB_MSG_1282, 346
ER_IB_MSG_1283, 346
ER_IB_MSG_1284, 346
ER_IB_MSG_1285, 362
ER_IB_MSG_129, 266

ER_IB_MSG_13, 260
ER_IB_MSG_130, 266
ER_IB_MSG_131, 267
ER_IB_MSG_132, 267
ER_IB_MSG_133, 267
ER_IB_MSG_134, 267
ER_IB_MSG_135, 267
ER_IB_MSG_1357, 377
ER_IB_MSG_1358, 377
ER_IB_MSG_1359, 377
ER_IB_MSG_136, 267
ER_IB_MSG_137, 267
ER_IB_MSG_1372, 378
ER_IB_MSG_1373, 378
ER_IB_MSG_1374, 378
ER_IB_MSG_1375, 378
ER_IB_MSG_138, 267
ER_IB_MSG_1381, 378
ER_IB_MSG_139, 267
ER_IB_MSG_14, 260
ER_IB_MSG_140, 267
ER_IB_MSG_141, 267
ER_IB_MSG_142, 267
ER_IB_MSG_143, 267
ER_IB_MSG_144, 267
ER_IB_MSG_145, 267
ER_IB_MSG_146, 268
ER_IB_MSG_147, 268
ER_IB_MSG_148, 268
ER_IB_MSG_15, 260
ER_IB_MSG_156, 268
ER_IB_MSG_157, 268
ER_IB_MSG_158, 268
ER_IB_MSG_159, 268
ER_IB_MSG_16, 260
ER_IB_MSG_160, 268
ER_IB_MSG_161, 269
ER_IB_MSG_162, 269
ER_IB_MSG_163, 269
ER_IB_MSG_164, 269
ER_IB_MSG_165, 269
ER_IB_MSG_166, 269
ER_IB_MSG_167, 269
ER_IB_MSG_168, 269
ER_IB_MSG_169, 269
ER_IB_MSG_17, 260
ER_IB_MSG_170, 269
ER_IB_MSG_171, 269
ER_IB_MSG_172, 269
ER_IB_MSG_173, 269
ER_IB_MSG_174, 269
ER_IB_MSG_175, 269
ER_IB_MSG_176, 270
ER_IB_MSG_177, 270

ER_IB_MSG_178, 270
ER_IB_MSG_179, 270
ER_IB_MSG_18, 260
ER_IB_MSG_180, 270
ER_IB_MSG_182, 270
ER_IB_MSG_183, 270
ER_IB_MSG_184, 270
ER_IB_MSG_187, 270
ER_IB_MSG_188, 270
ER_IB_MSG_189, 270
ER_IB_MSG_19, 260
ER_IB_MSG_190, 270
ER_IB_MSG_191, 270
ER_IB_MSG_192, 270
ER_IB_MSG_193, 271
ER_IB_MSG_194, 271
ER_IB_MSG_195, 271
ER_IB_MSG_196, 271
ER_IB_MSG_197, 271
ER_IB_MSG_198, 271
ER_IB_MSG_199, 271
ER_IB_MSG_2, 259
ER_IB_MSG_20, 260
ER_IB_MSG_200, 271
ER_IB_MSG_201, 271
ER_IB_MSG_202, 271
ER_IB_MSG_203, 271
ER_IB_MSG_204, 271
ER_IB_MSG_205, 271
ER_IB_MSG_206, 271
ER_IB_MSG_207, 271
ER_IB_MSG_208, 272
ER_IB_MSG_209, 272
ER_IB_MSG_21, 260
ER_IB_MSG_210, 272
ER_IB_MSG_211, 272
ER_IB_MSG_212, 272
ER_IB_MSG_213, 272
ER_IB_MSG_214, 272
ER_IB_MSG_215, 272
ER_IB_MSG_216, 272
ER_IB_MSG_217, 272
ER_IB_MSG_218, 272
ER_IB_MSG_219, 272
ER_IB_MSG_22, 260
ER_IB_MSG_220, 272
ER_IB_MSG_221, 272
ER_IB_MSG_222, 272
ER_IB_MSG_223, 273
ER_IB_MSG_224, 273
ER_IB_MSG_225, 273
ER_IB_MSG_226, 273
ER_IB_MSG_229, 273
ER_IB_MSG_23, 260
ER_IB_MSG_230, 273
ER_IB_MSG_231, 273
ER_IB_MSG_232, 273
ER_IB_MSG_233, 273
ER_IB_MSG_234, 273
ER_IB_MSG_235, 273
ER_IB_MSG_236, 273
ER_IB_MSG_237, 273
ER_IB_MSG_238, 273
ER_IB_MSG_239, 273
ER_IB_MSG_24, 260
ER_IB_MSG_240, 274
ER_IB_MSG_241, 274
ER_IB_MSG_242, 274
ER_IB_MSG_243, 274
ER_IB_MSG_244, 274
ER_IB_MSG_245, 274
ER_IB_MSG_246, 274
ER_IB_MSG_247, 274
ER_IB_MSG_248, 274
ER_IB_MSG_249, 274
ER_IB_MSG_25, 260
ER_IB_MSG_250, 274
ER_IB_MSG_251, 274
ER_IB_MSG_252, 274
ER_IB_MSG_253, 274
ER_IB_MSG_254, 274
ER_IB_MSG_255, 275
ER_IB_MSG_256, 275
ER_IB_MSG_257, 275
ER_IB_MSG_258, 275
ER_IB_MSG_259, 275
ER_IB_MSG_26, 260
ER_IB_MSG_260, 275
ER_IB_MSG_261, 275
ER_IB_MSG_262, 275
ER_IB_MSG_263, 275
ER_IB_MSG_264, 275
ER_IB_MSG_265, 275
ER_IB_MSG_266, 275
ER_IB_MSG_267, 275
ER_IB_MSG_268, 275
ER_IB_MSG_269, 275
ER_IB_MSG_27, 260
ER_IB_MSG_270, 276
ER_IB_MSG_271, 276
ER_IB_MSG_272, 276
ER_IB_MSG_273, 276
ER_IB_MSG_278, 276
ER_IB_MSG_28, 261
ER_IB_MSG_280, 276
ER_IB_MSG_281, 276
ER_IB_MSG_282, 276
ER_IB_MSG_283, 276

ER_IB_MSG_284, 276
ER_IB_MSG_285, 276
ER_IB_MSG_287, 276
ER_IB_MSG_288, 276
ER_IB_MSG_289, 277
ER_IB_MSG_29, 261
ER_IB_MSG_291, 277
ER_IB_MSG_292, 277
ER_IB_MSG_293, 277
ER_IB_MSG_294, 277
ER_IB_MSG_295, 277
ER_IB_MSG_296, 277
ER_IB_MSG_297, 277
ER_IB_MSG_298, 277
ER_IB_MSG_299, 277
ER_IB_MSG_3, 259
ER_IB_MSG_30, 261
ER_IB_MSG_300, 277
ER_IB_MSG_301, 277
ER_IB_MSG_303, 278
ER_IB_MSG_304, 278
ER_IB_MSG_305, 278
ER_IB_MSG_306, 278
ER_IB_MSG_307, 278
ER_IB_MSG_308, 278
ER_IB_MSG_309, 278
ER_IB_MSG_310, 278
ER_IB_MSG_311, 278
ER_IB_MSG_312, 278
ER_IB_MSG_313, 278
ER_IB_MSG_314, 278
ER_IB_MSG_315, 278
ER_IB_MSG_316, 278
ER_IB_MSG_317, 279
ER_IB_MSG_318, 279
ER_IB_MSG_319, 279
ER_IB_MSG_32, 261
ER_IB_MSG_320, 279
ER_IB_MSG_321, 279
ER_IB_MSG_322, 279
ER_IB_MSG_323, 279
ER_IB_MSG_324, 279
ER_IB_MSG_325, 279
ER_IB_MSG_326, 279
ER_IB_MSG_328, 279
ER_IB_MSG_329, 279
ER_IB_MSG_33, 261
ER_IB_MSG_330, 279
ER_IB_MSG_331, 279
ER_IB_MSG_332, 279
ER_IB_MSG_333, 280
ER_IB_MSG_334, 280
ER_IB_MSG_335, 280
ER_IB_MSG_336, 280

ER_IB_MSG_337, 280
ER_IB_MSG_338, 280
ER_IB_MSG_339, 280
ER_IB_MSG_34, 261
ER_IB_MSG_340, 280
ER_IB_MSG_341, 280
ER_IB_MSG_342, 280
ER_IB_MSG_343, 280
ER_IB_MSG_344, 280
ER_IB_MSG_345, 280
ER_IB_MSG_346, 280
ER_IB_MSG_347, 280
ER_IB_MSG_348, 281
ER_IB_MSG_349, 281
ER_IB_MSG_35, 261
ER_IB_MSG_350, 281
ER_IB_MSG_354, 281
ER_IB_MSG_355, 281
ER_IB_MSG_356, 281
ER_IB_MSG_357, 281
ER_IB_MSG_358, 281
ER_IB_MSG_359, 281
ER_IB_MSG_36, 261
ER_IB_MSG_360, 281
ER_IB_MSG_361, 281
ER_IB_MSG_362, 281
ER_IB_MSG_364, 281
ER_IB_MSG_365, 281
ER_IB_MSG_367, 282
ER_IB_MSG_368, 282
ER_IB_MSG_369, 282
ER_IB_MSG_37, 261
ER_IB_MSG_370, 282
ER_IB_MSG_371, 282
ER_IB_MSG_372, 282
ER_IB_MSG_373, 282
ER_IB_MSG_374, 282
ER_IB_MSG_375, 282
ER_IB_MSG_376, 282
ER_IB_MSG_377, 282
ER_IB_MSG_378, 282
ER_IB_MSG_379, 282
ER_IB_MSG_38, 261
ER_IB_MSG_380, 282
ER_IB_MSG_381, 283
ER_IB_MSG_382, 283
ER_IB_MSG_383, 283
ER_IB_MSG_384, 283
ER_IB_MSG_385, 283
ER_IB_MSG_386, 283
ER_IB_MSG_387, 283
ER_IB_MSG_39, 261
ER_IB_MSG_390, 283
ER_IB_MSG_391, 283

ER_IB_MSG_392, 283
ER_IB_MSG_393, 283
ER_IB_MSG_394, 283
ER_IB_MSG_395, 283
ER_IB_MSG_396, 284
ER_IB_MSG_397, 284
ER_IB_MSG_398, 284
ER_IB_MSG_399, 284
ER_IB_MSG_4, 259
ER_IB_MSG_40, 261
ER_IB_MSG_401, 284
ER_IB_MSG_402, 284
ER_IB_MSG_403, 284
ER_IB_MSG_404, 284
ER_IB_MSG_405, 284
ER_IB_MSG_406, 284
ER_IB_MSG_407, 284
ER_IB_MSG_408, 284
ER_IB_MSG_409, 284
ER_IB_MSG_41, 261
ER_IB_MSG_410, 284
ER_IB_MSG_411, 284
ER_IB_MSG_412, 285
ER_IB_MSG_413, 285
ER_IB_MSG_414, 285
ER_IB_MSG_415, 285
ER_IB_MSG_416, 285
ER_IB_MSG_417, 285
ER_IB_MSG_418, 285
ER_IB_MSG_419, 285
ER_IB_MSG_42, 261
ER_IB_MSG_420, 285
ER_IB_MSG_421, 285
ER_IB_MSG_422, 285
ER_IB_MSG_423, 285
ER_IB_MSG_424, 285
ER_IB_MSG_425, 285
ER_IB_MSG_426, 285
ER_IB_MSG_427, 286
ER_IB_MSG_428, 286
ER_IB_MSG_429, 286
ER_IB_MSG_43, 261
ER_IB_MSG_430, 286
ER_IB_MSG_431, 286
ER_IB_MSG_432, 286
ER_IB_MSG_433, 286
ER_IB_MSG_434, 286
ER_IB_MSG_435, 286
ER_IB_MSG_436, 286
ER_IB_MSG_437, 286
ER_IB_MSG_438, 286
ER_IB_MSG_439, 286
ER_IB_MSG_44, 262
ER_IB_MSG_440, 286
ER_IB_MSG_441, 286
ER_IB_MSG_442, 287
ER_IB_MSG_443, 287
ER_IB_MSG_445, 287
ER_IB_MSG_446, 287
ER_IB_MSG_447, 287
ER_IB_MSG_448, 287
ER_IB_MSG_449, 287
ER_IB_MSG_45, 262
ER_IB_MSG_450, 287
ER_IB_MSG_451, 287
ER_IB_MSG_452, 287
ER_IB_MSG_453, 287
ER_IB_MSG_454, 287
ER_IB_MSG_455, 287
ER_IB_MSG_456, 287
ER_IB_MSG_457, 287
ER_IB_MSG_458, 288
ER_IB_MSG_459, 288
ER_IB_MSG_46, 262
ER_IB_MSG_460, 288
ER_IB_MSG_461, 288
ER_IB_MSG_462, 288
ER_IB_MSG_463, 288
ER_IB_MSG_464, 288
ER_IB_MSG_465, 288
ER_IB_MSG_466, 288
ER_IB_MSG_467, 288
ER_IB_MSG_468, 288
ER_IB_MSG_469, 288
ER_IB_MSG_47, 262
ER_IB_MSG_470, 288
ER_IB_MSG_471, 288
ER_IB_MSG_472, 288
ER_IB_MSG_473, 289
ER_IB_MSG_474, 289
ER_IB_MSG_475, 289
ER_IB_MSG_476, 289
ER_IB_MSG_477, 289
ER_IB_MSG_478, 289
ER_IB_MSG_479, 289
ER_IB_MSG_48, 262
ER_IB_MSG_480, 289
ER_IB_MSG_481, 289
ER_IB_MSG_482, 289
ER_IB_MSG_483, 289
ER_IB_MSG_484, 289
ER_IB_MSG_485, 289
ER_IB_MSG_486, 289
ER_IB_MSG_487, 289
ER_IB_MSG_488, 290
ER_IB_MSG_489, 290
ER_IB_MSG_49, 262
ER_IB_MSG_490, 290

ER_IB_MSG_491, 290	ER_IB_MSG_544, 293
ER_IB_MSG_492, 290	ER_IB_MSG_545, 293
ER_IB_MSG_493, 290	ER_IB_MSG_546, 293
ER_IB_MSG_494, 290	ER_IB_MSG_547, 293
ER_IB_MSG_495, 290	ER_IB_MSG_548, 293
ER_IB_MSG_496, 290	ER_IB_MSG_549, 293
ER_IB_MSG_497, 290	ER_IB_MSG_55, 262
ER_IB_MSG_498, 290	ER_IB_MSG_550, 293
ER_IB_MSG_499, 290	ER_IB_MSG_551, 293
ER_IB_MSG_5, 259	ER_IB_MSG_552, 293
ER_IB_MSG_50, 262	ER_IB_MSG_553, 294
ER_IB_MSG_500, 290	ER_IB_MSG_554, 294
ER_IB_MSG_501, 290	ER_IB_MSG_555, 294
ER_IB_MSG_502, 290	ER_IB_MSG_556, 294
ER_IB_MSG_503, 291	ER_IB_MSG_557, 294
ER_IB_MSG_504, 291	ER_IB_MSG_558, 294
ER_IB_MSG_505, 291	ER_IB_MSG_559, 294
ER_IB_MSG_506, 291	ER_IB_MSG_56, 262
ER_IB_MSG_507, 291	ER_IB_MSG_560, 294
ER_IB_MSG_508, 291	ER_IB_MSG_561, 294
ER_IB_MSG_509, 291	ER_IB_MSG_562, 294
ER_IB_MSG_51, 262	ER_IB_MSG_563, 294
ER_IB_MSG_510, 291	ER_IB_MSG_564, 294
ER_IB_MSG_511, 291	ER_IB_MSG_566, 294
ER_IB_MSG_512, 291	ER_IB_MSG_567, 294
ER_IB_MSG_513, 291	ER_IB_MSG_568, 295
ER_IB_MSG_514, 291	ER_IB_MSG_569, 295
ER_IB_MSG_515, 291	ER_IB_MSG_57, 262
ER_IB_MSG_516, 291	ER_IB_MSG_570, 295
ER_IB_MSG_517, 291	ER_IB_MSG_571, 295
ER_IB_MSG_518, 292	ER_IB_MSG_573, 295
ER_IB_MSG_519, 292	ER_IB_MSG_574, 295
ER_IB_MSG_52, 262	ER_IB_MSG_578, 295
ER_IB_MSG_520, 292	ER_IB_MSG_579, 295
ER_IB_MSG_521, 292	ER_IB_MSG_57_STAT_SPACE_DELETE_FAIL, 373
ER_IB_MSG_522, 292	ER_IB_MSG_57_UNDO_SPACE_DELETE_FAIL, 370
ER_IB_MSG_523, 292	ER_IB_MSG_58, 262
ER_IB_MSG_524, 292	ER_IB_MSG_580, 295
ER_IB_MSG_525, 292	ER_IB_MSG_581, 295
ER_IB_MSG_526, 292	ER_IB_MSG_582, 295
ER_IB_MSG_527, 292	ER_IB_MSG_583, 295
ER_IB_MSG_53, 262	ER_IB_MSG_584, 295
ER_IB_MSG_530, 292	ER_IB_MSG_585, 295
ER_IB_MSG_531, 292	ER_IB_MSG_586, 295
ER_IB_MSG_532, 292	ER_IB_MSG_587, 296
ER_IB_MSG_533, 292	ER_IB_MSG_588, 296
ER_IB_MSG_534, 292	ER_IB_MSG_589, 296
ER_IB_MSG_537, 293	ER_IB_MSG_59, 263
ER_IB_MSG_538, 293	ER_IB_MSG_590, 296
ER_IB_MSG_539, 293	ER_IB_MSG_591, 296
ER_IB_MSG_54, 262	ER_IB_MSG_592, 296
ER_IB_MSG_540, 293	ER_IB_MSG_593, 296
ER_IB_MSG_541, 293	ER_IB_MSG_594, 296
ER_IB_MSG_543, 293	ER_IB_MSG_595, 296

ER_IB_MSG_596, 296
ER_IB_MSG_597, 296
ER_IB_MSG_598, 296
ER_IB_MSG_599, 296
ER_IB_MSG_6, 259
ER_IB_MSG_60, 263
ER_IB_MSG_600, 296
ER_IB_MSG_601, 296
ER_IB_MSG_602, 297
ER_IB_MSG_603, 297
ER_IB_MSG_604, 297
ER_IB_MSG_605, 297
ER_IB_MSG_606, 297
ER_IB_MSG_607, 297
ER_IB_MSG_608, 297
ER_IB_MSG_609, 297
ER_IB_MSG_61, 263
ER_IB_MSG_611, 297
ER_IB_MSG_612, 297
ER_IB_MSG_613, 297
ER_IB_MSG_614, 297
ER_IB_MSG_615, 297
ER_IB_MSG_616, 297
ER_IB_MSG_617, 297
ER_IB_MSG_619, 298
ER_IB_MSG_62, 263
ER_IB_MSG_623, 298
ER_IB_MSG_624, 298
ER_IB_MSG_626, 298
ER_IB_MSG_627, 298
ER_IB_MSG_628, 298
ER_IB_MSG_629, 298
ER_IB_MSG_63, 263
ER_IB_MSG_630, 298
ER_IB_MSG_631, 298
ER_IB_MSG_632, 298
ER_IB_MSG_633, 298
ER_IB_MSG_634, 298
ER_IB_MSG_635, 299
ER_IB_MSG_636, 299
ER_IB_MSG_637, 299
ER_IB_MSG_638, 299
ER_IB_MSG_639, 299
ER_IB_MSG_64, 263
ER_IB_MSG_642, 299
ER_IB_MSG_643, 299
ER_IB_MSG_644, 299
ER_IB_MSG_645, 299
ER_IB_MSG_646, 299
ER_IB_MSG_647, 299
ER_IB_MSG_648, 299
ER_IB_MSG_649, 299
ER_IB_MSG_65, 263
ER_IB_MSG_650, 299
ER_IB_MSG_651, 299
ER_IB_MSG_652, 300
ER_IB_MSG_654, 300
ER_IB_MSG_655, 300
ER_IB_MSG_656, 300
ER_IB_MSG_657, 300
ER_IB_MSG_658, 300
ER_IB_MSG_659, 300
ER_IB_MSG_66, 263
ER_IB_MSG_660, 300
ER_IB_MSG_661, 300
ER_IB_MSG_662, 300
ER_IB_MSG_663, 300
ER_IB_MSG_67, 263
ER_IB_MSG_68, 263
ER_IB_MSG_69, 263
ER_IB_MSG_694, 300
ER_IB_MSG_695, 300
ER_IB_MSG_696, 300
ER_IB_MSG_697, 301
ER_IB_MSG_699, 301
ER_IB_MSG_7, 259
ER_IB_MSG_70, 263
ER_IB_MSG_707, 301
ER_IB_MSG_708, 301
ER_IB_MSG_709, 301
ER_IB_MSG_71, 263
ER_IB_MSG_710, 301
ER_IB_MSG_711, 301
ER_IB_MSG_712, 302
ER_IB_MSG_713, 302
ER_IB_MSG_714, 302
ER_IB_MSG_715, 302
ER_IB_MSG_716, 302
ER_IB_MSG_718, 302
ER_IB_MSG_719, 302
ER_IB_MSG_72, 263
ER_IB_MSG_720, 302
ER_IB_MSG_722, 302
ER_IB_MSG_723, 302
ER_IB_MSG_724, 302
ER_IB_MSG_725, 302
ER_IB_MSG_726, 302
ER_IB_MSG_727, 303
ER_IB_MSG_728, 303
ER_IB_MSG_73, 263
ER_IB_MSG_737, 303
ER_IB_MSG_738, 303
ER_IB_MSG_739, 303
ER_IB_MSG_74, 264
ER_IB_MSG_740, 303
ER_IB_MSG_741, 304
ER_IB_MSG_742, 304
ER_IB_MSG_743, 304

ER_IB_MSG_744, 304
ER_IB_MSG_745, 304
ER_IB_MSG_746, 304
ER_IB_MSG_747, 304
ER_IB_MSG_748, 304
ER_IB_MSG_749, 304
ER_IB_MSG_75, 264
ER_IB_MSG_750, 304
ER_IB_MSG_751, 304
ER_IB_MSG_752, 304
ER_IB_MSG_753, 304
ER_IB_MSG_754, 304
ER_IB_MSG_755, 304
ER_IB_MSG_756, 305
ER_IB_MSG_757, 305
ER_IB_MSG_758, 305
ER_IB_MSG_759, 305
ER_IB_MSG_76, 264
ER_IB_MSG_760, 305
ER_IB_MSG_761, 305
ER_IB_MSG_762, 305
ER_IB_MSG_763, 305
ER_IB_MSG_764, 305
ER_IB_MSG_765, 305
ER_IB_MSG_766, 305
ER_IB_MSG_767, 305
ER_IB_MSG_768, 305
ER_IB_MSG_769, 305
ER_IB_MSG_77, 264
ER_IB_MSG_770, 305
ER_IB_MSG_771, 306
ER_IB_MSG_772, 306
ER_IB_MSG_773, 306
ER_IB_MSG_774, 306
ER_IB_MSG_775, 306
ER_IB_MSG_776, 306
ER_IB_MSG_777, 306
ER_IB_MSG_778, 306
ER_IB_MSG_779, 306
ER_IB_MSG_78, 264
ER_IB_MSG_780, 306
ER_IB_MSG_781, 306
ER_IB_MSG_782, 306
ER_IB_MSG_783, 306
ER_IB_MSG_784, 306
ER_IB_MSG_785, 306
ER_IB_MSG_786, 307
ER_IB_MSG_787, 307
ER_IB_MSG_788, 307
ER_IB_MSG_789, 307
ER_IB_MSG_79, 264
ER_IB_MSG_790, 307
ER_IB_MSG_791, 307
ER_IB_MSG_792, 307

ER_IB_MSG_793, 307
ER_IB_MSG_794, 307
ER_IB_MSG_795, 307
ER_IB_MSG_796, 307
ER_IB_MSG_797, 307
ER_IB_MSG_798, 307
ER_IB_MSG_799, 307
ER_IB_MSG_8, 259
ER_IB_MSG_80, 264
ER_IB_MSG_800, 307
ER_IB_MSG_801, 308
ER_IB_MSG_802, 308
ER_IB_MSG_803, 308
ER_IB_MSG_804, 308
ER_IB_MSG_805, 308
ER_IB_MSG_806, 308
ER_IB_MSG_807, 308
ER_IB_MSG_808, 308
ER_IB_MSG_809, 308
ER_IB_MSG_81, 264
ER_IB_MSG_810, 308
ER_IB_MSG_811, 308
ER_IB_MSG_812, 308
ER_IB_MSG_813, 308
ER_IB_MSG_814, 308
ER_IB_MSG_815, 308
ER_IB_MSG_816, 309
ER_IB_MSG_817, 309
ER_IB_MSG_818, 309
ER_IB_MSG_819, 309
ER_IB_MSG_82, 264
ER_IB_MSG_820, 309
ER_IB_MSG_821, 309
ER_IB_MSG_822, 309
ER_IB_MSG_823, 309
ER_IB_MSG_824, 309
ER_IB_MSG_825, 309
ER_IB_MSG_826, 309
ER_IB_MSG_827, 309
ER_IB_MSG_828, 309
ER_IB_MSG_829, 309
ER_IB_MSG_83, 264
ER_IB_MSG_830, 309
ER_IB_MSG_831, 310
ER_IB_MSG_832, 310
ER_IB_MSG_833, 310
ER_IB_MSG_834, 310
ER_IB_MSG_835, 310
ER_IB_MSG_836, 310
ER_IB_MSG_837, 310
ER_IB_MSG_838, 310
ER_IB_MSG_839, 310
ER_IB_MSG_84, 264
ER_IB_MSG_840, 310

ER_IB_MSG_841, 310
ER_IB_MSG_842, 310
ER_IB_MSG_844, 310
ER_IB_MSG_845, 310
ER_IB_MSG_847, 311
ER_IB_MSG_848, 311
ER_IB_MSG_849, 311
ER_IB_MSG_85, 264
ER_IB_MSG_850, 311
ER_IB_MSG_851, 311
ER_IB_MSG_852, 311
ER_IB_MSG_853, 311
ER_IB_MSG_854, 311
ER_IB_MSG_855, 311
ER_IB_MSG_856, 311
ER_IB_MSG_857, 311
ER_IB_MSG_858, 311
ER_IB_MSG_859, 311
ER_IB_MSG_86, 264
ER_IB_MSG_860, 311
ER_IB_MSG_861, 312
ER_IB_MSG_862, 312
ER_IB_MSG_863, 312
ER_IB_MSG_864, 312
ER_IB_MSG_865, 312
ER_IB_MSG_866, 312
ER_IB_MSG_867, 312
ER_IB_MSG_868, 312
ER_IB_MSG_869, 312
ER_IB_MSG_870, 312
ER_IB_MSG_871, 312
ER_IB_MSG_872, 312
ER_IB_MSG_873, 312
ER_IB_MSG_874, 312
ER_IB_MSG_875, 312
ER_IB_MSG_876, 313
ER_IB_MSG_877, 313
ER_IB_MSG_878, 313
ER_IB_MSG_879, 313
ER_IB_MSG_880, 313
ER_IB_MSG_881, 313
ER_IB_MSG_882, 313
ER_IB_MSG_883, 313
ER_IB_MSG_884, 313
ER_IB_MSG_885, 313
ER_IB_MSG_886, 313
ER_IB_MSG_887, 313
ER_IB_MSG_888, 313
ER_IB_MSG_889, 313
ER_IB_MSG_890, 313
ER_IB_MSG_891, 314
ER_IB_MSG_892, 314
ER_IB_MSG_893, 314
ER_IB_MSG_894, 314

ER_IB_MSG_895, 314
ER_IB_MSG_896, 314
ER_IB_MSG_897, 314
ER_IB_MSG_898, 314
ER_IB_MSG_899, 314
ER_IB_MSG_9, 259
ER_IB_MSG_900, 314
ER_IB_MSG_901, 314
ER_IB_MSG_902, 314
ER_IB_MSG_903, 314
ER_IB_MSG_904, 314
ER_IB_MSG_905, 314
ER_IB_MSG_906, 315
ER_IB_MSG_907, 315
ER_IB_MSG_908, 315
ER_IB_MSG_909, 315
ER_IB_MSG_910, 315
ER_IB_MSG_911, 315
ER_IB_MSG_912, 315
ER_IB_MSG_913, 315
ER_IB_MSG_914, 315
ER_IB_MSG_915, 315
ER_IB_MSG_916, 315
ER_IB_MSG_917, 315
ER_IB_MSG_918, 315
ER_IB_MSG_919, 315
ER_IB_MSG_920, 315
ER_IB_MSG_921, 316
ER_IB_MSG_922, 316
ER_IB_MSG_923, 316
ER_IB_MSG_924, 316
ER_IB_MSG_925, 316
ER_IB_MSG_926, 316
ER_IB_MSG_927, 316
ER_IB_MSG_928, 316
ER_IB_MSG_929, 316
ER_IB_MSG_930, 316
ER_IB_MSG_931, 316
ER_IB_MSG_932, 316
ER_IB_MSG_933, 316
ER_IB_MSG_934, 316
ER_IB_MSG_935, 316
ER_IB_MSG_936, 317
ER_IB_MSG_937, 317
ER_IB_MSG_938, 317
ER_IB_MSG_939, 317
ER_IB_MSG_940, 317
ER_IB_MSG_941, 317
ER_IB_MSG_942, 317
ER_IB_MSG_943, 317
ER_IB_MSG_944, 317
ER_IB_MSG_945, 317
ER_IB_MSG_946, 317
ER_IB_MSG_948, 317

ER_IB_MSG_949, 317	ER_IB_MSG_998, 321
ER_IB_MSG_95, 265	ER_IB_MSG_999, 321
ER_IB_MSG_950, 317	ER_IB_MSG_BAD_DBLWR_FILE_NAME, 371
ER_IB_MSG_951, 318	ER_IB_MSG_BTREE_LEVEL_LIMIT_EXCEEDED,
ER_IB_MSG_952, 318	364
ER_IB_MSG_953, 318	ER_IB_MSG_BUF_PENDING_IO, 328
ER_IB_MSG_954, 318	ER_IB_MSG_BUF_PENDING_IO_ON_SHUTDOWN,
ER_IB_MSG_955, 318	337
ER_IB_MSG_956, 318	ER_IB_MSG_BUF_POOL_RESIZE_CODE_STATUS,
ER_IB_MSG_957, 318	405
ER_IB_MSG_958, 318	ER_IB_MSG_BUF_POOL_RESIZE_COMPLETE_CUR_CODE,
ER_IB_MSG_959, 318	405
ER_IB_MSG_96, 265	ER_IB_MSG_BUF_POOL_RESIZE_PROGRESS_UPDATE,
ER_IB_MSG_960, 318	405
ER_IB_MSG_961, 318	ER_IB_MSG_CANNOT_FIND_DD_UNDO_SPACE,
ER_IB_MSG_962, 318	374
ER_IB_MSG_963, 318	ER_IB_MSG_CANNOT_OPEN_57_UNDO, 326
ER_IB_MSG_964, 318	ER_IB_MSG_CANT_DECRYPT_REDO_LOG, 311
ER_IB_MSG_965, 318	ER_IB_MSG_CANT_ENCRYPT_REDO_LOG_DATA,
ER_IB_MSG_966, 319	310
ER_IB_MSG_967, 319	ER_IB_MSG_CLEAR_INSTANT_DROP_COLUMN_METADATA,
ER_IB_MSG_968, 319	404
ER_IB_MSG_969, 319	ER_IB_MSG_CLOCK_GETTIME_FAILED, 362
ER_IB_MSG_97, 265	ER_IB_MSG_CLOCK_MONOTONIC_UNSUPPORTED,
ER_IB_MSG_970, 319	362
ER_IB_MSG_971, 319	ER_IB_MSG_CLONE_DDL_APPLY, 392
ER_IB_MSG_972, 319	ER_IB_MSG_CLONE_DDL_INVALIDATE, 392
ER_IB_MSG_973, 319	ER_IB_MSG_CLONE_DDL_NTFN, 392
ER_IB_MSG_974, 319	ER_IB_MSG_CREATED_UNDO_SPACE, 380
ER_IB_MSG_975, 319	ER_IB_MSG_DATA_DIRECTORY_NOT_INITIALIZED_OR_CORR
ER_IB_MSG_976, 319	330
ER_IB_MSG_977, 319	ER_IB_MSG_DBLWR_1285, 370
ER_IB_MSG_978, 319	ER_IB_MSG_DBLWR_1286, 371
ER_IB_MSG_979, 319	ER_IB_MSG_DBLWR_1287, 371
ER_IB_MSG_98, 265	ER_IB_MSG_DBLWR_1288, 371
ER_IB_MSG_980, 319	ER_IB_MSG_DBLWR_1290, 371
ER_IB_MSG_981, 320	ER_IB_MSG_DBLWR_1293, 371
ER_IB_MSG_982, 320	ER_IB_MSG_DBLWR_1294, 371
ER_IB_MSG_983, 320	ER_IB_MSG_DBLWR_1295, 371
ER_IB_MSG_984, 320	ER_IB_MSG_DBLWR_1296, 371
ER_IB_MSG_985, 320	ER_IB_MSG_DBLWR_1297, 371
ER_IB_MSG_986, 320	ER_IB_MSG_DBLWR_1298, 371
ER_IB_MSG_987, 320	ER_IB_MSG_DBLWR_1300, 371
ER_IB_MSG_988, 320	ER_IB_MSG_DBLWR_1301, 371
ER_IB_MSG_989, 320	ER_IB_MSG_DBLWR_1304, 371
ER_IB_MSG_99, 265	ER_IB_MSG_DBLWR_1305, 371
ER_IB_MSG_990, 320	ER_IB_MSG_DBLWR_1306, 372
ER_IB_MSG_991, 320	ER_IB_MSG_DBLWR_1307, 372
ER_IB_MSG_992, 320	ER_IB_MSG_DBLWR_1308, 372
ER_IB_MSG_993, 320	ER_IB_MSG_DBLWR_1309, 372
ER_IB_MSG_994, 320	ER_IB_MSG_DBLWR_1310, 372
ER_IB_MSG_995, 320	ER_IB_MSG_DBLWR_1311, 372
ER_IB_MSG_996, 321	ER_IB_MSG_DBLWR_1312, 372
ER_IB_MSG_997, 321	ER_IB_MSG_DBLWR_1313, 372

ER_IB_MSG_DBLWR_1314, 372
ER_IB_MSG_DBLWR_1315, 372
ER_IB_MSG_DBLWR_1316, 372
ER_IB_MSG_DBLWR_1317, 372
ER_IB_MSG_DBLWR_1318, 372
ER_IB_MSG_DBLWR_1320, 372
ER_IB_MSG_DBLWR_1321, 373
ER_IB_MSG_DBLWR_1323, 373
ER_IB_MSG_DBLWR_1324, 373
ER_IB_MSG_DBLWR_1325, 373
ER_IB_MSG_DBLWR_1326, 373
ER_IB_MSG_DBLWR_1327, 373
ER_IB_MSG_DBLWR_LOAD_WRONG_SIZE, 372
ER_IB_MSG_DBLWR_OPEN_OR_CREATE_WRONG_SIZE, 373
ER_IB_MSG_DDL_FAIL_NO_BUILDER, 415
ER_IB_MSG_DDL_LOG_DELETE_BY_ID_OK, 300
ER_IB_MSG_DDL_LOG_DELETE_BY_ID_TMCT, 361
ER_IB_MSG_DDL_LOG_FAIL_POST_DDL, 361
ER_IB_MSG_DEPRECATED_INNODB_UNDO_TABLESPACE, 351
ER_IB_MSG_DICT_PARTITION_NOT_FOUND, 370
ER_IB_MSG_DOWNGRADE_PARTITION_FILE, 369
ER_IB_MSG_DROPPED_UNDO_SPACE, 380
ER_IB_MSG_ERROR_OPENING_NEW_UNDO_SPACE, 350
ER_IB_MSG_FAILED_SDI_Z_BUF_ERROR, 350
ER_IB_MSG_FAILED_SDI_Z_MEM_ERROR, 350
ER_IB_MSG_FAILED_TO_ALLOCATE_WAIT, 350
ER_IB_MSG_FAILED_TO_FINISH_TRUNCATE, 351
ER_IB_MSG_FAIL_TO_SAVE_SPACE_STATE, 350
ER_IB_MSG_FILE_RESIZE, 325
ER_IB_MSG_FIL_STATE_MOVED_CHANGED_NAME, 369
ER_IB_MSG_FIL_STATE_MOVED_CHANGED_PATH, 369
ER_IB_MSG_FIL_STATE_MOVED_CORRECTED, 369
ER_IB_MSG_FIL_STATE_MOVED_PREV, 428
ER_IB_MSG_FIL_STATE_MOVED_PREV_OR_HAS_DATA, 428
ER_IB_MSG_FIL_STATE_MOVED_TOO_MANY, 369
ER_IB_MSG_FOUND_WRONG_UNDO_SPACE, 350
ER_IB_MSG_GENERAL_TABLESPACE_UNDER_DATADIR, 283
ER_IB_MSG_GTID_FLUSH_AT_SHUTDOWN, 373
ER_IB_MSG_IBUF_CURSOR_RESTORATION_FAILED, 298
ER_IB_MSG_IBUF_FAILED_TO_RESTORE_POSITION, 298
ER_IB_MSG_IGNORE_SCAN_PATH, 282
ER_IB_MSG_IMPLICIT_TABLESPACE_IN_DATADIR, 283
ER_IB_MSG_INCORRECT_SIZE, 380
ER_IB_MSG_INJECT_CRASH, 379
ER_IB_MSG_INJECT_FAILURE, 379
ER_IB_MSG_INNODB_END_INITIALIZE, 373
ER_IB_MSG_INNODB_FLUSH_METHOD, 428
ER_IB_MSG_INNODB_START_INITIALIZE, 373
ER_IB_MSG_INVALID_LOCATION_FOR_TABLE, 294
ER_IB_MSG_INVALID_LOCATION_FOR_TABLESPACE, 374
ER_IB_MSG_INVALID_LOCATION_WRONG_DB, 374
ER_IB_MSG_INVALID_PAGE_TYPE, 405
ER_IB_MSG_LOCK_FREE_HASH_USAGE_STATS, 351
ER_IB_MSG_LOG_CHECKPOINT_FOUND, 399
ER_IB_MSG_LOG_CORRUPT, 301
ER_IB_MSG_LOG_FILES_CANNOT_ENCRYPT_IN_READ_ONLY, 337
ER_IB_MSG_LOG_FILES_CAPACITY_CHANGED, 399
ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE, 303
ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE_AND_READ_ONLY, 398
ER_IB_MSG_LOG_FILES_CREATED_BY_MEB, 303
ER_IB_MSG_LOG_FILES_CREATED_BY_MEB_AND_READ_ONLY, 303
ER_IB_MSG_LOG_FILES_CREATED_BY_UNKNOWN_CREATE, 400
ER_IB_MSG_LOG_FILES_CREATE_AND_READ_ONLY_MODE, 325
ER_IB_MSG_LOG_FILES_DIFFERENT_SIZES, 330
ER_IB_MSG_LOG_FILES_ENCRYPTION_INIT_FAILED, 337
ER_IB_MSG_LOG_FILES_FOUND_MISSING, 400
ER_IB_MSG_LOG_FILES_INITIALIZED, 325
ER_IB_MSG_LOG_FILES_INVALID_SET, 330
ER_IB_MSG_LOG_FILES_RESIZE_CANCELLED, 399
ER_IB_MSG_LOG_FILES_RESIZE_FINISHED, 400
ER_IB_MSG_LOG_FILES_RESIZE_ON_START, 335
ER_IB_MSG_LOG_FILES_RESIZE_REQUESTED, 399
ER_IB_MSG_LOG_FILES_REWRITING, 330
ER_IB_MSG_LOG_FILES_UPGRADE, 400
ER_IB_MSG_LOG_FILE_DIFFERENT_FORMATS, 400
ER_IB_MSG_LOG_FILE_FOREIGN_UUID, 399
ER_IB_MSG_LOG_FILE_FORMAT_TOO_NEW, 400
ER_IB_MSG_LOG_FILE_FORMAT_TOO_OLD, 400
ER_IB_MSG_LOG_FILE_FORMAT_UNKNOWN, 301
ER_IB_MSG_LOG_FILE_HEADER_INVALID_CHECKSUM, 338

ER_IB_MSG_LOG_FILE_HEADER_READ_FAILED, 397	ER_IB_MSG_LOG_PFS_CREATE_TABLES_FAILED, 401
ER_IB_MSG_LOG_FILE_INVALID_LSN_RANGES, 399	ER_IB_MSG_LOG_PRE_8_0_30_MISSING_FILE0, 400
ER_IB_MSG_LOG_FILE_INVALID_START_LSN, 399	ER_IB_MSG_LOG_UPGRADE_CLONED_DB, 399
ER_IB_MSG_LOG_FILE_IS_EMPTY, 397	ER_IB_MSG_LOG_UPGRADE_CORRUPTION__UNEXPECTED, 399
ER_IB_MSG_LOG_FILE_MARK_AS_UNUSED_FAILED, 401	ER_IB_MSG_LOG_UPGRADE_FORCED_RECV, 398
ER_IB_MSG_LOG_FILE_MARK_CURRENT_AS_INCOMPLETE, 400	ER_IB_MSG_LOG_UPGRADE_IN_READ_ONLY_MODE, 399
ER_IB_MSG_LOG_FILE_MISSING_FOR_ID, 399	ER_IB_MSG_LOG_UPGRADE_UNINITIALIZED_FILES, 399
ER_IB_MSG_LOG_FILE_OPEN_FAILED, 325	ER_IB_MSG_LOG_WRITER_ABORTS_LOG_ARCHIVER, 336
ER_IB_MSG_LOG_FILE_OS_CREATE_FAILED, 325	ER_IB_MSG_LOG_WRITER_ENTERED_EXTRA_MARGIN, 398
ER_IB_MSG_LOG_FILE_PREPARE_ON_CREATE_FAILED, 325	ER_IB_MSG_LOG_WRITER_EXITED_EXTRA_MARGIN, 398
ER_IB_MSG_LOG_FILE_REMOVE_FAILED, 400	ER_IB_MSG_LOG_WRITER_OUT_OF_SPACE, 336
ER_IB_MSG_LOG_FILE_RENAME_ON_CREATE_FAILED, 400	ER_IB_MSG_LOG_WRITER_WAITING_FOR_ARCHIVER, 337
ER_IB_MSG_LOG_FILE_RESIZE_FAILED, 325	ER_IB_MSG_LOG_WRITER_WAIT_ON_CONSUMER, 404
ER_IB_MSG_LOG_FILE_SIZE_INVALID, 330	ER_IB_MSG_LOG_WRITER_WAIT_ON_NEW_LOG_FILE, 398
ER_IB_MSG_LOG_FILE_TOO_BIG, 397	ER_IB_MSG_LOG_WRITER_WRITE_FAILED, 398
ER_IB_MSG_LOG_FILE_TOO_SMALL, 397	ER_IB_MSG_MADVISE_FAILED, 350
ER_IB_MSG_LOG_FILE_TRUNCATE, 401	ER_IB_MSG_MADV_DONTDUMP_UNSUPPORTED, 350
ER_IB_MSG_LOG_FILE_UNUSED_MARK_AS_IN_USE_FAILED, 401	ER_IB_MSG_MASTER_KEY_ROTATED, 380
ER_IB_MSG_LOG_FILE_UNUSED_REMOVE_FAILED, 401	ER_IB_MSG_MAX_UNDO_SPACES_REACHED, 350
ER_IB_MSG_LOG_FILE_UNUSED_RENAME_FAILED, 401	ER_IB_MSG_NOT_END_WITH_IBU, 351
ER_IB_MSG_LOG_FILE_UNUSED_RESIZE_FAILED, 401	ER_IB_MSG_NO_ENCRYPT_PROGRESS_FOUND, 346
ER_IB_MSG_LOG_FORMAT_BEFORE_5_7_9, 338	ER_IB_MSG_PAGE_ARCH_NO_RESET_POINTS, 373
ER_IB_MSG_LOG_FORMAT_BEFORE_8_0_30, 301	ER_IB_MSG_PARSE_OLD_REDO_INDEX_VERSION, 404
ER_IB_MSG_LOG_FORMAT_OLD, 303	ER_IB_MSG_PAR_RSEG_INIT_COMPLETE_MSG, 390
ER_IB_MSG_LOG_FORMAT_OLD_AND_LOG_CORRUPTED, 301	ER_IB_MSG_PAR_RSEG_INIT_TIME_MSG, 390
ER_IB_MSG_LOG_FORMAT_OLD_AND_NO_CLEAN_SHUTDOWN, 301	ER_IB_MSG_POST_RECOVER_DDL_LOG_RECOVER, 361
ER_IB_MSG_LOG_INIT_DIR_LIST_FAILED, 398	ER_IB_MSG_POST_RECOVER_POST_TS_ENCRYPT, 361
ER_IB_MSG_LOG_INIT_DIR_MISSING_SUBDIR, 398	ER_IB_MSG_RECOVERY_CHECKPOINT_FROM_BEFORE_CLEANUP, 303
ER_IB_MSG_LOG_INIT_DIR_NOT_EMPTY_WONT_INITIALIZE, 398	ER_IB_MSG_RECOVERY_CHECKPOINT_NOT_FOUND, 301
ER_IB_MSG_LOG_PARAMS_CONCURRENCY_MARGIN_INVALID, 338	ER_IB_MSG_RECOVERY_CHECKPOINT_OUTSIDE_LOG_FILE, 398
ER_IB_MSG_LOG_PARAMS_DEDICATED_SERVER_IGNORED, 401	ER_IB_MSG_RECOVERY_CORRUPT, 330
ER_IB_MSG_LOG_PARAMS_FILE_SIZE_UNUSED, 398	ER_IB_MSG_RECOVERY_IN_READ_ONLY, 303
ER_IB_MSG_LOG_PARAMS_LEGACY_USAGE, 401	ER_IB_MSG_RECOVERY_IS_NEEDED, 303
ER_IB_MSG_LOG_PARAMS_N_FILES_UNUSED, 398	
ER_IB_MSG_LOG_PFS_ACQUIRE_SERVICES_FAILED, 400	

ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG_	ER_IB_MSG_MERGES	ER_IB_MSG_MERGES, 369
390	ER_IB_MSG_MERGES	ER_IB_MSG_MERGES, 369
ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG_	ER_IB_MSG_USING_UNDO_SPACE,	350
390	ER_IB_MSG_WAIT_FOR_ENCRYPT_THREAD,	346
ER_IB_MSG_RECOVERY_SKIPPED_IN_READ_ONLY_MODE,	ER_IB_MSG_WRONG_TABLESPACE_DIR,	351
302	ER_IB_PARALLEL_READER_WORKER_INFO,	405
ER_IB_MSG_REENCRYPTED_GENERAL_TABLESPACE_KEY,	ER_IB_PRIMARY_KEY_IS_INSTANT,	409
389	ER_IB_RDBLWR_BYTES_INFO,	397
ER_IB_MSG_REENCRYPTED_TABLESPACE_KEY,	ER_IB_RECV_FIRST_REC_GROUP_INVALID,	362
389	ER_IB_RELOCK_LATCH_ORDER_VIOLATION,	377
ER_IB_MSG_RESUME_OP_FOR_SPACE,	ER_IB_RESURRECT_ACQUIRE_TABLE_LOCK,	411
346	ER_IB_RESURRECT_IDENTIFY_TABLE_TO_LOCK,	411
ER_IB_MSG_SCANNING_TEMP_TABLESPACE_DIR,	ER_IB_RESURRECT_RECORD_COMPLETE,	411
377	ER_IB_RESURRECT_RECORD_PROGRESS,	411
ER_IB_MSG_SDI_Z_STREAM_ERROR,	ER_IB_RESURRECT_TRX_INSERT,	411
350	ER_IB_RESURRECT_TRX_INSERT_COMPLETE,	411
ER_IB_MSG_SDI_Z_UNKNOWN_ERROR,	ER_IB_RESURRECT_TRX_UPDATE,	411
350	ER_IB_RESURRECT_TRX_UPDATE_COMPLETE,	411
ER_IB_MSG_SKIP_HIDDEN_DIR,	ER_IB_SELECT_COUNT_STAR,	410
368	ER_IB_SYNC_READ_FAILED,	419
ER_IB_MSG_STATS_SAMPLING_TOO_LARGE,	ER_IB_TABLESPACE_PATH_VALIDATION_SKIPPED,	376
384	ER_IB_TMP_TABLESPACE_CANNOT_CREATE_DIRECTORY,	377
ER_IB_MSG_SUBMIT_DETAILED_BUG_REPORT,	ER_IB_UNABLE_TO_EXPAND_TEMPORARY_TABLESPACE,	377
426	ER_IB_WARN_ACCESSING_NONEXISTING_SPACE,	276
ER_IB_MSG_THREAD_CONCURRENCY_CHANGED,	ER_IB_WARN_MANY_NON_LRU_FILES_OPENED,	395
339	ER_IB_WARN_OPEN_PARTITION_FILE,	369
ER_IB_MSG_TOO_LONG_PATH,	ER_IB_WRN_ENCRYPTION_INFO_SIZE_MISMATCH,	392
362	ER_IB_WRN_FAILED_TO_ACQUIRE_SERVICE,	385
ER_IB_MSG_TRX_RECOVERY_ROLLBACK_COMPLETED,	ER_IB_WRN_FAST_SHUTDOWN_REDO_DISABLED,	375
333	ER_IB_WRN_IGNORE_REDO_LOG_CAPACITY,	408
ER_IB_MSG_TRX_RECOVERY_ROLLBACK_NOT_COMPLETED,	ER_IB_WRN_OLD_GEOMETRY_TYPE,	386
376	ER_IB_WRN_PAGE_ARCH_FLUSH_DATA,	374
ER_IB_MSG_TRYING_TO_OPEN_FILE_FOR_LONG_TIME,	ER_IB_WRN_REDO_DISABLED,	375
395	ER_IB_WRN_REDO_ENABLED,	375
ER_IB_MSG_UNDO_ALTERED_ACTIVE,	ER_IB_WRONG_PAGEID_AFTER_SYNC_READ,	418
379	ER_IB_WRONG_PAGE_ID,	418
ER_IB_MSG_UNDO_ALTERED_INACTIVE,	ER_IDENTIFIED_BY_UNSUPPORTED,	118
379	ER_IDENT_CAUSES_TOO_LONG_PATH,	58
ER_IB_MSG_UNDO_ENCRYPTION_INFO_LOADED,	ER_IDENT_CAUSES_TOO_LONG_PATH_IN_UPGRADE,	366
392	ER_IF_NOT_EXISTS_UNSUPPORTED_TRG_EXISTS_ON_D	
ER_IB_MSG_UNDO_MARKED_ACTIVE,		
379		
ER_IB_MSG_UNDO_MARKED_EMPTY,		
379		
ER_IB_MSG_UNDO_MARKED_FOR_TRUNCATE,		
332		
ER_IB_MSG_UNDO_TRUNCATE_COMPLETE,		
332		
ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_CLONE,		
379		
ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_FAILURE,		
332		
ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_LOG_CREATE,		
332		
ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_MDL,		
379		
ER_IB_MSG_UNDO_TRUNCATE_FAIL_TO_READ_LOG_FILE,		
332		
ER_IB_MSG_UNDO_TRUNCATE_START,		
332		
ER_IB_MSG_UNDO_TRUNCATE_TOO_OFTEN,		
374		
ER_IB_MSG_UNEXPECTED_FILE_EXISTS,		
277		
ER_IB_MSG_UNPROTECTED_LOCATION_ALLOWED,		
281		
ER_IB_MSG_UPGRADE_PARTITION_FILE,		
369		

ER_IF_NOT_EXISTS_UNSUPPORTED_UDF_NATIVE_FUNC_IN_EXPRESSION, 122	ER_INNODB_CANNOT_CREATE_TABLE, 201
ER_ILLEGAL_GRANT_FOR_TABLE, 13	ER_INNODB_CANNOT_FIND_INDEX_IN_INNODB_DD, 189
ER_ILLEGAL_HA, 5	ER_INNODB_CLOSING_CONNECTION_ROLLS_BACK, 189
ER_ILLEGAL_HA_CREATE_OPTION, 34	ER_INNODB_CLUSTERED_INDEX_PRIVATE, 189
ER_ILLEGAL_PRIVILEGE_LEVEL, 84	ER_INNODB_COMPRESSION_FAILURE, 116
ER_ILLEGAL_REFERENCE, 19	ER_INNODB_DIFF_IN_REF_LEN, 201
ER_ILLEGAL_USER_VAR, 65	ER_INNODB_DIRTY_WATER_MARK_NOT_LOW, 188
ER_ILLEGAL_VALUE_FOR_TYPE, 27	ER_INNODB_ERROR_LOGGER_FATAL_MSG, 203
ER_IMPLICIT_COMPARISON_FOR_JSON, 112	ER_INNODB_ERROR_LOGGER_MSG, 203
ER_IMPOSSIBLE_STRING_CONVERSION, 112	ER_INNODB_FAILED_TO_FIND_IDX, 201
ER_IMP_INCOMPATIBLE_CFG_VERSION, 109	ER_INNODB_FAILED_TO_FIND_IDX_FROM_DICT_CACHE, 201
ER_IMP_INCOMPATIBLE_DD_VERSION, 84	ER_INNODB_FAILED_TO_FIND_IDX_WITH_KEY_NO, 201
ER_IMP_INCOMPATIBLE_MYSQLD_VERSION, 84	ER_INNODB_FILES_SAME, 189
ER_IMP_INCOMPATIBLE_SDI_VERSION, 84	ER_INNODB_FORCED_RECOVERY, 59
ER_IMP_NO_FILES_MATCHED, 83	ER_INNODB_FT_AUX_NOT_HEX_ID, 59
ER_IMP_SCHEMA_DOES_NOT_EXIST, 83	ER_INNODB_FT_LIMIT, 53
ER_IMP_TABLE_ALREADY_EXISTS, 84	ER_INNODB_FT_WRONG_DOCID_COLUMN, 54
ER_INCOMPATIBLE_TYPE_AGG, 136	ER_INNODB_FT_WRONG_DOCID_INDEX, 54
ER_INCONSISTENT_ERROR, 340	ER_INNODB_IDX_CNT_FEWER_THAN_DEFINED_IN_MYSQL, 202
ER_INCONSISTENT_PARTITION_INFO_ERROR, 34	ER_INNODB_IDX_CNT_MORE_THAN_DEFINED_IN_MYSQL, 201
ER_INCONSISTENT_TYPE_OF_FUNCTIONS_ERROR, 35	ER_INNODB_IDX_COLUMN_CNT_DIFF, 202
ER_INCORRECT_CURRENT_PASSWORD, 104	ER_INNODB_ILLEGAL_COLON_IN_POOL, 188
ER_INCORRECT_GLOBAL_LOCAL_VAR, 19	ER_INNODB_IMPORT_DROP_COL_METADATA_MISMATCH, 128
ER_INCORRECT_TYPE, 65	ER_INNODB_IMPORT_ENUM_NULL_TERMINATOR_MISSING, 128
ER_INDEX_COLUMN_TOO_LONG, 47	ER_INNODB_IMPORT_ERROR, 55
ER_INDEX_CORRUPT, 47	ER_INNODB_IMPORT_WRONG_DROPPED_ENUM_LENGTH, 128
ER_INDEX_OTHER_THAN_PK, 124	ER_INNODB_IMPORT_WRONG_NUMBER_OF_INDEXES_TOO_MANY_INITIALIZE, 128
ER_INDEX_TYPE_NOT_SUPPORTED_FOR_SPATIAL_INDEX, 92	ER_INNODB_IMPORT_WRONG_NUMBER_OF_INDEXES_ZERO_INITIALIZE, 128
ER_INFORMATION_SCHEMA_VERSION_CHANGE, 414	ER_INNODB_INCOMPATIBLE_WITH_TABLESPACE, 115
ER_INIT_BOOTSTRAP_COMPLETE, 168	ER_INNODB_INDEX_COLUMN_INFO_UNLIKE_MYSQLS, 189
ER_INIT_CANT_OPEN_BOOTSTRAP_FILE, 168	ER_INNODB_INDEX_CORRUPT, 55
ER_INIT_CREATING_DD, 169	ER_INNODB_INSTANT_ADD_DROP_NOT_SUPPORTED_MAX_SIZE, 126
ER_INIT_DATADIR_EXISTS_AND_NOT_WRITABLE_WONT_INITIALIZE, 168	ER_INNODB_INSTANT_ADD_NOT_SUPPORTED_MAX_FIELDS, 126
ER_INIT_DATADIR_EXISTS_AND_PATH_TOO_LONG_WONT_INITIALIZE, 168	ER_INNODB_INTERNAL_INDEX, 201
ER_INIT_DATADIR_EXISTS_WONT_INITIALIZE, 168	ER_INNODB_INVALID_AUTOEXTEND_SIZE_VALUE, 115
ER_INIT_DATADIR_NOT_EMPTY_WONT_INITIALIZE, 168	
ER_INIT_FAILED_TO_GENERATE_ROOT_PASSWORD, 368	
ER_INIT_GENERATING_TEMP_PASSWORD_FOR_ROOT, 168	
ER_INIT_ROOT_WITHOUT_PASSWORD, 168	
ER_INNODB_ACTIVE_INDEX_CHANGE_FAILED, 201	
ER_INNODB_AUTOEXTEND_SIZE_OUT_OF_RANGE, 115	

ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY, 188	ER_INNODB_USE_MONITOR_GROUP_NAME, 202
ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY_LOCATION, 351	ER_INSECURE_CHANGE_SOURCE, 51
ER_INNODB_INVALID_LOG_GROUP_HOME_DIR, 188	ER_INSECURE_PLAIN_TEXT, 51
ER_INNODB_INVALID_MONITOR_COUNTER_NAME, 202	ER_INSERT_INFO, 9
ER_INNODB_INVALID_PAGE_SIZE, 188	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG, 46
ER_INNODB_IO_CAPACITY_EXCEEDS_MAX, 188	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG, 45
ER_INNODB_IO_WRITE_ERROR_RETRYING, 381	ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_SQL_LO, 46
ER_INNODB_IO_WRITE_FAILED, 381	ER_INSTALL_COMPONENT_SET_NULL_VALUE, 126
ER_INNODB_MANDATORY, 142	ER_INSTALL_COMPONENT_SET_UNUSED_VALUE, 126
ER_INNODB_MAX_ROW_VERSION, 121	ER_INSTALL_PLUGIN_CONFLICT_CLIENT, 117
ER_INNODB_MONITOR_DEFAULT_VALUE_NOT_DEFINED, 202	ER_INSTALL_PLUGIN_CONFLICT_LOG, 389
ER_INNODB_MONITOR_IS_ENABLED, 202	ER_INTERNAL_ERROR, 55
ER_INNODB_NO_FT_TEMP_TABLE, 53	ER_INTERSECT_ALL_MAX_DUPLICATES_EXCEEDED, 123
ER_INNODB_ONLINE_LOG_TOO_BIG, 54	ER_INVALID_ADMIN_ADDRESS, 353
ER_INNODB_OUT_OF_RESOURCES, 370	ER_INVALID_ARGUMENT_FOR_LOGARITHM, 61
ER_INNODB_PK_NOT_IN_MYSQL, 189	ER_INVALID_ASSIGNMENT_TARGET, 117
ER_INNODB_PK_ONLY_IN_MYSQL, 189	ER_INVALID_AUTHENTICATION_POLICY, 392
ER_INNODB_READ_ONLY, 59	ER_INVALID_BITWISE_AGGREGATE_OPERANDS_SIZE, 77
ER_INNODB_REDO_ARCHIVING_ENABLED, 112	ER_INVALID_BITWISE_OPERANDS_SIZE, 77
ER_INNODB_REDO_DISABLED, 112	ER_INVALID_CAST, 113
ER_INNODB_REDO_LOG_ARCHIVE_ACTIVE, 101	ER_INVALID_CAST_POLYGON_RING_DIRECTION, 116
ER_INNODB_REDO_LOG_ARCHIVE_DIRS_INVALID, 101	ER_INVALID_CAST_TO_GEOMETRY, 116
ER_INNODB_REDO_LOG_ARCHIVE_DIR_CLASH, 101	ER_INVALID_CAST_TO_JSON, 71
ER_INNODB_REDO_LOG_ARCHIVE_DIR_EMPTY, 101	ER_INVALID_CHARACTER_STRING, 23
ER_INNODB_REDO_LOG_ARCHIVE_DIR_PERMISSIONS, 101	ER_INVALID_CHARSET_AND_DEFAULT_IS_MB, 161
ER_INNODB_REDO_LOG_ARCHIVE_FAILED, 101	ER_INVALID_COLLATION_FOR_CHARSET, 193
ER_INNODB_REDO_LOG_ARCHIVE_FILE_CREATE, 101	ER_INVALID_DD_OBJECT, 76
ER_INNODB_REDO_LOG_ARCHIVE_INACTIVE, 101	ER_INVALID_DD_OBJECT_ID, 76
ER_INNODB_REDO_LOG_ARCHIVE_LABEL_NOT_FOUND, 101	ER_INVALID_DD_OBJECT_NAME, 76
ER_INNODB_REDO_LOG_ARCHIVE_NO_SUCH_DIR, 101	ER_INVALID_DEFAULT, 8
ER_INNODB_REDO_LOG_ARCHIVE_SESSION, 101	ER_INVALID_DEFAULT_UTF8MB4_COLLATION, 91
ER_INNODB_REDO_LOG_ARCHIVE_START_SUBDIR_PATH, 101	ER_INVALID_ENCRYPTION_OPTION, 74
ER_INNODB_REDO_LOG_ARCHIVE_START_TIMEOUT, 101	ER_INVALID_ENCRYPTION_REQUEST, 100
ER_INNODB_TRX_XLATION_TABLE_OOM, 189	ER_INVALID_ERROR_LOG_NAME, 150
ER_INNODB_UNABLE_TO_ACQUIRE_DD_OBJECT, 374	ER_INVALID_FIELD_SIZE, 61
ER_INNODB_UNDO_LOG_FULL, 61	ER_INVALID_FILE_FORMAT, 427
ER_INNODB_UNKNOWN_COLLATION, 188	ER_INVALID_GEOJSON CRS_NOT_TOP_LEVEL, 88
ER_INNODB_UNREGISTERED_TRX_ACTIVE, 189	ER_INVALID_GEOJSON_MISSING_MEMBER, 65
	ER_INVALID_GEOJSON_UNSPECIFIED, 65
	ER_INVALID_GEOJSON_WRONG_TYPE, 65
	ER_INVALID_GROUP_FUNC_USE, 11
	ER_INVALID_INFO_IN_FRM, 161
	ER_INVALID_INSTRUMENT, 142
	ER_INVALID_JSON_ATTRIBUTE, 111

ER_INVALID_JSON_BINARY_DATA, 71
ER_INVALID_JSON_CHARSET, 71
ER_INVALID_JSON_CHARSET_IN_FUNCTION, 71
ER_INVALID_JSON_DATA, 65
ER_INVALID_JSON_PATH, 71
ER_INVALID_JSON_PATH_ARRAY_CELL, 73
ER_INVALID_JSON_PATH_CHARSET, 71
ER_INVALID_JSON_PATH_WILDCARD, 71
ER_INVALID_JSON_TEXT, 71
ER_INVALID_JSON_TEXT_IN_PARAM, 71
ER_INVALID_JSON_TYPE, 102
ER_INVALID_JSON_VALUE_FOR_CAST, 72
ER_INVALID_JSON_VALUE_FOR_FUNC_INDEX,
105
ER_INVALID_MFA_OPERATIONS_FOR_PASSWORDLESS_LOGIN,
118
ER_INVALID_MFA_PLUGIN_SPECIFIED, 118
ER_INVALID_MULTIPLE_CLAUSES, 100
ER_INVALID_NAMED_PIPE_FULL_ACCESS_GROUP,
358
ER_INVALID_NO_OF_ARGS, 83
ER_INVALID_ON_UPDATE, 22
ER_INVALID_OPTION_CHARACTERS, 80
ER_INVALID_OPTION_END_CHARACTER, 80
ER_INVALID_OPTION_KEY, 80
ER_INVALID_OPTION_KEY_VALUE_PAIR, 80
ER_INVALID_OPTION_START_CHARACTER, 80
ER_INVALID_OPTION_VALUE, 80
ER_INVALID_OR_OLD_TABLE_OR_DB_NAME, 170
ER_INVALID_PARAMETER_USE, 113
ER_INVALID_PLUGIN_FOR_REGISTRATION, 118
ER_INVALID_PROPERTY_KEY, 355
ER_INVALID_RPL_WILD_TABLE_FILTER_PATTERN,
65
ER_INVALID_SERVER_DOWNGRADE_NOT_PATCH,
414
ER_INVALID_SERVER_UPGRADE_NOT_LTS, 414
ER_INVALID_THREAD_ID, 87
ER_INVALID_THREAD_PRIORITY, 87
ER_INVALID_TIME_ZONE_INTERVAL, 113
ER_INVALID_TLS_VERSION, 395
ER_INVALID_TYPE_FOR_JSON, 71
ER_INVALID_USER_ATTRIBUTE_JSON, 111
ER_INVALID_USER_FOR_REGISTRATION, 118
ER_INVALID_USE_OF_FORCE_OPTION, 87
ER_INVALID_USE_OF_NULL, 13
ER_INVALID_VALUE_FOR_ENFORCE_GTID_CONSISTENCY,
139
ER_INVALID_VALUE_OF_BIND_ADDRESSES, 346
ER_INVALID_VCPU_ID, 86
ER_INVALID_VCPU_RANGE, 87
ER_INVALID_XPLUGIN_SOCKET_SAME_AS_SERVER,
374
ER_INVALID_YEAR_COLUMN_LENGTH, 55
ER_IO_ERR_LOG_INDEX_READ, 27
ER_IO_READ_ERROR, 54
ER_IO_WRITE_ERROR, 55
ER_IPSOCK_ERROR, 8
ER_IS_QUERY_INVALID_CLAUSE, 79
ER_I_S_SKIPPED_TABLESPACE, 86
ER_JSON_BAD_ONE_OR_ALL_ARG, 72
ER_JSON_DOCUMENT_NULL_KEY, 72
ER_JSON_DOCUMENT_TOO_DEEP, 72
ER_JSON_KEY_TOO_BIG, 72
ER_JSON_PARSE_ERROR, 151
ER_JSON_SCHEMA_VALIDATION_ERROR_WITH_DETAILED_F
108
ER_JSON_USED_AS_KEY, 72
ER_JSON_VACUOUS_PATH, 72
ER_JSON_VALUE_OUT_OF_RANGE_FOR_FUNC_INDEX,
105
ER_JSON_VALUE_TOO_BIG, 72
ER_JT_MAX_NESTED_PATH, 88
ER_JT_VALUE_OUT_OF_RANGE, 88
ER_KERBEROS_CREATE_USER, 117
ER_KEYCACHE_OOM, 144
ER_KEYRING_ACCESS_DENIED_ERROR, 75
ER_KEYRING_AWS_CMK_ID_NOT_SET, 227
ER_KEYRING_AWS_FAILED_TO_ACCESS_DATA_FILE,
227
ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_FROM_CONF
226
ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_ID_FROM_CO
226
ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYR
227
ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEYR
227
ER_KEYRING_AWS_FAILED_TO_CONNECT_KMS,
228
ER_KEYRING_AWS_FAILED_TO_DECRYPT_KEY,
228
ER_KEYRING_AWS_FAILED_TO_ENCRYPT_KEY,
228
ER_KEYRING_AWS_FAILED_TO_FLUSH_KEYRING_TO_FILE,
228
ER_KEYRING_AWS_FAILED_TO_GENERATE_KEY_DUE_TO_IN
228
ER_KEYRING_AWS_FAILED_TO_GENERATE_NEW_KEY,
228
ER_KEYRING_AWS_FAILED_TO_GET_KMS_CREDENTIAL_FRO
227
ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_INTERNAL_ER
227
ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_PLUGIN_INTER
227
ER_KEYRING_AWS_FAILED_TO_OPEN_CONF_FILE,
226

ER_KEYRING_AWS_FAILED_TO_RESTORE_FROM_BACKUP_FILE,	228	ER_KEYRING_FAILED_TO_REMOVE_KEY_DUE_TO_EMPTY_KEYRING,	224
ER_KEYRING_AWS_FAILED_TO_RE_ENCRYPT_KEY,	228	ER_KEYRING_FAILED_TO_RESTORE_FROM_BACKUP_FILE,	223
ER_KEYRING_AWS_FAILED_TO_ROTATE_CMK,	228	ER_KEYRING_FAILED_TO_TRUNCATE_FILE,	223
ER_KEYRING_AWS_FAILED_TO_SET_CMK_ID,	226	ER_KEYRING_FILE_IO_ERROR,	223
ER_KEYRING_AWS_FAILED_TO_SET_REGION,	226	ER_KEYRING_FOUND_MALFORMED_BACKUP_FILE,	223
ER_KEYRING_AWS_FOUND_MALFORMED_BACKUP_FILE,	228	ER_KEYRING_INCORRECT_FILE,	223
ER_KEYRING_AWS_INCORRECT_FILE,	228	ER_KEYRING_INVALID_KEY_LENGTH,	222
ER_KEYRING_AWS_INCORRECT_PROXY,	366	ER_KEYRING_INVALID_KEY_TYPE,	222
ER_KEYRING_AWS_INCORRECT_REGION,	228	ER_KEYRING_KEY_FETCH_FAILED_DUE_TO_EMPTY_KEYRING,	224
ER_KEYRING_AWS_INIT_FAILURE,	227	ER_KEYRING_LOGGER_ERROR_MSG,	213
ER_KEYRING_AWS_INVALID_CONF_FILE_PATH,	227	ER_KEYRING_MIGRATE_FAILED,	339
ER_KEYRING_AWS_INVALID_DATA_FILE_PATH,	227	ER_KEYRING_MIGRATE_MEMORY_DEALLOCATION_FAILED,	426
ER_KEYRING_AWS_INVALID_KEY_LENGTH_FOR_CIPHER,	227	ER_KEYRING_MIGRATE_SKIPPED_KEY,	426
ER_KEYRING_AWS_UDF_AWS_KMS_ERROR,	75	ER_KEYRING_MIGRATION_EXTRA_OPTIONS,	259
ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_EMPTY_KEYRING,	223	ER_KEYRING_MIGRATION_FAILED,	204
ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_INVALID_KEY_ID,	223	ER_KEYRING_MIGRATION_FAILURE,	75
ER_KEYRING_COMPONENT_EXCEPTION,	384	ER_KEYRING_MIGRATION_STATUS,	75
ER_KEYRING_COMPONENT_KEYRING_FILE_DECRYPT_FAILED,	425	ER_KEYRING_MIGRATION_SUCCESSFUL,	204
ER_KEYRING_COMPONENT_KEYRING_FILE_INVALID_FORMAT,	425	ER_KEYRING_OCI_HTTP_REQUEST,	405
ER_KEYRING_COMPONENT_KEYRING_FILE_JSON_EXTENSION_FAILED,	425	ER_KEYRING_OCI_INVALID_JSON,	405
ER_KEYRING_COMPONENT_KEYRING_FILE_KEY_EXTENSION_FAILED,	425	ER_KEYRING_OCI_PARSE_JSON,	405
ER_KEYRING_COMPONENT_KEYRING_FILE_NAME_EMPTY,	425	ER_KEYRING_OKV_CONNECTION_TO_SERVER_FAILED,	225
ER_KEYRING_COMPONENT_KEYRING_FILE_READ_FAILED,	425	ER_KEYRING_OKV_FAILED_TO_ACTIVATE_KEYS,	225
ER_KEYRING_COMPONENT_MEMORY_ALLOCATION_ERROR,	384	ER_KEYRING_OKV_FAILED_TO_ADD_ATTRIBUTE,	225
ER_KEYRING_COMPONENT_NOT_INITIALIZED,	384	ER_KEYRING_OKV_FAILED_TO_FETCH_KEY,	225
ER_KEYRING_FAILED_TO_FLUSH_KEYRING_TO_FILE,	223	ER_KEYRING_OKV_FAILED_TO_FIND_SERVER_ENTRY,	225
ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING,	224	ER_KEYRING_OKV_FAILED_TO_FIND_STANDBY_SERVER,	225
ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING_BACKUP,	224	ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY,	225
ER_KEYRING_FAILED_TO_GET_FILE_STAT,	223	ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY_DUE_TO_ERROR,	225
ER_KEYRING_FAILED_TO_LOAD_KEYRING_CONTENT,	223	ER_KEYRING_OKV_FAILED_TO_INIT_CLIENT,	225
ER_KEYRING_FAILED_TO_REMOVE_FILE,	223	ER_KEYRING_OKV_FAILED_TO_INIT_SSL_LAYER,	225
		ER_KEYRING_OKV_FAILED_TO_LOAD_KEY_UID,	225
		ER_KEYRING_OKV_FAILED_TO_LOAD_SSL_TRUST_STORE,	226
		ER_KEYRING_OKV_FAILED_TO_PARSE_CONF_FILE,	225
		ER_KEYRING_OKV_FAILED_TO_REMOVE_KEY,	225
		ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY,	226

ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY_SIGNATURE,	226	ER_LANGUAGE_COMPONENT_SET_SYSTEM_VARIABLE,	135
ER_KEYRING_OKV_FAILED_TO_SET_CERTIFICATE_FILE,	226	ER_LANGUAGE_COMPONENT_TIMEZONE,	135
ER_KEYRING_OKV_FAILED_TO_SET_KEY_FILE,	226	ER_LANGUAGE_COMPONENT_UNSUPPORTED_LANGUAGE,	127
ER_KEYRING_OKV_FAILED_TO_STORE_KEY,	225	ER_LANGUAGE_COMPONENT_UNSUPPORTED_TYPE,	135
ER_KEYRING_OKV_FAILED_TO_STORE_OR_GENERATE_KEY,	225	ER_LANGUAGE_COMPONENT_VM_API_FUNCTION_ERROR,	424
ER_KEYRING_OKV_INCORRECT_KEY_VAULT_CONFIGURATION,	224	ER_LANGUAGE_COMPONENT_VM_INTERNAL_ERROR,	424
ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INCORRECT_CONFIG,	224	ER_LANGUAGE_COMPONENT_WARNING,	416
ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INTERNAL_ERROR,	224	ER_LATITUDE_OUT_OF_RANGE,	84
ER_KEYRING_OKV_INVALID_KEY_LENGTH_FOR_CIPHER,	224	ER_LDAP_AUTH_CERTIFICATE_NAME,	254
ER_KEYRING_OKV_INVALID_KEY_TYPE,	224	ER_LDAP_AUTH_COMMUNICATION_HOST_INFO,	256
ER_KEYRING_OKV_KEY_MISMATCH,	226	ER_LDAP_AUTH_CONNECTION_CREATOR_ENTER,	255
ER_KEYRING_OKV_STANDBY_SERVER_COUNT_EXCEEDED,	396	ER_LDAP_AUTH_CONNECTION_GET_LDAP_INFO_NULL,	256
ER_KEYRING_OPERATION_FAILED_DUE_TO_INTERNAL_ERROR,	223	ER_LDAP_AUTH_CONNECTION_POOL_INIT_FAILED,	255
ER_KEYRING_UDF_KEYRING_SERVICE_ERROR,	74	ER_LDAP_AUTH_CONNECTION_POOL_REINIT_ENTER,	257
ER_KEYRING_UNKNOWN_ERROR,	223	ER_LDAP_AUTH_CONNECTION_PUSHED_TO_POOL,	255
ER_KEY_COLUMN_DOES_NOT_EXIST,	8	ER_LDAP_AUTH_CONN_POOL_DEINITIALIZING,	253
ER_KEY_DOES_NOT_EXIST,	15	ER_LDAP_AUTH_CONN_POOL_INITIALIZING,	253
ER_KEY_NOT_FOUND,	5	ER_LDAP_AUTH_CONN_POOL_NOT_CREATED,	253
ER_KEY_PART_0,	28	ER_LDAP_AUTH_CREATE_CONNECTION_KEY,	256
ER_KEY_REF_DO_NOT_MATCH_TABLE_REF,	19	ER_LDAP_AUTH_CREATING_LDAP_CONNECTION,	255
ER_KILLED_THREADS_OF_PLUGIN,	169	ER_LDAP_AUTH_DEINIT_FAILED,	252
ER_KILLING_THREAD,	169	ER_LDAP_AUTH_DELETING_CONNECTION_KEY,	256
ER_KILL_DENIED_ERROR,	9	ER_LDAP_AUTH_DISTINGUISHED_NAME,	256
ER_LANGUAGE_COMPONENT,	127	ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_CONNECTION,	257
ER_LANGUAGE_COMPONENT_CANNOT_UNINSTALL,	127	ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT,	252
ER_LANGUAGE_COMPONENT_CONCURRENCY_LIMIT,	135	ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT_CREATE,	252
ER_LANGUAGE_COMPONENT_CONVERSION,	135	ER_LDAP_AUTH_FAILED_TO_CREATE_OR_GET_CONNECTION,	252
ER_LANGUAGE_COMPONENT_ERROR,	416	ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_NOT_READY_POOL,	254
ER_LANGUAGE_COMPONENT_INFO,	416	ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_POOL_IN_RECON,	254
ER_LANGUAGE_COMPONENT_INSTALL_ERROR,	424		
ER_LANGUAGE_COMPONENT_INTERNAL,	134		
ER_LANGUAGE_COMPONENT_INTERNAL_ERROR,	424		
ER_LANGUAGE_COMPONENT_KEYWORD,	135		
ER_LANGUAGE_COMPONENT_NOT_AVAILABLE,	127		
ER_LANGUAGE_COMPONENT_RUNTIME,	135		
ER_LANGUAGE_COMPONENT_SERVER_ERROR,	424		

ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNECTION, 257	ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION, 257
ER_LDAP_AUTH_FAILED_TO_GET_CONNECTION_AS_PENDING, 254	ER_LDAP_AUTH_POOL_REINITIALIZING, 253
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_DEINITIALIZED_STATE, 254	ER_LDAP_AUTH_RETURNING_CONNECTION_TO_POOL, 255
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_INITIALIZED_STATE, 254	ER_LDAP_AUTH_SASL_BIND_SUCCESS_INFO, 256
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_READY_STATE, 254	ER_LDAP_AUTH_SASL_PROCESS_SASL, 256
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_READY_STATE, 254	ER_LDAP_AUTH_SASL_REQUEST_FROM_CLIENT, 256
ER_LDAP_AUTH_FAILED_TO_POOL_DEINIT, 254	ER_LDAP_AUTH_SEARCHED_USER_GRP_NAME, 254
ER_LDAP_AUTH_FAILED_TO_SEARCH_DN, 257	ER_LDAP_AUTH_SEARCH_USER_GROUP_ATTR_NOT_FOUND, 255
ER_LDAP_AUTH_FAILED_TO_WRITE_PACKET, 253	ER_LDAP_AUTH_SETTING_USERNAME, 253
ER_LDAP_AUTH_FREEING_CONNECTION, 255	ER_LDAP_AUTH_SKIPPING_USER_GROUP_SEARCH, 252
ER_LDAP_AUTH_GETTING_CONNECTION_FROM_POOL, 255	ER_LDAP_AUTH_STARTED_FOR_USER, 256
ER_LDAP_AUTH_GRP_DN_PARSING_FAILED, 356	ER_LDAP_AUTH_STARTING_TLS, 256
ER_LDAP_AUTH_GRP_INCORRECT_ATTRIBUTE, 356	ER_LDAP_AUTH_TLS_CONF, 252
ER_LDAP_AUTH_GRP_INFO_FOUND_IN_MANY_OBJECTS, 356	ER_LDAP_AUTH_TLS_CONNECTION, 252
ER_LDAP_AUTH_GRP_IS_FULL_DN, 253	ER_LDAP_AUTH_USER_AUTH_DATA, 253
ER_LDAP_AUTH_GRP_NULL_ATTRIBUTE_VALUE, 356	ER_LDAP_AUTH_USER_BIND_FAILED, 257
ER_LDAP_AUTH_GRP_OBJECT_HAS_USER_INFO, 356	ER_LDAP_AUTH_USER_FOUND_IN_MANY_GRPS, 254
ER_LDAP_AUTH_GRP_SEARCH_NOT_SPECIAL_HDL, 356	ER_LDAP_AUTH_USER_GROUP_SEARCH_FAILED, 257
ER_LDAP_AUTH_GRP_SEARCH_SPECIAL_HDL, 253	ER_LDAP_AUTH_USER_GROUP_SEARCH_INFO, 253
ER_LDAP_AUTH_GRP_USER_OBJECT_HAS_GROUP_INFO, 356	ER_LDAP_AUTH_USER_GROUP_SEARCH_ROOT_BIND, 349
ER_LDAP_AUTH_INFO_FOR_USER, 253	ER_LDAP_AUTH_USER_HAS_MULTIPLE_GRP_NAMES, 254
ER_LDAP_AUTH_INFO_USER_MAP, 427	ER_LDAP_AUTH_USER_NOT_FOUND_IN_ANY_GRP, 253
ER_LDAP_AUTH_INIT_FAILED, 256	ER_LDAP_AUTH_ZERO_MAX_POOL_SIZE_UNCHANGED, 253
ER_LDAP_AUTH_LDAPS, 356	ER_LDAP_EMPTY_USERDN_PASSWORD, 364
ER_LDAP_AUTH_LDAP_INFO_NULL, 255	ER_LDAP_MAPPING_CHECK_DELIMI_QUOTE, 357
ER_LDAP_AUTH_MAX_ALLOWED_CONNECTION_LIMIT, 255	ER_LDAP_MAPPING_EMPTY_MAPPING, 357
ER_LDAP_AUTH_MAX_POOL_SIZE_SET_FAILED, 255	ER_LDAP_MAPPING_GETTING_NEXT_MAPPING, 357
ER_LDAP_AUTH_METHOD_TO_CLIENT, 256	ER_LDAP_MAPPING_GET_USER_PROXY, 356
ER_LDAP_AUTH_OBJECT_CREATE_TIMESTAMP, 254	ER_LDAP_MAPPING_INFO, 357
ER_LDAP_AUTH_OR_GROUP_RETRIEVAL_FAILED, 257	ER_LDAP_MAPPING_IS_QUOTE, 358
ER_LDAP_AUTH_PLUGIN_FAILED_TO_READ_PACKET, 255	ER_LDAP_MAPPING_NON_DESIRED_STATE, 358
ER_LDAP_AUTH_POOLED_CONNECTION_KEY, 256	ER_LDAP_MAPPING_NO_SEPEARATOR_END_OF_GROUP, 357
ER_LDAP_AUTH_POOL_DISABLE_MAX_SIZE_ZERO, 252	ER_LDAP_MAPPING_PARSING_CURRENT_STATE, 357
	ER_LDAP_MAPPING_PARSING_ERROR, 358
	ER_LDAP_MAPPING_PARSING_MAPPING_INFO, 358
	ER_LDAP_MAPPING_PROCESS_DELIMITER, 357

ER_LDAP_MAPPING_PROCESS_DELIMITER_COMMA_NOT_FOUND, 357
 ER_LDAP_MAPPING_PROCESS_DELIMITER_EQUAL_NOT_FOUND, 357
 ER_LDAP_MAPPING_PROCESS_DELIMITER_TRY_COMMA, 357
 ER_LDAP_MAPPING_PROCESS_MAPPING, 357
 ER_LDAP_MAPPING_TRIMMING_SPACES, 358
 ER_LDAP_MAPPING_USER_DONT_BELONG_GROUP, 357
 ER_LH_AVRO_CANNOT_PARSE_HEADER, 134
 ER_LH_AVRO_DECODING_ERR, 133
 ER_LH_AVRO_ENUM_CANNOT_CONVERT_CHARSET, 132
 ER_LH_AVRO_ENUM_MISMATCH, 132
 ER_LH_AVRO_FILE_DATA_CORRUPT, 132
 ER_LH_AVRO_FILE_ENDS_UNEXPECTEDLY, 132
 ER_LH_AVRO_HEADER_METADATA_ERR, 133
 ER_LH_AVRO_HEADER_MISMATCH, 132
 ER_LH_AVRO_HEADER_NO_SCHEMA, 133
 ER_LH_AVRO_INVALID_BLOCK_RECORD_COUNT, 132
 ER_LH_AVRO_INVALID_BLOCK_SIZE, 132
 ER_LH_AVRO_INVALID_NAME_IN_SCHEMA, 133
 ER_LH_AVRO_INVALID_UNION, 132
 ER_LH_AVRO_NO_CODEC_IN_HEADER, 133
 ER_LH_AVRO_SCHEMA_DEPTH_EXCEEDS_MAX, 132
 ER_LH_AVRO_TYPE_CANNOT_CONVERT, 132
 ER_LH_AWS_AUTH_ERR, 131
 ER_LH_BAD_VALUE, 130
 ER_LH_CANNOT_CONVERT_STRING, 131
 ER_LH_CHARSET_UNSUPPORTED, 131
 ER_LH_COLUMN_MAX_ERR, 131
 ER_LH_COLUMN_MISMATCH_ERR, 131
 ER_LH_COL_IS_EMPTY, 130
 ER_LH_COL_IS_EMPTY_WARN, 130
 ER_LH_COL_NOT_NULLABLE, 130
 ER_LH_CSV_PARSING_ERR, 131
 ER_LH_DATETIME_FORMAT, 131
 ER_LH_DECIMAL_OOM_ERR, 130
 ER_LH_DECIMAL_PRECISION_EXCEEDS_SCHEMA, 130
 ER_LH_DECIMAL_UNKNOWN_ERR, 130
 ER_LH_DUPLICATE_FILE, 132
 ER_LH_EMPTY_FILE, 132
 ER_LH_EXCEEDS_MAX, 131
 ER_LH_EXCEEDS_MIN, 130
 ER_LH_FORMAT_HEADER_NO_MAGIC_BYTES, 133
 ER_LH_INFER_FILE_HAS_NO_DATA, 134
 ER_LH_INFER_JSON_INVALID_SCHEMA, 136
 ER_LH_INFER_NO_DATA, 134
 ER_LH_INFER_NO_FILES, 134
 ER_LH_INFER_SCHEMA_MISMATCH, 133
 ER_LH_INFER_WARN_GOT_EXCEPTION, 134
 ER_LH_INVALID_JSON_FILE_FORMAT_SCHEMA, 136
 ER_LH_JSON_FILE_FORMAT_WARN_INFER_SCHEMA, 136
 ER_LH_JSON_PARSING, 135
 ER_LH_NO_FILES_FOUND, 132
 ER_LH_OOM, 133
 ER_LH_OUT_OF_RANGE, 131
 ER_LH_PARQUET_CANNOT_LOCATE_OFFSET, 133
 ER_LH_PARQUET_CANNOT_LOCATE_SCHEMA, 133
 ER_LH_PARQUET_CANNOT_READ_HEADER, 134
 ER_LH_PARQUET_CANT_OPEN_FILE, 134
 ER_LH_PARQUET_DECIMAL_CONVERSION_ERR, 131
 ER_LH_PARQUET_NON_UTF8_FILE_ENC, 133
 ER_LH_PARQUET_ROW_GROUP_SIZE_EXCEEDS_MAX, 133
 ER_LH_PARQUET_SCHEMA_MISMATCH, 133
 ER_LH_PARQUET_TYPE_CANNOT_CONVERT, 133
 ER_LH_REAL_IS_NAN, 131
 ER_LH_RESOURCE_PRINCIPAL_BUCKET_ERR, 132
 ER_LH_RESOURCE_PRINCIPAL_ERR, 131
 ER_LH_STRING_TOO_LONG, 132
 ER_LH_TOO_LARGE_ROW_ERR, 134
 ER_LH_TOO_LARGE_VALUE_ERR, 134
 ER_LH_USER_DATA_ACCESS_FAILED, 136
 ER_LH_WARN_COL_MISSING_NOT_NULLABLE, 130
 ER_LH_WARN_DECIMAL_ROUNDING, 130
 ER_LH_WARN_EXCEEDS_MAX_TRUNCATING, 131
 ER_LH_WARN_EXCEEDS_MIN_TRUNCATING, 131
 ER_LH_WARN_INFER_SKIPPED_FILES, 134
 ER_LH_WARN_INFER_SKIPPED_LINES, 133
 ER_LH_WARN_INFER_USE_DEFAULT_COL_NAMES, 134
 ER_LH_WARN_TRUNCATED, 131
 ER_LIMITED_PART_RANGE, 36
 ER_LOAD_BULK_DATA_FAILED, 125
 ER_LOAD_BULK_DATA_UNSORTED, 124
 ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL, 126
 ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL_LOG, 408
 ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD, 125
 ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD_LOG, 408
 ER_LOAD_DATA_INFILE_FAILED_IN_UNEXPECTED_WAY, 152

ER_LOAD_FROM_FIXED_SIZE_ROWS_TO_VAR, 29
 ER_LOAD_INFO, 9
 ER_LOCAL_VARIABLE, 18
 ER_LOCKING_SERVICE_DEADLOCK, 70
 ER_LOCKING_SERVICE_TIMEOUT, 70
 ER_LOCKING_SERVICE_WRONG_NAME, 70
 ER_LOCK_ABORTED, 46
 ER_LOCK_DEADLOCK, 17
 ER_LOCK_NOWAIT, 81
 ER_LOCK_ORDER_DEPENDENCIES_SYNTAX, 364
 ER_LOCK_ORDER_FAILED_READ_FILE, 364
 ER_LOCK_ORDER_FAILED_WRITE_FILE, 364
 ER_LOCK_ORDER_INIT_FAILED, 363
 ER_LOCK_ORDER_MESSAGE, 364
 ER_LOCK_ORDER_SCANNER_SYNTAX, 364
 ER_LOCK_OR_ACTIVE_TRANSACTION, 16
 ER_LOCK_REFUSED_BY_ENGINE, 74
 ER_LOCK_TABLE_FULL, 17
 ER_LOCK_WAIT_TIMEOUT, 17
 ER_LOG_BIN_BETTER_WITH_NAME, 148
 ER_LOG_CANNOT_PURGE_BINLOG_WITH_BACKUP_LOCK, 413
 ER_LOG_CANNOT_WRITE, 137
 ER_LOG_CANNOT_WRITE_EXTENDED, 366
 ER_LOG_CLIENT_INTERACTION_TIMEOUT, 426
 ER_LOG_COMPONENT_CANNOT_INIT, 381
 ER_LOG_COMPONENT_FLUSH_FAILED, 389
 ER_LOG_DEPRECATED_NON_COMPOSABLE_MULTIPLE_ENGINES, 428
 ER_LOG_FILES_GIVEN_LOG_OUTPUT_IS_TABLE, 147
 ER_LOG_FILE_CANNOT_OPEN, 218
 ER_LOG_FILE_INVALID, 147
 ER_LOG_GENERAL_CANNOT_OPEN, 137
 ER_LOG_IN_USE, 28
 ER_LOG_OUTPUT_CONTRADICTION, 147
 ER_LOG_PARTITION_PREFIX_KEY_NOT_SUPPORTED, 427
 ER_LOG_PRINTF_MSG, 203
 ER_LOG_PRIV_CHECKS_REQUIRE_ROW_FORMAT_NOT_SUPPORTED, 369
 ER_LOG_PURGE_NO_FILE, 41
 ER_LOG_PURGE_UNKNOWN_ERR, 28
 ER_LOG_SANITIZATION, 427
 ER_LOG_SLOW_CANNOT_OPEN, 137
 ER_LOG_SYSLOG_CANNOT_OPEN, 137
 ER_LONGITUDE_OUT_OF_RANGE, 84
 ER_LOWER_CASE_TABLE_NAMES_CS_DD_ON_CI_FS_UNSUPPORTED, 148
 ER_LOWER_CASE_TABLE_NAMES_USING_0, 148
 ER_LOWER_CASE_TABLE_NAMES_USING_2, 148
 ER_MALFORMED_GTID_SET_ENCODING, 52
 ER_MALFORMED_GTID_SET_SPECIFICATION, 52
 ER_MALFORMED_GTID_SPECIFICATION, 52
 ER_MALFORMED_PACKET, 56
 ER_MANDATORY_ROLE, 85
 ER_MASTER_KEY_ROTATION_BINLOG_FAILED, 74
 ER_MASTER_KEY_ROTATION_NOT_SUPPORTED_BY_SE, 74
 ER_MASTER_KEY_ROTATION_SE_UNAVAILABLE, 74
 ER_MAXVALUE_IN_VALUES_IN, 44
 ER_MAX_PREPARED_STMT_COUNT_REACHED, 33
 ER_MDL_OUT_OF_RESOURCES, 112
 ER_MECAB_CHARSET_LOADED, 207
 ER_MECAB_CREATE_LATTICE_FAILED, 207
 ER_MECAB_CREATING_MODEL, 207
 ER_MECAB_FAILED_TO_CREATE_MODEL, 207
 ER_MECAB_FAILED_TO_CREATE_TRIGGER, 207
 ER_MECAB_NOT_SUPPORTED, 206
 ER_MECAB_NOT_VERIFIED, 206
 ER_MECAB_OOM_WHILE_PARSING_TEXT, 207
 ER_MECAB_PARSE_FAILED, 207
 ER_MECAB_UNSUPPORTED_CHARSET, 207
 ER_MESSAGE_AND_STATEMENT, 45
 ER_MFA_METHODS_IDENTICAL, 118
 ER_MFA_METHODS_INVALID_ORDER, 118
 ER_MFA_METHOD_EXISTS, 118
 ER_MFA_METHOD_NOT_EXISTS, 118
 ER_MFA_PLUGIN_NOT_LOADED, 395
 ER_MFA_USER_ATTRIBUTES_CORRUPT, 395
 ER_MICROSECOND_TIMER_IS_NOT_AVAILABLE, 201
 ER_MIGRATE_TABLE_TO_DD_OOM, 370
 ER_MISPLACED_INTO, 109
 ER_MISSING_ACL_SYSTEM_TABLE, 195
 ER_MISSING_CURRENT_PASSWORD, 104
 ER_MISSING_GRANT_SYSTEM_TABLE, 195
 ER_MISSING_HA_CREATE_OPTION, 61
 ER_MISSING_JSON_TABLE_VALUE, 87
 ER_MISSING_JSON_VALUE, 110
 ER_MISSING_KEY, 60
 ER_MISSING_SKIP_REPLICA, 21
 ER_MISSING_TABLESPACE_FILE, 85
 ER_MIXING_NOT_ALLOWED, 18
 ER_MIX_HANDLER_ERROR, 35
 ER_MIX_OF_GROUP_FUNC_AND_FIELDS, 13
 ER_MIX_OF_GROUP_FUNC_AND_FIELDS_V2, 66
 ER_MTA_CANT_PARALLEL, 51
 ER_MTA_UNSUPPORTED_SOURCE_CANT_RUN_WITH_GAPS, 54
 ER_MTA_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX, 58
 ER_MTA_FEATURE_IS_NOT_SUPPORTED, 50
 ER_MTA_INCONSISTENT_DATA, 51

ER_MTA_RECOVERY_FAILURE, 54	ER_NET_OK_PACKET_TOO_LARGE, 65
ER_MTA_RESET_WORKERS, 54	ER_NET_PACKETS_OUT_OF_ORDER, 14
ER_MTA_UPDATED_DBS_GREATER_MAX, 50	ER_NET_PACKET_TOO_LARGE, 13
ER_MTR_MSG_1, 390	ER_NET_READ_ERROR, 14
ER_MULTIPLE_CONSTRAINTS_WITH_SAME_NAME, 108	ER_NET_READ_ERROR_FROM_PIPE, 13
ER_MULTIPLE_DEF_CONST_IN_LIST_PART_ERROR, 35	ER_NET_READ_INTERRUPTED, 14
ER_MULTIPLE_INTO_CLAUSES, 109	ER_NET_UNCOMPRESS_ERROR, 14
ER_MULTIPLE_JSON_VALUES, 110	ER_NET_WAIT_ERROR, 362
ER_MULTIPLE_PRI_KEY, 8	ER_NET_WAIT_ERROR2, 386
ER_MULTI_UPDATE_KEY_CONFLICT, 47	ER_NET_WRITE_INTERRUPTED, 14
ER_MUST_CHANGE_PASSWORD, 55	ER_NEW_ABORTING_CONNECTION, 15
ER_MUST_CHANGE_PASSWORD_LOGIN, 58	ER_NO, 3
ER_MYINIT_FAILED, 146	ER_NONEXISTING_GRANT, 13
ER_MYISAM_CHECK_METHOD_ERROR, 202	ER_NONEXISTING_PROC_GRANT, 29
ER_MYISAM_CRASHED_ERROR, 202	ER_NONEXISTING_TABLE_GRANT, 13
ER_MYISAM_CRASHED_ERROR_IN, 153	ER_NONPOSITIVE_RADIUS, 90
ER_MYISAM_CRASHED_ERROR_IN_THREAD, 153	ER_NONUNIQU_TABLE, 8
ER_MYSQLBACKUP_CLIENT_MSG, 120	ER_NONUPDATEABLE_COLUMN, 26
ER_MYSQLBACKUP_MSG, 367	ER_NON_BOOLEAN_EXPR_FOR_CHECK_CONSTRAINT, 99
ER_MYSQL_NATIVE_PASSWORD_SECOND_PASSWORD_USED_INFORMATION, 353	ER_NON_DEFAULT_VALUE_FOR_GENERATED_COLUMN, 108
ER_MY_MALLOC_GETPROCADDRESS_FAILED, 397	ER_NON_GROUPING_FIELD_USED, 33
ER_MY_MALLOC_LOADLIBRARY_FAILED, 397	ER_NON_INSERTABLE_TABLE, 33
ER_MY_MALLOC_USING_JEMALLOC, 396	ER_NON_RO_SELECT_DISABLE_TIMER, 62
ER_MY_MALLOC_USING_STD_MALLOC, 397	ER_NON_SCALAR_USED_AS_KEY, 136
ER_MY_NET_WRITE_FAILED_FALLING_BACK_ON_STDERR, 180	ER_NON_UNIQ_ERROR, 6
ER_M_BIGGER_THAN_D, 30	ER_NON_UPDATABLE_TABLE, 22
ER_NAME_BECOMES_EMPTY, 33	ER_NORMAL_SERVER_SHUTDOWN, 339
ER_NANOSECOND_TIMER_IS_NOT_AVAILABLE, 200	ER_NOTE_COMPONENT_KEYRING_OCI_MISSING_NAME_OR_SLOT, 404
ER_NATIVE_FCT_NAME_COLLISION, 40	ER_NOTE_COMPONENT_SLOT_DEREGISTRATION_SUCCESS, 410
ER_NDBINFO_NOT_UPGRADING_SCHEMA, 373	ER_NOTE_COMPONENT_SLOT_REGISTRATION_SUCCESS, 410
ER_NDBINFO_UPGRADING_SCHEMA, 373	ER_NOTE_KEYRING_COMPONENT_AES_DATA_IDENTIFIER_ERROR, 385
ER_NDBINFO_UPGRADING_SCHEMA_FAIL, 373	ER_NOTE_KEYRING_COMPONENT_AES_INVALID_KEY, 385
ER_NDB_LOG_ENTRY, 188	ER_NOTE_KEYRING_COMPONENT_AES_INVALID_MODE_BLOCK, 384
ER_NDB_LOG_ENTRY_WITH_PREFIX, 188	ER_NOTE_KEYRING_COMPONENT_AES_OPERATION_ERROR, 385
ER_NDB_REPLICATION_SCHEMA_ERROR, 42	ER_NOTE_KEYRING_COMPONENT_EMPTY_DATA_ID, 425
ER_NEED_FILE_INSTEAD_OF_DIR, 148	ER_NOTE_KEYRING_COMPONENT_GENERATE_FAILED, 385
ER_NEED_LOG_BIN, 148	ER_NOTE_KEYRING_COMPONENT_INITIALIZED, 385
ER_NEED_REPREPARE, 41	ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ITERATION_CARD_ADDRESS, 385
ER_NETWORK_NAMESPACES_NOT_SUPPORTED, 361	ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ITERATION_CARD_ADDRESS, 385
ER_NETWORK_NAMESPACE_FILE_PATH_TOO_LONG, 362	ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ITERATION_CARD_ADDRESS, 385
ER_NETWORK_NAMESPACE_NOT_ALLOWED_FOR_WRITE, 361	ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ITERATION_CARD_ADDRESS, 385
ER_NETWORK_READ_EVENT_CHECKSUM_FAILURE, 340	ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ITERATION_CARD_ADDRESS, 385
ER_NET_ERROR_ON_WRITE, 14	ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ITERATION_CARD_ADDRESS, 385
ER_NET_FCNTL_ERROR, 14	ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ITERATION_CARD_ADDRESS, 385

ER_NOTE_KEYRING_COMPONENT_KEY_READ_ITERATION_NOT_REFERENCED_ROW_2, 32	426	ER_NO_SECURE_TRANSPORTS_CONFIGURED,
ER_NOTE_KEYRING_COMPONENT_KEY_READ_ITERATION_INIT_FAILED,	425	ER_NO_SESSION_TEMP, 104
ER_NOTE_KEYRING_COMPONENT_METADATA_ITERATION_NO_SUCH_INDEX, 8	385	ER_NO_SUCH_INDEX, 8
ER_NOTE_KEYRING_COMPONENT_NOT_INITIALIZED,	425	ER_NO_SUCH_TABLE, 13
ER_NOTE_KEYRING_COMPONENT_READ_DATA_NOT_FOUND,	385	ER_NO_SUCH_THREAD, 9
ER_NOTE_KEYRING_COMPONENT_REMOVE_FAILED,	385	ER_NO_SUCH_USER, 32
ER_NOTE_KEYRING_COMPONENT_STORE_FAILED,	385	ER_NO_SUPER_WITHOUT_USER_PLUGIN, 159
ER_NOTE_KEYRING_COMPONENT_WRITE_MAXIMUM_DATA_LENGTH,	385	ER_NO_SYSTEM_SCHEMA_ACCESS, 79
ER_NOT_ALLOWED_COMMAND, 13		ER_NO_SYSTEM_TABLESPACE_ACCESS, 79
ER_NOT_ALLOWED_WITH_START_TRANSACTION,	111	ER_NO_SYSTEM_TABLE_ACCESS, 80
ER_NOT_FORM_FILE, 5		ER_NO_SYSTEM_TABLE_ACCESS_FOR_DICTIONARY_TABLE,
ER_NOT_HINT_UPDATABLE_VARIABLE, 85		ER_NO_SYSTEM_TABLE_ACCESS_FOR_SYSTEM_TABLE,
ER_NOT_IMPLEMENTED_FOR_CARTESIAN_SRS,	90	80
ER_NOT_IMPLEMENTED_FOR_GEOGRAPHIC_SRS,	84	ER_NO_SYSTEM_TABLE_ACCESS_FOR_TABLE,
ER_NOT_IMPLEMENTED_FOR_PROJECTED_SRS,	90	80
ER_NOT_IMPLEMENTED_GET_TABLESPACE_STATISTICS,	218	ER_NO_SYSTEM_VIEW_ACCESS, 84
ER_NOT_KEYFILE, 5		ER_NO_TABLES_USED, 10
ER_NOT_RIGHT_NOW, 146		ER_NO_THD_NO_UUID, 141
ER_NOT_SUPPORTED_AUTH_MODE, 20		ER_NO_TRIGGERS_ON_SYSTEM_SCHEMA, 33
ER_NOT_SUPPORTED_YET, 19		ER_NO_UNIQUE_LOGFILE, 10
ER_NOT_VALID_PASSWORD, 55		ER_NPIPE_CANT_CREATE, 190
ER_NO_ACCESS_TO_NATIVE_FCT, 80		ER_NPIPE_FAILED_TO_INIT_SECURITY_DESCRIPTOR,
ER_NO_BINARY_LOGGING, 28		164
ER_NO_BINLOG_ERROR, 36		ER_NPIPE_FAILED_TO_SET_SECURITY_DESCRIPTOR,
ER_NO_CSV_NO_LOG_TABLES, 147		164
ER_NO_DB_ERROR, 6		ER_NPIPE_PIPE_ALREADY_IN_USE, 164
ER_NO_DEFAULT, 18		ER_NULL_CANT_BE_PERSISTED_FOR_READONLY,
ER_NO_DEFAULT_FOR_FIELD, 27		127
ER_NO_DEFAULT_FOR_VIEW_FIELD, 30		ER_NULL_COLUMN_IN_INDEX, 11
ER_NO_ERROR_LOG_PARSER_CONFIGURED,	380	ER_NULL_IN_VALUES_LESS_THAN, 39
ER_NO_FORMAT_DESCRIPTION_EVENT_BEFORE_BINLOG_STATEMENT,	41	ER_NUMERIC_JSON_VALUE_OUT_OF_RANGE, 72
ER_NO_FT_MATERIALIZED_SUBQUERY, 61		ER_NUM_THREADS_STILL_ALIVE, 417
ER_NO_PARTITION_FOR_GIVEN_VALUE, 37		ER_OBSOLETE_FILE_PRIVILEGE_FOR_REPLICATION_CHANNELS,
ER_NO_PARTITION_FOR_GIVEN_VALUE_SILENT,	40	368
ER_NO_PARTS_ERROR, 35		ER_OBSOLETE_REQUIRE_ROW_FORMAT_VIOLATION,
ER_NO_PATH_FOR_SHARED_LIBRARY, 345		369
ER_NO_PERMISSION_TO_CREATE_USER, 17		ER_OLD_FILE_FORMAT, 32
ER_NO_REFERENCED_ROW, 17		ER_OLD_KEYFILE, 5
		ER_OLD_TEMPORALS_UPGRADED, 59
		ER_ONLY_FD_AND_RBR_EVENTS_ALLOWED_IN_BINLOG,
		49
		ER_ONLY_IMPLEMENTED_FOR_SRID_0_AND_4326,
		89
		ER_ONLY INTEGERS ALLOWED, 39
		ER_ONLY_ON_RANGE_LIST_PARTITION, 36
		ER_OOM, 146
		ER_OOM_SAVE_GTIDS, 340
		ER_OPEN_AS_READONLY, 5
		ER_OPEN_ROLE_TABLES, 78
		ER_OPERAND_COLUMNS, 19

ER_OPERATION_NOT_ALLOWED_ON_GR_SECONDARY 117
 ER_OPERATION_NOT_ALLOWED_WHILE_PRIMARY_CHANGE 121
 ER_OPTION_PREVENTS_STATEMENT, 22
 ER_OPT_WRONG_TREE, 137
 ER_OUTOFMEMORY, 5
 ER_OUT_OF_RESOURCES, 5
 ER_OUT_OF_SORTMEMORY, 5
 ER_PAGE_TRACKING_CANNOT_PURGE, 98
 ER_PAGE_TRACKING_NOT_STARTED, 98
 ER_PAGE_TRACKING_RANGE_NOT_TRACKED, 98
 ER_PARSER_TRACE, 137
 ER_PARSE_ERROR, 7
 ER_PARSE_ERROR_IN_DIGEST_FN, 88
 ER_PARSING_VIEW, 141
 ER_PARTIAL_REVOKES_EXIST, 105
 ER_PARTIAL_REVOKE_AND_DB_GRANT_BOTH_EXISTS, 105
 ER_PARTITIONS_MUST_BE_DEFINED_ERROR, 34
 ER_PARTITION_CLAUSE_ON_NONPARTITIONED, 50
 ER_PARTITION_COLUMN_LIST_ERROR, 43
 ER_PARTITION_CONST_DOMAIN_ERROR, 38
 ER_PARTITION_ENTRY_ERROR, 35
 ER_PARTITION_EXCHANGE_DIFFERENT_OPTION, 49
 ER_PARTITION_EXCHANGE_FOREIGN_KEY, 50
 ER_PARTITION_EXCHANGE_PART_TABLE, 49
 ER_PARTITION_EXCHANGE_TEMP_TABLE, 49
 ER_PARTITION_FIELDS_TOO_LONG, 44
 ER_PARTITION_FUNCTION_FAILURE, 36
 ER_PARTITION_FUNCTION_IS_NOT_ALLOWED, 38
 ER_PARTITION_FUNC_NOT_ALLOWED_ERROR, 34
 ER_PARTITION_HANDLER_ADMIN_MSG, 202
 ER_PARTITION_INSTEAD_OF_SUBPARTITION, 49
 ER_PARTITION_MAXVALUE_ERROR, 34
 ER_PARTITION_MERGE_ERROR, 39
 ER_PARTITION_MGMT_ON_NONPARTITIONED, 35
 ER_PARTITION_MOVE_CREATED_DUPLICATE_ROW_P 190
 ER_PARTITION_NAME, 42
 ER_PARTITION_NOT_DEFINED_ERROR, 35
 ER_PARTITION_NO_TEMPORARY, 38
 ER_PARTITION_PREFIX_KEY_NOT_SUPPORTED, 135
 ER_PARTITION_REQUIRES_VALUES_ERROR, 34
 ER_PARTITION_WRONG_NO_PART_ERROR, 34
 ER_PARTITION_WRONG_NO_SUBPART_ERROR, 34
 ER_PARTITION_WRONG_VALUES_ERROR, 34
 ER_PART_EXPR_TOO_LONG, 84
 ER_PASSWORD_ANONYMOUS_USER, 12
 ER_PASSWORD_CANNOT_BE_RETAINED_ON_PLUGIN_CHAN 105
 ER_PASSWORD_EXPIRE_ANONYMOUS_USER, 61
 ER_PASSWORD_FORMAT, 56
 ER_PASSWORD_NOT_ALLOWED, 12
 ER_PASSWORD_NO_MATCH, 12
 ER_PATH_IN_DATADIR, 85
 ER_PATH_LENGTH, 45
 ER_PERFORMANCE_SCHEMA_VERSION_CHANGE, 414
 ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_BOOT 193
 ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_SHUT 193
 ER_PERFSCHEMA_INIT_FAILED, 148
 ER_PERFSCHEMA_TABLES_INIT_FAILED, 194
 ER_PERSISTED_VARIABLES_DECRYPTION_FAILED, 396
 ER_PERSISTED_VARIABLES_ENCRYPTION_FAILED, 396
 ER_PERSISTED_VARIABLES_KEYRING_SUPPORT_REQUIRED 396
 ER_PERSISTED_VARIABLES_LACK_KEYRING_SUPPORT, 396
 ER_PERSISTED_VARIABLES_MASTER_KEY_CANNOT_BE_GE 396
 ER_PERSISTED_VARIABLES_MASTER_KEY_NOT_FOUND, 396
 ER_PERSISTENT_PRIVILEGES_BOOTSTRAP, 193
 ER_PERSIST_ONLY_ACCESS_DENIED_ERROR, 85
 ER_PERSIST_OPTION_HOST_TRUNCATED, 362
 ER_PERSIST_OPTION_STATUS, 218
 ER_PERSIST_OPTION_USER_TRUNCATED, 362
 ER_PER_CHANNEL_RPL_FILTER_CONF_FOR_GRP_RPL, 200
 ER_PFS_MALLOC_ARRAY_OOM, 201
 ER_PFS_MALLOC_ARRAY_OVERFLOW, 201
 ER_PFS_NOTIFICATION_FUNCTION_REGISTER_FAILED, 196
 ER_PID_FILEPATH_LOCATIONS_INACCESSIBLE, 345
 ER_PID_FILE_PRIV_DIRECTORY_INSECURE, 258
 ER_PK_INDEX_CANT_BE_INVISIBLE, 77
 ER_PLUGGABLE_PROTOCOL_COMMAND_NOT_SUPPORTED, 70
 ER_PLUGINS_SHUTDOWN_END, 417
 ER_PLUGINS_SHUTDOWN_START, 417
 ER_PLUGIN_BAD_OPTIONS, 180
 ER_PLUGIN_CANNOT_BE_UNINSTALLED, 60
 ER_PLUGIN_CANT_LOAD, 179
 ER_PLUGIN_CANT_OPEN_PLUGIN_TABLE, 179

ER_PLUGIN_CANT_SET_PERSISTENT_OPTIONS, 180
 ER_PLUGIN_COMMON_FAILED_TO_OPEN_FILTER_TABLES, 217
 ER_PLUGIN_COMMON_FAILED_TO_OPEN_TABLE, 217
 ER_PLUGIN_DELETE_BUILTIN, 41
 ER_PLUGIN_DID_NOT_DEINITIALIZE_THREADS, 169
 ER_PLUGIN_DISABLED, 180
 ER_PLUGIN_EXCEPTION_OPERATION_FAILED, 408
 ER_PLUGIN_FAILED_DEINITIALIZATION, 179
 ER_PLUGIN_FAILED_TO_OPEN_TABLE, 343
 ER_PLUGIN_FAILED_TO_OPEN_TABLES, 343
 ER_PLUGIN_FORCING_SHUTDOWN, 179
 ER_PLUGIN_HAS_CONFLICTING_SYSTEM_VARIABLES, 180
 ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_DEINITIALIZATION, 179
 ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_SHUTDOWN, 179
 ER_PLUGIN_INIT_FAILED, 151
 ER_PLUGIN_INSTALL_ERROR, 349
 ER_PLUGIN_INVALID_TABLE_DEFINITION, 389
 ER_PLUGIN_IS_NOT_LOADED, 37
 ER_PLUGIN_IS_PERMANENT, 47
 ER_PLUGIN_LOAD_OPTIONS_IGNORED, 368
 ER_PLUGIN_LOAD_PARAMETER_TOO_LONG, 179
 ER_PLUGIN_NOT_EARLY, 101
 ER_PLUGIN_NOT_EARLY_DUP, 362
 ER_PLUGIN_NO_INSTALL, 48
 ER_PLUGIN_NO_INSTALL_DUP, 362
 ER_PLUGIN_NO_UNINSTALL, 48
 ER_PLUGIN_OOM, 180
 ER_PLUGIN_PARSING_OPTIONS_FAILED, 180
 ER_PLUGIN_REGISTRATION_DONE, 118
 ER_PLUGIN_REGISTRATION_FAILED, 179
 ER_PLUGIN_REQUIRES_REGISTRATION, 118
 ER_PLUGIN_SHUTTING_DOWN_PLUGIN, 179
 ER_PLUGIN_UNINSTALL_ERROR, 349
 ER_PLUGIN_UNKNOWN_VARIABLE_TYPE, 179
 ER_PLUGIN_VARIABLE_MISSING_NAME, 180
 ER_PLUGIN_VARIABLE_NOT_ALLOCATED_THREAD_LOCAL, 180
 ER_PLUGIN_VARIABLE_SET_READ_ONLY, 179
 ER_POINTLESS_WITHOUT_SLOWLOG, 142
 ER_POLYGON_TOO_LARGE, 92
 ER_PREPARE_FOR_PRIMARY_ENGINE, 390
 ER_PREPARE_FOR_SECONDARY_ENGINE, 358
 ER_PREVENTS_VARIABLE_WITHOUT_RBR, 67
 ER_PRIMARY_CANT_HAVE_NULL, 15
 ER_PRIVILEGE_DEREGISTRATION, 412
 ER_PRIVILEGE_REGISTRATION, 412
 ER_PRIVILEGE_SYSTEM_INIT_FAILED, 194
 ER_PROCACCESS_DENIED_ERROR, 27
 ER_PROC_AUTO_GRANT_FAIL, 29
 ER_PROC_AUTO_REVOKE_FAIL, 29
 ER_PROTOCOL_COMPRESSION_RESET_LOG, 367
 ER_PS_MANY_PARAM, 28
 ER_PS_NO_RECURSION, 31
 ER_QUALIFY_WITHOUT_WINDOW_FUNCTION, 129
 ER_QUERY_INTERRUPTED, 24
 ER_QUERY_ON_FOREIGN_DATA_SOURCE, 31
 ER_QUERY_TIMEOUT, 62
 ER_RANGE_NOT_INCREASING_ERROR, 34
 ER_READING_TABLE_FAILED, 151
 ER_READY, 8
 ER_READ_LOG_EVENT_FAILED, 199
 ER_READ_ONLY_MODE, 56
 ER_READ_ONLY_TRANSACTION, 17
 ER_REALLY_RUN_AS_ROOT, 145
 ER_RECORD_FILE_FULL, 11
 ER_RECOVERING_TABLE, 181
 ER_REDUCED_DBLWR_FILE_CORRUPTED, 413
 ER_REDUCED_DBLWR_PAGE_FOUND, 413
 ER_REFERENCED_TRG_DOES_NOT_EXIST, 61
 ER_REGEXP_BAD_ESCAPE_SEQUENCE, 89
 ER_REGEXP_BAD_INTERVAL, 89
 ER_REGEXP_BUFFER_OVERFLOW, 89
 ER_REGEXP_ERROR, 13
 ER_REGEXP_ILLEGAL_ARGUMENT, 89
 ER_REGEXP_INDEX_OUTOFBOUNDS_ERROR, 89
 ER_REGEXP_INTERNAL_ERROR, 89
 ER_REGEXP_INVALID_BACK_REF, 89
 ER_REGEXP_INVALID_CAPTURE_GROUP_NAME, 104
 ER_REGEXP_INVALID_FLAG, 105
 ER_REGEXP_INVALID_RANGE, 89
 ER_REGEXP_LOOK_BEHIND_LIMIT, 89
 ER_REGEXP_MAX_LT_MIN, 89
 ER_REGEXP_MISMATCHED_PAREN, 89
 ER_REGEXP_MISSING_CLOSE_BRACKET, 89
 ER_REGEXP_MISSING_FILE, 120
 ER_REGEXP_MISSING_ICU_DATADIR, 395
 ER_REGEXP_MISSING_RESOURCE, 120
 ER_REGEXP_PATTERN_TOO_BIG, 90
 ER_REGEXP_RULE_SYNTAX, 89
 ER_REGEXP_STACK_OVERFLOW, 90
 ER_REGEXP_TIME_OUT, 90
 ER_REGEXP_UNIMPLEMENTED, 89
 ER_REGEX_NUMBER_TOO_BIG, 114
 ER_RELAY_LOG_FAIL, 27
 ER_RELAY_LOG_INIT, 28
 ER_RELAY_LOG_SPACE_LIMIT_DISABLED, 346
 ER_RELOAD_KEYRING_FAILURE, 116

ER_REMOVED_SPACES, 33
 ER_RENAMED_NAME, 42
 ER_RENAME_ROLE, 78
 ER_REORG_HASH_ONLY_ON_SAME_NO, 36
 ER_REORG_NO_PARAM_ERROR, 36
 ER_REORG_OUTSIDE_RANGE, 36
 ER_REORG_PARTITION_NOT_EXIST, 36
 ER_REPLACE_INACCESSIBLE_ROWS, 64
 ER_REPLICATION_INCOMPATIBLE_TABLE_WITH_GIPK, 406
 ER_REPLICA_AM_INIT_REPOSITORY, 59
 ER_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_PRIMARY, 382
 ER_REPLICA_ANON_TO_GTID_IS_LOCAL_OR_UUID_AND_GTID_MODE_SOURCE, 382
 ER_REPLICA_CANT_CREATE_CONVERSION, 45
 ER_REPLICA_CANT_USE_TEMPDIR, 176
 ER_REPLICA_CHANGE_SOURCE_TO_EXECUTED, 176
 ER_REPLICA_CHANNEL_DOES_NOT_EXIST, 65
 ER_REPLICA_CHANNEL_IO_THREAD_MUST_STOP, 62
 ER_REPLICA_CHANNEL_MUST_STOP, 66
 ER_REPLICA_CHANNEL_NAME_INVALID_OR_TOO_LONG, 66
 ER_REPLICA_CHANNEL_NOT_RUNNING, 66
 ER_REPLICA_CHANNEL_OPERATION_NOT_ALLOWED, 71
 ER_REPLICA_CHANNEL_SQL_SKIP_COUNTER, 66
 ER_REPLICA_CHANNEL_SQL_THREAD_MUST_STOP, 66
 ER_REPLICA_CHANNEL_WAS_NOT_RUNNING, 66
 ER_REPLICA_CHANNEL_WAS_RUNNING, 66
 ER_REPLICA_CM_INIT_REPOSITORY, 59
 ER_REPLICA_CONFIGURATION, 53
 ER_REPLICA_CORRUPT_EVENT, 41
 ER_REPLICA_CREATE_EVENT_FAILURE, 340
 ER_REPLICA_FATAL_ERROR, 340
 ER_REPLICA_HAS_MORE_GTIDS_THAN_SOURCE, 60
 ER_REPLICA_HEARTBEAT_FAILURE, 340
 ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE, 42
 ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX, 47
 ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN, 47
 ER_REPLICA_IGNORED_SSL_PARAMS, 21
 ER_REPLICA_IGNORED_TABLE, 19
 ER_REPLICA_IGNORE_SERVER_IDS, 43
 ER_REPLICA_INCIDENT, 340
 ER_REPLICA_KILLED_AFTER_RECONNECT, 200
 ER_REPLICA_MAX_CHANNELS_EXCEEDED, 66
 ER_REPLICA_MULTIPLE_CHANNELS_CMD, 66
 ER_REPLICA_NEW_CHANNEL_WRONG_REPOSITORY, 66
 ER_REPLICA_NOT_RUNNING, 16
 ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS, 200
 ER_REPLICA_POSSIBLY_DIVERGED_AFTER_DDL, 91
 ER_REPLICA_RECONNECT_FAILED, 199
 ER_REPLICA_RELAY_LOG_PURGE_FAILED, 194
 ER_REPLICA_RELAY_LOG_READ_FAILURE, 341
 ER_REPLICA_RELAY_LOG_TRUNCATE_INFO, 194
 ER_REPLICA_RELAY_LOG_WRITE_FAILURE, 341
 ER_REPLICA_SILENT_RETRY_TRANSACTION, 54
 ER_REPLICA_SOURCE_CONNECTION_FAILURE, 340
 ER_REPLICA_SQL_THREAD_MUST_STOP, 61
 ER_REPLICA_SQL_THREAD_STOPPED_AFTER_GTIDS_REACHED, 163
 ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS_ALLOWED, 163
 ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS_REACHED, 163
 ER_REPLICA_SQL_THREAD_STOPPED_GAP_TRX_PROCESSING, 163
 ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_CONDITION_BECOMES_TRUE, 163
 ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_POSITION_REACHED, 163
 ER_REPLICA_THREAD, 16
 ER_REPLICA_WORKER_STOPPED_PREVIOUS_THD_ERROR, 62
 ER_REQUIRES_PRIMARY_KEY, 15
 ER_REQUIRE_ROW_FORMAT_INVALID_VALUE, 108
 ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATE_WARNINGS, 126
 ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATE_WARNINGS, 408
 ER_RESERVED_SYNTAX, 28
 ER_RESERVED_TABLESPACE_NAME, 91
 ER_RESET_SOURCE_TO_VALUE_OUT_OF_RANGE, 80
 ER_RESIGNAL_WITHOUT_ACTIVE_HANDLER, 43
 ER_RESOURCE_GROUP_BIND_FAILED, 87
 ER_RESOURCE_GROUP_BUSY, 87
 ER_RESOURCE_GROUP_DISABLED, 87
 ER_RESOURCE_GROUP_EXISTS, 86
 ER_RESOURCE_GROUP_IS_DISABLED, 196
 ER_RESOURCE_GROUP_METADATA_UPDATE_SKIPPED, 195
 ER_RESOURCE_GROUP_NOT_EXISTS, 86
 ER_RESOURCE_GROUP_POST_INIT_FAILED, 193
 ER_RESOURCE_GROUP_SUBSYSTEM_INIT_FAILED, 193

ER_RESOURCE_GROUP_VALIDATION_FAILED, 195
ER_RESTART_RECEIVED_INFO, 204
ER_RESTART_SERVER_FAILED, 90
ER_RESULT_SIZE_LIMIT_EXCEEDED, 134
ER_RES_GRP_FAILED_DETERMINE_CPU_COUNT, 197
ER_RES_GRP_FAILED_TO_DETERMINE_NICE_CAPABILITY, 196
ER_RES_GRP_FAILED_TO_GET_THREAD_HANDLE, 196
ER_RES_GRP_FEATURE_NOT_AVAILABLE, 197
ER_RES_GRP_GET_THREAD_Prio_NOT_SUPPORTED, 196
ER_RES_GRP_INVALID_THREAD_PRIORITY, 197
ER_RES_GRP_INVALID_VCPU_ID, 203
ER_RES_GRP_INVALID_VCPU_RANGE, 203
ER_RES_GRP_SET_THREAD_PRIORITY_FAILED, 196
ER_RES_GRP_SET_THR_AFFINITY_FAILED, 196
ER_RES_GRP_SET_THR_AFFINITY_TO_CPUS_FAILED, 196
ER_RES_GRP_SOLARIS_PROCESSOR_AFFINITY_FAILED, 197
ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_CPU_ID_FAILED, 197
ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_THREAD_ID_FAILED, 197
ER_RES_GRP_THD_UNBIND_FROM_CPU_FAILED, 196
ER_RETRYING_REPAIR_WITHOUT_QUICK, 180
ER_RETRYING_REPAIR_WITH_KEYCACHE, 180
ER_REVOKE_GRANTS, 21
ER_REWRITER_LOAD_FAILED, 218
ER_REWRITER_OOM, 218
ER_REWRITER_QUERY_ERROR_MSG, 216
ER_REWRITER_QUERY_FAILED, 216
ER_REWRITER_READ_FAILED, 218
ER_REWRITER_TABLE_MALFORMED_ERROR, 218
ER_ROLE_GRANTED_TO_ITSELF, 115
ER_ROLE_NOT_GRANTED, 78
ER_ROW_DATA_TOO_BIG_TO_WRITE_IN_BINLOG, 199
ER_ROW_DOES_NOT_MATCH_GIVEN_PARTITION_SET, 50
ER_ROW_DOES_NOT_MATCH_PARTITION, 49
ER_ROW_IN_WRONG_PARTITION, 58
ER_ROW_IN_WRONG_PARTITION_PLEASE_REPAIR, 153
ER_ROW_IS_REFERENCED, 18
ER_ROW_IS_REFERENCED_2, 32
ER_ROW_SINGLE_PARTITION_FIELD_ERROR, 44
ER_RPL_AM_INIT_INFO_MSG, 202
ER_RPL_ASYNC_CHANNEL_CANT_CONNECT, 381
ER_RPL_ASYNC_CHANNEL_CANT_CONNECT_NO_QUORUM, 381
ER_RPL_ASYNC_CHANNEL_STOPPED_QUORUM_LOST, 381
ER_RPL_ASYNC_CHECK_CONNECTION_ERROR, 423
ER_RPL_ASYNC_GET_GROUP_MEMBERSHIP_DETAILS_ERROR, 423
ER_RPL_ASYNC_MANAGED_NAME_ADDED, 382
ER_RPL_ASYNC_MANAGED_NAME_REMOVED, 382
ER_RPL_ASYNC_MONITOR_IO_THD_FETCH_GROUP_MAJOR_VERSION_FAILED, 423
ER_RPL_ASYNC_NEXT_FAILOVER_CHANNEL_SELECTED, 409
ER_RPL_ASYNC_READ_FAILOVER_TABLE, 382
ER_RPL_ASYNC_RECONNECT_AUTO_POSITION_OFF, 112
ER_RPL_ASYNC_RECONNECT_FAIL_NO_SOURCE, 380
ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF, 423
ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF_CHANNEL_CANT_CONNECT, 423
ER_RPL_ASYNC_REPLICA_IO_THD_FETCH_GROUP_MAJOR_VERSION_FAILED, 423
ER_RPL_ASYNC_SENDER_ADDED, 381
ER_RPL_ASYNC_SENDER_REMOVED, 381
ER_RPL_BINLOG_FILTERS_OOM, 144
ER_RPL_BINLOG_RELAY_DELEGATES_INIT_FAILED, 151
ER_RPL_BINLOG_SKIPPING_REMAINING_HEARTBEAT_IN_RELAY_LOG, 169
ER_RPL_BINLOG_SOURCE_SENDS_HEARTBEAT, 169
ER_RPL_BINLOG_SOURCE_USES_CHECKSUM_AND_REPLICAS, 169
ER_RPL_BINLOG_STARTING_DUMP, 169
ER_RPL_BINLOG_STORAGE_DELEGATES_INIT_FAILED, 151
ER_RPL_BINLOG_TRANSMIT_DELEGATES_INIT_FAILED, 151
ER_RPL_CANNOT_OPEN_RELAY_LOG, 393
ER_RPL_CANT_ADD_DO_TABLE, 147
ER_RPL_CANT_ADD_IGNORE_TABLE, 147
ER_RPL_CANT_CREATE_REPLICA_THREAD, 172
ER_RPL_CANT_FIND_FOLLOWUP_FILE, 174
ER_RPL_CANT_HAVE_SAME_BASENAME, 191
ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_AM_INIT_INFO, 177
ER_RPL_CANT_MAKE_PATHS, 148
ER_RPL_CANT_OPEN_INFO_TABLE, 164

ER_RPL_CANT_OPEN_LOG_IN_AM_INIT_INFO, 177	ER_RPL_FAILED_TO_RESET_STATE_IN_REPLICA_INFO_REPO, 165
ER_RPL_CANT_SCAN_INFO_TABLE, 165	ER_RPL_FAILED_TO_STAT_LOG_IN_INDEX, 176
ER_RPL_CANT_STOP_REPLICA_WHILE_LOCKED_BACKUP, 102	ER_RPL_FILTERS_NOT_ATTACHED_TO_CHANNEL, 200
ER_RPL_CHANNELS_REQUIRE_NON_ZERO_SERVER_ID, 165	ER_RPL_FILTER_ADD_WILD_DO_TABLE_FAILED, 194
ER_RPL_CORRUPTED_INFO_TABLE, 165	ER_RPL_FILTER_ADD_WILD_IGNORE_TABLE_FAILED, 194
ER_RPL_CORRUPTED_KEYS_IN_INFO_TABLE, 165	ER_RPL_GTID_LOG_EVENT_IN_STREAM, 167
ER_RPL_ENCRYPTION_CANNOT_ROTATE_BINLOG_MASTER_KEY, 98	ER_RPL_GTID_MEMORY_FINALLY_AVAILABLE, 166
ER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT, 97	ER_RPL_GTID_MODE_REQUIRES_ENFORCE_GTID_CONSISTENCY, 191
ER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY, 96	ER_RPL_GTID_TABLE_CANNOT_OPEN, 138
ER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY, 97	ER_RPL_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION, 349
ER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY, 97	ER_RPL_GTID_UNSAFE_STMT_CREATE_SELECT, 339
ER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS, 96	ER_RPL_GTID_UNSAFE_STMT_ON_NON_TRANS_TABLE, 339
ER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY, 97	ER_RPL_INCOMPATIBLE_DECIMAL_IN_RBR, 168
ER_RPL_ENCRYPTION_HEADER_ERROR, 96	ER_RPL_INCONSISTENT_SEQUENCE_NO_IN_TRX, 165
ER_RPL_ENCRYPTION_KEYRING_INVALID_KEY, 96	ER_RPL_INCONSISTENT_TIMESTAMPS_IN_TRX, 165
ER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED, 97	ER_RPL_INCREMENTING_MEMBER_ACTION_VERSION, 391
ER_RPL_ENCRYPTION_KEY_NOT_FOUND, 96	ER_RPL_INFINITY_DENIED, 150
ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED, 97	ER_RPL_INFINITY_IGNORED, 150
ER_RPL_ENCRYPTION_UNABLE_TO_CHANGE_OPTIONS, 97	ER_RPL_INFO_DATA_TOO_LONG, 50
ER_RPL_ERROR_CREATING_APPLIER_METADATA, 165	ER_RPL_IO_THREAD_KILLED, 199
ER_RPL_ERROR_CREATING_CONNECTION_METADATA, 165	ER_RPL_KILL_OLD_DUMP_THREAD_ENCOUNTERED, 428
ER_RPL_ERROR_LOOKING_FOR_LOG, 174	ER_RPL_LOG_ENTRY_EXCEEDS_REPLICA_MAX_ALLOWED_LENGTH, 174
ER_RPL_ERROR_READING_REPLICA_WORKER_CONFIGURATION, 178	ER_RPL_LOG_NOT_FOUND_WHILE_COUNTING_RELAY_LOG_ENTRIES, 176
ER_RPL_ERROR_READING_SOURCE_CONFIGURATION, 179	ER_RPL_MTA_ALLOW_COMMIT_OUT_OF_ORDER, 429
ER_RPL_ERROR_WRITING_RELAY_LOG_CONFIGURATION, 177	ER_RPL_MTA_AUTOMATIC_RECOVERY_FAILED, 172
ER_RPL_ERROR_WRITING_SOURCE_CONFIGURATION, 179	ER_RPL_MTA_CHECKPOINT_PERIOD_DIFFERS_FROM_COUNT, 174
ER_RPL_FAILED_TO_CREATE_CACHE_FOR_INFO_FILE, 166	ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA, 174
ER_RPL_FAILED_TO_CREATE_NEW_INFO_FILE, 166	ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA_FOR_GROUP, 174
ER_RPL_FAILED_TO_DELETE_FROM_REPLICA_WORKER_CONFIGURATION, 165	ER_RPL_MTA_RECOVERY_CANT_OPEN_RELAY_LOG, 172
ER_RPL_FAILED_TO_OPEN_INFO_FILE, 166	ER_RPL_MTA_RECOVERY_COMPLETE, 173
ER_RPL_FAILED_TO_OPEN_RELAY_LOG, 178	ER_RPL_MTA_RECOVERY_FAILED_TO_START_COORDINATION, 172

ER_RPL_MTA_RECOVERY_STARTING_COORDINATOR,	ER_RPL_REPLICA_COULD_NOT_CREATE_CHANNEL_LIST
171	166
ER_RPL_MTA_RECOVERY_SUCCESSFUL, 172	ER_RPL_REPLICA_DUMP_THREAD_KILLED_BY_SOURCE,
ER_RPL_MTA_REPLICA_COORDINATOR_HAS_WAITED,	173
178	ER_RPL_REPLICA_ERROR_INFO_FROM_DA, 175
ER_RPL_MTA_STATISTICS, 173	ER_RPL_REPLICA_ERROR_LOADING_USER_DEFINED_LIE
ER_RPL_MULTISOURCE_REQUIRES_TABLE_TYPE_REPO	OSITORIES,
166	ER_RPL_REPLICA_ERROR_READING_FROM_SERVER,
ER_RPL_OPEN_INDEX_FILE_FAILED, 177	173
ER_RPL_PLEASE_USE_OPTION_RELAY_LOG, 177	ER_RPL_REPLICA_ERROR_READING_RELAY_LOG_EVENT
ER_RPL_PLUGIN_FUNCTION_FAILED, 151	176
ER_RPL_RECOVERY_ERROR, 171	ER_RPL_REPLICA_ERROR_REQUESTING_BINLOG_DUMP
ER_RPL_RECOVERY_ERROR_READ_RELAY_LOG,	174
171	ER_RPL_REPLICA_ERROR_RETRYING, 173
ER_RPL_RECOVERY_FILE_SOURCE_POS_INFO,	ER_RPL_REPLICA_ERROR_RUNNING_QUERY,
171	175
ER_RPL_RECOVERY_IO_ERROR_READING_RELAY_LOG	INDEX,REPLICA_FAILED_TO_CREATE_CHANNEL_FROM
171	166
ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SOURCE,	REPLICA_FAILED_TO_CREATE_OR_RECOVER_I
171	170
ER_RPL_RECOVERY_REPLICATE_SAME_SERVER_ID	REQUIRES_POSITION,
171	166
ER_RPL_RECOVERY_SKIPPED_GROUP_REPLICATION	CHANNEL,REPLICA_FAILED_TO_INIT_CONNECTION_META
171	166
ER_RPL_RELAY_LOG_INDEX_NEEDS_FILE_NOT_DIRECTO	RYP,REPLICA_FAILED_TO_INIT_PARTITIONS_HASH,
177	175
ER_RPL_RELAY_LOG_NEEDS_FILE_NOT_DIRECTORY,	ER_RPL_REPLICA_FILTER_CREATE_FAILED, 194
177	ER_RPL_REPLICA_FORCING_TO_RECONNECT_IO_THREA
ER_RPL_RELAY_LOG_RECOVERY_GTID_ONLY,	173
395	ER_RPL_REPLICA_GENERIC_MESSAGE, 165
ER_RPL_RELAY_LOG_RECOVERY_INFO_AFTER_CLONE	ER_RPL_REPLICA_GLOBAL_FILTERS_COPY_FAILED,
370	194
ER_RPL_REPLICA_ADDITIONAL_ERROR_INFO_FROM	ER_RPL_REPLICA_INCORRECT_CHANNEL, 190
175	ER_RPL_REPLICA_INSECURE_CHANGE_SOURCE,
ER_RPL_REPLICA_AUTO_POSITION_IS_1_AND_GTID_M	ODE_IS_OFF,
171	ER_RPL_REPLICA_IO_THREAD_ABORTED_WAITING_FOR
ER_RPL_REPLICA_CANT_FLUSH_CONNECTION_META	DATA_REPOS,
172	ER_RPL_REPLICA_IO_THREAD_CANT_REGISTER_ON_SO
ER_RPL_REPLICA_CANT_INITIALIZE_REPLICA_WORKER	173
174	ER_RPL_REPLICA_IO_THREAD_DETECTED_UNEXPECTED
ER_RPL_REPLICA_CANT_INIT_RELAY_LOG_POSITION,	176
173	ER_RPL_REPLICA_IO_THREAD_EXITING, 174
ER_RPL_REPLICA_CANT_START_REPLICA_FOR_CHANNE	L,REPLICA_IO_THREAD_KILLED, 173
171	ER_RPL_REPLICA_IO_THREAD_STOP_CMD_EXEC_TIMEO
ER_RPL_REPLICA_CANT_STOP_REPLICA_FOR_CHANNE	179
171	ER_RPL_REPLICA_IO_THREAD_WAS_KILLED, 172
ER_RPL_REPLICA_CANT_USE_CHARSET, 176	ER_RPL_REPLICA_MONITOR_IO_THREAD_EXITING,
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_REPLICA	TION_RESUMED,
176	ER_RPL_REPLICA_MONITOR_IO_THREAD_RECONNECT
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_STA	RTEDED_FILE_BASED,
409	ER_RPL_REPLICA_NEW_C_M_NEEDS_REPOS_TYPE_OTH
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_STA	RTEDED_GTID_BASED,
409	ER_RPL_REPLICA_NEXT_LOG_IS_ACTIVE, 176
	ER_RPL_REPLICA_NEXT_LOG_IS_INACTIVE, 176

ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_CONNECTION, 175	ER_RPL_REPLICA_UNSUPPORTED_UNIGNORABLE_EVENT_IN_STREAM, 167
ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_NUMBER_OF_ROWS, 368	ER_RPL_REPLICA_WRONG_FORMAT_CANT_FIND_NEXT_RELAY_LOG, 178
ER_RPL_REPLICA_READ_INVALID_EVENT_FROM_SOURCE, 175	ER_RPL_WORKER_CANT_READ_RELAY_LOG, 178
ER_RPL_REPLICA_REPORT_HOST_TOO_LONG, 172	ER_RPL_WORKER_ID_IS, 165
ER_RPL_REPLICA_REPORT_PASSWORD_TOO_LONG, 173	ER_RPL_ZOMBIE_ENCOUNTERED, 138
ER_RPL_REPLICA_REPORT_USER_TOO_LONG, 173	ER_RUNNING_APPLIER_PREVENTS_SWITCH_GLOBAL_BINLOG, 93
ER_RPL_REPLICA_RESET_FILTER_OPTIONS, 194	ER_RUN_HOOK_ERROR, 67
ER_RPL_REPLICA_SECONDS_BEHIND_SOURCE_DUBIOUS, 172	ER_SAME_NAME_PARTITION, 36
ER_RPL_REPLICA_SKIP_COUNTER_EXECUTED, 175	ER_SAME_NAME_PARTITION_FIELD, 43
ER_RPL_REPLICA_SOURCE_UUID_HAS_CHANGED_HOST, 409	ER_SCHEDULER_KILLING, 140
ER_RPL_REPLICA_SOURCE_UUID_HAS_NOT_CHANGED, 409	ER_SCHEDULER_STARTED, 140
ER_RPL_REPLICA_SOURCE_UUID_HOST_PORT_HAS_CHANGED, 409	ER_SCHEDULER_STOPPED, 140
ER_RPL_REPLICA_SQL_THREAD_DETECTED_UNEXPECTED_SCHEMA_SEQUENCE, 369	ER_SCHEDULER_STOPPING_FAILED_TO_CREATE_WORKER, 140
ER_RPL_REPLICA_SQL_THREAD_EXITING, 175	ER_SCHEDULER_STOPPING_FAILED_TO_GET_EVENT, 140
ER_RPL_REPLICA_SQL_THREAD_IO_ERROR_READING_EVENT, 176	ER_SCHEDULER_WAITING, 140
ER_RPL_REPLICA_SQL_THREAD_STARTING, 175	ER_SCHEMA_DIR_CREATE_FAILED, 88
ER_RPL_REPLICA_SQL_THREAD_STARTING_WITH_PRIMARY_KEY_CHECKS, 368	ER_SCHEMA_DIR_EXISTS, 88
ER_RPL_REPLICA_SQL_THREAD_STOP_CMD_EXEC_TIMEOUT, 339	ER_SCHEMA_DIR_MISSING, 88
ER_RPL_REPLICA_STOPPING_AS_SOURCE_OOM, 174	ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED, 370
ER_RPL_REPLICA_USES_CHECKSUM_AND_SOURCE_FILTER, 172	ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_SECONDARY, 370
ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED, 174	ER_SCHEMA_READ_ONLY, 112
ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED_SECONDARY, 175	ER_SCHEMA_CHECKS_INVALID_TABLESPACE, 116
ER_RPL_REPO_HAS_GAPS, 139	ER_SDI_OPERATION_FAILED, 87
ER_RPL_REWRITEDB_EMPTY_FROM, 147	ER_SDI_OPERATION_FAILED_MISSING_RECORD, 109
ER_RPL_REWRITEDB_EMPTY_TO, 147	ER_SECONDARY_ENGINE, 104
ER_RPL_REWRITEDB_MISSING_ARROW, 147	ER_SECONDARY_ENGINE_DDL, 104
ER_RPL_SERVER_ID_MISSING, 172	ER_SECONDARY_ENGINE_DDL_FAILED, 413
ER_RPL_SSL_INFO_IN_CONNECTION_METADATA_IGNORED, 179	ER_SECONDARY_ENGINE_DDL_TRACK_PROGRESS, 413
ER_RPL_TRX_DELEGATES_INIT_FAILED, 151	ER_SECONDARY_ENGINE_PLUGIN, 103
ER_RPL_UNEXPECTED_BEGIN_IN_STREAM, 167	ER_SECONDARY_ENGINE_PASSWORD_CANNOT_BE_EMPTY, 103
ER_RPL_UNEXPECTED_COMMIT_ROLLBACK_OR_XID_IGNORED, 167	ER_SECURE_AUTH_VALUE_UNSUPPORTED, 142
ER_RPL_UNEXPECTED_XA_ROLLBACK_IN_STREAM, 167	ER_SECURE_TRANSPORT_REQUIRED, 72
	ER_SEC_FILE_PRIV_ARGUMENT_TOO_LONG, 144
	ER_SEC_FILE_PRIV_CANT_ACCESS_DIR, 143
	ER_SEC_FILE_PRIV_CANT_STAT, 144
	ER_SEC_FILE_PRIV_DIRECTORY_INSECURE, 143
	ER_SEC_FILE_PRIV_DIRECTORY_PERMISSIONS, 144
	ER_SEC_FILE_PRIV_EMPTY, 143
	ER_SELECT_REDUCE_IN_STREAM_IGNORED, 143
	ER_SEC_FILE_PRIV_NULL, 143
	ER_SELECT_REDUCE, 20
	ER_SEMISYNC_ADD_ACK_TO_SLOT, 210

ER_SEMISYNC_BINLOG_REPLY_IS_AHEAD, 209	ER_SEMISYNC_RPL_SWITCHED_ON, 209
ER_SEMISYNC_BINLOG_WRITE_OUT_OF_ORDER, 208	ER_SEMISYNC_SERVER_REPLY, 208
ER_SEMISYNC_CLEARED_ACTIVE_TRANSACTION_TILL_POS, 208	ER_SEMISYNC_SOCKET_FD_TOO_LARGE, 211
ER_SEMISYNC_CLEARED_ALL_ACTIVE_TRANSACTION_NODES, 208	ER_SEMISYNC_SOURCE_FAILED_ON_NET_FLUSH, 210
ER_SEMISYNC_DISABLED_ON_SOURCE, 208	ER_SEMISYNC_SOURCE_GOT_REPLY_AT_POS, 209
ER_SEMISYNC_EXECUTION_FAILED_ON_SOURCE, 212	ER_SEMISYNC_SOURCE_OOM, 208
ER_SEMISYNC_FAILED_REGISTER_REPLICA_TO_RECEIVER, 210	ER_SEMISYNC_SOURCE_SIGNAL_ALL_WAITING_THREADS, 209
ER_SEMISYNC_FAILED_TO_ALLOCATE_TRX_NODE, 207	ER_SEMISYNC_SOURCE_TRX_WAIT_POS, 209
ER_SEMISYNC_FAILED_TO_INSERT_TRX_NODE, 210	ER_SEMISYNC_STARTING_ACK_RECEIVER_THD, 210
ER_SEMISYNC_FAILED_TO_START_ACK_RECEIVER_THD, 210	ER_SEMISYNC_START_BINLOG_DUMP_TO_REPLICA, 210
ER_SEMISYNC_FAILED_TO_STOP_ACK_RECEIVER_THD, 212	ER_SEMISYNC_STOPPING_ACK_RECEIVER_THREAD, 210
ER_SEMISYNC_FAILED_TO_WAIT_ON_DUMP_SOCKET, 210	ER_SEMISYNC_STOP_BINLOG_DUMP_TO_REPLICA, 211
ER_SEMISYNC_FORCED_SHUTDOWN, 208	ER_SEMISYNC_SYNC_HEADER_UPDATE_INFO, 209
ER_SEMISYNC_FUNCTION_CALLED_TWICE, 208	ER_SEMISYNC_TRACE_ENTER_FUNC, 207
ER_SEMISYNC_INIT_WAIT_POS, 209	ER_SEMISYNC_TRACE_EXIT, 207
ER_SEMISYNC_INSERT_LOG_INFO_IN_ENTRY, 208	ER_SEMISYNC_TRACE_EXIT_WITH_BOOL_EXIT_CODE, 207
ER_SEMISYNC_MISSING_MAGIC_NO_FOR_SEMISYNC_PKT, 211	ER_SEMISYNC_TRACE_EXIT_WITH_INT_EXIT_CODE, 207
ER_SEMISYNC_MOVE_BACK_WAIT_POS, 209	ER_SEMISYNC_TRX_SKIPPED_AT_POS, 210
ER_SEMISYNC_NOT_SUPPORTED_BY_SOURCE, 212	ER_SEMISYNC_UNREGISTERED_REPLICATOR, 211
ER_SEMISYNC_NO_SPACE_IN_THE_PKT, 209	ER_SEMISYNC_UNREGISTER_BINLOG_STORAGE_OBSERVER, 211
ER_SEMISYNC_PROBE_LOG_INFO_IN_ENTRY, 208	ER_SEMISYNC_UNREGISTER_BINLOG_TRANSMIT_OBSERVER, 211
ER_SEMISYNC_RECEIVED_ACK_IS_SMALLER, 210	ER_SEMISYNC_UNREGISTER_TRX_OBSERVER_FAILED, 211
ER_SEMISYNC_REPLICA_NET_FLUSH_REPLY_FAILED, 211	ER_SEMISYNC_UPDATE_EXISTING_REPLICA_ACK, 210
ER_SEMISYNC_REPLICA_REPLY, 211	ER_SEMISYNC_WAIT_FOR_BINLOG_TIMEDOUT, 209
ER_SEMISYNC_REPLICA_REPLY_WITH_BINLOG_INFO, 211	ER_SEMISYNC_WAIT_TIME_ASSESSMENT_FOR_COMMIT, 209
ER_SEMISYNC_REPLICA_SEND_REPLY_FAILED, 211	ER_SEMISYNC_WAIT_TIME_FOR_BINLOG_SENT, 209
ER_SEMISYNC_REPLICA_SET_FAILED, 212	ER_SERVERID_TOO_LARGE, 149
ER_SEMISYNC_REPLICA_START, 211	ER_SERVER_ACL_TABLE_ERROR, 342
ER_SEMISYNC_REPLY_BINLOG_FILE_TOO_LARGE, 208	ER_SERVER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_SYNC, 358
ER_SEMISYNC_REPLY_MAGIC_NO_ERROR, 208	ER_SERVER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_COPY, 358
ER_SEMISYNC_REPLY_PKT_LENGTH_TOO_SMALL, 208	ER_SERVER_BINLOG_UNSAFE_SYSTEM_FUNCTION, 361
ER_SEMISYNC_RPL_ENABLED_ON_SOURCE, 208	ER_SERVER_CANNOT_LOAD_FROM_TABLE_V2, 342
ER_SEMISYNC_RPL_INIT_FOR_TRX, 207	
ER_SEMISYNC_RPL_SWITCHED_OFF, 209	

ER_SERVER_CANT_OPEN_FILE, 342	ER_SERVER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY, 352
ER_SERVER_CERT_VERIFY_FAILED, 416	ER_SERVER_RPL_ENCRYPTION_HEADER_ERROR, 352
ER_SERVER_COL_COUNT_DOESNT_MATCH_CORRUPTED, 342	ER_SERVER_RPL_ENCRYPTION_IGNORE_ROTATE_MASTER_KEY, 353
ER_SERVER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE, 342	ER_SERVER_RPL_ENCRYPTION_KEYRING_INVALID_KEY, 352
ER_SERVER_COST_FAILED_TO_READ, 167	ER_SERVER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED, 352
ER_SERVER_COST_INVALID_COST_CONSTANT, 166	ER_SERVER_RPL_ENCRYPTION_KEY_NOT_FOUND, 352
ER_SERVER_COST_UNKNOWN_COST_CONSTANT, 166	ER_SERVER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED, 352
ER_SERVER_DISK_FULL_NOWAIT, 341	ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_INITIALIZE, 352
ER_SERVER_DOWNGRADE_FROM_VERSION, 414	ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_ROTATE_MASTER_KEY, 353
ER_SERVER_DOWNGRADE_HELP_TABLE_STATUS, 426	ER_SERVER_SHUTDOWN, 7
ER_SERVER_DOWNGRADE_STATUS, 414	ER_SERVER_SHUTDOWN_COMPLETE, 191
ER_SERVER_DOWNGRADE_SYS_SCHEMA, 426	ER_SERVER_SHUTDOWN_INFO, 344
ER_SERVER_FILE_NOT_FOUND, 342	ER_SERVER_SOURCE_FATAL_ERROR_READING_BINLOG, 340
ER_SERVER_FILE_USED, 342	ER_SERVER_STARTUP_ADMIN_INTERFACE, 353
ER_SERVER_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN_REPOSITORY, 348	ER_SERVER_STARTUP_MSG, 192
ER_SERVER_HANDLER_ERROR, 341	ER_SERVER_TABLE_CHECK_FAILED, 342
ER_SERVER_INIT_COMPILED_IN_COMMANDS, 202	ER_SERVER_TEST_MESSAGE, 343
ER_SERVER_ISNT_AVAILABLE, 73	ER_SERVER_UNKNOWN_SYSTEM_VARIABLE, 341
ER_SERVER_NET_PACKET_TOO_LARGE, 341	ER_SERVER_UPGRADE_CHECKING_DB, 360
ER_SERVER_NEW_ABORTING_CONNECTION, 341	ER_SERVER_UPGRADE_EMPTY_SYS, 360
ER_SERVER_NOT_FORM_FILE, 341	ER_SERVER_UPGRADE_FAILED, 359
ER_SERVER_NO_SESSION_TO_SEND_TO, 341	ER_SERVER_UPGRADE_FROM_VERSION, 356
ER_SERVER_NO_SYSTEM_TABLE_ACCESS, 341	ER_SERVER_UPGRADE_HELP_TABLE_STATUS, 361
ER_SERVER_OFFLINE_MODE, 62	ER_SERVER_UPGRADE_INFO_FILE, 360
ER_SERVER_OUTOFMEMORY, 193	ER_SERVER_UPGRADE_MYSQL_TABLES, 360
ER_SERVER_OUT_OF_RESOURCES, 192	ER_SERVER_UPGRADE_NO_SYS_VERSION, 360
ER_SERVER_OUT_OF_SORTMEMORY, 341	ER_SERVER_UPGRADE_OFF, 359
ER_SERVER_RECORD_FILE_FULL, 341	ER_SERVER_UPGRADE_PENDING, 359
ER_SERVER_REPLICA_AM_INIT_REPOSITORY, 341	ER_SERVER_UPGRADE_REPAIR_REQUIRED, 360
ER_SERVER_REPLICA_CM_INIT_REPOSITORY, 341	ER_SERVER_UPGRADE_REPAIR_STATUS, 360
ER_SERVER_REPLICA_CONVERSION_FAILED, 342	ER_SERVER_UPGRADE_SKIP, 359
ER_SERVER_REPLICA_IGNORED_TABLE, 342	ER_SERVER_UPGRADE_STATUS, 359
ER_SERVER_REPLICA_INIT_QUERY_FAILED, 342	ER_SERVER_UPGRADE_SYSTEM_TABLES, 360
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT, 355	ER_SERVER_UPGRADE_SYS_SCHEMA, 360
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY, 352	ER_SERVER_UPGRADE_SYS_SCHEMA_OBJECT_COUNT, 360
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY, 352	ER_SERVER_UPGRADE_SYS_SCHEMA_OUTDATED, 360
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY, 352	ER_SERVER_UPGRADE_SYS_SCHEMA_UP_TO_DATE, 360
ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS, 352	ER_SERVER_UPGRADE_SYS_VERSION_EMPTY, 360

ER_SERVER_UPGRADE_VERSION_NOT_SUPPORTED, 355
 ER_SERVER_WARN_DEPRECATED, 358
 ER_SERVER_WRONG_VALUE_FOR_VAR, 348
 ER_SESSION_WAS_KILLED, 73
 ER_SETNS_FAILED, 361
 ER_SET_CONSTANTS_ONLY, 16
 ER_SET_EVENT_FAILED, 345
 ER_SET_PASSWORD_AUTH_PLUGIN_ERROR, 122
 ER_SET_STATEMENT_CANNOT_INVOKE_FUNCTION, 52
 ER_SE_TYPECODE_CONFLICT, 153
 ER_SHA256_PASSWORD_SECOND_PASSWORD_USED_INFORMATION, 353
 ER_SHAPE_PREDICTION_UDF, 123
 ER_SHARED_TABLESPACE_USED_BY_PARTITIONED_TABLES, 349
 ER_SHA_PWD_AUTH_REQUIRES_RSA_OR_SSL, 217
 ER_SHA_PWD_FAILED_TO_GENERATE_MULTI_ROUND_HASH, 216
 ER_SHA_PWD_FAILED_TO_PARSE_AUTH_STRING, 216
 ER_SHA_PWD_RSA_KEY_TOO_LONG, 217
 ER_SHA_PWD_SALT_FOR_USER_CORRUPT, 217
 ER_SHUTDOWN_COMPLETE, 8
 ER_SHUTTING_DOWN_REPLICA_THREADS, 145
 ER_SIGNAL_BAD_CONDITION_TYPE, 43
 ER_SIGNAL_EXCEPTION, 43
 ER_SIGNAL_NOT_FOUND, 43
 ER_SIGNAL_WARN, 43
 ER_SIMULATED_INJECTION_ERROR, 128
 ER_SIZE_OVERFLOW_ERROR, 37
 ER_SKIP_UPDATING_METADATA_IN_SE_RO_MODE, 199
 ER_SLOW_LOG_MODE_IGNORED_WHEN_NOT_LOGGING_TO_FILE, 97
 ER_SOURCE, 15
 ER_SOURCE_DELAY_VALUE_OUT_OF_RANGE, 49
 ER_SOURCE_FATAL_ERROR_READING_BINLOG, 19
 ER_SOURCE_HAS_PURGED_REQUIRED_GTIDS, 53
 ER_SOURCE_NET_READ, 15
 ER_SOURCE_NET_WRITE, 15
 ER_SPATIAL_CANT_HAVE_NULL, 20
 ER_SPATIAL_FUNCTIONAL_INDEX, 94
 ER_SPATIAL_MUST_HAVE_GEOM_COL, 46
 ER_SPATIAL_UNIQUE_INDEX, 92
 ER_SPECIFIC_ACCESS_DENIED, 130
 ER_SPECIFIC_ACCESS_DENIED_ERROR, 18
 ER_SPVAR_NONINTEGER_TYPE, 114
 ER_SP_ALREADY_EXISTS, 23
 ER_SP_BADRETURN, 23
 ER_SP_BADSELECT, 23
 ER_SP_BADSTATEMENT, 24
 ER_SP_BAD_CURSOR_QUERY, 24
 ER_SP_BAD_CURSOR_SELECT, 24
 ER_SP_BAD_SQLSTATE, 29
 ER_SP_BAD_VAR_SHADOW, 32
 ER_SP_CANT ALTER, 25
 ER_SP_CANT_SET_AUTOCOMMIT, 32
 ER_SP_CASE_NOT_FOUND, 25
 ER_SP_COND_MISMATCH, 24
 ER_SP_CURSOR_AFTER_HANDLER, 25
 ER_SP_CURSOR_ALREADY_OPEN, 24
 ER_SP_CURSOR_MISMATCH, 24
 ER_SP_CURSOR_NOT_OPEN, 24
 ER_SP_DOES_NOT_EXIST, 23
 ER_SP_DROP_FAILED, 23
 ER_SP_DUP_COND, 25
 ER_SP_DUP_CURS, 25
 ER_SP_DUP_HANDLER, 29
 ER_SP_DUP_PARAM, 25
 ER_SP_DUP_VAR, 25
 ER_SP_FETCH_NO_DATA, 25
 ER_SP_LABEL_MISMATCH, 23
 ER_SP_LABEL_REDEFINE, 23
 ER_SP_LILABEL_MISMATCH, 23
 ER_SP_LOAD_FAILED, 77
 ER_SP_NORETURN, 24
 ER_SP_NORETURNEND, 24
 ER_SP_NOT_VAR_ARG, 30
 ER_SP_NO_AGGREGATE, 33
 ER_SP_NO ALTER LANGUAGE, 127
 ER_SP_NO DROP SP, 26
 ER_SP_NO_RECURSION, 30
 ER_SP_NO_RECURSIVE_CREATE, 23
 ER_SP_NO_RESET, 30
 ER_SP_NO_RECURSION_LIMIT, 32
 ER_SP_STORE_FAILED, 23
 ER_SP_SUBSELECT_NYI, 25
 ER_SP_UNDECLARED_VAR, 24
 ER_SP_UNINIT_VAR, 23
 ER_SP_VARCOND_AFTER_CURSHNDLR, 25
 ER_SP_WRONG_NAME, 32
 ER_SP_WRONG_NO_OF_ARGS, 24
 ER_SP_WRONG_NO_OF_FETCH_ARGS, 24
 ER_SQLTHREAD_WITH_SECURE_REPLICA, 51
 ER_SQL_AUTHOR_DEFAULT_ROLES_FAIL, 153
 ER_SQL_HA_READ_FAILED, 151
 ER_SQL_MODE_MERGED, 70
 ER_SQL_MODE_MERGED_WITH_STRICT_MODE, 191
 ER_SQL_REPLICA_SKIP_COUNTER_USED_WITH_GTID_M, 114
 ER_SQL_USER_TABLE ALTER WARNING, 153
 ER_SQL_USER_TABLE_CREATE WARNING, 153

ER_SRS_ATTRIBUTE_STRING_TOO_LONG, 91
ER_SRS_GEOGCS_INVALID_AXES, 92
ER_SRS_ID_ALREADY_EXISTS, 90
ER_SRS_INVALID_ANGULAR_UNIT, 93
ER_SRS_INVALID_CHARACTER_IN_ATTRIBUTE,
91
ER_SRS_INVALID_HEIGHT, 123
ER_SRS_INVALID_INVERSE_FLATTENING, 92
ER_SRS_INVALID_LATITUDE_OF_ORIGIN, 122
ER_SRS_INVALID_LATITUDE_POLAR_STERE_VAR_A,
123
ER_SRS_INVALID_LONGITUDE_OF_ORIGIN, 122
ER_SRS_INVALID_PRIME_MERIDIAN, 93
ER_SRS_INVALID_SCALING, 123
ER_SRS_INVALID_SEMI_MAJOR_AXIS, 92
ER_SRS_INVALID_ZONE_WIDTH, 123
ER_SRS_MISSING_MANDATORY_ATTRIBUTE, 90
ER_SRS_MULTIPLE_ATTRIBUTE_DEFINITIONS, 90
ER_SRS_NAME_CANT_BE_EMPTY_OR_WHITESPACE,
90
ER_SRS_NOT_CARTESIAN, 77
ER_SRS_NOT_CARTESIAN_UNDEFINED, 77
ER_SRS_NOT_FOUND, 79
ER_SRS_NOT_GEOGRAPHIC, 92
ER_SRS_ORGANIZATION_CANT_BE_EMPTY_OR_WHITESPACE,
90
ER_SRS_PARSE_ERROR, 77
ER_SRS_PROJ_PARAMETER_MISSING, 77
ER_SRS_UNUSED_PROJ_PARAMETER_PRESENT,
122
ER_SRV_END, 417
ER_SRV_INIT_END, 417
ER_SRV_INIT_START, 417
ER_SRV_START, 417
ER_SR_BOGUS_VALUE, 151
ER_SR_INVALID_CONTEXT, 151
ER_SSL_FIPS_MODE_ERROR, 218
ER_SSL_LIBRARY_ERROR, 141
ER_SSL_MEMORY_INSTRUMENTATION_INIT_FAILED,
349
ER_SSL_TRYING_DATADIR_DEFAULTS, 149
ER_STACKSIZE_UNEXPECTED, 149
ER_STACK_BACKTRACE, 405
ER_STACK_OVERRUN, 11
ER_STACK_OVERRUN_NEED_MORE, 31
ER_STARTING_AS, 145
ER_STARTING_INIT, 344
ER_STARTING_REPLICA_MONITOR_IO_THREAD,
114
ER_STARTUP, 29
ER_START_REPLICA_CHANNEL_INVALID_CONFIGURATION,
129
ER_START_REPLICA_CHANNEL_INVALID_CONFIGURATION,
419
ER_STATEMENT_NOT_ALLOWED_AFTER_START_TRANSACTION,
111
ER_STD_BAD_ALLOC_ERROR, 63
ER_STD_DOMAIN_ERROR, 63
ER_STD_INVALID_ARGUMENT, 64
ER_STD_LENGTH_ERROR, 63
ER_STD_LOGIC_ERROR, 64
ER_STD_OUT_OF_RANGE_ERROR, 64
ER_STD_OVERFLOW_ERROR, 64
ER_STD_RANGE_ERROR, 64
ER_STD_REGEX_ERROR, 102
ER_STD_RUNTIME_ERROR, 64
ER_STD_UNDERFLOW_ERROR, 64
ER_STD_UNKNOWN_EXCEPTION, 64
ER_STMT_CACHE_FULL, 47
ER_STMT_EXECUTION_NOT_ALLOWED_WITHIN_SP_OR_TRG,
135
ER_STMT_HAS_NO_OPEN_CURSOR, 30
ER_STMT_NOT_ALLOWED_IN_SF_OR_TRG, 25
ER_STOP_REPLICA_IO_THREAD_DISK_SPACE,
218
ER_STOP_REPLICA_IO_THREAD_TIMEOUT, 59
ER_STOP_REPLICA_MONITOR_IO_THREAD_TIMEOUT,
114
ER_STOP_REPLICA_SQL_THREAD_TIMEOUT, 59
ER_STORAGE_ENGINE_NOT_LOADED, 60
ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_DIRECT,
46
ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_FORMAT,
38
ER_STORED_FUNCTION_PREVENTS_SWITCH_SQL_LOG_BIN,
46
ER_SUBPARTITION_ERROR, 35
ER_SUBPARTITION_NAME, 42
ER_SUBQUERY_NO_1_ROW, 19
ER_SUBQUERY_TRANSFORM_REJECTED, 111
ER_SUPPORTED_ONLY_WITH_HYPERGRAPH,
130
ER_SWITCH_TMP_ENGINE, 81
ER_SYNTAX_ERROR, 13
ER_SYSTEMD_NOTIFY_CONNECT_FAILED, 257
ER_SYSTEMD_NOTIFY_DEBUG, 404
ER_SYSTEMD_NOTIFY_PATH_TOO_LONG, 257
ER_SYSTEMD_NOTIFY_WRITE_FAILED, 257
ER_SYSTEM_SCHEMA_NOT_FOUND, 138
ER_SYSTEM_TABLES_NOT_SUPPORTED_BY_STORAGE_ENGINE,
192
ER_SYSTEM_TABLE_NOT_TRANSACTIONAL, 178
ER_SYSTEM_VIEW_INIT_FAILED, 193
ER_SYSVAR_CHANGE_DURING_QUERY, 106
ER_SYSVAR_COMPONENT_FAILED_TO_MAKE_VARIABLE_PERSISTENT,
217
ER_SYSVAR_COMPONENT_FAILED_TO_PARSE_VARIABLE,
217

ER_SYS_VAR_COMPONENT_OOM, 217
 ER_SYS_VAR_COMPONENT_UNKNOWN_VARIABLE_TYPE, 217
 ER_SYS_VAR_COMPONENT_VARIABLE_SET_READ_ONLY, 217
 ER_SYS_VAR_DEREGISTRATION, 412
 ER_SYS_VAR_NOT_FOUND, 345
 ER_SYS_VAR_REGISTRATION, 412
 ER_TABLEACCESS_DENIED_ERROR, 13
 ER_TABLENAME_NOT_ALLOWED_HERE, 20
 ER_TABLESAMPLE_ONLY_ON_BASE_TABLES, 134
 ER_TABLESAMPLE_PERCENTAGE, 134
 ER_TABLESPACE_AUTO_EXTEND_ERROR, 37
 ER_TABLESPACE_CANNOT_BE_DECRYPTED, 100
 ER_TABLESPACE_CANNOT_BE_ENCRYPTED, 100
 ER_TABLESPACE_CANNOT_ENCRYPT, 74
 ER_TABLESPACE_DISCARDED, 55
 ER_TABLESPACE_DUP_FILENAME, 83
 ER_TABLESPACE_ENGINE_MISMATCH, 86
 ER_TABLESPACE_EXISTS, 55
 ER_TABLESPACE_IS_NOT_EMPTY, 69
 ER_TABLESPACE_MISSING, 55
 ER_TABLESPACE_MISSING_WITH_NAME, 76
 ER_TABLESPACE_TYPE_UNKNOWN, 100
 ER_TABLES_DIFFERENT_METADATA, 49
 ER_TABLE_CANT_HANDLE_AUTO_INCREMENT, 14
 ER_TABLE_CANT_HANDLE_BLOB, 14
 ER_TABLE_CANT_HANDLE_FT, 17
 ER_TABLE_CANT_HANDLE_SPKEYS, 33
 ER_TABLE_CHECK_INTACT, 150
 ER_TABLE_CORRUPT, 59
 ER_TABLE_CREATED_WITH_DIFFERENT_VERSION, 161
 ER_TABLE_DEF_CHANGED, 29
 ER_TABLE_EXISTS_ERROR, 6
 ER_TABLE_HAS_NO_FT, 51
 ER_TABLE_INCOMPATIBLE_DECIMAL_FIELD, 160
 ER_TABLE_INCOMPATIBLE_YEAR_FIELD, 161
 ER_TABLE_IN_FK_CHECK, 49
 ER_TABLE_IN_SHARED_TABLESPACE, 124
 ER_TABLE_IN_SYSTEM_TABLESPACE, 54
 ER_TABLE_MUST_HAVE_A_VISIBLE_COLUMN, 116
 ER_TABLE_MUST_HAVE_COLUMNS, 11
 ER_TABLE_NAME, 42
 ER_TABLE_NAME_CAUSES_TOO_LONG_PATH, 106
 ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED, 370
 ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_FK, 370
 ER_TABLE_NEEDS_DUMP_UPGRADE, 204
 ER_TABLE_NEEDS_REBUILD, 47
 ER_TABLE_NEEDS_UPGRADE, 32
 ER_TABLE_NOT_EMPTY, 124
 ER_TABLE_NOT_LOCKED, 10
 ER_TABLE_NOT_LOCKED_FOR_WRITE, 10
 ER_TABLE_NO_PRIMARY_KEY, 124
 ER_TABLE_REFERENCED, 75
 ER_TABLE_SCHEMA_MISMATCH, 54
 ER_TABLE_UPGRADE_REQUIRED, 192
 ER_TABLE_VALUE_CONSTRUCTOR_CANNOT_HAVE_DEFAULT, 108
 ER_TABLE_VALUE_CONSTRUCTOR_MUST_HAVE_COLUMNS, 108
 ER_TABLE_WITHOUT_PK, 93
 ER_TABLE_WRONG_KEY_DEFINITION, 161
 ER_TARGET_TABLESPACE_UNENCRYPTED, 100
 ER_TC_BAD_MAGIC_IN_TC_LOG, 170
 ER_TC_CANT_AUTO_RECOVER_WITH_TC_HEURISTIC_RECOVERY, 170
 ER_TC_HEURISTIC_RECOVERY_FAILED, 170
 ER_TC_HEURISTIC_RECOVERY_MODE, 170
 ER_TC_NEED_N_SE_SUPPORTING_2PC_FOR_RECOVERY, 170
 ER_TC_RECOVERING_AFTER_CRASH_USING, 170
 ER_TC_RECOVERY_FAILED_THESE_ARE_YOUR_OPTIONS, 170
 ER_TC_RESTART_WITHOUT_TC_HEURISTIC_RECOVERY, 170
 ER_TELEMETRY_ERROR, 417
 ER_TELEMETRY_INFO, 416
 ER_TELEMETRY_WARNING, 416
 ER_TEMPORARY_NAME, 42
 ER_TEMP_FILE_WRITE_FAILURE, 59
 ER_TEMP_TABLE_PREVENTS_SWITCH_GLOBAL_BINLOG, 93
 ER_TEMP_TABLE_PREVENTS_SWITCH_SESSION_BINLOG, 93
 ER_TEXTFILE_NOT_READABLE, 9
 ER_TF_FORBIDDEN_JOIN_TYPE, 88
 ER_TF_MUST_HAVE_ALIAS, 87
 ER_THE_USER_ABIDES, 146
 ER_THREAD_HANDLING_OOM, 143
 ER_THREAD_POOL_ALGORITHM_INVALID, 205
 ER_THREAD_POOL_BUFFER_TOO_SMALL, 206
 ER_THREAD_POOL_CANNOT_REGISTER_DYNAMIC_PRIVILEGES, 404
 ER_THREAD_POOL_CANNOT_SET_THREAD_SPECIFIC_DATA, 206
 ER_THREAD_POOL_CONNECTION_REPORT, 413
 ER_THREAD_POOL_CON_HANDLER_INIT_FAILED, 206
 ER_THREAD_POOL_DEDICATED_LISTENERS_INVALID, 397

ER_THREAD_POOL_FAILED_PROCESS_CONNECT_EVENT,	ER_TOO_LONG_BODY, 31
206	ER_TOO_LONG_FIELD_COMMENT, 42
ER_THREAD_POOL_FAILED_TO_CREATE_CONNECT_HANDLER,	ER_TOO_LONG_IDENT, 7
206	ER_TOO_LONG_INDEX_COMMENT, 46
ER_THREAD_POOL_FAILED_TO_CREATE_POOL,	ER_TOO_LONG_KEY, 8
206	ER_TOO_LONG_ROUTINE_COMMENT, 77
ER_THREAD_POOL_FAILED_TO_CREATE_THD_AND_AUTHCONN,	ER_TOO_LONG_SET_ENUM_VALUE, 76
206	ER_TOO_LONG_STRING, 14
ER_THREAD_POOL_IDLE_CONNECTION_CLOSED,	ER_TOO_LONG_TABLESPACE_COMMENT, 83
409	ER_TOO_LONG_TABLE_COMMENT, 42
ER_THREAD_POOL_INIT_FAILED, 206	ER_TOO_LONG_TABLE_PARTITION_COMMENT,
ER_THREAD_POOL_INVALID_PRIO_KICKUP_TIMER,	53
205	ER_TOO_MANY_CONCURRENT_TRXS, 42
ER_THREAD_POOL_INVALID_STALL_LIMIT, 205	ER_TOO_MANY_FIELDS, 11
ER_THREAD_POOL_LOW_LEVEL_REARM_FAILED,	ER_TOO_MANY_GROUP_BY_MODIFIER_BRANCHES,
206	129
ER_THREAD_POOL_MAX_UNUSED_THREADS_INVALID,	ER_TOO_MANY_KEYS, 8
205	ER_TOO_MANY_KEY_PARTS, 8
ER_THREAD_POOL_MTL_DISABLE, 427	ER_TOO_MANY_PARTITIONS_ERROR, 35
ER_THREAD_POOL_MTL_REENABLE, 427	ER_TOO_MANY_PARTITION_FUNC_FIELDS_ERROR,
ER_THREAD_POOL_NOT_SUPPORTED_ON_PLATFORM4,	44
205	ER_TOO_MANY_ROWS, 15
ER_THREAD_POOL_PFS_TABLES_ADD_FAILED,	ER_TOO_MANY_STORAGE_ENGINES, 153
351	ER_TOO_MANY_TABLES, 11
ER_THREAD_POOL_PFS_TABLES_INIT_FAILED,	ER_TOO_MANY_USER_CONNECTIONS, 16
351	ER_TOO_MANY_VALUES_ERROR, 44
ER_THREAD_POOL_PLUGIN_STARTED, 397	ER_TOO_MANY_WINDOWS, 120
ER_THREAD_POOL_QUERY_THREADS_PER_GROUP_INVALID,	INVALID_VECTOR_CONVERSION, 136
405	ER_TP_CANNOT_DISABLE_MTL_WITH_DL, 137
ER_THREAD_POOL_QUERY_THRS_PER_GRP_EXCEEDS_TXN_QUERY_LIMIT,	ER_TXN_QUERY_THRS_PER_GRP_EXCEEDS_TXN_THR_LIMIT,
405	123
ER_THREAD_POOL_RATE_LIMITED_ERROR_MSGS,	ER_TRACK_VARIABLES_BOGUS, 147
206	ER_TRANSACTION_ROLLBACK_DURING_COMMIT,
ER_THREAD_POOL_SIZE_TOO_HIGH, 205	68
ER_THREAD_POOL_SIZE_TOO_LOW, 205	ER_TRANSFORM_SOURCE_SRS_MISSING_TOWGS84,
ER_THREAD_POOL_SYSVAR_CHANGE, 405	93
ER_THREAD_PRIORITY_IGNORED, 190	ER_TRANSFORM_SOURCE_SRS_NOT_SUPPORTED,
ER_THREAD_STILL_ALIVE, 417	93
ER_TLS_CONFIGURATION_REUSED, 376	ER_TRANSFORM_TARGET_SRS_MISSING_TOWGS84,
ER_TLS_CONFIGURED_FOR_CHANNEL, 375	93
ER_TLS_LIBRARY_ERROR_INTERNAL, 416	ER_TRANSFORM_TARGET_SRS_NOT_SUPPORTED,
ER_TMPDIR_PATH_TOO_LONG, 380	93
ER_TMP_SESSION_FOR_VAR, 404	ER_TRANSPORTS_WHAT_TRANSPORTS, 145
ER_TOO_BIG_DISPLAYWIDTH, 31	ER_TRANS_CACHE_FULL, 16
ER_TOO_BIG_ENUM, 76	ER_TREE_CORRUPT_2_CONSECUTIVE_REDS,
ER_TOO_BIG_FIELDLENGTH, 8	177
ER_TOO_BIG_FOR_UNCOMPRESS, 20	ER_TREE_CORRUPT_INCORRECT_BLACK_COUNT,
ER_TOO_BIG_PRECISION, 30	177
ER_TOO_BIG_ROW_SIZE, 11	ER_TREE_CORRUPT_PARENT_SHOULD_POINT_AT_PARENT,
ER_TOO_BIG_SCALE, 30	177
ER_TOO_BIG_SELECT, 10	ER_TREE_CORRUPT_RIGHT_IS_LEFT, 177
ER_TOO_BIG_SET, 10	ER_TREE_CORRUPT_ROOT_SHOULD_BE_BLACK,
ER_TOO_HIGH_LEVEL_OF_NESTING_FOR_SELECT,	177
33	ER_TRG_ALREADY_EXISTS, 26

ER_TRG_CANT_CHANGE_ROW, 27
 ER_TRG_CANT_OPEN_TABLE, 41
 ER_TRG_CANT_PARSE, 150
 ER_TRG_CORRUPTED_FILE, 40
 ER_TRG_CREATION_CTX_NOT_SET, 192
 ER_TRG_DOES_NOT_EXIST, 26
 ER_TRG_INVALID_CREATION_CTX, 40
 ER_TRG_IN_WRONG_SCHEMA, 31
 ER_TRG_NO_CLIENT_CHARSET, 141
 ER_TRG_NO_CREATION_CTX, 40
 ER_TRG_NO_DEFINER, 32
 ER_TRG_NO_SUCH_ROW_IN_TRG, 27
 ER_TRG_ON_VIEW_OR_TEMP_TABLE, 27
 ER_TRG_WITHOUT_DEFINER, 141
 ER_TRG_WRONG_ORDER, 356
 ER_TRHEAD_POOL_LOW_LEVEL_INIT_FAILED, 206
 ER_TRIGGER_INVALID_VALUE, 137
 ER_TRUNCATED_WRONG_VALUE, 22
 ER_TRUNCATED_WRONG_VALUE_FOR_FIELD, 27
 ER_TRUNCATE_ILLEGAL_FK, 47
 ER_TRX_GTID_COLLECT_REJECT, 153
 ER_TRX_WRITE_SET_OOM, 153
 ER_TURNING_LOGGING_OFF_FOR_THE_DURATION, 188
 ER_TURNING_ON_PARTIAL_REVOKES, 358
 ER_TZ_CANT_BUILD_MKTIME_MAP, 163
 ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE, 162
 ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE_ID, 162
 ER_TZ_CANT_OPEN_AND_LOCK_TIME_ZONE_TABLE, 162
 ER_TZ_ERROR_LOADING_LEAP_SECOND_TABLE, 162
 ER_TZ_NO_TRANSITION_TYPES_IN_TIME_ZONE, 163
 ER_TZ_OOM_INITIALIZING_TIME_ZONES, 161
 ER_TZ_OOM_LOADING_LEAP_SECOND_TABLE, 162
 ER_TZ_OOM_LOADING_TIME_ZONE_DESCRIPTION, 163
 ER_TZ_OOM_WHILE_LOADING_TIME_ZONE, 163
 ER_TZ_OOM_WHILE_SETTING_TIME_ZONE, 163
 ER_TZ_TOO_MANY_LEAPS_IN_LEAP_SECOND_TABLE, 162
 ER_TZ_TRANSITION_TABLE_BAD_TRANSITION_TYPE, 163
 ER_TZ_TRANSITION_TABLE_LOAD_ERROR, 163
 ER_TZ_TRANSITION_TABLE_TOO_MANY_TRANSITIONS, 162
 ER_TZ_TRANSITION_TYPE_TABLE_ABBREVIATIONS_EXCEEDS_SPACE, 162
 ER_TZ_TRANSITION_TYPE_TABLE_LOAD_ERROR, 162
 ER_TZ_TRANSITION_TYPE_TABLE_TYPE_TOO_LARGE, 162
 ER_TZ_UNKNOWN_OR_ILLEGAL_DEFAULT_TIME_ZONE, 162
 ER_UDF_ALREADY_EXISTS, 345
 ER_UDF_CANT_ALLOC_FOR_FUNCTION, 152
 ER_UDF_CANT_ALLOC_FOR_STRUCTURES, 152
 ER_UDF_CANT_OPEN_FUNCTION_TABLE, 152
 ER_UDF_DEREGISTRATION, 412
 ER_UDF_DROP_DYNAMICALLY_REGISTERED, 84
 ER_UDF_ERROR, 75
 ER_UDF_EXEC_FAILURE, 412
 ER_UDF_EXEC_FAILURE_REASON, 412
 ER_UDF_EXISTS, 12
 ER_UDF_INVALID_ROW_IN_FUNCTION_TABLE, 152
 ER_UDF_NO_PATHS, 12
 ER_UDF_REGISTER_ERROR, 380
 ER_UDF_REGISTER_SERVICE_ERROR, 380
 ER_UDF_REGISTRATION, 412
 ER_UDF_UNREGISTER_ERROR, 380
 ER_UNKNOWN_AUTH_ID_OR_ACCESS_DENIED_FOR_GRANT, 100
 ER_UNABLE_TO_BUILD_HISTOGRAM, 85
 ER_UNABLE_TO_COLLECT_LOG_STATUS, 91
 ER_UNABLE_TO_DROP_COLUMN_STATISTICS, 85
 ER_UNABLE_TO_RESOLVE_HOSTNAME, 140
 ER_UNABLE_TO_RESOLVE_IP, 140
 ER_UNABLE_TO_SET_OPTION, 91
 ER_UNABLE_TO_STORE_COLUMN_STATISTICS, 84
 ER_UNABLE_TO_STORE_STATISTICS, 79
 ER_UNABLE_TO_UPDATE_COLUMN_STATISTICS, 85
 ER_UNDISCLOSED_PARSE_ERROR_IN_DIGEST_FN, 88
 ER_UNDO_RECORD_TOO_BIG, 48
 ER_UNEXPECTED_GEOMETRY_TYPE, 77
 ER_UNIQUE_KEY_NEED_ALL_FIELDS_IN_PF, 35
 ER_UNIT_NOT_FOUND, 105
 ER_UNKNOWN_ALTER_ALGORITHM, 54
 ER_UNKNOWN_ALTER_LOCK, 54
 ER_UNKNOWN_AUTHID, 77
 ER_UNKNOWN_AUTH_ID_IN_MANDATORY_ROLE, 195
 ER_UNKNOWN_CHARACTER_SET, 11
 ER_UNKNOWN_COLLATION, 21
 ER_UNKNOWN_COM_ERROR, 6
 ER_UNKNOWN_ERROR, 10
 ER_UNKNOWN_ERROR_DETECTED_IN_SE, 199
 ER_UNKNOWN_ERROR_NUMBER, 152
 ER_UNKNOWN_EXPLAIN_FORMAT, 53

ER_UNKNOWN_KEY_CACHE, 22
ER_UNKNOWN_LOCALE, 43
ER_UNKNOWN_NETWORK_NAMESPACE, 361
ER_UNKNOWN_PARTITION, 49
ER_UNKNOWN_PROCEDURE, 10
ER_UNKNOWN_STMT_HANDLER, 19
ER_UNKNOWN_STORAGE_ENGINE, 22
ER_UNKNOWN_SYSTEM_VARIABLE, 16
ER_UNKNOWN_TABLE, 10
ER_UNKNOWN_TABLESPACE_TYPE, 349
ER_UNKNOWN_TABLE_IN_UPGRADE, 366
ER_UNKNOWN_TARGET_BINLOG, 27
ER_UNKNOWN_TIME_ZONE, 22
ER_UNKNOWN_UNSUPPORTED_STORAGE_ENGINE, 142
ER_UNKNOWN_VARIABLE_IN_PERSISTED_CONFIG_FILE, 345
ER_UNRESOLVED_HINT_NAME, 70
ER_UNRESOLVED_TABLE_LOCK, 80
ER_UNSUPPORTED_LOG_ENGINE, 39
ER_UNSUPPORTED_ACTION_ON_DEFAULT_VAL_GENERATED, 95
ER_UNSUPPORTED_ACTION_ON_GENERATED_COLUMN, 68
ER_UNSUPPORTED_ALTER_ENCRYPTION_INPLACE, 74
ER_UNSUPPORTED_ALTER_INPLACE_ON_VIRTUAL_COLUMN, 68
ER_UNSUPPORTED_ALTER_ONLINE_ON_VIRTUAL_COLUMN, 74
ER_UNSUPPORTED_DATE, 145
ER_UNSUPPORTED_ENGINE, 49
ER_UNSUPPORTED_EXTENSION, 11
ER_UNSUPPORTED_INDEX_ALGORITHM, 76
ER_UNSUPPORTED_PS, 22
ER_UNSUPPORTED_SQL_MODE, 105
ER_UNSUPPORTED_USE_OF_GRANT_AS, 100
ER_UNSUPPORTED_COMPRESSED_TEMPORARY_TABLE, 76
ER_UNTIL_COND_IGNORED, 21
ER_UPDATE_GTID_PURGED_WITH_GR, 106
ER_UPDATE_INFO, 12
ER_UPDATE_LOG_DEPRECATED_IGNORED, 24
ER_UPDATE_LOG_DEPRECATED_TRANSLATED, 24
ER_UPDATE_TABLE_USED, 9
ER_UPDATE_WITHOUT_KEY_IN_SAFE_MODE, 15
ER_UPDATING_DD_TABLE, 76
ER_UPGRADE_NONEXISTENT_SCHEMA, 380
ER_UPGRADE_PARSE_ERROR, 349
ER_USAGE_DEPRECATION_COUNTER, 415
ER_USERNAME, 33
ER_USERNAME_TRUNCATED, 376
ER_USER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED, 109
ER_USER_ALREADY_EXISTS, 73
ER_USER_COLUMN_OLD_LENGTH, 74
ER_USER_DOES_NOT_EXIST, 73
ER_USER_LIMIT_REACHED, 18
ER_USER_LOCK_DEADLOCK, 64
ER_USER_LOCK_OVERLONG_NAME, 126
ER_USER_LOCK_WRONG_NAME, 64
ER_USER_NOT_IN_EXTRA_USERS_BINLOG_POSSIBLY_INCORRECTLY_DELETED, 160
ER_USER_REFERENCED_AS_DEFINER, 113
ER_USER_REGISTRATION_FAILED, 118
ER_USER_REQUIRES_ROOT, 145
ER_USER_WHAT_USER, 145
ER_USING_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTION_FAILED, 115
ER_UUID_INVALID, 142
ER_UUID_IS, 142
ER_UUID_SALT, 142
ER_UUID_SCRUB, 142
ER_VALGRIND_COUNT_LEAKS, 152
ER_VALGRIND_DO_QUICK_LEAK_CHECK, 151
ER_VALIDATE_PASSWORD_INSUFFICIENT_CHANGED_CHARACTERS, 127
ER_VALIDATE_PWD_CONVERT_TO_BUFFER_FAILED, 258
ER_VALIDATE_PWD_COULD_BE_NULL, 258
ER_VALIDATE_PWD_DICT_FILE_NOT_LOADED, 215
ER_VALIDATE_PWD_DICT_FILE_NOT_SPECIFIED, 215
ER_VALIDATE_PWD_DICT_FILE_OPEN_FAILED, 258
ER_VALIDATE_PWD_DICT_FILE_TOO_BIG, 215
ER_VALIDATE_PWD_FAILED_TO_GET_FLD_FROM_SECURITY_CONTEXT, 215
ER_VALIDATE_PWD_FAILED_TO_GET_SECURITY_CTX, 215
ER_VALIDATE_PWD_FAILED_TO_READ_DICT_FILE, 215
ER_VALIDATE_PWD_LENGTH_CHANGED, 216
ER_VALIDATE_PWD_STATUS_VAR_REGISTRATION_FAILED, 258
ER_VALIDATE_PWD_STATUS_VAR_UNREGISTRATION_FAILED, 258
ER_VALIDATE_PWD_STRING_CONV_TO_BUFFER_FAILED, 258
ER_VALIDATE_PWD_STRING_CONV_TO_LOWERCASE_FAILED, 258
ER_VALIDATE_PWD_STRING_HANDLER_MEM_ALLOCATION_FAILED, 258
ER_VALIDATE_PWD_STRONG_POLICY_DICT_FILE_UNSPECIFIED, 258

ER_VALIDATE_PWD_VARIABLE_REGISTRATION_FAILED, 258	ER_WARNING_PASSWORD_HISTORY_CLAUSES_VOID, 86
ER_VALIDATE_PWD_VARIABLE_UNREGISTRATION_FAILED, 259	ER_WARNING_RETAIN_CURRENT_PASSWORD_CLAUSE, 353
ER_VALUES_IS_NOT_INT_TYPE_ERROR, 47	ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS, 117
ER_VALUE_OUT_OF_RANGE, 119	ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS, 389
ER_VARIABLE_IS_NOT_STRUCT, 21	ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE_SECONDS, 117
ER_VARIABLE_IS_READONLY, 41	ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE_SECONDS, 389
ER_VARIABLE_NOT_PERSISTED, 79	ER_WARN_ALLOWED_PACKET_OVERFLOWED, 23
ER_VARIABLE_NOT_SETTABLE_IN_SF_OR_TRIGGER, 51	ER_WARN_ASYNC_CONN_FAILOVER_NETWORK_NAMES, 116
ER_VARIABLE_NOT_SETTABLE_IN_SP, 56	ER_WARN_AUDIT_LOG_DISABLED, 395
ER_VARIABLE_NOT_SETTABLE_IN_TRANSACTION, 51	ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_ONLY_DISABLED, 117
ER_VAR_CANT_BE_READ, 19	ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_ONLY_DISABLED, 390
ER_VAR_DOES_NOT_EXIST, 84	ER_WARN_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANAGED_USERS, 368
ER_VERBOSE_HINT, 147	ER_WARN_BAD_MAX_EXECUTION_TIME, 69
ER_VERBOSE_REQUIRES_HELP, 142	ER_WARN_BINLOG_PARTIAL_UPDATES_DISABLED, 86
ER_VIEW_CHECKSUM, 28	ER_WARN_BINLOG_PARTIAL_UPDATES_SUGGESTS_PARTIAL_UPDATES_ENABLED, 86
ER_VIEW_CHECK_FAILED, 27	ER_WARN_CANNOT_FREE_COMPONENT_DATA_DEALLOCATED, 411
ER_VIEW_CREATION_CTX_NOT_SET, 192	ER_WARN_CANNOT_PERSIST_SENSITIVE_VARIABLES, 396
ER_VIEW_DELETE_MERGE_VIEW, 28	ER_WARN_CANNOT_SECURELY_PERSIST_SENSITIVE_VARIABLES, 121
ER_VIEW_FRM_NO_USER, 32	ER_WARN_CANT_DROP_DEFAULT_KEYCACHE, 31
ER_VIEW_INVALID, 26	ER_WARN_CANT_OPEN_CERTIFICATE, 416
ER_VIEW_INVALID_CREATION_CTX, 40	ER_WARN_CA_CERT_VERIFY_FAILED, 416
ER_VIEW_MULTIUPDATE, 28	ER_WARN_CERTIFICATE_ERROR_STRING, 416
ER_VIEW_NONUPD_CHECK, 27	ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFESTATION_FAILURE, 410
ER_VIEW_NO_CREATION_CTX, 40	ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFESTATION_FAILURE, 384
ER_VIEW_NO_EXPLAIN, 26	ER_WARN_COMPONENT_KEYRING_OCI_DUPLICATE_KEYS, 405
ER_VIEW_NO_INSERT_FIELD_LIST, 28	ER_WARN_CONFLICTING_HINT, 70
ER_VIEW_OTHER_USER, 32	ER_WARN_C_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO_POSITION, 10
ER_VIEW_PREVENT_UPDATE, 31	ER_WARN_DATA_OUT_OF_RANGE, 20
ER_VIEW_RECURSIVE, 33	ER_WARN_DATA_OUT_OF_RANGE_FUNCTIONAL_INDEX_CREATED_TEMP_TABLE, 50
ER_VIEW_SELECT_CLAUSE, 26	ER_WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX_CREATED_TEMP_TABLE, 50
ER_VIEW_SELECT_TMPTABLE, 26	
ER_VIEW_SELECT_VARIABLE, 26	
ER_VIEW_UNKNOWN_CHARSET_OR_COLLATION, 138	
ER_VIEW_UNPARSABLE, 161	
ER_VIEW_WRONG_LIST, 26	
ER_VTOKEN_PLUGIN_TOKEN_MISMATCH, 70	
ER_VTOKEN_PLUGIN_TOKEN_NOT_FOUND, 71	
ER_WAITING_FOR_NO_CONNECTIONS, 415	
ER_WAITING_FOR_NO_THDS, 415	
ER_WAITPID_FAILED, 202	
ER_WARNING_AUTHCACHE_INVALID_USER_ATTRIBUTES, 353	
ER_WARNING_DISCARD_OLD_PASSWORD_CLAUSE_VOID, 353	
ER_WARNING_NOT_COMPLETE_ROLLBACK, 16	
ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_CREATED_TEMP_TABLE, 50	
ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_DROPPED_TEMP_TABLE, 50	

ER_WARN_DA_PRIVILEGE_NOT_REGISTERED, 107	ER_WARN_DEPRECATED_UTF8MB3_COLLATION_OPTION, 349
ER_WARN_DEPRECATED_CHARSET_OPTION, 395	ER_WARN_DEPRECATED_UTF8_ALIAS_OPTION, 349
ER_WARN_DEPRECATED_CLIENT_NO_SCHEMA_OPTION, 124	ER_WARN_DEPRECATED_VALUES_FUNCTION_ALWAYS_NULL, 110
ER_WARN_DEPRECATED_COLLATION, 120	ER_WARN_DEPRECATED_WITH_NOTE, 127
ER_WARN_DEPRECATED_COLLATION_OPTION, 395	ER_WARN_DEPRECATED_YEAR_UNSIGNED, 109
ER_WARN_DEPRECATED_DATETIME_DELIMITER, 121	ER_WARN_DEPRECATED_ZEROFILL, 102
ER_WARN_DEPRECATED_DYNAMIC_PRIV_FOR_USER, 418	ER_WARN_ENGINE_TRANSACTION_ROLLBACK, 41
ER_WARN_DEPRECATED_DYNAMIC_PRIV_IN_GRANT, 128	ER_WARN_FAILED_TO_SETUP_TLS, 416
ER_WARN_DEPRECATED_ENGINE_SYNTAX_NO_REPLACEMENT, 129	ER_WARN_FIELD_RESOLVED, 21
ER_WARN_DEPRECATED_FLOAT_AUTO_INCREMENT, 102	ER_WARN_FUNC_INDEX_NOT_APPLICABLE, 106
ER_WARN_DEPRECATED_FLOAT_DIGITS, 102	ER_WARN_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE, 359
ER_WARN_DEPRECATED_FLOAT_UNSIGNED, 102	ER_WARN_GTID_THRESHOLD_BREACH, 382
ER_WARN_DEPRECATED_FOUND_ROWS, 110	ER_WARN_HOSTNAME_WONT_WORK, 22
ER_WARN_DEPRECATED_IDENT, 123	ER_WARN_HYPERGRAPH_EXPERIMENTAL, 113
ER_WARN_DEPRECATED_INNER_INTO, 110	ER_WARN_INCORRECT_PRIVILEGE_FOR_DB_RESTRICTIONS, 359
ER_WARN_DEPRECATED_INTEGER_DISPLAY_WIDTH, 102	ER_WARN_INDEX_NOT_APPLICABLE, 50
ER_WARN_DEPRECATED_JSON_TABLE_ON_ERROR_OPTION, 110	ER_WARN_INVALID_DB_RESTRICTIONS, 359
ER_WARN_DEPRECATED_NESTED_COMMENT_SYNTAX, 96	ER_WARN_INVALID_HINT, 84
ER_WARN_DEPRECATED_NON_STANDARD_KEY, 135	ER_WARN_INVALID_TIMESTAMP, 23
ER_WARN_DEPRECATED_OR_BLOCKED_CIPHER, 414	ER_WARN_I_S_SKIPPED_TABLE, 46
ER_WARN_DEPRECATED_SQLMODE, 67	ER_WARN_INVALID_LANGUAGE_COMPONENT_CANNOT_UNINSTALL, 424
ER_WARN_DEPRECATED_SQL_CALC_FOUND_ROWS, 110	ER_WARN_INVALID_RESOURCE_LIMIT, 425
ER_WARN_DEPRECATED_SUPERFLUOUS_DELIMITER, 121	ER_WARN_LEGACY_SYNTAX_CONVERTED, 60
ER_WARN_DEPRECATED_SYNTAX, 22	ER_WARN_LOG_DEPRECATED_NON_STANDARD_KEY, 427
ER_WARN_DEPRECATED_SYNTAX_NO_REPLACEMENT, 45	ER_WARN_LOG_PRIVILEGE_CHECKS_USER_CORRUPT, 367
ER_WARN_DEPRECATED_SYNTAX_WITH_VER, 38	ER_WARN_LOG_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST, 367
ER_WARN_DEPRECATED_SYSVAR_UPDATE, 67	ER_WARN_LOG_PRIVILEGE_CHECKS_USER_NEEDS_RPL_APPLICABLE, 367
ER_WARN_DEPRECATED_USER_DEFINED_COLLATION, 126	ER_WARN_L_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO_POSITION, 393
ER_WARN_DEPRECATED_USER_DEFINED_COLLATION_OPTION, 410	ER_WARN_MIGRATION_EMPTY_SOURCE_KEYRING, 396
ER_WARN_DEPRECATED_USER_SET_EXPR, 96	ER_WARN_NO_KEYRING_COMPONENT_SERVICE_FOUND, 384
ER_WARN_DEPRECATED_UTF8MB3_CHARSET_OPTION, 349	ER_WARN_NO_SERVERID_SPECIFIED, 191
ER_WARN_DEPRECATED_UTF8MB3_COLLATION, 96	ER_WARN_NO_SPACE_VERSION_COMMENT, 126
	ER_WARN_NO_TABLESPACE_OPTION, NULL_TO_NOTNULL, 20
	ER_WARN_ONLY_SOURCE_LOG_FILE_NO_POS, 62
	ER_WARN_ON_MODIFYING_GTID_EXECUTED_TABLE, 70
	ER_WARN_OPEN_TEMP_TABLES_MUST_BE_ZERO, 62

ER_WARN_OPTIMIZER_HINT_SYNTAX_ERROR, 69	ER_WINDOW_CIRCULARITY_IN_WINDOW_GRAPH,
ER_WARN_OPTION_RESET_AND_IGNORED_DURING_INITIALIZE,	INITIALIZE,
418	ER_WINDOW_DUPLICATE_NAME, 82
ER_WARN_PARTIAL_REVOKE_AND_DB_GRANT,	ER_WINDOW_EXPLAIN_JSON, 83
359	ER_WINDOW_FRAME_END_ILLEGAL, 82
ER_WARN_PROPERTY_STRING_PARSE_FAILED,	ER_WINDOW_FRAME_ILLEGAL, 82
355	ER_WINDOW_FRAME_START_ILLEGAL, 82
ER_WARN_PURGE_LOG_IN_USE, 58	ER_WINDOW_FUNCTION_IGNORES_FRAME, 83
ER_WARN_PURGE_LOG_IS_ACTIVE, 58	ER_WINDOW_ILLEGAL_ORDER_BY, 82
ER_WARN_REGEX_USING_DEFAULT, 120	ER_WINDOW_INVALID_WINDOW_FUNC_ALIAS_USE,
ER_WARN_REMOVED_SQL_MODE, 350	82
ER_WARN_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_WINDOW_CHANGEWINDOW_FUNC_USE, 82	ER_WINDOW_INVALID_WINDOW_FUNC_USE, 82
388	ER_WINDOW_NESTED_WINDOW_FUNC_USE_IN_WINDOW
ER_WARN_REPLICA_GTID_ONLY_AND_GTID_MODE_NOT_ON,	NOT_ON,
393	ER_WINDOW_NO_CHILD_PARTITIONING, 81
ER_WARN_RESERVED_SRID_RANGE, 91	ER_WINDOW_NO_GROUP_ORDER_UNUSED, 83
ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SOURCE,	ER_WINDOW_NO_INHERIT_FRAME, 82
368	ER_WINDOW_NO_REDEFINE_ORDER_BY, 82
ER_WARN_SCHEDULED_TASK_RUN_FAILED, 413	ER_WINDOW_NO_SUCH_WINDOW, 81
ER_WARN_SF_UDF_NAME_COLLISION, 120	ER_WINDOW_RANGE_BOUND_NOT_CONSTANT,
ER_WARN_SP_STATEMENT_PARTIALLY_EXECUTED,	82
135	ER_WINDOW_RANGE_FRAME_NUMERIC_TYPE,
ER_WARN_SQL_AFTER_MTS_GAPS_GAP_NOT_CALCULATED,	NOT,
117	ER_WINDOW_RANGE_FRAME_ORDER_TYPE, 82
ER_WARN_SRS_ID_ALREADY_EXISTS, 91	ER_WINDOW_RANGE_FRAME_TEMPORAL_TYPE,
ER_WARN_SRS_NOT_FOUND, 77	82
ER_WARN_SRS_NOT_FOUND_AXIS_ORDER, 80	ER_WINDOW_ROWS_INTERVAL_USE, 83
ER_WARN_TLS_CHANNEL_INITIALIZATION_ERROR,	ER_WIN_LISTEN_BUT_HOW, 146
375	ER_WIN_LOAD_LIBRARY_FAILED, 202
ER_WARN_TOO_FEW_RECORDS, 20	ER_WL9236_NOW_UNUSED, 83
ER_WARN_TOO_MANY_RECORDS, 20	ER_WRITABLE_CONFIG_REMOVED, 144
ER_WARN_TRG_ALREADY_EXISTS, 121	ER_WRITE_ROW_TO_PARTITION_FAILED, 195
ER_WARN_TRIGGER_DOESNT_HAVE_CREATED,	ER_WRITE_SET_EXCEEDS_LIMIT, 75
61	ER_WRONG_ARGUMENTS, 17
ER_WARN_UNKNOWN_KEYRING_AWS_REGION,	ER_WRONG_AUTO_KEY, 8
367	ER_WRONG_COLUMN_NAME, 14
ER_WARN_UNKNOWN_QB_NAME, 70	ER_WRONG_COMPRESSION_ALGORITHM_CLIENT,
ER_WARN_UNLOAD_THE_NOT_PERSISTED, 79	107
ER_WARN_UNSUPPORTED_HINT, 77	ER_WRONG_COMPRESSION_LEVEL_CLIENT, 107
ER_WARN_UNSUPPORTED_MAX_EXECUTION_TIME,	ER_WRONG_COUNT_FOR_KEY, 178
70	ER_WRONG_COUNT_FOR_ORIGIN, 178
ER_WARN_USING_OTHER_HANDLER, 21	ER_WRONG_COUNT_OF_ELEMENTS, 178
ER_WARN_VAR_VALUE_CHANGE_NOT_SUPPORTED,	ER_WRONG_DATETIME_SPEC, 144
113	ER_WRONG_DB_NAME, 10
ER_WARN_VIEW_MERGE, 26	ER_WRONG_EXPR_IN_PARTITION_FUNC_ERROR,
ER_WARN_VIEW_WITHOUT_KEY, 26	34
ER_WARN_WRONG_COMPRESSION_ALGORITHM_LOGGER_WRONG_FIELD_SPEC, 7	ER_WRONG_FIELD_SPEC, 7
367	ER_WRONG_FIELD_TERMINATORS, 9
ER_WARN_WRONG_COMPRESSION_LEVEL_LOG,	ER_WRONG_FIELD_WITH_GROUP, 7
367	ER_WRONG_FIELD_WITH_GROUP_V2, 66
ER_WASTEFUL_NET_BUFFER_SIZE, 142	ER_WRONG_FILE_NAME, 69
ER_WILDCARD_NOT_ALLOWED_FOR_MULTIADDRESS_AND_WRONG_FK_DEF, 19	ER_WRONG_FK_DEF, 19
361	ER_WRONG_FK_OPTION_FOR_GENERATED_COLUMN,
	68

ER_WRONG_GROUP_FIELD, 7
 ER_WRONG_JSON_TABLE_VALUE, 87
 ER_WRONG_KEY_COLUMN, 14
 ER_WRONG_KEY_COLUMN_FUNCTIONAL_INDEX, 94
 ER_WRONG_LOCK_OF_SYSTEM_TABLE, 30
 ER_WRONG_MRG_TABLE, 14
 ER_WRONG_MVI_VALUE, 106
 ER_WRONG_NAME_FOR_CATALOG, 21
 ER_WRONG_NAME_FOR_INDEX, 21
 ER_WRONG_NATIVE_TABLE_STRUCTURE, 45
 ER_WRONG_NUMBER_OF_COLUMNS_IN_SELECT, 18
 ER_WRONG_OBJECT, 26
 ER_WRONG_OUTER_JOIN_UNUSED, 11
 ER_WRONG_PARAMCOUNT_TO_NATIVE_FCT, 39
 ER_WRONG_PARAMCOUNT_TO_PROCEDURE, 10
 ER_WRONG_PARAMETERS_TO_NATIVE_FCT, 39
 ER_WRONG_PARAMETERS_TO_PROCEDURE, 10
 ER_WRONG_PARAMETERS_TO_STORED_FCT, 39
 ER_WRONG_PARTITION_NAME, 39
 ER_WRONG_PERFSCHEMA_USAGE, 46
 ER_WRONG_SIZE_NUMBER, 37
 ER_WRONG_SRID_FOR_COLUMN, 86
 ER_WRONG_STRING_LENGTH, 33
 ER_WRONG_SUB_KEY, 9
 ER_WRONG_SUM_SELECT, 7
 ER_WRONG_TABLESPACE_NAME, 69
 ER_WRONG_TABLE_NAME, 10
 ER_WRONG_TYPE_COLUMN_VALUE_ERROR, 43
 ER_WRONG_TYPE_FOR_COLUMN_PREFIX_IDX_FLD, 201
 ER_WRONG_TYPE_FOR_VAR, 18
 ER_WRONG_USAGE, 18
 ER_WRONG_VALUE, 37
 ER_WRONG_VALUE_COUNT, 7
 ER_WRONG_VALUE_COUNT_ON_ROW, 12
 ER_WRONG_VALUE_FOR_TYPE, 29
 ER_WRONG_VALUE_FOR_VAR, 18
 ER_WRONG_VALUE_FOR_VAR_PLUS_ACTIONABLE_PART, 111
 ER_X509_CANT_CHMOD_KEY, 157
 ER_X509_CANT_CREATE_CERT, 157
 ER_X509_CANT_READ_CA_CERT, 157
 ER_X509_CANT_READ_CA_KEY, 157
 ER_X509_CANT_WRITE_CERT, 157
 ER_X509_CANT_WRITE_KEY, 157
 ER_X509_CIPHERS_MISMATCH, 156
 ER_X509_ISSUER_MISMATCH, 156
 ER_X509_NEEDS_RSA_PRIVKEY, 157
 ER_X509_SUBJECT_MISMATCH, 157
 ER_XAER_DUPID, 31
 ER_XAER_INVALID, 28
 ER_XAER_NOTA, 28
 ER_XAER_OUTSIDE, 29
 ER_XAER_RMERR, 29
 ER_XAER_RMFAIL, 29
 ER_XA_CANT_CREATE_MDL_BACKUP, 366
 ER_XA_NO_MULTI_2PC_HEURISTIC_RECOVER, 152
 ER_XA_RBDEADLOCK, 41
 ER_XA_RBROLLBACK, 29
 ER_XA_RBTIMEOUT, 41
 ER_XA_RECOVERY_DONE, 152
 ER_XA_RECOVER_EXPLANATION, 152
 ER_XA_RECOVER_FOUND_TRX_IN_SE, 152
 ER_XA_RECOVER_FOUND_XA_TRX, 152
 ER_XA_REPLICATION_FILTERS, 105
 ER_XA_RETRY, 75
 ER_XA_STARTING_RECOVERY, 152
 ER_XA_TEMP_TABLE, 121
 ER_XPLUGIN_ALL_IO_INTERFACES_DISABLED, 221
 ER_XPLUGIN_BUFFER_PAGE_ALLOC_FAILED, 219
 ER_XPLUGIN_CLIENT_KILL_MSG, 221
 ER_XPLUGIN_COMPRESSION_ERROR, 367
 ER_XPLUGIN_DETECTED_HANGING_CLIENTS, 219
 ER_XPLUGIN_EMPTY_ADMIN_CMD, 222
 ER_XPLUGIN_ERROR_MSG, 216
 ER_XPLUGIN_ERROR_READING_SOCKET, 221
 ER_XPLUGIN_EXCEPTION_IN_EVENT_LOOP, 220
 ER_XPLUGIN_EXCEPTION_IN_TASK_SCHEDULER, 220
 ER_XPLUGIN_EXISTING_USER_ACCOUNT_WITH_INCOMPLETE, 221
 ER_XPLUGIN_FAILED_AT_SSL_CONF, 220
 ER_XPLUGIN_FAILED_TO_ACCEPT_CLIENT, 219
 ER_XPLUGIN_FAILED_TO_BIND_INTERFACE_ADDRESS, 375
 ER_XPLUGIN_FAILED_TO_CLOSE_SQL_SESSION, 222
 ER_XPLUGIN_FAILED_TO_CREATE_SESSION_FOR_CONN, 220
 ER_XPLUGIN_FAILED_TO_EXECUTE_ADMIN_CMD, 222
 ER_XPLUGIN_FAILED_TO_GET_CREATION_STMT, 222
 ER_XPLUGIN_FAILED_TO_GET_ENGINE_INFO, 222
 ER_XPLUGIN_FAILED_TO_GET_SECURITY_CTX, 221
 ER_XPLUGIN_FAILED_TO_GET_SYS_VAR, 222
 ER_XPLUGIN_FAILED_TO_INITIALIZE_SESSION, 220
 ER_XPLUGIN_FAILED_TO_OPEN_INTERNAL_SESSION, 222

ER_XPLUGIN_FAILED_TO_PREPARE_IO_INTERFACES, 219	ER_XPLUING_NET_STARTUP_FAILED, 220
ER_XPLUGIN_FAILED_TO_RESET_IPV6_V6ONLY_FLAG, 222	ER_YES, 3
ER_XPLUGIN_FAILED_TO_SCHEDULE_CLIENT, 219	ER_ZLIB_Z_BUF_ERROR, 20
ER_XPLUGIN_FAILED_TO_SET_MIN_NUMBER_OF_WORKERS, 221	ER_ZLIB_Z_DATA_ERROR, 20
ER_XPLUGIN_FAILED_TO_SET_SO_REUSEADDR_FLAG, 222	ER_ZLIB_Z_MEM_ERROR, 20
ER_XPLUGIN_FAILED_TO_STOP_SERVICES, 340	WARN_AES_KEY_SIZE, 76
ER_XPLUGIN_FAILED_TO_SWITCH_CONTEXT, 222	WARN_COND_ITEM_TRUNCATED, 43
ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX, 348	WARN_DATA_TRUNCATED, 21
ER_XPLUGIN_FAILED_TO_UNREGISTER_UDF, 222	WARN_NAMED_PIPE_ACCESS_EVERYONE, 60
ER_XPLUGIN_FAILED_TO_USE_SSL_CONF, 216	WARN_NON_ASCII_SEPARATOR_NOT_IMPLEMENTED, 42
ER_XPLUGIN_FAILED_TO_VALIDATE_ADDRESS, 375	WARN_NO_CONNECTION_METADATA, 41
ER_XPLUGIN_FORCE_STOP_CLIENT, 219	WARN_ON_BLOCKHOLE_IN_RBR, 59
ER_XPLUGIN_IPv6_AVAILABLE, 221	WARN_OPTION_BELOW_LIMIT, 47
ER_XPLUGIN_LISTENER_SETUP_FAILED, 220	WARN_OPTION_IGNORED, 41
ER_XPLUGIN_LISTENER_STATUS_MSG, 221	WARN_PLUGIN_BUSY, 41
ER_XPLUGIN_LISTENER_SYS_VARIABLE_ERROR, 221	WARN_UNENCRYPTED_TABLE_IN_ENCRYPTED_DB, 99
ER_XPLUGIN_MAX_AUTH_ATTEMPTS_REACHED, 219	WARN_UNSUPPORTED_ACL_TABLES_READ, 114
ER_XPLUGIN_MESSAGE_TOO_LONG, 220	WARN_USELESS_SPATIAL_INDEX, 88
ER_XPLUGIN_PEER_DISCONNECTED_WHILE_READING, 221	ER_ABORTING error code, 145
ER_XPLUGIN_READ_FAILED_CLOSING_CONNECTION, 221	ER_ABORTING_CONNECTION error code, 13
ER_XPLUGIN_REFERENCE_TO_SECURE_CONN_WITH_EXPIRES, 216	ER_ABORTING_USER_CONNECTION error code, 191
ER_XPLUGIN_REFERENCE_TO_USER_ACCOUNT_DOES_NOT_EXIST, 220	ER_ACCESS_DENIED_CHANGE_USER_ERROR error code, 59
ER_XPLUGIN_RETRYING_BIND_ON_PORT, 221	ER_ACCESS_DENIED_ERROR error code, 6
ER_XPLUGIN_SRV_SESSION_INIT_THREAD_FAILED, 219	ER_ACCESS_DENIED_ERROR_WITHOUT_PASSWORD error code, 192
ER_XPLUGIN_STARTUP_FAILED, 216	ER_ACCESS_DENIED_ERROR_WITH_PASSWORD error code, 192
ER_XPLUGIN_TASK_SCHEDULING_FAILED, 220	ER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED_BY_IP, error code, 370
ER_XPLUGIN_UNABLE_TO_ACCEPT_CONNECTION, 221	ER_ACCESS_DENIED_FOR_USER_ACCOUNT_LOCKED, error code, 192
ER_XPLUGIN_UNABLE_TO_USE_USER_SESSION_ACCOUNT, 220	ER_ACCESS_DENIED_NO_PASSWORD_ERROR error code, 47
ER_XPLUGIN_UNEXPECTED_EXCEPTION_DISPATCHING, 220	ER_ACCESS_DENIED_NO_PROXY error code, 136
ER_XPLUGIN_UNINITIALIZED_MESSAGE, 220	ER_ACCESS_DENIED_NO_PROXY_GRANT error code, 136
ER_XPLUGIN_USING_SSL_CONF_FROM_MYSQLX, 216	ER_ACCESS_DENIED_NO_PROXY_GRANT_WITH_NAME error code, 427
ER_XPLUGIN_USING_SSL_CONF_FROM_SERVER, 216	ER_ACCESS_DENIED_NO_PROXY_WITH_NAME error code, 427
ER_XPLUGIN_USING_SSL_FOR_TLS_CONNECTION, 216	ER_ACCOUNT_HAS_BEEN_LOCKED error code, 69
	ER_ACCOUNT_WITH_EXPIRED_PASSWORD error code, 397
	ER_ACL_OPERATION_FAILED error code, 76
	ER_ACL_WRONG_OR_MISSING_ACL_TABLES_LOG error code, 364
	ER_ADDRESSES_FOR_HOSTNAME_HEADER error code, 141
	ER_ADDRESSES_FOR_HOSTNAME_LIST_ITEM error code, 141

ER_ADD_PARTITION_NO_NEW_PARTITION error code, 36	ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_VIEW_CHANGE_U error code, 116
ER_ADD_PARTITION_SUBPART_ERROR error code, 36	ER_APPLIER_LOG_EVENT_VALIDATION_ERROR error code, 85
ER_ADMIN_WRONG_MRG_TABLE error code, 33	ER_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_REQUIRE error code, 114
ER_AES_INVALID_IV error code, 59	ER_ATTRIBUTE_IGNORED error code, 87
ER_AES_INVALID_KDF_ITERATIONS error code, 76	ER_AUDIT_API_ABORT error code, 73
ER_AES_INVALID_KDF_NAME error code, 75	ER_AUDIT_CANT_ABORT_COMMAND error code, 190
ER_AES_INVALID_KDF_OPTION_SIZE error code, 76	ER_AUDIT_CANT_ABORT_EVENT error code, 190
ER_AGGREGATE_IN_ORDER_NOT_SELECT error code, 65	ER_AUDIT_LOG_CANNOT_GENERATE_PASSWORD error code, 368
ER_AGGREGATE_ORDER_FOR_UNION error code, 62	ER_AUDIT_LOG_CANNOT_READ_PASSWORD error code, 363
ER_AGGREGATE_ORDER_NON_AGG_QUERY error code, 62	ER_AUDIT_LOG_CANNOT_REMOVE_PASSWORD error code, 363
ER_ALTER_CONSTRAINT_ENFORCEMENT_NOT_SUPPORTED error code, 108	ER_AUDIT_LOG_CANNOT_SET_LOG_POLICY_WITH_OTHER_PO error code, 213
ER_ALTER_FILEGROUP_FAILED error code, 37	ER_AUDIT_LOG_CANNOT_STORE_PASSWORD error code, 363
ER_ALTER_INFO error code, 9	ER_AUDIT_LOG_COULD_NOT_CREATE_AES_KEY error code, 344
ER_ALTER_OPERATION_NOT_SUPPORTED error code, 57	ER_AUDIT_LOG_COULD_NOT_OPEN_FILE_FOR_READING error code, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 57	ER_AUDIT_LOG_EC_WRITER_FAILED_TO_CREATE_FILE error code, 214
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 58	ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_COMPRESSION error code, 214
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 58	ER_AUDIT_LOG_EC_WRITER_FAILED_TO_INIT_ENCRYPTION error code, 214
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 57	ER_AUDIT_LOG_ENCRYPTION_PASSWORD_CANNOT_BE_FETCH error code, 344
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 120	ER_AUDIT_LOG_ENCRYPTION_PASSWORD_HAS_NOT_BEEN_S error code, 344
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 57	ER_AUDIT_LOG_FILE_AUTO_PRUNED error code, 384
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 57	ER_AUDIT_LOG_FILE_HAS_BEEN_SUCCESSFULLY_PROCESSE error code, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 58	ER_AUDIT_LOG_FILE_NAME_DOES_NOT_HAVE_REQUIRED_FO error code, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 65	ER_AUDIT_LOG_FILE_NAME_KEYRING_ID_VALUE_IS_MISSING error code, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 58	ER_AUDIT_LOG_FILE_NAME_TIMESTAMP_VALUE_IS_MISSING error code, 363
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 57	ER_AUDIT_LOG_FILTER_FAILED error code, 384
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 58	ER_AUDIT_LOG_FILTER_FAILED_TO_CLOSE_TABLE_AFTER_RE error code, 215
ER_ALTER_OPERATION_NOT_SUPPORTED_REASON error code, 57	ER_AUDIT_LOG_FILTER_FAILED_TO_DELETE_FROM_TABLE error code, 215
ER_AMBIGUOUS_FIELD_TERM error code, 34	ER_AUDIT_LOG_FILTER_FAILED_TO_INIT_TABLE_FOR_READ error code, 215
ER_ANONYMOUS_AUTH_ID_NOT_ALLOWED_IN_MANDATORY_R error code, 195	ER_AUDIT_LOG_FILTER_FAILED_TO_INSERT_INTO_TABLE error code, 214
ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NAME error code, 115	ER_AUDIT_LOG_FILTER_FAILED_TO_READ_TABLE error code, 215

ER_AUDIT_LOG_FILTER_FAILED_TO_STORE_TABLE_FILES error code, 214	ER_AUDIT_LOG_SWITCHING_TO_INCLUDE_LIST error code, 213
ER_AUDIT_LOG_FILTER_FAILED_TO_UPDATE_TABLE error code, 214	ER_AUDIT_LOG_TABLE_DEFINITION_NOT_UPDATED error code, 345
ER_AUDIT_LOG_FILTER_FLD_FILTERNAME_CANNOT_BE_EMPTY error code, 215	ER_AUDIT_LOG_UDF_INSUFFICIENT_PRIVILEGE error code, 343
ER_AUDIT_LOG_FILTER_IS_NOT_INSTALLED error code, 213	ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_COUNT error code, 366
ER_AUDIT_LOG_FILTER_RESULT_MSG error code, 214	ER_AUDIT_LOG_UDF_INVALID_ARGUMENT_TYPE error code, 366
ER_AUDIT_LOG_FILTER_USER_AND_HOST_CANNOT_BE_EMPTY error code, 215	ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH error code, 366
ER_AUDIT_LOG_HAS_NOT_BEEN_INSTALLED error code, 366	ER_AUDIT_LOG_UDF_READ_INVALID_MAX_ARRAY_LENGTH error code, 75
ER_AUDIT_LOG_HOST_NAME_INVALID_CHARACTER error code, 343	ER_AUDIT_LOG_USER_FIRST_CHARACTER_MUST_BE_ALPHA error code, 344
ER_AUDIT_LOG_INDEX_MAP_CANNOT_ACCESS_DIRECTORY error code, 213	ER_AUDIT_LOG_USER_NAME_INVALID_CHARACTER error code, 343
ER_AUDIT_LOG_INSUFFICIENT_PRIVILEGE error code, 106	ER_AUDIT_LOG_WRITER_DEST_FILE_ALREADY_EXISTS error code, 213
ER_AUDIT_LOG_INVALID_FILE_CONTENT error code, 363	ER_AUDIT_LOG_WRITER_FAILED_TO_WRITE_TO_FILE error code, 213
ER_AUDIT_LOG_INVALID_FLUSH_INTERVAL_VALUE error code, 413	ER_AUDIT_LOG_WRITER_INCOMPLETE_FILE_RENAMED error code, 213
ER_AUDIT_LOG_JSON_FILTERING_NOT_ENABLED error code, 343	ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED error code, 213
ER_AUDIT_LOG_JSON_FILTER_DOES_NOT_EXIST error code, 344	ER_AUDIT_LOG_WRITER_RENAME_FILE_FAILED_REMOVE error code, 213
ER_AUDIT_LOG_JSON_FILTER_NAME_CANNOT_BE_EMPTY error code, 343	ER_AUDIT_PLUGIN_DOES_NOT_SUPPORT_AUDIT_AUTH_EVENT error code, 161
ER_AUDIT_LOG_JSON_FILTER_PARSING_ERROR error code, 343	ER_AUDIT_PLUGIN_HAS_INVALID_DATA error code, 161
ER_AUDIT_LOG_JSON_READER_BUF_TOO_SMALL error code, 214	ER_AUDIT_WARNING error code, 190
ER_AUDIT_LOG_JSON_READER_FAILED_TO_OPEN_FILE error code, 214	ER_AUTHCACHE_CANT_INIT_GRANT_SUBSYSTEM error code, 159
ER_AUDIT_LOG_JSON_READER_FAILED_TO_PARSE error code, 214	ER_AUTHCACHE_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLE error code, 159
ER_AUDIT_LOG_JSON_READER_FILE_PARSING_ERROR error code, 214	ER_AUTHCACHE_DB_ENTRY_LOWERCASED_REVOKE_WILL_FAIL error code, 159
ER_AUDIT_LOG_JSON_USER_NAME_CANNOT_BE_EMPTY error code, 344	ER_AUTHCACHE_DB_IGNORED_EMPTY_NAME error code, 159
ER_AUDIT_LOG_KEYRING_ID_TIMESTAMP_VALUE_IS_INVALID error code, 363	ER_AUTHCACHE_DB_SKIPPED_NEEDS_RESOLVE error code, 159
ER_AUDIT_LOG_NO_KEYRING_PLUGIN_INSTALLED error code, 343	ER_AUTHCACHE_DEFAULT_ROLES_IGNORED_EMPTY_NAME error code, 376
ER_AUDIT_LOG_ONLY_INCLUDE_LIST_USED error code, 213	ER_AUTHCACHE_DEFAULT_ROLES_UNKNOWN_AUTHORIZATION error code, 376
ER_AUDIT_LOG_PASSWORD_HAS_BEEN_COPIED error code, 363	ER_AUTHCACHE_EXPIRED_PASSWORD_UNSUPPORTED error code, 159
ER_AUDIT_LOG_RENAME_LOG_FILE_BEFORE_FLUSH error code, 214	ER_AUTHCACHE_PLUGIN_CONFIG error code, 158
ER_AUDIT_LOG_SUPER_PRIVILEGE_REQUIRED error code, 366	ER_AUTHCACHE_PLUGIN_MISSING error code, 158
	ER_AUTHCACHE_PROCS_PRIV_ENTRY_IGNORED_BAD_ROLE error code, 159

ER_AUTHCACHE_PROCS_PRIV_SKIPPED_NEEDS_RESOLVE	ER_AUTHENTICATION_PLUGIN_SIGNATURE_CORRUPT
error code, 159	error code, 392
ER_AUTHCACHE_PROXIES_PRIV_SKIPPED_NEEDS_RESOLVE	ER_AUTHENTICATION_PLUGIN_VERIFY_SIGNATURE_FAILED
error code, 158	error code, 392
ER_AUTHCACHE_ROLE_EDGES_IGNORED_EMPTY_NAME	ER_AUTHENTICATION_POLICY_MISMATCH
error code, 376	error code, 118
ER_AUTHCACHE_ROLE_EDGES_UNKNOWN_AUTHORIZATION	ER_AUTH_CANT_ACTIVATE_ROLE
error code, 376	error code, 157
ER_AUTHCACHE_TABLES_PRIV_SKIPPED_NEEDS_RESOLVE	ER_AUTH_CANT_CREATE_RSA_PAIR
error code, 160	error code, 157
ER_AUTHCACHE_TABLE_PROXIES_PRIV_MISSING	ER_AUTH_CANT_WRITE_PRIVKEY
error code, 159	error code, 157
ER_AUTHCACHE_USER_IGNORED_DEPRECATED_PASSWORD	ER_AUTH_CERTS_SAVED_TO_DATADIR
error code, 158	error code, 157
ER_AUTHCACHE_USER_IGNORED_INVALID_PASSWORD	ER_AUTH_CERT_GENERATION_DISABLED
error code, 159	error code, 158
ER_AUTHCACHE_USER_IGNORED_NEEDS_PLUGIN	ER_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY_ROLE
error code, 158	error code, 358
ER_AUTHCACHE_USER_SKIPPED_NEEDS_RESOLVE	ER_AUTH_KERBEROS_LOGGER_GENERIC_MSG
error code, 158	error code, 389
ER_AUTHCACHE_USER_TABLE_DODGY	ER_AUTH_KEYS_SAVED_TO_DATADIR
error code, 158	error code, 158
ER_AUTHENTICATION_OCI_DOWNLOAD_IDDP_PUBLIC_KEY	ER_AUTH_KEY_GENERATION_DISABLED
error code, 412	error code, 158
ER_AUTHENTICATION_OCI_DOWNLOAD_PUBLIC_KEY	ER_AUTH_KEY_GENERATION_SKIPPED_PAIR_PRESENT
error code, 393	error code, 158
ER_AUTHENTICATION_OCI_IAM	ER_AUTH_LDAP_ERROR_LOGGER_ERROR_MSG
error code, 393	error code, 217
ER_AUTHENTICATION_OCI_IMDS	ER_AUTH_RSA_CANT_FIND
error code, 393	error code, 156
ER_AUTHENTICATION_OCI_INVALID_AUTHENTICATION_STRINGS	ER_AUTH_RSA_CANT_PARSE
error code, 393	error code, 156
ER_AUTHENTICATION_OCI_INVALID_TOKEN	ER_AUTH_RSA_CANT_READ
error code, 411	error code, 156
ER_AUTHENTICATION_OCI_NONCE	ER_AUTH_RSA_CONF_PREVENTS_KEY_GENERATION
error code, 394	error code, 158
ER_AUTHENTICATION_OCI_NO_GROUPS_FOUND	ER_AUTH_RSA_FILES_NOT_FOUND
error code, 393	error code, 156
ER_AUTHENTICATION_OCI_NO_MATCHING_GROUPS	ER_AUTH_SSL_CONF_PREVENTS_CERT_GENERATION
error code, 393	error code, 157
ER_AUTHENTICATION_OCI_PLUGIN_NOT_INITIALIZED	ER_AUTH_USING_EXISTING_CERTS
error code, 393	error code, 157
ER_AUTHENTICATION_OCI_PRIVATE_KEY_ERROR	ER_AUTOINC_READ_FAILED
error code, 393	error code, 33
ER_AUTHENTICATION_OCI_TOKEN_DETAILS_MISMATCH	ER_AUTO_CONVERT
error code, 411	error code, 19
ER_AUTHENTICATION_OCI_TOKEN_NOT_VERIFIED	ER_AUTO_INCREMENT_CONFLICT
error code, 411	error code, 59
ER_AUTHENTICATION_PLUGIN_AUTH_DATA_CORRUPT	ER_AUTO_INCREMENT_NOT_SUPPORTED_FOR_FLOAT_DOUBLE
error code, 392	error code, 426
ER_AUTHENTICATION_PLUGIN_LOG	ER_AUTO_OPTIONS_FAILED
error code, 393	error code, 149
ER_AUTHENTICATION_PLUGIN_OOM	ER_AUTO_POSITION_REQUIRES_GTID_MODE_NOT_OFF
error code, 392	error code, 52
ER_AUTHENTICATION_PLUGIN_REGISTRATION_FAILED	ER_BACKGROUND_HISTOGRAM_UPDATE
error code, 392	error code, 426
ER_AUTHENTICATION_PLUGIN_REGISTRATION_INSUFFICIENT_BUFFER	ER_BACK_IN_TIME
error code, 392	error code, 144
	ER_BAD_DB_ERROR
	error code, 6
	ER_BAD_FIELD_ERROR
	error code, 7
	ER_BAD_FT_COLUMN
	error code, 22
	ER_BAD_HOST_ERROR
	error code, 6
	ER_BAD_LOG_STATEMENT
	error code, 39
	ER_BAD_NULL_ERROR
	error code, 6
	ER_BAD_NULL_ERROR_NOT_IGNORED
	error code, 88

ER_BAD_REPLICA error code, 16
 ER_BAD_REPLICA_AUTO_POSITION error code, 52
 ER_BAD_REPLICA_UNTIL_COND error code, 21
 ER_BAD_TABLE_ERROR error code, 6
 ER_BAD_TIMESTAMP_FORMAT error code, 123
 ER_BASE64_DECODE_ERROR error code, 39
 ER_BASEDIR_SET_TO error code, 194
 ER_BEFORE_DML_VALIDATION_ERROR error code, 67
 ER_BEG_INITFILE error code, 146
 ER_BEYOND_SERVER_DOWNGRADE_THRESHOLD error code, 414
 ER_BEYOND_SERVER_UPGRADE_THRESHOLD error code, 414
 ER_BINLOG_CACHE_SIZE_GREATER_THAN_MAX error code, 50
 ER_BINLOG_CACHE_SIZE_TOO_LARGE error code, 190
 ER_BINLOG_CANT_APPEND_LOG_TO_TMP_INDEX error code, 185
 ER_BINLOG_CANT_CLEAR_IN_USE_FLAG_FOR_CRASHED_BINLOG error code, 187
 ER_BINLOG_CANT_CLOSE_TMP_INDEX error code, 186
 ER_BINLOG_CANT_COPY_INDEX_TO_TMP error code, 186
 ER_BINLOG_CANT_DELETE_FILE error code, 185
 ER_BINLOG_CANT_DELETE_FILE_AND_READ_BINLOG_INDEX error code, 187
 ER_BINLOG_CANT_DELETE_LOG_FILE_DOES_INDEX_MATCH error code, 187
 ER_BINLOG_CANT_FIND_LOG_IN_INDEX error code, 187
 ER_BINLOG_CANT_GENERATE_NEW_FILE_NAME error code, 185
 ER_BINLOG_CANT_LOCATE_OLD_BINLOG_OR_RELAY_LOG error code, 185
 ER_BINLOG_CANT_MOVE_TMP_TO_INDEX error code, 186
 ER_BINLOG_CANT_OPEN_CRASHED_BINLOG error code, 187
 ER_BINLOG_CANT_OPEN_FOR_LOGGING error code, 184
 ER_BINLOG_CANT_OPEN_TMP_INDEX error code, 186
 ER_BINLOG_CANT_RESIZE_CACHE error code, 184
 ER_BINLOG_CANT_SET_TMP_INDEX_NAME error code, 185
 ER_BINLOG_CANT_TRIM_CRASHED_BINLOG error code, 187
 ER_BINLOG_CANT_USE_FOR_LOGGING error code, 185
 ER_BINLOG_CRASHED_BINLOG_TRIMMED error code, 187
 ER_BINLOG_CRASH_RECOVERY_COMMIT_FAILED error code, 402
 ER_BINLOG_CRASH_RECOVERY_ENGINE_RESULTS error code, 402
 ER_BINLOG_CRASH_RECOVERY_ERROR_RETURNED_SE error code, 402
 ER_BINLOG_CRASH_RECOVERY_MALFORMED_LOG error code, 402
 ER_BINLOG_CRASH_RECOVERY_PREPARE_FAILED error code, 402
 ER_BINLOG_CRASH_RECOVERY_ROLLBACK_FAILED error code, 402
 ER_BINLOG_CREATE_ROUTINE_NEED_SUPER error code, 30
 ER_BINLOG_END error code, 145
 ER_BINLOG_ERROR_READING_GTIDS_FROM_BINARY_LOG error code, 184
 ER_BINLOG_ERROR_READING_GTIDS_FROM_RELAY_LOG error code, 184
 ER_BINLOG_EVENTS_READ_FROM_APPLIER_METADATA error code, 184
 ER_BINLOG_EVENTS_READ_FROM_BINLOG_INFO error code, 184
 ER_BINLOG_EVENT_WRITE_TO_STMT_CACHE_FAILED error code, 194
 ER_BINLOG_FAILED_TO_CLOSE_INDEX_FILE_WHILE_REBUILD error code, 185
 ER_BINLOG_FAILED_TO_DELETE_INDEX_FILE_WHILE_REBUILD error code, 185
 ER_BINLOG_FAILED_TO_DELETE_LOG_FILE error code, 187
 ER_BINLOG_FAILED_TO_OPEN_INDEX_FILE_AFTER_REBUILD error code, 185
 ER_BINLOG_FAILED_TO_OPEN_REGISTER_FILE error code, 186
 ER_BINLOG_FAILED_TO_OPEN_TEMPORARY_INDEX_FILE error code, 185
 ER_BINLOG_FAILED_TO_READ_REGISTER_FILE error code, 187
 ER_BINLOG_FAILED_TO_REINIT_REGISTER_FILE error code, 186
 ER_BINLOG_FAILED_TO_RENAME_INDEX_FILE_WHILE_REBUILD error code, 185
 ER_BINLOG_FAILED_TO_RUN_AFTER_FLUSH_HOOK error code, 188
 ER_BINLOG_FAILED_TO_RUN_AFTER_SYNC_HOOK error code, 188
 ER_BINLOG_FAILED_TO_SET_PURGE_INDEX_FILE_NAME error code, 186
 ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE error code, 184
 ER_BINLOG_FAILED_TO_SYNC_INDEX_FILE_IN_OPEN error code, 185

ER_BINLOG_FAILED_TO_WRITE_DROP_FOR_TEMP_TABLE error code, 178	ER_BINLOG_RECOVERING_AFTER_CRASH_USING error code, 187
ER_BINLOG_FATAL_ERROR error code, 40	ER_BINLOG_ROW_ENGINE_AND_STMT_ENGINE error code, 44
ER_BINLOG_FILE_BEING_READ_NOT_PURGED error code, 184	ER_BINLOG_ROW_INJECTION_AND_STMT_ENGINE error code, 44
ER_BINLOG_FILE_EXTENSION_NUMBER_EXHAUSTED error code, 184	ER_BINLOG_ROW_INJECTION_AND_STMT_MODE error code, 44
ER_BINLOG_FILE_EXTENSION_NUMBER_RUNNING_LOW error code, 184	ER_BINLOG_ROW_LOGGING_FAILED error code, 37
ER_BINLOG_FILE_NAME_TOO_LONG error code, 184	ER_BINLOG_ROW_MODE_AND_STMT_ENGINE error code, 44
ER_BINLOG_FILE_OPEN_FAILED error code, 194	ER_BINLOG_ROW_VALUE_OPTION_IGNORED error code, 339
ER_BINLOG_IO_ERROR_READING_HEADER error code, 184	ER_BINLOG_ROW_VALUE_OPTION_USED_ONLY_FOR_AFTER_I error code, 339
ER_BINLOG_LOGGING_IMPOSSIBLE error code, 40	ER_BINLOG_STMT_CACHE_SIZE_GREATER_THAN_MAX error code, 50
ER_BINLOG_LOGGING_INCIDENT_TO_STOP_REPLICAS error code, 187	ER_BINLOG_STMT_CACHE_SIZE_TOO_LARGE error code, 190
ER_BINLOG_LOGGING_NOT_POSSIBLE error code, 203	ER_BINLOG_STMT_MODE_AND_NO_REPL_TABLES error code, 57
ER_BINLOG_LOGICAL_CORRUPTION error code, 58	ER_BINLOG_STMT_MODE_AND_ROW_ENGINE error code, 44
ER_BINLOG_MALFORMED_OR_OLD_RELAY_LOG error code, 204	ER_BINLOG_UNABLE_TO_ROTATE_GTID_TABLE_READONLY error code, 361
ER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION error code, 98	ER_BINLOG_UNSAFE_ACL_TABLE_READ_IN_DML_DDL error code, 114
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP error code, 98	ER_BINLOG_UNSAFE_AND_STMT_ENGINE error code, 44
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP error code, 98	ER_BINLOG_UNSAFE_AUTOINC_COLUMNS error code, 45
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_OPERATE error code, 98	ER_BINLOG_UNSAFE_AUTOINC_NOT_FIRST error code, 49
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_REENCRYPT error code, 98	ER_BINLOG_UNSAFE_CREATE_IGNORE_SELECT error code, 48
ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_ROTATE error code, 98	ER_BINLOG_UNSAFE_CREATE_REPLACE_SELECT error code, 48
ER_BINLOG_MULTIPLE_ENGINES_AND_SELF_LOGGING_ENGINE error code, 44	ER_BINLOG_UNSAFE_CREATE_SELECT_AUTOINC error code, 48
ER_BINLOG_NEEDS_SERVERID error code, 148	ER_BINLOG_UNSAFE_DEFAULT_EXPRESSION_IN_SUBSTATEMENT error code, 362
ER_BINLOG_OOM_WRITING_DELETE_WHILE_OPENING_Generalized error code, 178	ER_BINLOG_UNSAFE_FULLTEXT_PLUGIN error code, 60
ER_BINLOG_PURGE_EMFILE error code, 40	ER_BINLOG_UNSAFE_INSERT_IGNORE_SELECT error code, 48
ER_BINLOG_PURGE_FATAL_ERR error code, 28	ER_BINLOG_UNSAFE_INSERT_SELECT_UPDATE error code, 48
ER_BINLOG_PURGE_LOGS_CALLED_WITH_FILE_NOT_FOUND error code, 186	ER_BINLOG_UNSAFE_INSERT_TWO_KEYS error code, 49
ER_BINLOG_PURGE_LOGS_CANT_COPY_TO_REGISTERED_FILE error code, 186	ER_BINLOG_UNSAFE_LIMIT error code, 45
ER_BINLOG_PURGE_LOGS_CANT_FLUSH_REGISTER_FILE error code, 186	ER_BINLOG_UNSAFE_MESSAGE_AND_STATEMENT error code, 191
ER_BINLOG_PURGE_LOGS_CANT_SYNC_INDEX_FILE error code, 186	ER_BINLOG_UNSAFE_MIXED_STATEMENT error code, 46
ER_BINLOG_PURGE_LOGS_FAILED_TO_PURGE_LOG error code, 186	
ER_BINLOG_PURGE_PROHIBITED error code, 27	

ER_BINLOG_UNSAFE_MULTIPLE_ENGINES_AND_SELF_FLUSHING error code, 46
 ER_BINLOG_UNSAFE_NONTRANS_AFTER_TRANS error code, 45
 ER_BINLOG_UNSAFE_NOWAIT error code, 81
 ER_BINLOG_UNSAFE_REPLACE_SELECT error code, 48
 ER_BINLOG_UNSAFE_ROUTINE error code, 30
 ER_BINLOG_UNSAFE_SKIP_LOCKED error code, 81
 ER_BINLOG_UNSAFE_STATEMENT error code, 40
 ER_BINLOG_UNSAFE_SYSTEM_FUNCTION error code, 45
 ER_BINLOG_UNSAFE_SYSTEM_TABLE error code, 45
 ER_BINLOG_UNSAFE_SYSTEM_VARIABLE error code, 45
 ER_BINLOG_UNSAFE_UDF error code, 45
 ER_BINLOG_UNSAFE_UPDATE_IGNORE error code, 48
 ER_BINLOG_UNSAFE_WRITE_AUTOINC_SELECT error code, 48
 ER_BINLOG_UNSAFE_XA error code, 75
 ER_BINLOG_WARNING_SUPPRESSED error code, 188
 ER_BLOBS_AND_NO_TERMINATED error code, 9
 ER_BLOB_CANT_HAVE_DEFAULT error code, 10
 ER_BLOB_FIELD_IN_PART_FUNC_ERROR error code, 35
 ER_BLOB_KEY_WITHOUT_LENGTH error code, 14
 ER_BLOB_USED_AS_KEY error code, 8
 ER_BLOCKED_CIPHER error code, 425
 ER_BOOST_GEOMETRY_CENTROID_EXCEPTION error code, 63
 ER_BOOST_GEOMETRY_EMPTY_INPUT_EXCEPTION error code, 63
 ER_BOOST_GEOMETRY_INCONSISTENT_TURNS_EXCEPTION error code, 69
 ER_BOOST_GEOMETRY_OVERLAY_INVALID_INPUT_EXCEPTION error code, 63
 ER_BOOST_GEOMETRY_SELF_INTERSECTION_POINT_EXCEPTION error code, 63
 ER_BOOST_GEOMETRY_TURN_INFO_EXCEPTION error code, 63
 ER_BOOST_GEOMETRY_UNKNOWN_EXCEPTION error code, 63
 ER_BOOTSTRAP_CANT_THREAD error code, 137
 ER_BUFPOOL_RESIZE_INPROGRESS error code, 73
 ER_BUILD_ID error code, 404
 ER_BULK_EXECUTOR_ERROR error code, 124
 ER_BULK_EXECUTOR_INFO error code, 406
 ER_BULK_LOADER_COLUMN_TOO_BIG_FOR_LEFTOVER_BUFFER error code, 124
 ER_BULK_LOADER_COMPONENT_ERROR error code, 124
 ER_BULK_LOADER_OPEN_FILE_CONTAINS_LESS_LINES_THAN_IGNORED error code, 125
 ER_BULK_LOADER_FILE_CONTAINS_LESS_LINES_THAN_IGNORED error code, 406
 ER_BULK_LOADER_INFO error code, 406
 ER_BULK_LOAD_DATA_FAILED error code, 124
 ER_BULK_LOAD_RESOURCE error code, 129
 ER_BULK_LOAD_SECONDARY_ENGINE error code, 129
 ER_BULK_LOAD_TABLE_HAS_INSTANT_COLS error code, 129
 ER_BULK_MERGE_INVALID_CHUNK error code, 128
 ER_BULK_MERGE_LOADER_INFO error code, 418
 ER_BULK_MERGE_NOT_ALL_CHUNKS_CONSUMED error code, 128
 ER_BULK_MULTI_READER_INFO error code, 418
 ER_BULK_MULTI_READER_OPEN_FILE_FAILED error code, 128
 ER_BULK_MULTI_READER_READ_FILE_FAILED error code, 128
 ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED error code, 125
 ER_BULK_PARSER_COPY_BUFFER_SIZE_EXCEEDED_LOG error code, 407
 ER_BULK_PARSER_ERROR error code, 136
 ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE error code, 125
 ER_BULK_PARSER_INCOMPLETE_ESCAPE_SEQUENCE_LOG error code, 408
 ER_BULK_PARSER_MISSING_ENCLOSED_BY error code, 125
 ER_BULK_PARSER_MISSING_ENCLOSED_BY_LOG error code, 407
 ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS_EXCEEDED error code, 125
 ER_BULK_PARSER_ROW_BUFFER_MAX_TOTAL_COLS_EXCEEDED_LOG error code, 407
 ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_NAME error code, 125
 ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_COLUMN_NAME_LOG error code, 407
 ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENDING_BRACKET error code, 125
 ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_ENDING_BRACKET_LOG error code, 407
 ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE_CHARACTER error code, 125
 ER_BULK_PARSER_UNEXPECTED_CHAR_AFTER_NULL_ESCAPE_CHARACTER_LOG error code, 407
 ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT error code, 125
 ER_BULK_PARSER_UNEXPECTED_END_OF_INPUT_LOG error code, 407

ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR error code, 125
 ER_BULK_PARSER_UNEXPECTED_ROW_TERMINATOR_LOG error code, 407
 ER_BULK_READER_COMMUNICATION_ERROR error code, 124
 ER_BULK_READER_COMMUNICATION_ERROR_LOG error code, 407
 ER_BULK_READER_COULDNT_RESOLVE_HOST error code, 129
 ER_BULK_READER_ERROR error code, 129
 ER_BULK_READER_FILE_DOESNT_EXIST error code, 129
 ER_BULK_READER_INFO error code, 406
 ER_BULK_READER_LIBCURL_ERROR error code, 124
 ER_BULK_READER_LIBCURL_ERROR_LOG error code, 407
 ER_BULK_READER_LIBCURL_INIT_FAILED error code, 124
 ER_BULK_READER_LIBCURL_INIT_FAILED_LOG error code, 406
 ER_BULK_READER_OPEN_FILE_FAILED error code, 129
 ER_BULK_READER_SERVER_ERROR error code, 124
 ER_BULK_READER_SERVER_ERROR_LOG error code, 407
 ER_BULK_READER_ZSTD_ERROR error code, 136
 ER_BULK_READER_ZSTD_ERROR_LOG error code, 427
 ER_BULK_SCANNER_INFO error code, 428
 ER_BULK_SORTING_LOADER_INFO error code, 418
 ER_BULK_SORTING_LOADER_WAIT error code, 129
 ER_BULK_SORTING_LOADER_WRITE error code, 129
 ER_BULK_WRITER_INFO error code, 418
 ER_BULK_WRITER_LIBCURL_ERROR error code, 128
 ER_BULK_WRITER_LIBCURL_ERROR_LOG error code, 418
 ER_BULK_WRITER_LIBCURL_INIT_FAILED error code, 128
 ER_BULK_WRITER_LIBCURL_INIT_FAILED_LOG error code, 418
 ER_CACHING_SHA2_PASSWORD_SECOND_PASSWORD_USED error code, 353
 ER_CALL_ME_LOCALHOST error code, 145
 ER_CANNOT_ADD_FOREIGN error code, 17
 ER_CANNOT_ADD_FOREIGN_BASE_COL_STORED error code, 75
 ER_CANNOT_ADD_FOREIGN_BASE_COL_VIRTUAL error code, 73
 ER_CANNOT_ALTER_SRID_DUE_TO_INDEX error code, 86
 ER_CANNOT_CHANGE_TO_ROOT_DIR error code, 193
 ER_CANNOT_CONVERT_STRING error code, 102
 ER_CANNOT_CREATE_VIRTUAL_INDEX_CONSTRAINT error code, 73
 ER_CANNOT_DISCARD_TEMPORARY_TABLE error code, 61
 ER_CANNOT_DROP_COLUMN_FUNCTIONAL_INDEX error code, 94
 ER_CANNOT_EXECUTE_IN_PRIMARY error code, 129
 ER_CANNOT_FIND_KEY_IN_KEYRING error code, 74
 ER_CANNOT_GET_SERVER_VERSION_FROM_TABLESPACE_HEADERS error code, 355
 ER_CANNOT_GRANT_ROLES_TO_ANONYMOUS_USER error code, 103
 ER_CANNOT_GRANT_SYSTEM_PRIV_TO_MANDATORY_ROLE error code, 105
 ER_CANNOT_INTERPRET_PERSISTED_SENSITIVE_VARIABLES error code, 396
 ER_CANNOT_LOAD_FROM_TABLE_V2 error code, 49
 ER_CANNOT_LOCK_USER_MANAGEMENT_CACHES error code, 79
 ER_CANNOT_LOG_PARTIAL_DROP_DATABASE_WITH_GTID error code, 67
 ER_CANNOT_PERSIST_SENSITIVE_VARIABLES error code, 121
 ER_CANNOT_PURGE_BINLOG_WITH_BACKUP_LOCK error code, 120
 ER_CANNOT_SET_DATABASE_ENCRYPTION error code, 100
 ER_CANNOT_SET_LOG_ERROR_SERVICES error code, 194
 ER_CANNOT_SET_SERVER_VERSION_IN_TABLESPACE_HEADERS error code, 355
 ER_CANNOT_SET_TABLESPACE_ENCRYPTION error code, 100
 ER_CANNOT_SET_TABLE_ENCRYPTION error code, 100
 ER_CANNOT_USER error code, 28
 ER_CANNOT_USER_REFERENCED_AS_DEFINER error code, 113
 ER_CANNOT_USE_AUTOEXTEND_SIZE_CLAUSE error code, 115
 ER_CANNOT_USE_ENCRYPTION_CLAUSE error code, 100
 ER_CANT_ACCESS_CAPATH error code, 149
 ER_CANT_AGGREGATE_2COLLATIONS error code, 21
 ER_CANT_AGGREGATE_3COLLATIONS error code, 21
 ER_CANT_AGGREGATE_NCOLLATIONS error code, 21
 ER_CANT_ALLOC_TABLE_OBJECT error code, 181
 ER_CANT_CHANGE_SYS_VAR_IN_READ_ONLY_MODE error code, 126
 ER_CANT_CHANGE_TX_CHARACTERISTICS error code, 39

ER_CANT_CHECK_PID_PATH error code, 258
 ER_CANT_CHOWN_DATADIR error code, 149
 ER_CANT_COMBINE_ANONYMOUS_TO_GTID_AND_AUTO_POSITION error code, 114
 ER_CANT_CREATE_ADMIN_THREAD error code, 353
 ER_CANT_CREATE_CACHE_FOR_DB_OPT error code, 182
 ER_CANT_CREATE_DB error code, 3
 ER_CANT_CREATE_FILE error code, 3
 ER_CANT_CREATE_GEOMETRY_OBJECT error code, 30
 ER_CANT_CREATE_HANDLER_FILE error code, 35
 ER_CANT_CREATE_HANDLER_OBJECT_FOR_TABLE error code, 181
 ER_CANT_CREATE_HANDLE_MGR_THREAD error code, 139
 ER_CANT_CREATE_INTERRUPT_THREAD error code, 144
 ER_CANT_CREATE_NAMED_PIPES_THREAD error code, 144
 ER_CANT_CREATE_PID_FILE error code, 143
 ER_CANT_CREATE_SCHEDULER_THREAD error code, 140
 ER_CANT_CREATE_SHM_THREAD error code, 144
 ER_CANT_CREATE_SHUTDOWN_THREAD error code, 143
 ER_CANT_CREATE_TABLE error code, 3
 ER_CANT_CREATE_TABLE_SHARE_FROM_FRM error code, 181
 ER_CANT_CREATE_TCPIP_THREAD error code, 144
 ER_CANT_CREATE_TEST_FILE error code, 143
 ER_CANT_CREATE_THREAD error code, 12
 ER_CANT_CREATE_USER_WITH_GRANT error code, 29
 ER_CANT_CREATE_UUID error code, 142
 ER_CANT_DETACH_SESSION_LEFT_BY_PLUGIN error code, 169
 ER_CANT_DO_IMPLICIT_COMMIT_IN_TRX_WHEN_GTID_ENABLED error code, 52
 ER_CANT_DO_THIS_DURING_AN_TRANSACTION error code, 15
 ER_CANT_DROP_FIELD_OR_KEY error code, 9
 ER_CANT_ENFORCE_GTID_CONSISTENCY_WITH_ONGOING_GTID_PROCESSING error code, 69
 ER_CANT_EXECUTE_COMMAND_WITH_ASSIGNED_GTID error code, 121
 ER_CANT_EXECUTE_IN_READ_ONLY_TRANSACTION error code, 53
 ER_CANT_FIND_DL_ENTRY error code, 12
 ER_CANT_FIND_SYSTEM_REC error code, 4
 ER_CANT_FIND_UDF error code, 11
 ER_CANT_GET_STAT error code, 4
 ER_CANT_HASH_DO_AND_IGNORE_RULES error code, 149
 ER_CANT_IDENTIFY_CHARSET_USING_DEFAULT error code, 182
 ER_CANT_INCREASE_MAX_OPEN_FILES error code, 146
 ER_CANT_INITIALIZE_BUILTIN_PLUGINS error code, 148
 ER_CANT_INITIALIZE_DYNAMIC_PLUGINS error code, 148
 ER_CANT_INITIALIZE_EARLY_PLUGINS error code, 148
 ER_CANT_INITIALIZE_GTID error code, 148
 ER_CANT_INITIALIZE_UDF error code, 11
 ER_CANT_INIT_DBS error code, 147
 ER_CANT_INIT_SCHEDULER_THREAD error code, 140
 ER_CANT_INIT_TC_LOG error code, 139
 ER_CANT_INIT_TIMER error code, 149
 ER_CANT_JOIN_SHUTDOWN_THREAD error code, 149
 ER_CANT_LOCK error code, 4
 ER_CANT_LOCK_LOG_TABLE error code, 38
 ER_CANT_LOCK_TABLE error code, 181
 ER_CANT_LOCK_TABLESPACE error code, 181
 ER_CANT_MODIFY_SRID_0 error code, 91
 ER_CANT_MODIFY_SRS_USED_BY_COLUMN error code, 91
 ER_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES error code, 161
 ER_CANT_OPEN_CA error code, 149
 ER_CANT_OPEN_DATADIR_AFTER_UPGRADE_FAILURE error code, 183
 ER_CANT_OPEN_DB_OPT_USING_DEFAULT_CHARSET error code, 181
 ER_CANT_OPEN_DIR error code, 183
 ER_CANT_OPEN_ERROR_LOG error code, 150
 ER_CANT_OPEN_FILE error code, 4
 ER_CANT_OPEN_FRM_FILE error code, 161
 ER_CANT_OPEN_LIBRARY error code, 12
 ER_CANT_OPEN_TABLE_MYSQL_PROC error code, 183
 ER_CANT_PARSE_STORED_ROUTINE_BODY error code, 182
 ER_CANT_PROCESS_EXPRESSION_FOR_GENERATED_COLUMNS error code, 368
 ER_CANT_READ_DIR error code, 4
 ER_CANT_READ_ERRMSG error code, 147
 ER_CANT_READ_FRM_FILE error code, 161
 ER_CANT_READ_TABLE_MYSQL_PROC error code, 183
 ER_CANT_REMOVE_ALL_FIELDS error code, 9
 ER_CANT_REMOVE_PID_FILE error code, 143
 ER_CANT_RENAME_LOG_TABLE error code, 39
 ER_CANT_REOPEN_TABLE error code, 12

ER_CANT_REPLICATE_ANONYMOUS_WITH_AUTO_POSITION error code, 342
 ER_CANT_REPLICATE_ANONYMOUS_WITH_GTID_MODE_OFF error code, 343
 ER_CANT_REPLICATE_GTID_WITH_GTID_MODE_OFF error code, 343
 ER_CANT_RESET_SOURCE error code, 75
 ER_CANT_RUN_COMMAND_SERVICES_RECURSIVELY error code, 127
 ER_CANT_SAVE_GTIDS error code, 149
 ER_CANT_SET_DATA_DIR error code, 351
 ER_CANT_SET_ERROR_LOG_SERVICE error code, 90
 ER_CANT_SET_ERROR_SUPPRESSION_LIST error code, 92
 ER_CANT_SET_ERROR_SUPPRESSION_LIST_FROM_COMMANDLINE error code, 346
 ER_CANT_SET_GTID_MODE error code, 68
 ER_CANT_SET_GTID_NEXT_LIST_TO_NON_NULL_WHEN_GTID_MODE_IS_OFF error code, 53
 ER_CANT_SET_GTID_NEXT_TO_ANONYMOUS_WHEN_GTID_MODE_IS_ON error code, 52
 ER_CANT_SET_GTID_NEXT_TO_AUTOMATIC_TAGGED_ERROR_CODE error code, 130
 ER_CANT_SET_GTID_NEXT_TO_GTID_WHEN_GTID_MODE_IS_OFF error code, 52
 ER_CANT_SET_GTID_NEXT_WHEN_OWNING_GTID error code, 53
 ER_CANT_SET_GTID_PURGED_DUE_SETS_CONSTRAINT error code, 79
 ER_CANT_SET_GTID_PURGED_WHEN_GTID_EXECUTED error code, 56
 ER_CANT_SET_GTID_PURGED_WHEN_OWNED_GTIDS error code, 57
 ER_CANT_SET_HANDLER_REFERENCE_FOR_TABLE error code, 181
 ER_CANT_SET_PATH_FOR error code, 183
 ER_CANT_SET_PERSISTED error code, 126
 ER_CANT_SET_SQL_AFTER_OR_BEFORE_GTIDS_WITH_PERSISTED error code, 115
 ER_CANT_SET_UP_PERSISTED_VALUES error code, 149
 ER_CANT_SET_VARIABLE_WHEN_OWNING_GTID error code, 71
 ER_CANT_START_ERROR_LOG_SERVICE error code, 193
 ER_CANT_STAT_DATADIR error code, 149
 ER_CANT_STAT_FILE error code, 187
 ER_CANT_UPDATE_TABLE_IN_CREATE_TABLE_SELECT error code, 50
 ER_CANT_UPDATE_USED_TABLE_IN_SF_OR_TRG error code, 31
 ER_CANT_UPDATE_WITH_READLOCK error code, 18
 ER_CANT_UPGRADE_GENERATED_COLUMNS_TO_DD error code, 181
 ER_CANT_USE_ANONYMOUS_TO_GTID_WITH_GTID_MODE_NO error code, 114
 ER_CANT_USE_AUTO_POSITION_WITH_GTID_MODE_OFF error code, 69
 ER_CANT_USE_GTID_ONLY_WITH_GTID_MODE_NOT_ON error code, 119
 ER_CANT_USE_OPTION_HERE error code, 19
 ER_CANT_USE_SAME_UUID_AS_GROUP_NAME error code, 115
 ER_CANT_USE_SAME_UUID_AS_VIEW_CHANGE_UUID error code, 116
 ER_CANT_WAIT_FOR_EXECUTED_GTID_SET_WHILE_OWNING error code, 73
 ER_CAPACITY_EXCEEDED error code, 73
 ER_CAPACITY_EXCEEDED_IN_PARSER error code, 74
 ER_CAPACITY_EXCEEDED_IN_RANGE_OPTIMIZER error code, 74
 ER_CHARSET_MODE_IS_OFF error code, 139
 ER_CA_SELF_SIGNED error code, 141
 ER_CHARSET_IS_NOT_ENFORCED_GTID_CONSISTENCY error code, 139
 ER_CHANGED_CHARSET error code, 139
 ER_CHANGED_MAX_CONNECTIONS error code, 146
 ER_CHANGED_MAX_OPEN_FILES error code, 146
 ER_CHANGED_TABLE_OPEN_CACHE error code, 146
 ER_CHANGE_REPLICATION_SOURCE_NO_OPTIONS_FOR_GTID error code, 119
 ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POSITION error code, 119
 ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POS_WITH error code, 119
 ER_CHANGE_REP_SOURCE_CANT_DISABLE_GTID_ONLY_WITH error code, 119
 ER_CHANGE_REP_SOURCE_CANT_DISABLE_REQ_ROW_FORMAT error code, 119
 ER_CHANGE_REP_SOURCE_GR_CHANNEL_WITH_GTID_MODE error code, 119
 ER_CHANGE_REP_SOURCE_PLUGIN error code, 50
 ER_CHANGE_RPL_SRC_WRONG_COMPRESSION_ALGORITHM error code, 116
 ER_CHANGE_SOURCE_PASSWORD_LENGTH error code, 64
 ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM error code, 106
 ER_CHANGE_SOURCE_WRONG_COMPRESSION_ALGORITHM error code, 107
 ER_CHANGE_SOURCE_WRONG_COMPRESSION_LEVEL_CLIENT error code, 106
 ER_CHARACTER_SET_MISMATCH error code, 113
 ER_CHECKING_TABLE error code, 181
 ER_CHECKREAD error code, 4
 ER_CHECK_CONSTRAINT_CLAUSE_USING_FK_REFER_ACTION error code, 99

ER_CHECK_CONSTRAINT_DUP_NAME error code, 99
 ER_CHECK_CONSTRAINT_FUNCTION_IS_NOT_ALLOWED error code, 99
 ER_CHECK_CONSTRAINT_NAMED_FUNCTION_IS_NOT_ALLOWED error code, 99
 ER_CHECK_CONSTRAINT_NOT_FOUND error code, 99
 ER_CHECK_CONSTRAINT_REFERS_AUTO_INCREMENTED_COLUMN error code, 99
 ER_CHECK_CONSTRAINT_REFERS_UNKNOWN_COLUMN error code, 99
 ER_CHECK_CONSTRAINT_ROW_VALUE error code, 99
 ER_CHECK_CONSTRAINT_VARIABLES error code, 99
 ER_CHECK_CONSTRAINT_VIOLATED error code, 99
 ER_CHECK_NOT_IMPLEMENTED error code, 15
 ER_CHECK_NO_SUCH_TABLE error code, 15
 ER_CHECK_TABLE_FUNCTIONS error code, 415
 ER_CHECK_TABLE_FUNCTIONS_DETAIL error code, 415
 ER_CHECK_TABLE_INSTANT_VERSION_BIT_SET error code, 408
 ER_CHECK_TABLE_MIN_REC_FLAG_NOT_SET error code, 410
 ER_CHECK_TABLE_MIN_REC_FLAG_SET error code, 410
 ER_CLIENT_DOES_NOT_SUPPORT error code, 86
 ER_CLIENT_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS error code, 123
 ER_CLIENT_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN_UTC error code, 93
 ER_CLIENT_INTERACTION_TIMEOUT error code, 116
 ER_CLIENT_KEYRING_UDF_KEY_INVALID error code, 107
 ER_CLIENT_KEYRING_UDF_KEY_TOO_LONG error code, 107
 ER_CLIENT_KEYRING_UDF_KEY_TYPE_INVALID error code, 107
 ER_CLIENT_KEYRING_UDF_KEY_TYPE_TOO_LONG error code, 107
 ER_CLIENT_LOCAL_FILES_DISABLED error code, 109
 ER_CLIENT_PRIVILEGE_CHECKS_USER_CANNOT_BE_PROMOTED error code, 107
 ER_CLIENT_PRIVILEGE_CHECKS_USER_CORRUPT error code, 107
 ER_CLIENT_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST error code, 107
 ER_CLIENT_PRIVILEGE_CHECKS_USER_NEEDS_RPL_APPLICATION error code, 107
 ER_CLIENT_QUERY_FAILURE_INVALID_NON_ROW_FORMAT error code, 108
 ER_CLONE_CHARSET error code, 103
 ER_CLONE_CLIENT_TRACE error code, 351
 ER_CLONE_CONFIG error code, 103
 ER_CLONE_CREATE_HANDLER_FAIL_TRACE error code, 200
 ER_CLONE_DDL_IN_PROGRESS error code, 85
 ER_CLONE_DISABLED error code, 103
 ER_CLONE_DISALLOWED error code, 103
 ER_CLONE_DISK_SPACE error code, 103
 ER_CLONE_DONOR error code, 102
 ER_CLONE_DONOR_TRACE error code, 351
 ER_CLONE_DONOR_VERSION error code, 102
 ER_CLONE_ENCRYPTION error code, 103
 ER_CLONE_HANDLER_EXIST_TRACE error code, 200
 ER_CLONE_IN_PROGRESS error code, 103
 ER_CLONE_LOOPBACK error code, 103
 ER_CLONE_NETWORK_PACKET error code, 109
 ER_CLONE_OS error code, 103
 ER_CLONE_PLATFORM error code, 103
 ER_CLONE_PLUGIN_MATCH error code, 103
 ER_CLONE_PLUGIN_NOT_LOADED_TRACE error code, 200
 ER_CLONE_PROTOCOL error code, 102
 ER_CLONE_PROTOCOL_TRACE error code, 351
 ER_CLONE_SERVER_TRACE error code, 351
 ER_CLONE_SHUTDOWN_TRACE error code, 365
 ER_CLONE_SYS_CONFIG error code, 103
 ER_CLONE_TOO_MANY_CONCURRENT_CLONES error code, 85
 ER_CMD_NEED_SUPER error code, 85
 ER_COALESCE_ONLY_ON_HASH_PARTITION error code, 36
 ER_COALESCE_PARTITION_NO_PARTITION error code, 36
 ER_COLUMN_CHARSET_IN_SBR error code, 86
 ER_COLLATION_CHARSET_MISMATCH error code, 20
 ER_COLUMNACCESS_DENIED_ERROR error code, 13
 ER_COLUMN_CHANGE_SIZE error code, 104
 ER_COLUMN_CHECK_CONSTRAINT_REFERENCES_OTHER_TABLE error code, 99
 ER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2 error code, 54
 ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE error code, 38
 ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V2 error code, 61
 ER_COMMANDS_BACKEND_FAILED_TO_FETCH_SECURITY_CONTEXT error code, 122
 ER_COMMAND_SERVICE_BACKEND_FAILED error code, 123
 ER_COMMENT_CONTAINS_INVALID_STRING error code, 121
 ER_COMPONENTS_NOT_ALLOWED_IN_SF_OR_TRG error code, 30
 ER_COMPONENTS_CANT_ACQUIRE_SERVICE_IMPLEMENTATION error code, 78
 ER_COMPONENTS_CANT_LOAD error code, 78
 ER_COMPONENTS_CANT_RELEASE_SERVICE error code, 78

ER_COMPONENTS_CANT_SATISFY_DEPENDENCY error code, 78	ER_COMPONENT_EE_FUNCTION_REGISTRATION_FAILURE error code, 402
ER_COMPONENTS_CANT_UNLOAD error code, 79	ER_COMPONENT_EE_INSUFFICIENT_LENGTH error code, 403
ER_COMPONENTS_FAILED_TO_ACQUIRE_SERVICE_IMPL error code, 203	ER_COMPONENT_EE_OPENSSL_ERROR error code, 403
ER_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP error code, 141	ER_COMPONENT_EE_SYS_VAR_DEREGISTRATION_FAILURE error code, 402
ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_DEINIT error code, 384	ER_COMPONENT_EE_SYS_VAR_REGISTRATION_FAILURE error code, 402
ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_INIT error code, 384	ER_COMPONENT_FILTER_CONFUSED error code, 218
ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN error code, 141	ER_COMPONENT_FILTER_DIAGNOSTICS error code, 218
ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN_END error code, 417	ER_COMPONENT_FILTER_FLABBERGASTED error code, 84
ER_COMPONENTS_INFRASTRUCTURE_SHUTDOWN_START error code, 417	ER_COMPONENT_FILTER_WRONG_VALUE error code, 340
ER_COMPONENTS_LOAD_CANT_INITIALIZE error code, 78	ER_COMPONENT_KEYRING_OCI_CREATE_PRIVATE_KEY error code, 404
ER_COMPONENTS_LOAD_CANT_REGISTER_SERVICE_IMPL error code, 78	ER_COMPONENT_KEYRING_OCI_INVALID_CONFIG_VAR error code, 418
ER_COMPONENTS_NO_SCHEME error code, 78	ER_COMPONENT_KEYRING_OCI_OPEN_KEY_FILE error code, 404
ER_COMPONENTS_NO_SCHEME_SERVICE error code, 78	ER_COMPONENT_KEYRING_OCI_READ_KEY_FILE error code, 404
ER_COMPONENTS_PERSIST_LOADER_BOOTSTRAP error code, 141	ER_COMPONENT_LOCK error code, 412
ER_COMPONENTS_UNLOAD_CANT_DEINITIALIZE error code, 78	ER_COMPONENT_MANIPULATE_ROW_FAILED error code, 79
ER_COMPONENTS_UNLOAD_CANT_UNREGISTER_SERVICE error code, 79	ER_COMPONENT_MASKING_ABI error code, 412
ER_COMPONENTS_UNLOAD_DUPLICATE_IN_GROUP error code, 79	ER_COMPONENT_MASKING_ABI_REASON error code, 413
ER_COMPONENTS_UNLOAD_NOT_LOADED error code, 78	ER_COMPONENT_MASKING_CANNOT_ACCESS_TABLE error code, 413
ER_COMPONENT_EE_DATA_DECRYPTION_ERROR error code, 403	ER_COMPONENT_MASKING_INVALID_FLUSH_INTERVAL_VALUE error code, 424
ER_COMPONENT_EE_DATA_ENCRYPTION_ERROR error code, 403	ER_COMPONENT_MASKING_NOTIFICATION_REGISTRATION_FA error code, 424
ER_COMPONENT_EE_DATA_LENGTH_OUT_OF_RANGE error code, 403	ER_COMPONENT_MASKING_OTHER_ERROR error code, 412
ER_COMPONENT_EE_DATA_SIGN_ERROR error code, 403	ER_COMPONENT_MASKING_RANDOM_CREATE error code, 413
ER_COMPONENT_EE_FUNCTION_DEREGISTRATION_FAIL error code, 402	ER_COMPONENT_MASKING_RANDOM_CREATE_REASON error code, 413
ER_COMPONENT_EE_FUNCTION_INVALID_ALGORITHM error code, 403	ER_COMPONENT_MASKING_VAR_REGISTRATION_FAILURE error code, 424
ER_COMPONENT_EE_FUNCTION_INVALID_ARGUMENTS error code, 403	ER_COMPONENT_SERVICE_CALL error code, 412
ER_COMPONENT_EE_FUNCTION_KEY_LENGTH_OUT_OF error code, 403	ER_COMPONENT_SERVICE_CALL_RESULT error code, 412
ER_COMPONENT_EE_FUNCTION_PRIVATE_KEY_GENERA error code, 403	ER_COMPONENT_TABLE_INCORRECT error code, 79
ER_COMPONENT_EE_FUNCTION_PUBLIC_KEY_GENERA error code, 403	ER_COMPONENT_TABLE_UNLOCK error code, 412
	ER_CONCURRENT_PROCEDURE_USAGE error code, 412
	ER_CONDITIONAL_DEBUG error code, 404

ER_COND_ITEM_TOO_LONG error code, 43
 ER_CONFIG_OPTION_WITHOUT_GROUP error code, 151
 ER_CONFIRMING_THE_FUTURE error code, 144
 ER_CONFLICTING_DECLARATIONS error code, 23
 ER_CONFLICT_FN_PARSE_ERROR error code, 42
 ER_CONNECTIONS_SHUTDOWN_END error code, 417
 ER_CONNECTIONS_SHUTDOWN_START error code, 417
 ER_CONNECTION_ABORTED error code, 339
 ER_CONNECTION_HANDLING_OOM error code, 143
 ER_CONNECTION_METADATA error code, 16
 ER_CONNECT_TO_FOREIGN_DATA_SOURCE error code, 30
 ER_CONNECT_TO_SOURCE error code, 18
 ER_CONN_ATTR_TRUNCATED error code, 156
 ER_CONN_CONTROL_DELAY_ACTION_INIT_FAILED error code, 219
 ER_CONN_CONTROL_ERROR_MSG error code, 217
 ER_CONN_CONTROL_EVENT_COORDINATOR_INIT_FAILED error code, 218
 ER_CONN_CONTROL_FAILED_TO_SET_CONN_DELAY error code, 219
 ER_CONN_CONTROL_FAILED_TO_UPDATE_CONN_DELAY error code, 219
 ER_CONN_CONTROL_INVALID_CONN_DELAY_TYPE error code, 219
 ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED error code, 219
 ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED error code, 218
 ER_CONN_INIT_CONNECT_IGNORED error code, 218
 ER_CONN_INIT_CONNECT_IGNORED_MFA error code, 413
 ER_CONN_LIMIT error code, 395
 ER_CONN_PER_THREAD_NO_THREAD error code, 154
 ER_CONN_PIP_CANT_CREATE_EVENT error code, 154
 ER_CONN_PIP_CANT_CREATE_PIPE error code, 154
 ER_CONN_SHM_CANT_CREATE_CONNECTION error code, 153
 ER_CONN_SHM_CANT_CREATE_SERVICE error code, 153
 ER_CONN_SHM_LISTENER error code, 153
 ER_CONN_SOCKET_ACCEPT_FAILED error code, 156
 ER_CONN_SOCKET_SELECT_FAILED error code, 156
 ER_CONN_TCP_ADDRESS error code, 154
 ER_CONN_TCP_BIND_FAIL error code, 155
 ER_CONN_TCP_BIND_RETRY error code, 155
 ER_CONN_TCP_CANT_RESET_V6ONLY error code, 154
 ER_CONN_TCP_CANT_RESOLVE_HOSTNAME error code, 154
 ER_CONN_TCP_CREATED error code, 154
 ER_CONN_TCP_ERROR_WITH_STRError error code, 154
 ER_CONN_TCP_IPV6_AVAILABLE error code, 154
 ER_CONN_TCP_IPV6_UNAVAILABLE error code, 154
 ER_CONN_TCP_IP_NOT_LOGGED error code, 155
 ER_CONN_TCP_IS_THERE_ANOTHER_USING_PORT error code, 154
 ER_CONN_TCP_LISTEN_FAIL error code, 155
 ER_CONN_TCP_NO_SOCKET error code, 154
 ER_CONN_TCP_RESOLVE_INFO error code, 155
 ER_CONN_TCP_START_FAIL error code, 155
 ER_CONN_UNIX_IS_THERE_ANOTHER_USING_SOCKET error code, 154
 ER_CONN_UNIX_LISTEN_FAILED error code, 155
 ER_CONN_UNIX_LOCK_FILE_CANT_CLOSE error code, 156
 ER_CONN_UNIX_LOCK_FILE_CANT_CREATE error code, 155
 ER_CONN_UNIX_LOCK_FILE_CANT_DELETE error code, 156
 ER_CONN_UNIX_LOCK_FILE_CANT_OPEN error code, 155
 ER_CONN_UNIX_LOCK_FILE_CANT_READ error code, 155
 ER_CONN_UNIX_LOCK_FILE_CANT_SYNC error code, 155
 ER_CONN_UNIX_LOCK_FILE_CANT_WRITE error code, 155
 ER_CONN_UNIX_LOCK_FILE_EMPTY error code, 156
 ER_CONN_UNIX_LOCK_FILE_FAIL error code, 155
 ER_CONN_UNIX_LOCK_FILE_GIVING_UP error code, 155
 ER_CONN_UNIX_LOCK_FILE_PIDLESS error code, 156
 ER_CONN_UNIX_NO_BIND_NO_START error code, 155
 ER_CONN_UNIX_NO_FD error code, 155
 ER_CONN_UNIX_PATH_TOO_LONG error code, 155
 ER_CONN_UNIX_PID_CLAIMED_SOCKET_FILE error code, 154
 ER_CONSECUTIVE_REORG_PARTITIONS error code, 36
 ER_CONSTRAINT_NOT_FOUND error code, 108
 ER_CONVERT_MULTI_VALUE error code, 413
 ER_CON_COUNT_ERROR error code, 5
 ER_CORE_VALUES error code, 144
 ER_CORRUPTED_JSON_DIFF error code, 86
 ER_CORRUPT_HELP_DB error code, 19
 ER_COULD_NOT_APPLY_JSON_DIFF error code, 86
 ER_COULD_NOT_CREATE_WINDOWS_REGISTRY_KEY error code, 348

ER_COULD_NOT_REINITIALIZE_AUDIT_LOG_FILTERS error code, 344
 ER_CRASHED_ON_REPAIR error code, 16
 ER_CRASHED_ON_USAGE error code, 16
 ER_CREATED_SYSTEM_WITH_VERSION error code, 199
 ER_CREATE_FILEGROUP_FAILED error code, 37
 ER_CREATE_SELECT_WITH_GIPK_DISALLOWED_IN_SCHEMA error code, 122
 ER_CREATING_NEW_UUID error code, 142
 ER_CREATING_NEW_UUID_FIRST_START error code, 193
 ER_CREDENTIALLESS_AUTO_USER_BAD error code, 143
 ER_CREDENTIALS_CONTRADICT_TO_HISTORY error code, 85
 ER_CTE_MAX_RECURSION_DEPTH error code, 85
 ER_CTE_RECURSIVE_FORBIDDEN_JOIN_ORDER error code, 81
 ER_CTE_RECURSIVE_FORBIDS_AGGREGATION error code, 81
 ER_CTE_RECURSIVE_NOT_UNION error code, 122
 ER_CTE_RECURSIVE_REQUIRES_NONRECURSIVE_FIRST error code, 81
 ER_CTE_RECURSIVE_REQUIRES_SINGLE_REFERENCE error code, 81
 ER_CTE_RECURSIVE_REQUIRES_UNION error code, 81
 ER_CURRENT_PASSWORD_CANNOT_BE_RETAINED error code, 105
 ER_CURRENT_PASSWORD_NOT_REQUIRED error code, 104
 ER_CUT_VALUE_GROUP_CONCAT error code, 20
 ER_CYCLE_TIMER_IS_NOT_AVAILABLE error code, 200
 ER_DATABASE_NAME error code, 42
 ER_DATA_DIRECTORY_UNUSABLE error code, 349
 ER_DATA_DIRECTORY_UNUSABLE_DELETABLE error code, 364
 ER_DATA_INCOMPATIBLE_WITH_VECTOR error code, 136
 ER_DATA_OUT_OF_RANGE error code, 46
 ER_DATA_TOO_LONG error code, 29
 ER_DATETIME_FUNCTION_OVERFLOW error code, 31
 ER_DA_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDATORY error code, 104
 ER_DA_CANT_OPEN_ERROR_LOG error code, 113
 ER_DA_CONN_LIMIT error code, 120
 ER_DA_ERROR_LOG_COMPONENT_FLUSH_FAILED error code, 117
 ER_DA_ERROR_LOG_MULTIPLE_FILTERS error code, 113
 ER_DA_ERROR_LOG_TABLE_DISABLED error code, 113
 ER_DA_GLOBAL_CONN_LIMIT error code, 120
 ER_DA_GRP_RPL_RECOVERY_ENDPOINT_FORMAT error code, 111
 ER_DA_GRP_RPL_RECOVERY_ENDPOINT_INVALID error code, 111
 ER_DA_GRP_RPL_STARTED_AUTO_REJOIN error code, 106
 ER_DA_INVALID_CONDITION_NUMBER error code, 51
 ER_DA_NO_ERROR_LOG_PARSER_CONFIGURED error code, 113
 ER_DA_OOM error code, 109
 ER_DA_PLUGIN_INSTALL_ERROR error code, 104
 ER_DA_RPL_GTID_TABLE_CANNOT_OPEN error code, 104
 ER_DA_SSL_FIPS_MODE_ERROR error code, 119
 ER_DA_SSL_LIBRARY_ERROR error code, 104
 ER_DA_UDF_INVALID_ARGUMENT_TO_SET_CHARSET error code, 109
 ER_DA_UDF_INVALID_CHARSET error code, 108
 ER_DA_UDF_INVALID_CHARSET_SPECIFIED error code, 108
 ER_DA_UDF_INVALID_COLLATION error code, 108
 ER_DA_UDF_INVALID_EXTENSION_ARGUMENT_TYPE error code, 108
 ER_DA_UDF_INVALID_RETURN_TYPE_TO_SET_CHARSET error code, 109
 ER_DA_UNKNOWN_ERROR_NUMBER error code, 104
 ER_DBACCESS_DENIED_ERROR error code, 6
 ER_DEBUG_CHECK_SHARES_DROPPED error code, 170
 ER_DEBUG_CHECK_SHARES_INFO error code, 170
 ER_DEBUG_CHECK_SHARES_OPEN error code, 170
 ER_DB_ACCESS_DENIED error code, 103
 ER_DB_CREATE_EXISTS error code, 4
 ER_DB_DROP_EXISTS error code, 4
 ER_DB_DROP_RMDIR error code, 4
 ER_DB_DROP_RMDIR2 error code, 83
 ER_DB_OPT_NOT_FOUND_USING_DEFAULT_CHARSET error code, 182
 ER_DDL_MSG_1 error code, 390
 ER_DD_ABORTING_PARTIAL_UPGRADE error code, 160
 ER_DD_CACHE_NOT_EMPTY_AT_SHUTDOWN error code, 138
 ER_DD_CANT_CREATE_OBJECT_KEY error code, 139
 ER_DD_CANT_CREATE_SP error code, 181
 ER_DD_CANT_FETCH_TABLE_DATA error code, 181
 ER_DD_CANT_FIX_SE_DATA error code, 181
 ER_DD_CANT_GET_OBJECT_KEY error code, 139
 ER_DD_CANT_RESOLVE_VIEW error code, 150
 ER_DD_CREATED_FOR_UPGRADE error code, 160
 ER_DD_ERROR_CREATING_ENTRY error code, 181

ER_DD_FAILSAFE error code, 137
 ER_DD_FRM_EXISTS_FOR_TABLE error code, 160
 ER_DD_INITIALIZE error code, 204
 ER_DD_INITIALIZE_SQL_ERROR error code, 345
 ER_DD_INIT_FAILED error code, 138
 ER_DD_INIT_UPGRADE_FAILED error code, 138
 ER_DD_METADATA_NOT_FOUND error code, 138
 ER_DD_MINOR_DOWNGRADE error code, 205
 ER_DD_MINOR_DOWNGRADE_VERSION_NOT_SUPPORTED error code, 205
 ER_DD_NO_VERSION_FOUND error code, 205
 ER_DD_NO_WRITES_NO_REPOPULATION error code, 137
 ER_DD_OBJECT_RELEASER_REMAINS error code, 138
 ER_DD_OBJECT_REMAINS error code, 138
 ER_DD_OBJECT_REMAINS_IN_RELEASER error code, 138
 ER_DD_RESTART error code, 204
 ER_DD_SCHEMA_NOT_FOUND error code, 160
 ER_DD_SE_INIT_FAILED error code, 160
 ER_DD_TABLESPACE_NOT_FOUND error code, 150
 ER_DD_TABLE_NOT_FOUND error code, 160
 ER_DD_TRG_CANT_ADD error code, 150
 ER_DD_TRG_CONNECTION_COLLATION_MISSING error code, 150
 ER_DD_TRG_DB_COLLATION_MISSING error code, 150
 ER_DD_TRG_DEFINER_OOM error code, 150
 ER_DD_TRG_FILE_UNREADABLE error code, 150
 ER_DD_UPDATE_DATADIR_FLAG_FAIL error code, 428
 ER_DD_UPDATING_PLUGIN_MD_FAILED error code, 138
 ER_DD_UPGRADE error code, 204
 ER_DD_UPGRADE_COMPLETED error code, 362
 ER_DD_UPGRADE_DD_OPEN_FAILED error code, 197
 ER_DD_UPGRADE_DD_POPULATED error code, 198
 ER_DD_UPGRADE_FAILED_FIND_VALID_DATA_DIR error code, 198
 ER_DD_UPGRADE_FAILED_INIT_DD_SE error code, 198
 ER_DD_UPGRADE_FAILED_TO_ACQUIRE_TABLESPACE error code, 197
 ER_DD_UPGRADE_FAILED_TO_CREATE_INDEX_STATS error code, 198
 ER_DD_UPGRADE_FAILED_TO_CREATE_TABLE_STATS error code, 198
 ER_DD_UPGRADE_FAILED_TO_FETCH_TABLES error code, 198
 ER_DD_UPGRADE_FAILED_TO_FETCH_TABLESPACES error code, 197
 ER_DD_UPGRADE_FAILED_TO_RESOLVE_TABLESPACE error code, 197
 ER_DD_UPGRADE_FAILED_TO_UPDATE_VER_NO_IN_TABLE error code, 204
 ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD_AB error code, 199
 ER_DD_UPGRADE_FOUND_PARTIALLY_UPGRADED_DD_CO error code, 199
 ER_DD_UPGRADE_INDEX_STATS_MIGRATE_COMPLETED error code, 198
 ER_DD_UPGRADE_INFO_FILE_CLOSE_FAILED error code, 198
 ER_DD_UPGRADE_INFO_FILE_OPEN_FAILED error code, 198
 ER_DD_UPGRADE_OFF error code, 204
 ER_DD_UPGRADE_RENAME_IDX_STATS_FILE_FAILED error code, 197
 ER_DD_UPGRADE_SCHEMA_UNAVAILABLE error code, 205
 ER_DD_UPGRADE_SDI_INFO_UPDATE_FAILED error code, 199
 ER_DD_UPGRADE_SE_LOGS_FAILED error code, 199
 ER_DD_UPGRADE_START error code, 198
 ER_DD_UPGRADE_TABLESPACE_MIGRATION_FAILED error code, 198
 ER_DD_UPGRADE_TABLE_INTACT_ERROR error code, 202
 ER_DD_UPGRADE_TABLE_STATS_MIGRATE_COMPLETED error code, 198
 ER_DD_UPGRADE_VERSION_NOT_SUPPORTED error code, 205
 ER_DD_UPGRADE_VIEW_COLUMN_NAME_TOO_LONG error code, 204
 ER_DD_VERSION_FOUND error code, 137
 ER_DD_VERSION_INSTALLED error code, 137
 ER_DD_VERSION_UNSUPPORTED error code, 137
 ER_DD_VIEW_CANT_ALLOC_CHARSET error code, 138
 ER_DD_VIEW_CANT_CREATE error code, 138
 ER_DD_VIEW_WITHOUT_DEFINER error code, 150
 ER_DEBUG_SYNC_EXECUTED error code, 139
 ER_DEBUG_SYNC_HIT error code, 139
 ER_DEBUG_SYNC_HIT_LIMIT error code, 43
 ER_DEBUG_SYNC_OOM error code, 139
 ER_DEBUG_SYNC_THREAD_MAX error code, 139
 ER_DEBUG_SYNC_TIMEOUT error code, 43
 ER_DEFAULT_AS_VAL_GENERATED error code, 95
 ER_DEFAULT_SE_UNAVAILABLE error code, 149
 ER_DEFAULT_VAL_GENERATED_FUNCTION_IS_NOT_ALLOWED error code, 95
 ER_DEFAULT_VAL_GENERATED_NAMED_FUNCTION_IS_NOT_ALLOWED error code, 95
 ER_DEFAULT_VAL_GENERATED_NON_PRIOR error code, 95
 ER_DEFAULT_VAL_GENERATED_REF_AUTO_INC error code, 95

ER_DEFAULT_VAL_GENERATED_ROW_VALUE error code, 95
 ER_DEFAULT_VAL_GENERATED_VARIABLES error code, 95
 ER_DEFINITION_CONTAINS_INVALID_STRING error code, 121
 ER_DEPART_WITH_GRACE error code, 141
 ER_DEPENDENT_BY_CHECK_CONSTRAINT error code, 110
 ER_DEPENDENT_BY_DEFAULT_GENERATED_VALUE error code, 95
 ER_DEPENDENT_BY_FUNCTIONAL_INDEX error code, 100
 ER_DEPENDENT_BY_GENERATED_COLUMN error code, 68
 ER_DEPENDENT_BY_PARTITION_FUNC error code, 102
 ER_DEPRECATED_NATIONAL error code, 91
 ER_DEPRECATED_PERSISTED_VARIABLE_WITH_ALIAS error code, 389
 ER_DEPRECATED_SYNTAX_NO_REPLACEMENT error code, 203
 ER_DEPRECATED_SYNTAX_WITH_REPLACEMENT error code, 203
 ER_DEPRECATED_TIMESTAMP_IMPLICIT_DEFAULTS error code, 143
 ER_DEPRECATED_UTF8_ALIAS error code, 91
 ER_DEPRECATE_MSG_NO_REPLACEMENT error code, 203
 ER_DEPRECATE_MSG_WITH_REPLACEMENT error code, 192
 ER_DERIVED_MUST_HAVE_ALIAS error code, 19
 ER_DES_FILE_WRONG_KEY error code, 151
 ER_DETACHED_SESSIONS_LEFT_BY_PLUGIN error code, 169
 ER_DETACHING_SESSION_LEFT_BY_PLUGIN error code, 169
 ER_DIMENSION_UNSUPPORTED error code, 65
 ER_DISABLED_STORAGE_ENGINE error code, 72
 ER_DISABLED_STORAGE_ENGINE_AS_DEFAULT error code, 139
 ER_DISABLE_AUTO_POSITION_REQUIRES_ASYNC_RECONNECTION error code, 112
 ER_DISABLE_GTID_MODE_REQUIRES_ASYNC_RECONNECTION error code, 112
 ER_DISALLOWED_OPERATION error code, 87
 ER_DISCARD_FK_CHECKS_RUNNING error code, 54
 ER_DISCONNECTING_REMAINING_CLIENTS error code, 145
 ER_DISK_FULL_NOWAIT error code, 88
 ER_DIVISION_BY_ZERO error code, 27
 ER_DONT_SUPPORT_REPLICA_PRESERVE_COMMIT_ORDER error code, 62
 ER_DROP_DATABASE_FAILED_RMDIR_MANUALLY error code, 204
 ER_DROP_FILEGROUP_FAILED error code, 37
 ER_DROP_INDEX_FK error code, 38
 ER_DROP_LAST_PARTITION error code, 36
 ER_DROP_PARTITION_NON_EXISTENT error code, 35
 ER_DROP_PK_COLUMN_TO_DROP_GIPK error code, 122
 ER_DUPLICATED_VALUE_IN_TYPE error code, 22
 ER_DUPLICATE_OPTION_KEY error code, 80
 ER_DUPLICATE_SYS_VAR error code, 345
 ER_DUPLICATE_TABLE_LOCK error code, 81
 ER_DUP_ARGUMENT error code, 18
 ER_DUP_ENTRY error code, 7
 ER_DUP_ENTRY_AUTOINCREMENT_CASE error code, 39
 ER_DUP_ENTRY_WITH_KEY_NAME error code, 40
 ER_DUP_FD_OPEN_FAILED error code, 193
 ER_DUP_FIELDNAME error code, 7
 ER_DUP_INDEX error code, 56
 ER_DUP_KEY error code, 4
 ER_DUP_KEYNAME error code, 7
 ER_DUP_LIST_ENTRY error code, 62
 ER_DUP_SIGNAL_SET error code, 43
 ER_DUP_UNIQUE error code, 14
 ER_DUP_UNKNOWN_IN_INDEX error code, 58
 ER_EMPTY_PIPELINE_FOR_ERROR_LOG_SERVICE error code, 90
 ER_EMPTY_PRIVILEGE_NAME_IGNORED error code, 380
 ER_EMPTY_QUERY error code, 7
 ER_ENDING_INIT error code, 344
 ER_END_INITFILE error code, 146
 ER_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING_G error code, 69
 ER_ENGINE_ATTRIBUTE_NOT_SUPPORTED error code, 111
 ER_ENGINE_CANNOT_BE_DEFAULT error code, 135
 ER_ENGINE_CANT_DROP_MISSING_TABLE error code, 83
 ER_ENGINE_CANT_DROP_TABLE error code, 83
 ER_ENGINE_CANT_CONNECT_TO_READ error code, 167
 ER_ENGINE_COST_INVALID_CONST_CONSTANT_FOR_SE_AND error code, 167
 ER_ENGINE_COST_INVALID_DEVICE_TYPE_FOR_SE error code, 167
 ER_ENGINE_COST_UNKNOWN_COST_CONSTANT error code, 167
 ER_ENGINE_COST_UNKNOWN_STORAGE_ENGINE error code, 167
 ER_ENGINE_OUT_OF_MEMORY error code, 61
 ER_ERRMSG_CANT_FIND_FILE error code, 160
 ER_ERRMSG_CANT_READ error code, 160

ER_ERRMSG_MISSING_IN_FILE error code, 160
 ER_ERRMSG_OOM error code, 160
 ER_ERRMSG_REPLACEMENTS_FAILED error code, 189
 ER_ERRMSG_REPLACEMENT_DODGY error code, 189
 ER_ERROR_DURING_COMMIT error code, 15
 ER_ERROR_DURING_FLUSH_LOGS error code, 15
 ER_ERROR_DURING_FLUSH_LOG_COMMIT_PHASE error code, 203
 ER_ERROR_DURING_OPTIMIZE_TABLE error code, 180
 ER_ERROR_DURING_ROLLBACK error code, 15
 ER_ERROR_ENABLING_KEYS error code, 180
 ER_ERROR_INFO_FROM_DA error code, 342
 ER_ERROR_IN_TRIGGER_BODY error code, 47
 ER_ERROR_IN_UNKNOWN_TRIGGER_BODY error code, 47
 ER_ERROR_LOG_DESTINATION_NOT_A_FILE error code, 380
 ER_ERROR_ON_MODIFYING_GTID_EXECUTED_TABLE error code, 74
 ER_ERROR_ON_READ error code, 4
 ER_ERROR_ON_RENAME error code, 5
 ER_ERROR_ON_SOURCE error code, 60
 ER_ERROR_ON_WRITE error code, 5
 ER_ERROR_WHEN_EXECUTING_COMMAND error code, 18
 ER_EVENT_ALREADY_EXISTS error code, 37
 ER_EVENT_CANNOT_ALTER_IN_THE_PAST error code, 40
 ER_EVENT_CANNOT_CREATE_IN_THE_PAST error code, 40
 ER_EVENT_CANT_FIND_TIMEZONE error code, 182
 ER_EVENT_CANT_GET_CHARSET error code, 182
 ER_EVENT_CANT_GET_COLLATION error code, 182
 ER_EVENT_CANT_GET_LOCK_FOR_DROPPING_EVENT error code, 183
 ER_EVENT_CANT_GET_TIMEZONE_FROM_FIELD error code, 182
 ER_EVENT_CANT_INIT_QUEUE error code, 139
 ER_EVENT_CANT_OPEN_TABLE_MYSQL_EVENT error code, 182
 ER_EVENT_DOES_NOT_EXIST error code, 37
 ER_EVENT_DROPPING error code, 168
 ER_EVENT_ENDS_BEFORE_STARTS error code, 37
 ER_EVENT_ERROR_CREATING_QUERY_TO_WRITE_TO_BINLOG error code, 183
 ER_EVENT_ERROR_DURING_COMPILATION error code, 168
 ER_EVENT_EXECUTION_FAILED error code, 140
 ER_EVENT_EXECUTION_FAILED_CANT_AUTHENTICATE error code, 168
 ER_EVENT_EXECUTION_FAILED_USER_LOST_EVEN_PRIVILEGES error code, 168
 ER_EVENT_EXEC_TIME_IN_THE_PAST error code, 38
 ER_EVENT_INTERVAL_NOT_POSITIVE_OR_TOO_BIG error code, 37
 ER_EVENT_INVALID_CREATION_CTX error code, 41
 ER_EVENT_LAST_EXECUTION error code, 140
 ER_EVENT_MESSAGE_STACK error code, 140
 ER_EVENT_PURGING_QUEUE error code, 140
 ER_EVENT_RECURSION_FORBIDDEN error code, 39
 ER_EVENT_SAME_NAME error code, 38
 ER_EVENT_SCHEDULER_ERROR_GETTING_EVENT_OBJECT error code, 183
 ER_EVENT_SCHEDULER_ERROR_LOADING_FROM_DB error code, 183
 ER_EVENT_SCHEDULER_GOT_BAD_DATA_FROM_TABLE error code, 183
 ER_EVENT_SET_VAR_ERROR error code, 39
 ER_EVENT_UNABLE_TO_DROP_EVENT error code, 183
 ER_EXCEEDED_MV_KEYS_NUM error code, 105
 ER_EXCEEDED_MV_KEYS_SPACE error code, 105
 ER_EXCEEDS_VECTOR_MAX_DIMENSIONS error code, 136
 ER_EXCEPTIONS_WRITE_ERROR error code, 42
 ER_EXCESS_ARGUMENTS error code, 147
 ER_EXPLAIN_INTO_ANALYZE_NOT_SUPPORTED error code, 127
 ER_EXPLAIN_INTO_FORMAT_NOT_SUPPORTED error code, 127
 ER_EXPLAIN_INTO_FOR_CONNECTION_NOT_SUPPORTED error code, 127
 ER_EXPLAIN_INTO_IMPLICIT_FORMAT_NOT_SUPPORTED error code, 127
 ER_EXPLAIN_NOT_SUPPORTED error code, 61
 ER_EXTERNAL_UNSUPPORTED_INDEX_ALGORITHM error code, 136
 ER_FAILED_DEFAULT_ROLES error code, 78
 ER_FAILED_GET_DD_PROPERTY error code, 414
 ER_FAILED_READ_FROM_PAR_FILE error code, 46
 ER_FAILED_REVOKE_ROLE error code, 78
 ER_FAILED_ROLE_GRANT error code, 77
 ER_FAILED_SET_DD_PROPERTY error code, 414
 ER_FAILED_START_MYSQLD_DAEMON error code, 193
 ER_FAILED_TO_ACQUIRE_LOCK_ON_RESOURCE_GROUP error code, 196
 ER_FAILED_TO_ADD_RESOURCE_GROUP_TO_MAP error code, 196
 ER_FAILED_TO_ADD_RPL_FILTER error code, 200
 ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP error code, 195
 ER_FAILED_TO_ALLOCATE_MEMORY_FOR_RESOURCE_GROUP error code, 195

ER_FAILED_TO_ALLOCATE_SSL_BIO error code, 345
 ER_FAILED_TO_APPLY_RESOURCE_GROUP_CONTROLS error code, 196
 ER_FAILED_TO_BINLOG_DROP_EVENT error code, 199
 ER_FAILED_TO_BUILD_DO_AND_IGNORE_TABLE_HASHES error code, 200
 ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE error code, 164
 ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE_COPY error code, 164
 ER_FAILED_TO_CONSTRUCT_DROP_EVENT_QUERY error code, 199
 ER_FAILED_TO_CREATE_GTID_TABLE_COMPRESSION_INDEX error code, 164
 ER_FAILED_TO_CREATE_SDI_FOR_TABLESPACE error code, 197
 ER_FAILED_TO_DECREMENT_NUMBER_OF_THREADS error code, 169
 ER_FAILED_TO_DELETE_FROM_GTID_EXECUTED_TABLE error code, 164
 ER_FAILED_TO_DESERIALIZE_RESOURCE_GROUP error code, 195
 ER_FAILED_TO_DETERMINE_IF_ROLE_IS_MANDATORY error code, 109
 ER_FAILED_TO_FETCH_MANDATORY_ROLE_LIST error code, 109
 ER_FAILED_TO_FIND_COLLATION_NAME error code, 192
 ER_FAILED_TO_FIND_DL_ENTRY error code, 190
 ER_FAILED_TO_FIND_LOCALE_NAME error code, 192
 ER_FAILED_TO_FIND_MYSQLD_STATUS error code, 203
 ER_FAILED_TO_GENERATE_UNIQUE_LOGFILE error code, 191
 ER_FAILED_TO_GET_ABSOLUTE_PATH error code, 193
 ER_FAILED_TO_HANDLE_DEFAULTS_FILE error code, 345
 ER_FAILED_TO_INIT_SYS_VAR error code, 345
 ER_FAILED_TO_INIT_THREAD_ATTR_FOR_GTID_TABLE_COMPRESSION error code, 164
 ER_FAILED_TO_JOIN_GTID_TABLE_COMPRESSION_THREADS error code, 164
 ER_FAILED_TO_LOCK_MEM error code, 146
 ER_FAILED_TO_OPEN_COST_CONSTANT_TABLES error code, 167
 ER_FAILED_TO_OPEN_SHARED_LIBRARY error code, 190
 ER_FAILED_TO_PERSIST_RESOURCE_GROUP_METADATA error code, 195
 ER_FAILED_TO_READ_FILE error code, 191
 ER_FAILED_TO_REMOVE_TEMP_TABLE error code, 178
 ER_FAILED_TO_REPAIR_TABLE error code, 178
 ER_FAILED_TO_SET_PERSISTED_OPTIONS error code, 203
 ER_FAILED_TO_START_REPLICA_THREAD error code, 199
 ER_FAILED_TO_STORE_SDI_FOR_TABLESPACE error code, 197
 ER_FAILED_TO_UPDATE_RESOURCE_GROUP error code, 195
 ER_FAILED_TO_VALIDATE_CERTIFICATES_SERVER_EXIT error code, 416
 ER_FAILED_TO_WRITE_TO_FILE error code, 191
 ER_FAIL_CHROOT error code, 146
 ER_FAIL_SETGID error code, 145
 ER_FAIL_SETREGID error code, 145
 ER_FAIL_SETREUID error code, 146
 ER_FAIL_SETUID error code, 145
 ER_FEATURE_DISABLED error code, 22
 ER_FEATURE_DISABLED_SEE_DOC error code, 73
 ER_FEATURE_NOT_AVAILABLE error code, 68
 ER_FEATURE_UNSUPPORTED error code, 87
 ER_FIELD_IN_GROUPING_NOT_GROUP_BY error code, 83
 ER_FIELD_IN_ORDER_NOT_SELECT error code, 65
 ER_FIELD_NOT_FOUND_PART_ERROR error code, 34
 ER_FIELD_SPECIFIED_TWICE error code, 10
 ER_FIELD_TYPE_NOT_ALLOWED_AS_PARTITION_FIELD error code, 44
 ER_FILEGROUP_OPTION_ONLY_ONCE error code, 37
 ER_FILE_CORRUPT error code, 60
 ER_FILE_EXISTS_DURING_UPGRADE error code, 183
 ER_FILE_EXISTS_ERROR error code, 9
 ER_FILE_HAS_OLD_FORMAT error code, 192
 ER_FILE_NOT_FOUND error code, 4
 ER_FILE_TYPE_UNKNOWN error code, 161
 ER_FILE_USED error code, 5
 ER_FIREWALL_ACCESS_DENIED error code, 212
 ER_FIREWALL_DEPRECATED_USER_PROFILE error code, 387
 ER_FIREWALL_FAILED_TO_READ_FIREWALL_TABLES error code, 212
 ER_FIREWALL_FAILED_TO_REG_DYNAMIC_PRIVILEGES error code, 212
 ER_FIREWALL_INVALID_RELOAD_INTERVAL_VALUE error code, 418
 ER_FIREWALL_PFS_TABLE_REGISTER_FAILED error code, 383
 ER_FIREWALL_RECORDING_STMT_WAS_TRUNCATED error code, 212
 ER_FIREWALL_RECORDING_STMT_WITHOUT_TEXT error code, 212
 ER_FIREWALL_RELOADING_CACHE error code, 212
 ER_FIREWALL_RESET_FOR_USER error code, 212

ER_FIREWALL_SCHEDULER_REGISTER_FAILED error code, 418
 ER_FIREWALL_SERVICES_NOT_ACQUIRED error code, 383
 ER_FIREWALL_SKIPPED_UNKNOWN_USER_MODE error code, 212
 ER_FIREWALL_STATUS_FLUSHED error code, 213
 ER_FIREWALL_SUSPICIOUS_STMT error code, 212
 ER_FIREWALL_UDF_REGISTER_FAILED error code, 383
 ER_FIXING_CLIENT_CHARSET error code, 146
 ER_FK_CANNOT_CHANGE_ENGINE error code, 95
 ER_FK_CANNOT_DROP_PARENT error code, 92
 ER_FK_CANNOT_OPEN_PARENT error code, 55
 ER_FK_CANNOT_USE_VIRTUAL_COLUMN error code, 92
 ER_FK_COLUMN_CANNOT_CHANGE error code, 56
 ER_FK_COLUMN_CANNOT_CHANGE_CHILD error code, 56
 ER_FK_COLUMN_CANNOT_DROP error code, 56
 ER_FK_COLUMN_CANNOT_DROP_CHILD error code, 56
 ER_FK_COLUMN_NOT_NULL error code, 56
 ER_FK_DEPTH_EXCEEDED error code, 61
 ER_FK_DUP_NAME error code, 56
 ER_FK_FAIL_ADD_SYSTEM error code, 55
 ER_FK_INCOMPATIBLE_COLUMNS error code, 96
 ER_FK_INCORRECT_OPTION error code, 56
 ER_FK_NO_COLUMN_PARENT error code, 92
 ER_FK_NO_INDEX_CHILD error code, 55
 ER_FK_NO_INDEX_PARENT error code, 55
 ER_FK_NO_UNIQUE_INDEX_PARENT error code, 135
 ER_FORBID_SCHEMA_CHANGE error code, 32
 ER_FORCE_CLOSE_THREAD error code, 191
 ER_FORCING_CLOSE error code, 8
 ER_FOREIGN_DATA_SOURCE_DOESNT_EXIST error code, 31
 ER_FOREIGN_DATA_STRING_INVALID error code, 31
 ER_FOREIGN_DATA_STRING_INVALID_CANT_CREATE error code, 31
 ER_FOREIGN_DUPLICATE_KEY_OLD_UNUSED error code, 38
 ER_FOREIGN_DUPLICATE_KEY_WITHOUT_CHILD_INFO error code, 51
 ER_FOREIGN_DUPLICATE_KEY_WITH_CHILD_INFO error code, 51
 ER_FOREIGN_KEY_ON_PARTITIONED error code, 35
 ER_FOREIGN_KEY_WITH_ATOMIC_CREATE_SELECT error code, 111
 ER_FOREIGN_SERVER_DOESNT_EXIST error code, 34
 ER_FOREIGN_SERVER_EXISTS error code, 34
 ER_FOUND_MISSING_GTIDS error code, 257
 ER_FOUND_ROWS_WHILE_REPAIRING error code, 180
 ER_FPARSER_BAD_HEADER error code, 25
 ER_FPARSER_EOF_IN_COMMENT error code, 25
 ER_FPARSER_EOF_IN_UNKNOWN_PARAMETER error code, 26
 ER_FPARSER_ERROR_IN_PARAMETER error code, 25
 ER_FPARSER_TOO_BIG_FILE error code, 25
 ER_FSEEK_FAIL error code, 27
 ER_FT_BOOL_SYNTAX_INVALID error code, 143
 ER_FT_MATCHING_KEY_NOT_FOUND error code, 16
 ER_FULLTEXT_FUNCTIONAL_INDEX error code, 94
 ER_FULLTEXT_NOT_SUPPORTED_WITH_PARTITIONING error code, 51
 ER_FULLTEXT_WITH_ROLLUP error code, 120
 ER_FUNCTIONAL_INDEX_DATA_IS_TOO_LONG error code, 106
 ER_FUNCTIONAL_INDEX_FUNCTION_IS_NOT_ALLOWED error code, 94
 ER_FUNCTIONAL_INDEX_ON_FIELD error code, 94
 ER_FUNCTIONAL_INDEX_ON_JSON_OR_GEOMETRY_FUNC error code, 94
 ER_FUNCTIONAL_INDEX_ON_LOB error code, 94
 ER_FUNCTIONAL_INDEX_PRIMARY_KEY error code, 94
 ER_FUNCTIONAL_INDEX_REF_AUTO_INCREMENT error code, 94
 ER_FUNCTIONAL_INDEX_ROW_VALUE_IS_NOT_ALLOWED error code, 97
 ER_FUNCTION_DOES_NOT_SUPPORT_CHARACTER_SET error code, 112
 ER_FUNCTION_NOT_DEFINED error code, 12
 ER_FUNC_INEXISTENT_NAME_COLLISION error code, 42
 ER_FUTURE_DATE error code, 145
 ER_GENERATED_COLUMN_FUNCTION_IS_NOT_ALLOWED error code, 68
 ER_GENERATED_COLUMN_NAMED_FUNCTION_IS_NOT_ALLOWED error code, 94
 ER_GENERATED_COLUMN_NON_PRIOR error code, 68
 ER_GENERATED_COLUMN_REF_AUTO_INC error code, 68
 ER_GENERATED_COLUMN_ROW_VALUE error code, 95
 ER_GENERATED_COLUMN_VARIABLES error code, 95
 ER_GEOMETRY_IN_UNKNOWN_LENGTH_UNIT error code, 104
 ER_GEOMETRY_PARAM_LATITUDE_OUT_OF_RANGE error code, 92
 ER_GEOMETRY_PARAM_LONGITUDE_OUT_OF_RANGE error code, 92

ER_GET_ERRMSG error code, 22
 ER_GET_ERRNO error code, 5
 ER_GET_ERRNO_FROM_STORAGE_ENGINE error code, 192
 ER_GET_STACKED_DA_WITHOUT_ACTIVE_HANDLER error code, 60
 ER_GET_TEMPORARY_ERRMSG error code, 22
 ER_GIPK_COLUMN_ALTER_NOT_ALLOWED error code, 122
 ER_GIPK_COLUMN_EXISTS error code, 122
 ER_GIPK_FAILED_AUTOINC_COLUMN_EXISTS error code, 122
 ER_GIS_DATA_WRONG_ENDIANNESS error code, 64
 ER_GIS_DIFFERENT_SRIDS error code, 63
 ER_GIS_DIFFERENT_SRIDS_AGGREGATION error code, 116
 ER_GIS_INVALID_DATA error code, 63
 ER_GIS_MAX_POINTS_IN_GEOMETRY_OVERFLOWED error code, 70
 ER_GIS_UNKNOWN_ERROR error code, 63
 ER_GIS_UNKNOWN_EXCEPTION error code, 63
 ER_GIS_UNSUPPORTED_ARGUMENT error code, 63
 ER_GLOBAL_CONN_LIMIT error code, 395
 ER_GLOBAL_VARIABLE error code, 18
 ER_GLOBSTAT_CHANGE_DURING_QUERY error code, 106
 ER_GNO_EXHAUSTED error code, 52
 ER_GRANT_WRONG_HOST_OR_USER error code, 13
 ER_GROUPING_ON_TIMESTAMP_IN_DST error code, 106
 ER_GROUP_REPLICATION_APPLIER_INIT_ERROR error code, 67
 ER_GROUP_REPLICATION_CERTIFICATION_MODULE_FAILURE error code, 422
 ER_GROUP_REPLICATION_CERTIFIER_MESSAGE_TOO_LARGE error code, 419
 ER_GROUP_REPLICATION_COMMAND_FAILURE error code, 87
 ER_GROUP_REPLICATION_COMMUNICATION_LAYER_FAILURE error code, 67
 ER_GROUP_REPLICATION_COMMUNICATION_LAYER_SESSION_ERROR error code, 67
 ER_GROUP_REPLICATION_COMPRESS_EXCEEDS_MAX_SIZE error code, 419
 ER_GROUP_REPLICATION_COMPRESS_OUT_OF_MEMORY error code, 420
 ER_GROUP_REPLICATION_COMPRESS_PROCESS error code, 419
 ER_GROUP_REPLICATION_CONFIGURATION error code, 67
 ER_GROUP_REPLICATION_DECOMPRESS_CORRUPTED error code, 420
 ER_GROUP_REPLICATION_DECOMPRESS_END error code, 420
 ER_GROUP_REPLICATION_DECOMPRESS_EXCEEDS_MAX_SIZE error code, 420
 ER_GROUP_REPLICATION_DECOMPRESS_OUT_OF_MEMORY error code, 420
 ER_GROUP_REPLICATION_DECOMPRESS_PROCESS error code, 420
 ER_GROUP_REPLICATION_DECOMPRESS_TRUNCATED error code, 420
 ER_GROUP_REPLICATION_ERROR_COMPRESS_INITIALIZE error code, 419
 ER_GROUP_REPLICATION_ERROR_DECOMPRESS_INITIALIZE error code, 420
 ER_GROUP_REPLICATION_ERROR_RECEIVED_WAITING_METADATA error code, 421
 ER_GROUP_REPLICATION_FORCE_MEMBERS_COMMAND_FAILURE error code, 123
 ER_GROUP_REPLICATION_MAX_GROUP_SIZE error code, 75
 ER_GROUP_REPLICATION_METADATA_CERT_INFO_ENCODING error code, 423
 ER_GROUP_REPLICATION_METADATA_CERT_INFO_ERROR_PACKET error code, 421
 ER_GROUP_REPLICATION_METADATA_CERT_INFO_PACKET_CHECKSUM error code, 423
 ER_GROUP_REPLICATION_METADATA_CERT_INFO_PACKET_ERROR error code, 422
 ER_GROUP_REPLICATION_METADATA_ERROR_ON_SEND_ERROR error code, 422
 ER_GROUP_REPLICATION_METADATA_INITIALIZATION_FAILURE error code, 422
 ER_GROUP_REPLICATION_METADATA_MEMORY_ALLOC error code, 422
 ER_GROUP_REPLICATION_METADATA_MESSAGE_PAYLOAD_ERROR error code, 421
 ER_GROUP_REPLICATION_METADATA_NO_VALID_DONOR error code, 423
 ER_GROUP_REPLICATION_METADATA_PAYLOAD_DECODING error code, 421
 ER_GROUP_REPLICATION_METADATA_PAYLOAD_EMPTY error code, 421
 ER_GROUP_REPLICATION_METADATA_PAYLOAD_TOO_LARGE error code, 421
 ER_GROUP_REPLICATION_METADATA_PROTOBUF_PARSING error code, 420
 ER_GROUP_REPLICATION_METADATA_READ_GTID_EXECUTED_ERROR error code, 421
 ER_GROUP_REPLICATION_METADATA_SAVE_RECOVERY_COPY error code, 421
 ER_GROUP_REPLICATION_METADATA_SENDER error code, 419
 ER_GROUP_REPLICATION_METADATA_SENDER_IS_REMOTE error code, 419
 ER_GROUP_REPLICATION_METADATA_SEND_ERROR error code, 421
 ER_GROUP_REPLICATION_METADATA_SET_IN_RECOVERY_FAILURE error code, 422

ER_GROUP_REPLICATION_NO_CERTIFICATION_DONOR_AVAILABLE error code, 423	ER_GRP_RPL_APPLIER_CHANNEL_STILL_RUNNING error code, 383
ER_GROUP_REPLICATION_PASSWORD_LENGTH error code, 111	ER_GRP_RPL_APPLIER_ERROR_PACKET_RECEIVED error code, 424
ER_GROUP_REPLICATION_PLUGIN_NOT_INSTALLED error code, 164	ER_GRP_RPL_APPLIER_EXECUTION_FATAL_ERROR error code, 229
ER_GROUP_REPLICATION_PROTOBUF_SERIALIZING_ERROR error code, 421	ER_GRP_RPL_APPLIER_HANDLER_IS_IN_USE error code, 248
ER_GROUP_REPLICATION_RECOVERY_ERROR_ADD_INDEX_EXECUTED error code, 422	ER_GRP_RPL_APPLIER_HANDLER_NOT_INITIALIZED error code, 248
ER_GROUP_REPLICATION_RECOVERY_FETCHING_GTID_EXECUTED error code, 422	ER_GRP_RPL_APPLIER_HANDLER_ROLE_IS_IN_USE error code, 249
ER_GROUP_REPLICATION_RECOVERY_METADATA_SENDER_NOTIFICATION error code, 422	ER_GRP_RPL_APPLIER_INITIALIZED error code, 246
ER_GROUP_REPLICATION_RECOVERY_SKIPPED_GTID_PRESENT error code, 422	ER_GRP_RPL_APPLIER_METADATA_REPO_MUST_BE_TABLE error code, 247
ER_GROUP_REPLICATION_RECOVERY_STOPPED_GTID_PRESENT error code, 423	ER_GRP_RPL_APPLIER_NOT_STARTED_DUE_TO_RUNNING error code, 246
ER_GROUP_REPLICATION_RUNNING error code, 67	ER_GRP_RPL_APPLIER_PIPELINE_NOT_DISPOSED error code, 229
ER_GROUP_REPLICATION_STOP_APPLIER_THREAD_TIMEOUT error code, 67	ER_GRP_RPL_APPLIER_TERMINATION_TIMED_OUT_ON_SHUTDOWN error code, 245
ER_GROUP_REPLICATION_TIMEOUT_ERROR_FETCHING_METADATA error code, 421	ER_GRP_RPL_APPLIER_THD_EXECUTION_ABORTED error code, 229
ER_GROUP_REPLICATION_UNKOWN_COMPRESSION_TYPE error code, 419	ER_GRP_RPL_APPLIER_THD_KILLED error code, 229
ER_GROUP_REPLICATION_USER_EMPTY_MSG error code, 110	ER_GRP_RPL_APPLIER_THD_SETUP_ERROR error code, 235
ER_GROUP_REPLICATION_USER_MANDATORY_MSG error code, 111	ER_GRP_RPL_APPLIER_THD_START_ERROR error code, 236
ER_GRP_OPERATION_NOT_ALLOWED_GRP_MUST_STOP error code, 110	ER_GRP_RPL_APPLIER_THD_STOP_ERROR error code, 236
ER_GRP_RPL_ABORTS_AS_SSL_NOT_SUPPORTED_BY_SERVER error code, 246	ER_GRP_RPL_APPOINTED_PRIMARY_NOT_PRESENT error code, 347
ER_GRP_RPL_ADD_GRP_SID_TO_GRP_GTIDSID_MAP_ERROR error code, 230	ER_GRP_RPL_AUTO_INC_OFFSET_RESET error code, 236
ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_LOCAL_GTID_FAILED error code, 237	ER_GRP_RPL_AUTO_INC_OFFSET_SET error code, 237
ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_REMOTE_GTID_FAILED error code, 238	ER_GRP_RPL_AUTO_INC_RESET error code, 236
ER_GRP_RPL_ADD_GTID_INFO_WITH_LOCAL_GTID_FAILED error code, 237	ER_GRP_RPL_AUTO_INC_SET error code, 237
ER_GRP_RPL_ADD_GTID_INFO_WITH_REMOTE_GTID_FAILED error code, 238	ER_GRP_RPL_BINLOG_DISABLED error code, 246
ER_GRP_RPL_ADD_GTID_TO_GRP_GTID_EXECUTED_ERROR error code, 230	ER_GRP_RPL_BLOCK_SIZE_DIFF_FROM_GRP error code, 235
ER_GRP_RPL_ADD_RETRIEVED_SET_TO_GRP_GTID_EXECUTED_ERROR error code, 230	ER_GRP_RPL_BROADCASTING_TRANS_TO_GRP_FAILED error code, 242
ER_GRP_RPL_ADD_VIEW_CHANGE_UUID_TO_GRP_SID_ERROR error code, 388	ER_GRP_RPL_BROADCAST_COMMIT_MSSG_TOO_BIG error code, 251
ER_GRP_RPL_ALL_DONORS_LEFT_ABORT_RECOVERY error code, 239	ER_GRP_RPL_BROADCAST_COMMIT_TRANS_MSSG_FAILED error code, 229
ER_GRP_RPL_ALL_OBSERVERS_UNREGISTERED error code, 246	ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_ERROR_STATE error code, 241
	ER_GRP_RPL_CANNOT_EXECUTE_TRANS_IN_OFFLINE_MODE error code, 241
	ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_RECOVERING error code, 241

ER_GRP_RPL_CANNOT_EXECUTE_TRANS_WHILE_STOPPING error code, 241
 ER_GRP_RPL_CANT_GENERATE_GTID error code, 231
 ER_GRP_RPL_CANT_KILL_THREAD error code, 365
 ER_GRP_RPL_CANT_READ_GRP_GTID_EXTRACTED error code, 231
 ER_GRP_RPL_CANT_READ_GTID error code, 231
 ER_GRP_RPL_CANT_READ_WRITE_SET_ITEM error code, 231
 ER_GRP_RPL_CERTIFICATION_INITIALIZATION_FAILURE error code, 230
 ER_GRP_RPL_CERTIFICATION_REC_PROCESS error code, 242
 ER_GRP_RPL_CERTIFIER_MSSG_PROCESS_ERROR error code, 232
 ER_GRP_RPL_CERT_BROADCAST_THREAD_CREATE_FAILED error code, 415
 ER_GRP_RPL_CERT_BROADCAST_THREAD_STARTED error code, 415
 ER_GRP_RPL_CERT_BROADCAST_THREAD_STOPPED error code, 416
 ER_GRP_RPL_CHANGE_GRP_MEM_NOT_PROCESSED error code, 233
 ER_GRP_RPL_CHANNEL_THREAD_WHEN_GROUP_ACTION error code, 347
 ER_GRP_RPL_CHECK_STATUS_TABLE error code, 239
 ER_GRP_RPL_CLONE_PROCESS_EXEC_ERROR error code, 365
 ER_GRP_RPL_CLONE_PROCESS_PREPARE_ERROR error code, 365
 ER_GRP_RPL_COMMUNICATION_SSL_CONF_INFO error code, 246
 ER_GRP_RPL_CONFIGURATION_ACTION_END error code, 347
 ER_GRP_RPL_CONFIGURATION_ACTION_ERROR error code, 347
 ER_GRP_RPL_CONFIGURATION_ACTION_KILLED_ERROR error code, 347
 ER_GRP_RPL_CONFIGURATION_ACTION_LOCAL_TERMINATION error code, 347
 ER_GRP_RPL_CONFIGURATION_ACTION_START error code, 347
 ER_GRP_RPL_CONFIG_RECOVERY error code, 239
 ER_GRP_RPL_CONFLICT_DETECTION_DISABLED error code, 232
 ER_GRP_RPL_CONNECTION_METADATA_REPO_MUST_BE_TABLE error code, 247
 ER_GRP_RPL_CONN_INTERNAL_PLUGIN_FAIL error code, 238
 ER_GRP_RPL_CONN_KILLED error code, 416
 ER_GRP_RPL_COPY_FROM_EMPTY_STRING error code, 238
 ER_GRP_RPL_CREATE_APPLIER_CACHE_ERROR error code, 229
 ER_GRP_RPL_CREATE_GRP_RPL_REC_CHANNEL error code, 239
 ER_GRP_RPL_CREATE_SESSION_UNABLE error code, 239
 ER_GRP_RPL_DATA_NOT_PROVIDED_BY_MEM error code, 234
 ER_GRP_RPL_DEBUG_OPTIONS error code, 250
 ER_GRP_RPL_DEFAULT_TABLE_ENCRYPTION_DIFF_FROM_GRP error code, 359
 ER_GRP_RPL_DISABLE_READ_ONLY_FAILED error code, 233
 ER_GRP_RPL_DISABLE_SRV_READ_MODE_RESTRICTED error code, 232
 ER_GRP_RPL_DONOR_CONN_TERMINATION error code, 240
 ER_GRP_RPL_DONOR_SERVER_CONN error code, 239
 ER_GRP_RPL_DONOR_TRANS_INFO_ERROR error code, 230
 ER_GRP_RPL_DONOR_VIEW_CHANGE_UUID_TRANS_INFO_ERROR error code, 388
 ER_GRP_RPL_ENABLE_READ_ONLY_FAILED error code, 233
 ER_GRP_RPL_ERROR_FETCHING_GTID_EXECUTED_SET error code, 230
 ER_GRP_RPL_ERROR_FETCHING_GTID_SET error code, 230
 ER_GRP_RPL_ERROR_GTID_EXECUTION_INFO error code, 229
 ER_GRP_RPL_ERROR_GTID_SET_EXTRACTION error code, 346
 ER_GRP_RPL_ERROR_MSG error code, 217
 ER_GRP_RPL_ERROR_ON_CERT_DB_INSTALL error code, 356
 ER_GRP_RPL_ERROR_ON_MESSAGE_SENDING error code, 347
 ER_GRP_RPL_ERROR_SENDING_SINGLE_PRIMARY_MSSG error code, 229
 ER_GRP_RPL_ERROR_SET_MULTI_CONSENSUS_LEADER error code, 394
 ER_GRP_RPL_ERROR_SET_SINGLE_CONSENSUS_LEADER error code, 394
 ER_GRP_RPL_ERROR_STOPPING_CHANNELS error code, 229
 ER_GRP_RPL_ERROR_WHILE_WAITING_FOR_CONFLICT_DETECTION error code, 242
 ER_GRP_RPL_ESTABLISHING_CONN_GRP_REC_DONOR error code, 239
 ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_ANOTHER_DONOR error code, 239
 ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_DONOR error code, 239

ER_GRP_RPL_EVENT_HANDLING_ERROR error code, 229	ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_STATE_OBSERVED error code, 245
ER_GRP_RPL_EXCEEDS_AUTO_INC_VALUE error code, 234	ER_GRP_RPL_FAILED_TO_REINIT_BINLOG_CACHE_FOR_REPLICATION error code, 241
ER_GRP_RPL_EXIT_GRP_GCS_ERROR error code, 250	ER_GRP_RPL_FAILED_TO_SHUTDOWN_REGISTRY_MODULE error code, 245
ER_GRP_RPL_FAILED_TO_BOOTSTRAP_EVENT_HANDLER error code, 248	ER_GRP_RPL_FAILED_TO_START_COMMUNICATION_ENGINE error code, 243
ER_GRP_RPL_FAILED_TO_BROADCAST_GRP_MEMBERSHIP_NOTIFICATION error code, 240	ER_GRP_RPL_FAILED_TO_START_ON_BOOT error code, 245
ER_GRP_RPL_FAILED_TO_BROADCAST_MEMBER_STATUS_NOTIFICATION error code, 240	ER_GRP_RPL_FAILED_TO_START_ON_SECONDARY_WITHOUT_NOTIFICATION error code, 243
ER_GRP_RPL_FAILED_TO_CALL_GRP_COMMUNICATION_INTERFACE error code, 244	ER_GRP_RPL_FAILED_TO_START_WITH_INVALID_SERVER_ID error code, 243
ER_GRP_RPL_FAILED_TO_CONFIRM_IF_SERVER_LEFT_GRP error code, 244	ER_GRP_RPL_FAILED_TO_STOP_ON_PLUGIN_UNINSTALL error code, 245
ER_GRP_RPL_FAILED_TO_CREATE_TRANS_CONTEXT error code, 241	ER_GRP_RPL_FAILED_TO_UNREGISTER_BINLOG_STATE_OBSERVER error code, 246
ER_GRP_RPL_FAILED_TO_ENABLE_READ_ONLY_MODE error code, 245	ER_GRP_RPL_FAILED_TO_UNREGISTER_SERVER_STATE_OBSERVER error code, 245
ER_GRP_RPL_FAILED_TO_ENABLE_SUPER_READ_ONLY_MODE error code, 243	ER_GRP_RPL_FAILED_TO_UNREGISTER_TRANS_STATE_OBSERVER error code, 245
ER_GRP_RPL_FAILED_TO_EXTRACT_TRANS_WRITE_SET error code, 241	ER_GRP_RPL_FAILOVER_CHANNEL_STATUS_PROPAGATION error code, 117
ER_GRP_RPL_FAILED_TO_GATHER_TRANS_WRITE_SET error code, 241	ER_GRP_RPL_FAILOVER_CONF_CHANNEL_DOES_NOT_EXIST error code, 391
ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_GRP error code, 246	ER_GRP_RPL_FAILOVER_CONF_DEFAULT_CONFIGURATION error code, 391
ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_VIEW error code, 388	ER_GRP_RPL_FAILOVER_CONF_GET_EXCHANGEABLE_DATA error code, 391
ER_GRP_RPL_FAILED_TO_INIT_APPLIER_HANDLER error code, 249	ER_GRP_RPL_FAILOVER_CONF_PARSE_ON_MEMBER_JOIN error code, 391
ER_GRP_RPL_FAILED_TO_INIT_APPLIER_MODULE error code, 246	ER_GRP_RPL_FAILOVER_CONF_UNABLE_TO_SET_DEFAULT error code, 391
ER_GRP_RPL_FAILED_TO_INIT_COMMUNICATION_ENGINE error code, 243	ER_GRP_RPL_FAILOVER_PRIMARY_BACK_TO_MAJORITY error code, 391
ER_GRP_RPL_FAILED_TO_INIT_HANDLER error code, 245	ER_GRP_RPL_FAILOVER_PRIMARY_WITHOUT_MAJORITY error code, 391
ER_GRP_RPL_FAILED_TO_INSERT_TRX_ON_TCM_ON_ART error code, 354	ER_GRP_RPL_FAILOVER_REGISTER_MESSAGE_LISTENER error code, 391
ER_GRP_RPL_FAILED_TO_LOG_VIEW_CHANGE error code, 401	ER_GRP_RPL_FATAL_REC_PROCESS error code, 242
ER_GRP_RPL_FAILED_TO_NOTIFY_GRP_MEMBERSHIP_EVENT error code, 240	ER_GRP_RPL_FETCH_FORMAT_DESC_LOG_EVENT_FAILED error code, 237
ER_GRP_RPL_FAILED_TO_PARSE_THE_GRP_NAME error code, 246	ER_GRP_RPL_FETCH_GTID_LOG_EVENT_FAILED error code, 237
ER_GRP_RPL_FAILED_TO_PARSE_THE_VIEW_CHANGE error code, 388	ER_GRP_RPL_FETCH_LOG_EVENT_FAILED error code, 238
ER_GRP_RPL_FAILED_TO_REGISTER_BINLOG_STATE_OBSERVER error code, 245	ER_GRP_RPL_FETCH_SNAPSHOT_VERSION_FAILED error code, 237
ER_GRP_RPL_FAILED_TO_REGISTER_SERVER_STATE_OBSERVER error code, 245	ER_GRP_RPL_FETCH_TRANS_CONTEXT_FAILED error code, 237
ER_GRP_RPL_FAILED_TO_REGISTER_TRANS_OUTCOME_NOTIFICATION error code, 242	ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FAILED error code, 237

ER_GRP_RPL_FETCH_TRANS_DATA_FAILED error code, 236
 ER_GRP_RPL_FETCH_VIEW_CHANGE_LOG_EVENT_FAILED error code, 238
 ER_GRP_RPL_FINISHED_AUTO_REJOIN error code, 359
 ER_GRP_RPL_FK_WITH_CASCADE_UNSUPPORTED error code, 236
 ER_GRP_RPL_FLOW_CONTROL_STATS error code, 251
 ER_GRP_RPL_FLOW_CTRL_MAX_QUOTA_SMALLER_THAN_MAX_QUOTA error code, 248
 ER_GRP_RPL_FLOW_CTRL_MIN_QUOTA_GREATER_THAN_MAX_QUOTA error code, 248
 ER_GRP_RPL_FLOW_CTRL_MIN_RECOVERY_QUOTA_GREATER_THAN_MAX_QUOTA error code, 248
 ER_GRP_RPL_FORCE_MEMBERS_MUST_BE_EMPTY error code, 243
 ER_GRP_RPL_FORCE_MEMBERS_WHEN_LEAVING error code, 356
 ER_GRP_RPL_FORCE_MEMBER_VALUE_SET error code, 251
 ER_GRP_RPL_FORCE_MEMBER_VALUE_SET_ERROR error code, 250
 ER_GRP_RPL_FORCE_MEMBER_VALUE_TIME_OUT error code, 251
 ER_GRP_RPL_GCS_GR_ERROR_MSG error code, 251
 ER_GRP_RPL_GCS_INTERFACE_ERROR error code, 250
 ER_GRP_RPL_GMS_LISTENER_FAILED_TO_LOG_NOTIFICATION error code, 250
 ER_GRP_RPL_GROUP_NAME_PARSE_ERROR error code, 230
 ER_GRP_RPL_GROUP_NAME_SAME_AS_VIEW_CHANGE_LOGGER error code, 387
 ER_GRP_RPL_GRP_COMMUNICATION_ENG_INIT_FAILED error code, 250
 ER_GRP_RPL_GRP_COMMUNICATION_INIT_WITH_CONFLICT error code, 248
 ER_GRP_RPL_GRP_MEMBER_OFFLINE error code, 250
 ER_GRP_RPL_GRP_NAME_IS_NOT_VALID_UUID error code, 247
 ER_GRP_RPL_GRP_NAME_IS_SAME_AS_ANONYMOUS error code, 382
 ER_GRP_RPL_GRP_NAME_IS_TOO_LONG error code, 247
 ER_GRP_RPL_GRP_NAME_OPTION_MANDATORY error code, 247
 ER_GRP_RPL_GRP_VIEW_CHANGE_UUID_IS_INCOMPLETE error code, 388
 ER_GRP_RPL_GTID_ALREADY_USED error code, 229
 ER_GRP_RPL_GTID_EXECUTED_EXTRACT_ERROR error code, 234
 ER_GRP_RPL_GTID_MODE_OFF error code, 247
 ER_GRP_RPL_GTID_PURGED_EXTRACT_ERROR error code, 365
 ER_GRP_RPL_GTID_SET_EXTRACT_ERROR error code, 234
 ER_GRP_RPL_GTID_SET_EXTRACT_ERROR_DURING_RECOVERY error code, 355
 ER_GRP_RPL_HAS_STARTED error code, 410
 ER_GRP_RPL_INCORRECT_TYPE_SET_FOR_PARALLEL_APPLICATION error code, 247
 ER_GRP_RPL_INVALID_OPTIONS_CERTIFICATION_INFO_FAILURE error code, 231
 ER_GRP_RPL_INVALID_OPTIONS_INTERNAL_QUERY error code, 238
 ER_GRP_RPL_INVALID_BINLOG_FORMAT error code, 362
 ER_GRP_RPL_INVALID_COMMUNICATION_PROTOCOL error code, 359
 ER_GRP_RPL_INVALID_DEBUG_OPTIONS error code, 250
 ER_GRP_RPL_INVALID_GTID_SET error code, 231
 ER_GRP_RPL_INVALID_SSL_RECOVERY_STRING error code, 248
 ER_GRP_RPL_IS_STARTING error code, 374
 ER_GRP_RPL_IS_STOPPED error code, 244
 ER_GRP_RPL_IS_STOPPING error code, 244
 ER_GRP_RPL_JOINER_EXIT_WHEN_GROUP_ACTION_RUNNING error code, 347
 ER_GRP_RPL_JOIN_WHEN_GROUP_ACTION_RUNNING error code, 347
 ER_GRP_RPL_KILLED_FAILED_ID error code, 238
 ER_GRP_RPL_KILLED_SESSION_ID error code, 238
 ER_GRP_RPL_LOCAL_GTID_SETS_PROCESS_ERROR error code, 235
 ER_GRP_RPL_LOG_REPLICA_UPDATES_NOT_SET error code, 247
 ER_GRP_RPL_LOWER_CASE_TABLE_NAMES_DIFF_FROM_GRP error code, 340
 ER_GRP_RPL_MAXIMUM_CONNECTION_RETRIES_REACHED error code, 239
 ER_GRP_RPL_MEMBER_ACTIONS_RESET error code, 387
 ER_GRP_RPL_MEMBER_ACTION_DEFAULT_CONFIGURATION error code, 386
 ER_GRP_RPL_MEMBER_ACTION_DISABLED error code, 387
 ER_GRP_RPL_MEMBER_ACTION_ENABLED error code, 387
 ER_GRP_RPL_MEMBER_ACTION_FAILURE error code, 386
 ER_GRP_RPL_MEMBER_ACTION_FAILURE_IGNORE error code, 386
 ER_GRP_RPL_MEMBER_ACTION_GET_EXCHANGEABLE_DATA error code, 386

ER_GRP_RPL_MEMBER_ACTION_INVALID_ACTIONS_ON_MEMBER_JOIN error code, 387
 ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_MEMBER_JOIN error code, 387
 ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_RECEIVER error code, 386
 ER_GRP_RPL_MEMBER_ACTION_TRIGGERED error code, 386
 ER_GRP_RPL_MEMBER_ACTION_UNABLE_TO_SET_DEFAULT_CONFIGURATION error code, 386
 ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS error code, 386
 ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS_ON_MEMBER_JOIN error code, 387
 ER_GRP_RPL_MEMBER_ADDED error code, 233
 ER_GRP_RPL_MEMBER_ALREADY_EXISTS error code, 234
 ER_GRP_RPL_MEMBER_CFG_INCOMPATIBLE_WITH_GRP error code, 235
 ER_GRP_RPL_MEMBER_CHANGE error code, 233
 ER_GRP_RPL_MEMBER_CONF_INFO error code, 244
 ER_GRP_RPL_MEMBER_CONTACT_RESTORED error code, 233
 ER_GRP_RPL_MEMBER_EXIT_PLUGIN_ERROR error code, 233
 ER_GRP_RPL_MEMBER_EXPELLED error code, 233
 ER_GRP_RPL_MEMBER_INFO_DOES_NOT_EXIST error code, 415
 ER_GRP_RPL_MEMBER_LEFT_GRP error code, 233
 ER_GRP_RPL_MEMBER_NOT_FOUND error code, 239
 ER_GRP_RPL_MEMBER_REMOVED error code, 233
 ER_GRP_RPL_MEMBER_SERVER_UUID_IS_INCOMPATIBLE_WITH_GRP error code, 244
 ER_GRP_RPL_MEMBER_STATS_INFO error code, 251
 ER_GRP_RPL_MEMBER_STOP_RPL_CHANNELS_ERROR error code, 235
 ER_GRP_RPL_MEMBER_TRANS_GREATER_THAN_GRP error code, 235
 ER_GRP_RPL_MEMBER_VERSION_LOWER_THAN_GRP error code, 235
 ER_GRP_RPL_MEMBER_VER_INCOMPATIBLE error code, 234
 ER_GRP_RPL_MEMBER_VER_READ_COMPATIBLE error code, 362
 ER_GRP_RPL_MEM_ONLINE error code, 232
 ER_GRP_RPL_MEM_REACHABLE error code, 232
 ER_GRP_RPL_MEM_UNREACHABLE error code, 232
 ER_GRP_RPL_MESSAGE_SERVICE_FATAL_ERROR error code, 367
 ER_GRP_RPL_MESSAGE_SERVICE_INIT_FAILURE error code, 106
 ER_GRP_RPL_MISSING_GRP_RPL_ACTION_COORDINATION error code, 347
 ER_GRP_RPL_MISSING_GRP_RPL_APPLIER error code, 232
 ER_GRP_RPL_MODULE_TERMINATE_ERROR error code, 247
 ER_GRP_RPL_MSG_DECODING_FAILED error code, 424
 ER_GRP_RPL_MSG_DISCARDED error code, 232
 ER_GRP_RPL_MSG_TOO_LONG_BROADCASTING_TRANS_F error code, 242
 ER_GRP_RPL_MULTIPLE_CACHE_TYPE_NOT_SUPPORTED error code, 241
 ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ERROR error code, 390
 ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_SERVER_ERROR error code, 417
 ER_GRP_RPL_NEEDS_INNODB_TABLE error code, 236
 ER_GRP_RPL_NEW_PRIMARY_ELECTED error code, 233
 ER_GRP_RPL_NOTIFY_CERTIFICATION_OUTCOME_FAILED error code, 237
 ER_GRP_RPL_NO_POSSIBLE_RECOVERY error code, 365
 ER_GRP_RPL_NO_STAGE_SERVICE error code, 348
 ER_GRP_RPL_NO_SUITABLE_PRIMARY_MEM error code, 234
 ER_GRP_RPL_NO_VALID_DONOR error code, 239
 ER_GRP_RPL_NULL_PACKET error code, 231
 ER_GRP_RPL_ONLY_ONE_SERVER_ALIVE error code, 247
 ER_GRP_RPL_OOM_FAILED_TO_GENERATE_IDENTIFICATION error code, 240
 ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_GRP error code, 394
 ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_OLD error code, 408
 ER_GRP_RPL_PIPELINE_CREATE_FAILED error code, 251
 ER_GRP_RPL_PIPELINE_FLUSH_FAIL error code, 251
 ER_GRP_RPL_PIPELINE_REINIT_FAILED_READ error code, 251
 ER_GRP_RPL_PIPELINE_REINIT_FAILED_WRITE error code, 251
 ER_GRP_RPL_PLUGIN_ABORT error code, 344
 ER_GRP_RPL_PLUGIN_STRUCT_INIT_NOT_POSSIBLE_ON error code, 243
 ER_GRP_RPL_PREEMPTIVE_GARBAGE_COLLECTION_DIFF error code, 426
 ER_GRP_RPL_PRIMARY_ELECTION_PROCESS_ERROR error code, 348
 ER_GRP_RPL_PRIMARY_ELECTION_STOP_ERROR error code, 348

ER_GRP_RPL_PRIMARY_KEY_NOT_DEFINED error code, 236	ER_GRP_RPL_RELEASE_COMMIT_AFTER_GROUP_PREPARE error code, 354
ER_GRP_RPL_PRIMARY_MEMBER_LEFT_GRP error code, 233	ER_GRP_RPL_REPLICA_APPLIER_THREAD_ERROR_OUT error code, 252
ER_GRP_RPL_PROCESS_GTID_SET_ERROR error code, 231	ER_GRP_RPL_REPLICA_APPLIER_THREAD_UNBLOCKED error code, 252
ER_GRP_RPL_PROCESS_INTERSECTION_GTID_SET_ERROR error code, 231	ER_GRP_RPL_REPLICA_IO_THD_PRIMARY_UNKNOWN error code, 236
ER_GRP_RPL_PURGE_APPLIER_LOGS error code, 235	ER_GRP_RPL_REPLICA_IO_THREAD_ERROR_OUT error code, 252
ER_GRP_RPL_PURGE_REC error code, 240	ER_GRP_RPL_REPLICA_IO_THREAD_UNBLOCKED error code, 252
ER_GRP_RPL_QUERY_FAIL error code, 238	ER_GRP_RPL_REPLICA_PRESERVE_COMMIT_ORDER_NOT_SET error code, 247
ER_GRP_RPL_READ_UNABLE_FOR_READ_ONLY_SUPPLIER error code, 243	ER_GRP_RPL_REPLICA_SQL_THD_ON_SECONDARY_MEMBER error code, 236
ER_GRP_RPL_RECEIVED_SET_MISSING_GTIDS error code, 231	ER_GRP_RPL_REPLICA_SQL_THD_PRIMARY_UNKNOWN error code, 236
ER_GRP_RPL_RECOVERY_CHANNEL_STILL_RUNNING error code, 115	ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_CLONE error code, 366
ER_GRP_RPL_RECOVERY_ENDPOINT_FORMAT error code, 374	ER_GRP_RPL_REPLICA_THREAD_ERROR_ON_SECONDARY_MEMBER error code, 392
ER_GRP_RPL_RECOVERY_ENDPOINT_INTERFACES_IPS error code, 375	ER_GRP_RPL_REQUESTING_NON_MEMBER_SERVER_TO_LEAVE error code, 244
ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID error code, 375	ER_GRP_RPL_RESET_APPLIER_MODULE_LOGS_ERROR error code, 235
ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID_DONOR_ENDPOINT error code, 375	ER_GRP_RPL_SALVE_IO_THD_ON_SECONDARY_MEMBER error code, 236
ER_GRP_RPL_RECOVERY_EVAL_ERROR error code, 365	ER_GRP_RPL_SENDDOWN_SENDDOWN_ERROR error code, 251
ER_GRP_RPL_RECOVERY_MODULE_TERMINATION_TIMEOUT error code, 245	ER_GRP_RPL_SEND_TRX_PREPARED_MESSAGE_FAILED error code, 354
ER_GRP_RPL_RECOVERY_STRAT_CHOICE error code, 365	ER_GRP_RPL_SEND_TRX_SYNC_BEFORE_EXECUTION_FAILED error code, 355
ER_GRP_RPL_RECOVERY_STRAT_CLONE_PURGED error code, 365	ER_GRP_RPL_SERVER_ALREADY_LEFT error code, 244
ER_GRP_RPL_RECOVERY_STRAT_CLONE_THRESHOLD error code, 365	ER_GRP_RPL_SERVER_CONN_ERROR error code, 230
ER_GRP_RPL_RECOVERY_STRAT_FALLBACK error code, 365	ER_GRP_RPL_SERVER_IS_ALREADY_LEAVING error code, 244
ER_GRP_RPL_RECOVERY_STRAT_NO_FALLBACK error code, 366	ER_GRP_RPL_SERVER_SET_TO_OFFLINE_MODE_DUE_TO_ERROR error code, 367
ER_GRP_RPL_RECOVERY_WAIT_APPLIER_BACKLOG_START error code, 427	ER_GRP_RPL_SERVER_SET_TO_READ_ONLY_DUE_TO_ERROR error code, 250
ER_GRP_RPL_RECOVERY_WAIT_APPLIER_BACKLOG_STOP error code, 427	ER_GRP_RPL_SERVER_UDF_ERROR error code, 348
ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_DEPENDENCIES error code, 354	ER_GRP_RPL_SESSION_OPEN_FAILED error code, 233
ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_GROUP_ERROR error code, 354	ER_GRP_RPL_SERVER_ALREADY_LEFT_GRP_COMMUNICATION_ENG_LOGGER_FAILED error code, 250
ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_SYNC_BEFORE_EXECUTION_FAILED error code, 355	ER_GRP_RPL_SINGLE_CONSENSUS_LEADER error code, 394
ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_DEPENDENCIES_COMMIT_FAILED error code, 354	ER_GRP_RPL_SINGLE_CONSENSUS_LEADER error code, 394
ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_WAIT_FOR_SYNC_BEFORE_EXECUTION_FAILED error code, 355	ER_GRP_RPL_STABLE_TRANS_ERROR error code, 231

ER_GRP_RPL_SINGLE_PRIM_MODE_NOT_ALLOWED_WITH_GRP_DATA_TRANSFER_SIZE error code, 247	ER_GRP_RPL_TRANS_WRITE_EXCEEDS_LIMIT error code, 242
ER_GRP_RPL_SQL_SERVICE_COMM_SESSION_NOT_INITIALIZED error code, 249	ER_GRP_RPL_TRANS_WRITE_SET_EXTRACT_DIFF_FROM_C error code, 235
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_FETCH_SECONDARY error code, 249	ER_GRP_RPL_TRX_ALREADY_EXISTS_ON_TCM_ON_AFTER error code, 354
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_INIT_SESSION error code, 249	ER_GRP_RPL_TRX_DOES_NOT_EXIST_ON_TCM_ON_HANDLI error code, 354
ER_GRP_RPL_SQL_SERVICE_FAILED_TO_RUN_SQL_QUERY error code, 249	ER_GRP_RPL_TRX_WAIT_FOR_GROUP_GTID_EXECUTED error code, 355
ER_GRP_RPL_SQL_SERVICE_MAX_CONN_ERROR_FROM_SERVER error code, 249	ER_GRP_RPL_TRX_WAIT_FOR_GROUP_PREPARE_FAILED error code, 354
ER_GRP_RPL_SQL_SERVICE_RETRIES_EXCEEDED_ON_SESSION error code, 249	ER_GRP_RPL_WAIT_FOR_SYNC_BEFORE_EXECUTION error code, 355
ER_GRP_RPL_SQL_SERVICE_SERVER_ACCESS_DENIED error code, 249	ER_GRP_UDF error code, 106
ER_GRP_RPL_SQL_SERVICE_SERVER_ERROR_ON_CONN error code, 250	ER_GRP_UDF_REGISTER_ERROR error code,
ER_GRP_RPL_SQL_SERVICE_SERVER_INTERNAL_FAILURE error code, 249	ER_GRP_UDF_REGISTER_SERVICE_ERROR error code, 348
ER_GRP_RPL_SQL_SERVICE_SERVER_SESSION_KILLED error code, 249	ER_GRP_UDF_UNREGISTER_ERROR error code, 348
ER_GRP_RPL_SRV_BLOCKED error code, 232	ER_GRP_UNABLE_TO_CERTIFY_PLUGIN_TRANS error code, 243
ER_GRP_RPL_SRV_BLOCKED_FOR_SECS error code, 232	ER_GRP_UNABLE_TO_CONVERT_EVENT_TO_PACKET error code, 251
ER_GRP_RPL_SRV_NOT_ONLINE error code, 232	ER_GRP_UNABLE_TO_CONVERT_PACKET_TO_EVENT error code, 251
ER_GRP_RPL_SRV_ONLINE error code, 232	ER_GRP_UNABLE_TO_ENSURE_EXECUTION_REC error code, 242
ER_GRP_RPL_SRV_PRIMARY_MEM error code, 233	ER_GRP_UNABLE_TO_EVALUATE_APPLIER_STATUS error code, 242
ER_GRP_RPL_SRV_SECONDARY_MEM error code, 234	ER_GRP_UNABLE_TO_INIT_COMMUNICATION_ENGINE error code, 246
ER_GRP_RPL_SSL_DISABLED error code, 246	ER_GRP_UNABLE_TO_KILL_CONN_REC_DONOR_APPL error code, 240
ER_GRP_RPL_STARTED_AUTO_REJOIN error code, 359	ER_GRP_UNABLE_TO_KILL_CONN_REC_DONOR_FAILO error code, 240
ER_GRP_RPL_STARTING_GRP_REC error code, 240	ER_GRP_UNABLE_TO_RESET_SERVER_READ_MODE error code, 243
ER_GRP_RPL_START_FAILED error code, 234	ER_GRP_UNBLOCK_CERTIFIED_TRANS error code, 243
ER_GRP_RPL_START_GRP_RPL_FAILED error code, 238	ER_GRP_UNBLOCK_WAITING_THD error code,
ER_GRP_RPL_STOPPING_GRP_REC error code, 240	ER_GRP_UNKNOWN_GRP_RPL_APPLIER_PIPELINE_RE error code, 248
ER_GRP_RPL_SUPER_READ_OFF error code, 238	ER_GRP_UNREACHABLE_MAJORITY_TIMEOUT_FOR_M error code, 250
ER_GRP_RPL_SUPER_READ_ON error code, 238	ER_GRP_UNSUPPORTED_TRANS_ISOLATION error code, 244
ER_GRP_RPL_SUPER_READ_ONLY_ACTIVATE_ERROR error code, 234	ER_GRP_UNSHUTDOWN error code, 244
ER_GRP_RPL_TIMEOUT_ON_VIEW_AFTER_JOINING_GRP error code, 244	ER_GRP_UPDATE_GRPGTID_EXECUTED_ERROR error code, 230
ER_GRP_RPL_TIMEOUT_RECEIVED_VC_LEAVE_ON_REJOIN error code, 379	ER_GRP_UPDATE_GRPGTID_VIEW_CHANGE_UUID_EX error code, 388
ER_GRP_RPL_TIMEOUT_RECEIVED_VC_ON_REJOIN error code, 359	
ER_GRP_RPL_TIMEOUT_RECEIVING_VIEW_CHANGE_ON error code, 244	
ER_GRP_RPL_TRANS_GREATER_THAN_GRP error code, 234	
ER_GRP_RPL_TRANS_NOT_PRESENT_IN_GRP error code, 234	

ER_GRP_RPL_UPDATE_GTID_SET_ERROR error code, 231	ER_GTID_MODE_ON_REQUIRES_ENFORCE_GTID_CONSISTENCY error code, 52
ER_GRP_RPL_UPDATE_LAST_CONFLICT_FREE_TRANSACTION_ERROR error code, 230	ER_GTID_NEXT_CANT_BE_AUTOMATIC_IF_GTID_NEXT_LIST_IS_EMPTY error code, 52
ER_GRP_RPL_UPDATE_SERV_CERTIFICATE_FAILED error code, 237	ER_GTID_NEXT_TAG_GTID_MODE_OFF error code, 130
ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_REF_VERSION_ERROR error code, 231	ER_GTID_NEXT_TYPE_UNDEFINED_GTID error code, 56
ER_GRP_RPL_VCLE_NOT_BEING_LOGGED error code, 420	ER_GTID_PURGED_WAS_CHANGED error code, 57
ER_GRP_RPL_VIEW_CHANGE_UUID_DIFF_FROM_GRP error code, 388	ER_GTID_PURGED_WAS_UPDATED error code, 191
ER_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLES error code, 117	ER_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION error code, 95
ER_GRP_RPL_VIEW_CHANGE_UUID_INVALID error code, 387	ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_AS_ERROR error code, 60
ER_GRP_RPL_VIEW_CHANGE_UUID_IS_SAME_AS_ANOTHER error code, 387	ER_GTID_UNSAFE_CREATE_SELECT error code, 53
ER_GRP_RPL_VIEW_CHANGE_UUID_PARSE_ERROR error code, 388	ER_GTID_UNSAFE_NON_TRANSACTIONAL_TABLE_OPERATION error code, 53
ER_GRP_RPL_VIEW_CHANGE_UUID_SAME_AS_GROUP_NAME error code, 387	ER_GTID_UUID error code, 53
ER_GRP_RPL_WAITING_FOR_VIEW_UPDATE error code, 244	ER_HANDLERTON_OOM error code, 153
ER_GRP_RPL_WAIT_FOR_DEPENDENCIES_FAILED error code, 354	ER_HANDSHAKE_ERROR error code, 6
ER_GRP_RPL_WHILE_SENDING_MSG_REC error code, 242	ER_HEALTH_ERROR error code, 383
ER_GRP_RPL_WRITE_IDENT_HASH_BASE64_ENCODING_FAILED error code, 240	ER_HEALTH_INFO error code, 382
ER_GRP_RPL_WRITE_TO_TRANSACTION_MESSAGE_FILE error code, 242	ER_HEALTH_WARNING error code, 383
ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN error code, 97	ER_HEALTH_WARNING_DISK_USAGE_LEVEL_1 error code, 383
ER_GRP_TRX_CONSISTENCY_BEFORE error code, 97	ER_HEALTH_WARNING_DISK_USAGE_LEVEL_2 error code, 383
ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED error code, 97	ER_HEALTH_WARNING_DISK_USAGE_LEVEL_3 error code, 383
ER_GRP_TRX_CONSISTENCY_NOT_ALLOWED error code, 97	ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_1 error code, 394
ER_GR_ELECTED_PRIMARY_GTID_INFORMATION error code, 369	ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_2 error code, 394
ER_GR_HOLD_KILLED error code, 96	ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_3 error code, 394
ER_GR_HOLD_MEMBER_STATUS_ERROR error code, 96	ER_HOSTNAME error code, 33
ER_GR_HOLD_WAIT_TIMEOUT error code, 96	ER_HOSTNAME_DOESNT_RESOLVE_TO error code, 141
ER_GTID_ALREADY_ADDED_BY_USER error code, 164	ER_HOSTNAME_RESEMBLES_IPV4 error code, 141
ER_GTID_EXECUTED_WAS_CHANGED error code, 57	ER_HOSTNAME_TOO_LONG error code, 110
ER_GTID_EXECUTED_WAS_UPDATED error code, 191	ER_HOSTNAME_TRUNCATED error code, 376
ER_GTID_MODE_CAN_ONLY_CHANGE_ONE_STEP_AT_A_TIME error code, 53	ER_HOST_IS_BLOCKED error code, 12
ER_GTID_MODE_OFF error code, 65	ER_HOST_NOT_PRIVILEGED error code, 12
	ER_HYPERGRAPH_NOT_SUPPORTED_YET error code, 113
	ER_IB_BUFFER_POOL_FULL error code, 406
	ER_IB_BUFFER_POOL_OVERUSE error code, 406
	ER_IB_BULK_FLUSHER_INFO error code, 406
	ER_IB_BULK_FLUSHER_PUNCH_HOLE error code, 416
	ER_IB_BULK_LOAD_MERGE_FAIL error code, 408
	ER_IB_BULK_LOAD_STATS_WARN error code, 424
	ER_IB_BULK_LOAD_SUBTREE_INFO error code, 406
	ER_IB_BULK_LOAD_THREAD_FAIL error code, 408

ER_IB_CANNOT_UPGRADE_WITH_DISCARDED_TABLESPACES error code, 376
 ER_IB_CLONE_GTID_PERSIST error code, 268
 ER_IB_CLONE_INTERNAL error code, 268
 ER_IB_CLONE_NON_INNODB_TABLE error code, 364
 ER_IB_CLONE_OPERATION error code, 364
 ER_IB_CLONE_PUNCH_HOLE error code, 268
 ER_IB_CLONE_RESTART error code, 364
 ER_IB_CLONE_SQL error code, 268
 ER_IB_CLONE_START_STOP error code, 364
 ER_IB_CLONE_STATUS_FILE error code, 268
 ER_IB_CLONE_TIMEOUT error code, 268
 ER_IB_CLONE_USER_DATA error code, 364
 ER_IB_CLONE_VALIDATE error code, 268
 ER_IB_DBLWR_BYTES_INFO error code, 397
 ER_IB_DBLWR_DECOMPRESS_FAILED error code, 381
 ER_IB_DBLWR_DECRYPT_FAILED error code, 381
 ER_IB_DBLWR_KEY_MISSING error code, 381
 ER_IB_DDL_CONVERT_HEAP_NOT_FOUND error code, 414
 ER_IB_DICT_INVALID_COLUMN_POSITION error code, 409
 ER_IB_DICT_LOG_TABLE_INFO error code, 409
 ER_IB_DUPLICATE_KEY error code, 406
 ER_IB_ERR_ACCESSING_OUT_OF_BOUND_FIELD_IN_INDEX error code, 333
 ER_IB_ERR_CORRUPT_TABLESPACE_UNRECOVERABLE error code, 423
 ER_IB_ERR_DDL_LOG_INSERT_FAILURE error code, 376
 ER_IB_ERR_FOUND_N_DUPLICATE_KEYS error code, 379
 ER_IB_ERR_FOUND_N_RECORDS_WRONG_ORDER error code, 379
 ER_IB_ERR_INDEX_DUPLICATE_KEY error code, 379
 ER_IB_ERR_INDEX_RECORDS_WRONG_ORDER error code, 378
 ER_IB_ERR_LOG_PARSING_BUFFER_OVERFLOW error code, 378
 ER_IB_ERR_NOT_ENOUGH_MEMORY_FOR_PARSE_BUFFER error code, 378
 ER_IB_ERR_PAGE_ARCH_DBLWR_INIT_FAILED error code, 390
 ER_IB_ERR_PAGE_ARCH_INVALID_DOUBLE_WRITE_BUFFER error code, 374
 ER_IB_ERR_PAGE_ARCH_INVALID_FORMAT error code, 374
 ER_IB_ERR_PAGE_ARCH_RECOVERY_FAILED error code, 374
 ER_IB_ERR_PAGE_DIRTY_AT_SHUTDOWN error code, 264
 ER_IB_ERR_PARALLEL_READ_OOM error code, 379
 ER_IB_ERR_RECOVERY_REDO_DISABLED error code, 375
 ER_IB_ERR_SCHED_SETAFFINITY_FAILED error code, 377
 ER_IB_ERR_TEMP_TABLESPACE_DIR_CONTAINS_SEMICOLON error code, 377
 ER_IB_ERR_TEMP_TABLESPACE_DIR_DOESNT_EXIST error code, 377
 ER_IB_ERR_TEMP_TABLESPACE_DIR_EMPTY error code, 377
 ER_IB_ERR_TEMP_TABLESPACE_DIR_SUBDIR_OF_DATADIR error code, 377
 ER_IB_ERR_UNKNOWN_PAGE_FETCH_MODE error code, 378
 ER_IB_ERR_ZLIB_BUF_ERROR error code, 378
 ER_IB_ERR_ZLIB_DATA_ERROR error code, 378
 ER_IB_ERR_ZLIB_MEM_ERROR error code, 378
 ER_IB_ERR_ZLIB_UNCOMPRESS_FAILED error code, 378
 ER_IB_ERR_ZLIB_UNKNOWN_ERROR error code, 378
 ER_IB_FAILED_TO_DELETE_TABLESPACE_FILE error code, 377
 ER_IB_FIXED_PAGE_ID error code, 418
 ER_IB_HIDDEN_NAME_CONFLICT error code, 409
 ER_IB_IMPORT_INDEX_METADATA_READ_FAILED error code, 317
 ER_IB_IMPORT_START_CFG_NAME error code, 322
 ER_IB_INDEX_BUILDER_DONE error code, 410
 ER_IB_INDEX_BUILDER_INIT error code, 410
 ER_IB_INDEX_LOADER_DONE error code, 410
 ER_IB_INDEX_LOG_VERSION_MISMATCH error code, 410
 ER_IB_INDEX_PART_TOO_LONG error code, 415
 ER_IB_INNODB_TBSP_OUT_OF_SPACE error code, 383
 ER_IB_LOAD_BULK_CONCURRENCY_REDUCED error code, 408
 ER_IB_LOB_ROLLBACK_INDEX_LEN error code, 368
 ER_IB_LOCK_VALIDATE_LATCH_ORDER_VIOLATION error code, 376
 ER_IB_LONG_AHI_DISABLE_WAIT error code, 270
 ER_IB_LONG_ROLLBACK error code, 426
 ER_IB_LONG_ROLLBACK_FULL error code, 426
 ER_IB_MSG_0 error code, 259
 ER_IB_MSG_1 error code, 259
 ER_IB_MSG_10 error code, 259
 ER_IB_MSG_100 error code, 265
 ER_IB_MSG_1000 error code, 321
 ER_IB_MSG_1001 error code, 321
 ER_IB_MSG_1002 error code, 321
 ER_IB_MSG_1003 error code, 321
 ER_IB_MSG_1004 error code, 321
 ER_IB_MSG_1005 error code, 321
 ER_IB_MSG_1006 error code, 321

ER_IB_MSG_1247 error code, 337
ER_IB_MSG_1248 error code, 337
ER_IB_MSG_1249 error code, 337
ER_IB_MSG_125 error code, 266
ER_IB_MSG_1250 error code, 337
ER_IB_MSG_1251 error code, 337
ER_IB_MSG_1253 error code, 338
ER_IB_MSG_1255 error code, 338
ER_IB_MSG_1256 error code, 338
ER_IB_MSG_1257 error code, 338
ER_IB_MSG_1258 error code, 338
ER_IB_MSG_1259 error code, 338
ER_IB_MSG_126 error code, 266
ER_IB_MSG_1260 error code, 338
ER_IB_MSG_1261 error code, 338
ER_IB_MSG_1262 error code, 338
ER_IB_MSG_1263 error code, 338
ER_IB_MSG_1266 error code, 338
ER_IB_MSG_1268 error code, 339
ER_IB_MSG_1269 error code, 339
ER_IB_MSG_127 error code, 266
ER_IB_MSG_1272 error code, 344
ER_IB_MSG_1273 error code, 345
ER_IB_MSG_1274 error code, 345
ER_IB_MSG_1275 error code, 346
ER_IB_MSG_1277 error code, 346
ER_IB_MSG_128 error code, 266
ER_IB_MSG_1280 error code, 346
ER_IB_MSG_1281 error code, 346
ER_IB_MSG_1282 error code, 346
ER_IB_MSG_1283 error code, 346
ER_IB_MSG_1284 error code, 346
ER_IB_MSG_1285 error code, 362
ER_IB_MSG_129 error code, 266
ER_IB_MSG_13 error code, 260
ER_IB_MSG_130 error code, 266
ER_IB_MSG_131 error code, 267
ER_IB_MSG_132 error code, 267
ER_IB_MSG_133 error code, 267
ER_IB_MSG_134 error code, 267
ER_IB_MSG_135 error code, 267
ER_IB_MSG_1357 error code, 377
ER_IB_MSG_1358 error code, 377
ER_IB_MSG_1359 error code, 377
ER_IB_MSG_136 error code, 267
ER_IB_MSG_137 error code, 267
ER_IB_MSG_1372 error code, 378
ER_IB_MSG_1373 error code, 378
ER_IB_MSG_1374 error code, 378
ER_IB_MSG_1375 error code, 378
ER_IB_MSG_138 error code, 267
ER_IB_MSG_1381 error code, 378
ER_IB_MSG_139 error code, 267
ER_IB_MSG_14 error code, 260

ER_IB_MSG_140 error code, 267
ER_IB_MSG_141 error code, 267
ER_IB_MSG_142 error code, 267
ER_IB_MSG_143 error code, 267
ER_IB_MSG_144 error code, 267
ER_IB_MSG_145 error code, 267
ER_IB_MSG_146 error code, 268
ER_IB_MSG_147 error code, 268
ER_IB_MSG_148 error code, 268
ER_IB_MSG_15 error code, 260
ER_IB_MSG_156 error code, 268
ER_IB_MSG_157 error code, 268
ER_IB_MSG_158 error code, 268
ER_IB_MSG_159 error code, 268
ER_IB_MSG_16 error code, 260
ER_IB_MSG_160 error code, 268
ER_IB_MSG_161 error code, 269
ER_IB_MSG_162 error code, 269
ER_IB_MSG_163 error code, 269
ER_IB_MSG_164 error code, 269
ER_IB_MSG_165 error code, 269
ER_IB_MSG_166 error code, 269
ER_IB_MSG_167 error code, 269
ER_IB_MSG_168 error code, 269
ER_IB_MSG_169 error code, 269
ER_IB_MSG_17 error code, 260
ER_IB_MSG_170 error code, 269
ER_IB_MSG_171 error code, 269
ER_IB_MSG_172 error code, 269
ER_IB_MSG_173 error code, 269
ER_IB_MSG_174 error code, 269
ER_IB_MSG_175 error code, 269
ER_IB_MSG_176 error code, 270
ER_IB_MSG_177 error code, 270
ER_IB_MSG_178 error code, 270
ER_IB_MSG_179 error code, 270
ER_IB_MSG_18 error code, 260
ER_IB_MSG_180 error code, 270
ER_IB_MSG_182 error code, 270
ER_IB_MSG_183 error code, 270
ER_IB_MSG_184 error code, 270
ER_IB_MSG_187 error code, 270
ER_IB_MSG_188 error code, 270
ER_IB_MSG_189 error code, 270
ER_IB_MSG_19 error code, 260
ER_IB_MSG_190 error code, 270
ER_IB_MSG_191 error code, 270
ER_IB_MSG_192 error code, 270
ER_IB_MSG_193 error code, 271
ER_IB_MSG_194 error code, 271
ER_IB_MSG_195 error code, 271
ER_IB_MSG_196 error code, 271
ER_IB_MSG_197 error code, 271
ER_IB_MSG_198 error code, 271

ER_IB_MSG_509 error code, 291
ER_IB_MSG_51 error code, 262
ER_IB_MSG_510 error code, 291
ER_IB_MSG_511 error code, 291
ER_IB_MSG_512 error code, 291
ER_IB_MSG_513 error code, 291
ER_IB_MSG_514 error code, 291
ER_IB_MSG_515 error code, 291
ER_IB_MSG_516 error code, 291
ER_IB_MSG_517 error code, 291
ER_IB_MSG_518 error code, 292
ER_IB_MSG_519 error code, 292
ER_IB_MSG_52 error code, 262
ER_IB_MSG_520 error code, 292
ER_IB_MSG_521 error code, 292
ER_IB_MSG_522 error code, 292
ER_IB_MSG_523 error code, 292
ER_IB_MSG_524 error code, 292
ER_IB_MSG_525 error code, 292
ER_IB_MSG_526 error code, 292
ER_IB_MSG_527 error code, 292
ER_IB_MSG_53 error code, 262
ER_IB_MSG_530 error code, 292
ER_IB_MSG_531 error code, 292
ER_IB_MSG_532 error code, 292
ER_IB_MSG_533 error code, 292
ER_IB_MSG_534 error code, 292
ER_IB_MSG_537 error code, 293
ER_IB_MSG_538 error code, 293
ER_IB_MSG_539 error code, 293
ER_IB_MSG_54 error code, 262
ER_IB_MSG_540 error code, 293
ER_IB_MSG_541 error code, 293
ER_IB_MSG_543 error code, 293
ER_IB_MSG_544 error code, 293
ER_IB_MSG_545 error code, 293
ER_IB_MSG_546 error code, 293
ER_IB_MSG_547 error code, 293
ER_IB_MSG_548 error code, 293
ER_IB_MSG_549 error code, 293
ER_IB_MSG_55 error code, 262
ER_IB_MSG_550 error code, 293
ER_IB_MSG_551 error code, 293
ER_IB_MSG_552 error code, 293
ER_IB_MSG_553 error code, 294
ER_IB_MSG_554 error code, 294
ER_IB_MSG_555 error code, 294
ER_IB_MSG_556 error code, 294
ER_IB_MSG_557 error code, 294
ER_IB_MSG_558 error code, 294
ER_IB_MSG_559 error code, 294
ER_IB_MSG_56 error code, 262
ER_IB_MSG_560 error code, 294
ER_IB_MSG_561 error code, 294

ER_IB_MSG_562 error code, 294
ER_IB_MSG_563 error code, 294
ER_IB_MSG_564 error code, 294
ER_IB_MSG_566 error code, 294
ER_IB_MSG_567 error code, 294
ER_IB_MSG_568 error code, 295
ER_IB_MSG_569 error code, 295
ER_IB_MSG_57 error code, 262
ER_IB_MSG_570 error code, 295
ER_IB_MSG_571 error code, 295
ER_IB_MSG_573 error code, 295
ER_IB_MSG_574 error code, 295
ER_IB_MSG_578 error code, 295
ER_IB_MSG_579 error code, 295
ER_IB_MSG_57_STAT_SPACE_DELETE_FAIL error code, 373
ER_IB_MSG_57_UNDO_SPACE_DELETE_FAIL error code, 370
ER_IB_MSG_58 error code, 262
ER_IB_MSG_580 error code, 295
ER_IB_MSG_581 error code, 295
ER_IB_MSG_582 error code, 295
ER_IB_MSG_583 error code, 295
ER_IB_MSG_584 error code, 295
ER_IB_MSG_585 error code, 295
ER_IB_MSG_586 error code, 295
ER_IB_MSG_587 error code, 296
ER_IB_MSG_588 error code, 296
ER_IB_MSG_589 error code, 296
ER_IB_MSG_59 error code, 263
ER_IB_MSG_590 error code, 296
ER_IB_MSG_591 error code, 296
ER_IB_MSG_592 error code, 296
ER_IB_MSG_593 error code, 296
ER_IB_MSG_594 error code, 296
ER_IB_MSG_595 error code, 296
ER_IB_MSG_596 error code, 296
ER_IB_MSG_597 error code, 296
ER_IB_MSG_598 error code, 296
ER_IB_MSG_599 error code, 296
ER_IB_MSG_6 error code, 259
ER_IB_MSG_60 error code, 263
ER_IB_MSG_600 error code, 296
ER_IB_MSG_601 error code, 296
ER_IB_MSG_602 error code, 297
ER_IB_MSG_603 error code, 297
ER_IB_MSG_604 error code, 297
ER_IB_MSG_605 error code, 297
ER_IB_MSG_606 error code, 297
ER_IB_MSG_607 error code, 297
ER_IB_MSG_608 error code, 297
ER_IB_MSG_609 error code, 297
ER_IB_MSG_61 error code, 263
ER_IB_MSG_611 error code, 297

ER_IB_MSG_612 error code, 297
ER_IB_MSG_613 error code, 297
ER_IB_MSG_614 error code, 297
ER_IB_MSG_615 error code, 297
ER_IB_MSG_616 error code, 297
ER_IB_MSG_617 error code, 297
ER_IB_MSG_619 error code, 298
ER_IB_MSG_62 error code, 263
ER_IB_MSG_623 error code, 298
ER_IB_MSG_624 error code, 298
ER_IB_MSG_626 error code, 298
ER_IB_MSG_627 error code, 298
ER_IB_MSG_628 error code, 298
ER_IB_MSG_629 error code, 298
ER_IB_MSG_63 error code, 263
ER_IB_MSG_630 error code, 298
ER_IB_MSG_631 error code, 298
ER_IB_MSG_632 error code, 298
ER_IB_MSG_633 error code, 298
ER_IB_MSG_634 error code, 298
ER_IB_MSG_635 error code, 299
ER_IB_MSG_636 error code, 299
ER_IB_MSG_637 error code, 299
ER_IB_MSG_638 error code, 299
ER_IB_MSG_639 error code, 299
ER_IB_MSG_64 error code, 263
ER_IB_MSG_642 error code, 299
ER_IB_MSG_643 error code, 299
ER_IB_MSG_644 error code, 299
ER_IB_MSG_645 error code, 299
ER_IB_MSG_646 error code, 299
ER_IB_MSG_647 error code, 299
ER_IB_MSG_648 error code, 299
ER_IB_MSG_649 error code, 299
ER_IB_MSG_65 error code, 263
ER_IB_MSG_650 error code, 299
ER_IB_MSG_651 error code, 299
ER_IB_MSG_652 error code, 300
ER_IB_MSG_654 error code, 300
ER_IB_MSG_655 error code, 300
ER_IB_MSG_656 error code, 300
ER_IB_MSG_657 error code, 300
ER_IB_MSG_658 error code, 300
ER_IB_MSG_659 error code, 300
ER_IB_MSG_66 error code, 263
ER_IB_MSG_660 error code, 300
ER_IB_MSG_661 error code, 300
ER_IB_MSG_662 error code, 300
ER_IB_MSG_663 error code, 300
ER_IB_MSG_67 error code, 263
ER_IB_MSG_68 error code, 263
ER_IB_MSG_69 error code, 263
ER_IB_MSG_694 error code, 300
ER_IB_MSG_695 error code, 300

ER_IB_MSG_696 error code, 300
ER_IB_MSG_697 error code, 301
ER_IB_MSG_699 error code, 301
ER_IB_MSG_7 error code, 259
ER_IB_MSG_70 error code, 263
ER_IB_MSG_707 error code, 301
ER_IB_MSG_708 error code, 301
ER_IB_MSG_709 error code, 301
ER_IB_MSG_71 error code, 263
ER_IB_MSG_710 error code, 301
ER_IB_MSG_711 error code, 301
ER_IB_MSG_712 error code, 302
ER_IB_MSG_713 error code, 302
ER_IB_MSG_714 error code, 302
ER_IB_MSG_715 error code, 302
ER_IB_MSG_716 error code, 302
ER_IB_MSG_718 error code, 302
ER_IB_MSG_719 error code, 302
ER_IB_MSG_72 error code, 263
ER_IB_MSG_720 error code, 302
ER_IB_MSG_722 error code, 302
ER_IB_MSG_723 error code, 302
ER_IB_MSG_724 error code, 302
ER_IB_MSG_725 error code, 302
ER_IB_MSG_726 error code, 302
ER_IB_MSG_727 error code, 303
ER_IB_MSG_728 error code, 303
ER_IB_MSG_73 error code, 263
ER_IB_MSG_737 error code, 303
ER_IB_MSG_738 error code, 303
ER_IB_MSG_739 error code, 303
ER_IB_MSG_74 error code, 264
ER_IB_MSG_740 error code, 303
ER_IB_MSG_741 error code, 304
ER_IB_MSG_742 error code, 304
ER_IB_MSG_743 error code, 304
ER_IB_MSG_744 error code, 304
ER_IB_MSG_745 error code, 304
ER_IB_MSG_746 error code, 304
ER_IB_MSG_747 error code, 304
ER_IB_MSG_748 error code, 304
ER_IB_MSG_749 error code, 304
ER_IB_MSG_75 error code, 264
ER_IB_MSG_750 error code, 304
ER_IB_MSG_751 error code, 304
ER_IB_MSG_752 error code, 304
ER_IB_MSG_753 error code, 304
ER_IB_MSG_754 error code, 304
ER_IB_MSG_755 error code, 304
ER_IB_MSG_756 error code, 305
ER_IB_MSG_757 error code, 305
ER_IB_MSG_758 error code, 305
ER_IB_MSG_759 error code, 305
ER_IB_MSG_76 error code, 264

ER_IB_MSG_965 error code, 318
 ER_IB_MSG_966 error code, 319
 ER_IB_MSG_967 error code, 319
 ER_IB_MSG_968 error code, 319
 ER_IB_MSG_969 error code, 319
 ER_IB_MSG_97 error code, 265
 ER_IB_MSG_970 error code, 319
 ER_IB_MSG_971 error code, 319
 ER_IB_MSG_972 error code, 319
 ER_IB_MSG_973 error code, 319
 ER_IB_MSG_974 error code, 319
 ER_IB_MSG_975 error code, 319
 ER_IB_MSG_976 error code, 319
 ER_IB_MSG_977 error code, 319
 ER_IB_MSG_978 error code, 319
 ER_IB_MSG_979 error code, 319
 ER_IB_MSG_98 error code, 265
 ER_IB_MSG_980 error code, 319
 ER_IB_MSG_981 error code, 320
 ER_IB_MSG_982 error code, 320
 ER_IB_MSG_983 error code, 320
 ER_IB_MSG_984 error code, 320
 ER_IB_MSG_985 error code, 320
 ER_IB_MSG_986 error code, 320
 ER_IB_MSG_987 error code, 320
 ER_IB_MSG_988 error code, 320
 ER_IB_MSG_989 error code, 320
 ER_IB_MSG_99 error code, 265
 ER_IB_MSG_990 error code, 320
 ER_IB_MSG_991 error code, 320
 ER_IB_MSG_992 error code, 320
 ER_IB_MSG_993 error code, 320
 ER_IB_MSG_994 error code, 320
 ER_IB_MSG_995 error code, 320
 ER_IB_MSG_996 error code, 321
 ER_IB_MSG_997 error code, 321
 ER_IB_MSG_998 error code, 321
 ER_IB_MSG_999 error code, 321
 ER_IB_MSG_BAD_DBLWR_FILE_NAME error code, 371
 ER_IB_MSG_BTREE_LEVEL_LIMIT_EXCEEDED error code, 364
 ER_IB_MSG_BUF_PENDING_IO error code, 328
 ER_IB_MSG_BUF_PENDING_IO_ON_SHUTDOWN error code, 337
 ER_IB_MSG_BUF_POOL_RESIZE_CODE_STATUS error code, 405
 ER_IB_MSG_BUF_POOL_RESIZE_COMPLETE_CUR_CORRUPT error code, 405
 ER_IB_MSG_BUF_POOL_RESIZE_PROGRESS_UPDATE error code, 405
 ER_IB_MSG_CANNOT_FIND_DD_UNDO_SPACE error code, 374
 ER_IB_MSG_CANNOT_OPEN_57_UNDO error code, 326
 ER_IB_MSG_CANT_DECRYPT_REDO_LOG error code, 311
 ER_IB_MSG_CANT_ENCRYPT_REDO_LOG_DATA error code, 310
 ER_IB_MSG_CLEAR_INSTANT_DROP_COLUMN_METADATA error code, 404
 ER_IB_MSG_CLOCK_GETTIME_FAILED error code, 362
 ER_IB_MSG_CLOCK_MONOTONIC_UNSUPPORTED error code, 362
 ER_IB_MSG_CLONE_DDL_APPLY error code, 392
 ER_IB_MSG_CLONE_DDL_INVALIDATE error code, 392
 ER_IB_MSG_CLONE_DDL_NTFN error code, 392
 ER_IB_MSG_CREATED_UNDO_SPACE error code, 380
 ER_IB_MSG_DATA_DIRECTORY_NOT_INITIALIZED_OR_CORRUPT error code, 330
 ER_IB_MSG_DBLWR_1285 error code, 370
 ER_IB_MSG_DBLWR_1286 error code, 371
 ER_IB_MSG_DBLWR_1287 error code, 371
 ER_IB_MSG_DBLWR_1288 error code, 371
 ER_IB_MSG_DBLWR_1290 error code, 371
 ER_IB_MSG_DBLWR_1293 error code, 371
 ER_IB_MSG_DBLWR_1294 error code, 371
 ER_IB_MSG_DBLWR_1295 error code, 371
 ER_IB_MSG_DBLWR_1296 error code, 371
 ER_IB_MSG_DBLWR_1297 error code, 371
 ER_IB_MSG_DBLWR_1298 error code, 371
 ER_IB_MSG_DBLWR_1300 error code, 371
 ER_IB_MSG_DBLWR_1301 error code, 371
 ER_IB_MSG_DBLWR_1304 error code, 371
 ER_IB_MSG_DBLWR_1305 error code, 371
 ER_IB_MSG_DBLWR_1306 error code, 372
 ER_IB_MSG_DBLWR_1307 error code, 372
 ER_IB_MSG_DBLWR_1308 error code, 372
 ER_IB_MSG_DBLWR_1309 error code, 372
 ER_IB_MSG_DBLWR_1310 error code, 372
 ER_IB_MSG_DBLWR_1311 error code, 372
 ER_IB_MSG_DBLWR_1312 error code, 372
 ER_IB_MSG_DBLWR_1313 error code, 372
 ER_IB_MSG_DBLWR_1314 error code, 372
 ER_IB_MSG_DBLWR_1315 error code, 372
 ER_IB_MSG_DBLWR_1316 error code, 372
 ER_IB_MSG_DBLWR_1317 error code, 372
 ER_IB_MSG_DBLWR_1318 error code, 372
 ER_IB_MSG_DBLWR_1320 error code, 372
 ER_IB_MSG_DBLWR_1321 error code, 373
 ER_IB_MSG_DBLWR_1323 error code, 373
 ER_IB_MSG_DBLWR_1324 error code, 373
 ER_IB_MSG_DBLWR_1325 error code, 373
 ER_IB_MSG_DBLWR_1326 error code, 373

ER_IB_MSG_DBLWR_1327 error code, 373
 ER_IB_MSG_DBLWR_LOAD_WRONG_SIZE error code, 372
 ER_IB_MSG_DBLWR_OPEN_OR_CREATE_WRONG_SIZE error code, 373
 ER_IB_MSG_DDL_FAIL_NO_BUILDER error code, 415
 ER_IB_MSG_DDL_LOG_DELETE_BY_ID_OK error code, 300
 ER_IB_MSG_DDL_LOG_DELETE_BY_ID_TMCT error code, 361
 ER_IB_MSG_DDL_LOG_FAIL_POST_DDL error code, 361
 ER_IB_MSG_DEPRECATED_INNODB_UNDO_TABLESPACE error code, 351
 ER_IB_MSG_DICT_PARTITION_NOT_FOUND error code, 370
 ER_IB_MSG_DOWNGRADE_PARTITION_FILE error code, 369
 ER_IB_MSG_DROPPED_UNDO_SPACE error code, 380
 ER_IB_MSG_ERROR_OPENING_NEW_UNDO_SPACE error code, 350
 ER_IB_MSG_FAILED_SDI_Z_BUF_ERROR error code, 350
 ER_IB_MSG_FAILED_SDI_Z_MEM_ERROR error code, 350
 ER_IB_MSG_FAILED_TO_ALLOCATE_WAIT error code, 350
 ER_IB_MSG_FAILED_TO_FINISH_TRUNCATE error code, 351
 ER_IB_MSG_FAIL_TO_SAVE_SPACE_STATE error code, 350
 ER_IB_MSG_FILE_RESIZE error code, 325
 ER_IB_MSG_FIL_STATE_MOVED_CHANGED_NAME error code, 369
 ER_IB_MSG_FIL_STATE_MOVED_CHANGED_PATH error code, 369
 ER_IB_MSG_FIL_STATE_MOVED_CORRECTED error code, 369
 ER_IB_MSG_FIL_STATE_MOVED_PREV error code, 428
 ER_IB_MSG_FIL_STATE_MOVED_PREV_OR_HAS_DATA error code, 428
 ER_IB_MSG_FIL_STATE_MOVED_TOO_MANY error code, 369
 ER_IB_MSG_FOUND_WRONG_UNDO_SPACE error code, 350
 ER_IB_MSG_GENERAL_TABLESPACE_UNDER_DATADIR error code, 283
 ER_IB_MSG_GTID_FLUSH_AT_SHUTDOWN error code, 373
 ER_IB_MSG_IBUF_CURSOR_RESTORATION_FAILED error code, 298
 ER_IB_MSG_IBUF_FAILED_TO_RESTORE_POSITION error code, 298
 ER_IB_MSG_IGNORE_SCAN_PATH error code, 282
 ER_IB_MSG_IMPLICIT_TABLESPACE_IN_DATADIR error code, 283
 ER_IB_MSG_INCORRECT_SIZE error code, 380
 ER_IB_MSG_INJECT_CRASH error code, 379
 ER_IB_MSG_INJECT_FAILURE error code, 379
 ER_IB_MSG_INNODB_END_INITIALIZE error code, 373
 ER_IB_MSG_INNODB_FLUSH_METHOD error code, 428
 ER_IB_MSG_INNODB_START_INITIALIZE error code, 373
 ER_IB_MSG_INVALID_LOCATION_FOR_TABLE error code, 294
 ER_IB_MSG_INVALID_LOCATION_FOR_TABLESPACE error code, 374
 ER_IB_MSG_INVALID_LOCATION_WRONG_DB error code, 374
 ER_IB_MSG_INVALID_PAGE_TYPE error code, 405
 ER_IB_MSG_LOCK_FREE_HASH_USAGE_STATS error code, 351
 ER_IB_MSG_LOG_CHECKPOINT_FOUND error code, 399
 ER_IB_MSG_LOG_CORRUPT error code, 301
 ER_IB_MSG_LOG_FILES_CANNOT_ENCRYPT_IN_READ_ONLY error code, 337
 ER_IB_MSG_LOG_FILES_CAPACITY_CHANGED error code, 399
 ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE error code, 303
 ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE_AND_READ_ONLY error code, 398
 ER_IB_MSG_LOG_FILES_CREATED_BY_MEB error code, 303
 ER_IB_MSG_LOG_FILES_CREATED_BY_MEB_AND_READ_ONLY error code, 303
 ER_IB_MSG_LOG_FILES_CREATED_BY_UNKNOWN_CREATOR error code, 400
 ER_IB_MSG_LOG_FILES_CREATE_AND_READ_ONLY_MODE error code, 325
 ER_IB_MSG_LOG_FILES_DIFFERENT_SIZES error code, 330
 ER_IB_MSG_LOG_FILES_ENCRYPTION_INIT_FAILED error code, 337
 ER_IB_MSG_LOG_FILES_FOUND_MISSING error code, 400
 ER_IB_MSG_LOG_FILES_INITIALIZED error code, 325
 ER_IB_MSG_LOG_FILES_INVALID_SET error code, 330
 ER_IB_MSG_LOG_FILES_RESIZE_CANCELLED error code, 399
 ER_IB_MSG_LOG_FILES_RESIZE_FINISHED error code, 400

ER_IB_MSG_LOG_FILES_RESIZE_ON_START error code, 335
 ER_IB_MSG_LOG_FILES_RESIZE_REQUESTED error code, 399
 ER_IB_MSG_LOG_FILES_REWRITING error code, 330
 ER_IB_MSG_LOG_FILES_UPGRADE error code, 400
 ER_IB_MSG_LOG_FILE_DIFFERENT_FORMATS error code, 400
 ER_IB_MSG_LOG_FILE_FOREIGN_UUID error code, 399
 ER_IB_MSG_LOG_FILE_FORMAT_TOO_NEW error code, 400
 ER_IB_MSG_LOG_FILE_FORMAT_TOO_OLD error code, 400
 ER_IB_MSG_LOG_FILE_FORMAT_UNKNOWN error code, 301
 ER_IB_MSG_LOG_FILE_HEADER_INVALID_CHECKSUM error code, 338
 ER_IB_MSG_LOG_FILE_HEADER_READ_FAILED error code, 397
 ER_IB_MSG_LOG_FILE_INVALID_LSN_RANGES error code, 399
 ER_IB_MSG_LOG_FILE_INVALID_START_LSN error code, 399
 ER_IB_MSG_LOG_FILE_IS_EMPTY error code, 397
 ER_IB_MSG_LOG_FILE_MARK_AS_UNUSED_FAILED error code, 401
 ER_IB_MSG_LOG_FILE_MARK_CURRENT_AS_INCOMPLETE error code, 400
 ER_IB_MSG_LOG_FILE_MISSING_FOR_ID error code, 399
 ER_IB_MSG_LOG_FILE_OPEN_FAILED error code, 325
 ER_IB_MSG_LOG_FILE_OS_CREATE_FAILED error code, 325
 ER_IB_MSG_LOG_FILE_PREPARE_ON_CREATE_FAILED error code, 325
 ER_IB_MSG_LOG_FILE_REMOVE_FAILED error code, 400
 ER_IB_MSG_LOG_FILE_RENAME_ON_CREATE_FAILED error code, 400
 ER_IB_MSG_LOG_FILE_RESIZE_FAILED error code, 325
 ER_IB_MSG_LOG_FILE_SIZE_INVALID error code, 330
 ER_IB_MSG_LOG_FILE_TOO_BIG error code, 397
 ER_IB_MSG_LOG_FILE_TOO_SMALL error code, 397
 ER_IB_MSG_LOG_FILE_TRUNCATE error code, 401
 ER_IB_MSG_LOG_FILE_UNUSED_MARK_AS_IN_USE_FAILED error code, 401
 ER_IB_MSG_LOG_FILE_UNUSED_REMOVE_FAILED error code, 401
 ER_IB_MSG_LOG_FILE_UNUSED_RENAME_FAILED error code, 401
 ER_IB_MSG_LOG_FILE_UNUSED_RESIZE_FAILED error code, 401
 ER_IB_MSG_LOG_FORMAT_BEFORE_5_7_9 error code, 338
 ER_IB_MSG_LOG_FORMAT_BEFORE_8_0_30 error code, 301
 ER_IB_MSG_LOG_FORMAT_OLD error code, 303
 ER_IB_MSG_LOG_FORMAT_OLD_AND_LOG_CORRUPTED error code, 301
 ER_IB_MSG_LOG_FORMAT_OLD_AND_NO_CLEAN_SHUTDOWN error code, 301
 ER_IB_MSG_LOG_INIT_DIR_LIST_FAILED error code, 398
 ER_IB_MSG_LOG_INIT_DIR_MISSING_SUBDIR error code, 398
 ER_IB_MSG_LOG_INIT_DIR_NOT_EMPTY_WONT_INITIALIZE error code, 398
 ER_IB_MSG_LOG_PARAMS_CONCURRENCY_MARGIN_UNSAFE error code, 338
 ER_IB_MSG_LOG_PARAMS_DEDICATED_SERVER_IGNORED error code, 401
 ER_IB_MSG_LOG_PARAMS_FILE_SIZE_UNUSED error code, 398
 ER_IB_MSG_LOG_PARAMS_LEGACY_USAGE error code, 401
 ER_IB_MSG_LOG_PARAMS_N_FILES_UNUSED error code, 398
 ER_IB_MSG_LOG_PFS_ACQUIRE_SERVICES_FAILED error code, 400
 ER_IB_MSG_LOG_PFS_CREATE_TABLES_FAILED error code, 401
 ER_IB_MSG_LOG_PRE_8_0_30_MISSING_FILE0 error code, 400
 ER_IB_MSG_LOG_UPGRADE_CLONED_DB error code, 399
 ER_IB_MSG_LOG_UPGRADE_CORRUPTION_UNEXPECTED error code, 399
 ER_IB_MSG_LOG_UPGRADE_FORCED_RECV error code, 398
 ER_IB_MSG_LOG_UPGRADE_IN_READ_ONLY_MODE error code, 399
 ER_IB_MSG_LOG_UPGRADE_UNINITIALIZED_FILES error code, 399
 ER_IB_MSG_LOG_WRITER_ABORTS_LOG_ARCHIVER error code, 336
 ER_IB_MSG_LOG_WRITER_ENTERED_EXTRA_MARGIN error code, 398
 ER_IB_MSG_LOG_WRITER_EXITED_EXTRA_MARGIN error code, 398
 ER_IB_MSG_LOG_WRITER_OUT_OF_SPACE error code, 336
 ER_IB_MSG_LOG_WRITER_WAITING_FOR_ARCHIVER error code, 337

ER_IB_MSG_LOG_WRITER_WAIT_ON_CONSUMER error code, 404
 ER_IB_MSG_LOG_WRITER_WAIT_ON_NEW_LOG_FILE error code, 398
 ER_IB_MSG_LOG_WRITER_WRITE_FAILED error code, 398
 ER_IB_MSG_MADVISE_FAILED error code, 350
 ER_IB_MSG_MADV_DONTDUMP_UNSUPPORTED error code, 350
 ER_IB_MSG_MASTER_KEY_ROTATED error code, 380
 ER_IB_MSG_MAX_UNDO_SPACES_REACHED error code, 350
 ER_IB_MSG_NOT_END_WITH_IBU error code, 351
 ER_IB_MSG_NO_ENCRYPT_PROGRESS_FOUND error code, 346
 ER_IB_MSG_PAGE_ARCH_NO_RESET_POINTS error code, 373
 ER_IB_MSG_PARSE_OLD_REDO_INDEX_VERSION error code, 404
 ER_IB_MSG_PAR_RSEG_INIT_COMPLETE_MSG error code, 390
 ER_IB_MSG_PAR_RSEG_INIT_TIME_MSG error code, 390
 ER_IB_MSG_POST_RECOVER_DDL_LOG_RECOVER error code, 361
 ER_IB_MSG_POST_RECOVER_POST_TS_ENCRYPT error code, 361
 ER_IB_MSG_RECOVERY_CHECKPOINT_FROM_BEFORE_CLEARED error code, 370
 ER_IB_MSG_RECOVERY_CHECKPOINT_NOT_FOUND error code, 301
 ER_IB_MSG_RECOVERY_CHECKPOINT_OUTSIDE_LOGFILE error code, 398
 ER_IB_MSG_RECOVERY_CORRUPT error code, 330
 ER_IB_MSG_RECOVERY_IN_READ_ONLY error code, 303
 ER_IB_MSG_RECOVERY_IS_NEEDED error code, 303
 ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG error code, 390
 ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG_UNEXPECTED error code, 390
 ER_IB_MSG_RECOVERY_SKIPPED_IN_READ_ONLY_MODE error code, 302
 ER_IB_MSG_REENCRYPTED_GENERAL_TABLESPACE_KEY error code, 389
 ER_IB_MSG_REENCRYPTED_TABLESPACE_KEY error code, 389
 ER_IB_MSG_RESUME_OP_FOR_SPACE error code, 346
 ER_IB_MSG_SCANNING_TEMP_TABLESPACE_DIR error code, 377
 ER_IB_MSG_SDI_Z_STREAM_ERROR error code, 350
 ER_IB_MSG_SDI_Z_UNKNOWN_ERROR error code, 350
 ER_IB_MSG_SKIP_HIDDEN_DIR error code, 368
 ER_IB_MSG_STATS_SAMPLING_TOO_LARGE error code, 384
 ER_IB_MSG_SUBMIT_DETAILED_BUG_REPORT error code, 426
 ER_IB_MSG_THREAD_CONCURRENCY_CHANGED error code, 339
 ER_IB_MSG_TOO_LONG_PATH error code, 362
 ER_IB_MSG_TRX_RECOVERY_ROLLBACK_COMPLETED error code, 333
 ER_IB_MSG_TRX_RECOVERY_ROLLBACK_NOT_COMPLETE error code, 376
 ER_IB_MSG_TRYING_TO_OPEN_FILE_FOR_LONG_TIME error code, 395
 ER_IB_MSG_UNDO_ALTERED_ACTIVE error code, 379
 ER_IB_MSG_UNDO_ALTERED_INACTIVE error code, 379
 ER_IB_MSG_UNDO_ENCRYPTION_INFO_LOADED error code, 392
 ER_IB_MSG_UNDO_MARKED_ACTIVE error code, 379
 ER_IB_MSG_UNDO_MARKED_EMPTY error code, 379
 ER_IB_MSG_UNDO_MARKED_FOR_TRUNCATE error code, 332
 ER_IB_MSG_UNDO_TRUNCATE_COMPLETE error code, 332
 ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_CLONE error code, 370
 ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_FAILURE error code, 332
 ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_LOG_CREATE error code, 332
 ER_IB_MSG_UNDO_TRUNCATE_DELAY_BY_MDL error code, 379
 ER_IB_MSG_UNDO_TRUNCATE_FAIL_TO_READ_LOG_FILE error code, 332
 ER_IB_MSG_UNDO_TRUNCATE_START error code, 332
 ER_IB_MSG_UNDO_TRUNCATE_TOO_OFTEN error code, 379
 ER_IB_MSG_UNEXPECTED_FILE_EXISTS error code, 379
 ER_IB_MSG_UNPROTECTED_LOCATION_ALLOWED error code, 281
 ER_IB_MSG_UPGRADE_PARTITION_FILE error code, 369
 ER_IB_MSG_UPGRADE_PARTITION_FILE_IMPORT error code, 369
 ER_IB_MSG_USING_UNDO_SPACE error code, 350
 ER_IB_MSG_WAIT_FOR_ENCRYPT_THREAD error code, 346
 ER_IB_MSG_WRONG_TABLESPACE_DIR error code, 351

ER_IB_PARALLEL_READER_WORKER_INFO error code, 405
ER_IB_PRIMARY_KEY_IS_INSTANT error code, 409
ER_IB_RDBLWR_BYTES_INFO error code, 397
ER_IB_RECV_FIRST_REC_GROUP_INVALID error code, 362
ER_IB_RELOCK_LATCH_ORDER_VIOLATION error code, 377
ER_IB_RESURRECT_ACQUIRE_TABLE_LOCK error code, 411
ER_IB_RESURRECT_IDENTIFY_TABLE_TO_LOCK error code, 411
ER_IB_RESURRECT_RECORD_COMPLETE error code, 411
ER_IB_RESURRECT_RECORD_PROGRESS error code, 411
ER_IB_RESURRECT_TRX_INSERT error code, 411
ER_IB_RESURRECT_TRX_INSERT_COMPLETE error code, 411
ER_IB_RESURRECT_TRX_UPDATE error code, 411
ER_IB_RESURRECT_TRX_UPDATE_COMPLETE error code, 411
ER_IB_SELECT_COUNT_STAR error code, 410
ER_IB_SYNC_READ_FAILED error code, 419
ER_IB_TABLESPACE_PATH_VALIDATION_SKIPPED error code, 376
ER_IB_TMP_TABLESPACE_CANNOT_CREATE_DIRECTORY error code, 377
ER_IB_UNABLE_TO_EXPAND_TEMPORARY_TABLESPACE error code, 377
ER_IB_WARN_ACCESSING_NONEXISTING_SPACE error code, 276
ER_IB_WARN_MANY_NON_LRU_FILES_OPENED error code, 395
ER_IB_WARN_OPEN_PARTITION_FILE error code, 369
ER_IB_WRN_ENCRYPTION_INFO_SIZE_MISMATCH error code, 392
ER_IB_WRN_FAILED_TO_ACQUIRE_SERVICE error code, 385
ER_IB_WRN_FAST_SHUTDOWN_REDO_DISABLED error code, 375
ER_IB_WRN_IGNORE_REDO_LOG_CAPACITY error code, 408
ER_IB_WRN_OLD_GEOMETRY_TYPE error code, 386
ER_IB_WRN_PAGE_ARCH_FLUSH_DATA error code, 374
ER_IB_WRN_REDO_DISABLED error code, 375
ER_IB_WRN_REDO_ENABLED error code, 375
ER_IB_WRONG_PAGEID_AFTER_SYNC_READ error code, 419
ER_IB_WRONG_PAGE_ID error code, 418
ER_IDENTIFIED_BY_UNSUPPORTED error code, 118
ER_IDENT_CAUSES_TOO_LONG_PATH error code, 58
ER_IDENT_CAUSES_TOO_LONG_PATH_IN_UPGRADE error code, 366
ER_IF_NOT_EXISTS_UNSUPPORTED_TRG_EXISTS_ON_DIFFER error code, 121
ER_IF_NOT_EXISTS_UNSUPPORTED_UDF_NATIVE_FCT_NAME error code, 122
ER_ILLEGAL_GRANT_FOR_TABLE error code, 13
ER_ILLEGAL_HA error code, 5
ER_ILLEGAL_HA_CREATE_OPTION error code, 34
ER_ILLEGAL_PRIVILEGE_LEVEL error code, 84
ER_ILLEGAL_REFERENCE error code, 19
ER_ILLEGAL_USER_VAR error code, 65
ER_ILLEGAL_VALUE_FOR_TYPE error code, 27
ER_IMPLICIT_COMPARISON_FOR_JSON error code, 112
ER_IMPOSSIBLE_STRING_CONVERSION error code, 112
ER_IMP_INCOMPATIBLE_CFG_VERSION error code, 109
ER_IMP_INCOMPATIBLE_DD_VERSION error code, 84
ER_IMP_INCOMPATIBLE_MYSQLD_VERSION error code, 84
ER_IMP_INCOMPATIBLE_SDI_VERSION error code, 84
ER_IMP_NO_FILES_MATCHED error code, 83
ER_IMP_SCHEMA_DOES_NOT_EXIST error code, 83
ER_IMP_TABLE_ALREADY_EXISTS error code, 84
ER_INCOMPATIBLE_TYPE_AGG error code, 136
ER_INCONSISTENT_ERROR error code, 340
ER_INCONSISTENT_PARTITION_INFO_ERROR error code, 34
ER_INCONSISTENT_TYPE_OF_FUNCTIONS_ERROR error code, 35
ER_INCORRECT_CURRENT_PASSWORD error code, 104
ER_INCORRECT_GLOBAL_LOCAL_VAR error code, 19
ER_INCORRECT_TYPE error code, 65
ER_INDEX_COLUMN_TOO_LONG error code, 47
ER_INDEX_CORRUPT error code, 47
ER_INDEX_OTHER_THAN_PK error code, 124
ER_INDEX_TYPE_NOT_SUPPORTED_FOR_SPATIAL_INDEX error code, 92
ER_INFORMATION_SCHEMA_VERSION_CHANGE error code, 414
ER_INIT_BOOTSTRAP_COMPLETE error code, 168
ER_INIT_CANT_OPEN_BOOTSTRAP_FILE error code, 168
ER_INIT_CREATING_DD error code, 169
ER_INIT_DATADIR_EXISTS_AND_NOT_WRITABLE_WONT_INITIALIZE error code, 168
ER_INIT_DATADIR_EXISTS_AND_PATH_TOO_LONG_WONT_INITIALIZE error code, 168
ER_INIT_DATADIR_EXISTS_WONT_INITIALIZE error code, 168

ER_INIT_DATADIR_NOT_EMPTY_WONT_INITIALIZE error code, 168
 ER_INIT_FAILED_TO_GENERATE_ROOT_PASSWORD error code, 368
 ER_INIT_GENERATING_TEMP_PASSWORD_FOR_ROOT error code, 168
 ER_INIT_ROOT_WITHOUT_PASSWORD error code, 168
 ER_INNODB_ACTIVE_INDEX_CHANGE_FAILED error code, 201
 ER_INNODB_AUTOEXTEND_SIZE_OUT_OF_RANGE error code, 115
 ER_INNODB_CANNOT_CREATE_TABLE error code, 201
 ER_INNODB_CANT_BUILD_INDEX_XLATION_TABLE_FOR error code, 189
 ER_INNODB_CANT_FIND_INDEX_IN_INNODB_DD error code, 189
 ER_INNODB_CLOSING_CONNECTION_ROLLS_BACK error code, 189
 ER_INNODB_CLUSTERED_INDEX_PRIVATE error code, 189
 ER_INNODB_COMPRESSION_FAILURE error code, 116
 ER_INNODB_DIFF_IN_REF_LEN error code, 201
 ER_INNODB_DIRTY_WATER_MARK_NOT_LOW error code, 188
 ER_INNODB_ERROR_LOGGER_FATAL_MSG error code, 203
 ER_INNODB_ERROR_LOGGER_MSG error code, 203
 ER_INNODB_FAILED_TO_FIND_IDX error code, 201
 ER_INNODB_FAILED_TO_FIND_IDX_FROM_DICT_CACHE error code, 201
 ER_INNODB_FAILED_TO_FIND_IDX_WITH_KEY_NO error code, 201
 ER_INNODB_FILES_SAME error code, 189
 ER_INNODB_FORCED_RECOVERY error code, 59
 ER_INNODB_FT_AUX_NOT_HEX_ID error code, 59
 ER_INNODB_FT_LIMIT error code, 53
 ER_INNODB_FT_WRONG_DOCID_COLUMN error code, 54
 ER_INNODB_FT_WRONG_DOCID_INDEX error code, 54
 ER_INNODB_IDX_CNT_FEWER_THAN_DEFINED_IN_MYSQL error code, 202
 ER_INNODB_IDX_CNT_MORE_THAN_DEFINED_IN_MYSQL error code, 201
 ER_INNODB_IDX_COLUMN_CNT_DIFF error code, 202
 ER_INNODB_ILLEGAL_COLON_IN_POOL error code, 188
 ER_INNODB_IMPORT_DROP_COL_METADATA_MISMATCH error code, 128
 ER_INNODB_IMPORT_ENUM_NULL_TERMINATOR_MISSING error code, 128
 ER_INNODB_IMPORT_ERROR error code, 55
 ER_INNODB_IMPORT_WRONG_DROPPED_ENUM_LENGTH error code, 128
 ER_INNODB_IMPORT_WRONG_NUMBER_OF_INDEXES_TOO error code, 128
 ER_INNODB_IMPORT_WRONG_NUMBER_OF_INDEXES_ZERO error code, 128
 ER_INNODB_INCOMPATIBLE_WITH_TABLESPACE error code, 115
 ER_INNODB_INDEX_COLUMN_INFO_UNLIKE_MYSQLS error code, 189
 ER_INNODB_INDEX_CORRUPT error code, 55
 ER_INNODB_INSTANT_ADD_DROP_NOT_SUPPORTED_MAX error code, 126
 ER_INNODB_INSTANT_ADD_NOT_SUPPORTED_MAX_FIELDS error code, 126
 ER_INNODB_INTERNAL_INDEX error code, 201
 ER_INNODB_INVALID_AUTOEXTEND_SIZE_VALUE error code, 115
 ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY error code, 188
 ER_INNODB_INVALID_INNODB_UNDO_DIRECTORY_LOCATION error code, 351
 ER_INNODB_INVALID_LOG_GROUP_HOME_DIR error code, 188
 ER_INNODB_INVALID_MONITOR_COUNTER_NAME error code, 202
 ER_INNODB_INVALID_PAGE_SIZE error code, 188
 ER_INNODB_IO_CAPACITY_EXCEEDS_MAX error code, 188
 ER_INNODB_IO_WRITE_ERROR_RETRYING error code, 381
 ER_INNODB_IO_WRITE_FAILED error code, 381
 ER_INNODB_MANDATORY error code, 142
 ER_INNODB_MAX_ROW_VERSION error code, 121
 ER_INNODB_MONITOR_DEFAULT_VALUE_NOT_DEFINED error code, 202
 ER_INNODB_MONITOR_IS_ENABLED error code, 202
 ER_INNODB_NO_FT_TEMP_TABLE error code, 53
 ER_INNODB_ONLINE_LOG_TOO_BIG error code, 54
 ER_INNODB_OUT_OF_RESOURCES error code, 370
 ER_INNODB_PK_NOT_IN_MYSQL error code, 189
 ER_INNODB_PK_ONLY_IN_MYSQL error code, 189
 ER_INNODB_READ_ONLY error code, 59
 ER_INNODB_REDO_ARCHIVING_ENABLED error code, 112
 ER_INNODB_REDO_DISABLED error code, 112
 ER_INNODB_REDO_LOG_ARCHIVE_ACTIVE error code, 101
 ER_INNODB_REDO_LOG_ARCHIVE_DIRS_INVALID error code, 101
 ER_INNODB_REDO_LOG_ARCHIVE_DIR_CLASH error code, 101

ER_INNODB_REDO_LOG_ARCHIVE_DIR_EMPTY error code, 101	ER_INVALID_AUTHENTICATION_POLICY error code, 392
ER_INNODB_REDO_LOG_ARCHIVE_DIR_PERMISSIONS error code, 101	ER_INVALID_BITWISE_AGGREGATE_OPERANDS_SIZE error code, 77
ER_INNODB_REDO_LOG_ARCHIVE_FAILED error code, 101	ER_INVALID_BITWISE_OPERANDS_SIZE error code, 77
ER_INNODB_REDO_LOG_ARCHIVE_FILE_CREATE error code, 101	ER_INVALID_CAST error code, 113
ER_INNODB_REDO_LOG_ARCHIVE_INACTIVE error code, 101	ER_INVALID_CAST_POLYGON_RING_DIRECTION error code, 116
ER_INNODB_REDO_LOG_ARCHIVE_LABEL_NOT_FOUND error code, 101	ER_INVALID_CAST_TO_GEOMETRY error code, 116
ER_INNODB_REDO_LOG_ARCHIVE_NO_SUCH_DIR error code, 101	ER_INVALID_CAST_TO_JSON error code, 71
ER_INNODB_REDO_LOG_ARCHIVE_SESSION error code, 101	ER_INVALID_CHARACTER_STRING error code, 23
ER_INNODB_REDO_LOG_ARCHIVE_START_SUBDIR_PATH error code, 101	ER_INVALID_CHARSET_AND_DEFAULT_IS_MB error code, 161
ER_INNODB_REDO_LOG_ARCHIVE_START_TIMEOUT error code, 101	ER_INVALID_COLLATION_FOR_CHARSET error code, 193
ER_INNODB_TRX_XLATION_TABLE_OOM error code, 189	ER_INVALID_DD_OBJECT error code, 76
ER_INNODB_UNABLE_TO_ACQUIRE_DD_OBJECT error code, 374	ER_INVALID_DD_OBJECT_ID error code, 76
ER_INNODB_UNDO_LOG_FULL error code, 61	ER_INVALID_DD_OBJECT_NAME error code, 76
ER_INNODB_UNKNOWN_COLLATION error code, 188	ER_INVALID_DEFAULT error code, 8
ER_INNODB_UNREGISTERED_TRX_ACTIVE error code, 189	ER_INVALID_DEFAULT_UTF8MB4_COLLATION error code, 91
ER_INNODB_USE_MONITOR_GROUP_NAME error code, 202	ER_INVALID_ENCRYPTION_OPTION error code, 74
ER_INSECURE_CHANGE_SOURCE error code, 51	ER_INVALID_ENCRYPTION_REQUEST error code, 100
ER_INSECURE_PLAIN_TEXT error code, 51	ER_INVALID_ERROR_LOG_NAME error code, 150
ER_INSERT_INFO error code, 9	ER_INVALID_FIELD_SIZE error code, 61
ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_FORMAT error code, 46	ER_INVALID_FILE_FORMAT error code, 427
ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_BINLOG_FORMAT error code, 45	ER_INVALID_GEOJSON CRS NOT TOP_LEVEL error code, 88
ER_INSIDE_TRANSACTION_PREVENTS_SWITCH_SQL_LOG_BIN error code, 46	ER_INVALID_GEOJSON_MISSING_MEMBER error code, 65
ER_INSTALL_COMPONENT_SET_NULL_VALUE error code, 126	ER_INVALID_GEOJSON_UNSPECIFIED error code, 65
ER_INSTALL_COMPONENT_SET_UNUSED_VALUE error code, 126	ER_INVALID_GEOJSON_WRONG_TYPE error code, 65
ER_INSTALL_PLUGIN_CONFLICT_CLIENT error code, 117	ER_INVALID_GROUP_FUNC_USE error code, 11
ER_INSTALL_PLUGIN_CONFLICT_LOG error code, 389	ER_INVALID_INFO_IN_FRM error code, 161
ER_INTERNAL_ERROR error code, 55	ER_INVALID_INSTRUMENT error code, 142
ER_INTERSECT_ALL_MAX_DUPLICATES_EXCEEDED error code, 123	ER_INVALID_JSON_ATTRIBUTE error code, 111
ER_INVALID_ADMIN_ADDRESS error code, 353	ER_INVALID_JSON_BINARY_DATA error code, 71
ER_INVALID_ARGUMENT_FOR_LOGARITHM error code, 61	ER_INVALID_JSON_CHARSET error code, 71
ER_INVALID_ASSIGNMENT_TARGET error code, 117	ER_INVALID_JSON_CHARSET_IN_FUNCTION error code, 71
	ER_INVALID_JSON_DATA error code, 65
	ER_INVALID_JSON_PATH error code, 71
	ER_INVALID_JSON_PATH_ARRAY_CELL error code, 73
	ER_INVALID_JSON_PATH_CHARSET error code, 71
	ER_INVALID_JSON_PATH_WILDCARD error code, 71
	ER_INVALID_JSON_TEXT error code, 71
	ER_INVALID_JSON_TEXT_IN_PARAM error code, 71
	ER_INVALID_JSON_TYPE error code, 102
	ER_INVALID_JSON_VALUE_FOR_CAST error code, 72
	ER_INVALID_JSON_VALUE_FOR_FUNC_INDEX error code, 105

ER_INVALID_MFA_OPERATIONS_FOR_PASSWORDLESS_USER error code, 118
 ER_INVALID_MFA_PLUGIN_SPECIFIED error code, 118
 ER_INVALID_MULTIPLE_CLAUSES error code, 100
 ER_INVALID_NAMED_PIPE_FULL_ACCESS_GROUP error code, 358
 ER_INVALID_NO_OF_ARGS error code, 83
 ER_INVALID_ON_UPDATE error code, 22
 ER_INVALID_OPTION_CHARACTERS error code, 80
 ER_INVALID_OPTION_END_CHARACTER error code, 80
 ER_INVALID_OPTION_KEY error code, 80
 ER_INVALID_OPTION_KEY_VALUE_PAIR error code, 80
 ER_INVALID_OPTION_START_CHARACTER error code, 80
 ER_INVALID_OPTION_VALUE error code, 80
 ER_INVALID_OR_OLD_TABLE_OR_DB_NAME error code, 170
 ER_INVALID_PARAMETER_USE error code, 113
 ER_INVALID_PLUGIN_FOR_REGISTRATION error code, 118
 ER_INVALID_PROPERTY_KEY error code, 355
 ER_INVALID_RPL_WILD_TABLE_FILTER_PATTERN error code, 65
 ER_INVALID_SERVER_DOWNGRADE_NOT_PATCH error code, 414
 ER_INVALID_SERVER_UPGRADE_NOT_LTS error code, 414
 ER_INVALID_THREAD_ID error code, 87
 ER_INVALID_THREAD_PRIORITY error code, 87
 ER_INVALID_TIME_ZONE_INTERVAL error code, 113
 ER_INVALID_TLS_VERSION error code, 395
 ER_INVALID_TYPE_FOR_JSON error code, 71
 ER_INVALID_USER_ATTRIBUTE_JSON error code, 111
 ER_INVALID_USER_FOR_REGISTRATION error code, 118
 ER_INVALID_USE_OF_FORCE_OPTION error code, 87
 ER_INVALID_USE_OF_NULL error code, 13
 ER_INVALID_VALUE_FOR_ENFORCE_GTID_CONSISTENCY error code, 139
 ER_INVALID_VALUE_OF_BIND_ADDRESSES error code, 346
 ER_INVALID_VCPU_ID error code, 86
 ER_INVALID_VCPU_RANGE error code, 87
 ER_INVALID_XPLUGIN_SOCKET_SAME_AS_SERVER error code, 374
 ER_INVALID_YEAR_COLUMN_LENGTH error code, 55
 ER_IO_ERR_LOG_INDEX_READ error code, 27
 ER_IO_READ_ERROR error code, 54
 ER_IO_WRITE_ERROR error code, 55
 ER_IPSOCK_ERROR error code, 8
 ER_INVALID_QUERY_INVALID_CLAUSE error code, 79
 ER_I_S_SKIPPED_TABLESPACE error code, 86
 ER_JSON_BAD_ONE_OR_ALL_ARG error code, 72
 ER_JSON_DOCUMENT_NULL_KEY error code, 72
 ER_JSON_DOCUMENT_TOO_DEEP error code, 72
 ER_JSON_KEY_TOO_BIG error code, 72
 ER_JSON_PARSE_ERROR error code, 151
 ER_JSON_SCHEMA_VALIDATION_ERROR_WITH_DETAILED error code, 108
 ER_JSON_USED_AS_KEY error code, 72
 ER_JSON_VACUOUS_PATH error code, 72
 ER_JSON_VALUE_OUT_OF_RANGE_FOR_FUNC_INDEX error code, 105
 ER_JSON_VALUE_TOO_BIG error code, 72
 ER_JT_MAX_NESTED_PATH error code, 88
 ER_JT_VALUE_OUT_OF_RANGE error code, 88
 ER_KERBEROS_CREATE_USER error code, 117
 ER_KEYCACHE_OOM error code, 144
 ER_KEYRING_ACCESS_DENIED_ERROR error code, 75
 ER_KEYRING_AWS_CMK_ID_NOT_SET error code, 227
 ER_KEYRING_AWS_FAILED_TO_ACCESS_DATA_FILE error code, 227
 ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_FROM_CONF error code, 226
 ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_ID_FROM_CONF error code, 226
 ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEY error code, 227
 ER_KEYRING_AWS_FAILED_TO_ACCESS_OR_CREATE_KEY error code, 227
 ER_KEYRING_AWS_FAILED_TO_CONNECT_KMS error code, 228
 ER_KEYRING_AWS_FAILED_TO_DECRYPT_KEY error code, 228
 ER_KEYRING_AWS_FAILED_TO_ENCRYPT_KEY error code, 228
 ER_KEYRING_AWS_FAILED_TO_FLUSH_KEYRING_TO_FILE error code, 228
 ER_KEYRING_AWS_FAILED_TO_GENERATE_KEY_DUE_TO_CONF error code, 228
 ER_KEYRING_AWS_FAILED_TO_GENERATE_NEW_KEY error code, 228
 ER_KEYRING_AWS_FAILED_TO_GET_KMS_CREDENTIAL_FROM_CONF error code, 227
 ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_INTERNAL_ERROR error code, 227
 ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_PLUGIN_INTERNAL error code, 227
 ER_KEYRING_AWS_FAILED_TO_OPEN_CONF_FILE error code, 226
 ER_KEYRING_AWS_FAILED_TO_RESTORE_FROM_BACKUP error code, 228

ER_KEYRING_AWS_FAILED_TO_RE_ENCRYPT_KEY error code, 228	ER_KEYRING_FAILED_TO_GET_FILE_STAT error code, 223
ER_KEYRING_AWS_FAILED_TO_ROTATE_CMK error code, 228	ER_KEYRING_FAILED_TO_LOAD_KEYRING_CONTENT error code, 223
ER_KEYRING_AWS_FAILED_TO_SET_CMK_ID error code, 226	ER_KEYRING_FAILED_TO_REMOVE_FILE error code, 223
ER_KEYRING_AWS_FAILED_TO_SET_REGION error code, 226	ER_KEYRING_FAILED_TO_REMOVE_KEY_DUE_TO_EMPTY_ID error code, 224
ER_KEYRING_AWS_FOUND_MALFORMED_BACKUP_FILE error code, 228	ER_KEYRING_FAILED_TO_RESTORE_FROM_BACKUP_FILE error code, 223
ER_KEYRING_AWS_INCORRECT_FILE error code, 228	ER_KEYRING_FAILED_TO_TRUNCATE_FILE error code, 223
ER_KEYRING_AWS_INCORRECT_PROXY error code, 366	ER_KEYRING_FILE_IO_ERROR error code, 223
ER_KEYRING_AWS_INCORRECT_REGION error code, 228	ER_KEYRING_FOUND_MALFORMED_BACKUP_FILE error code, 223
ER_KEYRING_AWS_INIT_FAILURE error code, 227	ER_KEYRING_INCORRECT_FILE error code, 223
ER_KEYRING_AWS_INVALID_CONF_FILE_PATH error code, 227	ER_KEYRING_INVALID_KEY_LENGTH error code, 222
ER_KEYRING_AWS_INVALID_DATA_FILE_PATH error code, 227	ER_KEYRING_INVALID_KEY_TYPE error code, 222
ER_KEYRING_AWS_INVALID_KEY_LENGTH_FOR_CIPHER error code, 227	ER_KEYRING_KEY_FETCH_FAILED_DUE_TO_EMPTY_KEY_ID error code, 224
ER_KEYRING_AWS_UDF_AWS_KMS_ERROR error code, 75	ER_KEYRING_LOGGER_ERROR_MSG error code, 213
ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_EMPTY_KEY_ID error code, 223	ER_KEYRING_MIGRATE_FAILED error code, 339
ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_INVALID_KEY error code, 223	ER_KEYRING_MIGRATE_MEMORY_DEALLOCATION_FAILED error code, 426
ER_KEYRING_COMPONENT_EXCEPTION error code, 384	ER_KEYRING_MIGRATE_SKIPPED_KEY error code, 426
ER_KEYRING_COMPONENT_KEYRING_FILE_DECRYPT_FAILED error code, 425	ER_KEYRING_MIGRATION_EXTRA_OPTIONS error code, 259
ER_KEYRING_COMPONENT_KEYRING_FILE_INVALID_FORMAT error code, 425	ER_KEYRING_MIGRATION_FAILED error code, 204
ER_KEYRING_COMPONENT_KEYRING_FILE_JSON_EXTENSION_FAILED error code, 425	ER_KEYRING_MIGRATION_FAILURE error code, 75
ER_KEYRING_COMPONENT_KEYRING_FILE_KEY_EXTENSION_FAILED error code, 425	ER_KEYRING_MIGRATION_STATUS error code, 75
ER_KEYRING_COMPONENT_KEYRING_FILE_NAME_EMPTY error code, 425	ER_KEYRING_MIGRATION_SUCCESSFUL error code, 204
ER_KEYRING_COMPONENT_KEYRING_FILE_READ_FAILED error code, 425	ER_KEYRING_OCI_HTTP_REQUEST error code, 405
ER_KEYRING_COMPONENT_MEMORY_ALLOCATION_ERROR error code, 384	ER_KEYRING_OCI_INVALID_JSON error code, 405
ER_KEYRING_COMPONENT_NOT_INITIALIZED error code, 384	ER_KEYRING_OCI_PARSE_JSON error code, 405
ER_KEYRING_FAILED_TO_FLUSH_KEYRING_TO_FILE error code, 223	ER_KEYRING_OKV_CONNECTION_TO_SERVER_FAILED error code, 225
ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING error code, 224	ER_KEYRING_OKV_FAILED_TO_ACTIVATE_KEYS error code, 225
ER_KEYRING_FAILED_TO_FLUSH_KEYS_TO_KEYRING_BACKUP error code, 224	ER_KEYRING_OKV_FAILED_TO_ADD_ATTRIBUTE error code, 225
	ER_KEYRING_OKV_FAILED_TO_FETCH_KEY error code, 225
	ER_KEYRING_OKV_FAILED_TO_FIND_SERVER_ENTRY error code, 224
	ER_KEYRING_OKV_FAILED_TO_FIND_STANDBY_SERVER_ENTRY error code, 225
	ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY error code, 225
	ER_KEYRING_OKV_FAILED_TO_GENERATE_KEY_DUE_TO_INTERRUPT error code, 224
	ER_KEYRING_OKV_FAILED_TO_INIT_CLIENT error code, 225

ER_KEYRING_OKV_FAILED_TO_INIT_SSL_LAYER error code, 225	ER_LANGUAGE_COMPONENT_CONVERSION error code, 135
ER_KEYRING_OKV_FAILED_TO_LOAD_KEY_UID error code, 225	ER_LANGUAGE_COMPONENT_ERROR error code, 416
ER_KEYRING_OKV_FAILED_TO_LOAD_SSL_TRUST_STORE error code, 226	ER_LANGUAGE_COMPONENT_INFO error code, 416
ER_KEYRING_OKV_FAILED_TO_PARSE_CONF_FILE error code, 225	ER_LANGUAGE_COMPONENT_INSTALL_ERROR error code, 424
ER_KEYRING_OKV_FAILED_TO_REMOVE_KEY error code, 225	ER_LANGUAGE_COMPONENT_INTERNAL error code, 134
ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY error code, 226	ER_LANGUAGE_COMPONENT_INTERNAL_ERROR error code, 424
ER_KEYRING_OKV_FAILED_TO_RETRIEVE_KEY_SIGNATURE error code, 226	ER_LANGUAGE_COMPONENT_KEYWORD error code, 135
ER_KEYRING_OKV_FAILED_TO_SET_CERTIFICATE_FILE error code, 226	ER_LANGUAGE_COMPONENT_NOT_AVAILABLE error code, 127
ER_KEYRING_OKV_FAILED_TO_SET_KEY_FILE error code, 226	ER_LANGUAGE_COMPONENT_RUNTIME error code, 135
ER_KEYRING_OKV_FAILED_TO_STORE_KEY error code, 225	ER_LANGUAGE_COMPONENT_SERVER_ERROR error code, 424
ER_KEYRING_OKV_FAILED_TO_STORE_OR_GENERATE_KEY error code, 225	ER_LANGUAGE_COMPONENT_SET_SYSTEM_VARIABLE error code, 135
ER_KEYRING_OKV_INCORRECT_KEY_VAULT_CONFIGURATION error code, 224	ER_LANGUAGE_COMPONENT_TIMEZONE error code, 135
ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INCORRECT_CONFIG error code, 224	ER_LANGUAGE_COMPONENT_UNSUPPORTED_LANGUAGE error code, 127
ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INTERNAL_ERROR error code, 224	ER_LANGUAGE_COMPONENT_UNSUPPORTED_TYPE error code, 135
ER_KEYRING_OKV_INVALID_KEY_LENGTH_FOR_CIPHER error code, 224	ER_LANGUAGE_COMPONENT_VM_API_FUNCTION_ERROR error code, 424
ER_KEYRING_OKV_INVALID_KEY_TYPE error code, 224	ER_LANGUAGE_COMPONENT_VM_INTERNAL_ERROR error code, 424
ER_KEYRING_OKV_KEY_MISMATCH error code, 226	ER_LANGUAGE_COMPONENT_WARNING error code, 416
ER_KEYRING_OKV_STANDBY_SERVER_COUNT_EXCEEDED error code, 396	ER_LDAP_AUTH_ATTRIBUTE_OUT_OF_RANGE error code, 84
ER_KEYRING_OPERATION_FAILED_DUE_TO_INTERNAL_ERROR error code, 223	ER_LDAP_AUTH_CHANGED error code, 204
ER_KEYRING_UDF_KEYRING_SERVICE_ERROR error code, 74	ER_LDAP_AUTH_ENTRY_NOT_FOUND error code, 340
ER_KEYRING_UNKNOWN_ERROR error code, 223	ER_LDAP_AUTH_CERTIFICATE_NAME error code, 254
ER_KEY_COLUMN_DOES_NOT_EXISTS error code, 8	ER_LDAP_AUTH_COMMUNICATION_HOST_INFO error code, 256
ER_KEY_DOES_NOT_EXISTS error code, 15	ER_LDAP_AUTH_CONNECTION_CREATOR_ENTER error code, 255
ER_KEY_NOT_FOUND error code, 5	ER_LDAP_AUTH_CONNECTION_GET_LDAP_INFO_NULL error code, 256
ER_KEY_PART_0 error code, 28	ER_LDAP_AUTH_CONNECTION_POOL_INIT_FAILED error code, 255
ER_KEY_REF_DO_NOT_MATCH_TABLE_REF error code, 19	ER_LDAP_AUTH_CONNECTION_POOL_REINIT_ENTER error code, 257
ER_KILLED_THREADS_OF_PLUGIN error code, 169	ER_LDAP_AUTH_CONNECTION_PUSHED_TO_POOL error code, 255
ER_KILLING_THREAD error code, 169	ER_LDAP_AUTH_CONN_POOL_DEINITIALIZING error code, 253
ER_KILL_DENIED_ERROR error code, 9	ER_LDAP_AUTH_CONN_POOL_INITIALIZING error code, 253
ER_LANGUAGE_COMPONENT error code, 127	
ER_LANGUAGE_COMPONENT_CANNOT_UNINSTALL error code, 127	
ER_LANGUAGE_COMPONENT_CONCURRENCY_LIMIT error code, 135	

ER_LDAP_AUTH_CONN_POOL_NOT_CREATED error code, 253	ER_LDAP_AUTH_GRP_SEARCH_NOT_SPECIAL_HDL error code, 356
ER_LDAP_AUTH_CREATE_CONNECTION_KEY error code, 256	ER_LDAP_AUTH_GRP_SEARCH_SPECIAL_HDL error code, 253
ER_LDAP_AUTH_CREATING_LDAP_CONNECTION error code, 255	ER_LDAP_AUTH_GRP_USER_OBJECT_HAS_GROUP_INFO error code, 356
ER_LDAP_AUTH_DEINIT_FAILED error code, 252	ER_LDAP_AUTH_INFO_FOR_USER error code, 253
ER_LDAP_AUTH_DELETING_CONNECTION_KEY error code, 256	ER_LDAP_AUTH_INFO_USER_MAP error code, 427
ER_LDAP_AUTH_DISTINGUISHED_NAME error code, 256	ER_LDAP_AUTH_INIT_FAILED error code, 256
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_CONNECTION error code, 257	ER_LDAP_AUTH_LDAPS error code, 356
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT error code, 252	ER_LDAP_AUTH_LDAP_INFO_NULL error code, 255
ER_LDAP_AUTH_FAILED_TO_CREATE_LDAP_OBJECT_CREATOR error code, 252	ER_LDAP_AUTH_MAX_ALLOWED_CONNECTION_LIMIT_HIT error code, 255
ER_LDAP_AUTH_FAILED_TO_CREATE_OR_GET_CONNECTION error code, 252	ER_LDAP_AUTH_MAX_POOL_SIZE_SET_FAILED error code, 255
ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_NOT_READY error code, 254	ER_LDAP_AUTH_METHOD_TO_CLIENT error code, 256
ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_POOL_IN_RECONNECT error code, 254	ER_LDAP_AUTH_OBJECT_CREATE_TIMESTAMP error code, 254
ER_LDAP_AUTH_FAILED_TO_DEINITIALIZE_POOL_IN_RECONNECT_WITH_PAUSE error code, 254	ER_LDAP_AUTH_OR_GROUP_RETRIEVAL_FAILED error code, 257
ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNECTION error code, 257	ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION error code, 256
ER_LDAP_AUTH_FAILED_TO_GET_CONNECTION_AS_PENDING error code, 254	ER_LDAP_AUTH_POOLED_CONNECTION_KEY error code, 256
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_DEINIT error code, 254	ER_LDAP_AUTH_READ_POOL_DISABLE_MAX_SIZE_ZERO error code, 252
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_INIT error code, 254	ER_LDAP_AUTH_POOL_GET_FAILED_TO_CREATE_CONNECTION error code, 257
ER_LDAP_AUTH_FAILED_TO_INITIALIZE_POOL_IN_RECONNECT error code, 254	ER_LDAP_AUTH_POOL_REINITIALIZING error code, 253
ER_LDAP_AUTH_FAILED_TO_POOL_DEINIT error code, 254	ER_LDAP_AUTH_RETURNING_CONNECTION_TO_POOL error code, 255
ER_LDAP_AUTH_FAILED_TO_SEARCH_DN error code, 257	ER_LDAP_AUTH_SASL_BIND_SUCCESS_INFO error code, 256
ER_LDAP_AUTH_FAILED_TO_WRITE_PACKET error code, 253	ER_LDAP_AUTH_SASL_PROCESS_SASL error code, 256
ER_LDAP_AUTH_FREEING_CONNECTION error code, 255	ER_LDAP_AUTH_SASL_REQUEST_FROM_CLIENT error code, 256
ER_LDAP_AUTH_GETTING_CONNECTION_FROM_POOL error code, 255	ER_LDAP_AUTH_SEARCHED_USER_GRP_NAME error code, 254
ER_LDAP_AUTH_GRP_DN_PARSING_FAILED error code, 356	ER_LDAP_AUTH_SEARCH_USER_GROUP_ATTR_NOT_FOUND error code, 255
ER_LDAP_AUTH_GRP_INCORRECT_ATTRIBUTE error code, 356	ER_LDAP_AUTH_SETTING_USERNAME error code, 253
ER_LDAP_AUTH_GRP_INFO_FOUND_IN_MANY_OBJECTS error code, 356	ER_LDAP_AUTH_SKIPPING_USER_GROUP_SEARCH error code, 252
ER_LDAP_AUTH_GRP_IS_FULL_DN error code, 253	ER_LDAP_AUTH_STARTED_FOR_USER error code, 256
ER_LDAP_AUTH_GRP_NULL_ATTRIBUTE_VALUE error code, 356	ER_LDAP_AUTH_STARTING_TLS error code, 256
ER_LDAP_AUTH_GRP_OBJECT_HAS_USER_INFO error code, 356	ER_LDAP_AUTH_TLS_CONF error code, 252
	ER_LDAP_AUTH_TLS_CONNECTION error code, 252
	ER_LDAP_AUTH_USER_AUTH_DATA error code, 253
	ER_LDAP_AUTH_USER_BIND_FAILED error code, 257

ER_LDAP_AUTH_USER_FOUND_IN_MANY_GRP	ER_LH_AVRO_ENUM_CANNOT_CONVERT_CHARSET
error code, 254	error code, 132
ER_LDAP_AUTH_USER_GROUP_SEARCH_FAILED	ER_LH_AVRO_ENUM_MISMATCH error code, 132
error code, 257	ER_LH_AVRO_FILE_DATA_CORRUPT error code, 132
ER_LDAP_AUTH_USER_GROUP_SEARCH_INFO error	ER_LH_AVRO_FILE_ENDS_UNEXPECTEDLY error
code, 253	code, 132
ER_LDAP_AUTH_USER_GROUP_SEARCH_ROOT_BIND	ER_LH_AVRO_HEADER_METADATA_ERR error code,
error code, 349	133
ER_LDAP_AUTH_USER_HAS_MULTIPLE_GRP_NAMES	ER_LH_AVRO_HEADER_MISMATCH error code, 132
error code, 254	ER_LH_AVRO_HEADER_NO_SCHEMA error code, 133
ER_LDAP_AUTH_USER_NOT_FOUND_IN_ANY_GRP	ER_LH_AVRO_INVALID_BLOCK_RECORD_COUNT
error code, 253	error code, 132
ER_LDAP_AUTH_ZERO_MAX_POOL_SIZE_UNCHANGED	ER_LH_AVRO_INVALID_BLOCK_SIZE error code, 132
error code, 253	ER_LH_AVRO_INVALID_NAME_IN_SCHEMA error
ER_LDAP_EMPTY_USERDN_PASSWORD error code,	code, 133
364	ER_LH_AVRO_INVALID_UNION error code, 132
ER_LDAP_MAPPING_CHECK_DELIMI_QUOTE error	ER_LH_AVRO_NO_CODEC_IN_HEADER error code,
code, 357	133
ER_LDAP_MAPPING_EMPTY_MAPPING error code,	ER_LH_AVRO_SCHEMA_DEPTH_EXCEEDS_MAX
357	error code, 132
ER_LDAP_MAPPING_GETTING_NEXT_MAPPING	ER_LH_AVRO_TYPE_CANNOT_CONVERT error code,
error code, 357	132
ER_LDAP_MAPPING_GET_USER_PROXY error code,	ER_LH_AWS_AUTH_ERR error code, 131
356	ER_LH_BAD_VALUE error code, 130
ER_LDAP_MAPPING_INFO error code, 357	ER_LH_CANNOT_CONVERT_STRING error code, 131
ER_LDAP_MAPPING_IS_QUOTE error code, 358	ER_LH_CHARSET_UNSUPPORTED error code, 131
ER_LDAP_MAPPING_NON_DESIRED_STATE error	ER_LH_COLUMN_MAX_ERR error code, 131
code, 358	ER_LH_COLUMN_MISMATCH_ERR error code, 131
ER_LDAP_MAPPING_NO_SEPEARATOR_END_OF_GRP	ER_LH_COL_IS_EMPTY error code, 130
error code, 357	ER_LH_COL_IS_EMPTY_WARN error code, 130
ER_LDAP_MAPPING_PARSING_CURRENT_STATE	ER_LH_COL_NOT_NULLABLE error code, 130
error code, 357	ER_LH_CSV_PARSING_ERR error code, 131
ER_LDAP_MAPPING_PARSING_ERROR error code,	ER_LH_DATETIME_FORMAT error code, 131
358	ER_LH_DECIMAL_OOM_ERR error code, 130
ER_LDAP_MAPPING_PARSING_MAPPING_INFO error	ER_LH_DECIMAL_PRECISION_EXCEEDS_SCHEMA
code, 358	error code, 130
ER_LDAP_MAPPING_PROCESS_DELIMITER error	ER_LH_DECIMAL_UNKNOWN_ERR error code, 130
code, 357	ER_LH_DUPLICATE_FILE error code, 132
ER_LDAP_MAPPING_PROCESS_DELIMITER_COMMA	ER_LH_EMPTY_FILE error code, 132
error code, 357	ER_LH_EXCEEDS_MAX error code, 131
ER_LDAP_MAPPING_PROCESS_DELIMITER_EQUAL	ER_LH_EXCEEDS_MIN error code, 130
error code, 357	ER_LH_FORMAT_HEADER_NO_MAGIC_BYTES error
ER_LDAP_MAPPING_PROCESS_DELIMITER_TRY_COMMA	code, 133
error code, 357	ER_LH_INFER_FILE_HAS_NO_DATA error code, 134
ER_LDAP_MAPPING_PROCESS_MAPPING error code,	ER_LH_INFER_JSON_INVALID_SCHEMA error code,
357	136
ER_LDAP_MAPPING_TRIMMING_SPACES error code,	ER_LH_INFER_NO_DATA error code, 134
358	ER_LH_INFER_NO_FILES error code, 134
ER_LDAP_MAPPING_USER_DONT_BELONG_GROUP	ER_LH_INFER_SCHEMA_MISMATCH error code, 133
error code, 357	ER_LH_INFER_WARN_GOT_EXCEPTION error code,
ER_LH_AVRO_CANNOT_PARSE_HEADER error code,	134
134	ER_LH_INVALID_JSON_FILE_FORMAT_SCHEMA
ER_LH_AVRO_DECODING_ERR error code, 133	error code, 136

ER_LH_JSON_FILE_FORMAT_WARN_INFER_SCHEMA error code, 136
 ER_LH_JSON_PARSING error code, 135
 ER_LH_NO_FILES_FOUND error code, 132
 ER_LH_OOM error code, 133
 ER_LH_OUT_OF_RANGE error code, 131
 ER_LH_PARQUET_CANNOT_LOCATE_OFFSET error code, 133
 ER_LH_PARQUET_CANNOT_LOCATE_SCHEMA error code, 133
 ER_LH_PARQUET_CANNOT_READ_HEADER error code, 134
 ER_LH_PARQUET_CANT_OPEN_FILE error code, 134
 ER_LH_PARQUET_DECIMAL_CONVERSION_ERR error code, 131
 ER_LH_PARQUET_NON_UTF8_FILE_ENC error code, 133
 ER_LH_PARQUET_ROW_GROUP_SIZE_EXCEEDS_MAX error code, 133
 ER_LH_PARQUET_SCHEMA_MISMATCH error code, 133
 ER_LH_PARQUET_TYPE_CANNOT_CONVERT error code, 133
 ER_LH_REAL_IS_NAN error code, 131
 ER_LH_RESOURCE_PRINCIPAL_BUCKET_ERR error code, 132
 ER_LH_RESOURCE_PRINCIPAL_ERR error code, 131
 ER_LH_STRING_TOO_LONG error code, 132
 ER_LH_TOO_LARGE_ROW_ERR error code, 134
 ER_LH_TOO_LARGE_VALUE_ERR error code, 134
 ER_LH_USER_DATA_ACCESS_FAILED error code, 136
 ER_LH_WARN_COL_MISSING_NOT_NULLABLE error code, 130
 ER_LH_WARN_DECIMAL_ROUNDING error code, 130
 ER_LH_WARN_EXCEEDS_MAX_TRUNCATING error code, 131
 ER_LH_WARN_EXCEEDS_MIN_TRUNCATING error code, 131
 ER_LH_WARN_INFER_SKIPPED_FILES error code, 134
 ER_LH_WARN_INFER_SKIPPED_LINES error code, 133
 ER_LH_WARN_INFER_USE_DEFAULT_COL_NAMES error code, 134
 ER_LH_WARN_TRUNCATED error code, 131
 ER_LIMITED_PART_RANGE error code, 36
 ER_LOAD_BULK_DATA_FAILED error code, 125
 ER_LOAD_BULK_DATA_UNSORTED error code, 124
 ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL error code, 126
 ER_LOAD_BULK_DATA_WARN_NULL_TO_NOTNULL_LOG error code, 408
 ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD error code, 125
 ER_LOAD_BULK_DATA_WRONG_VALUE_FOR_FIELD_LOG error code, 408
 ER_LOAD_DATA_INFILE_FAILED_IN_UNEXPECTED_WAY error code, 152
 ER_LOAD_FROM_FIXED_SIZE_ROWS_TO_VAR error code, 29
 ER_LOAD_INFO error code, 9
 ER_LOCAL_VARIABLE error code, 18
 ER_LOCKING_SERVICE_DEADLOCK error code, 70
 ER_LOCKING_SERVICE_TIMEOUT error code, 70
 ER_LOCKING_SERVICE_WRONG_NAME error code, 70
 ER_LOCK_ABORTED error code, 46
 ER_LOCK_DEADLOCK error code, 17
 ER_LOCK_NOWAIT error code, 81
 ER_LOCK_ORDER_DEPENDENCIES_SYNTAX error code, 364
 ER_LOCK_ORDER_FAILED_READ_FILE error code, 364
 ER_LOCK_ORDER_FAILED_WRITE_FILE error code, 364
 ER_LOCK_ORDER_INIT_FAILED error code, 363
 ER_LOCK_ORDER_MESSAGE error code, 364
 ER_LOCK_ORDER_SCANNER_SYNTAX error code, 364
 ER_LOCK_OR_ACTIVE_TRANSACTION error code, 16
 ER_LOCK_REFUSED_BY_ENGINE error code, 74
 ER_LOCK_TABLE_FULL error code, 17
 ER_LOCK_WAIT_TIMEOUT error code, 17
 ER_LOG_BIN_BETTER_WITH_NAME error code, 148
 ER_LOG_CANNOT_PURGE_BINLOG_WITH_BACKUP_LOCK error code, 413
 ER_LOG_CANNOT_WRITE error code, 137
 ER_LOG_CANNOT_WRITE_EXTENDED error code, 366
 ER_LOG_CLIENT_INTERACTION_TIMEOUT error code, 426
 ER_LOG_COMPONENT_CANNOT_INIT error code, 381
 ER_LOG_COMPONENT_FLUSH_FAILED error code, 389
 ER_LOG_DEPRECATED_NON_COMPOSABLE_MULTIPLE_ENGINE error code, 428
 ER_LOG_FILES_GIVEN_LOG_OUTPUT_IS_TABLE error code, 147
 ER_LOG_FILE_CANNOT_OPEN error code, 218
 ER_LOG_FILE_INVALID error code, 147
 ER_LOG_GENERAL_CANNOT_OPEN error code, 137
 ER_LOG_IN_USE error code, 28
 ER_LOG_OUTPUT_CONTRADICTORY error code, 147
 ER_LOG_PARTITION_PREFIX_KEY_NOT_SUPPORTED error code, 427
 ER_LOG_PRINTF_MSG error code, 203

ER_LOG_PRIV_CHECKS_REQUIRE_ROW_FORMAT_NO_INSETS error code, 369
 ER_LOG_PURGE_NO_FILE error code, 41
 ER_LOG_PURGE_UNKNOWN_ERR error code, 28
 ER_LOG_SANITIZATION error code, 427
 ER_LOG_SLOW_CANNOT_OPEN error code, 137
 ER_LOG_SYSLOG_CANNOT_OPEN error code, 137
 ER_LONGITUDE_OUT_OF_RANGE error code, 84
 ER_LOWER_CASE_TABLE_NAMES_CS_DD_ON_CI_FS_INCOMPATIBLE error code, 148
 ER_LOWER_CASE_TABLE_NAMES_USING_0 error code, 148
 ER_LOWER_CASE_TABLE_NAMES_USING_2 error code, 148
 ER_MALFORMED_GTID_SET_ENCODING error code, 52
 ER_MALFORMED_GTID_SET_SPECIFICATION error code, 52
 ER_MALFORMED_GTID_SPECIFICATION error code, 52
 ER_MALFORMED_PACKET error code, 56
 ER_MANDATORY_ROLE error code, 85
 ER_MASTER_KEY_ROTATION_BINLOG_FAILED error code, 74
 ER_MASTER_KEY_ROTATION_NOT_SUPPORTED_BY_SERVER error code, 74
 ER_MASTER_KEY_ROTATION_SE_UNAVAILABLE error code, 74
 ER_MAXVALUE_IN_VALUES_IN error code, 44
 ER_MAX_PREPARED_STMT_COUNT_REACHED error code, 33
 ER_MDL_OUT_OF_RESOURCES error code, 112
 ER_MECAB_CHARSET_LOADED error code, 207
 ER_MECAB_CREATE_LATTICE_FAILED error code, 207
 ER_MECAB_CREATING_MODEL error code, 207
 ER_MECAB_FAILED_TO_CREATE_MODEL error code, 207
 ER_MECAB_FAILED_TO_CREATE_TRIGGER error code, 207
 ER_MECAB_NOT_SUPPORTED error code, 206
 ER_MECAB_NOT_VERIFIED error code, 206
 ER_MECAB_OOM_WHILE_PARSING_TEXT error code, 207
 ER_MECAB_PARSE_FAILED error code, 207
 ER_MECAB_UNSUPPORTED_CHARSET error code, 207
 ER_MESSAGE_AND_STATEMENT error code, 45
 ER_MFA_METHODS_IDENTICAL error code, 118
 ER_MFA_METHODS_INVALID_ORDER error code, 118
 ER_MFA_METHOD_EXISTS error code, 118
 ER_MFA_METHOD_NOT_EXISTS error code, 118
 ER_MFA_PLUGIN_NOT_LOADED error code, 395
 ER_MFA_USER_ATTRIBUTES_CORRUPT error code, 395
 ER_MICROSECOND_TIMER_IS_NOT_AVAILABLE error code, 201
 ER_MIGRATE_TABLE_TO_DD_OOM error code, 370
 ER_MISPLACED_INTO error code, 109
 ER_MISSING_ACL_SYSTEM_TABLE error code, 195
 ER_MISSING_CURRENT_PASSWORD error code, 104
 ER_MISSING_DEFAULT_GRANT_SYSTEM_TABLE error code, 195
 ER_MISSING_HA_CREATE_OPTION error code, 61
 ER_MISSING_JSON_TABLE_VALUE error code, 87
 ER_MISSING_JSON_VALUE error code, 110
 ER_MISSING_KEY error code, 60
 ER_MISSING_SKIP_REPLICA error code, 21
 ER_MISSING_TABLESPACE_FILE error code, 85
 ER_MIXING_NOT_ALLOWED error code, 18
 ER_MIX_HANDLER_ERROR error code, 35
 ER_MIX_OF_GROUP_FUNC_AND_FIELDS error code, 13
 ER_MIX_OF_GROUP_FUNC_AND_FIELDS_V2 error code, 66
 ER_MTA_CANT_PARALLEL error code, 51
 ER_MTA_CHANGE_SOURCE_CANT_RUN_WITH_GAPS error code, 54
 ER_MTA_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX error code, 58
 ER_MTA_FEATURE_IS_NOT_SUPPORTED error code, 50
 ER_MTA_INCONSISTENT_DATA error code, 51
 ER_MTA_RECOVERY_FAILURE error code, 54
 ER_MTA_RESET_WORKERS error code, 54
 ER_MTA_UPDATED_DBS_GREATER_MAX error code, 50
 ER_MTR_MSG_1 error code, 390
 ER_MULTIPLE_CONSTRAINTS_WITH_SAME_NAME error code, 108
 ER_MULTIPLE_DEF_CONST_IN_LIST_PART_ERROR error code, 35
 ER_MULTIPLE_INTO_CLAUSES error code, 109
 ER_MULTIPLE_JSON_VALUES error code, 110
 ER_MULTIPLE_PRI_KEY error code, 8
 ER_MULTI_UPDATE_KEY_CONFLICT error code, 47
 ER_MUST_CHANGE_PASSWORD error code, 55
 ER_MUST_CHANGE_PASSWORD_LOGIN error code, 58
 ER_MYINIT_FAILED error code, 146
 ER_MYISAM_CHECK_METHOD_ERROR error code, 202
 ER_MYISAM_CRASHED_ERROR error code, 202
 ER_MYISAM_CRASHED_ERROR_IN error code, 153
 ER_MYISAM_CRASHED_ERROR_IN_THREAD error code, 153
 ER_MYSQLBACKUP_CLIENT_MSG error code, 120

ER_MYSQLBACKUP_MSG error code, 367
 ER_MYSQL_NATIVE_PASSWORD_SECOND_PASSWORD_USED error code, 8
 ER_MYSQL_NATIVE_PASSWORD_SECOND_PASSWORD_ERROR error code, 353
 ER_MY_MALLOC_GETPROCADDRESS_FAILED error code, 397
 ER_MY_MALLOC_LOADLIBRARY_FAILED error code, 397
 ER_MY_MALLOC_USING_JEMALLOC error code, 396
 ER_MY_MALLOC_USING_STD_MALLOC error code, 397
 ER_MY_NET_WRITE_FAILED_FALLING_BACK_ON_STDERR error code, 180
 ER_M_BIGGER_THAN_D error code, 30
 ER_NAME_BECOMES_EMPTY error code, 33
 ER_NANOSECOND_TIMER_IS_NOT_AVAILABLE error code, 200
 ER_NATIVE_FCT_NAME_COLLISION error code, 40
 ER_NDBINFO_NOT_UPGRADING_SCHEMA error code, 373
 ER_NDBINFO_UPGRADING_SCHEMA error code, 373
 ER_NDBINFO_UPGRADING_SCHEMA_FAIL error code, 373
 ER_NDB_LOG_ENTRY error code, 188
 ER_NDB_LOG_ENTRY_WITH_PREFIX error code, 188
 ER_NDB_REPLICATION_SCHEMA_ERROR error code, 42
 ER_NEED_FILE_INSTEAD_OF_DIR error code, 148
 ER_NEED_LOG_BIN error code, 148
 ER_NEED_REPREPARE error code, 41
 ER_NETWORK_NAMESPACES_NOT_SUPPORTED error code, 361
 ER_NETWORK_NAMESPACE_FILE_PATH_TOO_LONG error code, 362
 ER_NETWORK_NAMESPACE_NOT_ALLOWED_FOR_WRITE error code, 361
 ER_NETWORK_READ_EVENT_CHECKSUM_FAILURE error code, 340
 ER_NET_ERROR_ON_WRITE error code, 14
 ER_NET_FCNTL_ERROR error code, 14
 ER_NET_OK_PACKET_TOO_LARGE error code, 65
 ER_NET_PACKETS_OUT_OF_ORDER error code, 14
 ER_NET_PACKET_TOO_LARGE error code, 13
 ER_NET_READ_ERROR error code, 14
 ER_NET_READ_ERROR_FROM_PIPE error code, 13
 ER_NET_READ_INTERRUPTED error code, 14
 ER_NET_UNCOMPRESS_ERROR error code, 14
 ER_NET_WAIT_ERROR error code, 362
 ER_NET_WAIT_ERROR2 error code, 386
 ER_NET_WRITE_INTERRUPTED error code, 14
 ER_NEW_ABORTING_CONNECTION error code, 15
 ER_NO error code, 3
 ER_NONEXISTING_GRANT error code, 13
 ER_NONEXISTING_PROC_GRANT error code, 29
 ER_NONEXISTING_TABLE_GRANT error code, 13
 ER_NONPOSITIVE_RADIUS error code, 90
 ER_NONUPDATEABLE_COLUMN error code, 26
 ER_NON_BOOLEAN_EXPR_FOR_CHECK_CONSTRAINT error code, 99
 ER_NON_DEFAULT_VALUE_FOR_GENERATED_COLUMN error code, 68
 ER_NON_GROUPING_FIELD_USED error code, 33
 ER_NON_INSERTABLE_TABLE error code, 33
 ER_NON_RO_SELECT_DISABLE_TIMER error code, 62
 ER_NON_SCALAR_USED_AS_KEY error code, 136
 ER_NON_UNIQ_ERROR error code, 6
 ER_NON_UPDATABLE_TABLE error code, 22
 ER_NORMAL_SERVER_SHUTDOWN error code, 339
 ER_NOTE_COMPONENT_KEYRING_OCI_MISSING_NAME_OR_TV error code, 404
 ER_NOTE_COMPONENT_SLOT_DEREGISTRATION_SUCCESS error code, 410
 ER_NOTE_COMPONENT_SLOT_REGISTRATION_SUCCESS error code, 410
 ER_NOTE_KEYRING_COMPONENT_AES_DATA_IDENTIFIER_EMPTY error code, 385
 ER_NOTE_KEYRING_COMPONENT_AES_INVALID_KEY error code, 385
 ER_NOTE_KEYRING_COMPONENT_AES_INVALID_MODE_BLOCK error code, 384
 ER_NOTE_KEYRING_COMPONENT_AES_OPERATION_ERROR error code, 385
 ER_NOTE_KEYRING_COMPONENT_EMPTY_DATA_ID error code, 425
 ER_NOTE_KEYRING_COMPONENT_GENERATE_FAILED error code, 385
 ER_NOTE_KEYRING_COMPONENT_INITIALIZED error code, 384
 ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ITERATOR error code, 385
 ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ITERATOR error code, 425
 ER_NOTE_KEYRING_COMPONENT_KEY_READ_ITERATOR_FET error code, 426
 ER_NOTE_KEYRING_COMPONENT_KEY_READ_ITERATOR_INIT error code, 425
 ER_NOTE_KEYRING_COMPONENT_METADATA_ITERATOR_INVALID error code, 385
 ER_NOTE_KEYRING_COMPONENT_NOT_INITIALIZED error code, 425
 ER_NOTE_KEYRING_COMPONENT_READ_DATA_NOT_FOUND error code, 385
 ER_NOTE_KEYRING_COMPONENT_REMOVE_FAILED error code, 385
 ER_NOTE_KEYRING_COMPONENT_STORE_FAILED error code, 385

ER_NOTE_KEYRING_COMPONENT_WRITE_MAXIMUM_SIZE error code, 385
 ER_NOT_ALLOWED_COMMAND error code, 13
 ER_NOT_ALLOWED_WITH_START_TRANSACTION error code, 111
 ER_NOT_FORM_FILE error code, 5
 ER_NOT_HINT_UPDATABLE_VARIABLE error code, 85
 ER_NOT_IMPLEMENTED_FOR_CARTESIAN_SRS error code, 90
 ER_NOT_IMPLEMENTED_FOR_GEOGRAPHIC_SRS error code, 84
 ER_NOT_IMPLEMENTED_FOR_PROJECTED_SRS error code, 90
 ER_NOT_IMPLEMENTED_GET_TABLESPACE_STATISTICS error code, 218
 ER_NOT_KEYFILE error code, 5
 ER_NOT_RIGHT_NOW error code, 146
 ER_NOT_SUPPORTED_AUTH_MODE error code, 20
 ER_NOT_SUPPORTED_YET error code, 19
 ER_NOT_VALID_PASSWORD error code, 55
 ER_NO_ACCESS_TO_NATIVE_FCT error code, 80
 ER_NO_BINARY_LOGGING error code, 28
 ER_NO_BINLOG_ERROR error code, 36
 ER_NO_CSV_NO_LOG_TABLES error code, 147
 ER_NO_DB_ERROR error code, 6
 ER_NO_DEFAULT error code, 18
 ER_NO_DEFAULT_FOR_FIELD error code, 27
 ER_NO_DEFAULT_FOR_VIEW_FIELD error code, 30
 ER_NO_ERROR_LOG_PARSER_CONFIGURED error code, 380
 ER_NO_FORMAT_DESCRIPTION_EVENT_BEFORE_BINLOG_STATEMENT error code, 41
 ER_NO_FT_MATERIALIZED_SUBQUERY error code, 61
 ER_NO_PARTITION_FOR_GIVEN_VALUE error code, 37
 ER_NO_PARTITION_FOR_GIVEN_VALUE_SILENT error code, 40
 ER_NO_PARTS_ERROR error code, 35
 ER_NO_PATH_FOR_SHARED_LIBRARY error code, 345
 ER_NO_PERMISSION_TO_CREATE_USER error code, 17
 ER_NO_REFERENCED_ROW error code, 17
 ER_NO_REFERENCED_ROW_2 error code, 32
 ER_NO_SECURE_TRANSPORTS_CONFIGURED error code, 72
 ER_NO_SESSION_TEMP error code, 104
 ER_NO_SUCH_DB error code, 76
 ER_NO_SUCH_INDEX error code, 8
 ER_NO_SUCH_TABLE error code, 13
 ER_NO_SUCH_THREAD error code, 9
 ER_NO_SUCH_USER error code, 32
 ER_NO_SUPER_WITHOUT_USER_PLUGIN error code, 159
 ER_NO_SYSTEM_SCHEMA_ACCESS error code, 79
 ER_NO_SYSTEM_TABLESPACE_ACCESS error code, 79
 ER_NO_SYSTEM_TABLE_ACCESS error code, 80
 ER_NO_SYSTEM_TABLE_ACCESS_FOR_DICTIONARY_TABLES error code, 80
 ER_NO_SYSTEM_TABLE_ACCESS_FOR_SYSTEM_TABLE error code, 80
 ER_NO_SYSTEM_TABLE_ACCESS_FOR_TABLE error code, 80
 ER_NO_SYSTEM_VIEW_ACCESS error code, 84
 ER_NO_TABLES_USED error code, 10
 ER_NO_THD_NO_UUID error code, 141
 ER_NO_TRIGGERS_ON_SYSTEM_SCHEMA error code, 33
 ER_NO_UNIQUE_LOGFILE error code, 10
 ER_NPIPE_CANT_CREATE error code, 190
 ER_NPIPE_FAILED_TO_INIT_SECURITY_DESCRIPTOR error code, 164
 ER_NPIPE_FAILED_TO_SET_SECURITY_DESCRIPTOR error code, 164
 ER_NPIPE_PIPE_ALREADY_IN_USE error code, 164
 ER_NULL_CANT_BE_PERSISTED_FOR_READONLY error code, 127
 ER_NULL_COLUMN_IN_INDEX error code, 11
 ER_NULL_IN_VALUES_LESS_THAN error code, 39
 ER_NUMERIC_JSON_VALUE_OUT_OF_RANGE error code, 72
 ER_OLD_TEMPORALS_DEADLOCKS_STILL_ALIVE error code, 417
 ER_OBSOLETE_FILE_PRIVILEGE_FOR_REPLICATION_CHECK error code, 368
 ER_OBSOLETE_REQUIRE_ROW_FORMAT_VIOLATION error code, 369
 ER_OLD_FILE_FORMAT error code, 32
 ER_OLD_KEYFILE error code, 5
 ER_OLD_TEMPORALS_UPGRADED error code, 59
 ER_ONLY_FD_AND_RBR_EVENTS_ALLOWED_IN_BINLOG_STATEMENT error code, 49
 ER_ONLY_IMPLEMENTED_FOR_SRID_0_AND_4326 error code, 89
 ER_ONLY_INTEGERS_ALLOWED error code, 39
 ER_ONLY_ON_RANGE_LIST_PARTITION error code, 36
 ER_OOM error code, 146
 ER_OOM_SAVE_GTIDS error code, 340
 ER_OPEN_AS_READONLY error code, 5
 ER_OPEN_ROLE_TABLES error code, 78
 ER_OPERAND_COLUMNS error code, 19
 ER_OPERATION_NOT_ALLOWED_ON_GR_SECONDARY error code, 117
 ER_OPERATION_NOT_ALLOWED_WHILE_PRIMARY_CHANGING error code, 121

ER_OPTION_PREVENTS_STATEMENT error code, 22
 ER_OPT_WRONG_TREE error code, 137
 ER_OUTOFMEMORY error code, 5
 ER_OUT_OF_RESOURCES error code, 5
 ER_OUT_OF_SORTMEMORY error code, 5
 ER_PAGE_TRACKING_CANNOT_PURGE error code, 98
 ER_PAGE_TRACKING_NOT_STARTED error code, 98
 ER_PAGE_TRACKING_RANGE_NOT_TRACKED error code, 98
 ER_PARSER_TRACE error code, 137
 ER_PARSE_ERROR error code, 7
 ER_PARSE_ERROR_IN_DIGEST_FN error code, 88
 ER_PARSING_VIEW error code, 141
 ER_PARTIAL_REVOKES_EXIST error code, 105
 ER_PARTIAL_REVOKE_AND_DB_GRANT_BOTH_EXISTS error code, 105
 ER_PARTITIONS_MUST_BE_DEFINED_ERROR error code, 34
 ER_PARTITION_CLAUSE_ON_NONPARTITIONED error code, 50
 ER_PARTITION_COLUMN_LIST_ERROR error code, 43
 ER_PARTITION_CONST_DOMAIN_ERROR error code, 38
 ER_PARTITION_ENTRY_ERROR error code, 35
 ER_PARTITION_EXCHANGE_DIFFERENT_OPTION error code, 49
 ER_PARTITION_EXCHANGE_FOREIGN_KEY error code, 50
 ER_PARTITION_EXCHANGE_PART_TABLE error code, 49
 ER_PARTITION_EXCHANGE_TEMP_TABLE error code, 49
 ER_PARTITION_FIELDS_TOO_LONG error code, 44
 ER_PARTITION_FUNCTION_FAILURE error code, 36
 ER_PARTITION_FUNCTION_IS_NOT_ALLOWED error code, 38
 ER_PARTITION_FUNC_NOT_ALLOWED_ERROR error code, 34
 ER_PARTITION_HANDLER_ADMIN_MSG error code, 202
 ER_PARTITION_INSTEAD_OF_SUBPARTITION error code, 49
 ER_PARTITION_MAXVALUE_ERROR error code, 34
 ER_PARTITION_MERGE_ERROR error code, 39
 ER_PARTITION_MGMT_ON_NONPARTITIONED error code, 35
 ER_PARTITION_MOVE_CREATED_DUPLICATE_ROW_PLEASE_FIX error code, 190
 ER_PARTITION_NAME error code, 42
 ER_PARTITION_NOT_DEFINED_ERROR error code, 35
 ER_PARTITION_NO_TEMPORARY error code, 38
 ER_PARTITION_PREFIX_KEY_NOT_SUPPORTED error code, 135
 ER_PARTITION_REQUIRES_VALUES_ERROR error code, 34
 ER_PARTITION_WRONG_NO_PART_ERROR error code, 34
 ER_PARTITION_WRONG_NO_SUBPART_ERROR error code, 34
 ER_PARTITION_WRONG_VALUES_ERROR error code, 34
 ER_PART_EXPR_TOO_LONG error code, 84
 ER_PASSWORD_ANONYMOUS_USER error code, 12
 ER_PASSWORD_CANNOT_BE_RETAINED_ON_PLUGIN_CHANGE error code, 105
 ER_PASSWORD_EXPIRATION_NOT_SUPPORTED_BY_AUTH_METHOD error code, 88
 ER_PASSWORD_EXPIRE_ANONYMOUS_USER error code, 61
 ER_PASSWORD_FORMAT error code, 56
 ER_PASSWORD_NOT_ALLOWED error code, 12
 ER_PASSWORD_NO_MATCH error code, 12
 ER_PATH_IN_DATADIR error code, 85
 ER_PATH_LENGTH error code, 45
 ER_PERFORMANCE_SCHEMA_VERSION_CHANGE error code, 414
 ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP error code, 193
 ER_PERFSCHEMA_COMPONENTS_INFRASTRUCTURE_SHUTDOWN error code, 193
 ER_PERFSCHEMA_INIT_FAILED error code, 148
 ER_PERFSCHEMA_TABLES_INIT_FAILED error code, 194
 ER_PERSISTED_VARIABLES_DECRYPTION_FAILED error code, 396
 ER_PERSISTED_VARIABLES_ENCRYPTION_FAILED error code, 396
 ER_PERSISTED_VARIABLES_KEYRING_SUPPORT_REQUIRED error code, 396
 ER_PERSISTED_VARIABLES_LACK_KEYRING_SUPPORT error code, 396
 ER_PERSISTED_VARIABLES_MASTER_KEY_CANNOT_BE_GENERATED error code, 396
 ER_PERSISTED_VARIABLES_MASTER_KEY_NOT_FOUND error code, 396
 ER_PERSISTENT_PRIVILEGES_BOOTSTRAP error code, 193
 ER_PERSIST_ONLY_ACCESS_DENIED_ERROR error code, 85
 ER_PERSIST_OPTION_HOST_TRUNCATED error code, 362
 ER_PERSIST_OPTION_STATUS error code, 218
 ER_PERSIST_OPTION_USER_TRUNCATED error code, 362

ER_PER_CHANNEL_RPL_FILTER_CONF_FOR_GRP_RPL_PLUGIN_LOAD_OPTIONS_IGNORED error code, 200
 ER_PFS_MALLOC_ARRAY_OOM error code, 201
 ER_PFS_MALLOC_ARRAY_OVERFLOW error code, 201
 ER_PFS_NOTIFICATION_FUNCTION_REGISTER_FAILED error code, 196
 ER_PID_FILEPATH_LOCATIONS_INACCESSIBLE error code, 345
 ER_PID_FILE_PRIV_DIRECTORY_INSECURE error code, 258
 ER_PK_INDEX_CANT_BE_INVISIBLE error code, 77
 ER_PLUGGABLE_PROTOCOL_COMMAND_NOT_SUPPORTED error code, 70
 ER_PLUGINS_SHUTDOWN_END error code, 417
 ER_PLUGINS_SHUTDOWN_START error code, 417
 ER_PLUGIN_BAD_OPTIONS error code, 180
 ER_PLUGIN_CANNOT_BE_UNINSTALLED error code, 60
 ER_PLUGIN_CANT_LOAD error code, 179
 ER_PLUGIN_CANT_OPEN_PLUGIN_TABLE error code, 179
 ER_PLUGIN_CANT_SET_PERSISTENT_OPTIONS error code, 180
 ER_PLUGIN_COMMON_FAILED_TO_OPEN_FILTER_TABLE error code, 217
 ER_PLUGIN_COMMON_FAILED_TO_OPEN_TABLE error code, 217
 ER_PLUGIN_DELETE_BUILTIN error code, 41
 ER_PLUGIN_DID_NOT_DEINITIALIZE_THREADS error code, 169
 ER_PLUGIN_DISABLED error code, 180
 ER_PLUGIN_EXCEPTION_OPERATION_FAILED error code, 408
 ER_PLUGIN_FAILED_DEINITIALIZATION error code, 179
 ER_PLUGIN_FAILED_TO_OPEN_TABLE error code, 343
 ER_PLUGIN_FAILED_TO_OPEN_TABLES error code, 343
 ER_PLUGIN_FORCING_SHUTDOWN error code, 179
 ER_PLUGIN_HAS_CONFLICTING_SYSTEM_VARIABLES error code, 180
 ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_DEINITIALIZATION error code, 179
 ER_PLUGIN_HAS_NONZERO_REFCOUNT_AFTER_SHUTDOWN error code, 179
 ER_PLUGIN_INIT_FAILED error code, 151
 ER_PLUGIN_INSTALL_ERROR error code, 349
 ER_PLUGIN_INVALID_TABLE_DEFINITION error code, 389
 ER_PLUGIN_IS_NOT_LOADED error code, 37
 ER_PLUGIN_IS_PERMANENT error code, 47
 ER_PLUGIN_LOAD_OPTIONS_IGNORED error code, 368
 ER_PLUGIN_LOAD_PARAMETER_TOO_LONG error code, 179
 ER_PLUGIN_NOT_EARLY error code, 101
 ER_PLUGIN_NOT_EARLY_DUP error code, 362
 ER_PLUGIN_NO_INSTALL error code, 48
 ER_PLUGIN_NO_INSTALL_DUP error code, 362
 ER_PLUGIN_NO_UNINSTALL error code, 48
 ER_PLUGIN_OOM error code, 180
 ER_PLUGIN_PARSING_OPTIONS_FAILED error code, 180
 ER_PLUGIN_REGISTRATION_DONE error code, 118
 ER_PLUGIN_REGISTRATION_FAILED error code, 179
 ER_PLUGIN_REQUIRES_REGISTRATION error code, 118
 ER_PLUGIN_SHUTTING_DOWN_PLUGIN error code, 179
 ER_PLUGIN_UNINSTALL_ERROR error code, 349
 ER_PLUGIN_UNKNOWN_VARIABLE_TYPE error code, 179
 ER_PLUGIN_VARIABLE_MISSING_NAME error code, 180
 ER_PLUGIN_VARIABLE_NOT_ALLOCATED_THREAD_LOCAL error code, 180
 ER_PLUGIN_VARIABLE_SET_READ_ONLY error code, 179
 ER_POINTLESS_WITHOUT_SLOWLOG error code, 142
 ER_POLYGON_TOO_LARGE error code, 92
 ER_PREPARE_FOR_PRIMARY_ENGINE error code, 390
 ER_PREPARE_FOR_SECONDARY_ENGINE error code, 358
 ER_PREVENTS_VARIABLE_WITHOUT_RBR error code, 67
 ER_PRIMARY_CANT_HAVE_NULL error code, 15
 ER_PRIVILEGE_DEREGISTRATION error code, 412
 ER_PRIVILEGE_REGISTRATION error code, 412
 ER_PRIVILEGE_SYSTEM_INIT_FAILED error code, 194
 ER_PROCACCESS_DENIED_ERROR error code, 27
 ER_PROC_AUTO_GRANT_FAIL error code, 29
 ER_PROC_AUTO_REVOKE_FAIL error code, 29
 ER_PROTOCOL_COMPRESSION_RESET_LOG error code, 126
 ER_PS_MANY_PARAM error code, 28
 ER_PS_NO_RECURSION error code, 31
 ER_QUALIFY_WITHOUT_WINDOW_FUNCTION error code, 129
 ER_QUERY_INTERRUPTED error code, 24
 ER_QUERY_ON_FOREIGN_DATA_SOURCE error code, 31
 ER_QUERY_TIMEOUT error code, 62
 ER_RANGE_NOT_INCREASING_ERROR error code, 34

ER_READING_TABLE_FAILED error code, 151
ER_READY error code, 8
ER_READ_LOG_EVENT_FAILED error code, 199
ER_READ_ONLY_MODE error code, 56
ER_READ_ONLY_TRANSACTION error code, 17
ER_REALLY_RUN_AS_ROOT error code, 145
ER_RECORD_FILE_FULL error code, 11
ER_RECOVERING_TABLE error code, 181
ER_REDUCED_DBLWR_FILE_CORRUPTED error code, 413
ER_REDUCED_DBLWR_PAGE_FOUND error code, 413
ER_REFERENCED_TRG_DOES_NOT_EXIST error code, 61
ER_REGEX_BAD_ESCAPE_SEQUENCE error code, 89
ER_REGEX_BAD_INTERVAL error code, 89
ER_REGEX_BUFFER_OVERFLOW error code, 89
ER_REGEX_ERROR error code, 13
ER_REGEX_ILLEGAL_ARGUMENT error code, 89
ER_REGEX_INDEX_OUTOFBOUNDS_ERROR error code, 89
ER_REGEX_INTERNAL_ERROR error code, 89
ER_REGEX_INVALID_BACK_REF error code, 89
ER_REGEX_INVALID_CAPTURE_GROUP_NAME error code, 104
ER_REGEX_INVALID_FLAG error code, 105
ER_REGEX_INVALID_RANGE error code, 89
ER_REGEX_LOOK_BEHIND_LIMIT error code, 89
ER_REGEX_MAX_LT_MIN error code, 89
ER_REGEX_MISMATCHED_PAREN error code, 89
ER_REGEX_MISSING_CLOSE_BRACKET error code, 89
ER_REGEX_MISSING_FILE error code, 120
ER_REGEX_MISSING_ICU_DATADIR error code, 395
ER_REGEX_MISSING_RESOURCE error code, 120
ER_REGEX_PATTERN_TOO_BIG error code, 90
ER_REGEX_RULE_SYNTAX error code, 89
ER_REGEX_STACK_OVERFLOW error code, 90
ER_REGEX_TIME_OUT error code, 90
ER_REGEX_UNIMPLEMENTED error code, 89
ER_REGEX_NUMBER_TOO_BIG error code, 114
ER_RELAY_LOG_FAIL error code, 27
ER_RELAY_LOG_INIT error code, 28
ER_RELAY_LOG_SPACE_LIMIT_DISABLED error code, 346
ER_RELOAD_KEYRING_FAILURE error code, 116
ER_REMOVED_SPACES error code, 33
ER_RENAMED_NAME error code, 42
ER_RENAME_ROLE error code, 78
ER_REORG_HASH_ONLY_ON_SAME_NO error code, 36
ER_REORG_NO_PARAM_ERROR error code, 36
ER_REORG_OUTSIDE_RANGE error code, 36
ER_REORG_PARTITION_NOT_EXIST error code, 36
ER_REPLACE_INACCESSIBLE_ROWS error code, 64
ER_REPLICATION_INCOMPATIBLE_TABLE_WITH_GIPK error code, 406
ER_REPLICA_AM_INIT_REPOSITORY error code, 59
ER_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP error code, 382
ER_REPLICA_ANON_TO_GTID_IS_LOCAL_OR_UUID_AND_GTID error code, 382
ER_REPLICA_CANT_CREATE_CONVERSION error code, 45
ER_REPLICA_CANT_USE_TEMPDIR error code, 176
ER_REPLICA_CHANGE_SOURCE_TO_EXECUTED error code, 176
ER_REPLICA_CHANNEL_DOES_NOT_EXIST error code, 65
ER_REPLICA_CHANNEL_IO_THREAD_MUST_STOP error code, 62
ER_REPLICA_CHANNEL_MUST_STOP error code, 66
ER_REPLICA_CHANNEL_NAME_INVALID_OR_TOO_LONG error code, 66
ER_REPLICA_CHANNEL_NOT_RUNNING error code, 66
ER_REPLICA_CHANNEL_OPERATION_NOT_ALLOWED error code, 71
ER_REPLICA_CHANNEL_SQL_SKIP_COUNTER error code, 66
ER_REPLICA_CHANNEL_SQL_THREAD_MUST_STOP error code, 66
ER_REPLICA_CHANNEL_WAS_NOT_RUNNING error code, 66
ER_REPLICA_CHANNEL_WAS_RUNNING error code, 66
ER_REPLICA_CM_INIT_REPOSITORY error code, 59
ER_REPLICA_CONFIGURATION error code, 53
ER_REPLICA_CORRUPT_EVENT error code, 41
ER_REPLICA_CREATE_EVENT_FAILURE error code, 340
ER_REPLICA_FATAL_ERROR error code, 340
ER_REPLICA_HAS_MORE_GTIDS_THAN_SOURCE error code, 60
ER_REPLICA_HEARTBEAT_FAILURE error code, 340
ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE error code, 42
ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MAX error code, 47
ER_REPLICA_HEARTBEAT_VALUE_OUT_OF_RANGE_MIN error code, 47
ER_REPLICA_IGNORED_SSL_PARAMS error code, 21
ER_REPLICA_IGNORED_TABLE error code, 19
ER_REPLICA_IGNORE_SERVER_IDS error code, 43
ER_REPLICA_INCIDENT error code, 340
ER_REPLICA_KILLED_AFTER_RECONNECT error code, 200

ER_REPLICA_MAX_CHANNELS_EXCEEDED error code, 66	ER_RESOURCE_GROUP_BIND_FAILED error code, 87
ER_REPLICA_MULTIPLE_CHANNELS_CMD error code, 66	ER_RESOURCE_GROUP_BUSY error code, 87
ER_REPLICA_NEW_CHANNEL_WRONG_REPOSITORY error code, 66	ER_RESOURCE_GROUP_DISABLED error code, 87
ER_REPLICA_NOT_RUNNING error code, 16	ER_RESOURCE_GROUP_EXISTS error code, 86
ER_REPLICA_NOT_STARTED_ON_SOME_CHANNELS error code, 200	ER_RESOURCE_GROUP_IS_DISABLED error code, 196
ER_REPLICA_POSSIBLY_DIVERGED_AFTER_DDL error code, 91	ER_RESOURCE_GROUP_METADATA_UPDATE_SKIPPED error code, 195
ER_REPLICA_RECONNECT_FAILED error code, 199	ER_RESOURCE_GROUP_NOT_EXISTS error code, 86
ER_REPLICA_RELAY_LOG_PURGE_FAILED error code, 194	ER_RESOURCE_GROUP_POST_INIT_FAILED error code, 193
ER_REPLICA_RELAY_LOG_READ_FAILURE error code, 341	ER_RESOURCE_GROUP_SUBSYSTEM_INIT_FAILED error code, 193
ER_REPLICA_RELAY_LOG_TRUNCATE_INFO error code, 194	ER_RESOURCE_GROUP_VALIDATION_FAILED error code, 195
ER_REPLICA_RELAY_LOG_WRITE_FAILURE error code, 341	ER_RESTART_RECEIVED_INFO error code, 204
ER_REPLICA_SILENT_RETRY_TRANSACTION error code, 54	ER_RESTART_SERVER_FAILED error code, 90
ER_REPLICA_SOURCE_COM_FAILURE error code, 340	ER_RESULT_SIZE_LIMIT_EXCEEDED error code, 134
ER_REPLICA_SQL_THREAD_MUST_STOP error code, 61	ER_RES_GRP_FAILED_DETERMINE_CPU_COUNT error code, 197
ER_REPLICA_SQL_THREAD_STOPPED_AFTER_GTIDS error code, 163	ER_RES_GRP_FAILED_TO_DETERMINE_NICE_CAPABILITY error code, 196
ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS error code, 163	ER_RES_GRP_FAILED_TO_GET_THREAD_HANDLE error code, 196
ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS_ERROR_CODE error code, 163	ER_RES_GRP_FEATURE_NOT_AVAILABLE error code, 197
ER_REPLICA_SQL_THREAD_STOPPED_BEFORE_GTIDS_ERROR_CODE error code, 163	ER_RES_GRP_GET_THREAD_PRIO_NOT_SUPPORTED error code, 196
ER_REPLICA_SQL_THREAD_STOPPED_GAP_TRX_PROCESSED error code, 163	ER_RES_GRP_INVALID_THREAD_PRIORITY error code, 197
ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_CONDITION_OK error code, 163	ER_RES_GRP_INVALID_VCPU_ID error code, 203
ER_REPLICA_SQL_THREAD_STOPPED_UNTIL_POSITION_OK error code, 163	ER_RES_GRP_INVALID_VCPU_RANGE error code, 203
ER_REPLICA_THREAD error code, 16	ER_RES_GRP_SET_THREAD_PRIORITY_FAILED error code, 196
ER_REPLICA_WORKER_STOPPED_PREVIOUS_THD_ERROR error code, 62	ER_RES_GRP_SET_THR_AFFINITY_FAILED error code, 196
ER_REQUIRES_PRIMARY_KEY error code, 15	ER_RES_GRP_SET_THR_AFFINITY_TO_CPUS_FAILED error code, 196
ER_REQUIRE_ROW_FORMAT_INVALID_VALUE error code, 108	ER_RES_GRP_SOLARIS_PROCESSOR_AFFINITY_FAILED error code, 197
ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATED FROM WIDE error code, 126	ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_CPUID_FAILED error code, 197
ER_REQUIRE_TABLE_PRIMARY_KEY_CHECK_GENERATED FROM WIDE error code, 408	ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_THREAD_FAILED error code, 197
ER_RESERVED_SYNTAX error code, 28	ER_RES_GRP_THD_UNBIND_FROM_CPU_FAILED error code, 196
ER_RESERVED_TABLESPACE_NAME error code, 91	ER_REPAIR_IN_REPO error code, 196
ER_RESET_SOURCE_TO_VALUE_OUT_OF_RANGE error code, 80	ER_RETRYING_REPAIR_WITHOUT_QUICK error code, 180
ER_RESIGNAL_WITHOUT_ACTIVE_HANDLER error code, 43	ER_RETRYING_REPAIR_WITH_KEYCACHE error code, 180
	ER_REVOKE_GRANTS error code, 21
	ER_REWRITER_LOAD_FAILED error code, 218
	ER_REWRITER_OOM error code, 218

ER_REWRITER_QUERY_ERROR_MSG error code, 216
 ER_REWRITER_QUERY_FAILED error code, 216
 ER_REWRITER_READ_FAILED error code, 218
 ER_REWRITER_TABLE_MALFORMED_ERROR error code, 218
 ER_ROLE_GRANTED_TO_ITSELF error code, 115
 ER_ROLE_NOT_GRANTED error code, 78
 ER_ROW_DATA_TOO_BIG_TO_WRITE_IN_BINLOG error code, 199
 ER_ROW_DOES_NOT_MATCH_GIVEN_PARTITION_SET error code, 50
 ER_ROW_DOES_NOT_MATCH_PARTITION error code, 49
 ER_ROW_IN_WRONG_PARTITION error code, 58
 ER_ROW_IN_WRONG_PARTITION_PLEASE_REPAIR error code, 153
 ER_ROW_IS_REFERENCED error code, 18
 ER_ROW_IS_REFERENCED_2 error code, 32
 ER_ROW_SINGLE_PARTITION_FIELD_ERROR error code, 44
 ER_RPL_AM_INIT_INFO_MSG error code, 202
 ER_RPL_ASYNC_CHANNEL_CANT_CONNECT error code, 381
 ER_RPL_ASYNC_CHANNEL_CANT_CONNECT_NO_QUORUM error code, 381
 ER_RPL_ASYNC_CHANNEL_STOPPED_QUORUM_LOST error code, 381
 ER_RPL_ASYNC_CHECK_CONNECTION_ERROR error code, 423
 ER_RPL_ASYNC_GET_GROUP_MEMBERSHIP_DETAILS_ERROR error code, 423
 ER_RPL_ASYNC_MANAGED_NAME_ADDED error code, 382
 ER_RPL_ASYNC_MANAGED_NAME_REMOVED error code, 382
 ER_RPL_ASYNC_MONITOR_IO_THD_FETCH_GROUP_MEMBERSHIP_ERROR error code, 423
 ER_RPL_ASYNC_NEXT_FAILOVER_CHANNEL_SELECTED error code, 409
 ER_RPL_ASYNC_READ_FAILOVER_TABLE error code, 382
 ER_RPL_ASYNC_RECONNECT_AUTO_POSITION_OFF error code, 112
 ER_RPL_ASYNC_RECONNECT_FAIL_NO_SOURCE error code, 380
 ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF error code, 112
 ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF_CHANNEL error code, 383
 ER_RPL_ASYNC_REPLICA_IO_THD_FETCH_GROUP_MEMBERSHIP_ERROR error code, 423
 ER_RPL_ASYNC_SENDER_ADDED error code, 381
 ER_RPL_ASYNC_SENDER_REMOVED error code, 381
 ER_RPL_BINLOG_FILTERS_OOM error code, 144
 ER_RPL_BINLOG_RELAY_DELEGATES_INIT_FAILED error code, 151
 ER_RPL_BINLOG_SKIPPING_REMAINING_HEARTBEAT_INFO error code, 169
 ER_RPL_BINLOG_SOURCE_SENDS_HEARTBEAT error code, 169
 ER_RPL_BINLOG_SOURCE_USES_CHECKSUM_AND_REPLICATION error code, 169
 ER_RPL_BINLOG_STARTING_DUMP error code, 169
 ER_RPL_BINLOG_STORAGE_DELEGATES_INIT_FAILED error code, 151
 ER_RPL_BINLOG_TRANSMIT_DELEGATES_INIT_FAILED error code, 151
 ER_RPL_CANNOT_OPEN_RELAY_LOG error code, 393
 ER_RPL_CANT_ADD_DO_TABLE error code, 147
 ER_RPL_CANT_ADD_IGNORE_TABLE error code, 147
 ER_RPL_CANT_CREATE_REPLICA_THREAD error code, 172
 ER_RPL_CANT_FIND_FOLLOWUP_FILE error code, 174
 ER_RPL_CANT_HAVE_SAME_BASENAME error code, 191
 ER_RPL_CANT_INITIALIZE_GTID_SETS_IN_AM_INIT_INFO error code, 177
 ER_RPL_CANT_MAKE_PATHS error code, 148
 ER_RPL_CANT_OPEN_INFO_TABLE error code, 164
 ER_RPL_CANT_OPEN_LOG_IN_AM_INIT_INFO error code, 177
 ER_RPL_CANT_SCAN_INFO_TABLE error code, 165
 ER_RPL_CANT_STOP_REPLICA_WHILE_LOCKED_BACKUP error code, 102
 ER_RPL_CHANNELS_REQUIRE_NON_ZERO_SERVER_ID error code, 165
 ER_RPL_CORRUPTED_INFO_TABLE error code, 165
 ER_RPL_CORRUPTED_KEYS_IN_INFO_TABLE error code, 165
 ER_RPL_ENCRYPTION_CANNOT_ROTATE_BINLOG_MASTER_KEY error code, 98
 ER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT error code, 97
 ER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY error code, 96
 ER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY error code, 97
 ER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY error code, 97
 ER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS error code, 96
 ER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY error code, 97
 ER_RPL_ENCRYPTION_HEADER_ERROR error code, 96

ER_RPL_ENCRYPTION_KEYRING_INVALID_KEY error code, 96	ER_RPL_GTID_UNSAFE_STMT_CREATE_SELECT error code, 339
ER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED error code, 97	ER_RPL_GTID_UNSAFE_STMT_ON_NON_TRANS_TABLE error code, 339
ER_RPL_ENCRYPTION_KEY_NOT_FOUND error code, 96	ER_RPL_INCOMPATIBLE_DECIMAL_IN_RBR error code, 168
ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED error code, 97	ER_RPL_INCONSISTENT_SEQUENCE_NO_IN_TRX error code, 165
ER_RPL_ENCRYPTION_UNABLE_TO_CHANGE_OPTIONS error code, 97	ER_RPL_INCONSISTENT_TIMESTAMPS_IN_TRX error code, 165
ER_RPL_ERROR_CREATING_APPLIER_METADATA error code, 165	ER_RPL_INCREMENTING_MEMBER_ACTION_VERSION error code, 391
ER_RPL_ERROR_CREATING_CONNECTION_METADATA error code, 165	ER_RPL_INFINITY_DENIED error code, 150
ER_RPL_ERROR_LOOKING_FOR_LOG error code, 174	ER_RPL_INFINITY_IGNORED error code, 150
ER_RPL_ERROR_READING_REPLICA_WORKER_CONFIGURATION error code, 178	ER_RPL_INFO_DATA_TOO_LONG error code, 50
ER_RPL_ERROR_READING_SOURCE_CONFIGURATION error code, 179	ER_RPL_IO_THREAD_KILLED error code, 199
ER_RPL_ERROR_WRITING_RELAY_LOG_CONFIGURATION error code, 177	ER_RPL_KILL_OLD_DUMP_THREAD_ENCOUNTERED error code, 428
ER_RPL_ERROR_WRITING_SOURCE_CONFIGURATION error code, 179	ER_RPL_LOG_ENTRY_EXCEEDS_REPLICA_MAX_ALLOWED error code, 174
ER_RPL_FAILED_TO_CREATE_CACHE_FOR_INFO_FILE error code, 166	ER_RPL_LOG_NOT_FOUND_WHILE_COUNTING_RELAY_LOG error code, 176
ER_RPL_FAILED_TO_CREATE_NEW_INFO_FILE error code, 166	ER_RPL_MTA_ALLOW_COMMIT_OUT_OF_ORDER error code, 429
ER_RPL_FAILED_TO_DELETE_FROM_REPLICA_WORKER_REPOSITORY error code, 165	ER_RPL_MTA_AUTOMATIC_RECOVERY_FAILED error code, 172
ER_RPL_FAILED_TO_OPEN_INFO_FILE error code, 166	ER_RPL_MTA_CHECKPOINT_PERIOD_DIFFERS_FROM_COUNT error code, 174
ER_RPL_FAILED_TO_OPEN_RELAY_LOG error code, 178	ER_RPL_MTA_GROUP_RECOVERY_APPLIER_METADATA_FAILED error code, 174
ER_RPL_FAILED_TO_RESET_STATE_IN_REPLICA_INFO_REPOSITORY error code, 165	ER_RPL_MTA_RECOVERY_CANT_OPEN_RELAY_LOG error code, 172
ER_RPL_FAILED_TO_STAT_LOG_IN_INDEX error code, 176	ER_RPL_MTA_RECOVERY_COMPLETE error code, 173
ER_RPL_FILTERS_NOT_ATTACHED_TO_CHANNEL error code, 200	ER_RPL_MTA_RECOVERY_FAILED_TO_START_COORDINATOR error code, 172
ER_RPL_FILTER_ADD_WILD_DO_TABLE_FAILED error code, 194	ER_RPL_MTA_RECOVERY_STARTING_COORDINATOR error code, 171
ER_RPL_FILTER_ADD_WILD_IGNORE_TABLE_FAILED error code, 194	ER_RPL_MTA_RECOVERY_SUCCESSFUL error code, 172
ER_RPL_GTID_LOG_EVENT_IN_STREAM error code, 167	ER_RPL_MTA_REPLICA_COORDINATOR_HAS_WAITED error code, 178
ER_RPL_GTID_MEMORY_FINALLY_AVAILABLE error code, 166	ER_RPL_MTA_STATISTICS error code, 173
ER_RPL_GTID_MODE_REQUIRES_ENFORCE_GTID_CONSISTENCY error code, 191	ER_RPL_MULTISOURCE_REQUIRES_TABLE_TYPE_REPOSITORY error code, 166
ER_RPL_GTID_TABLE_CANNOT_OPEN error code, 138	ER_RPL_OPEN_INDEX_FILE_FAILED error code, 177
ER_RPL_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION error code, 349	ER_RPL_PLUGIN_FUNCTION_FAILED error code, 151
	ER_RPL_RECOVERY_ERROR error code, 171
	ER_RPL_RECOVERY_ERROR_READ_RELAY_LOG error code, 171

ER_RPL_RECOVERY_FILE_SOURCE_POS_INFO error code, 171	ER_RPL_REPLICA_ERROR_RETRYING error code, 173
ER_RPL_RECOVERY_IO_ERROR_READING_RELAY_LOG error code, 171	ER_RPL_REPLICA_ERROR_RUNNING_QUERY error code, 175
ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SOURCE error code, 171	ER_RPL_REPLICA_FAILED_TO_CREATE_CHANNEL_FROM_CON nection error code, 166
ER_RPL_RECOVERY_REPLICATE_SAME_SERVER_ID error code, 171	ER_RPL_REPLICA_FAILED_TO_CREATE_OR_RECOVER_INFO_R eposition error code, 170
ER_RPL_RECOVERY_SKIPPED_GROUP_REPLICATION error code, 171	ER_RPL_REPLICA_FAILED_TO_INIT_A_CONNECTION_METADATA error code, 166
ER_RPL_RELAY_LOG_INDEX_NEEDS_FILE_NOT_DIRECTO RY error code, 177	ER_RPL_REPLICA_FAILED_TO_INIT_CONNECTION_METADATA_ error code, 166
ER_RPL_RELAY_LOG_NEEDS_FILE_NOT_DIRECTORY error code, 177	ER_RPL_REPLICA_FAILED_TO_INIT_PARTITIONS_HASH error code, 175
ER_RPL_RELAY_LOG_RECOVERY_GTID_ONLY error code, 395	ER_RPL_REPLICA_FILTER_CREATE_FAILED error code, 194
ER_RPL_RELAY_LOG_RECOVERY_INFO_AFTER_CLONING error code, 370	ER_RPL_REPLICA_FORCING_TO_RECONNECT_IO_THREAD error code, 173
ER_RPL_REPLICA_ADDITIONAL_ERROR_INFO_FROM_ error code, 175	ER_RPL_REPLICA_GENERIC_MESSAGE error code, 165
ER_RPL_REPLICA_AUTO_POSITION_IS_1_AND_GTID_M ODES error code, 171	ER_RPL_REPLICA_GLOBAL_FILTERS_COPY_FAILED error code, 194
ER_RPL_REPLICA_CANT_FLUSH_CONNECTION_META DATA error code, 172	ER_RPL_REPLICA_INCORRECT_CHANNEL error code, 190
ER_RPL_REPLICA_CANT_INITIALIZE_REPLICA_WORKE R error code, 174	ER_RPL_REPLICA_INSECURE_CHANGE_SOURCE error code, 190
ER_RPL_REPLICA_CANT_INIT_RELAY_LOG_POSITION error code, 173	ER_RPL_REPLICA_IO_THREAD_ABORTED_WAITING_FOR_REL AY error code, 174
ER_RPL_REPLICA_CANT_START_REPLICA_FOR_CHANNE L error code, 171	ER_RPL_REPLICA_IO_THREAD_CANT_REGISTER_ON_SOURCE error code, 173
ER_RPL_REPLICA_CANT_STOP_REPLICA_FOR_CHANNE L error code, 171	ER_RPL_REPLICA_IO_THREAD_DETECTED_UNEXPECTED_EVE NT error code, 176
ER_RPL_REPLICA_CANT_USE_CHARSET error code, 176	ER_RPL_REPLICA_IO_THREAD_EXITING error code, 174
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_REPLICA FROM error code, 176	ER_RPL_REPLICA_IO_THREAD_KILLED error code, 173
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_ST ARTED error code, 409	ER_RPL_REPLICA_IO_THREAD_STOP_CMD_EXEC_TIMEOUT error code, 339
ER_RPL_REPLICA_CONNECTED_TO_SOURCE_RPL_ST ARTED error code, 409	ER_RPL_REPLICA_IO_THREAD_WAS_KILLED error code, 172
ER_RPL_REPLICA_COULD_NOT_CREATE_CHANNEL_LI ST error code, 166	ER_RPL_REPLICA_MONITOR_IO_THREAD_EXITING error code, 381
ER_RPL_REPLICA_DUMP_THREAD_KILLED_BY_SOURC E error code, 173	ER_RPL_REPLICA_MONITOR_IO_THREAD_RECONNECT_CHAN NEL error code, 382
ER_RPL_REPLICA_ERROR_INFO_FROM_DA error code, 175	ER_RPL_REPLICA_NEW_C_M_NEEDS_REPOS_TYPE_OTHER_T YPE error code, 176
ER_RPL_REPLICA_ERROR_LOADING_USER_DEFINED_ EVENT error code, 175	ER_RPL_REPLICA_NEXT_LOG_IS_ACTIVE error code, 176
ER_RPL_REPLICA_ERROR_READING_FROM_SERVER error code, 173	ER_RPL_REPLICA_NEXT_LOG_IS_INACTIVE error code, 176
ER_RPL_REPLICA_ERROR_READING_RELAY_LOG_EV ENT error code, 176	ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_CONFIGUR ATION error code, 175
ER_RPL_REPLICA_ERROR_REQUESTING_BINLOG_DUM P error code, 174	ER_RPL_REPLICA_QUEUE_EVENT_FAILED_INVALID_NON_ROW ID error code, 368

ER_RPL_REPLICA_READ_INVALID_EVENT_FROM_SOURCE error code, 175	ER_RPL_UNEXPECTED_XA_ROLLBACK_IN_STREAM error code, 167
ER_RPL_REPLICA_REPORT_HOST_TOO_LONG error code, 172	ER_RPL_UNSUPPORTED_UNIGNORABLE_EVENT_IN_STREAM error code, 167
ER_RPL_REPLICA_REPORT_PASSWORD_TOO_LONG error code, 173	ER_RPL_WORKER_CANT_FIND_NEXT_RELAY_LOG error code, 178
ER_RPL_REPLICA_REPORT_USER_TOO_LONG error code, 173	ER_RPL_WORKER_CANT_READ_RELAY_LOG error code, 178
ER_RPL_REPLICA_RESET_FILTER_OPTIONS error code, 194	ER_RPL_WORKER_ID_IS error code, 165
ER_RPL_REPLICA_SECONDS_BEHIND_SOURCE_DUBIOUS error code, 172	ER_RPL_ZOMBIE_ENCOUNTERED error code, 138
ER_RPL_REPLICA_SKIP_COUNTER_EXECUTED error code, 175	ER_RUNNING_APPLIER_PREVENTS_SWITCH_GLOBAL_BINLOG error code, 93
ER_RPL_REPLICA_SOURCE_UUID_HAS_CHANGED_HOST error code, 409	ER_RUN_HOOK_ERROR error code, 67
ER_RPL_REPLICA_SOURCE_UUID_HAS_NOT_CHANGED error code, 409	ER_SAME_NAME_PARTITION error code, 36
ER_RPL_REPLICA_SOURCE_UUID_HOST_PORT_HAS_CHANGED error code, 409	ER_SOME_UNCHANGED_CONDITION_FIELD error code, 43
ER_RPL_REPLICA_SQL_THREAD_DETECTED_UNEXPECTED_SEQUENCE error code, 369	ER_SCHEDULER_KILLING error code, 140
ER_RPL_REPLICA_SQL_THREAD_EXITING error code, 175	ER_SCHEDULER_STARTED error code, 140
ER_RPL_REPLICA_SQL_THREAD_IO_ERROR_READING error code, 176	ER_SCHEDULER_STOPPED error code, 140
ER_RPL_REPLICA_SQL_THREAD_STARTING error code, 175	ER_SCHEDULER_STOPPING_FAILED_TO_CREATE_WORKER error code, 140
ER_RPL_REPLICA_SQL_THREAD_STARTING_WITH_PROBLEMS error code, 368	ER_SCHEDULER_STOPPING_FAILED_TO_GET_EVENT error code, 140
ER_RPL_REPLICA_SQL_THREAD_STOP_CMD_EXEC_TIMEOUT error code, 339	ER_SCHEDULER_WAITING error code, 140
ER_RPL_REPLICA_STOPPING_AS_SOURCE_OOM error code, 174	ER_SCHEMA_DIR_CREATE_FAILED error code, 88
ER_RPL_REPLICA_USES_CHECKSUM_AND_SOURCE_FILTER error code, 172	ER_SCHEMA_DIR_EXISTS error code, 88
ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED error code, 174	ER_SCHEMA_DIR_MISSING error code, 88
ER_RPL_REPLICA_WORKER_THREAD_CREATION_FAILED_SECONDARY error code, 175	ER_SCHEMA_DIR_UNKNOWN error code, 88
ER_RPL_REPO_HAS_GAPS error code, 139	ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED error code, 88
ER_RPL_REWRITEDB_EMPTY_FROM error code, 147	ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_TABLES error code, 370
ER_RPL_REWRITEDB_EMPTY_TO error code, 147	ER_SCHEMA_READ_ONLY error code, 112
ER_RPL_REWRITEDB_MISSING_ARROW error code, 147	ER_SDI_GET_KEYS_INVALID_TABLESPACE error code, 116
ER_RPL_SERVER_ID_MISSING error code, 172	ER_SDI_OPERATION_FAILED error code, 87
ER_RPL_SSL_INFO_IN_CONNECTION_METADATA_IGNORED error code, 179	ER_SDI_OPERATION_FAILED_MISSING_RECORD error code, 109
ER_RPL_TRX_DELEGATES_INIT_FAILED error code, 151	ER_SECONDARY_ENGINE error code, 104
ER_RPL_UNEXPECTED_BEGIN_IN_STREAM error code, 167	ER_SECONDARY_ENGINE_DDL error code, 104
ER_RPL_UNEXPECTED_COMMIT_ROLLBACK_OR_XID_ERROR error code, 167	ER_SECONDARY_ENGINE_DDL_FAILED error code, 413
	ER_SECONDARY_ENGINE_DDL_TRACK_PROGRESS error code, 428
	ER_SECONDARY_ENGINE_PLUGIN error code, 103
	ER_SECOND_PASSWORD_CANNOT_BE_EMPTY error code, 103
	ER_SECURE_AUTH_VALUE_UNSUPPORTED error code, 142
	ER_SECURE_TRANSPORT_REQUIRED error code, 72
	ER_SEC_FILE_PRIV_ARGUMENT_TOO_LONG error code, 144
	ER_SEC_FILE_PRIV_CANT_ACCESS_DIR error code, 106
	ER_SEC_EVENT_IN_STREAM error code, 106
	ER_SEC_FILE_PRIV_CANT_STAT error code, 144

ER_SEC_FILE_PRIV_DIRECTORY_INSECURE error code, 143
 ER_SEC_FILE_PRIV_DIRECTORY_PERMISSIONS error code, 144
 ER_SEC_FILE_PRIV_EMPTY error code, 143
 ER_SEC_FILE_PRIV_IGNORED error code, 143
 ER_SEC_FILE_PRIV_NULL error code, 143
 ER_SELECT_REDUCED error code, 20
 ER_SEMISYNC_ADD_ACK_TO_SLOT error code, 210
 ER_SEMISYNC_BINLOG_REPLY_IS_AHEAD error code, 209
 ER_SEMISYNC_BINLOG_WRITE_OUT_OF_ORDER error code, 208
 ER_SEMISYNC_CLEARED_ACTIVE_TRANSACTION_TILL_POS error code, 208
 ER_SEMISYNC_CLEARED_ALL_ACTIVE_TRANSACTION_THREADS error code, 208
 ER_SEMISYNC_DISABLED_ON_SOURCE error code, 208
 ER_SEMISYNC_EXECUTION_FAILED_ON_SOURCE error code, 212
 ER_SEMISYNC_FAILED_REGISTER_REPLICA_TO_RECEIVER error code, 210
 ER_SEMISYNC_FAILED_TO_ALLOCATE_TRX_NODE error code, 207
 ER_SEMISYNC_FAILED_TO_INSERT_TRX_NODE error code, 210
 ER_SEMISYNC_FAILED_TO_START_ACK_RECEIVER_THREAD error code, 210
 ER_SEMISYNC_FAILED_TO_STOP_ACK_RECEIVER_THREAD error code, 212
 ER_SEMISYNC_FAILED_TO_WAIT_ON_DUMP_SOCKET error code, 210
 ER_SEMISYNC_FORCED_SHUTDOWN error code, 208
 ER_SEMISYNC_FUNCTION_CALLED_TWICE error code, 208
 ER_SEMISYNC_INIT_WAIT_POS error code, 209
 ER_SEMISYNC_INSERT_LOG_INFO_IN_ENTRY error code, 208
 ER_SEMISYNC_MISSING_MAGIC_NO_FOR_SEMISYNC_PACKET error code, 211
 ER_SEMISYNC_MOVE_BACK_WAIT_POS error code, 209
 ER_SEMISYNC_NOT_SUPPORTED_BY_SOURCE error code, 212
 ER_SEMISYNC_NO_SPACE_IN_THE_PKT error code, 209
 ER_SEMISYNC_PROBE_LOG_INFO_IN_ENTRY error code, 208
 ER_SEMISYNC_RECEIVED_ACK_IS_SMALLER error code, 210
 ER_SEMISYNC_REPLICA_NET_FLUSH_REPLY_FAILED error code, 211
 ER_SEMISYNC_REPLICA_REPLY error code, 211
 ER_SEMISYNC_REPLICA_REPLY_WITH_BINLOG_INFO error code, 211
 ER_SEMISYNC_REPLICA_SEND_REPLY_FAILED error code, 211
 ER_SEMISYNC_REPLICA_SET_FAILED error code, 212
 ER_SEMISYNC_REPLICA_START error code, 211
 ER_SEMISYNC_REPLY_BINLOG_FILE_TOO_LARGE error code, 208
 ER_SEMISYNC_REPLY_MAGIC_NO_ERROR error code, 208
 ER_SEMISYNC_REPLY_PKT_LENGTH_TOO_SMALL error code, 208
 ER_SEMISYNC_RPL_ENABLED_ON_SOURCE error code, 208
 ER_SEMISYNC_RPL_INIT_FOR_TRX error code, 207
 ER_SEMISYNC_RPL_SWITCHED_OFF error code, 209
 ER_SEMISYNC_RPL_SWITCHED_ON error code, 209
 ER_SEMISYNC_SERVER_REPLY error code, 208
 ER_SEMISYNC_SOCKET_FD_TOO_LARGE error code, 211
 ER_SEMISYNC_SOURCE_FAILED_ON_NET_FLUSH error code, 210
 ER_SEMISYNC_SOURCE_GOT_REPLY_AT_POS error code, 209
 ER_SEMISYNC_SOURCE_OOM error code, 208
 ER_SEMISYNC_SOURCE_SIGNAL_ALL_WAITING_THREADS error code, 209
 ER_SEMISYNC_SOURCE_TRX_WAIT_POS error code, 209
 ER_SEMISYNC_STARTING_ACK_RECEIVER_THD error code, 210
 ER_SEMISYNC_START_BINLOG_DUMP_TO_REPLICA error code, 210
 ER_SEMISYNC_STOPPING_ACK_RECEIVER_THREAD error code, 210
 ER_SEMISYNC_STOP_BINLOG_DUMP_TO_REPLICA error code, 211
 ER_SEMISYNC_SYNC_HEADER_UPDATE_INFO error code, 209
 ER_SEMISYNC_TRACE_ENTER_FUNC error code, 207
 ER_SEMISYNC_TRACE_EXIT error code, 207
 ER_SEMISYNC_TRACE_EXIT_WITH_BOOL_EXIT_CODE error code, 207
 ER_SEMISYNC_TRACE_EXIT_WITH_INT_EXIT_CODE error code, 207
 ER_SEMISYNC_TRX_SKIPPED_AT_POS error code, 210
 ER_SEMISYNC_UNREGISTERED_REPLICATOR error code, 211
 ER_SEMISYNC_UNREGISTER_BINLOG_STORAGE_OBSERVER error code, 211
 ER_SEMISYNC_UNREGISTER_BINLOG_TRANSMIT_OBSERVER error code, 211

ER_SEMISYNC_UNREGISTER_TRX_OBSERVER_FAILED error code, 211
 ER_SEMISYNC_UPDATE_EXISTING_REPLICA_ACK error code, 210
 ER_SEMISYNC_WAIT_FOR_BINLOG_TIMEDOUT error code, 209
 ER_SEMISYNC_WAIT_TIME_ASSESSMENT_FOR_COMMENT_TOO_LONG error code, 209
 ER_SEMISYNC_WAIT_TIME_FOR_BINLOG_SENT error code, 209
 ER_SERVERID_TOO_LARGE error code, 149
 ER_SERVER_ACL_TABLE_ERROR error code, 342
 ER_SERVER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_SYNC error code, 358
 ER_SERVER_BINLOG_MASTER_KEY_ROTATION_FAILED error code, 358
 ER_SERVER_BINLOG_UNSAFE_SYSTEM_FUNCTION error code, 361
 ER_SERVER_CANNOT_LOAD_FROM_TABLE_V2 error code, 342
 ER_SERVER_CANT_OPEN_FILE error code, 342
 ER_SERVER_CERT_VERIFY_FAILED error code, 416
 ER_SERVER_COL_COUNT_DOESNT_MATCH_CORRUPTED error code, 342
 ER_SERVER_COL_COUNT_DOESNT_MATCH_PLEASE_CREATE_THE_INDEX error code, 342
 ER_SERVER_COST_FAILED_TO_READ error code, 167
 ER_SERVER_COST_INVALID_COST_CONSTANT error code, 166
 ER_SERVER_COST_UNKNOWN_COST_CONSTANT error code, 166
 ER_SERVER_DISK_FULL_NOWAIT error code, 341
 ER_SERVER_DOWNGRADE_FROM_VERSION error code, 414
 ER_SERVER_DOWNGRADE_HELP_TABLE_STATUS error code, 426
 ER_SERVER_DOWNGRADE_STATUS error code, 414
 ER_SERVER_DOWNGRADE_SYS_SCHEMA error code, 426
 ER_SERVER_FILE_NOT_FOUND error code, 342
 ER_SERVER_FILE_USED error code, 342
 ER_SERVER_GTID_UNSAFE_CREATE_DROP_TEMP_TABLE_IN_TRANSACTION error code, 348
 ER_SERVER_HANDLER_ERROR error code, 341
 ER_SERVER_INIT_COMPILED_IN_COMMANDS error code, 202
 ER_SERVER_ISNT_AVAILABLE error code, 73
 ER_SERVER_NET_PACKET_TOO_LARGE error code, 341
 ER_SERVER_NEW_ABORTING_CONNECTION error code, 341
 ER_SERVER_NOT_FORM_FILE error code, 341
 ER_SERVER_NO_SESSION_TO_SEND_TO error code, 341
 ER_SERVER_NO_SYSTEM_TABLE_ACCESS error code, 341
 ER_SERVER_OFFLINE_MODE error code, 62
 ER_SERVER_OUTOFMEMORY error code, 193
 ER_SERVER_OUT_OF_RESOURCES error code, 192
 ER_SERVER_OUT_OF_SORTMEMORY error code, 341
 ER_SERVER_RECORD_FILE_FULL error code, 341
 ER_SERVER_REPLICA_AM_INIT_REPOSITORY error code, 341
 ER_SERVER_REPLICA_CM_INIT_REPOSITORY error code, 341
 ER_SERVER_REPLICA_KEY_CONVERSION_FAILED error code, 342
 ER_SERVER_REPLICA_IGNORED_TABLE error code, 342
 ER_SERVER_REPLICA_INIT_QUERY_FAILED error code, 342
 ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT error code, 355
 ER_SERVER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY error code, 352
 ER_SERVER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY error code, 352
 ER_SERVER_RPL_ENCRYPTION_FAILED_TO_REMOVE_KEY error code, 352
 ER_SERVER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOG error code, 352
 ER_SERVER_RPL_ENCRYPTION_FAILED_TO_STORE_KEY error code, 352
 ER_SERVER_RPL_ENCRYPTION_HEADER_ERROR error code, 352
 ER_SERVER_RPL_ENCRYPTION_IGNORE_ROTATE_MASTER error code, 353
 ER_SERVER_RPL_ENCRYPTION_KEYRING_INVALID_KEY error code, 352
 ER_SERVER_RPL_ENCRYPTION_KEY_EXISTS_UNEXPECTED error code, 352
 ER_SERVER_RPL_ENCRYPTION_KEY_NOT_FOUND error code, 352
 ER_SERVER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED error code, 352
 ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_INITIALIZE error code, 352
 ER_SERVER_RPL_ENCRYPTION_UNABLE_TO_ROTATE_MASTER error code, 353
 ER_SERVER_SHUTDOWN error code, 7
 ER_SERVER_SHUTDOWN_COMPLETE error code, 191
 ER_SERVER_SHUTDOWN_INFO error code, 344
 ER_SERVER_SOURCE_FATAL_ERROR_READING_BINLOG error code, 340

ER_SERVER_STARTUP_ADMIN_INTERFACE error code, 353
 ER_SERVER_STARTUP_MSG error code, 192
 ER_SERVER_TABLE_CHECK_FAILED error code, 342
 ER_SERVER_TEST_MESSAGE error code, 343
 ER_SERVER_UNKNOWN_SYSTEM_VARIABLE error code, 341
 ER_SERVER_UPGRADE_CHECKING_DB error code, 360
 ER_SERVER_UPGRADE_EMPTY_SYS error code, 360
 ER_SERVER_UPGRADE_FAILED error code, 359
 ER_SERVER_UPGRADE_FROM_VERSION error code, 356
 ER_SERVER_UPGRADE_HELP_TABLE_STATUS error code, 361
 ER_SERVER_UPGRADE_INFO_FILE error code, 360
 ER_SERVER_UPGRADE_MYSQL_TABLES error code, 360
 ER_SERVER_UPGRADE_NO_SYS_VERSION error code, 360
 ER_SERVER_UPGRADE_OFF error code, 359
 ER_SERVER_UPGRADE_PENDING error code, 359
 ER_SERVER_UPGRADE_REPAIR_REQUIRED error code, 360
 ER_SERVER_UPGRADE_REPAIR_STATUS error code, 360
 ER_SERVER_UPGRADE_SKIP error code, 359
 ER_SERVER_UPGRADE_STATUS error code, 359
 ER_SERVER_UPGRADE_SYSTEM_TABLES error code, 360
 ER_SERVER_UPGRADE_SYS_SCHEMA error code, 360
 ER_SERVER_UPGRADE_SYS_SCHEMA_OBJECT_COUNT error code, 360
 ER_SERVER_UPGRADE_SYS_SCHEMA_OUTDATED error code, 360
 ER_SERVER_UPGRADE_SYS_SCHEMA_UP_TO_DATE error code, 360
 ER_SERVER_UPGRADE_SYS_VERSION_EMPTY error code, 360
 ER_SERVER_UPGRADE_VERSION_NOT_SUPPORTED error code, 355
 ER_SERVER_WARN_DEPRECATED error code, 358
 ER_SERVER_WRONG_VALUE_FOR_VAR error code, 348
 ER_SESSION_WAS_KILLED error code, 73
 ER_SETNS_FAILED error code, 361
 ER_SET_CONSTANTS_ONLY error code, 16
 ER_SET_EVENT_FAILED error code, 345
 ER_SET_PASSWORD_AUTH_PLUGIN_ERROR error code, 122
 ER_SET_STATEMENT_CANNOT_INVOKE_FUNCTION error code, 52
 ER_SE_TYPECODE_CONFLICT error code, 153
 ER_SHA256_PASSWORD_SECOND_PASSWORD_USED_INFORMATION error code, 353
 ER_SHAPE_PREDICTION_UDF error code, 123
 ER_SHARED_TABLESPACE_USED_BY_PARTITIONED_TABLE error code, 349
 ER_SHA_PWD_AUTH_REQUIRES_RSA_OR_SSL error code, 217
 ER_SHA_PWD_FAILED_TO_GENERATE_MULTI_ROUND_HASH error code, 216
 ER_SHA_PWD_FAILED_TO_PARSE_AUTH_STRING error code, 216
 ER_SHA_PWD_RSA_KEY_TOO_LONG error code, 217
 ER_SHA_PWD_SALT_FOR_USER_CORRUPT error code, 217
 ER_SHUTDOWN_COMPLETE error code, 8
 ER_SHUTTING_DOWN_REPLICA_THREADS error code, 145
 ER_SIGNAL_BAD_CONDITION_TYPE error code, 43
 ER_SIGNAL_EXCEPTION error code, 43
 ER_SIGNAL_NOT_FOUND error code, 43
 ER_SIGNAL_WARN error code, 43
 ER_SIMULATED_INJECTION_ERROR error code, 128
 ER_SIZE_OVERFLOW_ERROR error code, 37
 ER_SKIP_UPDATING_METADATA_IN_SE_RO_MODE error code, 199
 ER_SLOW_LOG_MODE_IGNORED_WHEN_NOT_LOGGING_TO_FILE error code, 97
 ER_SOURCE error code, 15
 ER_SOURCE_DELAY_VALUE_OUT_OF_RANGE error code, 49
 ER_SOURCE_FATAL_ERROR_READING_BINLOG error code, 19
 ER_SOURCE_HAS_PURGED_REQUIRED_GTIDS error code, 53
 ER_SOURCE_NET_READ error code, 15
 ER_SOURCE_NET_WRITE error code, 15
 ER_SPATIAL_CANT_HAVE_NULL error code, 20
 ER_SPATIAL_FUNCTIONAL_INDEX error code, 94
 ER_SPATIAL_MUST_HAVE_GEOM_COL error code, 46
 ER_SPATIAL_UNIQUE_INDEX error code, 92
 ER_SPECIFIC_ACCESS_DENIED error code, 130
 ER_SPECIFIC_ACCESS_DENIED_ERROR error code, 18
 ER_SPVAR_NONINTEGER_TYPE error code, 114
 ER_SP_ALREADY_EXISTS error code, 23
 ER_SP_BADRETURN error code, 23
 ER_SP_BADSELECT error code, 23
 ER_SP_BADSTATEMENT error code, 24
 ER_SP_BAD_CURSOR_QUERY error code, 24
 ER_SP_BAD_CURSOR_SELECT error code, 24
 ER_SP_BAD_SQLSTATE error code, 29
 ER_SP_BAD_VAR_SHADOW error code, 32
 ER_SP_CANT_ALTER error code, 25
 ER_SP_CANT_SET_AUTOCOMMIT error code, 32

ER_SP_CASE_NOT_FOUND error code, 25
 ER_SP_COND_MISMATCH error code, 24
 ER_SP_CURSOR_AFTER_HANDLER error code, 25
 ER_SP_CURSOR_ALREADY_OPEN error code, 24
 ER_SP_CURSOR_MISMATCH error code, 24
 ER_SP_CURSOR_NOT_OPEN error code, 24
 ER_SP_DOES_NOT_EXIST error code, 23
 ER_SP_DROP_FAILED error code, 23
 ER_SP_DUP_COND error code, 25
 ER_SP_DUP_CURS error code, 25
 ER_SP_DUP_HANDLER error code, 29
 ER_SP_DUP_PARAM error code, 25
 ER_SP_DUP_VAR error code, 25
 ER_SP_FETCH_NO_DATA error code, 25
 ER_SP_LABEL_MISMATCH error code, 23
 ER_SP_LABEL_REDEFINE error code, 23
 ER_SP_LILABEL_MISMATCH error code, 23
 ER_SP_LOAD_FAILED error code, 77
 ER_SP_NORETURN error code, 24
 ER_SP_NORETURNEND error code, 24
 ER_SP_NOT_VAR_ARG error code, 30
 ER_SP_NO_AGGREGATE error code, 33
 ER_SP_NO_ALTER_LANGUAGE error code, 127
 ER_SP_NO_DROP_SP error code, 26
 ER_SP_NO_RECURSION error code, 30
 ER_SP_NO_RECURSIVE_CREATE error code, 23
 ER_SP_NO_RETSET error code, 30
 ER_SP_RECURSION_LIMIT error code, 32
 ER_SP_STORE_FAILED error code, 23
 ER_SP_SUBSELECT_NYI error code, 25
 ER_SP_UNDECLARED_VAR error code, 24
 ER_SP_UNINIT_VAR error code, 23
 ER_SP_VARCOND_AFTER_CURSHNDLR error code, 25
 ER_SP_WRONG_NAME error code, 32
 ER_SP_WRONG_NO_OF_ARGS error code, 24
 ER_SP_WRONG_NO_OF_FETCH_ARGS error code, 24
 ER_SQLTHREAD_WITH_SECURE_REPLICA error code, 51
 ER_SQL_AUTHOR_DEFAULT_ROLES_FAIL error code, 153
 ER_SQL_HA_READ_FAILED error code, 151
 ER_SQL_MODE_MERGED error code, 70
 ER_SQL_MODE_MERGED_WITH_STRICT_MODE error code, 191
 ER_SQL_REPLICA_SKIP_COUNTER_USED_WITH_GTID_MODE error code, 114
 ER_SQL_USER_TABLE ALTER_WARNING error code, 153
 ER_SQL_USER_TABLE_CREATE_WARNING error code, 153
 ER_SRS_ATTRIBUTE_STRING_TOO_LONG error code, 91
 ER_SRS_GEOGCS_INVALID_AXES error code, 92
 ER_SRS_ID_ALREADY_EXISTS error code, 90
 ER_SRS_INVALID_ANGULAR_UNIT error code, 93
 ER_SRS_INVALID_CHARACTER_IN_ATTRIBUTE error code, 91
 ER_SRS_INVALID_HEIGHT error code, 123
 ER_SRS_INVALID_INVERSE_FLATTENING error code, 92
 ER_SRS_INVALID_LATITUDE_OF_ORIGIN error code, 122
 ER_SRS_INVALID_LATITUDE_POLAR_STERE_VAR_A error code, 123
 ER_SRS_INVALID_LONGITUDE_OF_ORIGIN error code, 122
 ER_SRS_INVALID_PRIME_MERIDIAN error code, 93
 ER_SRS_INVALID_SCALING error code, 123
 ER_SRS_INVALID_SEMI_MAJOR_AXIS error code, 92
 ER_SRS_INVALID_ZONE_WIDTH error code, 123
 ER_SRS_MISSING_MANDATORY_ATTRIBUTE error code, 90
 ER_SRS_MULTIPLE_ATTRIBUTE_DEFINITIONS error code, 90
 ER_SRS_NAME_CANT_BE_EMPTY_OR_WHITESPACE error code, 90
 ER_SRS_NOT_CARTESIAN error code, 77
 ER_SRS_NOT_CARTESIAN_UNDEFINED error code, 77
 ER_SRS_NOT_FOUND error code, 79
 ER_SRS_NOT_GEOGRAPHIC error code, 92
 ER_SRS_ORGANIZATION_CANT_BE_EMPTY_OR_WHITESPACE error code, 90
 ER_SRS_PARSE_ERROR error code, 77
 ER_SRS_PROJ_PARAMETER_MISSING error code, 77
 ER_SRS_UNUSED_PROJ_PARAMETER_PRESENT error code, 122
 ER_SRV_END error code, 417
 ER_SRV_INIT_END error code, 417
 ER_SRV_INIT_START error code, 417
 ER_SRV_START error code, 417
 ER_SR_BOGUS_VALUE error code, 151
 ER_SR_INVALID_CONTEXT error code, 151
 ER_SSL_FIPS_MODE_ERROR error code, 218
 ER_SSL_LIBRARY_ERROR error code, 141
 ER_SSL_MEMORY_INSTRUMENTATION_INIT_FAILED error code, 349
 ER_SSL_TRYING_DATADIR_DEFAULTS error code, 140
 ER_STACKSIZE_UNEXPECTED error code, 149
 ER_STACK_BACKTRACE error code, 405
 ER_STACK_OVERRUN error code, 11
 ER_STACK_OVERRUN_NEED_MORE error code, 31
 ER_STARTING_AS error code, 145
 ER_STARTING_INIT error code, 344

ER_STARTING_REPLICA_MONITOR_IO_THREAD error code, 114	ER_SYSTEMD_NOTIFY_PATH_TOO_LONG error code, 257
ER_STARTUP error code, 29	ER_SYSTEMD_NOTIFY_WRITE_FAILED error code, 257
ER_START_REPLICA_CHANNEL_INVALID_CONFIGURATION error code, 129	ER_SYSTEM_SCHEMA_NOT_FOUND error code, 138
ER_START_REPLICA_CHANNEL_INVALID_CONFIGURATION error code, 419	ER_SYSTEM_TABLES_NOT_SUPPORTED_BY_STORAGE_ENGINE error code, 192
ER_STATEMENT_NOT_ALLOWED_AFTER_START_TRANSACTION error code, 111	ER_SYSTEM_TABLE_NOT_TRANSACTIONAL error code, 178
ER_STD_BAD_ALLOC_ERROR error code, 63	ER_SYSTEM_VIEW_INIT_FAILED error code, 193
ER_STD_DOMAIN_ERROR error code, 63	ER_SYSVAR_CHANGE_DURING_QUERY error code, 106
ER_STD_INVALID_ARGUMENT error code, 64	ER_SYS_VAR_COMPONENT_FAILED_TO_MAKE_VARIABLE_PERCENTAGE error code, 217
ER_STD_LENGTH_ERROR error code, 63	ER_SYS_VAR_COMPONENT_FAILED_TO_PARSE_VARIABLE_OPERATOR error code, 217
ER_STD_LOGIC_ERROR error code, 64	ER_SYS_VAR_COMPONENT_OOM error code, 217
ER_STD_OUT_OF_RANGE_ERROR error code, 64	ER_SYS_VAR_COMPONENT_UNKNOWN_VARIABLE_TYPE error code, 217
ER_STD_OVERFLOW_ERROR error code, 64	ER_SYS_VAR_COMPONENT_VARIABLE_SET_READ_ONLY error code, 217
ER_STD_RANGE_ERROR error code, 64	ER_SYS_VAR_DEREGISTRATION error code, 412
ER_STD_REGEX_ERROR error code, 102	ER_SYS_VAR_NOT_FOUND error code, 345
ER_STD_RUNTIME_ERROR error code, 64	ER_SYS_VAR_REGISTRATION error code, 412
ER_STD_UNDERFLOW_ERROR error code, 64	ER_TABLEACCESS_DENIED_ERROR error code, 13
ER_STD_UNKNOWN_EXCEPTION error code, 64	ER_TABLENAME_NOT_ALLOWED_HERE error code, 20
ER_STMT_CACHE_FULL error code, 47	ER_TABLESAMPLE_ONLY_ON_BASE_TABLES error code, 134
ER_STMT_EXECUTION_NOT_ALLOWED_WITHIN_SP_OR_TRIGGER error code, 135	ER_TABLESAMPLE_PERCENTAGE error code, 134
ER_STMT_HAS_NO_OPEN_CURSOR error code, 30	ER_TABLESPACE_AUTO_EXTEND_ERROR error code, 37
ER_STMT_NOT_ALLOWED_IN_SF_OR_TRG error code, 25	ER_TABLESPACE_CANNOT_BE_DECRYPTED error code, 100
ER_STOP_REPLICA_IO_THREAD_DISK_SPACE error code, 218	ER_TABLESPACE_CANNOT_BE_ENCRYPTED error code, 100
ER_STOP_REPLICA_IO_THREAD_TIMEOUT error code, 59	ER_TABLESPACE_CANNOT_ENCRYPT error code, 74
ER_STOP_REPLICA_MONITOR_IO_THREAD_TIMEOUT error code, 114	ER_TABLESPACE_DISCARDED error code, 55
ER_STOP_REPLICA_SQL_THREAD_TIMEOUT error code, 59	ER_TABLESPACE_DUP_FILENAME error code, 83
ER_STORAGE_ENGINE_NOT_LOADED error code, 60	ER_TABLESPACE_ENGINE_MISMATCH error code, 86
ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_FORMAT error code, 46	ER_TABLESPACE_EXISTS error code, 55
ER_STORED_FUNCTION_PREVENTS_SWITCH_BINLOG_FORMAT error code, 38	ER_TABLESPACE_IS_NOT_EMPTY error code, 69
ER_STORED_FUNCTION_PREVENTS_SWITCH_SQL_LOG_BIN error code, 46	ER_TABLESPACE_MISSING error code, 55
ER_SUBPARTITION_ERROR error code, 35	ER_TABLESPACE_MISSING_WITH_NAME error code, 76
ER_SUBPARTITION_NAME error code, 42	ER_TABLESPACE_TYPE_UNKNOWN error code, 100
ER_SUBQUERY_NO_1_ROW error code, 19	ER_TABLES_DIFFERENT_METADATA error code, 49
ER_SUBQUERY_TRANSFORM_REJECTED error code, 111	ER_TABLE_CANT_HANDLE_AUTO_INCREMENT error code, 14
ER_SUPPORTED_ONLY_WITH_HYPERGRAPH error code, 130	ER_TABLE_CANT_HANDLE_BLOB error code, 14
ER_SWITCH_TMP_ENGINE error code, 81	ER_TABLE_CANT_HANDLE_FT error code, 17
ER_SYNTAX_ERROR error code, 13	ER_TABLE_CANT_HANDLE_SPKEYS error code, 33
ER_SYSTEMD_NOTIFY_CONNECT_FAILED error code, 257	ER_TABLE_CHECK_INTACT error code, 150
ER_SYSTEMD_NOTIFY_DEBUG error code, 404	ER_TABLE_CORRUPT error code, 59

ER_TABLE_CREATED_WITH_DIFFERENT_VERSION error code, 161
 ER_TABLE_DEF_CHANGED error code, 29
 ER_TABLE_EXISTS_ERROR error code, 6
 ER_TABLE_HAS_NO_FT error code, 51
 ER_TABLE_INCOMPATIBLE_DECIMAL_FIELD error code, 160
 ER_TABLE_INCOMPATIBLE_YEAR_FIELD error code, 161
 ER_TABLE_IN_FK_CHECK error code, 49
 ER_TABLE_IN_SHARED_TABLESPACE error code, 124
 ER_TABLE_IN_SYSTEM_TABLESPACE error code, 54
 ER_TABLE_MUST_HAVE_A_VISIBLE_COLUMN error code, 116
 ER_TABLE_MUST_HAVE_COLUMNS error code, 11
 ER_TABLE_NAME error code, 42
 ER_TABLE_NAME_CAUSES_TOO_LONG_PATH error code, 106
 ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED error code, 370
 ER_TABLE_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_FK error code, 370
 ER_TABLE_NEEDS_DUMP_UPGRADE error code, 204
 ER_TABLE_NEEDS_REBUILD error code, 47
 ER_TABLE_NEEDS_UPGRADE error code, 32
 ER_TABLE_NOT_EMPTY error code, 124
 ER_TABLE_NOT_LOCKED error code, 10
 ER_TABLE_NOT_LOCKED_FOR_WRITE error code, 10
 ER_TABLE_NO_PRIMARY_KEY error code, 124
 ER_TABLE_REFERENCED error code, 75
 ER_TABLE_SCHEMA_MISMATCH error code, 54
 ER_TABLE_UPGRADE_REQUIRED error code, 192
 ER_TABLE_VALUE_CONSTRUCTOR_CANNOT_HAVE_DEFAULT error code, 108
 ER_TABLE_VALUE_CONSTRUCTOR_MUST_HAVE_COLUMNS error code, 108
 ER_TABLE_WITHOUT_PK error code, 93
 ER_TABLE_WRONG_KEY_DEFINITION error code, 161
 ER_TARGET_TABLESPACE_UNENCRYPTED error code, 100
 ER_TC_BAD_MAGIC_IN_TC_LOG error code, 170
 ER_TC_CANT_AUTO_RECOVER_WITH_TC_HEURISTIC_RECOVER error code, 170
 ER_TC_HEURISTIC_RECOVERY_FAILED error code, 170
 ER_TC_HEURISTIC_RECOVERY_MODE error code, 170
 ER_TC_NEED_N_SE_SUPPORTING_2PC_FOR_RECOVERY error code, 170
 ER_TC_RECOVERING_AFTER_CRASH_USING error code, 170
 ER_TC_RECOVERY_FAILED_THESE_ARE_YOUR_OPTIONS error code, 170
 ER_TC_RESTART_WITHOUT_TC_HEURISTIC_RECOVER error code, 170
 ER_TELEMETRY_ERROR error code, 417
 ER_TELEMETRY_INFO error code, 416
 ER_TELEMETRY_WARNING error code, 416
 ER_TEMPORARY_NAME error code, 42
 ER_TEMP_FILE_WRITE_FAILURE error code, 59
 ER_TEMP_TABLE_PREVENTS_SWITCH_GLOBAL_BINLOG_FILE error code, 93
 ER_TEMP_TABLE_PREVENTS_SWITCH_SESSION_BINLOG_FILE error code, 93
 ER_TEXTFILE_NOT_READABLE error code, 9
 ER_TF_FORBIDDEN_JOIN_TYPE error code, 88
 ER_TF_MUST_HAVE_ALIAS error code, 87
 ER_THE_USER_ABIDES error code, 146
 ER_THREAD_HANDLING_OOM error code, 143
 ER_THREAD_POOL_ALGORITHM_INVALID error code, 205
 ER_THREAD_POOL_BUFFER_TOO_SMALL error code, 206
 ER_THREAD_POOL_CANNOT_REGISTER_DYNAMIC_PRIVILEGE error code, 404
 ER_THREAD_POOL_CANNOT_SET_THREAD_SPECIFIC_DATA error code, 206
 ER_THREAD_POOL_CONNECTION_REPORT error code, 413
 ER_THREAD_POOL_CON_HANDLER_INIT_FAILED error code, 206
 ER_THREAD_POOL_DEDICATED_LISTENERS_INVALID error code, 397
 ER_THREAD_POOL_FAILED_PROCESS_CONNECT_EVENT error code, 206
 ER_THREAD_POOL_FAILED_TO_CREATE_CONNECT_HANDLER error code, 206
 ER_THREAD_POOL_FAILED_TO_CREATE_POOL error code, 206
 ER_THREAD_POOL_FAILED_TO_CREATE_THD_AND_AUTH error code, 206
 ER_THREAD_POOL_IDLE_CONNECTION_CLOSED error code, 409
 ER_THREAD_POOL_INIT_FAILED error code, 206
 ER_THREAD_POOL_INVALID_PRIO_KICKUP_TIMER error code, 205
 ER_THREAD_POOL_INVALID_STALL_LIMIT error code, 205
 ER_THREAD_POOL_LOW_LEVEL_REARM_FAILED error code, 206
 ER_THREAD_POOL_MAX_UNUSED_THREADS_INVALID error code, 205
 ER_THREAD_POOL_MTL_DISABLE error code, 427
 ER_THREAD_POOL_MTL_REENABLE error code, 427
 ER_THREAD_POOL_NOT_SUPPORTED_ON_PLATFORM error code, 205

ER_THREAD_POOL_PFS_TABLES_ADD_FAILED error code, 351
 ER_THREAD_POOL_PFS_TABLES_INIT_FAILED error code, 351
 ER_THREAD_POOL_PLUGIN_STARTED error code, 397
 ER_THREAD_POOL_QUERY_THREADS_PER_GROUP_INVALID error code, 405
 ER_THREAD_POOL_QUERY_THRS_PER_GRP_EXCEEDS_LIMIT error code, 405
 ER_THREAD_POOL_RATE_LIMITED_ERROR_MSGS error code, 206
 ER_THREAD_POOL_SIZE_TOO_HIGH error code, 205
 ER_THREAD_POOL_SIZE_TOO_LOW error code, 205
 ER_THREAD_POOL_SYSVAR_CHANGE error code, 405
 ER_THREAD_PRIORITY_IGNORED error code, 190
 ER_THREAD_STILL_ALIVE error code, 417
 ER_TLS_CONFIGURATION_REUSED error code, 376
 ER_TLS_CONFIGURED_FOR_CHANNEL error code, 375
 ER_TLS_LIBRARY_ERROR_INTERNAL error code, 416
 ER_TMPDIR_PATH_TOO_LONG error code, 380
 ER_TMP_SESSION_FOR_VAR error code, 404
 ER_TOO_BIG_DISPLAYWIDTH error code, 31
 ER_TOO_BIG_ENUM error code, 76
 ER_TOO_BIG_FIELDLENGTH error code, 8
 ER_TOO_BIG_FOR_UNCOMPRESS error code, 20
 ER_TOO_BIG_PRECISION error code, 30
 ER_TOO_BIG_ROW_SIZE error code, 11
 ER_TOO_BIG_SCALE error code, 30
 ER_TOO_BIG_SELECT error code, 10
 ER_TOO_BIG_SET error code, 10
 ER_TOO_HIGH_LEVEL_OF_NESTING_FOR_SELECT error code, 33
 ER_TOO_LONG_BODY error code, 31
 ER_TOO_LONG_FIELD_COMMENT error code, 42
 ER_TOO_LONG_IDENT error code, 7
 ER_TOO_LONG_INDEX_COMMENT error code, 46
 ER_TOO_LONG_KEY error code, 8
 ER_TOO_LONG_ROUTINE_COMMENT error code, 77
 ER_TOO_LONG_SET_ENUM_VALUE error code, 76
 ER_TOO_LONG_STRING error code, 14
 ER_TOO_LONG_TABLESPACE_COMMENT error code, 83
 ER_TOO_LONG_TABLE_COMMENT error code, 42
 ER_TOO_LONG_TABLE_PARTITION_COMMENT error code, 53
 ER_TOO_MANY_CONCURRENT_TRXS error code, 42
 ER_TOO_MANY_FIELDS error code, 11
 ER_TOO_MANY_GROUP_BY_MODIFIER_BRANCHES error code, 129
 ER_TOO_MANY_KEYS error code, 8
 ER_TOO_MANY_KEY_PARTS error code, 8
 ER_TOO_MANY_PARTITIONS_ERROR error code, 35
 ER_TOO_MANY_PARTITION_FUNC_FIELDS_ERROR error code, 44
 ER_TOO_MANY_ROWS error code, 15
 ER_TOO_MANY_STORAGE_ENGINES error code, 153
 ER_TOO_MANY_TABLES error code, 11
 ER_TOO_MANY_USER_CONNECTIONS error code, 16
 ER_TOO_MANY_VALUES_ERROR error code, 44
 ER_TRANSACTIONAL_WINDOW_FAILURE error code, 120
 ER_TO_VECTOR_CONVERSION error code, 136
 ER_TP_CANNOT_DISABLE_MTL_WITH_DL error code, 137
 ER_TP_QUERY_THRS_PER_GRP_EXCEEDS_TXN_THR_LIMIT error code, 123
 ER_TRACK_VARIABLES_BOGUS error code, 147
 ER_TRANSACTION_ROLLBACK_DURING_COMMIT error code, 68
 ER_TRANSFORM_SOURCE_SRS_MISSING_TOWGS84 error code, 93
 ER_TRANSFORM_SOURCE_SRS_NOT_SUPPORTED error code, 93
 ER_TRANSFORM_TARGET_SRS_MISSING_TOWGS84 error code, 93
 ER_TRANSFORM_TARGET_SRS_NOT_SUPPORTED error code, 93
 ER_TRANSPORTS_WHAT_TRANSPORTS error code, 145
 ER_TRANS_CACHE_FULL error code, 16
 ER_TREE_CORRUPT_2_CONSECUTIVE_REDS error code, 177
 ER_TREE_CORRUPT_INCORRECT_BLACK_COUNT error code, 177
 ER_TREE_CORRUPT_PARENT_SHOULD_POINT_AT_PARENT error code, 177
 ER_TREE_CORRUPT_RIGHT_IS_LEFT error code, 177
 ER_TREE_CORRUPT_ROOT_SHOULD_BE_BLACK error code, 177
 ER_TRG_ALREADY_EXISTS error code, 26
 ER_TRG_CANT_CHANGE_ROW error code, 27
 ER_TRG_CANT_OPEN_TABLE error code, 41
 ER_TRG_CANT_PARSE error code, 150
 ER_TRG_CORRUPTED_FILE error code, 40
 ER_TRG_CREATION_CTX_NOT_SET error code, 192
 ER_TRG_DOES_NOT_EXIST error code, 26
 ER_TRG_INVALID_CREATION_CTX error code, 40
 ER_TRG_IN_WRONG_SCHEMA error code, 31
 ER_TRG_NO_CLIENT_CHARSET error code, 141
 ER_TRG_NO_CREATION_CTX error code, 40
 ER_TRG_NO_DEFINER error code, 32
 ER_TRG_NO_SUCH_ROW_IN_TRG error code, 27
 ER_TRG_ON_VIEW_OR_TEMP_TABLE error code, 27
 ER_TRG_WITHOUT_DEFINER error code, 141
 ER_TRG_WRONG_ORDER error code, 356

ER_TRHEAD_POOL_LOW_LEVEL_INIT_FAILED error code, 206
 ER_TRIGGER_INVALID_VALUE error code, 137
 ER_TRUNCATED_WRONG_VALUE error code, 22
 ER_TRUNCATED_WRONG_VALUE_FOR_FIELD error code, 27
 ER_TRUNCATE_ILLEGAL_FK error code, 47
 ER_TRX_GTID_COLLECT_REJECT error code, 153
 ER_TRX_WRITE_SET_OOM error code, 153
 ER_TURNING_LOGGING_OFF_FOR_THE_DURATION error code, 188
 ER_TURNING_ON_PARTIAL_REVOKES error code, 358
 ER_TZ_CANT_BUILD_MKTIME_MAP error code, 163
 ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE error code, 162
 ER_TZ_CANT_FIND_DESCRIPTION_FOR_TIME_ZONE_1 error code, 162
 ER_TZ_CANT_OPEN_AND_LOCK_TIME_ZONE_TABLE error code, 162
 ER_TZ_ERROR_LOADING_LEAP_SECOND_TABLE error code, 162
 ER_TZ_NO_TRANSITION_TYPES_IN_TIME_ZONE error code, 163
 ER_TZ_OOM_INITIALIZING_TIME_ZONES error code, 161
 ER_TZ_OOM_LOADING_LEAP_SECOND_TABLE error code, 162
 ER_TZ_OOM_LOADING_TIME_ZONE_DESCRIPTION error code, 163
 ER_TZ_OOM_WHILE_LOADING_TIME_ZONE error code, 163
 ER_TZ_OOM_WHILE_SETTING_TIME_ZONE error code, 163
 ER_TZ_TOO_MANY_LEAPS_IN_LEAP_SECOND_TABLE error code, 162
 ER_TZ_TRANSITION_TABLE_BAD_TRANSITION_TYPE error code, 163
 ER_TZ_TRANSITION_TABLE_LOAD_ERROR error code, 163
 ER_TZ_TRANSITION_TABLE_TOO_MANY_TRANSITIONS error code, 162
 ER_TZ_TRANSITION_TYPE_TABLE_ABBREVIATIONS_EXCEEDS error code, 162
 ER_TZ_TRANSITION_TYPE_TABLE_LOAD_ERROR error code, 162
 ER_TZ_TRANSITION_TYPE_TABLE_TYPE_TOO_LARGE error code, 162
 ER_TZ_UNKNOWN_OR_ILLEGAL_DEFAULT_TIME_ZONE error code, 162
 ER_UDF_ALREADY_EXISTS error code, 345
 ER_UDF_CANT_ALLOC_FOR_FUNCTION error code, 152
 ER_UDF_CANT_ALLOC_FOR_STRUCTURES error code, 152
 ER_UDF_CANT_OPEN_FUNCTION_TABLE error code, 152
 ER_UDF_DEREGISTRATION error code, 412
 ER_UDF_DROP_DYNAMICALLY_REGISTERED error code, 84
 ER_UDF_ERROR error code, 75
 ER_UDF_EXEC_FAILURE error code, 412
 ER_UDF_EXEC_FAILURE_REASON error code, 412
 ER_UDF_EXISTS error code, 12
 ER_UDF_INVALID_ROW_IN_FUNCTION_TABLE error code, 152
 ER_UDF_NO_PATHS error code, 12
 ER_UDF_REGISTER_ERROR error code, 380
 ER_UDF_REGISTER_SERVICE_ERROR error code, 380
 ER_UDF_REGISTRATION error code, 412
 ER_UDF_UNREGISTER_ERROR error code, 380
 ER_UNKNOWN_AUTH_ID_OR_ACCESS_DENIED_FOR_GRANT error code, 100
 ER_UNABLE_TO_BUILD_HISTOGRAM error code, 85
 ER_UNABLE_TO_COLLECT_LOG_STATUS error code, 91
 ER_UNABLE_TO_DROP_COLUMN_STATISTICS error code, 85
 ER_UNABLE_TO_RESOLVE_HOSTNAME error code, 140
 ER_UNABLE_TO_RESOLVE_IP error code, 140
 ER_UNABLE_TO_SET_OPTION error code, 91
 ER_UNABLE_TO_STORE_COLUMN_STATISTICS error code, 84
 ER_UNABLE_TO_STORE_STATISTICS error code, 79
 ER_UNABLE_TO_UPDATE_COLUMN_STATISTICS error code, 85
 ER_UNDISCLOSED_PARSE_ERROR_IN_DIGEST_FN error code, 88
 ER_UNDO_RECORD_TOO_BIG error code, 48
 ER_UNEXPECTED_GEOMETRY_TYPE error code, 77
 ER_UNIQUE_KEY_NEED_ALL_FIELDS_IN_PF error code, 35
 ER_UNIT_NOT_FOUND error code, 105
 ER_UNKNOWN_ALTER_ALGORITHM error code, 54
 ER_UNKNOWN_ALTER_LOCK error code, 54
 ER_UNKNOWN_AUTHID error code, 77
 ER_UNKNOWN_AUTH_ID_IN_MANDATORY_ROLE error code, 195
 ER_UNKNOWN_CHARACTER_SET error code, 11
 ER_UNKNOWN_COLLATION error code, 21
 ER_UNKNOWN_COM_ERROR error code, 6
 ER_UNKNOWN_ERROR error code, 10
 ER_UNKNOWN_ERROR_DETECTED_IN_SE error code, 199
 ER_UNKNOWN_ERROR_NUMBER error code, 152

ER_UNKNOWN_EXPLAIN_FORMAT error code, 53
 ER_UNKNOWN_KEY_CACHE error code, 22
 ER_UNKNOWN_LOCALE error code, 43
 ER_UNKNOWN_NETWORK_NAMESPACE error code, 361
 ER_UNKNOWN_PARTITION error code, 49
 ER_UNKNOWN_PROCEDURE error code, 10
 ER_UNKNOWN_STMT_HANDLER error code, 19
 ER_UNKNOWN_STORAGE_ENGINE error code, 22
 ER_UNKNOWN_SYSTEM_VARIABLE error code, 16
 ER_UNKNOWN_TABLE error code, 10
 ER_UNKNOWN_TABLESPACE_TYPE error code, 349
 ER_UNKNOWN_TABLE_IN_UPGRADE error code, 366
 ER_UNKNOWN_TARGET_BINLOG error code, 27
 ER_UNKNOWN_TIME_ZONE error code, 22
 ER_UNKNOWN_UNSUPPORTED_STORAGE_ENGINE error code, 142
 ER_UNKNOWN_VARIABLE_IN_PERSISTED_CONFIG_FILE error code, 345
 ER_UNRESOLVED_HINT_NAME error code, 70
 ER_UNRESOLVED_TABLE_LOCK error code, 80
 ER_UNSUPPORTED_LOG_ENGINE error code, 39
 ER_UNSUPPORTED_ACTION_ON_DEFAULT_VAL_GENERATED error code, 95
 ER_UNSUPPORTED_ACTION_ON_GENERATED_COLUMNS error code, 68
 ER_UNSUPPORTED_ALTER_ENCRYPTION_INPLACE error code, 74
 ER_UNSUPPORTED_ALTER_INPLACE_ON_VIRTUAL_COLUMNS error code, 68
 ER_UNSUPPORTED_ALTER_ONLINE_ON_VIRTUAL_COLUMNS error code, 74
 ER_UNSUPPORTED_DATE error code, 145
 ER_UNSUPPORTED_ENGINE error code, 49
 ER_UNSUPPORTED_EXTENSION error code, 11
 ER_UNSUPPORTED_INDEX_ALGORITHM error code, 76
 ER_UNSUPPORTED_PS error code, 22
 ER_UNSUPPORTED_SQL_MODE error code, 105
 ER_UNSUPPORTED_USE_OF_GRANT_AS error code, 100
 ER_UNSUPPORTED_COMPRESSED_TEMPORARY_TABLE error code, 76
 ER_UNTIL_COND_IGNORED error code, 21
 ER_UPDATE_GTID_PURGED_WITH_GR error code, 106
 ER_UPDATE_INFO error code, 12
 ER_UPDATE_LOG_DEPRECATED_IGNORED error code, 24
 ER_UPDATE_LOG_DEPRECATED_TRANSLATED error code, 24
 ER_UPDATE_TABLE_USED error code, 9
 ER_UPDATE_WITHOUT_KEY_IN_SAFE_MODE error code, 15
 ER_UPDATING_DD_TABLE error code, 76
 ER_UPGRADE_NONEXISTENT_SCHEMA error code, 380
 ER_UPGRADE_PARSE_ERROR error code, 349
 ER_USAGE_DEPRECATION_COUNTER error code, 415
 ER_USERNAME error code, 33
 ER_USERNAME_TRUNCATED error code, 376
 ER_USER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED error code, 109
 ER_USER_ALREADY_EXISTS error code, 73
 ER_USER_COLUMN_OLD_LENGTH error code, 74
 ER_USER_DOES_NOT_EXIST error code, 73
 ER_USER_LIMIT_REACHED error code, 18
 ER_USER_LOCK_DEADLOCK error code, 64
 ER_USER_LOCK_OVERLONG_NAME error code, 126
 ER_USER_LOCK_WRONG_NAME error code, 64
 ER_USER_NOT_IN_EXTRA_USERS_BINLOG_POSSIBLY_INCOMPLETE error code, 160
 ER_USER_REFERENCED_AS_DEFINER error code, 113
 ER_USER_REGISTRATION_FAILED error code, 118
 ER_USER_REQUIRES_ROOT error code, 145
 ER_USER_WHAT_USER error code, 145
 ER_USING_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS error code, 115
 ER_UUID_INVALID error code, 142
 ER_UUID_IS error code, 142
 ER_UUID_SALT error code, 142
 ER_UUID_SCRUB error code, 142
 ER_UNMANGLED_COUNT_LEAKS error code, 152
 ER_VALGRIND_DO_QUICK_LEAK_CHECK error code, 151
 ER_VALIDATE_PASSWORD_INSUFFICIENT_CHANGED_CHARACTERS error code, 127
 ER_VALIDATE_PWD_CONVERT_TO_BUFFER_FAILED error code, 258
 ER_VALIDATE_PWD_COULD_BE_NULL error code, 258
 ER_VALIDATE_PWD_DICT_FILE_NOT_LOADED error code, 215
 ER_VALIDATE_PWD_DICT_FILE_NOT_SPECIFIED error code, 215
 ER_VALIDATE_PWD_DICT_FILE_OPEN_FAILED error code, 258
 ER_VALIDATE_PWD_DICT_FILE_TOO_BIG error code, 215
 ER_VALIDATE_PWD_FAILED_TO_GET_FLD_FROM_SECURITY_CONTEXT error code, 215
 ER_VALIDATE_PWD_FAILED_TO_GET_SECURITY_CTX error code, 215
 ER_VALIDATE_PWD_FAILED_TO_READ_DICT_FILE error code, 215

ER_VALIDATE_PWD_LENGTH_CHANGED error code, 216
 ER_VALIDATE_PWD_STATUS_VAR_REGISTRATION_FAILED error code, 258
 ER_VALIDATE_PWD_STATUS_VAR_UNREGISTRATION_FAILED error code, 258
 ER_VALIDATE_PWD_STRING_CONV_TO_BUFFER_FAILED error code, 258
 ER_VALIDATE_PWD_STRING_CONV_TO_LOWERCASE_FAILED error code, 258
 ER_VALIDATE_PWD_STRING_HANDLER_MEM_ALLOCATION_FAILED error code, 258
 ER_VALIDATE_PWD_STRONG_POLICY_DICT_FILE_UNSPECIFIED error code, 258
 ER_VALIDATE_PWD_VARIABLE_REGISTRATION_FAILED error code, 258
 ER_VALIDATE_PWD_VARIABLE_UNREGISTRATION_FAILED error code, 259
 ER_VALUES_IS_NOT_INT_TYPE_ERROR error code, 47
 ER_VALUE_OUT_OF_RANGE error code, 119
 ER_VARIABLE_IS_NOT_STRUCT error code, 21
 ER_VARIABLE_IS_READONLY error code, 41
 ER_VARIABLE_NOT_PERSISTED error code, 79
 ER_VARIABLE_NOT_SETTABLE_IN_SF_OR_TRIGGER error code, 51
 ER_VARIABLE_NOT_SETTABLE_IN_SP error code, 56
 ER_VARIABLE_NOT_SETTABLE_IN_TRANSACTION error code, 51
 ER_VAR_CANT_BE_READ error code, 19
 ER_VAR_DOES_NOT_EXIST error code, 84
 ER_VERBOSE_HINT error code, 147
 ER_VERBOSE_REQUIRES_HELP error code, 142
 ER_VIEW_CHECKSUM error code, 28
 ER_VIEW_CHECK_FAILED error code, 27
 ER_VIEW_CREATION_CTX_NOT_SET error code, 192
 ER_VIEW_DELETE_MERGE_VIEW error code, 28
 ER_VIEW_FRM_NO_USER error code, 32
 ER_VIEW_INVALID error code, 26
 ER_VIEW_INVALID_CREATION_CTX error code, 40
 ER_VIEW_MULTIUPDATE error code, 28
 ER_VIEW_NONUPD_CHECK error code, 27
 ER_VIEW_NO_CREATION_CTX error code, 40
 ER_VIEW_NO_EXPLAIN error code, 26
 ER_VIEW_NO_INSERT_FIELD_LIST error code, 28
 ER_VIEW_OTHER_USER error code, 32
 ER_VIEW_PREVENT_UPDATE error code, 31
 ER_VIEW_RECURSIVE error code, 33
 ER_VIEW_SELECT_CLAUSE error code, 26
 ER_VIEW_SELECT_TMPTABLE error code, 26
 ER_VIEW_SELECT_VARIABLE error code, 26
 ER_VIEW_UNKNOWN_CHARSET_OR_COLLATION error code, 138
 ER_VIEW_UNPARSABLE error code, 161
 ER_VIEW_WRONG_LIST error code, 26
 ER_VTOKEN_PLUGIN_TOKEN_MISMATCH error code, 415
 ER_VTOKEN_PLUGIN_TOKEN_NOT_FOUND error code, 415
 ER_WAITING_FOR_NO_CONNECTIONS error code, 415
 ER_WAITING_FOR_NO_THDS error code, 415
 ER_WAITPID_FAILED error code, 202
 ER_WARNING_AUTHCACHE_INVALID_USER_ATTRIBUTES error code, 153
 ER_WARNING_DISCARD_OLD_PASSWORD_CLAUSE_VOID error code, 353
 ER_WARNING_NOT_COMPLETE_ROLLBACK error code, 16
 ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_CREATE_INDEX error code, 50
 ER_WARNING_NOT_COMPLETE_ROLLBACK_WITH_DROPPE error code, 50
 ER_WARNING_PASSWORD_HISTORY_CLAUSES_VOID error code, 86
 ER_WARNING_RETAIN_CURRENT_PASSWORD_CLAUSE_VOID error code, 353
 ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS error code, 117
 ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS error code, 389
 ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE_ON error code, 117
 ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE_ON error code, 389
 ER_WARN_ALLOWED_PACKET_OVERFLOWED error code, 23
 ER_WARN_ASYNC_CONN_FAILOVER_NETWORK_NAMESPA error code, 116
 ER_WARN_AUDIT_LOG_DISABLED error code, 395
 ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_ONLY error code, 117
 ER_WARN_AUDIT_LOG_FORMAT_UNIX_TIMESTAMP_ONLY error code, 390
 ER_WARN_AUTH_ID_WITH_SYSTEM_USER_PRIV_IN_MANDA error code, 368
 ER_WARN_BAD_MAX_EXECUTION_TIME error code, 69
 ER_WARN_BINLOG_PARTIAL_UPDATES_DISABLED error code, 86
 ER_WARN_BINLOG_PARTIAL_UPDATES_SUGGESTS_PARTIAL error code, 86
 ER_WARN_CANNOT_FREE_COMPONENT_DATA_DEALLOCATI error code, 411
 ER_WARN_CANNOT_PERSIST_SENSITIVE_VARIABLES error code, 396
 ER_WARN_CANNOT_SECURELY_PERSIST_SENSITIVE_VARI error code, 121

ER_WARN_CANT_DROP_DEFAULT_KEYCACHE error code, 31	ER_WARN_DEPRECATED_JSON_TABLE_ON_ERROR_ON_EMPTY error code, 110
ER_WARN_CANT_OPEN_CERTIFICATE error code, 416	ER_WARN_DEPRECATED_NESTED_COMMENT_SYNTAX error code, 96
ER_WARN_CA_CERT_VERIFY_FAILED error code, 416	ER_WARN_DEPRECATED_NON_STANDARD_KEY error code, 135
ER_WARN_CERTIFICATE_ERROR_STRING error code, 416	ER_WARN_DEPRECATED_OR_BLOCKED_CIPHER error code, 414
ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_ERROR error code, 410	ER_WARN_DEPRECATED_SQLMODE error code, 67
ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_ERROR error code, 384	ER_WARN_DEPRECATED_SQL_CALC_FOUND_ROWS error code, 10
ER_WARN_COMPONENT_KEYRING_OCI_DUPLICATE_KEY error code, 405	ER_WARN_DEPRECATED_SUPERFLUOUS_DELIMITER error code, 121
ER_WARN_CONFLICTING_HINT error code, 70	ER_WARN_DEPRECATED_SYNTAX error code, 22
ER_WARN_C_DISABLE_GTID_ONLY_WITH_SOURCE_AUTO error code, 119	ER_WARN_DEPRECATED_SYNTAX_NO_REPLACEMENT error code, 45
ER_WARN_DATA_OUT_OF_RANGE error code, 20	ER_WARN_DEPRECATED_SYNTAX_INVALID_POS error code, 45
ER_WARN_DATA_OUT_OF_RANGE_FUNCTIONAL_INDEX error code, 94	ER_WARN_DEPRECATED_SYNTAX_WITH_VER error code, 38
ER_WARN_DATA_TRUNCATED_FUNCTIONAL_INDEX error code, 94	ER_WARN_DEPRECATED_SYSVAR_UPDATE error code, 67
ER_WARN_DA_PRIVILEGE_NOT_REGISTERED error code, 107	ER_WARN_DEPRECATED_USER_DEFINED_COLLATIONS error code, 126
ER_WARN_DEPRECATED_CHARSET_OPTION error code, 395	ER_WARN_DEPRECATED_USER_DEFINED_COLLATIONS_OPTION error code, 410
ER_WARN_DEPRECATED_CLIENT_NO_SCHEMA_OPTION error code, 124	ER_WARN_DEPRECATED_USER_SET_EXPR error code, 96
ER_WARN_DEPRECATED_COLLATION error code, 120	ER_WARN_DEPRECATED_UTF8MB3_CHARSET_OPTION error code, 349
ER_WARN_DEPRECATED_COLLATION_OPTION error code, 395	ER_WARN_DEPRECATED_UTF8MB3_COLLATION error code, 96
ER_WARN_DEPRECATED_DATETIME_DELIMITER error code, 121	ER_WARN_DEPRECATED_UTF8MB3_COLLATION_OPTION error code, 349
ER_WARN_DEPRECATED_DYNAMIC_PRIV_FOR_USER error code, 418	ER_WARN_DEPRECATED_UTF8_ALIAS_OPTION error code, 349
ER_WARN_DEPRECATED_DYNAMIC_PRIV_IN_GRANT error code, 128	ER_WARN_DEPRECATED_VALUES_FUNCTION_ALWAYS_NULL error code, 110
ER_WARN_DEPRECATED_ENGINE_SYNTAX_NO_REPLACEMENT error code, 129	ER_WARN_DEPRECATED_WITH_NOTE error code, 127
ER_WARN_DEPRECATED_FLOAT_AUTO_INCREMENT error code, 102	ER_WARN_DEPRECATED_YEAR_UNSIGNED error code, 109
ER_WARN_DEPRECATED_FLOAT_DIGITS error code, 102	ER_WARN_DEPRECATED_ZEROFILL error code, 102
ER_WARN_DEPRECATED_FLOAT_UNSIGNED error code, 102	ER_WARN_ENGINE_TRANSACTION_ROLLBACK error code, 41
ER_WARN_DEPRECATED_FOUND_ROWS error code, 110	ER_WARN_FAILED_TO_SETUP_TLS error code, 416
ER_WARN_DEPRECATED_IDENT error code, 123	ER_WARN_FIELD_RESOLVED error code, 21
ER_WARN_DEPRECATED_INNER_INTO error code, 110	ER_WARN_FUNC_INDEX_NOT_APPLICABLE error code, 106
ER_WARN_DEPRECATED_INTEGER_DISPLAY_WIDTH error code, 102	ER_WARN_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE error code, 389
	ER_WARN_GTID_THRESHOLD_BREACH error code, 382
	ER_WARN_HOSTNAME_WONT_WORK error code, 22
	ER_WARN_HYPERGRAPH_EXPERIMENTAL error code, 113

ER_WARN_INCORRECT_PRIVILEGE_FOR_DB_RESTRICTIONS error code, 359
 ER_WARN_INDEX_NOT_APPLICABLE error code, 50
 ER_WARN_INVALID_DB_RESTRICTIONS error code, 359
 ER_WARN_INVALID_HINT error code, 84
 ER_WARN_INVALID_TIMESTAMP error code, 23
 ER_WARN_I_S_SKIPPED_TABLE error code, 46
 ER_WARN_LANGUAGE_COMPONENT_CANNOT_UNINSTALL error code, 424
 ER_WARN_LANGUAGE_COMPONENT_RESOURCE_LIMIT error code, 425
 ER_WARN_LEGACY_SYNTAX_CONVERTED error code, 60
 ER_WARN_LOG_DEPRECATED_NON_STANDARD_KEY error code, 427
 ER_WARN_LOG_PRIVILEGE_CHECKS_USER_CORRUPT error code, 367
 ER_WARN_LOG_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST error code, 367
 ER_WARN_LOG_PRIVILEGE_CHECKS_USER_NEEDS_PERMISSION error code, 367
 ER_WARN_L_DISABLE_GTID_ONLY_WITH_SOURCE_AURORA_POSITIVE error code, 393
 ER_WARN_MIGRATION_EMPTY_SOURCE_KEYRING error code, 396
 ER_WARN_NO_KEYRING_COMPONENT_SERVICE_FOUND error code, 384
 ER_WARN_NO_SERVERID_SPECIFIED error code, 191
 ER_WARN_NO_SPACE_VERSION_COMMENT error code, 126
 ER_WARN_NULL_TO_NOTNULL error code, 20
 ER_WARN_ONLY_SOURCE_LOG_FILE_NO_POS error code, 62
 ER_WARN_ON_MODIFYING_GTID_EXECUTED_TABLE error code, 70
 ER_WARN_OPEN_TEMP_TABLES_MUST_BE_ZERO error code, 62
 ER_WARN_OPTIMIZER_HINT_SYNTAX_ERROR error code, 69
 ER_WARN_OPTION_RESET_AND_IGNORED_DURING_INSTALL error code, 418
 ER_WARN_PARTIAL_REVOKE_AND_DB_GRANT error code, 359
 ER_WARN_PROPERTY_STRING_PARSE_FAILED error code, 355
 ER_WARN_PURGE_LOG_IN_USE error code, 58
 ER_WARN_PURGE_LOG_IS_ACTIVE error code, 58
 ER_WARN_REGEX_USING_DEFAULT error code, 120
 ER_WARN_REMOVED_SQL_MODE error code, 350
 ER_WARN_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME error code, 388
 ER_WARN_REPLICA_GTID_ONLY_AND_GTID_MODE_NOT_COMPATIBLE error code, 393
 ER_WARN_RESERVED_SRID_RANGE error code, 91
 ER_WARN_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_SOURCE error code, 368
 ER_WARN_SCHEDULED_TASK_RUN_FAILED error code, 413
 ER_WARN_SF_UDF_NAME_COLLISION error code, 240
 ER_WARN_SP_STATEMENT_PARTIALLY_EXECUTED error code, 135
 ER_WARN_SQL_AFTER_MTS_GAPS_GAP_NOT_CALCULATED error code, 117
 ER_WARN_SRS_ID_ALREADY_EXISTS error code, 91
 ER_WARN_SRS_NOT_FOUND error code, 77
 ER_WARN_SRS_NOT_FOUND_AXIS_ORDER error code, 80
 ER_WARN_TLS_CHANNEL_INITIALIZATION_ERROR error code, 375
 ER_WARN_TOO_FEW_RECORDS error code, 20
 ER_WARN_TOO_MANY_RECORDS error code, 20
 ER_WARN_TRG_ALREADY_EXISTS error code, 121
 ER_WARN_TRIGGER_DOESNT_HAVE_CREATED error code, 61
 ER_WARN_UNKNOWN_KEYRING_AWS_REGION error code, 367
 ER_WARN_UNKNOWN_QB_NAME error code, 70
 ER_WARN_UNLOAD_THE_NOT_PERSISTED error code, 79
 ER_WARN_UNSUPPORTED_HINT error code, 77
 ER_WARN_UNSUPPORTED_MAX_EXECUTION_TIME error code, 70
 ER_WARN_USING_OTHER_HANDLER error code, 21
 ER_WARN_VAR_VALUE_CHANGE_NOT_SUPPORTED error code, 113
 ER_WARN_VIEW_MERGE error code, 26
 ER_WARN_VIEW_WITHOUT_KEY error code, 26
 ER_WARN_WRONG_COMPRESSION_ALGORITHM_LOG error code, 367
 ER_WARN_WRONG_COMPRESSION_LEVEL_LOG error code, 367
 ER_WARN_UNSAFE_NET_BUFFER_SIZE error code, 142
 ER_WILDCARD_NOT_ALLOWED_FOR_MULTIADDRESS_BINDING error code, 361
 ER_WINDOW_CIRCULARITY_IN_WINDOW_GRAPH error code, 81
 ER_WINDOW_DUPLICATE_NAME error code, 82
 ER_WINDOW_EXPLAIN_JSON error code, 83
 ER_WINDOW_FRAME_END_ILLEGAL error code, 82
 ER_WINDOW_FRAME_ILLEGAL error code, 82
 ER_WINDOW_FRAME_START_ILLEGAL error code, 82
 ER_WINDOW_FUNCTION_IGNORES_FRAME error code, 83
 ER_WINDOW_VIEW_CHANGE_UUID error code, 83
 ER_WINDOW_ILLEGAL_ORDER_BY error code, 82

ER_WINDOW_INVALID_WINDOW_FUNC_ALIAS_USE error code, 82
 ER_WINDOW_INVALID_WINDOW_FUNC_USE error code, 82
 ER_WINDOW_NESTED_WINDOW_FUNC_USE_IN_WINDOW error code, 82
 ER_WINDOW_NO_CHILD_PARTITIONING error code, 81
 ER_WINDOW_NO_GROUP_ORDER_UNUSED error code, 83
 ER_WINDOW_NO_INHERIT_FRAME error code, 82
 ER_WINDOW_NO_REDEFINE_ORDER_BY error code, 82
 ER_WINDOW_NO_SUCH_WINDOW error code, 81
 ER_WINDOW_RANGE_BOUND_NOT_CONSTANT error code, 82
 ER_WINDOW_RANGE_FRAME_NUMERIC_TYPE error code, 82
 ER_WINDOW_RANGE_FRAME_ORDER_TYPE error code, 82
 ER_WINDOW_RANGE_FRAME_TEMPORAL_TYPE error code, 82
 ER_WINDOW_ROWS_INTERVAL_USE error code, 83
 ER_WIN_LISTEN_BUT_HOW error code, 146
 ER_WIN_LOAD_LIBRARY_FAILED error code, 202
 ER_WL9236_NOW_UNUSED error code, 83
 ER_WRITABLE_CONFIG_REMOVED error code, 144
 ER_WRITE_ROW_TO_PARTITION_FAILED error code, 195
 ER_WRITE_SET_EXCEEDS_LIMIT error code, 75
 ER_WRONG_ARGUMENTS error code, 17
 ER_WRONG_AUTO_KEY error code, 8
 ER_WRONG_COLUMN_NAME error code, 14
 ER_WRONG_COMPRESSION_ALGORITHM_CLIENT error code, 107
 ER_WRONG_COMPRESSION_LEVEL_CLIENT error code, 107
 ER_WRONG_COUNT_FOR_KEY error code, 178
 ER_WRONG_COUNT_FOR_ORIGIN error code, 178
 ER_WRONG_COUNT_OF_ELEMENTS error code, 178
 ER_WRONG_DATETIME_SPEC error code, 144
 ER_WRONG_DB_NAME error code, 10
 ER_WRONG_EXPR_IN_PARTITION_FUNC_ERROR error code, 34
 ER_WRONG_FIELD_SPEC error code, 7
 ER_WRONG_FIELD_TERMINATORS error code, 9
 ER_WRONG_FIELD_WITH_GROUP error code, 7
 ER_WRONG_FIELD_WITH_GROUP_V2 error code, 66
 ER_WRONG_FILE_NAME error code, 69
 ER_WRONG_FK_DEF error code, 19
 ER_WRONG_FK_OPTION_FOR_GENERATED_COLUMN error code, 68
 ER_WRONG_GROUP_FIELD error code, 7
 ER_WRONG_JSON_TABLE_VALUE error code, 87
 ER_WRONG_KEY_COLUMN error code, 14
 ER_WRONG_KEY_COLUMN_FUNCTIONAL_INDEX error code, 94
 ER_WRONG_LOCK_OF_SYSTEM_TABLE error code, 14
 ER_WRONG_MRG_TABLE error code, 14
 ER_WRONG_MVI_VALUE error code, 106
 ER_WRONG_NAME_FOR_CATALOG error code, 21
 ER_WRONG_NAME_FOR_INDEX error code, 21
 ER_WRONG_NATIVE_TABLE_STRUCTURE error code, 45
 ER_WRONG_NUMBER_OF_COLUMNS_IN_SELECT error code, 18
 ER_WRONG_OBJECT error code, 26
 ER_WRONG_OUTER_JOIN_UNUSED error code, 11
 ER_WRONG_PARAMCOUNT_TO_NATIVE_FCT error code, 39
 ER_WRONG_PARAMCOUNT_TO_PROCEDURE error code, 10
 ER_WRONG_PARAMETERS_TO_NATIVE_FCT error code, 39
 ER_WRONG_PARAMETERS_TO_PROCEDURE error code, 10
 ER_WRONG_PARAMETERS_TO_STORED_FCT error code, 39
 ER_WRONG_PARTITION_NAME error code, 39
 ER_WRONG_PERFSHEMA_USAGE error code, 46
 ER_WRONG_SIZE_NUMBER error code, 37
 ER_WRONG_SRID_FOR_COLUMN error code, 86
 ER_WRONG_STRING_LENGTH error code, 33
 ER_WRONG_SUB_KEY error code, 9
 ER_WRONG_SUM_SELECT error code, 7
 ER_WRONG_TABLESPACE_NAME error code, 69
 ER_WRONG_TABLE_NAME error code, 10
 ER_WRONG_TYPE_COLUMN_VALUE_ERROR error code, 43
 ER_WRONG_TYPE_FOR_COLUMN_PREFIX_IDX_FLD error code, 201
 ER_WRONG_TYPE_FOR_VAR error code, 18
 ER_WRONG_USAGE error code, 18
 ER_WRONG_VALUE error code, 37
 ER_WRONG_VALUE_COUNT error code, 7
 ER_WRONG_VALUE_COUNT_ON_ROW error code, 12
 ER_WRONG_VALUE_FOR_TYPE error code, 29
 ER_WRONG_VALUE_FOR_VAR error code, 18
 ER_WRONG_VALUE_FOR_VAR_PLUS_ACTIONABLE_PART error code, 111
 ER_X509_CANT_CHMOD_KEY error code, 157
 ER_X509_CANT_CREATE_CERT error code, 157
 ER_X509_CANT_READ_CA_CERT error code, 157
 ER_X509_CANT_READ_CA_KEY error code, 157
 ER_X509_CANT_WRITE_CERT error code, 157
 ER_X509_CANT_WRITE_KEY error code, 157
 ER_X509_CIPHERS_MISMATCH error code, 156

ER_X509_ISSUER_MISMATCH error code, 156
 ER_X509_NEEDS_RSA_PRIVKEY error code, 157
 ER_X509_SUBJECT_MISMATCH error code, 157
 ER_XAER_DUPID error code, 31
 ER_XAER_INVALID error code, 28
 ER_XAER_NOTA error code, 28
 ER_XAER_OUTSIDE error code, 29
 ER_XAER_RMERR error code, 29
 ER_XAER_RMFAIL error code, 29
 ER_XA_CANT_CREATE_MDL_BACKUP error code, 366
 ER_XA_NO_MULTI_2PC_HEURISTIC_RECOVER error code, 152
 ER_XA_RBDEADLOCK error code, 41
 ER_XA_RBROLLBACK error code, 29
 ER_XA_RBTIMEOUT error code, 41
 ER_XA_RECOVERY_DONE error code, 152
 ER_XA_RECOVER_EXPLANATION error code, 152
 ER_XA_RECOVER_FOUND_TRX_IN_SE error code, 152
 ER_XA_RECOVER_FOUND_XA_TRX error code, 152
 ER_XA_REPLICATION_FILTERS error code, 105
 ER_XA_RETRY error code, 75
 ER_XA_STARTING_RECOVERY error code, 152
 ER_XA_TEMP_TABLE error code, 121
 ER_XPLUGIN_ALL_IO_INTERFACES_DISABLED error code, 221
 ER_XPLUGIN_BUFFER_PAGE_ALLOC_FAILED error code, 219
 ER_XPLUGIN_CLIENT_KILL_MSG error code, 221
 ER_XPLUGIN_COMPRESSION_ERROR error code, 367
 ER_XPLUGIN_DETECTED_HANGING_CLIENTS error code, 219
 ER_XPLUGIN_EMPTY_ADMIN_CMD error code, 222
 ER_XPLUGIN_ERROR_MSG error code, 216
 ER_XPLUGIN_ERROR_READING_SOCKET error code, 221
 ER_XPLUGIN_EXCEPTION_IN_EVENT_LOOP error code, 220
 ER_XPLUGIN_EXCEPTION_IN_TASK_SCHEDULER error code, 220
 ER_XPLUGIN_EXISTING_USER_ACCOUNT_WITH_INCORRECT_PRIVILEGES error code, 221
 ER_XPLUGIN_FAILED_AT_SSL_CONF error code, 220
 ER_XPLUGIN_FAILED_TO_ACCEPT_CLIENT error code, 219
 ER_XPLUGIN_FAILED_TO_BIND_INTERFACE_ADDRESS error code, 375
 ER_XPLUGIN_FAILED_TO_CLOSE_SQL_SESSION error code, 222
 ER_XPLUGIN_FAILED_TO_CREATE_SESSION_FOR_CONNECTION error code, 220
 ER_XPLUGIN_FAILED_TO_EXECUTE_ADMIN_CMD error code, 222
 ER_XPLUGIN_FAILED_TO_GET_CREATION_STMT error code, 222
 ER_XPLUGIN_FAILED_TO_GET_ENGINE_INFO error code, 222
 ER_XPLUGIN_FAILED_TO_GET_SECURITY_CTX error code, 221
 ER_XPLUGIN_FAILED_TO_GET_SYS_VAR error code, 222
 ER_XPLUGIN_FAILED_TO_INITIALIZE_SESSION error code, 220
 ER_XPLUGIN_FAILED_TO_OPEN_INTERNAL_SESSION error code, 222
 ER_XPLUGIN_FAILED_TO_PREPARE_IO_INTERFACES error code, 219
 ER_XPLUGIN_FAILED_TO_RESET_IPV6_V6ONLY_FLAG error code, 222
 ER_XPLUGIN_FAILED_TO_SCHEDULE_CLIENT error code, 219
 ER_XPLUGIN_FAILED_TO_SET_MIN_NUMBER_OF_WORKERS error code, 221
 ER_XPLUGIN_FAILED_TO_SET_SO_REUSEADDR_FLAG error code, 222
 ER_XPLUGIN_FAILED_TO_STOP_SERVICES error code, 340
 ER_XPLUGIN_FAILED_TO_SWITCH_CONTEXT error code, 222
 ER_XPLUGIN_FAILED_TO_SWITCH_SECURITY_CTX error code, 348
 ER_XPLUGIN_FAILED_TO_UNREGISTER_UDF error code, 222
 ER_XPLUGIN_FAILED_TO_USE_SSL_CONF error code, 216
 ER_XPLUGIN_FAILED_TO_VALIDATE_ADDRESS error code, 375
 ER_XPLUGIN_FORCE_STOP_CLIENT error code, 219
 ER_XPLUGIN_IPv6_AVAILABLE error code, 221
 ER_XPLUGIN_LISTENER_SETUP_FAILED error code, 220
 ER_XPLUGIN_LISTENER_STATUS_MSG error code, 221
 ER_XPLUGIN_LISTENER_SYS_VARIABLE_ERROR error code, 221
 ER_XPLUGIN_MAX_AUTH_ATTEMPTS_REACHED error code, 219
 ER_XPLUGIN_MESSAGE_TOO_LONG error code, 220
 ER_XPLUGIN_PEER_DISCONNECTED_WHILE_READING_MESSAGE error code, 221
 ER_XPLUGIN_READ_FAILED_CLOSING_CONNECTION error code, 221
 ER_XPLUGIN_REFERENCE_TO_SECURE_CONN_WITH_XPLUGIN error code, 216

ER_XPLUGIN_REFERENCE_TO_USER_ACCOUNT_DOC_SECTION
error code, 220
ER_XPLUGIN_RETRYING_BIND_ON_PORT error
code, 221
ER_XPLUGIN_SRV_SESSION_INIT_THREAD_FAILED
error code, 219
ER_XPLUGIN_STARTUP_FAILED error code, 216
ER_XPLUGIN_TASK_SCHEDULING_FAILED error
code, 220
ER_XPLUGIN_UNABLE_TO_ACCEPT_CONNECTION
error code, 221
ER_XPLUGIN_UNABLE_TO_USE_USER_SESSION_ACCOUNT
error code, 220
ER_XPLUGIN_UNEXPECTED_EXCEPTION_DISPATCHING_CMD
error code, 220
ER_XPLUGIN_UNINITIALIZED_MESSAGE error code,
220
ER_XPLUGIN_USING_SSL_CONF_FROM_MYSQLX
error code, 216
ER_XPLUGIN_USING_SSL_CONF_FROM_SERVER
error code, 216
ER_XPLUGIN_USING_SSL_FOR_TLS_CONNECTION
error code, 216
ER_XPLUING_NET_STARTUP_FAILED error code, 220
ER_YES error code, 3
ER_ZLIB_Z_BUF_ERROR error code, 20
ER_ZLIB_Z_DATA_ERROR error code, 20
ER_ZLIB_Z_MEM_ERROR error code, 20

W

WARN_AES_KEY_SIZE error code, 76
WARN_COND_ITEM_TRUNCATED error code, 43
WARN_DATA_TRUNCATED error code, 21
WARN_NAMED_PIPE_ACCESS_EVERYONE error
code, 60
WARN_NON_ASCII_SEPARATOR_NOT_IMPLEMENTED
error code, 42
WARN_NO_CONNECTION_METADATA error code, 41
WARN_ON_BLOCKHOLE_IN_RBR error code, 59
WARN_OPTION_BELOW_LIMIT error code, 47
WARN_OPTION_IGNORED error code, 41
WARN_PLUGIN_BUSY error code, 41
WARN_UNENCRYPTED_TABLE_IN_ENCRYPTED_DB
error code, 99
WARN_UNSUPPORTED_ACL_TABLES_READ error
code, 114
WARN_USELESS_SPATIAL_INDEX error code, 88