

Oracle® Fusion Middleware

Content Management REST Service Developer's Guide

11g Release 1 (11.1.1.6.0)

E15813-07

November 2011

The OASIS CMIS (Content Management Interoperability Services) Technical Committee works to standardize a web services interface specification that will enable greater interoperability of Enterprise Content Management (ECM) systems. For more information, see the OASIS CMIS site:

<http://www.oasis-open.org/committees/cmis/>

The Content Management REST Service provides a server that uses the CMIS RESTful AtomPub server binding to provide access to Oracle Content Server repositories configured in your application.

This guide is intended to be a supplement to the OASIS CMIS specification, and provides details on the specific implementation of the Content Management REST Service. Before continuing, all users should review the OASIS CMIS specification. This guide references the Content Management Interoperability Services (CMIS) Version 1.0, which can be viewed at the following URL:

<http://docs.oasis-open.org/cmis/CMIS/v1.0/cmis-spec-v1.0.html>.

The specification includes the domain model and two server bindings. As mentioned above, only the RESTful AtomPub binding is currently implemented by the Content Management REST Service. Users should be familiar with Atom and AtomPub, which are the default formats for responses.

Note: CMIS provides a lowest common denominator for a wide range of different content systems; it is not aligned directly with Oracle WebCenter Content (previously called Oracle UCM) functionality. Refer to the Content Management REST Service service document to identify available functionality.

This guide includes the following sections:

- [Section 1, "CMIS Part I - Domain Model"](#)
- [Section 2, "CMIS Part II: RESTful AtomPub Binding"](#)
- [Section 3, "Content Management REST Service Best Practices and Examples"](#)

1 CMIS Part I - Domain Model

Section 2: Domain Model in the CMIS specification defines a domain model that can be used by applications to work with one or more Content Management repositories.

- [Section 1.1, "Data Model"](#)
- [Section 1.2, "Services"](#)

1.1 Data Model

The Content Management REST Service service document consists of AtomPub workspaces. Each workspace maps to a content connection (only Oracle WebCenter Content repositories are supported by the Content Management REST Service). For details on the service document, see the next section, [Section 2, "CMIS Part II: RESTful AtomPub Binding"](#).

1.1.1 Repository

For this release, some of the optional capabilities listed in section 2.1.1 have not been implemented. Versioning, ACL, Policies, Relationships, Change Log, Folder Descendants/Tree, and Renditions will be considered for future releases.

Specifically, the Content Management REST Service implementation has the following optional capabilities:

```
capabilityGetDescendants = true
capabilityGetFolderTree = false
capabilityContentStreamUpdatability = anytime
capabilityChanges = none
capabilityRenditions = none
capabilityMultifiling = false
capabilityUnfiling = false
capabilityVersionSpecificFiling = false
capabilityPWCUpdateable = false
capabilityPWCSearchable = false
capabilityAllVersionsSearchable = false
capabilityJoin = none
capabilityACL = none
capabilityQuery = none, metadataonly, or both combined
```

1.1.2 Object

The Content Management REST Service supports document and folder objects. In CMIS the `cmis:baseTypeId` for a Node will be `cmis:folder` or `cmis:document`. Also, the `cmis:baseId` for a Type will be `cmis:folder` or `cmis:document`.

1.1.3 Object-Type

A CMIS Object-Type contains fields mapped from the Oracle WebCenter Content: Content Server metadata field definitions and Oracle WebCenter Content's Site Studio region definitions.

The mapping from Oracle WebCenter Content metadata fields to CMIS property definitions is as follows:

Table 1 Content Server Metadata Mappings

Oracle WebCenter Content Metadata	CMIS Property Definition
TEXT metadata field with option list configured with select list validated and YesNoView or TrueFalseView view	cmis:propertyBoolean
All other TEXT metadata fields	cmis:propertyString
LONG TEXT metadata field	cmis:propertyString
MEMO metadata field	cmis:propertyString
INTEGER metadata field	cmis:propertyInteger
DATE metadata field	cmis:propertyDateTime

Table 1 (Cont.) Content Server Metadata Mappings

Oracle WebCenter Content Metadata	CMIS Property Definition
DECIMAL metadata field	cmis:propertyDecimal

The mapping from Site Studio region definition fields to CMIS property definitions is as follows:

Table 2 Site Studio Region Definition Mappings

Site Studio Region Definition	CMIS Property Definition
Image Element Definition fields	cmis:propertyString
WYSIWYG Element Definition fields	cmis:propertyString
Plain Text Element Definition fields	cmis:propertyString
Static List Element Definition fields	cmis:propertyString

1.1.4 Document Object

Document Objects are the elementary information entities managed by the repository. As defined by the CMIS specification, Document Objects may be version-able, file-able, query-able, control-able and ACLControl-able. As stated earlier, the Content Management REST Service does not support versioning, multi-filing, Policies or ACL for this release.

If a Node is determined to be a Document (not a Folder) then any children it has will not be exposed through CMIS. In CMIS, each Document Object is associated with a single content stream, and for WebCenter CMIS REST, this stream is the Oracle WebCenter Content: Content Server binary associated with the document.

1.1.5 Folder Object

The CMIS specification states that Folder Objects do not have a content-stream and are not version-able. If a Node is determined to be a Folder, then the Content Management REST Service exposes it in this manner. (In Oracle WebCenter Content, folders do not have a content stream and are not versionable).

1.1.6 Relationship Object

Section 2.1.6: Relationship Object in the CMIS specification is not applicable; the Content Management REST Service does not support Relationships for this release.

1.1.7 Policy Object

Section 2.1.7: Policy Object in the CMIS specification is not applicable; the Content Management REST Service does not support Policies for this release.

1.1.8 Access Control

Most of *Section 2.1.8: Access Control* in the CMIS specification is not applicable; the Content Management REST Service does not support ACL for this release. See the next section for details on allowable actions.

1.1.8.1 AllowableActions Mapping This section lists allowable actions defined for Objects. Because of how this release is implemented, some of these are hard-coded for all objects. Other allowable actions will be set based on the repository configuration.

- canGetObjectRelationships = false
- canCreateRelationship = false
- canGetDescendants = false
- canGetFolderTree = false
- canCheckOut = false (versioning)
- canCancelCheckOut = false (versioning)
- canCheckIn = false (versioning)
- canAddObjectToFolder = false (multi-filing)
- canRemoveObjectFromFolder = false (unfiling/multi-filing)
- canApplyPolicy = false
- canGetAppliedPolicies = false
- canRemovePolicy = false
- canCreatePolicy = false
- canApplyACL = false
- canGetACL = false
- canGetRenditions = false
- canDeleteTree = true
- canGetAllVersions = false (versioning)

1.1.9 Versioning

Section 2.1.9: Versioning in the CMIS specification is not applicable; the Content Management REST Service does not support versioning for this release.

1.1.10 Query

CMIS queries return a Result Set where each Entry object will contain only the properties that were specified in the query. The Content Management REST Service does not support JOINS in queries, so each result entry will represent properties from a single node. Common searches use a query like "SELECT * FROM ...".

- The FROM clause specifies a content-type to be searched.
 - FROM cmis:document ==> any Oracle WebCenter Content document (for example, IDC:GlobalProfile)
 - FROM cmis:folder ==> any Oracle WebCenter Content folder (for example, IDC:Folder)
 - FROM typeQueryName ==> type's cmis queryName, as long as the type is queryable (for example, ora:t:IDC!;GlobalProfile)
- The cmis:document and cmis:folder types are always queryable. Other types will be queryable if they are searchable in the repository.
- The IN_FOLDER predicate is implemented as the folder ID specified, being the parent of the results.
- The IN_TREE predicate is implemented as the folder ID specified, being a parent in the folder structure of the results.

- The CONTAINS() predicate is a full-text query expression operator.
- Properties of cmis:document and cmis:folder will be queryable and orderable if their corresponding Oracle WebCenter Content system property is searchable and sortable. The system property mappings are:
 - cmis:createdBy ==> dDocAuthor
 - cmis:lastModifiedBy ==> dDocCreator
 - cmis:creationDate ==> dCreateDate
 - cmis:lastModificationDate ==> dLastModifiedDate (for 10g, folders map to dLastModifiedDate and documents map to dCreateDate)
 - cmis:name ==> dOriginalName (for a document) or dCollectionName (for a folder)
 - cmis:contentStreamFileName ==> dOriginalName
 - cmis:contentStreamLength ==> VaultFileSize
 - cmis:contentStreamMimeType ==> dFormat
 - cmis:objectId ==> dDocName
 - cmis:objectTypeId ==> Oracle WebCenter Content profile name or SiteStudio Region Definition name

Note: cmis:objectTypeId is never orderable.

- cmis:path ==> use IN_FOLDER or IN_TREE predicate

Note: Some repositories may have capabilities that are not representable in a CMIS query, and some repositories may have restrictions which will limit the CMIS-query predicates (or combinations of predicates) that can be used in a query. Use the mappings above to translate repository capabilities and restrictions into corresponding considerations for CMIS queries.

- Nested properties are not queryable or orderable.
- The Content Management REST Service implementation reports as orderable any properties which Oracle WebCenter Content specifies as sortable. This list can include properties which Oracle WebCenter Content cannot actually sort on. To allow ordering on a field for which Oracle WebCenter Content reports a sort error, follow the steps below to make the specified Oracle WebCenter Content field sortable:
 1. Go to **Administration** and open **Admin Applets**.
 2. Open the Configuration Manager applet and click **Advanced Search Design**.
 3. Edit the field you wish to make orderable and select **Is sortable**.
 4. Save your changes and exit Administration.

The table that follows lists specific search considerations and recommendations. For example queries, see [Section 3, "Content Management REST Service Best Practices and Examples"](#).

Table 3 Search Considerations and Recommendations

Consideration	Recommendation
Oracle WebCenter Content provides limited support for querying on null or non-null values.	Be aware of the differences in search behavior and do not write search expressions that depend on unsupported criteria.
Recursive search for folders is not supported by Oracle WebCenter Content, but is supported for documents if configured on the Oracle WebCenter Content server as described to the right.	<p>Scope the search to only include documents (add a select clause like <code>select * from cmis:document</code>).</p> <p>Set the search path on the Search object (add a where clause like <code>"where IN_TREE('/StellentRepository/IDC:Folder/2')</code>).</p> <p>Configure the <code>folders_g</code> <code>CollectiveSearchRecursiveContent</code> and related settings like <code>CollectionMaxBranch</code> in the Oracle WebCenter Content <code>config.cfg</code> file.</p>
Multivalued property operators perform substring matches. This is true for ANY <multiValuedQueryName> IN (<literal>, ...) or <literal> = ANY <multiValuedQueryName>. In Oracle WebCenter Content, a field with an option list stores values in a comma-delimited manner. For example, if you have values "A", "B", and "C", these will be represented as "A, B, C". Using an ANY or ANY IN search for 'A, B' will find this item.	Be aware of the differences in search behavior and consider changing the Oracle WebCenter Content option list delimiter character in the Configuration Manager applet to reduce the potential for finding extra matches.
When searching folders (<code>FROM cmis:folder</code>), at most one value can be specified per criteria. Each criteria is logically ANDed with the others to make a more selective query. There is no support for OR or NOT operators when searching folders.	Do not use OR and NOT in Oracle WebCenter Content folder search.
Not all properties are searchable, and if the search encounters a property that is not searchable, it will return a <code>ParseException</code> (400 error).	<p>Understand which properties are searchable for a given content type by examining the Oracle WebCenter Content Configuration Manager information fields section, or by reviewing the <code>ContentType</code> definition. Examine the URL for the <code>isSearchable</code> field setting</p> <p>Example URLs:</p> <p><code>http://myContentServer/idc/idcplg?IdcService=VCR_GET_CONTENT_TYPE&vcrContentType=IDC:Folder&IsSoap=1</code></p> <p>Or, examine the specific type through CMIS.</p>
Not all <code>ContentTypes</code> are searchable. An attempt to search for a non-searchable <code>ContentTypes</code> will throw an exception. For example, the <code>IDC:FileReference</code> <code>ContentType</code> is not searchable.	Be aware that not all <code>ContentTypes</code> are searchable.
Only String multi-valued properties can be searched.	Do not specify search for multi-valued property types other than String.
The NOT operator cannot be used for LONG properties.	Try to restructure the query using supported syntax.
Only one sort criteria is supported.	Do not write search expressions that use more than a single sort criteria.

Table 3 (Cont.) Search Considerations and Recommendations

Consideration	Recommendation
<p>Sorting on non-indexed fields results in an exception.</p> <p>Searching on a non-indexed field throws an exception, with the embedded exception code of, for example, "DRG-10837: section dStatus does not exist".</p>	<p>Understand which fields have been indexed before using them as sort criteria. Examine the URL for the <code>isSortable</code> field definition.</p> <p>Example URL: http://myContentServer/idc/idcplg?IdcService=GET_ADVANCED_SEARCH_OPTIONS&IsSoap=1,</p> <p>Or examine the type through CMIS to see if the property definition is queryable.</p>
Empty values are not allowed in a search query.	Do not use a criteria such as <code>cmis:name != ''</code> .
The <code>Notequals</code> operator is not supported for non-String properties	Be aware of the differences in search behavior and do not write search expressions that depend on unsupported criteria.
Multiple search paths on the same Oracle WebCenter Content repository are not supported.	Be aware of the differences in search behavior and do not write search expressions that depend on unsupported criteria.
<p>When searching for documents, recursive search (folder tree search) is supported if Oracle WebCenter Content is configured properly.</p> <p>If the search path is not set, then all documents in the repository will be searched (both filed and unfiled).</p>	<p>Configure the content server <code>folders_g</code> <code>CollectionSearchRecursiveContent</code> and related settings like <code>CollectionMaxBranch</code> in the Oracle WebCenter Content <code>config.cfg</code> file. These settings are described in the Oracle WebCenter Content documentation. To perform a document search scoped to a folder tree, use the <code>IN_TREE</code> predicate.</p>
When searching for documents and using the <code>LIKE</code> operator, wildcards (%) are only supported in the last path element.	Be aware of the differences in search behavior and do not write search expressions that depend upon unsupported criteria.
When searching documents (select * from <code>cmis:document</code>), it is not possible to limit the search to more than just a single content type; for example, this is not supported: <code>select * from IDC:MyProfile, IDC:AnotherProfile</code> because it has multiple explicit content types and <code>JOINS</code> are not supported.	If you need to limit the search to more than just a single content type, issue multiple queries to achieve the same behavior. If you want to search across all types, use <code>cmis:document</code> in the select statement.
Oracle WebCenter Content search does not support <code>OR</code> when <code>cmis:objectId</code> is specified in a query; other parameters can be <code>AND</code> ed with this criteria, but <code>OR</code> is not supported.	If this functionality is necessary, issue multiple queries to achieve the same behavior.
The <code>cmis:objectId</code> criteria only supports <code>=</code> , <code>!=</code> , and <code>like</code> . Use of <code>!=</code> is restricted to the case of excluding folders (which behaves the same as adding <code>select * from cmis:document</code>).	Be aware of the valid operators when using <code>cmis:objectId</code> criteria.
Queries may be case-sensitive depending on the selected Oracle WebCenter Content search engine.	Be aware that the Oracle WebCenter Content search engine selection can affect case-sensitivity. Metadata searches using <code>OracleTextSearch</code> as the search engine are generally case-insensitive. Metadata searches using <code>DATABASE.FULLTEXT</code> as the search engine are generally case-sensitive. The exact behavior sometimes varies by metadata field.

1.2 Services

The methods described in *Section 2.2 Services* of the CMIS specification are implemented by the Content Management REST Service; specific implementation details are covered in the next section, [Section 2, "CMIS Part II: RESTful AtomPub Binding"](#).

2 CMIS Part II: RESTful AtomPub Binding

Section 3: RESTful AtomPub Binding in the CMIS specification defines a specification based on AtomPub that can be used by applications to work with one or more Content Management Repositories. REST services are available through a WebCenter Portal: Spaces instance; for details, see the *Oracle Fusion Middleware Developer's Guide for Oracle WebCenter Portal*.

2.1 Service Document

All navigation of a repository begins with the AtomPub Service Document. From this document, all accessible content in a repository can be discovered through the collections, links, and templates.

The URI to the service document, relative to the CMIS web application's context-root, is `/rest/cmisis/repository`.

Therefore, if an application is deployed with a `library-context-root-override` as in the example above, the service document would be accessed through the following URL:

```
http://hostname:port/rest/cmisis/repository
```

Note: The REST application is only available with the WebCenter Portal: Spaces application and not with any custom portal application development. However, you can make HTTP requests from your portal application to access the REST and CMIS resources that are available in a Spaces application. You must make sure that the Spaces application is configured with the relevant content connections that you wish to access.

By default, this document will contain a workspace for each configured Oracle WebCenter Content repository (only Oracle WebCenter Content repositories are supported by CMIS REST in Oracle WebCenter Portal). A service document for a single repository can be obtained by using the `repositoryId` query parameter, as described in section 3.6.2.1 of the CMIS AtomPub binding specification.

As noted in the previous section, the service document consists of AtomPub workspaces. Each workspace maps to a Oracle WebCenter Portal Content Server connection.

Specific URIs beyond the service document are not published; it is assumed that users will start at the service document and navigate the collections and links down expected paths. The relationships of the links and the titles and types of the collections are all defined in the CMIS specification, and thus can be commonly navigated by a client implementation. There are also templates defined for each repository, for easier access of objects by path, object by ID, type by ID, and queries. The format of the variables for the path and ID templates can be discovered by viewing the Entries of Folders and Documents.

2.2 Response Formats

Section 3.1.3: Response Formats in the CMIS specification indicates that Atom/AtomPub style formats will be returned by default unless overridden by a supported media type expressed in the Accept header.

A generic AtomPub feed reader can walk through any of the feeds returned by the CMIS REST server. It will not see all the CMIS specifics, but will be able to navigate through links. In general, to set up a feed reader, you need to know the URI of a particular feed, which can be discovered by navigating through the service document, for example, the workspace link for "typesdescendants".

For details on query syntax, see the CMIS specification. For Content Management REST Service best practices and examples, see the next section, [Section 3, "Content Management REST Service Best Practices and Examples"](#).

2.3 Additional Functionality

The Content Management REST Service provides the following additional functionality beyond the CMIS specification.

- [Section 2.3.1, "Folder Children Collection"](#)
- [Section 2.3.2, "Document Entry"](#)
- [Section 2.3.3, "Content Stream"](#)

2.3.1 Folder Children Collection

The specification defines the following CMIS services:

- GET: getChildren
- POST: createDocument
or createFolder
or createPolicy
or moveObject
or addObjectToFolder

The Content Management REST Service provides the following additional services:

- POST: create
This service has five query parameters: uid, fileName, contentId, comments, simpleResponse, and one header parameter: Slug. This service is meant to be used as a simple binary request upload. A new document is created with this service. Slug and fileName are used to name the binary that is attached to the request (using both parameters is optional; only one needs to be defined and fileName is checked first). The comments parameter is optional and contentId is optional if Oracle WebCenter Content is set up to auto-generate the dDocName.
- POST: create Content-Type: multipart/form-data
This service has a single query parameter: uid, which is the uid of the folder in which the document is to be created. The boolean query parameter simpleResponse will return a response of media type: application/atom+xml;type=entry, if set to false. If set to true, a response of media type: text/html will be returned with a URI pointing to the newly created document. The comments and simpleResponse parameters are both optional, contentId is optional if Oracle WebCenter Content is set up to auto-generate the dDocName, and the name "fileUpload" is required.

<html>

```

<head>
  <title>simple post</title>
</head>
<body>
<form
action="http://<host>:<port>/rest/api/cmisis/children/StellentRepository?uid=IDC:
Folder/2"
  method="POST"
  enctype="multipart/form-data">
  Select a document to upload: <input type="file" name="fileUpload"/><br>
  <input type="hidden" name="comments" value="this is just a comment"/>
  <input type="hidden" name="contentId" value="uniqueID1"/>
  <input type="hidden" name="simpleResponse" value="true"/>
  <input type="submit" value="Submit"/>
</form>
</body>
</html>

```

2.3.2 Document Entry

The specification defines the following CMIS services:

- GET: getObject, getObjectOfLatestVersion (getObject)
- PUT: updateProperties
- DELETE: deleteObject

The Content Management REST Service provides the following additional services:

- POST: postToDelete
This service has two query parameters: uid and _method, and allows a document to be deleted through POST.

`http://<host>:<port>/rest/api/cmisis/document/repoName?uid=ABC&_method="delete"`

2.3.3 Content Stream

The specification defines the following CMIS services:

- GET: getContentStream
- PUT: setContentStream
- DELETE: deleteContentStream

The Content Management REST Service provides the following additional services:

- POST: postTunnelContentStream
This service has five query parameters: uid, overwriteFlag, fileName, comments, _method, and one header parameter: Slug. This service is meant to be used as a simple binary request upload or delete through POST. A document must already exist for this service. Slug and fileName are used to name the binary that is attached to the request (using both parameters is optional; only one needs to be defined and fileName is checked first). The overwriteFlag parameter defaults to true, the comments parameter is optional and valid values for _method are "delete" or "put" (not case sensitive).

`http://<host>:<port>/rest/api/cmisis/stream/repoName?uid=ABC&_method="delete"`

- POST: postTunnelContentStream
Content-Type: multipart/form-data
This service has a single query parameter: uid and is meant to be used as a simple

html multipart/form-data upload or delete through POST. A document must already exist for this service. The attribute name="fileUpload" is required, "comments" is optional, and valid values for "_method" are "delete" or "put" (not case sensitive).

```
<form
action="http://<host>:<port>/rest/api/cmisis/stream/repoName?uid=WDOC019113"
  method="POST"
  enctype="multipart/form-data">
  Select a document to upload: <input type="file" name="fileUpload" /><br>
  <input type="hidden" name="comments" value="this is just a comment" />
  <input type="hidden" name="_method" value="PUT" />
  <input type="submit" value="Submit" />
</form>
```

3 Content Management REST Service Best Practices and Examples

This section provides best practices and examples using the Content Management REST Service. For details on query syntax, see the CMIS specification.

3.1 Best Practices

The following list provides suggested best practices for repositories that use the Content Management REST Service.

- To determine the types that can be used in the "FROM" portion of a query, see the types collection from the AtomPub service document. The type must be queryable and the query name of that type must be used.

For example, IDC:GlobalProfile might have type information similar to the following:

```
<cmis:localName>IDC:GlobalProfile</cmis:localName>
<cmis:displayName>IDC:GlobalProfile</cmis:displayName>
<cmis:queryName>ora:t:IDC!;GlobalProfile</cmis:queryName>
<cmis:queryable>>true</cmis:queryable>
```

An example query for the type information above could be: "SELECT * FROM ora:t:IDC!;GlobalProfile".

- To determine the properties that can be used in the "SELECT" and "WHERE" portions of a query, see the entry for the associated type. Each property definition of that type will be listed and will have a setting for queryable and orderable. The cmis:queryname will be the value to be used in the query.

For example, IDC:GlobalProfile might have property definition information similar to the following:

```
<cmis:propertyStringDefinition>

<cmis:id>/stan118-ucm11g/IDC:GlobalProfile.ora:p:dDocName</cmis:id>
  <cmis:localName>dDocName</cmis:localName>
  <cmis:displayName>dDocName</cmis:displayName>
  <cmis:queryName>ora:p:dDocName</cmis:queryName>
  <cmis:description>Content ID</cmis:description>
  <cmis:propertyType>string</cmis:propertyType>
  <cmis:cardinality>single</cmis:cardinality>
  <cmis:updatability>readwrite</cmis:updatability>
```

```

    <cmis:inherited>>false</cmis:inherited>
    <cmis:required>>false</cmis:required>
    <cmis:queryable>>true</cmis:queryable>
    <cmis:orderable>>true</cmis:orderable>
  </cmis:propertyStringDefinition>

```

An example query for the property definition information above could be:
 "SELECT ora:p:dDocName FROM ora:t:IDC!;GlobalProfile"

- To keep queries more readable, avoid non-alphanumeric characters in ContentType and PropertyDefinition names.

3.2 Content Management REST Service Examples

This section provides some example queries. For details on query syntax, see the CMIS specification. (To get the full URI for a query, see the query URI template in the service document.)

- SELECT * from cmis:folder
- SELECT cmis:name, cmis:contentStreamFileName, cmis:contentStreamMimeType, cmis:contentStreamLength FROM cmis:document WHERE cmis:contentStreamFileName = 'BinaryName' AND cmis:contentStreamMimeType = 'text/html' AND cmis:contentStreamLength > 1
- SELECT cmis:name, cmis:creationDate, cmis:lastModificationDate FROM cmis:folder WHERE cmis:name = 'Trash' AND cmis:lastModificationDate > TIMESTAMP '2008-05-18T10:32:44.703-06:00'
- SELECT * FROM cmis:document WHERE cmis:name LIKE 'baker%'
- SELECT * FROM cmis:document WHERE cmis:name NOT IN ('nodeBoolean', 'nodeLong')
- SELECT cmis:name from cmis:document where IN_TREE('/StellentRepository')
- SELECT * FROM ora:t:IDC:GlobalProfile WHERE ora:p:xBooleanTestField = FALSE ORDER BY ora:p:dDocTitle ASC
- SELECT ora:p:xMultiValuedDelimiterTest FROM ora:t:IDC:GlobalProfile WHERE ANY ora:p:xMultiValuedDelimiterTest NOT IN ('four')
- SELECT cmis:name FROM ora:t:IDC:GlobalProfile WHERE CONTAINS('test') ORDER BY ora:p:dInDate DESC
- SELECT * FROM cmis:document where IN_TREE('/StellentRepository/IDC:Folder/2')

4 Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at

<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Copyright © 2010, 2011, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle America, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

