

Oracle® Fusion Middleware

WebLogic Scripting Tool Command Reference

11g Release 1 (10.3.6)

E13813-15

April 2014

This document describes all of the commands that are available to use with the WebLogic Scripting Tool (WLST). This document includes WLST commands for WebLogic Server, as well as custom WLST commands that can be used to manage installed Oracle Fusion Middleware components.

Copyright © 2007, 2014, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Contents

Preface	xxvii
Documentation Accessibility	xxvii
Conventions	xxvii
1 Introduction and Roadmap	
1.1 Document Scope and Audience.....	1-1
1.2 Guide to This Document.....	1-1
1.3 Related Documentation.....	1-3
1.4 New and Changed WLST Features in This Release.....	1-3
2 WebLogic Server WLST Online and Offline Command Reference	
2.1 WebLogic Server WLST Command Summary, Alphabetically By Command.....	2-1
2.2 WebLogic Server WLST Online Command Summary	2-6
2.3 WebLogic Server WLST Offline Command Summary.....	2-10
3 WLST Command and Variable Reference	
3.1 Overview of WLST Command Categories.....	3-1
3.2 Browse Commands.....	3-2
3.2.1 cd	3-2
3.2.2 currentTree.....	3-3
3.2.3 prompt.....	3-4
3.2.4 pwd	3-5
3.3 Control Commands	3-5
3.3.1 addTemplate.....	3-6
3.3.2 closeDomain	3-7
3.3.3 closeTemplate.....	3-7
3.3.4 connect.....	3-7
3.3.5 createDomain	3-11
3.3.6 disconnect	3-12
3.3.7 exit.....	3-13
3.3.8 readDomain	3-13
3.3.9 readTemplate.....	3-14
3.3.10 updateDomain	3-15
3.3.11 writeDomain.....	3-15
3.3.12 writeTemplate	3-16

3.4	Customization Commands.....	3-17
3.4.1	addHelpCommandGroup	3-17
3.4.2	addHelpCommand.....	3-18
3.5	Deployment Commands.....	3-19
3.5.1	deploy	3-20
3.5.2	distributeApplication	3-23
3.5.3	getWLDM.....	3-24
3.5.4	listApplications	3-25
3.5.5	loadApplication	3-25
3.5.6	redeploy	3-26
3.5.7	startApplication	3-27
3.5.8	stopApplication.....	3-28
3.5.9	undeploy	3-29
3.5.10	updateApplication.....	3-30
3.6	Diagnostics Commands	3-30
3.6.1	exportDiagnosticData	3-31
3.6.2	exportDiagnosticDataFromServer.....	3-32
3.6.3	getAvailableCapturedImages	3-33
3.6.4	saveDiagnosticImageCaptureFile.....	3-34
3.6.5	saveDiagnosticImageCaptureEntryFile.....	3-35
3.7	Editing Commands.....	3-36
3.7.1	activate.....	3-37
3.7.2	assign	3-38
3.7.3	cancelEdit	3-40
3.7.4	create.....	3-41
3.7.5	delete.....	3-42
3.7.6	encrypt.....	3-43
3.7.7	get.....	3-44
3.7.8	getActivationTask.....	3-44
3.7.9	invoke	3-45
3.7.10	isRestartRequired.....	3-46
3.7.11	loadDB.....	3-46
3.7.12	loadProperties	3-47
3.7.13	save	3-48
3.7.14	set	3-48
3.7.15	setOption.....	3-49
3.7.16	showChanges	3-51
3.7.17	startEdit	3-51
3.7.18	stopEdit	3-52
3.7.19	unassign	3-53
3.7.20	undo	3-55
3.7.21	validate	3-55
3.8	Information Commands.....	3-56
3.8.1	addListener	3-57
3.8.2	configToScript	3-58
3.8.3	dumpStack	3-59
3.8.4	dumpVariables.....	3-60

3.8.5	find	3-60
3.8.6	getConfigManager	3-61
3.8.7	getMBean	3-62
3.8.8	getMBI	3-62
3.8.9	getPath.....	3-63
3.8.10	listChildTypes	3-63
3.8.11	lookup.....	3-64
3.8.12	ls	3-64
3.8.13	man	3-68
3.8.14	redirect.....	3-68
3.8.15	removeListener.....	3-69
3.8.16	showListeners.....	3-69
3.8.17	startRecording	3-70
3.8.18	state	3-70
3.8.19	stopRecording	3-71
3.8.20	stopRedirect.....	3-72
3.8.21	storeUserConfig	3-72
3.8.22	threadDump	3-74
3.8.23	viewMBean	3-74
3.8.24	writeIniFile.....	3-75
3.9	Life Cycle Commands	3-76
3.9.1	migrate.....	3-76
3.9.2	resume	3-77
3.9.3	shutdown	3-78
3.9.4	start	3-80
3.9.5	startServer	3-81
3.9.6	suspend	3-82
3.10	Node Manager Commands	3-83
3.10.1	nm	3-84
3.10.2	nmConnect.....	3-84
3.10.3	nmDisconnect.....	3-86
3.10.4	nmEnroll.....	3-87
3.10.5	nmGenBootStartupProps.....	3-88
3.10.6	nmKill	3-88
3.10.7	nmLog.....	3-89
3.10.8	nmServerLog	3-90
3.10.9	nmServerStatus	3-90
3.10.10	nmStart	3-91
3.10.11	nmVersion.....	3-92
3.10.12	startNodeManager.....	3-92
3.10.13	stopNodeManager	3-93
3.11	Tree Commands	3-94
3.11.1	custom	3-94
3.11.2	domainConfig.....	3-95
3.11.3	domainCustom.....	3-96
3.11.4	domainRuntime	3-97
3.11.5	edit	3-98

3.11.6	jndi	3-99
3.11.7	serverConfig	3-99
3.11.8	serverRuntime	3-100
3.12	WLST Variable Reference	3-100

4 Infrastructure Security Custom WLST Commands

4.1	Overview of WLST Security Commands	4-1
4.2	Audit Configuration Commands	4-2
4.2.1	getNonJavaEEAuditMBeanName	4-2
4.2.2	getAuditPolicy	4-3
4.2.3	setAuditPolicy	4-4
4.2.4	getAuditRepository	4-6
4.2.5	setAuditRepository	4-6
4.2.6	listAuditEvents	4-7
4.2.7	exportAuditConfig	4-8
4.2.8	importAuditConfig	4-9
4.2.9	createAuditDBView	4-9
4.2.10	listAuditComponents	4-10
4.2.11	registerAudit	4-10
4.2.12	deregisterAudit	4-11
4.3	SSL Configuration Commands	4-11
4.3.1	addCertificateRequest	4-12
4.3.2	addSelfSignedCertificate	4-13
4.3.3	changeKeyStorePassword	4-14
4.3.4	changeWalletPassword	4-14
4.3.5	configureSSL	4-15
4.3.6	createKeyStore	4-16
4.3.7	createWallet	4-16
4.3.8	deleteKeyStore	4-17
4.3.9	deleteWallet	4-17
4.3.10	exportKeyStore	4-18
4.3.11	exportKeyStoreObject	4-18
4.3.12	exportWallet	4-19
4.3.13	exportWalletObject	4-20
4.3.14	generateKey	4-21
4.3.15	getKeyStoreObject	4-22
4.3.16	getSSL	4-23
4.3.17	getWalletObject	4-23
4.3.18	importKeyStore	4-24
4.3.19	importKeyStoreObject	4-25
4.3.20	importWallet	4-26
4.3.21	importWalletObject	4-26
4.3.22	listKeyStoreObjects	4-27
4.3.23	listKeyStores	4-28
4.3.24	listWalletObjects	4-28
4.3.25	listWallets	4-29
4.3.26	removeKeyStoreObject	4-30

4.3.27	removeWalletObject	4-31
4.4	Oracle Identity Federation Commands	4-32
4.4.1	addConfigListEntryInMap	4-34
4.4.2	addConfigMapEntryInMap	4-34
4.4.3	addConfigPropertyListEntry	4-35
4.4.4	addConfigPropertyMapEntry	4-35
4.4.5	addCustomAuthnEngine.....	4-36
4.4.6	addCustomSPEngine	4-36
4.4.7	addFederationListEntryInMap	4-37
4.4.8	addFederationMapEntryInMap	4-38
4.4.9	addFederationPropertyListEntry	4-38
4.4.10	addFederationPropertyMapEntry	4-39
4.4.11	deleteCustomAuthnEngine.....	4-39
4.4.12	deleteCustomSPEngine.....	4-40
4.4.13	deleteProviderFederation	4-40
4.4.14	deleteUserFederation	4-40
4.4.15	changeMessageStore	4-41
4.4.16	changePeerProviderDescription.....	4-41
4.4.17	changeSessionStore.....	4-42
4.4.18	createConfigPropertyList	4-42
4.4.19	createConfigPropertyListInMap.....	4-42
4.4.20	createConfigPropertyMap	4-43
4.4.21	createConfigPropertyMapInMap	4-43
4.4.22	createFederationPropertyList	4-44
4.4.23	createFederationPropertyListInMap.....	4-44
4.4.24	createFederationPropertyMap	4-44
4.4.25	createFederationPropertyMapInMap	4-45
4.4.26	createPeerProviderEntry.....	4-45
4.4.27	getConfigListValueInMap	4-46
4.4.28	getConfigMapEntryInMap	4-46
4.4.29	getConfigProperty	4-47
4.4.30	getConfigPropertyList.....	4-47
4.4.31	getConfigPropertyMapEntry	4-48
4.4.32	getConfigFederationListValueInMap	4-48
4.4.33	getConfigFederationMapEntryInMap	4-48
4.4.34	getConfigFederationProperty	4-49
4.4.35	getConfigFederationPropertyList.....	4-49
4.4.36	extractproviderprops.....	4-50
4.4.37	setproviderprops.....	4-50
4.4.38	getFederationPropertyMapEntry	4-51
4.4.39	listCustomAuthnEngines	4-51
4.4.40	listCustomSPEngines	4-51
4.4.41	loadMetadata.....	4-52
4.4.42	oifStatus.....	4-52
4.4.43	removeConfigListInMap	4-53
4.4.44	removeConfigMapEntryInMap	4-53
4.4.45	removeConfigMapInMap.....	4-54

4.4.46	removeConfigProperty	4-54
4.4.47	removeConfigPropertyList.....	4-55
4.4.48	removeConfigPropertyMap	4-55
4.4.49	removeConfigPropertyMapEntry	4-56
4.4.50	removeFederationListInMap	4-56
4.4.51	removeFederationMapInMap	4-56
4.4.52	removeFederationMapEntryInMap	4-57
4.4.53	removeFederationProperty	4-57
4.4.54	removeFederationPropertyList.....	4-58
4.4.55	removeFederationPropertyMap	4-58
4.4.56	removeFederationPropertyMapEntry	4-59
4.4.57	removePeerProviderEntry.....	4-59
4.4.58	setConfigProperty.....	4-59
4.4.59	setCustomAuthnEngine.....	4-60
4.4.60	setCustomSPEngine	4-60
4.4.61	setFederationProperty.....	4-61
4.5	Directory Integration Platform Commands.....	4-61
4.6	Security Commands	4-62
4.6.1	createAppRole	4-63
4.6.2	deleteAppRole.....	4-63
4.6.3	grantAppRole.....	4-64
4.6.4	revokeAppRole	4-64
4.6.5	listAppRoles	4-65
4.6.6	listAppRolesMembers.....	4-65
4.6.7	grantPermission	4-66
4.6.8	revokePermission.....	4-67
4.6.9	listPermissions.....	4-67
4.6.10	deleteAppPolicies	4-68
4.6.11	migrateSecurityStore	4-68
4.6.12	updateCred	4-72
4.6.13	createCred	4-72
4.6.14	deleteCred	4-73
4.6.15	modifyBootStrapCredential	4-73
4.6.16	addBootStrapCredential	4-74
4.6.17	exportEncryptionKey	4-74
4.6.18	importEncryptionKey	4-75
4.6.19	restoreEncryptionKey	4-76
4.6.20	rollOverEncryptionKey	4-76
4.6.21	reassociateSecurityStore	4-77
4.6.22	upgradeSecurityStore.....	4-78
4.6.23	createResourceType.....	4-79
4.6.24	getResourceType.....	4-80
4.6.25	deleteResourceType	4-80
4.6.26	listSecurityStoreInfo	4-81
4.6.27	listAppStripes.....	4-81
4.6.28	listCodeSourcePermissions	4-82
4.6.29	createResource.....	4-82

4.6.30	deleteResource	4-83
4.6.31	listResources	4-83
4.6.32	listResourceActions	4-84
4.6.33	createEntitlement	4-84
4.6.34	getEntitlement	4-85
4.6.35	deleteEntitlement	4-85
4.6.36	addResourceToEntitlement	4-86
4.6.37	revokeResourceFromEntitlement	4-87
4.6.38	listEntitlements	4-87
4.6.39	grantEntitlement	4-88
4.6.40	revokeEntitlement	4-88
4.6.41	listResourceTypes	4-89
4.6.42	updateTrustServiceConfig	4-89
4.7	Oracle Access Manager Commands	4-90
4.7.1	listOAMAuthnProviderParams	4-92
4.7.2	createOAMIdentityAsserter	4-93
4.7.3	updateOAMIdentityAsserter	4-93
4.7.4	createOAMAuthenticator	4-94
4.7.5	deleteOAMAuthnProvider	4-95
4.7.6	updateOAMAuthenticator	4-95
4.7.7	addOAMSSOProvider	4-96
4.7.8	displayTopology	4-97
4.7.9	displayMetrics	4-98
4.7.10	displayOamServer	4-98
4.7.11	createOamServer	4-98
4.7.12	editOamServer	4-99
4.7.13	deleteOamServer	4-100
4.7.14	displayOssoAgent	4-101
4.7.15	editOssoAgent	4-101
4.7.16	deleteOssoAgent	4-102
4.7.17	displayWebgateAgent	4-103
4.7.18	editWebgateAgent	4-103
4.7.19	deleteWebgateAgent	4-105
4.7.20	changeLoggerSetting	4-105
4.7.21	changeConfigDataEncryptionKey	4-106
4.7.22	displayUserIdentityStore	4-106
4.7.23	editUserIdentityStore	4-107
4.7.24	createUserIdentityStore	4-108
4.7.25	deleteUserIdentityStore	4-109
4.7.26	configRequestCacheType	4-110
4.7.27	displayRequestCacheType	4-110
4.7.28	exportPolicy	4-111
4.7.29	importPolicy	4-111
4.7.30	importPolicyDelta	4-112
4.7.31	migratePartnersToProd	4-112
4.7.32	exportPartners	4-113
4.7.33	importPartners	4-113

4.7.34	configureOAAM	4-114
4.7.35	registerOIFDAPPartner	4-114
4.7.36	enableCoexistMode	4-115
4.7.37	disableCoexistMode	4-115
4.7.38	editGITOValues	4-116
4.7.39	editWebgate11gAgent.....	4-117
4.7.40	deleteWebgate11gAgent	4-118
4.7.41	displayWebgate11gAgent	4-119
4.7.42	displayOAMMetrics	4-119
4.7.43	updateOIMHostPort.....	4-120
4.7.44	configureOIM	4-120
4.7.45	updateOSSOResponseCookieConfig.....	4-121
4.7.46	deleteOSSOResponseCookieConfig.....	4-122
4.7.47	displaySimpleModeGlobalPassphrase	4-122
4.7.48	exportSelectedPartners	4-122
4.7.49	migrateArtifacts	4-123
4.7.50	registerThirdPartyTAPPartner	4-123
4.8	Oracle Security Token Service.....	4-124
4.8.1	getPartner.....	4-126
4.8.2	getAllRequesterPartners	4-127
4.8.3	getAllRelyingPartyPartners	4-127
4.8.4	getAllIssuingAuthorityPartners	4-127
4.8.5	isPartnerPresent	4-128
4.8.6	createPartner.....	4-128
4.8.7	updatePartner.....	4-129
4.8.8	deletePartner	4-129
4.8.9	getPartnerUsernameTokenUsername	4-130
4.8.10	getPartnerUsernameTokenPassword	4-130
4.8.11	setPartnerUsernameTokenCredential	4-131
4.8.12	deletePartnerUsernameTokenCredential.....	4-131
4.8.13	getPartnerSigningCert.....	4-132
4.8.14	getPartnerEncryptionCert	4-132
4.8.15	setPartnerSigningCert	4-133
4.8.16	setPartnerEncryptionCert.....	4-133
4.8.17	deletePartnerSigningCert	4-134
4.8.18	deletePartnerEncryptionCert	4-134
4.8.19	getPartnerAllIdentityAttributes	4-134
4.8.20	getPartnerIdentityAttribute	4-135
4.8.21	setPartnerIdentityAttribute	4-135
4.8.22	deletePartnerIdentityAttribute	4-136
4.8.23	getAllWSPrefixAndPartnerMappings.....	4-137
4.8.24	getWSPrefixAndPartnerMapping	4-137
4.8.25	createWSPrefixAndPartnerMapping	4-137
4.8.26	deleteWSPrefixAndPartnerMapping.....	4-138
4.8.27	getAllPartnerProfiles.....	4-138
4.8.28	getPartnerProfile	4-139
4.8.29	createRequesterPartnerProfile	4-139

4.8.30	createRelyingPartyPartnerProfile.....	4-141
4.8.31	createIssuingAuthorityPartnerProfile	4-142
4.8.32	deletePartnerProfile.....	4-143
4.8.33	getAllIssuanceTemplates.....	4-143
4.8.34	getIssuanceTemplate	4-144
4.8.35	createIssuanceTemplate	4-144
4.8.36	deleteIssuanceTemplate.....	4-146
4.8.37	getAllValidationTemplates	4-146
4.8.38	getValidationTemplate	4-146
4.8.39	createWSSValidationTemplate	4-147
4.8.40	createWSTrustValidationTemplate.....	4-150
4.8.41	deleteValidationTemplate	4-152
4.9	Oracle Keystore Service	4-153
4.9.1	changeKeyPassword	4-154
4.9.2	changeKeyStorePassword	4-154
4.9.3	createKeyStore.....	4-155
4.9.4	deleteKeyStore	4-155
4.9.5	deleteKeyStoreEntry.....	4-156
4.9.6	exportKeyStore.....	4-156
4.9.7	exportKeyStoreCertificate	4-157
4.9.8	exportKeyStoreCertificateRequest	4-158
4.9.9	generateKeyPair.....	4-158
4.9.10	generateSecretKey	4-159
4.9.11	getKeyStoreCertificates.....	4-160
4.9.12	getKeyStoreSecretKeyProperties.....	4-160
4.9.13	importKeyStore	4-161
4.9.14	importKeyStoreCertificate.....	4-161
4.9.15	listExpiringCertificates.....	4-162
4.9.16	listKeyStoreAliases	4-163
4.9.17	listKeyStores	4-163

5 User Messaging Service (UMS) Custom WLST Commands

5.1	UMS WLST Command Group.....	5-1
5.1.1	manageUserMessagingPrefs.....	5-1
5.1.2	deployUserMessagingDriver	5-3

6 DMS Custom WLST Commands

6.1	DMS Metric Commands	6-1
6.1.1	displayMetricTableNames	6-2
6.1.2	displayMetricTables	6-3
6.1.3	dumpMetrics	6-6
6.1.4	reloadMetricRules.....	6-8
6.2	DMS Event Tracing Commands	6-9
6.2.1	addDMSEventDestination.....	6-10
6.2.2	addDMSEventFilter	6-11
6.2.3	addDMSEventRoute.....	6-14

6.2.4	enableDMSEventTrace.....	6-15
6.2.5	listDMSEventConfiguration.....	6-16
6.2.6	listDMSEventDestination	6-16
6.2.7	listDMSEventFilter	6-17
6.2.8	listDMSEventRoutes.....	6-18
6.2.9	removeDMSEventDestination	6-19
6.2.10	removeDMSEventFilter	6-19
6.2.11	removeDMSEventRoute	6-20
6.2.12	updateDMSEventDestination	6-21
6.2.13	updateDMSEventFilter	6-22
6.2.14	updateDMSEventRoute	6-22

7 Logging Custom WLST Commands

7.1	Log Configuration Commands.....	7-1
7.1.1	configureLogHandler.....	7-2
7.1.2	getLogLevel	7-6
7.1.3	listLoggers.....	7-7
7.1.4	listLogHandlers.....	7-8
7.1.5	setLogLevel.....	7-8
7.2	Search and Display Commands.....	7-10
7.2.1	displayLogs.....	7-10
7.2.2	listLogs	7-12
7.3	Selective Tracing Commands.....	7-13
7.3.1	configureTracingLoggers.....	7-14
7.3.2	listActiveTraces	7-14
7.3.3	listTracingLoggers	7-15
7.3.4	startTracing.....	7-16
7.3.5	stopTracing	7-16

8 Metadata Services (MDS) Custom WLST Commands

8.1	Repository Management Commands	8-1
8.1.1	createMetadataPartition.....	8-2
8.1.2	deleteMetadataPartition	8-2
8.1.3	deregisterMetadataDBRepository	8-3
8.1.4	registerMetadataDBRepository	8-3
8.2	Application Metadata Management Commands.....	8-4
8.2.1	deleteMetadata	8-4
8.2.2	exportMetadata	8-7
8.2.3	importMetadata	8-9
8.2.4	purgeMetadata	8-12
8.3	Sandbox Metadata Management Commands.....	8-12
8.3.1	exportSandboxMetadata.....	8-13
8.3.2	importSandboxMetadata	8-14
8.4	Application Label Management Commands.....	8-15
8.4.1	createMetadataLabel	8-16
8.4.2	deleteMetadataLabel	8-16
8.4.3	listMetadataLabels.....	8-17

8.4.4	promoteMetadataLabel.....	8-18
8.4.5	purgeMetadataLabels.....	8-18
8.5	Application Management Deployment Commands.....	8-20
8.5.1	getMDSArchiveConfig.....	8-20
8.5.2	importMAR.....	8-22
8.6	Multitenancy Management Commands.....	8-23
8.6.1	deprovisionTenant.....	8-23
8.6.2	listTenants.....	8-23

9 Oracle SOA Suite Custom WLSLT Commands

9.1	Overview of WLSLT Command Categories.....	9-1
9.2	Deployment Commands.....	9-2
9.2.1	sca_deployComposite.....	9-2
9.2.2	sca_undeployComposite.....	9-4
9.3	SOA Composite Application Management Commands.....	9-5
9.3.1	sca_startComposite.....	9-6
9.3.2	sca_stopComposite.....	9-7
9.3.3	sca_activateComposite.....	9-7
9.3.4	sca_retireComposite.....	9-8
9.3.5	sca_assignDefaultComposite.....	9-9
9.3.6	sca_getDefaultCompositeRevision.....	9-10
9.3.7	sca_listDeployedComposites.....	9-11
9.3.8	sca_listCompositesFailedInServerStart.....	9-11
9.4	SOA Composite Application Compilation Commands.....	9-12
9.4.1	sca_setProp.....	9-12
9.4.2	sca_compile.....	9-12
9.5	SOA Composite Application Packaging Commands.....	9-13
9.5.1	sca_package.....	9-14
9.6	SOA Composite Application Test Commands.....	9-15
9.6.1	sca_test.....	9-15
9.7	SOA Composite Application HTTP Client-Based Export and Import Commands.....	9-15
9.7.1	sca_exportComposite.....	9-16
9.7.2	sca_exportUpdates.....	9-17
9.7.3	sca_importUpdates.....	9-18
9.7.4	sca_exportSharedData.....	9-19
9.7.5	sca_removeSharedData.....	9-20
9.8	SOA Composite Application MBean-Based Export and Import Commands.....	9-21
9.8.1	sca_exportCompositeMb.....	9-21
9.8.2	sca_exportUpdatesMb.....	9-22
9.8.3	sca_importUpdatesMb.....	9-23
9.8.4	sca_exportSharedDataMb.....	9-23
9.9	SOA Composite Application Partition Management Commands.....	9-24
9.9.1	sca_createPartition.....	9-24
9.9.2	sca_deletePartition.....	9-25
9.9.3	sca_startCompositesInPartition.....	9-25
9.9.4	sca_stopCompositesInPartition.....	9-26
9.9.5	sca_activateCompositesInPartition.....	9-26

9.9.6	sca_retireCompositesInPartition	9-26
9.9.7	sca_listPartitions	9-27
9.9.8	sca_listCompositesInPartition	9-27
9.10	SOA Composite Application Preconfigured WLDF Watches Command	9-28
9.10.1	sca_createWatches	9-28
9.11	Configuration Plan Management Commands.....	9-28
9.11.1	sca_attachPlan	9-29
9.11.2	sca_extractPlan	9-29
9.11.3	sca_generatePlan.....	9-30
9.11.4	sca_validatePlan.....	9-31
9.12	Task Validation Commands	9-32
9.12.1	sca_validateTask	9-32

10 WebCenter Portal Custom WLST Commands

10.1	Overview of Oracle WebCenter Portal WLST Command Categories	10-2
10.2	General.....	10-3
10.2.1	deleteConnection	10-3
10.2.2	setWebCenterServiceFrameworkConfig	10-4
10.2.3	getWebCenterServiceFrameworkConfig	10-5
10.2.4	webcenterErrorOccurred	10-6
10.2.5	getWebCenterConnectionTypes.....	10-7
10.3	Analytics.....	10-7
10.3.1	createAnalyticsCollectorConnection.....	10-8
10.3.2	setAnalyticsCollectorConnection	10-10
10.3.3	listAnalyticsCollectorConnections	10-11
10.3.4	setDefaultAnalyticsCollectorConnection	10-12
10.3.5	listDefaultAnalyticsCollectorConnection	10-13
10.3.6	setAnalyticsCollectorConfig	10-14
10.3.7	listAnalyticsCollectorConfig.....	10-15
10.3.8	listAnalyticsEventTypes	10-16
10.4	Activity Graph.....	10-17
10.4.1	exportAGMetadata	10-18
10.4.2	importAGMetadata	10-18
10.4.3	exportAGProviderConfiguration	10-19
10.4.4	deleteAllAGMetadata	10-20
10.4.5	deleteAGAction.....	10-21
10.4.6	deleteAGNodeClass	10-21
10.4.7	deleteAGSimilarityCalculation	10-22
10.4.8	deleteAGRANKCalculation	10-23
10.4.9	deleteAGProviderAssignment	10-23
10.4.10	deleteAGQRPPRegistration	10-24
10.4.11	deleteAGProviderConfiguration.....	10-25
10.4.12	renameAGAction	10-25
10.4.13	renameAGNodeClass.....	10-26
10.4.14	setAGProperty.....	10-27
10.4.15	getAGProperty	10-28
10.4.16	setAGPasswordCredential	10-28

10.5	Activity Stream.....	10-29
10.5.1	archiveASByDate	10-30
10.5.2	archiveASByDeletedObjects.....	10-31
10.5.3	archiveASByClosedSpaces	10-31
10.5.4	archiveASByInactiveSpaces	10-32
10.5.5	restoreASByDate.....	10-33
10.5.6	truncateASArchive	10-33
10.5.7	archiveASBySpace	10-34
10.5.8	archiveASAllSpaces.....	10-35
10.5.9	archiveASByUser	10-35
10.5.10	archiveASAllUsers.....	10-36
10.5.11	archiveASByDeletedActors	10-37
10.5.12	showASStatistics	10-37
10.6	Content Repository	10-39
10.6.1	createJCRContentServerConnection	10-40
10.6.2	setJCRContentServerConnection.....	10-44
10.6.3	listJCRContentServerConnections	10-48
10.6.4	createJCRPortalConnection	10-49
10.6.5	setJCRPortalConnection	10-50
10.6.6	listJCRPortalConnections	10-51
10.6.7	createJCRFileSystemConnection	10-52
10.6.8	setJCRFileSystemConnection.....	10-53
10.6.9	listJCRFileSystemConnections	10-54
10.6.10	createJCRSharePointConnection	10-55
10.6.11	setJCRSharePointConnection.....	10-57
10.6.12	listJCRSharePointConnections.....	10-58
10.6.13	listDocumentsSpacesProperties.....	10-59
10.6.14	setDocumentsSpacesProperties	10-60
10.6.15	deleteDocumentsSpacesProperties	10-61
10.7	Discussions and Announcements	10-62
10.7.1	createDiscussionForumConnection	10-63
10.7.2	setDiscussionForumConnection	10-65
10.7.3	setDiscussionForumConnectionProperty	10-68
10.7.4	deleteDiscussionForumConnectionProperty	10-69
10.7.5	listDiscussionForumConnections	10-70
10.7.6	listDefaultDiscussionForumConnection	10-71
10.7.7	setDefaultDiscussionForumConnection.....	10-72
10.7.8	setDiscussionForumServiceProperty	10-73
10.7.9	removeDiscussionForumServiceProperty	10-74
10.7.10	listDiscussionForumServiceProperties	10-75
10.7.11	setAnnouncementServiceProperty.....	10-76
10.7.12	removeAnnouncementServiceProperty	10-76
10.7.13	listAnnouncementServiceProperties.....	10-77
10.7.14	addDiscussionsServerAdmin.....	10-78
10.7.15	addDiscussionsCategoryAdmin.....	10-79
10.7.16	syncDiscussionServerPermissions	10-79
10.7.17	setDiscussionsServerProperty	10-80

10.7.18	getDiscussionsServerProperty	10-81
10.7.19	removeDiscussionsServerProperty	10-82
10.8	External Applications	10-83
10.8.1	createExtAppConnection.....	10-83
10.8.2	setExtAppConnection	10-85
10.8.3	listExtAppConnections	10-86
10.8.4	addExtAppField.....	10-87
10.8.5	setExtAppField.....	10-88
10.8.6	removeExtAppField	10-89
10.8.7	addExtAppCredential	10-90
10.8.8	setExtAppCredential	10-91
10.8.9	removeExtAppCredential	10-92
10.9	Instant Messaging and Presence	10-93
10.9.1	createIMPConnection	10-94
10.9.2	setIMPConnection	10-96
10.9.3	setIMPConnectionProperty	10-98
10.9.4	deleteIMPConnectionProperty	10-99
10.9.5	listIMPAdapters	10-100
10.9.6	listIMPConnections	10-101
10.9.7	listDefaultIMPConnection.....	10-102
10.9.8	setDefaultIMPConnection	10-102
10.9.9	setIMPServiceProperty	10-103
10.9.10	removeIMPServiceProperty	10-105
10.9.11	listIMPServiceProperties.....	10-105
10.9.12	createIMPExtAppConnection	10-106
10.10	Mail	10-107
10.10.1	createMailConnection	10-108
10.10.2	setMailConnection	10-110
10.10.3	setMailConnectionProperty	10-112
10.10.4	deleteMailConnectionProperty	10-114
10.10.5	listMailConnections	10-114
10.10.6	listDefaultMailConnection	10-115
10.10.7	setDefaultMailConnection.....	10-116
10.10.8	setMailServiceProperty	10-117
10.10.9	removeMailServiceProperty	10-119
10.10.10	listMailServiceProperties	10-119
10.10.11	createMailExtApp	10-120
10.11	Notifications.....	10-121
10.11.1	setNotificationsConfig	10-121
10.11.2	getNotificationsConfig.....	10-123
10.12	People Connections	10-123
10.12.1	startSyncProfiles.....	10-124
10.12.2	stopSyncProfiles.....	10-125
10.12.3	isSyncProfilesRunning	10-125
10.12.4	syncProfile	10-126
10.12.5	setProfileConfig.....	10-126
10.12.6	getProfileConfig.....	10-128

10.12.7	listProfileConfig	10-128
10.12.8	setProfileCacheNumberOfObjects	10-129
10.12.9	setProfileSyncLDAPReadBatchSize	10-130
10.12.10	setProfileCacheTimeToLive	10-130
10.12.11	setProfilePhotoSync	10-131
10.12.12	printProfileConfig	10-132
10.13	Personal Events	10-133
10.13.1	createPersonalEventConnection	10-133
10.13.2	setPersonalEventConnection	10-134
10.13.3	listPersonalEventConnections	10-135
10.14	Personalization	10-136
10.14.1	createWCPSCMISConnection	10-137
10.14.2	createWCPSActivityGraphConnection	10-139
10.14.3	createWCPSPeopleConnection	10-140
10.14.4	createWCPSCustomConnection	10-141
10.14.5	listWCPSCMISConnection	10-141
10.14.6	listWCPSActivityGraphConnection	10-142
10.14.7	listWCPSPeopleConnection	10-143
10.14.8	listWCPSCustomConnection	10-144
10.14.9	deleteWCPSCMISConnection	10-145
10.14.10	deleteWCPSActivityGraphConnection	10-146
10.14.11	deleteWCPSPeopleConnection	10-146
10.14.12	deleteWCPSCustomConnection	10-147
10.14.13	setWCPSConnectionProperty	10-148
10.15	Portlet Producers	10-149
10.15.1	registerWSRPProducer	10-150
10.15.2	setWSRPProducer	10-154
10.15.3	listWSRPProducers	10-158
10.15.4	deregisterWSRPProducer	10-160
10.15.5	listWSRPProducerRegistrationProperties	10-160
10.15.6	listWSRPProducerUserCategories	10-161
10.15.7	mapWSRPProducerUserCategory	10-162
10.15.8	registerPDKJavaProducer	10-163
10.15.9	setPDKJavaProducer	10-165
10.15.10	deregisterPDKJavaProducer	10-167
10.15.11	listPDKJavaProducers	10-168
10.15.12	registerPageletProducer	10-169
10.15.13	setPageletProducer	10-170
10.15.14	listPageletProducers	10-171
10.15.15	deregisterPageletProducer	10-172
10.15.16	refreshProducer	10-173
10.15.17	listPortletClientConfig	10-174
10.15.18	setPortletClientConfig	10-174
10.15.19	getPortletClientConfig	10-176
10.15.20	registerOOTBProducers	10-177
10.15.21	deregisterOOTBProducers	10-179
10.15.22	registerSampleProducers	10-179

10.15.23	deregisterSampleProducers	10-180
10.16	Proxy Server.....	10-181
10.16.1	getWebCenterProxyConfig	10-181
10.16.2	setWebCenterProxyConfig.....	10-182
10.16.3	unsetWebCenterProxyConfig.....	10-183
10.16.4	getRssProxyConfig	10-183
10.16.5	setRssProxyConfig.....	10-184
10.16.6	unsetRssProxyConfig.....	10-185
10.17	Search - Oracle SES Search.....	10-185
10.17.1	createSESConnection.....	10-186
10.17.2	setSESConnection	10-187
10.17.3	listSESConnections	10-188
10.17.4	setSearchSESConfig.....	10-189
10.17.5	listSearchSESConfig.....	10-190
10.17.6	createFederationTrustedEntity	10-191
10.17.7	setSESVersion.....	10-192
10.17.8	listSESVersion.....	10-192
10.17.9	createDefaultSourceGroup	10-193
10.18	Search - Oracle SES Search Crawlers	10-194
10.18.1	createSpacesCrawler	10-195
10.18.2	createDocumentsCrawler	10-198
10.18.3	createDiscussionsCrawler	10-200
10.18.4	listSpacesCrawler.....	10-203
10.18.5	listDocumentsCrawler	10-204
10.18.6	listDiscussionsCrawler.....	10-205
10.18.7	startSpacesCrawler	10-206
10.18.8	startDocumentsCrawler.....	10-207
10.18.9	startDiscussionsCrawler	10-208
10.18.10	stopSpacesCrawler	10-209
10.18.11	stopDocumentsCrawler	10-209
10.18.12	stopDiscussionsCrawler	10-210
10.18.13	deleteSpacesCrawler	10-211
10.18.14	deleteDocumentsCrawler.....	10-212
10.18.15	deleteDiscussionsCrawler	10-213
10.19	Search - WebCenter Portal Search	10-214
10.19.1	setSearchConfig.....	10-214
10.19.2	listSearchConfig	10-215
10.19.3	setSpacesCrawlProperties	10-216
10.19.4	getSpacesCrawlProperties.....	10-217
10.20	Worklists	10-218
10.20.1	createBPELConnection.....	10-219
10.20.2	setBPELConnection	10-220
10.20.3	listBPELConnections	10-222
10.20.4	addWorklistConnection.....	10-223
10.20.5	removeWorklistConnection	10-224
10.20.6	listWorklistConnections.....	10-225
10.21	WebCenter Portal Application.....	10-226

10.21.1	getSpacesWorkflowConnectionName	10-227
10.21.2	setSpacesWorkflowConnectionName	10-227
10.21.3	refreshGroupSpaceCache	10-228
10.21.4	refreshSpaceTemplateCache	10-230
10.22	Identity Store	10-232
10.22.1	setWebCenterIdStoreSearchConfig.....	10-232
10.22.2	listWebCenterIdStoreSearchConfig	10-233
10.23	Lifecycle.....	10-234
10.23.1	deployWebCenterPortal	10-236
10.23.2	propagateWebCenterPortal.....	10-239
10.23.3	exportWebCenterPortals	10-241
10.23.4	exportWebCenterPortalTemplates.....	10-243
10.23.5	importWebCenterPortals.....	10-245
10.23.6	listWebCenterPortalArchive	10-248
10.23.7	exportWebCenterPortalChanges.....	10-249
10.23.8	importWebCenterPortalChanges	10-250
10.23.9	exportWebCenterPortalConnections	10-251
10.23.10	importWebCenterPortalConnections	10-254
10.23.11	setSpaceState.....	10-256
10.23.12	exportWebCenterResource.....	10-257
10.23.13	importWebCenterResource	10-259
10.23.14	importWebCenterTranslations	10-261
10.23.15	exportWebCenterApplication.....	10-262
10.23.16	importWebCenterApplication	10-263
10.23.17	exportPortletClientMetadata	10-264
10.23.18	importPortletClientMetadata.....	10-265
10.23.19	showProducerImportFailures	10-265
10.23.20	retryAllFailedProducerImports	10-266
10.23.21	cloneWebCenterManagedServer.....	10-267
10.23.22	exportGroupSpaces (Deprecated)	10-268
10.23.23	exportGroupSpaceTemplates (Deprecated).....	10-269
10.23.24	importGroupSpaces (Deprecated).....	10-270
10.24	Upgrade.....	10-272
10.24.1	upgradeWebCenterDomain.....	10-273
10.24.2	upgradeWebCenterPermissions.....	10-273
10.24.3	upgradeWebCenterApplication	10-274

11 Application Development Framework (ADF) Custom WLST Commands

11.1	Overview of WLST Command Categories.....	11-1
11.2	ADF-Specific WLST Commands.....	11-1
11.2.1	adf_createFileUrlConnection	11-2
11.2.2	adf_createHttpUrlConnection	11-2
11.2.3	adf_setURLConnectionAttributes	11-3
11.2.4	adf_listUrlConnection	11-3
11.2.5	getADFMArchiveConfig	11-4
11.2.6	exportJarVersions	11-6
11.2.7	exportApplicationJarVersions	11-6

11.2.8	exportApplicationSelectedJarVersions	11-7
11.2.9	createWebServiceConnection.....	11-8
11.2.10	listWebServiceConnection.....	11-8
11.2.11	deleteWebServiceConnection	11-9

12 Portal Custom WLST Commands

12.1	Database Access Descriptor Commands	12-1
12.1.1	listDads.....	12-2
12.1.2	createPortalDad.....	12-2
12.1.3	updatePortalDad.....	12-3
12.1.4	deletePortalDad	12-4
12.2	Configuration Commands.....	12-4
12.2.1	configurePortalCache	12-5
12.2.2	configurePortalPageEngine.....	12-5
12.2.3	listPortalWebcacheConfigAttributes	12-7
12.2.4	listPortalSiteConfigAttributes.....	12-7
12.2.5	listPortalOIDConfigAttributes.....	12-8
12.2.6	setPortalWebcacheConfig.....	12-8
12.2.7	setPortalOIDConfig	12-9
12.2.8	setPortalMidtierConfig	12-9

13 Java Required Files Custom WLST Commands

13.1	Java Required Files Commands.....	13-1
13.1.1	applyJRF.....	13-2
13.1.2	cloneDeployments	13-2

14 Web Services Custom WLST Commands

14.1	Overview of Web Services WLST Commands	14-1
14.1.1	Specifying Application, Composite, and Service Names	14-2
14.1.2	Web Services WLST Command Categories	14-3
14.2	Web Service and Client Management Commands	14-4
14.2.1	listWebServices	14-5
14.2.2	listWebServicePorts	14-7
14.2.3	listWebServiceConfiguration	14-8
14.2.4	setWebServiceConfiguration	14-10
14.2.5	listWebServiceClients.....	14-11
14.2.6	listWebServiceClientPorts	14-14
14.2.7	listWebServiceClientStubProperties	14-15
14.2.8	setWebServiceClientStubProperty	14-16
14.2.9	setWebServiceClientStubProperties.....	14-17
14.3	Policy Management Commands.....	14-19
14.3.1	listAvailableWebServicePolicies.....	14-20
14.3.2	listWebServicePolicies.....	14-20
14.3.3	attachWebServicePolicy	14-21
14.3.4	attachWebServicePolicies	14-23
14.3.5	enableWebServicePolicy	14-25

14.3.6	enableWebServicePolicies	14-27
14.3.7	detachWebServicePolicy	14-29
14.3.8	detachWebServicePolicies	14-30
14.3.9	listWebServiceClientPolicies	14-32
14.3.10	attachWebServiceClientPolicy	14-33
14.3.11	attachWebServiceClientPolicies.....	14-34
14.3.12	enableWebServiceClientPolicy	14-36
14.3.13	enableWebServiceClientPolicies.....	14-38
14.3.14	detachWebServiceClientPolicy	14-39
14.3.15	detachWebServiceClientPolicies	14-41
14.3.16	setWebServicePolicyOverride.....	14-42
14.4	Policy Set Management Commands	14-44
14.4.1	abortRepositorySession.....	14-45
14.4.2	attachPolicySet	14-45
14.4.3	attachPolicySetPolicy	14-46
14.4.4	beginRepositorySession	14-47
14.4.5	clonePolicySet.....	14-47
14.4.6	commitRepositorySession	14-48
14.4.7	createPolicySet.....	14-49
14.4.8	deleteAllPolicySets	14-50
14.4.9	deletePolicySet	14-51
14.4.10	describeRepositorySession	14-51
14.4.11	detachPolicySetPolicy	14-52
14.4.12	displayPolicySet.....	14-52
14.4.13	enablePolicySet	14-53
14.4.14	enablePolicySetPolicy.....	14-54
14.4.15	listPolicySets	14-54
14.4.16	migrateAttachments	14-55
14.4.17	modifyPolicySet	14-56
14.4.18	setPolicySetConstraint	14-57
14.4.19	setPolicySetDescription	14-58
14.4.20	setPolicySetPolicyOverride	14-58
14.4.21	validatePolicySet.....	14-59
14.5	Oracle WSM Repository Management Commands.....	14-60
14.5.1	upgradeWSMPolicyRepository	14-60
14.5.2	resetWSMPolicyRepository	14-61
14.5.3	exportRepository	14-62
14.5.4	importRepository.....	14-63
14.6	Deployment Descriptor Migration Commands	14-64
14.6.1	exportJRFWSApplicationPDD.....	14-65
14.6.2	importJRFWSApplicationPDD	14-65
14.6.3	savePddToAllAppInstancesInDomain.....	14-66
14.7	Token Issuer Trust Configuration Commands.....	14-67
14.7.1	deleteWSMTokenIssuerTrust.....	14-68
14.7.2	deleteWSMTokenIssuerTrustAttributeRule	14-68
14.7.3	displayWSMTokenIssuerTrust	14-69
14.7.4	setWSMTokenIssuerTrust	14-70

14.7.5	setWSMTokenIssuerTrustAttributeFilter.....	14-71
14.8	Diagnostic Commands.....	14-72
14.8.1	checkWSMStatus.....	14-72

15 Diagnostic Framework Custom WLST Commands

15.1	Incident Commands.....	15-1
15.1.1	createIncident.....	15-2
15.1.2	getIncidentFile.....	15-3
15.1.3	listADRHomes.....	15-3
15.1.4	listIncidents.....	15-4
15.1.5	listProblems.....	15-4
15.1.6	reloadCustomRules.....	15-5
15.1.7	showIncident.....	15-5
15.2	Diagnostic Dump Commands.....	15-6
15.2.1	describeDump.....	15-6
15.2.2	executeDump.....	15-7
15.2.3	listDumps.....	15-8
15.3	Dump Sampling Commands.....	15-9
15.3.1	addDumpSample.....	15-9
15.3.2	enableDumpSampling.....	15-10
15.3.3	getSamplingArchives.....	15-11
15.3.4	isDumpSamplingEnabled.....	15-11
15.3.5	listDumpSamples.....	15-12
15.3.6	removeDumpSample.....	15-13
15.3.7	updateDumpSample.....	15-13

16 Information Rights Management Custom WLST Commands

16.1	Overview of WLST IRM Commands.....	16-1
16.2	General Server Commands.....	16-2
16.2.1	addIRMRefreshPeriod.....	16-2
16.2.2	getIRMRefreshPeriod.....	16-3
16.2.3	getIRMRefreshPeriods.....	16-3
16.2.4	removeIRMRefreshPeriod.....	16-4
16.2.5	updateIRMRefreshPeriod.....	16-4
16.2.6	addIRMSyncWindow.....	16-5
16.2.7	getIRMSyncWindow.....	16-5
16.2.8	getIRMSyncWindows.....	16-5
16.2.9	removeIRMSyncWindow.....	16-6
16.2.10	updateIRMSyncWindow.....	16-6
16.2.11	getIRMCryptoSchema.....	16-7
16.2.12	setIRMCryptoSchema.....	16-7
16.2.13	getIRMDeviceCount.....	16-7
16.2.14	setIRMDeviceCount.....	16-8
16.2.15	getIRMJournalCleanUp.....	16-8
16.2.16	setIRMJournalCleanUp.....	16-8
16.2.17	getIRMLicenseStateCleanUp.....	16-9
16.2.18	setIRMLicenseStateCleanUp.....	16-9

16.2.19	getIRMPrivacyURL	16-10
16.2.20	setIRMPrivacyURL	16-10
16.2.21	getIRMKeyStore	16-11
16.2.22	setIRMKeyStore	16-11
16.3	Migration Commands	16-11
16.3.1	setIRMExportFolder	16-12
16.3.2	getIRMExportFolder.....	16-12
16.3.3	setIRMImportFolder.....	16-12
16.3.4	getIRMImportFolder	16-13
16.4	Test Content Commands	16-13
16.4.1	addIRMTTestContent	16-13
16.4.2	getIRMTTestContent	16-14
16.4.3	getIRMTTestContents	16-15
16.4.4	removeIRMTTestContent.....	16-15
16.4.5	updateIRMTTestContent	16-16
16.5	Languages Support Commands	16-16
16.5.1	addIRMTranslation	16-17
16.5.2	getIRMDefaultTranslation	16-17
16.5.3	getIRMTranslations	16-18
16.5.4	removeIRMTranslation	16-18
16.5.5	setIRMTranslations	16-18
16.6	Oracle IRM Desktop Installers Commands.....	16-19
16.6.1	addIRMDownload.....	16-19
16.6.2	getIRMDownload	16-20
16.6.3	getIRMDownloads.....	16-20
16.6.4	removeIRMDownload	16-21
16.6.5	updateIRMDownload	16-21

17 Oracle WebCenter: Imaging Custom WLST Commands

17.1	Overview of Imaging WLST Command Categories.....	17-1
17.2	Diagnostic Commands	17-1
17.2.1	clearIPMWorkflowFaults	17-2
17.2.2	listIPMWorkflowFaults.....	17-2
17.2.3	repairIPMWorkflowFaults	17-3
17.2.4	sumIPMWorkflowFaults	17-3
17.2.5	resetIpmDMSMetrics	17-4
17.3	Imaging Configuration Commands	17-4
17.3.1	createIPMConnection.....	17-5
17.3.2	getIPMConfig	17-6
17.3.3	grantIPMCredAccess.....	17-6
17.3.4	importIPMApplication.....	17-7
17.3.5	importIPMInput.....	17-8
17.3.6	importIPMSearch.....	17-10
17.3.7	listIPMConfig	17-11
17.3.8	listIPMExportFile	17-11
17.3.9	refreshIPMSecurity	17-11
17.3.10	setIPMConfig.....	17-12

17.3.11	submitIPMToWorkflow	17-12
---------	---------------------------	-------

18 Oracle Business Process Management Custom WLST Commands

18.1	BPMLifecycleAdmin Command Group	18-1
18.1.1	create_public_share	18-2
18.1.2	unlock_public_share.....	18-2
18.1.3	export_public_share	18-3
18.1.4	delete_public_share	18-4
18.1.5	publish_template	18-5
18.1.6	export_template	18-5
18.1.7	delete_template	18-6
18.1.8	connectProjectRepository	18-7
18.1.9	disconnectProjectRepository	18-7
18.1.10	importProject.....	18-8
18.1.11	createProject.....	18-8
18.1.12	deleteProject	18-9
18.1.13	exportProject.....	18-10
18.1.14	unlockProject	18-10

19 Oracle WebCenter Content Custom WLST Commands

19.1	Overview of WLST WebCenter Content Command Categories.....	19-1
19.2	WLST WebCenter Content Help	19-2
19.3	Getter and Setter Methods Implementation	19-2
19.4	Server Configuration Commands.....	19-3
19.4.1	getUCMHttpServerAddress	19-3
19.4.2	getUCMServerPort	19-4
19.4.3	setUCMServerPort.....	19-4
19.4.4	getUCMIpAddressFilter	19-4
19.4.5	setUCMIpAddressFilter.....	19-5
19.4.6	getUCMUseSSL.....	19-5
19.5	Email Configuration Commands.....	19-6
19.5.1	getUCMMailServer.....	19-6
19.5.2	setUCMMailServer	19-6
19.5.3	getUCMSmtpPort	19-7
19.5.4	getUCMSysAdminAddress.....	19-7
19.5.5	setUCMSysAdminAddress	19-8
19.6	System Status Commands	19-8
19.6.1	getUCMCSVersion	19-8
19.6.2	getUCMServerUptime	19-9
19.7	General Configuration Commands.....	19-9
19.7.1	getUCMOverrideFormat	19-10
19.7.2	setUCMOverrideFormat.....	19-10
19.7.3	getUCMDownloadApplet.....	19-11
19.7.4	setUCMDownloadApplet.....	19-11
19.7.5	getUCMMultiUpload.....	19-11
19.7.6	setUCMMultiUpload	19-12
19.7.7	getUCMUseAccounts.....	19-12

19.7.8	setUCMUseAccounts	19-13
19.7.9	getUCMIsAutoNumber	19-13
19.7.10	setUCMIsAutoNumber.....	19-14
19.7.11	getUCMAutoNumberPrefix.....	19-14
19.7.12	setUCMAutoNumberPrefix	19-14
19.7.13	getUCMMajorRevLabelSeq.....	19-15
19.7.14	setUCMMajorRevLabelSeq	19-15
19.7.15	getUCMMinorRevLabelSeq.....	19-16
19.7.16	setUCMMinorRevLabelSeq.....	19-16
19.7.17	getUCMJspServerEnabled.....	19-17
19.7.18	setUCMJspServerEnabled	19-17
19.7.19	getUCMJspEnabledGroups.....	19-17
19.7.20	setUCMJspEnabledGroups	19-18
19.8	Content Security Configuration Commands	19-18
19.8.1	getUCMCopyAccess	19-19
19.8.2	setUCMCopyAccess	19-19
19.8.3	getUCMExclusiveCheckout	19-20
19.8.4	setUCMExclusiveCheckout.....	19-20
19.8.5	getUCMAuthorDelete.....	19-20
19.8.6	setUCMAuthorDelete	19-21
19.8.7	getUCMShowOnlyKnownAccounts.....	19-21
19.8.8	setUCMShowOnlyKnownAccounts	19-22
19.9	Component Manager Configuration Commands	19-22
19.9.1	getUCMComponentStatus	19-23
19.9.2	setUCMComponentStatus.....	19-23
19.9.3	installUCMComponent.....	19-23
19.9.4	uninstallUCMComponent	19-24
19.9.5	downloadUCMComponent	19-24
19.9.6	getUCMComponentConfig.....	19-25
19.9.7	updateUCMComponentConfig.....	19-25
19.10	Records Management Configuration Commands	19-25
19.10.1	getRMLevel.....	19-26
19.10.2	getRMConfigurationLevel.....	19-26
19.10.3	getRMFeatures	19-27
19.10.4	getRMDispositionActions	19-28
19.10.5	rmUpdate.....	19-28
19.10.6	addOutgoingProvider.....	19-29
19.10.7	registerSource.....	19-30
19.11	User Interface Commands	19-30
19.11.1	displayWccAdfConfig.....	19-31
19.11.2	updateWccAdfConfig	19-32
19.12	User Interface Connection Commands.....	19-34
19.12.1	createRIDCConnection	19-35
19.12.2	updateRIDCConnection	19-35
19.12.3	listRIDCConnections.....	19-37
19.12.4	deleteRIDCConnection	19-37
19.12.5	displayRIDCConnection.....	19-37

20 Oracle WebCenter Capture Custom WLST Commands

20.1	Overview of WLST Oracle WebCenter Capture Command Categories.....	20-1
20.2	Configuration Commands.....	20-1
20.2.1	listWorkspaces	20-2
20.2.2	listBatches	20-2
20.2.3	exportBatch.....	20-3
20.2.4	exportWorkspace	20-3
20.2.5	importWorkspace	20-4
20.2.6	unlockBatch	20-4
20.2.7	listLockedBatches	20-5
20.2.8	listCaptureConfig	20-5
20.2.9	getCaptureConfig	20-6
20.2.10	setCaptureConfig.....	20-6
20.2.11	scanForClientBundles	20-6
20.2.12	deleteBundle.....	20-7

21 Enterprise Scheduler Custom WLST Commands

21.1	Enterprise Scheduler Custom Commands	21-1
21.1.1	essGetRequestContent	21-2
21.1.2	essManageRequest.....	21-3
21.1.3	essManageRuntimeConfig	21-3
21.1.4	essManageServer	21-4
21.1.5	essQueryRequests.....	21-5

Preface

This preface describes the document accessibility features and conversions used in this guide—*WebLogic Scripting Tool Command Reference*.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit

<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

Introduction and Roadmap

This section describes the contents and organization of this guide—*WebLogic Scripting Tool Command Reference*.

- [Section 1.1, "Document Scope and Audience"](#)
- [Section 1.2, "Guide to This Document"](#)
- [Section 1.3, "Related Documentation"](#)
- [Section 1.4, "New and Changed WLST Features in This Release"](#)

1.1 Document Scope and Audience

This document describes all of the commands that are available to use with the WebLogic Scripting Tool (WLST). This document includes WLST commands for WebLogic Server, as well as custom WLST commands that can be used to manage installed Oracle Fusion Middleware components.

Note: Custom WLST commands for a given Oracle Fusion Middleware component are available for use only if the component is installed in the *ORACLE_HOME* directory.

This document is written for WebLogic Server administrators and operators who deploy Java EE applications using the Java Platform, Enterprise Edition (Java EE) from Oracle. It is assumed that readers are familiar with Web technologies and the operating system and platform where WebLogic Server is installed.

1.2 Guide to This Document

This document is organized as follows:

- This chapter, "Introduction and Roadmap," introduces the organization of this guide and lists related documentation.
- [Chapter 2, "WebLogic Server WLST Online and Offline Command Reference,"](#) summarizes WebLogic Server WLST commands alphabetically and by online/offline usage.
- [Chapter 3, "WLST Command and Variable Reference,"](#) provides detailed descriptions for each of the WebLogic Server WLST commands and variables.
- [Chapter 4, "Infrastructure Security Custom WLST Commands,"](#) provides detailed descriptions for each of the custom WLST commands that can be used to manage the Oracle Fusion Middleware Infrastructure Security components.

- [Chapter 5, "User Messaging Service \(UMS\) Custom WLST Commands,"](#) provides detailed descriptions of the custom WLST commands that can be used to manage the Oracle Fusion Middleware User Messaging Service (UMS) component.
- [Chapter 6, "DMS Custom WLST Commands,"](#) provides detailed descriptions of the custom WLST commands that can be used to manage the Oracle Fusion Middleware Dynamic Monitoring Service (DMS) component.
- [Chapter 7, "Logging Custom WLST Commands,"](#) provides detailed descriptions of the custom WLST commands that can be used to manage the Oracle Fusion Middleware Logging component.
- [Chapter 8, "Metadata Services \(MDS\) Custom WLST Commands,"](#) provides detailed descriptions of the custom WLST commands that can be used to manage the Oracle Fusion Middleware Metadata Services (MDS) component.
- [Chapter 9, "Oracle SOA Suite Custom WLST Commands,"](#) provides detailed descriptions of the custom WLST commands that can be used to manage the Oracle Fusion Middleware SOA component.
- [Chapter 10, "WebCenter Portal Custom WLST Commands,"](#) provides detailed descriptions for each of the custom WLST commands that can be used to manage the Oracle Fusion Middleware WebCenter Portal component.
- [Chapter 11, "Application Development Framework \(ADF\) Custom WLST Commands,"](#) provides detailed descriptions of the custom WLST commands that can be used to manage the Oracle Fusion Middleware ADF component.
- [Chapter 12, "Portal Custom WLST Commands,"](#) provides detailed descriptions of the custom WLST commands that can be used to manage the Oracle Fusion Middleware Portals component.
- [Chapter 13, "Java Required Files Custom WLST Commands,"](#) provides detailed descriptions of the custom WLST commands that can be used to manage the Oracle Fusion Middleware JRF component.
- [Chapter 14, "Web Services Custom WLST Commands,"](#) provides detailed descriptions of the custom WLST commands that can be used to manage the Oracle Fusion Middleware Web Services component.
- [Chapter 15, "Diagnostic Framework Custom WLST Commands,"](#) provides detailed descriptions of the custom WLST commands that can be used to manage the Oracle Fusion Middleware Diagnostic Framework component.
- [Chapter 16, "Information Rights Management Custom WLST Commands,"](#) provides detailed descriptions of the custom WLST commands that can be used to manage the Oracle Fusion Middleware Information Rights Management component.
- [Chapter 17, "Oracle WebCenter: Imaging Custom WLST Commands,"](#) provides detailed descriptions of the custom WLST commands that can be used to manage the Oracle Imaging and Process Management component.
- [Chapter 18, "Oracle Business Process Management Custom WLST Commands,"](#) provides detailed descriptions of the custom WLST commands for Oracle Business Process Management.
- [Chapter 19, "Oracle WebCenter Content Custom WLST Commands,"](#) provides detailed descriptions of the custom WLST commands for Oracle WebCenter Content.

- [Chapter 20, "Oracle WebCenter Capture Custom WLST Commands,"](#) provides detailed descriptions of the custom WLST commands for Oracle WebCenter Capture.
- [Chapter 21, "Enterprise Scheduler Custom WLST Commands,"](#) provides detailed descriptions of the custom WLST commands for Oracle Enterprise Scheduling Service (ESS).

1.3 Related Documentation

For information about how to use the WebLogic Scripting Tool, refer to *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

WLST is one of several interfaces for managing and monitoring WebLogic Server. For information about the other management interfaces, see:

- "Using Ant Tasks to Configure and Use a WebLogic Server Domain" in *Oracle Fusion Middleware Developing Applications for Oracle WebLogic Server*, describes using WebLogic Ant tasks for starting and stopping WebLogic Server instances and configuring WebLogic domains.
- "Deployment Tools" in *Oracle Fusion Middleware Deploying Applications to Oracle WebLogic Server* describes several tools that WebLogic Server provides for deploying applications and stand-alone modules.
- *Administration Console Online Help* describes a Web-based graphical user interface for managing and monitoring WebLogic domains.
- *Creating WebLogic Domains Using the Configuration Wizard* describes using a graphical user interface to create a WebLogic domain or extend an existing one.
- *Oracle Fusion Middleware Creating Templates and Domains Using the Pack and Unpack Commands* describes commands that recreate existing WebLogic domains quickly and easily.
- *Oracle Fusion Middleware Developing Custom Management Utilities With JMX for Oracle WebLogic Server* describes using Java Management Extensions (JMX) APIs to monitor and modify WebLogic Server resources.
- *Oracle Fusion Middleware SNMP Management Guide for Oracle WebLogic Server* describes using Simple Network Management Protocol (SNMP) to monitor WebLogic domains.
- *Oracle Fusion Middleware Administrator's Guide* describes how to manage Oracle Fusion Middleware, including how to start and stop Oracle Fusion Middleware, how to configure and reconfigure components, and how to back up and recover.

1.4 New and Changed WLST Features in This Release

For a comprehensive listing of the new WebLogic Server features introduced in this release, see *Oracle Fusion Middleware What's New in Oracle WebLogic Server*.

WebLogic Server WLST Online and Offline Command Reference

This chapter provides an alphabetized lists of all WLST online and offline commands. The following sections summarize the WebLogic Server WLST commands, as follows:

- [Section 2.1, "WebLogic Server WLST Command Summary, Alphabetically By Command"](#)
- [Section 2.2, "WebLogic Server WLST Online Command Summary"](#)
- [Section 2.3, "WebLogic Server WLST Offline Command Summary"](#)

Note: You can list a summary of all online and offline commands from the command-line using the following commands, respectively:

```
help("online")
help("offline")
```

For information about custom WLST commands for Fusion Middleware (FMW) components, refer to the appropriate chapter in this document. For information on how to run FMW custom commands, see "Using Custom WLST Commands" in the *Oracle Fusion Middleware Administrator's Guide*.

2.1 WebLogic Server WLST Command Summary, Alphabetically By Command

The following tables summarizes each of the WebLogic Server WLST commands, alphabetically by command. This table does not include custom WLST commands for FMW components. For a list of custom commands for a given FMW component, refer to the appropriate chapter in this document.

Table 2–1 WebLogic Server WLST Command Summary

This command...	Enables you to...	Use with WLST...
activate	Activate changes saved during the current editing session but not yet deployed.	Online
addHelpCommand	Adds new command help for a command to an existing command group. Once added to the group, the command (along with a brief description) is displayed in the command list for the group when you enter the <code>help('commandGroup')</code> command.	Online or Offline

Table 2–1 (Cont.) WebLogic Server WLST Command Summary

This command...	Enables you to...	Use with WLST...
addHelpCommandGroup	Adds a new help command group to those shown by the WLST <code>help()</code> command.	Online or Offline
addListener	Add a JMX listener to the specified MBean.	Online
addTemplate	Extend the current WebLogic domain using an application or service extension template.	Offline
assign	Assign resources to one or more destinations.	Offline
cancelEdit	Cancel an edit session, release the edit lock, and discard all unsaved changes. This operation can be called by any user with administrator privileges, even if the user did not start the edit session.	Online
cd	Navigate the hierarchy of configuration or runtime beans.	Online or Offline
closeDomain	Close the current WebLogic domain.	Offline
closeTemplate	Close the current domain template.	Offline
configToScript	Convert an existing server configuration (<code>config</code> directory) to an executable WLST script.	Online or Offline
connect	Connect WLST to a WebLogic Server instance.	Online or Offline
create	Create a configuration bean of the specified type for the current bean.	Online or Offline
currentTree	Return the current location in the hierarchy.	Online
custom	Navigate to the root of custom MBeans that are registered in the Runtime MBean Server.	Online
delete	Delete an instance of a configuration bean of the specified type for the current configuration bean.	Online or Offline
deploy	Deploy an application to a WebLogic Server instance.	Online
disconnect	Disconnect WLST from a WebLogic Server instance.	Online
distributeApplication	Copy the deployment bundle to the specified targets.	Online
domainConfig	Navigate to the last MBean to which you navigated in the domain configuration hierarchy or to the root of the hierarchy, <code>DomainMBean</code> .	Online
domainCustom	Navigate to the tree of custom MBeans that are registered in the Domain Runtime MBean Server.	Online
domainRuntime	Navigate to the last MBean to which you navigated in the domain runtime hierarchy or to the root of the hierarchy, <code>DomainRuntimeMBean</code> .	Online
dumpStack	Display stack trace from the last exception that occurred while performing a WLST action, and reset the stack trace.	Online or Offline

Table 2–1 (Cont.) WebLogic Server WLST Command Summary

This command...	Enables you to...	Use with WLST...
<code>dumpVariables</code>	Display all variables used by WLST, including their name and value.	Online or Offline
<code>edit</code>	Navigate to the last MBean to which you navigated in the configuration edit MBean hierarchy or to the root of the hierarchy, <code>DomainMBean</code> .	Online
<code>encrypt</code>	Encrypt the specified string.	Online
<code>exit</code>	Exit WLST from the user session and close the scripting shell.	Online or Offline
<code>exportDiagnosticData</code>	Execute a query against the specified log file.	Offline
<code>exportDiagnosticDataFromServer</code>	Executes a query on the server side and retrieves the exported WebLogic Diagnostic Framework (WLDF) data.	Online
<code>find</code>	Find MBeans and attributes in the current hierarchy.	Online
<code>get</code>	Return the value of the specified attribute.	Online or Offline
<code>getActivationTask</code>	Return the latest <code>ActivationTask</code> MBean on which a user can get status.	Online
<code>getAvailableCapturedImages</code>	Returns a list of the previously captured diagnostic images.	Online
<code>getConfigManager</code>	Return the latest <code>ConfigurationManagerBean</code> MBean which manages the change process.	Online
<code>getMBean</code>	Return the MBean by browsing to the specified path.	Online
<code>getMBeanInfo</code>	Return the <code>MBeanInfo</code> for the specified <code>MBeanType</code> or the <code>cmo</code> variable.	Online
<code>getPath</code>	Return the MBean path for the specified MBean instance.	Online
<code>getWLDM</code>	Return the <code>WebLogicDeploymentManager</code> object.	Online
<code>invoke</code>	Invoke a management operation on the current configuration bean.	Online
<code>isRestartRequired</code>	Determine whether a server restart is required.	Online
<code>jndi</code>	Navigates to the JNDI tree for the server to which WLST is currently connected.	Online
<code>listApplications</code>	List all applications that are currently deployed in the domain.	Online
<code>listChildTypes</code>	List all the children MBeans that can be created or deleted for the <code>cmo</code> .	Online
<code>loadApplication</code>	Load an application and deployment plan into memory.	Online or Offline
<code>loadDB</code>	Load SQL files into a database.	Offline
<code>loadProperties</code>	Load property values from a file.	Online and Offline
<code>lookup</code>	Look up the specified MBean.	Online

Table 2–1 (Cont.) WebLogic Server WLST Command Summary

This command...	Enables you to...	Use with WLST...
<code>ls</code>	List all child beans and/or attributes for the current configuration or runtime bean.	Online or Offline
<code>man</code>	Display help from <code>MBeanInfo</code> for the current MBean or its specified attribute.	Online
<code>migrate</code>	Migrate services to a target server within a cluster.	Online
<code>nm</code>	Determine whether WLST is connected to Node Manager.	Online
<code>nmConnect</code>	Connect WLST to Node Manager to establish a session.	Online or Offline
<code>nmDisconnect</code>	Disconnect WLST from a Node Manager session.	Online or Offline
<code>nmEnroll</code>	Enroll the machine on which WLST is currently running.	Online
<code>nmGenBootStartupProps</code>	Generates the Node Manager property files, <code>boot.properties</code> and <code>startup.properties</code> , for the specified server.	Online
<code>nmKill</code>	Kill the specified server instance that was started with Node Manager.	Online or Offline
<code>nmLog</code>	Return the Node Manager log.	Online or Offline
<code>nmServerLog</code>	Return the server output log of the server that was started with Node Manager.	Online or Offline
<code>nmServerStatus</code>	Return the status of the server that was started with Node Manager.	Online or Offline
<code>nmStart</code>	Start a server in the current domain using Node Manager.	Online or Offline
<code>nmVersion</code>	Return the Node Manager server version.	Online or Offline
<code>prompt</code>	Toggle the display of path information at the prompt.	Online or Offline
<code>pwd</code>	Display the current location in the configuration or runtime bean hierarchy.	Online or Offline
<code>readDomain</code>	Open an existing WebLogic domain for updating.	Offline
<code>readTemplate</code>	Open an existing domain template for WebLogic domain creation.	Offline
<code>redeploy</code>	Reload classes and redeploy a previously deployed application.	Online

Table 2–1 (Cont.) WebLogic Server WLST Command Summary

This command...	Enables you to...	Use with WLST...
<code>redirect</code>	Redirect WLST output to the specified filename.	Online or Offline
<code>removeListener</code>	Remove a listener that was previously defined.	Online
<code>resume</code>	Resume a server instance that is suspended or in ADMIN state.	Online
<code>save</code>	Save the edits that have been made but have not yet been saved.	Online
<code>saveDiagnosticImageCaptureFile</code>	Downloads the specified diagnostic image capture.	Online
<code>saveDiagnosticImageCaptureEntryFile</code>	Downloads a specific entry from the diagnostic image capture.	Online
<code>serverRuntime</code>	Navigate to the last MBean to which you navigated in the runtime MBean hierarchy or to the root of the hierarchy, <code>ServerRuntimeMBean</code> .	Online
<code>set</code>	Set the specified attribute value for the current configuration bean.	Online or Offline
<code>setOption</code>	Set options related to a WebLogic domain creation or update	Offline
<code>showChanges</code>	Show the changes made by the current user during the current edit session.	Online
<code>showListeners</code>	Show all listeners that are currently defined.	Online
<code>shutdown</code>	Gracefully shut down a running server instance or cluster.	Online
<code>start</code>	Start a Managed Server instance or a cluster using Node Manager.	Online
<code>startApplication</code>	Start an application, making it available to users.	Online
<code>startEdit</code>	Start a configuration edit session on behalf of the currently connected user.	Online
<code>startNodeManager</code>	Start Node Manager at default port (5556).	Online or Offline
<code>startRecording</code>	Record all user interactions with WLST; useful for capturing commands to replay.	Online or Offline
<code>startServer</code>	Start the Administration Server.	Online or Offline
<code>state</code>	Returns a map of servers or clusters and their state using Node Manager.	Online
<code>stopApplication</code>	Stop an application, making it unavailable to users.	Online
<code>stopEdit</code>	Stop the current edit session, release the edit lock, and discard unsaved changes.	Online
<code>stopNodeManager</code>	Stop Node Manager.	Online or Offline

Table 2–1 (Cont.) WebLogic Server WLST Command Summary

This command...	Enables you to...	Use with WLST...
stopRecording	Stop recording WLST commands.	Online or Offline
stopRedirect	Stop the redirection of WLST output to a file.	Online or Offline
storeUserConfig	Create a user configuration file and an associated key file.	Online
suspend	Suspend a running server.	Online
threadDump	Display a thread dump for the specified server.	Online or Offline
undeploy	Undeploy an application from the specified servers.	Online
updateApplication	Update an application configuration using a new deployment plan.	Online
updateDomain	Update and save the current domain.	Offline
unassign	Unassign applications or services from one or more destinations.	Offline
undo	Revert all unsaved or unactivated edits.	Online
validate	Validate the changes that have been made but have not yet been saved.	Online
viewMBean	Display information about an MBean, such as the attribute names and values, and operations.	Online
writeDomain	Write the domain configuration information to the specified directory.	Offline
writeIniFile	Convert WLST definitions and method declarations to a Python (.py) file.	Online or Offline
writeTemplate	Writes the domain configuration information to the specified domain template.	Offline

2.2 WebLogic Server WLST Online Command Summary

The following table summarizes the WebLogic Server WLST online commands, alphabetically by command. This table does not include custom WLST commands for FMW components. For a list of custom commands for a given FMW component, refer to the appropriate chapter in this document.

Table 2–2 WebLogic Server WLST Online Command Summary

This command...	Enables you to...
activate	Activate changes saved during the current editing session but not yet deployed.
addHelpCommand	Adds new command help for a command to an existing command group. Once added to the group, the command (along with a brief description) is displayed in the command list for the group when you enter the <code>help('commandGroup')</code> command.

Table 2–2 (Cont.) WebLogic Server WLST Online Command Summary

This command...	Enables you to...
<code>addHelpCommandGroup</code>	Adds a new help command group to those shown by the WLST <code>help()</code> command, and specifies the resource bundle in which the help information is defined for the group.
<code>addListener</code>	Add a JMX listener to the specified MBean.
<code>cancelEdit</code>	Cancel an edit session, release the edit lock, and discard all unsaved changes. This operation can be called by any user with administrator privileges, even if the user did not start the edit session.
<code>cd</code>	Navigate the hierarchy of configuration or runtime beans.
<code>configToScript</code>	Convert an existing server configuration (<code>config</code> directory) to an executable WLST script.
<code>connect</code>	Connect WLST to a WebLogic Server instance.
<code>create</code>	Create a configuration bean of the specified type for the current bean.
<code>currentTree</code>	Return the current tree location.
<code>custom</code>	Navigate to the root of custom MBeans that are registered in the Runtime MBean Server.
<code>delete</code>	Delete an instance of a configuration bean of the specified type for the current configuration bean.
<code>deploy</code>	Deploy an application to a WebLogic Server instance.
<code>disconnect</code>	Disconnect WLST from a WebLogic Server instance.
<code>distributeApplication</code>	Copy the deployment bundle to the specified targets.
<code>domainConfig</code>	Navigate to the last MBean to which you navigated in the domain configuration hierarchy or to the root of the hierarchy, <code>DomainMBean</code> .
<code>domainCustom</code>	Navigate to the tree of custom MBeans that are registered in the Domain Runtime MBean Server.
<code>domainRuntime</code>	Navigate to the last MBean to which you navigated in the domain runtime hierarchy or to the root of the hierarchy, <code>DomainRuntimeMBean</code> .
<code>dumpStack</code>	Display stack trace from the last exception that occurred, and reset the trace.
<code>dumpVariables</code>	Display all variables used by WLST, including their name and value.
<code>edit</code>	Navigate to the last MBean to which you navigated in the configuration edit MBean hierarchy or to the root of the hierarchy, <code>DomainMBean</code> .
<code>encrypt</code>	Encrypt the specified string.
<code>exit</code>	Exit WLST from the interactive session and close the scripting shell.
<code>exportDiagnosticDataFromServer</code>	Execute a query on the server side and retrieves the exported WebLogic Diagnostic Framework (WLDF) data.
<code>find</code>	Find MBeans and attributes in the current hierarchy.
<code>get</code>	Return the value of the specified attribute.
<code>getActivationTask</code>	Return the latest <code>ActivationTask</code> MBean on which a user can get status.

Table 2–2 (Cont.) WebLogic Server WLST Online Command Summary

This command...	Enables you to...
<code>getAvailableCapturedImages</code>	Returns a list of the previously captured diagnostic images.
<code>getConfigManager</code>	Return the latest <code>ConfigurationManagerBean</code> MBean which manages the change process.
<code>getMBean</code>	Return the MBean by browsing to the specified path.
<code>getMBeanInfo</code>	Return the <code>MBeanInfo</code> for the specified <code>MBeanType</code> or the <code>cmo</code> variable.
<code>getPath</code>	Return the MBean path for the specified MBean instance.
<code>getWLDM</code>	Return the WebLogic <code>DeploymentManager</code> object.
<code>invoke</code>	Invoke a management operation on the current configuration bean.
<code>isRestartRequired</code>	Determine whether a server restart is required.
<code>jndi</code>	Navigates to the JNDI tree for the server to which WLST is currently connected.
<code>listApplications</code>	List all applications that are currently deployed in the domain.
<code>listChildTypes</code>	List all the children MBeans that can be created or deleted for the <code>cmo</code> .
<code>loadApplication</code>	Load an application and deployment plan into memory.
<code>loadProperties</code>	Load property values from a file.
<code>lookup</code>	Look up the specified MBean.
<code>ls</code>	List all child beans and/or attributes for the current configuration or runtime bean.
<code>man</code>	Display help from <code>MBeanInfo</code> for the current MBean or its specified attribute.
<code>migrate</code>	Migrate services to a target server within a cluster.
<code>nm</code>	Determine whether WLST is connected to Node Manager.
<code>nmConnect</code>	Connect WLST to Node Manager to establish a session.
<code>nmDisconnect</code>	Disconnect WLST from a Node Manager session.
<code>nmEnroll</code>	Enroll the machine on which WLST is currently running.
<code>nmGenBootStartupProps</code>	Generates the Node Manager property files, <code>boot.properties</code> and <code>startup.properties</code> , for the specified server.
<code>nmKill</code>	Kill the specified server instance that was started with Node Manager.
<code>nmLog</code>	Return the Node Manager log.
<code>nmServerLog</code>	Return the server output log of the server that was started with Node Manager.
<code>nmServerStatus</code>	Return the status of the server that was started with Node Manager.
<code>nmStart</code>	Start a server in the current domain using Node Manager.
<code>nmVersion</code>	Return the Node Manager server version.
<code>prompt</code>	Toggle the display of path information at the prompt.

Table 2–2 (Cont.) WebLogic Server WLST Online Command Summary

This command...	Enables you to...
<code>pwd</code>	Display the current location in the configuration or runtime bean hierarchy.
<code>redeploy</code>	Reload classes and redeploy a previously deployed application.
<code>redirect</code>	Redirect WLST output to the specified filename.
<code>removeListener</code>	Remove a listener that was previously defined.
<code>resume</code>	Resume a server instance that is suspended or in ADMIN state.
<code>save</code>	Save the edits that have been made but have not yet been saved.
<code>saveDiagnosticImageCaptureFile</code>	Downloads the specified diagnostic image capture.
<code>saveDiagnosticImageCaptureEntryFile</code>	Downloads a specific entry from the diagnostic image capture.
<code>serverConfig</code>	Navigate to the last MBean to which you navigated in the configuration MBean hierarchy or to the root of the hierarchy, <code>DomainMBean</code> .
<code>serverRuntime</code>	Navigate to the last MBean to which you navigated in the runtime MBean hierarchy or to the root of the hierarchy, <code>ServerRuntimeMBean</code> .
<code>set</code>	Set the specified attribute value for the current configuration bean.
<code>showChanges</code>	Show the changes made by the current user during the current edit session.
<code>showListeners</code>	Show all listeners that are currently defined.
<code>shutdown</code>	Gracefully shut down a running server instance or cluster.
<code>start</code>	Start a Managed Server instance or a cluster using Node Manager.
<code>startApplication</code>	Start an application, making it available to users.
<code>startEdit</code>	Start a configuration edit session on behalf of the currently connected user.
<code>startNodeManager</code>	Start Node Manager at default port (5556).
<code>startRecording</code>	Record all user interactions with WLST; useful for capturing commands to replay.
<code>startServer</code>	Start the Administration Server.
<code>state</code>	Returns a map of servers or clusters and their state using Node Manager
<code>stopApplication</code>	Stop an application, making it un available to users.
<code>stopEdit</code>	Stop the current edit session, release the edit lock, and discard unsaved changes.
<code>stopNodeManager</code>	Stop Node Manager.
<code>stopRedirect</code>	Stop the redirection of WLST output to a file.
<code>storeUserConfig</code>	Create a user configuration file and an associated key file.
<code>suspend</code>	Suspend a running server.
<code>threadDump</code>	Display a thread dump for the specified server.
<code>undeploy</code>	Undeploy an application from the specified servers.

Table 2–2 (Cont.) WebLogic Server WLST Online Command Summary

This command...	Enables you to...
<code>undo</code>	Revert all unsaved or unactivated edits.
<code>updateApplication</code>	Update an application configuration using a new deployment plan.
<code>validate</code>	Validate the changes that have been made but have not yet been saved.
<code>viewMBean</code>	Display information about an MBean, such as the attribute names and values, and operations.
<code>writeIniFile</code>	Convert WLST definitions and method declarations to a Python (.py) file.

2.3 WebLogic Server WLST Offline Command Summary

The following table summarizes the WebLogic Server WLST offline commands, alphabetically by command.

Table 2–3 WebLogic Server WLST Offline Command Summary

This command...	Enables you to...
<code>addHelpCommand</code>	Adds new command help for a command to an existing command group. Once added to the group, the command (along with a brief description) is displayed in the command list for the group when you enter the <code>help('commandGroup')</code> command.
<code>addHelpCommandGroup</code>	Adds a new help command group to those shown by the WLST <code>help()</code> command, and specifies the resource bundle in which the help information is defined for the group.
<code>addTemplate</code>	Extend the current domain using an application or service extension template.
<code>assign</code>	Assign resources to one or more destinations.
<code>cd</code>	Navigate the hierarchy of configuration or runtime beans.
<code>closeDomain</code>	Close the current domain.
<code>closeTemplate</code>	Close the current domain template.
<code>configToScript</code>	Convert an existing server configuration (<code>config</code> directory) to an executable WLST script.
<code>connect</code>	Connect WLST to a WebLogic Server instance.
<code>create</code>	Create a configuration bean of the specified type for the current bean.
<code>delete</code>	Delete an instance of a configuration bean of the specified type for the current configuration bean.
<code>dumpStack</code>	Display stack trace from the last exception that occurred while performing a WLST action, and reset the stack trace.
<code>dumpVariables</code>	Display all variables used by WLST, including their name and value.
<code>exit</code>	Exit WLST from the interactive session and close the scripting shell.
<code>exportDiagnosticData</code>	Execute a query against the specified log file.
<code>get</code>	Return the value of the specified attribute.

Table 2–3 (Cont.) WebLogic Server WLST Offline Command Summary

This command...	Enables you to...
<code>loadApplication</code>	Load an application and deployment plan into memory.
<code>loadDB</code>	Load SQL files into a database.
<code>loadProperties</code>	Load property values from a file.
<code>ls</code>	List all child beans and/or attributes for the current configuration or runtime bean.
<code>nmConnect</code>	Connect WLST to Node Manager to establish a session.
<code>prompt</code>	Toggle the display of path information at the prompt.
<code>pwd</code>	Display the current location in the configuration or runtime bean hierarchy.
<code>readDomain</code>	Open an existing WebLogic domain for updating.
<code>readTemplate</code>	Open an existing domain template for domain creation.
<code>redirect</code>	Redirect WLST output to the specified filename.
<code>set</code>	Set the specified attribute value for the current configuration bean.
<code>setOption</code>	Set options related to a WebLogic domain creation or update.
<code>startNodeManager</code>	Start Node Manager at default port (5556).
<code>startRecording</code>	Record all user interactions with WLST; useful for capturing commands to replay.
<code>startServer</code>	Start the Administration Server.
<code>stopNodeManager</code>	Stop Node Manager.
<code>stopRedirect</code>	Stop the redirection of WLST output to a file.
<code>threadDump</code>	Display a thread dump for the specified server.
<code>unassign</code>	Unassign applications or services from one or more destinations.
<code>updateDomain</code>	Update and save the current domain.
<code>writeDomain</code>	Write the domain configuration information to the specified directory.
<code>writeIniFile</code>	Convert WLST definitions and method declarations to a Python (.py) file.
<code>writeTemplate</code>	Writes the domain configuration information to the specified domain template.

WLST Command and Variable Reference

This chapter provides detailed descriptions of WLST commands, command syntax, arguments and command examples. It also lists and describes the available WLST variables.

The following sections describe the WLST commands and variables in detail. Topics include:

- [Section 3.1, "Overview of WLST Command Categories"](#)
- [Section 3.2, "Browse Commands"](#)
- [Section 3.3, "Control Commands"](#)
- [Section 3.4, "Customization Commands"](#)
- [Section 3.5, "Deployment Commands"](#)
- [Section 3.6, "Diagnostics Commands"](#)
- [Section 3.7, "Editing Commands"](#)
- [Section 3.8, "Information Commands"](#)
- [Section 3.9, "Life Cycle Commands"](#)
- [Section 3.10, "Node Manager Commands"](#)
- [Section 3.11, "Tree Commands"](#)
- [Section 3.12, "WLST Variable Reference"](#)

3.1 Overview of WLST Command Categories

Note: It is recommended that you review "Syntax for WLST Commands" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool* for command syntax requirements.

WLST commands are divided into the following categories.

Table 3–1 WLST Command Categories

Command Category	Description
Section 3.2, "Browse Commands"	Navigate the hierarchy of configuration or runtime beans and control the prompt display.

Table 3–1 (Cont.) WLST Command Categories

Command Category	Description
Section 3.3, "Control Commands"	<ul style="list-style-type: none"> ■ Connect to or disconnect from a server. ■ Create and configure a WebLogic domain or domain template. ■ Exit WLST.
Section 3.4, "Customization Commands"	Add the command group help and command help that is displayed by the WLST <code>help()</code> and <code>help('commandGroup')</code> commands.
Section 3.5, "Deployment Commands"	<ul style="list-style-type: none"> ■ Deploy, undeploy, and redeploy applications and standalone modules to a WebLogic Server instance. ■ Update an existing deployment plan. ■ Interrogate the WebLogic Deployment Manager object. ■ Start and stop a deployed application.
Section 3.6, "Diagnostics Commands"	Export diagnostic data.
Section 3.7, "Editing Commands"	Interrogate and edit configuration beans.
Section 3.8, "Information Commands"	Interrogate WebLogic domains, servers, and variables, and provide configuration bean, runtime bean, and WLST-related information.
Section 3.9, "Life Cycle Commands"	Manage the life cycle of a server instance.
Section 3.10, "Node Manager Commands"	Start, shut down, restart, and monitor WebLogic Server instances using Node Manager.
Section 3.11, "Tree Commands"	Navigate among MBean hierarchies.

3.2 Browse Commands

Use the WLST browse commands, listed in [Table 3–2](#), to navigate the hierarchy of configuration or runtime beans and control the prompt display.

Table 3–2 Browse Commands for WLST Configuration

Use this command...	To...	Use with WLST...
<code>cd</code>	Navigate the hierarchy of configuration or runtime beans.	Online or Offline
<code>currentTree</code>	Return the current location in the hierarchy.	Online
<code>prompt</code>	Toggle the display of path information at the prompt.	Online or Offline
<code>pwd</code>	Display the current location in the hierarchy.	Online or Offline

3.2.1 cd

Command Category: Browse Commands

Use with WLST: Online or Offline

3.2.1.1 Description

Navigates the hierarchy of configuration or runtime beans. This command uses a model that is similar to navigating a file system in a Windows or UNIX command shell. For example, to navigate back to a parent configuration or runtime bean, enter `cd('..')`. The character string `..` (dot-dot), refers to the directory immediately above the current directory. To get back to the root bean after navigating to a bean that is deep in the hierarchy, enter `cd('/')`.

You can navigate to beans in the current hierarchy and to any child or instance.

The `cd` command returns a stub of the configuration or runtime bean instance, if one exists. If you navigate to a type, this command returns a stub of the configuration or runtime bean instance from which you navigated. In the event of an error, the command returns a `WLSTException`.

Note: The `cmo` variable is initialized to the root of all domain configuration beans when you first connect WLST to a server instance. It reflects the parent configuration bean type until you navigate to an instance. For more information about the `cmo` variable, see "Changing the Current Management Object" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

3.2.1.2 Syntax

`cd(mbeanName)`

Argument	Definition
<code>mbeanName</code>	Path to the bean in the namespace.

3.2.1.3 Examples

The following example navigates the hierarchy of configuration beans. The first command navigates to the `Servers` configuration bean type, the second, to the `myserver` configuration bean instance, and the last back up two levels to the original directory location.

```
wls:/mydomain/serverConfig> cd('Servers')
wls:/mydomain/serverConfig/Servers> cd('myserver')
wls:/mydomain/serverConfig/Servers/myserver> cd('../..')
wls:/mydomain/serverConfig>
```

3.2.2 currentTree

Command Category: Browse Commands

Use with WLST: Online

3.2.2.1 Description

Returns the current location in the hierarchy. This command enables you to store the current location in the hierarchy and easily return to it after browsing. In the event of an error, the command returns a `WLSTException`.

3.2.2.2 Syntax

`currentTree()`

3.2.2.3 Example

The following example stores the current location in the hierarchy in `myTree` and uses it to navigate back to the Edit MBean hierarchy from the runtime MBean hierarchy on an Administration Server instance.

```
wls:/mydomain/edit> myTree=currentTree()
wls:/mydomain/edit> serverRuntime()
Location changed to serverRuntime tree. This is a read-only tree with
ServerRuntimeMBean as the root.
For more help, use help('serverRuntime')

wls:/mydomain/serverRuntime> myTree()
wls:/mydomain/edit>
```

3.2.3 prompt

Command Category: Browse Commands

Use with WLST: Online or Offline

3.2.3.1 Description

Toggles the display of path information at the prompt, when entered without an argument. This command is useful when the prompt becomes too long due to the length of the path.

You can also explicitly specify `on` or `off` as an argument to the command. When you specify `off`, WLST hides the WLST prompt and defaults to the Jython prompt. By default, the WLST prompt displays the configuration or runtime navigation path information.

When you disable the prompt details, to determine your current location in the hierarchy, you can use the `pwd` command, as described in [Section 3.2.4, "pwd"](#).

In the event of an error, the command returns a `WLSTException`.

3.2.3.2 Syntax

```
prompt (myPrompt)
```

Argument	Definition
<code>myPrompt</code>	<p>Optional. Hides or displays WLST prompt. Valid values include <code>off</code> or <code>on</code>.</p> <ul style="list-style-type: none"> The <code>off</code> argument hides the WLST prompt. <p>If you run <code>prompt('off')</code>, when using WLST online, the prompt defaults to the Jython prompt. You can create a new prompt using Jython syntax. For more information about programming using Jython, see http://www.jython.org. In this case, if you subsequently enter the <code>prompt</code> command without arguments, WLST displays the WLST command prompt without the path information. To redisplay the path information, enter <code>prompt()</code> again, or enter <code>prompt('on')</code>.</p> The <code>on</code> argument displays the default WLST prompt, including the path information.

3.2.3.3 Examples

The following example hides and then redisplay the path information at the prompt.

```
wls:/mydomain/serverConfig/Servers/myserver> prompt()
wls:/> prompt()
wls:/mydomain/serverConfig/Servers/myserver>
```


The following example hides the prompt and defaults to the Jython prompt (since the command is run using WLST online), changes the Jython prompt, and then redisplay the WLST prompt. This example also demonstrates the use of the `pwd` command.

Note: For more information about programming using Jython, see <http://www.jython.org>.

```
wls:/mydomain/serverConfig/Servers/myserver> prompt('off')
>>>sys.ps1="myprompt>"
myprompt> prompt()
wls:> pwd()
'serverConfig:Servers/myserver'
wls:> prompt()
wls:/mydomain/serverConfig/Servers/myserver>
```

3.2.4 pwd

Command Category: Browse Commands

Use with WLST: Online or Offline

3.2.4.1 Description

Displays the current location in the configuration or runtime bean hierarchy.

This command is useful when you have turned off the prompt display of the path information using the `prompt` command, as described in [Section 3.2.3, "prompt"](#).

In the event of an error, the command returns a `WLSTException`.

3.2.4.2 Syntax

```
pwd()
```

3.2.4.3 Example

The following example displays the current location in the configuration bean hierarchy.

```
wls:/mydomain/serverConfig/Servers/myserver/Log/myserver> pwd()
'serverConfig:/Servers/myserver/Log/myserver'
```

3.3 Control Commands

Use the WLST control commands, listed in [Table 3–3](#), to perform the following tasks:

- Connect to or disconnect from a server (`connect` and `disconnect` commands)
- Create a new WebLogic domain from a domain template, similar to the Configuration Wizard (`createDomain`, `readTemplate`, `writeDomain`, and `closeTemplate` commands)
- Update an existing WebLogic domain, offline (`readDomain`, `addTemplate`, `updateDomain`, and `closeDomain` commands)
- Write a domain template (`writeTemplate` command)
- Exit WLST

[Table 3–3](#) lists the control commands for WLST configuration.

Table 3–3 Control Commands for WLST Configuration

Use this command...	To...	Use with WLST...
<code>connect</code>	Connect WLST to a WebLogic Server instance.	Online or Offline
<code>disconnect</code>	Disconnect WLST from a WebLogic Server instance.	Online
<code>createDomain</code>	Create a new WebLogic domain using the specified template.	Offline
<code>readTemplate</code>	Open an existing domain template for domain creation.	Offline
<code>writeDomain</code>	Write the domain configuration information to the specified directory.	Offline
<code>closeTemplate</code>	Close the current domain template.	Offline
<code>readDomain</code>	Open an existing WebLogic domain for updating.	Offline
<code>addTemplate</code>	Extend the current WebLogic domain using an application or service extension template.	Offline
<code>updateDomain</code>	Update and save the current domain.	Offline
<code>closeDomain</code>	Close the current domain.	Offline
<code>writeTemplate</code>	Writes the configuration information to the specified domain template file.	Offline
<code>exit</code>	Exit WLST from the interactive session and close the scripting shell.	Online or Offline

3.3.1 addTemplate

Command Category: Control Commands

Use with WLST: Offline

3.3.1.1 Description

Extends the current WebLogic domain using an application or service extension template. Use the Template Builder to create an application or service extension template. See *Oracle WebLogic Server Creating Templates Using the Domain Template Builder*.

In the event of an error, the command returns a `WLSTException`.

3.3.1.2 Syntax

```
addTemplate(templateFileName)
```

Argument	Definition
<code>templateFileName</code>	Name of the application or service extension template.

3.3.1.3 Example

The following example opens a WebLogic domain and extends it using the specified extension template, `DefaultWebApp.jar`.

```
wls:/offline> readDomain('c:/Oracle/Middleware/user_projects/domains/wlw')
```

```
wls:/offline/wlw> addTemplate('c:/Oracle/Middleware/wlserver_10.3
/common/templates/applications/DefaultWebApp.jar')
wls:/offline/wlw>
```

3.3.2 closeDomain

Command Category: Control Commands

Use with WLST: Offline

3.3.2.1 Description

Closes the current domain. The domain is no longer available for editing once it is closed. In the event of an error, the command returns a `WLSTException`.

3.3.2.2 Syntax

```
closeDomain()
```

3.3.2.3 Example

The following example closes the current domain:

```
wls:/offline> readDomain('c:/Oracle/Middleware/user_projects/domains/medrec')
...
wls:/offline/medrec> updateDomain()
wls:/offline/medrec> closeDomain()
wls:/offline>
```

3.3.3 closeTemplate

Command Category: Control Commands

Use with WLST: Offline

3.3.3.1 Description

Closes the current domain template. The domain template is no longer available once it is closed. In the event of an error, the command returns a `WLSTException`.

3.3.3.2 Syntax

```
closeTemplate()
```

3.3.3.3 Example

The following example opens an existing domain template, performs some operations, and then closes the current domain template.

```
wls:/offline> readTemplate('c:/Oracle/Middleware/wlserver_10.3
/common/templates/domains/wls.jar')
...
wls:/offline/wls> closeTemplate()
wls:/offline>
```

3.3.4 connect

Command Category: Control Commands

Use with WLST: Online or Offline

3.3.4.1 Description

Connects WLST to a WebLogic Server instance.

Requires you to provide the credentials (user name and password) of a user who has been defined in the active WebLogic security realm. Once you are connected, a collection of security policies determine which configuration attributes you are permitted to view or modify. (See "Default Security Policies for MBeans" in the *WebLogic Server MBean Reference*.)

You can supply user credentials by doing any of the following:

- Enter the credentials on the command line. This option is recommended only if you are using WLST in interactive mode.
- Enter the credentials on the command line, then use the `storeUserConfig` command to create a user configuration file that contains your credentials in an encrypted form and a key file that WebLogic Server uses to unencrypt the credentials. On subsequent WLST sessions (or in WLST scripts), supply the name of the user configuration file and key file instead of entering the credentials on the command line. This option is recommended if you use WLST in script mode because it prevents you from storing unencrypted user credentials in your scripts.
- Use the credentials that are stored in the Administration Server's `boot.properties` file. By default, when you create an Administration Server in development mode, WebLogic Server encrypts the credentials that were used to create the server and stores them in a `boot.properties` file. When you create an Administration Server in production mode, no `boot.properties` file is created. If your production domain does not contain a `boot.properties` file, you can create one manually; see "Creating a Boot Identify File for an Administration Server" in *Oracle Fusion Middleware Managing Server Startup and Shutdown for Oracle WebLogic Server*.

When you run the `connect` command, if there is a `boot.properties` file containing the encrypted username and password for the domain, you do not have to enter the username and password to connect to the Administration Server. You do, however, have to specify the name of the Administration Server in the `connect` command.

Please note:

- If you run the `connect` command in a script without specifying the username and password or user configuration file and key file, a `WLSException` occurs. In interactive mode, you are prompted for the username and password.
- Oracle strongly recommends that you connect WLST to the server through the SSL port or administration port. If you do not, the following warning message is displayed:

```
Warning: An insecure protocol was used to connect to the server. To ensure
on-the-wire security, the SSL port or Admin port should be used instead.
```

- If you are connecting to a WebLogic Server instance through an SSL listen port on a server that is using the demonstration SSL keys and certificates, invoke WLST using the following command:

```
java -Dweblogic.security.SSL.ignoreHostnameVerification=true
-Dweblogic.security.TrustKeyStore=DemoTrust weblogic.WLST
```

For more information about invoking WLST, see "Main Steps for Using WLST in Interactive or Script Mode" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

- If you are connecting to a WebLogic Server instance via HTTP, ensure that the `TunnelingEnabled` attribute is set to `true` for the WebLogic Server instance. For more information, see "TunnelingEnabled" in *Oracle Fusion Middleware Oracle WebLogic Server MBean Reference*.
- When trying to connect to the WebLogic Server Administration Server from WLST using `localhost` as the host name, the following message may be displayed if the `listen-address` attribute of the Administration Server has been restricted to certain IP addresses:

```
javax.naming.CommunicationException [Root exception is
java.net.ConnectException : <t3://HOST:PORT> : Destination unreachable;
nested exception is: java.net.ConnectException: Connection refused; No
available router to destination
```

You can use either of the following workarounds for this issue:

- Check that the `listen-address` attribute of the Administration Server has been set correctly. For example, in the domain configuration file:

```
<server>
  <name>AdminServer</name>
  <ssl>
    .
    .
    .
  </ssl>
  <machine>your_machine</machine>
  <!-- listen-address><your_ip_address></listen-address -->
</server>
```

- Use the hostname of the Administration Server, instead of `localhost`, in the WLST connect command.

After successfully connecting to a WebLogic Server instance, all the local variables are initialized.

In the event of an error, the command returns a `WLSTException`.

3.3.4.2 Syntax

```
connect([username, password], [url], [timeout])
connect([userConfigFile, userKeyFile], [url], [timeout])
connect([url], [adminServerName], [timeout])
```

Argument	Definition
<i>username</i>	Optional. Username of the operator who is connecting WLST to the server. If not specified, WLST processes the command as described above.
<i>password</i>	Optional. Password of the operator who is connecting WLST to the server. If not specified, WLST processes the command as described above.
<i>url</i>	Optional. Listen address and listen port of the server instance, specified using the following format: [protocol://]listen-address:listen-port. If not specified, this argument defaults to <code>t3://localhost:7001</code> .

Argument	Definition
<i>timeout</i>	<p>Optional. The number of milliseconds that WLST waits for online commands to complete (return).</p> <p>When you invoke a WLST online command, WLST connects to an MBean Server, invokes an MBean server method, and returns the results of the invocation. If the MBean server method does not return within the timeout period, WLST abandons its invocation attempt. Use the following syntax for this argument:</p> <pre>timeout='milliseconds'</pre> <p>A value of 0 indicates that the operation will not time out. This argument defaults to 300,000 ms (or 5 minutes).</p>
<i>userConfigFile</i>	<p>Optional. Name and location of a user configuration file which contains an encrypted username and password. Use the following syntax for this argument:</p> <pre>userConfigFile='file-system-path'</pre> <p>If not specified, WLST processes the command as described above.</p> <p>When you create a user configuration file, the <code>storeUserConfig</code> command uses a key file to encrypt the username and password. Only the key file that encrypts a user configuration file can decrypt the username and password. (See Section 3.8.21, "storeUserConfig".)</p>
<i>userKeyFile</i>	<p>Optional. Name and location of the key file that is associated with the specified user configuration file and is used to decrypt it. Use the following syntax for this argument:</p> <pre>userKeyFile='file-system-path'</pre> <p>If not specified, WLST processes the command as described above.</p> <p>See Section 3.8.21, "storeUserConfig".</p>
<i>adminServerName</i>	<p>Optional. Name of the Administration Server for the domain. Causes the connect command to use the credentials that are stored in the Administration Server's <code>boot.properties</code> file. Use the following syntax for this argument:</p> <pre>adminServerName='server-name'</pre> <p>This argument is valid only when you start WLST from a domain directory. If the <code>boot.properties</code> file for the Administration Server is located in the domain directory, then you do not need to specify this argument.</p> <p>If not specified, WLST processes the command as described above.</p>

3.3.4.3 Examples

The following example connects WLST to a WebLogic Server instance. In this example, the Administration Server name defaults to `AdminServer`. Note that a warning is displayed if the SSL or administration port is not used to connect to the server.

```
wls:/offline> connect('weblogic','welcome1','t3://localhost:8001')
Connecting to weblogic server instance running at t3://localhost:8001 as
username weblogic...
```

```
Successfully connected to Admin Server 'AdminServer' that belongs to domain
'mydomain'.
```

```
Warning: An insecure protocol was used to connect to the server. To ensure
on-the-wire security, the SSL port or Admin port should be used instead.
```

```
wls:/mydomain/serverConfig>
```

The following example connects WLST to a WebLogic Server instance at the specified URL. In this example, the username and password are passed as variables. This example uses a secure protocol.

```
wls:/offline> username = 'weblogic'
wls:/offline> password = 'welcome1'
wls:/offline> connect (username,password,'t3s://myhost:8001')
Connecting to weblogic server instance running at t3://myhost:8001 as
username weblogic...
```

Successfully connected to Admin Server 'AdminServer' that belongs to domain 'mydomain'.

```
wls:/mydomain/serverConfig>
```

The following example connects WLST to a WebLogic Server instance using a user configuration and key file to provide user credentials.

```
wls:/offline> connect (userConfigFile='c:/myfiles/myuserconfigfile.secure',
userKeyFile='c:/myfiles/myuserkeyfile.secure')
Connecting to t3://localhost:7001 with userid username ...
```

Successfully connected to Admin Server 'AdminServer' that belongs to domain 'mydomain'.

```
wls:/mydomain/serverConfig>
```

The following example shows the prompts that are displayed in interactive mode if you run the command without parameters:

```
wls:/offline> connect ()
Please enter your username :username
Please enter your password :
Please enter your server URL [t3://localhost:7001] :
Connecting to t3://localhost:7001 with userid username
```

3.3.5 createDomain

Command Category: Control Commands

Use with WLST: Offline

3.3.5.1 Description

Creates a WebLogic domain using the specified template.

Note: The `createDomain` command is similar in functionality to the `unpack` command, as described in *Oracle Fusion Middleware Creating Templates and Domains Using the Pack and Unpack Commands*.

In the event of an error, the command returns a `WLSTException`.

3.3.5.2 Syntax

```
createDomain(domainTemplate, domainDir, user, password)
```

Argument	Definition
<i>domainTemplate</i>	Name and location of the domain template from which you want to create a domain.

Argument	Definition
<i>domainDir</i>	Name of the directory to which you want to write the domain configuration information. Oracle recommends that you create all domains for your environment outside of the Middleware home directory. This makes it easier for you to remove an existing installation or install a new version of WebLogic Server without having to recreate your domains and applications.
<i>user</i>	Name of the default user.
<i>password</i>	Password of the default user.

3.3.5.3 Example

The following example creates a new WebLogic domain using the Avitek MedRec template and sets the default username to `weblogic` and the password to `welcome1`. The domain is saved to the following directory:

```
c:/Oracle/Middleware/wlserver_10.3/user_projects/domains/medrec.
```

```
wls:/offline> createDomain('c:/Oracle/Middleware/wlserver_10.3/common
/templates/domains/wls_medrec.jar', 'c:/Oracle/Middleware/user_
projects/domains/medrec',
'weblogic', 'welcome1')
```

3.3.6 disconnect

Command Category: Control Commands

Use with WLST: Online

3.3.6.1 Description

Disconnects WLST from a WebLogic Server instance. The `disconnect` command does not cause WLST to exit the interactive scripting shell; it closes the current WebLogic Server instance connection and resets all the variables while keeping the interactive shell alive.

In the event of an error, the command returns a `WLSTException`.

You can connect to another WebLogic Server instance using the `connect` command, as described in [Section 3.3.4, "connect"](#).

3.3.6.2 Syntax

```
disconnect (force)
```

Argument	Definition
<i>force</i>	Optional. Boolean value specifying whether WLST should disconnect without waiting for the active sessions to complete. This argument defaults to <code>false</code> , indicating that all active sessions must complete before disconnect.

3.3.6.3 Example

The following example disconnects from a running server:

```
wls:/mydomain/serverConfig> disconnect()
Disconnected from weblogic server: myserver
wls:/offline>
```


3.3.7 exit

Command Category: Control Commands

Use with WLST: Online or Offline

3.3.7.1 Description

Exits WLST from the user session and closes the scripting shell.

If there is an edit session in progress, WLST prompts you for confirmation. To skip the prompt, set the *defaultAnswer* argument to *y*.

By default, WLST calls `System.exit(0)` for the current WLST JVM when exiting WLST. If you would like the JVM to exit with a different exit code, you can specify a value using the *exitCode* argument.

Note: When the WLST exit command is issued within an Ant script, it may also exit the execution of the Ant script. It is recommended that when invoking WLST within an Ant script, you fork a new JVM by specifying `fork="true"`.

In the event of an error, the command returns a `WLSTException`.

3.3.7.2 Syntax

```
exit([defaultAnswer], [exitcode])
```

Argument	Definition
<i>defaultAnswer</i>	Optional. Default response, if you would prefer not to be prompted at the command line. Valid values are <i>y</i> and <i>n</i> . This argument defaults to null, and WLST prompts you for a response.
<i>exitcode</i>	Optional. Exit code to set when exiting WLST.

3.3.7.3 Example

The following example disconnects from the user session and closes the scripting shell.

```
wls:/mydomain/serverConfig> exit()
Exiting WebLogic Scripting Tool ...
c:\>
```

The following example disconnects from the user session, closes the scripting shell, and sets the error code to 101.

```
wls:/mydomain/serverConfig> exit(exitcode=101)
Exiting WebLogic Scripting Tool ...
c:\>
```

3.3.8 readDomain

Command Category: Control Commands

Use with WLST: Offline

3.3.8.1 Description

Opens an existing WebLogic domain for updating.

WLST offline provides read and write access to the configuration data that is persisted in the `config` directory for the WebLogic domain, or in a domain template JAR created using Template Builder. This data is a collection of XML documents and expresses a hierarchy of management objects.

When you open a template or WebLogic domain, WLST is placed at the root of the configuration hierarchy for that domain, and the prompt is updated to reflect the current location in the configuration hierarchy. For example:

```
wls:/offline/base_domain>
```

For more information, see "Navigating and Interrogating MBeans" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

In the event of an error, the command returns a `WLSTException`.

3.3.8.2 Syntax

```
readDomain(domainDirName)
```

Argument	Definition
<i>domainDirName</i>	Name of the WebLogic domain directory that you want to open.

3.3.8.3 Example

The following example opens the `medrec` domain for editing.

```
wls:/offline> readDomain('c:/Oracle/Middleware/user_projects/domains/medrec')
wls:/offline/medrec>
```

3.3.9 readTemplate

Command Category: Control Commands

Use with WLST: Offline

3.3.9.1 Description

Opens an existing domain template for domain creation.

When you open a domain template, WLST is placed into the configuration bean hierarchy for that domain template, and the prompt is updated to reflect the current location in the configuration hierarchy. For example:

```
wls:/offline/base_domain>
```

WebLogic Server configuration beans exist within a hierarchical structure. In the WLST file system, the hierarchies correspond to drives; types and instances are directories; attributes and operations are files. WLST traverses the hierarchical structure of configuration beans using commands such as `cd`, `ls`, and `pwd` in a similar way that you would navigate a file system in a UNIX or Windows command shell. After navigating to a configuration bean instance, you interact with the bean using WLST commands. For more information, see "Navigating and Interrogating MBeans" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

Note: Using WLST and a domain template, you can only create and access security information when you are creating a new WebLogic domain. When you are updating a WebLogic domain, you cannot access security information through WLST.

In the event of an error, the command returns a `WLSTException`.

3.3.9.2 Syntax

```
readTemplate(templateFileName)
```

Argument	Definition
<i>templateFileName</i>	Name of the JAR file corresponding to the domain template.

3.3.9.3 Example

The following example opens the `medrec.jar` domain template for WebLogic domain creation.

```
wls:/offline> readTemplate('c:/Oracle/Middleware/wlserver_10.3/common/templates
/domains/wls_medrec.jar')
wls:/offline/wls_medrec>
```

3.3.10 updateDomain

Command Category: Control Commands

Use with WLST: Offline

3.3.10.1 Description

Updates and saves the current WebLogic domain. The domain continues to be editable after you update and save it.

In the event of an error, the command returns a `WLSTException`.

3.3.10.2 Syntax

```
updateDomain()
```

3.3.10.3 Example

The following examples opens the `medrec` domain, performs some operations, and updates and saves the current domain:

```
wls:/offline> readDomain('c:/Oracle/Middleware/user_projects/domains/medrec')
...
wls:/offline/medrec> updateDomain()
```

3.3.11 writeDomain

Command Category: Control Commands

Use with WLST: Offline

3.3.11.1 Description

Writes the domain configuration information to the specified directory.

Once you write the WebLogic domain to file system, you can continue to update the domain template object that exists in memory, and reissue the `writeDomain` command to store the domain configuration to a new or existing file.

By default, when you write a WebLogic domain, the associated applications are written to `WL_HOME/user_projects/applications/domainname`, where `WL_HOME` specifies the WebLogic Server home directory and `domainname` specifies the

name of the WebLogic domain. This directory must be empty; otherwise, WLST displays an error.

When you have finished using the domain template object in memory, close it using the `closeTemplate` command. If you want to edit the WebLogic domain that has been saved to disk, you can open it using the `readDomain` command.

Notes: The name of the WebLogic domain is derived from the name of the domain directory. For example, for a domain saved to `c:/Oracle/Middleware/user_projects/domains/myMedrec`, the domain name is `myMedrec`.

When updating an existing domain, you must use `updateDomain` in place of `writeDomain()`.

Before writing the domain, you must define a password for the default user, if it is not already defined. For example:

```
cd('/Security/base_domain/User/weblogic')
cmo.setPassword('welcome1')
```

In the event of an error, the command returns a `WLSTException`.

3.3.11.2 Syntax

```
writeDomain(domainDir)
```

Argument	Definition
<i>domainDir</i>	Name of the directory to which you want to write the domain configuration information.

3.3.11.3 Example

The following example reads the `medrec.jar` domain templates, performs some operations, and writes the domain configuration information to the `c:/Oracle/Middleware/user_projects/domains/medrec` directory.

```
wls:/offline> readTemplate('c:/Oracle/Middleware/wlserver_10.3/common/templates/
domains/wls.jar')
...
wls:/offline/base_domain> writeDomain('c:/Oracle/Middleware/user_
projects/domains/base_domain')
```

3.3.12 writeTemplate

Command Category: Control Commands

Use with WLST: Offline

3.3.12.1 Description

Writes the domain configuration information to the specified domain template. You can use the domain configuration template to recreate the WebLogic domain.

Once you write the configuration information to the domain configuration template, you can continue to update the WebLogic domain or domain template object that exists in memory, and reissue the `writeDomain` or `writeTemplate` command to store the domain configuration to a new or existing WebLogic domain or domain

template file. For more information, see [Section 3.3.11, "writeDomain"](#) or [Section 3.3.12, "writeTemplate"](#), respectively.

In the event of an error, the command returns a `WLSTException`.

Note: The `writeTemplate` command is similar in functionality to the `pack` command; see "The pack Command" in *Oracle Fusion Middleware Creating Templates and Domains Using the pack and unpack Commands*. However, `writeTemplate` does not support creating a Managed Server template.

3.3.12.2 Syntax

```
writeTemplate(templateName)
```

Argument	Definition
<code>templateName</code>	Name of the domain template to store the domain configuration information.

3.3.12.3 Example

The following example writes the current domain configuration to the domain template named `c:/Oracle/Middleware/user_projects/templates/myTemplate.jar`.

```
wls:/offline> readDomain('c:/Oracle/Middleware/user_projects/domains/mydomain')
...
wls:/offline/base_domain> writeTemplate('c:/Oracle/Middleware/user_projects
/templates/myTemplate.jar')
```

3.4 Customization Commands

Use the WLST customization commands, listed in [Table 3–4](#), to add the command group `help` and command `help` that is listed by the WLST `help()` and `help('commandGroup')` commands. For more information about adding command help to WLST, see "Adding Integrated Help for Custom Commands" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

Table 3–4 Customization Commands for WLST Configuration

This command...	Enables you to...	Use with WLST...
addHelpCommandGroup	Adds a new help command group to those shown by the WLST <code>help()</code> command.	Online or Offline
addHelpCommand	Adds new command help for a command to an existing command group. Once added to the group, the command (along with a brief description) is displayed in the command list for the group when you enter the <code>help('commandGroup')</code> command.	Online or Offline

3.4.1 addHelpCommandGroup

Command Category: Customization Commands

Use with WLST: Online or Offline

3.4.1.1 Description

Adds a new command help group to those shown by the WLST `help()` command, and specifies the resource bundle in which the help information is defined for the group.

3.4.1.2 Syntax

```
addHelpCommandGroup(commandGroup, resourceBundleName)
```

Argument	Definition
<code>commandGroup</code>	Use a unique name for the command group. Do not use a command group name that is already shown by the WLST <code>help()</code> command.
<code>resourceBundleName</code>	Represents either a class name or property resource file name. The resource bundle contains help text for entries for the command group using a standard pattern. The resource bundle name will be passed to <code>ResourceBundle.getBundle(...)</code> . Multiple command groups can use the same resource bundle. The resource bundle must be present in the classpath. See "Adding Integrated Help for Custom Commands" in <i>Oracle Fusion Middleware Oracle WebLogic Scripting Tool</i> for information on how to define the help text for each command group and command. For more information on resourceBundles and localization, refer to http://download.oracle.com/javase/6/docs/api/java/util/ResourceBundle.html .

3.4.1.3 Examples

The following example adds the `boot` command group to the list of groups shown by the `help()` command, and specifies that the help text is located in the property resource file 'myhelp':

```
wls:/offline> addHelpCommandGroup('boot', 'myhelp')
```

The following example adds the `boot` command group to the list of groups shown by the `help()` command, and specifies that the help text is located in the class `foo.bar.MyResourceBundleClass`:

```
wls:/offline> addHelpCommandGroup('boot', 'foo.bar.MyResourceBundleClass')
```

3.4.2 addHelpCommand

Command Category: Customization Commands

Use with WLST: Online or Offline

3.4.2.1 Description

Adds new command help for a command to an existing command group. Once added to the group, the command (along with a brief description) is displayed in the command list for the group when you enter the `help('commandGroup')` command. You can also specify whether or not the command is listed by the `help('online')` and `help('offline')` commands.

3.4.2.2 Syntax

```
addHelpCommand(commandName, commandGroup, [offline=false, online=false])
```

Argument	Definition
<code>commandName</code>	The name of the command as defined in the command group specified by <code>commandGroup</code> .
<code>commandGroup</code>	The <code>commandGroup</code> to which the command belongs.
<code>online</code>	Optional. Boolean value that determines whether or not the command shows up in the <code>help('online')</code> output. The default value is <code>'false'</code> .
<code>offline</code>	Optional. Boolean value that determines whether or not the command shows up in the <code>help('offline')</code> output. The default value is <code>'false'</code> .

3.4.2.3 Example

The following example shows how to add the online command `bootDB` to the listing output by the `help('boot')` and `help('online')` commands:

```
wls:/offline> addHelpCommand('bootDB','boot',online='true',offline='false')
```

3.5 Deployment Commands

Use the WLST deployment commands, listed in [Table 3–5](#), to:

- Deploy, undeploy, and redeploy applications and standalone modules to a WebLogic Server instance.
- Update an existing deployment plan.
- Interrogate the WebLogic Deployment Manager object.
- Start and stop a deployed application.

For more information about deploying applications, see *Oracle Fusion Middleware Deploying Applications to Oracle WebLogic Server*.

Table 3–5 Deployment Commands for WLST Configuration

This command...	Enables you to...	Use with WLST...
deploy	Deploy an application to a WebLogic Server instance.	Online
distributeApplication	Copy the deployment bundle to the specified targets.	Online
getWLDM	Return the WebLogic DeploymentManager object.	Online
listApplications	List all applications that are currently deployed in the WebLogic domain.	Online
loadApplication	Load an application and deployment plan into memory.	Online and Offline
redploy	Redeploy a previously deployed application.	Online
startApplication	Start an application, making it available to users.	Online
stopApplication	Stop an application, making it unavailable to users.	Online
undeploy	Undeploy an application from the specified servers.	Online

Table 3–5 (Cont.) Deployment Commands for WLST Configuration

This command...	Enables you to...	Use with WLST...
updateApplication	Update an application configuration using a new deployment plan.	Online

3.5.1 deploy

Command Category: Deployment Commands

Use with WLST: Online

3.5.1.1 Description

Deploys an application to a WebLogic Server instance.

The `deploy` command returns a `WLSTProgress` object that you can access to check the status of the command. For more information about the `WLSTProgress` object, see "WLSTProgress Object" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*. In the event of an error, the command returns a `WLSTException`.

Note: If there is an edit session in progress, the `deploy` command does not block user interaction.

3.5.1.2 Syntax

```
deploy(appName, path, [targets], [stageMode], [planPath], [options])
```

Argument	Definition
<code>appName</code>	Name of the application or standalone Java EE module to be deployed.
<code>path</code>	Name of the application directory, archive file, or root of the exploded archive directory to be deployed.
<code>targets</code>	Optional. Comma-separated list of the targets. Each target may be qualified with a Java EE module name (for example, <code>module1@server1</code>) enabling you to deploy different modules of the application archive on different servers. This argument defaults to the server to which WLST is currently connected.
<code>stageMode</code>	Optional. Staging mode for the application you are deploying. Valid values are <code>stage</code> , <code>nostage</code> , and <code>external_stage</code> . For information about the staging modes, see "Controlling Deployment File Copying with Staging Modes" in <i>Oracle Fusion Middleware Deploying Applications to Oracle WebLogic Server</i> . If you do not specify a stage mode, the default stage mode is used. On the Administration Server, the default stage mode is <code>nostage</code> and on Managed Servers, it is <code>stage</code> .
<code>planPath</code>	Optional. Name of the deployment plan file. The filename can be absolute or relative to the application directory. This argument defaults to the <code>plan/plan.xml</code> file in the application directory, if one exists.

Argument	Definition
<i>options</i>	<p data-bbox="683 233 1403 285">Optional. Comma-separated list of deployment options, specified as name-value pairs. Valid options include:</p> <ul style="list-style-type: none"> <li data-bbox="683 300 1338 352">■ altDD—Location of the alternate application deployment descriptor on the Administration Server. <li data-bbox="683 367 1357 420">■ altWlsDD—Location of the alternate WebLogic application deployment descriptor on the Administration Server. <li data-bbox="683 434 1182 462">■ archiveVersion—Archive version number. <li data-bbox="683 476 1446 680">■ block—Boolean value specifying whether WLST should block user interaction until the command completes. This option defaults to <code>true</code>. If set to <code>false</code>, WLST returns control to the user after issuing the command; you can query the <code>WLSTProgress</code> object to determine the status of the command. If you are importing WLST as a Jython module, as described in "Importing WLST as a Jython Module" in <i>Oracle Fusion Middleware Oracle WebLogic Scripting Tool</i>, <code>block</code> is always set to <code>true</code>. <li data-bbox="683 695 1430 747">■ clusterDeploymentTimeout—Time, in milliseconds, granted for a cluster deployment task on this application. <li data-bbox="683 762 1446 814">■ createPlan—Boolean value indicating that user would like to create a default plan. This option defaults to <code>false</code>. <li data-bbox="683 829 1446 957">■ defaultSubmoduleTargets—Boolean value indicating that targeting for qualifying JMS submodules should be derived by the system, see "Using Sub-Module Targeting with JMS Application Modules" in <i>Oracle Fusion Middleware Deploying Applications to Oracle WebLogic Server</i>. Default value is <code>true</code>. <li data-bbox="683 972 1430 1131">■ deploymentPrincipalName—String value specifying the principal for deploying the file or archive during server starts (static deployment; it does not effect the current deployment task). Make sure the user exists. This option adds <code><deployment-principal-name></code> to the <code><app-deployment></code> element in the <code>config.xml</code> file. <li data-bbox="683 1146 1386 1173">■ forceUndeployTimeout—Force undeployment timeout value. <li data-bbox="683 1188 1409 1289">■ gracefulIgnoreSessions—Boolean value specifying whether the graceful production to admin mode operation should ignore pending HTTP sessions. This option defaults to <code>false</code> and only applies if <code>gracefulProductionToAdmin</code> is set to <code>true</code>. <li data-bbox="683 1304 1430 1383">■ gracefulProductionToAdmin—Boolean value specifying whether the production to Admin mode operation should be graceful. This option defaults to <code>false</code>. <li data-bbox="683 1398 1430 1451">■ libImplVersion—Implementation version of the library, if it is not present in the manifest. <li data-bbox="683 1465 1430 1518">■ libraryModule—Boolean value specifying whether the module is a library module. This option defaults to <code>false</code>.

Argument	Definition
<i>options</i> (Continued)	<ul style="list-style-type: none"> ■ libSpecVersion—Specification version of the library, if it is not present in the manifest. ■ planVersion—Plan version number. ■ remote—Boolean value specifying whether the operation will be remote from the file system that contains the source. Use this option when you are on a different machine from the Administration Server and the deployment files are already at the specified location where the Administration Server is located. This option defaults to false. ■ retireGracefully—Retirement policy to gracefully retire an application only after it has completed all in-flight work. This policy is only meaningful for stop and redeploy operations and is mutually exclusive to the retire timeout policy. ■ retireTimeout—Time (in seconds) WLST waits before retiring an application that has been replaced with a newer version. This option default to -1, which specifies graceful timeout. ■ securityModel—Security model. Valid values include: DDOnly, CustomRoles, CustomRolesAndPolicies, and Advanced. ■ securityValidationEnabled—Boolean value specifying whether security validation is enabled. ■ subModuleTargets—Submodule level targets for JMS modules. For example, submod@mod-jms.xml@target submoduleName@target. ■ testMode—Boolean value specifying whether to start the Web application with restricted access. This option defaults to false. ■ timeout—Time (in milliseconds) that WLST waits for the deployment process to complete before canceling the operation. A value of 0 indicates that the operation will not time out. This argument defaults to 300,000 ms (or 5 minutes). ■ upload—Boolean value specifying whether the application files are uploaded to the WebLogic Server Administration Server's upload directory prior to deployment. Use this option when the Administration Server cannot access the application files through the file system. This option defaults to false. ■ versionIdentifier—Version identifier.

3.5.1.3 Example

The following example deploys the `businessApp` application located at `c:/myapps/business`. A default deployment plan is created.

The `deploy` command returns a `WLSTProgress` object that you can access to check the status of the command. The `WLSTProgress` object is captured in a user-defined variable, in this case, `progress`.

```
wls:/mydomain/serverConfig/Servers> progress= deploy(appName='businessApp',
path='c:/myapps/business',createplan='true')
```

The previous example stores the `WLSTProgress` object returned in a user-defined variable, in this case, `progress`. You can then use the `progress` variable to print the status of the `deploy` command. For example:

```
wls:/mydomain/serverConfig/Servers> progress.printStatus()
Current Status of your Deployment:
Deployment command type: deploy
Deployment State       : completed
Deployment Message    : null
```

```
wls:/mydomain/serverConfig/Servers>
```

For more information about the `WLSTProgress` object, see "WLSTProgress Object" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

The following example deploys the `demoApp` application in the archive file located at `c:/myapps/demos/app/demoApp.ear`, targeting the application modules to `myserver`, and using the deployment plan file located in `c:/myapps/demos/app/plan/plan.xml`. WLST waits 120,000 ms for the process to complete.

```
wls:/mydomain/serverConfig/Servers> deploy('demoApp',
'c:/myapps/demos/app/demoApp.ear', targets='myserver',
planPath='c:/myapps/demos/app/plan/plan.xml', timeout=120000)
```

The following example deploys the `jmsApp` application located at `c:/myapps/demos/jmsApp/demo-jms.xml`, targeting the application module to a specific target.

```
wls:/mydomain/serverConfig/Servers> deploy('jmsApp',path=
'c:/myapps/demos/jmsApps/demo-jms.xml', submoduleTargets='jmsApp@managed1')
```

The following example shows how to set the application version (`appVersion`) to a unique identifier to support production (side-by-side) redeployment. This example deploys the `demoApp` application in the archive file located at `c:/myapps/demos/app/demoApp.ear`, and sets the application and archive version numbers to the specified values.

```
wls:/mydomain/serverConfig> deploy('demoApp', 'c:/myapps/demos/app/demoApp.ear',
archiveVersion='901-101', appVersion='901-102')
```

For more information about production redeployment strategies, see "Redeploying Applications in a Production Environment" in *Oracle Fusion Middleware Deploying Applications to Oracle WebLogic Server*.

3.5.2 distributeApplication

Command Category: Deployment Commands

Use with WLST: Online

3.5.2.1 Description

Copies the deployment bundle to the specified targets. The deployment bundle includes module, configuration data, and any additional generated code. The `distributeApplication` command does not start deployment.

The `distributeApplication` command returns a `WLSTProgress` object that you can access to check the status of the command. For more information about the `WLSTProgress` object, see "WLSTProgress Object" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*. In the event of an error, the command returns a `WLSTException`.

3.5.2.2 Syntax

```
distributeApplication(appPath, [planPath], [targets], [options])
```

Argument	Definition
<i>appPath</i>	Name of the archive file or root of the exploded archive directory to be deployed.
<i>planPath</i>	Optional. Name of the deployment plan file. The filename can be absolute or relative to the application directory. This argument defaults to the <code>plan/plan.xml</code> file in the application directory, if one exists.
<i>targets</i>	Optional. Comma-separated list of targets. Each target may be qualified with a Java EE module name (for example, <code>module1@server1</code>) enabling you to deploy different modules of the application archive on different servers. This argument defaults to the server to which WLST is currently connected.
<i>options</i>	Optional. Comma-separated list of deployment options, specified as name-value pairs. For a list of valid deployment options, see the <i>options</i> argument description in Section 3.5.1, "deploy" .

3.5.2.3 Example

The following example loads the `BigApp` application located in the `c:/myapps` directory, and stores the `WLSTProgress` object in a user-defined variable, in this case, `progress`.

The following example distributes the `c:/myapps/BigApp` application to the `myserver`, `oamserver1`, and `oamcluster` servers, using the deployment plan defined at `c:/deployment/BigApp/plan.xml`.

```
wls:/offline> progress=distributeApplication('c:/myapps/BigApp',
'c:/deployment/BigApp/plan.xml', 'myserver,oamserver1,oamcluster')
Distributing Application and Plan ...
Successfully distributed the application.
```

The previous example stores the `WLSTProgress` object in a user-defined variable, in this case, `progress`. You can then use the `progress` variable to determine if the `distributeApplication` command has completed. For example:

```
wls:/mydomain/serverConfig/Servers> progress.isCompleted()
1
wls:/mydomain/serverConfig/Servers>
```

For more information about the `WLSTProgress` object, see "WLSTProgress Object" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

3.5.3 getWLDM

Command Category: Deployment Commands

Use with WLST: Online

3.5.3.1 Description

Returns the `WebLogicDeploymentManager` object. You can use the object methods to configure and deploy applications. WLST must be connected to an Administration Server to run this command. In the event of an error, the command returns a `WLSTException`.

3.5.3.2 Syntax

```
getWLDM()
```

3.5.3.3 Example

The following example gets the `WebLogicDeploymentManager` object and stores it in the `wldm` variable.

```
wls:/mydomain/serverConfig> wldm=getWLDM()
wls:/mydomain/serverConfig> wldm.isConnected()
1
wls:/mydomain/serverConfig>
```

3.5.4 listApplications

Command Category: Deployment Commands

Use with WLST: Online

3.5.4.1 Description

Lists all applications that are currently deployed in the WebLogic domain.

In the event of an error, the command returns a `WLSTException`.

3.5.4.2 Syntax

```
listApplications()
```

3.5.4.3 Example

The following example lists all the applications currently deployed in `mydomain`.

```
wls:/mydomain/serverConfig> listApplications()
SamplesSearchWebApp
asyncServletEar
jspSimpleTagEar
ejb30
webservicesJwsSimpleEar
ejb20BeanMgedEar
xmlBeanEar
extServletAnnotationsEar
examplesWebApp
apache_xbean.jar
mainWebApp
jdbcRowSetsEar
```

3.5.5 loadApplication

Command Category: Deployment Commands

Use with WLST: Online and Offline

3.5.5.1 Description

Loads an application and deployment plan into memory. When used in online mode, you can connect only to the Administration Server; you cannot connect to a Managed Server.

The `loadApplication` command returns a `WLSTPlan` object that you can access to make changes to the deployment plan. For more information about the `WLSTPlan` object, see "WLSTPlan Object" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*. In the event of an error, the command returns a `WLSTException`.

3.5.5.2 Syntax

```
loadApplication(appPath, [planPath], [createPlan])
```

Argument	Definition
<i>appPath</i>	Name of the top-level parent application directory, archive file, or root of the exploded archive directory containing the application to be loaded.
<i>planPath</i>	Optional. Name of the deployment plan file. The filename can be absolute or relative to the application directory. This argument defaults to the <code>plan/plan.xml</code> file in the application directory, if one exists.
<i>createPlan</i>	Optional. Boolean value specifying whether WLST should create a plan in the application directory if the specified plan does not exist. This argument defaults to <code>true</code> .

3.5.5.3 Example

The following example loads the `c:/myapps/myejb.jar` application using the plan file at `c:/myplans/myejb/plan.xml`.

```
wls:/offline> myPlan=loadApplication('c:/myapps/myejb.jar',
'c:/myplans/myejb/plan.xml')
Loading application from c:/myapps/myejb.jar and deployment plan from
c:/myplans/myejb/plan.xml ...
Successfully loaded the application.
```

The previous example stores the `WLSTPlan` object returned in the `myPlan` variable. You can then use `myPlan` variable to display information about the plan, such as the variables. For example:

```
wls:/offline> myPlan.showVariables()
MyEJB jndi.ejb
MyWAR app.foo
```

For more information about the `WLSTPlan` object, see "WLSTPlan Object" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

3.5.6 redeploy

Command Category: Deployment Commands

Use with WLST: Online

3.5.6.1 Description

Reloads classes and redeploys a previously deployed application.

The `redeploy` command returns a `WLSTProgress` object that you can access to check the status of the command. For more information about the `WLSTProgress` object, see "WLSTProgress Object" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

In the event of an error, the command returns a `WLSTException`.

For more information about redeploying applications, see "Overview of Common Deployment Scenarios" in *Oracle Fusion Middleware Deploying Applications to Oracle WebLogic Server*.

3.5.6.2 Syntax

```
redeploy(appName, [planPath], [options])
```

Argument	Definition
<i>appName</i>	Name of the application to be redeployed.
<i>planPath</i>	Optional. Name of the deployment plan file. The filename can be absolute or relative to the application directory. This argument defaults to the <code>plan/plan.xml</code> file in the application directory, if one exists.
<i>options</i>	<p>Optional. Comma-separated list of deployment options, specified as name-value pairs. For a list of valid deployment options, see <i>options</i> argument description in Section 3.5.1, "deploy".</p> <p>In addition, the following deployment option can be specified for the <code>redeploy</code> command:</p> <ul style="list-style-type: none"> ▪ appPath—Name of the archive file or root of the exploded archive directory to be redeployed. ▪ deploymentPrincipalName—String value specifying the principal for redeploying the file or archive during server starts. You can use this option to overwrite the current <code><deployment-principal-name></code> in the <code>config.xml</code> file.

3.5.6.3 Example

The following example redeploys `myApp` application using the `plan.xml` file located in the `c:/myapps` directory.

```
wls:/mydomain/serverConfig> progress=redeploy('myApp' 'c:/myapps/plan.xml')
Redeploying application 'myApp' ...
Redeployment of 'myApp' is successful
wls:/mydomain/serverConfig>
```

The previous example stores the `WLSTProgress` object returned in a user-defined variable, in this case, `progress`. You can then use the `progress` variable to access the state of the `redeploy` command. For example:

```
wls:/mydomain/serverConfig/Servers> progress.getState()
'completed'
wls:/mydomain/serverConfig/Servers>
```

For more information about the `WLSTProgress` object, see "WLSTProgress Object" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

3.5.7 startApplication

Command Category: Deployment Commands

Use with WLST: Online

3.5.7.1 Description

Starts an application, making it available to users. The application must be fully configured and available in the WebLogic domain.

The `startApplication` command returns a `WLSTProgress` object that you can access to check the status of the command. For more information about the `WLSTProgress` object, see "WLSTProgress Object" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*. In the event of an error, the command returns a `WLSTException`.

3.5.7.2 Syntax

```
startApplication(appName, [options])
```

Argument	Definition
<i>appName</i>	Name of the application to start, as specified in the <code>plan.xml</code> file.
<i>options</i>	Optional. Comma-separated list of deployment options, specified as name-value pairs. For a list of valid deployment options, see <i>options</i> argument description in Section 3.5.1, "deploy" .

3.5.7.3 Example

The following example starts the `BigApp` application with the specified deployment options.

```
wls:/mydomain/serverConfig/Servers> progress=startApplication('BigApp',
stageMode='NOSTAGE', testMode='false')
Starting the application...
Successfully started the application.
```

The previous example stores the `WLSTProgress` object returned in a user-defined variable, in this case, `progress`. You can then use the `progress` variable to access the state of the `startApplication` command. For example:

```
wls:/mydomain/serverConfig/Servers> progress.getState()
'completed'
wls:/mydomain/serverConfig/Servers>
```

For more information about the `WLSTProgress` object, see "WLSTProgress Object" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

3.5.8 stopApplication

Command Category: Deployment Commands

Use with WLST: Online

3.5.8.1 Description

Stops an application, making it unavailable to users. The application must be fully configured and available in the WebLogic domain.

The `stopApplication` command returns a `WLSTProgress` object that you can access to check the status of the command. For more information about the `WLSTProgress` object, see "WLSTProgress Object" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

In the event of an error, the command returns a `WLSTException`.

3.5.8.2 Syntax

```
stopApplication(appName, [options])
```

Argument	Definition
<i>appName</i>	Name of the application to stop, as specified in the <code>plan.xml</code> file.
<i>options</i>	Optional. Comma-separated list of deployment options, specified as name-value pairs. For a list of valid deployment options, see <i>options</i> argument description in Section 3.5.1, "deploy" .

3.5.8.3 Example

The following example stops the `BigApp` application.


```
wls:/offline> progress=stopApplication('BigApp')
Stopping the application...
Successfully stopped the application.
```

The previous example stores the `WLSTProgress` object returned in a user-defined variable, in this case, `progress`. You can then use the `progress` variable to check whether `stopApplication` command is running. For example:

```
wls:/mydomain/serverConfig/Servers> progress.isRunning()
0
wls:/mydomain/serverConfig/Servers>
```

For more information about the `WLSTProgress` object, see "WLSTProgress Object" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

3.5.9 undeploy

Command Category: Deployment Commands

Use with WLST: Online

3.5.9.1 Description

Undeploys an application from the specified servers.

The `undeploy` command returns a `WLSTProgress` object that you can access to check the status of the command. For more information about the `WLSTProgress` object, see "WLSTProgress Object" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*. In the event of an error, the command returns a `WLSTException`.

For more information about deploying and undeploying applications, see "Overview of Common Deployment Scenarios" in *Oracle Fusion Middleware Deploying Applications to Oracle WebLogic Server*.

3.5.9.2 Syntax

```
undeploy(appName, [targets], [options])
```

Argument	Definition
<code>appName</code>	Deployment name for the deployed application.
<code>targets</code>	Optional. List of the target servers from which the application will be removed. If not specified, defaults to all current targets.
<code>options</code>	Optional. Comma-separated list of deployment options, specified as name-value pairs. For a list of valid deployment options, see <code>options</code> argument description in Section 3.5.1, "deploy" .

3.5.9.3 Example

The following example removes the `businessApp` application from all target servers. WLST waits 60,000 ms for the process to complete.

```
wls:/mydomain/serverConfig> undeploy('businessApp', timeout=60000)
Undeploying application businessApp ...
<Jul 20, 2005 9:34:15 AM EDT> <Info> <J2EE Deployment SPI> <BEA-260121>
<Initiating undeploy operation for application, businessApp [archive: null],
to AdminServer .>
Completed the undeployment of Application with status
Current Status of your Deployment:
Deployment command type: undeploy
```

```

Deployment State      : completed
Deployment Message   : no message
wls:/mydomain/serverConfig>

```

3.5.10 updateApplication

Command Category: Deployment Commands

Use with WLST: Online

3.5.10.1 Description

Updates an application configuration using a new deployment plan. The application must be fully configured and available in the WebLogic domain.

The `updateApplication` command returns a `WLSTProgress` object that you can access to check the status of the command. For more information about the `WLSTProgress` object, see "WLSTProgress Object" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*. In the event of an error, the command returns a `WLSTException`.

3.5.10.2 Syntax

```
updateApplication(appName, [planPath], [options])
```

Argument	Definition
<code>appName</code>	Name of the application, as specified in the current <code>plan.xml</code> file.
<code>planPath</code>	Optional. Name of the new deployment plan file. The filename can be absolute or relative to the application directory.
<code>options</code>	Optional. Comma-separated list of deployment options, specified as name-value pairs. For a list of valid deployment options, see <code>options</code> argument description in Section 3.5.1, "deploy" .

3.5.10.3 Example

The following example updates the application configuration for `BigApp` using the `plan.xml` file located in `c:/myapps/BigApp/newPlan`.

```

wls:/offline> progress=updateApplication('BigApp',
'c:/myapps/BigApp/newPlan/plan.xml', stageMode='STAGE', testMode='false')
Updating the application...
Successfully updated the application.

```

The previous example stores the `WLSTProgress` object returned in a user-defined variable, in this case, `progress`. You can then use the `progress` variable to access the state of the `updateApplication` command. For example:

```

wls:/mydomain/serverConfig/Servers> progress.getState()
'completed'
wls:/mydomain/serverConfig/Servers>

```

For more information about the `WLSTProgress` object, see "WLSTProgress Object" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

3.6 Diagnostics Commands

Use the WLST diagnostics commands, listed in [Table 3–6](#), to retrieve diagnostics data by executing queries against the WebLogic Diagnostics Framework (WLDF) data

stores. For more information about WLDF, see *Oracle Fusion Middleware Configuring and Using the Diagnostics Framework for Oracle WebLogic Server*.

Table 3–6 Diagnostic Command for WLST Configuration

This command...	Enables you to...	Use with WLST...
<code>exportDiagnosticData</code>	Execute a query against the specified log file.	Offline
<code>exportDiagnosticDataFromServer</code>	Executes a query on the server side and retrieves the exported WebLogic Diagnostic Framework (WLDF) data.	Online
<code>getAvailableCapturedImages</code>	Returns a list of the previously captured diagnostic images.	Online
<code>saveDiagnosticImageCaptureFile</code>	Downloads the specified diagnostic image capture.	Online
<code>saveDiagnosticImageCaptureEntryFile</code>	Downloads a specific entry from the diagnostic image capture.	Online

3.6.1 exportDiagnosticData

Command Category: Diagnostics Commands

Use with WLST: Offline

3.6.1.1 Description

Executes a query against the specified log file. The results are saved to an XML file.

For more information about the WebLogic Server Diagnostic Service, see *Oracle Fusion Middleware Configuring and Using the Diagnostics Framework for Oracle WebLogic Server*.

In the event of an error, the command returns a `WLSTException`.

3.6.1.2 Syntax

```
exportDiagnosticData([options])
```

Argument	Definition
<i>options</i>	<p>Optional. Comma-separated list of export diagnostic options, specified as name-value pairs. Valid options include:</p> <ul style="list-style-type: none"> ■ beginTimestamp—Timestamp (inclusive) of the earliest record to be added to the result set. This option defaults to 0. ■ endTimestamp—Timestamp (exclusive) of the latest record to be added to the result set. This option defaults to <code>Long.MAX_VALUE</code>. ■ exportFileName—Name of the file to which the data is exported. This option defaults to <code>export.xml</code>. ■ logicalName—Logical name of the log file being read. Valid values include: <code>HarvestedDataArchive</code>, <code>EventsDataArchive</code>, <code>ServerLog</code>, <code>DomainLog</code>, <code>HTTPAccessLog</code>, <code>WebAppLog</code>, <code>ConnectorLog</code>, and <code>JMSMessageLog</code>. This option defaults to <code>ServerLog</code>. ■ logName—Base log filename containing the log data to be exported. This option defaults to <code>myserver.log</code>. ■ logRotationDir—Directory containing the rotated log files. This option defaults to <code>."</code> (the same directory in which the log file is stored). ■ query—Expression specifying the filter condition for the data records to be included in the result set. This option defaults to <code>""</code> (empty string), which returns all data. For more information, see "WLDF Query Language" in <i>Oracle Fusion Middleware Configuring and Using the Diagnostics Framework for Oracle WebLogic Server</i>. ■ storeDir—Location of the diagnostic store for the server. This option defaults to <code>../data/store/diagnostics</code>.

3.6.1.3 Example

The following example executes a query against the `ServerLog` named `myserver.log` and stores the results in the file named `myExport.xml`.

```
wls:/offline/mydomain>exportDiagnosticData(logicalName='ServerLog',
logName='myserver.log', exportFileName='myExport.xml')
{'elfFields': '', 'logName': 'myserver.log', 'logRotationDir': '.',
'endTimeStamp': 9223372036854775807L, 'exportFileName': 'export.xml',
'storeDir': '../data/store/diagnostics', 'logicalName': 'ServerLog',
'query': '', 'beginTimestamp': 0}
```

```
Exporting diagnostic data to export.xml
<Aug 2, 2005 6:58:21 PM EDT> <Info> <Store> <BEA-280050> <Persistent store
"WLS_DIAGNOSTICS" opened: directory="c:\Oracle\Middleware
\wlserver_10.3\server\data\store\diagnostics"
writePolicy="Disabled" blockSize=512 directIO=false driver="wfileio2">
```

```
wls:/mydomain/serverRuntime>
```

3.6.2 exportDiagnosticDataFromServer

Command Category: Diagnostics Commands

Use with WLST: Online

3.6.2.1 Description

Executes a query on the server side and retrieves the exported WebLogic Diagnostic Framework (WLDF) data. The results are saved to an XML file.

For more information about the WebLogic Server Diagnostic Service, see *Oracle Fusion Middleware Configuring and Using the Diagnostics Framework for Oracle WebLogic Server*.

In the event of an error, the command returns a `WLSTException`.

3.6.2.2 Syntax

```
exportDiagnosticDataFromServer([options])
```

Argument	Definition
<i>options</i>	<p>Optional. Comma-separated list of export diagnostic options, specified as name-value pairs. Valid options include:</p> <ul style="list-style-type: none"> ▪ beginTimestamp—Timestamp (inclusive) of the earliest record to be added to the result set. This option defaults to 0. ▪ endTimestamp—Timestamp (exclusive) of the latest record to be added to the result set. This option defaults to <code>Long.MAX_VALUE</code>. ▪ exportFileName—Name of the file to which the data is exported. This option defaults to <code>export.xml</code>. ▪ logicalName—Logical name of the log file being read. Valid values include: <code>HarvestedDataArchive</code>, <code>EventsDataArchive</code>, <code>ServerLog</code>, <code>DomainLog</code>, <code>HTTPAccessLog</code>, <code>WebAppLog</code>, <code>ConnectorLog</code>, and <code>JMSMessageLog</code>. This option defaults to <code>ServerLog</code>. ▪ query—Expression specifying the filter condition for the data records to be included in the result set. This option defaults to "" (empty string), which returns all data.

3.6.2.3 Example

The following example executes a query against the `HTTPAccessLog` and stores the results in the file named `myExport.xml`.

```
wls:/mydomain/serverRuntime>
exportDiagnosticDataFromServer(logicalName="HTTPAccessLog",
exportFileName="myExport.xml")
```

3.6.3 getAvailableCapturedImages

Command Category: Diagnostics Commands

Use with WLST: Online

3.6.3.1 Description

Returns, as an array of strings, a list of the previously captured diagnostic images that are stored in the image destination directory configured on the server. The default directory is `SERVER\logs\diagnostic_images`.

This command is useful for identifying a diagnostic image capture that you want to download, or for identifying a diagnostic image capture from which you want to download a specific entry.

For more information about the WebLogic Server Diagnostic Service, see *Oracle Fusion Middleware Configuring and Using the Diagnostics Framework for Oracle WebLogic Server*.

In the event of an error, the command returns a `WLSTException`.

3.6.3.2 Syntax

```
getAvailableCapturedImages()
```

3.6.3.3 Example

The following example returns an array of strings named `images`, which contains a list of the diagnostic image capture files available in the image destination directory, and prints the entries contained in the diagnostic image named `diagnostic_image_myserver_2009_06_15_14_58_36.zip`.

```
wls:/mydomain/serverRuntime>images=getAvailableCapturedImages()
Connecting to http://localhost:7001 with userid weblogic ...
wls:/mydomain/serverRuntime>print images [ 'diagnostic_image_myserver_2009_06_15_
14_58_36.zip' ]
```

3.6.4 saveDiagnosticImageCaptureFile

Command Category: Diagnostics Commands

Use with WLST: Online

3.6.4.1 Description

Downloads the specified diagnostic image capture from the server to which WLST is currently connected.

For more information about the WebLogic Server Diagnostic Service, see *Oracle Fusion Middleware Configuring and Using the Diagnostics Framework for Oracle WebLogic Server*.

In the event of an error, the command returns a `WLSTException`.

3.6.4.2 Syntax

```
saveDiagnosticImageCaptureFile(imageName, [outputFile])
```

Argument	Definition
<code>imageName</code>	The name of the diagnostic image capture to download.
<code>outputFile</code>	Optional. Local path and file name in which the retrieved diagnostic image capture is to be stored. If not specified, this argument defaults to the value of <code>imageName</code> and the current working directory.

3.6.4.3 Example

The following example retrieves the list of the diagnostic image captures that are stored in the image destination directory on the server. It then shows two uses of the `saveDiagnosticImageCaptureFile` command. In the first use, the first diagnostic image capture in the list is downloaded to the local machine using the default output file name. In the second use, the first diagnostic image capture in the list is downloaded to the local machine in the file `mylocalimg.zip`.

```
wls:/mydomain/serverRuntime>images=getAvailableCapturedImages()
Connecting to http://localhost:7001 with userid weblogic ...
wls:/mydomain/serverConfig> saveDiagnosticImageCaptureFile(images[0])
Retrieving diagnostic_image_myserver_2009_06_25_12_12_50.zip to local
path diagnostic_image_myserver_2009_06_25_12_12_50.zip
Connecting to http://localhost:7001 with userid weblogic ...
wls:/mydomain/serverConfig> saveDiagnosticImageCaptureFile(images[0],
'mylocalimg.zip')
Retrieving diagnostic_image_myserver_2009_06_25_12_12_50.zip to local
path mylocalimg.zip
Connecting to http://localhost:7001 with userid weblogic ...
```

3.6.5 saveDiagnosticImageCaptureEntryFile

Command Category: Diagnostics Commands

Use with WLST: Online

3.6.5.1 Description

Downloads a specific entry from the diagnostic image capture that is located on the server to which WLST is currently connected.

For more information about the WebLogic Server Diagnostic Service, see *Oracle Fusion Middleware Configuring and Using the Diagnostics Framework for Oracle WebLogic Server*.

In the event of an error, the command returns a `WLSTException`.

3.6.5.2 Syntax

```
saveDiagnosticImageCaptureEntryFile(imageName, imageEntryName, [outputFile])
```

Argument	Definition
<i>imageName</i>	Name of the diagnostic image capture containing the desired entry.
<i>imageEntryName</i>	Name of the specific entry to be retrieved from the diagnostic image capture. This can be one of the following: image.summary JTA.img JRockitFlightRecorder.jfr FlightRecording.jfr WatchSource.img configuration.img WORK_MANAGER.img JNDI_IMAGE_SOURCE.img APPLICATION.img InstrumentationImageSource.img SAF.img Logging.img PERSISTENT_STORE.img JDBC.img PathService.img JMS.img Deployment.img JVM.img CONNECTOR.img
<i>outputFile</i>	Optional. Local path and file name in which the entry retrieved from the diagnostic image capture is to be stored. If not specified, this argument defaults to the value of <i>imageEntryName</i> and the current working directory.

3.6.5.3 Example

The following example gets the list of diagnostic image captures, then uses the `saveDiagnosticImageCaptureEntryFile` twice. In the first use, this example retrieves the image summary to the local machine using the default output file name. In the second use, it retrieves the image summary to the local machine in the file `myimage.summary`.

```
wls:/mydomain/serverRuntime> images=getAvailableCapturedImages()
Connecting to http://localhost:7001 with userid weblogic ...
wls:/mydomain/serverConfig> saveDiagnosticImageCaptureEntryFile(images[0],
'image.summary')
```

```

Retrieving entry image.summary from diagnostic_image_myserver_2009_06_25_12_12_
50.zip to local path image.summary
Connecting to http://localhost:7001 with userid weblogic ...
wls:/mydomain/serverConfig> saveDiagnosticImageCaptureEntryFile(images[0],
'image.summary', 'myimage.summary')
Retrieving entry image.summary from diagnostic_image_myserver_2009_06_25_12_12_
50.zip to local path myimage.summary
Connecting to http://localhost:7001 with userid weblogic ...

```

3.7 Editing Commands

Use the WLST editing commands, listed in [Table 3-7](#), to interrogate and edit configuration beans.

Note: To edit configuration beans, you must be connected to an Administration Server, and you must navigate to the edit tree and start an edit session, as described in [Section 3.11.5, "edit"](#) and [Section 3.7.17, "startEdit"](#), respectively.

If you connect to a Managed Server, WLST functionality is limited to browsing the configuration bean hierarchy. While you cannot use WLST to change the values of MBeans on Managed Servers, it is possible to use the Management APIs to do so. Oracle recommends that you change only the values of configuration MBeans on the Administration Server. Changing the values of MBeans on Managed Servers can lead to an inconsistent domain configuration.

For more information about editing configuration beans, see "Using WLST Online to Update an Existing WebLogic Domain" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

Table 3-7 Editing Commands for WLST Configuration

This command...	Enables you to...	Use with WLST...
activate	Activate changes saved during the current editing session but not yet deployed.	Online or Offline
assign	Assign resources to one or more destinations.	Offline
cancelEdit	Cancel an edit session, release the edit lock, and discard all unsaved changes. This operation can be called by any user with administrator privileges, even if the user did not start the edit session.	Online
create	Create a configuration bean of the specified type for the current bean.	Online or Offline
delete	Delete an instance of a configuration for the current configuration bean.	Online or Offline
encrypt	Encrypt the specified string.	Online
get	Return the value of the specified attribute.	Online or Offline
getActivationTask	Return the latest <code>ActivationTask</code> MBean on which a user can get status.	Online
invoke	Invokes a management operation on the current configuration bean.	Online

Table 3–7 (Cont.) Editing Commands for WLST Configuration

This command...	Enables you to...	Use with WLST...
<code>isRestartRequired</code>	Determine whether a server restart is required.	Online
<code>loadDB</code>	Load SQL files into a database.	Offline
<code>loadProperties</code>	Load property values from a file.	Online or Offline
<code>save</code>	Save the edits that have been made but have not yet been saved.	Online
<code>set</code>	Set the specified attribute value for the current configuration bean.	Online or Offline
<code>setOption</code>	Set options related to a WebLogic domain creation or update.	Offline
<code>showChanges</code>	Show the changes made to the configuration by the current user during the current edit session.	Online
<code>startEdit</code>	Starts a configuration edit session on behalf of the currently connected user.	Online
<code>stopEdit</code>	Stop the current edit session, release the edit lock, and discard unsaved changes.	Online
<code>unassign</code>	Unassign applications or resources from one or more destinations.	Offline
<code>undo</code>	Revert all unsaved or unactivated edits.	Online
<code>validate</code>	Validate the changes that have been made but have not yet been saved.	Online

3.7.1 activate

Command Category: Editing Commands

Use with WLST: Online

3.7.1.1 Description

Activates changes saved during the current editing session but not yet deployed. This command prints a message if a server restart is required for the changes that are being activated.

The `activate` command returns the latest `ActivationTask` MBean which reflects the state of changes that a user is currently making or has made recently. You can then invoke methods to get information about the latest Configuration Manager activate task in progress or just completed. In the event of an error, the command returns a `WLSTException`.

3.7.1.2 Syntax

```
activate([timeout], [block])
```

Argument	Definition
<code>timeout</code>	Optional. Time (in milliseconds) that WLST waits for the activation of configuration changes to complete before canceling the operation. A value of -1 indicates that the operation will not time out. This argument defaults to 300,000 ms (or 5 minutes).

Argument	Definition
<i>block</i>	Optional. Boolean value specifying whether WLST should block user interaction until the command completes. This argument defaults to <code>false</code> , indicating that user interaction is not blocked. In this case, WLST returns control to the user after issuing the command and assigns the task MBean associated with the current task to a variable that you can use to check its status. If you are importing WLST as a Jython module, as described in "Importing WLST as a Jython Module" in <i>Oracle Fusion Middleware Oracle WebLogic Scripting Tool</i> , <i>block</i> is always set to <code>true</code> .

3.7.1.3 Example

The following example activates the changes made during the current edit session that have been saved to disk, but that have not yet been activated. WLST waits for 100,000 ms for the activation to complete, and 200,000 ms before the activation is stopped.

```
wls:/mydomain/edit !> activate(200000, block='true')
Activating all your changes, this may take a while ...
The edit lock associated with this edit session is released once the activation is
completed.
Action completed.
wls:/mydomain/edit>
```

3.7.2 assign

Command Category: Editing Commands

Use with WLST: Offline

3.7.2.1 Description

Assigns resources to one or more destinations.

In the event of an error, the command returns a `WLSTException`.

3.7.2.2 Syntax

```
assign(sourceType, sourceName, destinationType, destinationName)
```

Argument	Definition
<i>sourceType</i>	Type of configuration bean to be assigned. This value can be set to one of the following values: <ul style="list-style-type: none"> ▪ <code>AppDeployment</code> ▪ <code>Library</code> ▪ <code>securityType</code> (such as <code>User</code>) ▪ <code>Server</code> ▪ <code>service</code> (such as <code>JDBCSystemResource</code>) ▪ <code>service.SubDeployment</code>, where <i>service</i> specifies the service type of the <code>SubDeployment</code> (such as <code>JMSSystemResource.SubDeployment</code>); you can also specify nested subdeployments (such as <code>AppDeployment.SubDeployment.SubDeployment</code>) <p>Guidelines for setting this value are provided below.</p>

Argument	Definition
<i>sourceName</i>	<p>Name of the resource to be assigned. Multiple names can be specified, separated by commas, or you can use the wildcard (*) character to specify all resources of the specified type.</p> <p>Specify subdeployments using the following format: <i>service.subDeployment</i>, where <i>service</i> specifies the parent service and <i>subDeployment</i> specifies the name of the subdeployment. For example, <i>myJMSResource.myQueueSubDeployment</i>. You can also specify nested subdeployments, such as <i>MedRecEAR.MedRecAppScopedJMS.MedRecJMSServer</i>.</p> <p>Note: A given subdeployment name cannot contain a dot (.), as the assign command will interpret it as a nested subdeployment.</p>
<i>destinationType</i>	Type of destination. Guidelines for setting this value are provided below.
<i>destinationName</i>	Name of the destination. Multiple names can be specified, separated by commas.

Use the following guidelines for setting the *sourceType* and *destinationType*:

- When assigning **application deployments**, set the values as follows:
 - *sourceType*: *AppDeployment*
 - *destinationType*: *Target*
- When assigning **libraries**, set the values as follows:
 - *sourceType*: *Library*
 - *destinationType*: *Target*
- When assigning **services**, set the values as follows:
 - *sourceType*: Name of the specific server, such as *JDBCSystemResource*
 - *destinationType*: *Target*
- When assigning **servers to clusters**, set the values as follows:
 - *sourceType*: *Server*
 - *destinationType*: *Cluster*
- When assigning **subdeployments**, set the values as follows:
 - *sourceType*: *service.SubDeployment*, where *service* specifies the parent of the *SubDeployment*, such as *JMSSystemResource.SubDeployment*; you can also specify nested subdeployments (such as *AppDeployment.SubDeployment.SubDeployment*)
 - *destinationType*: *Target*
- When assigning **security types**, set the values as follows:
 - *sourceType*: Name of the security type, such as *User*
 - *destinationType*: Name of the destination security type, such as *Group*

3.7.2.3 Example

The following examples:

- Assign the servers *myServer* and *myServer2* to the cluster *myCluster*.

```
wls:/offline/mydomain> assign("Server", "myServer,myServer2", "Cluster",
"myCluster")
```

- Assign all servers to the cluster `myCluster`.

```
wls:/offline/mydomain> assign("Server", "*", "Cluster", "myCluster")
```

- Assign the application deployment `myAppDeployment` to the target server `newServer`.

```
wls:/offline/mydomain> assign("AppDeployment", "myAppDeployment", "Target",
"newServer")
```

- Assign the user `newUser` to the group `Monitors`.

```
wls:/offline/mydomain> assign("User", "newUser", "Group", "Monitors")
```

- Assign the SubDeployment `myQueueSubDeployment`, which is a child of the JMS resource `myJMSResource`, to the target server `newServer`.

```
wls:/offline/mydomain> assign('JMSSystemResource.SubDeployment',
'myJMSResource.myQueueSubDeployment', 'Target', 'newServer')
```

- Assign the nested SubDeployment `MedRecAppScopedJMS.MedRecJMSServer`, which is a child of the AppDeployment `AppDeployment`, to the target server `AdminServer`.

```
wls:/offline/mydomain>assign('AppDeployment.SubDeployment.SubDeployment
', 'MedRecEAR.MedRecAppScopedJMS.MedRecJMSServer', 'Target', 'AdminServer')
```

3.7.3 cancelEdit

Command Category: Editing Commands

Use with WLST: Online

3.7.3.1 Description

Cancels an edit session, releases the edit lock, and discards all unsaved changes.

The user issuing this command does not have to be the current editor; this allows an administrator to cancel an edit session, if necessary, to enable other users to start an edit session.

In the event of an error, the command returns a `WLSTException`.

3.7.3.2 Syntax

```
cancelEdit([defaultAnswer])
```

Argument	Definition
<i>defaultAnswer</i>	Optional. Default response, if you would prefer not to be prompted at the command line. Valid values are <code>y</code> and <code>n</code> . This argument defaults to null, and WLST prompts you for a response.

3.7.3.3 Example

The following example cancels the current editing session. WLST prompts for verification before canceling.

```
wls:/mydomain/edit !> cancelEdit()
Sure you would like to cancel the edit session? (y/n)y
```

```
Edit session is cancelled successfully
wls:/mydomain/edit>
```

3.7.4 create

Command Category: Editing Commands

Use with WLST: Online or Offline

3.7.4.1 Description

Creates a configuration bean of the specified type for the current bean.

The `create` command returns a stub for the newly created configuration bean. In the event of an error, the command returns a `WLSTException`.

Note: Child types must be created under an instance of their parent type. You can only create configuration beans that are children of the current Configuration Management Object (`cmo`) type. For more information about the `cmo` variable, see "Changing the Current Management Object" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

Please note the following when using the `create` command with **WLST online**:

- You must be connected to an Administration Server. You cannot use the `create` command for runtime MBeans or when WLST is connected to a Managed Server instance.
- You must navigate to the edit configuration MBean hierarchy using the `edit` command before issuing this command. See [Section 3.11.5, "edit"](#).
- You can use the `create` command to create a WebLogic Server configuration MBean that is a child of the current MBean type.

Please note the following when using the `create` command with **WLST offline**:

- When using WLST offline, the following characters are not valid in object names: period (`.`), forward slash (`/`), or backward slash (`\`).

For more information about:

- Creating MBeans, see "Understanding WebLogic Server MBeans" in *Developing Custom Management Utilities with JMX*.
- Examples of creating specific types of MBean resources, for example, a JMS or JDBC system resource, refer to the WLST sample scripts installed with your product, as described in "WLST Sample Scripts" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.
- MBeans, their child types, attributes, and operations, see *Oracle Fusion Middleware Oracle WebLogic Server MBean Reference*.

3.7.4.2 Syntax

```
create(name, childMBeanType, [baseProviderType])
```

Argument	Definition
<code>name</code>	Name of the configuration bean that you are creating.

Argument	Definition
<i>childMBeanType</i>	Type of configuration bean that you are creating. You can create instances of any type defined in the <code>config.xml</code> file except custom security types. For more information about valid configuration beans, see <i>Oracle Fusion Middleware Oracle WebLogic Server MBean Reference</i> .
<i>baseProviderType</i>	When creating a security provider, specifies the base security provider type, for example, <code>AuthenticationProvider</code> . This argument defaults to <code>None</code> .

3.7.4.3 Example

The following example creates a child configuration bean of type `Server` named `newServer` for the current configuration bean, storing the stub as `server1`:

```
wls:/mydomain/edit !> server1=create('newServer','Server')
Server with name 'newServer' has been created successfully.
wls:/mydomain/edit !> server1.getName()
'newServer'
wls:/mydomain/edit !>
```

The following example creates an authentication provider security provider called `myProvider`:

```
wls:/mydomain/edit !> cd('SecurityConfiguration/mydomain/Realms/myrealm')
wls:/mydomain/edit !>
create('myProvider','weblogic.security.providers.authentication.SQLOAuthenticator',
'AuthenticationProvider')
wls:/mydomain/edit !> cd('AuthenticationProviders/myProvider')
wls:/mydomain/edit !> set('ControlFlag','REQUIRED')
```

The following example creates a machine named `highsec_nm` and sets attributes for the associated Node Manager.

```
wls:/mydomain/edit !> create('highsec_nm','Machine')
wls:/mydomain/edit !> cd('Machine/highsec_nm/NodeManager/highsec_nm')
wls:/mydomain/edit !> set('DebugEnabled','true')
wls:/mydomain/edit !> set('ListenAddress','innes')
wls:/mydomain/edit !> set('NMType','SSL')
wls:/mydomain/edit !> set('ShellCommand','')
```

3.7.5 delete

Command Category: Editing Commands

Use with WLST: Online or Offline

3.7.5.1 Description

Deletes an instance of a configuration bean of the specified type for the current configuration bean.

In the event of an error, the command returns a `WLSTException`.

Note: You can only delete configuration beans that are children of current Configuration Management Object (`cmo`) type. For more information about the `cmo` variable, see "Changing the Current Management Object" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

3.7.5.2 Syntax

```
delete(name, childMBeanType)
```

Argument	Definition
<i>name</i>	Name of the child configuration bean to delete.
<i>childMBeanType</i>	Type of the configuration bean to be deleted. You can delete instances of any type defined in the <code>config.xml</code> file. For more information about valid configuration beans, see <i>Oracle Fusion Middleware Oracle WebLogic Server MBean Reference</i> .

3.7.5.3 Example

The following example deletes the configuration bean of type `Server` named `newServer`:

```
wls:/mydomain/edit !> delete('newServer','Server')
Server with name 'newServer' has been deleted successfully.
wls:/mydomain/edit !>
```

3.7.6 encrypt

Command Category: Editing Commands

Use with WLST: Online

3.7.6.1 Description

Encrypts the specified string. You can then use the encrypted string in your configuration file or as an argument to a command.

You must invoke this command once for each WebLogic domain in which you want to use the encrypted string. The string can be used only in the WebLogic domain for which it was originally encrypted.

In the event of an error, the command returns a `WLSTException`.

3.7.6.2 Syntax

```
encrypt(obj, [domainDir])
```

Argument	Definition
<i>obj</i>	String that you want to encrypt.
<i>domainDir</i>	Optional. Absolute path name of a WebLogic domain directory. The encrypted string can be used only by the WebLogic domain that is contained within the specified directory. If you do not specify this argument, the command encrypts the string for use in the WebLogic domain to which WLST is currently connected.

3.7.6.3 Example

The following example encrypts the specified string using the `security/SerializedSystemIni.dat` file in the specified WebLogic domain directory.

```
wls:/mydomain/serverConfig>
es=encrypt('myPassword','c:/Oracle/Middleware/domains/mydomain')
```

3.7.7 get

Command Category: Editing Commands

Use with WLST: Online or Offline

3.7.7.1 Description

Returns the value of the specified attribute. For more information about the MBean attributes that can be viewed, see *Oracle WebLogic Server MBean Reference*. In the event of an error, the command returns a `WLSTException`.

Note: You can list all attributes and their current values by entering `ls('a')`. For more information, see [Section 3.8.12, "ls"](#).

Alternatively, you can use the `cmo` variable to perform any `get` method on the current configuration bean. For example:

```
cmo.getListenPort()
```

For more information about the `cmo` variable, see "Changing the Current Management Object" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

3.7.7.2 Syntax

```
get(attrName)
```

Argument	Definition
<code>attrName</code>	Name of the attribute to be displayed. You can specify the full pathname of the attribute. If no pathname is specified, the attribute is displayed for the current configuration object.

3.7.7.3 Example

The following example returns the value of the `AdministrationPort` for the current configuration bean.

```
wls:/mydomain/serverConfig> get('AdministrationPort')
9002
```

Alternatively, you can use the `cmo` variable:

```
cmo.getAdministrationPort()
```

3.7.8 getActivationTask

Command Category: Editing Commands

Use with WLST: Online

3.7.8.1 Description

Return the latest `ActivationTask` MBean on which a user can get status. The `ActivationTask` MBean reflects the state of changes that a user has made recently in WLST. You can then invoke methods to get information about the latest Configuration Manager activate task in progress or just completed. In the event of an error, the command returns a `WLSTException`.

Note: If you have activated changes outside of WLST, use the ConfigurationManagerMBean `getActivationTasks()` method to get access to Activation Tasks created in other tools.

3.7.8.2 Syntax

```
getActivationTask()
```

3.7.8.3 Example

The following example returns the latest `ActivationTask` MBean on which a user can get status and stores it within the task variable.

```
wls:/mydomain/edit> task=getActivationTask()
wls:/mydomain/edit> if task!=None:
...   task.getState()
...
4
```

3.7.9 invoke

Command Category: Editing Commands

Use with WLST: Online

3.7.9.1 Description

Invokes a management operation on the current configuration bean. Typically, you use this command to invoke operations other than the `get` and `set` operations that most WebLogic Server configuration beans provide. The class objects are loaded through the same class loader that is used for loading the configuration bean on which the action is invoked.

You cannot use the `invoke` command when WLST is connected to a Managed Server instance.

If successful, the `invoke` command returns the object that is returned by the operation invoked. In the event of an error, the command returns a `WLSTException`.

3.7.9.2 Syntax

```
invoke(methodName, parameters, signatures)
```

Argument	Definition
<i>methodName</i>	Name of the method to be invoked.
<i>parameters</i>	An array of parameters to be passed to the method call.
<i>signatures</i>	An array containing the signature of the action.

3.7.9.3 Example

The following example invokes the `lookupServer` method on the current configuration bean.

```
wls:/mydomain/config> objs =
jarray.array([java.lang.String("oamserver")], java.lang.Object)
wls:/mydomain/edit> strs = jarray.array(["java.lang.String"], java.lang.String)
wls:/mydomain/edit> invoke('lookupServer', objs, strs)
true
```

```
wls:/mydomain/edit>
```

3.7.10 isRestartRequired

Command Category: Editing Commands

Use with WLST: Online

3.7.10.1 Description

Determines whether a server restart is required.

If you invoke this command while an edit session is in progress, the response is based on the edits that are currently in progress. If you specify the name of an attribute, WLST indicates whether a server restart is required for that attribute only.

In the event of an error, the command returns a `WLSTException`.

3.7.10.2 Syntax

```
isRestartRequired([attributeName])
```

Argument	Definition
<i>attributeName</i>	Optional. Name of a specific attribute for which you want to check if a server restart is required.

3.7.10.3 Example

The following example specifies whether a server restart is required for all changes made during the current WLST session.

```
wls:/mydomain/edit !> isRestartRequired()
Server re-start is REQUIRED for the set of changes in progress.
```

The following attribute(s) have been changed on MBeans that require server re-start.

```
MBean Changed : mydomain:Name=mydomain,Type=Domain
Attributes changed : AutoConfigurationSaveEnabled
```

The following example specifies whether a server restart is required if you edit the `ConsoleEnabled` attribute.

```
wls:/mydomain/edit !> isRestartRequired("ConsoleEnabled")
Server re-start is REQUIRED if you change the attribute ConsoleEnabled
wls:/mydomain/edit !>
```

3.7.11 loadDB

Command Category: Editing Commands

Use with WLST: Offline

3.7.11.1 Description

Loads SQL files into a database.

The `loadDB` command loads the SQL files from a template file. This command can only be issued after a domain template or extension template has been loaded into memory (see [Section 3.3.8, "readDomain"](#) and [Section 3.3.9, "readTemplate"](#)).

Before executing this command, ensure that the following conditions are true:

- The appropriate database is running.
- SQL files exist for the specified database and version.

To verify that the appropriate SQL files exist, open the domain template and locate the relevant SQL file list, `jdbc.index`, in the `_jdbc_` directory. For example, for Oracle 9i, the SQL file list is located at `_jdbc_\Oracle\9i\jdbc.index`.

The command fails if the above conditions are not met.

In the event of an error, the command returns a `WLSTException`.

3.7.11.2 Syntax

```
loadDB(dbVersion, datasourceName, dbCategory)
```

Argument	Definition
<i>dbVersion</i>	Version of the database for which the SQL files are intended to be used.
<i>datasourceName</i>	Name of the JDBC data source to be used to load SQL files.
<i>dbCategory</i>	Optional. Database category associated with the specified data source. For more information about the <code>jdbc.index</code> file and database categories, see "Files Typically Included in a Template" in the <i>Oracle WebLogic Server Domain Template Reference</i> .

3.7.11.3 Example

The following example loads SQL files related to Drop/Create P13N Database Objects intended for version 5.1 of the database, using the `p13nDataSource` JDBC data source.

```
wls:/offline/mydomain> loadDB('5.1', 'p13nDataSource', 'Drop/Create P13N Database Objects')
```

3.7.12 loadProperties

Command Category: Editing Commands

Use with WLST: Online and Offline

3.7.12.1 Description

Loads property values from a file and makes them available in the WLST session.

This command cannot be used when you are importing WLST as a Jython module, as described in "Importing WLST as a Jython Module" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

In the event of an error, the command returns a `WLSTException`.

3.7.12.2 Syntax

```
loadProperties(fileName)
```

Argument	Definition
<i>fileName</i>	Properties file pathname.

3.7.12.3 Example

This example gets and sets the properties file values.

```
wls:/mydomain/serverConfig> loadProperties('c:/temp/myLoad.properties')
```

3.7.13 save

Command Category: Editing Commands

Use with WLST: Online

3.7.13.1 Description

Saves the edits that have been made but have not yet been saved. This command is only valid when an edit session is in progress. For information about starting an edit session, see [Section 3.7.17, "startEdit"](#).

In the event of an error, the command returns a `WLSTException`.

3.7.13.2 Syntax

```
save()
```

3.7.13.3 Example

The following example saves the edits that have not yet been saved to disk.

```
wls:/mydomain/edit !> save()
Saving all your changes ...
Saved all your changes successfully.
wls:/mydomain/edit !>
```

3.7.14 set

Command Category: Editing Commands

Use with WLST: Online or Offline

3.7.14.1 Description

Sets the value of a specified attribute in the current management object. When using WLST offline, this command writes the attribute value to the domain configuration files. When using WLST online, this command sets the value of an MBean attribute. Online changes are written to the domain configuration file when you activate your edits.

In the event of an error, the command returns a `WLSTException`.

For information about setting encrypted attributes (all encrypted attributes have names that end with `Encrypted`), see "Writing and Reading Encrypted Configuration Values" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

Note the following when using **WLST online**:

- You must be in an edit session to use this command. See [Section 3.7.17, "startEdit"](#).
- You cannot use this command when WLST is connected to a Managed Server.
- As an alternative to this command, you can use the `cmo` variable with the following syntax:

```
cmo.setAttrName(value)
```

For example, instead of using `set('ListenPort', 7011)`, you can use:

```
cmo.setListenPort(7011)
```

For more information about the `cmo` variable, see "Changing the Current Management Object" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

3.7.14.2 Syntax

```
set(attrName, value)
```

Argument	Definition
<code>attrName</code>	Name of the attribute to be set.
<code>value</code>	Value of the attribute to be set. Note: This value should <i>not</i> be enclosed in single or double quotes. See the examples.

3.7.14.3 Example

The following example sets the `ArchiveConfigurationCount` attribute of `DomainMBean` to 10:

```
wls:/mydomain/serverConfig> set('ArchiveConfigurationCount', 10)
```

The following example sets the long value of the `T1TimerInterval` attribute of a custom Mbean to 123:

```
wls:/mydomain/serverConfig> set('T1TimerInterval', Long(123))
```

The following example sets the boolean value of the `MyBooleanAttribute` attribute of a custom Mbean to true:

```
wls:/mydomain/serverConfig> set('MyBooleanAttribute', Boolean(true))
```

3.7.15 setOption

Command Category: Editing Commands

Use with WLST: Offline

3.7.15.1 Description

Sets options related to a WebLogic domain creation or update. In the event of an error, the command returns a `WLSTException`.

3.7.15.2 Syntax

```
setOption(optionName, optionValue)
```

Argument	Definition
<i>optionName</i>	<p>Name of the option to set.</p> <p>Available options for domain creation include:</p> <ul style="list-style-type: none"> ■ CreateStartMenu—Boolean value specifying whether to create a Start Menu shortcut on a Windows platform. This option defaults to <code>true</code>. <p>Note: If a user with Administrator privileges installed the software and chose to create the Start menu entries in the All Users folder, only users with Administrator privileges can create Start menu entries in the same folder when creating a WebLogic domain using the Configuration Wizard or WLST. That is, if a user without Administrator privileges uses the Configuration Wizard or WLST from this installation to create domains, Start menu shortcuts to the domains are not created. In this case, the users can manually create shortcuts in their local Start menu folder, if desired.</p> ■ DomainName—Name of the WebLogic domain. By default, the name of the WebLogic domain is derived from the name of the domain directory. For example, for a WebLogic domain saved to <code>c:/Oracle/Middleware/user_projects/domains/myMedrec</code>, the domain name is <code>myMedrec</code>. By setting DomainName, the name of the created domain will be independent of the domain directory name. ■ JavaHome—Home directory for the JVM to be used when starting the server. The default for this option depends on the platform on which you install WebLogic Server. ■ OverwriteDomain—Boolean value specifying whether to allow an existing WebLogic domain to be overwritten. This option defaults to <code>false</code>. ■ ServerStartMode—Mode to use when starting the server for the newly created WebLogic domain. This value can be <code>dev</code> (development) or <code>prod</code> (production). This option defaults to <code>dev</code>. <p>Available options for domain updates include:</p> <ul style="list-style-type: none"> ■ AllowCasualUpdate—Boolean value specifying whether to allow a WebLogic domain to be updated without adding an extension template. This option defaults to <code>true</code>. ■ ReplaceDuplicates—Boolean value specifying whether to keep original configuration elements in the WebLogic domain or replace the elements with corresponding ones from an extension template when there is a conflict. This option defaults to <code>true</code>. <p>Available options for both domain creation and domain updates include:</p> <ul style="list-style-type: none"> ■ AppDir—Application directory to be used when a separate directory is desired for applications, as specified by the template. This option defaults to <code>WL_HOME/user_projects/applications/domainname</code>, where <code>WL_HOME</code> specifies the WebLogic Server home directory and <code>domainname</code> specifies the name of the WebLogic domain. ■ AutoAdjustSubDeploymentTarget—Boolean value specifying whether WLST automatically adjusts targets for the subdeployments of AppDeployments. This option defaults to <code>true</code>. To deactivate this feature, set the option to <code>false</code> and explicitly set the targeting for AppDeployment subdeployments before writing or updating the WebLogic domain or domain template. ■ AutoDeploy—Boolean value specifying whether to activate auto deployment when a cluster or multiple Managed Servers are created. This option defaults to <code>true</code>. To deactivate this feature, set the option to <code>false</code> on the first line of your script.
<i>optionValue</i>	<p>Value for the option.</p> <p>Note: Boolean values can be specified as a String (<code>true</code>, <code>false</code>) or integer (0, 1).</p>

3.7.15.3 Example

The following example sets the `CreateStartMenu` option to `false`:

```
wls:/offline> setOption('CreateStartMenu', 'false')
```

3.7.16 showChanges

Command Category: Editing Commands

Use with WLST: Online

3.7.16.1 Description

Shows the changes made to the configuration by the current user during the current edit session. In the event of an error, the command returns a `WLSTException`.

3.7.16.2 Syntax

```
showChanges ([onlyInMemory])
```

Argument	Definition
<i>onlyInMemory</i>	Optional. Boolean value specifying whether to display only the changes that have not yet been saved. This argument defaults to <code>false</code> , indicating that all changes that have been made from the start of the session are displayed.

3.7.16.3 Example

The following example shows all of the changes made by the current user to the configuration since the start of the current edit session.

```
wls:/mydomain/edit !> showChanges ()
```

Changes that are in memory and saved to disc but not yet activated are:

```
MBean Changed          : com.bea:Name=basicWLSDomain,Type=Domain
Operation Invoked      : add
Attribute Modified     : Machines
Attributes Old Value   : null
Attributes New Value   : Mach1
Server Restart Required : false
```

```
MBean Changed          : com.bea:Name=basicWLSDomain,Type=Domain
Operation Invoked      : add
Attribute Modified     : Servers
Attributes Old Value   : null
Attributes New Value   : myserver
Server Restart Required : false
```

3.7.17 startEdit

Command Category: Editing Commands

Use with WLST: Online

3.7.17.1 Description

Starts a configuration edit session on behalf of the currently connected user. You must navigate to the edit configuration MBean hierarchy using the `edit` command before issuing this command. For more information, see [Section 3.11.5, "edit"](#).

This command must be called prior to invoking any command to modify the WebLogic domain configuration.

In the event of an error, the command returns a `WLSTException`.

Note: WLST automatically starts an edit session if it detects that there is an edit session that is already in progress by the same user, which may have been started via the Administration Console or another WLST session.

3.7.17.2 Syntax

```
startEdit([waitTimeInMillis], [timeoutInMillis], [exclusive])
```

Argument	Definition
<i>waitTimeInMillis</i>	Optional. Time (in milliseconds) that WLST waits until it gets a lock, in the event that another user has a lock. This argument defaults to 0 ms.
<i>timeOutInMillis</i>	Optional. Timeout (in milliseconds) that WLST waits to release the edit lock. This argument defaults to -1 ms, indicating that this edit session never expires.
<i>exclusive</i>	Optional. Specifies whether the edit session should be an exclusive session. If set to <code>true</code> , if the same owner enters the <code>startEdit</code> command, WLST waits until the current edit session lock is released before starting the new edit session. The exclusive lock times out according to the time specified in <i>timeOutInMillis</i> . This argument defaults to <code>false</code> .

3.7.17.3 Example

The following example saves the edits that have not yet been saved to disk.

```
wls:/mydomain/edit> startEdit(60000, 120000)
Starting an edit session ...
Started edit session, please be sure to save and activate your changes once you
are done.
wls:/mydomain/edit !>
```

3.7.18 stopEdit

Command Category: Editing Commands

Use with WLST: Online

3.7.18.1 Description

Stops the current edit session, releases the edit lock, and discards unsaved changes.

In the event of an error, the command returns a `WLSTException`.

3.7.18.2 Syntax

```
stopEdit([defaultAnswer])
```

Argument	Definition
<i>defaultAnswer</i>	Optional. Default response, if you would prefer not to be prompted at the command line. Valid values are <code>y</code> and <code>n</code> . This argument defaults to null, and WLST prompts you for a response.

3.7.18.3 Example

The following example stops the current editing session. WLST prompts for verification before canceling.

```
wls:/mydomain/edit !> stopEdit()
Sure you would like to stop your edit session? (y/n)
y
Edit session has been stopped successfully.
wls:/mydomain/edit>
```

3.7.19 unassign

Command Category: Editing Commands

Use with WLST: Offline

3.7.19.1 Description

Unassign applications or resources from one or more destinations.

In the event of an error, the command returns a `WLSTException`.

3.7.19.2 Syntax

```
unassign(sourceType, sourceName, destinationType, destinationName)
```

Argument	Definition
<i>sourceType</i>	Type of configuration bean to be unassigned. This value can be set to one of the following values: <ul style="list-style-type: none"> ▪ <code>AppDeployment</code> ▪ <code>Library</code> ▪ <code>securityType</code> (such as <code>User</code>) ▪ <code>Server</code> ▪ <code>service</code> (such as <code>JDBCSystemResource</code>) ▪ <code>service.SubDeployment</code>, where <code>service</code> specifies the service type of the <code>SubDeployment</code> (such as <code>JMSSystemResource.SubDeployment</code>); you can also specify nested subdeployments (such as <code>AppDeployment.SubDeployment.SubDeployment</code>)
<i>sourceName</i>	Name of the application or resource to be unassigned. Multiple names can be specified, separated by commas, or you can use the wildcard (*) character to specify all resources of the specified type. Specify subdeployments using the following format: <code>service.subDeployment</code> , where <code>service</code> specifies the parent service and <code>subDeployment</code> specifies the name of the subdeployment. For example, <code>myJMSResource.myQueueSubDeployment</code> . You can also specify nested subdeployments, such as <code>MedRecEAR.MedRecAppScopedJMS.MedRecJMSServer</code> .
<i>destinationType</i>	Type of destination. Guidelines for setting this value are provided below.
<i>destinationName</i>	Name of the destination. Multiple names can be specified, separated by commas.

Use the following guidelines for setting the `sourceType` and `destinationType`:

- When unassigning **application deployments**, set the values as follows:

- *sourceType*: AppDeployment
- *destinationType*: Target
- When unassigning **libraries**, set the values as follows:
 - *sourceType*: Library
 - *destinationType*: Target
- When unassigning **security types**, set the values as follows:
 - *sourceType*: Name of the security type, such as User
 - *destinationType*: Name of the destination security type, such as Group
- When unassigning **servers** from **clusters**, set the values as follows:
 - *sourceType*: Server
 - *destinationType*: Cluster
- When unassigning **services**, set the values as follows:
 - *sourceType*: Name of the specific server, such as JDBCSystemResource
 - *destinationType*: Target
- When unassigning **subdeployments**, set the values as follows:
 - *sourceType*: *service*.SubDeployment, where *service* specifies the parent of the SubDeployment, such as JMSSystemResource.SubDeployment; you can also specify nested subdeployments (such as AppDeployment.SubDeployment.SubDeployment)
 - *destinationType*: Target

3.7.19.3 Example

The following examples:

- Unassign the servers myServer and myServer2 from the cluster myCluster.


```
wls:/offline/medrec> unassign("Server", "myServer,myServer2", "Cluster", "myCluster")
```
- Unassign all servers from the cluster myCluster.


```
wls:/offline/mydomain> unassign("Server", "*", "Cluster", "myCluster")
```
- Unassign the user newUser from the group Monitors.


```
wls:/offline/medrec> unassign("User", "newUser", "Group", "Monitors")
```
- Unassign the application deployment myAppDeployment from the target server newServer.


```
wls:/offline/mydomain> unassign("AppDeployment", "myAppDeployment", "Target", "newServer")
```
- Unassign the nested SubDeployment MedRecAppScopedJMS.MedRecJMSServer, which is a child of the AppDeployment AppDeployment, from the target server AdminServer.


```
wls:/offline/mydomain> assign('AppDeployment.SubDeployment.SubDeployment', 'MedRecEAR.MedRecAppScopedJMS.MedRecJMSServer', 'Target', 'AdminServer')
```

3.7.20 undo

Command Category: Editing Commands

Use with WLST: Online

3.7.20.1 Description

Reverts all unsaved or unactivated edits.

You specify whether to revert all unactivated edits (including those that have been saved to disk), or all edits made since the last *save* operation. This command does not release the edit session.

In the event of an error, the command returns a `WLSTException`.

3.7.20.2 Syntax

```
undo([unactivatedChanges], [defaultAnswer])
```

Argument	Definition
<i>unactivatedChanges</i>	Optional. Boolean value specifying whether to undo all unactivated changes, including edits that have been saved to disk. This argument defaults to <code>false</code> , indicating that all edits since the last <i>save</i> operation are reverted.
<i>defaultAnswer</i>	Optional. Default response, if you would prefer not to be prompted at the command line. Valid values are <code>y</code> and <code>n</code> . This argument defaults to null, and WLST prompts you for a response.

3.7.20.3 Example

The following example reverts all changes since the last *save* operation. WLST prompts for verification before reverting.

```
wls:/mydomain/edit !> undo()
Sure you would like to undo your changes? (y/n)
y
Discarded your in-memory changes successfully.
wls:/mydomain/edit>
```

The following example reverts all unactivated changes. WLST prompts for verification before reverting.

```
wls:/mydomain/edit !> undo('true')
Sure you would like to undo your changes? (y/n)
y
Discarded all your changes successfully.
wls:/mydomain/edit>
```

3.7.21 validate

Command Category: Editing Commands

Use with WLST: Online

3.7.21.1 Description

Validates the changes that have been made but have not yet been saved. This command enables you to verify that all changes are valid before saving them.

In the event of an error, the command returns a `WLSTException`.

3.7.21.2 Syntax

```
validate()
```

3.7.21.3 Example

The following example validates all changes that have been made but have not yet been saved.

```
wls:/mydomain/edit !> validate()
Validating changes ...
Validated the changes successfully
```

3.8 Information Commands

Use the WLST information commands, listed in [Table 3–8](#), to interrogate domains, servers, and variables, and provide configuration bean, runtime bean, and WLST-related information.

Table 3–8 Information Commands for WLST Configuration

This command...	Enables you to...	Use with WLST...
addListener	Add a JMX listener to the specified MBean.	Online
configToScript	Convert an existing server configuration (config directory) to an executable WLST script	Online or Offline
dumpStack	Display stack trace from the last exception that occurred while performing a WLST action, and reset the stack trace.	Online or Offline
dumpVariables	Display all variables used by WLST, including their name and value.	Online or Offline
find	Find MBeans and attributes in the current hierarchy.	Online
getConfigManager	Return the latest ConfigurationManagerBean MBean which manages the change process.	Online
getMBean	Return the MBean by browsing to the specified path.	Online
getMBeanInfo	Return the MBeanInfo for the specified MBeanType or the cmo variable.	Online
getPath	Return the MBean path for the specified MBean instance.	Online
listChildTypes	List all the children MBeans that can be created or deleted for the cmo type.	Online
lookup	Look up the specified MBean.	Online
ls	List all child beans and/or attributes for the current configuration or runtime bean.	Online or Offline
man	Display help from MBeanInfo for the current MBean or its specified attribute.	Online
redirect	Redirect WLST output to the specified filename.	Online
removeListener	Remove a listener that was previously defined.	Online

Table 3–8 (Cont.) Information Commands for WLST Configuration

This command...	Enables you to...	Use with WLST...
<code>showListeners</code>	Show all listeners that are currently defined.	Online
<code>startRecording</code>	Record all user interactions with WLST; useful for capturing commands to replay.	Online or Offline
<code>state</code>	Returns a map of servers or clusters and their state using Node Manager.	Online
<code>stopRecording</code>	Stop recording WLST commands.	Online or Offline
<code>stopRedirect</code>	Stop redirection of WLST output to a file.	Online or Offline
<code>storeUserConfig</code>	Create a user configuration file and an associated key file.	Online
<code>threadDump</code>	Display a thread dump for the specified server.	Online or Offline
<code>viewMBean</code>	Display information about an MBean, such as the attribute names and values, and operations.	Online
<code>writeIniFile</code>	Convert WLST definitions and method declarations to a Python (.py) file.	Online or Offline

3.8.1 addListener

Command Category: Information Commands

Use with WLST: Online

3.8.1.1 Description

Adds a JMX listener to the specified MBean. Any changes made to the MBean are reported to standard out and/or are saved to the specified configuration file.

In the event of an error, the command returns a `WLSTException`.

3.8.1.2 Syntax

```
addListener(mbean, [attributeNames], [logFile], [listenerName])
```

Argument	Definition
<i>mbean</i>	Name of the MBean or MBean object to listen on.
<i>attributeNames</i>	Optional. Comma-separated list of all attribute names on which you would like to add a JMX listener. This argument defaults to null, and adds a JMX listener for all attributes.
<i>logFile</i>	Optional. Name and location of the log file to which you want to write listener information. This argument defaults to standard out.
<i>listenerName</i>	Optional. Name of the JMX listener. This argument defaults to a WLST-generated name.

3.8.1.3 Example

The following example defines a JMX listener on the `cmo` MBean for the `Notes` and `ArchiveConfigurationCount` attributes. The listener is named `domain-listener` and is stored in `./listeners/domain.log`.

```
wls:/mydomain/serverConfig> addListener(cmo, "Notes,ArchiveConfigurationCount",
"../listeners/domain.log","domain-listener")
```

3.8.2 configToScript

Command Category: Information Commands

Use with WLST: Online or Offline

Converts an existing server configuration (config directory) to an executable WLST script. You can use the resulting script to re-create the resources on other servers.

Note: If you use `configToScript` for a domain that contains other Fusion Middleware components in addition to WebLogic Server, be aware that `configToScript` does not include the configuration for those components in the resulting WLST script. Only the WebLogic Server configuration is included in the script. If your domain contains other Fusion Middleware components in addition to WebLogic Server, Oracle recommends that you use `pack` and `unpack` to create the domain on remote servers. See *Oracle Fusion Middleware Creating Templates and Domains Using the Pack and Unpack Commands*.

The `configToScript` command creates the following files:

- A WLST script that contains the commands needed to recreate the configuration.
- A properties file that contains domain-specific values. You can update the values in this file to create new domains that are similar to the original configuration.
- A user configuration file and an associated key file to store encrypted attributes. The user configuration file contains the encrypted information. The key file contains a secret key that is used to encrypt and decrypt the encrypted information.

When you run the generated script:

- If a server is currently running, WLST will try to connect using the values in the properties file and then run the script commands to create the server resources.
- If no server is currently running, WLST will start a server with the values in the properties file, run the script commands to create the server resources, and shutdown the server. This may cause WLST to exit from the command shell.

In the event of an error, the command returns a `WLSTException`.

3.8.2.1 Syntax

```
configToScript([configPath], [pyPath], [overwrite], [propertiesFile],
[createDeploymentScript])
```

Argument	Definition
<code>configPath</code>	Optional. Path to the domain directory that contains the configuration that you want to convert. This argument defaults to the directory from which you start WLST (.).
<code>pyPath</code>	Optional. Path and filename to which you want to write the converted WLST script. This argument defaults to <code>./config/config.py</code> .

Argument	Definition
<i>overwrite</i>	Optional. Boolean value specifying whether the script file should be overwritten if it already exists. This argument defaults to <i>true</i> , indicating that the script file is overwritten.
<i>propertiesFile</i>	Optional. Path to the directory in which you want WLST to write the properties files. This argument defaults to the pathname specified for the <i>scriptPath</i> argument.
<i>createDeploymentScript</i>	Optional. Boolean value specifying whether WLST creates a script that performs deployments only. This argument defaults to <i>false</i> , indicating that a deployment script is not created.

3.8.2.2 Example

The following example converts the configuration to a WLST script `config.py`. By default, the configuration file is loaded from `./config`, the script file is saved to `.config/config.py`, and the properties file is saved to `.config/config.py.properties`.

```
wls:/offline> configToScript()
configToScript is loading configuration from c:\Oracle\Middleware
\user_projects\domains\wls\config\config.xml ...
Completed configuration load, now converting resources to wlst script...
configToScript completed successfully
The WLST script is written to c:\Oracle\Middleware
\user_projects\domains\wls\config\config.py
and the properties file associated with this script is written to c:\Oracle\
Middleware\user_projects\domains\wls\config\config.py.properties
wls:/offline>
```

The following example converts server resources configured in the file `c:\Oracle\Middleware\user_projects\domains\mydomain\config` directory to a WLST script `c:\Oracle\Middleware\myscripts\config.py`.

```
wls:/offline> configToScript('c:\Oracle\Middleware\user_projects\domains
/mydomain', 'c:\Oracle\Middleware\myscripts')
configToScript is loading configuration from c:\Oracle\Middleware
\user_projects\domains\mydomain\config\config.xml ...
Completed configuration load, now converting resources to wlst script...
configToScript completed successfully
The WLST script is written to c:\Oracle\Middleware\myscripts\config.py
and the properties file associated with this script is written to
c:\Oracle\Middleware\mydomain\config.py.properties
wls:/offline>
```

3.8.3 dumpStack

Command Category: Information Commands

Use with WLST: Online or Offline

3.8.3.1 Description

Displays the stack trace from the last exception that occurred while performing a WLST action, and resets the stack trace.

If successful, the `dumpstack` command returns the `Throwable` object. In the event of an error, the command returns a `WLSTException`.

3.8.3.2 Syntax

```
dumpStack()
```

3.8.3.3 Example

This example displays the stack trace.

```
wls:/myserver/serverConfig> dumpStack()  
com.bea.plateng.domain.script.jython.WLSTException: java.lang.reflect.Invocation  
TargetException  
...
```

3.8.4 dumpVariables

Command Category: Information Commands

Use with WLST: Online or Offline

3.8.4.1 Description

Displays all the variables used by WLST, including their name and value. In the event of an error, the command returns a `WLSTException`.

3.8.4.2 Syntax

```
dumpVariables()
```

3.8.4.3 Example

This example displays all the current variables and their values.

```
wls:/mydomain/serverConfig> dumpVariables()  
adminHome weblogic.rmi.internal.BasicRemoteRef - hostID:  
  '-1 108080150904263937S:localhost:[7001,8001,-1,-1,-1,-1,-1]:  
  mydomain:AdminServer', oid: '259', channel: 'null'  
cmgr [MBeanServerInvocationHandler]com.bea:Name=ConfigurationManager,  
  Type=weblogic.management.mbeanservers.edit.ConfigurationManagerMBean  
cmo [MBeanServerInvocationHandler]com.bea:Name=mydomain,Type=Domain  
connected true  
domainName mydomain  
...  
wls:/mydomain/serverConfig>
```

3.8.5 find

Command Category: Information Commands

Use with WLST: Online

3.8.5.1 Description

Finds MBeans and attributes in the current hierarchy.

WLST returns the pathname to the MBean that stores the attribute and/or attribute type, and its value. If `searchInstancesOnly` is set to `false`, this command also searches the `MBeanType` paths that are not instantiated in the server, but that can be created. In the event of an error, the command returns a `WLSTException`.

3.8.5.2 Syntax

```
find([name], [type], [searchInstancesOnly])
```


Argument	Definition
<i>name</i>	Optional. Name of the attribute to find.
<i>type</i>	Optional. Type of the attribute to find.
<i>searchInstancesOnly</i>	Optional. Boolean value specifying whether to search registered instances only or to also search MBeanTypes paths that are not instantiated in the server, but that can be created. This argument defaults to <code>true</code> , indicating only the registered instances will be searched.

3.8.5.3 Example

The following example searches for an attribute named `javaCompiler` in the current configuration hierarchy.

```
wls:/mydomain/serverConfig> find(name = 'JavaCompiler')
Finding 'JavaCompiler' in all registered MBean instances ...
/Servers/AdminServer          JavaCompilerPreClassPath    null
/Servers/AdminServer          JavaCompiler                 java
/Servers/AdminServer          JavaCompilerPostClassPath   null
wls:/mydomain/serverConfig>
```

The following example searches for an attribute of type `JMSRuntime` in the current configuration hierarchy.

```
wls:/mydomain/serverRuntime> find(type='JMSRuntime')
Finding MBean of type 'JMSRuntime' in all the instances ...
/JMSRuntime/AdminServer.jms
wls:/mydomain/serverRuntime>
```

The following example searches for an attribute named `execute` in the current configuration hierarchy. The `searchInstancesOnly` argument is set to `false`, indicating to also search MBeanTypes that are not instantiated in the server.

```
wls:/mydomain/serverConfig> find(name='execute', searchInstancesOnly='false')
Finding 'execute' in all registered MBean instances ...
/Servers/AdminServer          ExecuteQueues [Ljavax.management.ObjectName;@1aa7dbc
/Servers/AdminSever          Use81StyleExecuteQueues     false
Now finding 'execute' in all MBean Types that can be instantiated ...
/Servers                      ExecuteQueues
/Servers                      Use81StyleExecuteQueues
wls:/mydomain/serverConfig>
```

3.8.6 getConfigManager

Command Category: Information Commands

Use with WLST: Online

3.8.6.1 Description

Returns the latest `ConfigurationManager` MBean which manages the change process. You can then invoke methods to manage configuration changes across a WebLogic domain. In the event of an error, the command returns a `WLSTException`.

3.8.6.2 Syntax

```
getConfigManager()
```

3.8.6.3 Example

The following example returns the latest `ConfigurationManagerBean` MBean and stores it in a `cm` variable.

```
wls:/mydomain/serverConfig> cm=getConfigManager()
wls:/mydomain/serverConfig> cm.getType()
'weblogic.management.mbeanservers.edit.ConfigurationManagerMBean'
```

3.8.7 getMBean

Command Category: Information Commands

Use with WLST: Online

3.8.7.1 Description

Returns the MBean by browsing to the specified path. In the event of an error, the command returns a `WLSTException`.

Note: No exception is thrown if the MBean is not found.

3.8.7.2 Syntax

```
getMBean (mbeanPath)
```

Argument	Definition
<i>mbeanPath</i>	Path name to the MBean in the current hierarchy.

3.8.7.3 Example

The following example returns the MBean specified by the path.

```
wls:/mydomain/edit !> com=getMBean('Servers/myserver/COM/myserver')
wls:/mydomain/edit !> com.getType()
'Server'
```

3.8.8 getMBI

Command Category: Information Commands

Use with WLST: Online

3.8.8.1 Description

Returns the `MBeanInfo` for the specified `MBeanType` or the `cmo` variable. In the event of an error, the command returns a `WLSTException`.

3.8.8.2 Syntax

```
getMBI ([mbeanType])
```

Argument	Definition
<i>mbeanType</i>	Optional. <code>MBeanType</code> for which the <code>MBeanInfo</code> is displayed.

3.8.8.3 Example

The following example gets the `MBeanInfo` for the specified `MBeanType` and stores it in the variable `svrMbi`.

```
wls:/mydomain/serverConfig>
svrMbi=getMBean('weblogic.management.configuration.ServerMBean')
```

3.8.9 getPath

Command Category: Information Commands

Use with WLST: Online

3.8.9.1 Description

Returns the MBean path for the specified MBean instance or ObjectName for the MBean in the current tree. In the event of an error, the command returns a `WLSTException`.

3.8.9.2 Syntax

```
getPath(mbean)
```

Argument	Definition
mbean	MBean instance or ObjectName for the MBean in the current tree for which you want to return the MBean path.

3.8.9.3 Example

The following example returns the MBean specified by the path.

```
wls:/mydomain/edit !> path=getPath('com.bea:Name=myserver,Type=Server')
wls:/mydomain/edit !> print path
'Servers/myserver'
```

3.8.10 listChildTypes

Command Category: Information Commands

Use with WLST: Online

3.8.10.1 Description

Lists all the child MBeans that can be created or deleted for the `cmo`. The `cmo` variable specifies the configuration bean instance to which you last navigated using WLST. For more information about the `cmo` variable, see "Changing the Current Management Object" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

In the event of an error, the command returns a `WLSTException`.

3.8.10.2 Syntax

```
listChildTypes([parent])
```

Argument	Definition
parent	Optional. Parent type for which you want the children types listed.

3.8.10.3 Example

The following example lists the children MBeans that can be created or deleted for the `cmo` type.

```
wls:/mydomain/serverConfig> listChildTypes()
AppDeployments
```

```

BridgeDestinations
CachingRealms
Clusters
...
wls:/mydomain/serverConfig>

```

3.8.11 lookup

Command Category: Information Commands

Use with WLST: Online

3.8.11.1 Description

Looks up the specified MBean. The MBean must be a child of the current MBean. In the event of an error, the command returns a `WLSTException`.

3.8.11.2 Syntax

```
lookup(name, [childMBeanType])
```

Argument	Definition
<i>name</i>	Name of the MBean that you want to lookup.
<i>childMBeanType</i>	Optional. The type of the MBean that you want to lookup.

3.8.11.3 Example

The following example looks up the specified server, `myserver`, and stores the returned stub in the `sbean` variable.

```

wls:/mydomain/serverConfig> sbean=lookup('myserver', 'Server')
wls:/mydomain/serverConfig> sbean.getType()
'Server'
wls:/mydomain/serverConfig>

```

3.8.12 ls

Command Category: Information Commands

Use with WLST: Online or Offline

3.8.12.1 Description

Lists the attributes, operations, and child management objects of the specified management object.

In the event of an error, the command returns a `WLSTException`.

By default, the output is returned as a string and is arranged in three columns:

Note: By default, the `ls()` function echos its output so that it appears on the console in which you are running WLST. You can disable this by including the following command in your WLST script:

```
WLS.setShowLSResult(flag)
```

`flag` is a Boolean value. If it is 0 (false), then output from `ls()` to stdout is disabled and will not appear on the console. If it is set to 1 (true), then output from `ls()` to stdout is enabled

- The first column displays a set of codes that describe the listed item. See [Table 3–9](#).
- The second column displays the item name.
- When the item is an attribute, the third column displays the attribute value. If an attribute is encrypted, the third column displays asterisks instead of the value. (See "Writing and Reading Encrypted Configuration Values" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.)
- When the item is an operation, the third column uses the following pattern to display the operation's return type and input parameters: `returnType: parameterType(parameterName)`

Table 3–9 *ls* Command Output Information

Code	Description
d	Indicates that the item is a child management object. Like a directory in a UNIX or Windows file system, you can use the <code>cd</code> command to make the child object the current management object.
r	Indicates that the item is a child management object or an attribute that is readable, assuming that current user has been given read permission by the security realm's policies. (See "Default Security Policies for MBeans" in the <i>Oracle Fusion Middleware Oracle WebLogic Server MBean Reference</i> .)
w	Indicates that the item is an attribute that is writable, assuming that current user has been given write permission by the security realm's policies. (See "Default Security Policies for MBeans" in the <i>Oracle WebLogic Server MBean Reference</i> .)
x	Indicates that the item is an operation that can be executed, assuming that current user has been given execute permission by the security realm's policies. (See "Default Security Policies for MBeans" in the <i>Oracle Fusion Middleware Oracle WebLogic Server MBean Reference</i> .)

By default, the output lists all attributes, operations, and child management objects of the current management object. To filter the output or to see a list for a different management object, you can specify a command argument.

Note: As a performance optimization, when using WLST offline, WebLogic Server does not store most of its default values in the configuration files for the WebLogic domain. In some cases, this optimization prevents entire management objects from being displayed by WLST offline (because WebLogic Server has never written the corresponding XML elements to the domain configuration files). For example, if you never modify the default logging severity level for a WebLogic domain while the domain is active, WLST offline will not display the `Log` management object for the domain.

If you want to change the default value of attributes whose management object is not displayed by WLST offline, you must first use the `create` command to create the management object. Then you can `cd` to the management object and change the attribute value. See [Section 3.7.4, "create"](#).

3.8.12.2 Syntax

```
ls( [ a | c | o ] [ moPath ] )
```

```
ls( [ moPath ] returnMap [ returnType ] )
```

Argument	Definition
a	Optional. Displays only the attributes of the specified management object (suppresses the display of other items).
c	Optional. Displays only the child management objects of the specified management object (suppresses the display of other items).
o	Optional. Displays only the operations that can be invoked on the specified management object (suppresses the display of other items). This argument is only applicable for WLST online.
<i>moPath</i>	Optional. Path name to the management object for which you want to list attributes, operations, and child management objects. You can specify a pathname that is relative to your current location in the hierarchy or an absolute pathname. With WLST offline, use the forward-slash character (/) to specify the root of the configuration document. With WLST online, you can list the contents of MBeans in any management hierarchy (see Section 3.11, "Tree Commands"). Use the following syntax to specify the root of a hierarchy: <i>root-name: /</i> For example, to list the root of the server runtime hierarchy: <code>ls('serverRuntime:/')</code> If you do not specify this argument, the command lists items for the current management object.
<i>returnMap</i>	Optional. Boolean value that determines whether the command returns values as a map. This argument defaults to <code>false</code> , which causes this command to return a <code>String</code> .
<i>returnType</i>	Optional. Controls the output returned in the map. Specify <code>a</code> , <code>c</code> , or <code>o</code> , which filter the output as described at the top of this table. This argument is valid only if <code>returnMap</code> is set to <code>true</code> . This argument defaults to <code>c</code> .

3.8.12.3 Example

The following example displays all the child configuration beans, and attribute names and values for the `examples` domain, which has been loaded into memory, in WLST offline mode:

```
wls:/offline/mydomain > ls()
dr--  AppDeployments
dr--  BridgeDestinations
dr--  Clusters
dr--  CustomResources
dr--  DeploymentConfiguration
dr--  Deployments
dr--  EmbeddedLDAP
dr--  ErrorHandlings
dr--  FileStores
dr--  InternalAppDeployments
dr--  InternalLibraries
dr--  JDBCDataSourceFactories
dr--  JDBCStores
dr--  JDBCSystemResources
dr--  JMSBridgeDestinations
dr--  JMSInteropModules
dr--  JMSServers
dr--  JMSSystemResources
dr--  JMX
...
wls:/offline/examples>
```

The following example displays all the attribute names and values in `DomainMBean`:

```
wls:/mydomain/serverConfig> ls('a')
-r--  AdminServerName                AdminServer
-r--  AdministrationMBeanAuditingEnabled  false
-r--  AdministrationPort              9002
-r--  AdministrationPortEnabled        false
-r--  AdministrationProtocol           t3s
-r--  ArchiveConfigurationCount         0
-r--  ClusterConstraintsEnabled         false
-r--  ConfigBackupEnabled               false
-r--  ConfigurationAuditType           none
-r--  ConfigurationVersion              9.0.0.0
-r--  ConsoleContextPath                console
-r--  ConsoleEnabled                    true
-r--  ConsoleExtensionDirectory          console-ext
-r--  DomainVersion                     9.0.0.0
-r--  LastModificationTime              0
-r--  Name                              basicWLSDomain
-r--  Notes                             null
-r--  Parent                            null
-r--  ProductionModeEnabled             false
-r--  RootDirectory                     .
-r--  Type                              Domain
wls:/mydomain/serverConfig>
```

The following example displays all the child beans and attribute names and values in `Servers MBean`:

```
wls:/mydomain/serverConfig> ls('Servers')
dr--  AdminServer
```

The following example displays the attribute names and values for the specified MBean path and returns the information in a map:

```
wls:/mydomain/serverConfig> svrAttrList = ls('edit:/Servers/myserver', 'true',
'a')
-rw- AcceptBacklog                50
-rw- AdminReconnectIntervalSeconds 10
-rw- AdministrationPort            9002
-rw- AdministrationProtocol        t3s
-rw- AutoKillIfFailed              false
-rw- AutoMigrationEnabled          false
-rw- AutoRestart                   true
-rw- COMEnabled                    false
-rw- ClasspathServletDisabled      false
-rw- ClientCertProxyEnabled        false
-rw- Cluster                       null
-rw- ClusterRuntime                 null
-rw- ClusterWeight                 100
wls:/mydomain/serverConfig>
```

3.8.13 man

Command Category: Information Commands

Use with WLST: Online

3.8.13.1 Description

Displays help from `MBeanInfo` for the current MBean or its specified attribute. In the event of an error, the command returns a `WLSTException`.

3.8.13.2 Syntax

```
man([attrName])
```

Argument	Definition
<i>attrName</i>	Optional. MBean attribute name for which you would like to display help. If not specified, WLST displays helps for the current MBean.

3.8.13.3 Example

The following example displays help from `MBeanInfo` for the `ServerMBean` bean.

```
wls:/mydomain/serverConfig> man('Servers')
dynamic : true
creator : createServer
destroyer : destroyServer
description : <p>Returns the ServerMBeans representing the servers that have been
configured to be part of this domain.</p>
descriptorType : Attribute
Name : Servers
interfaceClassName : [Lweblogic.management.configuration.ServerMBean;
displayName : Servers
relationship : containment
```

3.8.14 redirect

Command Category: Information Commands

Use with WLST: Online

3.8.14.1 Description

Redirects WLST information, error, and debug messages to the specified filename. Also redirects the output of the `dumpStack()` and `dumpVariables()` commands to the specified filename.

In the event of an error, the command returns a `WLSTException`.

3.8.14.2 Syntax

```
redirect(outputFile, [toStdOut])
```

Argument	Definition
<i>outputFile</i>	Name of the file to which you want to record the WLST commands. The filename can be absolute or relative to the directory from which you started WLST.
<i>toStdOut</i>	Optional. Boolean value specifying whether the output should be sent to <code>stdout</code> . This argument defaults to <code>true</code> , indicating that the output will be sent to <code>stdout</code> .

3.8.14.3 Example

The following example begins redirecting WLST output to the `logs/wlst.log` file:

```
wls:/mydomain/serverConfig> redirect('./logs/wlst.log')
```

3.8.15 removeListener

Command Category: Information Commands

Use with WLST: Online

3.8.15.1 Description

Removes a listener that was previously defined. If you do not specify an argument, WLST removes all listeners defined for all MBeans. For information about setting a listener, see [Section 3.8.1, "addListener"](#).

In the event of an error, the command returns a `WLSTException`.

3.8.15.2 Syntax

```
removeListener([mbean], [listenerName])
```

Argument	Definition
<i>mbean</i>	Optional. Name of the MBean or MBean object for which you want to remove the previously defined listeners.
<i>listenerName</i>	Optional. Name of the listener to be removed.

3.8.15.3 Example

The following example removes the listener named `mylistener`.

```
wls:/mydomain/serverConfig> removeListener(listenerName="mylistener")
```

3.8.16 showListeners

Command Category: Information Commands

Use with WLST: Online

3.8.16.1 Description

Shows all listeners that are currently defined. For information about setting a listener, see [Section 3.8.1, "addListener"](#).

In the event of an error, the command returns a `WLSTException`.

3.8.16.2 Syntax

```
showListeners()
```

3.8.16.3 Example

The following example shows all listeners that are currently defined.

```
wls:/mydomain/serverConfig> showListeners()
```

3.8.17 startRecording

Command Category: Information Commands

Use with WLST: Online or Offline

3.8.17.1 Description

Records all user interactions with WLST. This command is useful for capturing commands for replay.

In the event of an error, the command returns a `WLSTException`.

This command cannot be used when you are importing WLST as a Jython module, as described in "Importing WLST as a Jython Module" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

3.8.17.2 Syntax

```
startRecording(recordFile, [recordAll])
```

Argument	Definition
<code>recordFile</code>	Name of the file to which you want to record the WLST commands. The filename can be absolute or relative to the directory from which you invoked WLST.
<code>recordAll</code>	Optional. Boolean value specifying whether to capture all user interactions in the file. This argument defaults to <code>false</code> , indicating that only WLST commands are captured, and not WLST command output.

3.8.17.3 Example

The following example begins recording WLST commands in the `record.py` file:

```
wls:/mydomain/serverConfig> startRecording('c:/myScripts/record.py')
Starting recording to c:/myScripts/record.py
wls:/mydomain/serverConfig>
```

3.8.18 state

Command Category: Information Commands

Use with WLST: Online

3.8.18.1 Description

Using Node Manager, returns a map of servers or clusters and their state. Node Manager must be running.

For more information about server states, see "Understanding Server Life Cycle" in *Oracle Fusion Middleware Managing Server Startup and Shutdown for Oracle WebLogic Server*.

In the event of an error, the command returns a `WLSTException`.

3.8.18.2 Syntax

```
state(name, [type])
```

Argument	Definition
<code>name</code>	Name of the server or cluster for which you want to retrieve the current state.
<code>type</code>	Optional. Type, <code>Server</code> or <code>Cluster</code> . This argument defaults to <code>Server</code> . When returning the state of a cluster, you must set this argument explicitly to <code>Cluster</code> , or the command will fail.

3.8.18.3 Example

The following example returns the state of the Managed Server, `managed1`.

```
wls:/mydomain/serverConfig> state('managed1','Server')
Current state of "managed1": SUSPENDED
wls:/mydomain/serverConfig>
```

The following example returns the state of the cluster, `mycluster`.

```
wls:/mydomain/serverConfig> state('mycluster','Cluster')
There are 3 server(s) in cluster: mycluster

States of the servers are
MServer1---SHUTDOWN
MServer2---SHUTDOWN
MServer3---SHUTDOWN
wls:/mydomain/serverConfig>
```

3.8.19 stopRecording

Command Category: Information Commands

Use with WLST: Online or Offline

3.8.19.1 Description

Stops recording WLST commands. For information about starting a recording, see [Section 3.8.17, "startRecording"](#).

In the event of an error, the command returns a `WLSTException`.

3.8.19.2 Syntax

```
stopRecording()
```

3.8.19.3 Example

The following example stops recording WLST commands.

```
wls:/mydomain/serverConfig> stopRecording()
```

```
Stopping recording to c:\myScripts\record.py  
wls:/mydomain/serverConfig>
```

3.8.20 stopRedirect

Command Category: Information Commands

Use with WLST: Online or Offline

3.8.20.1 Description

Stops the redirection of WLST output to a file, if redirection is in progress.

In the event of an error, the command returns a `WLSTException`.

3.8.20.2 Syntax

```
stopRedirect()
```

3.8.20.3 Example

The following example stops the redirection of WLST output to a file:

```
wls:/mydomain/serverConfig> stopRedirect()  
WLST output will not be redirected to myfile.txt any more
```

3.8.21 storeUserConfig

Command Category: Information Commands

Use with WLST: Online

3.8.21.1 Description

Creates a user configuration file and an associated key file. The user configuration file contains an encrypted username and password. The key file contains a secret key that is used to encrypt and decrypt the username and password.

Only the key file that originally encrypted the username and password can be used to decrypt the values. If you lose the key file, you must create a new user configuration and key file pair.

In the event of an error, the command returns a `WLSTException`.

3.8.21.2 Syntax

```
storeUserConfig([userConfigFile], [userKeyFile], [nm])
```

Argument	Definition
<i>userConfigFile</i>	<p>Optional. Name of the file to store the user configuration. The pathname can be absolute or relative to the file-system directory from which you started WLST.</p> <p>If you do not specify this argument, the command stores the file in your home directory as determined by your JVM. The location of the home directory depends on the SDK and type of operating system on which WLST is running. The default filename is based on the following pattern:</p> <p><i>username-WebLogicConfig.properties</i></p> <p>where <i>username</i> is the user name that you used to log in to the operating system.</p> <p>The command also prints to standard out the location in which it created the file.</p>
<i>userKeyFile</i>	<p>Optional. Name of the file to store the key information that is associated with the user configuration file that you specify. The pathname can be absolute or relative to the file-system directory from which you started WLST.</p> <p>If you do not specify this argument, the command stores the file in your home directory as determined by your JVM. The location of the home directory depends on the SDK and type of operating system on which WLST is running. The default filename is based on the following pattern:</p> <p><i>username-WebLogicKey.properties</i></p> <p>where <i>username</i> is the user name that you used to log in to the operating system.</p> <p>The command also prints to standard out the location in which it created the file.</p>
<i>nm</i>	<p>Optional. Boolean value specifying whether to store the username and password for Node Manager or WebLogic Server. If set to true, the Node Manager username and password is stored. This argument default to false.</p>

3.8.21.3 Example

The following example creates and stores a user configuration file and key file in the default location.

```
wls:/mydomain/serverConfig> storeUserConfig()
Creating the key file can reduce the security of your system if it is not kept in
a secured location after it is created. Do you want to create the key file? y or n
y
The username and password that were used for this current WLS connection are
stored in C:\Documents and Settings\pat\pat-WebLogicConfig.properties
and C:\Documents and Settings\pat\pat-WebLogicKey.properties.
```

The following example creates and stores a user configuration file and key file in the specified locations.

```
wls:/mydomain/serverConfig> storeUserConfig('c:/myFiles/myuserconfigfile.secure',
'c:/myFiles/myuserkeyfile.secure')
Creating the key file can reduce the security of your system if it is not kept in
a secured location after it is created. Do you want to create the key file? y or n
y
The username and password that were used for this current WLS connection are
stored in c:/myFiles/mysuserconfigfile.secure and c:/myFiles/myuserkeyfile.secure
wls:/mydomain/serverConfig>
```

3.8.22 threadDump

Command Category: Information Commands

Use with WLST: Online or Offline

3.8.22.1 Description

Displays a thread dump for the specified server. In the event of an error, the command returns a `WLSTException`.

3.8.22.2 Syntax

```
threadDump([writeToFile], [fileName], [serverName])
```

Argument	Definition
<i>writeToFile</i>	Optional. Boolean value specifying whether to save the output to a file. This argument defaults to <code>true</code> , indicating that output is saved to a file.
<i>fileName</i>	Optional. Name of the file to which the output is written. The filename can be absolute or relative to the directory where WLST is running. This argument defaults to <code>Thread_Dump_serverName</code> file, where <i>serverName</i> indicates the name of the server. This argument is valid only if <i>writeToFile</i> is set to <code>true</code> .
<i>serverName</i>	Optional. Server name for which the thread dump is requested. This argument defaults to the server to which WLST is connected. If you are connected to an Administration Server, you can display a thread dump for the Administration Server and any Managed Server that is running in the WebLogic domain. If you are connected to a Managed Server, you can only display a thread dump for that Managed Server.

3.8.22.3 Example

The following example displays the thread dump for the current server and saves the output to the `Thread_Dump_serverName` file.

```
wls:/mydomain/serverConfig> threadDump()
```

The following example displays the thread dump for the server `managedServer`. The information is not saved to a file.

```
wls:/mydomain/serverConfig> threadDump(writeToFile='false',
serverName='managedServer')
```

3.8.23 viewMBean

Command Category: Information Commands

Use with WLST: Online

3.8.23.1 Description

Displays information about an MBean, such as the attribute names and values, and operations. In the event of an error, the command returns a `WLSTException`.

3.8.23.2 Syntax

```
viewMBean(mbean)
```

Argument	Definition
<i>mbean</i>	MBean for which you want to display information.

3.8.23.3 Example

The following example displays information about the current MBean, `cmo`.

```
wls:/mydomain/serverConfig> cmo.getType()
'Domain'
wls:/mydomain/serverConfig> viewMBean(cmo)
Attribute Names and Values
-----
XMLEntityCaches    null
Targets    javax.management.ObjectName[com.bea
:Name=MedRecJMSServer, Type=JMSServer,
    com.bea:Name=WSStoreForwardInternalJMSServerMedRecServer, Type=JMSServer,
    com.bea:Name=MedRecWseeJMSServer, Type=JMSServer,
    com.bea:Name=PhysWSEEJMSServer, Type=JMSServer,
    com.bea:Name=MedRecSAFAgent, Type=SAFAgent,
    com.bea:Name=AdminServer, Type=Server]
RootDirectory    .
EmbeddedLDAP    com.bea:Name=OOTB_medrec, Type=EmbeddedLDAP
RemoteSAFContexts    null
Libraries    javax.management.ObjectName[com.bea
...
wls:/mydomain/serverConfig>
```

3.8.24 writelnifile

Command Category: Information Commands

Use with WLST: Online

3.8.24.1 Description

Converts WLST definitions and method declarations to a Python (`.py`) file to enable advanced users to import them as a Jython module. After importing, the definitions and method declarations are available to other Jython modules and can be accessed directly using Jython syntax. For more information, see "Importing WLST as a Jython Module" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

In the event of an error, the command returns a `WLSTException`.

3.8.24.2 Syntax

```
writeIniFile(filePath)
```

Argument	Definition
<i>filePath</i>	Full pathname to the file that you want to save the converted information.

3.8.24.3 Example

The following example converts WLST to a Python file named `wl.py`.

```
wls:/offline> writeIniFile("wl.py")
The Ini file is successfully written to wl.py
wls:/offline>
```

3.9 Life Cycle Commands

Use the WLST life cycle commands, listed in [Table 3–10](#), to manage the life cycle of a server instance.

For more information about the life cycle of a server instance, see "Understanding Server Life Cycle" in *Oracle Fusion Middleware Managing Server Startup and Shutdown for Oracle WebLogic Server*.

Table 3–10 Life Cycle Commands for WLST Configuration

This command...	Enables you to...	Use with WLST...
migrate	Migrate services to a target server within a cluster.	Online
resume	Resume a server instance that is suspended or in ADMIN state.	Online
shutdown	Gracefully shut down a running server instance or cluster.	Online
start	Start a Managed Server instance or a cluster using Node Manager.	Online
startServer	Start the Administration Server.	Online or Offline
suspend	Suspend a running server.	Online

3.9.1 migrate

Command Category: Life Cycle Commands

Use with WLST: Online

3.9.1.1 Description

Migrates the specified services (JTA, JMS, or Server) to a targeted server within a cluster. In the event of an error, the command returns a `WLSTException`.

For information about migrating services, see "Service Migration" in *Oracle Fusion Middleware Using Clusters for Oracle WebLogic Server*.

3.9.1.2 Syntax

```
migrate(sname, destinationName, [sourceDown], [destinationDown], [migrationType])
```

Argument	Definition
<i>sname</i>	Name of the server from which the services should be migrated.
<i>destinationName</i>	Name of the machine or server to which you want to migrate the services.
<i>sourceDown</i>	Optional. Boolean value specifying whether the source server is down. This argument defaults to <code>true</code> , indicating that the source server is not running. When migrating JTA services, the <i>sourceDown</i> argument is ignored, if specified, and defaults to <code>true</code> . The source server must be down in order for the migration of JTA services to succeed.

Argument	Definition
<i>destinationDown</i>	<p>Optional. Boolean value specifying whether the destination server is down. This argument defaults to <code>false</code>, indicating that the destination server is running.</p> <p>If the destination is not running, and you do not set this argument to <code>true</code>, WLST returns a <code>MigrationException</code>.</p> <p>When migrating JMS-related services to a non-running server instance, the server instance will activate the JMS services upon the next startup. When migrating the JTA Transaction Recovery Service to a non-running server instance, the target server instance will assume recovery services when it is started.</p>
<i>migrationType</i>	<p>Optional. Type of service(s) that you want to migrate. Valid values include:</p> <ul style="list-style-type: none"> ▪ <code>jms</code>—Migrate JMS-related services (JMS server, SAF agent, path service, and the WebLogic persistent store) only. ▪ <code>jta</code>—Migrate JTA services only. ▪ <code>server</code>—Migrate Server services only. ▪ <code>all</code>—Migrate all JTA and JMS services. <p>This argument defaults to <code>all</code>.</p>

3.9.1.3 Example

The following example migrates all JMS and JTA services on `server1` to the server `server2`. The boolean arguments specify that the source server is down and the destination server is running.

```
wls:/mydomain/edit !> migrate('server1','server2', 'true', 'false', 'all')
Migrating all JMS and JTA services from 'server1' to destination 'server2' ...
wls:/mydomain/edit !>
```

The following example migrates all Server services on `server1` to the server `server2`. The boolean arguments specify that the source server is down and the destination server is running.

```
wls:/mydomain/edit !> migrate('server1','server2', 'true', 'false', 'Server')
Migrating singleton server services from 'server1' to machine 'server2'...
wls:/mydomain/edit !>
```

3.9.2 resume

Command Category: Life Cycle Commands

Use with WLST: Online

3.9.2.1 Description

Resumes a server instance that is suspended or in `ADMIN` state. This command moves a server to the `RUNNING` state. For more information about server states, see "Understanding Server Life Cycle" in *Oracle Fusion Middleware Managing Server Startup and Shutdown for Oracle WebLogic Server*.

In the event of an error, the command returns a `WLSTException`.

3.9.2.2 Syntax

```
resume([sname], [block])
```

Argument	Definition
<i>sname</i>	Name of the server to resume. This argument defaults to the server to which WLST is currently connected.
<i>block</i>	Optional. Boolean value specifying whether WLST should block user interaction until the server is resumed. This argument defaults to <code>false</code> , indicating that user interaction is not blocked. In this case, WLST returns control to the user after issuing the command and assigns the task MBean associated with the current task to a variable that you can use to check its status. If you are importing WLST as a Jython module, as described in "Importing WLST as a Jython Module" in <i>Oracle Fusion Middleware Oracle WebLogic Scripting Tool</i> , <code>block</code> is always set to <code>true</code> .

3.9.2.3 Example

The following example resumes a Managed Server instance.

```
wls:/mydomain/serverConfig> resume('managed1', block='true')
Server 'managed1' resumed successfully.
wls:/mydomain/serverConfig>
```

3.9.3 shutdown

Command Category: Life Cycle Commands

Use with WLST: Online

3.9.3.1 Description

Gracefully shuts down a running server instance or a cluster. The `shutdown` command waits for all the in-process work to be completed before shutting down the server or cluster.

You shut down a server to which WLST is connected by entering the `shutdown` command without any arguments.

When connected to a Managed Server instance, you only use the `shutdown` command to shut down the Managed Server instance to which WLST is connected; you cannot shut down another server while connected to a Managed Server instance.

WLST uses Node Manager to shut down a Managed Server. When shutting down a Managed Server, Node Manager must be running.

In the event of an error, the command returns a `WLSTException`.

3.9.3.2 Syntax

```
shutdown([name], [entityType], [ignoreSessions], [timeOut], [force], [block])
```

Argument	Definition
<i>name</i>	Optional. Name of the server or cluster to shutdown. This argument defaults to the server to which WLST is currently connected.
<i>entityType</i>	Optional. Type, <code>Server</code> or <code>Cluster</code> . This argument defaults to <code>Server</code> . When shutting down a cluster, you must set this argument explicitly to <code>Cluster</code> , or the command will fail.
<i>ignoreSessions</i>	Optional. Boolean value specifying whether WLST should drop all HTTP sessions immediately or wait for HTTP sessions to complete or timeout while shutting down. This argument defaults to <code>false</code> , indicating that all HTTP sessions must complete or timeout.

Argument	Definition
<i>timeOut</i>	Optional. Time (in seconds) that WLST waits for subsystems to complete in-process work and suspend themselves before shutting down the server. This argument defaults to 0 seconds, indicating that there is no timeout.
<i>force</i>	Optional. Boolean value specifying whether WLST should terminate a server instance or a cluster without waiting for the active sessions to complete. This argument defaults to <i>false</i> , indicating that all active sessions must complete before shutdown.
<i>block</i>	Optional. Boolean value specifying whether WLST should block user interaction until the server is shutdown. This argument defaults to <i>false</i> , indicating that user interaction is not blocked. In this case, WLST returns control to the user after issuing the command and assigns the task MBean associated with the current task to a variable that you can use to check its status. If you are importing WLST as a Jython module, as described in "Importing WLST as a Jython Module" in <i>Oracle Fusion Middleware Oracle WebLogic Scripting Tool</i> , <i>block</i> is always set to <i>true</i> .

3.9.3.3 Example

The following example instructs WLST to shutdown the server to which you are connected:

```
wls:/mydomain/serverConfig> shutdown()
Shutting down the admin server that you are currently connected to .....
Disconnected from weblogic server: AdminServer
```

The following example instructs WLST to wait 1000 seconds for HTTP sessions to complete or timeout (at 1000 seconds) before shutting down *myserver*:

```
wls:/mydomain/serverConfig> shutdown('myserver', 'Server', 'false', 1000,
block='false')
```

The following example instructs WLST to drop all HTTP sessions immediately while connected to a Managed Server instance:

```
wls:/mydomain/serverConfig> shutdown('MServer1', 'Server', 'true', 1200)
Shutting down a managed server that you are connected to ...
Disconnected from weblogic server: MServer1
```

The following example instructs WLST to shutdown the cluster *mycluster*:

```
wls:/mydomain/serverConfig> shutdown('mycluster', 'Cluster')
Shutting down the cluster with name mycluster
Shutdown of cluster mycluster has been issued, please
refer to the logs to check if the cluster shutdown is successful.
Use the state(<server-name>) or state(<cluster-name>,"Cluster")
to check the status of the server or cluster
wls:/mydomain/serverConfig> state('mycluster', 'Cluster')
There are 3 server(s) in cluster: mycluster
```

```
States of the servers are
MServer1---SHUTDOWN
MServer2---SHUTDOWN
MServer3---SHUTDOWN
wls:/mydomain/serverConfig>
```

3.9.4 start

Command Category: Life Cycle Commands

Use with WLST: Online

3.9.4.1 Description

Starts a Managed Server instance or a cluster using Node Manager. WLST must be connected to the Administration Server and Node Manager must be running.

For more information about WLST commands used to connect to and use Node Manager, see [Section 3.10, "Node Manager Commands"](#).

In the event of an error, the command returns a `WLSTException`.

3.9.4.2 Syntax

```
start(name, [type], [url], [block])
```

Argument	Definition
<i>name</i>	Name of the Managed Server or cluster to start.
<i>type</i>	Optional. Type, <code>Server</code> or <code>Cluster</code> . This argument defaults to <code>Server</code> . When starting a cluster, you must set this argument explicitly to <code>Cluster</code> , or the command will fail.
<i>url</i>	Optional. Listen address and listen port of the server instance, specified using the following format: <code>[protocol://]listen-address:listen-port</code> . If not specified, this argument defaults to <code>t3://localhost:7001</code> .
<i>block</i>	Optional. Boolean value specifying whether WLST should block user interaction until the server or cluster is started. This argument defaults to <code>false</code> , indicating that user interaction is not blocked. In this case, WLST returns control to the user after issuing the command and assigns the task MBean associated with the current task to a variable that you can use to check its status. If you are importing WLST as a Jython module, as described "Importing WLST as a Jython Module" in <i>Oracle Fusion Middleware Oracle WebLogic Scripting Tool</i> , <i>block</i> is always set to <code>true</code> .

3.9.4.3 Example

The following example instructs Node Manager to start a Managed Server instance; the listen address is `localhost` and listen port is `8801`. WLST returns control to the user after issuing this command, as `block` is set to `false`.

```
wls:/mydomain/serverConfig> start('myserver', 'Server', block='false')
Starting server myserver ...
Server with name myserver started successfully.
wls:/mydomain/serverConfig>
```

The following example instructs Node Manager to start a cluster. WLST block user interaction until the cluster is started, as `block` defaults to `true`.

```
wls:/mydomain/serverConfig> start('mycluster', 'Cluster')
Starting the following servers in Cluster, mycluster: MS1, MS2, MS3...
.....
All servers in the cluster mycluster are started successfully.
wls:/mydomain/serverConfig>
```

3.9.5 startServer

Command Category: Life Cycle Commands

Use with WLST: Online or Offline

3.9.5.1 Description

Starts the Administration Server. In the event of an error, the command returns a `WLSTException`.

Note: You can use `startServer` only to start a WebLogic Administration Server, by running WLST from the `WL_HOME/common/bin` directory. You cannot use `startServer` to start an integrated WebLogic Administration Server (that is, an Administration Server for a Fusion Middleware Suite product installed in an `ORACLE_HOME` directory).

To start the Administration server for a Fusion Middleware Suite product other than WebLogic Server, use either of the following methods:

- Execute the server startup script for the associated WebLogic domain.
 - Start the server using Node Manager. If you use this method, make sure that the `startScriptEnabled` property is set to `true` in Node Manager.
-

3.9.5.2 Syntax

```
startServer([adminServerName], [domainName], [url], [username], [password],
[domainDir], [block], [timeout], [serverLog], [systemProperties], [jvmArgs]
[spaceAsJvmArgsDelimiter])
```

Argument	Definition
<i>adminServerName</i>	Optional. Name of the Administration Server to start. This argument defaults to <code>myserver</code> .
<i>domainName</i>	Optional. Name of the WebLogic domain to which the Administration Server belongs. This argument defaults to <code>mydomain</code> .
<i>url</i>	Optional. URL of the Administration Server. The URL supplied with the <code>startServer</code> command will override the listen address and port specified in the <code>config.xml</code> file. If not specified on the command line or in the <code>config.xml</code> file, this argument defaults to <code>t3://localhost:7001</code> .
<i>username</i>	Optional. Username use to connect WLST to the server. This argument defaults to <code>weblogic</code> .
<i>password</i>	Optional. Password used to connect WLST to the server. This argument defaults to <code>welcome1</code> .
<i>domainDir</i>	Optional. Domain directory in which the Administration Server is being started. This argument defaults to the directory from which you started WLST.

Argument	Definition
<i>block</i>	Optional. Boolean value specifying whether WLST blocks user interaction until the server is started. When <i>block</i> is set to <i>false</i> , WLST returns control to the user after issuing the command. This argument defaults to <i>true</i> , indicating that user interaction is blocked. If you are importing WLST as a Jython module, as described in "Importing WLST as a Jython Module" in <i>Oracle Fusion Middleware Oracle WebLogic Scripting Tool</i> , <i>block</i> is always set to <i>true</i> .
<i>timeout</i>	Optional. Time (in milliseconds) that WLST waits for the server to start before canceling the operation. The default value is 60000 milliseconds. This argument is only applicable when <i>block</i> is set to <i>true</i> .
<i>serverLog</i>	Optional. Location of the server log file. This argument defaults to <i>stdout</i> .
<i>systemProperties</i>	Optional. System properties to pass to the server process. System properties should be specified as comma-separated name-value pairs, and the name-value pairs should be separated by equals sign (=).
<i>jvmArgs</i>	Optional. JVM arguments to pass to the server process. Multiple arguments can be specified, separated by commas.
<i>spaceAsJvmArgsDelimiter</i>	Optional. Boolean value specifying whether JVM arguments are space delimited. The default value is <i>false</i> .

3.9.5.3 Example

The following example starts the Administration Server named *demoServer* in the *demoDomain*.

```
wls:/offline> startServer('demoServer','demoDomain','t3://localhost:8001',
'weblogic','wlsdomain','c:/mydomains/wls','false', 60000,
jvmArgs='-XX:MaxPermSize=75m, -Xmx512m, -XX:+UseParallelGC')
wls:/offline>
```

3.9.6 suspend

Command Category: Life Cycle Commands

Use with WLST: Online

3.9.6.1 Description

Suspends a running server. This command moves a server from the *RUNNING* state to the *ADMIN* state. For more information about server states, see "Understanding Server Life Cycle" in *Oracle Fusion Middleware Managing Server Startup and Shutdown for Oracle WebLogic Server*.

In the event of an error, the command returns a *WLSTException*.

3.9.6.2 Syntax

```
suspend([sname], [ignoreSessions], [timeOut], [force], [block])
```

Argument	Definition
<i>sname</i>	Optional. Name of the server to suspend. The argument defaults to the server to which WLST is currently connected.
<i>ignoreSessions</i>	Optional. Boolean value specifying whether WLST should drop all HTTP sessions immediately or wait for HTTP sessions to complete or time out while suspending. This argument defaults to <i>false</i> , indicating that HTTP sessions must complete or time out.

Argument	Definition
<code>timeOut</code>	Optional. Time (in seconds) the WLST waits for the server to complete in-process work before suspending the server. This argument defaults to 0 seconds, indicating that there is no timeout.
<code>force</code>	Optional. Boolean value specifying whether WLST should suspend the server without waiting for active sessions to complete. This argument defaults to <code>false</code> , indicating that all active sessions must complete before suspending the server.
<code>block</code>	Optional. Boolean value specifying whether WLST blocks user interaction until the server is started. This argument defaults to <code>false</code> , indicating that user interaction is not blocked. In this case, WLST returns control to the user after issuing the command and assigns the task MBean associated with the current task to a variable that you can use to check its status. If you are importing WLST as a Jython module, as described in "Importing WLST as a Jython Module" in <i>Oracle Fusion Middleware Oracle WebLogic Scripting Tool</i> , <code>block</code> is always set to <code>true</code> .

3.9.6.3 Example

The following example suspends a Managed Server instance:

```
wls:/mydomain/serverConfig> suspend('managed1')
Server 'managed1' suspended successfully.
wls:/mydomain/serverConfig>
```

3.10 Node Manager Commands

Use the WLST Node Managers commands, listed in [Table 3–11](#), to start, shut down, restart, and monitor WebLogic Server instances.

Note: Node Manager must be running before you can execute the commands within this category.

For more information about Node Manager, see "Using Node Manager" in the *Oracle Fusion Middleware Node Manager Administrator's Guide for Oracle WebLogic Server*.

Table 3–11 Node Manager Commands for WLST Configuration

This command...	Enables you to...	Use with WLST...
<code>nm</code>	Determine whether WLST is connected to Node Manager.	Online
<code>nmConnect</code>	Connect WLST to Node Manager to establish a session.	Online or Offline
<code>nmDisconnect</code>	Disconnect WLST from a Node Manager session.	Online or Offline
<code>nmEnroll</code>	Enables the Node Manager on the current computer to manage servers in a specified WebLogic domain.	Online
<code>nmGenBootStartupProps</code>	Generates the Node Manager property files, <code>boot.properties</code> and <code>startup.properties</code> , for the specified server.	Online
<code>nmKill</code>	Kill the specified server instance that was started with Node Manager.	Online or Offline

Table 3–11 (Cont.) Node Manager Commands for WLST Configuration

This command...	Enables you to...	Use with WLST...
<code>nmLog</code>	Return the Node Manager log.	Online or Offline
<code>nmServerLog</code>	Return the server output log of the server that was started with Node Manager.	Online or Offline
<code>nmServerStatus</code>	Return the status of the server that was started with Node Manager.	Online or Offline
<code>nmStart</code>	Start a server in the current WebLogic domain using Node Manager.	Online or Offline
<code>nmVersion</code>	Return the Node Manager version.	Online or Offline
<code>startNodeManager</code>	Starts Node Manager on the same computer that is running WLST.	Online or Offline
<code>stopNodeManager</code>	Stops Node Manager.	Online or Offline

3.10.1 nm

Command Category: Node Manager Commands

Use with WLST: Online or Offline

3.10.1.1 Description

Determines whether WLST is connected to Node Manager. Returns `true` or `false` and prints a descriptive message. Node Manager must be running before you can execute this command.

In the event of an error, the command returns a `WLSTException`.

3.10.1.2 Syntax

```
nm()
```

3.10.1.3 Example

The following example indicates that WLST is currently connected to Node Manager that is monitoring `mydomain`.

```
wls:/mydomain/serverConfig> nm()
Currently connected to Node Manager that is monitoring the domain "mydomain"
wls:/mydomain/serverConfig>
```

The following example indicates that WLST is not currently connected to Node Manager.

```
wls:/mydomain/serverConfig> nm()
Not connected to any Node Manager
wls:/mydomain/serverConfig>
```

3.10.2 nmConnect

Command Category: Node Manager Commands

Use with WLST: Online or Offline

3.10.2.1 Description

Connects WLST to Node Manager to establish a session. After connecting to Node Manager, you can invoke any Node Manager commands via WLST. Node Manager must be running before you can execute this command.

Note: If you have previously used the `connect` command in the current WLST session, `nmconnect` uses the same user credentials as were used for the `connect` command, unless you specify otherwise.

Once connected, the WLST prompt displays as follows, where *domainName* indicates the name of the WebLogic domain that is being managed: `wls:/nm/domainName>`. If you then connect WLST to a WebLogic Server instance, the prompt is changed to reflect the WebLogic Server instance. You can use the `nm` command to determine whether WLST is connected to Node Manager, as described in [Section 3.10.1, "nm"](#).

In the event of an error, the command returns a `WLSTException`.

3.10.2.2 Syntax

```
nmConnect([username, password], [host], [port], [domainName], [domainDir]
[nmType], [verbose])
```

```
nmConnect([userConfigFile, userKeyFile], [host], [port], [domainName], [domainDir]
[nmType], [verbose])
```

Argument	Definition
<i>username</i>	Username of the operator who is connecting WLST to Node Manager. The username defaults to <code>weblogic</code> . Note: When running a server in production mode, you must specify the username and password explicitly on the command line to ensure that the appropriate username and password are used when connecting to Node Manager.
<i>password</i>	Password of the operator who is connecting WLST to Node Manager. The password defaults to <code>welcome1</code> . Note: When running a server in production mode, you must specify the username and password explicitly on the command line to ensure that the appropriate username and password are used when connecting to Node Manager.
<i>host</i>	Optional. Host name of Node Manager. This argument defaults to <code>localhost</code> .
<i>port</i>	Optional. Port number of Node Manager. This argument defaults to a value that is based on the Node Manager type, as follows: <ul style="list-style-type: none"> ■ For <code>plain</code> type, defaults to 5556 ■ For <code>rsh</code> type, defaults to 514 ■ For <code>ssh</code> type, defaults to 22 ■ For <code>ssl</code> type, defaults to 5556
<i>domainName</i>	Optional. Name of the WebLogic domain that you want to manage. This argument defaults to <code>mydomain</code> .
<i>domainDir</i>	Optional. Path of the domain directory to which you want to save the Node Manager secret file (<code>nm_password.properties</code>) and <code>SerializedSystemIni.dat</code> file. This argument defaults to the directory in which WLST was started.

Argument	Definition
<i>nmType</i>	<p>The Node Manager type. Valid values are:</p> <ul style="list-style-type: none"> ■ <code>plain</code> for plain socket Java-based implementation <p>Note: If you specify <code>plain</code> for <code>nmType</code>, you must manually set the <code>SecureListener</code> parameter in <code>WL_HOME/common/nodemanager/nodemanager.properties</code> to <code>false</code>. Otherwise, the <code>nmConnect</code> command will fail.</p> <ul style="list-style-type: none"> ■ <code>rsh</code> for RSH implementation ■ <code>ssh</code> for script-based SSH implementation ■ <code>ssl</code> for Java-based SSL implementation <p>This argument defaults to <code>ssl</code>.</p>
<i>verbose</i>	<p>Optional. Boolean value specifying whether WLST connects to Node Manager in verbose mode. This argument defaults to <code>false</code>, disabling verbose mode.</p>
<i>userConfigFile</i>	<p>Optional. Name and location of a user configuration file which contains an encrypted username and password.</p> <p>When you create a user configuration file, the <code>storeUserConfig</code> command uses a key file to encrypt the username and password. Only the key file that encrypts a user configuration file can decrypt the username and password. (See Section 3.8.21, "storeUserConfig".)</p>
<i>userKeyFile</i>	<p>Optional. Name and location of the key file that is associated with the specified user configuration file and is used to decrypt it. (See Section 3.8.21, "storeUserConfig".)</p>

3.10.2.3 Example

The following example connects WLST to Node Manager to monitor the `oamdomain` domain using the default host and port numbers and `plain` Node Manager type.

```
wls:/myserver/serverConfig> nmConnect('weblogic', 'welcome1', 'localhost',
'5555', 'oamdomain', 'c:/Oracle/Middleware/user_projects/domains/oamdomain', 'ssl')
Connecting to Node Manager Server ...
Successfully connected to Node Manager.
wls:/nm/oamdomain>
```

The following example connects WLST to a Node Manager Server instance using a user configuration and key file to provide user credentials.

```
wls:/myserver/serverConfig> nmConnect(userConfigFile='
c:/myfiles/myuserconfigfile.secure',
userKeyFile='c:/myfiles/myuserkeyfile.secure',
host='172.18.137.82', port=26106, domainName='mydomain',
domainDir='c:/myfiles/mydomain', mType='ssl')
Connecting to Node Manager Server ...
Successfully connected to Node Manager.
wls:/nm/mydomain>
```

3.10.3 nmDisconnect

Command Category: Node Manager Commands

Use with WLST: Online or Offline

WLST must be connected to Node Manager to run this command.

3.10.3.1 Description

Disconnects WLST from a Node Manager session.

In the event of an error, the command returns a `WLSTException`.

3.10.3.2 Syntax

```
nmDisconnect()
```

3.10.3.3 Example

The following example disconnects WLST from a Node Manager session.

```
wls:/nm/oamdomain> nmDisconnect()
Successfully disconnected from Node Manager
wls:/myserver/serverConfig>
```

3.10.4 nmEnroll

Command Category: Node Manager Commands

Use with WLST: Online

3.10.4.1 Description

Enrolls the machine on which WLST is currently running. WLST must be connected to an Administration Server to run this command; WLST does not need to be connected to Node Manager.

This command downloads the following files from the Administration Server:

- Node Manager secret file (`nm_password.properties`), which contains the encrypted username and password that is used for server authentication
- `SerializedSystemIni.dat` file

This command also updates the `nodemanager.domains` file under the `WL_HOME/common/nodemanager` directory with the domain information, where `WL_HOME` refers to the top-level installation directory for WebLogic Server.

You must run this command once per WebLogic domain per machine unless that domain shares the root directory of the Administration Server.

If the machine is already enrolled when you run this command, the Node Manager secret file (`nm_password.properties`) is refreshed with the latest information from the Administration Server.

In the event of an error, the command returns a `WLSTException`.

3.10.4.2 Syntax

```
nmEnroll([domainDir], [nmHome])
```

Argument	Definition
<i>domainDir</i>	Optional. Path of the domain directory to which you want to save the Node Manager secret file (<code>nm_password.properties</code>) and <code>SerializedSystemIni.dat</code> file. This argument defaults to the directory in which WLST was started.
<i>nmHome</i>	Optional. Path to the Node Manager home. The <code>nodemanager.domains</code> file, containing the domain information, is written to this directory. This argument defaults to <code>WL_HOME/common/nodemanager</code> , where <code>WL_HOME</code> refers to the top-level installation directory for WebLogic Server.

3.10.4.3 Example

The following example enrolls the current machine with Node Manager and saves the Node Manager secret file (`nm_password.properties`) and `SerializedSystemIni.dat` file to

`c:/Oracle/Middleware/mydomain/common/nodemanager/nm_password.properties`. The `nodemanager.domains` file is written to `WL_HOME/common/nodemanager` by default.

```
wls:/mydomain/serverConfig>
nmEnroll('c:/Oracle/Middleware/mydomain/common/nodemanager')
Enrolling this machine with the domain directory at
c:\Oracle\Middleware\mydomain\common\nodemanager...
Successfully enrolled this machine with the domain directory at
C:\Oracle\Middleware\mydomain\common\nodemanager
wls:/mydomain/serverConfig>
```

3.10.5 nmGenBootStartupProps

Command Category: Node Manager Commands

Use with WLST: Online

3.10.5.1 Description

Generates the Node Manager property files, `boot.properties` and `startup.properties`, for the specified server. The Node Manager property files are stored relative to the root directory of the specified server. The target root directory must be on the same machine on which you are running the command.

You must specify the name of a server; otherwise, the command will fail.

In the event of an error, the command returns a `WLSTException`.

3.10.5.2 Syntax

```
nmGenBootStartupProps(serverName)
```

Argument	Definition
<code>serverName</code>	Name of the server for which Node Manager property files are generated.

3.10.5.3 Example

The following example generates `boot.properties` and `startup.properties` in the root directory of the specified server, `ms1`.

```
wls:/mydomain/serverConfig> nmGenBootStartupProps('ms1')
Successfully generated boot.properties at
c:\Oracle\Middleware\mydomain\servers\ms1\data\nodemanager\boot.properties
Successfully generated startup.properties at
c:\Oracle\Middleware\mydomain\servers\ms1\data\nodemanager\startup.properties
wls:/mydomain/serverConfig>
```

3.10.6 nmKill

Command Category: Node Manager Commands

Use with WLST: Online or Offline

WLST must be connected to Node Manager to run this command.

3.10.6.1 Description

Kills the specified server instance that was started with Node Manager.

If you do not specify a server name using the *serverName* argument, the argument defaults to *myServer*, which must match your server name or the command will fail.

If you attempt to kill a server instance that was not started using Node Manager, the command displays an error.

In the event of an error, the command returns a `WLSTException`.

3.10.6.2 Syntax

```
nmKill([serverName], [serverType])
```

Argument	Definition
<i>serverName</i>	Optional. Name of the server to be killed. This argument defaults to <i>myserver</i> .
<i>serverType</i>	Optional. The type of server to start. This argument defaults to <i>WebLogic</i> . Another valid option is <i>Coherence</i> .

3.10.6.3 Example

The following example kills the server named *oamserver*.

```
wls:/nm/oamdomain> nmKill('oamserver')
Killing server 'oamserver' ...
Server oamServer killed successfully.
wls:/nm/oamdomain>
```

3.10.7 nmLog

Command Category: Node Manager Commands

Use with WLST: Online or Offline

WLST must be connected to Node Manager to run this command.

3.10.7.1 Description

Returns the Node Manager log.

In the event of an error, the command returns a `WLSTException`.

3.10.7.2 Syntax

```
nmLog([writer])
```

Argument	Definition
<i>writer</i>	Optional. <code>java.io.Writer</code> object to which you want to stream the log output. This argument defaults to the WLST writer stream.

3.10.7.3 Example

The following example displays the Node Manager log.

```
wls:/nm/oamdomain> nmLog()
Successfully retrieved the Node Manager log and written.
wls:/nm/oamdomain>
```

3.10.8 nmServerLog

Command Category: Node Manager Commands

Use with WLST: Online or Offline

WLST must be connected to Node Manager to run this command.

3.10.8.1 Description

Returns the server output log of the server that was started with Node Manager.

In the event of an error, the command returns a `WLSTException`.

3.10.8.2 Syntax

```
nmServerLog([serverName], [writer], [serverType])
```

Argument	Definition
<i>serverName</i>	Optional. Name of the server for which you want to display the server output log. This argument defaults to <code>myserver</code> .
<i>writer</i>	Optional. <code>java.io.Writer</code> object to which you want to stream the log output. This argument defaults to the WLSTInterpreter standard out, if not specified.
<i>serverType</i>	Optional. The type of server to start. This argument defaults to WebLogic. Another valid option is Coherence.

3.10.8.3 Example

The following example displays the server output log for the `oamserver` server and writes the log output to `myWriter`.

```
wls:/nm/oamdomain> nmServerLog('oamserver',myWriter)
Successfully retrieved the server log and written.
wls:/nm/oamdomain>
```

3.10.9 nmServerStatus

Command Category: Node Manager Commands

Use with WLST: Online or Offline

WLST must be connected to Node Manager to run this command.

3.10.9.1 Description

Returns the status of the server that was started with Node Manager.

In the event of an error, the command returns a `WLSTException`.

3.10.9.2 Syntax

```
nmServerStatus([serverName], [serverType])
```

Argument	Definition
<i>serverName</i>	Optional. Name of the server for which you want to display the status. This argument defaults to <code>myserver</code> .
<i>serverType</i>	Optional. The type of server to start. This argument defaults to WebLogic. Another valid option is Coherence.

3.10.9.3 Example

The following example displays the status of the server named `oamserver`, which was started with Node Manager.

```
wls:/nm/oamdomain> nmServerStatus('oamserver')
RUNNING
wls:/nm/oamdomain>
```

3.10.10 nmStart

Command Category: Node Manager Commands

Use with WLST: Online or Offline

WLST must be connected to Node Manager to run this command.

3.10.10.1 Description

Starts a server in the current WebLogic domain using Node Manager.

In the event of an error, the command returns a `WLSTException`.

Note: `boot.properties` must exist in order to start a server with `nmStart`. If this is the first time you are starting a server, you must manually create it in order to use `nmStart`.

Alternatively, you can use the `nmStartprops` argument to provide user credentials (after connecting to Node Manager):

```
prps = makePropertiesObject("username=weblogic, password=welcome1")
nmStart("AdminServer", props=prps)
```

3.10.10.2 Syntax

```
nmStart([serverName], [domainDir], [props], [writer], [serverType])
```

Argument	Definition
<i>serverName</i>	Optional. Name of the server to be started.
<i>domainDir</i>	Optional. Domain directory of the server to be started. This argument defaults to the directory from which you started WLST.
<i>props</i>	Optional. System properties to apply to the new server.
<i>writer</i>	Optional. <code>java.io.Writer</code> object to which the server output is written. This argument defaults to the WLST writer.
<i>serverType</i>	Optional. The type of server to start. This argument defaults to WebLogic. Another valid option is Coherence.

3.10.10.3 Example

The following example starts the `managed1` server in the current WebLogic domain using Node Manager.

```
wls:/nm/mydomain> nmStart("managed1")
Starting server managed1 ...
Server managed1 started successfully
wls:/nm/mydomain>
```

The following example starts the Administration Server in the specified WebLogic domain using Node Manager. In this example, the `prps` variable stores the system property settings and is passed to the command using the `prps` argument.

```
wls:/nm/mydomain> prps = makePropertiesObject("weblogic.ListenPort=8001")
wls:/nm/mydomain> nmStart("AdminServer",prps=prps)
Starting server AdminServer...
Server AdminServer started successfully
wls:/nm/mydomain>
```

3.10.11 nmVersion

Command Category: Node Manager Commands

Use with WLST: Online or Offline

WLST must be connected to Node Manager to run this command.

3.10.11.1 Description

Returns the Node Manager version.

In the event of an error, the command returns a `WLSTException`.

3.10.11.2 Syntax

```
nmVersion()
```

3.10.11.3 Example

The following example displays the Node Manager version.

```
wls:/nm/oamdomain> nmVersion()
The Node Manager version that you are currently connected to is 9.0.0.0
wls:/nm/oamdomain>
```

3.10.12 startNodeManager

Command Category: Node Manager Commands

Use with WLST: Online or Offline

3.10.12.1 Description

Starts Node Manager on the same computer that is running WLST.

Notes: The WebLogic Server custom installation process optionally installs and starts Node Manager as a Windows service on Windows systems. For more information, see "About Installing Node Manager as a Windows Service" in the *Oracle Fusion Middleware Installation Guide for Oracle WebLogic Server*. In this case, you do not need to start the Node Manager manually.

In production environments, Oracle recommends that you do *not* use the `startNodeManager` command to start Node Manager. The recommended approach is to install Node Manager as a service or daemon, or to use the `startNodeManager` script (`startNodeManager.sh` or `startNodeManger.cmd`).

If Node Manager is already running when you invoke the `startNodeManager` command, the following message is displayed:

```
A Node Manager has already been started.
Cannot start another Node Manager process via WLST
```

In the event of an error, the command returns a `WLSTException`.

3.10.12.2 Syntax

```
startNodeManager([verbose], [nmProperties])
```

Argument	Definition
<i>verbose</i>	Optional. Boolean value specifying whether WLST starts Node Manager in verbose mode. This argument defaults to <code>false</code> , disabling verbose mode.
<i>nmProperties</i>	Optional. Comma-separated list of Node Manager properties, specified as name-value pairs. Node Manager properties include, but are not limited to, the following: <code>NodeManagerHome</code> , <code>ListenAddress</code> , <code>ListenPort</code> , and <code>PropertiesFile</code> .

3.10.12.3 Example

The following example displays the Node Manager server version.

```
wls:/mydomain/serverConfig> startNodeManager(verbose='true',
NodeManagerHome='c:/Oracle/Middleware/wlserver_10.3/common/nodemanager',
ListenPort='6666', ListenAddress='myhost'))
Launching Node Manager ...
Successfully launched the Node Manager.
The Node Manager process is running independent of the WLST process
Exiting WLST will not stop the Node Manager process. Please refer
to the Node Manager logs for more information.
The Node Manager logs will be under c:\Oracle\Middleware\wlserver_
10.3\common\nodemanager.
wls:/mydomain/serverConfig>
```

3.10.13 stopNodeManager

Command Category: Node Manager Commands

Use with WLST: Online or Offline

3.10.13.1 Description

Stops the Node Manager process.

Note: In order to stop the Node Manager process, you must have either started Node Manager with `startNodeManager`, or Node Manager must have been started with the property `QuitEnabled=true`. You can configure this property in `$WLS_HOME/common/nodemanager.properties`. This allows you to connect to the Node Manager to shut it down.

If the Node Manager is not running when you invoke the `stopNodeManager` command, the following message is displayed:

```
Cannot stop the Node Manager unless you are connected to it.
```

3.10.13.2 Syntax

```
stopNodeManager()
```

3.10.13.3 Example

The following example stops the Node Manager process for the `base_domain` domain.

```
wls:/nm/base_domain> stopNodeManager()
Stopped Node Manager Process successfully
wls:/offline>
```

3.11 Tree Commands

Use the WLST tree commands, listed in [Table 3–12](#), to navigate among MBean hierarchies.

Table 3–12 Tree Commands for WLST Configuration

Use this command...	To...	Use with WLST...
custom	Navigate to the root of custom MBeans that are registered in the server.	Online
domainConfig	Navigate to the last MBean to which you navigated in the domain configuration hierarchy or to the root of the hierarchy, <code>DomainMBean</code> .	Online
domainCustom	Navigate to the root of custom MBeans that are registered in the Domain Runtime MBean Server	Online
domainRuntime	Navigate to the last MBean to which you navigated in the domain runtime hierarchy or to the root of the hierarchy, <code>DomainRuntimeMBean</code> .	Online
edit	Navigate to the last MBean to which you navigated in the edit configuration MBean hierarchy or to the root of the hierarchy, <code>DomainMBean</code> .	Online
jndi	Navigates to the JNDI tree for the server to which WLST is currently connected.	Online
serverConfig	Navigate to the last MBean to which you navigated in the configuration MBean hierarchy or to the root of the hierarchy, <code>DomainMBean</code> .	Online
serverRuntime	Navigate to the last MBean to which you navigated in the runtime MBean hierarchy or to the root of the hierarchy, <code>ServerRuntimeMBean</code> .	Online

3.11.1 custom

Command Category: Tree Commands

Use with WLST: Online

3.11.1.1 Description

Navigates to the root of custom MBeans that are registered in the Runtime MBean Server. WLST navigates, interrogates, and edits custom MBeans as it does domain MBeans; however, custom MBeans cannot use the `cmo` variable because a stub is not available.

Note: When navigating to the `custom` tree, WLST queries all MBeans in the compatibility MBean server, the runtime MBean server, and potentially the JVM platform MBean server to locate the custom MBeans. Depending on the number of MBeans in the current WebLogic domain, this process may take a few minutes, and WLST may not return a prompt right away.

The `custom` command is available when WLST is connected to an Administration Server instance or a Managed Server instance. When connected to a WebLogic Integration or WebLogic Portal server, WLST can interact with all the WebLogic Integration or WebLogic Portal server MBeans.

For more information about custom MBeans, see *Oracle Fusion Middleware Developing Custom Management Utilities With JMX for Oracle WebLogic Server*.

In the event of an error, the command returns a `WLSTException`.

Note: You can also navigate to custom MBeans on the Domain Runtime MBean Server using the `domainCustom()` command. See [Section 3.11.3, "domainCustom,"](#) for more information.

3.11.1.2 Syntax

```
custom()
```

3.11.1.3 Example

The following example navigates from the configuration MBean hierarchy to the custom MBean hierarchy on a Administration Server instance.

```
wls:/mydomain/serverConfig> custom()
Location changed to custom tree. This is a writeable tree with No root. For more
help, use help('custom')
wls:/mydomain/custom>
```

3.11.2 domainConfig

Command Category: Tree Commands

Use with WLST: Online

3.11.2.1 Description

Navigates to the last MBean to which you navigated in the domain Configuration hierarchy or to the root of the hierarchy, `DomainMBean`. This read-only hierarchy stores the configuration MBeans that represent your current WebLogic domain.

In the event of an error, the command returns a `WLSTException`.

3.11.2.2 Syntax

```
domainConfig()
```

3.11.2.3 Example

The following example navigates from the configuration MBean hierarchy to the WebLogic domain Configuration hierarchy on an Administration Server instance.

```
wls:/mydomain/serverConfig> domainConfig()
```

```
Location changed to domainConfig tree. This is a read-only tree with DomainMBean
as the root.
For more help, use help('domainConfig')
wls:/mydomain/domainConfig> ls()
dr--  AppDeployments
dr--  BridgeDestinations
dr--  Clusters
dr--  CustomResources
dr--  DeploymentConfiguration
dr--  Deployments
dr--  EmbeddedLDAP
dr--  ErrorHandlings
dr--  FileStores
dr--  InternalAppDeployments
dr--  InternalLibraries
dr--  JDBCDataSourceFactories
dr--  JDBCStores
dr--  JDBCSystemResources
dr--  JMSBridgeDestinations
dr--  JMSInteropModules
dr--  JMSServers
dr--  JMSSystemResources
...
wls:/mydomain/domainConfig>
```

3.11.3 domainCustom

Command Category: Tree Commands

Use with WLST: Online

3.11.3.1 Description

Navigates to the domain custom tree of custom MBeans that are registered in the Domain Runtime MBean Server. WLST navigates, interrogates, and edits domain custom MBeans as it does domain MBeans; however, domain custom MBeans cannot use the `cmo` variable because a stub is not available.

Note: When navigating to the domainCustom tree, WLST queries all MBeans in the Domain Runtime MBean Server, the Runtime MBean Servers on each server, and potentially the JVM platform MBean server to locate the custom MBeans. Depending on the number of MBeans in the current WebLogic domain, this process may take a few minutes, and WLST may not return a prompt right away. It is recommended that a JMX query Object Name Pattern be specified to limit the amount of searching performed.

The `domainCustom` command is available only when WLST is connected to an Administration Server instance.

For more information about the Domain Runtime MBean Server, see "Understanding WebLogic Server MBeans" in *Oracle Fusion Middleware Developing Custom Management Utilities With JMX for Oracle WebLogic Server*.

In the event of an error, the command returns a `WLSTException`.

3.11.3.2 Syntax

```
domainCustom(ObjectNamePattern)
```

Argument	Definition
<i>ObjectNamePattern</i>	A JMX query pattern, such as <code>sip:*</code> . The default value is null or <code>*:*</code> .

3.11.3.3 Example

The following example navigates from the configuration MBean hierarchy to the domain custom MBean hierarchy on an Administration Server instance:

```
wls:/mydomain/serverConfig> domainCustom()
Location changed to domain custom tree. This is a writeable tree with No root. For
more help, use help('domainCustom').
```

```
wls:/mydomain/domainCustom
```

3.11.4 domainRuntime

Command Category: Tree Commands

Use with WLST: Online

3.11.4.1 Description

Navigates to the last MBean to which you navigated in the domain Runtime hierarchy or to the root of the hierarchy, `DomainRuntimeMBean`. This read-only hierarchy stores the runtime MBeans that represent your current WebLogic domain.

In the event of an error, the command returns a `WLSTException`.

3.11.4.2 Syntax

```
domainRuntime()
```

3.11.4.3 Example

The following example navigates from the configuration MBean hierarchy to the domain Runtime hierarchy on an Administration Server instance.

```
wls:/mydomain/serverConfig> domainRuntime()
wls:/mydomain/domainRuntime> ls()
dr-- AppRuntimeStateRuntime
dr-- DeployerRuntime
dr-- DomainServices
dr-- LogRuntime
dr-- MessageDrivenControlEJBRuntime
dr-- MigratableServiceCoordinatorRuntime
dr-- MigrationDataRuntimes
dr-- SNMPAgentRuntime
dr-- ServerLifeCycleRuntimes
dr-- ServerRuntimes
dr-- ServerServices

-r-- ActivationTime                Mon Aug 01 11:41:25 EDT 2005
-r-- Clusters                      null
-r-- MigrationDataRuntimes        null
-r-- Name                          sampleMedRecDomain
-rw- Parent                        null
-r-- SNMPAgentRuntime             null
```

```

-r--      Type                               DomainRuntime
-r-x      restartSystemResource             Void :
          WebLogicMBean(weblogic.management.configuration.SystemResourceMBean)
wls:/mydomain/domainRuntime>

```

3.11.5 edit

Command Category: Tree Commands

Use with WLST: Online

3.11.5.1 Description

Navigates to the last MBean to which you navigated in the edit configuration MBean hierarchy or to the root of the hierarchy, `DomainMBean`. This writable hierarchy stores all of the configuration MBeans that represent your current WebLogic domain.

Note: To edit configuration beans, you must be connected to an Administration Server. If you connect to a Managed Server, WLST functionality is limited to browsing the configuration bean hierarchy. While you cannot use WLST to change the values of MBeans on Managed Servers, it is possible to use the Management APIs to do so. Oracle recommends that you change only the values of configuration MBeans on the Administration Server. Changing the values of MBeans on Managed Servers can lead to an inconsistent domain configuration.

For more information about editing configuration beans, see "Using WLST Online to Update an Existing WebLogic Domain" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

In the event of an error, the command returns a `WLSTException`.

3.11.5.2 Syntax

```
edit()
```

3.11.5.3 Example

The following example illustrates how to navigate from the server configuration MBean hierarchy to the editable copy of the domain configuration MBean hierarchy, in an Administration Server instance.

```

wls:/myserver/serverConfig> edit()
Location changed to edit tree. This is a writeable tree with DomainMBean as the
root.
For more help, use help('edit')
wls:/myserver/edit !> ls()
dr--  AppDeployments
dr--  BridgeDestinations
dr--  Clusters
dr--  DeploymentConfiguration
dr--  Deployments
dr--  EmbeddedLDAP
...
wls:/myserver/edit !>

```

3.11.6 jndi

Command Category: Tree Commands

Use with WLST: Online

3.11.6.1 Description

Navigates to the JNDI tree for the server to which WLST is currently connected. This read-only tree holds all the elements that are currently bound in JNDI.

In the event of an error, the command returns a `WLSTException`.

3.11.6.2 Syntax

```
jndi()
```

3.11.6.3 Example

The following example navigates from the runtime MBean hierarchy to the Domain JNDI tree on an Administration Server instance.

```
wls:/myserver/runtime> jndi()
Location changed to jndi tree. This is a read-only tree with No root. For more
help, use help('jndi')
wls:/myserver/jndi> ls()
dr--  ejb
dr--  javax
dr--  jms
dr--  weblogic
...
```

3.11.7 serverConfig

Command Category: Tree Commands

Use with WLST: Online

3.11.7.1 Description

Navigates to the last MBean to which you navigated in the configuration MBean hierarchy or to the root of the hierarchy, `DomainMBean`.

This read-only hierarchy stores the configuration MBeans that represent the server to which WLST is currently connected. The MBean attribute values include any command-line overrides that a user specified while starting the server.

In the event of an error, the command returns a `WLSTException`.

For more information, see "Navigating Among MBean Hierarchies" in *Oracle Fusion Middleware Oracle WebLogic Scripting Tool*.

3.11.7.2 Syntax

```
serverConfig()
```

3.11.7.3 Example

The following example navigates from the domain runtime MBean hierarchy to the configuration MBean hierarchy on an Administration Server instance.

```
wls:/mydomain/domainRuntime> serverConfig()
wls:/mydomain/serverConfig>
```

3.11.8 serverRuntime

Command Category: Tree Commands

Use with WLST: Online

3.11.8.1 Description

Navigates to the last MBean to which you navigated in the runtime MBean hierarchy or to the root of the hierarchy, `ServerRuntimeMBean`. This read-only hierarchy stores the runtime MBeans that represent the server to which WLST is currently connected.

In the event of an error, the command returns a `WLSTException`.

3.11.8.2 Syntax

```
serverRuntime()
```

3.11.8.3 Example

The following example navigates from the configuration MBean hierarchy to the runtime MBean hierarchy on an Administration Server instance.

```
wls:/mydomain/serverConfig> serverRuntime()  
Location changed to serverRuntime tree. This is a read-only tree with  
ServerRuntimeMBean as the root.  
For more help, use help('serverRuntime')  
wls:/mydomain/serverRuntime>
```

3.12 WLST Variable Reference

[Table 3–13](#) describes WLST variables and their common usage. All variables are initialized to default values at the start of a user session and are changed according to the user interaction with WLST.

Table 3–13 WLST Variables

Variable	Description	Example
cmgr	The cmgr variable is set to the ConfigurationManagerMBean. You can use this variable to get the current value of any ConfigurationManagerMBean attribute.	wls:/mydomain/edit> cmgr.getCurrentEditor() 'weblogic'
cmo	Current Management Object. The cmo variable is set to the bean instance to which you navigate using WLST. You can use this variable to perform any get, set, or invoke method on the current bean instance. WLST sets the variable to the current WLST path. For example, when you change to the serverConfig hierarchy, cmo is set to DomainMBean. When you change to the serverRuntime hierarchy, cmo is set to ServerRuntimeMBean. The variable is available in all WLST hierarchies except custom and jndi.	wls:/mydomain/edit> cmo.setAdministrationPort(9092)
connected	Boolean value specifying whether WLST is connected to a running server. WLST sets this variable to true when connected to a running server; otherwise, WLST sets it to false.	wls:/mydomain/serverConfig> print connected false
domainName	Name of the WebLogic domain to which WLST is connected.	wls:/mydomain/serverConfig> print domainName mydomain
domainRuntimeService	DomainRuntimeServiceMBean MBean. This variable is available only when WLST is connected to the Administration Server.	wls:/mydomain/serverConfig> domainService.getServerName() 'myserver'
editService	EditServiceMBean MBean. This variable is available only when WLST is connected to the Administration Server.	wls:/mydomain/edit> dc = editService.getDomainConfiguration()
exitonerror	Boolean value specifying whether WLST terminates script execution when it encounters an exception. This variable defaults to true, indicating that script execution is terminated when WLST encounters an error. This variable is not applicable when running WLST in interactive mode.	wls:/mydomain/serverConfig> print exitonerror true
home	Represents the local MBeanHome.	wls:/mydomain/serverConfig> print home weblogic.rmi.internal.BasicRemoteRef - hostID: '-hostID:[7001,7001,-1,-1,-1,-1,-1]:mydomain:Admin Server', oid: '260', channel: 'null'
isAdminServer	Boolean value specifying whether WLST is connected to a WebLogic Administration Server instance. WLST sets this variable to true if WLST is connected to a WebLogic Administration Server; otherwise, WLST sets it to false.	wls:/mydomain/serverConfig> print isAdminServer true

Table 3–13 (Cont.) WLST Variables

Variable	Description	Example
mbs	MBeanServerConnection object that corresponds to the current location in the hierarchy.	wls:/mydomain/serverConfig> mbs.isRegistered(ObjectName('mydomain:Name=mydomain,Type=Domain'))
recording	Boolean value specifying whether WLST is recording commands. WLST sets this variable to true when the startRecording command is entered; otherwise, WLST sets this variable to false.	wls:/mydomain/serverConfig> print recording true
runtimeService	RuntimeServiceMBean MBean.	wls:/mydomain/serverConfig> sr=runtimeService.getServerRuntime()
serverName	Name of the server to which WLST is connected.	wls:/mydomain/serverConfig> print serverName myserver
typeService	TypeServiceMBean MBean.	wls:/mydomain/serverConfig> mi=typeService.getMBeanInfo('weblogic.management.configuration.ServerMBean')
username	Name of user currently connected to WLST.	wls:/mydomain/serverConfig> print username weblogic
version	Current version of the running server to which WLST is connected.	wls:/mydomain/serverConfig> print version WebLogic Server 9.0 Thu Aug 31 12:15:50 PST 2005 778899

Infrastructure Security Custom WLST Commands

This chapter provides detailed descriptions of custom WLST commands for infrastructure security, including command syntax, arguments and command examples.

The following sections describe the Oracle Fusion Middleware Infrastructure Security custom WLST commands in detail. Topics include:

- [Section 4.1, "Overview of WLST Security Commands"](#)
- [Section 4.2, "Audit Configuration Commands"](#)
- [Section 4.3, "SSL Configuration Commands"](#)
- [Section 4.4, "Oracle Identity Federation Commands"](#)
- [Section 4.5, "Directory Integration Platform Commands"](#)
- [Section 4.6, "Security Commands"](#)
- [Section 4.7, "Oracle Access Manager Commands"](#)
- [Section 4.8, "Oracle Security Token Service"](#)
- [Section 4.9, "Oracle Keystore Service"](#)

For additional information about Oracle Platform Security Services, see *Oracle Fusion Middleware Application Security Guide*.

Note: To use the Infrastructure Security custom WLST commands, you must invoke the WLST script from the Oracle Common home. See "Using Custom WLST Commands" in the *Oracle Fusion Middleware Administrator's Guide*.

4.1 Overview of WLST Security Commands

WLST security commands are divided into the following categories:

Table 4–1 WLST Command Categories

Command Category	Description
Audit Configuration Commands	View and manage audit policies and the audit repository configuration

Table 4–1 (Cont.) WLST Command Categories

Command Category	Description
SSL Configuration Commands	View and manage wallets, JKS keystores, and SSL configuration for Oracle HTTP Server, Oracle WebCache, Oracle Internet Directory, and Oracle Virtual Directory components.
Oracle Identity Federation Commands	View and manage configuration for Oracle Identity Federation
Directory Integration Platform Commands	For information on DIP tools, see "Oracle Directory Integration Platform Tools" in the <i>Oracle Fusion Middleware Reference for Oracle Identity Management</i>
Security Commands	Manage domain and credential domain stores and migrate domain policy store.
Oracle Access Manager Commands	Manage OAM-related components, such as authorization providers, identity asserters, and SSO providers.

4.2 Audit Configuration Commands

Use the WLST commands listed in [Table 4–2](#) to view and manage audit policies and the audit repository configuration.

Table 4–2 WLST Audit Commands

Use this command...	To...	Use with WLST...
getNonJavaEEAuditMBeanName	Display the mBean name for a non-Java EE component.	Online
getAuditPolicy	Display audit policy settings.	Online
setAuditPolicy	Update audit policy settings.	Online
getAuditRepository	Display audit repository settings.	Online
setAuditRepository	Update audit repository settings.	Online
listAuditEvents	List audit events for one or all components.	Online
exportAuditConfig	Export a component's audit configuration.	Online
importAuditConfig	Import a component's audit configuration.	Online
createAuditDBView	Create an audit definitions view in the database.	Online
listAuditComponents	List components that can be audited.	Online
registerAudit	Registers audit definitions for a specified component in the audit store.	Online
deregisterAudit	Removes audit definitions of a specified component from the audit store.	Online

For more information, see the *Oracle Fusion Middleware Application Security Guide*.

4.2.1 getNonJavaEEAuditMBeanName

Online command that displays the mbean name for non-Java EE components.

4.2.1.1 Description

This command displays the mbean name for non-Java EE components given the instance name, component name, component type, and the name of the Oracle WebLogic Server on which the component's audit mbean is running. The mbean name is a required parameter to other audit WLST commands when managing a non-Java EE component.

4.2.1.2 Syntax

```
getNonJavaEEAuditMBeanName(instName, compName, compType, svrName)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid values are ohs, oid, ovd, and WebCache.
<i>svrName</i>	Specifies the name of the Oracle WebLogic Server.

4.2.1.3 Example

The following interactive command displays the mBean name for an Oracle Internet Directory:

```
wls:/mydomain/serverConfig> getNonJavaEEAuditMBeanName(instName='inst1',
compName='oid1', compType='oid', svrName='AdminServer')
```

4.2.2 getAuditPolicy

Online command that displays the audit policy settings.

4.2.2.1 Description

This command displays audit policy settings including the filter preset, special users, custom events, maximum log file size, and maximum log directory size. The component mbean name is required for non-Java EE components like Oracle Internet Directory and Oracle Virtual Directory.

Note: You can obtain a non-Java EE component's MBean name using the [getNonJavaEEAuditMBeanName](#) command.

4.2.2.2 Syntax

```
getAuditPolicy([mbeanName, componentType])
```

Argument	Definition
<i>mbeanName</i>	Specifies the name of the component audit MBean for non-Java EE components.
<i>componentType</i>	Requests the audit policy for a specific component registered in the audit store. If not specified, the audit policy in <code>jps-config.xml</code> is returned.

4.2.2.3 Examples

The following command displays the audit settings for a Java EE component:

```
wls:/mydomain/serverConfig> getAuditPolicy()
Location changed to domainRuntime tree. This is a read-only tree with DomainMBean
as the root.
For more help, use help(domainRuntime)
```

```
FilterPreset:All
Max Log File Size:104857600
Max Log Dir Size:0
```

The following command displays the audit settings for MBean CSAuditProxyMBean:

```
wls:/mydomain/serverConfig>
getAuditPolicy(on='oracle.security.audit.test:type=CSAuditMBean,
name=CSAuditProxyMBean')
```

4.2.3 setAuditPolicy

Online command that updates an audit policy.

4.2.3.1 Description

Online command that configures the audit policy settings. You can set the filter preset, add or remove users, and add or remove custom events. The component mbean name is required for non-Java EE components like Oracle Internet Directory and Oracle Virtual Directory.

Note: You can obtain a non-Java EE component's MBean name using the [getNonJavaEEAuditMBeanName](#) command.

4.2.3.2 Syntax

```
setAuditPolicy([mbeanName], [filterPreset], [addSpecialUsers],
[removeSpecialUsers], [addCustomEvents], [removeCustomEvents], [componentType],
[maxDirSize], [maxFileSize], [andCriteria], [orCriteria], [componentEventsFile])
```

Argument	Definition
<i>mbeanName</i>	Specifies the name of the component audit MBean for non-Java EE components.
<i>filterPreset</i>	Specifies the filter preset to be changed.
<i>addSpecialUsers</i>	Specifies the special users to be added.
<i>removeSpecialUsers</i>	Specifies the special users to be removed.
<i>addCustomEvents</i>	Specifies the custom events to be added.
<i>removeCustomEvents</i>	Specifies the custom events to be removed.
<i>componentType</i>	Specifies the component definition type to be updated. If not specified, the audit configuration defined in jps-config.xml is modified.
<i>maxDirSize</i>	Specifies the maximum size of the log directory.
<i>maxFileSize</i>	Specifies the maximum size of the log file.
<i>andCriteria</i>	Specifies the and criteria in a custom filter preset definition.
<i>orCriteria</i>	Specifies the or criteria in a custom filter preset definition.

Argument	Definition
<i>componentEventsFile</i>	Specifies a component definition file under the 11g Release 1 (11.1.1.6) metadata model. This parameter is required if you wish to create/update an audit policy in the audit store for an 11g Release 1 (11.1.1.6) metadata model component, and the filter preset level is set to "Custom".

4.2.3.3 Examples

The following interactive command sets audit policy to None level, and adds users user2 and user3 while removing user1 from the policy:

```
wls:/mydomain/serverConfig> setAuditPolicy (filterPreset=
'None',addSpecialUsers='user2,user3',removeSpecialUsers='user1')
```

```
wls:/mydomain/serverConfig> getAuditPolicy();
Already in Domain Runtime Tree
```

```
FilterPreset:None
Special Users:user2,user3
Max Log File Size:104857600
Max Log Dir Size:0
```

The following interactive command adds login events while removing logout events from the policy:

```
wls:/mydomain/serverConfig> setAuditPolicy(filterPreset=
'Custom',addCustomEvents='UserLogin',removeCustomEvents='UserLogout')
```

The following interactive command sets audit policy to a Low level:

```
wls:/IDMDomain/domainRuntime> setAuditPolicy(filterPreset='Low');
Already in Domain Runtime Tree
Audit Policy Information updated successfully
```

```
wls:/IDMDomain/domainRuntime> getAuditPolicy();
Already in Domain Runtime Tree
FilterPreset:Low
Max Log File Size:104857600
Max Log Dir Size:0
```

The following command sets a custom filter to audit the CheckAuthorization event:

```
wls:/IDMDomain/domainRuntime> setAuditPolicy(filterPreset='Custom',
addCustomEvents='JPS:CheckAuthorization');
```

```
Already in Domain Runtime Tree
```

```
Audit Policy Information updated successfully
```

```
wls:/IDMDomain/domainRuntime> getAuditPolicy();
Already in Domain Runtime Tree
```

```
FilterPreset:Custom
Special Users:user1
Max Log File Size:104857600
Max Log Dir Size:0
Custom Events:JPS:CheckAuthorization
```

4.2.4 getAuditRepository

Online command that displays audit repository settings.

4.2.4.1 Description

This command displays audit repository settings for Java EE components and applications (for other components like Oracle Internet Directory, the repository configuration resides in `opmn.xml`). Also displays database configuration if the repository is a database type.

4.2.4.2 Syntax

```
getAuditRepository
```

4.2.4.3 Example

The following command displays audit repository configuration:

```
wls:/IDMDomain/domainRuntime> getAuditRepository()
Already in Domain Runtime Tree

Repository Type:File
```

4.2.5 setAuditRepository

Online command that updates audit repository settings.

4.2.5.1 Description

This command sets the audit repository settings for Java EE components and applications (for other components like Oracle Internet Directory, the repository is configured by editing `opmn.xml`).

4.2.5.2 Syntax

```
setAuditRepository([switchToDB], [dataSourceName], [interval])
```

Argument	Definition
<i>switchToDB</i>	If <code>true</code> , switches the repository from file to database.
<i>dataSourceName</i>	Specifies the name of the data source.
<i>interval</i>	Specifies intervals at which the audit loader kicks off.

4.2.5.3 Examples

The following command switches from a file repository to a database repository:

```
wls:/IDMDomain/domainRuntime> setAuditRepository(switchToDB='true');
Already in Domain Runtime Tree

Audit Repository Information updated

wls:/IDMDomain/domainRuntime> getAuditRepository();
Already in Domain Runtime Tree

JNDI Name:jdbc/AuditDB
Interval:15
Repository Type:DB
```


The following interactive command changes audit repository to a specific database and sets the audit loader interval to 14 seconds:

```
wls:/mydomain/serverConfig>
setAuditRepository(switchToDB='true',dataSourceName='jdbcAuditDB',interval='14')
```

4.2.6 listAuditEvents

Online command that displays a component's audit events.

4.2.6.1 Description

This command displays a component's audit events and attributes. For non-Java EE components, pass the component mbean name as a parameter. Java EE applications and services like Oracle Platform Security Services (OPSS) do not need the mbean parameter. Without a component type, all generic attributes applicable to all components are displayed.

Note: You can obtain a non-Java EE component's MBean name using the [getNonJavaEEAuditMBeanName](#) command.

4.2.6.2 Syntax

```
listAuditEvents ([mbeanName], [componentType])
```

Argument	Definition
<i>mbeanName</i>	Specifies the name of the component MBean.
<i>componentType</i>	Specifies the component type to limit the list to all events of the component type.

4.2.6.3 Examples

The following command displays audit events for the Oracle Platform Security Services component:

```
wls:/IDMDomain/domainRuntime> listAuditEvents(componentType='JPS');
Already in Domain Runtime Tree
```

Common Attributes

ComponentType

Type of the component. For MAS integrated SystemComponents this is the componentType

InstanceId

Name of the MAS Instance, that this component belongs to

HostId

DNS hostname of originating host

HostNwaddr

IP or other network address of originating host

ModuleId

ID of the module that originated the message. Interpretation is unique within Component ID.

ProcessId

ID of the process that originated the message

The following command displays audit events for Oracle HTTP Server:

```
wls:/mydomain/serverConfig> listAuditEvents(componentType='ohs')
```

The following command displays all audit events:

```
wls:/IDMDomain/domainRuntime> listAuditEvents();
Already in Domain Runtime Tree

Components:
DIP
JPS
OIF
OWSM-AGENT
OWSM-PM-EJB
ReportsServer
WS-PolicyAttachment
WebCache
WebServices
Attributes applicable to all components:
ComponentType
InstanceId
HostId
HostNwaddr
ModuleId
ProcessId
OracleHome
HomeInstance
ECID
RID
...
```

4.2.7 exportAuditConfig

Online command that exports a component's audit configuration.

4.2.7.1 Description

This command exports the audit configuration to a file. For non-Java EE components, pass the component mbean name as a parameter. Java EE applications and services like Oracle Platform Security Services (OPSS) do not need the mbean parameter.

Note: You can obtain a non-Java EE component's MBean name using the [getNonJavaEEAuditMBeanName](#) command.

4.2.7.2 Syntax

```
exportAuditConfig([mbeanName], fileName, [componentType])
```

Argument	Definition
<i>mbeanName</i>	Specifies the name of the non-Java EE component MBean.
<i>fileName</i>	Specifies the path and file name to which the audit configuration should be exported.
<i>componentType</i>	Specifies that only events of the given component be exported to the file. If not specified, the audit configuration in <code>jps-config.xml</code> is exported.

4.2.7.3 Examples

The following interactive command exports the audit configuration for a component:

```
wls:/mydomain/serverConfig>
```

```
exportAuditConfig(on='oracle.security.audit.test:type=CSAuditMBean,
name=CSAuditProxyMBean', fileName='/tmp/auditconfig')
```

The following interactive command exports the audit configuration for a Java EE component; no mBean is specified:

```
wls:/mydomain/serverConfig> exportAuditConfig(fileName='/tmp/auditconfig')
```

4.2.8 importAuditConfig

Online command that imports a component's audit configuration.

4.2.8.1 Description

This command imports the audit configuration from an external file. For non-Java EE components, pass the component mbean name as a parameter. Java EE applications and services like Oracle Platform Security Services (OPSS) do not need the mbean parameter.

Note: You can obtain a non-Java EE component's MBean name using the [getNonJavaEEAuditMBeanName](#) command.

4.2.8.2 Syntax

```
importAuditConfig([mbeanName], fileName, [componentType])
```

Argument	Definition
<i>mbeanName</i>	Specifies the name of the non-Java EE component MBean.
<i>fileName</i>	Specifies the path and file name from which the audit configuration should be imported.
<i>componentType</i>	Specifies that only events of the given component be imported from the file. If not specified, the audit configuration in <code>jps-config.xml</code> is imported.

4.2.8.3 Examples

The following interactive command imports the audit configuration for a component:

```
wls:/mydomain/serverConfig>
importAuditConfig(on='oracle.security.audit.test:type=CSAuditMBean,
name='CSAuditProxyMBean', fileName='/tmp/auditconfig')
```

The following interactive command imports the audit configuration from a file; no mBean is specified:

```
wls:/mydomain/serverConfig> importAuditConfig(fileName='/tmp/auditconfig')
```

4.2.9 createAuditDBView

Creates a SQL script that can generate a view for audit in the database.

4.2.9.1 Description

This command generates a SQL script that you can use to create a database view of the audit definitions of a specified component. The script is written to the specified file and also printed out to the console.

Upon execution, the result of the SQL script depends on the audit model at your site:

- If using the 11.1.1.6.0 model, and the component is registered in the audit store, the script creates a view using the system component tables (IAU_COMMON, IAU_USERSESSION, IAU_AUDITSERVICE and IAU_CUSTOM) for the specified component.
- If using the pre-11.1.1.6.0 model, the component is not registered in the audit store but its event definitions reside in the component_events.xml file (in the oracle_common/modules/oracle.iau_11.1.1/components/<componentType> dir), and the view is created using the IAU_BASE and component tables.

4.2.9.2 Syntax

```
createAuditDBView(fileName, componentType)
```

Argument	Definition
<i>fileName</i>	Specifies the path and file name to which the SQL script is written.
<i>componentType</i>	The component whose definitions are the basis of the view.

4.2.9.3 Example

```
wls:/mydomain/serverConfig>
createAuditDBView(fileName="/tmp/JPSAuditView.sql", componentType="JPS")
```

4.2.10 listAuditComponents

Lists components that can be audited.

4.2.10.1 Description

This command creates a list of the components that can be audited. It lists components registered in the audit store using both the 11.1.1.6.0 model and the pre-11.1.1.6.0 model.

4.2.10.2 Syntax

```
listAuditComponents(fileName)
```

Argument	Definition
<i>fileName</i>	Specifies the path and file name to which the output is written.

4.2.10.3 Example

```
listAuditComponents(fileName = "/tmp/complist.txt")
```

4.2.11 registerAudit

Registers the specified component in the audit store.

4.2.11.1 Description

Adds the event definition and translation content for a specified component to the audit store. If you try to register using the pre-11.1.1.6.0 audit XML schema definition, it is upgraded to the 11.1.1.6.0 XML schema definition and then registered with the audit store.

4.2.11.2 Syntax

```
registerAudit(xmlFile, [xlfFile], componentType, [mode=OVERWRITE|UPGRADE])
```

Argument	Definition
<i>xmlFile</i>	Specifies the Component Event definition file.
<i>xlfFile</i>	Specifies the component xlf jar file. Optional.
<i>componentType</i>	Specifies the component to be registered.
<i>mode</i>	OVERWRITE or UPGRADE. Default is UPGRADE.

4.2.11.3 Example

```
wls:/mydomain/serverConfig>registerAudit(xmlFile="/tmp/comp.xml",
xmlFile="/tmp/comp_xlf.jar", componentType="AuditApp", mode="UPGRADE")
```

4.2.12 deregisterAudit

Removes the event definition and translation content for the specified component from the audit store.

4.2.12.1 Description

Removes an existing event definition and translation content for a specified component or application from the audit store.

4.2.12.2 Syntax

```
deregisterAudit(componentType)
```

Argument	Definition
<i>componentType</i>	Specifies the component whose definitions are to be removed.

4.2.12.3 Example

```
deregisterAudit(componentType="AuditApp")
```

4.3 SSL Configuration Commands

Use the WLST commands listed in [Table 4–3](#) to view and manage SSL configuration for Oracle Fusion Middleware components.

Table 4–3 WLST Commands for SSL Configuration

Use this command...	To...	Use with WLST...
addCertificateRequest	Generate a certificate signing request in an Oracle wallet.	Online
addSelfSignedCertificate	Add a self-signed certificate to an Oracle wallet.	Online
changeKeyStorePassword	Change the password to a JKS keystore.	Online
changeWalletPassword	Change the password to an Oracle wallet.	Online
configureSSL	Set the SSL attributes for a component listener.	Online

Table 4–3 (Cont.) WLST Commands for SSL Configuration

Use this command...	To...	Use with WLST...
<code>createKeyStore</code>	Create a JKS keystore.	Online
<code>createWallet</code>	Create an Oracle wallet.	Online
<code>deleteKeyStore</code>	Delete a JKS keystore.	Online
<code>deleteWallet</code>	Delete an Oracle wallet.	Online
<code>exportKeyStore</code>	Export a JKS keystore to a file.	Online
<code>exportKeyStoreObject</code>	Export an object from a JKS keystore to a file.	Online
<code>exportWallet</code>	Export an Oracle wallet to a file.	Online
<code>exportWalletObject</code>	Export an object from an Oracle wallet to a file.	Online
<code>generateKey</code>	Generate a key pair in a JKS keystore.	Online
<code>getKeyStoreObject</code>	Display a certificate or other object present in a JKS keystore.	Online
<code>getSSL</code>	Display the SSL attributes for a component listener.	Online
<code>getWalletObject</code>	Display a certificate or other object present in an Oracle wallet.	Online
<code>importKeyStore</code>	Import a JKS keystore from a file.	Online
<code>importKeyStoreObject</code>	Import a certificate or other object from a file to a JKS keystore.	Online
<code>importWallet</code>	Import an Oracle wallet from a file.	Online
<code>importWalletObject</code>	Import a certificate or other object from a file to an Oracle wallet.	Online
<code>listKeyStoreObjects</code>	List all objects present in a JKS keystore.	Online
<code>listKeyStores</code>	List all JKS keystores configured for a component instance.	Online
<code>listWalletObjects</code>	List all objects present in an Oracle wallet.	Online
<code>listWallets</code>	List all Oracle wallets configured for a component instance.	Online
<code>removeKeyStoreObject</code>	Remove a certificate or other object from a component instance's JKS keystore.	Online
<code>removeWalletObject</code>	Remove a certificate or other object from a component instance's Oracle wallet.	Online

For more information, see the *Oracle Fusion Middleware Administrator's Guide*.

4.3.1 addCertificateRequest

Online command that generates a certificate signing request in an Oracle wallet.

4.3.1.1 Description

This command generates a certificate signing request in Base64 encoded PKCS#10 format in an Oracle wallet for a component instance (Oracle HTTP Server, Oracle WebCache or Oracle Internet Directory). To get a certificate signed by a certificate authority (CA), send the certificate signing request to your CA.

4.3.1.2 Syntax

```
addCertificateRequest(instName, compName, compType, walletName, password, DN,
keySize)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid values are 'ohs', 'oid', and 'webcache'.
<i>walletName</i>	Specifies the name of the wallet file.
<i>password</i>	Specifies the password of the wallet.
<i>DN</i>	Specifies the Distinguished Name of the key pair entry.
<i>keySize</i>	Specifies the key size in bits.

4.3.1.3 Example

The following command generates a certificate signing request with DN `cn=www.acme.com` and key size 1024 in `wallet1`, for Oracle Internet Directory instance `oid1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> addCertificateRequest('inst1', 'oid1',
'oid','wallet1', 'password', 'cn=www.acme.com', '1024')
```

4.3.2 addSelfSignedCertificate

Online command that adds a self-signed certificate.

4.3.2.1 Description

This command creates a key pair and wraps it in a self-signed certificate in an Oracle wallet for the specified component instance (Oracle HTTP Server, Oracle WebCache or Oracle Internet Directory). Only keys based on the RSA algorithm are generated.

4.3.2.2 Syntax

```
addSelfSignedCertificate(instName, compName, compType, walletName, password, DN,
keySize)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid values are 'ohs', 'oid', and 'webcache'.
<i>walletName</i>	Specifies the name of the wallet file.
<i>password</i>	Specifies the password of the wallet.
<i>DN</i>	Specifies the Distinguished Name of the key pair entry.
<i>keySize</i>	Specifies the key size in bits.

4.3.2.3 Example

The following command adds a self-signed certificate with DN `cn=www.acme.com`, key size 1024 to `wallet1`, for Oracle Internet Directory instance `oid1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> addSelfSignedCertificate('inst1', 'oid1',
'oid','wallet1', 'password', 'cn=www.acme.com', '1024')
```

4.3.3 changeKeyStorePassword

Online command that changes the keystore password.

4.3.3.1 Description

This command changes the password of a Java Keystore (JKS) file for an Oracle Virtual Directory instance.

4.3.3.2 Syntax

```
changeKeyStorePassword(instName, compName, compType, keystoreName, currPassword,
newPassword)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid value is 'ovd'.
<i>keystoreName</i>	Specifies the filename of the keystore.
<i>currPassword</i>	Specifies the current keystore password.
<i>newPassword</i>	Specifies the new keystore password.

4.3.3.3 Example

The following command changes the password of file `keys.jks` for Oracle Virtual Directory instance `ovd1` in application server instance `inst1`:

```
wls:/mydomain/serverConfig> changeKeyStorePassword('inst1', 'ovd1',
'ovd','keys.jks', 'currpassword', 'newpassword')
```

4.3.4 changeWalletPassword

Online command that changes the password of an Oracle wallet.

4.3.4.1 Description

This command changes the password of an Oracle wallet for the specified component instance (Oracle HTTP Server, Oracle WebCache or Oracle Internet Directory). This command is only applicable to password-protected wallets.

4.3.4.2 Syntax

```
changeWalletPassword(instName, compName, compType, walletName, currPassword,
newPassword)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.

Argument	Definition
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid values are 'oid', 'ohs', and 'webcache'.
<i>walletName</i>	Specifies the filename of the wallet.
<i>currPassword</i>	Specifies the current wallet password.
<i>newPassword</i>	Specifies the new wallet password.

4.3.4.3 Example

The following command changes the password for `wallet1` from `currpassword` to `newpassword` for Oracle HTTP Server instance `ohs1` in application server instance `inst1`:

```
wls:/mydomain/serverConfig> changeWalletPassword('inst1', 'ohs1', 'ohs','wallet1', 'currpassword', 'newpassword')
```

4.3.5 configureSSL

Online command that sets SSL attributes.

4.3.5.1 Description

This command sets the SSL attributes for a component listener. The attributes are specified in a properties file format (name=value). If a properties file is not provided, or it does not contain any SSL attributes, default attribute values are used. For component-specific SSL attribute value defaults, see the chapter "SSL Configuration in Oracle Fusion Middleware" in the *Oracle Fusion Middleware Administrator's Guide*.

4.3.5.2 Syntax

```
configureSSL(instName, compName, compType, listener, filePath)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid values are 'oid', 'ovd', 'ohs', and 'webcache'.
<i>listener</i>	Specifies the name of the component listener to be configured for SSL.
<i>filePath</i>	Specifies the absolute path of the properties file containing the SSL attributes to set.

4.3.5.3 Examples

The following command configures SSL attributes specified in the properties file `/tmp/ssl.properties` for Oracle Virtual Directory instance `ovd1` in application server instance `inst1`, for listener `listener1`:

```
wls:/mydomain/serverConfig> configureSSL('inst1', 'ovd1', 'ovd', 'listener1', '/tmp/ssl.properties')
```

The following command configures SSL attributes without specifying a properties file. Since no file is provided, the default SSL attribute values are used:

```
wls:/mydomain/serverConfig> configureSSL('inst1', 'ovd1', 'ovd', 'listener2')
```

4.3.6 createKeyStore

Online command that creates a JKS keystore.

4.3.6.1 Description

This command creates a Java keystore (JKS) for the specified Oracle Virtual Directory instance. For keystore file location and other information, see the chapter "Managing Keystores, Wallets, and Certificates" in the *Oracle Fusion Middleware Administrator's Guide*.

4.3.6.2 Syntax

```
createKeyStore(instName, compName, compType, keystoreName, password)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid value is 'ovd'.
<i>keystoreName</i>	Specifies the filename of the keystore file to be created.
<i>password</i>	Specifies the keystore password.

4.3.6.3 Example

The following command creates JKS file `keys.jks` with password `password` for Oracle Virtual Directory instance `ovd1` in application server instance `inst1`:

```
wls:/mydomain/serverConfig> createKeyStore('inst1', 'ovd1', 'ovd', 'keys.jks', 'password')
```

4.3.7 createWallet

Online command that creates an Oracle wallet.

4.3.7.1 Description

This command creates an Oracle wallet for the specified component instance (Oracle HTTP Server, Oracle WebCache or Oracle Internet Directory). Wallets can be of password-protected or auto-login type. For wallet details, see the chapter "Managing Keystores, Wallets, and Certificates" in the *Oracle Fusion Middleware Administrator's Guide*.

4.3.7.2 Syntax

```
createWallet(instName, compName, compType, walletName, password)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid values are 'oid', 'ohs', and 'webcache'.
<i>walletName</i>	Specifies the name of the wallet file to be created.

Argument	Definition
<i>password</i>	Specifies the wallet password.

4.3.7.3 Examples

The following command creates a wallet named `wallet1` with password `password`, for Oracle HTTP Server instance `ohs1` in application server instance `inst1`:

```
wls:/mydomain/serverConfig> createWallet('inst1', 'ohs1', 'ohs','wallet1',
'password')
```

The following command creates an auto-login wallet named `wallet2` for Oracle WebCache instance `wc1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> createWallet('inst1', 'wc1', 'webcache','wallet2', '')
```

4.3.8 deleteKeyStore

Online command that deletes a keystore.

4.3.8.1 Description

This command deletes a keystore for a specified Oracle Virtual Directory instance.

4.3.8.2 Syntax

```
deleteKeyStore(instName, compName, compType, keystoreName)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid value is 'ovd'.
<i>keystoreName</i>	Specifies the name of the keystore file to delete.

4.3.8.3 Example

The following command deletes JKS file `keys.jks` for Oracle Virtual Directory instance `ovd1` in application server instance `inst1`:

```
wls:/mydomain/serverConfig> deleteKeyStore('inst1', 'ovd1', 'ovd','keys.jks')
```

4.3.9 deleteWallet

Online command that deletes an Oracle wallet.

4.3.9.1 Description

This command deletes an Oracle wallet for the specified component instance (Oracle HTTP Server, Oracle WebCache or Oracle Internet Directory).

4.3.9.2 Syntax

```
deleteWallet(instName, compName, compType, walletName)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.

Argument	Definition
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid values are 'oid', 'ohs', and 'webcache'.
<i>walletName</i>	Specifies the name of the wallet file to be deleted.

4.3.9.3 Example

The following command deletes a wallet named `wallet1` for Oracle HTTP Server instance `ohs1` in application server instance `inst1`:

```
wls:/mydomain/serverConfig> deleteWallet('inst1', 'ohs1', 'ohs', 'wallet1')
```

4.3.10 exportKeyStore

Online command that exports the keystore to a file.

4.3.10.1 Description

This command exports a keystore, configured for the specified Oracle Virtual Directory instance, to a file under the given directory. The exported filename is the same as the keystore name.

4.3.10.2 Syntax

```
exportKeyStore(instName, compName, compType, keystoreName, password, path)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid value is 'ovd'.
<i>keystoreName</i>	Specifies the name of the keystore file.
<i>password</i>	Specifies the password of the keystore.
<i>path</i>	Specifies the absolute path of the directory under which the keystore is exported.

4.3.10.3 Example

The following command exports the keystore `keys.jks` for Oracle Virtual Directory instance `ovd1` to file `keys.jks` under `/tmp`:

```
wls:/mydomain/serverConfig> exportKeyStore('inst1', 'ovd1', 'ovd', 'keys.jks', 'password', '/tmp')
```

4.3.11 exportKeyStoreObject

Online command that exports an object from a keystore to a file.

4.3.11.1 Description

This command exports a certificate signing request, certificate/certificate chain, or trusted certificate present in a Java keystore (JKS) to a file for the specified Oracle Virtual Directory instance. The certificate signing request is generated before exporting the object. The alias specifies the object to be exported.

4.3.11.2 Syntax

```
exportKeyStoreObject(instName, compName, compType, keystoreName, password, type,
path, alias)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid value is 'ovd'.
<i>keystoreName</i>	Specifies the name of the keystore file.
<i>password</i>	Specifies the password of the keystore.
<i>type</i>	Specifies the type of the keystore object to be exported. Valid values are 'CertificateRequest', 'Certificate', 'TrustedCertificate' and 'TrustedChain'.
<i>path</i>	Specifies the absolute path of the directory under which the object is exported as a file named base64.txt.
<i>alias</i>	Specifies the alias of the keystore object to be exported.

4.3.11.3 Examples

The following command generates and exports a certificate signing request from the key-pair indicated by alias `mykey` in `keys.jks`, for Oracle Virtual Directory instance `ovd1` in application server instance `inst1`. The certificate signing request is exported under the directory `/tmp`:

```
wls:/mydomain/serverConfig> exportKeyStoreObject('inst1', 'ovd1',
'ovd','keys.jks', 'password', 'CertificateRequest', '/tmp','mykey')
```

The following command exports a certificate or certificate chain indicated by alias `mykey` in `keys.jks`, for Oracle Virtual Directory instance `ovd1`, in application server instance `inst1`. The certificate or certificate chain is exported under the directory `/tmp`:

```
wls:/mydomain/serverConfig> exportKeyStoreObject('inst1', 'ovd1',
'ovd','keys.jks', 'password', 'Certificate', '/tmp','mykey')
```

The following command exports a trusted certificate indicated by alias `mykey` in `keys.jks`, for Oracle Virtual Directory instance `ovd1`, in application server instance `inst1`. The trusted certificate is exported under the directory `/tmp`:

```
wls:/mydomain/serverConfig> exportKeyStoreObject('inst1', 'ovd1',
'ovd','keys.jks', 'password', 'TrustedCertificate', '/tmp','mykey')
```

4.3.12 exportWallet

Online command that exports an Oracle wallet.

4.3.12.1 Description

This command exports an Oracle wallet, configured for a specified component instance (Oracle HTTP Server, Oracle WebCache or Oracle Internet Directory), to file(s) under the given directory. If the exported file is an auto-login only wallet, the file name is 'cwallet.sso'. If it is password-protected wallet, two files are created: 'ewallet.p12' and 'cwallet.sso'.

4.3.12.2 Syntax

```
exportWallet(instName, compName, compType, walletName,password, path)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid values are 'oid', 'ohs', and 'webcache'.
<i>walletName</i>	Specifies the name of the wallet file.
<i>password</i>	Specifies the password of the wallet.
<i>path</i>	Specifies the absolute path of the directory under which the object is exported.

4.3.12.3 Examples

The following command exports auto-login wallet `wallet1` for Oracle Internet Directory instance `oid1` to file `cwallet.sso` under `/tmp`:

```
wls:/mydomain/serverConfig> exportWallet('inst1', 'oid1', 'oid',
'wallet1','','/tmp')
```

The following command exports password-protected wallet `wallet2` for Oracle Internet Directory instance `oid1` to two files, `ewallet.p12` and `cwallet.sso`, under `/tmp`:

```
wls:/mydomain/serverConfig> exportWallet('inst1', 'oid1', 'oid', 'wallet2',
'password', '/tmp')
```

4.3.13 exportWalletObject

Online command that exports a certificate or other wallet object to a file.

4.3.13.1 Description

This command exports a certificate signing request, certificate, certificate chain or trusted certificate present in an Oracle wallet to a file for the specified component instance (Oracle HTTP Server, Oracle WebCache or Oracle Internet Directory). DN is used to indicate the object to be exported.

4.3.13.2 Syntax

```
exportWalletObject(instName, compName, compType, walletName, password, type, path,
DN)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid values are 'ohs', 'oid', and 'webcache'.
<i>walletName</i>	Specifies the name of the wallet file.
<i>password</i>	Specifies the password of the wallet.
<i>type</i>	Specifies the type of wallet object to be exported. Valid values are 'CertificateRequest', 'Certificate', 'TrustedCertificate' or 'TrustedChain'.

Argument	Definition
<i>path</i>	Specifies the absolute path of the directory under which the object is exported as a file base64.txt.
<i>DN</i>	Specifies the Distinguished Name of the wallet object being exported.

4.3.13.3 Examples

The following command exports a certificate signing request with DN `cn=www.acme.com` in `wallet1`, for Oracle Internet Directory instance `oid1`, in application server instance `inst1`. The certificate signing request is exported under the directory `/tmp`:

```
wls:/mydomain/serverConfig> exportWalletObject('inst1', 'oid1',
'oid','wallet1', 'password', 'CertificateRequest', '/tmp','cn=www.acme.com')
```

The following command exports a certificate with DN `cn=www.acme.com` in `wallet1`, for Oracle Internet Directory instance `oid1`, in application server instance `inst1`. The certificate or certificate chain is exported under the directory `/tmp`:

```
wls:/mydomain/serverConfig> exportWalletObject('inst1', 'oid1',
'oid','wallet1', 'password', 'Certificate', '/tmp','cn=www.acme.com')
```

The following command exports a trusted certificate with DN `cn=www.acme.com` in `wallet1`, for Oracle Internet Directory instance `oid1`, in application server instance `inst1`. The trusted certificate is exported under the directory `/tmp`:

```
wls:/mydomain/serverConfig> exportWalletObject('inst1', 'oid1',
'oid','wallet1', 'password', 'TrustedCertificate', '/tmp','cn=www.acme.com')
```

The following command exports a certificate chain with DN `cn=www.acme.com` in `wallet1`, for Oracle Internet Directory instance `oid1`, in application server instance `inst1`. The certificate or certificate chain is exported under the directory `/tmp`:

```
wls:/mydomain/serverConfig> exportWalletObject('inst1', 'oid1',
'oid','wallet1', 'password', 'TrustedChain', '/tmp','cn=www.acme.com')
```

4.3.14 generateKey

Online command that generates a key pair in a Java keystore.

4.3.14.1 Description

This command generates a key pair in a Java keystore (JKS) for Oracle Virtual Directory. It also wraps the key pair in a self-signed certificate. Only keys based on the RSA algorithm are generated.

4.3.14.2 Syntax

```
generateKey(instName, compName, compType, keystoreName, password, DN, keySize,
alias, algorithm)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid value is 'ovd'.
<i>keystoreName</i>	Specifies the name of the keystore.

Argument	Definition
<i>password</i>	Specifies the password of the keystore.
<i>DN</i>	Specifies the Distinguished Name of the key pair entry.
<i>keySize</i>	Specifies the key size in bits.
<i>alias</i>	Specifies the alias of the key pair entry in the keystore.
<i>algorithm</i>	Specifies the key algorithm. Valid value is 'RSA'.

4.3.14.3 Examples

The following command generates a key pair with DN `cn=www.acme.com`, key size 1024, algorithm `RSA` and alias `mykey` in `keys.jks`, for Oracle Virtual Directory instance `ovd1` in application server instance `inst1`:

```
wls:/mydomain/serverConfig> generateKey('inst1', 'ovd1', 'ovd', 'keys.jks',
'password', 'cn=www.acme.com', '1024', 'mykey', 'RSA')
```

The following command is the same as above, except it does not explicitly specify the key algorithm:

```
wls:/mydomain/serverConfig> generateKey('inst1', 'ovd1', 'ovd', 'keys.jks',
'password', 'cn=www.acme.com', '1024', 'mykey')
```

4.3.15 getKeyStoreObject

Online command that shows details about a keystore object.

4.3.15.1 Description

This command displays a specific certificate or trusted certificate present in a Java keystore (JKS) for Oracle Virtual Directory. The keystore object is indicated by its index number, as given by the `listKeyStoreObjects` command. It shows the certificate details including DN, key size, algorithm, and other information.

4.3.15.2 Syntax

```
getKeyStoreObject(instName, compName, compType, keystoreName, password, type,
index)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid value is 'ovd'.
<i>keystoreName</i>	Specifies the name of the keystore file.
<i>password</i>	Specifies the password of the keystore.
<i>type</i>	Specifies the type of the keystore object to be listed. Valid values are 'Certificate' and 'TrustedCertificate'.
<i>index</i>	Specifies the index number of the keystore object as returned by the <code>listKeyStoreObjects</code> command.

4.3.15.3 Examples

The following command shows a trusted certificate with index 1 present in `keys.jks`, for Oracle Virtual Directory instance `ovd1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> getKeyStoreObject('inst1', 'ovd1', 'ovd','keys.jks',
'password', 'TrustedCertificate', '1')
```

The following command shows a certificate with index 1 present in `keys.jks`, for Oracle Virtual Directory instance `ovd1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> getKeyStoreObject('inst1', 'ovd1', 'ovd','keys.jks',
'password', 'Certificate', '1')
```

4.3.16 getSSL

Online command that lists the configured SSL attributes.

4.3.16.1 Description

This command lists the configured SSL attributes for the specified component listener. For Oracle Internet Directory, the listener name is always `sslport1`.

4.3.16.2 Syntax

```
getSSL(instName, compName, compType, listener)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid values are 'ovd', 'oid', 'ohs', and 'webcache'.
<i>listener</i>	Specifies the name of the component listener.

4.3.16.3 Example

The following command shows the SSL attributes configured for Oracle Internet Directory instance `oid1`, in application server instance `inst1`, for listener `sslport1`:

```
wls:/mydomain/serverConfig> getSSL('inst1', 'oid1', 'oid', 'sslport1')
```

4.3.17 getWalletObject

Online command that displays information about a certificate or other object in an Oracle wallet.

4.3.17.1 Description

This command displays a specific certificate signing request, certificate or trusted certificate present in an Oracle wallet for the specified component instance (Oracle HTTP Server, Oracle WebCache or Oracle Internet Directory). The wallet object is indicated by its index number, as given by the `listWalletObjects` command. For certificates or trusted certificates, it shows the certificate details including DN, key size, algorithm and other data. For certificate signing requests, it shows the subject DN, key size and algorithm.

4.3.17.2 Syntax

```
getWalletObject(instName, compName, compType, walletName, password, type, index)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid values are 'ohs', 'oid', and 'webcache'.
<i>walletName</i>	Specifies the name of the wallet file.
<i>password</i>	Specifies the password of the wallet.
<i>type</i>	Specifies the type of wallet object to be exported. Valid values are 'CertificateRequest', 'Certificate', and 'TrustedCertificate'.
<i>index</i>	Specifies the index number of the wallet object as returned by the <code>listWalletObjects</code> command.

4.3.17.3 Examples

The following command shows certificate signing request details for the object with index 0 present in `wallet1`, for Oracle Internet Directory instance `oid1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> getKeyStoreObject('inst1', 'oid1',
'oid','wallet1','password', 'CertificateRequest', '0')
```

The following command shows certificate details for the object with index 0 present in `wallet1`, for Oracle Internet Directory instance `oid1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> getKeyStoreObject('inst1', 'oid1',
'oid','wallet1','password', 'Certificate', '0')
```

The following command shows trusted certificate details for the object with index 0, present in `wallet1`, for Oracle Internet Directory instance `oid1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> getKeyStoreObject('inst1', 'oid1',
'oid','wallet1','password', 'TrustedCertificate', '0')
```

4.3.18 importKeyStore

Online command that imports a keystore from a file.

4.3.18.1 Description

This command imports a Java keystore (JKS) from a file to the specified Oracle Virtual Directory instance for manageability. The component instance name must be unique.

4.3.18.2 Syntax

```
importKeyStore(instName, compName, compType, keystoreName, password, filePath)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance.

Argument	Definition
<i>compType</i>	Specifies the type of component. Valid value is 'ovd'.
<i>keystoreName</i>	Specifies the name of the keystore being imported. This name must be unique for this component instance.
<i>password</i>	Specifies the password of the keystore.
<i>filePath</i>	Specifies the absolute path of the keystore file to be imported.

4.3.18.3 Example

The following command imports the keystore `/tmp/keys.jks` as `file.jks` into Oracle Virtual Directory instance `ovd1`. Subsequently, the keystore is managed through the name `file.jks`:

```
wls:/mydomain/serverConfig> importKeyStore('inst1', 'ovd1', 'ovd', 'file.jks',
'password', '/tmp/keys.jks')
```

4.3.19 importKeyStoreObject

Online command that imports an object from a file to a keystore.

4.3.19.1 Description

This command imports a certificate, certificate chain, or trusted certificate into a Java keystore (JKS) for Oracle Virtual Directory, assigning it the specified alias which must be unique in the keystore. If a certificate or certificate chain is being imported, the alias must match that of the corresponding key-pair.

4.3.19.2 Syntax

```
importKeyStoreObject(instName, compName, compType, keystoreName, password, type,
filePath, alias)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid value is 'ovd'.
<i>keystoreName</i>	Specifies the name of the keystore.
<i>password</i>	Specifies the password of the keystore.
<i>type</i>	Specifies the type of the keystore object to be imported. Valid values are 'Certificate' and 'TrustedCertificate'.
<i>filePath</i>	Specifies the absolute path of the file containing the keystore object.
<i>alias</i>	Specifies the alias to assign to the keystore object to be imported.

4.3.19.3 Examples

The following command imports a certificate or certificate chain from file `cert.txt` into `keys.jks`, using alias `mykey` for Oracle Virtual Directory instance `ovd1`, in application server instance `inst1`. The file `keys.jks` must already have an alias `mykey` for a key-pair whose public key matches that in the certificate being imported:

```
wls:/mydomain/serverConfig> > importKeyStoreObject('inst1', 'ovd1',
'ovd', 'keys.jks', 'password', 'Certificate', '/tmp/cert.txt', 'mykey')
```

The following command imports a trusted certificate from file `trust.txt` into `keys.jks` using alias `mykey1`, for Oracle Virtual Directory instance `ovd1` in application server instance `inst1`:

```
wls:/mydomain/serverConfig> importKeyStoreObject('inst1', 'ovd1',
'ovd','keys.jks', 'password', 'TrustedCertificate','/tmp/trust.txt', 'mykey1')
```

4.3.20 importWallet

Online command that imports an Oracle wallet from a file.

4.3.20.1 Description

This command imports an Oracle wallet from a file to the specified component instance (Oracle HTTP Server, Oracle WebCache, or Oracle Internet Directory) for manageability. If the wallet being imported is an auto-login wallet, the file path must point to `cwallet.sso`; if the wallet is password-protected, it must point to `ewallet.p12`. The wallet name must be unique for the component instance.

4.3.20.2 Syntax

```
importWallet(instName, compName, compType, walletName, password, filePath)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid values are 'ohs', 'oid', and 'webcache'.
<i>walletName</i>	Specifies the name of the wallet being imported. The name must be unique for the component instance.
<i>password</i>	Specifies the password of the wallet.
<i>filePath</i>	Specifies the absolute path of the wallet file being imported.

4.3.20.3 Examples

The following command imports auto-login wallet file `/tmp/cwallet.sso` as `wallet1` into Oracle Internet Directory instance `oid1`. Subsequently, the wallet is managed with the name `wallet1`. No password is passed since it is an auto-login wallet:

```
wls:/mydomain/serverConfig> importWallet('inst1', 'oid1', 'oid', 'wallet1', '',
'/tmp/cwallet.sso')
```

The following command imports password-protected wallet `/tmp/ewallet.p12` as `wallet2` into Oracle Internet Directory instance `oid1`. Subsequently, the wallet is managed with the name `wallet2`. The wallet password is passed as a parameter:

```
wls:/mydomain/serverConfig> importWallet('inst1', 'oid1', 'oid', 'wallet2',
'password', '/tmp/ewallet.p12')
```

4.3.21 importWalletObject

Online command that imports a certificate or other object into an Oracle wallet.

4.3.21.1 Description

This command imports a certificate, trusted certificate or certificate chain into an Oracle wallet for the specified component instance (Oracle HTTP Server, Oracle WebCache component or Oracle Internet Directory). When importing a certificate, use the same wallet file from which the certificate signing request was generated.

4.3.21.2 Syntax

```
importWalletObject(instName, compName, compType, walletName, password, type,
filePath)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid values are 'ohs', 'oid', and 'webcache'.
<i>walletName</i>	Specifies the name of the wallet file.
<i>password</i>	Specifies the password of the wallet.
<i>type</i>	Specifies the type of wallet object to be imported. Valid values are 'Certificate', 'TrustedCertificate' and 'TrustedChain'.
<i>filePath</i>	Specifies the absolute path of the file containing the wallet object.

4.3.21.3 Examples

The following command imports a certificate chain in PKCS#7 format from file `chain.txt` into `wallet1`, for Oracle Internet Directory instance `oid1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> importWalletObject('inst1', 'oid1', 'oid','wallet1',
'password', 'TrustedChain', '/tmp/chain.txt')
```

The following command imports a certificate from file `cert.txt` into `wallet1`, for Oracle Internet Directory instance `oid1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> importWalletObject('inst1', 'oid1', 'oid','wallet1',
'password', 'Certificate', '/tmp/cert.txt')
```

The following command imports a trusted certificate from file `trust.txt` into `wallet1`, for Oracle Internet Directory instance `oid1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> importWalletObject('inst1', 'oid1', 'oid','wallet1',
'password', 'TrustedCertificate', '/tmp/trust.txt')
```

4.3.22 listKeyStoreObjects

Online command that lists the contents of a keystore.

4.3.22.1 Description

This command lists all the certificates or trusted certificates present in a Java keystore (JKS) for Oracle Virtual Directory.

4.3.22.2 Syntax

```
listKeyStoreObjects(instName, compName, compType, keystoreName, password, type)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid value is 'ovd'.
<i>keystoreName</i>	Specifies the name of the keystore file.
<i>password</i>	Specifies the password of the keystore.
<i>type</i>	Specifies the type of keystore object to be listed. Valid values are 'Certificate' and 'TrustedCertificate'.

4.3.22.3 Examples

The following command lists all trusted certificates present in `keys.jks`, for Oracle Virtual Directory instance `ovd1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> listKeyStoreObjects('inst1', 'ovd1', 'ovd', 'keys.jks',
'password', 'TrustedCertificate')
```

The following command lists all certificates present in `keys.jks`, for Oracle Virtual Directory instance `ovd1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> listKeyStoreObjects('inst1', 'ovd1', 'ovd', 'keys.jks',
'password', 'Certificate')
```

4.3.23 listKeyStores

Online command that lists all the keystores for a component.

4.3.23.1 Description

This command lists all the Java keystores (JKS) configured for the specified Oracle Virtual Directory instance.

4.3.23.2 Syntax

```
listKeyStores(instName, compName, compType)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance
<i>compType</i>	Specifies the type of component. Valid value is 'ovd'.

4.3.23.3 Example

The following command lists all keystores for Oracle Virtual Directory instance `ovd1` in application server instance `inst1`:

```
wls:/mydomain/serverConfig> listKeyStores('inst1', 'ovd1', 'ovd')
```

4.3.24 listWalletObjects

Online command that lists all objects in an Oracle wallet.

4.3.24.1 Description

This command lists all certificate signing requests, certificates, or trusted certificates present in an Oracle wallet for the specified component instance (Oracle HTTP Server, Oracle WebCache or Oracle Internet Directory).

4.3.24.2 Syntax

```
listWalletObjects(instName, compName, compType, walletName, password, type)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid values are 'ohs', 'oid', and 'webcache'.
<i>walletName</i>	Specifies the name of the wallet file.
<i>password</i>	Specifies the password of the wallet.
<i>type</i>	Specifies the type of wallet object to be listed. Valid values are 'CertificateRequest', 'Certificate', and 'TrustedCertificate'.

4.3.24.3 Examples

The following command lists all certificate signing requests in `wallet1`, for Oracle Internet Directory instance `oid1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> > listWalletObjects('inst1', 'oid1',
'oid','wallet1','password', 'CertificateRequest')
```

The following command lists all certificates in `wallet1`, for Oracle Internet Directory instance `oid1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> listWalletObjects('inst1', 'oid1',
'oid','wallet1','password', 'Certificate')
```

The following command lists all trusted certificates in `wallet1`, for Oracle Internet Directory instance `oid1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> listWalletObjects('inst1', 'oid1',
'oid','wallet1','password', 'TrustedCertificate')
```

4.3.25 listWallets

Online command that lists all wallets configured for a component instance.

4.3.25.1 Description

This command displays all the wallets configured for the specified component instance (Oracle HTTP Server, Oracle WebCache or Oracle Internet Directory), and identifies the auto-login wallets.

4.3.25.2 Syntax

```
listWallets(instName, compName, compType)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.

Argument	Definition
<i>compName</i>	Specifies the name of the component instance
<i>compType</i>	Specifies the type of component. Valid values are 'ohs', 'oid', and 'webcache'.

4.3.25.3 Example

The following command lists all wallets for Oracle Internet Directory instance `oid1` in application server instance `inst1`:

```
wls:/mydomain/serverConfig> listWallets('inst1', 'oid1', 'oid')
```

4.3.26 removeKeyStoreObject

Online command that removes an object from a keystore.

4.3.26.1 Description

This command removes a certificate request, certificate, trusted certificate, or all trusted certificates from a Java keystore (JKS) for Oracle Virtual Directory. Use an alias to remove a specific object; no alias is needed if all trusted certificates are being removed.

4.3.26.2 Syntax

```
removeKeyStoreObject(instName, compName, compType, keystoreName, password, type, alias)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid value is 'ovd'.
<i>keystoreName</i>	Specifies the name of the keystore file.
<i>password</i>	Specifies the password of the keystore.
<i>type</i>	Specifies the type of the keystore object to be removed. Valid values are 'Certificate', 'TrustedCertificate' or 'TrustedAll'.
<i>alias</i>	Specifies the alias of the keystore object to be removed.

4.3.26.3 Examples

The following command removes a certificate or certificate chain denoted by alias `mykey` in `keys.jks`, for Oracle Virtual Directory instance `ovd1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> removeKeyStoreObject('inst1', 'ovd1', 'ovd', 'keys.jks', 'password', 'Certificate', 'mykey')
```

The following command removes a trusted certificate denoted by alias `mykey` in `keys.jks`, for Oracle Virtual Directory instance `ovd1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> removeKeyStoreObject('inst1', 'ovd1', 'ovd', 'keys.jks', 'password', 'TrustedCertificate', 'mykey')
```


The following command removes all trusted certificates in `keys.jks`, for Oracle Virtual Directory instance `ovd1`, in application server instance `inst1`. Since no alias is required, the value `None` is passed for that parameter:

```
wls:/mydomain/serverConfig> removeKeyStoreObject('inst1', 'ovd1',
'ovd','keys.jks', 'password', 'TrustedAll',None)
```

4.3.27 removeWalletObject

Online command that removes a certificate or other object from an Oracle wallet.

4.3.27.1 Description

This command removes a certificate signing request, certificate, trusted certificate or all trusted certificates from an Oracle wallet for the specified component instance (Oracle HTTP Server, Oracle WebCache or Oracle Internet Directory). DN is used to indicate the object to be removed.

4.3.27.2 Syntax

```
removeWalletObject(instName, compName, compType, walletName, password, type, DN)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid values are 'ohs', 'oid', and 'webcache'.
<i>walletName</i>	Specifies the name of the wallet file.
<i>password</i>	Specifies the password of the wallet.
<i>type</i>	Specifies the type of the keystore object to be removed. Valid values are 'CertificateRequest', 'Certificate', 'TrustedCertificate' or 'TrustedAll'.
<i>DN</i>	Specifies the Distinguished Name of the wallet object to be removed.

4.3.27.3 Examples

The following command removes all trusted certificates from `wallet1`, for Oracle Internet Directory instance `oid1`, in application server instance `inst1`. It is not necessary to provide a DN, so we pass null (denoted by `None`) for the DN parameter:

```
wls:/mydomain/serverConfig> removeWalletObject('inst1', 'oid1', 'oid','wallet1',
'password', 'TrustedAll',None)
```

The following command removes a certificate signing request indicated by DN `cn=www.acme.com` from `wallet1`, for Oracle Internet Directory instance `oid1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> removeWalletObject('inst1', 'oid1', 'oid','wallet1',
'password', 'CertificateRequest','cn=www.acme.com')
```

The following command removes a certificate indicated by DN `cn=www.acme.com` from `wallet1`, for Oracle Internet Directory instance `oid1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> removeWalletObject('inst1', 'oid1', 'oid','wallet1',
'password', 'Certificate','cn=www.acme.com')
```

The following command removes a trusted certificate indicated by DN `cn=www.acme.com` from `wallet1`, for Oracle Internet Directory instance `oid1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> removeWalletObject('inst1', 'oid1', 'oid', 'wallet1',
'password', 'TrustedCertificate', 'cn=www.acme.com')
```

4.4 Oracle Identity Federation Commands

Use the WLST commands listed in [Table 4-4](#) to view and manage configuration for Oracle Identity Federation.

Table 4-4 WLST Commands for Oracle Identity Federation

Use this command...	To...	Use with WLST...
addConfigListEntryInMap	Add a configuration list entry to a map.	Online
addConfigMapEntryInMap	Add a configuration map entry to a map.	Online
addConfigPropertyListEntry	Add a configuration property list entry.	Online
addConfigPropertyMapEntry	Add a configuration property map entry to the map.	Online
addCustomAuthnEngine	Add a custom authentication engine.	Online
addCustomSPEngine	Add a custom SP engine.	Online
addFederationListEntryInMap	Add a federations list entry to the map.	Online
addFederationMapEntryInMap	Add a federation map entry to the map.	Online
addFederationPropertyListEntry	Add a federation property list entry.	Online
addFederationPropertyMapEntry	Add a federation property map entry.	Online
deleteCustomAuthnEngine	Delete a custom authentication engine.	Online
deleteCustomSPEngine	Delete a custom SP engine.	Online
deleteProviderFederation	Delete a provider from the federation.	Online
deleteUserFederation	Delete a user from the federation.	Online
changeMessageStore	Change the message store to memory or RDBMS.	Online
changePeerProviderDescription	Change a peer provider's description.	Online
changeSessionStore	Change the session store to memory or RDBMS.	Online
createConfigPropertyList	Create a configuration property list.	Online
createConfigPropertyListInMap	Create a configuration property list in the map.	Online
createConfigPropertyMap	Create a configuration property map.	Online
createConfigPropertyMapInMap	Create a nested configuration property map in a map.	Online
createFederationPropertyList	Create a federation property list.	Online
createFederationPropertyListInMap	Create a federation property list in the map.	Online
createFederationPropertyMap	Create a federation property map.	Online

Table 4–4 (Cont.) WLST Commands for Oracle Identity Federation

Use this command...	To...	Use with WLST...
createFederationPropertyMapInMap	Create a nested federation property map in a map.	Online
createPeerProviderEntry	Create a peer provider entry.	Online
getConfigListValueInMap	Retrieve a configuration list value from the map.	Online
getConfigMapEntryInMap	Retrieve a configuration map value from the map.	Online
getConfigProperty	Retrieve a configuration property entry.	Online
getConfigPropertyList	Retrieve a configuration property list.	Online
getConfigPropertyMapEntry	Retrieve a configuration property map entry.	Online
getFederationListValueInMap	Retrieve a federation list value from the map.	Online
getFederationMapEntryInMap	Retrieve a federation map entry from a nested map.	Online
getFederationProperty	Retrieve a federation property.	Online
getFederationPropertyList	Retrieve the federation property list.	Online
extractproviderprops	Export all provider configuration properties to a text file.	Script
setproviderprops	Set a provider's properties based on an input text file.	Script
getFederationPropertyMapEntry	Retrieve a federation property map entry.	Online
listCustomAuthnEngines	Display the list of custom authentication engines.	Online
listCustomSPEngines	Display the list of custom SP engines.	Online
loadMetadata	Load metadata from a file.	Online
oifStatus	Display the current status of Oracle Identity Federation on the managed server.	Online
removeConfigListInMap	Delete a configuration list in the map.	Online
removeConfigMapEntryInMap	Delete a configuration map entry in the map.	Online
removeConfigMapInMap	Delete a nested configuration map.	Online
removeConfigProperty	Delete a configuration property.	Online
removeConfigPropertyList	Delete a property list.	Online
removeConfigPropertyMap	Delete a property map.	Online
removeConfigPropertyMapEntry	Delete an entry in the property map.	Online
removeFederationListInMap	Delete a federation list in the map.	Online
removeFederationMapInMap	Delete a nested federation map.	Online
removeFederationMapEntryInMap	Delete a nested federation map entry.	Online
removeFederationProperty	Delete a federation property.	Online
removeFederationPropertyList	Delete a federation property list.	Online

Table 4–4 (Cont.) WLST Commands for Oracle Identity Federation

Use this command...	To...	Use with WLST...
removeFederationPropertyMap	Delete a federation property map.	Online
removeFederationPropertyMapEntry	Delete a federation property map entry.	Online
removePeerProviderEntry	Delete a peer provider entry.	Online
setConfigProperty	Set a configuration property.	Online
setCustomAuthnEngine	Define a custom authentication engine.	Online
setCustomSPEngine	Define a custom SP engine.	Online
setFederationProperty	Set a federation property.	Online

For more information, see the *Oracle Fusion Middleware Administrator's Guide for Oracle Identity Federation*.

4.4.1 addConfigListEntryInMap

Online command that adds a property value to a map.

4.4.1.1 Description

This command adds a property value to a nested list inside a map in config.xml.

4.4.1.2 Syntax

```
addConfigListEntryInMap(configName, mapname, listName, value, type)
```

Argument	Definition
<i>configname</i>	Specifies the name of the configuration (for example, idpsaml20, serverconfig, spsaml20, ...) to be updated.
<i>mapname</i>	Specifies the name of the property to map to be changed in config.xml.
<i>listname</i>	Specifies the name of the list.
<i>value</i>	Specifies the property value.
<i>type</i>	Specifies the type of property, BOOLEAN or STRING or LONG.

4.4.1.3 Example

The following command adds `valueA` to a map list in server configuration:

```
wls:/mydomain/serverConfig>
addConfigListEntryInMap('serverconfig', 'mymap', 'mylistA', 'valueA', 'string')
```

4.4.2 addConfigMapEntryInMap

Online command that adds a nested map property entry in a map.

4.4.2.1 Description

This command that adds a property name/value pair to a map nested inside a map in config.xml.

4.4.2.2 Syntax

```
addConfigMapEntryInMap(configName, mapname, nestedMapName, propName, value, type)
```

Argument	Definition
<i>configName</i>	Specifies the name of the configuration (for example, idpsaml20, serverconfig, spsaml20, ...) to be updated.
<i>mapname</i>	Specifies the name of the property map to be changed in config.xml.
<i>nestedMapName</i>	name of the nested property map to be changed.
<i>propName</i>	Specifies the name of the list.
<i>value</i>	Specifies the property value.
<i>type</i>	Specifies the type of property, BOOLEAN or STRING or LONG.

4.4.2.3 Example

The following command adds a boolean name/value pair to `nestedmapB` inside the map `mymap`.

```
wls:/mydomain/serverConfig>
addConfigMapEntryInMap('serverconfig','mymap','nestedmapB','myvarB','true',
'boolean')
```

4.4.3 addConfigPropertyListEntry

Online command that adds a list property entry to config.xml.

4.4.3.1 Description

This command adds a property value to a list in config.xml.

4.4.3.2 Syntax

```
addConfigPropertyListEntry(configName, listName, value, type)
```

Argument	Definition
<i>configName</i>	Specifies the name of the configuration (for example, idpsaml20, serverconfig, spsaml20, ...) to be updated.
<i>listName</i>	Specifies the name of the property list to be added in config.xml.
<i>value</i>	Specifies the new property list value. The entered value is appended to the list.
<i>type</i>	Specifies the type of property, BOOLEAN or STRING or LONG.

4.4.3.3 Example

The following command adds a string value to `mylistA`.

```
wls:/mydomain/serverConfig>
addConfigPropertyListEntry('serverconfig','mylistA','valueA','string')
```

4.4.4 addConfigPropertyMapEntry

Online command that adds a property name/value entry in a map in config.xml.

4.4.4.1 Description

This command adds a property name/value entry in a map in config.xml.

4.4.4.2 Syntax

```
addConfigPropertyMapEntry(configName, mapName, propName, value, type)
```

Argument	Definition
<i>configname</i>	Specifies the name of the configuration (for example, idpsaml20, serverconfig, spsaml20, ...) to be updated.
<i>mapname</i>	Specifies the name of the property map in config.xml.
<i>propName</i>	Specifies the name of the property map.
<i>value</i>	Specifies the property map value to be added.
<i>type</i>	Specifies the type of property, BOOLEAN or STRING or LONG.

4.4.4.3 Example

The following command adds `valueA` of string type to a map.

```
wls:/mydomain/serverConfig>
addConfigPropertyMapEntry('serverconfig','mymapA','myvarA','valueA','string')
```

4.4.5 addCustomAuthnEngine

Online command that adds a custom authentication integration engine.

4.4.5.1 Description

This command adds a custom authentication integration engine to config.xml.

4.4.5.2 Syntax

```
addCustomAuthnEngine(name, [enabled], [webContext], [authnRelativePath],
[logoutRelativePath], [logoutEnabled])
```

Argument	Definition
<i>name</i>	Specifies the name of the custom engine.
<i>enabled</i>	This flag specifies whether the engine is enabled (true) or not (false, default).
<i>webContext</i>	Specifies the web context for the engine.
<i>authnRelativePath</i>	Specifies the authentication relative path URL for the engine.
<i>logoutRelativePath</i>	Specifies the logout relative path URL for the engine.
<i>logoutEnabled</i>	This flag is set true to enable logout for the engine, else false.

4.4.5.3 Example

The following command defines an engine named `test` and enables it.

```
wls:/mydomain/serverConfig> addCustomAuthnEngine('test','true')
```

4.4.6 addCustomSPEngine

Online command that adds a custom service provider (SP) engine.

4.4.6.1 Description

This command adds a custom SP integration engine to config.xml.

4.4.6.2 Syntax

```
addCustomSPEngine(name, [enabled, [authnMech], [webContext], [authnRelativePath],
[logoutRelativePath], [logoutEnabled])
```

Argument	Definition
<i>name</i>	Specifies the name of the custom engine.
<i>enabled</i>	This flag specifies whether the engine is enabled (true) or not (false).
<i>authnMech</i>	Specifies the authentication mechanism for the engine.
<i>webContext</i>	Specifies the web context for the engine.
<i>authnRelativePath</i>	Specifies the authentication relative path URL for the engine.
<i>logoutRelativePath</i>	Specifies the logout relative path URL for the engine.
<i>logoutEnabled</i>	This flag is set true to enable logout for the engine, else false.

4.4.6.3 Example

The following command adds an engine and gives it a disabled status.

```
addCustomSPEngine('new
engine','false','oracle:fed:authentication:unspecified','webcontext')
```

4.4.7 addFederationListEntryInMap

Online command that adds a list property entry in a map.

4.4.7.1 Description

This command adds a property value to a nested list inside a map in cot.xml.

4.4.7.2 Syntax

```
addFederationListEntryInMap(providerID, mapname, listName, value, type)
```

Argument	Definition
<i>providerID</i>	Specifies the provider ID.
<i>mapname</i>	Specifies the name of the property map to be changed in cot.xml.
<i>listName</i>	Specifies the name of the property list to be added to the map.
<i>value</i>	Specifies the property list value to be added. The entered value is appended to the list.
<i>type</i>	Specifies the type of property, BOOLEAN or STRING or LONG.

4.4.7.3 Example

The following command adds a boolean property list to mymap.

```
wls:/mydomain/serverConfig>
addFederationListEntryInMap('providerB','mymap','mylistB','true','boolean')
```

4.4.8 addFederationMapEntryInMap

Online command that adds a nested map property entry in a map.

4.4.8.1 Description

This command adds a property name/value pair to a map nested inside a map in cot.xml.

4.4.8.2 Syntax

```
addFederationMapEntryInMap(providerID, mapname, nestedMapName, propName, value, type)
```

Argument	Definition
<i>providerID</i>	Specifies the provider ID.
<i>mapname</i>	Specifies the name of the property map to be changed in cot.xml.
<i>nestedMapName</i>	Specifies the name of the nested property map to be changed.
<i>propName</i>	Specifies the name of the property to be updated in the map.
<i>value</i>	Specifies the property value to be added. The entered value is appended to the list.
<i>type</i>	Specifies the type of property, BOOLEAN or STRING or LONG.

4.4.8.3 Example

The following command adds a value of type string to the myvarA property in a nested map.

```
wls:/mydomain/serverConfig>
addFederationMapEntryInMap('providerA', 'mymap', 'nestedmapA', 'myvarA', 'valueA',
'string')
```

4.4.9 addFederationPropertyListEntry

Online command that adds a list property entry.

4.4.9.1 Description

This command adds a property value to a list in cot.xml.

4.4.9.2 Syntax

```
addFederationPropertyListEntry(providerID, listName, value, type)
```

Argument	Definition
<i>providerID</i>	Specifies the provider ID.
<i>listName</i>	Specifies the name of the property list to be updated.
<i>value</i>	Specifies the property list value to be added. The entered value is appended to the list.
<i>type</i>	Specifies the type of property, BOOLEAN or STRING or LONG.

4.4.9.3 Example

The following command adds a value in string format to a specified property list.


```
wls:/mydomain/serverConfig>
addFederationPropertyListEntry('providerA', 'mylistA', 'valueA', 'string')
```

4.4.10 addFederationPropertyMapEntry

Online command that a property name/value entry in a map.

4.4.10.1 Description

This command adds a property name/value pair to a map in cot.xml.

4.4.10.2 Syntax

```
addFederationPropertyMapEntry(providerID, mapName, propName, value, type)
```

Argument	Definition
<i>providerID</i>	Specifies the provider ID.
<i>mapName</i>	Specifies the name of the property map to be changed in cot.xml.
<i>propName</i>	Specifies the name of the property to be added in the map.
<i>value</i>	Specifies the property value to be added. The entered value is appended to the list.
<i>type</i>	Specifies the type of property, BOOLEAN or STRING or LONG.

4.4.10.3 Example

The following command adds boolean property `myvarB` to a map.

```
wls:/mydomain/serverConfig>
addFederationPropertyMapEntry('providerA', 'mymapB', 'myvarB', 'true', 'boolean')
```

4.4.11 deleteCustomAuthnEngine

Online command that deletes a custom authentication integration engine from the configuration.

4.4.11.1 Description

This command deletes a custom authentication integration engine in config.xml. You must provide the engine ID for an existing custom authentication engine in config.xml.

4.4.11.2 Syntax

```
deleteCustomAuthnEngine(engineID)
```

Argument	Definition
<i>engineID</i>	Specifies the engine ID of an existing engine to be deleted.

4.4.11.3 Example

The following command deletes the authentication engine with ID `id1234`.

```
wls:/mydomain/serverConfig> deleteCustomAuthnEngine('id1234')
```

4.4.12 deleteCustomSPEngine

Online command that deletes a custom service provider (SP) integration engine from the configuration.

4.4.12.1 Description

This command deletes a custom SP integration engine in config.xml. The EngineID for an existing custom SP engine in config.xml must be provided.

4.4.12.2 Syntax

```
ddeleteCustomSPEngine(engineID)
```

Argument	Definition
<i>engineID</i>	Specifies the engine ID of an existing engine to be deleted.

4.4.12.3 Example

The following command deletes the engine with ID id1234.

```
wls:/mydomain/serverConfig> deleteCustomSPEngine('id1234')
```

4.4.13 deleteProviderFederation

Online command that deletes federations for given provider.

4.4.13.1 Description

This command deletes federations for given provider ID.

4.4.13.2 Syntax

```
deleteProviderFederation(providerID)
```

Argument	Definition
<i>providerID</i>	Specifies the ProviderID for the peer provider for which federation is to be deleted.

4.4.13.3 Example

The following command deletes providerA:

```
wls:/mydomain/serverConfig> deleteProviderFederation(providerA)
```

4.4.14 deleteUserFederation

Online command that deletes federations for given users.

4.4.14.1 Description

This command deletes federations for the given list of users.

4.4.14.2 Syntax

```
deleteUserFederation([user1, ...])
```

Argument	Definition
<i>user1</i>	Specifies a comma-separated list of users whose federations are to be deleted. At least one user must be specified.

4.4.14.3 Example

The following command deletes federations for three users:

```
wls:/mydomain/serverConfig> deleteUserFederation(['userA', 'userB', 'userC'])
```

4.4.15 changeMessageStore

Online command that changes the message store between memory and RDBMS.

4.4.15.1 Description

This command changes the message store to memory or RDBMS.

4.4.15.2 Syntax

```
changeMessageStore(type, [jndiname])
```

Argument	Definition
<i>type</i>	Specifies the type of store, RDBMS or Memory. Default is Memory.
<i>jndiname</i>	Specifies the jndi name to set for the store. Required if type is RDBMS.

4.4.15.3 Example

The following command changes the message store to RDBMS:

```
wls:/mydomain/serverConfig> changeMessageStore('RDBMS', 'jdbc/mydb')
```

4.4.16 changePeerProviderDescription

Online command that changes the peer provider description.

4.4.16.1 Description

This command updates a peer provider description in cot.xml.

4.4.16.2 Syntax

```
changePeerProviderDescription(providerID, description)
```

Argument	Definition
<i>providerID</i>	Specifies the provider ID.
<i>description</i>	Specifies the provider description.

4.4.16.3 Example

The following command updates the description of a provider:

```
wls:/mydomain/serverConfig> changePeerProviderDescription('providerA', 'new description')
```

4.4.17 changeSessionStore

Online command that changes the session store between memory and RDBMS.

4.4.17.1 Description

This command changes the session store to memory or RDBMS.

4.4.17.2 Syntax

```
changeSessionStore(type, [jndiname])
```

Argument	Definition
<i>type</i>	Specifies the type of store, RDBMS or Memory. Default is Memory.
<i>jndiname</i>	Specifies the jndi name to set for the store. Required if type is RDBMS.

4.4.17.3 Example

The following command changes the session store to RDBMS.

```
wls:/mydomain/serverConfig> changeSessionStore('RDBMS','jdbc/mydb')
```

4.4.18 createConfigPropertyList

Online command that creates a property list.

4.4.18.1 Description

This command creates a property list in config.xml.

4.4.18.2 Syntax

```
createConfigPropertyList(configName, listName)
```

Argument	Definition
<i>configName</i>	Specifies the name of the configuration (for example, idpsaml20, serverconfig, spsaml20, ...) to be updated.
<i>listName</i>	Specifies the property list name.

4.4.18.3 Example

The following command creates property list mylistA.

```
wls:/mydomain/serverConfig> createConfigPropertyList('serverconfig','mylistA')
```

4.4.19 createConfigPropertyListInMap

Online command that creates a property list nested in the property map.

4.4.19.1 Description

This command creates a property list, nested in the property map, in config.xml.

4.4.19.2 Syntax

```
createConfigPropertyListInMap(configName, mapName, listName)
```

Argument	Definition
<i>configName</i>	Specifies the name of the configuration (for example, idpsaml20, serverconfig, spsaml20, ...) to be updated.
<i>mapName</i>	Specifies an existing property map to contain the nested list.
<i>listName</i>	Specifies the property list name.

4.4.19.3 Example

The following command creates property list `mylistA` nested in a property map.

```
wls:/mydomain/serverConfig>
createConfigPropertyListInMap('serverconfig','mymapA','mylistA')
```

4.4.20 createConfigPropertyMap

Online command that creates a property map.

4.4.20.1 Description

This command that creates a property map in `config.xml`.

4.4.20.2 Syntax

```
createConfigPropertyMap(configName, mapName)
```

Argument	Definition
<i>configName</i>	Specifies the name of the configuration (for example, idpsaml20, serverconfig, spsaml20, ...) to be updated.
<i>mapName</i>	Specifies the property map to create.

4.4.20.3 Example

The following command creates property map `mymapA`:

```
wls:/mydomain/serverConfig> createConfigPropertyMap('serverconfig','mymapA')
```

4.4.21 createConfigPropertyMapInMap

Online command that creates a property map.

4.4.21.1 Description

This command that creates a property map in `config.xml`.

4.4.21.2 Syntax

```
createConfigPropertyMapInMap(configName, mapName, nestedMapName)
```

Argument	Definition
<i>configName</i>	Specifies the name of the configuration (for example, idpsaml20, serverconfig, spsaml20, ...) to be updated.
<i>mapName</i>	Specifies the name of an existing property map.
<i>nestedMapName</i>	Specifies the name of the property map to create nested inside <code>mapName</code> .

4.4.21.3 Example

The following command creates nested property map `nestedmymapA`:

```
wls:/mydomain/serverConfig>
createConfigPropertyMapInMap('serverconfig','mymapA','nestedmapA')
```

4.4.22 createFederationPropertyList

Online command that creates a property list.

4.4.22.1 Description

This command creates a property list in `cot.xml`.

4.4.22.2 Syntax

```
createFederationPropertyList(providerID, listName)
```

Argument	Definition
<i>providerID</i>	Specifies the provider ID.
<i>listName</i>	Specifies the name of the property list.

4.4.22.3 Example

The following command creates property list `mylistA`:

```
wls:/mydomain/serverConfig> createFederationPropertyList('providerA','mylistA')
```

4.4.23 createFederationPropertyListInMap

Online command that creates a property list nested in a property map.

4.4.23.1 Description

This command creates a property list, nested in a property map, in `cot.xml`.

4.4.23.2 Syntax

```
createFederationPropertyListInMap(providerID, mapName, listName)
```

Argument	Definition
<i>providerID</i>	Specifies the provider ID.
<i>mapName</i>	Specifies an existing property map to contain the nested list.
<i>listName</i>	Specifies the name of the property list.

4.4.23.3 Example

The following command creates nested property list `mylistA`:

```
wls:/mydomain/serverConfig>
createFederationPropertyListInMap('providerA','mymapA','mylistA')
```

4.4.24 createFederationPropertyMap

Online command that creates a property map.

4.4.24.1 Description

This command that creates a property map in cot.xml.

4.4.24.2 Syntax

```
createFederationPropertyMap(providerID, mapName)
```

Argument	Definition
<i>providerID</i>	Specifies the provider ID.
<i>mapName</i>	Specifies the name of the property map to be added to cot.xml.

4.4.24.3 Example

The following command creates property map mymapA:

```
wls:/mydomain/serverConfig> createFederationPropertyMap('providerA','mymapA')
```

4.4.25 createFederationPropertyMapInMap

Online command that creates a nested property map.

4.4.25.1 Description

This command that creates a property map, nested in another property map, in cot.xml.

4.4.25.2 Syntax

```
createFederationPropertyMapInMap(providerID, mapName, nestedMapName)
```

Argument	Definition
<i>providerID</i>	Specifies the provider ID.
<i>mapName</i>	Specifies the name of an existing property map.
<i>nestedMapName</i>	Specifies the name of the property map to be nested inside mapName in cot.xml.

4.4.25.3 Example

The following command creates nested property map nestedmapA:

```
wls:/mydomain/serverConfig>
createFederationPropertyMapInMap('providerA','mymapA','nestedmapA')
```

4.4.26 createPeerProviderEntry

Online command that creates a peer provider property map entry.

4.4.26.1 Description

This command creates a peer provider as a Map property entry to cot.xml.

4.4.26.2 Syntax

```
createPeerProviderEntry(providerID, description, providerType, version)
```

Argument	Definition
<i>providerID</i>	Specifies the provider ID to be created.
<i>description</i>	This is the description of the provider ID.
<i>providerType</i>	Specifies the provider type of the peer provider to be created.
<i>version</i>	Specifies the version of the peer provider to be created.

4.4.26.3 Example

The following command creates a SAML 2.0 service provider:

```
wls:/mydomain/serverConfig> createPeerProviderEntry('providerA','idp
test','SP','SAML2.0')
```

4.4.27 getConfigListValueInMap

Online command that returns a list nested in a map.

4.4.27.1 Description

This command returns a list, nested in a map, from config.xml.

4.4.27.2 Syntax

```
getConfigListValueInMap(configName, mapName, listName)
```

Argument	Definition
<i>configName</i>	Specifies the name of the configuration (for example, idpsaml20, serverconfig, spsaml20, ...) to be accessed.
<i>mapName</i>	Specifies the name of the property map.
<i>listName</i>	Specifies the name of the list to be fetched from the map.

4.4.27.3 Example

The following command returns mylistA:

```
wls:/mydomain/serverConfig>
getConfigListValueInMap('serverConfig','mymapA','mylistA')
```

4.4.28 getConfigMapEntryInMap

Online command that returns a map property entry nested in a map.

4.4.28.1 Description

This command returns a map property entry, nested in a map, from config.xml.

4.4.28.2 Syntax

```
getConfigMapEntryInMap(configName, mapname, nestedMapName, propName)
```

Argument	Definition
<i>configName</i>	Specifies the name of the configuration (for example, idpsaml20, serverconfig, spsaml20, ...) to be accessed.
<i>mapname</i>	Specifies the name of the property map.

Argument	Definition
<i>nestedMapName</i>	Specifies the name of the nested property map.
<i>propName</i>	Specifies the name of the property to be fetched from the nested map.

4.4.28.3 Example

The following command returns property entry myvarA:

```
wls:/mydomain/serverConfig>
getConfigMapEntryInMap('serverconfig','mymap','nestedmapA','myvarA')
```

4.4.29 getConfigProperty

Online command that returns a property value.

4.4.29.1 Description

This command returns a property value from config.xml.

4.4.29.2 Syntax

```
getConfigProperty(configName, propName)
```

Argument	Definition
<i>configName</i>	Specifies the name of the configuration (for example, idpsaml20, serverconfig, spsaml20, ...) to be accessed.
<i>propName</i>	Specifies the name of the property to be fetched from the nested map.

4.4.29.3 Example

The following command returns property myvarA:

```
wls:/mydomain/serverConfig> getConfigProperty('serverconfig','myvarA')
```

4.4.30 getConfigPropertyList

Online command that returns a property list.

4.4.30.1 Description

This command returns a property list from config.xml.

4.4.30.2 Syntax

```
getConfigPropertyList(configName, listName)
```

Argument	Definition
<i>configName</i>	Specifies the configuration name.
<i>listName</i>	Specifies the name of the property list to be fetched from config.xml.

4.4.30.3 Example

The following command returns mylistA:

```
wls:/mydomain/serverConfig> getConfigPropertyList('serverconfig','mylistA')
```

4.4.31 getConfigPropertyMapEntry

Online command that returns a property value from a map.

4.4.31.1 Description

This command returns a property value from a map in config.xml.

4.4.31.2 Syntax

```
getConfigPropertyMapEntry(configName, mapName, propName)
```

Argument	Definition
<i>configName</i>	Specifies the configuration name (for example, idpsaml20, serverconfig, spsaml20, ...).
<i>mapName</i>	Specifies the name of the property map.
<i>propName</i>	Specifies the name of the property to be fetched from the map in config.xml.

4.4.31.3 Example

The following command returns property propA:

```
wls:/mydomain/serverConfig> getConfigPropertyMapEntry('serverconfig','mapA',
'propA')
```

4.4.32 getFederationListValueInMap

Online command that returns a list value nested in a map.

4.4.32.1 Description

This command returns a list value nested in a map from cot.xml.

4.4.32.2 Syntax

```
getFederationListValueInMap(providerID, mapName, listName)
```

Argument	Definition
<i>providerID</i>	Specifies the name of the peer provider to be accessed.
<i>mapName</i>	Specifies the name of the property map.
<i>listName</i>	Specifies the name of the list to be fetched from the map.

4.4.32.3 Example

The following command returns nested list myListA:

```
wls:/mydomain/serverConfig>
getFederationListValueInMap('providerA','mymapA','mylistA')
```

4.4.33 getFederationMapEntryInMap

Online command that returns a map property entry nested in a map.

4.4.33.1 Description

This command returns a map property entry, nested in a map, from cot.xml.

4.4.33.2 Syntax

```
getFederationMapEntryInMap(providerID, mapname, nestedMapName, propName)
```

Argument	Definition
<i>providerID</i>	Specifies the name of the peer provider to be accessed.
<i>mapName</i>	Specifies the name of the property map.
<i>nestedMapName</i>	Specifies the name of the nested property map.
<i>propName</i>	Specifies the name of the property to be fetched from the nested map.

4.4.33.3 Example

The following command returns property entry `myvarA`:

```
wls:/mydomain/serverConfig>
getFederationMapEntryInMap('providerA', 'mymap', 'nestedmapA', 'myvarA')
```

4.4.34 getFederationProperty

Online command that returns a property value.

4.4.34.1 Description

This command returns a property value from `cot.xml`.

4.4.34.2 Syntax

```
getFederationProperty(providerID, propName)
```

Argument	Definition
<i>providerID</i>	Specifies the name of the peer provider to be accessed.
<i>propName</i>	Specifies the name of the property to be fetched from <code>cot.xml</code> .

4.4.34.3 Example

The following command returns property `myvarA`:

```
wls:/mydomain/serverConfig> getFederationProperty('providerA', 'myvarA')
```

4.4.35 getFederationPropertyList

Online command that returns a property list.

4.4.35.1 Description

This command returns a property list from `cot.xml`.

4.4.35.2 Syntax

```
getFederationPropertyList(providerID, listName)
```

Argument	Definition
<i>providerID</i>	Specifies the name of the peer provider to be accessed.
<i>listName</i>	Specifies the name of the list to be fetched from the map.

4.4.35.3 Example

The following command returns list mylistA:

```
wls:/mydomain/serverConfig> getFederationPropertyList('providerA','mylistA')
```

4.4.36 extractproviderprops

A WLST script that exports the properties of a provider.

4.4.36.1 Description

A WLST script that extracts all the configuration properties of the specified provider and exports them to a text file. You can later use this file to set the same properties on another provider. Execute this command from a UNIX or Windows command shell prompt and not from the WLST command shell. This script is stored in `ORACLE_HOME/fed/scripts`.

4.4.36.2 Syntax

```
extractproviderprops.py providerID filename
```

Argument	Definition
<i>providerID</i>	Specifies the name of the provider whose properties are to be extracted.
<i>filename</i>	Specifies the name of the text file to which the provider properties are extracted.

When you execute the script, you are prompted for the WebLogic administrator credentials and the connection URL; for the latter, specify the Managed Server port, not the Administration Server port.

File Format

The format of the extract file is:

```
TYPE:NAME:PROPNAME:PROPVALUE:PROPTYPE
```

For example:

```
X:X:sendattribute:false:boolean
MAP:attributelist/mailemail:datastore-attr:mail:string
LIST:sendattributefornameid:unspecified::string
```

4.4.37 setproviderprops

A WLST script that sets the properties of a provider using values from a text file.

4.4.37.1 Description

A WLST script that sets the properties of a provider using values from a text file. Execute this command from a UNIX or Windows command shell prompt and not from the WLST command shell. This script is stored in `ORACLE_HOME/fed/scripts`.

The text file is generated by the [extractproviderprops](#) command.

4.4.37.2 Syntax

```
setproviderprops.py providerID filename
```

Argument	Definition
<i>providerID</i>	Specifies the name of the provider whose properties are to be updated.
<i>filename</i>	Specifies the name of the input file from which to read the properties.

When you execute the script, you are prompted for the WebLogic administrator credentials and the connection URL; for the latter, specify the Managed Server port, not the Administration Server port.

4.4.38 getFederationPropertyMapEntry

Online command that returns a property value from a map.

4.4.38.1 Description

This command returns a property value from a map in cot.xml.

4.4.38.2 Syntax

```
getFederationPropertyMapEntry(providerID, mapName, propName)
```

Argument	Definition
<i>providerID</i>	Specifies the name of the peer provider to be accessed.
<i>mapName</i>	Specifies the name of the property map.
<i>propName</i>	Specifies the name of the property to be fetched from the nested map.

4.4.38.3 Example

The following command returns property `propA` from a map:

```
wls:/mydomain/serverConfig> getFederationPropertyMapEntry('providerA', 'mapA',
'propA')
```

4.4.39 listCustomAuthnEngines

Online command that returns a list of custom authentication integration engines.

4.4.39.1 Description

This command returns a list of custom authentication integration engines from `config.xml`.

4.4.39.2 Syntax

```
listCustomAuthnEngines()
```

4.4.39.3 Example

The following command returns the list of all SP engines:

```
wls:/mydomain/serverConfig> listCustomAuthnEngines()
```

4.4.40 listCustomSPEngines

Online command that returns a list of custom SP integration engines.

4.4.40.1 Description

This command returns a list of custom service provider (SP) integration engines from `config.xml`.

4.4.40.2 Syntax

```
listCustomSPEngines()
```

4.4.40.3 Example

The following command returns the list of all SP integration engines:

```
wls:/mydomain/serverConfig> listCustomSPEngines()
```

4.4.41 loadMetadata

Online command that loads metadata from an input file.

4.4.41.1 Description

This command loads metadata from an input file into `cot.xml`.

4.4.41.2 Syntax

```
loadMetadata(metadataFile,description)
```

Argument	Definition
<i>metadataFile</i>	Specifies the metadata file of the peer provider to be added or updated.
<i>description</i>	This is a brief description of the peer provider to be loaded.

4.4.41.3 Example

The following command loads metadata from the file `metadataFile.xml`:

```
wls:/mydomain/serverConfig> loadMetadata('/home/metadataFile.xml','some description')
```

4.4.42 oifStatus

Online command that reports the current status of the Oracle Identity Federation application in the managed server to which WLST is connected.

4.4.42.1 Description

This command displays the current status of Oracle Identity Federation on the managed server.

4.4.42.2 Syntax

```
loifStatus('serverurl', 'configfile', 'keyfile')
```

Argument	Definition
<i>serverurl</i>	Specifies the URL of the managed server.
<i>configfile</i>	This is a pre-defined user configuration file created with the WLST <code>storeUserConfig</code> command.

Argument	Definition
<i>keyfile</i>	This is a pre-defined key file created with the WLST storeUserConfig command

4.4.42.3 Example

The following command provides no arguments; WLST prompts you for the Oracle WebLogic Server username, password, and the managed server URL, then displays the federation server status:

```
wls:/mydomain/serverConfig> oifStatus()
```

The following command provides only the managed server URL; WLST prompts you for the Oracle WebLogic Server username and password:

```
wls:/mydomain/serverConfig> oifStatus('', '', 't3://localhost:7499')
```

The following command provides all arguments needed for WLST to display the federation server status:

```
wls:/mydomain/serverConfig> oifStatus('configfileA', 'keyfileB',
't3://localhost:7499')
```

4.4.43 removeConfigListInMap

Online command that removes a list property nested in a map.

4.4.43.1 Description

This command removes a list property nested in a map from config.xml.

4.4.43.2 Syntax

```
removeConfigListInMap(configName, mapName, listName)
```

Argument	Definition
<i>configName</i>	Specifies the name of the configuration (for example, idpsaml20, serverconfig, spsaml20, ...) to be accessed.
<i>mapName</i>	Specifies the name of the property map.
<i>listName</i>	Specifies the name of the list to be removed from the map.

4.4.43.3 Example

The following command removes the list property mylistA:

```
wls:/mydomain/serverConfig>
removeConfigListInMap('serverConfig', 'mymapA', 'mylistA')
```

4.4.44 removeConfigMapEntryInMap

Online command that removes a map property nested in a map.

4.4.44.1 Description

This command removes a map property entry nested in a map from config.xml.

4.4.44.2 Syntax

```
removeConfigMapEntryInMap(configName, mapname, nestedMapName, propName)
```

Argument	Definition
<i>configName</i>	Specifies the name of the configuration (for example, idpsaml20, serverconfig, spsaml20, ...) to be accessed.
<i>mapName</i>	Specifies the name of the property map.
<i>nestedMapName</i>	Specifies the name of the nested property map.
<i>propName</i>	Specifies the name of the property to be removed from the nested map.

4.4.44.3 Example

The following command removes the nested property myvarA:

```
wls:/mydomain/serverConfig>
removeConfigMapEntryInMap('serverconfig','mymap','nestedmapA','myvarA')
```

4.4.45 removeConfigMapInMap

Online command that removes a map property nested in a map.

4.4.45.1 Description

This command removes a map property entry nested in a map from config.xml.

4.4.45.2 Syntax

```
removeConfigMapEntryInMap(configName, mapName, nestedMapName, propName)
```

Argument	Definition
<i>configName</i>	Specifies the name of the configuration (for example, idpsaml20, serverconfig, spsaml20, ...) to be updated.
<i>mapName</i>	Specifies the name of the property map.
<i>nestedMapName</i>	Specifies the name of the nested property map.
<i>propName</i>	Specifies the name of the property to be removed from the nested map.

4.4.45.3 Example

The following command removes the nested property myvarA:

```
wls:/mydomain/serverConfig>
removeConfigMapEntryInMap('serverconfig','mymap','nestedmapA','myvarA')
```

4.4.46 removeConfigProperty

Online command that removes a configuration property.

4.4.46.1 Description

This command removes a property from config.xml.

4.4.46.2 Syntax

```
removeConfigProperty(configName, propName)
```


Argument	Definition
<i>configName</i>	Specifies the name of the configuration (for example, idpsaml20, serverconfig, spsaml20, ...) to be updated.
<i>propName</i>	Specifies the name of the property to be removed.

4.4.46.3 Example

The following command removes the property myvarA:

```
wls:/mydomain/serverConfig> removeConfigProperty('serverconfig','myvarA')
```

4.4.47 removeConfigPropertyList

Online command that removes a configuration property list.

4.4.47.1 Description

This command removes a property list from config.xml.

4.4.47.2 Syntax

```
removeConfigPropertyList(configName, listName)
```

Argument	Definition
<i>configName</i>	Specifies the name of the configuration (for example, idpsaml20, serverconfig, spsaml20, ...) to be updated.
<i>listName</i>	Specifies the name of the property list to be removed.

4.4.47.3 Example

The following command removes the property list mylistA:

```
wls:/mydomain/serverConfig> removeConfigPropertyList('serverconfig','mylistA')
```

4.4.48 removeConfigPropertyMap

Online command that removes a property map.

4.4.48.1 Description

This command removes a property map in config.xml.

4.4.48.2 Syntax

```
removeConfigPropertyMap(configName, mapName)
```

Argument	Definition
<i>configName</i>	Specifies the name of the configuration (for example, idpsaml20, serverconfig, spsaml20, ...) to be updated.
<i>mapName</i>	Specifies the name of the property map to be removed.

4.4.48.3 Example

The following command removes mapA:

```
wls:/mydomain/serverConfig> removeConfigPropertyMap('serverconfig','mapA')
```

4.4.49 removeConfigPropertyMapEntry

Online command that removes a property value from a map.

4.4.49.1 Description

This command removes a property value from a map in config.xml.

4.4.49.2 Syntax

```
removeConfigPropertyMapEntry(configName, mapName, propName)
```

Argument	Definition
<i>configName</i>	Specifies the name of the configuration (for example, idpsaml20, serverconfig, spsaml20, ...) to be updated.
<i>mapName</i>	Specifies the name of the property map to be updated.
<i>propName</i>	Specifies the name of the property to be removed from the map.

4.4.49.3 Example

The following command removes property propA:

```
wls:/mydomain/serverConfig> removeConfigPropertyMapEntry('serverconfig', 'mapA', 'propA')
```

4.4.50 removeFederationListInMap

Online command that removes a property list in a map.

4.4.50.1 Description

This command removes a property list in a map, in cot.xml.

4.4.50.2 Syntax

```
removeFederationListInMap(providerID, mapName, listName)
```

Argument	Definition
<i>providerID</i>	Specifies the name of the peer provider to be accessed.
<i>mapName</i>	Specifies the name of the property map.
<i>listName</i>	Specifies the name of the property list to be removed.

4.4.50.3 Example

The following command removes mylistA in mymapA:

```
wls:/mydomain/serverConfig> removeFederationListInMap('providerA', 'mymapA', 'mylistA')
```

4.4.51 removeFederationMapInMap

Online command that removes a nested map in a map.

4.4.51.1 Description

This command removes a property map nested inside a map in cot.xml.

4.4.51.2 Syntax

```
removeFederationMapInMap(providerID, mapname, nestedMapName)
```

Argument	Definition
<i>providerID</i>	Specifies the name of the peer provider to be accessed.
<i>mapName</i>	Specifies the name of the property map containing the nested map.
<i>nestedMapName</i>	Specifies the name of the nested property map to be removed.

4.4.51.3 Example

The following command removes `nestedmapA` in `mymap`:

```
wls:/mydomain/serverConfig>
removeFederationMapInMap('providerA','mymap','nestedmapA')
```

4.4.52 removeFederationMapEntryInMap

Online command that removes a nested map property entry in a map.

4.4.52.1 Description

This command removes a property name/value pair to a map nested inside a map in `cot.xml`.

4.4.52.2 Syntax

```
removeFederationMapEntryInMap(providerID, mapname, nestedMapName, propName)
```

Argument	Definition
<i>providerID</i>	Specifies the name of the peer provider to be accessed.
<i>mapName</i>	Specifies the name of the property map containing the nested map.
<i>nestedMapName</i>	Specifies the name of the nested property map.
<i>propName</i>	Specifies the name of the property to be removed from the nested map.

4.4.52.3 Example

The following command removes map property entry `myvarA`:

```
wls:/mydomain/serverConfig>
removeFederationMapEntryInMap('providerA','mymap','nestedmapA','myvarA')
```

4.4.53 removeFederationProperty

Online command that removes a property value.

4.4.53.1 Description

This command removes a property entry in `cot.xml`.

4.4.53.2 Syntax

```
removeFederationProperty(providerID, propName)
```

Argument	Definition
<i>providerID</i>	Specifies the name of the peer provider to be updated.
<i>propName</i>	Specifies the name of the property to be removed.

4.4.53.3 Example

The following command removes the provider property myvarA:

```
wls:/mydomain/serverConfig> removeFederationProperty('providerA','myvarA')
```

4.4.54 removeFederationPropertyList

Online command that removes a property list entry.

4.4.54.1 Description

This command removes a property list entry in cot.xml.

4.4.54.2 Syntax

```
removeFederationPropertyList(providerID, listName)
```

Argument	Definition
<i>providerID</i>	Specifies the name of the peer provider to be accessed.
<i>listName</i>	Specifies the name of the property list to be removed.

4.4.54.3 Example

The following command removes mylistA:

```
wls:/mydomain/serverConfig> removeFederationPropertyList('providerA','mylistA')
```

4.4.55 removeFederationPropertyMap

Online command that removes a property map.

4.4.55.1 Description

This command removes a property map in cot.xml.

4.4.55.2 Syntax

```
removeFederationPropertyMap(providerID, mapName)
```

Argument	Definition
<i>providerID</i>	Specifies the name of the peer provider to be accessed.
<i>mapName</i>	Specifies the name of the property map to be removed.

4.4.55.3 Example

The following command removes a map:

```
wls:/mydomain/serverConfig> removeFederationPropertyMap('providerA','mapA')
```

4.4.56 removeFederationPropertyMapEntry

Online command that removes a property value from a map.

4.4.56.1 Description

This command removes a property value from a map in cot.xml.

4.4.56.2 Syntax

```
removeFederationPropertyMapEntry(providerID, mapName, propName)
```

Argument	Definition
<i>providerID</i>	Specifies the name of the peer provider to be accessed.
<i>mapName</i>	Specifies the name of the property map to be updated.
<i>propName</i>	Specifies the name of the property to be removed from the map.

4.4.56.3 Example

The following command removes property `propA` from a map:

```
wls:/mydomain/serverConfig> removeFederationPropertyMapEntry('providerA', 'mapA', 'propA')
```

4.4.57 removePeerProviderEntry

Online command that removes a peer provider entry.

4.4.57.1 Description

This command removes a peer provider entry from cot.xml.

4.4.57.2 Syntax

```
removePeerProviderEntry(providerID)
```

Argument	Definition
<i>providerID</i>	Specifies the name of the peer provider to be removed.

4.4.57.3 Example

The following command removes `providerA`:

```
wls:/mydomain/serverConfig> removePeerProviderEntry('providerA')
```

4.4.58 setConfigProperty

Online command that sets a property value in config.xml.

4.4.58.1 Description

This command adds or updates a property value in config.xml.

4.4.58.2 Syntax

```
setConfigProperty(configname, propName, value, type)
```

Argument	Definition
<i>configName</i>	Specifies the name of the configuration (for example, idpsaml20, serverconfig, spsaml20, ...) to be updated.
<i>propName</i>	Specifies the name of the property to be added/updated in config.xml.
<i>value</i>	Specifies the property value.
<i>type</i>	Specifies the type of property, BOOLEAN or STRING or LONG.

4.4.58.3 Example

The following command sets the property `myvarA` and its value in the server configuration:

```
wls:/mydomain/serverConfig>
setConfigProperty('serverconfig','myvarA','myvalA','string')
```

4.4.59 setCustomAuthnEngine

Online command that updates a custom authentication integration engine.

4.4.59.1 Description

This command updates a custom authentication integration engine in config.xml.

4.4.59.2 Syntax

```
setCustomAuthnEngine(engineID, name, [enabled], [webContext], [authnRelativePath],
[logoutRelativePath], [logoutEnabled])
```

Argument	Definition
<i>engineID</i>	Specifies the engine ID of an existing engine.
<i>name</i>	Specifies the name of the custom engine.
<i>enabled</i>	This flag specifies whether the engine is enabled (true) or not (false).
<i>webContext</i>	Specifies the web context for the engine.
<i>authnRelativePath</i>	Specifies the authentication relative path URL for the engine.
<i>logoutRelativePath</i>	Specifies the logout relative path URL for the engine.
<i>logoutEnabled</i>	This flag is set true to enable logout for the engine, else false.

4.4.59.3 Example

The following command updates the configuration of custom authentication engine `abcdef`:

```
wls:/mydomain/serverConfig> setCustomAuthnEngine('abcdef',
'custom one','false','oracle:fed:authentication:unspecified','webcontext')
```

4.4.60 setCustomSPEngine

Online command that updates a custom SP integration engine.

4.4.60.1 Description

This command updates an existing custom SP integration engine in config.xml.

4.4.60.2 Syntax

```
setCustomSPEngine(engineID, name, [enabled, [authnMech], [webContext],
[authnRelativePath], [logoutRelativePath], [logoutEnabled])
```

Argument	Definition
<i>engineID</i>	Specifies the engine ID of an existing custom engine.
<i>name</i>	Specifies the name of the custom engine.
<i>enabled</i>	This flag specifies whether the engine is enabled (true) or not (false).
<i>authnMech</i>	Specifies the authentication mechanism for the engine.
<i>webContext</i>	Specifies the web context for the engine.
<i>authnRelativePath</i>	Specifies the authentication relative path URL for the engine.
<i>logoutRelativePath</i>	Specifies the logout relative path URL for the engine.
<i>logoutEnabled</i>	This flag is set true to enable logout for the engine, else false.

4.4.60.3 Example

The following command sets the name and the enabled flag for the engine with ID `engineID2`:

```
wls:/mydomain/serverConfig> setCustomSPEngine('engineid2','test','true')
```

4.4.61 setFederationProperty

Online command that adds or updates a property value.

4.4.61.1 Description

This command adds a property entry or updates an existing entry in `cot.xml`.

4.4.61.2 Syntax

```
setFederationProperty(providerID, propName, value, type)
```

Argument	Definition
<i>providerID</i>	Specifies the name of the peer provider to be updated.
<i>propName</i>	Specifies the name of the property to be added/updated in <code>cot.xml</code> .
<i>value</i>	Specifies the property value.
<i>type</i>	Specifies the type of property, BOOLEAN or STRING or LONG.

4.4.61.3 Example

The following command creates the property `myvarA` and sets its value:

```
wls:/mydomain/serverConfig>
setFederationProperty('providerA','myvarA','myvalA','string')
```

4.5 Directory Integration Platform Commands

Some of the Directory Integration Platform (DIP) tools use WLST internally, and therefore, there are no custom WLST commands available to run from the WLST command prompt or to use within scripts. For information on DIP tools, see "Oracle

Directory Integration Platform Tools" in the *Oracle Fusion Middleware Reference for Oracle Identity Management*.

4.6 Security Commands

Use the WLST security commands listed in [Table 4–5](#) to operate on a domain policy or credential store, to migrate policies and credentials from a source repository to a target repository, and to import and export (credential) encryption keys.

Table 4–5 WLST Security Commands

Use this command...	To...	Use with WLST...
listSecurityStoreInfo	List the type and location of the OPSS security store, and the user allowed to access it.	Offline
listAppStripes	List application stripes in policy store.	Online
listCodeSourcePermissions	List permissions assigned to a source code in global policies.	Online
createAppRole	Create a new application role.	Online
deleteAppRole	Remove an application role.	Online
grantAppRole	Add a principal to a role.	Online
revokeAppRole	Remove a principal from a role.	Online
listAppRoles	List all roles in an application.	Online
listAppRolesMembers	List all members in an application role.	Online
grantPermission	Create a new permission.	Online
revokePermission	Remove a permission.	Online
listPermissions	List all permissions granted to a principal.	Online
deleteAppPolicies	Remove all policies in an application.	Online
migrateSecurityStore	Migrate policies or credentials from a source repository to a target repository.	Offline
updateCred	Modify the attribute values of a credential.	Online
createCred	Create a new credential.	Online
deleteCred	Remove a credential.	Online
modifyBootstrapCredential	Update bootstrap credential store	Offline
addBootstrapCredential	Add a credential to the bootstrap credential store.	Offline
exportEncryptionKey	Export the domain encryption key to the file <code>ewallet.p12</code> .	Offline
importEncryptionKey	Import the encryption key in file <code>ewallet.p12</code> to the domain.	Offline
restoreEncryptionKey	Restore the domain encryption key as it was before the last importing.	Offline
rollOverEncryptionKey	Create a new credential store encryption key.	Offline
reassociateSecurityStore	Reassociate policies and credentials to an LDAP repository	Online
upgradeSecurityStore	Upgrade security data from data used with release 10.1.x to data used with release 11.	Offline

Table 4–5 (Cont.) WLST Security Commands

Use this command...	To...	Use with WLST...
createResourceType	Create a new resource type.	Online
getResourceType	Fetch an existing resource type.	Online
deleteResourceType	Remove an existing resource type.	Online
createResource	Create a resource.	Online
deleteResource	Remove a resource.	Online
listResources	List resources in an application stripe.	Online
listResourceActions	List actions in a resource.	Online
createEntitlement	Create an entitlement.	Online
getEntitlement	List an entitlement.	Online
deleteEntitlement	Remove an entitlement.	Online
addResourceToEntitlement	Add a resource to an entitlement.	Online
revokeResourceFromEntitlement	Remove a resource from an entitlement	Online
listEntitlements	List entitlements in an application stripe.	Online
grantEntitlement	Create an entitlement.	Online
revokeEntitlement	Remove an entitlement.	Online
listResourceTypes	List resource types in an application stripe.	Online
updateTrustServiceConfig	Update the trust store configuration.	Online

4.6.1 createAppRole

Online command that creates a new application role.

4.6.1.1 Description

Creates a new application role in the domain policy store with a given application and role name. In the event of an error, the command returns a `WLSTException`.

4.6.1.2 Syntax

```
createAppRole(appStripe, appRoleName)
```

Argument	Definition
<i>appStripe</i>	Specifies an application stripe.
<i>appRoleName</i>	Specifies a role name.

4.6.1.3 Example

The following invocation creates a new application role with application stripe `myApp` and role name `myRole`:

```
wls:/mydomain/serverConfig> createAppRole(appStripe="myApp", appRoleName="myRole")
```

4.6.2 deleteAppRole

Online command that removes an application role.

4.6.2.1 Description

Removes an application role in the domain policy store with a given application and role name. In the event of an error, the command returns a `WLSTException`.

4.6.2.2 Syntax

```
createAppRole(appStripe, appRoleName)
```

Argument	Definition
<i>appStripe</i>	Specifies an application stripe.
<i>appRoleName</i>	Specifies a role name.

4.6.2.3 Example

The following invocation removes the role with application stripe `myApp` and role name `myRole`:

```
wls:/mydomain/serverConfig> createAppRole(appStripe="myApp", appRoleName="myRole")
```

4.6.3 grantAppRole

Online command that adds a principal to a role.

4.6.3.1 Description

Adds a principal (class or name) to a role with a given application stripe and name. In the event of an error, the command returns a `WLSTException`.

4.6.3.2 Syntax

```
grantAppRole(appStripe, appRoleName,principalClass, principalName)
```

Argument	Definition
<i>appStripe</i>	Specifies an application stripe.
<i>appRoleName</i>	Specifies a role name.
<i>principalClass</i>	Specifies the fully qualified name of a class.
<i>principalName</i>	Specifies the principal name.

4.6.3.3 Example

The following invocation adds a principal to the role with application stripe `myApp` and role name `myRole`:

```
wls:/mydomain/serverConfig> grantAppRole(appStripe="myApp",
appRoleName="myRole",principalClass="com.example.xyzPrincipal",
principalName="myPrincipal")
```

4.6.4 revokeAppRole

Online command that removes a principal from a role.

4.6.4.1 Description

Removes a principal (class or name) from a role with a given application stripe and name. In the event of an error, the command returns a `WLSTException`.

4.6.4.2 Syntax

```
revokeAppRole(appStripe, appRoleName, principalClass, principalName)
```

Argument	Definition
<i>appStripe</i>	Specifies an application stripe.
<i>appRoleName</i>	Specifies a role name.
<i>principalClass</i>	Specifies the fully qualified name of a class.
<i>principalName</i>	Specifies the principal name.

4.6.4.3 Example

The following invocation removes a principal to the role with application stripe `myApp` and role name `myRole`:

```
wls:/mydomain/serverConfig> revokeAppRole(appStripe="myApp",
appRoleName="myRole",principalClass="com.example.xyzPrincipal",
principalName="myPrincipal")
```

4.6.5 listAppRoles

Online command that lists all roles in an application.

4.6.5.1 Description

Lists all roles within a given application stripe. In the event of an error, the command returns a `WLSTException`.

4.6.5.2 Syntax

```
listAppRoles(appStripe)
```

Argument	Definition
<i>appStripe</i>	Specifies an application stripe.

4.6.5.3 Example

The following invocation returns all roles with application stripe `myApp`:

```
wls:/mydomain/serverConfig> listAppRoles(appStripe="myApp")
```

4.6.6 listAppRolesMembers

Online command that lists all members in a role.

4.6.6.1 Description

Lists all members in a role with a given application stripe and role name. In the event of an error, the command returns a `WLSTException`.

4.6.6.2 Syntax

```
listAppRoleMembers(appStripe, appRoleName)
```

Argument	Definition
<i>appStripe</i>	Specifies an application stripe.

Argument	Definition
<i>appRoleName</i>	Specifies a role name.

4.6.6.3 Example

The following invocation returns all members in the role with application stripe `myApp` and role name `myRole`:

```
wls:/mydomain/serverConfig> listAppRoleMembers (appStripe="myApp",
appRoleName="myRole")
```

4.6.7 grantPermission

Online command that creates a new permission.

4.6.7.1 Description

Creates a new permission for a given code base or URL. In the event of an error, the command returns a `WLSTException`.

4.6.7.2 Syntax

Optional arguments are enclosed in between square brackets.

```
grantPermission([appStripe,] [codeBaseURL,] [principalClass,] [principalName,]
permClass, [permTarget,] [permActions])
```

Argument	Definition
<i>appStripe</i>	Specifies an application stripe. If not specified, the command works on system policies.
<i>codeBaseURL</i>	Specifies the URL of the code granted the permission.
<i>principalClass</i>	Specifies the fully qualified name of a class (grantee).
<i>principalName</i>	Specifies the name of the grantee principal.
<i>permClass</i>	Specifies the fully qualified name of the permission class.
<i>permTarget</i>	Specifies, when available, the name of the permission target. Some permissions may not include this attribute.
<i>permActions</i>	Specifies a comma-separated list of actions granted. Some permissions may not include this attribute and the actions available depend on the permission class.

4.6.7.3 Examples

The following invocation creates a new application permission (for the application with application stripe `myApp`) with the specified data:

```
wls:/mydomain/serverConfig> grantPermission(appStripe="myApp",
principalClass="my.custom.Principal", principalName="manager",
permClass="java.security.AllPermission")
```

The following invocation creates a new system permission with the specified data:

```
wls:/mydomain/serverConfig> grantPermission(principalClass="my.custom.Principal",
principalName="manager",
permClass="java.io.FilePermission", permTarget="/tmp/fileName.ext",
permTarget="/tmp/fileName.ext", permActions="read,write")
```

4.6.8 revokePermission

Online command that removes a permission.

4.6.8.1 Description

Removes a permission for a given code base or URL. In the event of an error, the command returns a `WLSTException`.

4.6.8.2 Syntax

Optional arguments are enclosed in between square brackets.

```
revokePermission([appStripe,] [codeBaseURL,] [principalClass,] [principalName,]
permClass, [permTarget,] [permActions])
```

Argument	Definition
<i>appStripe</i>	Specifies an application stripe. If not specified, the command works on system policies.
<i>codeBaseURL</i>	Specifies the URL of the code granted the permission.
<i>principalClass</i>	Specifies the fully qualified name of a class (grantee).
<i>principalName</i>	Specifies the name of the grantee principal.
<i>permClass</i>	Specifies the fully qualified name of the permission class.
<i>permTarget</i>	Specifies, when available, the name of the permission target. Some permissions may not include this attribute.
<i>permActions</i>	Specifies a comma-separated list of actions granted. Some permissions may not include this attribute and the actions available depend on the permission class.

4.6.8.3 Examples

The following invocation removes the application permission (for the application with application stripe `myApp`) with the specified data:

```
wls:/mydomain/serverConfig> revokePermission(appStripe="myApp",
principalClass="my.custom.Principal", principalName="manager",
permClass="java.security.AllPermission")
```

The following invocation removes the system permission with the specified data:

```
wls:/mydomain/serverConfig> revokePermission(principalClass="my.custom.Principal",
principalName="manager",
permClass="java.io.FilePermission", permTarget="/tmp/fileName.ext",
permActions="read,write")
```

4.6.9 listPermissions

Online command that lists all permissions granted to a given principal.

4.6.9.1 Description

Lists all permissions granted to a given principal. In the event of an error, the command returns a `WLSTException`.

4.6.9.2 Syntax

Optional arguments are enclosed in between square brackets.

```
listPermissions([appStripe,] principalClass, principalName)
```

Argument	Definition
<i>appStripe</i>	Specifies an application stripe. If not specified, the command works on system policies.
<i>principalClass</i>	Specifies the fully qualified name of a class (grantee).
<i>principalName</i>	Specifies the name of the grantee principal.

4.6.9.3 Examples

The following invocation lists all permissions granted to a principal by the policies of application `myApp`:

```
wls:/mydomain/serverConfig> listPermissions(appStripe="myApp",
principalClass="my.custom.Principal",principalName="manager")
```

The following invocation lists all permissions granted to a principal by system policies:

```
wls:/mydomain/serverConfig> listPermissions(principalClass="my.custom.Principal",
principalName="manager")
```

4.6.10 deleteAppPolicies

Online command that removes all policies with a given application stripe.

4.6.10.1 Description

Removes all policies with a given application stripe. In the event of an error, the command returns a `WLSTException`.

4.6.10.2 Syntax

```
deleteAppPolicies(appStripe)
```

Argument	Definition
<i>appStripe</i>	Specifies an application stripe. If not specified, the command works on system policies.

4.6.10.3 Example

The following invocation removes all policies of application `myApp`:

```
wls:/mydomain/serverConfig> deleteAppPolicies(appStripe="myApp")
```

4.6.11 migrateSecurityStore

Offline command that migrates identities, application-specific, system policies, a specific credential folder, or all credentials.

4.6.11.1 Description

Migrates identities, application-specific, or system policies from a source repository to a target repository. Migrates a specific credential folder or all credentials.

The kinds of the repositories where the source and target data is stored is transparent to the command, and any combination of file-based and LDAP-based repositories is

allowed (LDAP-repositories must use an OVD or an OID LDAP server only). In the event of an error, the command returns a `WLSTException`.

4.6.11.2 Syntax

The command syntax varies depending on the scope (system or application-specific or both) of the policies being migrated.

Optional arguments are enclosed in square brackets.

To migrate identities, use the following syntax:

```
migrateSecurityStore(type="idStore", configFile, src, dst, [dstLdifFile])
```

To migrate all policies (system *and* application-specific, for all applications) use the following syntax

```
migrateSecurityStore(type="policyStore", configFile, src,
dst, [overWrite,] [preserveAppRoleGuid])
```

To migrate *just* system policies, use the following syntax:

```
migrateSecurityStore(type="globalPolicies", configFile, src, dst, [overWrite])
```

To migrate *just* application-specific policies, for one application, use the following syntax:

```
migrateSecurityStore(type="appPolicies", configFile,src, dst, srcApp
[,dstApp] [,overWrite] [,migrateIdStoreMapping][,preserveAppRoleGuid] [,mode])
```

To migrate *all* credentials, use the following syntax:

```
migrateSecurityStore(type="credStore", configFile, src, dst, [overWrite])
```

To migrate *just* one credential folder, use the following syntax:

```
migrateSecurityStore(type="folderCred", configFile,src, dst, [srcFolder,]
[dstFolde,] [srcConfigFile,] [overWrite])
```

Argument	Definition
<code>type</code>	Specifies the type of policies migrates. To migrate identities, set it to <code>idStore</code> . To migrate all policies (system and application-specific, for all applications), set to <code>policyStore</code> . To migrate just system policies, set to <code>globalPolicies</code> . To migrate just application-specific policies, set to <code>appPolicies</code> . To migrate all credentials, set to <code>credStore</code> . To migrate just one credential folder, set to <code>folderCred</code> .
<code>configFile</code>	Specifies the location of a configuration file <code>jps-config.xml</code> relative to the directory where the command is run. The configuration file passed need not be an actual domain configuration file, but it can be assembled <i>just</i> to specify the source and destination repositories of the migration.
<code>src</code>	Specifies the name of a <code>jps-context</code> in the configuration file passed to the argument <code>configFile</code> , where the source store is specified.
<code>dst</code>	Specifies the name of another <code>jps-context</code> in the configuration file passed to the argument <code>configFile</code> , where the destination store is specified.

Argument	Definition
<i>srcApp</i>	Specifies the name of the source application, that is, the application whose policies are being migrated.
<i>dstApp</i>	Specifies the name of the target application, that is, the application whose policies are being written. If unspecified, it defaults to the name of the source application.
<i>srcFolder</i>	Specifies the name of the folder from where credentials are migrated. This argument is optional. If unspecified, the credential store is assumed to have only one folder and the value of this argument defaults to the name of that folder.
<i>dstFolder</i>	Specifies the folder to where the source credentials are migrated. This argument is optional and, if unspecified, defaults to the folder passed to <i>srcFolder</i> .
<i>srcConfigFile</i>	Specifies the location of an alternate configuration file, and it is used in the special case in which credentials are not configured in the file passed to <i>configFile</i> . This argument is optional. If unspecified, it defaults to the value passed to <i>configFile</i> ; if specified, the value passed to <i>configFile</i> is ignored.
<i>overWrite</i>	Specifies whether data in the target matching data being migrated should be overwritten by or merged with the source data. Optional and false by default. Set to true to overwrite matching data; set to false to merge matching data.
<i>migrateIdStoreMapping</i>	Specifies whether the migration of application policies should include or exclude the migration of enterprise policies. Optional and true by default. Set it to False to exclude enterprise policies from the migration of application policies.
<i>dstLdifFile</i>	Specifies the location where the LDIF file will be created. Required only if destination is an LDAP-based identity store. Notice that the LDIF file is not imported into the LDAP server; the importing of the file LDIF should be done manually, after the file has been edited to account for the appropriate attributes required in your LDAP server.
<i>preserveAppRoleGuid</i>	Specifies whether the migration of policies should preserve or recreate GUIDs. Optional and false, by default. Set to true to preserve GUIDs; set to false to recreated GUIDs.
<i>mode</i>	Specifies whether the migration should stop and signal an error upon encountering a duplicate principal or a duplicate permission in an application policy. Set to lax to allow the migration to continue upon encountering duplicate items, to migrate just one of the duplicated items, and to log a warning to this effect; set to strict to force the migration to stop upon encountering duplicate items. If unspecified, it defaults to strict.

Note the following requirements about the passed arguments:

- The file `jps-config.xml` is found in the passed location.
- The file `jps-config.xml` includes the passed `jps-contexts`.
- The source and the destination context names are distinct. From these two contexts, the command determines the locations of the source and the target repositories involved in the migration.

4.6.11.3 Example

The following invocation illustrates the migration of the file-based policies of application `PolicyServlet1` to file-based policies of application `PolicyServlet2`,

that does not stop on encountering duplicate principals or permissions, that migrates just one of duplicate items, and that logs a warning when duplicates are found:

```
wls:/mydomain/serverConfig> migrateSecurityStore(type="appPolicies",
configFile="jps-congif.xml", src="default1", dst="context2",
srcApp="PolicyServlet1", dstApp="PolicyServlet2", overwrite="true", mode="lax")
```

The above invocation assumes that:

- The file `jps-config.xml` is located in the directory where the command is run (current directory).
- That file includes the following elements:

```
<serviceInstance name="policystore1.xml" provider="some.provider">
  <property name="location" value="jazn-data1.xml"/>
</serviceInstance>
<serviceInstance name="policystore2.xml" provider="some.provider">
  <property name="location" value="jazn-data2.xml"/>
</serviceInstance>
...
<jpsContext name="default1">
  <serviceInstanceRef ref="policystore1.xml"/>
  ...
</jpsContext>
<jpsContext name="context2">
  <serviceInstanceRef ref="policystore2.xml"/>
  ...
</jpsContext>
```

The file-based policies for the two applications involved in the migration are defined in the files `jazn-data1.xml` and `jazn-data2.xml`, which are not shown but assumed located in the current directory.

The following invocation illustrates the migration of file-based credentials from one location to another:

```
wls:/mydomain/serverConfig> migrateSecurityStore(type="credStore",
configFile="jps-congif.xml", src="default1", dst="context2")
```

The above invocation assumes that:

- The file `jps-config.xml` is located in the directory where the command is run (current directory).
- That file includes the following elements:

```
<serviceInstance name="credstore1" provider="some.provider">
  <property name="location" value="./credstore1/cwallet.sso"/>
</serviceInstance>
<serviceInstance name="credstore2" provider="some.provider">
  <property name="location" value="./credstore2/cwallet.sso"/>
</serviceInstance>
...
<jpsContext name="default1">
  <serviceInstanceRef ref="credstore1"/>
  ...
</jpsContext>
<jpsContext name="context2">
  <serviceInstanceRef ref="credstore2"/>
  ...
</jpsContext>
```

For detailed configuration examples to use with this command, see "Migrating Policies Manually" in *Oracle Fusion Middleware Application Security Guide*.

4.6.12 updateCred

Online command that modifies the type, user name, and password of a credential.

4.6.12.1 Description

Modifies the type, user name, password, URL, and port number of a credential in the domain credential store with given map name and key name. This command can update the data encapsulated in credentials of type password only. In the event of an error, the command returns a `WLSTException`. This command runs in interactive mode only.

4.6.12.2 Syntax

Optional arguments are enclosed in square brackets.

```
updateCred(map, key, user, password, [desc])
```

Argument	Definition
<i>map</i>	Specifies a map name (folder).
<i>key</i>	Specifies a key name.
<i>user</i>	Specifies the credential user name.
<i>password</i>	Specifies the credential password.
<i>desc</i>	Specifies a string describing the credential.

4.6.12.3 Example

The following invocation updates a password credential with the specified data:

```
wls:/mydomain/serverConfig> updateCred(map="myMap", key="myKey", user="myUsr",
password="myPassw", desc="updated passw cred to connect to app xyz")
```

4.6.13 createCred

Online command that creates a new credential in the domain credential store.

4.6.13.1 Description

Creates a new credential in the domain credential store with a given map name, key name, type, user name and password, URL and port number. In the event of an error, the command returns a `WLSTException`. This command runs in interactive mode only.

4.6.13.2 Syntax

Optional arguments are enclosed in square brackets.

```
createCred(map, key, user, password, [desc])
```

Argument	Definition
<i>map</i>	Specifies a map name (folder).
<i>key</i>	Specifies a key name.

Argument	Definition
<i>user</i>	Specifies the credential user name.
<i>password</i>	Specifies the credential password.
<i>desc</i>	Specifies a string describing the credential.

4.6.13.3 Example

The following invocation creates a new password credential with the specified data:

```
wls:/mydomain/serverConfig> createCred(map="myMap, key="myKey", user="myUsr",
password="myPassw", desc="updated usr name and passw to connect to app xyz")
```

4.6.14 deleteCred

Online command that removes a credential in the domain credential store.

4.6.14.1 Description

Removes a credential with given map name and key name from the domain credential store. In the event of an error, the command returns a `WLSTException`.

4.6.14.2 Syntax

```
deleteCred(map, key)
```

Argument	Definition
<i>map</i>	Specifies a map name (folder).
<i>key</i>	Specifies a key name.

4.6.14.3 Example

The following invocation removes the credential with map name `myMap` and key name `myKey`:

```
wls:/mydomain/serverConfig> deleteCred(map="myApp", key="myKey")
```

4.6.15 modifyBootStrapCredential

Offline command that updates a bootstrap credential store.

4.6.15.1 Description

Updates a bootstrap credential store with given user name and password. In the event of an error, the command returns a `WLSTException`.

Typically used in the following scenario: suppose that the domain policy and credential stores are LDAP-based, and the credentials to access the LDAP store (stored in the LDAP server) are changed. Then this command can be used to seed those changes into the bootstrap credential store.

4.6.15.2 Syntax

```
modifyBootStrapCredential(jpsConfigFile, username, password)
```

Argument	Definition
<i>jpsConfigFile</i>	Specifies the location of the file <code>jps-config.xml</code> relative to the location where the command is run.
<i>username</i>	Specifies the distinguished name of the user in the LDAP store.
<i>password</i>	Specifies the password of the user.

4.6.15.3 Example

Suppose that in the LDAP store, the password of the user with distinguished name `cn=orcladmin` has been changed to `welcome1`, and that the configuration file `jps-config.xml` is located in the current directory.

Then the following invocation changes the password in the bootstrap credential store to `welcome1`:

```
wls:/mydomain/serverConfig>
modifyBootStrapCredential(jpsConfigFile='./jps-config.xml',
username='cn=orcladmin', password='welcome1')
```

Any output regarding the audit service can be disregarded.

4.6.16 addBootStrapCredential

Offline command that adds a credential to the bootstrap credential store.

4.6.16.1 Description

Adds a password credential with the given map, key, user name, and user password to the bootstrap credentials configured in the default JPS context of a JPS configuration file. In the event of an error, the command returns a `WLSTException`.

4.6.16.2 Syntax

```
addBootStrapCredential(jpsConfigFile, map, key, username, password)
```

Argument	Definition
<i>jpsConfigFile</i>	Specifies the location of the file <code>jps-config.xml</code> relative to the location where the command is run.
<i>map</i>	Specifies the map of the credential to add.
<i>key</i>	Specifies the key of the credential to add.
<i>username</i>	Specifies the name of the user in the credential to add.
<i>password</i>	Specifies the password of the user in the credential to add.

4.6.16.3 Example

The following invocation adds a credential to the bootstrap credential store:

```
wls:/mydomain/serverConfig>
addBootStrapCredential(jpsConfigFile='./jps-config.xml', map='myMapName',
key='myKeyName', username='myUser', password='myPassword')
```

4.6.17 exportEncryptionKey

Offline command that extracts the encryption key from a domain's bootstrap wallet to the file `ewallet.p12`.

4.6.17.1 Description

Writes the domain's credential encryption key to the file `ewallet.p12`. The password passed must be used to import data from that file with the command `importEncryptionKey`.

4.6.17.2 Syntax

```
exportEncryptionKey(jpsConfigFile, keyFilePath, keyFilePassword)
```

Argument	Definition
<i>jpsConfigFile</i>	Specifies the location of the file <code>jps-config.xml</code> relative to the location where the command is run.
<i>keyFilePath</i>	Specifies the directory where the file <code>ewallet.p12</code> is created; note that the content of this file is encrypted and secured by the value passed to <code>keyFilePassword</code> .
<i>keyFilePassword</i>	Specifies the password to secure the file <code>ewallet.p12</code> ; note that this same password must be used when importing that file.

4.6.17.3 Example

The following invocation writes the file `ewallet.p12` in the directory `myDir`:

```
exportEncryptionKey(jpsConfigFile="pathName", keyFilePath="myDir"
, keyFilePassword="password")
```

4.6.18 importEncryptionKey

Offline command that imports keys from the specified `ewallet.p12` file into the domain.

4.6.18.1 Description

Imports encryption keys from the file `ewallet.p12` into the domain. The password passed must be the same as that used to create the file with the command `exportEncryptionKey`.

4.6.18.2 Syntax

```
importEncryptionKey(jpsConfigFile, keyFilePath, keyFilePassword)
```

Argument	Definition
<i>jpsConfigFile</i>	Specifies the location of the file <code>jps-config.xml</code> relative to the location where the command is run.
<i>keyFilePath</i>	Specifies the directory where the <code>ewallet.p12</code> is located.
<i>keyFilePassword</i>	Specifies the password used when the file <code>ewallet.p12</code> was generated.

4.6.18.3 Example

```
importEncryptionKey(jpsConfigFile="pathName", keyFilePath="dirloc"
, keyFilePassword="password")
```

4.6.19 restoreEncryptionKey

Offline command to restore the domain credential encryption key.

4.6.19.1 Description

Restores the state of the domain bootstrap keys as it was before running `importEncryptionKey`.

4.6.19.2 Syntax

```
restoreEncryptionKey(jpsConfigFile)
```

Argument	Definition
<i>jpsConfigFile</i>	Specifies the location of the file <code>jps-config.xml</code> relative to the location where the command is run.

4.6.19.3 Example

```
restoreEncryptionKey(jpsConfigFile="pathName")
```

4.6.20 rollOverEncryptionKey

Offline command to create a new domain credential encryption key.

4.6.20.1 Description

Creates a new credential encryption key in the domain wallet. Note the following important points:

- It should be executed from the administration server in the domain. No server restart is needed after invoking this script.
- If the domain is the only domain accessing the security store, nothing else is required.
- However, if two or more domains share the security store, the newly generated key should be exported from the domain where the script was run and imported into each of the other domains sharing the security store, using the scripts [exportEncryptionKey](#) and [importEncryptionKey](#).
- On the WebSphere platform, the script name is `Opss.rollOverEncryptionKey`.

4.6.20.2 Syntax

```
rollOverEncryptionKey(jpsConfigFile)
```

Argument	Definition
<i>jpsConfigFile</i>	Specifies the location of the file <code>jps-config.xml</code> relative to the location where the command is run.

4.6.20.3 Example

```
rollOverEncryptionKey(jpsConfigFile="pathName")
```

4.6.21 reassociateSecurityStore

Online command that migrates the policy and credential stores to an LDAP repository.

4.6.21.1 Description

Migrates, within a give domain, *both* the policy store and the credential store to a target LDAP server repository. The only kinds of LDAP servers allowed are OID or OVD. This command also allows setting up a policy store shared by different domains (see optional argument `join` below). In the event of an error, the command returns a `WLSTException`. This command runs in interactive mode only.

4.6.21.2 Syntax

```
reassociateSecurityStore(domain, admin, password, ldapurl, servertype, jpsroot [,
join] [,keyFilePath, keyFilePassword])
```

Argument	Definition
<code>domain</code>	Specifies the domain name where the reassociating takes place.
<code>admin</code>	Specifies the administrator's user name on the LDAP server. The format is <code>cn=userName</code> .
<code>password</code>	Specifies the password associated with the user specified for the argument <code>admin</code> .
<code>ldapurl</code>	Specifies the URI of the LDAP server. The format is <code>ldap://host:port</code> , if you are using a default port, or <code>ldaps://host:port</code> , if you are using a secure LDAP port. The secure port must be configured specially for this function and it is distinct from the default (non-secure) port.
<code>servertype</code>	Specifies the kind of the target LDAP server. The only valid types are <code>OID</code> or <code>OVD</code> .
<code>jpsroot</code>	Specifies the root node in the target LDAP repository under which all data is migrated. The format is <code>cn=nodeName</code> .
<code>join</code>	Specifies whether the domain is to share a policy store specified in some other domain. Optional. Set to <code>true</code> to share an existing policy store in another domain; set to <code>false</code> otherwise. If unspecified, it defaults to <code>false</code> . The use of this argument allows multiple WebLogic domains to point to the same logical policy store.
<code>keyFilePath</code>	Specifies the directory where the <code>ewallet.p12</code> is located.
<code>keyFilePassword</code>	Specifies the password used when the file <code>ewallet.p12</code> was generated.

4.6.21.3 Examples

The following invocation reassociates the domain policies and credentials to an LDAP Oracle Internet Directory server:

```
wls:/mydomain/serverConfig> reassociateSecurityStore(domain="myDomain",
admin="cn=adminName", password="myPass",ldapurl="ldap://myhost.example.com:3060",
servertype="OID", jpsroot="cn=testNode")
```

Suppose that you want some *other* domain (distinct from `myDomain`, say `otherDomain`) to share the policy store in `myDomain`. Then you would invoke the command as follows:

```
wls:/mydomain/serverConfig> reassociateSecurityStore(domain="otherDomain",
admin="cn=adminName", password="myPass", ldapurl="ldap://myhost.example.com:3060",
servertype="OID", jpsroot="cn=testNode", join="true")
```

4.6.22 upgradeSecurityStore

Offline command that migrates release 10.1.x security data to release 11 security data.

4.6.22.1 Description

Migrates identity, policy, and credential data used in release 10.1.x to security data that can be used with release 11. The migration of each kind of data is performed with separate invocations of this command. In the event of an error, the command returns a `WLSTException`.

4.6.22.2 Syntax

The syntax varies according to the type of data being updated.

To upgrade 10.1.x XML identity data to 11 XML identity data, use the following syntax:

```
updateSecurityStore(type="xmlIdStore", jpsConfigFile, srcJaznDataFile, srcRealm, dst)
```

To upgrade a 10.1.x XML policy data to 11 XML policy data, use the following syntax:

```
updateSecurityStore(type="xmlPolicyStore", jpsConfigFile, srcJaznDataFile, dst)
```

To upgrade a 10.1.x OID LDAP-based policy data to 11 XML policy data, use the following syntax:

```
updateSecurityStore(type="oidPolicyStore", jpsConfigFile, srcJaznDataFile, dst)
```

To upgrade a 10.1.x XML credential data to 11 XML credential data, use the following syntax:

```
updateSecurityStore(type="xmlCredStore", jpsConfigFile, srcJaznDataFile, users, dst)
```

Argument	Definition
<i>type</i>	Specifies the kind of security data being upgraded. The only valid values are <code>xmlIdStore</code> , <code>xmlPolicyStore</code> , <code>oidPolicyStore</code> , and <code>xmlCredStore</code> .
<i>jpsConfigFile</i>	Specifies the location of a configuration file <code>jps-config.xml</code> relative to the directory where the command is run. The target store of the upgrading is read from the context specified with the argument <code>dst</code> .
<i>srcJaznDataFile</i>	Specifies the location of a 10.1.x jazn data file relative to the directory where the command is run. This argument is required if the specified <code>type</code> is <code>xmlIdStore</code> , <code>xmlPolicyStore</code> , or <code>xmlCredStore</code> .
<i>srcJaznConfigFile</i>	Specifies the location of a 10.1.x jazn configuration file relative to the directory where the command is run. This argument is required if the specified <code>type</code> is <code>oidPolicyStore</code> .
<i>srcRealm</i>	Specifies the name of the realm from which identities need be migrated. This argument is required if the specified <code>type</code> is <code>xmlIdStore</code> .
<i>users</i>	Specifies a comma-separated list of users each formatted as <code>realmName/userName</code> . This argument is required if the specified <code>type</code> is <code>xmlCredStore</code> .

Argument	Definition
<i>dst</i>	Specifies the name of the <code>jpsContext</code> in the file passed to the argument <code>jpsConfigFile</code> where the destination store is configured. Optional. If unspecified, it defaults to the default context in the file passed in the argument <code>jpsConfigFile</code> .

4.6.22.3 Examples

The following invocation migrates 10.1.3 file-based identities to an 11 file-based identity store:

```
wls:/mydomain/serverConfig> upgradeSecurityStore(type="xmlIdStore",
jpsConfigFile="jps-config.xml", srcJaznDataFile="jazn-data.xml",
srcRealm="jazn.com")
```

The following invocation migrates a 10.1.3 OID-based policy store to an 11 file-based policy store:

```
wls:/mydomain/serverConfig> upgradeSecurityStore(type="oidPolicyStore",
jpsConfigFile="jps-config.xml", srcJaznDataFile="jazn-data.xml",
dst="destinationContext")
```

4.6.23 createResourceType

Online command that creates a new resource type in the domain policy store within a given application stripe.

4.6.23.1 Description

Creates a new resource type element in the domain policy store within a given application stripe and with specified name, display name, description, and actions. Optional arguments are enclosed in between square brackets; all other arguments are required. In the event of an error, the command returns a `WLSTException`.

4.6.23.2 Syntax

Optional arguments are enclosed in square brackets.

```
createResourceType(appStripe, resourceName, displayName, description [,
provider] [, matcher], actions [, delimiter])
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where to insert the resource type.
<i>resourceTypeName</i>	Specifies the name of the resource type to insert.
<i>displayName</i>	Specifies the name for the resource type used in UI gadgets.
<i>description</i>	Specifies a brief description of the resource type.
<i>provider</i>	Specifies the provider for the resource type.
<i>matcher</i>	Specifies the class of the resource type. If unspecified, it defaults to <code>oracle.security.jps.ResourcePermission</code> .
<i>actions</i>	Specifies the actions allowed on instances of the resource type.
<i>delimiter</i>	Specifies the character used to delimit the list of actions. If unspecified, it defaults to comma <code>,</code> .

4.6.23.3 Example

The following invocation creates a resource type in the stripe myApplication with actions BWPrint and ColorPrint delimited by a semicolon:

```
wls:/mydomain/serverConfig> createResourceType (appStripe="myApplication",
resourceTypeName="resTypeName", displayName="displName", description="A resource
type", provider="Printer", matcher="com.printer.Printer",
actions="BWPrint;ColorPrint" [, delimiter=";"])
```

4.6.24 getResourceType

Online command that fetches a resource type from the domain policy store within a given application stripe.

4.6.24.1 Description

Gets the relevant parameters of a <resource-type> entry in the domain policy store within a given application stripe and with specified name. In the event of an error, the command returns a WLSTException.

4.6.24.2 Syntax

```
getResourceType (appStripe, resourceTypeName)
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe from where to fetch the resource type.
<i>resourceTypeName</i>	Specifies the name of the resource type to fetch.

4.6.24.3 Example

The following invocation fetches the resource type myResType from the stripe myApplication:

```
wls:/mydomain/serverConfig> getResourceType (appStripe="myApplication",
resourceTypeName="myResType")
```

4.6.25 deleteResourceType

Online command that removes a resource type from the domain policy store within a given application stripe.

4.6.25.1 Description

Removes a <resource-type> entry in the domain policy store within a given application stripe and with specified name. In the event of an error, the command returns a WLSTException.

4.6.25.2 Syntax

```
deleteResourceType (appStripe, resourceTypeName)
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe from where to remove the resource type.
<i>resourceTypeName</i>	Specifies the name of the resource type to remove.

4.6.25.3 Example

The following invocation removes the resource type `myResType` from the stripe `myApplication`:

```
wls:/mydomain/serverConfig> deleteResourceType (appStripe="myApplication",
resourceTypeName="myResType")
```

4.6.26 listSecurityStoreInfo

Offline command that lists the type, the location, and the administrative user of the domain security store.

4.6.26.1 Description

The script runs in offline mode and outputs the type of the OPSS security store (file, OID, or DB), its location, and the user allowed to access it (typically a security administrator).

4.6.26.2 Syntax

```
listSecurityStoreInfo (domainConfig="configFilePath")
```

Argument	Definition
<i>domainConfig</i>	Specifies the full absolute path to the OPSS configuration file <code>jps-config.xml</code> ; the file <code>jps-config-jse.xml</code> is also expected to be in the passed directory.

4.6.26.3 Example

The following invocation returns the type, location, and administrative user of the OPSS policy store:

```
wls:/mydomain/serverConfig>
listSecurityStoreInfo (domainConfig="/home/myConfigPathDirectory/config/fmwconfig")
```

4.6.27 listAppStripes

Online or offline command that lists the application stripes in the policy store.

4.6.27.1 Description

This script can be run in offline or online mode. When run in offline mode, a configuration file must be passed, and it lists the application stripes in the policy store referred to by the configuration in the default context of the passed configuration file; the default configuration *must not* have a service instance reference to an identity store. When run in online mode, a configuration file must not be passed, and it lists stripes in the policy store of the domain to which you connect. In any mode, if a regular expression is passed, it lists the application stripes with names that match the regular expression; otherwise, it lists all application stripes.

If this command is used in offline mode after reassociating to a DB-based store, the configuration file produced by the reassociation *must* be manually edited as described in "Running `listAppStripes` after Reassociating to a DB-Based Store" in *Oracle Fusion Middleware Application Security Guide*.

4.6.27.2 Syntax

```
listAppStripes ([configFile="configFileName"] [, regularExpression="aRegExp"])
```

Argument	Definition
<i>configFile</i>	Specifies the path to the OPSS configuration file. Optional. If specified, the script runs offline; the default context in the specified configuration file <i>must not</i> have a service instance reference to an identity store. If unspecified, the script runs online and it lists application stripes in the policy store.
<i>regularExpression</i>	Specifies the regular expression that returned stripe names should match. Optional. If unspecified, it matches all names. To match substrings, use the character <code>*</code> .

4.6.27.3 Examples

The following (online) invocation returns the list of application stripes in the policy store:

```
wls:/mydomain/serverConfig> listAppStripes
```

The following (offline) invocation returns the list of application stripes in the policy store referenced in the default context of the specified configuration file:

```
wls:/mydomain/serverConfig> listAppStripes(configFile="
/home/myFile/jps-config.xml")
```

The following (online) invocation returns the list of application stripes that contain the prefix App:

```
wls:/mydomain/serverConfig> listAppStripes(regularExpression="App*")
```

4.6.28 listCodeSourcePermissions

Online command that lists permissions assigned to a source code in global policies.

4.6.28.1 Description

This command allows listing codebase permissions in global policies.

4.6.28.2 Syntax

```
listCodeSourcePermissions([codeBase="codeUrl"])
```

Argument	Definition
<i>codeBaseURL</i>	Specifies the name of the grantee codebase URL.

4.6.28.3 Examples

The following invocation returns the list permissions assigned to a code source in all global policies:

```
wls:/mydomain/serverConfig>
listCodeSourcePermissions(codeBaseURL="file:/tmp/lib/myJars.jar")
```

4.6.29 createResource

Online command that creates a new resource.

4.6.29.1 Description

Creates a resource of a specified type in a specified application stripe. The passed resource type must exist in the passed application stripe.

4.6.29.2 Syntax

```
createResource(appStripe="appStripeName", name="resName", type="resTypeName"
[, -displayName="dispName" ] [, -description="descript"])
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where the resource is created.
<i>name</i>	Specifies the name of the resource created.
<i>type</i>	Specifies the type of resource created. The passed resource type <i>must</i> be present in the application stripe at the time this script is invoked.
<i>displayName</i>	Specifies the display name of the resource created. Optional.
<i>description</i>	Specifies the description of the resource created. Optional.

4.6.29.3 Example

The following invocation creates the resource myResource in the stripe myApplication:

```
wls:/mydomain/serverConfig> createResource(appStripe="myApplication",
name="myResource", type="myResType", displayName="myNewResource")
```

4.6.30 deleteResource

Online command that deletes a resource.

4.6.30.1 Description

Deletes a resource and all its references from entitlements in an application stripe. It performs a cascading deletion: if the entitlement refers to one resource only, it removes the entitlement; otherwise, it removes from the entitlement the resource actions for the passed type.

4.6.30.2 Syntax

```
deleteResource(appStripe="appStripeName", name="resName", type="resTypeName")
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where the resource is deleted.
<i>name</i>	Specifies the name of the resource deleted.
<i>type</i>	Specifies the type of resource deleted. The passed resource type <i>must</i> be present in the application stripe at the time this script is invoked.

4.6.30.3 Example

The following invocation deletes the resource myResource in the stripe myApplication:

```
wls:/mydomain/serverConfig> deleteResource(appStripe="myApplication",
name="myResource", type="myResType")
```

4.6.31 listResources

Online command that lists resources in a specified application stripe.

4.6.31.1 Description

If a resource type is specified, it lists all the resources of the specified resource type; otherwise, it lists all the resources of all types.

4.6.31.2 Syntax

```
listResources (appStripe="appStripeName" [, type="resTypeName"])
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where the resources are listed.
<i>type</i>	Specifies the type of resource listed. The passed resource type <i>must</i> be present in the application stripe at the time this script is invoked.

4.6.31.3 Example

The following invocation lists all resources of type myResType in the stripe myApplication:

```
wls:/mydomain/serverConfig> listResources (appStripe="myApplication",
type="myResType")
```

4.6.32 listResourceActions

Online command that lists the resources and actions in an entitlement.

4.6.32.1 Description

Lists the resources and actions in an entitlement within an application stripe.

4.6.32.2 Syntax

```
listResourceActions (appStripe="appStripeName", permSetName="entitlementName")
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where the entitlement resides.
<i>permSetName</i>	Specifies the name of the entitlement whose resources and actions to list.

4.6.32.3 Example

The following invocation lists the resources and actions of the entitlement myEntitlement in the stripe myApplication:

```
wls:/mydomain/serverConfig> listResourceActions (appStripe="myApplication",
permSetName="myEntitlement")
```

4.6.33 createEntitlement

Online command that creates a new entitlement.

4.6.33.1 Description

Creates a new entitlement with just one resource and a list of actions in a specified application stripe. Use `addResourceToEntitlement` to add additional resources to an existing entitlement; use `revokeResourceFromEntitlement` to delete resources from an existing entitlement.

4.6.33.2 Syntax

```
createEntitlement (appStripe="appStripeName", name="entitlementName",
resourceName="resName", actions="actionList" [-displayName="dispName"]
[-description="descript"])
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where the entitlement is created.
<i>name</i>	Specifies the name of the entitlement created.
<i>resourceName</i>	Specifies the name of the one resource member of the entitlement created.
<i>actions</i>	Specifies a comma-separated the list of actions for the resource resourceName.
<i>displayName</i>	Specifies the display name of the resource created. Optional.
<i>description</i>	Specifies the description of the entitlement created. Optional.

4.6.33.3 Example

The following invocation creates the entitlement myEntitlement with just the resource myResource in the stripe myApplication:

```
wls:/mydomain/serverConfig> createEntitlement (appStripe="myApplication",
name="myEntitlement", resourceName="myResource", actions="read,write")
```

4.6.34 getEntitlement

Online command that gets an entitlement.

4.6.34.1 Description

Returns the name, display name, and all the resources (with their actions) of an entitlement in an application stripe.

4.6.34.2 Syntax

```
getEntitlement (appStripe="appStripeName", name="entitlementName")
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where the entitlement is located.
<i>name</i>	Specifies the name of the entitlement to access.

4.6.34.3 Example

The following invocation returns the information of the entitlement myEntitlement in the stripe myApplication:

```
wls:/mydomain/serverConfig> getEntitlement (appStripe="myApplication",
name="myEntitlement")
```

4.6.35 deleteEntitlement

Online command that deletes an entitlement.

4.6.35.1 Description

Deletes an entitlement in a specified application stripe. It performs a cascading deletion by removing all references to the specified entitlement in the application stripe.

4.6.35.2 Syntax

```
deleteEntitlement (appStripe="appStripeName", name="entitlementName")
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where the entitlement is deleted.
<i>name</i>	Specifies the name of the entitlement to delete.

4.6.35.3 Example

The following invocation deletes the entitlement myEntitlement in the stripe myApplication:

```
wls:/mydomain/serverConfig> deleteEntitlement (appStripe="myApplication",
name="myEntitlement")
```

4.6.36 addResourceToEntitlement

Online command that adds a resource with specified actions to an entitlement.

4.6.36.1 Description

Adds a resource with specified actions to an entitlement in a specified application stripe. The passed resource type must exist in the passed application stripe.

4.6.36.2 Syntax

```
addResourceToEntitlement (appStripe="appStripeName", name="entName",
resourceName="resName", actions="actionList")
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where the entitlement is located.
<i>name</i>	Specifies the name of the entitlement to modify.
<i>resourceName</i>	Specifies the name of the resource to add.
<i>resourceType</i>	Specifies the type of the resource to add. The passed resource type <i>must</i> be present in the application stripe at the time this script is invoked.
<i>actions</i>	Specifies the comma-separated list of actions for the added resource.

4.6.36.3 Example

The following invocation adds the resource myResource to the entitlement myEntitlement in the application stripe myApplication:

```
wls:/mydomain/serverConfig> addResourceToEntitlement (appStripe="myApplication",
name="myEntitlement", resourceName="myResource", resourceType="myResType",
actions="view,edit")
```


4.6.37 revokeResourceFromEntitlement

Online command that removes a resource from an entitlement.

4.6.37.1 Description

Removes a resource from an entitlement in a specified application stripe.

4.6.37.2 Syntax

```
revokeResourceFromEntitlement(appStripe="appStripeName", name="entName",
resourceName="resName", resourceType="resTypeName", actions="actionList")
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where the entitlement is located.
<i>name</i>	Specifies the name of the entitlement to modify.
<i>resourceName</i>	Specifies the name of the resource to remove.
<i>resourceType</i>	Specifies the type of the resource to remove.
<i>actions</i>	Specifies the comma-separated list of actions to remove.

4.6.37.3 Example

The following invocation removes the resource myResource from the entitlement myEntitlement in the stripe myApplication:

```
wls:/mydomain/serverConfig>
revokeResourceFromEntitlement(appStripe="myApplication", name="myEntitlement",
resourceName="myResource", resourceType="myResType", actions="view,edit")
```

4.6.38 listEntitlements

Online command that lists the entitlements in an application stripe.

4.6.38.1 Description

Lists all the entitlements in an application stripe. If a resource name and a resource type are specified, it lists the entitlements that have a resource of the specified type matching the specified resource name; otherwise, it lists all the entitlements in the application stripe.

4.6.38.2 Syntax

```
listEntitlements(appStripe="appStripeName" [,resourceTypeName="resTypeName",
resourceName="resName"])
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe from where to list entitlements.
<i>resourceTypeName</i>	Specifies the name of the type of the resources to list. Optional.
<i>resourceName</i>	Specifies the name of resource to match. Optional.

4.6.38.3 Examples

The following invocation lists all the entitlements in the stripe myApplication:

```
wls:/mydomain/serverConfig> listEntitlements(appStripe="myApplication")
```

The following invocation lists all the entitlements in the stripe myApplication that contain a resource type myResType and a resource whose name match the resource name myResName:

```
wls:/mydomain/serverConfig> listEntitlements(appStripe="myApplication",
resourceTypeName="myResType", resourceName="myResName")
```

4.6.39 grantEntitlement

Online command that creates a new entitlement.

4.6.39.1 Description

Creates a new entitlement with a specified principal in a specified application stripe.

4.6.39.2 Syntax

```
grantEntitlement(appStripe="appStripeName", principalClass="principalClass",
principalName="principalName" ,-permSetName="entName")
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where the entitlement is created.
<i>principalClass</i>	Specifies the class associated with the principal.
<i>principalName</i>	Specifies the name of the principal to which the entitlement is granted.
<i>permSetName</i>	Specifies the name of the entitlement created.

4.6.39.3 Example

The following invocation creates the entitlement myEntitlement in the stripe myApplication:

```
wls:/mydomain/serverConfig> grantEntitlement(appStripe="myApplication",
principalClass="oracle.security.jps.service.policystore.ApplicationRole",
principalName="myPrincipalName", permSetName="myEntitlement")
```

4.6.40 revokeEntitlement

Online command that deletes an entitlement.

4.6.40.1 Description

Deletes an entitlement and revokes the entitlement from the principal in a specified application stripe.

4.6.40.2 Syntax

```
revokeEntitlement(appStripe="appStripeName", principalClass="principalClass",
principalName="principalName" ,-permSetName="entName")
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where the entitlement is deleted.
<i>principalClass</i>	Specifies the class associated with the principal.
<i>principalName</i>	Specifies the name of the principal to which the entitlement is revoked.
<i>permSetName</i>	Specifies the name of the entitlement deleted.

4.6.40.3 Example

The following invocation deleted the entitlement myEntitlement in the stripe myApplication:

```
wls:/mydomain/serverConfig> revokeEntitlement(appStripe="myApplication",
principalClass="oracle.security.jps.service.policystore.ApplicationRole",
principalName="myPrincipalName", permSetName="myEntitlement")
```

4.6.41 listResourceTypes

Online command that lists resource types.

4.6.41.1 Description

Lists all the resource types in a specified application stripe.

4.6.41.2 Syntax

```
listResourceTypes(appStripe="appStripeName")
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where the resource types are located.

4.6.41.3 Example

The following invocation lists all resource types in the stripe myApplication:

```
wls:/mydomain/serverConfig> listResourceTypes(appStripe="myApplication")
```

4.6.42 updateTrustServiceConfig

Online command that updates the domain trust service configuration values.

4.6.42.1 Description

Updates the trust service configuration with the values passed in a file.

4.6.42.2 Syntax

```
updateTrustServiceConfig([providerName="<the proverde name>",] propsFile="<path to
the property file>")
```

Argument	Definition
<i>providerName</i>	Specifies the trust service provider name. Optional. If unspecified, it defaults to <code>trust.provider.embedded</code> .
<i>propsFile</i>	Specifies the path to the property file. Required.

4.6.42.3 Example

The following invocation updates the trust service store with the values specified in the property file myProps:

```
wls:/mydomain/serverConfig> updateTrustServiceConfig(propsFile="myProps")
```

The following is a sample property file:

```
trust.keystoreType=KSS
trust.keyStoreName=kss://<stripeName>/<keystoreName>
trust.trustStoreName=kss://<stripeName>/<truststoreName>
```

```
trust.aliasName=<aliasName>
trust.issuerName=<aliasName>
```

The type can be KSS or JKS; if a property is set to the empty string, then that property is removed from the trust service configuration.

4.7 Oracle Access Manager Commands

Use the WLST commands listed in [Table 4–6](#) to manage Oracle Access Manager (OAM)-related components, such as authorization providers, identity asserters, and SSO providers, as well as to display metrics and deployment topology, manage Oracle Access Manager server and agent configuration and logger settings.

Table 4–6 WLST Oracle Access Manager Commands

Use this command...	To...	Use with WLST...
listOAMAuthnProviderParams	List the parameters set for an Oracle Access Manager authentication or identity assertion provider.	Online
createOAMIdentityAsserter	Create a new identity asserter.	Online
updateOAMIdentityAsserter	Update an existing identity asserter.	Online
createOAMAuthenticator	Create a new authenticator.	Online
deleteOAMAuthnProvider	Delete an existing authentication provider.	Online
updateOAMAuthenticator	Update an existing authenticator.	Online
addOAMSSOProvider	Add a new SSO provider.	Online
displayTopology	List the details of deployed Oracle Access Manager Servers.	Online Offline
displayMetrics	Display the performance metrics of an Oracle Access Manager Server and domain	Online
displayOamServer	Display Oracle Access Manager Server configuration details.	Online Offline
createOamServer	Create an entry for an Oracle Access Manager Server configuration.	Online Offline
editOamServer	Edit the entry for an Oracle Access Manager Server configuration.	Online Offline
deleteOamServer	Delete the named Oracle Access Manager Server configuration.	Online Offline
displayOssoAgent	Display OSSO Agent configuration details.	Online Offline
editOssoAgent	Edit OSSO Agent configuration details.	Online Offline
deleteOssoAgent	Delete the named OSSO Agent configuration.	Online Offline
displayWebgateAgent	Display WebGate Agent configuration details.	Online Offline

Table 4–6 (Cont.) WLST Oracle Access Manager Commands

Use this command...	To...	Use with WLST...
<code>editWebgateAgent</code>	Edit 10g WebGate Agent registration details.	Online Offline
<code>deleteWebgateAgent</code>	Delete the named 10g WebGate Agent configuration.	Online Offline
<code>changeLoggerSetting</code>	Change Logger Settings.	Online Offline
<code>changeConfigDataEncryptionKey</code>	Regenerate the configuration data encryption key and re-encrypt data.	Online Offline
<code>displayUserIdentityStore</code>	Display a user identity store registration.	Online Offline
<code>editUserIdentityStore</code>	Edit a user identity store registration.	Online Offline
<code>createUserIdentityStore</code>	Create a user identity store registration.	Online Offline
<code>deleteUserIdentityStore</code>	Delete a user identity store registration.	Online Offline
<code>configRequestCacheType</code>	Configure the SSO server request cache type.	Online Offline
<code>displayRequestCacheType</code>	Display the SSO server request cache type entry.	Online Offline
<code>exportPolicy</code>	Export Oracle Access Manager policy data from a test (source) to an intermediate Oracle Access Manager file.	Online
<code>importPolicy</code>	Import Oracle Access Manager policy data from the Oracle Access Manager file specified.	Online
<code>importPolicyDelta</code>	Import Oracle Access Manager policy changes from the Oracle Access Manager file specified.	Online
<code>migratePartnersToProd</code>	Migrate partners from the source Oracle Access Manager Server to the specified target Oracle Access Manager Server.	Online
<code>exportPartners</code>	Export the Oracle Access Manager partners from the source to the intermediate Oracle Access Manager file specified.	Online
<code>importPartners</code>	Import the Oracle Access Manager partners from the intermediate Oracle Access Manager file specified.	Online
<code>configureOAAM</code>	Configure the Oracle Access Manager-Oracle Adaptive Access Manager basic integration.	Online
<code>registerOIFDAPPartner</code>	Register Oracle Identity Federation as Delegated Authentication Protocol (DAP) Partner.	Online Offline
<code>enableCoexistMode</code>	Enable the Coexist Mode.	Online
<code>disableCoexistMode</code>	Disable the Coexist Mode.	Online

Table 4–6 (Cont.) WLST Oracle Access Manager Commands

Use this command...	To...	Use with WLST...
<code>editGITOValues</code>	Edit GITO configuration parameters.	Online Offline
<code>editWebgate11gAgent</code>	Edit an 11g WebGate registration.	Online Offline
<code>deleteWebgate11gAgent</code>	Remove an 11g WebGate Agent registration.	Online Offline
<code>displayWebgate11gAgent</code>	Display an 11g WebGate Agent registration.	Online Offline
<code>displayOAMMetrics</code>	Display metrics of OAM Servers.	Online Offline
<code>updateOIMHostPort</code>	Update the Oracle Identity Manager configuration when integrated with Oracle Access Manager.	Online Offline
<code>configureOIM</code>	Creates an Agent registration specific to Oracle Identity Manager when integrated with Oracle Access Manager.	Online
<code>updateOSSOResponseCookieConfig</code>	Updates OSSO Proxy response cookie settings.	Online Offline
<code>deleteOSSOResponseCookieConfig</code>	Deletes OSSO Proxy response cookie settings.	Online Offline
<code>displaySimpleModeGlobalPassphrase</code>	Displays the simple mode global passphrase in plain text from the system configuration.	Online
<code>exportSelectedPartners</code>	Exports selected OAM Partners to the intermediate OAM file specified.	Online
<code>migrateArtifacts</code>	Migrates artifacts based on the input artifact file.	Online
<code>registerThirdPartyTAPPartner</code>	Registers any third party as a Trusted Authentication Protocol (TAP) Partner.	Online

4.7.1 listOAMAuthnProviderParams

Online command that lists the values of the parameters in effect in a domain authenticator or identity assserter.

4.7.1.1 Description

Lists the values of the parameters set for a given Oracle Access Manager authenticator or identity assserter. In the event of an error, the command returns a `WLSTException`.

4.7.1.2 Syntax

```
listOAMAuthnProviderParams (name)
```

Argument	Definition
<code>name</code>	Specifies the name of the authenticator or identity assserter.

4.7.1.3 Example

The following invocation lists the parameters and values set for the asserter named `myIdAsserter`:

```
listOAMAuthnProviderParams (name="myIdAsserter")
```

4.7.2 createOAMIdentityAsserter

Online command that creates an Oracle Access Manager identity asserter in the current domain.

4.7.2.1 Description

Creates an identity asserter with a given name in the current domain. Before executing this command, make sure that no Oracle Access Manager identity asserter is already configured in the current domain. In the event of an error, the command returns a `WLSTException`.

4.7.2.2 Syntax

```
createOAMIdentityAsserter (name)
```

Argument	Definition
<i>name</i>	Specifies the name of the new identity asserter. If no name is specified, it defaults to "OAMIdentityAsserter".

4.7.2.3 Example

The following invocation creates a new identity asserter named `OAMIdentityAsserter`:

```
createOAMIdentityAsserter (name="OAMIdentityAsserter")
```

4.7.3 updateOAMIdentityAsserter

Online command that updates the values of parameters of the Oracle Access Manager identity asserter in the current domain.

4.7.3.1 Description

Updates the value of given parameters of the domain Oracle Access Manager identity asserter. In the event of an error, the command returns a `WLSTException`.

4.7.3.2 Syntax

```
updateOAMIdentityAsserter (name, paramNameValueList)
```

Argument	Definition
<i>name</i>	Specifies the name of the Oracle Access Manager identity asserter whose parameter values to update.

Argument	Definition
<i>paramNameValueList</i>	<p>Specifies the comma-separated list of pairs of parameter name-value to be updated. The format of each pair is:</p> <pre>paramName="paramValue"</pre> <p>The parameter names that can be updated are the following only:</p> <ul style="list-style-type: none"> ▪ <code>accessGateName</code>—The name of the AccessGate used by the authenticator. ▪ <code>accessGatePwd</code>—The password to the AccessGate used by the authenticator. ▪ <code>pAccessServer</code>—The name of the primary access server. Values must have the format <code>hostName:portNumber</code>. ▪ <code>sAccessServer</code>—The name of the secondary access server. Values must have the format <code>hostName:portNumber</code>. ▪ <code>transportSecurity</code>—The mode of communication between AccessGate and OAM Access Server. ▪ <code>keystorePwd</code>—The password to access the domain key store. ▪ <code>keystorePath</code>—The absolute path of the JKS key store used for SSL communication between the authenticator and OAM Access Server. ▪ <code>simpleModePassphrase</code>—The password shared by AccessGate and OAM Access Server in simple communication mode. ▪ <code>truststorePath</code>—The absolute path of the JKS trust store used for SSL communication between the authenticator and OAM Access Server. ▪ <code>poolMaxConnections</code>—The maximum number of connections in the OAM Server connection pool. ▪ <code>poolMinConnections</code>—The minimum number of connections in the OAM Server connection pool. ▪ <code>ssoHeaderName</code>—The SSO header name. ▪ <code>controlFlag</code>—The JAAS control flag that sets up dependencies among all authenticators in the domain. Values can be only <code>REQUIRED</code>, <code>SUFFICIENT</code>, <code>REQUISITE</code>, or <code>OPTIONAL</code>. ▪ <code>appDomain</code>—The name of the application domain.

4.7.3.3 Example

The following invocation updates the parameters `accessGateName`, `accessGatePwd`, `pAccessServer`, and `ssoHeaderName` in the Oracle Access Manager identity asserter named `myIdAsserter`:

```
updateOAMIdentityAsserter (name="myIdAsserter",
accessGateName="OAM IAP AccessGate", accessGatePwd="welcome1",
pAccessServer="myhost.domain.com:5543", ssoHeaderName="OAM_SSO_HEADER")
```

4.7.4 createOAMAuthenticator

Online command that creates an Oracle Access Manager authenticator in the current domain.

4.7.4.1 Description

Creates an Oracle Access Manager authenticator with a given name in the current domain. Before executing this command, make sure that no Oracle Access Manager

authenticator is already configured in the default security domain. In the event of an error, the command returns a `WLSTException`.

4.7.4.2 Syntax

```
createOAMAuthenticator(name)
```

Argument	Definition
<i>name</i>	Specifies the name of the new authentication provider in the default domain. If no name is specified, it defaults to "OAMAuthenticator".

4.7.4.3 Example

The following invocation creates a new authentication provider named `OAMAuthenticator`:

```
createOAMAuthenticator(name="OAMAuthenticator")
```

4.7.5 deleteOAMAuthnProvider

Online command that deletes the OAM authenticator from the current domain.

4.7.5.1 Description

Deletes the OAM authenticator with a given name from the current domain. In the event of an error, the command returns a `WLSTException`.

4.7.5.2 Syntax

```
deleteOAMAuthnProvider(name)
```

Argument	Definition
<i>name</i>	Specifies the name of the authentication provider to delete.

4.7.5.3 Example

The following invocation deletes the authenticator `myAuthenticator`:

```
deleteOAMAuthnProvider(name="myAuthenticator")
```

4.7.6 updateOAMAuthenticator

Online command that updates the values of parameters of the Oracle Access Manager authenticator in the current domain.

4.7.6.1 Description

Updates the value of given parameters of the domain Oracle Access Manager authenticator. In the event of an error, the command returns a `WLSTException`.

4.7.6.2 Syntax

```
updateOAMAuthenticator(name, paramNameValueList)
```

Argument	Definition
<i>name</i>	Specifies the name of the Oracle Access Manager authenticator whose parameter values to update.

Argument	Definition
<i>paramNameValueList</i>	<p>Specifies the comma-separated list of pairs of parameter name-value to be updated. The format of each pair is</p> <pre>paramName= 'paramValue'</pre> <p>The only parameter names that can be updated are the following:</p> <ul style="list-style-type: none"> ▪ <code>accessGateName</code>—The name of the AccessGate used by the authenticator. ▪ <code>accessGatePwd</code>—The password to the AccessGate used by the authenticator. ▪ <code>pAccessServer</code>—The name of the primary access server. Values must have the format <code>hostName:portNumber</code>. ▪ <code>sAccessServer</code>—The name of the secondary access server. Values must have the format <code>hostName:portNumber</code>. ▪ <code>transportSecurity</code>—The mode of communication between AccessGate and OAM Access Server: <code>open</code>, <code>simple</code>, or <code>cert</code>. ▪ <code>keystorePwd</code>—The password to access the domain key store. ▪ <code>keystorePath</code>—The absolute path of the JKS key store used for SSL communication between the authenticator and OAM Access Server. ▪ <code>simpleModePassphrase</code>—The password shared by AccessGate and OAM Access Server in simple communication mode. ▪ <code>truststorePath</code>—The absolute path of the JKS trust store used for SSL communication between the authenticator and OAM Access Server. ▪ <code>poolMaxConnections</code>—The maximum number of connections in the OAM Server connection pool. ▪ <code>poolMinConnections</code>—The minimum number of connections in the OAM Server connection pool. ▪ <code>useRetNameAsPrincipal</code>—Specifies whether the user name retrieved from the OAM authenticator should be used as the name of the Principal in the Subject. ▪ <code>controlFlag</code>—The JAAS control flag that sets up dependencies among all authenticators in the domain. Values can be only <code>REQUIRED</code>, <code>SUFFICIENT</code>, <code>REQUISITE</code>, or <code>OPTIONAL</code>. ▪ <code>appDomain</code>—The name of the application domain.

4.7.6.3 Example

The following invocation updates the parameters `accessGateName`, `accessGatePwd`, and `pAccessServer` in the Oracle Access Manager authenticator named `myAuthenticator`:

```
updateOAMAuthenticator(name="myAuthenticator",
accessGateName="OAM AP AccessGate", accessGatePwd="welcome1",
pAccessServer="myhost.domain.com:5543")
```

4.7.7 addOAMSSOProvider

Online command that adds an Oracle Access Manager SSO provider with the given login URI, logout URI, and auto-login URI.

4.7.7.1 Description

Adds an SSO provider with the given login URI, logout URI, and auto-login URI. This command modifies the domain `jps-config.xml` by adding an Oracle Access Manager SSO service instance with the required properties. In the event of an error, the command returns a `WLSTException`.

4.7.7.2 Syntax

```
addOAMSSOProvider(loginuri, logouturi, autologinuri, beginimpuri, endimpuri)
```

Argument	Definition
<i>loginuri</i>	Required. Specifies the URI of the login page and triggers SSO authentication.
<i>logouturi</i>	Optional. Specifies the URI of the logout page and logs the signed-on user out. If unspecified, defaults to <code>logouturi=NONE</code> . Set to "" to ensure that ADF security calls the OPSS logout service, which uses the implementation of the class <code>OAMSSOServiceImpl</code> to clear the cookie <code>ObsSOCookie</code> . More generally, an ADF-secured web application that would like to clear cookies without logging out the user should use this setting.
<i>autologinuri</i>	Required. Specifies the URI of the autologin page. Optional. If unspecified, it defaults to <code>autologin=NONE</code> .
<i>beginimpuri</i>	Optional. Specifies the URI that triggers the impersonation SSO session.
<i>endimpuri</i>	Optional. Specifies the URI that terminates the impersonation SSO session.

4.7.7.3 Example

The following invocation adds an SSO provider with the passed URIs; note the special behavior implied by the setting `logouturi=""` and the impersonation parameters, as explained in the above table:

```
addOAMSSOProvider(loginuri="/${app.context}/adfAuthentication",
logouturi="/oamssso/logout.html",
beginimpuri="https://login.acme.com/impersonationInit.html"
endimpuri="https://login.acme.com/impersonationTerm.html")
autologin="/fooBar.cgi")
```

4.7.8 displayTopology

Online and offline command that displays the information about all the OAM Servers in a deployment.

4.7.8.1 Description

Lists the topology of deployed OAM Servers. There are no arguments for this command.

4.7.8.2 Syntax

```
displayTopology
```

4.7.8.3 Example

The following invocation lists the details of all deployed OAM Servers, as described above:

`displayTopology`

4.7.9 displayMetrics

Online command that displays the performance metrics of an OAM Server and domain.

4.7.9.1 Description

Displays the performance metrics of an OAM Server and domain specific to collectors, including host, process, and server names. There are no arguments for this command.

If none of the arguments are specified all the details of all the servers and collectors are displayed.

4.7.9.2 Syntax

`displayMetrics()`

4.7.9.3 Example

The following invocation lists all metrics specific to named collectors, as described above:

`displayMetrics()`

4.7.10 displayOamServer

Online and offline command that displays OAM Server registration details.

4.7.10.1 Description

Displays OAM Server registration details, including the host, port, registration name, OAM Proxy port and server ID, and, optionally, the OAM Proxy shared secret.

The scope of this command is an instance, only. The scope is not an argument.

4.7.10.2 Syntax

`displayOamServer(host,port)`

Argument	Definition
<i>host</i>	Mandatory. Specifies the name of the OAM Server host.
<i>port</i>	Mandatory. Specifies the listening port of the OAM Server host.
<i>domainhome</i>	Offline mode: Mandatory Online mode: Optional

4.7.10.3 Example

The following invocation lists all metrics specific to named collectors, as described above:

`displayOamServer(host="my_host", port="15000", domainHome="domainHome1")`

4.7.11 createOamServer

Online and offline command that creates an OAM Server entry in the system configuration.

4.7.11.1 Description

Creates an OAM Server registration, including the host, port, registration name, OAM Proxy port and server ID, and, optionally, the OAM Proxy shared secret.

The scope of this command is an instance, only. The scope is not an argument

4.7.11.2 Syntax

```
createOamServer(host, port, paramNameValueList)
```

Argument	Definition
<i>host</i>	Mandatory. Specifies the name of the OAM Server host.
<i>port</i>	Mandatory. Specifies the listening port of the OAM Server host.
<i>domainHome</i>	Offline mode: Mandatory Online mode: Optional
<i>paramNameValueList</i>	Specifies the comma-separated list of parameter name-value pairs. The format of each pair is: paramName='paramValue' Mandatory: <ul style="list-style-type: none"> ▪ configurationProfile—The name of this instance registration, which appears under Server Instances on the System Configuration tab in the OAM Administration Console. ▪ oamProxyPort—The listening port of this instance. ▪ oamProxyServerID—The name of the OAM Proxy for this server instance, which will appear under the OAM Proxy sub tab of the server instance in the OAM Administration Console. ▪ siteName—siteName/serverName for the instance.

4.7.11.3 Example

The following invocation creates a configuration for *your_host* with listening port 15000. The configuration entry in the Administration Console will be *oam_server1*. The OAM Proxy port is 3004 and the OAM Proxy Server ID is *AccessServerConfigProxy*:

```
createOamServer(host="my_host", port="15000", configurationProfile="oam_server1", oamProxyPort="3004", oamProxyServerID="ProxyID", siteName="siteName1", domainHome="domainHome1")
```

4.7.12 editOamServer

Online and offline command that enables you to edit OAM Server registration details.

4.7.12.1 Description

Edits the registration for an OAM Server, which can include the host, port, registration name, OAM Proxy port and server ID, and, optionally, the OAM Proxy shared secret.

The scope of this command is an instance, only. The scope is not an argument.

4.7.12.2 Syntax

```
editOamServer(name, port, paramNameValueList)
```

Argument	Definition
<i>name</i>	Mandatory. Specifies the name of the OAM Server host.
<i>port</i>	Mandatory. Specifies the port number of the OAM Server host.
<i>domainHome</i>	Offline mode: Mandatory Online mode: Optional
<i>paramNameValueList</i>	Specifies the comma-separated list of parameter name-value pairs. The format of each pair is: <code>paramName='paramValue'</code> Mandatory: <ul style="list-style-type: none"> ■ <code>configurationProfile</code>—The name of this instance registration, which appears under Server Instances on the System Configuration tab in the OAM Administration Console. ■ <code>oamProxyPort</code>—The listening port of this instance. ■ <code>oamProxyServerID</code>—The name of the OAM Proxy for this server instance, which will appear under the OAM Proxy sub tab of the server instance in the OAM Administration Console. ■ <code>siteName</code>—<code>siteName/serverName</code> for the instance.

4.7.12.3 Example

You can use any of the optional attributes to change current settings. The following invocation enables you to add the OAM Proxy shared secret to the configuration entry `oam_server1`.

```
editOamServer(name="oam_server1", port="15000",configurationProfile=
"oam_server1", oamProxyPort="3004",oamProxyServerID="Proxy1",
siteName="siteName1",domainHome="domainHome1")
```

4.7.13 deleteOamServer

Online and offline command that enables you to delete the named OAM Server registration.

4.7.13.1 Description

Deletes an entire OAM Server configuration.

The scope of this command is an instance, only. The scope is not an argument.

4.7.13.2 Syntax

```
deleteOamServer(host,port)
```

Argument	Definition
<i>host</i>	Mandatory. Specifies the name of the OAM Server host.
<i>port</i>	Mandatory. Specifies the listening port of the OAM Server host.
<i>domainhome</i>	Offline mode: Mandatory Online mode: Optional

4.7.13.3 Example

The following invocation enables you to delete the OAM Server registration for `oam_server1` with listening port 15000.

```
deleteOamServer(host="oam_server1",port="15000",domainHome="domainHome1")
```

4.7.14 displayOssoAgent

Online and offline command that displays OSSO Agent configuration details.

4.7.14.1 Description

Displays OSSO Agent registration details, which also appear in the OAM Administration Console.

The scope of this command is an instance, only. The scope is not an argument

4.7.14.2 Syntax

```
displayOssoAgent (agentName)
```

Argument	Definition
<i>agentName</i>	Mandatory. Specifies the name of the OSSO Agent.
<i>domainhome</i>	Offline mode: Mandatory Online mode: Optional

4.7.14.3 Example

The following invocation displays the OSSO Agent's registration information:

```
displayOssoAgent (agentName="OSSOAgent1",domainHome="domainHome1")
```

4.7.15 editOssoAgent

Online and offline command that enables you to edit an OSSO Agent registration.

4.7.15.1 Description

Changes OSSO Agent configuration details, including the Site Token, Success URL, Failure URL, Home URL, Logout URL, Start Date, End Date, Administrator ID, and Administrator Info.

The scope of this command is an instance, only. The scope is not an argument

4.7.15.2 Syntax

```
editOssoAgent (agentName, paramNameValueList)
```

Argument	Definition
<i>agentName</i>	Mandatory. Specifies the name of the OSSO Agent.
<i>domainhome</i>	Offline mode: Mandatory Online mode: Optional

Argument	Definition
<i>paramNameValueList</i>	<p>Specifies the comma-separated list of parameter name-value pairs to be updated. The format of each pair is:</p> <pre>paramName='paramValue'</pre> <p>Optional:</p> <ul style="list-style-type: none"> ▪ <i>siteToken</i>—The Application Token used by the partner when requesting authentication. ▪ <i>successUrl</i>—The redirect URL to be used upon successful authentication. ▪ <i>failureUrl</i>—The redirect URL to be used if authentication fails. ▪ <i>homeUrl</i>—The redirect URL to be used for the Home page after authentication. ▪ <i>logoutUrl</i>—The redirect URL to be used when logging out. This redirects the user to the global logout page on the server ▪ <i>startDate</i>—First month, day, and year for which login to the application is allowed by the server. ▪ <i>endDate</i>—Final month, day, and year for which login to the application is allowed by the server. ▪ <i>adminId</i>—Administrator login ID for this mod_osso instance. ▪ <i>adminInfo</i>—Administrator details for this mod_osso instance.

4.7.15.3 Example

The following invocation changes the Administrator ID and information in the registration entry for *OSSOAgent1*:

```
editOssoAgent(agentName="OSSOAgent1", siteToken="siteToken",
successUrl="successUrl", failureUrl="failureUrl", homeUrl="homeUrl",
logoutUrl="logoutUrl", startDate="2009-12-10", endDate="2012-12-30",
adminId= 345", adminInfo="Agent11", domainHome="domainHome1")
```

4.7.16 deleteOssoAgent

Online and offline command that enables you to delete an OSSO Agent registration.

4.7.16.1 Description

Removes an OSSO Agent configuration.

The scope of this command is an instance, only. The scope is not an argument

4.7.16.2 Syntax

```
deleteOssoAgent (agentName)
```

Argument	Definition
<i>agentName</i>	Mandatory. Specifies the name of the OSSO Agent.
<i>domainhome</i>	Offline mode: Mandatory Online mode: Optional

4.7.16.3 Example

The following invocation removes the OSSO Agent named *OSSOAgent1*:


```
deleteOssoAgent(agentName="OSSOAgent1", domainHome="domainHome1")
```

4.7.17 displayWebgateAgent

Online and offline command that displays a 10g WebGate registration.

4.7.17.1 Description

Displays all 10g WebGate registration details, which can also be seen in the OAM Administration Console.

The scope of this command is an instance, only. The scope is not an argument

4.7.17.2 Syntax

```
displayWebgateAgent(agentName)
```

Argument	Definition
<i>agentName</i>	Mandatory. Specifies the name of the WebGate Agent.
<i>domainhome</i>	Offline mode: Mandatory Online mode: Optional

4.7.17.3 Example

The following invocation displays registration information for my_WebGate:

```
displayWebgateAgent(agentName="my_Webgate", domainHome="domainHome1")
```

4.7.18 editWebgateAgent

Online and offline command that enables you to edit a 10g WebGate registration.

4.7.18.1 Description

Enables you to change 10g WebGate Agent registration details.

The scope of this command is an instance, only. The scope is not an argument

4.7.18.2 Syntax

```
editWebgateAgent(agentName, paramNameValueList)
```

Argument	Definition
<i>agentName</i>	Mandatory. Specifies the name of the WebGate Agent.
<i>domainhome</i>	Offline mode: Mandatory Online mode: Optional

Argument	Definition
<i>paramNameValueList</i>	<p>Specifies the comma-separated list of parameter name-value pairs to be updated. The format of each pair is:</p> <pre>paramName='paramValue'</pre> <p>Mandatory:</p> <ul style="list-style-type: none"> ▪ <code>agentId</code>—Name of the OAM Agent (WebGate). <p>Optional:</p> <ul style="list-style-type: none"> ▪ <code>accessClientPassword</code>—An optional password for this WebGate Agent. ▪ <code>state</code>—Whether the OAM Agent is enabled or disabled. ▪ <code>preferredHost</code>—Prevents security holes that can be created if a host's identifier is not included in the Host Identifiers list. For virtual hosting, you must use the Host Identifiers feature. ▪ <code>aaaTimeoutThreshold</code>—Number (in seconds) to wait for a response from the OAM Run-time Server. If this parameter is set, it is used as an application TCP/IP timeout instead of the default TCP/IP timeout. Default = -1 (default network TCP/IP timeout is used). ▪ <code>security</code>—Level of transport security to and from the OAM Run-time Server: open, simple, or cert. ▪ <code>primaryCookieDomain</code>—The Web server domain on which the OAM Agent is deployed, for instance, <i>acompany.com</i>. ▪ <code>maxConnections</code>—The maximum number of connections that this OAM Agent can establish with the OAM Server. This number must be the same as (or greater than) the number of connections that are actually associated with this agent. Default = 1. ▪ <code>maxCacheElements</code>—Number of elements maintained in the cache. Cache elements are URLs or Authentication Schemes. The value of this setting refers to the maximum consolidated count for elements in both of these caches. Default = 10000. ▪ <code>cacheTimeout</code>—Amount of time cached information remains in the OAM Agent cache when the information is neither used nor referenced. Default = 1800 (seconds). ▪ <code>cookieSessionTime</code>—Amount of time that the ObSSOCookie persists. Default = 3600 (seconds)*. ▪ <code>maxSessionTime</code>—Maximum amount of time, in seconds, that a user's authentication session is valid regardless of their activity. At the expiration of this time, the user is re-challenged for authentication. This is a forced logout. Default = 3600 (seconds). A value of 0 disables this timeout setting. ▪ <code>idleSessionTimeout</code>—Amount of time in seconds that a user's authentication session remains valid without accessing any OAM Agent protected resources. Default = 3600 (seconds). A value of 0 disables this timeout setting. ▪ <code>failoverThreshold</code>—Number representing the point when this OAM Agent opens connections to a Secondary OAM Server. Default = 1.

4.7.18.3 Example

You can alter any or all of the settings. Use the following invocation to change specific information in the WebGate Agent registration, including the Agent ID, state, maximum connections, OAM Server timeout, primary cookie domain, cache time out,

cookie session timeout, maximum session timeout, idle session timeout, and failover threshold, as follows:

```
editWebgateAgent (agentName="my_WebGate", agentId="WebGate2", state=
"enabled", maxConnections="2", aaaTimeOutThreshold="2",
primaryCookieDomain="adomain.com", cacheTimeOut="1200",
cookieSessionTime=1500, maxSessionTime=1500, idleSessionTimeout=
"1500", failoverThreshold="25", domainHome="domainHome1")
```

4.7.19 deleteWebgateAgent

Online and offline command that enables you to delete a 10g WebGate Agent registration.

4.7.19.1 Description

Removes an 10g WebGate Agent registration.

The scope of this command is an instance, only. The scope is not an argument

4.7.19.2 Syntax

```
deleteWebgateAgent (agentName)
```

Argument	Definition
<i>agentName</i>	Mandatory. Specifies the name of the WebGate Agent.
<i>domainhome</i>	Offline mode: Mandatory Online mode: Optional

4.7.19.3 Example

The following invocation removes the WebGate Agent named `my_WebGate`:

```
deleteWebgateAgent (agentName="my_WebGate", domainHome="domainHome1")
```

4.7.20 changeLoggerSetting

Online and offline command that changes the logger level.

4.7.20.1 Description

Changes the level of one or more, or all, loggers.

The scope of this command is an instance, only. The scope is not an argument.

4.7.20.2 Syntax

```
changeLoggerSetting (loggerName='', loggerLevel='')
```

Argument	Definition
<i>loggerName</i>	Optional. Specifies the OAM logger name. Multiple OAM logger names can be specified, separated by commas, or you can use the wildcard (*) character to specify all OAM collectors, which is the default.
<i>loggerLevel</i>	SEVERE, WARNING, INFO, CONFIG, FINE.

4.7.20.3 Example

The following invocation changes the logger level to SEVERE:

```
changeLoggerSetting(loggerName=" ", loggerLevel=SEVERE)
```

4.7.21 changeConfigDataEncryptionKey

Offline command that regenerates the configuration data encryption key.

4.7.21.1 Description

Regenerates the configuration data encryption key, re-encrypts the configuration data using the new key, and outputs attribute information of the identity store.

The scope of this command is an instance, only. The scope is not an argument.

4.7.21.2 Syntax

```
changePasswordEncKey (oldpassword='', newPassword='')
```

Argument	Definition
<i>oldPassword</i>	Mandatory. Specifies the password that retrieves the current encryption key.
<i>newPassword</i>	Mandatory. Defines a new password that protects the newly generated encryption key.

4.7.21.3 Example

The following invocation changes the old and new password, regenerates the key, and re-encrypts the configuration data:

```
changePasswordEncKey(oldpassword="oldpassword",  
newPassword="newpassword")
```

4.7.22 displayUserIdentityStore

Online and offline command that displays user identity store registration information.

4.7.22.1 Description

Displays information of the user identity store registered with Oracle Access Manager.

The scope of this command is an instance, only. The scope is not an argument.

4.7.22.2 Syntax

```
displayUserIdentityStore(name)
```

Argument	Definition
<i>name</i>	Mandatory. Specifies the name of the LDAP user identity store.
<i>domainhome</i>	Offline mode: Mandatory Online mode: Optional

4.7.22.3 Example

The following invocation displays registration details of the user identity store:

```
displayUserIdentityStore(name="ID_store1", domainHome="domainHome1")
```

4.7.23 editUserIdentityStore

Online and offline command that changes attributes of the user identity store for Oracle Access Manager.

4.7.23.1 Description

Changes one or more attributes of the user identity store registered with Oracle Access Manager.

The scope of this command is an instance, only. The scope is not an argument.

4.7.23.2 Syntax

```
editUserIdentityStore (name, paramNameValueList)
```

Argument	Definition
<i>name</i>	Mandatory. Specifies the unique name of the LDAP user identity store (only upper and lower case alpha characters and numbers).
<i>domainhome</i>	Offline mode: Mandatory Online mode: Optional
<i>paramNameValueList</i>	Specifies the comma-separated list of parameter name-value pairs. The format of each pair is: paramName= 'paramValue' Include one or more of the following parameter name-value pairs, in addition to those in createUserIdentityStore , to change the OAM user identity store configuration: <ul style="list-style-type: none"> ▪ <i>userFilterObjectClasses</i>—List of user filter object classes (separated by semi-colon). ▪ <i>groupFilterObjectClasses</i>—List of group filter object classes (separated by semi-colon). ▪ <i>referralPolicy</i>—LDAP referral policy (either "follow", "ignore" or "throw"). ▪ <i>searchTimeLimit</i>—Time limit in seconds for LDAP Search operation. ▪ <i>minConnections</i>—Minimum number of connections in the connection pool. ▪ <i>maxConnections</i>—Maximum number of connections in the connection pool. ▪ <i>connectionWaitTimeout</i>—Number of seconds to wait for obtaining a connection from the pool. ▪ <i>connectionRetryCount</i>—Number of attempts to establish a connection to identity store. ▪ <i>groupNameAttr</i>—Name of the attribute to look up the user groups. For example: <i>ou=people,ou=myrealm,dc=base_domain</i> ▪ <i>groupCacheEnabled</i>—Toggle (true/false) to enable LDAP group cache. ▪ <i>groupCacheSize</i>—Number of entries in LDAP group cache. ▪ <i>groupCacheTTL</i>—Total time to live for each entry of LDAP group cache.

4.7.23.3 Example

The following invocation changes the LDAP URL of the user identity store for OAM:

```
editUserIdentityStore(name="identity_store_name",  
LDAP_url="ldap://localhost:7003", domainHome="domainHome1")
```

4.7.24 createUserIdentityStore

Online and offline command that creates a user identity store registration for Oracle Access Manager.

4.7.24.1 Description

Creates an entry for a new user identity store to be registered with Oracle Access Manager.

The scope of this command is an instance, only. The scope is not an argument.

4.7.24.2 Syntax

```
createUserIdentityStore(name=, paramNameValueList)
```

Argument	Definition
<i>name</i>	Mandatory. Specifies the unique name of the LDAP user identity store (only upper and lower case alpha characters and numbers).
<i>domainhome</i>	Offline mode: Mandatory Online mode: Optional

Argument	Definition
<i>paramNameValueList</i>	<p>Specifies the comma-separated list of parameter name-value pairs. The format of each pair is:</p> <pre>paramName='paramValue'</pre> <p>Mandatory:</p> <ul style="list-style-type: none"> ▪ <i>name</i>—The name for this user ID store. ▪ <i>principal</i>—The login ID of the LDAP administrator. For example, <i>cn=Admin</i>. ▪ <i>credential</i>—The password of the Principal, which is encrypted for security. ▪ <i>type</i>—The type of the LDAP ID store to be created. ▪ <i>userAttr</i>—User attributes of the store. ▪ <i>usersearchbase</i>—The node under which user data is stored in the LDAP ID store to be created. For example: <i>cn=users</i>. ▪ <i>groupSearchBase</i>—The node under which group data is stored in the LDAP ID store to be created. Mandatory Attribute. For example: <i>cn=groups</i>. ▪ <i>ldapUrl</i>—The URL for the LDAP host, including port number of the LDAP ID store to be created. For example, <i>ldap://localhost:7001</i>. <p>Optional:</p> <ul style="list-style-type: none"> ▪ <i>roleSecAdmin</i>—Name of the Admin group with all privileges for LDAP ID store. ▪ <i>roleSysMonitor</i>—Name of the Admin group with read-only privileges for LDAP ID store to be created. ▪ <i>roleSysManager</i>—Name of the Admin group with day-to-day operational privileges for LDAP ID store to be created. ▪ <i>ldapProvider</i>—A supported LDAP provider. For example, OVD. ▪ <i>isPrimary</i>—The designation of the primary User Identity Store. Boolean field. ▪ <i>userIDProvider</i>—User Identity Provider of the store to be created. ▪ <i>domainHome</i>—Domain Home location.

4.7.24.3 Example

The following invocation creates a new Oracle Internet Directory user identity store definition for use with Oracle Access Manager:

```
createUserIdentityStore (name="Name1", principal="Principal1",
credential="Credential1", type="OID", userAttr="userAttr1",
ldapProvider="ldapProvider", roleSecAdmin="roleSecAdmin1",
roleSysMonitor="roleSysMonitor", roleSysManager="roleSysManager",
roleAppAdmin="roleAppAdmin", userSearchBase="cn=users",
ldapUrl="ldapUrl", isPrimary="isPrimary", userIDProvider="userIDProvider",
groupSearchBase="cn=groups", domainHome="domainHome1")
```

4.7.25 deleteUserIdentityStore

Online and offline command that removes a Oracle Access Manager user identity store registration.

4.7.25.1 Description

Deletes the user identity store registered with Oracle Access Manager.

The scope of this command is an instance, only. The scope is not an argument.

4.7.25.2 Syntax

```
deleteUserIdentityStore(name)
```

Argument	Definition
<i>name</i>	Mandatory. Specifies the name of the LDAP user identity store to be removed.
<i>domainhome</i>	Offline mode: Mandatory Online mode: Optional

4.7.25.3 Example

The following invocation deletes the registration of the user identity store:

```
deleteUserIdentityStore(name="identity_store", domainHome="domainHome1")
```

4.7.26 configRequestCacheType

Online and offline command that configures the SSO server request cache type.

4.7.26.1 Description

Configures the SSO server request cache type.

The scope of this command is an instance, only. The scope is not an argument.

4.7.26.2 Syntax

```
configRequestCacheType(type)
```

Argument	Definition
<i>type</i>	Mandatory. Specifies requestCacheType. requestCacheType—The value of request cache type: BASIC or COOKIE.

4.7.26.3 Example

The following invocation identifies the request cache type as Cookie:

```
configRequestCacheType(type="COOKIE")
```

4.7.27 displayRequestCacheType

Online and offline command that displays the SSO server request cache type.

4.7.27.1 Description

Displays the SSO server request cache type entry.

The scope of this command is an instance, only. The scope is not an argument.

4.7.27.2 Syntax

```
displayRequestCacheType(domainHome)
```


Argument	Definition
<i>type</i>	Mandatory. Specifies requestCacheType. requestCacheType—The value of request cache type: BASIC or COOKIE.
<i>domainhome</i>	Offline mode: Mandatory Online mode: Optional

4.7.27.3 Example

The following invocation displays the request cache type.

```
displayRequestCacheType(domainHome="domainHome")
```

4.7.28 exportPolicy

Online only command that exports OAM policy data from a test (source) environment to the intermediate Oracle Access Manager file specified.

4.7.28.1 Description

Exports OAM policy data from a test (source) environment to the intermediate Oracle Access Manager file.

The scope of this command is an instance, only. The scope is not an argument.

4.7.28.2 Syntax

```
exportPolicy(pathTempOAMPolicyFile)
```

Argument	Definition
<i>pathTempOAMPolicyFile</i>	Mandatory. Specifies the path to the temporary Oracle Access Manager file.

4.7.28.3 Example

The following invocation specifies the path to the temporary file used when exporting policy data from a test (source) environment.

```
exportPolicy(pathTempOAMPolicyFile="oam_policy.xml")
```

4.7.29 importPolicy

Online only command that imports the OAM policy data from the intermediate Oracle Access Manager file specified.

4.7.29.1 Description

Imports the OAM policy data from the intermediate Oracle Access Manager file specified.

The scope of this command is an instance, only. The scope is not an argument.

4.7.29.2 Syntax

```
importPolicy(pathTempOAMPolicyFile)
```

Argument	Definition
<i>pathTempOAMPolicyFile</i>	Mandatory. Specifies the path to the temporary OAM file.

4.7.29.3 Example

The following invocation specifies the path to the temporary file used when importing policy data to a production (target).

```
importPolicy(pathTempOAMPolicyFile="oam_policy.xml")
```

4.7.30 importPolicyDelta

Online only command that imports the OAM policy changes from the intermediate Oracle Access Manager file specified.

4.7.30.1 Description

Imports the OAM policy changes from the intermediate Oracle Access Manager file specified.

The scope of this command is an instance, only. The scope is not an argument.

4.7.30.2 Syntax

```
importPolicyDelta(pathTempOAMPolicyFile)
```

Argument	Definition
<i>pathTempOAMPolicyFile</i>	Mandatory. Specifies the path to the temporary Oracle Access Manager file.

4.7.30.3 Example

The following invocation specifies the path to the temporary file used when importing only changed policy data to a production (target).

```
importPolicyDelta(pathTempOAMPolicyFile="oam_policy_delta.xml")
```

4.7.31 migratePartnersToProd

Online only command that migrates partners from the current (source) OAM Server to the specified (target) OAM Server.

4.7.31.1 Description

Migrates partners from the current (source) OAM Server to the specified (target) OAM Server.

The scope of this command is an instance, only. The scope is not an argument.

4.7.31.2 Syntax

```
migratePartnersToProd(prodServerHost, prodServerPort, prodServerAdminUser, prodServerAdminPwd)
```

Argument	Definition
<i>prodServerHost</i>	Host name of the target OAM Server to which partners are to be migrated.

Argument	Definition
<i>prodServerPort</i>	Port of the target OAM Server to which partners are to be migrated.
<i>prodServerAdminUser</i>	Administrator of the target OAM Server to which partners are to be migrated.
<i>prodServerAdminPwd</i>	Target OAM Server administrator's password.

4.7.31.3 Example

The following invocation specifies the required information.

```
migratePartnersToProd(prodServerHost="host",prodServerPort="port",
prodServerAdminUser="weblogic",prodServerAdminPwd="welcome")
```

4.7.32 exportPartners

Online only command that exports Oracle Access Manager partners from the source to the intermediate Oracle Access Manager file specified.

4.7.32.1 Description

Exports the Oracle Access Manager partners from the source to the intermediate Oracle Access Manager file specified.

The scope of this command is an instance, only. The scope is not an argument.

4.7.32.2 Syntax

```
exportPartners(pathTempOAMPartnerFile)
```

Argument	Definition
<i>pathTempOAMPartnerFile</i>	Mandatory. Specifies the path to the temporary Oracle Access Manager partner file.

4.7.32.3 Example

The following invocation specifies the path to the intermediate OAM partners file.

```
exportPartners(pathTempOAMPartnerFile="oam_partners.xml")
```

4.7.33 importPartners

Online only command that imports Oracle Access Manager partners from the intermediate Oracle Access Manager file specified.

4.7.33.1 Description

Imports the OAM partners from the intermediate Oracle Access Manager file specified.

The scope of this command is an instance, only. The scope is not an argument.

4.7.33.2 Syntax

```
importPartners(pathTempOAMPartnerFile)
```

Argument	Definition
<i>pathTempOAMPartnerFile</i>	Mandatory. Specifies the path to the temporary OAM partner file.

4.7.33.3 Example

The following invocation specifies the path to the intermediate OAM partners file.

```
importPartners (pathTempOAMPartnerFile="oam_partners.xml")
```

4.7.34 configureOAAM

Online only command that configures the Oracle Access Manager-Oracle Adaptive Access Manager basic integration.

4.7.34.1 Description

Configures the OAM-OAAM basic integration.

The scope of this command is an instance, only. The scope is not an argument.

4.7.34.2 Syntax

```
configureOAAM(dataSourceName,paramNameValueList)
```

Argument	Definition
<i>dataSourceName</i>	Name of the data source to be created
<i>paramNameValueList</i>	Specifies the comma-separated list of parameter name-value pairs. The format of each pair is: paramName='paramValue' Mandatory: <ul style="list-style-type: none"> ▪ <i>hostName</i>—The name of the database host. ▪ <i>port</i>—Database port. ▪ <i>sid</i>—The database sid (database identifier). ▪ <i>userName</i>—OAAM schema name. ▪ <i>passWord</i>—OAAM schema password. Optional: <ul style="list-style-type: none"> ▪ <i>maxConnectionSize</i>—Max connection reserve time out size. ▪ <i>maxPoolSize</i>—Maximum size for connection pool. ▪ <i>serverName</i>—Target server for the data source.

4.7.34.3 Example

The following invocation configures the Oracle Access Manager-Oracle Adaptive Access Manager basic integration.

```
configureOAAM(dataSourceName = "MyOAAMDS", hostName = "host.us.co.com",
port = "1521", sid = "sid", userName = "username", passWord = "password",
maxConnectionSize = None, maxPoolSize = None, serverName = "oam_server1")
```

4.7.35 registerOIFDAPPartner

Online and offline command that registers Oracle Identity Federation as a Delegated Authentication Protocol (DAP) Partner.

4.7.35.1 Description

Registers Oracle Identity Federation as Delegated Authentication Protocol (DAP) Partner.

The scope of this command is an instance only. The scope is not an argument.

4.7.35.2 Syntax

```
registerOIFDAPPartner()
```

Argument	Definition
<i>paramNameValueList</i>	<p>Specifies the comma-separated list of parameter name-value pairs. The format of each pair is:</p> <pre>paramName='paramValue'</pre> <p>Mandatory:</p> <p>Include the following parameter name-value pairs to create a new OAM user identity store configuration:</p> <ul style="list-style-type: none"> ▪ <code>keystoreLocation</code>—Location of the Keystore file (generated at the OIF Server). ▪ <code>logoutURL</code>—The OIF Server's logout URL. <p>Optional:</p> <ul style="list-style-type: none"> ▪ <code>rolloverInterval</code>—The Rollover Interval for the keys used to encrypt/decrypt SASSO Tokens.

4.7.35.3 Example

The following invocation illustrates use of all parameters.

```
registerOIFDAPPartner(keystoreLocation="/scratch/keystore",
logoutURL="http://<oifhost>:<oifport>/fed/user/sploosso?doneURL=http://<oamhost>:
<oam port>/ngam/server/pages/logout.jsp", rolloverTime="526")
```

4.7.36 enableCoexistMode

Online command that enables the Coexist Mode.

4.7.36.1 Description

Enables the Coexist Mode.

The scope of this command is an instance, only. The scope is not an argument.

4.7.36.2 Syntax

```
enableCoexistMode()
```

4.7.36.3 Example

The following invocation enables the Coexist Mode.

```
enableCoexistMode
```

4.7.37 disableCoexistMode

Online command that disables the Coexist Mode.

4.7.37.1 Description

Disables the Coexist Mode.

The scope of this command is an instance, only. The scope is not an argument.

4.7.37.2 Syntax

```
disableCoexistMode()
```

4.7.37.3 Example

The following invocation enables the Coexist Mode.

```
disableCoexistMode
```

4.7.38 editGITOVales

Online and offline command that edits GITO configuration parameters.

4.7.38.1 Description

Edits GITO configuration parameters.

The scope of this command is an instance, only. The scope is not an argument.

4.7.38.2 Syntax

```
editGITOVales(gitoEnabled, paramNameValueList)
```

Argument	Definition
<i>gitoEnabled</i>	True (or false). Allows (or denies) user to set GITO enabled property.
<i>domainhome</i>	Offline mode: Mandatory Online mode: Optional
<i>paramNameValueList</i>	Specifies the comma-separated list of parameter name-value pairs. The format of each pair is: <code>paramName='paramValue'</code> Mandatory: Include the following parameter name-value pairs to create a new OAM user identity store configuration: <ul style="list-style-type: none"> ▪ <code>gitoCookieDomain</code>—Allows user to set the GITO cookie domain entry. Optional: <ul style="list-style-type: none"> ▪ <code>gitoCookieName</code>—Allows user to set the GITO cookie name. ▪ <code>gitoVersion</code>—Allows user to set the GITO version. Can be ONLY v1.0 or v3.0. ▪ <code>gitoTimeout</code>—Allows user to set the GITO timeout value. ▪ <code>gitoSecureCookieEnabled</code>—True (or false). Allows (or denies) user to set the GITO cookie enabled property.

4.7.38.3 Example

The following invocation edits GITO configuration parameters.

```
editGITOVales(gitoEnabled="true",gitoCookieDomain=".abc.com",gitoCookieName="ABC",gitoVersion="v1.0",gitoTimeout="20",gitoSecureCookieEnabled="false",domainHome="/
```

```
abc/def/ijk")\n
```

4.7.39 editWebgate11gAgent

Online and offline command that edits an 11g WebGate registration.

4.7.39.1 Description

Edits an 11g WebGate registration.

The scope of this command is an instance, only. The scope is not an argument.

4.7.39.2 Syntax

```
editWebgate11gAgent(agentname, paramNameValueList)
```

Argument	Definition
<i>agentname</i>	Name of the registered OAM 11g WebGate agent to be edited.
<i>domainhome</i>	Offline mode: Mandatory Online mode: Optional

Argument	Definition
<i>paramNameValueList</i>	<p>Specifies the comma-separated list of parameter name-value pairs. The format of each pair is:</p> <pre>paramName='paramValue'</pre> <p>Optional:</p> <p><i>accessClientPassword</i>—Unique password for this WebGate</p> <p><i>state</i>—Specifies whether or the agent is enabled or disabled.</p> <p><i>security</i>—Level of communication security between the Agent and the OAM Server: Open, Simple, Cert.</p> <p><i>aaaTimeoutThreshold</i>—Number (in seconds) to wait for a response from the OAM Server.</p> <p><i>logoutUrls</i>—List of URLs that trigger the logout handler, which removes the ObsSOCookie.</p> <p><i>maxConnections</i>—The maximum number of connections that this OAM Agent can establish with the OAM Server.</p> <p><i>maxCacheElements</i>—Number of elements maintained in the cache.</p> <p><i>cacheTimeout</i>—Amount of time cached information remains in the OAM Agent cache when the information is neither used nor referenced. Default = 1800 (seconds).</p> <p><i>logoutCallbackUrl</i> —The URL to <code>oam_logout_success</code>, which clears cookies during the call back. By default, this is based on the Agent base URL supplied during agent registration. For example:</p> <pre>http://<host>:<port></pre> <p><i>maxSessionTime</i>—Maximum amount of time in seconds that a user's authentication session is valid, regardless of their activity.</p> <p><i>logoutRedirectUrl</i>—The URL (absolute path) to the central logout page (<code>logout.html</code>). By default, this is based on the OAM Administration Console host name with a default port of 14200.</p> <p><i>failoverThreshold</i>—Number representing the point when this OAM Agent opens connections to a Secondary OAM Server.</p> <p><i>tokenValidityPeriod</i>—Amount of time in seconds that a user's authentication session remains valid without accessing any OAM Agent protected resources.</p> <p><i>logoutTargetUrlParamName</i>—The value for this is name for the query parameter that the OPSS applications passes to WebGate during logout.</p>

4.7.39.3 Example

The following invocation lists all mandatory and optional parameters.

```
editWebgate11gAgent(agentName="WebgateAgent1", accessClientPasswd = "welcome1",
state = "Enabled", preferredHost="141.144.168.148:2001", aaaTimeoutThreshold="10",
security = "open", logOutUrls = "http://<host>:<port>", maxConnections = "16"
maxCacheElems = "10000" , cacheTimeout = "1800", logoutCallbackUrl =
"http://<host>:<port>", maxSessionTime = "24", logoutRedirectUrl =
"logoutRedirectUrl", failoverThreshold = "1", tokenValidityPeriod="aPeriod"
logoutTargetUrlParamName = "logoutTargetUrl", domainHome="domainHome1")
```

4.7.40 deleteWebgate11gAgent

Online and offline command that enables you to delete an 11g WebGate Agent registration.

4.7.40.1 Description

Removes an 11g WebGate Agent registration.

The scope of this command is an instance, only. The scope is not an argument

4.7.40.2 Syntax

```
deleteWebgate11gAgent (agentName)
```

Argument	Definition
<i>agentName</i>	Mandatory. Specifies the name of the 11g WebGate Agent.
<i>domainhome</i>	Offline mode: Mandatory Online mode: Optional

4.7.40.3 Example

The following invocation removes the 11g WebGate Agent named `my_11gWebGate`:

```
deleteWebgate11gAgent (agentName="my_11gWebGate", domainHome="domainHome1")
```

4.7.41 displayWebgate11gAgent

Online and offline command that enables you to display an 11g WebGate Agent registration.

4.7.41.1 Description

Displays an 11g WebGate Agent registration.

The scope of this command is an instance, only. The scope is not an argument

4.7.41.2 Syntax

```
displayWebgate11gAgent (agentName)
```

Argument	Definition
<i>agentName</i>	Mandatory. Specifies the name of the WebGate Agent.
<i>domainhome</i>	Offline mode: Mandatory Online mode: Optional

4.7.41.3 Example

The following invocation displays the WebGate Agent named `my_11gWebGate`:

```
displayWebgate11gAgent (agentName="my_11gWebGate", domainHome="domainHome1")
```

4.7.42 displayOAMMetrics

Online and offline command that enables the display of metrics of OAM Servers.

4.7.42.1 Description

Enables the display of metrics of OAM Servers.

The scope of this command is an instance, only. The scope is not an argument.

4.7.42.2 Syntax

```
displayOAMMetrics (domainHome)
```

Argument	Definition
<i>domainhome</i>	Offline mode: Mandatory Online mode: Optional

4.7.42.3 Example

The following invocation enables the display of metrics of OAM Servers.

```
displayOAMMetrics (domainHome=(domainHome1"))
```

4.7.43 updateOIMHostPort

Online only command that updates the Oracle Identity Manager configuration when integrated with Oracle Access Manager.

4.7.43.1 Description

Updates the Oracle Identity manager configuration in system configuration.

The scope of this command is an instance, only. The scope is not an argument.

4.7.43.2 Syntax

```
updateOIMHostPort(hostname, port, secureProtocol)
```

Argument	Definition
<i>hostname</i>	Name of the Oracle Identity Manager host.
<i>port</i>	Port of the Oracle Identity Manager host.
<i>secureProtocol</i>	True or false.

4.7.43.3 Example

The following invocation illustrates this command.

```
updateOIMHostPort(hostName="OIM host", port="7777", secureProtocol="true")
```

4.7.44 configureOIM

Online only command that creates an agent registration specific to Oracle Identity Manager when integrated with Oracle Access Manager.

4.7.44.1 Description

Creates an Agent registration specific to Oracle Identity Manager when integrated with Oracle Access Manager.

The scope of this command is an instance, only. The scope is not an argument.

4.7.44.2 Syntax

```
updateOIMHostPort(hostname, port, secureProtocol)
```

Argument	Definition
<i>hostname</i>	Name of the Oracle Identity Manager host.
<i>port</i>	Port of the Oracle Identity Manager Managed Server.
<i>oimSecureProtocolEnabled</i>	True or false (depending on HTTP or HTTPS).
<i>oimAccessGatePwd</i>	If provided will be the agent password for Open mode
<i>oimCookieDomain</i>	Domain to which the cookie is to be set
<i>oimWgId</i>	Agent registration name.
<i>oimWgVersion</i>	Possible values 10g or 11g. If not provided, default is 10g.

4.7.44.3 Example

The following invocation illustrates this command.

```
updateOIMHostPort(hostName="OIM host", port="7777", secureProtocol="true")
configureOIM(oimHost="OIM host", oimPort="7777", oimSecureProtocolEnabled="true",
oimAccessGatePwd = "Access Gate Password", oimCookieDomain = "OIM Cookie Domain",
oimWgId="OIM Webgate ID", oimWgVersion="OIM Webgate Version")
```

4.7.45 updateOSSOResponseCookieConfig

Online and offline command that updates OSSO Proxy response cookie settings.

4.7.45.1 Description

Updates OSSO Proxy response cookie settings.

The scope of this command is an instance, only. The scope is not an argument.

4.7.45.2 Syntax

```
updateOSSOResponseCookieConfig()
```

Argument	Definition
<i>domainhome</i>	Offline mode: Mandatory Online mode: Optional
<i>cookieName</i>	Optional. Name of the cookie for which settings are updated. If not specified, the global setting is updated.
<i>cookieMaxAge</i>	Maximum age of a cookie in minutes. A negative value sets a session cookie.
<i>isSecureCookie</i>	Boolean flag specifies if cookie should be secure (sent only over SSL channel).
<i>cookieDomain</i>	The domain of the cookie.

4.7.45.3 Example

The following invocation illustrates this command.

```
updateOSSOResponseCookieConfig(cookieName = "<cookieName>",
cookieMaxAge = "<cookie age in minutes>", isSecureCookie = "true | false",
cookieDomain="<domain of the cookie>", domainHome = "<wls_domain_home_path>")
```

4.7.46 deleteOSSOResponseCookieConfig

Online and offline command that deletes OSSO Proxy response cookie settings.

4.7.46.1 Description

Deletes OSSO Proxy response cookie settings.

The scope of this command is an instance, only. The scope is not an argument.

4.7.46.2 Syntax

```
deleteOSSOResponseCookieConfig()
```

Argument	Definition
<i>domainhome</i>	Offline mode: Mandatory Online mode: Optional
<i>cookieName</i>	Mandatory. Name of the cookie for which settings are deleted.

4.7.46.3 Example

The following invocation illustrates this command.

```
deleteOSSOResponseCookieConfig(cookieName = "<cookieName>",
cookieDomain="<domain of the cookie>", domainHome = "<wls_domain_home_path>")
```

4.7.47 displaySimpleModeGlobalPassphrase

Displays the simple mode global passphrase in plain text from the system configuration.

4.7.47.1 Description

Online only command that displays the simple mode global passphrase in plain text from the system configuration.

4.7.47.2 Syntax

```
displaySimpleModeGlobalPassphrase
```

There are no arguments for this command.

4.7.47.3 Example

The following invocation illustrates this command.

```
displaySimpleModeGlobalPassphrase
```

4.7.48 exportSelectedPartners

Exports selected OAM Partners.

4.7.48.1 Description

Exports selected OAM Partners to the intermediate OAM file specified.

4.7.48.2 Syntax

`exportSelectedPartners`

Argument	Definition
<i>pathTempOAMPartnerFile</i>	The temporary file containing partners to be migrated.
<i>partnersNameList</i>	comma separated list of partner ids to be migrated

4.7.48.3 Example

The following invocation illustrates this command.

```
exportSelectedPartners (pathTempOAMPartnerFile="/exampleroot/parent/tempfile.extn"
partnersNameList="partner1,partner2")
```

4.7.49 migrateArtifacts

Migrates artifacts.

4.7.49.1 Description

Migrates artifacts based on the input artifact file.

4.7.49.2 Syntax

`migrateArtifacts`

Argument	Definition
<i>path</i>	Location of the artifacts file is present
<i>password</i>	Password used while generating original artifacts.
<i>type</i>	InPlace or OutOfPlace
<i>isIncremental</i>	true or false. If true, an incremental upgrade is done.

4.7.49.3 Example

The following invocation illustrates this command.

```
migrateArtifacts(path = "/exampleroot/parent/t", password = "password", type =
"InPlace", isIncremental="false")
```

4.7.50 registerThirdPartyTAPPartner

Registers any third party as a Trusted Authentication Protocol (TAP) Partner.

4.7.50.1 Description

Registers any third party as a Trusted Authentication Protocol (TAP) Partner.

4.7.50.2 Syntax

`registerThirdPartyTAPPartner`

Argument	Definition
<i>path</i>	Location of the artifacts file is present
<i>password</i>	Password used while generating original artifacts.

Argument	Definition
<i>partnerName</i>	Name of partner. Can be any name used for identifying the third party partner.
<i>keystoreLocation</i>	The jceks file location.
<i>password</i>	password
<i>tapTokenVersion</i>	Version of the Trusted Authentication Protocol.
<i>tapScheme</i>	Trusted Authentication Protocol Authn Scheme (TAPScheme, out of the box.)
<i>tapRedirectUrl</i>	Third party access URL.

4.7.50.3 Example

```
registerThirdPartyTAPPartner (partnerName="ThirdPartyTAPPartner",keystoreLocation=
"/scratch/DAPKeyStore/mykeystore.jks",password="test",tapTokenVersion="v2.0",
tapScheme="TAPScheme",tapRedirectUrl="http://thirdpartyserverhost:port/
loginPage.jsp");
```

4.8 Oracle Security Token Service

Table 4–7 describes the various types of WLST commands available for the Oracle Security Token Service.

Table 4–7 WLST Oracle Security Token Service Command Groups

OSTS Command Type	Description
Partner Commands	WLST commands related to tasks involving partners.
Relying Party Partner Mapping Commands	The WS Prefix to Relying Party Partner mappings are used to map a service URL, specified in the AppliesTo field of a WS-Trust RST request, to a partner of type Relying Party. The WS prefix string can be an exact service URL, or a URL with a parent path to the service URL. For example, if a mapping is defined to map a WS Prefix (http://test.com/service) to a Relying Party (RelyingPartyPartnerTest), then the following service URLs would be mapped to the Relying Party: http://test.com/service , http://test.com/service/calculatorService , http://test.com/service/shop/cart...
Partner Profiles Commands	WLST commands related to tasks involving partner profiles.
Issuance Templates Commands	WLST commands related to tasks involving issuance templates.
Validation Templates Commands	WLST commands related to tasks involving validation templates.

Use the WLST commands listed in Table 4–8 to manage Oracle Security Token Service

Table 4–8 WLST Commands Oracle Security Token Service

Use this command...	To...	Use with WLST...
Partner Commands		
getPartner	Retrieve a partner and print result.	Online
getAllRequesterPartners	Retrieve the names of Requester partners.	Online
getAllRelyingPartyPartners	Retrieve the names of all Relying Party partners.	Online
getAllIssuingAuthorityPartners	Retrieve the names of all Issuing Authority partners.	Online

Table 4–8 (Cont.) WLST Commands Oracle Security Token Service

Use this command...	To...	Use with WLST...
isPartnerPresent	Query OSTs to determine whether or not the partner exists in the Partner store.	Online
createPartner	Create a new Partner entry.	Online
updatePartner	Update an existing Partner entry based on the provided information.	Online
deletePartner	Delete a partner entry.	Online
getPartnerUsernameTokenUsername	Retrieve the partner's username value.	Online
getPartnerUsernameTokenPassword	Retrieve the partner's password value.	Online
setPartnerUsernameTokenCredential	Set the username and password values of a partner entry.	Online
deletePartnerUsernameTokenCredential	Remove the username and password values from a partner entry.	Online
getPartnerSigningCert	Retrieve the Base64 encoded signing certificate for the partner.	Online
getPartnerEncryptionCert	Retrieve the Base64 encoded encryption certificate for the partner.	Online
setPartnerSigningCert	Upload the signing certificate to the partner entry.	Online
setPartnerEncryptionCert	Upload the encryption certificate to the partner entry.	Online
deletePartnerSigningCert	Remove the signing certificate from the partner entry.	Online Offline
deletePartnerEncryptionCert	Remove the encryption certificate from the partner entry.	Online Offline
getPartnerAllIdentityAttributes	Retrieve and display all Identity mapping attributes used to map a token to a requester partner.	Online Offline
getPartnerIdentityAttribute	Retrieve and display the identity mapping attribute.	Online Offline
setPartnerIdentityAttribute	Set the identity mapping attribute for a requester partner.	Online Offline
deletePartnerIdentityAttribute	Delete the identity mapping attribute for a requester partner.	Online Offline
Relying Party Partner Mapping Commands		
getAllWSPrefixAndPartnerMappings	Retrieve and display all WS Prefixes.	Online Offline
getWSPrefixAndPartnerMapping	Retrieve and display the Relying Party Partner mapped to the specified wsprefix parameter.	Online Offline
createWSPrefixAndPartnerMapping	Create a new WS Prefix mapping to a Relying Partner.	Online Offline

Table 4–8 (Cont.) WLST Commands Oracle Security Token Service

Use this command...	To...	Use with WLST...
deleteWSPrefixAndPartnerMapping	Delete an existing WS Prefix mapping to a Relying Partner.	Online Offline
Partner Profiles Commands		
getAllPartnerProfiles	Retrieve the names of all the existing partner profiles.	Online
getPartnerProfile	Retrieve partner profile configuration data.	Online
createRequesterPartnerProfile	Create a new Requester Partner profile with default configuration data.	Online
createRelyingPartyPartnerProfile	Create a new Relying Party Partner profile with default configuration data.	Online
createIssuingAuthorityPartnerProfile	Create a new Issuing Authority Partner profile with default configuration data.	Online
deletePartnerProfile	Delete an existing partner profile.	Online
Issuance Template Commands		
getAllIssuanceTemplates	Retrieve the names of all the existing Issuance Templates.	Online Offline
getIssuanceTemplate	Retrieve configuration data of a specific Issuance Template.	Online
createIssuanceTemplate	Create a new Issuance Template with default configuration data.	Online
deleteIssuanceTemplate	Delete an existing Issuance Template.	Online Offline
Validation Template Commands		
getAllValidationTemplates	Retrieve the names of all the existing Validation Templates.	Online Offline
getValidationTemplate	Retrieve configuration data of a specific Validation Template.	Online Offline
createWSSValidationTemplate	Create a new WS Security Validation Template with default configuration data.	Online Offline
createWSTrustValidationTemplate	Create a new WS Trust Validation Template with default configuration data.	Online Offline
deleteValidationTemplate	Delete an existing Issuance Template.	Online Offline

4.8.1 getPartner

Online command that retrieves the Partner entry and prints out the configuration for this partner.

4.8.1.1 Description

Retrieves the Partner entry and prints out the configuration for this partner.

4.8.1.2 Syntax

```
getPartner (partnerId)
```

Argument	Definition
<i>partnerId</i>	Specifies the partnerId: the ID of the partner.

4.8.1.3 Example

The following invocation retrieves the Partner entry and prints out the configuration for `customPartner`:

```
getPartner (partnerId="customPartner")
```

4.8.2 getAllRequesterPartners

Online command that retrieves Requester type partners.

4.8.2.1 Description

Retrieves Requester type partners.

4.8.2.2 Syntax

```
getAllRequesterPartners()
```

4.8.2.3 Example

The following invocation retrieves Requester type partners:

```
getAllRequesterPartners()
```

4.8.3 getAllRelyingPartyPartners

Online command that retrieves Relying Party partners.

4.8.3.1 Description

Retrieves the Relying Party partners.

4.8.3.2 Syntax

```
getAllRelyingPartyPartners()
```

4.8.3.3 Example

The following invocation retrieves Relying Party partners:

```
getAllRelyingPartyPartners()
```

4.8.4 getAllIssuingAuthorityPartners

Online command that retrieves Issuing Authority partners and prints out the result.

4.8.4.1 Description

Retrieves the Issuing Authority partners and prints out the result.

4.8.4.2 Syntax

```
getAllIssuingAuthorityPartners()
```

4.8.4.3 Example

The following invocation retrieves Issuing Authority partners and prints out the result:

```
getAllIssuingAuthorityPartners()
```

4.8.5 isPartnerPresent

Online command that queries OSTS to determine whether or not the specified partner exists in the Partner store.

4.8.5.1 Description

Queries OSTS to determine whether or not the specified partner exists in the Partner store, and prints out the result.

4.8.5.2 Syntax

```
isPartnerPresent(partnerId)
```

Argument	Definition
<i>partnerId</i>	Specifies the ID of the partner.

4.8.5.3 Example

The following invocation queries OSTS to determine whether or not `customPartner` exists in the Partner store, and prints out the result:

```
isPartnerPresent(partnerId="customPartner")
```

4.8.6 createPartner

Online command that creates a new Partner entry.

4.8.6.1 Description

Creates a new Partner entry based on provided information. Displays a message indicating the result of the operation.

4.8.6.2 Syntax

```
createPartner(partnerId, partnerType, partnerProfileId, description,
bIsTrusted)
```

Argument	Definition
<i>partnerId</i>	Specifies the ID of the new partner to be created.
<i>partnerType</i>	Specifies the type of partner. Values can be one of the following: <ul style="list-style-type: none"> ▪ STS_REQUESTER for Requester ▪ STS_RELIVING_PARTY for Relying Party ▪ STS_ISSUING_AUTHORITY for Issuing Authority
<i>partnerProfileId</i>	Specifies the profile ID to be attached to this partner. It must reference an existing partner profile, and the type of the partner profile must be compliant with the type of the new partner entry.
<i>description</i>	Specifies the optional description of this new partner entry.

Argument	Definition
<i>bIsTrusted</i>	A value that indicates whether or not this new partner is trusted. Value can be either: <ul style="list-style-type: none"> ▪ true for trusted ▪ false if not trusted

4.8.6.3 Example

The following invocation creates STS_Requestor partner, customPartner, custom-partnerprofile with a description (custom requester), with a trust value of true, displays a message indicating the result of the operation:

```
createPartner(partnerId="customPartner", partnerType="STS_REQUESTER",
partnerProfileId="custom-partnerprofile", description="custom requester",
bIsTrusted="true")
```

4.8.7 updatePartner

Online command that updates an existing Partner entry.

4.8.7.1 Description

Updates an existing Partner entry based on the provided information. Displays a message indicating the result of the operation.

4.8.7.2 Syntax

```
updatePartner(partnerId, partnerProfileId, description, bIsTrusted)
```

Argument	Definition
<i>partnerId</i>	Specifies the ID of the new partner to be updated.
<i>partnerProfileId</i>	Specifies the partner profile ID. It must reference an existing partner profile, and the type of the partner profile must be compliant with the type of the new partner entry.
<i>description</i>	Specifies the optional description of this new partner entry.
<i>bIsTrusted</i>	A value that indicates whether or not this new partner is trusted. Value can be either: <ul style="list-style-type: none"> ▪ true for trusted ▪ false if not trusted

4.8.7.3 Example

The following invocation updates customPartner with a new profile ID, (x509-wss-validtemp), description (custom requester with new profile id), and a trust value of false. A message indicates the result of the operation:

```
updatePartner(partnerId="customPartner", partnerProfileId="x509-wss-validtemp",
description="custom requester with new profile id", bIsTrusted="false")
```

4.8.8 deletePartner

Online command that deletes a partner entry from OSTs.

4.8.8.1 Description

Deletes an existing Partner entry referenced by the `partnerId` parameter from OSTs, and prints out the result of the operation.

4.8.8.2 Syntax

```
deletePartner(partnerId)
```

Argument	Definition
<i>partnerId</i>	Specifies the ID of the partner to be deleted.

4.8.8.3 Example

The following invocation deletes the `customPartner` partner entry referenced by the `partnerId` parameter from OSTs, and prints out the result of the operation:

```
deletePartner(partnerId="customPartner")
```

4.8.9 getPartnerUsernameTokenUsername

Online command that retrieves a partner's username value that will be used for UNT credentials partner validation or mapping operation.

4.8.9.1 Description

Retrieves a partner's username value that will be used for UNT credentials partner validation or mapping operation, and displays the value.

4.8.9.2 Syntax

```
getPartnerUsernameTokenUsername(partnerId)
```

Argument	Definition
<i>partnerId</i>	Specifies the ID of the partner.

4.8.9.3 Example

The following invocation retrieves the `customPartner` partner username value that will be used for UNT credentials partner validation or mapping operation, and displays the value:

```
getPartnerUsernameTokenUsername(partnerId="customPartner")
```

4.8.10 getPartnerUsernameTokenPassword

Online command that retrieves a partner's password value that will be used for UNT credentials partner validation or mapping operation.

4.8.10.1 Description

Retrieves a partner password value that will be used for UNT credentials partner validation or mapping operation, and displays the value.

4.8.10.2 Syntax

```
getPartnerUsernameTokenPassword(partnerId)
```

Argument	Definition
<i>partnerId</i>	Specifies the ID of the partner.

4.8.10.3 Example

The following invocation retrieves `customPartner` partner password value that will be used for UNT credentials partner validation or mapping operation, and displays the value:

```
getPartnerUsernameTokenPassword(partnerId="customPartner")
```

4.8.11 setPartnerUsernameTokenCredential

Online command that sets the username and password values of a partner entry, that will be used for UNT credentials partner validation or mapping operation.

4.8.11.1 Description

Sets the username and password values of a partner entry, that will be used for UNT credentials partner validation or mapping operation. Displays the result of the operation.

4.8.11.2 Syntax

```
setPartnerUsernameTokenCredential(partnerId, UTUsername, UTPassword)
```

Argument	Definition
<i>partnerId</i>	Specifies the ID of the partner.
<i>UTUsername</i>	Specifies the username value used for UNT credentials validation or mapping operations.
<i>UTPassword</i>	Specifies the password value used for UNT credentials validation or mapping operations.

4.8.11.3 Example

The following invocation sets the username and password values of the `customPartner` partner entry, and displays the result of the operation:

```
setPartnerUsernameTokenCredential(partnerId="customPartner", UTUsername="test", UTPassword="password")
```

4.8.12 deletePartnerUsernameTokenCredential

Online command that removes the username and password values from a partner entry that are used for UNT credentials partner validation or mapping operation, and displays the result of the operation.

4.8.12.1 Description

Removes the username and password values from a partner entry that are used for UNT credentials partner validation or mapping operation, and displays the result of the operation.

4.8.12.2 Syntax

```
deletePartnerUsernameTokenCredential(partnerId)
```

Argument	Definition
<i>partnerId</i>	Specifies the ID of the partner to be deleted.

4.8.12.3 Example

The following invocation removes the username and password values from a partner entry that are used for UNT credentials partner validation or mapping operation, and displays the result of the operation:

```
deletePartnerUsernameTokenCredential (partnerId="customPartner")
```

4.8.13 getPartnerSigningCert

Online command that retrieves the Base64 encoded signing certificate for the partner referenced by the partnerId parameter, and displays its value, as a Base64 encoded string.

4.8.13.1 Description

Retrieves the Base64 encoded signing certificate for the partner referenced by the partnerId parameter, and displays its value, as a Base64 encoded string.

4.8.13.2 Syntax

```
getPartnerSigningCert (partnerId)
```

Argument	Definition
<i>partnerId</i>	Specifies the ID of the partner.

4.8.13.3 Example

The following invocation retrieves Base64 encoded signing certificate for the partner referenced by the partnerId parameter, and displays its value, as a Base64 encoded string:

```
getPartnerSigningCert (partnerId="customPartner")
```

4.8.14 getPartnerEncryptionCert

Online command that retrieves the Base64 encoded encryption certificate, and displays its value as a Base64 encoded string.

4.8.14.1 Description

Retrieves the Base64 encoded encryption certificate for the partner referenced by the partnerId parameter, and displays its value as a Base64 encoded string.

4.8.14.2 Syntax

```
getPartnerEncryptionCert (partnerId)
```

Argument	Definition
<i>partnerId</i>	Specifies the ID of the partner.

4.8.14.3 Example

The following invocation retrieves the Base64 encoded encryption certificate for the partner referenced by the `partnerId` parameter, and displays its value, as a Base64 encoded string:

```
getPartnerEncryptionCert (partnerId="customPartner")
```

4.8.15 setPartnerSigningCert

Online command that Uploads the provided certificate to the partner entry as the signing certificate. Displays the result of the operation.

4.8.15.1 Description

Uploads the provided certificate to the partner entry (referenced by the `partnerId` parameter) as the signing certificate. The supported formats of the certificate are DER and PEM. Displays the result of the operation.

4.8.15.2 Syntax

```
setPartnerSigningCert (partnerId, certFile)
```

Argument	Definition
<i>partnerId</i>	Specifies the ID of the partner.
<i>certFile</i>	Specifies the location of the certificate on the local filesystem. Supported formats of the certificate are DER and PEM.

4.8.15.3 Example

The following invocation uploads the provided certificate to the partner entry `customPartner` as the signing certificate. Displays the result of the operation:

```
setPartnerSigningCert (partnerId="customPartner", certFile="/temp/signing_cert")
```

4.8.16 setPartnerEncryptionCert

Online command that Uploads the provided certificate to the partner entry as the encryption certificate. Displays the result of the operation.

4.8.16.1 Description

Uploads the provided certificate to the partner entry (referenced by the `partnerId` parameter) as the encryption certificate. Displays the result of the operation.

4.8.16.2 Syntax

```
setPartnerEncryptionCert (partnerId, certFile)
```

Argument	Definition
<i>partnerId</i>	Specifies the ID of the partner.
<i>certFile</i>	Specifies the location of the certificate on the local filesystem. Supported formats of the certificate are DER and PEM.

4.8.16.3 Example

The following invocation uploads the provided certificate to the partner entry `customPartner` as the signing certificate. Displays the result of the operation:

```
setPartnerSigningCert (partnerId="customPartner", certFile="/temp/signing_cert")
```

4.8.17 deletePartnerSigningCert

Online command that removes the encryption certificate from the partner entry and displays the result of the operation.

4.8.17.1 Description

Removes the encryption certificate from the partner entry, referenced by the `partnerId` parameter, and displays the result of the operation.

4.8.17.2 Syntax

```
deletePartnerSigningCert (partnerId)
```

Argument	Definition
<i>partnerId</i>	Specifies the ID of the partner.

4.8.17.3 Example

The following invocation removes the encryption certificate from the partner entry, `customPartner`, and displays the result of the operation:

```
deletePartnerSigningCert (partnerId="customPartner")
```

4.8.18 deletePartnerEncryptionCert

Online command that removes the signing certificate from the partner entry and displays the result of the operation.

4.8.18.1 Description

Removes the signing certificate from the partner entry, referenced by the `partnerId` parameter, and displays the result of the operation.

4.8.18.2 Syntax

```
deletePartnerEncryptionCert (partnerId)
```

Argument	Definition
<i>partnerId</i>	Specifies the ID of the partner.

4.8.18.3 Example

The following invocation removes the signing certificate from the partner entry, `customPartner`, and displays the result of the operation:

```
deletePartnerEncryptionCert (partnerId="customPartner")
```

4.8.19 getPartnerAllIdentityAttributes

Online command that retrieves and displays all the identity mapping attributes used to map a token to a requester partner, or to map binding data (SSL Client certificate or HTTP Basic Username) to a requester partner.

4.8.19.1 Description

Retrieves and displays all the identity mapping attributes used to map a token to a requester partner, or to map binding data (SSL Client certificate or HTTP Basic Username) to a requester partner.

The identity mapping attributes only exist for partners of type Requester.

4.8.19.2 Syntax

```
getPartnerAllIdentityAttributes(partnerId)
```

Argument	Definition
<i>partnerId</i>	Specifies the ID of the Requester partner. Identity mapping attributes only exist for partners of type Requester

4.8.19.3 Example

The following invocation retrieves and displays all the identity mapping attributes used to map a token to a requester partner, or to map binding data (SSL Client certificate or HTTP Basic Username) to a requester partner: `customPartner`.

```
getPartnerAllIdentityAttributes(partnerId="customPartner")
```

4.8.20 getPartnerIdentityAttribute

Online command that retrieves and displays identity mapping attributes used to map a token or to map binding data to a requester partner.

4.8.20.1 Description

Retrieves and displays an identity mapping attribute used to map a token to a requester partner, or to map binding data (SSL Client certificate or HTTP Basic Username) to a requester partner.

The identity mapping attributes only exist for partners of type Requester.

4.8.20.2 Syntax

```
getPartnerIdentityAttribute(partnerId, identityAttributeName)
```

Argument	Definition
<i>partnerId</i>	Specifies the ID of the Requester partner.
<i>IdentityAttributeName</i>	Specifies the name of the identity mapping attribute to retrieve and display. For example: <code>httpbasicusername</code> .

4.8.20.3 Example

The following invocation retrieves and displays one `identityAttribute` and its value as specified by `identityAttributeName`.

```
getPartnerIdentityAttribute(partnerId="customPartner",
identityAttributeName="httpbasicusername")
```

4.8.21 setPartnerIdentityAttribute

Online command that sets the identity mapping attribute for the Requester partner.

4.8.21.1 Description

Set the identity mapping attribute specified by `identityAttributeName` for the partner of type requester specified by the `partnerId` parameter. These identity mapping attributes only exist for Requester partners. Displays the result of the operation.

4.8.21.2 Syntax

```
setPartnerIdentityAttribute(partnerId, identityAttributeName,
identityAttributeValue)
```

Argument	Definition
<i>partnerId</i>	Specifies the ID of the partner of type Requester.
<i>identityAttributeName</i>	Specifies the name of the identity mapping attribute to retrieve and display.
<i>identityAttributeValue</i>	Specifies the value of the identity mapping attribute to set.

4.8.21.3 Example

The following invocation sets the identity mapping attribute specified by `identityAttributeName` for the Requester partner of type requester specified by the `partnerId` parameter. Displays the result of the operation.

```
setPartnerIdentityAttribute(partnerId="customPartner",
identityAttributeName="httpbasicusername", identityAttributeValue="test")
```

4.8.22 deletePartnerIdentityAttribute

Online command that deletes the identity mapping attribute.

4.8.22.1 Description

Deletes the identity mapping attribute specified by `identityAttributeName`.

The identity mapping attributes used to map a token to a requester partner, or to map binding data (SSL Client certificate or HTTP Basic Username) to a requester partner, and they only exist for Requester partners.

4.8.22.2 Syntax

```
deletePartnerIdentityAttribute(partnerId, identityAttributeName)
```

Argument	Definition
<i>partnerId</i>	Specifies the ID of the partner.
<i>identityAttributeName</i>	Specifies the name of the identity mapping attribute to delete.

4.8.22.3 Example

The following invocation deletes the identity mapping attribute specified by `identityAttributeName` for Requester partner `customPartner`.

```
deletePartnerIdentityAttribute(partnerId="customPartner",
identityAttributeName="httpbasicusername")
```

4.8.23 getAllWSPrefixAndPartnerMappings

Online command that retrieves and displays all WS Prefixes to Relying Party Partner mappings.

4.8.23.1 Description

Retrieves and displays all WS Prefixes to Relying Party Partner mappings.

4.8.23.2 Syntax

```
getAllWSPrefixAndPartnerMappings ()
```

4.8.23.3 Example

The following invocation retrieves and displays the WS Prefixes.

```
getAllWSPrefixAndPartnerMappings ()
```

4.8.24 getWSPrefixAndPartnerMapping

Online command that retrieves and displays the Relying Party Partner mapped to the specified wsprefix parameter, if a mapping for that WS Prefix exists.

4.8.24.1 Description

Retrieves and displays the Relying Party Partner mapped to the specified wsprefix parameter, if a mapping for that WS Prefix exists.

4.8.24.2 Syntax

```
getWSPrefixAndPartnerMapping (wsprefix)
```

Argument	Definition
<i>wsprefix</i>	Specifies the WS Prefix entry to retrieve and display. The path is optional. If specified, it should take the following form: <i>http_protocol://hostname_ip/path</i>

4.8.24.3 Example

The following invocation retrieves and displays the Relying Party Partner mapped to the specified wsprefix parameter, if a mapping for that WS Prefix exists.

```
getWSPrefixAndPartnerMapping (wsprefix="http://host1.example.com/path")
```

4.8.25 createWSPrefixAndPartnerMapping

Online command that creates a new WS Prefix mapping to a Relying Partner.

4.8.25.1 Description

Creates a new WS Prefix mapping to a Relying Partner referenced by the partnerid parameter, and displays the result of the operation.

4.8.25.2 Syntax

```
createWSPrefixAndPartnerMapping (wsprefix, partnerid, description)
```

Argument	Definition
<i>wsprefix</i>	Specifies the WS Prefix entry to retrieve and display. The path is optional. If specified, it should take the following form: <i>http_protocol://hostname_ip/path</i>
<i>partnerId</i>	Specifies the ID of the partner.
<i>description</i>	Specifies an optional description.

4.8.25.3 Example

The following invocation creates a new WS Prefix mapping to a Relying Partner Partner referenced by the partnerid parameter, and displays the result of the operation.

```
createWSPrefixAndPartnerMapping(ws_prefix="http://host1.example.com/path",
partnerid="customRPpartner", description="some description")
```

4.8.26 deleteWSPrefixAndPartnerMapping

Online command that deletes an existing mapping of WS Prefix to a Relying Partner Partner.

4.8.26.1 Description

Deletes an existing mapping of WS Prefix to a Relying Partner, and displays the result of the operation.

4.8.26.2 Syntax

```
deleteWSPrefixAndPartnerMapping(ws_prefix)
```

Argument	Definition
<i>wsprefix</i>	Specifies the WS Prefix entry to retrieve and display. The path is optional. If specified, it should take the following form: <i>http_protocol://hostname_ip/path</i>

4.8.26.3 Example

The following invocation deletes the existing mapping of WS Prefix to a Relying Partner, and displays the result of the operation.

```
deleteWSPrefixAndPartnerMapping(ws_prefix="http://host1.example.com/path")
```

4.8.27 getAllPartnerProfiles

Online command that retrieves the names of all the existing partner profiles and displays them.

4.8.27.1 Description

Retrieves the names of all the existing partner profiles and displays them.

4.8.27.2 Syntax

```
getAllPartnerProfiles()
```

4.8.27.3 Example

The following invocation retrieves the names of all the existing partner profiles and displays them.

```
getAllPartnerProfiles()
```

4.8.28 getPartnerProfile

Online command that retrieves the configuration data of a specific partner profile, and displays the content of the profile.

4.8.28.1 Description

Retrieves the configuration data of the partner profile referenced by the `partnerProfileId` parameter, and displays the content of the profile.

4.8.28.2 Syntax

```
getPartnerProfile(partnerProfileId)
```

Argument	Definition
<i>partnerProfileId</i>	Specifies the name of the partner profile.

4.8.28.3 Example

The following invocation retrieves the configuration data of the partner profile referenced by the `partnerProfileId` parameter, and displays the content of the profile.

```
getPartnerProfile(partnerProfileId="custom-partnerprofile")
```

4.8.29 createRequesterPartnerProfile

Online command that creates a new requester partner profile with default configuration data.

4.8.29.1 Description

Creates a new requester partner profile with default configuration data, and displays the result of the operation.

[Table 4–9](#) describes the default configuration created with this command.

Table 4–9 Default Configuration: createRequesterPartnerProfile

Element	Description
<i>Return Error for Missing Claims</i>	Default: false
<i>Allow Unmapped Claims</i>	Default: false

Table 4–9 (Cont.) Default Configuration: createRequesterPartnerProfile

Element	Description
<i>Token Type Configuration</i>	<p>The Token Type Configuration table includes the following entries. There are no mappings of token type to WS-Trust Validation Template:</p> <ul style="list-style-type: none"> <p>SAML 1.1 token type mapped to the following External URI:</p> <pre>http://docs.oasis-open.org/wss/oasis-wss-saml-token-profile-1.1#SAMLV1.1</pre> <p>The SAML 1.1 token type is not mapped to any WS-Trust Validation Template.</p> <p>SAML 2.0 token type mapped to the following External URI:</p> <pre>http://docs.oasis-open.org/wss/oasis-wss-saml-token-profile-1.1#SAMLV2.0</pre> <p>The SAML 2.0 token type is not mapped to any WS-Trust Validation Template.</p> <p>Username token type mapped to the following External URI:</p> <pre>http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-username-token-profile-1.0#UsernameToken</pre> <p>The Username token type is not mapped to any WS-Trust Validation Template.</p> <p>Note: Token Type Configuration and token type to Validation Template mapping are both empty</p>
<i>Attribute Name Mapping</i>	<p>Default: The Attribute Name Mapping table is empty by default.</p>

4.8.29.2 Syntax

```
createRequesterPartnerProfile(partnerProfileId, defaultRelyingPartyPPID,
description)
```

Argument	Definition
<i>partnerProfileId</i>	Specifies the name of the partner profile.
<i>defaultRelyingPartyPPID</i>	Specifies the relying party partner profile to use, if the AppliesTo field is missing from the RST or if it could not be mapped to a Relying Party Partner.
<i>description</i>	Specifies the optional description for this partner profile

4.8.29.3 Example

The following invocation creates a new requester partner profile with default configuration data, and displays the result of the operation. For default data descriptions, see [Table 4–9](#).

```
createRequesterPartnerProfile(partnerProfileId="custom-partnerprofile",
defaultRelyingPartyPPID="rpPartnerProfileTest", description="custom
partner profile")
```

4.8.30 createRelyingPartyPartnerProfile

Online command that creates a new relying party partner profile with default configuration data.

4.8.30.1 Description

Creates a new relying party partner profile with default configuration data, and displays the result of the operation.

Table 4–10 describes the default configuration created with this command.

Table 4–10 Default Configuration: createRelyingPartyPartnerProfile

Element	Description
Download Policy	Default: false
Allow Unmapped Claims	Default: false
Token Type Configuration	<p>The Token Type Configuration will contain a single entry, with:</p> <ul style="list-style-type: none"> ■ The token type set to the type of Issuance Template referenced by defaultIssuanceTemplateID ■ The Issuance template set to defaultIssuanceTemplateID <p>Note: For the token type of the issuance template referenced by defaultIssuanceTemplateID, it will be linked to the issuance template, while the other token types will not be linked to any issuance template.</p> <p>If the issuance template referenced by defaultIssuanceTemplateID is of custom token type, the table will only contain one entry, with the custom token type, mapped to the custom token type as the external URI, and mapped to the issuance template referenced by defaultIssuanceTemplateID</p>
Attribute Name Mapping	The Attribute Name Mapping table is empty by default.

4.8.30.2 Syntax

```
createRelyingPartyPartnerProfile(partnerProfileId, defaultIssuanceTemplateID,
description)
```

Argument	Definition
<i>partnerProfileId</i>	Specifies the name of the partner profile.
<i>defaultIssuanceTemplateID</i>	Specifies the default issuance template and token type to issue if no token type was specified in the RST.
<i>description</i>	Specifies the optional description for this partner profile

4.8.30.3 Example

The following invocation creates a new relying party partner profile with default configuration data, and displays the result of the operation.

```
createRelyingPartyPartnerProfile(partnerProfileId="custom-partnerprofile",
defaultIssuanceTemplateID="saml11-issuance-template", description="custom partner
profile")
```

4.8.31 createlssuingAuthorityPartnerProfile

Online command that creates a new issuing authority partner profile with default configuration data.

4.8.31.1 Description

Creates a new issuing authority partner profile with the default configuration data in [Table 4–11](#), and displays the result of the operation.

Table 4–11 Default Configuration: createlssuingAuthorityPartnerProfile

Element	Description
Server Clockdrift	Default: 600 seconds
Token Mapping	<p>The Token Mapping Section will be configured as follows:</p> <ul style="list-style-type: none"> ▪ Override Simple User Mapping: false ▪ Override User NameID Mapping: false ▪ Override Attribute Based User Mapping: false ▪ Override Simple Partner Mapping: false ▪ Override Partner NameID Mapping: false <p>Empty fields</p> <ul style="list-style-type: none"> ▪ simple user mapping ▪ attribute based user mapping ▪ simple partner mapping
Partner NameID Mapping	<p>The Partner NameID Mapping table will be provisioned with the following entries as NameID format. However, without any data in the datastore column the issuance template referenced by defaultIssuanceTemplateID is of token type SAML 1.1, SAML 2.0, or Username.</p> <p>The table will contain the following entries:</p> <ul style="list-style-type: none"> ▪ urn:oasis:names:tc:SAML:1.1:nameid-format:WindowsDomainQualifiedName ▪ urn:oasis:names:tc:SAML:1.1:nameid-format:X509SubjectName ▪ urn:oasis:names:tc:SAML:1.1:nameid-format:emailAddress ▪ urn:oasis:names:tc:SAML:1.1:nameid-format:unspecified ▪ urn:oasis:names:tc:SAML:2.0:nameid-format:kerberos ▪ urn:oasis:names:tc:SAML:2.0:nameid-format:persistent
User NameID Mapping	<p>The User NameID Mapping table will be provisioned with the following entries as NameID format:</p> <ul style="list-style-type: none"> ▪ urn:oasis:names:tc:SAML:1.1:nameid-format:WindowsDomainQualifiedName, empty datastore column ▪ urn:oasis:names:tc:SAML:1.1:nameid-format:X509SubjectName, dn set in the datastore column ▪ urn:oasis:names:tc:SAML:1.1:nameid-format:emailAddress, mail set in the datastore column ▪ urn:oasis:names:tc:SAML:1.1:nameid-format:unspecified, empty datastore column ▪ urn:oasis:names:tc:SAML:2.0:nameid-format:kerberos, empty datastore column ▪ urn:oasis:names:tc:SAML:2.0:nameid-format:persistent, empty datastore column

Table 4–11 (Cont.) Default Configuration: createIssuingAuthorityPartnerProfile

Element	Description
Attribute Mapping	The Attribute Value Mapping and Attribute Name Mapping table is empty by default.

4.8.31.2 Syntax

```
createIssuingAuthorityPartnerProfile(partnerProfileId, description)
```

Argument	Definition
<i>partnerProfileId</i>	Specifies the name of the partner profile.
<i>description</i>	Specifies the optional description for this partner profile

4.8.31.3 Example

The following invocation a new issuing authority partner profile with default configuration data, and displays the result of the operation.

```
createIssuingAuthorityPartnerProfile(partnerProfileId="custom-partnerprofile"
description="custom partner profile")
```

4.8.32 deletePartnerProfile

Online command that deletes an partner profile referenced by the partnerProfileId parameter.

4.8.32.1 Description

Deletes an partner profile referenced by the partnerProfileId parameter, and displays the result of the operation.

4.8.32.2 Syntax

```
deletePartnerProfile(partnerProfileId)
```

Argument	Definition
<i>partnerProfileId</i>	Specifies the name of the partner profile to be removed.

4.8.32.3 Example

The following invocation deletes an partner profile referenced by the partnerProfileId parameter, and displays the result of the operation.

```
deletePartnerProfile(partnerProfileId="custom-partnerprofile")
```

4.8.33 getAllIssuanceTemplates

Online command that retrieves the names of all the existing issuance templates.

4.8.33.1 Description

Retrieves the names of all the existing issuance templates and displays them.

4.8.33.2 Syntax

```
getAllIssuanceTemplates
```

4.8.33.3 Example

The following invocation retrieves the names of all the existing issuance templates and displays them.

```
getAllIssuanceTemplates
```

4.8.34 getIssuanceTemplate

Online command that retrieves the configuration data of a specific issuance template.

4.8.34.1 Description

Retrieves the configuration data of the issuance template referenced by the `issuanceTemplateId` parameter, and displays the content of the template.

4.8.34.2 Syntax

```
getIssuanceTemplate(issuanceTemplateId)
```

Argument	Definition
<code>issuanceTemplateId</code>	Specifies the name of the issuance template.

4.8.34.3 Example

The following invocation retrieves the configuration data of the issuance template referenced by the `issuanceTemplateId` parameter, and displays the content of the template.

```
getIssuanceTemplate(issuanceTemplateId="custom-issuancetemp")
```

4.8.35 createIssuanceTemplate

Online command that creates a new issuance template with default configuration data.

4.8.35.1 Description

Creates a new issuance template with default configuration data, and displays the result of the operation.

[Table 4–12](#) describes the default configuration for this command.

Table 4–12 Default Configuration: createIssuanceTemplate

Token Type	Description
Username	<p>The issuance template will be created with the following default values:</p> <ul style="list-style-type: none"> ▪ Send Encrypted Token: false ▪ NameID User Attribute: uid ▪ NameID User Attribute Store: User Store ▪ Password Attribute: (empty) ▪ Include Nonce: true ▪ Include Timestamp: true

Table 4–12 (Cont.) Default Configuration: *createIssuanceTemplate*

Token Type	Description
SAML 1.1 or SAML 2.0	<p>The issuance template will be created with the following default values:</p> <ul style="list-style-type: none"> ▪ Send Encrypted Token: false ▪ Assertion Issuer: OAM Hostname ▪ NameID Format: Email Address ▪ NameID User Attribute: mail ▪ NameID User Attribute Store: User Store ▪ NameID Qualifier: (empty) ▪ Include Authn Statement: true ▪ Include Attr Statement: true ▪ Sign Assertion: true ▪ Include Certificate in Signature: true ▪ Send Encrypted NameID: false (SAML 2.0 only) ▪ Default Subject Confirmation Method: Sender Vouches ▪ Compute HOK Symmetric Key: true ▪ HOK Symmetric Key Generation Algorithm: http://www.w3.org/2001/04/xmlenc#aes128-cbc <p>Empty tables: Attribute Name Mapping, Attribute Value Mapping and Attribute Value Filter</p>
Custom Type	<p>The issuance template will be created with the following default values:</p> <ul style="list-style-type: none"> ▪ Send Encrypted Token: false

4.8.35.2 Syntax

```
createIssuanceTemplate(issuanceTemplateId, tokenType, signingKeyId,
description)
```

Argument	Definition
<i>issuanceTemplateId</i>	Specifies the name of the issuance template to be created.
<i>tokenType</i>	<p>Possible values can be:</p> <ul style="list-style-type: none"> ▪ username: indicates that the token type is UsernameToken ▪ saml11: indicates that the token type is a SAML 1.1 Assertion ▪ saml20: indicates that the token type is a SAML 2.0 Assertion ▪ <other>: in this case, the token type is assumed to be a custom token type, referenced by <other> (replace <other> by a value)
<i>signingKeyId</i>	Specifies the keyID referencing the key entry (defined in the STS General Settings UI section) that will be used to sign outgoing SAML Assertions. Only required when token type is saml11 or saml20.
<i>description</i>	An optional description.

4.8.35.3 Example

The following invocation creates a new issuance template with default configuration data, and displays the result of the operation.

```
createIssuanceTemplate(issuanceTemplateId="custom-issuancetemp",
```

```
tokenType="saml20", signingKeyId="osts_signing", description="custom issuance
template")
```

4.8.36 deleteIssuanceTemplate

Online command that deletes an issuance template referenced by the `issuanceTemplateId` parameter, and displays the result of the operation.

4.8.36.1 Description

Deletes an issuance template referenced by the `issuanceTemplateId` parameter, and displays the result of the operation.

4.8.36.2 Syntax

```
deleteIssuanceTemplate(issuanceTemplateId)
```

Argument	Definition
<i>issuanceTemplateId</i>	Specifies the name of the existing issuance template to be removed.

4.8.36.3 Example

The following invocation deletes an issuance template referenced by the `issuanceTemplateId` parameter, and displays the result of the operation.

```
deleteIssuanceTemplate(issuanceTemplateId="custom-issuancetemp")
```

4.8.37 getAllValidationTemplates

Online command that retrieves the names of all the existing validation templates.

4.8.37.1 Description

Retrieves the names of all the existing validation templates and displays them.

4.8.37.2 Syntax

```
getAllValidationTemplates()
```

4.8.37.3 Example

The following invocation retrieves the names of all the existing validation templates and displays them.

```
getAllValidationTemplates()
```

4.8.38 getValidationTemplate

Online command that retrieves the configuration data of a specific validation template, and displays the content of the template.

4.8.38.1 Description

Retrieves the configuration data of the validation template referenced by the `validationTemplateId` parameter, and displays the content of the template.

4.8.38.2 Syntax

```
getValidationTemplate(validationTemplateId)
```

Argument	Definition
<i>validationTemplateId</i>	Specifies the name of the existing validation template.

4.8.38.3 Example

The following invocation retrieves the configuration data of a specific validation template, and displays the content of the template.

```
getValidationTemplate(validationTemplateId="custom-wss-validtemp")
```

4.8.39 createWSSValidationTemplate

Online command that creates a new validation template with default configuration data.

4.8.39.1 Description

Creates a new validation template with default configuration data, and displays the result of the operation.

The WSS validation template is created with the values in [Table 4–13](#), depending on the token type.

Table 4–13 Default Configuration: createWSSValidationTemplate

Token Type	Description
Username	The validation template will be created with the following default values: <ul style="list-style-type: none"> ■ Timestamp Lifespan: 600 seconds ■ Enable Credential Validation: true ■ Validation Source: Partner ■ Token Mapping: Map token to Partner ■ Enable Simple Partner Mapping: true ■ Partner Datastore Attribute: username

Table 4–13 (Cont.) Default Configuration: createWSSValidationTemplate

Token Type	Description
SAML 1.1 or SAML 2.0	<p>The validation template will be created with the following default values:</p> <ul style="list-style-type: none"> ■ Authentication Timeout: 3600 seconds ■ Timestamp Lifespan: 3600 seconds <p>The Token Mapping section will be created with the following default values:</p> <ul style="list-style-type: none"> ■ Map token: Map token to Partner ■ Enable Simple User Mapping: false ■ Enable User NameID Mapping: false ■ Enable Attribute Based User Mapping: false ■ Enable Simple Partner Mapping: false ■ Enable Partner NameID Mapping: false <p>Empty fields: User Token Attribute, User Datastore Attribute and Attribute Based User Mapping</p> <p>Also:</p> <ul style="list-style-type: none"> ■ Partner Token Attribute: NameID ■ Partner Datastore Attribute: username <p>Partner NameID Mapping table will be provisioned with the following entries as NameID format, but without any data in the datastore column:</p> <ul style="list-style-type: none"> ■ urn:oasis:names:tc:SAML:1.1:nameid-format:WindowsDomainQualified Name ■ urn:oasis:names:tc:SAML:1.1:nameid-format:X509SubjectName ■ urn:oasis:names:tc:SAML:1.1:nameid-format:emailAddress ■ urn:oasis:names:tc:SAML:1.1:nameid-format:unspecified ■ urn:oasis:names:tc:SAML:2.0:nameid-format:kerberos ■ urn:oasis:names:tc:SAML:2.0:nameid-format:persistent <p>User NameID Mapping table will be provisioned with the following entries as NameID format:</p> <ul style="list-style-type: none"> ■ urn:oasis:names:tc:SAML:1.1:nameid-format:WindowsDomainQualified Name, empty datastore column ■ urn:oasis:names:tc:SAML:1.1:nameid-format:X509SubjectName, dn set in the datastore column ■ urn:oasis:names:tc:SAML:1.1:nameid-format:emailAddress, mail set in the datastore column ■ urn:oasis:names:tc:SAML:1.1:nameid-format:unspecified, empty datastore column ■ urn:oasis:names:tc:SAML:2.0:nameid-format:kerberos, empty datastore column ■ urn:oasis:names:tc:SAML:2.0:nameid-format:persistent, empty datastore column

Table 4–13 (Cont.) Default Configuration: createWSSValidationTemplate

Token Type	Description
X.509	<p>The Token Mapping section will be created with the following default values:</p> <ul style="list-style-type: none"> ■ Map token: Map token to Partner ■ Enable Simple User Mapping: false ■ Enable Attribute Based User Mapping: false ■ Enable Simple Partner Mapping: true <p>Empty fields: User Token Attribute, User Datastore Attribute and Attribute Based User Mapping</p> <p>Also:</p> <ul style="list-style-type: none"> ■ Partner Token Attribute: DN ■ Partner Datastore Attribute: sslclientcertdn
Kerberos	<p>The Token Mapping section will be created with the following default values:</p> <ul style="list-style-type: none"> ■ Map token: Map token to User ■ Enable Simple User Mapping: true ■ Enable Attribute Based User Mapping: false ■ Enable Simple Partner Mapping: false <p>Empty fields: Partner Token Attribute, Partner Datastore Attribute and Attribute Based User Mapping</p> <p>Also:</p> <ul style="list-style-type: none"> ■ User Token Attribute: TPE_KERBEROS_PRINCIPAL_FULL ■ User Datastore Attribute: mail

4.8.39.2 Syntax

```
createWSSValidationTemplate(templateId, tokenType,
defaultRequesterPPID, description)
```

Argument	Definition
<i>templateId</i>	Specifies the name of the name of the validation template to be created.
<i>tokenType</i>	<p>Specifies the token type of the validation template. Possible values can be:</p> <ul style="list-style-type: none"> ■ username: indicates that the token type is UsernameToken ■ saml11: indicates that the token type is a SAML 1.1 Assertion ■ saml20: indicates that the token type is a SAML 2.0 Assertion ■ x509: indicates that the token type is an X.509 certificate ■ kerberos: indicates that the token type is a Kerberos token ■ oam: indicates that the token type is OAM
<i>defaultRequesterPPID</i>	Specifies the Requester partner profile to use if OSTs is configured not to map the incoming message to a requester.
<i>description</i>	Specifies an optional description.

4.8.39.3 Example

The following invocation creates a new validation template with default configuration data, and displays the result of the operation.

```
createWSSValidationTemplate(templateId="custom-wss-validtemp", tokenType="custom",
defaultRequesterPPID="requesterPartnerProfileTest", description="custom validation
template")
```

4.8.40 createWSTrustValidationTemplate

Online command that creates a new WS-Trust validation template with default configuration data.

4.8.40.1 Description

Creates a new WS-Trust validation template with default configuration data, and displays the result of the operation.

The WS-Trust validation template is created with the values in [Table 4–14](#), depending on the token type.

Table 4–14 Default Configuration: createWSTrustValidationTemplate

Token Type	Description
Username	<p>The WS-Trust validation template will be created with the following default values:</p> <ul style="list-style-type: none"> ■ Timestamp Lifespan: 600 seconds ■ Enable Credential Validation: false ■ Validation Source: User Store ■ Token Mapping: Map token to User ■ Enable Simple User Mapping: true ■ USer Datastore Attribute: uid

Table 4–14 (Cont.) Default Configuration: createWSTrustValidationTemplate

Token Type	Description
SAML 1.1 or SAML 2.0	<p>The WS-Trust validation template will be created with the following default values:</p> <ul style="list-style-type: none"> ■ Authentication Timeout: 3600 seconds ■ Timestamp Lifespan: 3600 seconds <p>The Token Mapping section will be created with the following default values:</p> <ul style="list-style-type: none"> ■ Map token: Map token to User ■ Enable Simple User Mapping: false ■ Enable User NameID Mapping: true ■ Enable Attribute Based User Mapping: false <p>Empty fields: User Datastore Attribute, Attribute Based User Mapping</p> <p>User NameID Mapping table will be provisioned with the following entries as NameID format:</p> <ul style="list-style-type: none"> ■ urn:oasis:names:tc:SAML:1.1:nameid-format:WindowsDomainQualifiedName, empty datastore column ■ urn:oasis:names:tc:SAML:1.1:nameid-format:X509SubjectName, dn set in the datastore column ■ urn:oasis:names:tc:SAML:1.1:nameid-format:emailAddress, mail set in the datastore column ■ urn:oasis:names:tc:SAML:1.1:nameid-format:unspecified, empty datastore column ■ urn:oasis:names:tc:SAML:2.0:nameid-format:kerberos, empty datastore column ■ urn:oasis:names:tc:SAML:2.0:nameid-format:persistent, empty datastore column
X.509	<p>The WS-Trust Token Mapping section will be created with the following default values:</p> <ul style="list-style-type: none"> ■ Map token: Map token to User ■ Enable Simple User Mapping: true ■ Enable Attribute Based User Mapping: false ■ Enable Simple Partner Mapping: true ■ User Token Attribute: CN ■ User Datastore Attribute: CN ■ Attribute Based User Mapping (empty)
Kerberos	<p>The WS-Trust Token Mapping section will be created with the following default values:</p> <ul style="list-style-type: none"> ■ Map token: Map token to User ■ Enable Simple User Mapping: true ■ Enable Attribute Based User Mapping: false ■ Attribute Based User Mapping (empty) ■ User Token Attribute: TPE_KERBEROS_PRINCIPAL_FULL ■ User Datastore Attribute: mail

Table 4–14 (Cont.) Default Configuration: createWSTrustValidationTemplate

Token Type	Description
OAM	<p>The WS-Trust Token Mapping section will be created with the following default values:</p> <ul style="list-style-type: none"> ▪ Map token: Map token to User ▪ Enable Simple User Mapping: true ▪ Enable Attribute Based User Mapping: false ▪ Attribute Based User Mapping (empty) ▪ User Token Attribute: TPE_NAME_ID ▪ User Datastore Attribute: uid
custom	<p>The WS-Trust Token Mapping section will be created with the following default values:</p> <ul style="list-style-type: none"> ▪ Map token: Map token to None ▪ Enable Simple User Mapping: false ▪ Enable Attribute Based User Mapping: false ▪ Attribute Based User Mapping (empty) ▪ User Token Attribute: (empty) ▪ User Datastore Attribute: (empty)

4.8.40.2 Syntax

```
createWSTrustValidationTemplate(templateId, tokenType, description)
```

Argument	Definition
<i>templateId</i>	Specifies the name of the name of the WS-Trust validation template to be created.
<i>tokenType</i>	<p>Specifies the token type of the WS-Trust validation template. Possible values can be:</p> <ul style="list-style-type: none"> ▪ username: indicates that the token type is UsernameToken ▪ saml11: indicates that the token type is a SAML 1.1 Assertion ▪ saml20: indicates that the token type is a SAML 2.0 Assertion ▪ x509: indicates that the token type is an X.509 certificate ▪ kerberos: indicates that the token type is a Kerberos token ▪ oam: indicates that the token type is an Oracle Access Manager token, supported by default ▪ <other>: in this case, the token type is assumed to be a custom token type, referenced by <other> (replace <other> by a value)
<i>description</i>	Specifies an optional description.

4.8.40.3 Example

The following invocation creates a new WS-Trust validation template with default configuration data, and displays the result of the operation.

```
createWSTrustValidationTemplate(templateId="custom-wss-validtemp",
tokenType="custom", description="custom validation template")
```

4.8.41 deleteValidationTemplate

Online command that deletes a validation template.

4.8.41.1 Description

Deletes a validation template referenced by the `validationTemplateId` parameter, and displays the result of the operation.

4.8.41.2 Syntax

```
deleteValidationTemplate(validationTemplateId)
```

Argument	Definition
<code>validationTemplateId</code>	Specifies the name of the validation template to be removed.

4.8.41.3 Example

The following invocation deletes a validation template referenced by the `validationTemplateId` parameter, and displays the result of the operation.

```
deleteValidationTemplate(validationTemplateId="custom-wss-validtemp")
```

4.9 Oracle Keystore Service

This section contains commands used with the OPSS keystore service.

Note: You need to acquire an OPSS handle to use keystore service commands. For details, see *Managing Keys and Certificates with the Keystore Service* in the *Oracle Fusion Middleware Application Security Guide*.

Table 4–15 lists the WLST commands used to manage the keystore service.

Table 4–15 OPSS Keystore Service Commands

Use this Command...	to...
<code>changeKeyPassword</code>	Change the password for a key.
<code>changeKeyStorePassword</code>	Change the password on a keystore.
<code>createKeyStore</code>	Create a keystore.
<code>deleteKeyStore</code>	Delete a keystore.
<code>deleteKeyStoreEntry</code>	Delete an entry in a keystore.
<code>exportKeyStore</code>	Export a keystore to file.
<code>exportKeyStoreCertificate</code>	Export a certificate to a file.
<code>exportKeyStoreCertificateRequest</code>	Export a certificate request to a file.
<code>generateKeyPair</code>	Generate a keypair.
<code>generateSecretKey</code>	Generate a secret key.
<code>getKeyStoreCertificates</code>	Get information about a certificate or trusted certificate.
<code>getKeyStoreSecretKeyProperties</code>	Get the secret key properties.
<code>importKeyStore</code>	Import a keystore from file.
<code>importKeyStoreCertificate</code>	Import a certificate or other object.

Table 4–15 (Cont.) OPSS Keystore Service Commands

Use this Command...	to...
listExpiringCertificates	List certificates expiring in a specified period.
listKeyStoreAliases	List aliases in a keystore.
listKeyStores	List all the keystores in a stripe.

4.9.1 changeKeyPassword

Changes a key password.

4.9.1.1 Description

Changes the password for a key.

4.9.1.2 Syntax

```
svc.changeKeyPassword(appStripe='stripe', name='keystore', password='password',
alias='alias', currentkeypassword='currentkeypassword',
newkeypassword='newkeypassword')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe containing the keystore
<i>name</i>	Specifies the name of the keystore
<i>password</i>	Specifies the keystore password
<i>alias</i>	Specifies the alias of the key entry whose password is changed
<i>currentkeypassword</i>	Specifies the current key password
<i>newkeypassword</i>	Specifies the new key password

4.9.1.3 Example

This example changes the password on the key entry `orakey`:

```
svc.changeKeyPassword(appStripe='system', name='keystore', password='password',
alias='orakey', currentkeypassword='currentkeypassword',
newkeypassword='newkeypassword')
```

4.9.2 changeKeyStorePassword

Changes the password of a keystore.

4.9.2.1 Description

Changes the password of the specified keystore.

4.9.2.2 Syntax

```
svc.changeKeyStorePassword(appStripe='stripe', name='keystore',
currentpassword='currentpassword', newpassword='newpassword')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe containing the keystore
<i>name</i>	Specifies the name of the keystore
<i>currentpassword</i>	Specifies the current keystore password
<i>newpassword</i>	Specifies the new keystore password

4.9.2.3 Example

This example changes the password for `keystore2`.

```
svc.changeKeyStorePassword(appStripe='system', name='keystore2',
currentpassword='currentpassword', newpassword='newpassword')
```

4.9.3 createKeyStore

This keystore service command creates a new keystore.

4.9.3.1 Description

Creates a new keystore on the given application stripe.

4.9.3.2 Syntax

```
svc.createKeyStore(appStripe='stripe', name='keystore',
password='password', permission=true|false)
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe where the keystore is created.
<i>name</i>	Specifies the name of the new keystore.
<i>password</i>	Specifies the keystore password.
<i>permission</i>	This parameter is true if the keystore is protected by permission only, false if protected by both permission and password.

4.9.3.3 Example

This example creates a keystore named `keystore1`.

```
svc.createKeyStore(appStripe='system', name='keystore1', password='password',
permission=true)
```

4.9.4 deleteKeyStore

Deletes the named keystore.

4.9.4.1 Description

This keystore service command deletes a specified keystore.

4.9.4.2 Syntax

```
svc.deleteKeyStore(appStripe='stripe', name='keystore', password='password')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe where the keystore resides.
<i>name</i>	Specifies the name of the keystore to be deleted.
<i>password</i>	Specifies the keystore password.

4.9.4.3 Example

This example deletes the keystore named `keystore1`.

```
svc.deleteKeyStore(appStripe='system', name='keystore1', password='password')
```

4.9.5 deleteKeyStoreEntry

Deletes a keystore entry.

4.9.5.1 Description

This command deletes the specified entry in a keystore.

4.9.5.2 Syntax

```
svc.deleteKeyStoreEntry(appStripe='stripe', name='keystore',
password='password', alias='alias', keypassword='keypassword')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe where the keystore resides.
<i>name</i>	Specifies the name of the keystore.
<i>password</i>	Specifies the keystore password.
<i>alias</i>	Specifies the alias of the entry to be deleted
<i>keypassword</i>	Specifies the key password of the entry to be deleted

4.9.5.3 Example

This example deletes a keystore entry denoted by alias `orakey`.

```
svc.deleteKeyStoreEntry(appStripe='system', name='keystore2', password='password',
alias='orakey', keypassword='keypassword')
```

4.9.6 exportKeyStore

Exports a keystore to a file.

4.9.6.1 Description

Exports a keystore to the specified file.

4.9.6.2 Syntax

```
svc.exportKeyStore(appStripe='stripe', name='keystore', password='password',
aliases='comma-separated-aliases', keypasswords='comma-separated-keypasswords',
type='keystore-type', filepath='absolute_file_path')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe where the keystore resides.
<i>name</i>	Specifies the name of the keystore.
<i>password</i>	Specifies the keystore password.
<i>aliases</i>	Comma separated list of aliases to be exported.
<i>keypasswords</i>	Comma separated list of the key passwords corresponding to aliases.
<i>type</i>	Exported keystore type. Valid values are 'JKS' or 'JCEKS'.
<i>filepath</i>	Absolute path of the file where keystore is exported.

4.9.6.3 Example

This example exports two aliases from the specified keystore.

```
svc.exportKeyStore(appStripe='system', name='keystore2',
password='password', aliases='orakey,seckey',
keypasswords='keypassword1,keypassword2',
type='JKS', filepath='/tmp/file.jks')
```

4.9.7 exportKeyStoreCertificate

Exports a certificate.

4.9.7.1 Description

Exports a certificate, trusted certificate or certificate chain.

4.9.7.2 Syntax

```
svc.exportKeyStoreCertificate(appStripe='stripe', name='keystore',
password='password', alias='alias', keypassword='keypassword',
type='entrytype', filepath='absolute_file_path')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe where the keystore resides.
<i>name</i>	Specifies the name of the keystore.
<i>password</i>	Specifies the keystore password.
<i>alias</i>	Specifies the alias of the entry to be exported
<i>keypassword</i>	Specifies the key password.
<i>type</i>	Specifies the type of keystore entry to be exported. Valid values are 'Certificate', 'TrustedCertificate' or 'CertificateChain'.

Argument	Definition
<i>filepath</i>	Specifies the absolute path of the file where certificate, trusted certificate or certificate chain is exported.

4.9.7.3 Example

This example exports a certificate corresponding to the `orakey` alias:

```
svc.exportKeyStoreCertificate(appStripe='system', name='keystore2',
password='password', alias='orakey', keypassword='keypassword',
type='Certificate', filepath='/tmp/cert.txt')
```

4.9.8 exportKeyStoreCertificateRequest

Exports a certificate request.

4.9.8.1 Description

Generates and exports a certificate request from a keystore.

4.9.8.2 Syntax

```
svc.exportKeyStoreCertificateRequest(appStripe='stripe', name='keystore',
password='password', alias='alias', keypassword='keypassword',
filepath='absolute_file_path')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe where the keystore resides.
<i>name</i>	Specifies the name of the keystore.
<i>password</i>	Specifies the keystore password.
<i>alias</i>	Specifies the entry's alias name.
<i>keypassword</i>	Specifies the key password.
<i>filepath</i>	Specifies the absolute path of the file where certificate request is exported.

4.9.8.3 Example

This example exports a certificate request corresponding to the `orakey` alias.

```
svc.exportKeyStoreCertificateRequest(appStripe='system', name='keystore2',
password='password', alias='orakey', keypassword='keypassword',
filepath='/tmp/certreq.txt')
```

4.9.9 generateKeyPair

Generates a key pair in a keystore.

4.9.9.1 Description

Generates a key pair in a keystore and wraps it in a demo CA-signed certificate.

4.9.9.2 Syntax

```
svc.generateKeyPair(appStripe='stripe', name='keystore', password='password',
```



```
dn='distinguishedname', keysize='keysize', alias='alias',
keypassword='keypassword')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe where the keystore resides.
<i>name</i>	Specifies the name of the keystore.
<i>password</i>	Specifies the keystore password.
<i>dn</i>	Specifies the distinguished name of the certificate wrapping the key pair.
<i>keysize</i>	Specifies the key size.
<i>alias</i>	Specifies the alias of the key pair entry.
<i>keypassword</i>	Specifies the key password.

4.9.9.3 Example

This example generates a keypair in `keystore2`.

```
svc.generateKeyPair(appStripe='system', name='keystore2', password='password',
dn='cn=www.oracle.com', keysize='1024', alias='orakey', keypassword='keypassword')
```

4.9.10 generateSecretKey

Generates a secret key.

4.9.10.1 Description

Generates a symmetric key in a keystore.

4.9.10.2 Syntax

```
svc.generateSecretKey(appStripe='stripe', name='keystore', password='password',
algorithm='algorithm', keysize='keysize', alias='alias',
keypassword='keypassword')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe where the keystore resides.
<i>name</i>	Specifies the name of the keystore.
<i>password</i>	Specifies the keystore password.
<i>algorithm</i>	Specifies the symmetric key algorithm.
<i>keysize</i>	Specifies the key size.
<i>alias</i>	Specifies the alias of the key entry.
<i>keypassword</i>	Specifies the key password.

4.9.10.3 Example

This example generates a keypair with keysize 128 in `keystore2`.

```
svc.generateSecretKey(appStripe='system', name='keystore2', password='password',
```

```
algorithm='AES', keysize='128', alias='seckey', keypassword='keypassword')
```

4.9.11 getKeyStoreCertificates

Gets a certificate from the keystore.

4.9.11.1 Description

Retrieves information about a certificate or trusted certificate.

4.9.11.2 Syntax

```
svc.getKeyStoreCertificates(appStripe='stripe', name='keystore',
password='password', alias='alias', keypassword='keypassword')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe where the keystore resides.
<i>name</i>	Specifies the name of the keystore.
<i>password</i>	Specifies the keystore password.
<i>alias</i>	Specifies the alias of the certificate, trusted certificate or certificate chain to be displayed.
<i>keypassword</i>	Specifies the key password.

4.9.11.3 Example

This example gets certificates associated with `keystore3`.

```
svc.getKeyStoreCertificates(appStripe='system', name='keystore3',
password='password', alias='orakey', keypassword='keypassword')
```

4.9.12 getKeyStoreSecretKeyProperties

Retrieves secret key properties.

4.9.12.1 Description

Retrieves secret key properties like the algorithm.

4.9.12.2 Syntax

```
svc.getKeyStoreSecretKeyProperties(appStripe='stripe', name='keystore',
password='password', alias='alias', keypassword='keypassword')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe where the keystore resides.
<i>name</i>	Specifies the name of the keystore.
<i>password</i>	Specifies the keystore password.
<i>alias</i>	Specifies the alias of the secret key whose properties are displayed.

Argument	Definition
<i>keypassword</i>	Specifies the secret key password.

4.9.12.3 Example

This example gets properties for secret key `seckey`:

```
svc.getKeyStoreSecretKeyProperties(appStripe='system', name='keystore3',
password='password', alias='seckey', keypassword='keypassword')
```

4.9.13 importKeyStore

Imports a keystore from file.

4.9.13.1 Description

Imports a keystore from a system file.

4.9.13.2 Syntax

```
svc.importKeyStore(appStripe='stripe', name='keystore', password='password',
aliases='comma-separated-aliases', keypasswords='comma-separated-keypasswords',
type='keystore-type', permission=true|false, filepath='absolute_file_path')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe where the keystore resides.
<i>name</i>	Specifies the name of the keystore.
<i>password</i>	Specifies the keystore password.
<i>aliases</i>	Specifies the comma-separated aliases of the entries to be imported from file.
<i>keypasswords</i>	Specifies the comma-separated passwords of the keys in file.
<i>type</i>	Specifies the imported keystore type. Valid values are 'JKS' or 'JCEKS'.
<i>filepath</i>	Specifies the absolute path of the keystore file to be imported.
<i>permission</i>	Specifies true if keystore is protected by permission only, false if protected by both permission and password.

4.9.13.3 Example

This example imports a file to `keystore2`:

```
svc.importKeyStore(appStripe='system', name='keystore2',
password='password', aliases='orakey,seckey', keypasswords='keypassword1,
keypassword2', type='JKS', permission=true, filepath='/tmp/file.jks')
```

4.9.14 importKeyStoreCertificate

Imports a certificate or other specified object.

4.9.14.1 Description

Imports a certificate, trusted certificate or certificate chain.

4.9.14.2 Syntax

```
svc.importKeyStoreCertificate(appStripe='stripe', name='keystore',
password='password', alias='alias', keypassword='keypassword',
type='entrytype', filepath='absolute_file_path')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe where the keystore resides.
<i>name</i>	Specifies the name of the keystore.
<i>password</i>	Specifies the keystore password.
<i>alias</i>	Specifies the alias of the entry to be imported.
<i>keypassword</i>	Specifies the key password of the newly imported entry.
<i>type</i>	Specifies the type of keystore entry to be imported. Valid values are 'Certificate', 'TrustedCertificate' or 'CertificateChain'.
<i>filepath</i>	Specifies the absolute path of the file from where certificate, trusted certificate or certificate chain is imported.

4.9.14.3 Example

This example imports a certificate into `keystore2`.

```
svc.importKeyStoreCertificate(appStripe='system', name='keystore2',
password='password', alias='orakey', keypassword='keypassword',
type='Certificate', filepath='/tmp/cert.txt')
```

4.9.15 listExpiringCertificates

Lists expiring certificates.

4.9.15.1 Description

Lists expiring certificates and optionally renews them.

4.9.15.2 Syntax

```
svc.listExpiringCertificates(days='days', autorenew=true|false)
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>days</i>	Specifies that the list should only include certificates within this many days from expiration.
<i>autorenew</i>	Specifies true for automatically renewing expiring certificates, false for only listing them.

4.9.15.3 Example

This example lists certificates expiring within one year, and requests that they be renewed:

```
svc.listExpiringCertificates(days='365', autorenew=true)
```

4.9.16 listKeyStoreAliases

Lists the aliases in a keystore.

4.9.16.1 Description

Lists the aliases in a keystore for a given type of entry.

4.9.16.2 Syntax

The syntax is as follows:

```
svc.listKeyStoreAliases(appStripe='stripe', name='keystore',
password='password', type='entrytype')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe where the keystore resides.
<i>name</i>	Specifies the name of the keystore.
<i>password</i>	Specifies the keystore password.
<i>type</i>	Specifies the type of entry for which aliases are listed. Valid values are 'Certificate', 'TrustedCertificate', 'SecretKey' or '*'.

4.9.16.3 Example

This example lists secret keys in `keystore2`:

```
svc.listKeyStoreAliases(appStripe='system', name='keystore2',
password='password', type='SecretKey')
```

4.9.17 listKeyStores

Lists all the keystores in a stripe.

4.9.17.1 Description

Lists all the keystores in the specified stripe.

4.9.17.2 Syntax

```
svc.listKeyStores(appStripe='stripe')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe whose keystores are listed.

4.9.17.3 Example

This example lists all keystores on all stripes.

```
svc.listKeyStores(appStripe='*')
```

User Messaging Service (UMS) Custom WLST Commands

This chapter provides detailed descriptions of custom WLST commands for UMS, including command syntax, arguments and command examples.

Use the User Messaging Service commands, listed in [Table 5–1](#), to download user messaging preferences from your backend database.

Note: To use these commands, you must invoke WLST from the Oracle home in which the component has been installed. See "Using Custom WLST Commands" in the *Oracle Fusion Middleware Administrator's Guide*.

Table 5–1 User Messaging Service for WLST Configuration

Command category	Description
Section 5.1, "UMS WLST Command Group"	Manage Oracle Unified Messaging Service commands.

5.1 UMS WLST Command Group

The UMS WLST commands are listed under the command group "ums".

5.1.1 manageUserMessagingPrefs

Command Category: UMS

Use with WLST: Offline

5.1.1.1 Description

`manageUserMessagingPrefs` is used to download the user messaging preferences from a backend database to the specified XML file, or to upload the user messaging preferences from an XML file into the backend database.

5.1.1.2 Syntax

```
manageUserMessagingPrefs (operation=, filename, url, username, password,
[encoding], [guid], [merge] )
```

Argument	Definition
operation	specifies the upload or download operation to be performed.
filename	For download, a unique file name (path) to download the user preferences to. For example, /tmp/download.xml (Linux) or C:\\temp\\download.xml (Windows). For upload, the file name (path) from which to upload the user preferences.
url	The JNDI URL to access the User Messaging Server. For example: t3://<hostname>:<port>
username	The username with login permission to access the User Messaging Server.
password	The password of the username.
encoding	Character encoding to use to download the user preferences.
guid	The globally unique identifier (guid) of a list of users to use to download their preferences. If no guid is specified, the preferences for all users are downloaded.
merge	This option is for upload only. Valid values are: create_new (default): Create new user device, device addresses and/or ruleset entities. An exception will be thrown if an entity with the same primary key already exists and processing will terminate. overwrite: Remove all existing entities of a user and then create new entities. append: Only upload entities that do not already exist.

5.1.1.3 Examples

To download the user messaging preferences of all users to the specified file.

```
wls:offline> manageUserMessagingPrefs(operation='download',
filename='download.xml', url='t3://localhost:8001', username='weblogic',
password='<password>')
```

To download the user messaging preferences of all users to the specified file using UTF-8 character encoding.

```
wls:offline> manageUserMessagingPrefs(operation='download',
filename='download.xml', url='t3://localhost:8001', username='weblogic',
password='<password>', encoding='UTF-8')
```

To download the user messaging preferences of the user with guid 'john.doe' to the specified file.

```
wls:offline> manageUserMessagingPrefs(operation='download',
filename='download.xml', url='t3://localhost:8001', username='weblogic',
password='<password>', guid='john.doe')
```

To download the user messaging preferences of the users with guid 'john.doe' and 'jane.doe' to the specified file using UTF-8 character encoding.

```
wls:offline> manageUserMessagingPrefs(operation='download',
filename='download.xml', url='t3://localhost:8001', username='weblogic',
password='<password>', guid='john.doe,jane.doe', encoding='UTF-8')
```

To upload the user messaging preferences from the specified file to the backend database.


```
wls:offline> manageUserMessagingPrefs(operation='upload', filename='upload.xml',
url='t3://localhost:8001', username='weblogic', password='<password>')
```

To upload the user messaging preferences from the specified file to the backend database and overwrite existing preferences.

```
wls:offline> manageUserMessagingPrefs(operation='upload', filename='upload.xml',
url='t3://localhost:8001', username='weblogic', password='<password>',
merge='overwrite')
```

5.1.2 deployUserMessagingDriver

Command Category: UMS

Use with WLST: Online

5.1.2.1 Description

`deployUserMessagingDriver` is used to deploy additional instances of user messaging drivers.

Specify a base driver type (for example: email, xmpp, voicexml, and others) and a short name for the new driver deployment. The string *usermessagingdriver-* will be prepended to the specified application name. Any valid parameters for the *deploy* command can be specified, and will be passed through when the driver is deployed.

5.1.2.2 Syntax

```
deployUserMessagingDriver(baseDriver, appName, [targets], [stageMode],
[options])
```

Argument	Definition
baseDriver	Specifies the base messaging driver type. Must be a known driver type, such as 'email', 'proxy', 'smp', 'voicexml', or 'xmpp'.
appName	A short descriptive name for the new deployment. The specified value will be prepended with the string <i>usermessagingdriver-</i>
targets	Optional. Additional arguments that are valid for the <i>deploy</i> command can be specified and will be passed through when the new driver is deployed.
stageMode	
options	

5.1.2.3 Examples

To deploy a second instance of an email driver with name *myEmail*.

```
wls:base_domain/serverConfig> deployUserMessagingDriver(baseDriver='email',
appName='myEmail')
```

To deploy a second instance of an email driver, specifying deployment targets.

```
wls:base_domain/serverConfig> deployUserMessagingDriver(baseDriver='email',
appName='email2', targets='server1,server2')
```

DMS Custom WLST Commands

This chapter provides detailed descriptions of custom WLST commands for Dynamic Monitoring Service (DMS), which you can use to view performance metrics and to configure Event Tracing. This chapter includes command syntax, arguments and command examples.

Note: To use these DMS custom WLST commands, you must invoke the WLST script from the Oracle Common home. See "Using Custom WLST Commands" in the *Oracle Fusion Middleware Administrator's Guide*.

Use the DMS commands in the categories in [Table 6–1](#) to view performance metrics and to configure Event Tracing.

Table 6–1 DMS Command Categories

Command category	Description
DMS Metric Commands	View information about performance metrics.
DMS Event Tracing Commands	Configure Event Tracing

6.1 DMS Metric Commands

Use the commands in [Table 6–2](#) to view information about a specific performance metric, a set of performance metrics, or all performance metrics for a particular server or component.

For additional details about metrics, see the chapter "Monitoring Oracle Fusion Middleware" in the *Oracle Fusion Middleware Administrator's Guide* and the appendix "Understanding the Oracle Dynamic Monitoring Service" in the *Oracle Fusion Middleware Performance and Tuning Guide*.

Table 6–2 DMS Commands

Use this command...	To...	Use with WLST...
displayMetricTableNames	Displays the names of the available DMS metric tables.	Online
displayMetricTables	Displays the content of the DMS metric tables.	Online
dumpMetrics	Displays available metrics.	Online
reloadMetricRules	Reloads the metric rules.	Online

6.1.1 displayMetricTableNames

Command Category: DMS Metrics

Use with WLST: Online

6.1.1.1 Description

Displays the names of the available DMS metric tables. The returned value is a list of metric table names.

6.1.1.2 Syntax

```
displayMetricTableNames([servers])
```

Argument	Definition
<i>servers</i>	<p>Optional. Specifies the servers from which to retrieve metrics. Valid values are a list of WebLogic Server instance names and system component names.</p> <p>To specify one server, use the following syntax:</p> <pre>servers='servername'</pre> <p>To specify multiple servers, use one of the following syntax options:</p> <pre>servers=['servername1', 'servername2', ...]</pre> <pre>servers=('servername1', 'servername2', ...)</pre> <p>If this argument is not specified, the command returns the list of metric table names for all WebLogic servers and system components.</p> <p>Note that the name of a system component instance is not a fixed string. It is the UID of the instance. The UID changes at each instance restart. The UID uses the format:</p> <pre>/install_type/component_type/UID</pre> <p>To find the UID, use the following OPMN command:</p> <pre>opmnctl status -l</pre>

6.1.1.3 Examples

The following example displays metric table names for all WebLogic servers and system components:

```
displayMetricTableNames()
ADF
ADFc
ADFc_Metadata_Service
ADFc_Region
ADFc_Taskflow
ADFc_Viewport
BAM_common_connectionpool
BAM_common_connectionpool_main
BAM_common_messaging
BAM_common_messaging_consumers
.
.
.
```

The following example displays metric table names for the WebLogic Managed Server `soa_server1`:

```
displayMetricTableNames(servers='soa_server1')
ADF
```

```
JVM
JVM_ClassLoader
JVM_Compiler
JVM_GC
JVM_Memory
JVM_MemoryPool
JVM_MemorySet
JVM_OS
JVM_Runtime
.
.
.
```

The following example displays metric table names for two WebLogic Managed Servers:

```
displayMetricTableNames(servers=['soa_server1', 'bam-server1'])
ADF
ADFc
ADFc_Metadata_Service
ADFc_Region
ADFc_Taskflow
ADFc_Viewport
BAM_common_connectionpool
BAM_common_connectionpool_main
BAM_common_messaging
BAM_common_messaging_consumers
.
.
.
```

The following example displays the metric table names for Oracle Web Cache. Note that the name of a system component instance is not a fixed string. It includes the UID of the instance, which changes at each instance restart. To find the UID, use the following OPMN command:

```
opmnctl status -l
```

Then, use the display MetricTableNames command. For example:

```
displayMetricTableNames(servers=('/web_tier/webcache1/123456789'))
```

6.1.2 displayMetricTables

Command Category: DMS Metrics

Use with WLST: Online

6.1.2.1 Description

Displays the content of the DMS metric tables.

The returned value is list of DMS metric tables, with the following information about each table:

- The metric table name.
- The metric table schema information.
- The metric table Rows.

The metric table schema information contains the following:

- The name of the column.

- The type of the column value.
- The unit of the column.
- The description of the column.

6.1.2.2 Syntax

```
displayMetricTables([metricTable_1] [, metricTable_2], [...] [, servers]
                    [, variables])
```

Argument	Definition
<i>metricTable_n</i>	<p>Optional. Specifies a list of metric tables. By default, this argument displays all available metrics. The metric table name can contain special characters for simple pattern matching. The character '?' matches any single character. The character '*' matches zero or more characters.</p> <p>You specify the metric table name. You can specify multiple metric table names in a comma-separated list.</p> <p>These are the same names output by the WLST command <code>displayMetricTableNames</code>.</p>
<i>servers</i>	<p>Optional. Specifies the servers from which to retrieve metrics. Valid values are a list of WebLogic Server instance names and system component names.</p> <p>To specify one server, use the following syntax:</p> <pre>servers='servername'</pre> <p>To specify multiple servers, use one of the following syntax options:</p> <pre>servers=['servername1', 'servername2', ...] servers=('servername1', 'servername2', ...)</pre> <p>If this argument is not specified, the command returns the list of metric tables for all WebLogic servers and system components.</p> <p>Note that the name of a system component instance is not a fixed string. It is the UID of the instance. The UID changes at each instance restart. The UID uses the format:</p> <pre>/install_type/component_type/UID</pre> <p>To find the UID, use the following OPMN command:</p> <pre>opmnctl status -l</pre>
<i>variables</i>	<p>Optional. Defines the metric aggregation parameters. Valid values are a set of name-value pairs. It uses the following syntax:</p> <pre>variables={name1:value1, name2:value2, ...}</pre> <p>The specific name-value pairs depend on the aggregated metric tables. Each aggregated metric table has its specific set of variable names.</p>

6.1.2.3 Examples

The following example displays the data from the JVM and the `weblogic.management.runtime.WebAppComponentRuntimeMBean` metric tables, and limits it to data retrieved from `soa_server1` and `bam_server1`:

```
displayMetricTables('JVM','weblogic.management.runtime.WebAppComponentRuntimeMBean',
                    servers=['soa_server1','bam_server1'])
.
.
.
ApplicationRuntime:      soa-infra
ComponentName:          /integration/services/IdentityService
ContextRoot:            /integration/services/IdentityService
DeploymentState:        2
```

```

FilterDispatchedRequestsEnabled:      false
IndexDirectoryEnabled:  false
JSPDebug:          false
JSPKeepGenerated:   false
JSPPageCheckSecs:   1
JSPVerbose:        true
ModuleId:           /integration/services/IdentityService
ModuleURI:          IdentityService.war
Name:               soa_server1_/integration/services/IdentityService
ObjectName:         com.bea:ApplicationRuntime=soa-infra,Name=soa_server1_
/integration/services/IdentityService,
ServerRuntime=soa_server1,Type=WebAppComponentRuntime
OpenSessionsCurrentCount: 0
OpenSessionsHighCount: 0
.
.
.

```

The following example displays the aggregated metric tables with the specified metric aggregation parameters:

```

displayMetricTables('j2ee_application:webservices_port_rollup',
  servers=['soa_server1','bam_server1'],
  variables={'host':'hostname', 'servletName':'dms'})

```

```

-----
j2ee_application:webservices_port_rollup
-----

```

```

Faults: 0
Requests: 0
Requests.averageTime: 0.0
Requests.totalTime: 0.0
ServerName: soa_server1
moduleName: RuntimeConfigService
moduleType: WEBS
portName: RuntimeConfigServicePortSAML
processRequest.active: 0
service.throughput: 0.0
service.time: 0.0
startTime: 1238182359291
webserviceName: RuntimeConfigService

```

```

Faults: 0
Requests: 0
Requests.averageTime: 0.0
Requests.totalTime: 0.0
ServerName: soa_server1
moduleName: TaskMetadataService
moduleType: WEBS
portName: TaskMetadataServicePort
processRequest.active: 0
service.throughput: 0.0
service.time: 0.0
startTime: 1238182358096
webserviceName: TaskMetadataService

```

```

.
.
.

```

The following example displays the metric tables which names match the specified patterns:

```
displayMetricTables('J??', 'JVM_*')
.
.
.
-----
JVM_ThreadStats
-----

Host:    hostname.com
JVM:    JVM
Name:    threads
Parent:  /JVM/MxBeans
Process:      AdminServer:9001
ServerName:   AdminServer
contention.value:  enabled in JVM
daemon.value:  60      threads
deadlock.value:  0      threads
live.value:    61      threads
peak.value:    66      threads
started.value:  241     threads

Host:    hostname.com
JVM:    JVM
Name:    threads
Parent:  /JVM/MxBeans
Process:      soa_server1:9001
ServerName:   soa_server1
contention.value:  enabled in JVM
daemon.value:  68      threads
deadlock.value:  0      threads
live.value:    74      threads
peak.value:    74      threads
started.value:  105     threads
.
.
.
```

6.1.3 dumpMetrics

Command Category: DMS Metrics

Use with WLST: Online

6.1.3.1 Description

Displays available metrics in the internal format or in XML. The returned value is a text document.

6.1.3.2 Syntax

```
dumpMetrics([servers] [, format])
```


Argument	Definition
<i>servers</i>	<p>Optional. Specifies the servers from which to retrieve metrics. Valid values are a list of WebLogic Server instance names and system component names.</p> <p>To specify one server, use the following syntax:</p> <pre>servers='servername'</pre> <p>To specify multiple servers, use one of the following syntax options:</p> <pre>servers=['servername1', 'servername2', ...] servers=('servername1', 'servername2', ...)</pre> <p>If this argument is not specified, the command returns the list of metric tables for all WebLogic servers and system components.</p> <p>Note that the name of a system component instance is not a fixed string. It is the UID of the instance. The UID changes at each instance restart. The UID uses the format:</p> <pre>/install_type/component_type/UID</pre> <p>To find the UID, use the following OPMN command:</p> <pre>opmnctl status -l</pre>
<i>format</i>	<p>Optional. Specifies the command output format. Valid values are 'raw' (the default), 'xml', and 'pdml'. For example:</p> <pre>format='raw' format='xml' format='pdml'</pre> <p>DMS raw format is a simple metric display format; it displays one metric per line.</p>

6.1.3.3 Examples

The following example outputs all available metrics, including native WebLogic Server metrics and internal DMS metrics, in the XML format:

```
dumpMetrics(format='xml')
<table name='weblogic_j2eeserver:jvm' keys='ServerName serverName'
  componentId='bam_server1' cacheable='false'>
<row cacheable='false'>
<column name='serverName'><![CDATA[bam_server1]]></column>
<column name='nurserySize.value' type='DOUBLE'>0.0</column>
<column name='jdkVersion.value'><![CDATA[1.6.0_05]]></column>
<column name='jdkVendor.value'><![CDATA[BEA Systems, Inc.]]></column>
<column name='daemonThreads.active' type='LONG'>68</column>
<column name='cpuUsage.percentage' type='DOUBLE'>100.0</column>
<column name='threads.active' type='LONG'>71</column>
<column name='ServerName'><![CDATA[bam_server1]]></column>
<column name='heapUsed.value' type='DOUBLE'>0.0</column>
</row>
```

The following example outputs metrics from Server-0 in the default raw format:

```
dumpMetrics(servers='Server-0')
.
.
.
/JVM/MxBeans/threads/Thread-44 [type=JVM_Thread]
ECID.value:      null
RID.value: null
blocked.value:   0      msec
blockedCount.value: 1      times
cpu.value: 40      msecs
```

```

lockName.value:    null
lockOwnerID.value: null
lockOwnerName.value:    null
name.value:        LDAPConnThread-0 ldap://10.229.149.27:7001
state.value:       RUNNABLE
waited.value:      0      msec
waitedCount.value: 0      times
/JVM/MxBeans/threads/Thread-45 [type=JVM_Thread]
ECID.value:        null
RID.value: null
blocked.value:     0      msec
.
.
.

```

The following example outputs metrics from `soa_server1` and `bam_server1` in XML format:

```

dumpMetrics(servers=['soa_server1', 'bam_server1'], format='xml')
<table name='oracle_soainfra:high_latency_sync_composites' keys='ServerName
soainfra_composite soainfra_composite_revision soainfra_domain'
componentId='bam_server1' cacheable='false'>
</table>
<table name='weblogic_j2eeserver:ejb_transaction' keys='ServerName appName
ejbModuleName name serverName' componentId='bam_server1' cacheable='false'>
<row cacheable='false'>
<column name='serverName'><![CDATA[bam_server1]]></column>
<column name='name'><![CDATA[MessagingClientParlayX]]></column>
<column name='ejbTransactionCommit.percentage' type='DOUBLE'>0.0</column>
<column name='ejbTransactionRollback.completed' type='LONG'>0</column>
<column name='ejbTransactionTimeout.throughput' type='DOUBLE'>0.0</column>
<column name='ejbTransactionCommit.completed' type='LONG'>0</column>
<column name='ejbTransactionTimeout.completed' type='LONG'>0</column>
<column name='appName'><![CDATA[usermessagingserver]]></column>
<column name='ejbTransactionRollback.throughput' type='DOUBLE'>0.0</column>
<column name='ServerName'><![CDATA[bam_server1]]></column>
<column name='ejbTransactionCommit.throughput' type='DOUBLE'>0.0</column>
<column
name='ejbModuleName'><![CDATA[sdpMessagingClient-ejb-parlayx.jar]]></column>
</row>
.
.
.

```

6.1.4 reloadMetricRules

Command Category: DMS Metrics

Use with WLST: Online

6.1.4.1 Description

Reloads the metric rules. You must run this command after you deploy system components or after you modify metric rules. Generally, Oracle does not recommend that you modify metric rules.

6.1.4.2 Syntax

```
reloadMetricRules()
```

6.1.4.3 Example

The following example reloads metric rules for all servers running in the domain:

```
reloadMetricRules()
```

```
Location changed to domainRuntime tree. This is a read-only tree with DomainMBean
as the root.
```

```
For more help, use help(domainRuntime)
```

```
loaded 'server-oracle_eps_server-11.0.xml'
loaded 'server-weblogic_j2eeserver-11.0.xml'
loaded 'server-oracle_bamweb-11.0.xml'
loaded 'server-oracle_federation-11.0.xml'
loaded 'server-portal-11.0.xml'
loaded 'server-weblogic_j2ee_application_webcenter-11.0.xml'
.
.
.
```

6.2 DMS Event Tracing Commands

Use the commands in [Table 6–3](#) to configure Event Tracing. Event Tracing configures live tracing with no restarts. DMS metrics that were updated using Oracle Fusion Middleware products may be traced using the DMS Event Tracing feature.

For information about using DMS Event Tracing, see "DMS Tracing and Events" in the *Oracle Fusion Middleware Performance and Tuning Guide*.

Table 6–3 DMS Tracing Commands

Use this command...	To...	Use with WLST...
addDMSEventDestination	Add a new destination to the Event Tracing configuration.	Online
addDMSEventFilter	Add a filter to the Event Tracing configuration.	Online
addDMSEventRoute	Adds the specified event route to the Event Tracing configuration	Online
enableDMSEventTrace	Enable an event trace and create a filter with a specified condition and destination and an enabled event-route.	Online
listDMSEventConfiguration	Display an overview of the event tracing configuration.	Online
listDMSEventDestination	Display the full configuration for a destination or a list of all destinations.	Online
listDMSEventFilter	Displays the configuration of a filter or a list of all filters.	Online
listDMSEventRoutes	Displays event routes and their status (enabled or disabled).	Online
removeDMSEventDestination	Removes the specified destination.	Online
removeDMSEventFilter	Removes the specified filter.	Online
removeDMSEventRoute	Removes the specified event route.	Online
updateDMSEventDestination	Updates configuration of an event destination.	Online
updateDMSEventFilter	Updates the configuration of an event filter.	Online
updateDMSEventRoute	Updates the configuration of an event route.	Online

6.2.1 addDMSEventDestination

Command Category: DMS Event Tracing

Use with WLST: Online

6.2.1.1 Description

Adds a new destination to the Event Tracing configuration. If a destination with the same ID already exists, the command reports this and does not add the destination. You must be connected to the Administration Server to add a destination. If you are not, an error is returned.

6.2.1.2 Syntax

```
addDMSEventDestination(id=id [, name=dest_name] ,class=class_name
    [, props= {'name': 'value'...}] [,server=server_name])
```

Argument	Definition
<code>id</code>	The unique identifier for the specified destination.
<code>name</code>	Optional. A name for the destination.
<code>class</code>	The full class name of the destination. See Table 6-4 for a list of available classes.
<code>props</code>	Optional. The name/value properties to use for the destination. Some destinations require properties. For example, the <code>LoggerDestination</code> class requires the property <code>loggerName</code> . See addDMSEventFilter for information about the syntax and allowed values.
<code>server</code>	Optional. The server on which to perform this operation. The default is the server to which you are connected.

[Table 6-4](#) shows the built-in destinations, with the full runtime class name.

Table 6-4 Built-In Destinations

Runtime Destination Class Name	Description
<code>oracle.dms.trace2.runtime.LoggerDestination</code>	Uses ODL to send the log messages to a file.
<code>oracle.dms.event.HTTPRequestTrackerDestination</code>	Dumps the set of active HTTP requests, allowing an administrator to get a snapshot of activity.
<code>oracle.dms.jrockit.jfr.JFRDestination</code>	Passes events to the JRockit Flight Recorder so that they can be viewed in the context of other data coming from the JRockit JVM and WLDF using JRockit Mission Control.
<code>oracle.dms.jmx.MetricMBeanFactory</code>	Exposes Nouns as MBeans.
<code>oracle.dms.util.StackTraceCollatorDestination</code>	Collates the stack traces that are in play whenever the events of interest occur. This is primarily a debugging tool. The collated data is written out on shutdown, and also when an event being handled has not been reported for a certain period of time (defaults to one minute).

6.2.1.3 Examples

The following example adds a destination with the ID `jfr`, the name `Flight-Recorder`, and the class `oracle.dms.event.JRockitFlightRecorder`:

```
addDMSEventDestination(id='jfr', name='Flight-Recorder',
                       class='oracle.dms.event.JRockitFlightRecorder')
```

Destination "jfr" added.

The following example adds a destination with the ID `destination1`, the name `File-system`, the class `oracle.dms.trace2.runtime.LoggerDestination`. Because the `LoggerDestination` requires the property `loggerName`, it sets the value to `trace2-logger`:

```
addDMSEventDestination(id='destination1', name='File-system',
                       class='oracle.dms.trace2.runtime.LoggerDestination',
                       props={'loggerName': 'trace2-logger'})
```

Destination "destination1" added.

The following example attempts to add a destination with an ID that already exists:

```
addDMSEventDestination(id='destination1', name='File-system',
                       class='oracle.dms.trace2.runtime.LoggerDestination',
                       props={'loggerName': 'trace2-logger'})
```

Destination "destination1" already exists. Unable to add this.

6.2.2 addDMSEventFilter

Command Category: DMS Event Tracing

Use with WLST: Online

6.2.2.1 Description

Adds a filter to the Event Tracing configuration. If a filter with the same ID already exists, the command returns an error and does not add the filter.

You must be connected to the Administration Server to add an event filter. If you are not, an error message is reported.

6.2.2.2 Syntax

```
addDMSEventFilter(id=id [, name=name] [, etypes]
                  , props= {'prop-name': 'value'...}
                  [, server=server_name])
```

Argument	Definition
<code>id</code>	The unique identifier for specified filter.
<code>name</code>	Optional. The name of the filter.
<code>etypes</code>	Optional. A string containing a comma-separated list of event/action pairs. This argument allows you to create a filter with a broader granularity when used with a condition. It also allows you to create a filter with a broader range of metrics. For example, all nouns or all nouns with the action create.
<code>props</code>	<i>prop-name</i> : The name of the filter property. <code><condition></code> is the only valid property, and only one condition may be specified. <i>value</i> : The value of the property of the filter.

Argument	Definition
<i>server</i>	Optional. The server on which to perform this operation. The default is the server to which you are connected.

The following shows the syntax for `etypes`:

```
<etypes> ::=  
<type>:[<action>]
```

The following lists the valid etypes:

```
EXECUTION_CONTEXT  
EXECUTION_CONTEXT:START  
EXECUTION_CONTEXT:STOP  
HTTP_REQUEST  
HTTP_REQUEST:START  
HTTP_REQUEST:STOP  
NOUN  
NOUN:CREATE  
NOUN:DELETE  
STATE_SENSOR  
STATE_SENSOR:CREATE  
STATE_SENSOR:DELETE
```

The following shows an etype with two event/action pairs, separated by a comma:

```
etypes='NOUN:DELETE, STATE_SENSOR:DELETE'
```

The following shows the syntax for the `<condition>` property of the argument `props`. The arguments are described in the tables following the syntax:

```
<condition> ::=  
<type> [<operator> <condition>]
```

```
<type> ::=  
<nountype> | <context>
```

```
<nountype> ::=  
NOUNTYPE <nountype-operator> value
```

```
<nountype-operator> ::=  
"equals" | "starts_with" | "contains" | "not_equals"
```

```
<context> ::=  
CONTEXT <name> <context-operator> [<value>] [IGNORECASE=true|false]  
[DATATYPE="string|long|double"  
]
```

```
<context-operator> ::=  
"equals" | "starts_with" | "contains" | "not_equals" | "is_null" | "gt" | "le" |  
"ge"
```

```
<operator> ::=  
AND |OR
```

The following table describes the arguments for `<type>`:

Value	Description
<nountype>	Each Sensor, with its associated metric, is organized in a hierarchy according to Nouns. A Noun type is a name that reflects the set of metrics being collected. For example, JDBC could be a Noun type. For information about Sensors and Nouns, see "Understanding Common DMS Terms and Concepts" in the <i>Oracle Fusion Middleware Performance and Tuning Guide</i> .
<context>	An Execution Context is an association of the Execution Context ID (ECID), Relationship ID (RID), and Maps of Values. This argument allows the data stored in the map of values to be inspected and used by the filter. For example, if the map contains the key "user", you can create a filter that returns requests with "user" equal to "bruce".

The following table describes the arguments for <nountype>:

Value	Description
NOUNTYPE	A keyword.
<nountype-operator>	The following are valid operators: <ul style="list-style-type: none"> ▪ equals: Filters only if the Noun type name equals the value. ▪ starts_with: Filters only if the Noun type name starts with the value. ▪ contains: Filters only if the Noun type name equals the value. ▪ not_equals: Filters only if the Noun type name does not equal the value.
value	The name of the Noun type on which to operate. The name can be any object for which you want to measure performance.

The following table describes <context>

Value	Description
CONTEXT	A keyword.
name	The name of the context to filter.
value	The name of the context on which to operate.
<context-operator>	The following are valid operators: <ul style="list-style-type: none"> ▪ equals: Filters only if the context name equals the value. ▪ starts_with: Filters only if the context name starts with the value. ▪ contains: Filters only if the context name equals the value. ▪ not_equals: Filters only if the context name does not equal the value. ▪ is_null: Filters only if the context name is null. ▪ lt: Filters only if the context name is less than the value. ▪ gt: Filters only if the context name is greater than the value. ▪ le: Filters only if the context name is less than or equal to the value. ▪ ge: Filters only if the context name is greater than or equal to the value.
IGNORECASE	Optional. If specified, the case of a string datatype is ignored. The default is that the case of a string datatype is checked.

Value	Description
DATATYPE	Optional. The valid values are string, long, or double. The default is string. The IGNORECASE AND DATATYPE are not dependent on position in the command.

6.2.2.3 Examples

The following example adds a filter with the name MyFilter, specifying a Noun type and context:

```
addDMSEventFilter(id='mds1', name='MyFilter',
    props={'condition': 'NOUNTYPE equals MDS_Connections AND CONTEXT user equals bruce IGNORECASE'})
```

Filter "mds1" added.

The following example attempts to add a filter with the same id. The command returns an error:

```
addDMSEventFilter(id='mds1', name='MyFilter',
    props={'condition': 'NOUNTYPE equals MDS_Connections AND CONTEXT user equals bruce'})
```

Filter "mds1" already exists. Unable to add this.

The following example adds a filter with two event/action pairs:

```
addDMSEventFilter(id='mds2', name='MyFilter',
    etypes='NOUN:CREATE,HTTP_REQUEST:START',
    props={'condition': 'NOUNTYPE equals MDS_Connections AND CONTEXT user equals bruce IGNORECASE=true'})
```

Filter "mds2" added.

6.2.3 addDMSEventRoute

Command Category: DMS Event Tracing

Use with WLST: Online

6.2.3.1 Description

Adds the specified event route to the Event Tracing configuration. If an event route with the same ID already exists, the command returns an error and does not add the event route.

You must be connected to the Administration Server to add an event route. If you are not, an error is returned.

6.2.3.2 Syntax

```
addDMSEventRoute([filterid=filter_id], destinationid=destination_id,
    [enable=true|false] [,server=server_name])
```

Argument	Definition
filterid	Optional. The unique identifier for the filter.

Argument	Definition
<i>destinationid</i>	The unique identifier for the specific destination. The destination must exist.
<i>enable</i>	Optional. Enables the filter. Valid values are <code>true</code> and <code>false</code> . The default is <code>true</code> .
<i>server</i>	Optional. The server on which to perform this operation. The default is the server to which you are connected.

6.2.3.3 Examples

The following example adds an event route with the filter id of `mds1` and the destination id of `jfr`:

```
addDMSEventRoute(filterid='mds1', destinationid='jfr', enable='false')
Event-route for filter "mds1", destination "jfr" added.
```

The following example attempts to add an event route that already exists:

```
addDMSEventRoute(filterid='mds1', destinationid='jfr', enable='false')
Event-route for filter "mds1", destination "jfr" already exists. Unable to add this.
```

6.2.4 enableDMSEventTrace

Command Category: DMS Event Tracing

Use with WLST: Online

6.2.4.1 Description

Enables an event trace and creates a filter with a specified condition and destination and an enabled event-route. This is a simple way to start filtering, without having to explicitly create a filter, destination and event-route, but with less configuration options. The specified destination must exist.

You must be connected to the Administration Server to enable a DMS event trace. If you are not, an error is returned.

If you require a more complex configuration, use the [addDMSEventDestination](#), [addDMSEventFilter](#), and [addDMSEventRoute](#).

6.2.4.2 Syntax

```
enableDMSEventTrace(destinationid=destinationid [, etypes=etype]
                    [, condition=condition] [, server=server_name])
```

Argument	Definition
<i>destinationid</i>	The unique identifier for the specific destination. Any existing destination is valid.
<i>etypes</i>	Optional. A string containing a comma-separated list of event/action pairs. See addDMSEventFilter for a list of available etypes.
<i>condition</i>	Optional. A condition on which to filter. See addDMSEventFilter for the syntax for a condition. If no condition is specified, all DMS events will be passed
<i>server</i>	Optional. The server on which to perform this operation. The default is the server to which you are connected.

6.2.4.3 Example

The following example enables an event trace with a specified condition:

```
enableDMSEventTrace(condition='CONTEXT username EQUALS Joe AND CONTEXT ip EQUALS 192.168.1.5')
```

Filter "EventTrace9", using Destination "LoggerDestination" added, and event-route enabled.

6.2.5 listDMSEventConfiguration

Command Category: DMS Event Tracing

Use with WLST: Online

6.2.5.1 Description

Displays an overview of the Event Tracing configuration.

6.2.5.2 Syntax

```
listDMSEventConfiguration([server=server_name])
```

Argument	Definition
<i>server</i>	Optional. The server on which to perform this operation. The default is the server to which you are connected.

6.2.5.3 Example

The following example lists the configuration for the Managed Server to which you are connected:

```
listDMSEventConfiguration()
```

Event routes:

```
FILTER      DESTINATION
MyFilter    des1
MyFilter    des2
null        des3
```

Filters with no event route:

```
Fred
```

Destinations with no event route:

```
des4
```

6.2.6 listDMSEventDestination

Command Category: DMS Event Tracing

Use with WLST: Online

6.2.6.1 Description

For a specific destination, display the full configuration. If no destination ID is specified, list the destination ID and name for all the destinations in the Event Tracing configuration.

6.2.6.2 Syntax

```
listDMSEventDestination([id=id] [, server=server_name])
```

Argument	Definition
id	Optional. The unique identifier for the specific destination.
server	Optional. The server on which to perform this operation. The default is the server to which you are connected.

6.2.6.3 Examples

The following example displays information about the destinations for the Managed Server to which you are connected:

```
listDMSEventDestination()
ID : destination1
NAME: File-system
ID : jrf
NAME: Flight-Recorder
```

The following example displays information about the destinations for the Managed Server, MS1:

```
listDMSEventDestination(server='MS1')
ID          NAME
Network1   Send file over network
desman1    File-system
```

The following example displays information about the destination destination1:

```
listDMSEventDestination(id='destination1')
ID: destination1
NAME: File-system
CLASS: oracle.dms.trace2.runtime.LoggerDestination
PROPERTIES:
NAME      VALUE
LoggerName trace2-logger
```

6.2.7 listDMSEventFilter

Command Category: DMS Event Tracing

Use with WLST: Online

6.2.7.1 Description

For a specific filter, displays the full configuration. If you do not specify a filter ID, the command displays the filter ID and name for all the filters in the Event Tracing configuration.

6.2.7.2 Syntax

```
listDMSEventFilter([id=id] [, server=server_name])
```

Argument	Definition
id	Optional. The unique identifier for specified filter.
server	Optional. The server on which to perform this operation. The default is the server to which you are connected.

6.2.7.3 Example

The following example displays the list of all the filters in the Event Tracing configuration:

```
listDMSEventFilter()
```

```
ID      NAME
mds1   MyFilter
mds2   MDS2Filter
```

The following example displays the configuration of the filter mds1:

```
listDMSEventFilter(id='mds1')
```

```
ID      : mds1
NAME: MyFilter
PROPERTIES
CONDITION: NOUNTYPE equals MDS_Connections AND CONTEXT user equals
bruce IGNORECASE=false
```

6.2.8 listDMSEventRoutes

Command Category: DMS Event Tracing

Use with WLST: Online

6.2.8.1 Description

List the events routes and their status (enabled or disabled) that are associated with the specified filter or destination. If you do not specify a filterid or destinationid, this command lists all the event routes in the Event Tracing configuration.

6.2.8.2 Syntax

```
listDMSEventRoutes([filterid=filter_id] [, destinationid=destination_id]
                  [, server=server_name])
```

Argument	Definition
filterid	Optional. The unique identifier for the filter.
destinationid	Optional. The unique identifier for the specific destination. The destination must exist.
server	Optional. The server on which to perform this operation. The default is the server to which you are connected.

6.2.8.3 Examples

The following example lists all event routes:

```
listDMSEventRoutes()
FILTER      : mdsbruce
DESTINATION: jfr
ENABLED     : false
FILTER      : null
DESTINATION: destination1
ENABLED     : true
```

The following example lists the event routes with the filter id of filter1:

```
listDMSEventRoutes(filterid='filter1')
```

```

FILTER      : filter1
DESTINATION: jfr
ENABLED     : true
FILTER      : filter1
DESTINATION: destination1
ENABLED     : true

```

The following example lists the event routes with the destination id of destination1:

```

listDMSEventRoutes(destinationid='destination1')
FILTER      : filter1
DESTINATION: destination1
ENABLED     : true

```

6.2.9 removeDMSEventDestination

Command Category: DMS Event Tracing

Use with WLST: Online

6.2.9.1 Description

Removes an existing destination from the Event Tracing configuration. You can remove a destination only if no event route depends on the destination. If an event route that depends on the destination exists, a warning is returned.

You must be connected to the Administration Server to remove a destination. If you are not, an error is returned.

6.2.9.2 Syntax

```
removeDMSEventDestination(id=id [, server=server_name])
```

Argument	Definition
<i>id</i>	The unique identifier for the destination to be removed.
<i>server</i>	Optional. The server on which to perform this operation. The default is the server to which you are connected.

6.2.9.3 Examples

The following example removes the destination jfr:

```
removeDMSEventDestination(id='jfr')
```

```
Destination "jfr" removed.
```

The following example attempts to remove the destination styx.inpass.db1. However, because an event route exists for the destination, the command returns an error.

```
removeDMSEventDestination(id='styx.inpass.db1')
```

```
Destination "'styx.inpass.db1'" cannot be removed. An event-route currently
exists for that destination. Remove the event-route first using the command
removeDMSEventRoute().
```

6.2.10 removeDMSEventFilter

Command Category: DMS Event Tracing

Use with WLST: Online

6.2.10.1 Description

Removes an existing filter from the Event Tracing configuration. You can remove a filter only if no event route depends on the filter. If an event route that depends on the filter exists, a warning is returned.

You must be connected to the Administration Server to remove an event filter. If you are not, an error is returned.

6.2.10.2 Syntax

```
removeDMSEventFilter(id=id [, server=server_name])
```

Argument	Definition
<i>id</i>	The unique identifier for the filter to be removed.
<i>server</i>	Optional. The server on which to perform this operation. The default is the server to which you are connected.

6.2.10.3 Example

The following example removes the filter `mds1`:

```
removeDMSEventFilter(id='mds1')
```

Filter "mds1" removed.

The following example attempts to remove a filter for which an event-route currently exists:

```
removeDMSEventFilter(id='allaccounts')
```

Filter "allaccounts" cannot be removed. An event-route currently exists for that filter. Remove the event-route first using the command `removeDMSEventRoute()`.

6.2.11 removeDMSEventRoute

Command Category: DMS Event Tracing

Use with WLST: Online

6.2.11.1 Description

Removes the specified event route. You must be connected to the Administration Server to add an event route. If you are not, an error is returned.

6.2.11.2 Syntax

```
removeDMSEventRoute([filterid=filter_id] [, destinationid=destination_id]
                    [, server=server_name])
```

Argument	Definition
<i>filterid</i>	Optional. The unique identifier for the filter.
<i>destinationid</i>	Optional. The unique identifier for the specific destination. The destination must exist.
<i>server</i>	Optional. The server on which to perform this operation. The default is the server to which you are connected.

6.2.11.3 Example

The following example removes the event route with the filterid mds1 and the destination jfr:

```
removeDMSEventRoute(filterid='mds1', destinationid='jfr')
Event-route for filter "mds1", destination "jfr" removed
```

The following example removes the event route with the destination destination1:

```
removeDMSEventRoute(destinationid='destination1')
Event-route for filter "None", destination "destination1" removed
```

6.2.12 updateDMSEventDestination

Command Category: DMS Event Tracing

Use with WLST: Online

6.2.12.1 Description

Updates an existing destination, allowing a specified argument to be updated. You must be connected to the Administration Server to update a destination. If you are not, an error is returned.

6.2.12.2 Syntax

```
updateDMSEventDestination(id=id [, name=dest_name], class=class_name
    [,props= {'name': 'value'...}] [, server=server_name])
```

Argument	Definition
id	The unique identifier for the destination to be updated.
name	Optional. A name for the destination.
class	The full classname of the destination. See Table 6-4 for a list of available destinations.
props	Optional. The name/value properties to use for the destination. You can add a new property, or update or remove an existing one. If you update properties, you must specify all properties. If you omit a property, it is removed. For example, if a destination contains the properties LoggerName and severity, and you omit severity, it will be removed from the destination. See addDMSEventFilter for information about the syntax and allowed values.
server	Optional. The server on which to perform this operation. The default is the server to which you are connected.

6.2.12.3 Examples

The following example updates the name of the destination jfr:

```
updateDMSEventDestination(id='jfr', name='Alternative Flight-Recorder')
```

Destination "jfr" updated.

The following example attempts to update a destination that does not exist. The command returns an error:

```
updateDMSEventDestination(id='destination1',
    props={'loggerName': 'MyNewTrace2-logger'})
```

Destination "destination1" does not yet exist. Unable to update this.

6.2.13 updateDMSEventFilter

Command Category: DMS Event Tracing

Use with WLST: Online

6.2.13.1 Description

Updates an existing filter in the Event Tracing configuration.

You must be connected to the Administration Server to update an event filter. If you are not, an error is returned.

6.2.13.2 Syntax

```
updateDMSEventFilter(id=id [, name=name] [, etypes=etypes],
                    props= {'prop-name': 'value'...}
                    [, server=server_name])
```

Argument	Definition
id	The unique identifier for the filter to be updated.
name	Optional. The name of the filter to be updated.
etypes	Optional. A string containing a comma-separated list of event/action pairs. See addDMSEventFilter for a list of valid values.
props	<i>prop-name</i> : The name of the filter property. <i><condition></i> is the only valid property, and only one condition may be specified. See addDMSEventFilter for information on the syntax of <i>prop-name</i> . <i>value</i> : The value of the property of the filter.
server	Optional. The server on which to perform this operation. The default is the server to which you are connected.

6.2.13.3 Examples

The following example updates the filter properties for the filter with the id mds1:

```
updateDMSEventFilter(id='mds1',
                    props={'condition': 'NOUNTYPE equals XYZ_Total_Connections AND CONTEXT user equals bruce'})
```

Filter "mds1" updated.

The following example attempts to update a filter that does not exist:

```
updateDMSEventFilter(id='Filter2')
```

Filter "Filter2" does not yet exist. Unable to update this.

6.2.14 updateDMSEventRoute

Command Category: DMS Event Tracing

Use with WLST: Online

6.2.14.1 Description

Enables or disables the specified event route. You must be connected to the Administration Server to update an event route. If you are not, an error is returned.

6.2.14.2 Syntax

```
updateDMSEventRoute([filterid=filter_id], destinationid=destination_id
[, enable=true|false] [, server=server_name])
```

Argument	Definition
<i>filterid</i>	Optional. The unique identifier for the filter.
<i>destinationid</i>	Optional. The unique identifier for the specific destination. The destination must exist.
<i>enable</i>	Optional. Enables the filter. Valid values are <code>true</code> and <code>false</code> .
<i>server</i>	Optional. The server on which to perform this operation. The default is the server to which you are connected.

6.2.14.3 Example

The following example disables the event route with the filterid `mds1` and the destinationid `jfr`:

```
updateDMSEventRoute(filterid='mds1', destinationid='jfr', enable='false')
Event-route for filter "mds1", destination "jfr" disabled .
```

Logging Custom WLST Commands

This chapter provides detailed descriptions of custom WLST commands for logging, including command syntax, arguments and command examples. Use the logging commands to configure settings for log files and to view and search log files.

For additional details about configuring and searching log files, see "Managing Log Files and Diagnostic Data" in the *Oracle Fusion Middleware Administrator's Guide*.

Note: To use these logging custom WLST commands, you must invoke the WLST script from the Oracle Common home. See "Using Custom WLST Commands" in the *Oracle Fusion Middleware Administrator's Guide*.

Table 7–1 describes the different categories of logging commands.

Table 7–1 Logging Command Categories

Command category	Description
Log Configuration Commands	Configure settings for log files, such as the level of information written to the file or the maximum file size.
Search and Display Commands	View Oracle Fusion Middleware log files and search log files for particular messages.
Selective Tracing Commands	Configure and use selective tracing, which specifies that messages are traced for specific server, loggers, or users.

7.1 Log Configuration Commands

Use the commands in Table 7–2 to configure settings for log files, such as the level of information written to the file or the maximum file size. In the Use with WLST column, online means the command can only be used when connected to a running server. Offline means the command can only be used when not connected to a running server. Online or offline means the command can be used in both situations.

Table 7–2 Logging Configuration Commands

Use this command...	To...	Use with WLST...
configureLogHandler	Configure an existing log handler, add a new handler, or remove existing handlers.	Online
getLogLevel	Get the level for a given logger.	Online
listLoggers	Get the list of loggers and the level of each logger.	Online

Table 7–2 (Cont.) Logging Configuration Commands

Use this command...	To...	Use with WLST...
listLogHandlers	List the configuration of one of more log handlers.	Online
setLogLevel	Set the level for a given logger.	Online

7.1.1 configureLogHandler

Command Category: Log Configuration

Use with WLST: Online

7.1.1.1 Description

Configures an existing Java logging handler, adds a new handler, or removes an existing handler. It returns a `java.util.List` with one entry for each handler. Each entry is a `javax.management.openmbean.CompositeData` object describing the handler.

With this command, you can change the location of the log files, the frequency of the rotation of log files, and other log file properties.

7.1.1.2 Syntax

```
configureLogHandler (options)
```

Argument	Definition
<i>options</i>	<p data-bbox="656 239 1446 296">Comma-separated list of options, specified as name-value pairs. Valid options include:</p> <ul style="list-style-type: none"> <li data-bbox="656 306 1446 422"> <p data-bbox="656 306 1446 384">■ target—The name of a WebLogic Server instance, or a string describing a system component. For system components, refer to the component's documentation for details.</p> <p data-bbox="703 401 1333 422">The default value is the server to which WLST is connected.</p> <li data-bbox="656 438 1317 462"> <p data-bbox="656 438 1317 462">■ name—The name of a log handler. This option is required.</p> <li data-bbox="656 478 1446 663"> <p data-bbox="656 478 1446 585">■ maxFileSize—The value of the maximum file size for an ODL handler. The value is a string representing a numeric value, optionally followed by a suffix indicating a size unit (k for kilobytes, m for megabytes, g for gigabytes).</p> <p data-bbox="703 596 1328 619">If you do not specify a suffix, the value is returned in bytes.</p> <p data-bbox="703 636 1365 659">Note that this option does not apply to the QuickTrace handler.</p> <li data-bbox="656 676 1446 821"> <p data-bbox="656 676 1446 783">■ maxLogSize—The value of the maximum size of the log files for an ODL handler. The value is a string representing a numeric value, optionally followed by a suffix indicating a size unit (k for kilobytes, m for megabytes, g for gigabytes).</p> <p data-bbox="703 793 1365 816">Note that this option does not apply to the QuickTrace handler.</p> <li data-bbox="656 837 1446 1058"> <p data-bbox="656 837 1446 1016">■ rotationFrequency—The value of the rotation frequency for an ODL handler. The value is a string representing a numeric value, optionally followed by a suffix indicating a time unit (m for minutes, h for hours, d for days). The default unit is minutes. The following special values are also accepted and are converted to a numeric value in minutes: HOUR, HOURLY, DAY, DAILY, WEEK, WEEKLY, MONTH, MONTHLY.</p> <p data-bbox="703 1033 1365 1056">Note that this option does not apply to the QuickTrace handler.</p> <li data-bbox="656 1075 1446 1251"> <p data-bbox="656 1075 1446 1205">■ baseRotationTime—The base rotation time, to be used with the rotationFrequency option. The value must be a string representing a date/time value. It can be a full date/time in ISO 8601 date/time format, or a short form including only hours and minutes. The default baseRotationTime is 00:00.</p> <p data-bbox="703 1220 1365 1243">Note that this option does not apply to the QuickTrace handler.</p>

Argument	Definition
<i>options</i> (continued)	<ul style="list-style-type: none"> ■ retentionPeriod—The amount of time that the log file is retained. The value must be a string representing a numeric value, optionally followed by a suffix indicating a time unit (m for minutes, h for hours, d for days). The default unit is minutes. The following special values are also accepted and are converted to a numeric value in minutes: HOUR, HOURLY, DAY, DAILY, WEEK, WEEKLY, MONTH, MONTHLY. Note that this option does not apply to the QuickTrace handler. ■ format—The format for the ODL handler. Valid values are one of the following strings: "ODL-Text" or "ODL-XML". The default format is ODL-Text. ■ encoding—The character encoding for the log file. ■ path—The log file path. Note that this option does not apply to the QuickTrace handler. ■ handlerType—The name of the Java class that provides the handler implementation. It must be an instance of java.util.logging.Handler or oracle.core.ojdl.logging.HandlerFactory. ■ propertyName—The name of an advanced handler property to be added or updated. The property value is specified with the propertyValue option. See the documentation for the handler for valid properties. ■ propertyValue—The new value for the handler property defined by the propertyName option. ■ addProperty—A Jython boolean value. Used in conjunction with the propertyName and propertyValue options to define that a new property is to be added to the handler. ■ removeProperty—A list of one or more handler properties to be removed. ■ addHandler—A boolean value. If the value is true, then the named handler will be added. ■ removeHandler—A boolean value. If the value is true, then the named handler is removed. ■ level—A Java or ODL level value. The handler level will be set to the given level. ■ addToLogger—A list of logger names. The handler is added to the given logger names. ■ removeFromLogger—A list of logger names. The handler is removed from the given loggers. ■ useParentHandlers—A boolean value. Sets the useParentHandlers flag on the loggers defined by the addToLogger or removeFromLogger options.

The following table lists the properties for the quicktrace-handler. This handler allows you to trace messages from specific loggers and store the messages in memory. For more information, see "Configuring and Using QuickTrace" in the *Oracle Fusion Middleware Administrator's Guide*.

QuickTrace Property	Description
bufferSize	The approximate size of the circular QuickTrace buffer, in which log records are stored in memory. Note that actual memory consumption may be less than, but not more than this value.

QuickTrace Property	Description
enableDMSMetrics	If specified as true, DMS metrics are enabled for the quicktrace-handler. The default is true.
enableUserBuffer	<p>If specified as true, the handler maintains an individual buffer for each user specified in the reserveBufferUserID property. If the user is not defined in the reserveBufferUserID property, the messages are cached in the COMMON buffer.</p> <p>If specified as false, the handler maintains only one buffer, COMMON.</p> <p>The default is false.</p>
flushOnDump	If specified as true, the buffer is flushed when you execute the executeDump command. The default is true.
includeMessageArguments	If specified as true, message arguments are included with the formatted log messages that have a message ID. The default is false.
maxFieldLength	<p>The maximum length, in bytes, for each field in a message. The fields can include the message text, supplemental attributes, thread name, source class name, source method name, and message arguments.</p> <p>The default is 240 bytes.</p> <p>A small number can restrict the amount of information returned for a message. An excessively number can reduce the amount of log records in the buffer because each message uses more bytes.</p>
reserveBufferUserID	A list of user IDs, separated by a comma. If enableUserBuffer is specified as true, any log messages related to the user are written to a separate buffer.
supplementalAttributes	<p>A list of supplemental attribute names. The attributes are listed in the logging.xml file.</p> <p>Setting supplemental attributes requires additional memory or CPU time.</p>
useDefaultAttributes	If specified as true, default attribute values are added to each log message. The default attributes are HOST_ID, HOST_NWADDR, and USER_ID.
useLoggingContext	<p>If specified as true, the log message includes DMS logging context attributes. The default is false.</p> <p>If you enable this option, the trace requires additional CPU time.</p>
useRealThreadID	<p>If specified as true, the handler attempts to use the real thread ID instead of the thread ID that is provided by the java.util.logging.logRecord. The default is false.</p> <p>If you enable this option, the trace requires additional CPU time.</p>
useThreadName	If specified as true, the log message includes the thread name instead of the thread ID. The default is false.

7.1.1.3 Examples

The following example specifies the maximum file size for the odl-handler:

```
configureLogHandler(name="odl-handler", maxFileSize="5M")
```

The following example specifies the rotation frequency for the odl-handler:

```
configureLogHandler(name="odl-handler", rotationFrequency="daily")
```

The following example specifies the rotation frequency and the retention period for the odl-handler. It also removes the properties maxFileSize and maxLogSize:

```
configureLogHandler(name="odl-handler", rotationFrequency="daily",
    retentionPeriod="week", removeProperty=['maxFileSize','maxLogSize'])
```

The following example configures the quicktrace-handler, adding the logger oracle.adf.faces, and enabling user buffers for user1 and user2:

```
configureLogHandler(name="quicktrace-handler", addToLogger="oracle.adf.faces",
    propertyName="enableUserBuffer", propertyValue="true",
    propertyName="reserveBufferUserID", propertyValue="user1, user2")
```

The oracle.adf logger is associated with the handlers odl-handler, wls-domain, and console-handler. When you set the level of the logger, these handlers will use the same level (TRACE:1) for the logger oracle.adf. As a result, much information will be written to the log files, consuming resources. To avoid consuming resources, set the level of the handlers to a lower level, such as WARNING or INFORMATION. For example:

```
configureLogHandler(name="odl-handler", level="WARNING:1")
configureLogHandler(name="wls-domain", level="WARNING:1")
configureLogHandler(name="console-handler", level="WARNING:1")
```

7.1.2 getLogLevel

Command Category: Log Configuration

Use with WLST: Online

7.1.2.1 Description

Returns the level of a given Java logger.

The returned value is a string with the logger's level, or None if the logger does not exist. An empty string indicates that the logger level is null.

7.1.2.2 Syntax

```
getLogLevel(options)
```

Argument	Definition
<i>options</i>	Comma-separated list of options, specified as name-value pairs. Valid options include: <ul style="list-style-type: none"> ▪ target—The name of a WebLogic Server instance, or a string describing a system component. For system components, refer to the component's documentation for details. The default value is the server to which WLST is connected. ▪ logger—A logger name. An empty string denotes the root logger. This option is required and has no default. ▪ runtime—A Jython boolean value (0 or 1) that determines if the operation is to list runtime loggers or config loggers. The default value is 1 (runtime).

7.1.2.3 Examples

The following example returns the level for the logger oracle:


```
getLogLevel(logger='oracle')
```

The following example returns the level for the logger oracle, specifying only config loggers, not runtime loggers:

```
getLogLevel(logger='oracle', runtime=0)
```

The following example returns the level for the logger oracle on the Oracle WebLogic Server server2:

```
getLogLevel(logger='oracle', target='server2')
```

7.1.3 listLoggers

Command Category: Log Configuration

Use with WLST: Online

7.1.3.1 Description

Lists Java loggers and their levels. The command returns a PyDictionary object where the keys are logger names and the associated values are the logger levels. An empty level is used to indicate that the logger does not have the level set.

7.1.3.2 Syntax

```
listLoggers([options])
```

Argument	Definition
<i>options</i>	<p>An optional comma-separated list of options, specified as name-value pairs. Valid options include:</p> <ul style="list-style-type: none"> ▪ target—The name of a WebLogic Server instance, or a string describing a system component. For system components, refer to the component's documentation for details. The default value is the server to which WLST is connected. ▪ pattern—A regular expression pattern that is used to filter logger names. The default value returns all logger names. ▪ runtime—A Jython boolean value (0 or 1) that determines if the operation is to list runtime loggers or config loggers. The default value is 1 (runtime).

7.1.3.3 Examples

The following example lists all of the loggers:

```
listLoggers()
```

The following example lists all of the loggers that start with the name oracle.*.

```
listLoggers(pattern="oracle.*")
```

The following example list all config loggers:

```
listLoggers(runtime=0)
```

The following example list all loggers for the WebLogic Server server1:

```
listLoggers(target="server1")
```

7.1.4 listLogHandlers

Command Category: Log Configuration

Use with WLST: Online

7.1.4.1 Description

Lists Java log handlers configuration. This command returns a `java.util.List` with one entry for each handler. Each entry is a `javax.management.openmbean.CompositeData` object describing the handler.

7.1.4.2 Syntax

```
listLogHandlers([options])
```

Argument	Definition
<i>options</i>	An optional comma-separated list of options, specified as name-value pairs. Valid options include: <ul style="list-style-type: none">▪ target—The name of a WebLogic Server instance, or a string describing a system component. For system components, refer to the component's documentation for details. The default value is the server to which WLST is connected.▪ name—The name of a log handler. If the name is not provided, then all handlers are listed.

7.1.4.3 Examples

The following example lists all log handlers:

```
listLogHandlers()
```

The following example lists all log handlers named odl-handler:

```
listLogHandlers(name="odl-handler")
```

The following example lists all log handlers for the WebLogic Server server1:

```
listLogHandlers(target="server1")
```

7.1.5 setLogLevel

Command Category: Log Configuration

Use with WLST: Online

7.1.5.1 Description

Sets the level of information written by a given Java logger to a log file.

7.1.5.2 Syntax

```
setLogLevel(options)
```

Argument	Definition
<i>options</i>	<p>Comma-separated list of options, specified as name-value pairs. Valid options include:</p> <ul style="list-style-type: none"> <p>■ target—The name of a WebLogic Server instance, or a string describing a system component. For system components, refer to the component's documentation for details.</p> <p>The default value is the server to which WLST is connected.</p> <p>■ logger—A logger name. An empty string denotes the root logger.</p> <p>This option is required and has no default. The command throws an exception if the logger does not exist, unless the <code>addLogger</code> option is also used.</p> <p>■ addLogger—A Jython boolean value (0 or 1) that determines if the logger should be created if it does not exist. This option is deprecated for runtime mode. Adding a runtime logger may have no effect because the logger may be garbage collected. If you need to set the level for a logger that has not yet been created, use the <code>persist</code> mode.</p> <p>■ level—The level name. It can be either a Java level or an ODL level. Some valid Java levels are: SEVERE, WARNING, INFO, CONFIG, FINE, FINER, OR FINEST. Valid ODL levels include a message type followed by a colon and a message level. The valid ODL message types are: INCIDENT_ ERROR, ERROR, WARNING, NOTIFICATION, TRACE, and UNKNOWN. The message level is represented by an integer value that qualifies the message type. Possible values are from 1 (highest severity) through 32 (lowest severity).</p> <p>An empty string can be used to set the level to null (inherited from parent).</p> <p>This option is required; there is no default value.</p> <p>■ runtime—A Jython boolean value (0 or 1) that determines if the operation is to list runtime loggers or config loggers. The default value is 1 (runtime). If the target is a system component that does not support changing runtime loggers, this option is ignored.</p> <p>Note: Because runtime loggers may be garbage collected, you should change the level of the runtime logger only if you know that the logger exists and that there is a strong reference to the logger. If the logger is garbage collected, any changes made to the logger level in runtime mode that are not persisted may be lost.</p> <p>■ persist—A Jython boolean value (0 or 1) that determines if the level should be saved to the configuration file. The default value is 1.</p>

7.1.5.3 Examples

The following example sets the log level to NOTIFICATION:1 for the logger `oracle.my.logger`:

```
setLogLevel(logger="oracle.my.logger", level="NOTIFICATION:1")
```

The following example sets the log level to TRACE:1 for the logger `oracle.my.logger` and specifies that the level should be saved to the configuration file:

```
setLogLevel(logger="oracle.my.logger", level="TRACE:1", persist=0)
```

The following example sets the log level to WARNING for the config logger `oracle.my.logger` on the WebLogic Server `server1`:

```
setLogLevel(target="server1", logger="oracle.my.logger", level="WARNING", runtime=0)
```

7.2 Search and Display Commands

Use the commands in [Table 7-3](#) to view Oracle Fusion Middleware log files and to search log files for particular messages.

Table 7-3 Search and Display Commands

Use this command...	To...	Use with WLST...
displayLogs	List the logs for one or more components.	Online or Offline
listLogs	Search and display the contents of log files.	Online or Offline

7.2.1 displayLogs

Command Category: Search and Display

Use with WLST: Online or Offline

7.2.1.1 Description

Search and display the contents of diagnostic log files. The command returns a value only when the `returnData` option is set to true. By default it will not return any data. The return value depends on the option used.

7.2.1.2 Syntax

```
displayLogs([searchString,][options])
```

Argument	Definition
<i>searchString</i>	<p>An optional search string. Only messages that contain the given string (case-insensitive) will be returned.</p> <p>Note that the <code>displayLogs</code> command can read logs in multiple formats and it converts the messages to ODL format. The search will be performed in the native format, if possible. Otherwise, it may be performed in the message contents, and it may exclude mark-up. Therefore you should avoid using mark-up characters in the search string.</p>
<i>options</i>	<p>An optional comma-separated list of options, specified as name-value pairs. Valid options include:</p> <ul style="list-style-type: none"> ▪ target—The name of a WebLogic Server instance, or a system component. For a system component, the syntax for the target is: <code>opmn:instance-name/component-name</code> In connected mode, the default target is the WebLogic domain. In disconnected mode, there is no default; the <code>target</code> option is required. ▪ oracleInstance—Defines the path to the <code>ORACLE_INSTANCE</code> or WebLogic domain home. The command is executed in disconnected mode when you use this parameter. ▪ log—A log file path. The command will read messages from the given log file. If the log file path is not given, the command will read all logs associated with the given target.

Argument	Definition
options (continued)	<ul style="list-style-type: none"> <li data-bbox="646 233 1448 338">■ last—An integer value. Restricts the search to messages logged within the last minutes. The value can have a suffix <i>s</i> (second), <i>m</i> (minute), <i>h</i> (hour), or <i>d</i> (day) to specify a different time unit. (For example, <code>last=2h</code> will be interpreted as the last 2 hours). <li data-bbox="646 348 1448 401">■ tail—An integer value. Restrict the search to the last <i>n</i> messages from each log file and limits the number of messages displayed to <i>n</i>. <li data-bbox="646 411 1448 611">■ pattern—A regular expression pattern. Only messages that contain the given pattern are returned. Using the pattern option is similar to using the <code>searchString</code> argument, except that you can use a regular expression. The regular expression pattern search is case sensitive (unless you explicitly turn on case-insensitive flags in the pattern). The pattern must follow <code>java.util.regex</code> syntax. <li data-bbox="646 621 1448 674">■ ecid—A string or string sequence containing one or more Execution Context ID (ECID) values to be used as a filter for log messages. <li data-bbox="646 684 1448 737">■ component—A string or string sequence containing one or more component ID values to be used as a filter for log messages. <li data-bbox="646 747 1448 800">■ module—A string or string sequence containing one or more module ID values to be used as a filter for log messages. <li data-bbox="646 810 1448 863">■ type—A string or string sequence containing one or more message type values to be used as a filter for log messages. <li data-bbox="646 873 1448 926">■ app—A string or string sequence containing one or more application values to be used as a filter for log messages. <li data-bbox="646 936 1448 1010">■ query—A string that specifies an expression used to filter the contents of log messages. A simple expression has the form: <i>field-name operator value</i> where <i>field-name</i> is a log record field name and <i>operator</i> is an appropriate operator for the field type (for example, you can specify <code>equals</code>, <code>startsWith</code>, <code>contains</code> or <code>matches</code> for string fields). A field name is either one of the standard ODL attribute names (such as <code>COMPONENT_ID</code>, <code>MSG_TYPE</code>, <code>MSG_TEXT</code>, and <code>SUPPL_DETAIL</code>), or the name of a supplemental attribute (application specific), prefixed by <code>SUPPL_ATTR</code>. (For example, <code>SUPPL_ATTR.myAttribute</code>). A few common supplemental attributes can be used without the prefix. For example, you can use <code>APP</code> to filter by application name. You can combine multiple simple expressions using the boolean operators <code>and</code>, <code>or</code> and <code>not</code> to create complex expressions, and you can use parenthesis for grouping expressions. See the <i>Oracle Fusion Middleware Administrator's Guide</i> for a detailed description of the query syntax. <li data-bbox="646 1535 1448 1608">■ groupBy—A string list. When the <code>groupBy</code> option is used, the output is a count of log messages, grouped by the attributes defined in the string list. <li data-bbox="646 1619 1448 1776">■ orderBy—A string list that defines the sort order for the result. The values are log message attribute names. The name may be extended with an optional suffix <code>:asc</code> or <code>:desc</code> to specify ascending or descending sorting. The default sort order is ascending. By default, the result is sorted by time. <li data-bbox="646 1787 1448 1896">■ returnData—A Jython boolean value (0 or 1). If the value is <code>true</code> the command will return data (for example, to be used in a script). The default value is <code>false</code>, which means that the command only displays the data but does not return any data.

Argument	Definition
<i>options</i> (continued)	<ul style="list-style-type: none"> ▪ format—A string defined the output format. Valid values are ODL-Text, ODL-XML, ODL-complete and simple. The default format is ODL-Text. ▪ exportFile—The name of a file to where the command output is written. By default, the output is written to standard output. ▪ follow (f)—Puts the command in "follow" mode so that it continues to read the logs and display messages as new messages are added to the logs (similar to the UNIX <code>tail -f</code> command). The command will not return when the <code>f</code> option is used. This option is currently not supported with system components.

7.2.1.3 Examples

The following example displays the last 100 messages from all log files in the domain:

```
displayLogs (tail=100)
```

The following example displays all messages logged in the last 15 minutes:

```
displayLogs (last='15m')
```

The following example displays log messages that contain a given string:

```
displayLogs ('Exception')
```

The following example displays log messages that contain a given ECID:

```
displayLogs (ecid='0000H19TwKUCs1T6uBi8UH181kWX000002')
```

The following example displays log messages of type ERROR or INCIDENT_ERROR:

```
displayLogs (type=['ERROR', 'INCIDENT_ERROR'])
```

The following example displays log messages for a given Java EE application:

```
displayLogs (app="myApplication")
```

The following example displays messages for a system component, ohs1:

```
displayLogs (target="opmn:instance1/ohs1")
```

The following example displays a message summary by component and type:

```
displayLogs (groupBy=['COMPONENT_ID', 'MSG_TYPE'])
```

The following example displays messages for a particular time interval:

```
displayLogs (query="TIME from 11:15 and TIME to 11:20")
```

The following example shows an advanced query:

```
displayLogs (query="TIME from 11:15 and TIME to 11:20 and ( MSG_TEXT contains  
exception or SUPPL_DETAIL contains exception )")
```

A similar query could be written as:

```
displayLogs ("exception", query="TIME from 11:15 and TIME to 11:20")
```

7.2.2 listLogs

Command Category: Search and Display

Use with WLST: Online or Offline

7.2.2.1 Description

Lists log files for Oracle Fusion Middleware components. This command returns a PyArray with one element for each log. The elements of the array are `javax.management.openmbean.CompositeData` objects describing each log.

7.2.2.2 Syntax

```
listLogs([options])
```

Argument	Definition
<i>options</i>	<p>An optional comma-separated list of options, specified as name-value pairs. Valid options include:</p> <ul style="list-style-type: none"> ▪ target—The name of a WebLogic Server instance, or an Oracle Fusion Middleware system component. For a system component, the syntax for the target is: <i>opmn:instance-name/component-name</i> In connected mode, the default target is the WebLogic domain. In disconnected mode, there is no default; the target option is required. ▪ oracleInstance—Defines the path to the ORACLE_INSTANCE or WebLogic domain home. The command is executed in disconnected mode when you use this parameter. ▪ unit—defines the unit to use for reporting file size. Valid values are B (bytes), K (kilobytes), M (megabytes), G (gigabytes), or H (display size in a human-readable form, similar to the UNIX <code>ls -h</code> option). The default value is H. ▪ fullTime—A Jython Boolean value. If true, reports the full time for the log file last modified time. Otherwise, it displays a short version of the time. The default value is false.

7.2.2.3 Examples

The following example lists all of the log files for the WebLogic domain:

```
listLogs()
```

The following example lists the log files for the WebLogic Server `server1`:

```
listLogs(target="server1")
```

The following example lists the log files for the Oracle HTTP Server `ohs1`:

```
listLogs(target="opmn:instance1/ohs1")
```

The following example, used in disconnected mode, lists the log files for the WebLogic Server `server1`:

```
listLogs(oracleInstance="/middleware/user_projects/domains/base_domain",
        target="server1")
```

7.3 Selective Tracing Commands

Use the commands in [Table 7-4](#) to configure and use selective tracing. Selective tracing provides fine-grained logging for specified users or other properties of a request. In the Use with WLST column, online means the command can only be used when connected to a running server.

Table 7-4 Tracing Commands

Use this command...	To...	Use with WLST...
<code>configureTracingLoggers</code>	Configures one or more loggers for selective tracing.	Online
<code>listActiveTraces</code>	Lists the active traces.	Online
<code>listTracingLoggers</code>	Lists the loggers that support selective tracing.	Online
<code>startTracing</code>	Starts a selective tracing sessions.	Online
<code>stopTracing</code>	Stops one or more selective tracing sessions.	Online

7.3.1 `configureTracingLoggers`

Command Category: Tracing

Use with WLST: Online

7.3.1.1 Description

Configures one or more loggers for selective tracing. This command also enables or disables a logger for selective tracing.

7.3.1.2 Syntax

```
configureTracingLoggers([options])
```

Argument	Definition
<i>options</i>	<p>A comma-separated list of options, specified as name-value pairs. Valid options are:</p> <ul style="list-style-type: none"> ▪ target—Optional. The name of a WebLogic Server instance, or an array of strings containing one or more target names. By default, loggers on all running server instances in the domain that are JRF-enabled will be configured for tracing. ▪ pattern—A regular expression pattern that is used to filter logger names. The default value matches all tracing logger names. ▪ action—Enables or disables all loggers for tracing. Valid values are <code>enable</code> and <code>disable</code>. This option is required; there is no default value.

7.3.1.3 Examples

The following example configures selective tracing for all loggers beginning with `oracle.security`:

```
configureTracingLoggers(pattern='oracle.security.*', action="enable")  
Configured 62 loggers
```

The following example disables selective tracing for all loggers:

```
configureTracingLoggers(action="disable")  
Configured 1244 loggers
```

7.3.2 `listActiveTraces`

Command Category: Tracing

Use with WLST: Online

7.3.2.1 Description

Lists the active traces.

7.3.2.2 Syntax

```
listActiveTraces([options])
```

Argument	Definition
<i>options</i>	A comma-separated list of options, specified as name-value pairs. Valid options are: <ul style="list-style-type: none"> ▪ target—Optional. The name of a WebLogic Server instance, or an array of strings containing one or more target names. By default, loggers on all running server instances in the domain that are JRF-enabled are listed.

7.3.2.3 Example

The following example lists the active traces:

```
listActiveTraces()
```

```
-----+-----+-----+-----+-----+-----
Trace ID                               |Attr. Name|Attr. Value| Level| Exp. Time |Description
-----+-----+-----+-----+-----+-----
a9580e65-13c4-420b-977e-5ba7dd88ca7f |USER_ID  |user1      | FINE |           |
a04b47f7-2830-4d80-92ee-ba160cdacf6b |USER_ID  |user2      | FINE |           |
```

7.3.3 listTracingLoggers

Command Category: Tracing

Use with WLST: Online or Offline

7.3.3.1 Description

Lists the loggers that support selective tracing. This command displays a table of logger names and their tracing status. The status `enabled` means that the logger is enabled for tracing on all servers. The status `disabled` means that the logger is disabled for tracing on all servers. The status `mixed` means that the logger is enabled for tracing on some servers, but disabled on others.

7.3.3.2 Syntax

```
listTracingLoggers([options])
```

Argument	Definition
<i>options</i>	A comma-separated list of options, specified as name-value pairs. Valid options are: <ul style="list-style-type: none"> ▪ target—Optional. The name of a WebLogic Server instance, or an array of strings containing one or more target names. By default, loggers on all running server instances in the domain that are JRF-enabled are listed. ▪ pattern—A regular expression pattern that is used to filter logger names. The default value matches all tracing logger names.

7.3.3.3 Example

The following example lists all tracing loggers beginning with `oracle.security`:

```
listTracingLoggers(pattern="oracle.security.*")
```

```
-----+-----+-----+-----+-----+-----
Logger                               | Status
```

```

-----+-----
oracle.security                               | enabled
oracle.security.audit.logger                  | enabled
oracle.security.jps.az.common.util.JpsLock   | enabled
.
.
.
    
```

7.3.4 startTracing

Command Category: Tracing

Use with WLST: Online

7.3.4.1 Description

Starts a new selective tracing session for a specified user or DMS context attribute at a specified level of tracing.

7.3.4.2 Syntax

```
startTracing([options])
```

Argument	Definition
<i>options</i>	<p>A comma-separated list of options, specified as name-value pairs. Valid options are:</p> <ul style="list-style-type: none"> ▪ target—Optional. The name of a WebLogic Server instance, or an array of strings containing one or more target names. By default, loggers on all running server instances in the domain that are JRF-enabled are included in the trace. ▪ traceId—Optional. An identifier for the tracing session. If a traceId is not provided, the command generates a unique traceId. ▪ attrName—Optional, unless the user argument is not specified. Valid values are USER_ID, APP, CLIENT_HOST, CLIENT_ADDR, composite_name, WEBSERVICE.name, WEBSERVICE_PORT.name. ▪ attrValue—Required if attrName is specified. The value of the attribute. ▪ user—The user name. Messages associated with the user are returned. This is equivalent to passing the USER_ID with the attrName and AttrValue options. ▪ level—Required. The tracing level. The level must be a valid Java or ODL level. See the table "Mapping of Log Levels Among ODL, Oracle WebLogic Server, and Java" in the <i>Oracle Fusion Middleware Administrator's Guide</i>. ▪ desc—Optional. A description of the tracing session.

7.3.4.3 Example

The following example starts a trace for messages associated with user1 and sets the level of information to FINE:

```

startTracing(user="user1", level="FINE")
Started tracing with ID: 885649f7-8efd-4a7a-9898-accbfc0bbba3
    
```

7.3.5 stopTracing

Command Category: Tracing

Use with WLST: Online

7.3.5.1 Description

Stops one or more selective tracing sessions.

7.3.5.2 Syntax

```
stopTracing([options])
```

Argument	Definition
<i>options</i>	<p>A comma-separated list of options, specified as name-value pairs. Valid options are:</p> <ul style="list-style-type: none"> ▪ target—Optional. The name of a WebLogic Server instance, or an array of strings containing one or more target names. By default, loggers on all running server instances in the domain that are JRF-enabled are included in the operation. ▪ stopAll—A Jython boolean value (0 or 1) that determines if all of the active traces are stopped. Required if the <code>traceId</code>, <code>user</code>, or <code>attrName</code> and <code>attrValue</code> arguments are not specified. The default value is 0 (false). ▪ traceId—An identifier for the tracing session to be stopped. Required if the <code>stopAll</code>, <code>user</code>, or <code>attrName</code> and <code>attrValue</code> arguments are not specified. ▪ attrName—Valid values are <code>USER_ID</code>, <code>APP</code>, <code>CLIENT_HOST</code>, <code>CLIENT_ADDR</code>, <code>composite_name</code>, <code>WEBSERVICE.name</code>, <code>WEBSERVICE_PORT.name</code>. Required if the <code>traceId</code>, <code>user</code>, <code>stopAll</code> arguments are not specified. ▪ attrValue—Required if <code>attrName</code> is specified. The value of the attribute. ▪ user—The user name. All tracing sessions associated with the user are stopped. Required if the <code>stopAll</code>, <code>traceId</code>, or <code>attrName</code> and <code>attrValue</code> arguments are not specified.

7.3.5.3 Examples

The following example stops a tracing session with a specified `traceId`:

```
stopTracing(traceId="a04b47f7-2830-4d80-92ee-ba160cdacf6b")
Stopped 1 traces
```

The following example stops all tracing sessions:

```
stopTracing(stopAll=1)
Stopped 1 traces
```

Metadata Services (MDS) Custom WLST Commands

This chapter provides detailed descriptions of WLST commands for Oracle Metadata Services (MDS), including command syntax, arguments and command examples.

For additional details about creating and managing an MDS repository, see the chapter "Managing the Metadata Repository" in the *Oracle Fusion Middleware Administrator's Guide*. For information about the roles needed to perform each operation, see "Understanding MDS Operations" in the *Oracle Fusion Middleware Administrator's Guide*.

Note: To use these MDS custom WLST commands, you must invoke the WLST script from the Oracle Common home. See "Using Custom WLST Commands" in the *Oracle Fusion Middleware Administrator's Guide*.

Use the Oracle Metadata Services (MDS) commands in the categories listed in [Table 8–1](#) to manage MDS.

Table 8–1 MDS Command Categories

Command category	Description
Repository Management Commands	Manage the MDS repository.
Application Metadata Management Commands	Manage the application metadata in the MDS repository.
Sandbox Metadata Management Commands	Manage the metadata in a sandbox in the MDS repository.
Application Label Management Commands	Manage the labels for the application.
Application Management Deployment Commands	Manage the application deployment.
Multitenancy Management Commands	Manage tenants.

8.1 Repository Management Commands

Use the MDS commands listed in [Table 8–2](#) to manage the MDS repository. In the Use with WLST column, online means the command can only be used when connected to a running Administration Server. Offline means the command can only be used when

not connected to a running server. Online or offline means the command can be used in both situations.

Table 8–2 Repository Management Commands

Use this command...	To...	Use with WLST...
<code>createMetadataPartition</code>	Create a metadata repository partition.	Online
<code>deleteMetadataPartition</code>	Delete a metadata repository partition.	Online
<code>deregisterMetadataDBRepository</code>	Deregister a database-based MDS repository.	Online
<code>registerMetadataDBRepository</code>	Register a database-based MDS repository.	Online

8.1.1 createMetadataPartition

Command Category: Repository Management

Use with WLST: Online

8.1.1.1 Description

A metadata repository is used as a common repository for managing metadata of different applications. Many applications use the MDS repository to manage their metadata. Each deployed application uses a logical partition in metadata repository. This logical partition also helps in maintaining the metadata lifecycle. Before deploying an application, you create a partition for it in MDS repository. This command creates a partition with the given name in the specified repository.

8.1.1.2 Syntax

```
createMetadataPartition(repository, partition)
```

Argument	Definition
<i>repository</i>	The name of the repository where the partition will be created.
<i>partition</i>	The name of the partition to create in the repository.

8.1.1.3 Example

The following example creates the metadata partition `partition1` in the repository `mds-myrepos`:

```
wls:/weblogic/serverConfig> createMetadataPartition(repository='mds-myrepos',
                                     partition='partition1')
Executing operation: createMetadataPartition
Metadata partition created: partition1
"partition1"
```

8.1.2 deleteMetadataPartition

Command Category: Repository Management

Use with WLST: Online

8.1.2.1 Description

Deletes a metadata partition in the specified repository. When you delete a repository partition, all of the metadata in that partition is lost.

8.1.2.2 Syntax

```
deleteMetadataPartition(repository, partition)
```

Argument	Definition
<i>repository</i>	The name of the repository that contains the partition.
<i>partition</i>	The name of the partition to delete in the repository.

8.1.2.3 Example

The following example deletes the metadata partition `partition1` from the repository `mds-myrepos`:

```
wls:/weblogic/serverConfig> deleteMetadataPartition(repository='mds-myrepos',
                                                    partition='partition1')
```

Executing operation: deleteMetadataPartition

Metadata partition deleted: partition1

8.1.3 deregisterMetadataDBRepository

Command Category: Repository Management

Use with WLST: Online

8.1.3.1 Description

Removes the database metadata repository registration as a System JDBC data source in the domain. After this command completes successfully, applications can no longer use this repository.

8.1.3.2 Syntax

```
deregisterMetadataDBRepository(name)
```

Argument	Definition
<i>name</i>	The name of the repository to deregister.

8.1.3.3 Example

The following example deregisters the metadata repository `mds-myrepos`:

```
wls:/weblogic/serverConfig> deregisterMetadataDBRepository('mds-myrepos')
```

Executing operation: deregisterMetadataDBRepository.

Metadata DB repository "mds-myrepos" was deregistered successfully.

8.1.4 registerMetadataDBRepository

Command Category: Repository Management

Use with WLST: Online

8.1.4.1 Description

A database metadata repository should be registered with WebLogic Server instances before the application can use it. This command registers a System JDBC data source with the domain for use as database-based metadata repository.

8.1.4.2 Syntax

```
registerMetadataDBRepository(name, dbVendor, host, port, dbName, user, password
[, targetServers])
```

Argument	Definition
<i>name</i>	The name of the repository to register. If the name you supply does not begin with mds-, the commands adds the prefix mds-.
<i>dbVendor</i>	The database vendor. The acceptable values are ORACLE, MSSQL, IBMDB2, and MYSQL.
<i>host</i>	The host name or the IP address of the database.
<i>port</i>	The port number used by the database.
<i>dbName</i>	The service name of the database. For example, orcl.hostname.com
<i>user</i>	The database user name.
<i>password</i>	The password for the database user.
<i>targetServers</i>	Optional. The WebLogic Server instances to which this repository will be registered. If this argument is not specified, then the repository will be registered only to the Administration Server. To specify multiple servers, separate the names with a comma. Register the repository with all Managed Servers to which the application will be deployed.

8.1.4.3 Example

The following example registers the metadata repository `myrepos` to two servers, and specifies the database parameters:

```
wls:/weblogic/serverConfig> registerMetadataDBRepository('myrepos','ORACLE',
    'test.oracle.com','1521','mds','user1','x','server1,server2')
Executing operation: registerMetadataDBRepository.
Metadata DB repository "mds-myrepos" was registered successfully.
'mds-myrepos'
```

8.2 Application Metadata Management Commands

Use the commands in [Table 8-3](#) to manage application metadata.

Table 8-3 Application Metadata Commands

Use this command...	To...	Use with WLST...
deleteMetadata	Deletes the metadata in the application repository.	Online
exportMetadata	Exports metadata for an application.	Online
importMetadata	Imports metadata for an application.	Online
purgeMetadata	Purge metadata.	Online

8.2.1 deleteMetadata

Command Category: Application Metadata

Use with WLST: Online

8.2.1.1 Description

Deletes the selected documents from the application repository. When this command is run against repositories that support versioning (that is, database-based repositories), delete is logical and marks the tip version (the latest version) of the selected documents as "deleted" in the MDS repository partition.

You may want to delete metadata when the metadata is moved from one repository to another. In such a case, after you have exported the metadata, you can delete the metadata in the original repository.

8.2.1.2 Syntax

```
deleteMetadata(application, server, docs [, restrictCustTo] [, excludeAllCust]
[, excludeBaseDocs] [, excludeExtendedMetadata] [, cancelOnException] [,
applicationVersion] [, tenantName])
```

Argument	Definition
<i>application</i>	The name of the application for which the metadata is to be deleted.
<i>server</i>	The target server on which this application is deployed.
<i>docs</i>	<p>A list of comma-separated, fully qualified document names or document name patterns, or both. The patterns can have the following wildcard characters: * and **.</p> <p>The asterisk (*) represents all documents under the current namespace. The double asterisk (**) represents all documents under the current namespace and also recursively includes all documents in subnamespaces.</p> <p>For example, "/oracle/*" will include all documents under "/oracle/" but not include documents under "/oracle/mds/".</p> <p>As another example, "/oracle/**" will include all documents under "/oracle/" and also under "/oracle/mds/" and any other documents further in the namespace chain.</p>
<i>restrictCustTo</i>	<p>Optional. Valid values are percent (%) or a list of comma-separated customization layer names used to restrict the delete operation to delete only customization documents that match the specified customization layers. Each customization layer name can contain, within a pair of brackets, optional customization layer values and value patterns separated by commas.</p> <p>For example:</p> <pre>restrictCustTo="user[scott]" restrictCustTo="site[site1],user[scott]" restrictCustTo="site[site1, %_2],user[scott, m%]"</pre> <p>If you do not specify this argument, only customization classes declared in the cust-config element of adf-config.xml are deleted. If there is no cust-config element declared in adf-config.xml, all customization classes are deleted.</p> <p>If you specify percent (%) as the value of this argument, all customizations are deleted, whether or not they are declared in the cust-config element of adf-config.xml.</p> <p>Use this option to delete all customizations or a subset of declared customizations. You can also use this option to delete customizations from customization classes that are not declared in the cust-config element of adf-config.xml.</p>

Argument	Definition
<i>excludeAllCust</i>	Optional. A Boolean value (true or false) that specifies whether or not to delete all customization documents. This argument defaults to false. It overrides the restrictCustTo option.
<i>excludeBaseDocs</i>	Optional. A Boolean value (true or false) that specifies whether or not to delete base documents. This argument defaults to false.
<i>excludeExtendedMetadata</i>	Optional. A Boolean value (true or false) that specifies whether or not to delete the Extended Metadata documents. This argument defaults to false.
<i>cancelOnException</i>	Optional. A Boolean value (true or false) that specifies whether or not to abort the delete operation when an exception is encountered. On abort, the delete is rolled back if that is supported by the target store. This argument defaults to true.
<i>applicationVersion</i>	Optional. The application version, if multiple versions of the same application are deployed.
<i>tenantName</i>	A unique name identifying the tenant to use for this operation. This argument is required for a multitenant application and is not applicable for a non-multitenant application. For a non-multitenant application, any specified value will be ignored.

8.2.1.3 Examples

The following example deletes metadata files under the package `mypackage` from `mdsApp` deployed in the server `server1`:

```
wls:/weblogic/serverConfig> deleteMetadata(application='mdsapp',
      server='server1', docs='/mypackage/*')
Executing operation: deleteMetadata.
"deleteMetadata" operation completed. Summary of "deleteMetadata" operation is:
List of documents successfully deleted:
/mypackage/jobs.xml
/mypackage/mo.xml
/mypackage/mdssys/cust/site/site1/jobs.xml.xml
/mypackage/mdssys/cust/site/site1/mo.xml.xml
4 documents successfully deleted.
```

The following example deletes metadata files under the package `mypackage` from `mdsApp` deployed in the server `server1` and excludes extended metadata and all customizations:

```
wls:/weblogic/serverConfig> deleteMetadata(application='mdsapp',
      server='server1', docs='/mypackage/*', cancelOnException='false',
      excludeExtendedMetadata='true',
      excludeAllCust='true')
Executing operation: deleteMetadata.
"deleteMetadata" operation completed. Summary of "deleteMetadata" operation is:
List of documents successfully deleted:
/mypackage/jobs.xml
/mypackage/mo.xml
2 documents successfully deleted.
```

The following example deletes metadata files belonging to tenant `tenant1` under the package `mypackage` from the application `app1` deployed in the server `server1`:

```
wls:/weblogic/serverConfig> deleteMetadata(application='app1', server='server1',
      docs='/mypackage/**', tenantName='tenant1')
Executing operation: deleteMetadata.
```

```
deleteMetadata" operation completed. Summary of "deleteMetadata" operation is:
List of documents successfully deleted:
/mypackage/jobs.xml
/mypackage/mdssys/cust/site/site1/jobs.xml.xml
/mypackage/mdssys/cust/site/site2/mo.xml.xml
/mypackage/mdssys/cust/user/user1/mo.xml.xml
```

8.2.2 exportMetadata

Command Category: Application Metadata

Use with WLST: Online

8.2.2.1 Description

Exports application metadata. Use this command and the importMetadata command to transfer application metadata from one server location (for example, testing) to another server location (for example, production).

This command exports application metadata including customizations. However, by default, only those customizations from customization classes that are defined in the cust-config element of adf.config.xml are exported. To export customizations from customization classes not declared, use the restrictCustTo option.

8.2.2.2 Syntax

```
exportMetadata(application, server, toLocation [, docs]
[, restrictCustTo] [, excludeCustFor] [, excludeAllCust] [, excludeBaseDocs]
[, excludeExtendedMetadata] [, excludeSeededDocs]
[, fromLabel][, toLabel] [, applicationVersion] [, remote] [, tenantName])
```

Argument	Definition
<i>application</i>	The name of the application from which the metadata is to be exported.
<i>server</i>	The target server on which this application is deployed.
<i>toLocation</i>	<p>The target directory or archive file (.jar, .JAR, .zip or .ZIP) to which documents selected from the source partition will be transferred. If you export to a directory, the directory must be a local or network directory or file where the application is physically deployed. If you export to an archive, the archive can be located on a local or network directory or file where the application is physically deployed, or on the system on which you are executing the command.</p> <p>If the location does not exist in the file system, a directory will be created except that when the names ends with .jar, .JAR, .zip or .ZIP, an archive file will be created. If the archive file already exists, the exportMetadata operation will overwrite the file.</p> <p>This argument can be used as temporary file system for transferring metadata from one server to another. For more information, see "Moving Metadata from a Source System to a Target System" in the <i>Oracle Fusion Middleware Administrator's Guide</i>.</p>

Argument	Definition
<i>docs</i>	<p>Optional. A list of comma-separated, fully qualified document names or document name patterns, or both. The patterns can have the following wildcard characters: * and **.</p> <p>This argument defaults to "/*", which exports all the metadata in the repository.</p> <p>The asterisk (*) represents all documents under the current namespace. The double asterisk (**) represents all documents under the current namespace and also recursively includes all documents in subnamespaces.</p> <p>For example, "/oracle/*" will include all documents under "/oracle/" but not include documents under "/oracle/mds/".</p> <p>"/oracle/**" will include all documents under "/oracle/" and also under "/oracle/mds/" and any other documents further in the namespace chain.</p>
<i>restrictCustTo</i>	<p>Optional. Valid values are percent (%) or a list of comma-separated customization layer names used to restrict the export operation to export only customization documents that match the specified customization layers. Each customization layer name can contain, within a pair of brackets, optional customization layer values and value patterns separated by commas.</p> <p>For example:</p> <pre data-bbox="667 911 1268 995">restrictCustTo="user[scott]" restrictCustTo="site[site1],user[scott]" restrictCustTo="site[site1, %_2],user[scott, m%]"</pre> <p>If you do not specify this argument, only customization classes declared in the cust-config element of adf-config.xml are exported. If there is no cust-config element declared in adf-config.xml, all customization classes are exported.</p> <p>If you specify percent (%) as the value of this argument, all customizations are exported, whether or not they are declared in the cust-config element of adf-config.xml.</p> <p>Use this option to export all customizations or a subset of declared customizations. You can also use this option to export customizations from customization classes that are not declared in the cust-config element of adf-config.xml.</p> <p>This argument is ignored if the excludeAllCust argument is also specified.</p>
<i>excludeCustFor</i>	<p>Optional. A list of comma-separated customization layer names used to restrict the export operation to exclude customization documents that match the specified customization layers from being exported.</p> <p>This argument is ignored if the excludeAllCust argument is also specified.</p>
<i>excludeAllCust</i>	<p>Optional. A Boolean value (true or false) that specifies whether or not to export all customization documents. This argument defaults to false. This argument overrides the restrictCustTo and excludeCustFor arguments.</p>
<i>excludeBaseDocs</i>	<p>Optional. A Boolean value (true or false) that specifies whether or not to export base documents. This argument defaults to false.</p>
<i>excludeExtendedMetadata</i>	<p>Optional. A Boolean value (true or false) that specifies whether or not to export the Extended Metadata documents. This argument defaults to false.</p>

Argument	Definition
<code>excludeSeededDocs</code>	Optional. A Boolean value (true or false) that specifies whether all documents or only non-seeded documents are exported. Seeded documents are those documents that are packaged in a MAR. To exclude seeded documents, specify true. The default is false.
<code>fromLabel</code>	Optional. Transfers the documents from the source partition that is associated with this label.
<code>toLabel</code>	Optional. Works with the <code>fromLabel</code> argument to transfer the delta between <code>fromLabel</code> to <code>toLabel</code> from the source partition.
<code>applicationVersion</code>	Optional. The application version, if multiple versions of the same application are deployed.
<code>remote</code>	Optional. A Boolean value (true or false) that specifies whether the archive file will be written to a location where the application is deployed (false) or to the system on which you are executing the command (true). The default is false.
<code>tenantName</code>	A unique name identifying the tenant to use for this operation. This argument is required for a multitenant application and is not applicable for a non-multitenant application. For a non-multitenant application, any specified value will be ignored.

8.2.2.3 Examples

The following example exports all metadata files from the application `mdsapp` deployed in the server `server1`.

```
wls:/weblogic/serverConfig> exportMetadata(application='mdsapp',
                                     server='server1',toLocation='/tmp/myrepos',docs='/**')
Location changed to domainRuntime tree. This is a read-only tree with DomainMBean
as the root.
For more help, use help(domainRuntime)
Executing operation: exportMetadata.
"exportMetadata" operation completed. Summary of "exportMetadata" operation is:
List of documents successfully transferred:
/mypackage/write.xml
/mypackage/write1.xml
/sample1.jspx
```

The following example exports only the customization documents under the layer `user` without any base documents from label `label1` to label `label2`:

```
wls:/weblogic/serverConfig> exportMetadata(application='mdsapp',
                                     server='server1',toLocation='/tmp/myrepos',
                                     restrictCustTo='user',
                                     excludeBaseDocs='true',
                                     fromLabel='label1',
                                     toLabel='label2',
                                     applicationVersion='11.1.1')
List of documents successfully transferred:
/mypackage/mdssys/cust/user/user1/write1.xml.xml
/mypackage/mdssys/cust/user/user2/write2.xml.xml
2 documents successfully transferred.
```

8.2.3 importMetadata

Command Category: Application Metadata

Use with WLST: Online

8.2.3.1 Description

Imports application metadata. Use the `exportMetadata` command and this command to transfer application metadata from one server location (for example, testing) to another server location (for example, production).

8.2.3.2 Syntax

```
importMetadata(application, server, fromLocation [, docs]
[, restrictCustTo] [, excludeAllCust] [, excludeBaseDocs]
[, excludeExtendedMetadata] [, excludeUnmodifiedDocs]
[, cancelOnException] [, applicationVersion] [, remote] [, tenantName])
```

Argument	Definition
<i>application</i>	The name of the application for which the metadata is to be imported.
<i>server</i>	The target server on which this application is deployed.
<i>fromLocation</i>	<p>The source directory or archive file from which documents will be selected for transfer. If you exported to a directory, the directory must be a local or network directory or file where the application is physically deployed. If you exported to an archive, the archive can be located on a local or network directory or file where the application is physically deployed, or on the system on which you are executing the command.</p> <p>This argument can be used as a temporary file system location for transferring metadata from one server to another. For more information, see "Moving Metadata from a Source System to a Target System" in the <i>Oracle Fusion Middleware Administrator's Guide</i>.</p>
<i>docs</i>	<p>Optional. A list of comma-separated, fully qualified document names or document name patterns, or both. The patterns can have the following wildcard characters: * and **.</p> <p>This argument defaults to <code>"/**"</code>, which imports all of the documents in the repository.</p> <p>The asterisk (*) represents all documents under the current namespace. The double asterisk (**) represents all documents under the current namespace and also recursively includes all documents in subnamespaces.</p> <p>For example, <code>"/oracle/*"</code> will include all documents under <code>"/oracle/"</code> but not include documents under <code>"/oracle/mds/"</code>.</p> <p><code>"/oracle/**"</code> will include all documents under <code>"/oracle/"</code> and also under <code>"/oracle/mds/"</code> and any other documents further in the namespace chain.</p>

Argument	Definition
<i>restrictCustTo</i>	<p>Optional. Valid values are percent (%) or a list of comma-separated customization layer names used to restrict the import operation to import only customization documents that match the specified customization layers, including customization classes that are not declared in the cust-config element of adf-config.xml. Each customization layer name can contain, within a pair of brackets, optional customization layer values and value patterns separated by commas.</p> <p>For example:</p> <pre>restrictCustTo="user[scott]" restrictCustTo="site[site1],user[scott]" restrictCustTo="site[site1, %_2],user[scott, m%]"</pre> <p>If you do not specify this argument, only customization classes declared in the cust-config element of adf-config.xml are imported. If there is no cust-config element declared in adf-config.xml, all customization classes are imported.</p> <p>If you specify percent (%) as the value of this argument, all customizations are imported, whether or not they are declared in the cust-config element of adf-config.xml.</p> <p>Use this option to import all customizations or a subset of declared customizations. You can also use this option to export customizations from customization classes that are not declared in the cust-config element of adf-config.xml.</p> <p>This argument is ignored if the excludeAllCust argument is also specified.</p>
<i>excludeAllCust</i>	<p>Optional. A Boolean value (true or false) that specifies whether or not to import all customization documents. This argument defaults to false. This argument overrides the restrictCustTo argument.</p>
<i>excludeBaseDocs</i>	<p>Optional. A Boolean value (true or false) that specifies whether or not to import base documents. This argument defaults to false.</p>
<i>excludeExtendedMetadata</i>	<p>Optional. A Boolean value (true or false) that specifies whether or not to import the Extended Metadata documents. This argument defaults to false.</p>
<i>excludeUnmodifiedDocs</i>	<p>Optional. A Boolean value (true or false) that specifies whether only changed documents are imported.</p> <p>If you specify true, only changed documents are imported.</p> <p>The default is false.</p>
<i>cancelOnException</i>	<p>Optional. A Boolean value (true or false) that specifies whether or not to abort the import operation when an exception is encountered.</p> <p>The default is true.</p>
<i>applicationVersion</i>	<p>Optional. The application version, if multiple versions of the same application are deployed.</p>
<i>remote</i>	<p>Optional. A Boolean value (true or false) that specifies whether the archive file is in a location where the application is deployed (false) or on the system on which you are executing the command (true).</p> <p>The default is false.</p>
<i>tenantName</i>	<p>A unique name identifying the tenant to use for this operation. This argument is required for a multitenant application and is not applicable for a non-multitenant application. For a non-multitenant application, any specified value will be ignored.</p>

8.2.3.3 Example

The following example imports all metadata available in /tmp/myrepos to the application mdsapp deployed in the server server1:

```
wls:/weblogic/serverConfig> importMetadata(application='mdsapp', server='server1',
                                         fromLocation='/tmp/myrepos', docs="/**")
Executing operation: importMetadata.
"importMetadata" operation completed. Summary of "importMetadata" operation is:
List of documents successfully transferred:
/app1/jobs.xml
/app1/mo.xml
2 documents successfully transferred.
```

8.2.4 purgeMetadata

Command Category: Application Metadata

Use with WLST: Online

8.2.4.1 Description

Purges the older (non-tip) versions of unlabeled documents from the application's repository. All unlabeled documents will be purged if they are expired, based on Time-To-Live (the olderThan argument). This command is applicable only for repositories that support versioning, that is, database-based repositories.

8.2.4.2 Syntax

```
purgeMetadata(application, server, olderThan [, applicationVersion])
```

Argument	Definition
<i>application</i>	The name of the application, used to identify the partition in the repository on which the purge operation will be run.
<i>server</i>	The target server on which this application is deployed.
<i>olderThan</i>	Document versions that are older than this value (in seconds) will be purged. The maximum value is 2147483647 seconds.
<i>applicationVersion</i>	Optional. The application version, if multiple versions of the same application are deployed.

8.2.4.3 Example

The following example purges the document version history for the application mdsapp deployed in the server server1, if the version is older than 10 seconds:

```
wls:/weblogic/serverConfig> purgeMetadata('mdsapp', 'server1', 10)
Executing operation: purgeMetadata.
Metadata purged: Total number of versions: 10.
Number of versions purged: 0.
```

8.3 Sandbox Metadata Management Commands

Use the commands in [Table 8-4](#) to manage metadata in a sandbox. A sandbox is a temporary location for testing changes before moving them to a production system. Sandboxes are not visible to most users until they are applied.

Table 8–4 Sandbox Metadata Management Commands

Use this command...	To...	Use with WLST...
<code>exportSandboxMetadata</code>	Exports the metadata from a sandbox.	Online
<code>importSandboxMetadata</code>	Imports metadata into a sandbox.	Online

8.3.1 exportSandboxMetadata

Command Category: Sandbox Metadata Management

Use with WLST: Online

8.3.1.1 Description

Exports the changes to the metadata from a sandbox on a test system.

You can only use this command with a database-based MDS repository.

8.3.1.2 Syntax

```
exportSandboxMetadata(application, server, toArchive, sandboxName
    [, restrictCustTo] [, applicationVersion] [, remote] [, tenantName)
```

Argument	Definition
<i>application</i>	The name of the application from which the metadata is to be exported.
<i>server</i>	The target server on which this application is deployed.
<i>toArchive</i>	The target archive file (.jar, .JAR, .zip or .ZIP) to which the sandbox contents will be transferred. The archive can be located on a local or network directory where the application is physically deployed. If you specify the -remote argument, the archive can be located on the system on which you are executing the command.
<i>sandboxName</i>	The name of the sandbox to export.
<i>restrictCustTo</i>	<p>Optional. Valid values are percent (%) or a list of comma-separated customization layer names used to restrict the export operation to export only customization documents that match the specified customization layers. Each customization layer name can contain, within a pair of brackets, optional customization layer values and value patterns separated by commas.</p> <p>For example:</p> <pre>restrictCustTo="user[scott]" restrictCustTo="site[site1],user[scott]" restrictCustTo="site[site1, %_2],user[scott, m%]"</pre> <p>If you do not specify this argument or if you specify percent (%) as the value of this argument, all customizations are exported, whether or not they are declared in the cust-config element of adf-config.xml.</p> <p>Use this option to export all customizations or a subset of declared customizations. You can also use this option to export customizations from customization classes that are not declared in the cust-config element of adf-config.xml.</p> <p>This argument is ignored if the excludeAllCust argument is also specified.</p>

Argument	Definition
<i>applicationVersion</i>	Optional. The application version, if multiple versions of the same application are deployed.
<i>remote</i>	Optional. A Boolean value (true or false) that specifies whether the archive file will be written to a location where the application is deployed (false) or to the system on which you are executing the command (true). The default is false.
<i>tenantName</i>	A unique name identifying the tenant to use for this operation. This argument is required for a multitenant application and is not applicable for a non-multitenant application. For a non-multitenant application, any specified value will be ignored.

8.3.1.3 Example

The following example exports a sandbox from the MDS repository for the application myapp:

```
wls:/weblogic/serverConfig>exportSandboxMetadata('myapp', 'server1',
        '/tmp/sandbox1.jar', 'sandbox1')
```

8.3.2 importSandboxMetadata

Command Category: Sandbox Metadata Management

Use with WLST: Online

8.3.2.1 Description

Imports the contents of a sandbox archive to another sandbox in the MDS repository partition of the specified application. It can also update the contents of a given archive to a sandbox in the MDS repository partition of a given application. All customizations are imported, whether or not they are declared in the cust-config element of adf-config.xml.

You can only use this command with a database-based MDS repository.

8.3.2.2 Syntax

```
importSandboxMetadata(application, server, fromArchive [, forceSBCreation]
        [, useExistingSandbox] [, sandboxName] [, applicationVersion]
        [, remote] [, tenantName])
```

Argument	Definition
<i>application</i>	The name of the application for which the metadata is to be imported.
<i>server</i>	The target server on which this application is deployed.
<i>fromArchive</i>	The source archive file from which documents will be selected for transfer. The archive can be located on a local or network directory where the application is physically deployed. If you specify the <code>-remote</code> argument, the archive can be located on the system on which you are executing the command.

Argument	Definition
<i>forceSBCreation</i>	Optional. A Boolean value (true or false) that specifies whether the operation will overwrite an existing sandbox with the same name. When the argument is set to <code>true</code> , if the <code>fromArchive</code> argument specifies a sandbox with the same name as one that already exists in the application's partition, the original sandbox is deleted and a new sandbox is created. When the argument is set to <code>false</code> , if a sandbox with the same name exists, an exception is thrown. The default is <code>false</code> .
<i>useExistingSandbox</i>	Optional. When set to <code>true</code> , the contents of the archive are imported to the sandbox specified with the <code>sandboxName</code> argument. This argument is ignored if there is no value specified for <code>sandboxName</code> . The default is <code>false</code> .
<i>sandboxName</i>	Optional. The name of the sandbox to update. This argument is ignored if <code>useExistingSandbox</code> is <code>false</code> .
<i>applicationVersion</i>	Optional. The application version, if multiple versions of the same application are deployed.
<i>remote</i>	Optional. A Boolean value (true or false) that specifies whether the archive file is in a location where the application is deployed (false) or on the system on which you are executing the command (true). The default is <code>false</code> .
<i>tenantName</i>	A unique name identifying the tenant to use for this operation. This argument is required for a multitenant application and is not applicable for a non-multitenant application. For a non-multitenant application, any specified value will be ignored.

8.3.2.3 Examples

The following example imports the contents of the sandbox `sandbox1.jar`:

```
wls:/weblogic/serverConfig> importSandboxMetadata(application='myapp', 'server1',
'/tmp/sandbox1.jar')
```

The following example updates the sandbox `sandbox1.jar`:

```
wls:/weblogic/serverConfig> importSandboxMetadata('myapp', 'server1',
'/tmp/sandbox1.jar', useExistingSandbox='true', sandboxName='sandbox1')
```

8.4 Application Label Management Commands

Use the commands in [Table 8–5](#) to manage labels for applications.

Table 8–5 Application Label Management Commands

Use this command...	To...	Use with WLST...
createMetadataLabel	Creates a metadata label.	Online
deleteMetadataLabel	Deletes a metadata label from the repository partition.	Online
listMetadataLabels	Lists metadata labels in the repository partition.	Online
promoteMetadataLabel	Promotes the metadata associated with a label to tip.	Online
purgeMetadataLabels	Deletes the labels matching the specified criteria.	Online

8.4.1 createMetadataLabel

Command Category: Application Label Management

Use with WLST: Online

8.4.1.1 Description

Creates a new label for the documents in the application's repository partition. This command is applicable only for repositories that support versioning.

8.4.1.2 Syntax

```
createMetadataLabel(application, server, name [, applicationVersion] [,
tenantName])
```

Argument	Definition
<i>application</i>	The name of the application for which a label will be created in the partition configured for this application.
<i>server</i>	The target server on which this application is deployed. If the application is deployed to multiple Managed Servers in a cluster, you can use the name of any of the server names. You cannot specify multiple server names.
<i>name</i>	The name of the label to create in the repository partition.
<i>applicationVersion</i>	Optional. The application version, if multiple versions of the same application are deployed.
<i>tenantName</i>	A unique name identifying the tenant to use for this operation. This argument is required for a multitenant application and is not applicable for a non-multitenant application. For a non-multitenant application, any specified value will be ignored.

8.4.1.3 Example

The following example creates the label `label1` for the application `mdsapp` deployed in the server `server1`:

```
wls:/weblogic/serverConfig> createMetadataLabel('mdsapp','server1','label1')
Executing operation: createMetadataLabel.
Created metadata label "label1".
```

8.4.2 deleteMetadataLabel

Command Category: Application Label Management

Use with WLST: Online

8.4.2.1 Description

Deletes a label for the documents in the application's repository partition. This command is applicable only for repositories that support versioning.

8.4.2.2 Syntax

```
deleteMetadataLabel(application, server, name [, applicationVersion] [,
tenantName])
```

Argument	Definition
<i>application</i>	The name of the application from whose associated partition the label is to be deleted.
<i>server</i>	The target server on which this application is deployed. If the application is deployed to multiple Managed Servers in a cluster, you can use the name of any of the server names. You cannot specify multiple server names.
<i>name</i>	The name of the label to delete in the repository partition.
<i>applicationVersion</i>	Optional. The application version, if multiple versions of the same application are deployed.
<i>tenantName</i>	A unique name identifying the tenant to use for this operation. This argument is required for a multitenant application and is not applicable for a non-multitenant application. For a non-multitenant application, any specified value will be ignored.

8.4.2.3 Example

The following example deletes the metadata label `label1` from the application `mdsapp` deployed in the server `server1`:

```
wls:/weblogic/serverConfig> deleteMetadataLabel('mdsapp','server1','label1')
Executing operation: deleteMetadataLabel.
Deleted metadata label "label1".
```

8.4.3 listMetadataLabels

Command Category:

Use with WLST: Online

8.4.3.1 Description

Lists all of the metadata labels in the application's repository partition. This command is applicable only for repositories that support versioning.

8.4.3.2 Syntax

```
listMetadataLabels(application, server [, applicationVersion] [, tenantName])
```

Argument	Definition
<i>application</i>	The name of the application for which all of the labels in the repository partition should be listed.
<i>server</i>	The target server on which this application is deployed. If the application is deployed to multiple Managed Servers in a cluster, you can use the name of any of the server names. You cannot specify multiple server names.
<i>applicationVersion</i>	Optional. The application version, if multiple versions of the same application are deployed.
<i>tenantName</i>	A unique name identifying the tenant to use for this operation. This argument is required for a multitenant application and is not applicable for a non-multitenant application. For a non-multitenant application, any specified value will be ignored.

8.4.3.3 Example

The following example lists the metadata labels available for the application `mdsapp` deployed in the server `server1`:

```
wls:/weblogic/serverConfig> listMetadataLabels('mdsapp', 'server1')
Executing operation: listMetadataLabels.
Database Repository partition contains the following labels:
label2
label3
```

8.4.4 promoteMetadataLabel

Command Category: Application Label Management

Use with WLST: Online

8.4.4.1 Description

Promotes documents associated with a label to the tip version in the repository. This command is useful to achieve rollback capability. This command is applicable only for repositories that support versioning.

8.4.4.2 Syntax

```
promoteMetadataLabel(application, server, name [, applicationVersion] [,
tenantName])
```

Argument	Definition
<i>application</i>	The name of the application in whose associated repository the metadata is to be promoted to tip.
<i>server</i>	The target server on which this application is deployed. If the application is deployed to multiple Managed Servers in a cluster, you can use the name of any of the server names. You cannot specify multiple server names.
<i>name</i>	The name of the label to promote in the repository partition.
<i>applicationVersion</i>	Optional. The application version, if multiple versions of the same application are deployed.
<i>tenantName</i>	A unique name identifying the tenant to use for this operation. This argument is required for a multitenant application and is not applicable for a non-multitenant application. For a non-multitenant application, any specified value will be ignored.

8.4.4.3 Example

The following example promotes the metadata label `label1` to tip in the application `mdsapp` deployed in the server `server1`:

```
wls:/weblogic/serverConfig> promoteMetadataLabel('mdsapp', 'server1', 'label1')
Executing operation: promoteMetadataLabel.
Promoted metadata label "label1" to tip.
```

8.4.5 purgeMetadataLabels

Command Category: Application Label Management

Use with WLST: Online

8.4.5.1 Description

Purges or lists the metadata labels that match the given pattern or age, but does not delete the metadata documents that were part of the label. You can delete the documents by executing the [purgeMetadata](#) command.

8.4.5.2 Syntax

```
purgeMetadataLabels(repository, partition [, namePattern] [, olderThanInMin]
[, infoOnly] [, tenantName])
```

Argument	Definition
<i>repository</i>	The name of the MDS repository that contains the partition whose metadata labels will be purged or listed.
<i>partition</i>	The name of the partition whose metadata labels will be purged or listed.
<i>namePattern</i>	Optional. A pattern that matches the names of labels. The pattern can contain the following special characters: <ul style="list-style-type: none"> ▪ The percent (%) character, which matches any number of characters. ▪ The underscore (_) character, which matches exactly one arbitrary character. ▪ The backslash character ('\'), which can be used to escape the percent, the underscore, and the backslash (itself) characters, so they match only %, _ or \.
<i>olderThanInMin</i>	Optional. The age of the labels, in minutes. The default is 525600 (one year).
<i>infoOnly</i>	Optional. Valid values are true or false. If you set it to true, it does not purge the labels, but lists the labels that match the specified pattern. The default is false.
<i>tenantName</i>	A unique name identifying the tenant to use for this operation. This argument is required for a multitenant application and is not applicable for a non-multitenant application. For a non-multitenant application, any specified value will be ignored.

8.4.5.3 Examples

The following example lists the labels that match the specified namePattern, but does not delete them:

```
wls:/weblogic/serverConfig> purgeMetadataLabels(repository='mds-myRepos',
partition='partition1', namePattern='mylabel*', infoOnly='true')
```

The following example purges the labels that match the specified namePattern and that are older than a year:

```
wls:/weblogic/serverConfig> purgeMetadataLabels(repository='mds-myRepos',
partition='partition1', namePattern='mylabel*')
```

The following example deletes labels that match the specified namePattern and that are older than 30 minutes:

```
wls:/weblogic/serverConfig> purgeMetadataLabels(repository='mds-myRepos',
partition='partition1',
namePattern='mylabel*', olderThanInMin='30')
```

8.5 Application Management Deployment Commands

Use the commands in [Table 8–6](#) to manage deployment.

Table 8–6 Application Management Deployment Commands

Use this command...	To...	Use with WLST...
getMDSArchiveConfig	Returns an MDSArchiveConfig object.	Offline
importMAR	Imports an MAR.	Online

8.5.1 getMDSArchiveConfig

Command Category: Application Management Deployment

Use with WLST: Offline

8.5.1.1 Description

Returns a handle to the MDSArchiveConfig object for the specified archive. The returned MDSArchiveConfig object's methods can be used to change application and shared repository configuration in an archive.

The MDSArchiveConfig object provides the following methods:

- **setAppMetadataRepository**—This method sets the connection details for the application metadata repository.

If the archive's existing adf-config.xml file does not contain any configuration for the application's metadata repository, then you must provide all necessary arguments to define the target repository. To define a database-based repository, provide the repository, partition, type, and jndi arguments. For a file-based repository, provide the path argument instead of jndi.

If the adf-config.xml file already contains some configuration for the application's metadata repository, you can provide only a subset of arguments that you want to change. You do not need to provide all arguments in such a case. However, if the store type is changed, then the corresponding jndi or path argument is required.

- **setAppSharedMetadataRepository**—This method sets the connection details for the shared repository in the application archive that is mapped to specified namespace.

If the archive's existing adf-config.xml file does not contain any configuration for a shared metadata repository mapped to the specified namespace, you must provide all required arguments (in this case, repository, partition, type, and jndi or path). For a database-based repository, provide the jndi argument. For a file-based repository, path is a required argument.

If the adf-config.xml file already contains some configuration for a shared metadata repository mapped to the specified namespace and you want to change some specific arguments, you can provide only a subset of those arguments; all others are not needed.

- **save**—If you specify the toLocation argument, then the changes will be stored in the target archive file and the original file will remain unchanged. Otherwise, the changes will be saved in the original file itself.

8.5.1.2 Syntax

```
archiveConfigObject = getMDSArchiveConfig(fromLocation)
```


Argument	Definition
<i>fromLocation</i>	The name of the ear file, including its complete path.

The syntax for `setAppMetadataRepository` is:

```
archiveConfigObject.setAppMetadataRepository([repository] [, partition]
[, type] [, jndi] [, path])
```

Argument	Definition
<i>repository</i>	Optional. The name of the application's repository.
<i>partition</i>	Optional. The name of the partition for the application's metadata.
<i>type</i>	Optional. The type of connection, file or database, to the repository. Valid values are 'File' or 'DB' (case insensitive).
<i>jndi</i>	Optional. The JNDI location for the database connection. This argument is required if the type is set to DB. This argument is not considered if the type is set to File.
<i>path</i>	Optional. The directory for the metadata files. This argument is required if the type is set to File. This argument is not considered if the type is set to DB.

The syntax for `setAppSharedMetadataRepository` is:

```
archiveConfigObject.setAppSharedMetadataRepository(namespace [, repository]
[, partition] [, type] [, jndi] [, path])
```

Argument	Definition
<i>namespace</i>	The namespace used for looking up the shared repository to set connection details.
<i>repository</i>	Optional. The name of the application's shared repository.
<i>partition</i>	Optional. The name of the partition for the application's shared metadata.
<i>type</i>	Optional. The type of connection, file or database, to the repository. Valid values are 'File' or 'DB' (case insensitive).
<i>jndi</i>	Optional. The JNDI location for the database connection. This argument is required if the type is set to DB. This argument will not be considered if the type is set to File.
<i>path</i>	Optional. The location of the file metadata store. This argument is required if the type is set to File. This argument will not be considered if the type is set to DB.

The syntax for `save` is:

```
archiveConfigObject.save([toLocation])
```

Argument	Definition
<i>toLocation</i>	Optional. The file name, including the absolute path to store the changes. If this option is not provided, the changes are written to the archive represented by this configuration object.

8.5.1.3 Examples

In the following example, if the adf-config.xml file in the archive does not have the application and shared metadata repositories defined, then you should provide the complete connection information.

```
wls:/offline> archive = getMDSArchiveConfig(fromLocation='/tmp/testArchive.ear')

wls:/offline> archive.setAppMetadataRepository(repository='AppRepos1',
        partition='partition1', type='DB', jndi='mds-jndi1')

wls:/offline> archive.setAppSharedMetadataRepository(namespace='/a',
        repository='SharedRepos1', partition='partition2', type='File',
        path='/temp/dir')
wls:/offline> archive.save()
```

In the following example, if the adf-config.xml file in the archive already has the application and shared metadata repositories defined, all arguments are optional. You can set only the arguments you want to change.

```
wls:/offline> archive = getMDSArchiveConfig(fromLocation='/tmp/testArchive.ear')
wls:/offline> archive.setAppMetadataRepository(partition='MDS-partition2')
wls:/offline> archive.setAppSharedMetadataRepository(namespace='/a',
        repository='SharedRepos2')
wls:/offline> archive.save(toLocation='/tmp/targetArchive.ear')
```

8.5.2 importMAR

Command Category: Application Management Deployment

Use with WLST: Online

8.5.2.1 Description

Imports the metadata from the MAR that is packaged with the application's EAR file. If the MAR had already been imported into the partition, the command deletes the previous version and imports the new version.

8.5.2.2 Syntax

```
importMAR(application, server [, force] [, applicationVersion] )
```

Argument	Definition
<i>application</i>	The name of the application for which the metadata is to be imported.
<i>server</i>	The target server on which this application is deployed.
<i>force</i>	Optional. A Boolean value (true or false) that specifies whether only changed documents and MARs are imported. For a database-based repository, if you set this argument to false, only new or changed documents from changed MARs are imported. The command creates a label for each MAR for which documents are imported. The label has the following format: <code>postDeploy_application_name_MAR_name_MAR_checksum</code> For a file-based repository, if you set this argument to false, only changed MARs are imported. The command does not compare individual documents. The command creates a file in the repository for each imported MAR. The default is true.

Argument	Definition
<i>applicationVersion</i>	Optional. The application version, if multiple versions of the same application are deployed.

8.5.2.3 Example

The following example imports metadata from the MAR to the application `mdsapp`:

```
wls:/weblogic/serverConfig> importMAR('mdsapp','server1')
Executing operation: importMAR.
"importMAR" operation completed. Summary of "importMAR" operation is:
/app1/jobs.xml
/app1/mo.xml
2 documents successfully transferred.
```

8.6 Multitenancy Management Commands

Use the commands in [Table 8-7](#) to manage tenants.

Table 8-7 Multitenancy Management Commands

Use this command...	To...	Use with WLST...
deprovisionTenant	Deprovisions a tenant from the metadata store.	Online
listTenants	Lists the tenants.	Online

8.6.1 deprovisionTenant

Deprovisions a tenant from the metadata store. All metadata associated with the tenant will be removed from the store

8.6.1.1 Syntax

```
deprovisionTenant(repository, partition, tenantName)
```

Argument	Definition
<i>repository</i>	The name of the repository that contains the tenant.
<i>partition</i>	The name of the partition that contains the tenant.
<i>tenantName</i>	A unique name identifying the tenant to use for this operation.

8.6.1.2 Example

The following example deprovisions the tenant with tenantName `tenant1`:

```
wls:/weblogic/serverConfig> deprovisionTenant("mds-myrepos", "part1", "tenant1")
Executing operation: deprovisionTenant.
Tenant "tenant1" has been deprovisioned.
```

8.6.2 listTenants

Lists all tenants in an MDS Repository partition.

8.6.2.1 Syntax

```
listTenants(repository, partition)
```

Argument	Definition
<i>repository</i>	The name of the repository that contains the tenants.
<i>partition</i>	The name of the partition that contains the tenants.

8.6.2.2 Example

The following example lists all tenants in the specified repository and partition:

```
wls:/weblogic/serverConfig> listTenants("mds-myrepos", "part1")  
Executing operation: listTenants.  
0 GLOBAL  
1 tenant1  
2 tenant2  
3 tenant3
```

Oracle SOA Suite Custom WLST Commands

This chapter describes how to use custom WLST commands in Oracle SOA Suite to deploy, manage, compile, package, test, export, import, partition, and diagnosis SOA composite applications; manage configuration plans; and validate human workflow tasks. Command line syntax, arguments, and command examples are also provided.

Note: To use these commands, you must invoke WLST from the Oracle home in which the component has been installed. See "Using Custom WLST Commands" in the *Oracle Fusion Middleware Administrator's Guide*.

This chapter includes the following sections:

- [Section 9.1, "Overview of WSLT Command Categories"](#)
- [Section 9.2, "Deployment Commands"](#)
- [Section 9.3, "SOA Composite Application Management Commands"](#)
- [Section 9.4, "SOA Composite Application Compilation Commands"](#)
- [Section 9.5, "SOA Composite Application Packaging Commands"](#)
- [Section 9.6, "SOA Composite Application Test Commands"](#)
- [Section 9.7, "SOA Composite Application HTTP Client-Based Export and Import Commands"](#)
- [Section 9.8, "SOA Composite Application MBean-Based Export and Import Commands"](#)
- [Section 9.9, "SOA Composite Application Partition Management Commands"](#)
- [Section 9.10, "SOA Composite Application Preconfigured WLDF Watches Command"](#)
- [Section 9.11, "Configuration Plan Management Commands"](#)
- [Section 9.12, "Task Validation Commands"](#)

For additional details about deployment, configuration plans, and test suites, see *Oracle Fusion Middleware Developer's Guide for Oracle SOA Suite*.

9.1 Overview of WSLT Command Categories

WLST commands are divided into the categories shown in [Table 9-1](#).

Table 9–1 Oracle SOA Suite Command Categories

Command category	Description
Deployment Commands	Deploy and undeploy SOA composite applications.
SOA Composite Application Management Commands	Start, stop, activate, retire, assign a default revision version, and list deployed SOA composite applications.
Configuration Plan Management Commands	Attach, extract, generate, and validate configuration plans for SOA composite applications.
Task Validation Commands	Validate human workflow tasks.
SOA Composite Application Compilation Commands	Compile SOA composite applications.
SOA Composite Application Packaging Commands	Package SOA composite applications into archive files to deploy.
SOA Composite Application Test Commands	Test SOA composite applications prior to deployment in a production environment.
SOA Composite Application HTTP Client-Based Export and Import Commands	Export and import SOA composite applications based on the HTTP client.
SOA Composite Application MBean-Based Export and Import Commands	Export and import SOA composite applications on the server-based composite store MBean (CompositeStoreMBean).
SOA Composite Application Partition Management Commands	Logically group different revisions of your SOA composite applications into separate sections.

9.2 Deployment Commands

Use the deployment commands, listed in [Table 9–2](#), to deploy and undeploy SOA composite applications.

Table 9–2 Deployment Commands for WLST Configuration

Use this command...	To...	Use with WLST...
sca_deployComposite	Deploy a SOA composite application.	Offline
sca_undeployComposite	Undeploy a SOA composite application.	Offline

9.2.1 sca_deployComposite

Command Category: Deployment Commands

Use with WLST: Offline

9.2.1.1 Description

Deploys a SOA composite application to the Oracle WebLogic Server. This command does *not* package the artifact files of the application for deployment. See [Section 9.5, "SOA Composite Application Packaging Commands"](#) for instructions on packaging a SOA composite application.

9.2.1.2 Syntax

```
sca_deployComposite(serverURL, sarLocation, [overwrite], [user], [password],
[forceDefault], [configplan], [partition])
```

Argument	Definition
<i>serverURL</i>	URL of the server that hosts the SOA Infrastructure application (for example, <code>http://myhost10:7001</code>).
<i>sarLocation</i>	Absolute path to one the following: <ul style="list-style-type: none"> ▪ SOA archive (SAR) file. A SAR file is a special JAR file that requires a prefix of <code>sca_</code> (for example, <code>sca>HelloWorld_rev1.0.jar</code>). The SAR file can be deployed with the deployment commands (such as <code>sca_deployComposite()</code>), but a regular <code>.jar</code> file is not treated as a special SAR file. ▪ ZIP file that includes multiple SARs, metadata archives (MARs), or both. ▪ Enterprise archive (EAR) file that contains a SAR file.
<i>overwrite</i>	Optional. Indicates whether to overwrite an existing SOA composite application file. <ul style="list-style-type: none"> ▪ <code>false</code> (default): Does not overwrite the file. ▪ <code>true</code>: Overwrites the file.
<i>user</i>	Optional. User name to access the composite deployer servlet when basic authentication is configured.
<i>password</i>	Optional. Password to access the composite deployer servlet when basic authentication is configured.
<i>forceDefault</i>	Optional. Indicates whether to set the new composite as the default. <ul style="list-style-type: none"> ▪ <code>true</code> (default): Makes it the default composite. ▪ <code>false</code>: Does not make it the default composite.
<i>configplan</i>	Optional. Absolute path of a configuration plan to be applied to a specified SAR file or to all SAR files included in the ZIP file.
<i>partition</i>	Optional. The name of the partition in which to deploy the SOA composite application. The default value is <code>default</code> . If you do not specify a partition, the composite is automatically deployed into the <code>default</code> partition.

Note: Human workflow artifacts such as task mapped attributes (previously known as flex field mappings) and rules (such as vacation rules) are defined based on the namespace of the task definition. Therefore, the following issues are true when the same SOA composite application with a human workflow task is deployed into multiple partitions:

- For the same task definition type, mapped attributes defined in one partition are visible in another partition.
 - Rules defined on a task definition in one partition can apply to the same definition in another partition.
-
-

9.2.1.3 Examples

The following example deploys the HelloWorld application.

```
wls:/mydomain/ServerConfig> sca_deployComposite("http://myhost10:7001",
"/tmp/sca_HelloWorld_rev1.0.jar")
```

The following example deploys the HelloWorld application as the default version.

```
wls:/mydomain/ServerConfig> sca_deployComposite("http://myhost10:7001",
"/tmp/sca_HelloWorld_rev1.0.jar", true)
```

The following example deploys the HelloWorld application with a required user name when basic authentication is configured. You are then prompted to provide the password for this user name.

```
wls:/mydomain/ServerConfig> sca_deployComposite("http://myhost10:7001",
"/tmp/sca_HelloWorld_rev1.0.jar", user="weblogic")
Password:
```

The following example deploys the HelloWorld application and applies the configuration plan named `deployplan.xml`.

```
wls:/mydomain/ServerConfig> sca_deployComposite("http://myhost10:7001",
"/tmp/sca_HelloWorld_rev1.0.jar", forceDefault=false,
configplan="/tmp/deployplan.xml")
```

The following example deploys the HelloWorld ZIP file, which can include multiple SARs, MARs, or both.

```
wls:/mydomain/ServerConfig> sca_deployComposite("http://myhost:7001",
"/tmp/HelloWorld.zip")
```

The following example deploys the HelloWorld application to the myPartition partition.

```
wls:/mydomain/ServerConfig> sca_deployComposite("http://stadb10:7001",
"/tmp/sca_HelloWorld_rev1.0.jar", partition="myPartition")
```

9.2.2 sca_undeployComposite

Command Category: Deployment Commands

Use with WLST: Offline

9.2.2.1 Description

Undeploys a currently deployed SOA composite application.

9.2.2.2 Syntax

```
sca_undeployComposite(serverURL, compositeName, revision, [user], [password],
[partition])
```

Argument	Definition
<i>serverURL</i>	URL of the server that hosts the SOA Infrastructure application (for example, <code>http://myhost10:7001</code>).
<i>compositeName</i>	Name of the SOA composite application.
<i>revision</i>	Revision ID of the SOA composite application.
<i>user</i>	Optional. User name to access the composite deployer servlet when basic authentication is configured.
<i>password</i>	Optional. Password to access the composite deployer servlet when basic authentication is configured.
<i>partition</i>	Optional. The name of the partition in which the SOA composite application is located. The default value is <code>default</code> . If you do not specify a partition, the <code>default</code> partition is searched for the SOA composite application. However, no other partitions are searched.

9.2.2.3 Examples

The following example undeploys the `HelloWorld` application.

```
wls:/mydomain/ServerConfig> sca_undeployComposite("http://myhost10:7001",
"HelloWorld", "1.0")
```

The following example undeploys the `HelloWorld` application with a required user name when basic authentication is configured. You are then prompted to provide the password for this user name.

```
wls:/mydomain/ServerConfig> sca_undeployComposite("http://myhost10:7001",
"HelloWorld", "1.0", user="weblogic")
Password:
```

The following example undeploys the `HelloWorld` application in the `myPartition` partition.

```
wls:/mydomain/ServerConfig> sca_undeployComposite("http://stadb10:7001",
"HelloWorld", "1.0", partition='myPartition')
```

9.3 SOA Composite Application Management Commands

Use the management commands, listed in [Table 9–3](#), to start, stop, activate, retire, assign a default revision version, and list deployed SOA composite applications.

Table 9–3 SOA Composite Application Management Commands for WLST Configuration

Use this command...	To...	Use with WLST...
<code>sca_startComposite</code>	Start a previously stopped SOA composite application.	Offline
<code>sca_stopComposite</code>	Stop a SOA composite application.	Offline
<code>sca_activateComposite</code>	Activate a previously retired SOA composite application.	Offline
<code>sca_retireComposite</code>	Retire a SOA composite application.	Offline

Table 9–3 (Cont.) SOA Composite Application Management Commands for WLST

Use this command...	To...	Use with WLST...
<code>sca_assignDefaultComposite</code>	Assign the default revision version to a SOA composite application.	Offline
<code>sca_getDefaultCompositeRevision</code>	List the revision of the default composite of the given composite series.	Offline
<code>sca_listDeployedComposites</code>	List the deployed SOA composite applications.	Offline
<code>sca_listCompositesFailedInServerStart</code>	List the SOA composite applications that failed during server startup.	Offline

9.3.1 `sca_startComposite`

Command Category: Application Management Commands

Use with WLST: Offline

9.3.1.1 Description

Starts a previously stopped SOA composite application.

9.3.1.2 Syntax

```
sca_startComposite(host, port, user, password, compositeName, revision, [label], [partition])
```

Argument	Definition
<i>host</i>	Hostname of the Oracle WebLogic Server (for example, <code>myhost</code>).
<i>port</i>	Port of the Oracle WebLogic Server (for example, <code>7001</code>).
<i>user</i>	User name for connecting to the running server to get MBean information (for example, <code>weblogic</code>).
<i>password</i>	Password for the user name.
<i>compositeName</i>	Name of the SOA composite application.
<i>revision</i>	Revision of the SOA composite application.
<i>label</i>	Optional. Label of the SOA composite application. The label identifies the metadata service (MDS) artifacts associated with the application. If the label is not specified, the system finds the latest one.
<i>partition</i>	Optional. The name of the partition in which the SOA composite application is located. The default value is <code>default</code> . If you do not specify a partition, the <code>default</code> partition is searched for the SOA composite application. However, no other partitions are searched.

9.3.1.3 Example

The following example starts revision 1.0 of the `HelloWorld` application.

```
wls:/mydomain/ServerConfig> sca_startComposite("myhost", "7001", "weblogic", "welcome1", "HelloWorld", "1.0")
```

The following example starts revision 1.0 of the `HelloWorld` application in the partition `myPartition`.

```
wls:/mydomain/ServerConfig> sca_startComposite("stadp10", "7001", "weblogic",
"weblogic", "HelloWorld", "1.0", partition="myPartition")
```

9.3.2 sca_stopComposite

Command Category: Application Management Commands

Use with WLST: Offline

9.3.2.1 Description

Stops a currently running SOA composite application.

9.3.2.2 Syntax

```
sca_stopComposite(host, port, user, password, compositeName, revision, [label],
[partition])
```

Argument	Definition
<i>host</i>	Hostname of the Oracle WebLogic Server (for example, myhost).
<i>port</i>	Port of the Oracle WebLogic Server (for example, 7001).
<i>user</i>	User name for connecting to the running server to get MBean information (for example, weblogic).
<i>password</i>	Password for the user name.
<i>compositeName</i>	Name of the SOA composite application.
<i>revision</i>	Revision of the SOA composite application.
<i>label</i>	Optional. Label of the SOA composite application. The label identifies the MDS artifacts associated with the application. If the label is not specified, the system finds the latest one.
<i>partition</i>	Optional. The name of the partition in which the SOA composite application is located. The default value is <code>default</code> . If you do not specify a partition, the <code>default</code> partition is searched for the SOA composite application. However, no other partitions are searched.

9.3.2.3 Example

The following example stops revision 1.0 of the HelloWorld application.

```
wls:/mydomain/ServerConfig> sca_stopComposite("myhost", "7001", "weblogic",
"welcome1", "HelloWorld", "1.0")
```

The following example stops revision 1.0 of the HelloWorld application in the partition myPartition.

```
wls:/mydomain/ServerConfig> sca_stopComposite("stadp10", "7001", "weblogic",
"weblogic", "HelloWorld", "1.0", partition="myPartition")
```

9.3.3 sca_activateComposite

Command Category: Application Management Commands

Use with WLST: Offline

9.3.3.1 Description

Activates a retired SOA composite application and its instances. You can then create new instances.

9.3.3.2 Syntax

```
sca_activateComposite(host, port, user, password, compositeName, revision,
[label], [partition])
```

Argument	Definition
<i>host</i>	Hostname of the Oracle WebLogic Server (for example, myhost).
<i>port</i>	Port of the Oracle WebLogic Server (for example, 7001).
<i>user</i>	User name for connecting to the running server to get MBean information (for example, weblogic).
<i>password</i>	Password for the user name.
<i>compositeName</i>	Name of the SOA composite application.
<i>revision</i>	Revision of the SOA composite application.
<i>label</i>	Optional. Label of the SOA composite application. The label identifies the MDS artifacts associated with the application. If the label is not specified, the system finds the latest one.
<i>partition</i>	Optional. The name of the partition in which the SOA composite application is located. The default value is default. If you do not specify a partition, the default partition is searched for the SOA composite application. However, no other partitions are searched.

9.3.3.3 Example

The following example activates revision 1.0 of the HelloWorld application.

```
wls:/mydomain/ServerConfig> sca_activateComposite("myhost", "7001", "weblogic",
"welcome1", "HelloWorld", "1.0")
```

The following example activates revision 1.0 of the HelloWorld application in the partition myPartition.

```
wls:/mydomain/ServerConfig> sca_activateComposite("stadb10", "7001", "weblogic",
"weblogic", "HelloWorld", "1.0", partition="myPartition")
```

9.3.4 sca_retireComposite

Command Category: Application Management Commands

Use with WLST: Offline

9.3.4.1 Description

Stops and retires a SOA composite application and all its running instances. If the process life cycle is retired, you cannot create a new instance. Existing instances are allowed to complete normally.

9.3.4.2 Syntax

```
sca_retireComposite(host, port, user, password, compositeName, revision, [label],
[partition])
```

Argument	Definition
<i>host</i>	Hostname of the Oracle WebLogic Server (for example, myhost).
<i>port</i>	Port of the Oracle WebLogic Server (for example, 7001).

Argument	Definition
<i>user</i>	User name for connecting to the running server to get MBean information (for example, <code>weblogic</code>).
<i>password</i>	Password for the user name.
<i>compositeName</i>	Name of the SOA composite application.
<i>revision</i>	Revision of the SOA composite application.
<i>label</i>	Optional. Label of the SOA composite application. The label identifies the MDS artifacts associated with the application. If the label is not specified, the system finds the latest one.
<i>partition</i>	Optional. The name of the partition in which the SOA composite application is located. The default value is <code>default</code> . If you do not specify a partition, the <code>default</code> partition is searched for the SOA composite application. However, no other partitions are searched.

9.3.4.3 Example

The following example retires revision 1.0 of the `HelloWorld` application.

```
wls:/mydomain/ServerConfig> sca_retireComposite("myhost", "7001", "weblogic",
"welcome1", "HelloWorld", "1.0")
```

The following example retires revision 1.0 of the `HelloWorld` application in the partition `myPartition`.

```
wls:/mydomain/ServerConfig> sca_retireComposite("stadp10", "7001", "weblogic",
"weblogic", "HelloWorld", "1.0", partition="myPartition")
```

9.3.5 sca_assignDefaultComposite

Command Category: Application Management Commands

Use with WLST: Offline

9.3.5.1 Description

Sets a SOA composite application revision as the default version. This revision is instantiated when a new request comes in.

9.3.5.2 Syntax

```
sca_assignDefaultComposite(host, port, user, password, compositeName, revision,
[partition])
```

Argument	Definition
<i>host</i>	Hostname of the Oracle WebLogic Server (for example, <code>myhost</code>).
<i>port</i>	Port of the Oracle WebLogic Server (for example, <code>7001</code>).
<i>user</i>	User name for connecting to the running server to get MBean information (for example, <code>weblogic</code>).
<i>password</i>	Password for the user name.
<i>compositeName</i>	Name of the SOA composite application.
<i>revision</i>	Revision of the SOA composite application.

Argument	Definition
<i>partition</i>	Optional. The name of the partition in which the SOA composite application is located. The default value is <code>default</code> . If you do not specify a partition, the <code>default</code> partition is searched for the SOA composite application. However, no other partitions are searched.

9.3.5.3 Example

The following example sets revision 1.0 of the HelloWorld application as the default version.

```
wls:/mydomain/ServerConfig> sca_assignDefaultComposite("myhost", "7001",
"weblogic", "welcome1", "HelloWorld", "1.0")
```

The following example sets revision 1.0 of the HelloWorld application located in the partition `myPartition` as the default version.

```
wls:/mydomain/ServerConfig> sca_assignDefaultComposite("stadp10", "7001",
"weblogic", "weblogic", "HelloWorld", "1.0", partition="myPartition")
```

9.3.6 sca_getDefaultCompositeRevision

Command Category: Application Management Commands

Use with WLST: Offline

9.3.6.1 Description

Lists the revision of the default composite of the given composite series.

9.3.6.2 Syntax

```
sca_getDefaultCompositeRevision(host, port, user, password, compositeName,
partition)
```

Argument	Definition
<i>host</i>	Hostname of the Oracle WebLogic Server (for example, <code>myhost</code>).
<i>port</i>	Port of the Oracle WebLogic Server (for example, <code>7001</code>).
<i>user</i>	User name for connecting to the running server to get MBean information (for example, <code>weblogic</code>).
<i>password</i>	Password for the user name.
<i>compositeName</i>	Name of the SOA composite application.
<i>partition</i>	Optional. The name of the partition in which the SOA composite application is located. The default value is <code>default</code> . If you do not specify a partition, the default partition is searched for the SOA composite application. However, no other partitions are searched.

9.3.6.3 Example

The following example returns the revision of the default composite of the given composite series.

```
wls:/mydomain/ServerConfig> sca_getDefaultCompositeRevision("myhost", "7001",
"weblogic", "weblogic", "HelloWorld")
```

The following example returns the revision of the default composite of the given composite series in the partition named `myPartition`.

```
wls:/mydomain/ServerConfig> sca_getDefaultCompositeRevision("myhost", "7001",
"weblogic", "weblogic", "HelloWorld", partition="myPartition")
```

9.3.7 sca_listDeployedComposites

Command Category: Application Management Commands

Use with WLST: Offline

9.3.7.1 Description

Lists all SOA composite applications deployed to the SOA platform.

9.3.7.2 Syntax

```
sca_listDeployedComposites(host, port, user, password)
```

Argument	Definition
<i>host</i>	Hostname of the Oracle WebLogic Server (for example, myhost).
<i>port</i>	Port of the Oracle WebLogic Server (for example, 7001).
<i>user</i>	User name for connecting to the running server to get MBean information (for example, weblogic).
<i>password</i>	Password for the user name.

9.3.7.3 Example

The following example lists all the deployed SOA composite applications on the server myhost.

```
wls:/mydomain/ServerConfig> sca_listDeployedComposites('myhost', '7001',
'weblogic', 'welcome1')
```

9.3.8 sca_listCompositesFailedInServerStart

Command Category: Application Management Commands

Use with WLST: Offline

9.3.8.1 Description

List the SOA composite applications that failed during server startup.

9.3.8.2 Syntax

```
sca_listCompositesFailedInServerStart (host, port, user, password)
```

Argument	Definition
<i>host</i>	Hostname of the Oracle WebLogic Server (for example, myhost).
<i>port</i>	Port of the SOA server (for example, 7001).
<i>user</i>	User name for connecting to the running server to get MBean information (for example, weblogic).
<i>password</i>	Password for the user name.

9.3.8.3 Example

The following example lists the SOA composite applications that failed during server startup.

```
wls:/mydomain/ServerConfig> sca_listCompositesFailedInServerStart('myhost'
'7001','weblogic', 'welcome1')
```

If a SOA composite application failed, output is displayed in the following format:

```
Following 1 composites failed in SOA server start process:
1. BPELInvokesHello[1.0], partition=default, mode=active, state=on,
isDefault=true, deployedTime=2012-09-28T00:48:13.182-07:00
```

9.4 SOA Composite Application Compilation Commands

Use the compilation commands, listed in [Table 9-4](#), to compile SOA composite applications.

Table 9-4 SOA Composite Application Compilation Commands for WLST Configuration

Use this command...	To...	Use with WLST...
sca_setProp	Set JVM system properties.	Offline
sca_compile	Compile a SOA composite application.	Offline

9.4.1 sca_setProp

Command Category: Application Compilation Commands

Use with WLST: Offline

9.4.1.1 Description

Sets JVM system properties. This command can also set secure socket layer (SSL) system properties before using `sca_deployComposite` and `sca_undeployComposite` over SSL.

9.4.1.2 Syntax

```
sca_setProp(propName, propValue)
```

Argument	Definition
<i>propName</i>	Property name.
<i>propValue</i>	Property value.

9.4.1.3 Example

The following example sets the property name and property value.

```
wls:/mydomain/ServerConfig> sca_setProp("oracle.home",
"/scratch/myusername/beahome/AS11gR1SOA")
```

9.4.2 sca_compile

Command Category: Application Compilation Commands

Use with WLST: Offline

9.4.2.1 Description

Compiles a SOA composite application.

Note: The `sca_compile` command requires the `oracle.home` property to find the `ant-sca-compile.xml` script. This must be set once. You can use the `scac_setProp` command or the `oracleHome` property to set a value.

9.4.2.2 Syntax

```
sca_compile(composite, [outXml], [error], [appHome], [displayLevel], [oracleHome])
```

Argument	Definition
<code>composite</code>	Absolute path of a composite file in the expanded (unzipped) SAR directory.
<code>outXml</code>	Optional. Absolute path of an output XML file.
<code>error</code>	Optional. Absolute path of an error file.
<code>appHome</code>	Optional. Absolute path of the application home directory. This property is required if you have shared data.
<code>displayLevel</code>	Optional. The level of information to display. The default value is 1.
<code>oracleHome</code>	Optional. The <code>oracle.home</code> property.

9.4.2.3 Examples

The following example compiles the `FirstComposite` application.

```
wls:/mydomain/ServerConfig> sca_compile("/tmp/FirstComposite_
rev1.0/composite.xml", displayLevel=2)
```

The following example compiles the `FirstComposite` application and captures details in the `myout.xml` file. The `error.out` file captures any errors.

```
wls:/mydomain/ServerConfig> sca_compile("/tmp/FirstComposite_
rev1.0/composite.xml", outXml="/tmp/myout.xml", error="error.out")
```

The following example compiles the `FirstComposite` application. The `oracleHome` property is set to find the `ant-sca-compile.xml` script.

```
wls:/mydomain/ServerConfig> sca_compile("/tmp/FirstComposite_
rev1.0/composite.xml", displayLevel=2,
oracleHome="/scratch/myusername/beahome/AS11gR1SOA")
```

9.5 SOA Composite Application Packaging Commands

Use the packaging command, listed in [Table 9-5](#), to package SOA composite applications into a composite SAR file.

Table 9-5 SOA Composite Application Packaging Command for WLST Configuration

Use this command...	To...	Use with WLST...
sca_package	Package the SOA composite application files into a composite SAR file.	Offline

9.5.1 sca_package

Command Category: Application Packaging Commands

Use with WLST: Offline

9.5.1.1 Description

Packages the SOA composite application files into a composite SAR file. This command performs the following operations:

- Calls `sca_compile` to compile the composite artifacts in `${compositeDir}`.
- Calls `javac` to compile any source code under `${compositeDir}/src`.
- Replaces the revision in `${compositeDir}/composite.xml`.
- Packages the artifacts to create `sca_${compositeName}_rev${revision}.jar` in `${compositeDir}/deploy`.

Note: The `sca_package` command requires `oracle.home` to find the `ant-sca-package.xml` script. This must be set once. You can use the `scac_setProp` command or `oracleHome` property to set this property.

9.5.1.2 Syntax

```
sca_package(compositeDir, compositeName, revision, [appHome], [oracleHome])
```

Argument	Definition
<code>compositeDir</code>	Absolute path of a directory that contains composite artifacts.
<code>compositeName</code>	Name of the composite.
<code>revision</code>	Revision ID of the composite.
<code>appHome</code>	Optional. Absolute path of the application home directory. This property is required if you have shared data.
<code>oracleHome</code>	Optional. The <code>oracle.home</code> property.

9.5.1.3 Examples

The following example packages the `OrderBookingComposite` application. The `appHome` property is set because this application uses shared data.

```
wls:/mydomain/ServerConfig> sca_package("/tmp/app_data/OrderBookingComposite",
"OrderBookingComposite", "1.0", appHome="/tmp/app_data")
```

The following example packages the `HelloSOAComposite` application.

```
wls:/mydomain/ServerConfig> sca_package
("/tmp/HelloSOAApplication/HelloSOAComposite", "HelloSOAComposite", "1.0")
```

The following example packages the `HelloSOAComposite` application. The `oracleHome` property is set to find the `ant-sca-compile.xml` script.

```
wls:/mydomain/ServerConfig> sca_package
("/tmp/HelloSOAApplication/HelloSOAComposite", "HelloSOAComposite", "1.0",
oracleHome="/scratch/myusername/beahome/AS11gR1SOA")
```

9.6 SOA Composite Application Test Commands

Use the SOA composite application test command, listed in [Table 9–6](#), to test a SOA composite applications.

Table 9–6 SOA Composite Application Test Command for WLST Configuration

Use this command...	To...	Use with WLST...
<code>sca_test</code>	Test deployed SOA composite applications.	Offline

9.6.1 `sca_test`

Command Category: Application Test Commands

Use with WLST: Offline

9.6.1.1 Description

Tests deployed SOA composite applications prior to deployment in a production environment. You create suites of tests in Oracle JDeveloper. The `sca_test` command calls `ant-sca-test.xml`.

9.6.1.2 Syntax

```
sca_test('compositeName', 'revision', 'testsuiteName', 'jndiPropFile',
[oracleHome='oracleHome'], [javaHome='javaHome'])
```

Argument	Definition
<code>compositeName</code>	Name of the SOA composite application.
<code>revision</code>	Revision ID of the SOA composite application.
<code>testsuiteName</code>	Name of the test suite.
<code>jndiPropFile</code>	Absolute path to the JNDI property file.
<code>oracleHome</code>	Optional. The <code>oracle.home</code> system property.
<code>javaHome</code>	Optional. The <code>java.passed.home</code> system property.

9.6.1.3 Examples

The following example runs the `OrderBookingMainTestsuite` test suite.

```
wls:/mydomain/ServerConfig> sca_test('OrderBookingComposite', '1.0',
'OrderBookingMainTestsuite', '/tmp/tmp-jndi.properties',
oracleHome='/scratch/<user>/beahome/AS11gR1SOA/',
javaHome='/scratch/<user>/beahome/jdk160_05')
```

9.7 SOA Composite Application HTTP Client-Based Export and Import Commands

Use the SOA composite application commands, listed in [Table 9–7](#), to export and import SOA composite applications based on the HTTP client. The SOA Infrastructure must be running to use these commands.

Table 9–7 SOA Composite Application Export and Import Commands for WLST Configuration

Use this command...	To...	Use with WLST...
sca_exportComposite	Export a SOA composite application into a SAR file.	Offline
sca_exportUpdates	Export postdeployment changes of a SOA composite application into a JAR file.	Offline
sca_importUpdates	Import postdeployment changes of a SOA composite application.	Offline
sca_exportSharedData	Export shared data of a given pattern into a JAR file.	Offline
sca_removeSharedData	Removes a top-level shared data folder.	Offline

9.7.1 sca_exportComposite

Command Category: Application Export and Import Commands

Use with WLST: Offline

9.7.1.1 Description

Exports a SOA composite application into a SAR file.

9.7.1.2 Syntax

```
sca_exportComposite(serverURL, updateType, sarFile, compositeName, revision,
[user], [password], [partition])
```

Argument	Definition
<i>serverURL</i>	URL of the server that hosts the SOA Infrastructure application (for example, <code>http://stabc:8001</code>).
<i>updateType</i>	Type of postdeployment changes to be exported: <ul style="list-style-type: none"> ▪ <code>all</code>: Includes all postdeployment changes. ▪ <code>property</code>: Includes only property postdeployment changes (binding component properties, composite properties such as audit level settings and payload validation status, and policy attachments). ▪ <code>runtime</code>: Includes only runtime (rules dictionary and domain value maps (DVMs)) and metadata postdeployment changes. ▪ <code>none</code>: Exports the original composite without any postdeployment changes (including property changes and runtime changes).
<i>sarFile</i>	Absolute path of a SAR file to generate (a <code>.jar</code> file that begins with <code>sca_</code>).
<i>compositeName</i>	Name of the composite to export.
<i>revision</i>	Revision of the composite to export.
<i>user</i>	Optional. The user name for accessing the server when basic configuration is configured. Use the following syntax for this argument: <pre>user='username'</pre>

Argument	Definition
<i>password</i>	Optional. The password for accessing the server when basic configuration is configured. Use the following syntax for this argument: <code>password= '<i>password</i>'</code>
<i>partition</i>	Optional. The name of the partition in which the SOA composite application is located. The default value is <code>default</code> .

9.7.1.3 Examples

The following example exports the composite without including any postdeployment changes.

```
wls:/offline/mydomain/ServerConfig> sca_exportComposite('http://stabc:8001',
'none', '/tmp/sca_HelloWorld_rev1.0.jar', 'HelloWorld', '1.0')
```

The following example exports a composite with all postdeployment updates.

```
wls:/offline/mydomain/ServerConfig> sca_exportComposite('http://stabc:8001',
'all', '/tmp/sca_HelloWorld_rev1.0-all.jar', 'HelloWorld', '1.0')
```

The following example exports a composite with property postdeployment updates.

```
wls:/offline/mydomain/ServerConfig> sca_exportComposite('http://stabc:8001',
'property', '/tmp/sca_HelloWorld_rev1.0-prop.jar', 'HelloWorld', '1.0')
```

The following example exports a composite with runtime/metadata postdeployment updates.

```
wls:/offline/mydomain/ServerConfig> sca_exportComposite('http://stabc:8001',
'runtime', '/tmp/sca_HelloWorld_rev1.0-runtime.jar', 'HelloWorld', '1.0')
```

The following example exports a composite in the `myPartition` partition without including any postdeployment updates:

```
wls:/offline/mydomain/ServerConfig> sca_exportComposite('http://stabc:8001',
'none', '/tmp/sca_HelloWorld_rev1.0.jar', 'HelloWorld', '1.0',
partition='myPartition')
```

9.7.2 sca_exportUpdates

Command Category: Application Export and Import Commands

Use with WLST: Offline

9.7.2.1 Description

Exports postdeployment changes of a SOA composite application into a JAR file.

9.7.2.2 Syntax

```
sca_exportUpdates(serverURL, updateType, jarFile, compositeName, revision,
[user], [password], [partition])
```

Argument	Definition
<i>serverURL</i>	URL of the server that hosts the SOA Infrastructure application (for example, <code>http://stabc:8001</code>).

Argument	Definition
<i>updateType</i>	The type of postdeployment changes to be exported. <ul style="list-style-type: none"> ■ <i>all</i>: Includes all postdeployment changes. ■ <i>property</i>: Includes only property postdeployment changes (binding component properties, composite properties such as audit level settings and payload validation status, and policy attachments). ■ <i>runtime</i>: Includes only runtime (rules dictionary and domain value maps (DVMs)) and metadata postdeployment changes.
<i>jarFile</i>	Absolute path of a JAR file to generate. <code>sca_exportUpdates()</code> creates a regular <code>.jar</code> file that cannot be imported using regular deployment commands. It must be imported by using <code>sca_importUpdates()</code> .
<i>compositeName</i>	Name of the composite to export.
<i>revision</i>	Revision of the composite to export.
<i>user</i>	Optional. The user name for accessing the server when basic configuration is configured. Use the following syntax for this argument: <code>user='username'</code>
<i>password</i>	Optional. The password for accessing the server when basic configuration is configured. Use the following syntax for this argument: <code>password='password'</code>
<i>partition</i>	Optional. The name of the partition in which the SOA composite application is located. The default value is <code>default</code> .

9.7.2.3 Examples

The following example exports all postdeployment updates.

```
wls:/offline/mydomain/ServerConfig> sca_exportUpdates('http://stabc:8001', 'all',
'/tmp/all-HelloWorld_rev1.0.jar', 'HelloWorld', '1.0')
```

The following example exports property postdeployment updates.

```
wls:/offline/mydomain/ServerConfig> sca_exportUpdates('http://stabc:8001',
'property', '/tmp/prop-HelloWorld_rev1.0.jar', 'HelloWorld', '1.0')
```

The following example exports runtime/metadata postdeployment updates.

```
wls:/offline/mydomain/ServerConfig> sca_exportUpdates('http://stabc:8001',
'runtime', '/tmp/runtime-HelloWorld_rev1.0.jar', 'HelloWorld', '1.0')
```

The following example exports postdeployment changes of a composite in the partition `myPartition` into a JAR file.

```
wls:/offline/mydomain/ServerConfig> sca_exportUpdates(serverURL, updateType,
jarFile, compositeName, revision, user=None, password=None,
partition='myPartition')
```

9.7.3 sca_importUpdates

Command Category: Application Export and Import Commands

Use with WLST: Offline

9.7.3.1 Description

Imports postdeployment changes of a SOA composite application.

9.7.3.2 Syntax

```
sca_importUpdates(serverURL, jarFile, compositeName, revision, [user],
[password])
```

Argument	Definition
<i>serverURL</i>	URL of the server that hosts the SOA Infrastructure application (for example, <code>http://stabc:8001</code>).
<i>jarFile</i>	Absolute path of a JAR file that contains postdeployment changes.
<i>compositeName</i>	Name of the composite to which the postdeployment changes are imported.
<i>revision</i>	Revision of the composite to which the postdeployment changes are imported.
<i>user</i>	Optional. The user name for accessing the server when basic configuration is configured. Use the following syntax for this argument: <code>user='username'</code>
<i>password</i>	Optional. The password for accessing the server when basic configuration is configured. Use the following syntax for this argument: <code>password='password'</code>
<i>partition</i>	Optional. The name of the partition in which the SOA composite application is located. The default value is <code>default</code> .

9.7.3.3 Examples

The following example imports postdeployment changes of a SOA composite application.

```
wls:/offline/mydomain/ServerConfig> sca_importUpdates('http://stabc:8001',
'/tmp/all-HelloWorld_rev1.0.jar', 'HelloWorld', '1.0')
```

The following example imports postdeployment changes of a composite in the partition `myPartition`.

```
wls:/offline/mydomain/ServerConfig> sca_importUpdates(serverURL, jarFile,
compositeName, revision, user=None, password=None, partition='myPartition')
```

9.7.4 sca_exportSharedData

Command Category: Application Export and Import Commands

Use with WLST: Offline

9.7.4.1 Description

Exports shared data of a given pattern into a JAR file.

9.7.4.2 Syntax

```
sca_exportSharedData(serverURL, jarFile, pattern, [user], [password])
```

Argument	Definition
<i>serverURL</i>	URL of the server that hosts the SOA Infrastructure application (for example, <code>http://stabc:8001</code>).
<i>jarFile</i>	Absolute path of a JAR file to generate.
<i>pattern</i>	The file pattern supported by MDS transfer APIs. Use the semicolon delimiter (;) if more than one pattern is specified. Exclude the shared data namespace <code>/apps</code> in the pattern. For example: <code>/Project1/**;/Project2/**</code> This example exports all documents under <code>/apps/Project1</code> and <code>/apps/Project2</code> .
<i>user</i>	Optional. The user name for accessing the server when basic configuration is configured. Use the following syntax for this argument: <code>user='username'</code>
<i>password</i>	Optional. The password for accessing the server when basic configuration is configured. Use the following syntax for this argument: <code>password='password'</code>

9.7.4.3 Examples

The following example exports shared data of a given pattern into a JAR file.

```
wls:/offline/mydomain/ServerConfig> sca_exportSharedData('http://stabc:8001',
'/tmp/MySharedData.jar', '/Project1/**')
```

9.7.5 sca_removeSharedData

Command Category: Application Export and Import Commands

Use with WLST: Offline

9.7.5.1 Description

Removes a top-level shared data folder, even if there are composites deployed in the service engine.

9.7.5.2 Syntax

```
sca_removeSharedData(serverURL, folderName, [user], [password])
```

Argument	Definition
<i>serverURL</i>	URL of the server that hosts the SOA Infrastructure application (for example, <code>http://stabc:8001</code>).
<i>folderName</i>	The name of a top-level shared data folder to be removed.
<i>user</i>	Optional. The user name for accessing the server when basic configuration is configured. Use the following syntax for this argument: <code>user='username'</code>
<i>password</i>	Optional. The password for accessing the server when basic configuration is configured. Use the following syntax for this argument: <code>password='password'</code>

9.7.5.3 Examples

The following example removes the top-level shared data `Project1` folder.

```
sca_removeSharedData('http://stabc:8001', 'Project1')
```

9.8 SOA Composite Application MBean-Based Export and Import Commands

Use the deployment commands, listed in [Table 9–8](#), to export and import SOA composite applications on the server-based composite store MBean (`CompositeStoreMBean`).

Table 9–8 SOA Composite Application Export and Import Commands for WLST Configuration

Use this command...	To...	Use with WLST...
sca_exportCompositeMb	Export a SOA composite application into a SAR file.	Online
sca_exportUpdatesMb	Export postdeployment changes of a SOA composite application into a JAR file.	Online
sca_importUpdatesMb	Import postdeployment changes of a SOA composite application.	Online
sca_exportSharedDataMb	Export shared data of a given pattern into a JAR file.	Online

If you use this option, note that the file generated in the export commands and the file read in the import command must be on the host where the server is running (either an Oracle WebLogic Administration Server or a managed SOA server).

The composite store MBean is registered as both a server runtime MBean of the SOA server and as a domain runtime MBean of the Oracle WebLogic Administration Server, which allows the import and export to continue working while SOA servers are down. Only WLST commands are provided for using the composite store MBean; there are no `ant` commands.

You must run the `connect()` command to connect to either a SOA server or an Oracle WebLogic Administration Server.

```
wls:offline>connect('weblogic', 'password', 't3://stabc:8001')
```

If you use the domain runtime MBean while the SOA servers are down, you must run the `domainRuntime()` command.

```
wls:offline>connect('weblogic', 'password', 't3://stabc:7001')
wls:/soainfra/serverConfig>domainRuntime()
```

9.8.1 sca_exportCompositeMb

Command Category: Application Export and Import Commands

Use with WLST: Online

9.8.1.1 Description

Exports a SOA composite application into a SAR file.

9.8.1.2 Syntax

```
sca_exportCompositeMb(updateType, sarFile, compositeName, revision)
```

Argument	Definition
<i>updateType</i>	Type of postdeployment changes to be exported: <ul style="list-style-type: none"> ▪ all: All postdeployment changes are included. ▪ property: Property changes are included (binding component properties, composite properties such as audit level settings and payload validation status, and policy attachments). ▪ runtime: Postdeployment runtime changes are included (rules dictionary and domain value maps (DVMs)).
<i>sarFile</i>	Absolute path of a SAR file to generate.
<i>compositeName</i>	Name of the composite to export.
<i>revision</i>	Revision of the composite to export.

9.8.1.3 Examples

This example exports composite without including any postdeployment changes.

```
wls:/mydomain/ServerConfig> sca_exportCompositeMb('none', '/tmp/sca_HelloWorld_rev1.0.jar', 'HelloWorld', '1.0')
```

This example exports a composite with all postdeployment updates.

```
wls:/mydomain/ServerConfig> sca_exportCompositeMb('all', '/tmp/sca_HelloWorld_rev1.0-all.jar', 'HelloWorld', '1.0')
```

This example exports a composite with property postdeployment updates.

```
wls:/mydomain/ServerConfig> sca_exportCompositeMb('property', '/tmp/sca_HelloWorld_rev1.0-prop.jar', 'HelloWorld', '1.0')
```

This example exports a composite with runtime/metadata postdeployment updates.

```
wls:/mydomain/ServerConfig> sca_exportCompositeMb('runtime', '/tmp/sca_HelloWorld_rev1.0-runtime.jar', 'HelloWorld', '1.0')
```

9.8.2 sca_exportUpdatesMb

Command Category: Application Export and Import Commands

Use with WLST: Online

9.8.2.1 Description

Exports postdeployment changes of a SOA composite application into a JAR file.

9.8.2.2 Syntax

```
sca_exportUpdatesMb(updateType, jarFile, compositeName, revision)
```

Argument	Definition
<i>updateType</i>	Type of postdeployment changes to be exported: all , property , or runtime .
<i>jarFile</i>	Absolute path of a JAR file to generate.
<i>compositeName</i>	Name of the composite to export.

Argument	Definition
<i>revision</i>	Revision of the composite to export.

9.8.2.3 Examples

The following example exports all postdeployment updates.

```
wls:/mydomain/ServerConfig> sca_exportUpdatesMb('all',
'/tmp/all-HelloWorld_rev1.0.jar', 'HelloWorld', '1.0')
```

The following example exports property postdeployment updates.

```
wls:/mydomain/ServerConfig> sca_exportUpdatesMB('property',
'/tmp/prop-HelloWorld_rev1.0.jar', 'HelloWorld', '1.0')
```

The following example exports runtime/metadata postdeployment updates.

```
wls:/mydomain/ServerConfig> sca_exportUpdatesMB('runtime',
'/tmp/runtime-HelloWorld_rev1.0.jar', 'HelloWorld', '1.0')
```

9.8.3 sca_importUpdatesMb

Command Category: Application Export and Import Commands

Use with WLST: Online

9.8.3.1 Description

Imports postdeployment changes of a SOA composite application.

9.8.3.2 Syntax

```
sca_importUpdatesMb(jarFile, compositeName, revision)
```

Argument	Definition
<i>jarFile</i>	Absolute path of a JAR file that contains postdeployment changes.
<i>compositeName</i>	Name of the composite to which the postdeployment changes are imported.
<i>revision</i>	Revision of the composite to which the postdeployment changes are imported.

9.8.3.3 Examples

The following example imports postdeployment changes of a SOA composite application.

```
wls:/mydomain/ServerConfig> sca_importUpdatesMb('/tmp/all-HelloWorld_rev1.0.jar',
'HelloWorld', '1.0')
```

9.8.4 sca_exportSharedDataMb

Command Category: Application Export and Import Commands

Use with WLST: Online

9.8.4.1 Description

Exports shared data of a given pattern into a JAR file.

9.8.4.2 Syntax

```
sca_exportSharedDataMb(jarFile, pattern)
```

Argument	Definition
<i>jarFile</i>	Absolute path of a JAR file to generate.
<i>pattern</i>	The file pattern supported by MDS transfer APIs. Use the semicolon delimiter (;) if more than one pattern is specified. Exclude the shared data namespace /apps in the pattern. For example: /Project1/**;/Project2/** This example exports all documents under /apps/Project1 and /apps/Project2.

9.8.4.3 Examples

This example exports shared data of given pattern into a JAR file.

```
wls:/mydomain/ServerConfig> sca_exportSharedDataMb('/tmp/MySharedData.jar',
'/Project1/**')
```

9.9 SOA Composite Application Partition Management Commands

Use the deployment commands, listed in [Table 9–9](#), to manage partitions. Partitioning enable you to logically group different revisions of your SOA composite applications into separate sections. This is similar to the concept of domains in the 10.1.x releases of Oracle BPEL Process Manager.

Table 9–9 SOA Composite Application Partition Management Commands for WLST Configuration

Use this command...	To...	Use with WLST...
sca_createPartition	Create a partition.	Online
sca_deletePartition	Undeploy all SOA composite applications in a partition before deleting the partition.	Online
sca_startCompositesInPartition	Start all SOA composite applications in a partition.	Online
sca_stopCompositesInPartition	Stop all SOA composite applications in a partition.	Online
sca_activateCompositesInPartition	Activate all SOA composite applications in a partition.	Online
sca_retireCompositesInPartition	Retire all SOA composite applications in a partition.	Online
sca_listPartitions	List all partitions in the SOA Infrastructure.	Online
sca_listCompositesInPartition	List all composites in a specific partition.	Online

9.9.1 sca_createPartition

Command Category: Application Partition Management Commands

Use with WLST: Online

9.9.1.1 Description

Creates a partition.

9.9.1.2 Syntax

```
sca_createPartition(partitionName)
```

Argument	Definition
<i>partitionName</i>	The name of the partition.

9.9.1.3 Examples

This example creates a partition named myPartition.

```
wls:/mydomain/ServerConfig> sca_createPartition('myPartition')
```

9.9.2 sca_deletePartition

Command Category: Application Partition Management Commands

Use with WLST: Online

9.9.2.1 Description

Undeploys all composites in a partition before deleting the partition.

9.9.2.2 Syntax

```
sca_deletePartition(partitionName)
```

Argument	Definition
<i>partitionName</i>	The name of the partition.

9.9.2.3 Examples

This example undeploys all composites in the myPartition partition before deleting the partition.

```
wls:/mydomain/ServerConfig> sca_deletePartition('myPartition')
```

9.9.3 sca_startCompositesInPartition

Command Category: Application Partition Management Commands

Use with WLST: Online

9.9.3.1 Description

Starts all composites in a partition.

9.9.3.2 Syntax

```
sca_startCompositesInPartition(partitionName)
```

Argument	Definition
<i>partitionName</i>	The name of the partition.

9.9.3.3 Examples

This example starts all composites in the myPartition partition.

```
wls:/mydomain/ServerConfig> sca_startCompositesInPartition('myPartition')
```

9.9.4 sca_stopCompositesInPartition

Command Category: Application Partition Management Commands

Use with WLST: Online

9.9.4.1 Description

Stops all composites in a partition.

9.9.4.2 Syntax

```
sca_stopCompositesInPartition(partitionName)
```

Argument	Definition
<i>partitionName</i>	The name of the partition.

9.9.4.3 Examples

This example stops all composites in the myPartition partition.

```
wls:/mydomain/ServerConfig> sca_stopCompositesInPartition('myPartition')
```

9.9.5 sca_activateCompositesInPartition

Command Category: Application Partition Management Commands

Use with WLST: Online

9.9.5.1 Description

Activates all composites in a partition.

9.9.5.2 Syntax

```
sca_activateCompositesInPartition(partitionName)
```

Argument	Definition
<i>partitionName</i>	The name of the partition.

9.9.5.3 Examples

This example activates all composites in the myPartition partition.

```
wls:/mydomain/ServerConfig> sca_activateCompositesInPartition('myPartition')
```

9.9.6 sca_retireCompositesInPartition

Command Category: Application Partition Management Commands

Use with WLST: Online

9.9.6.1 Description

Retires all composites in a partition.

9.9.6.2 Syntax

```
sca_retireCompositesInPartition(partitionName)
```

Argument	Definition
<i>partitionName</i>	The name of the partition.

9.9.6.3 Examples

This example retires all composites in the myPartition partition.

```
wls:/mydomain/ServerConfig> sca_retireCompositesInPartition('myPartition')
```

9.9.7 sca_listPartitions

Command Category: Application Partition Management Commands

Use with WLST: Online

9.9.7.1 Description

Lists all partitions in the SOA Infrastructure.

9.9.7.2 Syntax

```
sca_listPartitions()
```

9.9.7.3 Examples

This example lists all partitions in the SOA Infrastructure.

```
wls:/mydomain/ServerConfig> sca_listPartitions()
```

9.9.8 sca_listCompositesInPartition

Command Category: Application Partition Management Commands

Use with WLST: Online

9.9.8.1 Description

Lists all composites in a partition.

9.9.8.2 Syntax

```
sca_listCompositesInPartition(partitionName)
```

Argument	Definition
<i>partitionName</i>	The name of the partition.

9.9.8.3 Examples

This example lists all composites in the myPartition partition.

```
sca_listCompositesInPartition(myPartition)
```

9.10 SOA Composite Application Preconfigured WLDF Watches Command

Use the diagnostic command, listed in [Table 9–10](#), to enable preconfigured WebLogic Diagnostic Framework (WLDF) watches for deployment, memory, and elapsed time of web service calls. You use WLDF watches and notifications to collect diagnostic data to identify problems. This data enables you to isolate and diagnose faults when they occur.

Table 9–10 SOA Composite Application Preconfigured WLDF Watches Command for WLST Configuration

Use this command...	To...	Use with WLST...
sca_createWatches	Enable preconfigured WLDF watches.	Online

9.10.1 sca_createWatches

Command Category: Application Diagnostic Command

Use with WLST: Online

9.10.1.1 Description

Enable preconfigured WLDF watches for deployment, memory, and elapsed time of web service calls.

9.10.1.2 Syntax

```
sca_createWatches()
```

Note: There are no arguments to specify with this command.

9.10.1.3 Examples

This example enables the preconfigured WLDF watches for deployment, memory, and elapsed time of web service calls.

```
sca_createWatches()
```

9.11 Configuration Plan Management Commands

Use the configuration plan management commands, listed in [Table 9–11](#), to attach, extract, generate, and validate configuration plans for SOA composite applications.

Table 9–11 Configuration Plan Management Commands for WLST Configuration

Use this command...	To...	Use with WLST...
sca_attachPlan	Attach the configuration plan file to the SOA composite application JAR file.	Offline
sca_extractPlan	Extract a configuration plan packaged with the JAR file for editing.	Offline
sca_generatePlan	Generate a configuration plan for editing.	Offline
sca_validatePlan	Validate the configuration plan.	Offline

9.11.1 sca_attachPlan

Command Category: Configuration Plan Management Commands

Use with WLST: Offline

9.11.1.1 Description

Attaches the configuration plan file to the SOA composite application file. If a plan already exists in the file, it is overwritten with this new plan.

9.11.1.2 Syntax

```
sca_attachPlan(sar, configPlan, [overwrite], [verbose])
```

Argument	Definition
<i>sar</i>	Absolute path of the SAR file.
<i>configPlan</i>	Absolute path of the configuration plan file.
<i>overwrite</i>	Optional. Indicates whether to overwrite an existing configuration plan in the SAR file. <ul style="list-style-type: none"> ▪ <code>false</code> (default): Does not overwrite the plan. ▪ <code>true</code>: Overwrites the plan.
<i>verbose</i>	Optional. Indicates whether to print more information about the configuration plan attachment. <ul style="list-style-type: none"> ▪ <code>true</code> (default): Prints more information. ▪ <code>false</code>: Does not print more information.

9.11.1.3 Examples

The following example attaches the `configplan.xml` configuration plan file to the HelloWorld application.

```
wls:/mydomain/ServerConfig> sca_attachPlan("/tmp/sca_HelloWorld_rev1.0.jar",
"/tmp/configplan.xml")
```

The following example overwrites the existing configuration plan with `configplan.xml` file in the HelloWorld application.

```
wls:/mydomain/ServerConfig> sca_attachPlan("/tmp/sca_HelloWorld_rev1.0.jar",
"/tmp/configplan.xml", overwrite=true)
```

9.11.2 sca_extractPlan

Command Category: Configuration Plan Management Commands

Use with WLST: Offline

9.11.2.1 Description

Extracts a configuration plan packaged with the SOA composite application file for editing. This is an optional step. If no plan exists, this is the same as creating a new file with `sca_generatePlan`.

9.11.2.2 Syntax

```
sca_extractPlan(sar, configPlan, [overwrite], [verbose])
```

Argument	Definition
<i>sar</i>	Absolute path of a SAR file.
<i>configPlan</i>	Absolute path of a configuration plan file to which to be extracted.
<i>overwrite</i>	Optional. Indicates whether to overwrite an existing configuration plan file in the SAR file. <ul style="list-style-type: none"> ▪ <code>false</code> (default): Does not overwrite the plan. ▪ <code>true</code>: Overwrites the plan.
<i>verbose</i>	Optional. Indicates whether to print more information about configuration plan extraction. <ul style="list-style-type: none"> ▪ <code>true</code> (default): Prints more information. ▪ <code>false</code>: Does not print more information.

9.11.2.3 Example

The following example extracts the `configplan.xml` file for editing from the HelloWorld application.

```
wls:/mydomain/ServerConfig> sca_extractPlan("/tmp/sca_HelloWorld_rev1.0.jar",
"/tmp/configplan.xml")
```

The following example extracts the `configplan.xml` file for editing from the HelloWorld application. This command also overwrites the existing plan.

```
wls:/mydomain/ServerConfig> sca_extractPlan("/tmp/sca_HelloWorld_rev1.0.jar",
"/tmp/configplan.xml", overwrite=true)
```

9.11.3 sca_generatePlan

Command Category: Configuration Plan Management Commands

Use with WLST: Offline

9.11.3.1 Description

Generates a configuration plan for editing.

9.11.3.2 Syntax

```
sca_generatePlan(configPlan, sar, composite, [overwrite], [verbose])
```

Argument	Definition
<i>configPlan</i>	Absolute path of the configuration plan file to be generated.
<i>sar</i>	Absolute path of the SAR file.
<i>composite</i>	Absolute path of the <code>composite.xml</code> file in the expanded (unzipped) SAR directory.
<i>overwrite</i>	Optional. Indicates whether to overwrite an existing configuration plan file: <ul style="list-style-type: none"> ▪ <code>false</code> (default): Does not overwrite the plan. ▪ <code>true</code>: Overwrites the plan.
<i>verbose</i>	Indicates whether to print more information about plan generation: <ul style="list-style-type: none"> ▪ <code>true</code> (default): Prints more information. ▪ <code>false</code>: Does not print more information.

9.11.3.3 Examples

The following example generates the `myplan.xml` configuration plan file for the HelloWorld application.

```
wls:/mydomain/ServerConfig> sca_generatePlan("/tmp/myplan.xml",
sar="/tmp/sca_HelloWorld_rev1.0.jar")
```

The following example generates the `myplan2.xml` configuration plan file for the HelloWorld application. The `myplan2.xml` file overwrites the existing plan.

```
wls:/mydomain/ServerConfig> sca_generatePlan("/tmp/myplan2.xml",
composite="/tmp/HelloWorld_rev1.0/composite.xml", overwrite=true)
```

9.11.4 sca_validatePlan

Command Category: Configuration Plan Management Commands

Use with WLST: Offline

9.11.4.1 Description

Validates the configuration plan. This command identifies all search and replacement changes to be made during deployment. Use this option for debugging only.

9.11.4.2 Syntax

```
sca_validatePlan(reportFile, configPlan, [sar], [composite], [overwrite],
[verbose])
```

Argument	Definition
<i>reportFile</i>	Absolute path of the report file to be generated. Validation results are written to this file.
<i>configPlan</i>	Absolute path of the configuration plan file.
<i>sar</i>	Optional. The absolute path of the SAR file.
<i>composite</i>	Optional. The absolute path of the <code>composite.xml</code> file in the expanded (unzipped) SAR directory.
<i>overwrite</i>	Optional. Indicates whether to overwrite an existing configuration plan file: <ul style="list-style-type: none"> ▪ <code>false</code> (default): Does not overwrite the plan. ▪ <code>true</code>: Overwrites the plan.
<i>verbose</i>	Optional. Indicates whether to print more information about configuration plan validation. <ul style="list-style-type: none"> ▪ <code>true</code> (default): Prints more information. ▪ <code>false</code>: Does not print more information.

9.11.4.3 Examples

The following example validates the `configplan.xml` configuration plan file for the HelloWorld application.

```
wls:/mydomain/ServerConfig> sca_validatePlan("/tmp/myreport.xml",
"/tmp/configplan.xml", sar="/tmp/sca_HelloWorld_rev1.0.jar")
```

The following example validates the `configplan.xml` configuration plan file for the HelloWorld application. The `configplan.xml` plan overwrites the existing plan.

```
wls:/mydomain/ServerConfig> sca_validatePlan("/tmp/myreport.xml",
"/tmp/configplan.xml", composite="/tmp/HelloWorld_rev1.0/composite.xml",
overwrite=true)
```

9.12 Task Validation Commands

Use the task validation command, listed in [Table 9–12](#), to validate human workflow tasks.

Table 9–12 Task Validation Command for WLST Configuration

Use this command...	To...	Use with WLST...
sca_validateTask	Validate a human workflow task.	Offline

9.12.1 sca_validateTask

Command Category: Task Validation Commands

Use with WLST: Offline

9.12.1.1 Description

Validates a human workflow task contained in the `.task` file that you created when designing a human task in the Human Task Editor.

9.12.1.2 Syntax

```
sca_validateTask(taskFile, outXml, [displayLevel])
```

Argument	Definition
<i>taskFile</i>	Absolute path to the task definition file (<code>.task</code>).
<i>outXml</i>	Absolute path to an output XML file.
<i>displayLevel</i>	Optional. The level of information to display. The default value is 1.

9.12.1.3 Example

The following example validates the `WFTaskDefinition.task` file of the human task.

```
wls:/mydomain/ServerConfig> sca_validateTask("/tmp/WFTaskDefinition.task",
"/tmp/out.xml", displayLevel=2)
```

WebCenter Portal Custom WLST Commands

This chapter describes WebLogic Scripting Tool (WLST) commands for Oracle WebCenter Portal. These commands enable you to configure WebCenter Portal or Portal Framework applications and components from the command-line. For additional details about Oracle WebCenter Portal configuration, see *Oracle Fusion Middleware Administering Oracle WebCenter Portal*.

Notes: To use these commands, you must invoke WLST from the Oracle home in which the component has been installed. See "Using Custom WLST Commands" in the *Oracle Fusion Middleware Administrator's Guide*.

Most configuration changes made using these WLST commands are only effective after you restart the Managed Server on which WebCenter Portal or your own Portal Framework application is deployed. There are some exceptions, including WLST commands for [External Applications](#), [Portlet Producers](#), and [Lifecycle](#).

Oracle WebCenter Portal's custom WLST commands are described in the following sections:

- [Section 10.1, "Overview of Oracle WebCenter Portal WLST Command Categories"](#)
- [Section 10.2, "General"](#)
- [Section 10.3, "Analytics"](#)
- [Section 10.4, "Activity Graph"](#)
- [Section 10.5, "Activity Stream"](#)
- [Section 10.6, "Content Repository"](#)
- [Section 10.7, "Discussions and Announcements"](#)
- [Section 10.8, "External Applications"](#)
- [Section 10.9, "Instant Messaging and Presence"](#)
- [Section 10.10, "Mail"](#)
- [Section 10.11, "Notifications"](#)
- [Section 10.12, "People Connections"](#)
- [Section 10.13, "Personal Events"](#)
- [Section 10.14, "Personalization"](#)

- [Section 10.15, "Portlet Producers"](#)
- [Section 10.16, "Proxy Server"](#)
- [Section 10.17, "Search - Oracle SES Search"](#)
- [Section 10.18, "Search - Oracle SES Search Crawlers"](#)
- [Section 10.19, "Search - WebCenter Portal Search"](#)
- [Section 10.20, "Worklists"](#)
- [Section 10.21, "WebCenter Portal Application"](#)
- [Section 10.22, "Identity Store"](#)
- [Section 10.23, "Lifecycle"](#)
- [Section 10.24, "Upgrade"](#)

10.1 Overview of Oracle WebCenter Portal WLST Command Categories

Oracle WebCenter Portal's WLST commands are grouped into the several categories (Table 10–1).

Most configuration changes made using these WLST commands are only effective after you restart the Managed Server on which WebCenter Portal or your own Portal Framework application is deployed. The only exceptions are the [External Applications](#), [Portlet Producers](#), and [Lifecycle](#) WLST commands.

Table 10–1 WLST Command Categories

Command Category	Description
General	Manage connections for WebCenter Portal and Portal Framework applications.
Analytics	Manage analytics collector connections and configure the analytics collector (on <code>WC_Uutilities</code>).
Activity Graph	Manage activity graph metadata and provider configuration (on <code>WC_Uutilities</code>).
Activity Stream	Archive and restore activity stream data.
Content Repository	Manage content repository connections and configure document services.
Discussions and Announcements	Manage discussions server connections and configure discussions and announcements.
External Applications	Manage external application connections.
Instant Messaging and Presence	Manage instant messaging and presence server connections and configure instant messaging and presence.
Mail	Manage mail server connections and configure mail.
Notifications	Manage settings for notifications.
People Connections	Manage profile information.
Personal Events	Manage personal event server connections.
Personalization	Manage personalization server connections.
Portlet Producers	Manage portlet producers.
Proxy Server	Manage proxy settings for RSS and activity stream.

Table 10–1 (Cont.) WLST Command Categories

Command Category	Description
Search - Oracle SES Search	Manage Oracle Secure Enterprise Search (SES) connections and other search-related properties.
Search - Oracle SES Search Crawlers	Manage Oracle Secure Enterprise Search (SES) crawlers.
Search - WebCenter Portal Search	Manage search crawlers for the WebCenter Portal and Portal Framework applications.
Worklists	Manage BPEL server connections.
WebCenter Portal Application	Manage WebCenter Portal workflow settings and portal metadata.
Identity Store	Configure options while searching an application's identity store.
Lifecycle	Export and import application metadata, individual portals, portal templates, portal assets, and portlet producer metadata.
Upgrade	Upgrade from a previous Oracle WebCenter Portal release.

10.2 General

Use the General commands, listed in [Table 10–2](#), to manage connections, and perform other general tasks.

Configuration changes made using these WLST commands are only effective after restarting the Managed Server on which WebCenter Portal or your own Portal Framework application is deployed. For details, see *Oracle Fusion Middleware Administering Oracle WebCenter Portal*.

Table 10–2 General WLST Commands

Use This Command...	To...	Use with WLST...
deleteConnection	Delete any connection.	Online
getWebCenterConnectionTypes	List all connection types.	Online
setWebCenterServiceFrameworkConfig	Set WebCenter Portal Service Framework configuration properties.	Online
getWebCenterServiceFrameworkConfig	Return WebCenter Portal Framework configuration properties.	Online
webcenterErrorOccurred	Return status information for the last Oracle WebCenter Portal command executed.	Online

10.2.1 deleteConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.2.1.1 Description

Deletes a named connection currently configured for WebCenter Portal or your own Portal Framework application.

If you use `deleteConnection` to delete a WSRP or PDK-Java producer connection (instead of using `deregisterWSRPProducer` or `deregisterPDKJavaProducer`),

unused secondary connections will remain, which you might want to remove. For example, when you delete a WSRP producer connection, its associated web service connection remains and when you delete a PDK-Java producer connection, its associated URL connection remains.

Note: `deleteConnection` cannot be used to delete connections configured for personalization services. Instead, use [deleteWCPSCMISConnection](#), [deleteWCPSActivityGraphConnection](#), [deleteWCPSPeopleConnection](#), or [deleteWCPSCustomConnection](#).

10.2.1.2 Syntax

```
deleteConnection(appName, name, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Connection name.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.2.1.3 Example

The following example deletes a connection configured for WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig> deleteConnection(appName='webcenter',
name='MyConnection')
```

10.2.2 setWebCenterServiceFrameworkConfig

Module: Oracle WebCenter Portal

Use with WLST: Online

10.2.2.1 Description

Sets configuration properties for Oracle WebCenter Portal's services framework, such as the Resource Action Handler class and display as popup properties.

10.2.2.2 Syntax

```
setWebCenterServiceFrameworkConfig(appName, [resourceActionHandlerClassName,
resourceActionHandlerDisplayInPopup, server, applicationVersion])
```


Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>resourceActionHandlerClassName</i>	Optional. Class used by the Service Framework Resource Action Handler.
<i>resourceActionHandlerDisplayInPopup</i>	Optional. Indicates whether the Resource Action Handler displays resources in a popup or inline. Valid options are 1 (true) and 0 (false).
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.2.2.3 Example

The following example sets the WebCenter Portal Service Framework Resource Action Handler class to `my.company.ResourceActionHandler`:

```
wls:/wc_domain/domainRuntime>
setWebCenterServiceFrameworkConfig(appName='webcenter',
resourceActionHandlerClassName='my.company.ResourceActionHandler')
```

Successfully set the WebCenter Portal service framework configuration.
Resource Action Handler class: `my.company.ResourceActionHandler`
To effect connection changes, you must restart the managed server on which the application is deployed.

The following example sets only the WebCenter Portal Service Framework Resource Action Handler display as popup value to 1 (true):

```
wls:/wc_domain/domainRuntime>
setWebCenterServiceFrameworkConfig(appName='webcenter',
resourceActionHandlerDisplayInPopup=1)
```

Successfully set the WebCenter Portal service framework configuration.
Resource Action Handler Display In Popup: `true`
To effect connection changes, you must restart the managed server on which the application is deployed.

10.2.3 getWebCenterServiceFrameworkConfig

Module: Oracle WebCenter Portal

Use with WLST: Online

10.2.3.1 Description

Returns WebCenter Portal Service Framework configuration property settings, such as:

- `resourceActionHandlerClassName`: Class currently used by the WebCenter Portal Service Framework Resource Action Handler

- `resourceActionHandlerDisplayInPopup`: Indicates whether the Resource Action Handler displays resources in a popup or inline. Valid options are 1 (true) and 0 (false).

10.2.3.2 Syntax

```
getWebCenterServiceFrameworkConfig(appName, [server, applicationVersion])
```

Argument	Definition
<code>appName</code>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<code>server</code>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<code>applicationVersion</code>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.2.3.3 Example

The following example returns the service framework resource action handler class and display as popup properties, for WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig>getWebCenterServiceFrameworkConfig(appName='webcenter')
Resource Action Handler Class: my.company.ResourceActionHandler
Resource Action Handler Display In Popup: true
```

10.2.4 webcenterErrorOccurred

Module: Oracle WebCenter Portal

Use with WLST: Online

10.2.4.1 Description

Returns the status of last WebCenter Portal command executed.

Use the `webcenterErrorOccurred` command to determine the status of the last WebCenter Portal command executed. The command returns 1 if an error occurred or 0 otherwise.

10.2.4.2 Syntax

```
webcenterErrorOccurred ()
```

10.2.4.3 Example

The following example returns 1 if an error occurred:

```
wls:/mydomain/serverConfig> webcenterErrorOccurred()
```

10.2.5 getWebCenterConnectionTypes

Module: Oracle WebCenter Portal

Use with WLST: Online

10.2.5.1 Description

Lists all the Oracle WebCenter Portal connection types.

10.2.5.2 Syntax

```
getWebCenterConnectionTypes(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.2.5.3 Example

The following example returns connection types for WebCenter Portal (`webcenter`):

```
wls:/mydomain/serverConfig>getWebCenterConnectionTypes(appName='webcenter')
```

10.3 Analytics

This section includes the following sub sections:

- [Analytics Collector Connections](#)
- [Analytics Collector and Cluster Configuration](#)

Analytics Collector Connections

Use the commands listed in [Table 10-3](#) to manage analytics collector connections for WebCenter Portal and Portal Framework applications. Events raised in these portal applications using OpenUsage APIs can be sent to an analytics collector for use by analytics and activity graph.

Connection configuration changes made using these Oracle WebCenter Portal WLST commands are only effective after your restart the Managed Server on which the application is deployed. For details, see *Oracle Fusion Middleware Administering Oracle WebCenter Portal*.

Table 10–3 Analytics Collector Connection WLST Commands

Use this command...	To...	Use with WLST...
<code>createAnalyticsCollectorConnection</code>	Create a connection to an analytics collector for WebCenter Portal or a Portal Framework application.	Online
<code>setAnalyticsCollectorConnection</code>	Edit an existing analytics collector connection.	Online
<code>listAnalyticsCollectorConnections</code>	List all of the analytics collector connections that are configured for WebCenter Portal or a Portal Framework application.	Online
<code>setDefaultAnalyticsCollectorConnection</code>	Specify the default (or active) analytics collector connection for WebCenter Portal or a Portal Framework application.	Online
<code>listDefaultAnalyticsCollectorConnection</code>	Return connection details for the analytics collector being used by WebCenter Portal and Portal Framework application.	Online

Analytics Collector and Cluster Configuration

Use the commands listed in [Table 10–4](#) to configure event collection properties for the analytics collector that is deployed on the `WC_Uutilities` managed server.

If you reconfigure the analytics collector or set up clustering, you must restart the managed server on which the analytic collector is deployed (`WC_Uutilities`).

Table 10–4 Analytics Collector Configuration WLST Commands

Use this command...	To...	Use with WLST...
<code>setAnalyticsCollectorConfig</code>	Set analytics collector options, and cluster options if operating a clustered environment.	Online
<code>listAnalyticsCollectorConfig</code>	Return analytics collector settings.	Online
<code>listAnalyticsEventTypes</code>	List events currently registered with the analytics collector.	Online

10.3.1 createAnalyticsCollectorConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.3.1.1 Description

Creates a connection to an analytics collector for a named application.

Events raised in WebCenter Portal or a Portal Framework application using OpenUsage APIs can be sent to an analytics collector for use by analytics and activity graph.

While you can register multiple analytics collector connections for an application, only one analytics collector connection is used - the default (or active) connection where `default=1`.

10.3.1.2 Syntax

```
createAnalyticsCollectorConnection(appName, connectionName, [isUnicast,
collectorhost, clusterName, collectorPort, isEnabled, timeout, default, server,
```

```
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>connectionName</i>	Connection name. The name must be unique across all connection types within application.
<i>isUnicast</i>	Optional. Specifies whether events are sent to a clustered analytics collector in multicast mode or whether a single analytics collector using unicast communication is required. Valid values are 1 (true) and 0 (false). The default value is 1 (unicast).
<i>collectorHost</i>	Optional. Host name where the analytics collector is running. The default value is <code>localhost</code> . Only required for unicast communication, that is, where <code>isUnicast=1</code> .
<i>clusterName</i>	Optional. Name of the cluster where a clustered analytics collector is running. Only required for multicast communication, that is, where <code>isUnicast=0</code> .
<i>collectorPort</i>	Optional. Port on which the analytics collector listens for events. The default value is 31314.
<i>isEnabled</i>	Optional. Specifies whether to send analytics events raised using OpenUsage APIs to the analytics collector. Valid values 1 (true) and 0 (false). The default value is 0. Analytics events are sent to the analytics collector when <code>isEnabled=1</code> and <code>default=1</code> .
<i>timeout</i>	Optional. Length of time (in seconds) to wait for a response from the analytics collector. Default value is 30. Only required for multicast communication, that is, where <code>isUnicast=0</code> .
<i>default</i>	Optional. Indicates whether this connection is the default (or active) analytics collector connection for the application. Valid values are 1 (true) and 0 (false). When set to 1, the application sends events on this connection. When set to 0, the connection is not used. The default for this argument is 0. While you can register multiple analytics collector connections for an application, only one connection is used by analytics and activity graph—the default (or active) connection.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.3.1.3 Example

The following example creates a connection named `MyAnalyticsCollector` for WebCenter Portal (`webcenter`). Events are sent to a single analytics collector using *unicast* communication:

```
wls:/weblogic/serverConfig>createAnalyticsCollectorConnection(appName='webcenter',
connectionName='MyAnalyticsCollector', isUnicast=1,
collectorHost='myhost.com', collectorPort=31314, isEnabled=1, timeout=30,
default=1)
```

The following example creates a connection named MyAnalyticsCollector for WebCenter Portal. Events are sent to a clustered analytics collector in *multicast* mode

```
wls:/weblogic/serverConfig>createAnalyticsCollectorConnection(appName='webcenter',
connectionName='MyAnalyticsCollector', isUnicast=0,
clusterName='collector-cluster',
ccollectorPort=31314, isEnabled=1, timeout=30, default=1)
```

10.3.2 setAnalyticsCollectorConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.3.2.1 Description

Edits an existing analytics collector connection for a named application.

Events raised in WebCenter Portal or a Portal Framework application using OpenUsage APIs can be sent to an analytics collector for use by analytics and activity graph.

While you can register multiple analytics collector connections for an application, only one analytics collector connection is used - the default (or active) connection.

10.3.2.2 Syntax

```
setAnalyticsCollectorConnection(appName, connectionName, [isUnicast,
collectorHost, clusterName, collectorPort, isEnabled, timeout, default, server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>connectionName</i>	Connection name. The name must be unique across all connection types within application.
<i>isUnicast</i>	Optional. Specifies whether events are sent to a clustered analytics collector in multicast mode or whether a single analytics collector using unicast communication is required. Valid values are 1 (true) and 0 (false). The default value is 1 (unicast).
<i>collectorHost</i>	Optional. Host name where the analytics collector is running. The default value is <code>localhost</code> . Only required for unicast communication, that is, where <code>isUnicast=1</code> .
<i>clusterName</i>	Optional. Name of the cluster where a clustered analytics collector is running. Only required for multicast communication, that is, where <code>isUnicast=0</code> .
<i>collectorPort</i>	Optional. Port on which the analytics collector listens for events. The default value is 31314.

Argument	Definition
<i>isEnabled</i>	Optional. Specifies whether to send analytics events raised using OpenUsage APIs to the analytics collector. Valid values are 1 (true) and 0 (false). The default value is false. Analytics events are sent to the analytics collector when <code>isEnabled=1</code> and <code>default=1</code> .
<i>timeout</i>	Optional. Length of time (in seconds) to wait for a response from the analytics collector. Default value is 30. Only required for multicast communication, that is, where <code>isUnicast=0</code> .
<i>default</i>	Optional. Indicates whether this connection is the default (or active) analytics collector connection for the application. Valid values are 1 (true) and 0 (false). When set to 1, the application sends events on this connection. When set to 0, the connection is not used. The default for this argument is 0. While you can register multiple analytics collector connections for an application, only one connection is used by analytics and activity graph—the default (or active) connection.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.3.2.3 Example

The following example edits host and port details for an existing analytics collector connection named `MyAnalyticsCollector`. On this connection, events are sent to a single analytics collector in *unicast* mode:

```
wls:/weblogic/serverConfig>setAnalyticsCollectorConnection(appName='webcenter',
connectionName='MyAnalyticsCollector', collectorHost='myhost.com',
collectorPort=31314)
```

The following example edits cluster, port, and timeout details for an existing analytics collector connection named `MyAnalyticsCollector`. On this connection, events are sent to a clustered analytics collector in *multicast* mode:

```
wls:/weblogic/serverConfig>setAnalyticsCollectorConnection(appName='webcenter',
connectionName='MyAnalyticsCollector', clusterName='collector-cluster',
collectorPort=31314, timeout=60)
```

10.3.3 listAnalyticsCollectorConnections

Module: Oracle WebCenter Portal

Use with WLST: Online

10.3.3.1 Description

Lists connection names and details for all analytics collector connections that are configured for a named application.

10.3.3.2 Syntax

```
listAnalyticsCollectorConnections(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <i>webcenter</i> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <i>WC_Spaces</i> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.3.3.3 Examples

The following example lists connection names and details for all the analytics collector connections that are currently configured for WebCenter Portal (*webcenter*):

```
wls:/weblogic/serverConfig>listAnalyticsCollectorConnections(appName='webcenter')
```

```
-----
MyAnalyticsCollector
-----
ClusterName/HostName: localhost
Port: 31314
Timeout: 30
Unicast: 1 (true)
Enabled: 1 (true)

-----
TestAnalyticsCollector
-----
ClusterName/HostName: localhost
Port: 32456
Timeout: 456
Unicast: 1 (true)
Enabled: 1 (true)
-----
```

10.3.4 setDefaultAnalyticsCollectorConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.3.4.1 Description

Specifies the default analytics collector connection for a named application.

The default analytics collector connection is used to send events raised in WebCenter Portal or a Portal Framework application using OpenUsage APIs to an analytics collector for use by analytics and activity graph

While you can register multiple analytics collector connections for an application, only one analytics collector connection is used-- the default (or active) connection.

10.3.4.2 Syntax

```
setDefaultAnalyticsCollectorConnection(appName, name, [server,
applicationVersion])
```


Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing analytics collector connection.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.3.4.3 Example

The following example configures the connection `MyAnalyticsCollector` for events raised in WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig> setDefaultAnalyticsCollectorConnection
(appName='webcenter', name='MyAnalyticsCollector')
```

The following example resets the default connection name:

```
wls:/weblogic/serverConfig> setDefaultAnalyticsCollectorConnection
(appName='webcenter', name='')
```

10.3.5 listDefaultAnalyticsCollectorConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.3.5.1 Description

Return details about the analytics collector connection that is currently configured for a named application.

While you can register multiple analytics collector connections for an application, only one analytics collector connection is used—the default (or active) connection.

10.3.5.2 Syntax

```
listDefaultAnalyticsCollectorConnection(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.3.5.3 Examples

The following example returns details about the analytics collector connection that is currently configured for a WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig>listDefaultAnalyticsCollectorConnection(appName='webcenter')
```

```
-----
MyAnalyticsCollector
-----
ClusterName/HostName: localhost
Port: 31314
Timeout: 30
Unicast: 1 (true)
Enabled: 1 (true)
-----
```

10.3.6 setAnalyticsCollectorConfig

Module: Oracle WebCenter Portal

Use with WLST: Online

10.3.6.1 Description

Configure the analytics collector deployed on the `WC_Uutilities` managed server. Additionally, in a clustered environment, use this commands to set cluster settings.

10.3.6.2 Syntax

```
setAnalyticsCollectorConfig(appName, [collectorHost, defaultPort, maxPort, broadcastType, clusterEnabled, clusterName, heartbeatFrequency, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the analytics collector application in which to perform this operation--always <code>analytics-collector</code> .
<i>collectorHost</i>	Optional. Name of the host on which the analytics collector is running. The default value is <code>localhost</code> .
<i>defaultPort</i>	Optional. Default port number on which the analytics collector listens. The default value is <code>31314</code> .
<i>maxPort</i>	Optional. Highest port number that the analytics collector can use when allocating a listener. This property is mostly used in a clustered environment where more than one collector is running in the same box. Each collector listens for incoming UDP messages on a free port within a given port range. The range is from the default port number to the <code>maxPort</code> number.
<i>broadcastType</i>	Optional. Indicates the network channel on which the analytics collector broadcasts a 'heartbeat' to advertise its location to event producers. Valid values are <code>Broadcast</code> and <code>Multicast</code> . <ul style="list-style-type: none"> ■ <code>Broadcast</code> - use the standard network broadcast channel. ■ <code>Multicast</code> - use a special fixed multicast address.

Argument	Definition
<i>clusterEnabled</i>	Optional. Indicates whether the analytics collector is deployed in a cluster. Valid values are 1 (true) and 0 (false). If set to 1, <i>clusterName</i> must also be defined.
<i>clusterName</i>	Optional. Name of the analytics collector cluster. Only required when <i>clusterEnabled</i> =1
<i>heartbeatFrequency</i>	Optional. Broadcast analytics collector listening information every 'n' seconds. The default frequency is 10 seconds. The analytics collector periodically broadcasts a 'heartbeat' to advertise its location (<i>hostName</i>). In a clustered environment, WebCenter Portal and Portal Framework applications use the heartbeat to determine which analytics collectors are available.
<i>server</i>	Optional. Name of the managed server where the analytics collector is deployed. For example, <i>WC_Uutilities</i> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.3.6.3 Example

The following example changes the default port to 31315:

```
wls:/weblogic/serverConfig>setAnalyticsCollectorConfig(appName='analytics-collector', defaultPort=31315)
```

10.3.7 listAnalyticsCollectorConfig

Module: Oracle WebCenter Portal

Use with WLST: Online

10.3.7.1 Description

Returns analytics collector settings.

10.3.7.2 Syntax

```
listAnalyticsCollectorConfig(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the analytics collector application in which to perform this operation--always <i>analytics-collector</i> .
<i>server</i>	Optional. Name of the managed server where the analytics collector is deployed. For example, <i>WC_Uutilities</i> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.3.7.3 Examples

The following command lists current settings for the analytics collector that is configured for an application named *webcenter*:

```
wls:/weblogic/serverConfig>listAnalyticsCollectorConfig(appName='analytics-collector')
```

This is sample output for a standalone analytics collector:

```
CollectorHost = localhost
CollectorDefaultPort = 31314
CollectorMaximumPort = 31314
BroadcastType = Multicast
ClusterEnabled =
ClusterName =
ClusterBroadcastFrequency = 55
```

This is sample output for an analytics collector in a clustered environment:

```
CollectorHost = localhost
CollectorDefaultPort = 31314
CollectorMaximumPort = 31318
BroadcastType = Multicast
ClusterEnabled = 1
ClusterName = myCluster
ClusterBroadcastFrequency = 55
```

10.3.8 listAnalyticsEventTypes

Module: Oracle WebCenter Portal

Use with WLST: Online

10.3.8.1 Description

Lists all the events currently registered with the analytics collector.

10.3.8.2 Syntax

```
listAnalyticsEventTypes(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.3.8.3 Examples

The following command lists all the events currently registered with the analytics collector for use by WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig>listAnalyticsEventTypes(appName='webcenter')
```

Sample output:

```
{HTTP://WWW.ORACLE.COM/ANALYTICS/WC}DISCUSSION_ANNOUNCEMENTEDIT
{HTTP://WWW.ORACLE.COM/ANALYTICS/WC}DISCUSSION_TOPICDELETE
```

```
{HTTP://WWW.ORACLE.COM/ANALYTICS/WC}PAGEEDIT
{HTTP://WWW.ORACLE.COM/ANALYTICS/WC}DOCLIB_DOCUMENTCREATE
{HTTP://WWW.ORACLE.COM/ANALYTICS/WC}LOGINS
...
```

10.4 Activity Graph

Use the commands listed in [Table 10–5](#) to manage system properties and metadata for activity graph.

Configuration changes made using the `setAGProperty` WLST command are only effective after you restart the managed server on which the activity graph application is deployed (`WC_UtIlItIeS`). For all other commands, configuration changes are effective immediately.

See also, "Managing Activity Graph" in the *Oracle Fusion Middleware Administering Oracle WebCenter Portal*.

Table 10–5 Activity Graph WLST Commands

Use this command...	To...	Use with WLST...
<code>exportAGMetadata</code>	Export activity graph metadata definitions to an XML file.	Online
<code>importAGMetadata</code>	Import activity graph metadata definitions from an XML file.	Online
<code>exportAGProviderConfiguration</code>	Export provider configuration, for a given provider, to an activity graph metadata definition file.	Online
<code>deleteAllAGMetadata</code>	Delete all the activity graph metadata that is defined for an application.	Online
<code>deleteAGAction</code>	Delete the metadata for an action registered with activity graph.	Online
<code>deleteAGNodeClass</code>	Delete the metadata for a node class registered with activity graph.	Online
<code>deleteAGSimilarityCalculation</code>	Delete the metadata for a similarity calculation registered with activity graph.	Online
<code>deleteAGRankCalculation</code>	Delete the metadata for a rank calculation registered with activity graph.	Online
<code>deleteAGProviderAssignment</code>	Delete the metadata for a provider assignment registered with activity graph.	Online
<code>deleteAGQRPPRegistration</code>	Delete the metadata for a QRPP registered with activity graph.	Online
<code>deleteAGProviderConfiguration</code>	Delete the metadata for a provider configuration registered with activity graph.	Online
<code>renameAGAction</code>	Change the URN of an action registered with activity graph.	Online
<code>renameAGNodeClass</code>	Change the URN of a node class registered with activity graph.	Online
<code>setAGProperty</code>	Set a system property for activity graph.	Online
<code>getAGProperty</code>	Return the current setting for a given activity graph property.	Online

Table 10–5 (Cont.) Activity Graph WLST Commands

Use this command...	To...	Use with WLST...
<code>setAGPasswordCredential</code>	Set credentials (user name and password) for an activity graph property.	Online

10.4.1 exportAGMetadata

Module: Oracle WebCenter Portal

Use with WLST: Online

10.4.1.1 Description

Exports activity graph metadata definitions to an XML file.

10.4.1.2 Syntax

```
exportAGMetadata(appName, directoryPath, definitionFileName,
includeProviderConfigurations, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the activity graph application in which to perform this operation—always <code>activitygraph-engines</code> .
<i>directoryPath</i>	Destination directory for the XML file that will be generated. If you specify a directory that does not exist then it will be created.
<i>definitionFileName</i>	Name for the XML file that will be generated. If a file with the same name exists in the destination directory then it will be overwritten.
<i>includeProviderConfigurations</i>	Determines whether the export includes provider configuration metadata. Valid values are 1 (true) and 0 (false). Provider configurations are a subset of activity graph metadata that you may want to manage separately from the other metadata.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Uilities</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the activity graph application is deployed.

10.4.1.3 Example

The following example exports activity graph metadata definitions to an XML file named `ag-metadata.xml`, at the specified location:

```
wls:/weblogic/serverConfig> exportAGMetadata(appName='activitygraph-engines',
directoryPath='/scratch/myAGmetadata', definitionFileName='ag-metadata.xml',
includeProviderConfigurations=1)
```

10.4.2 importAGMetadata

Module: Oracle WebCenter Portal

Use with WLST: Online

10.4.2.1 Description

Imports activity graph metadata definitions from an XML file.

On import, new activity graph metadata definitions are created on the target and existing definitions are overwritten.

10.4.2.2 Syntax

```
importAGMetadata(appName, definitionFilePath, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the activity graph application in which to perform this operation—always <code>activitygraph-engines</code> .
<i>definitionFilePath</i>	Relative path to the XML file containing metadata definitions. For example, <code>metadata/import-metadata.xml</code> .
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Uilities</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the activity graph application is deployed.

10.4.2.3 Example

The following example imports activity graph metadata definitions from a file name `import-metadata.xml`:

```
wls:/weblogic/serverConfig> importAGMetadata(appName='activitygraph-engines',
definitionFilePath='metadata/import-metadata.xml')
```

10.4.3 exportAGProviderConfiguration

Module: Oracle WebCenter Portal

Use with WLST: Online

10.4.3.1 Description

Exports provider configuration, for a given provider, to an activity graph metadata definition file.

10.4.3.2 Syntax

```
exportAGProviderConfiguration(appName, directoryPath, definitionFileName, urn,
[server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the activity graph application in which to perform this operation—always <code>activitygraph-engines</code> .
<i>directoryPath</i>	Destination directory for the XML file that will be generated. If you specify a directory that does not exist, then it will be created.
<i>definitionFilePath</i>	Name for the XML file that will be generated. If a file with the same name exists in the destination directory then it will be overwritten.
<i>urn</i>	URN for the activity graph provider to export. For example: <code>oracle.webcenter.activitygraph.providers.analytics</code>

Argument	Definition
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Uilities</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the activity graph application is deployed.

10.4.3.3 Example

The following example exports configuration information for the activity graph provider `oracle.webcenter.activitygraph.providers.analytics` to an XML file named `ag-provider-config.xml`, at the specified location:

```
wls:/weblogic/serverConfig>
exportAGProviderConfiguration(appName='activitygraph-engines',
directoryPath='/scratch/myAGmetadata',
definitionFileName='ag-provider-config.xml',
urn='oracle.webcenter.activitygraph.providers.analytics')
```

10.4.4 deleteAllAGMetadata

Module: Oracle WebCenter Portal

Use with WLST: Online

10.4.4.1 Description

Deletes all the activity graph metadata that is defined for WebCenter Portal or a Portal Framework application. The delete operation is immediate and non-reversible.

You can use this command in conjunction with the WLST command [importAGMetadata](#) to completely re-install activity graph metadata.

Note: Any data in the relation store, similarity store, and rank store will be deleted the next time the activity graph engines run.

10.4.4.2 Syntax

```
deleteAllAGMetadata(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the activity graph application in which to perform this operation—always <code>activitygraph-engines</code> .
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Uilities</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the activity graph application is deployed.

10.4.4.3 Example

The following example deletes all existing activity graph metadata:

```
wls:/weblogic/serverConfig> deleteAllAGMetadata(appName='activitygraph-engines')
```


10.4.5 deleteAGAction

Module: Oracle WebCenter Portal

Use with WLST: Online

10.4.5.1 Description

Deletes the metadata for an action that is currently registered with activity graph. The delete operation is immediate and non-reversible.

Note: Any data in the relation store that is associated with the action will be deleted the next time the activity graph engines run.

10.4.5.2 Syntax

```
deleteAGAction(appName, urn, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the activity graph application in which to perform this operation—always <code>activitygraph-engines</code> .
<i>urn</i>	URN for the activity graph action that you want to delete.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Uilities</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the activity graph application is deployed.

10.4.5.3 Example

The following example deletes activity graph metadata for the `connect` action:

```
wls:/weblogic/serverConfig> deleteAGAction(appName='activitygraph-engines',
urn='connect')
```

10.4.6 deleteAGNodeClass

Module: Oracle WebCenter Portal

Use with WLST: Online

10.4.6.1 Description

Deletes the metadata for a node class that is currently registered with activity graph. The delete operation is immediate and non-reversible.

Note: Any data in the relation store that is associated with the node class will be deleted the next time the activity graph engines run.

10.4.6.2 Syntax

```
deleteAGNodeClass(appName, urn, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the activity graph application in which to perform this operation—always <code>activitygraph-engines</code> .
<i>urn</i>	URN for the activity graph node class that you want to delete.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Uilities</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the activity graph application is deployed.

10.4.6.3 Example

The following example deletes activity graph metadata for the node class `WC.wiki-page`:

```
wls:/weblogic/serverConfig> deleteAGNodeClass(appName='activitygraph-engines',
urn='WC.wiki-page')
```

10.4.7 deleteAGSimilarityCalculation

Module: Oracle WebCenter Portal

Use with WLST: Online

10.4.7.1 Description

Deletes the metadata for a similarity calculation that is currently registered with activity graph. The delete operation is immediate and non-reversible.

10.4.7.2 Syntax

```
deleteAGSimilarityCalculation(appName, urn, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the activity graph application in which to perform this operation—always <code>activitygraph-engines</code> .
<i>urn</i>	URN for the activity graph similarity calculation that you want to delete.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Uilities</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the activity graph application is deployed.

10.4.7.3 Example

The following example deletes activity graph metadata for the similarity calculation `item-edit`:

```
wls:/weblogic/serverConfig>
deleteAGSimilarityCalculation(appName='activitygraph-engines', urn='item-edit')
```

10.4.8 deleteAGRankCalculation

Module: Oracle WebCenter Portal

Use with WLST: Online

10.4.8.1 Description

Deletes the metadata for a rank calculation that is currently registered with activity graph. The delete operation is immediate and non-reversible.

10.4.8.2 Syntax

```
deleteAGRankCalculation(appName, urn, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the activity graph application in which to perform this operation—always <code>activitygraph-engines</code> .
<i>urn</i>	URN for the activity graph rank calculation that you want to delete.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Uilities</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the activity graph application is deployed.

10.4.8.3 Example

The following example deletes activity graph metadata for the `activity-rank` calculation:

```
wls:/weblogic/serverConfig>
deleteAGRankCalculation(appName='activitygraph-engines', urn='activity-rank')
```

10.4.9 deleteAGProviderAssignment

Module: Oracle WebCenter Portal

Use with WLST: Online

10.4.9.1 Description

Deletes the metadata for a provider assignment that is currently registered with activity graph, that is, a provider assignment defined by the unique triple combination (`action`, `sourceClass`, `trgClass`).

The delete operation is immediate and non-reversible.

10.4.9.2 Syntax

```
deleteAGProviderAssignment(appName, actionURN, srcClasURN, trgClassURN [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the activity graph application in which to perform this operation—always <code>activitygraph-engines</code> .
<i>actionURN</i>	URN for the action.

Argument	Definition
<i>srcClassURN</i>	URN for the source node class.
<i>trgClassURN</i>	URN for the target node class.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <i>WC_Uilities</i> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the activity graph application is deployed.

10.4.9.3 Example

The following example deletes activity graph metadata for the provider assignment specified:

```
wls:/weblogic/serverConfig>
deleteAGRProviderAssignment(appName='activitygraph-engines', actionURN='connect',
srcClassURN='WC.user', trgClassURN='WC.user')
```

10.4.10 deleteAGQRPPRegistration

Module: Oracle WebCenter Portal

Use with WLST: Online

10.4.10.1 Description

Deletes the metadata for a QRPP (Query Result Post Processor) that is currently registered with activity graph.

The delete operation is immediate and non-reversible.

10.4.10.2 Syntax

```
deleteAGQRPPRegistration(appName, urn [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the activity graph application in which to perform this operation—always <i>activitygraph-engines</i> .
<i>urn</i>	URN for the QRPP that you want to delete.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <i>WC_Uilities</i> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the activity graph application is deployed.

10.4.10.3 Example

The following example deletes activity graph metadata for a QRPP named Event store metadata QRPP:

```
wls:/weblogic/serverConfig>
deleteAGQRPPRegistration(appName='activitygraph-engines', urn='Event store
metadata QRPP')
```

10.4.11 deleteAGProviderConfiguration

Module: Oracle WebCenter Portal

Use with WLST: Online

10.4.11.1 Description

Deletes the metadata for a provider configuration. The delete operation is immediate and non-reversible.

10.4.11.2 Syntax

```
deleteAGProviderConfiguration(appName, urn [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the activity graph application in which to perform this operation—always <code>activitygraph-engines</code> .
<i>urn</i>	URN for the activity graph provider that you want to delete.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Uilities</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the activity graph application is deployed.

10.4.11.3 Example

The following example deletes configuration information for the activity graph provider `oracle.webcenter.activitygraph.providers.analytics`:

```
wls:/weblogic/serverConfig>
deleteAGProviderConfiguration(appName='activitygraph-engines',
urn='oracle.webcenter.activitygraph.providers.analytics')
```

10.4.12 renameAGAction

Module: Oracle WebCenter Portal

Use with WLST: Online

10.4.12.1 Description

Changes the URN of an action that is currently registered with activity graph. Any data in the relation store that is associated with the action is preserved.

Note: This command does not delete the action and create an action with a different name as this causes data associated with the original action to be deleted.

10.4.12.2 Syntax

```
renameAGAction(appName, currentURN, newURN, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the activity graph application in which to perform this operation—always <code>activitygraph-engines</code> .
<i>currentURN</i>	Current action URN.
<i>newURN</i>	New action URN.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Uilities</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the activity graph application is deployed.

10.4.12.3 Example

The following example changes the `connect` action URN to `people-connect`:

```
wls:/weblogic/serverConfig> renameAGAction(appName='activitygraph-engines',
currentURN='connect', newURN='people-connect')
```

10.4.13 renameAGNodeClass

Module: Oracle WebCenter Portal

Use with WLST: Online

10.4.13.1 Description

Changes the URN of a node class that is currently registered with activity graph. Any data in the relation store that is associated with the node class is preserved.

Note: This command does not delete the node class and create a node class with a different name as this would cause data associated with the original node class to be deleted.

10.4.13.2 Syntax

```
renameAGNodeClass(appName, currentURN, newURN, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the activity graph application in which to perform this operation—always <code>activitygraph-engines</code> .
<i>currentURN</i>	Current node class URN.
<i>newURN</i>	New node class URN.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Uilities</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the activity graph application is deployed.

10.4.13.3 Example

The following example changes the `WC.user` node class URN to `WC.people`:

```
wls:/weblogic/serverConfig> renameAGNodeClass (appName='activitygraph-engines',
currentURN='WC.user', newURN='WC.people')
```

10.4.14 setAGProperty

Module: Oracle WebCenter Portal

Use with WLST: Online

10.4.14.1 Description

Sets a system property for activity graph. This command sets a value based on the property's datatype (String, Integer, Float, Boolean).

Activity graph system properties include settings for:

- Oracle Secure Enterprise Search (SES) Admin API web service connection (oracle.webcenter.activitygraph.providers.datasources.ses.soa.p.admin.url and oracle.webcenter.activitygraph.providers.datasources.ses.soap.query.url)
- Rank engine configuration (oracle.webcenter.activitygraph.rankengine.enabled)

See also, "Managing Activity Graph" in the *Oracle Fusion Middleware Administering Oracle WebCenter Portal* for a list of system properties and their datatypes.

Configuration changes made using the setAGProperty WLST command are only effective after your restart the managed server on which the activity graph application is deployed (WC_Uilities).

10.4.14.2 Syntax

```
setAGProperty(appName, propertyName, propertyValue, propertyType, [server,
applicationVersion])
```

Argument	Definition
appName	Name of the activity graph application in which to perform this operation—always activitygraph-engines.
propertyName	Name of the activity graph property.
propertyValue	Value for the activity graph property.
propertyType	Datatype of the property. Valid values are: String, Int, Float or Boolean. Values are case sensitive.
server	Optional. Name of the managed server where the application is deployed. For example, WC_Uilities. Required when applications with the same name are deployed to different servers and also when you have a cluster.
applicationVersion	Optional. Version number of the deployed application. Required if more than one version of the activity graph application is deployed.

10.4.14.3 Example

The following example enables the Rank Engine:

```
wls:/weblogic/serverConfig> setAGProperty (appName='activitygraph-engines',
propertyName='oracle.webcenter.activitygraph.rankengine.enabled',
```

```
propertyValue=1, propertyType='Boolean')
```

10.4.15 getAGProperty

Module: Oracle WebCenter Portal

Use with WLST: Online

10.4.15.1 Description

Returns the current setting for a given activity graph property.

See also, "Managing Activity Graph" in the *Oracle Fusion Middleware Administering Oracle WebCenter Portal* for a list of valid system properties.

10.4.15.2 Syntax

```
getAGProperty(appName, propertyName, propertyType [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the activity graph application in which to perform this operation—always <code>activitygraph-engines</code> .
<i>propertyName</i>	Name of the activity graph property.
<i>propertyType</i>	Datatype of the property. Valid values are: <code>String</code> , <code>Int</code> , <code>Float</code> or <code>Boolean</code> . Values are case sensitive.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Uilities</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the activity graph application is deployed.

10.4.15.3 Example

The following example returns the current value of the system property `oracle.webcenter.activitygraph.providers.datasources.ses.soap.admin.url`:

```
wls:/weblogic/serverConfig>getAGProperty(appName='activitygraph-engines',
propertyName='oracle.webcenter.activitygraph.providers.datasources.ses.soap.admin.
url', propertyType='String')
```

10.4.16 setAGPasswordCredential

Module: Oracle WebCenter Portal

Use with WLST: Online

10.4.16.1 Description

Sets credentials (user name and password) for an activity graph credential property.

See also, "Managing Activity Graph" in the *Oracle Fusion Middleware Administering Oracle WebCenter Portal* for a list of properties with the `PasswordCredential` datatype, for example,

```
oracle.webcenter.activitygraph.providers.datasources.ses.soap.ad
min.credential.
```


10.4.16.2 Syntax

```
setAGPasswordCredentialProperty(appName, propertyName, userName, password,[server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the activity graph application in which to perform this operation—always <code>activitygraph-engines</code> .
<i>propertyName</i>	Name of the activity graph property that specifies credentials (and has <code>PasswordCredential</code> datatype).
<i>userName</i>	User name associated with the credential property.
<i>password</i>	Password associated with the user name specified.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Uutilities</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the activity graph application is deployed.

10.4.16.3 Example

The following example sets user name and password credentials for the Oracle SES Admin tool:

```
wls:/weblogic/serverConfig> setAGProperty(appName='activitygraph-engines',
propertyName='oracle.webcenter.activitygraph.providers.datasources.ses.soap.admin.
credential',
userName='eqsys', password='mypassword')
```

10.5 Activity Stream

Use the commands listed in [Table 10–6](#) to archive and restore activity stream data generated for WebCenter Portal and Portal Framework applications.

Configuration changes made using these WLST commands are only effective after you restart the Managed Server on which the application is deployed. For details, see *Oracle Fusion Middleware Administering Oracle WebCenter Portal*.

Table 10–6 Activity Stream WLST Commands

Use this command...	To...	Use with WLST...
archiveASByDate	Archive activity stream data that is older than a specified date.	Online
archiveASByDeletedObjects	Archive activity stream data associated with deleted objects.	Online
archiveASByClosedSpaces	Archive activity stream data associated with portals that are currently closed.	Online
archiveASByInactiveSpaces	Archive activity stream data associated with portals that have been inactive since a specified date.	Online
restoreASByDate	Restore archived activity stream data from a specified date into production tables.	Online
truncateASArchive	Truncates activity stream archive data.	Online
archiveASBySpace	Archive activity stream data associated with a portal.	Online

Table 10–6 (Cont.) Activity Stream WLST Commands

Use this command...	To...	Use with WLST...
archiveASAllSpaces	Archive activity stream data associated with all portals.	Online
archiveASByUser	Archive activity stream data associated with a user.	Online
archiveASAllUsers	Archive activity stream data associated with all users.	Online
archiveASByDeletedActors	Archive activity stream data associated with deleted actors.	Online
showASStatistics	Report activity stream statistics.	Online

10.5.1 archiveASByDate

Module: Oracle WebCenter Portal

Use with WLST: Online

10.5.1.1 Description

Archives activity stream data that is older than a specified date.

This command moves data from production tables to archive tables. Exceptions include `WC_ACTOR_DETAIL` and `WC_OBJECT_DETAIL`—data in these tables is copied to archive tables rather than moved.

Rows in `WC_OBJECT_DETAIL` that are not used by any activity element are deleted.

10.5.1.2 Syntax

```
archiveASByDate(appName, year, month, day, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>year</i>	Year before which to archive activity stream data. For example, 2009.
<i>month</i>	Month before which to archive activity stream data. For example, enter 1 for January, 2 for February, and so on.
<i>day</i>	Day of the month before which to archive activity stream data.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.5.1.3 Example

The following example archives activity stream data that is older than October 1, 2009 for WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig> archiveASByDate(appName='webcenter', year=2009, month=10, day=1)
```

10.5.2 archiveASByDeletedObjects

Module: Oracle WebCenter Portal

Use with WLST: Online

10.5.2.1 Description

Archives activity stream data associated with deleted objects.

This command moves data from production tables to archive tables, except for WC_ACTOR_DETAIL as data in this table is copied to the archive table rather than moved.

Rows in WC_OBJECT_DETAIL that satisfy the criteria (in this case, deleted objects) are deleted.

10.5.2.2 Syntax

```
archiveASByDeletedObjects(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.5.2.3 Example

The following example archives activity stream data associated with deleted objects from WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig> archiveASByDeletedObjects(appName='webcenter')
```

10.5.3 archiveASByClosedSpaces

Module: Oracle WebCenter Portal

Use with WLST: Online

10.5.3.1 Description

Archives activity stream data associated with portals that are currently closed.

This command moves data from production tables to archive tables, except for WC_ACTOR_DETAIL as data in this table is copied to the archive table rather than moved.

Rows in WC_OBJECT_DETAIL that satisfy the criteria (in this case, objects involved in activities of portals that are closed) are deleted.

10.5.3.2 Syntax

```
archiveASByClosedSpaces(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> .
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.5.3.3 Example

The following example archives activity stream data associated with portals that are currently marked as closed in WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig> archiveASByClosedSpaces (appName='webcenter')
```

10.5.4 archiveASByInactiveSpaces

Module: Oracle WebCenter Portal

Use with WLST: Online

10.5.4.1 Description

Archives activity stream data associated with portals that have been inactive since a specified date. An inactive portals an open or closed portal in which there has been no activity since the specified date.

This command moves data from production tables to archive tables, except for `WC_ACTOR_DETAIL`—data in this table is copied to the archive table rather than moved.

Rows in `WC_OBJECT_DETAIL` that satisfy the criteria (in this case, objects involved in activities of portals that have been inactive since the specified date) are deleted.

10.5.4.2 Syntax

```
archiveASByInactiveSpaces(appName, year, month, day, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> .
<i>year</i>	Year the portal became inactive. For example, 2009.
<i>month</i>	Month the portal became inactive. For example, enter 1 for January, 2 for February, and so on.
<i>day</i>	Day of the month the portal became inactive.
<i>server</i>	Optional. Name of the managed server where WebCenter Portal is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.5.4.3 Example

The following example archives activity stream data associated with portals that have been inactive (no activities have occurred, regardless of open or closed status) since October 1, 2009:

```
wls:/weblogic/serverConfig> archiveASByInactiveSpaces (appName='webcenter',
year=2009, month=10, day=1)
```

10.5.5 restoreASByDate

Module: Oracle WebCenter Portal

Use with WLST: Online

10.5.5.1 Description

Restores archived activity stream data from a specified date into production tables.

This command moves data from archive tables to production tables, except for WC_ACTOR_DETAIL as data in this table is not restored because data is not deleted from this table during the archive process.

Rows that already exist in the production tables are not changed during the restore process.

10.5.5.2 Syntax

```
restoreASByDate (appName, year, month, day, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>year</i>	Year from which to restore activity stream data. For example, 2009.
<i>month</i>	Month from which to restore activity stream data. For example, enter 1 for January, 2 for February, and so on.
<i>day</i>	Day of the month from which to restore activity stream data.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.5.5.3 Example

The following example restores activity stream data archived since October 1, 2009:

```
wls:/weblogic/serverConfig> restoreASByDate (appName='webcenter', year=2009,
month=10, day=1)
```

10.5.6 truncateASArchive

Module: Oracle WebCenter Portal

Use with WLST: Online

10.5.6.1 Description

Truncates activity stream archive data.

10.5.6.2 Syntax

```
truncateASArchive(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.5.6.3 Example

The following example truncates activity stream archive data:

```
wls:/weblogic/serverConfig>truncateASArchive(appName='webcenter')
```

10.5.7 archiveASBySpace

Module: Oracle WebCenter Portal

Use with WLST: Online

10.5.7.1 Description

Archives activity stream data associated with a named portal, only keeping a fixed number of activities.

This command moves data from production tables to archive tables.

10.5.7.2 Syntax

```
archiveASBySpace(appName, space, cnt, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> .
<i>space</i>	Name of the portal whose data you want to archive. For example, <code>MySalesPortal</code> .
<i>cnt</i>	Number of portal activities you want to keep in the production table. For example, <code>2000</code> .
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.

Argument	Definition
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.5.7.3 Example

The following example keeps the last 2000 activities associated with the portal `MySalesPortal` and archives the rest:

```
wls:/weblogic/serverConfig> archiveASBySpace (appName='webcenter',
space='MySalesPortal', cnt=2000)
```

10.5.8 archiveASAllSpaces

Module: Oracle WebCenter Portal

Use with WLST: Online

10.5.8.1 Description

Archives activity stream data for all portals, only keeping a fixed number of activities.

This command moves data from production tables to archive tables.

10.5.8.2 Syntax

```
archiveASAllSpaces(appName, cnt, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> .
<i>cnt</i>	Number of portal activities you want to keep in the production table. For example, <code>2000</code> .
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.5.8.3 Example

The following example keeps the last 2000 activities for each portal in production tables and archives the remaining activity stream data:

```
wls:/weblogic/serverConfig> archiveASAllSpaces (appName='webcenter', cnt=2000)
```

10.5.9 archiveASByUser

Module: Oracle WebCenter Portal

Use with WLST: Online

10.5.9.1 Description

Archives activity stream data associated with a single user, only keeping a fixed number of activities.

This command moves data from production tables to archive tables.

10.5.9.2 Syntax

```
archiveASByUser(appName, actor, cnt, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>actor</i>	Name of the user whose data you want to archive. For example, <code>Monty</code> .
<i>cnt</i>	Number of user activities you want to keep in the production table. For example, <code>2000</code> .
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.5.9.3 Example

The following example keeps the last 2000 activities associated with the user `Monty` and archives the rest:

```
wls:/weblogic/serverConfig> archiveASByUser(appName='webcenter', actor='Monty', cnt=2000)
```

10.5.10 archiveASAllUsers

Module: Oracle WebCenter Portal

Use with WLST: Online

10.5.10.1 Description

Archives activity stream data for all users, only keeping a fixed number of activities.

This command moves data from production tables to archive tables.

10.5.10.2 Syntax

```
archiveASAllUsers(appName, cnt, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>cnt</i>	Number of user activities you want to keep in the production table. For example, <code>2000</code> .

Argument	Definition
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.5.10.3 Example

The following example keeps the last 2000 activities for user in production tables and archives the remaining activity stream data:

```
wls:/weblogic/serverConfig> archiveASAllUsers (appName='webcenter', cnt=2000)
```

10.5.11 archiveASByDeletedActors

Module: Oracle WebCenter Portal

Use with WLST: Online

10.5.11.1 Description

Archives activity stream data associated with deleted users (actors).

This command moves data from production tables to archive tables. Rows in `WC_AS_ACTOR_DETAIL` that satisfy the criteria (in this case, deleted actors) are deleted.

10.5.11.2 Syntax

```
archiveASByDeletedActors (appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.5.11.3 Example

The following example archives activity stream data associated with deleted users for WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig> archiveASByDeletedActors (appName='webcenter')
```

10.5.12 showASStatistics

Module: Oracle WebCenter Portal

Use with WLST: Online

10.5.12.1 Description

Reports various activity stream statistics:

- Number of activities for top "N" portals, ordered by activity count
- Number of activities for top "N" users, ordered by activity count
- Number of activities after a specific date
- Number of activities after a specific date for top "N" portals, ordered by activity count
- number of activities after a specified date for top "N" users, ordered by activity count

10.5.12.2 Syntax

```
showASStatistics(appName, year, month, day, cnt, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>year</i>	Year from which to report activity stream statistics. For example, 2009.
<i>month</i>	Month from which to report activity stream statistics. For example, enter 1 for January, 2 for February, and so on.
<i>day</i>	Day of the month from which to report activity stream statistics.
<i>cnt</i>	Number of portals or users included in the report. For example, 50.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.5.12.3 Example

The following example reports activity stream statistics for the top 50 portals and top 50 users in WebCenter Portal (`webcenter`) since 6/12/2012:

```
wls:/weblogic/serverConfig> showASStatistics(appName='webcenter', year=2012,
month=7, day=18, cnt=3)
```

```
=====
Cutoff Date = 7/18/12 12:23 PM
Top Count = 3

1. Portals with most activity count are:
Portal Finance Count =10
Portal Photography Count =9
Portal Sport Count =7

2. Users with most activity count are:
User Monty Count =30
User Pat Count =20
```

User Dave Count =10

3. Total Activities after 7/18/12 12:23 PM =80

4. Portals with most activity count after specific date, are:

Portal Photography Count =9

Portal Finance Count =6

Portal Sport Count =6

5. Users with most activity count after specific date, are:

User Monty Count =10

User Dave Count =8

User Monica Count =7

10.6 Content Repository

Use the commands listed in [Table 10–7](#) to manage content repository connections and configure document services for WebCenter Portal and Portal Framework applications.

Configuration changes made using these WLST commands are only effective after your restart the Managed Server on which the application is deployed. For details, see *Oracle Fusion Middleware Administering Oracle WebCenter Portal*.

Table 10–7 Content Repository WLST Commands

Use this command...	To...	Use with WLST...
createJCRContentServerConnection	Create a connection to an Oracle WebCenter Content repository.	Online
setJCRContentServerConnection	Edit an existing Oracle WebCenter Content repository connection.	Online
listJCRContentServerConnections	List individual or all Oracle WebCenter Content repository connections that are configured for a named application.	Online
createJCRPortalConnection	Create an Oracle Portal repository connection.	Online
setJCRPortalConnection	Edit an existing Oracle Portal repository connection.	Online
listJCRPortalConnections	List all Oracle Portal connections that are configured for a named application.	Online
createJCRFileSystemConnection	Create a connection to a file system.	Online
setJCRFileSystemConnection	Edit an existing file system repository connection.	Online
listJCRFileSystemConnections	List individual or all file system connections configured for a named application.	Online
createJCRSharePointConnection	Create a Microsoft SharePoint 2007 repository connection.	Online
setJCRSharePointConnection	Edit a Microsoft SharePoint 2007 repository connection.	Online
listJCRSharePointConnections	List all Microsoft SharePoint 2007 connections that are configured for a named application.	Online

Table 10–7 (Cont.) Content Repository WLST Commands

Use this command...	To...	Use with WLST...
<code>listDocumentsSpacesProperties</code>	List properties for the back-end Content Server that is being used by WebCenter Portal.	Online
<code>setDocumentsSpacesProperties</code>	Modify properties for the back-end Content Server used by WebCenter Portal.	Online
<code>deleteDocumentsSpacesProperties</code>	Delete properties for the back-end Content Server used by WebCenter Portal.	Online

10.6.1 createJCRContentServerConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.6.1.1 Description

Creates a connection to an Oracle WebCenter Content repository for a named application.

10.6.1.2 Syntax

```
createJCRContentServerConnection(appName, name, socketType, [url, serverHost,
serverPort, keystoreLocation, keystorePassword, privateKeyAlias,
privateKeyPassword, webContextRoot, clientSecurityPolicy,
cacheInvalidationInterval, binaryCacheMaxEntrySize,
adminUsername, adminPassword, extAppId, timeout, isPrimary, server,
applicationVersion])
```

Argument	Definition
<code>appName</code>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<code>name</code>	Connection name. The name must be unique (across all connection types) within the application.

Argument	Definition
<i>socketType</i>	<p>Specifies whether Oracle WebCenter Content's Content Server connects on the content server listener port or the web server filter, and whether the listener port is SSL enabled.</p> <p>Valid values are <code>socket</code>, <code>web</code>, <code>socketssl</code>, and <code>jaxws</code>. This option has no default.</p> <p>Choose from:</p> <ul style="list-style-type: none"> ■ socket—Use an intradoc socket connection to connect to the Content Server. The client IP address must be added to the list of authorized addresses in the Content Server. In this case, the client is the machine on which Oracle WebCenter Portal is running. ■ socketssl—Use an intradoc socket connection to connect to the Content Server that is secured using the SSL protocol. The client's certificates must be imported in the server's trust store for the connection to be allowed. This is the most secure option, and the recommended option whenever identity propagation is required (for example, in WebCenter Portal). ■ web—Use an HTTP(S) connection to connect to the Content Server. Note that for WebCenter Portal, this option is not suitable for the active connection, that is, the back-end Content Server repository that is being used to store portal-specific documents and Home portal documents, because it does not allow identity propagation. ■ jaxws—Use a Java API for XML web services connection to connect to the Content Server.
<i>url</i>	<p>Optional. Content Server URL. Required only if <code>socketType</code> is set to <code>web</code> or <code>jaxws</code>.</p> <p>URL should be in the format:</p> <p><code>http://hostname:port/web_root/plugin_root</code></p> <p>For example: <code>http://mycontentserver/cms/idcplg</code></p>
<i>serverHost</i>	<p>Optional. Host name of the machine where the Content Server is running. Required if <code>socketType</code> is set to <code>socket</code> or <code>socketssl</code>.</p>
<i>serverPort</i>	<p>Optional. Port on which the Content Server listens. Required if <code>socketType</code> is set to <code>socket</code> or <code>socketssl</code>:</p> <ul style="list-style-type: none"> ■ Socket—Port specified for the incoming provider in the server. ■ Socket SSL—Port specified for the sslincoming provider in the server. <p>This property corresponds to the <code>IntradocServerPort</code> setting in the Content Server configuration file, which defaults to port 4444.</p>
<i>keystoreLocation</i>	<p>Optional. Location of key store that contains the private key used to sign the security assertions. Required only if <code>socketType</code> is set to <code>socketssl</code>.</p> <p>The key store location must be an absolute path.</p>
<i>keystorePassword</i>	<p>Optional. Password required to access the key store. Required only if <code>socketType</code> is set to <code>socketssl</code>.</p>
<i>privateKeyAlias</i>	<p>Optional. Client private key alias in the key store. The key is used to sign messages to the server. The public key corresponding to this private key must be imported in the server keystore.</p> <p>Required only if <code>socketType</code> is set to <code>socketssl</code>. The value for this argument must be a string that contains neither special characters nor white space.</p>

Argument	Definition
<code>privateKeyPassword</code>	Optional. Password to be used with the private key alias in the key store. Required only if <code>socketType</code> is set to <code>socketssl</code> .
<code>webContextRoot</code>	<p>Optional. Web server context root for the Content Server. Use the format <code>/<context_root></code>. For example, <code>/cs</code>.</p> <p>When specified, several Oracle WebCenter Content features based on <code>iFrame</code> are available in the application. This includes:</p> <ul style="list-style-type: none"> <p>■ Associating a content profile with files when uploading new or updated files to Content Server.</p> <p>For more information, see "Uploading Files" and "Uploading a New Version of an Existing File" in <i>Oracle Fusion Middleware Using Oracle WebCenter Portal</i>.</p> <p>■ Using the document review functionality available in Oracle AutoVue.</p> <p>For more information, see "Collaborating on Documents Using Oracle AutoVue" in <i>Oracle Fusion Middleware Using Oracle WebCenter Portal</i>.</p> <p>■ Editing advanced document properties.</p> <p>For more information, see "Working with File Properties" in <i>Oracle Fusion Middleware Using Oracle WebCenter Portal</i>.</p> <p>■ Viewing folder and file workflow details.</p> <p>For more information, see "Working with Workflow-Enabled Content" in <i>Oracle Fusion Middleware Using Oracle WebCenter Portal</i>.</p> <p>■ Previewing files in a slide viewer.</p> <p>For more information, see "Opening a File" in <i>Oracle Fusion Middleware Using Oracle WebCenter Portal</i>.</p> <p>■ Site Studio integration</p> <p>For more information, see <i>Oracle Fusion Middleware Using Oracle WebCenter Portal</i>.</p> <p><code>webContextRoot</code> is only applicable when <code>IDENTITY_PROPAGATION</code> is used for authentication, that is, when <code>extAppId</code> is set to an empty string.</p> <p>Note: To fully enable these Oracle WebCenter Content features you must access WebCenter Portal (or your Portal Framework application) through Oracle HTTPS Server (OHS) to expose Content Server and the application under the same host and port. Both the application and Content Server must also use single sign on. For information about setting up OHS to front-end WebCenter Portal and Portal Framework applications, see "Configuring Content Server" in <i>Oracle Fusion Middleware Administering Oracle WebCenter Portal</i>.</p> <p>If your application is connected to multiple Content Servers, Oracle recommends that each Content Server has a unique Web Server Context Root so that OHS re-direction works correctly.</p>
<code>clientSecurityPolicy</code>	<p>Optional. Client security policy to be used when the <code>socketType</code> is <code>jaxws</code>. For example: <code>oracle/wss11_saml_token_with_message_protection_service_policy</code></p> <p>Leave the field blank if your environment supports Global Policy Attachments (GPA).</p>
<code>cacheInvalidationInterval</code>	<p>Optional. Time between checks for external Content Server content changes (in minutes). WebCenter Portal automatically clears items that have changed from the cache. The <i>minimum</i> interval is 2 minutes.</p> <p>By default, cache invalidation is disabled (specified as 0) which means that no periodic checks are made for content changes.</p>

Argument	Definition
<code>binaryCacheMaxEntrySize</code>	<p>Optional. Maximum cacheable size (in bytes) for Content Server binary documents. Documents larger than this size are not cached by WebCenter Portal or Portal Framework applications.</p> <p>Defaults is 102400 bytes (100K).</p> <p>Tune this value based on your machine's memory configuration and the types of binary documents that you expect to cache.</p> <p>Most documents stored in Content Server are considered binary content, that is, images, plain text, Word documents, and so on. The only exception is Site Studio content which is stored in data files (CDF files) and cache separately in a Virtual Content Repository (VCR) cache (or node cache).</p>
<code>adminUsername</code>	<p>Optional. User name with administrative rights for this Content Server instance. This user will be used to fetch content type information based on profiles and track document changes for cache invalidation purpose.</p> <p>Defaults to <code>sysadmin</code>.</p>
<code>adminPassword</code>	<p>Optional. Password for the Content Server administrator specified in <code>adminUsername</code>. Required when <code>socketType</code> is set to <code>web</code>.</p>
<code>extAppId</code>	<p>Optional. External application used to authenticate users against the Content Server. This value should match the name of an existing external application connection. See also listExtAppConnections. If <code>extAppId</code> is not set, no change is made to the authentication method or external application ID.</p> <p>If <code>extAppId</code> is set to an empty string, the authentication method used is <code>IDENTITY_PROPAGATION</code>. With this method, the application and Content Server use the same identity store to authenticate users. Note that <code>extAppID</code> is mandatory when <code>socketType</code> is set to <code>web</code>.</p>
<code>timeout</code>	<p>Length of time allowed to log in to the Content Server (in ms) before issuing a connection timeout message, and the RIDC socket timeout used for all service requests for connection types <code>web</code>, <code>socket</code> and <code>socketssl</code>.</p> <p>If the timeout property is not set, the following values are used:</p> <ul style="list-style-type: none"> Login timeout - the default concurrency timeout for the <code>oracle.webcenter.content</code> resource is used (30s or 30000ms). Refer to "Configuring Concurrency Management" in <i>Oracle Fusion Middleware Performance and Tuning Guide</i> for more information. RIDC socket timeout - the default RIDC socket timeout (60s or 60000ms) is used for all service requests for connection types <code>socket</code>, <code>socketssl</code>, or <code>web</code>. <p>If the <code>timeout</code> property is set and the connection type is <code>socket</code>, <code>socketssl</code>, or <code>web</code>, Oracle recommends that you do not specify a value less than 60000ms as this would reduce the RIDC socket timeout and increase the likelihood that long running requests will time out. For example, timeouts may occur during long running searches, long file uploads, or long copy operations.</p>
<code>isPrimary</code>	<p>Optional. Valid string values are 1 (true) and 0 (false).</p> <p>1 specifies that this connection is the primary connection used for document services.</p> <p>This argument defaults to 0. When omitted or set to 0, the primary connection used for documents does not change.</p> <p>In WebCenter Portal, the primary connection is used to store portal-specific content and Home portal content.</p>

Argument	Definition
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <i>WC_Spaces</i> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.6.1.3 Examples

The following example creates a socket-based connection to an Oracle WebCenter Content repository running on *myhost.com* at port 4444. For authentication purposes, an existing external application named *myExtApp* is used. See also, [createExtAppConnection](#).

```
wls:/weblogic/serverConfig> createJCRContentServerConnection(appName='webcenter',
name='myContentServerConnection', socketType='socket',
serverHost='myhost.com', serverPort=4444, extAppId='myExtApp',
isPrimary=1)
```

The following example creates an SSL socket-based connection to an Oracle WebCenter Content repository.

```
wls:/weblogic/serverConfig> createJCRContentServerConnection(appName='webcenter',
name='myContentServerConnection', socketType='socketssl',
serverHost='myhost.com', serverPort=4444, keystoreLocation='d:/keys/here',
keystorePassword='AlphaSquad7',
privateKeyAlias='enigma', privateKeyPassword='S0larP13x1s',
extAppId='myExtApp')
```

The following example creates a JAX-WS (Java API for XML web services) connection to an Oracle WebCenter Content repository:

```
wls:/weblogic/serverConfig> createJCRContentServerConnection(appName='webcenter',
name='myContentServerConnection', socketType='jaxws',
url='http://myhost.com:9044/idcnativews', clientSecurityPolicy='oracle/wss10_saml_token_client_policy')
```

10.6.2 setJCRContentServerConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.6.2.1 Description

Edits an existing Oracle WebCenter Content repository connection. This command requires that you specify values for *appName* and *name*, plus one additional argument.

10.6.2.2 Syntax

```
setJCRContentServerConnection(appName, name, [socketType, url, serverHost,
serverPort, keystoreLocation, keystorePassword, privateKeyAlias,
privateKeyPassword, webContextRoot, clientSecurityPolicy,
cacheInvalidationInterval, binaryCacheMaxEntrySize, adminUsername, adminPassword,
extAppId, timeout, isPrimary, server, applicationVersion])
```


Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing Oracle WebCenter Content repository connection.
<i>socketType</i>	Optional. Specifies whether the Oracle WebCenter Content's Content Server connects on the content server listener port or the web server filter, and whether the listener port is SSL enabled. Valid values are <code>socket</code> , <code>web</code> , and <code>socketssl</code> . This option has no default. Choose from: <ul style="list-style-type: none"> ■ socket—Use an <code>intradoc</code> socket connection to connect to the Content Server. The client IP address must be added to the list of authorized addresses in the Content Server. In this case, the client is the machine on which Oracle WebCenter Portal is running. ■ socketssl—Use an <code>intradoc</code> socket connection to connect to the Content Server that is secured using the SSL protocol. The client's certificates must be imported in the server's trust store for the connection to be allowed. This is the most secure option, and the recommended option whenever identity propagation is required (for example, in WebCenter Portal). ■ web—Use an HTTP(S) connection to connect to the Content Server. Note that for WebCenter Portal, this option is not suitable for the active connection, that is, the back-end Content Server repository that is being used to store portal-specific documents and Home portal documents, because it does not allow identity propagation. ■ jaxws—Use a Java API for XML web services connection to connect to the Content Server.
<i>url</i>	Optional. Content Server URL. Required only if <code>socketType</code> is set to <code>web</code> or <code>jaxws</code> . URL should be in the format: <code>http://hostname:port/web_root/plugin_root</code> For example: <code>http://mycontentserver/cms/idcplg</code>
<i>serverHost</i>	Optional. Host name of the machine where the Content Server is running. Required if <code>socketType</code> is set to <code>socket</code> or <code>socketssl</code> .
<i>serverPort</i>	Optional. Port on which the Content Server listens. Required if <code>socketType</code> is set to <code>socket</code> or <code>socketssl</code> : <ul style="list-style-type: none"> ■ Socket—Port specified for the incoming provider in the server. ■ Socket SSL—Port specified for the <code>sslincoming</code> provider in the server. For example, <code>4444</code>
<i>keystoreLocation</i>	Optional. Location of key store that contains the private key used to sign the security assertions. Required only if <code>socketType</code> is set to <code>socketssl</code> . The key store location must be an absolute path.
<i>keystorePassword</i>	Optional. Password required to access the key store. Required only if <code>socketType</code> is set to <code>socketssl</code> .

Argument	Definition
<code>privateKeyAlias</code>	<p>Optional. Client private key alias in the key store. Required only if <code>socketType</code> is set to <code>socketssl</code>.</p> <p>The value for this argument must be a string that contains neither special characters nor white space.</p>
<code>privateKeyPassword</code>	<p>Optional. Password to be used with the private key alias in the key store. Required only if <code>socketType</code> is set to <code>socketssl</code>.</p>
<code>webContextRoot</code>	<p>Optional. Web server context root for the Content Server. Use the format <code><context_root></code>. For example, <code>/cs</code>.</p> <p>When specified, several Oracle WebCenter Content features based on <code>iFrame</code>, such as previewing files in a slide viewer, are available in WebCenter Portal or the Portal Framework application.</p> <p>Note: To fully enable these features you must access WebCenter Portal or the Portal Framework application through Oracle HTTPS Server (OHS) to expose Content Server and the application under the same host and port. In addition, both the application and the Content Server must use single sign on. For information about setting up OHS to front-end WebCenter Portal and Portal Framework applications, see "Configuring Content Server" in <i>Oracle Fusion Middleware Administering Oracle WebCenter Portal</i>.</p> <p><code>webContextRoot</code> is only applicable when <code>IDENTITY_PROPAGATION</code> is used for authentication, that is, when <code>extAppId</code> is set to an empty string.</p>
<code>clientSecurityPolicy</code>	<p>Optional. Client security policy to be used when the <code>socketType</code> is <code>jaxws</code>. For example: <code>oracle/wss11_saml_token_with_message_protection_service_policy</code></p> <p>Leave the field blank if your environment supports Global Policy Attachments (GPA).</p>
<code>cacheInvalidationInterval</code>	<p>Optional. Time between checks for external Content Server content changes (in minutes). WebCenter Portal automatically clears items that have changed from the cache. The <i>minimum</i> interval is 2 minutes.</p> <p>By default, cache invalidation is disabled (specified as 0) which means that no periodic checks are made for content changes.</p>
<code>binaryCacheMaxEntrySize</code>	<p>Optional. Maximum cacheable size (in bytes) for Content Server binary documents. Documents larger than this size are not cached by WebCenter Portal or the Portal Framework application. Defaults is 102400 bytes (100K).</p> <p>Tune this value based on your machine's memory configuration and the types of binary documents that you expect to cache.</p>
<code>adminUsername</code>	<p>Optional. User name with administrative rights for this Content Server instance. This user will be used to fetch content type information based on profiles and track document changes for cache invalidation purpose.</p> <p>Defaults to <code>sysadmin</code>.</p>
<code>adminPassword</code>	<p>Optional. Password for the Content Server administrator specified in <code>adminUsername</code>. Required when <code>socketType</code> is set to <code>web</code>.</p>
<code>extAppId</code>	<p>Optional. External application used to authenticate users against the Content Server. This value should match the name of an existing external application connection. See also listExtAppConnections. If <code>extAppId</code> is not set, no change is made to the authentication method or external application ID.</p> <p>If <code>extAppId</code> is set to an empty string, the authentication method used is <code>IDENTITY_PROPAGATION</code>. With this method, the application and Content Server use the same identity store to authenticate users.</p>

Argument	Definition
<i>timeout</i>	<p>Length of time allowed to log in to the Content Server (in ms) before issuing a connection timeout message, and the RIDC socket timeout used for all service requests for connection types <code>web</code>, <code>socket</code> and <code>socketssl</code>.</p> <p>If the timeout property is not set, the following values are used:</p> <ul style="list-style-type: none"> ■ Login timeout - the default concurrency timeout for the <code>oracle.webcenter.content</code> resource is used (30s or 30000ms). Refer to "Configuring Concurrency Management" in <i>Oracle Fusion Middleware Performance and Tuning Guide</i> for more information. ■ RIDC socket timeout - the default RIDC socket timeout (60s or 60000ms) is used for all service requests for connection types <code>socket</code>, <code>socketssl</code>, or <code>web</code>. <p>If the <code>timeout</code> property is set and the connection type is <code>socket</code>, <code>socketssl</code>, or <code>web</code>, Oracle recommends that you do not specify a value less than 60000ms as this would reduce the RIDC socket timeout and increase the likelihood that long running requests will time out. For example, timeouts may occur during long running searches, long file uploads, or long copy operations.</p>
<i>isPrimary</i>	<p>Optional. Valid string values are 1 (true) and 0 (false).</p> <p>1 specifies that this connection is the primary connection used for document services in the application.</p> <p>This argument defaults to 0. When omitted or set to 0, the primary connection used for documents does not change.</p> <p>In WebCenter Portal, the primary connection is used to store portal-specific content and Home portal content.</p>
<i>server</i>	<p>Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code>.</p> <p>Required when applications with the same name are deployed to different servers and also when you have a cluster.</p>
<i>applicationVersion</i>	<p>Optional. Version number of the deployed application. Required if more than one version of the application is deployed.</p>

10.6.2.3 Examples

The following example edits a socket-based connection to an Oracle WebCenter Content repository.

```
wls:/weblogic/serverConfig>setJCRContentServerConnection(appName='webcenter',
name='myContentServerConnection', socketType='socket',
serverHost='myhost.com', serverPort=4444,
extAppId='myExtApp', isPrimary=1)
```

The following example edits an SSL socket-based connection to an Oracle WebCenter Content repository.

```
wls:/weblogic/serverConfig>setJCRContentServerConnection(appName='webcenter',
name='myContentServerConnection', socketType='socketssl',
serverHost='myhost.com', serverPort=8443,
keystoreLocation='d:/keys/here', keystorePassword='T0PS3CR3T',
privateKeyAlias='TekJansen', privateKeyPassword='LadyNocturne',
extAppId='myExtApp', isPrimary=1)
```

The following example edits a JAX-WS (Java API for XML web services) connection to an Oracle WebCenter Content repository:

```
wls:/weblogic/serverConfig> setJCRContentServerConnection(appName='webcenter',
socketType='jaxws', url='http://myhost.com:9044/idcnativews',
clientSecurityPolicy='oracle/wss10_saml_token_client_policy')
```

10.6.3 listJCRContentServerConnections

Module: Oracle WebCenter Portal

Use with WLST: Online

10.6.3.1 Description

Without any arguments, this command lists all of the Oracle WebCenter Content repository connections that are configured for a named application.

10.6.3.2 Syntax

```
listJCRContentServerConnections(appName, [verbose, name, server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>verbose</i>	Optional. Displays content repository connection details in verbose mode. Valid options are 1 (true) and 0(false). When set to 1, <code>listJCRContentServerConnections</code> lists all Oracle WebCenter Content repository connections that are configured for the named application, along with their details. When set to 0, only connection names are listed. This argument defaults to 0.
<i>name</i>	Optional. Name of an existing Oracle WebCenter Content repository connection. When specified you can view connection details for a specific Oracle WebCenter Content repository connection. If you supply a value for <code>name</code> , you must supply a value for <code>verbose</code> .
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.6.3.3 Examples

The following example lists Oracle WebCenter Content repository connections configured for WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig> listJCRContentServerConnections(appName='webcenter')
```

The following example lists all properties of the Oracle WebCenter Content repository connection named `myContentServerConnection1`. The connection named `myContentServerConnection1` must exist and be an Oracle WebCenter Content repository connection. If, for example, you specify an Oracle Portal connection, the properties are not listed and an error displays.

```
wls:/weblogic/serverConfig>listJCRContentServerConnections (appName='webcenter',
verbose=1, name='myContentServerConnection1')
```

10.6.4 createJCRPortalConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.6.4.1 Description

Creates an Oracle Portal repository connection for a named application.

10.6.4.2 Syntax

```
createJCRPortalConnection(appName, name, dataSource, [extAppId, isPrimary,
timeout, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Connection name. The name must be unique (across all connection types) within the application.
<i>dataSource</i>	JNDI DataSource location used to connect to the portal. For example: <code>jdbc/MyPortalDS</code> The datasource must be on the server where the application is deployed.
<i>extAppId</i>	Optional. External application used to authenticate users against Oracle Portal. This value should match the name of an existing external application connection. See also listExtAppConnections . If <code>extAppId</code> is not set, no change is made to the authentication method or external application ID. If <code>extAppId</code> is set to an empty string, the authentication method used is <code>IDENTITY_PROPAGATION</code> . With this method, the application and Oracle Portal use the same identity store to authenticate users.
<i>timeout</i>	Optional. Length of time allowed to log in to Oracle Portal (in ms) before issuing a connection timeout message. If no timeout is set, the default concurrency timeout for the <code>oracle.webcenter.content</code> resource is used (30s or 30000ms). Refer to "Configuring Concurrency Management" in <i>Oracle Fusion Middleware Performance and Tuning Guide</i> for more information.
<i>isPrimary</i>	Optional. Valid string values are 1 (true) and 0 (false). 1 specifies that this connection is the primary connection used for document services in the application. This argument defaults to 0. When omitted or set to 0, the primary connection used for documents does not change. In WebCenter Portal, the primary connection must be an Oracle WebCenter Content repository connection.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.

Argument	Definition
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.6.4.3 Example

The following example creates a Oracle Portal connection named `myPortalConnection` using the data source `jdbc/portalDS` and specifies that an external application, named `myExtApp`, is used for authentication:

```
wls:/weblogic/serverConfig> createJCRPortalConnection(appName='myApp',
name='myPortalConnection', dataSource='jdbc/portalDS', extAppId='myExtApp',
isPrimary=1)
```

10.6.5 setJCRPortalConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.6.5.1 Description

Edits an existing Oracle Portal connection. This command requires that you specify values for either the `dataSource` or `isPrimary` argument.

10.6.5.2 Syntax

```
setJCRPortalConnection(appName, name, [dataSource, extAppId, timeout, isPrimary,
server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing Oracle Portal connection.
<i>dataSource</i>	Optional. JNDI DataSource location used to connect to the portal. For example: <code>jdbc/MyPortalDS</code> The datasource must be on the server where the application is deployed.
<i>extAppId</i>	Optional. External application used to authenticate users against Oracle Portal. This value should match the name of an existing external application connection. See also listExtAppConnections . If <code>extAppId</code> is not set, no change is made to the authentication method or external application ID. If <code>extAppId</code> is set to an empty string, the authentication method used is <code>IDENTITY_PROPAGATION</code> . With this method, the application and Oracle Portal use the same identity store to authenticate users.
<i>timeout</i>	Optional. Length of time allowed to log in to Oracle Portal (in ms) before issuing a connection timeout message. If no timeout is set, the default concurrency timeout for the <code>oracle.webcenter.content</code> resource is used (30s or 30000ms). Refer to "Configuring Concurrency Management" in <i>Oracle Fusion Middleware Performance and Tuning Guide</i> for more information.

Argument	Definition
<i>isPrimary</i>	Optional. Valid string values are 1 (true) and 0 (false). 1 specifies that this connection is the primary connection used for document services in the application. This argument defaults to 0. When omitted or set to 0, the primary connection used for documents does not change. In WebCenter Portal, the primary connection must be an Oracle WebCenter Content repository connection.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <i>WC_Spaces</i> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.6.5.3 Example

The following example edits Oracle Portal repository connection details:

```
wls:/weblogic/serverConfig> setJCRPortalConnection(appName='webcenter',
name='myPortalConnection', dataSource='/newPortalDS', extAppId='myExtApp',
isPrimary=0)
```

10.6.6 listJCRPortalConnections

Module: Oracle WebCenter Portal

Use with WLST: Online

10.6.6.1 Description

Without any arguments, this command lists all of the Oracle Portal connections that are configured for a named application.

10.6.6.2 Syntax

```
listJCRPortalConnections(appName, [verbose, name, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <i>webcenter</i> . For Portal Framework applications, specify the appropriate name.
<i>verbose</i>	Optional. Displays content repository connection details in verbose mode. Valid options are 1 (true) and 0 (false). When set to 1, <i>listJCRPortalConnections</i> lists all Oracle Portal connections that are configured for the application, along with their details. When set to 0, only connection names are listed. This argument defaults to 0.
<i>name</i>	Optional. Name of an existing Oracle Portal connection. When specified you can view connection details for a specific Oracle Portal connection. If you supply a value for <i>name</i> , you must supply a value for <i>verbose</i> .

Argument	Definition
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.6.6.3 Example

The following example lists all of the Oracle Portal connections that are configured for a WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig> listJCRPortalConnections (appName='webcenter',
verbose=1, name='myPortalConnection')
```

10.6.7 createJCRFileSystemConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.6.7.1 Description

Creates a connection to a file system repository.

Note: File system connections *must not* be used in production or enterprise application deployments. This feature is provided for development purposes only.

10.6.7.2 Syntax

```
createJCRFileSystemConnection(appName, name, path, [isPrimary, server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Connection name. The name must be unique (across all connection types) within the application.
<i>path</i>	Full path to a folder whose contents you want to expose through this file system connection. For example, if you have a folder called <code>C:\ProjectDocuments</code> and you want to expose content under that folder in your application, you need to specify this folder as the path argument to this command.

Argument	Definition
<i>isPrimary</i>	Optional. Valid values are 1 (true) and 0 (false). 1 specifies that this connection is the primary connection used for document services. When set to 0, and when the specified connection is the primary connection used for document services, the primary connection is reset. If this parameter is not set, the primary connection used for document services does not change. This argument has no default. In WebCenter Portal, the primary connection must be an Oracle WebCenter Content repository connection.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <i>WC_Spaces</i> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.6.7.3 Example

The following example creates a connection to a file system repository.

```
wls:/weblogic/serverConfig> createJCRFileSystemConnection(appName='webcenter',
name='FSACONNECTION', path='C:\\ProjectDocuments')
```

10.6.8 setJCRFileSystemConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.6.8.1 Description

Edits an existing file system repository connection. This command requires that you specify values for either the *path* or *isPrimary* arguments.

Note: File system connections *must not* be used in production or enterprise application deployments. This feature is provided for development purposes only.

10.6.8.2 Syntax

```
setJCRFileSystemConnection(appName, name, [path, isPrimary, server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <i>webcenter</i> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name for the connection to be used for document services.

Argument	Definition
<i>path</i>	<p>Full path to a folder whose contents you want to expose through this file system connection.</p> <p>For example, if you have a folder called <code>C:\ProjectDocuments</code> and you want to expose content under that folder in your application, you need to specify this folder as the <code>path</code> argument to this command.</p>
<i>isPrimary</i>	<p>Optional. Valid values are 1 (true) and 0 (false).</p> <p>1 specifies that this connection is the primary connection used for document services.</p> <p>When set to 0, and when the specified connection is the primary connection used for document services, the primary connection is reset. If this parameter is not set, the primary connection used for document services does not change. This argument has no default.</p> <p>In WebCenter Portal, the primary connection must be an Oracle WebCenter Content repository connection.</p>
<i>server</i>	<p>Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code>.</p> <p>Required when applications with the same name are deployed to different servers and also when you have a cluster.</p>
<i>applicationVersion</i>	<p>Optional. Version number of the deployed application. Required if more than one version of the application is deployed.</p>

10.6.8.3 Example

The following example edits connection details for a file system repository.

```
wls:/weblogic/serverConfig> setJCRFileSystemConnection(appName='webcenter',
name='FSACONNECTION', path='C:\\ProjectDocuments')
```

10.6.9 listJCRFileSystemConnections

Module: Oracle WebCenter Portal

Use with WLST: Online

10.6.9.1 Description

Without any arguments, this command lists all of the file system connections that are configured for a named application.

Note: File system connections *must not* be used in production or enterprise application deployments. This feature is provided for development purposes only.

10.6.9.2 Syntax

```
listJCRFileSystemConnections(appName, [verbose, name, server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	<p>Name of the application in which to perform this operation.</p> <p>For WebCenter Portal, the application name is always <code>webcenter</code>.</p> <p>For Portal Framework applications, specify the appropriate name.</p>

Argument	Definition
<i>verbose</i>	Optional. Displays content repository connection details in verbose mode. Valid options are 1 (true) and 0 (false). When set to 1, <code>listJCRFileSystemConnections</code> lists all file system connections that are configured for a named application, along with their details. When set to 0, only connection names are listed. This argument defaults to 0.
<i>name</i>	Optional. Name of an existing file system connection. When specified you can view connection details for a specific file system connection. If you supply a value for <i>name</i> , you must supply a value for <i>verbose</i> .
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.6.9.3 Examples

The following example lists all of the file system connections that are configured for WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig> listJCRFileSystemConnections (appName='webcenter')
```

The following example lists all of the file system connections that are configured, in verbose mode:

```
wls:/weblogic/serverConfig> listJCRFileSystemConnections (appName='webcenter', verbose=1)
```

10.6.10 createJCRSharePointConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.6.10.1 Description

Creates a connection to a Microsoft SharePoint 2007 repository for a named application.

10.6.10.2 Syntax

```
createJCRSharePointConnection(appName, name, url, [likeLimit, extAppId, timeout, isPrimary, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Connection name. The name must be unique (across all connection types) within the application.

Argument	Definition
<code>url</code>	<p>Web address of the SharePoint site to which you want to connect.</p> <p>For example, if the SharePoint site address is <code>http://mysharepoint.mycompany.com</code>, enter this value for the <code>url</code> argument.</p>
<code>likeLimit</code>	<p>Optional. Number of characters the <code>LIKE</code> operator matches. The default is 64.</p> <p>The SharePoint query language can use a <code>LIKE</code> keyword to constrain URL queries (document paths) that match a search pattern. By default, the <code>LIKE</code> operator supports a pattern match on strings up to 64 characters. Use this argument to specify a different character limit (any positive integer between 1 and 64) or enter <code>likeLimit=0</code> to disable the <code>LIKE</code> limit, that is, always send the full query string to the Microsoft SharePoint server.</p> <p>As Oracle recommends the default value (64), there is no need to specify this argument when you create a connection using the <code>WLST</code> command <code>createJCRSharePointConnection</code>.</p> <p>Note: Only specify a value above 64 if your SharePoint instance supports <code>LIKE</code> queries on URLs greater than 64 characters.</p>
<code>extAppId</code>	<p>Optional. External application used to authenticate users against the SharePoint repository. This value should match the name of an existing external application connection. See also <code>listExtAppConnections</code>.</p> <p>If <code>extAppId</code> is not set, the SharePoint repository connection will not work.</p> <p><code>extAppId</code> can be set or changed at any time using the <code>setJCRSharePointConnection</code> command.</p>
<code>timeout</code>	<p>Optional. Length of time allowed to log in to the SharePoint repository (in ms) before issuing a connection timeout message.</p> <p>If no timeout is set, the default concurrency timeout for the <code>oracle.webcenter.content</code> resource is used (30s or 30000ms). Refer to "Configuring Concurrency Management" in <i>Oracle Fusion Middleware Performance and Tuning Guide</i> for more information.</p>
<code>isPrimary</code>	<p>Optional. Valid values are 1 (true) and 0 (false).</p> <p>1 specifies that this connection is the primary connection used for document services.</p> <p>The argument defaults to 0. If this parameter is omitted, the primary connection used for document services does not change.</p> <p>In WebCenter Portal, the primary connection <i>must</i> be an Oracle WebCenter Content repository connection.</p>
<code>server</code>	<p>Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code>.</p> <p>Required when applications with the same name are deployed to different servers and also when you have a cluster.</p>
<code>applicationVersion</code>	<p>Optional. Version number of the deployed application. Required if more than one version of the application is deployed.</p>

10.6.10.3 Example

The following example creates a connection to a Microsoft SharePoint site.

```
wls:/weblogic/serverConfig> createJCRSharePointConnection(appName='webcenter',
name='MySPConnection', url='http://mysharepoint.mycompany.com',
extAppId='myExtApp')
```

10.6.11 setJCRSharePointConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.6.11.1 Description

Edits an existing Microsoft SharePoint 2007 repository connection. This command requires that you specify values for `appName` and `name`, plus at least one additional argument.

10.6.11.2 Syntax

```
setJCRSharePointConnection(appName, name, [url, likeLimit, extAppId, timeout,
isPrimary, server, applicationVersion])
```

Argument	Definition
<code>appName</code>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<code>name</code>	Name of an existing SharePoint connection.
<code>url</code>	Optional. Web address of the SharePoint site to which you want to connect. For example, if the SharePoint site address is <code>http://mysharepoint.mycompany.com</code> , enter this value for the <code>url</code> argument.
<code>likeLimit</code>	Optional. Number of characters the <code>LIKE</code> operator matches. The default is 64. The SharePoint query language can use a <code>LIKE</code> keyword to constrain URL queries (document paths) that match a search pattern. By default, the <code>LIKE</code> operator supports a pattern match on strings up to 64 characters. Use this argument to specify a different character limit (any positive integer between 1 and 64) or enter <code>likeLimit=0</code> to disable the <code>LIKE</code> limit, that is, always send the full query string to the Microsoft SharePoint server. Oracle recommends the default value (64). The default is suitable in most instances so, typically, there is no need to set a new value. To reset the default, specify <code>likeLimit=''</code> or <code>likeLimit=64</code> . Note: Only specify a value above 64 if your SharePoint instance supports <code>LIKE</code> queries on URLs greater than 64 characters.
<code>extAppId</code>	Optional. External application used to authenticate users against the SharePoint repository. This value should match the name of an existing external application connection. See also <code>listExtAppConnections</code> . If <code>extAppId</code> is not set, no change is made to the current external application ID. If no external application is set, the SharePoint connection will not work.
<code>timeout</code>	Optional. Length of time allowed to log in to the SharePoint repository (in ms) before issuing a connection timeout message. If no timeout is set, the default concurrency timeout for the <code>oracle.webcenter.content</code> resource is used (30s or 30000ms). Refer to "Configuring Concurrency Management" in <i>Oracle Fusion Middleware Performance and Tuning Guide</i> for more information.

Argument	Definition
<i>isPrimary</i>	Optional. Valid values are 1 (true) and 0 (false). 1 specifies that this connection is the primary connection used for documents services. When set to 0, and the specified connection is the primary connection used for document services, the primary connection is reset. If this parameter is not set, the primary connection used for documents does not change. This argument has no default. In WebCenter Portal, the primary connection <i>must</i> be an Oracle WebCenter Content repository connection.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.6.11.3 Example

The following example edits SharePoint repository connection details.

```
wls:/weblogic/serverConfig> setJCRSharePointConnection(appName='webcenter',
name='MySPConnection', url='http://mysharepoint.mycompany.com',
extAppId='myExtApp')
```

10.6.12 listJCRSharePointConnections

Module: Oracle WebCenter Portal

Use with WLST: Online

10.6.12.1 Description

Without any arguments, this command lists all of the SharePoint connections that are configured for a named application.

10.6.12.2 Syntax

```
listJCRSharePointConnections(appName, [verbose, name, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>verbose</i>	Optional. Displays SharePoint connection details in verbose mode. Valid options are 1 (true) and 0 (false). When set to 1, <code>listJCRSharePointConnections</code> lists all SharePoint connections that are configured for an application, along with their details. When set to 0, only connection names are listed. This argument defaults to 0.

Argument	Definition
<i>name</i>	Optional. Name of an existing SharePoint connection. When specified you can view connection details for a specific SharePoint connection. If you supply a value for <i>name</i> , you must supply a value for <i>verbose</i> .
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <i>WC_Spaces</i> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.6.12.3 Example

The following example lists the names of all the SharePoint connections that are configured for WebCenter Portal (*webcenter*):

```
wls:/weblogic/serverConfig> listJCRSharePointConnections(appName='webcenter')
```

The following example lists connection details for all of the SharePoint connections that are configured for WebCenter Portal (*webcenter*):

```
wls:/weblogic/serverConfig> listJCRSharePointConnections(appName='webcenter',
verbose=1)
```

10.6.13 listDocumentsSpacesProperties

Module: Oracle WebCenter Portal

Use with WLST: Online

10.6.13.1 Description

Lists properties for the back-end Oracle WebCenter Content repository that is being used by WebCenter Portal to store portal-specific documents and Home portal documents. This command is only valid for WebCenter Portal.

10.6.13.2 Syntax

```
listDocumentsSpacesProperties(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <i>webcenter</i> .
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <i>WC_Spaces</i> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.6.13.3 Example

The following example lists properties for the back-end Oracle WebCenter Content repository that is being used by a WebCenter Portal instance (*webcenter*) to store portal-specific documents and Home portal documents.

```
wls:/weblogic/serverConfig> listDocumentsSpacesProperties (appName='webcenter')
```

```
The Documents Spaces container is "/WebCenter1109"
The Documents repository administrator is "sysadmin"
The Documents Spaces container is "/WebCenter1109"
The Documents primary connection is "myOCSCONNECTION"
```

10.6.14 setDocumentsSpacesProperties

Module: Oracle WebCenter Portal

Use with WLST: Online

10.6.14.1 Description

Modifies properties for the back-end Oracle WebCenter Content repository that is being used by WebCenter Portal to store portal-related data. This command is only valid for WebCenter Portal.

10.6.14.2 Syntax

```
setDocumentsSpacesProperties(appName, [spacesRoot, adminUserName, applicationName,
server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> .
<i>spacesRoot</i>	Optional. Root folder under which WebCenter Portal content is stored. The value for this argument must use the format: <code>/<foldername></code> . For example, <code>/WebCenter</code> or <code>/WebCenterSpaces</code> . The <code>spacesRoot</code> cannot be <code>/</code> , the root itself, and it must be unique across applications. If the folder specified does not exist it will be created for you. Note that if you provide a value for this argument, you must also provide values for the <code>adminUserName</code> and <code>applicationName</code> arguments.
<i>adminUserName</i>	Optional. User name of the content repository administrator. For example: <code>sysadmin</code> . This user will be used to create and maintain folders for WebCenter Portal content and manage content access rights. Administrative privileges are required for this connection so that operations can be performed on behalf of WebCenter Portal users. Note that if you provide a value for this argument, you must also provide values for the <code>spacesRoot</code> and <code>applicationName</code> arguments.

Argument	Definition
<i>applicationName</i>	<p>Optional. Unique WebCenter Portal application identifier. This name is used to separate data when multiple WebCenter Portal applications share the same content repository, and must be unique across applications.</p> <p>The value for this argument must begin with an alphabetical character, followed by any combination of alphanumeric characters or the underscore character. The string must be less than or equal to 30 characters. Note that if you provide a value for this argument, you must also provide values for the <code>spacesRoot</code> and <code>adminUserName</code> arguments.</p> <p>The name specified here is also used to name document-related workflows, as follows:</p> <pre><applicationName><WorkflowName></pre> <pre><applicationName><WorkflowStepName></pre> <p>When naming workflows, only the first 14 characters of the Application Name are used.</p>
<i>server</i>	<p>Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code>.</p> <p>Required when applications with the same name are deployed to different servers and also when you have a cluster.</p>
<i>applicationVersion</i>	<p>Optional. Version number of the deployed application. Required if more than one version of the application is deployed.</p>

10.6.14.3 Examples

The following example modifies connection properties for the back-end Oracle WebCenter Content repository that is being used by WebCenter Portal to store portal-related documents:

```
wls:/weblogic/serverConfig> setDocumentsSpacesProperties(appName='webcenter',
spacesRoot='/AccountingSpaces', adminUserName='admin',
applicationName='WCAccounting')
```

The following example modifies the administrator's user name for the back-end Oracle WebCenter Content repository that is being used by WebCenter Portal to store portal-related documents:

```
wls:/weblogic/serverConfig> setDocumentsSpacesProperties(appName='webcenter',
adminUserName='sysadmin')
```

10.6.15 deleteDocumentsSpacesProperties

Module: Oracle WebCenter Portal

Use with WLST: Online

10.6.15.1 Description

Deletes properties for the back-end Oracle WebCenter Content repository used by WebCenter Portal, that is the `adminUserName`, `applicationName`, and `spacesRoot`. This command is only valid for WebCenter Portal.

10.6.15.2 Syntax

```
deleteDocumentsSpacesProperties(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> .
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.6.15.3 Example

The following example deletes connection properties (`adminUserName`, `applicationName`, `spacesRoot`) of the back-end Oracle WebCenter Content repository that is being used by WebCenter Portal:

```
wls:/weblogic/serverConfig> deleteDocumentsSpacesProperties (appName='webcenter')
```

10.7 Discussions and Announcements

Use the commands listed in [Table 10–8](#) to manage discussions server connections for WebCenter Portal and Portal Framework applications.

Configuration changes made using these WLST commands are only effective after your restart the Managed Server on which the application is deployed. For details, see *Oracle Fusion Middleware Administering Oracle WebCenter Portal*.

Table 10–8 Discussion and Announcement WLST Commands

Use this command...	To...	Use with WLST...
createDiscussionForumConnection	Create a new discussions server connection for a named application.	Online
setDiscussionForumConnection	Edit an existing discussions server connection.	Online
setDefaultDiscussionForumConnection	Specify the default connection for discussions and announcements.	Online
listDiscussionForumConnections	List all of the discussions server connections that are configured for a named application.	Online
listDefaultDiscussionForumConnection	List the default discussions server connection for a named application.	Online
setDiscussionForumConnectionProperty	Set an additional discussions server connection property.	Online
deleteDiscussionForumConnectionProperty	Delete a discussions server connection property.	Online
setDiscussionForumServiceProperty	Specify defaults for discussions.	Online
removeDiscussionForumServiceProperty	Remove defaults for discussions.	Online
listDiscussionForumServiceProperties	List discussions settings.	Online
setAnnouncementServiceProperty	Specify defaults for announcements.	Online
removeAnnouncementServiceProperty	Remove defaults for announcements.	Online

Table 10–8 (Cont.) Discussion and Announcement WLST Commands

Use this command...	To...	Use with WLST...
<code>listAnnouncementServiceProperties</code>	List announcements settings.	Online
<code>addDiscussionsServerAdmin</code>	Grant system administrator permissions on the discussions server to a user or a group.	Online
<code>addDiscussionsCategoryAdmin</code>	Grant category administrator permissions on the discussions server to a user or a group.	Online
<code>syncDiscussionServerPermissions</code>	Synchronizes discussion server permissions for subportals that inherit security from their parent.	Online
<code>setDiscussionsServerProperty</code>	Set discussions server properties.	Online
<code>getDiscussionsServerProperty</code>	Return discussions server property values.	Online
<code>removeDiscussionsServerProperty</code>	Remove current discussions server property values.	Online

10.7.1 createDiscussionForumConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.7.1.1 Description

Creates a new discussions server connection for a named application.

Discussions and announcements both require a discussions server connection. Discussions and announcements both use the same discussions server connection.

While you can register multiple discussions server connections for an application, only one connection is used for discussion and announcement services - the default (or active) connection.

10.7.1.2 Syntax

```
createDiscussionForumConnection(appName, name, url, adminUser,
[timeout, default, policyURIForAuthAccess, policyURIForPublicAccess,
recipientKeyAlias, server, applicationVersion])
```

Argument	Definition
<code>appName</code>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<code>name</code>	Connection name. The name must be unique (across all connection types) within the application.
<code>url</code>	URL of the discussions server hosting discussion forums and announcements. For example: <code>http://myhost:8888/owc_discussions</code> .

Argument	Definition
<i>adminUser</i>	<p>Name of the discussions server administrator. This account is used by discussions and announcements to perform administrative operations on behalf of WebCenter Portal users.</p> <p>This account is mostly used for managing discussions and announcements in the out-of-the-box <i>WebCenter Portal</i> application. It is not necessary for this user to be a <code>super admin</code>. However, the user must have administrative privileges on the current application root category for WebCenter Portal, that is, the category (on the discussions server) under which all portal-related discussions and announcements are stored.</p>
<i>policyURIForAuthenticatedAccess</i>	<p>Optional. URI to the SAML token based policy required for authenticated access to the discussions server web service.</p> <p>The client policy specified must be compatible with the service policy that is configured for the <code>OWCDiscussionsServiceAuthenticated</code> endpoint in the discussions server. Out-of-the-box, the default service policy is WSS 1.0 SAML Token Service Policy (<code>oracle/wss10_saml_token_service_policy</code>).</p> <p>Valid client policy values include:</p> <ul style="list-style-type: none"> ■ <code>oracle/wss10_saml_token_client_policy</code> (WSS 1.0 SAML Token Client Policy) ■ <code>oracle/wss11_saml_token_with_message_protection_client_policy</code> (WSS 1.1 SAML Token with Message Protection Client Policy) ■ GPA (Global Policy Attachment) - Use GPA if your environment supports Global Policy Attachments. In addition, ensure that the default policy is detached from the <code>OWCDiscussionsServiceAuthenticated</code> endpoint in the discussions server using the WLST command detachWebServicePolicy or Enterprise Manager. <p>See also "Managing Announcements and Discussions" in the <i>Oracle Fusion Middleware Administering Oracle WebCenter Portal</i>.</p>
<i>policyURIForPublicAccess</i>	<p>Optional. URI to the policy required to enforce message security and integrity for public access to the discussions server Web service.</p> <p>Default value is <code>oracle/no_authentication_client_policy</code>.</p> <p>The client policy specified must be compatible with the service policy that is configured for the <code>OWCDiscussionsServicePublic</code> endpoint in the discussions server. Out-of-the-box, a service policy is not configured for public access (<code>oracle/no_authentication_client_policy</code>).</p> <p>Valid client policy values include:</p> <ul style="list-style-type: none"> ■ <code>oracle/no_authentication_client_policy</code> (None) ■ <code>oracle/wss11_with_message_protection_client_policy</code> (WSS 1.1 Message Protection Client Policy) ■ GPA (Global Policy Attachment) - Use GPA if your environment supports Global Policy Attachments. In addition, you must ensure that the default policy attached to the <code>OWCDiscussionsServicePublic</code> endpoint in the discussions server is set to <code>oracle/no_authentication_service_policy</code>.

Argument	Definition
<i>recipientKeyAlias</i>	Optional. Recipient key alias to be used for message protected policies (applicable to the <code>OWCDiscussionsServicePublic</code> and <code>OWCDiscussionsServiceAuthenticated</code> endpoints). This is the alias to the certificate that contains the public key of the discussions server in the configured keystore. The default is null. See also "Configuring WS-Security" in the <i>Oracle Fusion Middleware Administering Oracle WebCenter Portal</i> .
<i>timeout</i>	Optional. Length of time (in seconds) discussions waits for a response from the discussions server before issuing a connection timeout message. This argument defaults to -1. When set to -1, the service default (10 seconds) applies.
<i>default</i>	Optional. Indicates that this connection is the default connection for discussions and announcements. Valid options are 1 (true) and 0 (false). When set to 1, discussions and announcements both use this connection. When set to 0, the connection is not used. The default is 0.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.7.1.3 Example

The following example creates a discussions server connection for WebCenter Portal:

```
wls:/weblogic/serverConfig>createDiscussionForumConnection(appName='webcenter',
name='MyDiscussionServer', url='http://myhost.com:8888/owc_discussions',
adminUser='admin', policyURIForAuthAccess='oracle/wss10_saml_token_client_policy',
default=0)
```

10.7.2 setDiscussionForumConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.7.2.1 Description

Edits an existing discussions server connection. Use this command to update connection attributes.

The connection is created using the [createDiscussionForumConnection](#) command.

10.7.2.2 Syntax

```
setDiscussionForumConnection(appName, name, [url, adminUser,
policyURIForAuthAccess, policyURIForPublicAccess, recipientKeyAlias, timeout,
default, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing discussions server connection.
<i>url</i>	Optional. URL to the discussions server.
<i>adminUser</i>	Optional. Name of the discussions server administrator. This account is used by discussions to perform administrative operations on behalf of WebCenter Portal users. This account is mostly used for managing discussions and announcements in the out-of-the-box <i>WebCenter Portal</i> application. It is not necessary for this user to be a <code>super admin</code> . However, the user must have administrative privileges on the current application root category for WebCenter Portal, that is, the category (on the discussions server) under which all portal-related discussions and announcements are stored.
<i>policyURIForAuthAccess</i>	Optional. URI to the SAML token based policy required for authenticated access to the discussions server web service. The client policy specified must be compatible with the service policy that is configured for the <code>OWCDiscussionsServiceAuthenticated</code> endpoint in the discussions server. Out-of-the-box, the default service policy is WSS 1.0 SAML Token Service Policy (<code>oracle/wss10_saml_token_service_policy</code>). Valid client policy values include: <ul style="list-style-type: none"> ▪ <code>oracle/wss10_saml_token_client_policy</code> (WSS 1.0 SAML Token Client Policy) ▪ <code>oracle/wss11_saml_token_with_message_protection_client_policy</code> (WSS 1.1 SAML Token with Message Protection Client Policy) ▪ GPA (Global Policy Attachment) - Use GPA if your environment supports Global Policy Attachments. In addition, ensure that the default policy is detached from the <code>OWCDiscussionsServiceAuthenticated</code> endpoint in the discussions server using the WLST command detachWebServicePolicy or Enterprise Manager. <p>See also "Managing Announcements and Discussions" in the <i>Oracle Fusion Middleware Administering Oracle WebCenter Portal</i>.</p>

Argument	Definition
<code>policyURIForPublicAccess</code>	<p>Optional. URI to the policy required to enforce message security and integrity for public access to the discussions server web service.</p> <p>Default value is <code>oracle/no_authentication_client_policy</code>.</p> <p>The client policy specified must be compatible with the service policy that is configured for the <code>OWCDiscussionsServicePublic</code> endpoint in the discussions server. Out-of-the-box, a service policy is not configured for public access (<code>oracle/no_authentication_client_policy</code>).</p> <p>Valid client values include:</p> <ul style="list-style-type: none"> ■ <code>oracle/no_authentication_client_policy</code> (None) ■ <code>oracle/wss11_with_message_protection_client_policy</code> (WSS 1.1 Message Protection Client Policy) ■ GPA (Global Policy Attachment) - Use GPA if your environment supports Global Policy Attachments. In addition, you must ensure that the default policy attached to the <code>OWCDiscussionsServicePublic</code> endpoint in the discussions server is set to <code>oracle/no_authentication_service_policy</code>.
<code>recipientKeyAlias</code>	<p>Optional. Recipient key alias to be used for message protected policies (applicable to the <code>OWCDiscussionsServicePublic</code> and <code>OWCDiscussionsServiceAuthenticated</code> endpoints). This is the alias to the certificate that contains the public key of the discussions server in the configured keystore. The default is null.</p> <p>See also "Configuring WS-Security" in the <i>Oracle Fusion Middleware Administering Oracle WebCenter Portal</i>.</p>
<code>timeout</code>	<p>Optional. Length of time (in seconds) discussions and announcements wait for a response from the discussions server before issuing a connection timeout message. This argument defaults to <code>-1</code>. When set to <code>-1</code>, the service default (10 seconds) applies.</p>
<code>default</code>	<p>Optional. Indicates that this connection is the default connection for discussions and announcements. Required only if more than one connection is defined.</p> <p>Valid options are <code>1</code> (true) and <code>0</code> (false). When set to <code>1</code>, discussions and announcements use this connection. When set to <code>0</code>, the connection is not used. The default is <code>0</code>.</p> <p>To specify that discussion and announcements use this connection, change the value from <code>0</code> to <code>1</code>.</p> <p>To disable this connection, use the removeDiscussionForumServiceProperty command:</p> <pre>removeDiscussionForumServiceProperty('appName='webcenter', property='selected.connection')</pre> <p>Note: While you can register multiple discussions server connections for an application, only one connection is used for discussions and announcements— the default (or active) connection.</p>
<code>server</code>	<p>Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code>.</p> <p>Required when applications with the same name are deployed to different servers and also when you have a cluster.</p>
<code>applicationVersion</code>	<p>Optional. Version number of the deployed application. Required if more than one version of the application is deployed.</p>

10.7.2.3 Example

The following example updates attributes for a secure discussions server connection named `MyDiscussionsServer`.

```
wls:/weblogic/serverConfig> setDiscussionForumConnection(appName='webcenter',
name='MyDiscussionServer', url='http://myhost.com:7786/owc_discussions',
adminUser='admin', policyURIForAuthAccess='oracle/wss10_saml_token_client_policy',
default=1)
```

10.7.3 setDiscussionForumConnectionProperty

Module: Oracle WebCenter Portal

Use with WLST: Online

10.7.3.1 Description

Sets a discussions server connection property. Use this command when additional parameters are required to connect to your discussions server.

This command provides an extensible way to add any connection property using a key and a value. (You are not limited to connection properties specified by [createDiscussionForumConnection](#) and [setDiscussionForumConnection](#).)

Note: Do not use the [setDiscussionForumConnectionProperty](#) to set connection properties available through [createDiscussionForumConnection](#) or [setDiscussionForumConnection](#). Attempting to do so, has no effect.

All known, additional connection properties are listed in [Table 10–9, "Additional Discussion Server Connection Properties"](#).

Table 10–9 Additional Discussion Server Connection Properties

Additional Connection Property	Description
<code>application.root.category.id</code>	(WebCenter Portal only) Application root category ID on the discussions server under which all discussion forums are stored. For example, if set to 3, then all forums are stored in the category with the ID 3.
<code>linkURL</code>	URL used to link users to the discussions server's Admin Console. Only required if it is different to the <code>url</code> argument specified using the createDiscussionForumConnection or setDiscussionForumConnection command. For example, when SSO or HTTPS is configured. Use the following format to specify an alternative public external URL: <code>protocol://host:port</code> For example: <code>http://example.com:7777</code>

10.7.3.2 Syntax

```
setDiscussionForumConnectionProperty(appName, name, key, value, [secure, server, applicationVersion])
```


Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing discussions server connection.
<i>key</i>	Name of the connection property. See also, Table 10–9, "Additional Discussion Server Connection Properties" .
<i>value</i>	Value for the property. Allows any property to be modified on the connection with a key and value.
<i>secure</i>	Optional. Indicates whether the property value must be stored securely using encryption. Valid options are 1 (true) and 0 (false). When 1, the value is encrypted. The default option is 0. Set to 1 if you are storing passwords.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.7.3.3 Example

The following example configures the category used to store discussion forums for a discussions server connection named `MyDiscussionServer`:

```
wls:/weblogic/serverConfig>setDiscussionForumConnectionProperty
(appName='webcenter', name='MyDiscussionServer',
key='application.root.category.id', value='3')
```

The following example configures an alternative, public external URL so users can access the discussions server's Admin Console:

```
wls:/weblogic/serverConfig>setDiscussionForumConnectionProperty
(appName='webcenter', name='MyDiscussionServer', key='linkURL',
value='http://example.com:7777')
```

The following example adds a custom discussions server connection property called `myProperty1` with a value `propertyValue1`:

```
wls:/weblogic/serverConfig>setDiscussionForumConnectionProperty
(appName='webcenter', name='MyDiscussionServer', key='myProperty1',
value='propertyValue1')
```

The following example adds a secured discussions server connection property called `securedProperty` with the value `secureValue`.

```
wls:/weblogic/serverConfig>setDiscussionForumConnectionProperty
(appName='webcenter', name='MyDiscussionServer', key='securedProperty',
value='secureValue', secure=1)
```

10.7.4 deleteDiscussionForumConnectionProperty

Module: Oracle WebCenter Portal

Use with WLST: Online

10.7.4.1 Description

Deletes a discussions server connection property. Take care when deleting connection properties because the connection may not work as expected if the configuration becomes invalid as a result.

This command can only delete *additional* connection properties added using the `setDiscussionForumConnectionProperty` command.

10.7.4.2 Syntax

```
deleteDiscussionForumConnectionProperty(appName, name, key, [server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing discussions server connection.
<i>key</i>	Name of the connection property you want to delete.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.7.4.3 Example

The following example deletes a discussions server connection property named `myProperty1`.

```
wls:/weblogic/serverConfig> deleteDiscussionForumConnectionProperty
(appName='webcenter', name='MyDiscussionServer', key='myProperty1')
```

10.7.5 listDiscussionForumConnections

Module: Oracle WebCenter Portal

Use with WLST: Online

10.7.5.1 Description

Lists all the discussions server connections that are configured for a named application.

10.7.5.2 Syntax

```
listDiscussionForumConnections(appName, [verbose, name, server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.

Argument	Definition
<i>verbose</i>	Optional. Valid options are 1 (true) and 0 (false) . When set to 1, <code>listDiscussionForumConnections</code> lists all of the discussions server connections that are configured for an application, along with their details. When set to 0, only connection names are listed. This argument defaults to 0.
<i>name</i>	Optional. Name of an existing discussions server connection. Use this argument to view connection details for a specific discussions server connection.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.7.5.3 Examples

The following example lists the names of all of the discussions server connections that are currently configured for WebCenter Portal:

```
wls:/weblogic/serverConfig>listDiscussionForumConnections (appName='webcenter')
```

The following example lists connection names and details for all of the discussions server connections currently configured for WebCenter Portal:

```
wls:/weblogic/serverConfig>listDiscussionForumConnections (appName='webcenter', verbose=1)
```

The following example lists connection details for a discussions server connection named `myDiscussionsServer`.

```
wls:/weblogic/serverConfig>listDiscussionForumConnections (appName='webcenter', name='myDiscussionsServer')
```

10.7.6 listDefaultDiscussionForumConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.7.6.1 Description

Names the discussions server connection that discussions and announcements service are using, in a named application. While you can register multiple discussions server connections for an application, discussions and announcements only uses one connection—known as the default (or active) connection.

10.7.6.2 Syntax

```
listDefaultDiscussionForumConnection (appName, [verbose, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>verbose</i>	Optional. Valid options are 1 (true) and 0 (false). When set to 1, the name and details of the discussions server connections are listed. When set to 0, only the connection name displays. This argument defaults to 0.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.7.6.3 Examples

The following example names the discussions server connection that discussions and announcements are using in WebCenter Portal:

```
wls:/weblogic/serverConfig>listDefaultDiscussionForumConnection(appName='webcenter')
```

The following example lists the name and details of the discussions server connection that discussions and announcements are using in WebCenter Portal:

```
wls:/weblogic/serverConfig>listDefaultDiscussionForumConnection(appName='webcenter', verbose=1)
```

10.7.7 setDefaultDiscussionForumConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.7.7.1 Description

Specifies the *default* discussions server connection for discussions and announcements in a named application.

While you can register multiple discussions server connections with an application, discussions and announcements only uses one connection—this is known as the default (or active) connection.

10.7.7.2 Syntax

```
setDefaultDiscussionForumConnection(appName, name, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing discussions server connection.

Argument	Definition
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.7.7.3 Example

The following example makes a connection named `myDiscussionServer` the default (or active) connection for discussions and announcements in WebCenter Portal:

```
wls:/weblogic/serverConfig> setDefaultDiscussionForumConnection
(appName='webcenter', name='myDiscussionServer')
```

10.7.8 setDiscussionForumServiceProperty

Module: Oracle WebCenter Portal

Use with WLST: Online

10.7.8.1 Description

Specifies default values for discussions, for a named application.

Configurable properties for discussions are listed in [Table 10–10, "Discussions - Configurable Properties"](#).

Table 10–10 Discussions - Configurable Properties

Configuration Property	Description
<i>topics.fetch.size</i>	Maximum number of topics fetched by discussions and displayed in the topics view.
<i>forums.fetch.size</i>	Maximum number of forums fetched by discussions and displayed in the forums view.
<i>recentTopics.fetch.size</i>	Maximum number of topics fetched by discussions and displayed in the recent topics view.
<i>watchedTopics.fetch.size</i>	Maximum number of topics fetched by discussions and displayed in the watched topics view.
<i>watchedForums.fetch.size</i>	Maximum number of forums fetched by discussions and displayed in the watched forums view.
<i>application.root.category.id</i>	Application root category ID on the discussions server under which all discussion forums are stored. For example, if set to 3, all forums are stored inside category 3.
<code>ForumGatewayManager.AUTO_START</code>	Communication through mail distribution lists can be published as discussion forum posts. This parameter starts or stops the gateway for this communication. For WebCenter Portal, the default value is 1, which means that as soon as you configure mail server settings through administration, the gateway starts. Set this to 0, and restart the managed server, to stop the gateway and disable this feature. For Portal Framework applications, the default value is 0. Set this to 1, and restart the managed server, to start the gateway and enable this feature.

10.7.8.2 Syntax

```
setDiscussionForumServiceProperty(appName, property, value, [server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>property</i>	Name of the configuration property.
<i>value</i>	Value for the property.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.7.8.3 Example

The following example changes the default number of topics displayed in topics view.

```
wls:/weblogic/serverConfig>setDiscussionForumServiceProperty
(appName='webcenter', property='topics.fetch.size', value='30')
```

10.7.9 removeDiscussionForumServiceProperty

Module: Oracle WebCenter Portal

Use with WLST: Online

10.7.9.1 Description

Removes the current value that is set for a discussions property. Use this command to remove any of the properties listed in [Table 10–10, "Discussions - Configurable Properties"](#).

Take care when using this command as removing values for these properties might cause unexpected behavior.

Note: Use this command syntax to disable the connection currently used for discussion and announcement services:

```
removeDiscussionForumServiceProperty('appName='webcenter', property='selected.connection')
```

This command forces the default connection argument to 0. See also, [setDiscussionForumConnection](#).

10.7.9.2 Syntax

```
removeDiscussionForumServiceProperty(appName, property, [server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>property</i>	Name of the configuration property.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.7.9.3 Example

The following example clears the current `topics.fetch.size` property for discussions in WebCenter Portal:

```
wls:/weblogic/serverConfig> removeDiscussionForumServiceProperty
(appName='webcenter', property='topics.fetch.size')
```

10.7.10 listDiscussionForumServiceProperties

Module: Oracle WebCenter Portal

Use with WLST: Online

10.7.10.1 Description

Lists all configurable properties for discussions.

10.7.10.2 Syntax

```
listDiscussionForumServiceProperties(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.7.10.3 Example

The following example lists configuration properties for discussions in WebCenter Portal:

```
wls:/weblogic/serverConfig>
listDiscussionForumServiceProperties(appName='webcenter')
```

10.7.11 setAnnouncementServiceProperty

Module: Oracle WebCenter Portal

Use with WLST: Online

10.7.11.1 Description

Specifies default values for announcements in a named application.

Configurable properties for announcements are listed in [Table 10-11](#), "Announcements - Configurable Properties".

Table 10-11 Announcements - Configurable Properties

Configuration Property	Description
<i>miniview.page_size</i>	Maximum number of announcements displayed in the announcements mini view.
<i>mainview.page_size</i>	Maximum number of announcements displayed in the announcements main view.
<i>linksview.page_size</i>	Maximum number of announcements displayed in the announcements links view.
<i>announcements.expiration.days</i>	Number of days that announcements display and remain editable.

10.7.11.2 Syntax

```
setAnnouncementServiceProperty(appName, property, value, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>property</i>	Name of the configuration property.
<i>value</i>	Property value.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.7.11.3 Example

The following example changes the default number of days that announcements display in WebCenter Portal:

```
wls:/weblogic/serverConfig>setAnnouncementServiceProperty(appName='webcenter',
property='announcements.expiration.days', value='21')
```

10.7.12 removeAnnouncementServiceProperty

Module: Oracle WebCenter Portal

Use with WLST: Online

10.7.12.1 Description

Removes the current value that is set for an announcements property. Use this command to remove any of the properties listed in [Table 10–11, "Announcements - Configurable Properties"](#).

Take care when using this command as removing values for these properties might cause unexpected behavior.

10.7.12.2 Syntax

```
removeAnnouncementServiceProperty(appName, property, [server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>property</i>	Name of the configuration property.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.7.12.3 Example

The following example clears the `announcements.expiration.days` property for announcements in WebCenter Portal:

```
wls:/weblogic/serverConfig>removeAnnouncementServiceProperty
(appName='webcenter', property='announcements.expiration.days')
```

10.7.13 listAnnouncementServiceProperties

Module: Oracle WebCenter Portal

Use with WLST: Online

10.7.13.1 Description

Lists all configurable properties for announcements, in a named application.

10.7.13.2 Syntax

```
listAnnouncementServiceProperties(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.

Argument	Definition
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.7.13.3 Example

The following example lists configuration properties for announcements in WebCenter Portal:

```
wls:/weblogic/serverConfig>listAnnouncementServiceProperties (appName='webcenter')
```

10.7.14 addDiscussionsServerAdmin

Module: Oracle WebCenter Portal

Use with WLST: Online

10.7.14.1 Description

Grants system administrator permissions on the discussions server to a user or a group. This command is useful when you connect the discussions server to a new identity store that does not contain any of the current administrators.

10.7.14.2 Syntax

```
addDiscussionsServerAdmin(appName, name, [type, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the discussions server application in which to perform this operation. For example, <code>owc_discussions</code> .
<i>name</i>	Name of the user or group to add as an administrator on the discussions server.
<i>type</i>	Optional. Identifies the type of identity. Valid values are <code>USER</code> and <code>GROUP</code> . The default value is <code>USER</code> .
<i>server</i>	Optional. Name of the managed server on which the application is deployed. For example, <code>WC_Collaboration</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.7.14.3 Example

The following example grants system administrator permissions on the discussions server to the user `weblogic`:

```
addDiscussionsServerAdmin(appName='owc_discussions', name='weblogic', type='USER')
```

The following example grants system administrator permissions on the discussions server to all users in the `Administrators` user group:

```
addDiscussionsServerAdmin(appName='owc_discussions', name='Administrators',
type='GROUP')
```

10.7.15 addDiscussionsCategoryAdmin

Module: Oracle WebCenter Portal

Use with WLST: Online

10.7.15.1 Description

Grants category administrator permissions on the discussions server to a user or a group for a specific category ID.

10.7.15.2 Syntax

```
addDiscussionsCategoryAdmin(appName, categoryId, name, [type, server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the discussions server application in which to perform this operation. For example, <i>owc_discussions</i> .
<i>categoryId</i>	The ID (number) of a category on the discussions server.
<i>name</i>	Name of the user or group to add as an administrator for the category on the discussions server.
<i>type</i>	Optional. Identifies the type of identity. Valid values are <i>USER</i> and <i>GROUP</i> . The default value is <i>USER</i> .
<i>server</i>	Optional. Name of the managed server on which the application is deployed. For example, <i>WC_Collaboration</i> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.7.15.3 Example

The following example grants category administrator permissions on the discussions server to the user *weblogic* for a category with an ID=2:

```
addDiscussionsCategoryAdmin(appName='owc_discussions', categoryId=2,
name='weblogic', type='USER')
```

The following example grants category administrator permissions on the discussions server to all users in the *Sales* user group for a category with an ID=2:

```
addDiscussionsCategoryAdmin(appName='owc_discussions', categoryId=2, name='Sales',
type='GROUP')
```

10.7.16 syncDiscussionServerPermissions

Module: Oracle WebCenter Portal

Use with WLST: Online

10.7.16.1 Description

(WebCenter Portal only) Synchronizes discussion server permissions for subportals that inherit security from their parent.

When you update discussions or announcement permissions for portal hierarchies in WebCenter Portal, the subportals do not automatically inherit the corresponding permission change on the discussions server. Therefore, whenever changes are made, you must run this command to synchronize discussions and announcement permissions within a portal hierarchy, such that subportals inherit the same discussions server permissions as their parent.

Note: To execute discussions server WLST commands, such as `syncDiscussionServerPermissions`, the user used to connect to the Admin Server must also have administrative privileges on the discussions server.

10.7.16.2 Syntax

```
syncDiscussionServerPermissions(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Optional. Name of the application in which to perform this operation. The default value is <code>webcenter</code> (the application name for WebCenter Portal).
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.7.16.3 Example

The following example synchronizes permissions for discussions and announcement in WebCenter Portal, that is, subportals inherit the same discussions server permissions as their parent:

```
wls:/weblogic/serverConfig> syncDiscussionServerPermissions (appName='webcenter')
```

10.7.17 setDiscussionsServerProperty

Module: Oracle WebCenter Portal

Use with WLST: Online

10.7.17.1 Description

Sets a discussions server property. Use this command to set a system property on the discussions server.

Note: To execute discussions server WLST commands, such as `setDiscussionsServerProperty`, the user used to connect to the Admin Server must also have administrative privileges on the discussions server.

10.7.17.2 Syntax

```
setDiscussionsServerProperty(appName, key, value, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the discussions server application in which to perform this operation. For example, <code>owc_discussions</code> .
<i>key</i>	Name of the discussions server property. For example, <code>owc_discussions.sso.mode</code> , <code>AuthFactory.className</code> , <code>UserManager.className</code> , <code>GroupManager.className</code> , <code>owc_discussions.setup.complete_11.1.1.2.0</code> , and so on.
<i>value</i>	Value for the discussions server property.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Collaboration</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.7.17.3 Example

The following example sets properties that configures the discussions server for SSO, where `example.com:8890/owc_discussions` is the base URL of the webtier on which the discussions server is deployed:

```
wls:/weblogic/serverConfig>setDiscussionsServerProperty(appName='owc_discussions',
key='owc_discussions.sso.mode', value='true')
```

```
wls:/weblogic/serverConfig>setDiscussionsServerProperty(appName='owc_discussions',
key='jiveURL', value='example.com:8890/owc_discussions')
```

10.7.18 getDiscussionsServerProperty

Module: Oracle WebCenter Portal

Use with WLST: Online

10.7.18.1 Description

Returns the current value of a discussions server property.

Note: To execute discussions server WLST commands, such as `getDiscussionsServerProperty`, the user used to connect to the Admin Server must also have administrative privileges on the discussions server.

10.7.18.2 Syntax

```
getDiscussionsServerProperty(appName, key, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the discussions server application in which to perform this operation. For example, <code>owc_discussions</code> .

Argument	Definition
<i>key</i>	Name of the discussions server property. For example, <code>owc_discussions.sso.mode</code> , <code>AuthFactory.className</code> , <code>UserManager.className</code> , <code>GroupManager.className</code> , <code>owc_discussions.setup.complete_11.1.1.2.0</code> , and so on.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Collaboration</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.7.18.3 Example

The following examples return the current value for some key discussions server properties:

```
wls:/weblogic/serverConfig>getDiscussionsServerProperty(appName='owc_discussions',
key='AuthFactory.className')
```

```
wls:/weblogic/serverConfig>getDiscussionsServerProperty(appName='owc_discussions',
key='UserManager.className')
```

```
wls:/weblogic/serverConfig>getDiscussionsServerProperty(appName='owc_discussions',
key='GroupManager.className')
```

```
wls:/weblogic/serverConfig>getDiscussionsServerProperty(appName='owc_discussions',
key='owc_discussions.setup.complete_11.1.1.2.0')
```

10.7.19 removeDiscussionsServerProperty

Module: Oracle WebCenter Portal

Use with WLST: Online

10.7.19.1 Description

Removes the current value that is set for a discussions server property.

Note: To execute discussions server WLST commands, such as `removeDiscussionsServerProperty`, the user used to connect to the Admin Server must also have administrative privileges on the discussion server.

10.7.19.2 Syntax

```
removeDiscussionsServerProperty(appName, key, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the discussions server application in which to perform this operation. For example, <code>owc_discussions</code> .

Argument	Definition
<i>key</i>	Name of the discussions server property. For example, <code>owc_discussions.sso.mode</code> , <code>AuthFactory.className</code> , <code>UserManager.className</code> , <code>GroupManager.className</code> , <code>owc_discussions.setup.complete_11.1.1.2.0</code> , and so on.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Collaboration</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.7.19.3 Example

The following example removes the current value for the 'SSO mode' property on the discussions server:

```
wls:/weblogic/serverConfig>removeDiscussionsServerProperty(appName='owc_discussions', key='owc_discussions.sso.mode')
```

10.8 External Applications

Use the commands listed in [Table 10–12](#) to manage external application connections for WebCenter Portal and Portal Framework applications.

Configuration changes made using these WLST commands are immediately available in the application, that is, you do not need to restart the managed server.

Table 10–12 External Application WLST Commands

Use this command...	To...	Use with WLST...
createExtAppConnection	Create an external application connection, for a named application.	Online
setExtAppConnection	Edit an existing external application connection.	Online
listExtAppConnections	List individual or all external applications that are configured for a named application.	Online
addExtAppField	Add another login field for a specific external application connection.	Online
setExtAppField	Edit the value and display-to-user setting for a specific external application login field.	Online
removeExtAppField	Remove an external application login field.	Online
addExtAppCredential	Specify shared or public credentials for an external application.	Online
setExtAppCredential	Edit shared or public credentials for an external application.	Online
removeExtAppCredential	Remove shared or public credentials currently configured for an external application.	Online

10.8.1 createExtAppConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.8.1.1 Description

Creates an external application connection for a named application.

10.8.1.2 Syntax

```
createExtAppConnection(appName, name, [displayName, url, authMethod,
userFieldName, pwdFieldName, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Connection name. The name must be unique (across all connection types) within WebCenter Portal or your Portal Framework application.
<i>displayName</i>	Optional. External application display name. A user friendly name for the external application that WebCenter Portal users will recognize. The display name must be unique across all external applications within WebCenter Portal or your Portal Framework application.
<i>url</i>	Optional. External application login URL. To determine an application's URL, navigate to the application's login page and note down the URL for that page. For example: <code>http://login.yahoo.com/config/login</code>
<i>authMethod</i>	Optional. Authentication mechanism used by the external application. Valid options are <code>GET</code> , <code>POST</code> , and <code>BASIC</code> . This argument defaults to <code>POST</code> .
<i>userFieldName</i>	Optional. Name that identifies the <i>user name</i> or <i>user ID</i> field on the external application's login form. To find this name, look at the HTML source for the login page. This argument does not specify user credentials. Mandatory if <code>authMethod</code> is <code>GET</code> or <code>POST</code> and a login <code>url</code> is specified. Not required if <code>BASIC</code> authentication method is selected.
<i>pwdFieldName</i>	Optional. Name that identifies the <i>password</i> field on the external application's login form. To find this name, look at the HTML source for the login page. This argument does not specify user credentials. Mandatory if <code>authMethod</code> is <code>GET</code> or <code>POST</code> and a login <code>url</code> is specified. Not required if <code>BASIC</code> authentication method is selected.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.8.1.3 Example

The following example creates a connection for an external application named `My Yahoo!`, in WebCenter Portal (`webcenter`).

```
wls:/weblogic/serverConfig> createExtAppConnection(appName='webcenter',
name='yahoo', displayName='My Yahoo!', url='http://login.yahoo.com/config/login',
```



```
authMethod='POST', userFieldName='login', pwdFieldName='password')
```

10.8.2 setExtAppConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.8.2.1 Description

Edits an existing external application connection.

10.8.2.2 Syntax

```
setExtAppConnection(appName, name, [displayName, url, authMethod,
userFieldName, pwdFieldName, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing external application connection.
<i>displayName</i>	Optional. External application display name. A user-friendly name for the external application that WebCenter Portal users will recognize. The display name must be unique across all external applications within WebCenter Portal or your Portal Framework application.
<i>url</i>	Optional. External application login URL. To determine an application's URL, navigate to the application's login page and note down the URL for that page.
<i>authMethod</i>	Optional. Authentication mechanism used by the external application. Valid options are <code>GET</code> , <code>POST</code> , and <code>BASIC</code> . This argument defaults to <code>POST</code> .
<i>userFieldName</i>	Optional. Name that identifies the <i>user name</i> or <i>user ID</i> field on the external application's login form. To find this name, look at the HTML source for the login page. This argument does not specify user credentials. Mandatory if <code>authMethod</code> is <code>GET</code> or <code>POST</code> and a login URL is specified but can be left blank if <code>BASIC</code> authentication method is selected.
<i>pwdFieldName</i>	Optional. Name that identifies the <i>password</i> field on the external application's login form. To find this name, look at the HTML source for the login page. This argument does not specify user credentials. Mandatory if <code>authMethod</code> is <code>GET</code> or <code>POST</code> , but can be left blank if <code>BASIC</code> authentication method is selected.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.8.2.3 Example

The following example updates the display name attribute for an external application named `yahoo`.

```
wls:/weblogic/serverConfig> setExtAppConnection(appName='webcenter',
name='yahoo', displayName='My Favorite Yahoo!')
```

10.8.3 listExtAppConnections

Module: Oracle WebCenter Portal

Use with WLST: Online

10.8.3.1 Description

When used with only the `appName` argument, this command lists the names of all the external applications currently configured for a named WebCenter Portal or your Portal Framework application.

10.8.3.2 Syntax

```
listExtAppConnections(appName, [verbose, name, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>verbose</i>	Optional. Displays external application details in verbose mode. Valid options are 1 (true) and 0 (false). When set to 1, <code>listExtAppConnections</code> lists all of the external applications that are configured for WebCenter Portal or your Portal Framework application, along with their details. When set to 0, <code>listExtAppConnections</code> lists only the names of the external applications. This argument defaults to 0. If you set this argument to 0, do not specify the name argument.
<i>name</i>	Optional. Name of an existing external application connection. You can use this argument to view details about a specific connection.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.8.3.3 Examples

The following example lists the names of all the external applications currently used by WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig> listExtAppConnections(appName='webcenter')
app1
app2
app3
```

The following example lists details for the external applications `app1`, `app2`, and `app3`.

```
wls:/weblogic/serverConfig> listExtAppConnections(appName='webcenter', verbose=1)
----
app1
----
Name: app1
Display Name: Application1
Login URL: http://app1
Authentication Method: POST
User Field Name: login
Password Field Name: passwd
Shared Credential: Disabled
Public Credential: Disabled
----
app2
----
Name: app2
Display Name: Application2
Login URL: http://app2
Authentication Method: POST
User Field Name: login
Password Field Name: passwd
Additional Fields: {Account1:1, Accout2:DefVal:0}
Shared Credential: Disabled
Public Credential: Enabled
----
app3
----
Name: app3
Display Name: Application3
Authentication Method: POST
Shared Credential: Enabled
Public Credential: Enabled
```

The following example lists details for external application app1 only.

```
wls:/weblogic/serverConfig> listExtAppConnections(appName='webcenter', verbose=1,
name='app1')
----
app1
----
Name: app1
Display Name: Application1
Login URL: http://app1
Authentication Method: POST
User Field Name: login
Password Field Name: passwd
Shared Credential: Disabled
Public Credential: Disabled
```

10.8.4 addExtAppField

Module: Oracle WebCenter Portal

Use with WLST: Online

10.8.4.1 Description

Adds another login field for a specific external application connection. For example, in addition to user name and password, an external application may require other login criteria such as `Host` and `MailAddress`.

Optionally, additional login fields can appear on the external application's login for a user to specify.

If you add another login field *and* the external application uses shared or public credentials, you can use the WLST commands `addExtAppCredential` and `setExtAppCredential` to update the shared/public credentials. See [Section 10.8.7, "addExtAppCredential"](#) and [Section 10.8.8, "setExtAppCredential"](#).

10.8.4.2 Syntax

```
addExtAppField(appName, name, fieldName, [fieldValue, displayToUser, server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing external application connection.
<i>fieldName</i>	Login field name. The name that identifies the field on the HTML login form. This field is not applicable if the application uses BASIC authentication.
<i>fieldValue</i>	Optional. Login field value. Enter a default value for the login field or leave blank for a user to specify. This argument is blank by default.
<i>displayToUser</i>	Optional. Specifies whether the login field displays on the external application's login screen. Valid options are 1 (true) and 0 (false). This argument defaults to 0. Note that if you set this argument to 0, you must specify the <code>fieldValue</code> .
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.8.4.3 Example

This example creates an additional field named `Account` with the default value `username.default.example` in an external application called `ABC`. This field will be displayed on `ABC`'s login screen.

```
wls:/weblogic/serverConfig> addExtAppField(appName='webcenter', name='ABC',
fieldName='Account', fieldValue='username.default.example', displayToUser=1)
```

10.8.5 setExtAppField

Module: Oracle WebCenter Portal

Use with WLST: Online

10.8.5.1 Description

Modifies the field value and display-to-user setting for one or more login fields currently configured for an external application. Either `fieldValue` or `displayToUser` must be specified along with the external application name and login field name. The `fieldValue` and `displayToUser` arguments are optional.

Using this command has implications on any shared or public credentials that you might have created for this external application. If you modify `displayToUser` to 1, you may also need to update existing shared user or public user credentials. See also [Section 10.8.8, "setExtAppCredential"](#).

10.8.5.2 Syntax

```
setExtAppField(appName, name, fieldName, [fieldValue, displayToUser, server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing external application connection.
<i>fieldName</i>	Name of an existing login field.
<i>fieldValue</i>	Optional. New or changed login field value. Enter a default value for the login field or leave blank for a user to specify. This argument is blank by default.
<i>displayToUser</i>	Optional. Specifies whether the login field displays on the external application's login screen. Valid options are 1 (true) and 0 (false). If set to 0, <code>fieldValue</code> must be specified.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.8.5.3 Example

The following example specifies a default value for a login field named `Account` and displays the field on the external application's credential provisioning screen:

```
wls:/weblogic/serverConfig> setExtAppField(appName='webcenter', name='ABC',
fieldName='Account', fieldValue='admin', displayToUser=1)
```

10.8.6 removeExtAppField

Module: Oracle WebCenter Portal

Use with WLST: Online

10.8.6.1 Description

Removes a login field from an external application connection.

This command has implications on any shared or public credentials that you may have created for this external application, that is, you may need to remove the login field from shared user or public user credentials.

You can use the `setExtAppCredential` command to remove a login field, if required. For example, external application `myApp` has an additional field called `Account` and public credentials were previously specified using:

```
addExtAppCredential(appName='webcenter', name='myApp', type='PUBLIC',
username='admin', password='mypublic.password', field='Account:admin@myhost.com')
```

If you remove the `Account` field, you can modify the credentials by running:

```
setExtAppCredential(appName='webcenter', name='myApp', type='PUBLIC',
username='admin', password='mypublic.password')
```

For details on using `setExtAppCredential`, see [Section 10.8.8, "setExtAppCredential"](#)

10.8.6.2 Syntax

```
removeExtAppField(appName, name, fieldName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Connection name.
<i>fieldName</i>	Login field that you want to remove.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.8.6.3 Example

The following example removes the additional login field named `Account` from an external application named `ABC`.

```
wls:/weblogic/serverConfig> removeExtAppField(appName='webcenter', name='ABC',
fieldName='Account')
```

10.8.7 addExtAppCredential

Module: Oracle WebCenter Portal

Use with WLST: Online

10.8.7.1 Description

Configures shared user or public user credentials for a specific external application.

When shared credentials are specified, every user accessing WebCenter Portal (or a Portal Framework application), is authenticated using the user name and password defined here. WebCenter Portal users are not presented with a login form.

Public users accessing this external application through WebCenter Portal (or the Portal Framework application) are logged in using the public credentials defined here.

If credentials already exists, a warning indicates that the `setExtAppCredential` command should be used instead.

10.8.7.2 Syntax

```
addExtAppCredential(appName, name, type, username, password, [field, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing external application connection.
<i>type</i>	Credential type. Valid values are <code>SHARED</code> and <code>PUBLIC</code> .
<i>username</i>	Name of the shared or public user.
<i>password</i>	Password for the shared or public user.
<i>field</i>	Optional. Additional login field value. Use the format <code>FieldName:FieldValue</code> , where <code>FieldName</code> names an additional login field configured with <code>displayToUser=1</code> .
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.8.7.3 Example

The following example specifies public credentials for an external application named ABC. The public user name is `mypublic.username`, the password is `mypublic.password`, and there is one additional field named `Account`.

```
wls:/weblogic/serverConfig> addExtAppCredential(appName='webcenter', name='ABC',
type='PUBLIC', username='mypublic.username', password='mypublic.password',
field='Account:username.example')
```

10.8.8 setExtAppCredential

Module: Oracle WebCenter Portal

Use with WLST: Online

10.8.8.1 Description

Modifies shared user or public user credentials currently configured for an external application. If the credential has already not been specified, then a warning indicates that `addExtAppCredential` needs to be used instead. See [Section 10.8.7, "addExtAppCredential"](#).

The arguments `username` and `password` are optional because `setExtAppCredential` only manipulates existing credentials. At least one of the parameters, `username`, `password` or `field`, must be specified.

You can use `setExtAppCredential` command to update passwords in systems that require changing passwords every few days.

10.8.8.2 Syntax

```
setExtAppCredential(appName, name, type, [username, password, field,
server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing external application connection.
<i>type</i>	Credential type. Valid values are <code>SHARED</code> and <code>PUBLIC</code> .
<i>username</i>	Optional. User name of the shared or public user.
<i>password</i>	Optional. Password for the shared or public user.
<i>field</i>	Optional. Additional login field value. Use the format <code>FieldName:FieldValue</code> , where <code>FieldName</code> names an additional login field configured with <code>displayToUser=1</code> .
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.8.8.3 Example

The following example changes the public user's login credentials for an external application named ABC.

```
wls:/weblogic/serverConfig> setExtAppCredential(appName='webcenter',name='ABC',
type='PUBLIC', username='username.example', password='password.example',
field='Account:username.example')
```

10.8.9 removeExtAppCredential

Module: Oracle WebCenter Portal

Use with WLST: Online

10.8.9.1 Description

Removes shared user or public user credentials currently configured for an external application.

If credentials do not exist, an error displays.

10.8.9.2 Syntax

```
removeExtAppCredential(appName, name, type, [server, applicationVersion])
```


Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing external application connection.
<i>type</i>	Credential type. Valid values are <code>SHARED</code> and <code>PUBLIC</code> .
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.8.9.3 Example

The following example removes shared credentials specified for an external application named ABC.

```
wls:/weblogic/serverConfig> removeExtAppCredential (appName='webcenter',
name='ABC', type='SHARED')
```

10.9 Instant Messaging and Presence

Use the commands listed in [Table 10–13](#), to manage instant messaging and presence server connections.

Configuration changes made using these WLST commands are only effective after your restart the Managed Server on which WebCenter Portal or your Portal Framework application is deployed. For details, see *Oracle Fusion Middleware Administering Oracle WebCenter Portal*.

Table 10–13 Instant Messaging and Presence WLST Commands

Use this command...	To...	Use with WLST...
createIMPConnection	Create a new instant messaging and presence server connection for a named application.	Online
setIMPConnection	Edit an existing instant messaging and presence server connection.	Online
setIMPConnectionProperty	Modify instant messaging and presence server connection properties.	Online
deleteIMPConnectionProperty	Delete an instant messaging and presence server connection property.	Online
listIMPAdapters	List which presence servers a named application supports.	Online
listIMPConnections	List all of the instant messaging and presence server connections that are configured for a named application.	Online
listDefaultIMPConnection	List the default instant messaging and presence server connection that is configured for a named application.	Online

Table 10–13 (Cont.) Instant Messaging and Presence WLST Commands

Use this command...	To...	Use with WLST...
setDefaultIMPConnection	Set a specified connection as the default instant messaging and presence server connection.	Online
setIMPServiceProperty	Specify defaults for instant messaging and presence.	Online
removeIMPServiceProperty	Remove defaults for instant messaging and presence.	Online
listIMPServiceProperties	List instant messaging and presence properties.	Online
createIMPExtAppConnection	Create an external application suitable for instant messaging and presence server connection.	Online

10.9.1 createIMPConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.9.1.1 Description

Creates an instant messaging and presence server connection for a named application.

Use the [listIMPAdapters](#) command to find out which types of instant messaging and presence servers are supported. Out-of-the-box, WebCenter Portal and Portal Framework applications support Microsoft Office Live Communications Server 2005 R2 (LCS), and Microsoft Office Communications Server 2007 SP1 (OCS), and Microsoft Lync 2010.

While you can register multiple presence server connections for WebCenter Portal or your own Portal Framework applications, only one connection is used for instant messaging and presence services—the default (or active) connection.

10.9.1.2 Syntax

```
createIMPConnection(appName, name, adapter, url, [appId, poolName,
userDomain, timeout, default, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal , the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Connection name. The name must be unique (across all connection types) within the application.
<i>adapter</i>	Adapter name. Specify the adapter that matches your instant messaging and presence server. Valid values are <code>LCS</code> and <code>OCS</code> . Choose <code>LCS</code> for Microsoft Live Communications Server 2005. Choose <code>OCS2007</code> for Microsoft Office Communications Server 2007 and Microsoft Lync.
<i>url</i>	URL of the sever hosting instant messaging and presence services. For example: <code>http://myocshost.com:8888</code>

Argument	Definition
<i>domain</i>	<p>Deprecated.</p> <p>Use the setIMPServiceProperty command to resolve IM addresses.</p>
<i>appId</i>	<p>Optional. External application associated with the presence server connection.</p> <p>If specified, external application credential information is used to authenticate users against the LCS, OCS, or Lync server. This argument is mandatory for LCS, OCS and Lync server connections.</p> <p>The external application you configure for instant messaging and presence services must use <code>authMethod=POST</code>, and specify an additional field with <code>fieldName='Account'</code> and <code>displaytoUser=1</code>. If an external application does not exist yet, use the WLST command createIMPExtAppConnection to create an external application that automatically has all the required additional fields.</p> <p>See also addExtAppField and setExtAppField.</p>
<i>poolName</i>	<p>Optional. Pool name that is required to create an LCS, OCS, or Lync connection. Refer to <i>Microsoft Live Communications Server, Microsoft Office Communications Server</i>, or Microsoft Lync Server documentation for details on pool names.</p> <p>This argument is mandatory for LCS, OCS, and Lync server connections.</p>
<i>userDomain</i>	<p>Optional. (OCS and Lync connections only.) Active Directory domain on the OCS/Lync server.</p> <p>This argument is mandatory for OCS/Lync server connections.</p>
<i>timeout</i>	<p>Optional. Length of time (in seconds) that instant messaging and presence waits for a response from the presence server before issuing a connection timeout message. This argument defaults to -1.</p> <p>When set to -1, the service default (10 seconds) applies.</p>
<i>default</i>	<p>Optional. Indicates whether this connection is the default connection for instant messaging and presence services.</p> <p>Valid values are 1 (true) and 0 (false). The default for this argument is 0.</p>
<i>server</i>	<p>Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code>.</p> <p>Required when applications with the same name are deployed to different servers and also when you have a cluster.</p>
<i>applicationVersion</i>	<p>Optional. Version number of the deployed application. Required if more than one version of the application is deployed.</p>

10.9.1.3 Examples

The following example creates an external application suitable for an instant messaging and presence server connection and then creates a connection named `myLCSPresenceServer` to a Microsoft Live Communications Server:

```
wls:/weblogic/serverConfig>createIMPExtApp(appName='webcenter', name='LCSExtApp',
displayName='IMP Ext App')
```

```
wls:/weblogic/serverConfig>createIMPConnection(appName='webcenter',
name='myLCSPresenceServer', adapter='LCS', url='http://mylcsHost.com/owc/lcs',
appId='LCSExtApp', poolName='pool1.myhost.com', timeout=60, default=1)
```

The following example creates an instant messaging and presence server connection to a Microsoft Office Communications Server named `myOCSPresenceServer`.

```
wls:/weblogic/serverConfig>createIMPConnection(appName='webcenter',
name='myOCSPresenceServer', adapter='OCS2007', url='http://myocshost.com/owc/ocs',
appId='OCSExtApp', userDomain='OCS', poolName='pool01.myocshost.com', timeout=60,
default=1)
```

The following example creates an instant messaging and presence server connection to a Microsoft Lync Server named `myLyncServer`.

```
wls:/weblogic/serverConfig>createIMPConnection(appName='webcenter',
name='myLyncServer', adapter='OCS2007',
url='http://mylynchost.com:8888' appId='LyncExtApp', userDomain='LYNC',
poolName='pool05.mylynchost.com', timeout=60, default=1))
```

10.9.2 setIMPConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.9.2.1 Description

Edits an existing instant messaging and presence server connection. Use this command to update connection attributes.

The connection is created using the [createIMPConnection](#) command.

10.9.2.2 Syntax

```
setIMPConnection(appName, name, [adapter, url, appId, poolName,
userDomain, timeout, default, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal , the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing presence server connection.
<i>adapter</i>	Optional. Adapter name. Specify the adapter that matches your instant messaging and presence server. Valid values are <code>LCS</code> , and <code>OCS2007</code> . Choose <code>LCS</code> for Microsoft Live Communications Server. Choose <code>OCS2007</code> for Microsoft Office Communications Server and Microsoft Lync Server.
<i>url</i>	Optional. URL of the server hosting instant messaging and presence services.
<i>domain</i>	Deprecated. Use the setIMPServiceProperty command to resolve IM addresses.

Argument	Definition
<i>appId</i>	<p>Optional. External application associated with the presence server connection.</p> <p>If specified, external application credential information is used to authenticate users against the LCS, OCS, or Lync server. This argument is mandatory for LCS, OCS and Lync server connections.</p> <p>The external application you configure for instant messaging and presence services must use <code>authMethod=POST</code>, and specify an additional field with <code>fieldName='Account'</code> and <code>displaytoUser=1</code>. If an external application does not exist yet, use the WLST command createIMPExtAppConnection to create an external application that automatically has all the required additional fields.</p> <p>See also addExtAppField and setExtAppField.</p>
<i>poolName</i>	<p>Optional. (LCS, OCS, and Lync) Pool name that is required to create an LCS, OCS, or Lync connection. Refer to <i>Microsoft Live Communications Server, Microsoft Office Communications Server</i> or Microsoft Lync Server documentation for details on pool names.</p> <p>This argument is mandatory for LCS, OCS, and Lync server connections.</p>
<i>userDomain</i>	<p>Optional. (OCS and Lync only.) Active Directory domain on the OCS server.</p> <p>This argument is mandatory for OCS/Lync server connections.</p>
<i>timeout</i>	<p>Optional. Length of time (in seconds) that instant messaging and presence waits for a response from the presence server before issuing a connection timeout message.</p> <p>This argument defaults to -1. When set to -1, the service default (10 seconds) applies.</p>
<i>default</i>	<p>Optional. Indicates whether this connection is the default connection for instant messaging and presence services. Valid values are 1 (true) and 0 (false). The default for this argument is 0.</p> <p>To specify that instant messaging and presence uses this connection, change the value from 0 to 1.</p> <p>To disable this connection, use the removeIMPServiceProperty command:</p> <pre>removeIMPServiceProperty('appName='webcenter', property='selected.connection')</pre> <p>While you can register multiple presence server connections for an application, only one connection is used for instant messaging and presence services—the default (or active) connection.</p>
<i>server</i>	<p>Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code>.</p> <p>Required when applications with the same name are deployed to different servers and also when you have a cluster.</p>
<i>applicationVersion</i>	<p>Optional. Version number of the deployed application. Required if more than one version of the application is deployed.</p>

10.9.2.3 Examples

The following example sets attributes on an existing instant messaging and presence server connection.

```
wls:/weblogic/serverConfig>setIMPConnection(appName='webcenter',
name='myOCSPresenceServer', adapter='OCS2007', url='http://myocshost.com/owc/ocs',
timeout=120, default=1)
```

The following example sets attributes on an existing instant messaging and presence server connection.

```
wls:/weblogic/serverConfig>setIMPConnection(appName='webcenter',
name='myLCSPresenceServer', adapter='LCS', url='http://mylcsHost.com/owc/lcs',
appId='LCSExtApp', poolName='pool3.myhost.com', default=0)
```

10.9.3 setIMPConnectionProperty

Module: Oracle WebCenter Portal

Use with WLST: Online

10.9.3.1 Description

Sets an instant messaging and presence server connection property. Use this command if additional parameters are required to connect to your presence server. This is an extensible way to add any connection property using a key and a value. (You are not limited to connection properties specified by [createIMPConnection](#) and [setIMPConnection](#).)

All known, additional connection properties are listed in [Table 10–14, "Additional Instant Messaging and Presence Connection Properties"](#).

Table 10–14 Additional Instant Messaging and Presence Connection Properties

Additional Connection Property	Description
<i>presence.url</i>	URL to the presence server. This must be supplied if presence is deployed on a separate server.
<i>contacts.url</i>	URL to the contact management service. This must be supplied if the contact management service is deployed on a separate server.
<i>call.url</i>	URL for the third-party call server. If no value is supplied, then this uses the same value as <i>base.connection.url</i> .
<i>call.method</i>	Supports values <i>sip</i> and <i>pstn</i> : When set to <i>sip</i> , the IMP service forwards the user's SIP address to the third-party call service. The third-party call service must decide on the routing of the call. When set to <i>pstn</i> , the user's phone number is based on the user's profile attribute (<i>BUSINESS_PHONE</i>). You can use the connection property <i>call.number.attribute</i> to change this default profile attribute (<i>BUSINESS_PHONE</i>) to any other attribute.
<i>call.domain</i>	The domain name of the <i>pstn</i> gateway. If no domain name is supplied, then this uses the domain value specified when the connection was created. Supply a domain name only when <i>call.method</i> is set to <i>pstn</i> .
<i>contact.number.attribute</i>	The attribute used to read users' phone numbers from the user profile. The default is <i>BUSINESS_PHONE</i> . Supply this attribute value only when <i>call.method</i> is set to <i>pstn</i> .

Table 10–14 (Cont.) Additional Instant Messaging and Presence Connection Properties

Additional Connection Property	Description
<i>primary.domain</i>	<p>If the WebCenter user identity is qualified with a domain (for example, john.doe@oracle.com), and if the presence server domain is different (for example, john.doe@example.com) then specify the primary domain oracle.com here.</p> <p>If the user identity is qualified with a domain and the presence server uses the same oracle.com domain, then it is not necessary that you specify the primary.domain.</p>

Note: Do not use the `setIMPConnectionProperty` to set connection properties available through `createIMPConnection` or `setIMPConnection`. Attempting to do so has no effect.

10.9.3.2 Syntax

```
setIMPConnectionProperty(appName, name, key, value, [secure, server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing presence server connection.
<i>key</i>	Name of the connection property. See Table 10–14, "Additional Instant Messaging and Presence Connection Properties".
<i>value</i>	Value for the property. Allows any property to be modified on the connection with a key and value.
<i>secure</i>	Optional. Indicates whether the property value must be stored securely using encryption. Valid options are 1 (true) and 0 (false). When 1, the value is encrypted. The default option is 0.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.9.3.3 Example

The following example adds a custom instant messaging and presence server connection property called `admin.user` with a default value `admin`:

```
wls:/weblogic/serverConfig>setIMPConnectionProperty(appName='webcenter',
name='MyLCSPresenceServer', key='admin.user', value='admin')
```

10.9.4 deleteIMPConnectionProperty

Module: Oracle WebCenter Portal

Use with WLST: Online

10.9.4.1 Description

Deletes an instant messaging and presence server connection property. Use caution when deleting connection properties because the connection might not work as expected if the configuration becomes invalid as a result.

This command can only delete *additional* connection properties added using the `setIMPConnectionProperty` command.

10.9.4.2 Syntax

```
deleteIMPConnectionProperty(appName, name, key, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing presence server connection.
<i>key</i>	Name of the connection property you want to delete.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.9.4.3 Example

The following example deletes an instant messaging and presence server connection property named `admin.user`.

```
wls:/weblogic/serverConfig>deleteIMPConnectionProperty(appName='webcenter',
name='MyLCSPresenceServer', key='admin.user')
```

10.9.5 listIMPAdapters

Module: Oracle WebCenter Portal

Use with WLST: Online

10.9.5.1 Description

Lists which types of instant messaging and presence servers Oracle WebCenter Portal supports. Out-of-the-box, WebCenter Portal and Portal Framework applications support Microsoft Live Communications Server 2005 R2 (LCS), Microsoft Office Communications Server 2007 SP1 (OCS) and Microsoft Lync 2010.

10.9.5.2 Syntax

```
listIMPAdapters()
```

10.9.5.3 Example

The following example lists which presence servers are supported:

```
wls:/weblogic/serverConfig>listIMPAdapters()
```


10.9.6 listIMPConnections

Module: Oracle WebCenter Portal

Use with WLST: Online

10.9.6.1 Description

Lists all of the instant messaging and presence server connections that are configured for a named application.

10.9.6.2 Syntax

```
listIMPConnections(appName,[verbose, name, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>verbose</i>	Optional. Displays presence server connection details in verbose mode. Valid values are 1 (true) and 0 (false). When set to 1, <code>listIMPConnections</code> lists all of the presence server connections that are configured for the named application, along with their details. When set to 0, only connection names are listed. This argument defaults to 0.
<i>name</i>	Optional. Name of an existing presence server connection. Use this argument to view connection details for a specific presence server connection. Note that if you use the <code>name</code> argument when <code>verbose</code> argument set to 1, the <code>verbose</code> argument is ignored.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.9.6.3 Examples

The following example lists all the instant messaging and presence server connections that are configured for WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig>listIMPConnections (appName='webcenter')
```

The following example lists all the instant messaging and presence server connections that are configured for WebCenter Portal in *verbose* mode:

```
wls:/weblogic/serverConfig>listIMPConnections (appName='webcenter', verbose=1)
```

The following example lists connection details for an instant messaging and presence server connections named `impConnection1`.

```
wls:/weblogic/serverConfig> listIMPConnections (appName='webcenter',  
name='impConnection1')
```

10.9.7 listDefaultIMPConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.9.7.1 Description

Lists the connection that instant messaging and presence is using, in a named application. While you can register multiple presence server connections for WebCenter Portal or your own Portal Framework applications, instant messaging and presence only uses one connection—the default (or active) connection.

If only one presence server connection is available, that connection is assumed to be the default connection.

10.9.7.2 Syntax

```
listDefaultIMPConnection(appName, verbose, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>verbose</i>	Optional. Displays the default presence server connection in verbose mode, if available. Valid options are 1 (true) and 0 (false). When set to 1, the name and details of the presence server connection are listed. When set to 0, only the connection name displays. This argument defaults to 0.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.9.7.3 Example

The following example lists the name and details of the connection that instant messaging and presence is using in WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig>listDefaultIMPConnection(appName='webcenter',
verbose=1)
```

10.9.8 setDefaultIMPConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.9.8.1 Description

Specifies the *default* connection for instant messaging and presence in a named application. While you can register multiple presence server connections with an application, instant messaging and presence only uses one connection—the default (or active) connection.

If only one presence server connection is available, that connection is assumed to be the default connection.

10.9.8.2 Syntax

```
setDefaultIMPConnection(appName, name, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing instant messaging and presence connection.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.9.8.3 Example

The following example makes a connection named `myPresenceServer` the default (or active) connection for instant messaging and presence in WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig>setDefaultIMPConnection (appName='webcenter',
name='myPresenceServer')
```

10.9.9 setIMPServiceProperty

Module: Oracle WebCenter Portal

Use with WLST: Online

10.9.9.1 Description

Specifies default values for instant messaging and presence.

Configurable properties for instant messaging and presence are listed in [Table 10–15, "Instant Messaging and Presence - Configurable Properties"](#).

Table 10–15 Instant Messaging and Presence - Configurable Properties

Configuration Property	Description
<i>selected.connection</i>	Connection used by instant messaging and presence.
<i>rtc.cache.time</i>	Cache timeout for instant messaging and presence data. The default is 60 seconds.

Table 10–15 (Cont.) Instant Messaging and Presence - Configurable Properties

Configuration Property	Description
<code>resolve.display.name.from.user.profile</code>	<p>Determines what to display if user display names are missing. When set to 0, and display name information is unavailable, only the user name displays in the application. When set to 1, and display name information is unavailable, display names are read from user profile data. Setting this option to 1 will impact performance. The default setting is 0.</p> <p>Display names are not mandatory in presence data. If WebCenter Portal or the Portal Framework application does not always provide display names by default and you consider this information important, set <code>resolve.display.name.from.user.profile</code> to 1 so that display names always display.</p>
<code>im.address.resolver.class</code>	<p>Resolver implementation used to map user names to IM addresses and IM addresses to user names.</p> <p>The default setting is <code>oracle.webcenter.collab.rtc.IMPAddressResolverImpl</code>. This implementation looks for IM addresses in the following places and in the order specified:</p> <ul style="list-style-type: none"> ■ User Preferences ■ User Credentials ■ User Profiles
<code>im.address.profile.attribute</code>	<p>User profile attribute used to determine a user's IM address. The default setting is <code>BUSINESS_EMAIL</code>.</p>

10.9.9.2 Syntax

```
setIMPServiceProperty(appName, property, value, [server, applicationVersion])
```

Argument	Definition
<code>appName</code>	<p>Name of the application in which to perform this operation.</p> <p>For WebCenter Portal, the application name is always <code>webcenter</code>.</p> <p>For Portal Framework applications, specify the appropriate name.</p>
<code>property</code>	Name of the configuration property.
<code>value</code>	Value for the property.
<code>server</code>	<p>Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code>.</p> <p>Required when applications with the same name are deployed to different servers and also when you have a cluster.</p>
<code>applicationVersion</code>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.9.9.3 Example

The following example changes the default cache timeout for instant messaging and presence data in WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig>setIMPServiceProperty(appName='webcenter',
property='rtc.cache.time', value='30')
```

10.9.10 removeIMPServiceProperty

Module: Oracle WebCenter Portal

Use with WLST: Online

10.9.10.1 Description

Removes the current value that is set for an instant messaging and presence property. Use this command to remove any of the properties listed in [Table 10–15, "Instant Messaging and Presence - Configurable Properties"](#).

Take care when using this command as removing values for these properties might cause unexpected behavior.

Note: Use this command syntax to disable the connection currently used by instant messaging and presence:

```
removeIMPServiceProperty('appName='webcenter',
property='selected.connection')
```

This command forces the default connection argument to 0. See also, [setIMPConnection](#).

10.9.10.2 Syntax

```
removeIMPServiceProperty(appName, property, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>property</i>	Name of the configuration property.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.9.10.3 Example

The following example clears the cache expiration value for instant messaging and presence in WebCenter Portal:

```
wls:/weblogic/serverConfig>removeIMPServiceProperty(appName='webcenter',
property='rtc.cache.time')
```

10.9.11 listIMPServiceProperties

Module: Oracle WebCenter Portal

Use with WLST: Online

10.9.11.1 Description

Lists all configurable properties for instant messaging and presence.

10.9.11.2 Syntax

```
listIMPServiceProperties(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.9.11.3 Example

The following example lists configuration properties for instant messaging and presence in WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig>listIMPServiceProperties(appName='webcenter')
```

10.9.12 createIMPExtAppConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.9.12.1 Description

Creates an external application suitable for instant messaging and presence server connections. The external application is configured with the required additional properties: `authMethod=POST`, and additional fields `fieldName='Account'` and `displaytoUser=1`.

10.9.12.2 Syntax

```
createIMPExtAppConnection(appName, name, [displayName, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Connection name. The name must be unique (across all connection types) within the application.
<i>displayName</i>	Optional. External application display name. A user friendly name for the application that users will recognize. The display name must be unique across all external applications within the application.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.

Argument	Definition
<code>applicationVersion</code>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.9.12.3 Example

The following example creates an external application named IMPxApp suitable for instant messaging and presence server connections:

```
wls:/weblogic/serverConfig>createIMPExtAppConnection(appName='webcenter',
name='IMPxApp', displayName='IMP Ext App')
```

10.10 Mail

Use the commands listed in [Table 10–16](#) to manage mail server connections for a named application.

You can register multiple mail server connections:

- **WebCenter Portal** supports multiple mail connections. The mail connection configured with `default=1` is the default connection for mail services in WebCenter Portal. All additional connections are offered as alternatives; WebCenter Portal users can choose which one they want to use through user preferences.
- **Portal Framework applications** only use one mail connection—the connection configured with `default=1`. Any additional connections are ignored.

Configuration changes made using these WLST commands are only effective after your restart the Managed Server on which the application is deployed. For details, see *Oracle Fusion Middleware Administering Oracle WebCenter Portal*.

Table 10–16 Mail WLST Commands

Use this command...	To...	Use with WLST...
<code>createMailConnection</code>	Create a mail server connection for a named application.	Online
<code>setMailConnection</code>	Edit an existing mail server connection.	Online
<code>setMailConnectionProperty</code>	Set mail server connection properties.	Online
<code>deleteMailConnectionProperty</code>	Delete a mail server connection property.	Online
<code>listMailConnections</code>	List all of the mail server connections that are configured for a named application.	Online
<code>listDefaultMailConnection</code>	List the default mail server connection that is configured for a named application.	Online
<code>setDefaultMailConnection</code>	Set a specified connection as the default mail server connection.	Online
<code>setMailServiceProperty</code>	Specify defaults for mail.	Online
<code>removeMailServiceProperty</code>	Remove defaults for mail.	Online
<code>listMailServiceProperties</code>	List properties for mail.	Online

Table 10–16 (Cont.) Mail WLST Commands

Use this command...	To...	Use with WLST...
<code>createMailExtApp</code>	Create an external application suitable for mail connections.	Online

10.10.1 createMailConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.10.1.1 Description

Creates a mail server connection for a named application.

WebCenter Portal and Portal Framework applications support the Microsoft Exchange Server or any mail server that supports IMAP4 and SMTP. The most important mail server connection attributes are: `imapHost`, `imapPort`, `imapSecured`, `smtpHost`, `smtpPort`, and `smtpSecured`

You can register multiple mail server connections:

- **WebCenter Portal** supports multiple mail connections. The mail connection configured with `default=1` is the default connection for mail services in WebCenter Portal. All additional connections are offered as alternatives; WebCenter Portal users can choose which one they want to use through user preferences.
- **Portal Framework applications** only use one mail connection—the connection configured with `default=1`. Any additional connections are ignored.

10.10.1.2 Syntax

```
createMailConnection(appName, name, [imapHost, imapPort, smtpHost, smtpPort,
imapSecured, smtpSecured, appId, timeout, default, server, applicationVersion])
```

Argument	Definition
<code>appName</code>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<code>name</code>	Connection name. The name must be unique (across all connection types) within the application.
<code>imapHost</code>	Optional. Host name of the machine on which the IMAP service is running.
<code>imapPort</code>	Optional. Port on which the IMAP service listens.
<code>smtpHost</code>	Optional. Host name of the machine where the SMTP service is running.
<code>smtpPort</code>	Optional. Port on which the SMTP service listens.
<code>imapSecured</code>	Optional. Specifies whether the mail server connection to the IMAP server is SSL-enabled. Valid values are 1 (true) and 0 (false) . The default for this argument is 0.

Argument	Definition
<i>smtpSecured</i>	Optional. Specifies whether the SMTP server is secured. Valid values are 1 (true) and 0 (false) . The default for this argument is 0.
<i>appId</i>	External application associated with the mail server connection. External application credential information is used to authenticate users against the IMAP and SMTP servers. The same credentials are supplied to authenticate the user on both the IMAP and SMTP servers. The external application you configure for mail must use <code>authMethod=POST</code> , and specify several additional login fields: <code>fieldName='Email Address' and displaytoUser=1</code> <code>fieldName='Your Name' and displaytoUser=1</code> <code>fieldName='Reply-To Address' and displaytoUser=1</code> If an external application does not exist yet, use the WLST command createMailExtApp to create an external application that automatically has all the required additional fields. See also createExtAppConnection .
<i>timeout</i>	Optional. Length of time (in seconds) that the mail waits to acquire a connection before terminating. This argument defaults to -1. When set to -1, the service default (10 seconds) applies.
<i>default</i>	Optional. Indicates whether this connection is the default connection for mail. Valid values are 1 (true) and 0 (false) . This argument defaults to 0. <ul style="list-style-type: none"> ▪ WebCenter Portal supports multiple mail connections. The mail connection configured with <code>default=1</code> is the default connection for mail services in WebCenter Portal. Additional connections, configured with <code>default=0</code>, are offered as alternatives; WebCenter Portal can choose which one they want to use through user preferences. ▪ Portal Framework applications only use one mail connection—the connection configured with <code>default=1</code>. Any additional connections are ignored.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.10.1.3 Examples

The following example creates an external application suitable for a mail server connection, and then creates a mail server connection named `myMailConnection` for WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig>createMailExtApp(appName='webcenter', name='extApp_Mail', displayName='Mail Ext App')
```

```
wls:/weblogic/serverConfig> reateMailConnection(appName='webcenter' ,
name='myMailConnection' , imapHost='myimaphost.com', imapPort=143 ,
smtpHost='mysmtphost.com' , smtpPort=25 , imapSecured=0, smtpSecured=0,
appId='extApp_Mail', timeout=60, default=1)
```

10.10.2 setMailConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.10.2.1 Description

Edits an existing mail connection. Use this command to update connection attributes.

The connection is created using the [createMailConnection](#) command.

(WebCenter Portal only.) This command enables you to set additional, optional, LDAP server attributes that cannot be set using `createMailConnection`. When LDAP details are defined, mail creates, edits, and deletes portal distribution lists in WebCenter Portal. Portal distribution lists are named after their portal (excluding non-java identifiers) and assigned a domain (derived from the `domain` attribute, for example, `@mycompany.com`). If LDAP details are not provided, portal distribution lists are not created or maintained. The mail server must be a *Microsoft Exchange Server*.

10.10.2.2 Syntax

```
setMailConnection(appName, name, [imapHost, imapPort, smtpHost, smtpPort,
imapSecured, smtpSecured, appId, default, ldapHost, ldapPort, ldapBaseDN,
ldapAdminUser, ldapAdminPassword, ldapSecured, domain, defaultUser, timeout,
server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing mail server connection.
<i>imapHost</i>	Optional. Host name of the machine on which the IMAP service is running.
<i>imapPort</i>	Optional. Port on which the IMAP service listens.
<i>smtpHost</i>	Optional. Host name of the machine where the SMTP service is running.
<i>smtpPort</i>	Optional. Port on which the SMTP service listens.
<i>imapSecured</i>	Optional. Specifies whether the connection to the IMAP server is secured (SSL-enabled). Valid values are 1 (true) and 0 (false). The default for this argument is 0.
<i>smtpSecured</i>	Optional. Specifies whether the connection to the SMTP server is secured (SSL-enabled). Valid values are 1 (true) and 0 (false). The default for this argument is 0.

Argument	Definition
<i>appId</i>	<p>Optional. External application associated with the mail server connection.</p> <p>External application credential information is used to authenticate users against the IMAP and SMTP servers. The same credentials are supplied to authenticate the user on both the IMAP and SMTP servers.</p> <p>The external application you configure for mail must use <code>authMethod=POST</code>, and specify several additional login fields:</p> <pre>fieldName='Email Address' and displaytoUser=1 fieldName='Your Name' and displaytoUser=1 fieldName='Reply-To Address' and displaytoUser=1</pre> <p>If an external application does not exist yet, use the WLST command createMailExtApp to create an external application that automatically has all the required additional fields.</p> <p>See also createExtAppConnection.</p>
<i>ldapHost</i>	Optional. Host name of the machine where the LDAP directory server is running.
<i>ldapPort</i>	Optional. Port on which the LDAP directory server listens.
<i>ldapBaseDN</i>	Optional. Base distinguished name for the LDAP schema. For example, <code>CN=Users, DC=oracle, DC=com</code> .
<i>ldapAdminUser</i>	Optional. User name of the LDAP directory server administrator. A valid administrator with privileges to make entries into the LDAP schema.
<i>ldapAdminPassword</i>	Optional. Password for the LDAP directory server administrator. This password will be stored in a secured store.
<i>ldapSecured</i>	<p>Optional. Specifies whether the connection to the LDAP server is secured (SSL enabled).</p> <p>Valid values are 1 (true) and 0 (false). The default for this argument is 0. Set this to 1 for all LDAP communications over SSL.</p>
<i>domain</i>	<p>Optional. Domain name appended to portal distribution lists.</p> <p>For example, if the domain attribute is set to <code>mycompany.com</code>, the Finance Project portal will maintain a distribution list named <code>FinanceProject@mycompany.com</code>.</p>
<i>defaultUser</i>	Optional. Comma-delimited list of user names to whom you want to grant moderation capabilities. These users become members of every portal distribution list that is created. The users specified must exist in the Base LDAP schema (specified in the <code>ldapBaseDN</code> argument).
<i>timeout</i>	<p>Optional. Length of time (in seconds) that mail waits to acquire a connection before terminating.</p> <p>This argument defaults to -1. When set to -1, the service default (10 seconds) applies.</p>

Argument	Definition
<i>default</i>	<p>Optional. Indicates whether this connection is the default (or active) connection for mail.</p> <p>Valid values are 1 (true) and 0 (false) . This argument defaults to 0. 1 specifies that this connection is the default connection for mail.</p> <ul style="list-style-type: none"> ▪ WebCenter Portal supports multiple mail connections. The mail connection configured with <code>default=1</code> is the default connection for mail services in WebCenter Portal. Additional connections, configured with <code>default=0</code>, are offered as alternatives; WebCenter Portal users can choose which one they want to use through user preferences. ▪ Portal Framework application only use one mail connection—the connection configured with <code>default=1</code>. Any additional connections are ignored. <p>A connection does not cease to be the default connection for mail if you change the <code>default</code> value from 0 to 1.</p> <p>To stop using a default connection, use the removeMailServiceProperty command as follows:</p> <pre>removeMailServiceProperty('appName='webcenter', property='selected.connection')</pre>
<i>server</i>	<p>Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code>.</p> <p>Required when applications with the same name are deployed to different servers and also when you have a cluster.</p>
<i>applicationVersion</i>	<p>Optional. Version number of the deployed application. Required if more than one version of the application is deployed.</p>

10.10.2.3 Examples

The following example sets individual attributes for a mail server connection configured for WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig>setMailConnection(appName='webcenter',
name='myMailConnection', imapHost='myimaphost.com', imapPort=143,
smtpHost='mysmtpHost.com' , smtpPort=25 , imapSecured=0, smtpSecured=0,
appId='extApp_Mail', timeout=60, default=1)
```

The following example sets individual attributes for a mail server connection:

```
wls:/weblogic/serverConfig>setMailConnection(appName='webcenter',
name='myMailConnection', imapPort=993, imapSecured=1, smtpPort=465 ,
smtpSecured=1)
```

The following example sets LDAP attributes for a mail server connection:

```
wls:/weblogic/serverConfig>setMailConnection(appName='webcenter',
name='myMailConnection', domain='mycompany.com', defaultUser='admin',
imapHost='myimaphost.com', imapPort=143, smtpHost='mysmtpHost.com',
imapSecured=0, smtpSecured=0, smtpPort=25, appId='extApp_Mail',
default=1, ldapHost='myldaphost.com', ldapPort=389,
ldapBaseDN='CN=Users,DC=exchange,DC=uk,DC=com', ldapAdminUser='administrator',
ldapAdminPassword='adminpswd', ldapSecured=0, timeout=60)
```

10.10.3 setMailConnectionProperty

Module: Oracle WebCenter Portal

Use with WLST: Online

10.10.3.1 Description

Sets a mail server connection property. Use this command if additional parameters are required to connect to your mail server. This is an extensible way to add any connection property using a key and a value. (You are not limited to connection properties specified by [createMailConnection](#) and [setMailConnection](#).)

All known, additional connection properties are listed in [Table 10–17, "Additional Mail Connection Properties"](#).

Table 10–17 Additional Mail Connection Properties

Additional Connection Property	Description
<code>charset</code>	Character set used on the connection. The default charset is UTF-8. To use a different character set, such as ISO-8859-1, set the <code>charset</code> connection property.
Various IMAP properties	Any valid IMAP connection property. For example, <code>mail.imap.connectionpoolsize</code> . A list of valid IMAP properties are listed in documentation for the <code>com.sun.mail.imap</code> package at: http://javamail.java.net/nonav/docs/api
Various SMTP properties	Any valid SMTP connection property. For example, <code>mail.smtp.timeout</code> . A list of valid SMTP properties are listed in the documentation for the <code>com.sun.mail.smtp</code> package at: http://javamail.java.net/nonav/docs/api

Note: Do not use the [setMailConnectionProperty](#) to set connection properties available through [createMailConnection](#) or [setMailConnection](#). Attempting to do so, has no effect.

10.10.3.2 Syntax

```
setMailConnectionProperty(appName, name, key, value, [secure, server, applicationVersion])
```

Argument	Definition
<code>appName</code>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<code>name</code>	Name of an existing mail server connection.
<code>key</code>	Name of the connection property.
<code>value</code>	Value for the property. Allows any property to be modified on the connection with a key and value.
<code>secure</code>	Optional. Indicates whether the property value must be stored securely using encryption. Valid options are 1 (true) and 0 (false). When 1, the value is encrypted. The default option is 0.
<code>server</code>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.

Argument	Definition
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.10.3.3 Example

The following example adds a custom mail server connection property called `myProperty1` with a default value `propertyValue1`:

```
wls:/weblogic/serverConfig> setMailConnectionProperty(appName='webcenter',
name='myMailServer', key='myProperty1', value='propertyValue1')
```

10.10.4 deleteMailConnectionProperty

Module: Oracle WebCenter Portal

Use with WLST: Online

10.10.4.1 Description

Deletes a mail server connection property. Take care when deleting connection properties because the connection may not work as expected if the configuration becomes invalid as a result.

This command can only delete *additional* connection properties added using the `setMailConnectionProperty` command.

10.10.4.2 Syntax

```
deleteMailConnectionProperty(appName, name, key, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing mail server connection.
<i>key</i>	Name of the connection property you want to delete.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.10.4.3 Example

The following example deletes a mail server connection property named `mailProperty1`:

```
wls:/weblogic/serverConfig> deleteMailConnectionProperty(appName='webcenter',
name='myMailServer', key='mailProperty1')
```

10.10.5 listMailConnections

Module: Oracle WebCenter Portal

Use with WLST: Online

10.10.5.1 Description

Lists all of the mail server connections that are configured for a named application.

10.10.5.2 Syntax

```
listMailConnection(appName, [verbose, name, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>verbose</i>	Optional. Displays mail server connection details in verbose mode. Valid options are 1 (true) and 0 (false). When set to 1, <code>listMailConnections</code> lists all of the mail server connections that are configured for an application, along with their details. When set to 0, only connection names are listed. This argument defaults to 0.
<i>name</i>	Optional. Name of an existing mail server connection. Use this argument to view connection details for a specific mail server connection.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.10.5.3 Example

The following example lists the names of mail server connections that are currently configured for WebCenter Portal:

```
wls:/weblogic/serverConfig>listMailConnections (appName='webcenter')
```

The following example lists connection names and details for all of the mail server connections that are currently configured for WebCenter Portal:

```
wls:/weblogic/serverConfig>listMailConnections (appName='webcenter', verbose=1)
```

The following example lists connection details for a mail server connection named `mailConnection1`:

```
wls:/weblogic/serverConfig>listMailConnections (appName='webcenter',  
name='mailConnection1')
```

10.10.6 listDefaultMailConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.10.6.1 Description

Lists the default mail server connection that mail is using in a named application.

You can register multiple mail server connections but there can only be one default connection:

- **WebCenter Portal** supports multiple mail connections. The mail connection configured with `default=1` is the default connection for mail services in WebCenter Portal. All additional connections are offered as alternatives; WebCenter Portal users can choose which one they want to use through user preferences.
- **Portal Framework applications** only use one mail connection—the connection configured with `default=1`. Any additional connections are ignored.

10.10.6.2 Syntax

```
listDefaultMailConnection(appName,[verbose, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>verbose</i>	Optional. Displays the default mail server connection in verbose mode, if available. Valid options are 1 (true) and 0 (false). When set to 1, the name and details of the mail server connection are listed. When set to 0, only the connection name displays. This argument defaults to 0.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.10.6.3 Example

The following example lists the name and details of the mail server connection that mail is using in WebCenter Portal:

```
wls:/weblogic/serverConfig>listDefaultMailConnection(appName='webcenter',
verbose=1)
```

10.10.7 setDefaultMailConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.10.7.1 Description

Specifies the *default* mail server connection for mail in a named application.

You can register multiple mail server connections but there can only be one default connection:

- **WebCenter Portal** supports multiple mail connections. The mail connection configured with `default=1` is the default connection for mail services in WebCenter Portal. All additional connections are offered as alternatives; WebCenter Portal users can choose which one they want to use through user preferences.
- **Portal Framework applications** only use one mail connection—the connection configured with `default=1`. Any additional connections are ignored.

10.10.7.2 Syntax

```
setDefaultMailConnection(appName, name, [server, applicationVersion])
```

Argument	Description
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing mail connection.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.10.7.3 Example

The following example configures mail to use a connection named `myMailServer` for the default connection in WebCenter Portal:

```
wls:/weblogic/serverConfig>setDefaultMailConnection(appName='webcenter',
name='myMailServer')
```

10.10.8 setMailServiceProperty

Module: Oracle WebCenter Portal

Use with WLST: Online

10.10.8.1 Description

Specifies default values for mail.

Configurable properties for mail are listed in [Table 10–18, "Mail - Configurable Properties"](#).

Table 10–18 Mail - Configurable Properties

Configuration Property	Description
<i>address.delimiter</i>	Defines the delimiter that is used to separate multiple mail addresses. A comma is used by default. Some mail servers require mail addresses in the form <code>lastname, firstname</code> and, in such cases, a semi-colon is required.

Table 10–18 (Cont.) Mail - Configurable Properties

Configuration Property	Description
<code>mail.emailgateway.polling.frequency</code>	<p>The frequency, in seconds, that portal distribution lists are checked for new incoming emails. The default is 1800 seconds (30 minutes).</p> <p>Email communication through portal distribution lists can be published as discussion forum posts on a discussions server. For details, see "Publishing Portal Mail in a Discussion Forum" in <i>Oracle Fusion Middleware Building Portals with Oracle WebCenter Portal</i>.</p>
<code>mail.messages.fetch.size</code>	Maximum number of messages displayed in mail inboxes.
<code>resolve.email.address.to.name</code>	<p>Determines whether user email addresses are resolved to WebCenter Portal user names when LDAP is configured. Valid values are 1 (true) and 0 (false). The default value is 0.</p> <p>When set to 1, WebCenter Portal user names display instead of email addresses in mail task flows.</p> <p>Set this property to 1 if the instant messaging and presence requires user names to obtain presence status because presence information cannot be obtained when mail provides email addresses. Setting this value to 1 does impact application performance so you must take this into consideration when setting this property.</p>
<code>mail.recipient.limit</code>	Restricts the number of recipients to a message. For example, setting this value to '500' limits the number of recipients to 500.

10.10.8.2 Syntax

```
setMailServiceProperty(appName, property, value, [server, applicationVersion])
```

Argument	Definition
<code>appName</code>	<p>Name of the application in which to perform this operation.</p> <p>For WebCenter Portal, the application name is always <code>webcenter</code>.</p> <p>For Portal Framework applications, specify the appropriate name.</p>
<code>property</code>	Name of the configuration property
<code>value</code>	Value for the property.
<code>server</code>	<p>Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code>.</p> <p>Required when applications with the same name are deployed to different servers and also when you have a cluster.</p>
<code>applicationVersion</code>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.10.8.3 Example

The following example increases the default number of messages displayed in mail inboxes to 100, in WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig>setMailServiceProperty (appName='webcenter',
property='mail.messages.fetch.size', value='100')
```

10.10.9 removeMailServiceProperty

Module: Oracle WebCenter Portal

Use with WLST: Online

10.10.9.1 Description

Removes the current value that is set for a mail property. Use this command to remove any of the properties listed in [Table 10–18, "Mail - Configurable Properties"](#).

Take care when using this command as removing values for these properties might cause unexpected behavior.

Note: Use this command syntax to stop mail from using the current default connection:

```
removeMailServiceProperty('appName='webcenter',
property='selected.connection')
```

This command forces the default connection argument to 0. See also, [setMailConnection](#).

10.10.9.2 Syntax

```
removeMailServiceProperty(appName, property, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>property</i>	Name of the configuration property.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.10.9.3 Example

The following example clears the current `mail.messages.fetch.size` setting for mail, in WebCenter Portal:

```
wls:/weblogic/serverConfig>removeMailServiceProperty(appName='webcenter',
property='mail.messages.fetch.size')
```

10.10.10 listMailServiceProperties

Module: Oracle WebCenter Portal

Use with WLST: Online

10.10.10.1 Description

Lists all configurable properties for mail.

10.10.10.2 Syntax

```
listMailServiceProperties(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.10.10.3 Example

The following example lists configurable properties for mail in WebCenter Portal:

```
wls:/weblogic/serverConfig>listMailServiceProperties(appName='webcenter')
```

10.10.11 createMailExtApp

Module: Oracle WebCenter Portal

Use with WLST: Online

10.10.11.1 Description

Creates an external application suitable for mail server connections. The external application is configured with all the required additional properties:

`authMethod=POST`, and specify several additional login fields:

`fieldName='Email Address' and displaytoUser=1`

`fieldName='Your Name' and displaytoUser=1`

`fieldName='Reply-To Address' and displaytoUser=1`

10.10.11.2 Syntax

```
createMailExtAppConnection(appName, name, [displayName, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Connection name. The name must be unique (across all connection types) within the application.
<i>displayName</i>	Optional. External application display name. A user friendly name for the external application that portal users will recognize. The display name must be unique across all external applications within the application.

Argument	Definition
<code>server</code>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<code>applicationVersion</code>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.10.11.3 Example

The following example creates an external application named `MailxApp` suitable for mail server connections.

```
wls:/weblogic/serverConfig>createMailExtAppConnection(appName='webcenter',
name='MailxApp', displayName='Mail Ext App')
```

10.11 Notifications

Use the commands listed in [Table 10–19](#) to manage settings for the notifications in a named application.

Configuration changes made using these WLST commands are only effective after you restart the Managed Server on which the application is deployed. For details, see *Oracle Fusion Middleware Administering Oracle WebCenter Portal*.

Table 10–19 Notifications WLST Commands

Use this command...	To...	Use with WLST...
<code>setNotificationsConfig</code>	Specify the connection used for routing notifications raised in a named application.	Online
<code>getNotificationsConfig</code>	Return details about the connection that is used to send notifications raised in a named application.	Online

10.11.1 setNotificationsConfig

Module: Oracle WebCenter Portal

Use with WLST: Online

10.11.1.1 Description

Specifies the connection used for routing notifications raised in a named application.

Use an existing mail server or BPEL server connection. If the application is connected to a BPEL server, the Oracle User Messaging Service (UMS) is available for routing notifications through multiple messaging channels, including mail, worklists, and SMS. If you configure notifications to use a BPEL server connection, you may specify a sender 'From' address for each available messaging channel. That is, you can specify a sender mail address and an SMS address.

Alternatively, you can route notification messages through a mail server. If you configure notifications to use a mail server connection, the external application associated with the mail server connection must contain shared credentials. Shared credentials are required for routing application-wide notifications.

10.11.1.2 Syntax

```
setNotificationsConfig(appName, type, name, [senderMailAddress, senderSMSAddress,
server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>type</i>	Type of connection used to send notifications. Valid values are <code>MAIL</code> and <code>BPEL</code> .
<i>name</i>	Name of an <i>existing</i> connection. Consider the following: <ul style="list-style-type: none"> ■ Mail server connection—The external application associated with the mail server connection must contain shared credentials. ■ BPEL server connection—Oracle User Messaging Service (UMS) must be available on the BPEL server.
<i>senderMailAddress</i>	Optional. Mail address from which all mail notifications are sent. Use the format: <code><email_alias><<email_address>> or <email address></code> . For example, <code>WebCenter Notification<notifications@webcenter.com> or notifications@webcenter.com</code> . This argument applies to notifications routed through BPEL servers. When a BPEL server is used and UMS is configured with multiple email drivers, this address is also used to identify the appropriate email driver. When a mail server is used, the "From Address" is the same user that is specified for the associated external application's shared credentials.
<i>senderSMSAddress</i>	Optional. SMS number from which all SMS notifications are sent. Typically, the SMS address format is a 4-6 digit number (without -, spaces, or any other characters). For example, <code>28734</code> . This argument applies to notifications routed through BPEL servers. When a BPEL server is used and UMS is configured with multiple SMS drivers, this address is also used to identify the appropriate SMS driver.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.11.1.3 Example

The following example specifies that notifications in WebCenter Portal (`webcenter`) use a BPEL server connection named `WebCenter-Worklist` and also defines the mail address and SMS address from which all notifications are sent:

```
wls:/weblogic/serverConfig>setNotificationsConfig(appName='webcenter',
type='BPEL',
name='WebCenter-Worklist', senderMailAddress='WebCenter
```

```
Notification<notifications@webcenter.com',
senderSMSAddress='28734')
```

10.11.2 getNotificationsConfig

Module: Oracle WebCenter Portal

Use with WLST: Online

10.11.2.1 Description

Returns details about the connection that is used to send notifications raised in a named application.

10.11.2.2 Syntax

```
getNotificationsConfig(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.11.2.3 Example

The following example returns details about the connection used by notifications service in WebCenter Portal:

```
wls:/weblogic/serverConfig>getNotificationsConfig(appName='webcenter')
```

```
ConnectionType:    BPEL
ConnectionName:   WebCenter-Worklist
SenderMailAddress: notifications@webcenter.com
SenderSMSAddress: 28776
```

10.12 People Connections

Use the commands listed in [Table 10–20](#) to manage user profile information in WebCenter Portal or your Portal Framework application.

Configuration changes made using these WLST commands are only effective after you restart the Managed Server on which WebCenter Portal or your Portal Framework application is deployed. For details, see *Oracle Fusion Middleware Administering Oracle WebCenter Portal*.

Table 10–20 People Connection WLST Commands

Use this command...	To...	Use with WLST...
<code>startSyncProfiles</code>	Synchronize profile information in the LDAP store, with the WebCenter Portal database schema.	Online
<code>syncProfile</code>	Synchronize profile information for a specific user.	Online
<code>stopSyncProfiles</code>	Stop the profile synchronization process.	Online
<code>isSyncProfilesRunning</code>	Check whether profile synchronization is in progress.	Online
<code>setProfileConfig</code>	Set profile properties.	Online
<code>getProfileConfig</code>	Return current profile properties.	Online
<code>listProfileConfig</code>	List current profile properties.	Online
<code>setProfilePhotoSync</code>	Specify whether to synchronize user profile photos in LDAP.	Online
<code>setProfileCacheNumberOfObjects</code>	Deprecated.	Online
<code>setProfileSyncLDAPReadBatchSize</code>	Deprecated.	Online
<code>setProfileCacheTimeToLive</code>	Deprecated.	Online
<code>printProfileConfig</code>	Deprecated.	Online

10.12.1 startSyncProfiles

Module: Oracle WebCenter Portal

Use with WLST: Online

10.12.1.1 Description

Synchronizes profile information in the LDAP store with the WebCenter Portal database schema.

10.12.1.2 Syntax

```
startSyncProfiles(appName, [server, applicationVersion])
```

Argument	Definition
<code>appName</code>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<code>server</code>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<code>applicationVersion</code>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.12.1.3 Example

The following example synchronizes user profiles for WebCenter Portal:

```
wls:/weblogic/serverConfig>startSyncProfiles(appName='webcenter')
```

10.12.2 stopSyncProfiles

Module: Oracle WebCenter Portal

Use with WLST: Online

10.12.2.1 Description

Stops the profile synchronization process, if currently in progress.

10.12.2.2 Syntax

```
stopSyncProfiles(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.12.2.3 Example

The following example stops the profile synchronization process for WebCenter Portal:

```
wls:/weblogic/serverConfig>stopSyncProfiles(appName='webcenter')
```

10.12.3 isSyncProfilesRunning

Module: Oracle WebCenter Portal

Use with WLST: Online

10.12.3.1 Description

Checks whether profile synchronization is in progress.

10.12.3.2 Syntax

```
isSyncProfilesRunning(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.

Argument	Definition
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <i>WC_Spaces</i> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.12.3.3 Example

The following example checks whether profile synchronization is in progress for WebCenter Portal:

```
wls:/weblogic/serverConfig>isSyncProfilesRunning (appName='webcenter')
```

10.12.4 syncProfile

Module: Oracle WebCenter Portal

Use with WLST: Online

10.12.4.1 Description

Synchronizes profile information for a specific user in the LDAP store with the WebCenter Portal schema.

10.12.4.2 Syntax

```
syncProfile(appName, userName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <i>webcenter</i> . For Portal Framework applications, specify the appropriate name.
<i>userName</i>	Name of the user whose profile information you want to synchronize.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <i>WC_Spaces</i> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.12.4.3 Example

The following example synchronizes profile information for a user named *monty*:

```
wls:/weblogic/serverConfig>syncProfile(appName='webcenter', userName='monty')
```

10.12.5 setProfileConfig

Module: Oracle WebCenter Portal

Use with WLST: Online

10.12.5.1 Description

Sets profile properties for a named application. If you omit a parameter, the corresponding configuration remains unchanged.

10.12.5.2 Syntax

```
setProfileConfig(appName, ProfilePageVersion, ProfileCacheNumberOfObjects,
ProfileCacheTimeToLive, ProfileSyncLDAPReadBatchSize, ProfileSyncHourOfDay,
ProfileSyncFrequencyInDays, server, applicationVersion]
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>ProfilePageVersion</i>	Optional. Specifies the profile page version to use. Valid values for <code>ProfilePageVersion</code> are: v1 - Use old-style profile pages (11.1.1.7.0 and earlier) v2 - Use the new profile page format (introduced in 11.1.1.8.0) The default value is v2.
<i>ProfileCacheNumberOfObjects</i>	Optional. Specifies the number of profile objects to keep in the profile cache. Any value between 1 and 10,000. The default value is 1000.
<i>ProfileCacheTimeToLive</i>	Optional. Specifies the length of time (in minutes) to keep a profile object in the cache. Any value between 1 and 1440. The default value is 60.
<i>ProfileSyncLDAPReadBatchSize</i>	Optional. Specifies the LDAP read batch size that is used during profile synchronization. Any value between 1 and 1,000. The default value is 1000.
<i>ProfileSyncHourOfDay</i>	Optional. Specifies when (the hour) to start profile synchronization. Any value between 0 and 23. The default value is 23, equivalent to 11pm.
<i>ProfileSyncFrequencyInDays</i>	Optional. Specifies how often profile synchronization takes place (in days). Any value greater than 0. The default value is 7.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.12.5.3 Example

The following example sets new values for the `ProfileCacheNumberOfObjects` and `ProfileCacheTimeToLive` configuration settings.

All other settings remain unchanged:

```
wls:/weblogic/serverConfig>setProfileConfig(appName='webcenter', ProfileCacheNumberOfObjects=2000, ProfileCacheTimeToLive=120)
```

10.12.6 getProfileConfig

Module: Oracle WebCenter Portal

Use with WLST: Online

10.12.6.1 Description

Returns current profile settings for a named application.

10.12.6.2 Syntax

```
getProfileConfig(appName, key, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>key</i>	Name of a profile property. Valid values include: - ProfilePageVersion - ProfileCacheNumberOfObjects - ProfileCacheTimeToLive - ProfileSyncLDAPReadBatchSize - ProfileSyncHourOfDay - ProfileSyncFrequencyInDays
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.12.6.3 Example

The following examples return current settings for various profile properties:

```
wls:/weblogic/serverConfig> getProfileConfig(appName='webcenter',
key='ProfilePageVersion')
wls:/weblogic/serverConfig> getProfileConfig(appName='webcenter',
key='ProfileCacheNumberOfObjects')
wls:/weblogic/serverConfig> getProfileConfig(appName='webcenter',
key='ProfileCacheTimeToLive')
wls:/weblogic/serverConfig> getProfileConfig(appName='webcenter',
key='ProfileSyncLDAPReadBatchSize')
wls:/weblogic/serverConfig> getProfileConfig(appName='webcenter',
key='ProfileSyncHourOfDay')
wls:/weblogic/serverConfig> getProfileConfig(appName='webcenter',
key='ProfileSyncFrequencyInDays')
```

10.12.7 listProfileConfig

Module: Oracle WebCenter Portal

Use with WLST: Online

10.12.7.1 Description

Lists the current profile settings for a named application.

10.12.7.2 Syntax

```
listProfileConfig(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.12.7.3 Example

The following example lists current profile settings for WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig>listProfileConfig(appName='webcenter')
```

10.12.8 setProfileCacheNumberOfObjects

Module: Oracle WebCenter Portal

Use with WLST: Online

10.12.8.1 Description

(Deprecated from 11.1.1.8.0. Use [setProfileConfig](#) instead.)

Sets the maximum number of profile objects to cache (in the profile cache).

10.12.8.2 Syntax

```
setProfileCacheNumberOfObjects(appName, noOfObjects, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>noOfObjects</i>	Number of profile objects to cache. Any value between 1 and 10,000. The default value is 1000.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.12.8.3 Example

The following example increases the size of the cache to 2,000 profiles:

```
wls:/weblogic/serverConfig>setProfileCacheNumberOfObjects (appName='webcenter',
noOfObjects=2000)
```

10.12.9 setProfileSyncLDAPReadBatchSize

Module: Oracle WebCenter Portal

Use with WLST: Online

10.12.9.1 Description

(Deprecated from 11.1.1.8.0. Use [setProfileConfig](#) instead.)

Sets the profile synchronization LDAP batch read size.

10.12.9.2 Syntax

```
setProfileSyncLDAPReadBatchSize(appName, batchSize, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>batchSize</i>	LDAP batch read size. Any value between 1 and 1000. The default value is 1000.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.12.9.3 Example

The following example increases the batch size to 2000 LDAP profiles:

```
wls:/weblogic/serverConfig>setProfileSyncLDAPReadBatchSize (appName='webcenter',
batchSize=800)
```

10.12.10 setProfileCacheTimeToLive

Module: Oracle WebCenter Portal

Use with WLST: Online

10.12.10.1 Description

(Deprecated from 11.1.1.8.0. Use [setProfileConfig](#) instead.)

Sets the time (in minutes) for a profile to live in the profile cache.

10.12.10.2 Syntax

```
setProfileCacheTimeToLive(appName, timeToLive, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>timeToLive</i>	Time to live for profile objects (in minutes) in the profile cache. The default value is 60 minutes.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.12.10.3 Example

The following example decreases the length of time profile objects are cached to 30 minutes:

```
wls:/weblogic/serverConfig>setProfileCacheTimeToLive(appName='webcenter',
timeToLive=30)
```

10.12.11 setProfilePhotoSync

Module: Oracle WebCenter Portal

Use with WLST: Online

10.12.11.1 Description

Specifies whether to synchronize the latest user profile photos in LDAP with WebCenter Portal's profile cache. When synchronization is enabled, profile photos are synchronized when the profile cache expires. When synchronization is disabled, profile photos are not synchronized with the WebCenter Portal's profile cache.

Note: The WLST command [setProfileCacheTimeToLive](#) defines the length of time profile objects live in the cache.

10.12.11.2 Syntax

```
setProfilePhotoSync(appName, enablePhotoSync, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.

Argument	Definition
<i>enablePhotoSync</i>	<p>Specifies whether to periodically synchronize user profile photos in LDAP. Valid values are 1 and 0.</p> <ul style="list-style-type: none"> 1 - Synchronize user profile photos periodically (after WebCenter Portal's profile cache expires). 0 - Profile photos in LDAP are not automatically synchronized with WebCenter Portal's profile cache. WebCenter Portal users must manually upload new photos through their profile page. <p>The default value is 1.</p>
<i>server</i>	<p>Optional. Name of the managed server where the application is deployed. For example, <i>WC_Spaces</i>.</p> <p>Required when applications with the same name are deployed to different servers and also when you have a cluster.</p>
<i>applicationVersion</i>	<p>Optional. Version number of the deployed application. Required if more than one version of the application is deployed.</p>

10.12.11.3 Example

The following example enables profile photo synchronization in WebCenter Portal:

```
wls:/weblogic/serverConfig>setProfilePhotoSync (appName='webcenter',
enablePhotoSync=1)
```

10.12.12 printProfileConfig

Module: Oracle WebCenter Portal

Use with WLST: Online

10.12.12.1 Description

(Deprecated from 11.1.1.8.0. Use [setProfileConfig](#) instead.)

Prints profile cache configuration values.

10.12.12.2 Syntax

```
printProfileConfig(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	<p>Name of the application in which to perform this operation.</p> <p>For WebCenter Portal, the application name is always <i>webcenter</i>.</p> <p>For Portal Framework applications, specify the appropriate name.</p>
<i>server</i>	<p>Optional. Name of the managed server where the application is deployed. For example, <i>WC_Spaces</i>.</p> <p>Required when applications with the same name are deployed to different servers and also when you have a cluster.</p>
<i>applicationVersion</i>	<p>Optional. Version number of the deployed application. Required if more than one version of the application is deployed.</p>

10.12.12.3 Example

The following example displays the current profile cache configuration for WebCenter Portal:


```
wls:/weblogic/serverConfig>printProfileConfig(appName='webcenter')
```

10.13 Personal Events

Use the commands listed in [Table 10–21](#) to manage personal events server connections for a named application.

Configuration changes made using these WLST commands are only effective after your restart the Managed Server on which the application is deployed. For details, see *Oracle Fusion Middleware Administering Oracle WebCenter Portal*.

Table 10–21 Personal Events WLST Commands

Use this command...	To...	Use with WLST...
createPersonalEventConnection	Create a personal events server connection for a named application.	Online
setPersonalEventConnection	Edit an existing personal events server connection.	Online
listPersonalEventConnections	List all of the personal events server connections that are configured for a named application	Online

10.13.1 createPersonalEventConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.13.1.1 Description

Creates a personal events server connection for a named application.

Personal events supports connections to Microsoft Exchange Server 2003 and Microsoft Exchange Server 2007.

While you can register multiple personal events connections for WebCenter Portal and Portal Framework applications, only one connection is used for personal events services - the default (or active) connection.

10.13.1.2 Syntax

```
createPersonalEventConnection(appName, name, webServiceUrl, adapterName, appId,
[default, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Connection name. The name must be unique (across all connection types within the application).
<i>webServiceUrl</i>	URL of the web service exposing the event application. Use the format: <code>protocol://host:port/appWebServiceInterface/WSName</code>

Argument	Definition
<i>adapterName</i>	Specify the adapter that matches the personal events server. Valid values are <code>MSEx2003</code> and <code>MSEx2007</code> . Choose <code>MSEx2003</code> for Microsoft Exchange Server 2003 and <code>MSEx2007</code> for Microsoft Exchange Server 2007. Each adapter has its own mechanism of authenticating and exchanging data
<i>appId</i>	External application associated with the Microsoft Exchange Server providing personal events services. If specified, external application credential information is used to authenticate users against the Microsoft Exchange Server.
<i>default</i>	Optional. Indicates whether this connection is the default connection for personal event services. Valid values are 1 (true) and 0 (false). The default for this argument is 0. To specify that personal events uses this connection, set the value to 1. While you can register multiple connections for WebCenter Portal and Portal Framework applications, only one connection is used for personal event services—the default (or active) connection.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.13.1.3 Example

The following example creates a connection named `MyPEConnection` for WebCenter Portal (`webcenter`). The connection points to a Microsoft Exchange Server 2007 and is designated as the default connection for personal event services:

```
wls:/weblogic/serverConfig>createPersonalEventConnection(appName='webcenter',
name='MyPEConnection', webServiceUrl='http://myexchange.com/EWS/Services.wsdl',
adapterName='MSEx2007', appId='ExtPEApp', default=1)
```

The following example creates a connection named `MyPEConnection` for a WebCenter Portal. The connection points to a Microsoft Exchange Server 2003:

```
wls:/weblogic/serverConfig>createPersonalEventConnection(appName='webcenter',
name='MyPEConnection',
webServiceUrl='http://myexchange.com/ExchangeWS/PersonalEventsWebService.asmx',
adapterName='MSEx2003', appId='ExtPEApp')
```

10.13.2 setPersonalEventConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.13.2.1 Description

Edits an existing personal events server connection configured for a named application.

10.13.2.2 Syntax

```
setPersonalEventConnection(appName, name, [webServiceUrl, adapterName, appId,
default, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing personal events server connection.
<i>webServiceUrl</i>	URL of the web service exposing the event application. Use the format: <i>protocol://host:port/appWebServiceInterface/WSName</i>
<i>adapterName</i>	Optional. Specify the adapter that matches the personal events server. Valid values are <code>MSEx2003</code> and <code>MSEx2007</code> . Choose <code>MSEx2003</code> for Microsoft Exchange Server 2003 and <code>MSEx2007</code> for Microsoft Exchange Server 2007. Each adapter has its own mechanism of authenticating and exchanging data
<i>appId</i>	Optional. External application associated with the Microsoft Exchange Server providing personal events services. If specified, external application credential information is used to authenticate users against the Microsoft Exchange Server.
<i>default</i>	Optional. Indicates whether this connection is the default connection for personal events. Valid values are 1 (true) and 0 (false). The default for this argument is 0. To specify that personal events uses this connection, set the value to 1. While you can register multiple connections for WebCenter Portal and Portal Framework applications, only one connection is used for personal event services—the default (or active) connection.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.13.2.3 Example

The following example updates the web service URL for a connection named `MyPEConnection`.

```
wls:/weblogic/serverConfig>setPersonalEventConnection(appName='webcenter',
name='MyPEConnection', webServiceUrl='http://myexchange.com/EWS/Services.wsdl')
```

The following example makes a connection named `MyPEConnection` the default connection for personal events services in WebCenter Portal.

```
wls:/weblogic/serverConfig>setPersonalEventConnection(appName='webcenter',
name='MyPEConnection', default=1)
```

10.13.3 listPersonalEventConnections

Module: Oracle WebCenter Portal

Use with WLST: Online

10.13.3.1 Description

Lists all of the personal events server connections that are configured for a named application.

10.13.3.2 Syntax

```
listPersonalEventConnections(appName, [verbose, name, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>verbose</i>	Optional. Displays connection details for personal events in verbose mode. Valid options are 1 (true) and 0 (false). When set to 1, <code>listPersonalEventConnections</code> lists all of the personal events server connections that are configured for a named application, along with their details. When set to 0, only connection names are listed. This argument defaults to 0. When set to 0, do not specify the name argument.
<i>name</i>	Optional. Name of an existing personal events connection. Use this argument to view connection details for a specific personal events server.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.13.3.3 Example

The following example lists connection names and details for all of the personal events server connections currently configured for WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig>listPersonalEventConnections(appName='webcenter',
verbose=1)
```

The following example displays connection details for a personal events server connection named `MyPEConnection`:

```
wls:/weblogic/serverConfig>listPersonalEventConnections(appName='webcenter',
verbose=1, name='MyPEConnection')
```

10.14 Personalization

Use the commands listed in [Table 10–22](#) to manage personalization connections for a named application.

Configuration changes made using these WLST commands are only effective after you restart the Managed Server on which personalization is deployed. For details, see *Oracle Fusion Middleware Administering Oracle WebCenter Portal*.

Table 10–22 Personalization WLST Commands

Use this command...	To...	Use with WLST...
createWCPSCMISConnection	Create a CMIS connection for the personalization.	Online
createWCPSPeopleConnection	Create a People connection for the personalization.	Online
createWCPSCustomConnection	Create a custom connection for the personalization.	Online
setWCPSCustomConnectionProperty	Modify properties of an existing connection for the personalization.	Online
listWCPSCMISConnection	List CMIS connections configured for the personalization.	Online
listWCPSPeopleConnection	List People connections configured for the personalization.	Online
listWCPSCustomConnection	List custom connections configured for the personalization.	Online
deleteWCPSCMISConnection	Delete a CMIS connection for the personalization.	Online
deleteWCPSPeopleConnection	Delete a People connection for the personalization.	Online
deleteWCPSCustomConnection	Delete a custom connection for the personalization.	Online

10.14.1 createWCPSCMISConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.14.1.1 Description

Creates a connection to a CMIS (Content Management Interoperability Service) provider for personalization services.

10.14.1.2 Syntax

```
createWCPSCMISConnection(name, repositoryId, host, port, [scheme, namespace,
isDefault, path, pathPrepend, servletPathPart, rewriteUrls, pathTrim,
timeoutInMilliseecs, propagateTimeoutExceptions, server])
```

Argument	Definition
<i>name</i>	Connection name. The name must be unique for this connection type within a namespace.

Argument	Definition
repositoryId	CMIS repository ID. Typically, the name of the Oracle WebCenter Content repository connection.
host	Hostname of the server that is hosting the CMIS REST service. Typically, the machine name of the WC_Spaces managed server.
port	Port of the server that is hosting the CMIS REST service. Typically, the port number of the WC_Spaces managed server.
scheme	Optional. HTTP scheme for accessing the CMIS REST service. Valid options are: http and https (for SSL) Defaults to http.
namespace	Optional. Namespace for the connection. If not specified or set to none, the connection is available to all namespaces.
isDefault	Optional. Indicates whether this connection is the default CMIS connection for personalization services. Valid values are 1 (true) or 0 (false). Defaults to 0.
path	Optional. CMIS service URL path. Defaults to: /api/cmisis/repository/<repositoryId>
pathPrepend	Optional. Base CMIS service URL path to prepend to the servletPathPart and path. Defaults to /rest.
servletPathPart	Optional. Servlet section of the CMIS service URL path.
rewriteUrls	Optional. Specifies how to rewrite URLs returned from the CMIS REST service. Valid options are producer, consumer, and none. Defaults to none. For more details, see 'Managing Personalization' in the <i>Oracle Fusion Middleware Administering Oracle WebCenter Portal</i> .
pathTrim	Optional. Specifies the path parts to trim from URLs returned from the CMIS REST service. Defaults to None. For more details, see 'Managing Personalization' in the <i>Oracle Fusion Middleware Administering Oracle WebCenter Portal</i> .
timeoutInMillisecs	Optional. Timeout in milliseconds (as a string) to wait for CMIS calls to return, or None for no timeout. Defaults to None.
propagateTimeoutExceptions	Optional. Valid values are 1 (true) and 0 (false). When set to 1, CMIS call timeouts raise an exception. When set to 0, exceptions are not raised.
server	Optional. Name of the Managed Server hosting personalization. This parameter is only required in a nondefault deployment configuration. No value is required for a default deployment where the WC_Uilities server hosts personalization.

10.14.1.3 Example

The following example creates a connection to a CMIS data provider:

```
wls:/weblogic/serverConfig>createWCPSCMISConnection(name='Repos1CMISConnection',
```

```
repositoryId='ucml1g-server', host='myhost.com', port=8888, scheme='http',
isDefault=1)
```

10.14.2 createWCPSActivityGraphConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.14.2.1 Description

Creates a connection to an activity graph data provider for personalization services.

10.14.2.2 Syntax

```
createWCPSActivityGraphConnection(name, host, port, [scheme, namespace, isDefault,
restResourceIndex, rewriteUrls, pathTrim, server)
```

Argument	Definition
<i>name</i>	Connection name. Must be unique for this connection type within a namespace.
<i>host</i>	Hostname of the server hosting activity graph REST services. Typically, the machine name of the WC_Spaces managed server.
<i>port</i>	Port of the server hosting activity graph services. Typically, the port number of the WC_Spaces managed server.
<i>scheme</i>	Optional. HTTP scheme for accessing activity graph. Valid options are <code>http</code> and <code>https</code> . Defaults to <code>http</code> .
<i>namespace</i>	Optional. Namespace for the connection. If not specified or set to <code>none</code> , the connection is available to all namespaces.
<i>isDefault</i>	Optional. Indicates whether this connection is the default activity graph connection. Valid values are <code>1</code> (<code>true</code>) or <code>0</code> (<code>false</code>). Defaults to <code>0</code> .
<i>restResourceIndex</i>	Optional. URL path for the resourceIndex of the REST server. Defaults to <code>/rest/api/resourceIndex</code> .
<i>rewriteUrls</i>	Optional. Specifies how to rewrite URLs returned from activity graph REST services. Valid options are <code>producer</code> , <code>consumer</code> , and <code>none</code> . Defaults to <code>none</code> . For more details, see 'Managing Personalization' in <i>Oracle Fusion Middleware Administering Oracle WebCenter Portal</i> .
<i>pathTrim</i>	Optional. Specifies the path parts to trim from URLs returned from activity graph REST services. Defaults to <code>None</code> . For more details, see 'Managing Personalization' in <i>Oracle Fusion Middleware Administering Oracle WebCenter Portal</i> .
<i>server</i>	Optional. Name of the Managed Server hosting personalization. This parameter is only required in a nondefault deployment configuration. No value is required for a default deployment where the WC_Uilities server hosts personalization services.

10.14.2.3 Example

The following example creates a connection to an activity graph data provider in a particular namespace:

```
wls:/weblogic/serverConfig> createWCPSActivityGraphConnection(name='AGConnection',
host='myhost.com', port=8888, namespace='myNamespace')
```

10.14.3 createWCPSPeopleConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.14.3.1 Description

Creates a connection to a people connections provider for personalization services.

10.14.3.2 Syntax

```
createWCPSPeopleConnection(name, host, port, [scheme], [namespace], [isDefault],
[restResourceIndex], [rewriteUrls], [pathTrim], [server])
```

Argument	Definition
<i>name</i>	Connection name. Must be unique for this connection type within a namespace.
<i>host</i>	Hostname of the server hosting the people connections REST service. Typically, the machine name of the WC_Spaces managed server.
<i>port</i>	Port of the server hosting people connections. Typically, the port number of the WC_Spaces managed server.
<i>scheme</i>	Optional. HTTP scheme for accessing people connection services. Valid options are <code>http</code> and <code>https</code> . Defaults to <code>http</code> .
<i>namespace</i>	Optional. Namespace for the connection. If not specified or set to <code>none</code> , the connection is available to all namespaces.
<i>isDefault</i>	Optional. Indicates whether this connection is the default for people connections. Valid values are <code>1 (true)</code> or <code>0 (false)</code> . Defaults to <code>0</code> .
<i>restResourceIndex</i>	Optional. URL path for the <code>resourceIndex</code> of the REST server. Defaults to <code>/rest/api/resourceIndex</code> .
<i>rewriteUrls</i>	Optional. Specifies how to rewrite URLs returned from the people connections REST service. Valid options are <code>producer</code> , <code>consumer</code> , and <code>none</code> . Defaults to <code>none</code> . For more details, see 'Managing Personalization' in <i>Oracle Fusion Middleware Administering Oracle WebCenter Portal</i> .
<i>pathTrim</i>	Optional. Specifies the path parts to trim from URLs returned from people connections. Defaults to <code>None</code> . For more details, see 'Managing Personalization' in <i>Oracle Fusion Middleware Administering Oracle WebCenter Portal</i> .
<i>server</i>	Optional. Name of the Managed Server hosting personalization services. This parameter is only required in a nondefault deployment configuration. No value is required for a default deployment where the WC_Utilities server hosts personalization services.

10.14.3.3 Example

The following example creates a connection to a people connections provider in the default namespace:

```
wls:/weblogic/serverConfig> createWCPSPeopleConnection(name='PeopleConnection',
host='myhost.com', port=8888)
```

10.14.4 createWCPSCustomConnection

Use with WLST: Online

10.14.4.1 Description

Creates a connection to a custom data provider for personalization services.

Custom connection types are used with custom data providers and property locators.

10.14.4.2 Syntax

```
createWCPSCustomConnection(name, type, [namespace, properties, [server]])
```

Argument	Definition
<i>name</i>	Connection name. Must be unique for this connection type within a namespace.
<i>type</i>	Custom connection type specific to the custom data provider or property locator implementation.
<i>namespace</i>	Optional. Namespace for the connection. If not specified or set to none, the connection is available to all namespaces.
<i>properties</i>	Optional. Dictionary of connection properties and values. The set of properties is specific to the connection type. All values in the dictionary must be strings.
<i>server</i>	Optional. Name of the Managed Server hosting personalization. This parameter is only required in a nondefault deployment configuration. No value is required for a default deployment where the <code>WC_Uutilities</code> server hosts personalization services.

10.14.4.3 Example

The following example creates a connection to a custom data provider with several properties:

```
wls:/weblogic/serverConfig> createWCPSCustomConnection(name='CustomConnection',
type='my.connection.type', properties={'prop1': 'value1', 'prop2', value2'})
```

10.14.5 listWCPSCMISConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.14.5.1 Description

Lists all CMIS (Content Management Interoperability Service) connections configured for personalization or lists a single connection.

10.14.5.2 Syntax

```
listWCPSCMISConnections([server], [verbose], [name], [namespace])
```

Argument	Definition
<i>server</i>	Optional. Name of the Managed Server hosting personalization. This parameter is only required in a nondefault deployment configuration. No value is required for a default deployment where the <code>WC_Utilities</code> server hosts personalization services.
<i>verbose</i>	Optional. Controls verbose or concise output. Valid options are 1 and 0. When set to 1, this command lists the CMIS connections and their properties. When set to 0, this command lists connection names only. Defaults to 1.
<i>name</i>	Optional. Name of an existing connection. If not specified or set to <code>None</code> , then all connections are listed.
<i>namespace</i>	Optional. Namespace for the connections you want to list. If not specified or set to <code>none</code> , this command lists connections configured to be available in all namespaces.

10.14.5.3 Example

The following example lists the names of all the CMIS connections:

```
wls:/weblogic/serverConfig> listWCPSCMISConnections(verbose=0)

Repos1CMISConnection
Repos2CMISConnection
```

The following example lists the details of one CMIS connection:

```
wls:/weblogic/serverConfig> listWCPSCMISConnections(name='Repos1CMISConnection')

-----
Repos1CMISConnection (type=cmis.provider.connection, namespace=*)
-----
host: myhost.com
isDefault: false
path: /api/cmris/repository/rep01
pathPrepend: /rest
port: 8888
repositoryId: ucml1g-server
rewriteUrls: none
scheme: http
```

10.14.6 listWCPSActivityGraphConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.14.6.1 Description

Lists all activity graph connections configured for the personalization or lists a single connection.

10.14.6.2 Syntax

```
listWCPSActivityGraphConnections([server], [verbose], [name], [namespace])
```

Argument	Definition
<i>server</i>	Optional. Name of the Managed Server hosting personalization service. This parameter is only required in a nondefault deployment configuration. No value is required for a default deployment where the <code>WC_Utilities</code> server hosts personalization services.
<i>verbose</i>	Optional. Controls verbose or concise output. Valid options are 1 and 0. When set to 1, this command lists the activity graph connections and their properties. When set to 0, this command lists connection names only. Defaults to 1.
<i>name</i>	Optional. Name of an existing connection. If not specified or set to None, then all connections are listed.
<i>namespace</i>	Optional. Namespace for the connection you want to list. If not specified or set to none, this command lists connections configured to be available in all namespaces.

10.14.6.3 Example

The following example lists the names of all activity graph data provider connections:

```
wls:/weblogic/serverConfig> listWCPSActivityGraphConnections(verbose=0)
```

```
AG1Connection
AG2Connection
```

The following example lists the details of one activity graph data provider connection:

```
wls:/weblogic/serverConfig> listWCPSActivityGraphConnections(name='AG1Connection')
```

```
-----
AG1Connection (type=activity.provider.connection, namespace=*)
-----
host: myhost.com
isDefault: false
port: 8888
restResourceIndex: /rest/api/resourceIndex
rewriteUrls: producer
scheme: http
```

10.14.7 listWCPSPeopleConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.14.7.1 Description

Lists all people connections configured for personalization or lists a single connection.

10.14.7.2 Syntax

```
listWCPSPeopleConnections([server], [verbose], [name], [namespace])
```

Argument	Definition
<i>server</i>	Optional. Name of the Managed Server hosting personalization. This parameter is only required in a nondefault deployment configuration. No value is required for a default deployment where the <code>WC_Utilities</code> server hosts personalization services.
<i>verbose</i>	Optional. Controls verbose or concise output. Valid options are 1 and 0. When set to 1, this command lists connection names and their properties. When set to 0, this command lists connection names only. Defaults to 1.
<i>name</i>	Optional. Name of an existing connection. If not specified or set to None, then all connections are listed.
<i>namespace</i>	Optional. Namespace for the connection you want to list. If not specified or set to none, this command lists connections configured to be available in all namespaces.

10.14.7.3 Example

The following example lists the names of all people connections for personalization:

```
wls:/weblogic/serverConfig> listWCPSPeopleConnections(verbose=0)

People1Connection
People2Connection
```

The following example lists the details of a single connection:

```
wls:/weblogic/serverConfig> listWCPSPeopleConnections(name='PeopleConnection')

-----
PeopleConnection (type=people.service.connection, namespace=*)
-----
host: myhost.com
isDefault: false
port: 8888
restResourceIndex: /rest/api/resourceIndex
rewriteUrls: producer
scheme: http
```

10.14.8 listWCPSCustomConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.14.8.1 Description

Lists all connections of a particular type configured for personalization or lists a single connection.

Custom connection types are used with custom data providers and property locators.

10.14.8.2 Syntax

```
listWCPSCustomConnections(type, [server], [verbose], [name], [namespace])
```

Argument	Definition
<i>type</i>	Custom connection type specific to the custom data provider or property locator implementation.
<i>server</i>	Optional. Name of the Managed Server hosting personalization. This parameter is only required in a nondefault deployment configuration. No value is required for a default deployment where the WC_Utilities server hosts personalization services.
<i>verbose</i>	Optional. Controls verbose or concise output. Valid options are 1 and 0. When set to 1, this command lists the connections and their properties. When set to 0, this command lists connection names only. Defaults to 1.
<i>name</i>	Optional. Name of an existing connection. If not specified or set to None, then all connections are listed.
<i>namespace</i>	Optional. Namespace for the connection you want to list. If not specified or set to none, this command lists connections configured to be available in all namespaces.

10.14.8.3 Example

The following example lists the names of all connections with the type `my.connection.type`:

```
wls:/weblogic/serverConfig> listWCPSCustomConnections(type='my.connection.type',
verbose=0)
```

```
Custom1Connection
Custom2Connection
```

The following example lists the details of one custom connection for personalization:

```
wls:/weblogic/serverConfig> listWCPSPeopleConnections(type='my.connection.type',
name='CustomConnection')
```

```
-----
CustomConnection (type=my.connection.type, namespace=*)
-----
host: myhost.com
isDefault: false
port: 8888
customConnectionProperty: someValue
scheme: http
```

10.14.9 deleteWCPSCMISConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.14.9.1 Description

Deletes a CMIS (Content Management Interoperability Service) connection configured for personalization.

10.14.9.2 Syntax

```
deleteWCPSMISConnection(name, [namespace, server])
```

Argument	Definition
<i>name</i>	Connection name.
<i>namespace</i>	Optional. Namespace for the connection you want to delete. If not specified or set to <i>none</i> , this command deletes connections configured to be available in all namespaces.
<i>server</i>	Optional. Name of the Managed Server hosting personalization. This parameter is only required in a nondefault deployment configuration. No value is required for a default deployment where the <i>WC_Utilities</i> server hosts personalization services.

10.14.9.3 Example

The following example deletes a CMIS connection configured for personalization:

```
wls:/weblogic/serverConfig>deleteWCPSMISConnection(name='ReposCMISConnection')
```

10.14.10 deleteWCPSActivityGraphConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.14.10.1 Description

Deletes an activity graph connection configured for personalization.

10.14.10.2 Syntax

```
deleteWCPSActivityGraphConnection(name, [namespace, server])
```

Argument	Definition
<i>name</i>	Connection name.
<i>namespace</i>	Optional. Namespace for the connection you want to delete. If not specified or set to <i>none</i> , this command deletes connections configured to be available in all namespaces.
<i>server</i>	Optional. Name of the Managed Server hosting personalization. This parameter is only required in a nondefault deployment configuration. No value is required for a default deployment where the <i>WC_Utilities</i> server hosts personalization services.

10.14.10.3 Example

The following example deletes an activity graph connection configured for personalization:

```
wls:/weblogic/serverConfig>deleteWCPSActivityGraphConnection(name='AGConnection')
```

10.14.11 deleteWCPSPeopleConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.14.11.1 Description

Deletes a people connection configured for personalization.

10.14.11.2 Syntax

```
deleteWCPSPeopleConnection(name, [namespace, server])
```

Argument	Definition
<i>name</i>	Connection name.
<i>namespace</i>	Optional. Namespace for the connection you want to delete. If not specified or set to <i>none</i> , this command deletes connections configured to be available in all namespaces.
<i>server</i>	Optional. Name of the Managed Server hosting personalization. This parameter is only required in a nondefault deployment configuration. No value is required for a default deployment where the <i>WC_Uutilities</i> server hosts personalization services.

10.14.11.3 Example

The following example deletes a people connection configured for personalization:

```
wls:/weblogic/serverConfig>deleteWCPSPeopleConnection(name='PeopleConnection')
```

10.14.12 deleteWCPSCustomConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.14.12.1 Description

Deletes a custom data provider connection configured for personalization.

10.14.12.2 Syntax

```
deleteWCPSCustomConnection(name, type, [namespace, server])
```

Argument	Definition
<i>name</i>	Connection name.
<i>type</i>	Custom connection type.
<i>namespace</i>	Optional. Namespace for the connection you want to delete. If not specified or set to <i>none</i> , this command deletes connections configured to be available in all namespaces.
<i>server</i>	Optional. Name of the Managed Server hosting personalization. This parameter is only required in a nondefault deployment configuration. No value is required for a default deployment where the <i>WC_Uutilities</i> server hosts personalization services.

10.14.12.3 Example

The following example deletes a custom data provider connection configured for personalization:

```
wls:/weblogic/serverConfig>deleteWCPSCustomConnection(name='CustomConnection', type='my.connection.type')
```

10.14.13 setWCPSConnectionProperty

Module: Oracle WebCenter Portal

Use with WLST: Online

10.14.13.1 Description

Add, modify, or delete properties of an existing connection for personalization. The properties supported by a connection are specific to the connection type:

- CMIS connections support the following properties: `repositoryId`, `host`, `port`, `scheme`, `path`, `pathPrepend`, `servletPathPart`, `rewriteUrls`, `pathTrim`, `isDefault`, `timeoutInMillisecs`, `propagateTimeoutException`
- See also, [createWCPSMISConnection](#).
- Activity graph and people connections support the following properties: `host`, `port`, `scheme`, `restResourceIndex`, `rewriteUrls`, `pathTrim`, `isDefault`

See also, [createWCPSActivityGraphConnection](#) and [createWCPSPeopleConnection](#).

10.14.13.2 Syntax

```
setWCPSConnectionProperty(connectionName, connectionType, propertyName,
propertyValue, [namespace], [server])
```

Argument	Definition
<i>connectionName</i>	Connection name.
<i>connectionType</i>	Connection type. Valid values are <code>WCPS_CMIS_CONNECTION_TYPE</code> , <code>WCPS_AG_CONNECTION_TYPE</code> , and <code>WCPS_PC_CONNECTION_TYPE</code> for CMIS, activity graph, and people connections, respectively. Alternatively, any valid, custom connection type can be specified
<i>propertyName</i>	Property name.
<i>propertyValue</i>	Property value as a string. Use <code>None</code> to remove a property value from the connection.
<i>namespace</i>	Optional. Namespace for the connection you want to change. If not specified or set to <code>none</code> , this command modifies properties of connections configured to be available in all namespaces.
<i>server</i>	Optional. Name of the Managed Server hosting personalization. This parameter is only required in a nondefault deployment configuration. No value is required for a default deployment where the <code>WC_Uutilities</code> server hosts personalization services.

10.14.13.3 Example

The following example changes or adds a property to a CMIS connection:

```
wls:/weblogic/serverConfig>
setWCPSConnectionProperty(connectionName='ReposCMISConnection',
connectionType=WCPS_CMIS_CONNECTION_TYPE,
propertyName='propagateTimeoutExceptions', propertyValue='false')
```

The following example removes a property from a custom data provider connection:

```
wls:/weblogic/serverConfig>
```



```
setWCPSCONNECTIONPROPERTY(connectionName='CustomConnection',
connectionType='my.connection.type', propertyName='prop2', propertyValue=None)
```

10.15 Portlet Producers

Use the commands listed in [Table 10–23](#) to manage portlet producers used in WebCenter Portal and Portal Framework applications.

All configuration changes made using these WLST commands are immediately available in the application.

Table 10–23 Portlet Producer WLST Commands

Use this command...	To...	Use with WLST...
registerWSRPProducer	Create and register a WSRP producer.	Online
setWSRPProducer	Edit WSRP producer registration details.	Online
listWSRPProducers	List WSRP producer registration details.	Online
deregisterWSRPProducer	Deregister a WSRP producer, and delete the associated WSRP and web service connections.	Online
listWSRPProducerRegistrationProperties	List registration properties supported by a WSRP producer.	Online
listWSRPProducerUserCategories	List any user categories that the WSRP producer might support.	Online
mapWSRPProducerUserCategory	Map a role that is defined in the specified application to a user category supported by a WSRP producer.	Online
registerPDKJavaProducer	Create and register an Oracle PDK-Java producer.	Online
setPDKJavaProducer	Edit PDK-Java producer registration details.	Online
listPDKJavaProducers	List registered Oracle PDK-Java producers.	Online
deregisterPDKJavaProducer	Deregister an Oracle PDK-Java producer, deleting the associated connection.	Online
registerPageletProducer	Create and register a pagelet producer.	Online
setPageletProducer	Edit pagelet producer registration details.	Online
listPageletProducers	List pagelet producer registration details.	Online
deregisterPageletProducer	Deregister a pagelet producer, deleting the associated connection.	Online
refreshProducer	Refresh the metadata stored for the named producer to reflect the portlets currently offered by that producer.	Online
listPortletClientConfig	List portlet client configuration for a named application.	Online
setPortletClientConfig	Edit portlet client configuration settings.	Online
getPortletClientConfig	Return portlet client configuration settings.	Online
registerOOTBProducers	Register out-of-the-box producers provided with Oracle WebCenter Portal.	Online
deregisterOOTBProducers	Deregister out-of-the-box producers provided with Oracle WebCenter Portal.	Online

Table 10–23 (Cont.) Portlet Producer WLST Commands

Use this command...	To...	Use with WLST...
registerSampleProducers	Register the sample producers provided with Oracle WebCenter Portal.	Online
deregisterSampleProducers	Deregister sample producers.	Online

10.15.1 registerWSRPProducer

Module: Oracle WebCenter Portal

Use with WLST: Online

10.15.1.1 Description

Creates a connection to a WSRP portlet producer and registers the WSRP producer with a named application. When you create a WSRP producer connection, a web service connection is also created named `<name>-wsconn` where `<name>` is the value specified for the name argument.

10.15.1.2 Syntax

```
registerWSRPProducer(appName, name, url, [proxyHost], [proxyPort],
[timeout], [externalApp], [registrationProperties], [tokenType], [issuer], [defUser],
[keyStorePath], [keyStorePswd], [sigKeyAlias], [sigKeyPswd], [encKeyAlias],
[encKeyPswd], [recptAlias], [enforcePolicyURI], [server], [applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Connection name. The name must be unique (across all connection types) within the application. The name you specify here will appear in Composer (under the <i>Portlets</i> folder).

Argument	Definition
<i>url</i>	<p>Producer WSDL URL. The syntax will vary according to your WSRP implementation, for example:</p> <pre>http://host_name:port_number/context_root/portlets/wsrp2?WSDL</pre> <pre>http://host_name:port_number/context_root/portlets/wsrp1?WSDL</pre> <pre>http://host_name:port_number/context_root/portlets/?WSDL (WSRP 1.0 for backward compatibility)</pre> <p>Where:</p> <ul style="list-style-type: none"> ■ <code>host_name</code> is the server where your producer is deployed ■ <code>port_number</code> is the HTTP listener port number ■ <code>context_root</code> is the web application's context root ■ <code>portlets[/wsrp(1 2)]?WSDL</code> is static text. The text entered here depends on how the producer is deployed. <p>For example:</p> <pre>http://myhost.com:7778/MyPortletApp/portlets/wsrp2?WSDL</pre>
<i>proxyHost</i>	<p>Optional. Host name or IP address of the proxy server.</p> <p>A proxy is required when the application and the remote portlet producer are separated by a firewall and an HTTP proxy is needed to communicate with the producer.</p>
<i>proxyPort</i>	<p>Optional. Port number on which the proxy server listens.</p>
<i>timeout</i>	<p>Optional. Timeout setting for communications with the producer, in seconds. For example, the maximum time the producer may take to register, deregister, or display portlets on portal pages. This argument defaults to 30.</p> <p>Individual portlets may define their own timeout period, which takes precedence over the value expressed here.</p>
<i>registrationProperties</i>	<p>Optional. A list of registration properties and their values. The format of this argument must be a comma-separated list of valid registration properties, each followed by an equals symbol and the value. For example: <code>name=Producer, key=123</code>. The registration properties for a producer can be found using <code>listWSRPProducerRegistrationProperties</code>. See Section 10.15.5, "listWSRPProducerRegistrationProperties".</p>

Argument	Definition
<i>tokenType</i>	<p data-bbox="625 220 1372 283">Optional. Type of token profile to use for authentication with this WSRP producer.</p> <p data-bbox="625 294 1372 325">When the argument <code>enforcePolicyURI=1</code>, valid values are:</p> <ul style="list-style-type: none"> <li data-bbox="625 336 1372 661"> <p data-bbox="625 336 1372 367">■ USERNAME_WITHOUT_PASSWORD (<code>oracle/wss10_username_id_propagation_with_msg_protection_client_policy</code>)—This policy provides message protection (integrity and confidentiality) and identity propagation for outbound SOAP requests in accordance with the WS-Security 1.0 standard. Credentials (<i>user name</i> only) are included in outbound SOAP request messages through a WS-Security UsernameToken header. No password is included.</p> <p data-bbox="673 556 1372 661">Message protection is provided using WS-Security 1.0's Basic128 suite of asymmetric key technologies. Specifically, RSA key mechanisms for message confidentiality, SHA-1 hashing algorithm for message integrity, and AES-128 bit encryption.</p> <li data-bbox="625 672 1372 1071"> <p data-bbox="625 672 1372 703">■ USERNAME_WITH_PASSWORD (<code>oracle/wss10_username_token_with_message_protection_client_policy</code>)—This policy provides message protection (integrity and confidentiality) and authentication for outbound SOAP requests in accordance with the WS-Security v1.0 standard. Both plain text and digest mechanisms are supported.</p> <p data-bbox="673 850 1372 955">This policy uses WS-Security's Basic 128 suite of asymmetric key technologies. Specifically, RSA key mechanism for message confidentiality, SHA-1 hashing algorithm for message integrity, and AES-128 bit encryption.</p> <p data-bbox="673 966 1372 1071">Use this token profile if the WSRP producer has a different identity store. You will need to define an external application pertaining to the producer and associate the external application with this producer.</p> <li data-bbox="625 1081 1372 1417"> <p data-bbox="625 1081 1372 1113">■ SAML_TOKEN_WITH_MSG_INTEGRITY (<code>wss10_saml_token_with_message_integrity_client_policy</code>)—This policy provides message-level integrity protection and SAML-based authentication for outbound SOAP requests in accordance with the WS-Security 1.0 standard. A SAML token, included in the SOAP message, is used in SAML-based authentication with sender vouches confirmation.</p> <p data-bbox="673 1291 1372 1354">This policy uses WS-Security's Basic 128 suite of asymmetric key technologies and SHA-1 hashing algorithm for message integrity.</p> <p data-bbox="673 1365 1372 1417">When this policy is selected, the recipient key alias (<code>recptAlias</code>) must be disabled.</p> <li data-bbox="625 1428 1372 1764"> <p data-bbox="625 1428 1372 1459">■ SAML_TOKEN_WITH_MSG_PROTECTION (<code>oracle/wss10_saml_token_with_message_protection_client_policy</code>)—This policy provides message-level protection (integrity and confidentiality) and SAML-based authentication for outbound SOAP requests in accordance with the WS-Security 1.0 standard. The web service consumer includes a SAML token in the SOAP header and the confirmation type is sender-vouches.</p> <p data-bbox="673 1627 1372 1764">This policy uses WS-Security's Basic 128 suite of asymmetric key technologies. Specifically, RSA key mechanisms for message confidentiality, SHA-1 hashing algorithm for message integrity, and AES-128 bit encryption. and SHA-1 hashing algorithm for message integrity.</p>

Argument	Definition
<i>tokenType</i> continued...	<ul style="list-style-type: none"> ■ WSS11_SAML_TOKEN_WITH_MSG_PROTECTION (oracle/wss11_saml_token_with_message_protection_client_policy)—This policy provides message-level protection (integrity and confidentiality) and SAML token population for outbound SOAP requests in accordance with the WS-Security 1.1 standard. A SAML token, included in the SOAP message, is used in SAML-based authentication with sender vouches confirmation. This policy uses the symmetric key technology for signing and encryption, and WS-Security's Basic 128 suite of asymmetric key technologies for endorsing signatures. ■ WSS10_SAML_TOKEN_ONLY (oracle/wss10_saml_token_client_policy)—This policy provides SAML-based authentication for outbound SOAP request messages in accordance with the WS-Security 1.0 standard. The policy propagates user identity and is typically used in intra departmental deployments where message protection and integrity checks are not required. <p>This policy does not require any keystore configuration.</p> <p>If the argument <code>enforcePolicyURI=0</code>, you can specify any <i>valid</i> Oracle Web Services Manager (OWSM) policy URI for the <code>tokenType</code> argument.</p>
<i>issuer</i>	<p>Optional. Name of the issuer of the token. The issuer name is the entity that vouches for the verification of the subject. For example: <code>www.oracle.com</code>.</p> <p>This argument only applies when the <code>tokenType</code> is: <code>SAML_TOKEN_WITH_MSG_PROTECTION</code>, <code>SAML_TOKEN_WITH_MSG_INTEGRITY</code>, <code>WSS10_SAML_TOKEN_ONLY</code>, <code>WSS11_SAML_TOKEN_WITH_MSG_PROTECTION</code>.</p>
<i>defUser</i>	<p>Optional. User name to assert to the remote producer when the user is not authenticated with the portal application.</p> <p>When unauthenticated, the identity <i>anonymous</i> is associated with the application user. The value <i>anonymous</i> may be inappropriate for the remote producer, so you may need to specify an alternative identity here. Keep in mind though, that in this case, the application has not authenticated the user so the default user you specify should be a low privileged user in the remote producer. If the user has authenticated to the application, the user's identity is asserted rather than the default user.</p> <p>This argument only applies when the <code>tokenType</code> is: <code>USERNAME_WITHOUT_PASSWORD</code>, <code>SAML_TOKEN_WITH_MSG_PROTECTION</code>, <code>SAML_TOKEN_WITH_MSG_INTEGRITY</code>, <code>WSS10_SAML_TOKEN_ONLY</code>, <code>WSS11_SAML_TOKEN_WITH_MSG_PROTECTION</code>.</p>
<i>extApp</i>	<p>Optional. This argument applies when the <code>tokenType</code> is <code>USERNAME_WITH_PASSWORD</code>. If this producer uses an external application to store and supply user credentials for authentication, use this argument to name the associated external application.</p>
<i>keyStorePath</i>	<p>Optional. Full path to the key store that contains the certificate and the private key that is used for signing some parts of the SOAP message, such as the security token and SOAP message body. The selected file should be a key store created with the Java keytool.</p>
<i>keyStorePswd</i>	<p>Optional. Password to the key store that was set when the key store was created.</p>
<i>sigKeyAlias</i>	<p>Optional. Identifier for the certificate associated with the private key that is used for signing.</p>
<i>sigKeyPswd</i>	<p>Optional. Password for accessing the key identified by the alias that is specified using the <code>sigKeyAlias</code> argument.</p>

Argument	Definition
<i>encKeyAlias</i>	Optional. Key alias to be used for encryption. A valid value is one of the key aliases that is located in the specified key store.
<i>encKeyPswd</i>	Optional. Password for accessing the encryption key.
<i>recptAlias</i>	Optional. Key store alias that is associated with the producer's certificate. This certificate is used to encrypt the message to the producer. Do not specify a recipient key alias when the <code>tokenType</code> is <code>SAML_TOKEN_WITH_MSG_INTEGRITY</code> .
<i>enforcePolicyURI</i>	Optional. Valid values are 1 (true) and 0 (false). When set to 1, users must specify one of the following token profiles for the <code>tokenType</code> argument: <code>USERNAME_WITHOUT_PASSWORD</code> , <code>USERNAME_WITH_PASSWORD</code> , <code>SAML_TOKEN_WITH_MSG_PROTECTION</code> , <code>SAML_TOKEN_WITH_MSG_INTEGRITY</code> , <code>WSS11_SAML_TOKEN_WITH_MSG_PROTECTION</code> , <code>WSS10_SAML_TOKEN_ONLY</code> When set to 0, users can specify any Oracle Web Services Manager (OWSM) policy URI. The user must ensure that the OWSM policy specified is valid. The default value is 1.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.15.1.3 Examples

The following example registers a WSRP producer named `WSRPSamples` with WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig> registerWSRPProducer(appName='webcenter',
name='WSRPSamples', url='http://myhost.com:9999/
portletapp/portlets/wsrp2?WSDL')
```

The following example registers a secure WSRP producer:

```
wls:/weblogic/serverConfig> registerWSRPProducer(appName='webcenter',
name='WSRPSamples2', url='http://myhost.com:8899/portletapp/portlets/wsrp2?WSDL',
tokenType='WSS11_SAML_TOKEN_WITH_MSG_PROTECTION', issuer='www.oracle.com',
defUser='anonymous', keyStorePath='/keys/mykeystore.jks', keyStorePswd='Test1',
sigKeyAlias='mysigalias', sigKeyPswd='mysigpswd', encKeyAlias='myencalias',
encKeyPswd='myencpswd', recptAlias='myrcptalias')
```

10.15.2 setWSRPProducer

Module: Oracle WebCenter Portal

Use with WLST: Online

10.15.2.1 Description

Edits registration details for an existing WSRP producer.

10.15.2.2 Syntax

```
setWSRPProducer(appName, name, [url], [proxyHost], [proxyPort], [timeout],
[externalApp], [tokenType],[issuer], [defUser], [keyStorePath], [keyStorePswd]
[sigKeyAlias], [sigKeyPswd], [encKeyAlias], [encKeyPswd], [recptAlias],
[enforcePolicyURI], [server], [applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always webcenter. For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing WSRP producer.
<i>url</i>	Optional. WSRP producer URL. The syntax will vary according to your WSRP implementation, for example: <pre>http://host_name:port_number/context_root/portlets/wsrp2?WSDL</pre> <pre>http://host_name:port_number/context_root/portlets/wsrp1?WSDL</pre> <pre>http://host_name:port_number/context_root/portlets/?WSDL (WSRP 1.0 for backward compatibility)</pre> Where: <ul style="list-style-type: none"> ■ <i>host_name</i> is the server where your producer is deployed ■ <i>port_number</i> is the HTTP listener port number ■ <i>context_root</i> is the Web application's context root ■ <i>portlets[/wsrp(1 2)]?WSDL</i> is static text. The text entered here depends on how the producer is deployed. For example: <pre>http://myhost:7778/MyPortletApp/portlets/wsrp2?WSDL</pre>
<i>proxyHost</i>	Optional. Host name or IP address of the proxy server. A proxy is required when the application and the remote portlet producer are separated by a firewall and an HTTP proxy is needed to communicate with the producer.
<i>proxyPort</i>	Optional. Port number on which the proxy server listens.
<i>timeout</i>	Optional. Timeout setting for communications with the producer, in seconds. For example, the maximum time the producer may take to register, deregister, or display portlets on portal pages. This argument defaults to 30. Individual portlets may define their own timeout period, which takes precedence over the value expressed here.
<i>extApp</i>	Optional. This argument applies when the <i>tokenType</i> is <code>USERNAME_WITH_PASSWORD</code> . If this producer uses an external application to store and supply user credentials for authentication, use this argument to name the associated external application.

Argument	Definition
<i>tokenType</i>	<p data-bbox="625 220 1372 283">Optional. Type of token profile to use for authentication with this WSRP producer.</p> <p data-bbox="625 294 1372 325">When the argument <code>enforcePolicyURI=1</code>, valid values are:</p> <ul style="list-style-type: none"> <li data-bbox="625 336 1372 682"> <p data-bbox="625 336 1372 367">■ USERNAME_WITHOUT_PASSWORD</p> <p data-bbox="673 378 1372 556">(oracle/wss10_username_id_propagation_with_msg_protection_client_policy)—This policy provides message protection (integrity and confidentiality) and identity propagation for outbound SOAP requests in accordance with the WS-Security 1.0 standard. Credentials (<i>user name</i> only) are included in outbound SOAP request messages through a WS-Security UsernameToken header. No password is included.</p> <p data-bbox="673 567 1372 682">Message protection is provided using WS-Security 1.0's Basic 128 suite of asymmetric key technologies. Specifically, RSA key mechanisms for message confidentiality, SHA-1 hashing algorithm for message integrity, and AES-128 bit encryption.</p> <li data-bbox="625 693 1372 1102"> <p data-bbox="625 693 1372 724">■ USERNAME_WITH_PASSWORD</p> <p data-bbox="673 735 1372 871">(oracle/wss10_username_token_with_message_protection_client_policy)—This policy provides message protection (integrity and confidentiality) and authentication for outbound SOAP requests in accordance with the WS-Security v1.0 standard. Both plain text and digest mechanisms are supported.</p> <p data-bbox="673 882 1372 987">This policy uses WS-Security's Basic 128 suite of asymmetric key technologies. Specifically, RSA key mechanism for message confidentiality, SHA-1 hashing algorithm for message integrity, and AES-128 bit encryption.</p> <p data-bbox="673 997 1372 1102">Use this token profile if the WSRP producer has a different identity store. You will need to define an external application pertaining to the producer and associate the external application with this producer.</p> <li data-bbox="625 1113 1372 1449"> <p data-bbox="625 1113 1372 1144">■ SAML_TOKEN_WITH_MSG_INTEGRITY</p> <p data-bbox="673 1155 1372 1312">(wss10_saml_token_with_message_integrity_client_policy)—This policy provides message-level integrity and SAML-based authentication for outbound SOAP requests in accordance with the WS-Security 1.0 standard. A SAML token, included in the SOAP message, is used in SAML-based authentication with sender vouches confirmation.</p> <p data-bbox="673 1323 1372 1386">This policy uses WS-Security's Basic 128 suite of asymmetric key technologies and SHA-1 hashing algorithm for message integrity.</p> <p data-bbox="673 1396 1372 1449">When this policy is selected, the recipient key alias (<code>recptAlias</code>) must be disabled.</p> <li data-bbox="625 1459 1372 1795"> <p data-bbox="625 1459 1372 1491">■ SAML_TOKEN_WITH_MSG_PROTECTION</p> <p data-bbox="673 1501 1372 1659">(oracle/wss10_saml_token_with_message_protection_client_policy)—This policy provides message-level protection (integrity and confidentiality) and SAML-based authentication for outbound SOAP requests in accordance with the WS-Security 1.0 standard. The Web service consumer includes a SAML token in the SOAP header and the confirmation type is sender-vouches.</p> <p data-bbox="673 1669 1372 1795">This policy uses WS-Security's Basic 128 suite of asymmetric key technologies. Specifically, RSA key mechanisms for message confidentiality, SHA-1 hashing algorithm for message integrity, and AES-128 bit encryption. and SHA-1 hashing algorithm for message integrity.</p>

Argument	Definition
<i>tokenType</i> continued...	<ul style="list-style-type: none"> ■ WSS11_SAML_TOKEN_WITH_MSG_PROTECTION (oracle/wss11_saml_token_with_message_protection_client_policy)—This policy enables message-level protection (integrity and confidentiality) and SAML token population for outbound SOAP requests in accordance with the WS-Security 1.1 standard. A SAML token, included in the SOAP message, is used in SAML-based authentication with sender vouches confirmation. This policy uses the symmetric key technology for signing and encryption, and WS-Security's Basic 128 suite of asymmetric key technologies for endorsing signatures. ■ WSS10_SAML_TOKEN_ONLY (oracle/wss10_saml_token_client_policy)—This policy includes SAML-tokens in outbound SOAP request messages in accordance with the WS-Security 1.0 standard. The policy propagates user identity and is typically used in intra departmental deployments where message protection and integrity checks are not required. This policy does not require any keystore configuration. If the argument <code>enforcePolicyURI=0</code>, you can specify any <i>valid</i> Oracle Web Services Manager (OWSM) policy URI for the <code>tokenType</code> argument.
<i>issuer</i>	<p>Optional. Name of the issuer of the token. The issuer name is the entity that vouches for the verification of the subject. For example: <code>www.oracle.com</code>.</p> <p>This argument only applies when the <code>tokenType</code> is: <code>SAML_TOKEN_WITH_MSG_PROTECTION</code>, <code>SAML_TOKEN_WITH_MSG_INTEGRITY</code>, <code>WSS10_SAML_TOKEN_ONLY</code>, <code>WSS11_SAML_TOKEN_WITH_MSG_PROTECTION</code>.</p>
<i>defUser</i>	<p>Optional. User name to assert to the remote producer when the user is not authenticated with the application.</p> <p>When unauthenticated, the identity <i>anonymous</i> is associated with the application user. The value <i>anonymous</i> may be inappropriate for the remote producer, so you may need to specify an alternative identity here. Keep in mind though, that in this case, the application has not authenticated the user so the default user you specify should be a low privileged user in the remote producer. If the user has authenticated to the application, the user's identity is asserted rather than the default user.</p> <p>This argument only applies when the <code>tokenType</code> is: <code>USERNAME_WITHOUT_PASSWORD</code>, <code>SAML_TOKEN_WITH_MSG_PROTECTION</code>, <code>SAML_TOKEN_WITH_MSG_INTEGRITY</code>, <code>WSS10_SAML_TOKEN_ONLY</code>, <code>WSS11_SAML_TOKEN_WITH_MSG_PROTECTION</code>.</p>
<i>keyStorePath</i>	Optional. Full path to the key store that contains the certificate and the private key that is used for signing some parts of the SOAP message, such as the security token and SOAP message body. The selected file should be a key store created with the Java keytool.
<i>keyStorePswd</i>	Optional. Password to the key store that was set when the key store was created.
<i>sigKeyAlias</i>	Optional. Identifier for the certificate associated with the private key that is used for signing.
<i>sigKeyPswd</i>	Optional. Password for accessing the key identified by the alias that is specified using the <code>sigKeyAlias</code> argument.

Argument	Definition
<i>encKeyAlias</i>	Optional. Key alias used by the producer to encrypt the return message. A valid value is one of the key aliases that is located in the specified key store. If not specified, the producer uses the signing key for encrypting the return message.
<i>encKeyPswd</i>	Optional. Password for accessing the encryption key.
<i>recptAlias</i>	Optional. Key store alias that is associated with the producer's certificate. This certificate is used to encrypt the outbound message to the producer. Do not specify a recipient key alias when the <code>tokenType</code> is <code>SAML_TOKEN_WITH_MSG_INTEGRITY</code> .
<i>enforcePolicyURI</i>	Optional. Valid values are 1 (true) and 0 (false). When set to 1, users must specify one of the following token profiles for the <code>tokenType</code> argument: <code>USERNAME_WITHOUT_PASSWORD</code> , <code>USERNAME_WITH_PASSWORD</code> , <code>SAML_TOKEN_WITH_MSG_PROTECTION</code> , <code>SAML_TOKEN_WITH_MSG_INTEGRITY</code> , <code>WSS11_SAML_TOKEN_WITH_MSG_PROTECTION</code> , <code>WSS10_SAML_TOKEN_ONLY</code> When set to 0, users can specify any Oracle Web Services Manager (OWSM) policy URI. The user must ensure that the OWSM policy specified is valid. The default value is 1.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.15.2.3 Example

This example increases the timeout, for the `WSRP` producer, to 60 seconds:

```
wls:/weblogic/serverConfig>setWSRPProducer (appName='webcenter',
name='WSRPSamples', timeout=60)
```

This example updates security properties on a secure `WSRP` producer:

```
wls:/weblogic/serverConfig>setWSRPProducer (appName='webcenter',
name='WSRPSamples2', tokenType='WSS11_SAML_TOKEN_WITH_MSG_PROTECTION',
issuer='www.oracle.com', defUser='anonymous',
keyStorePath='/keys/mykeystore.jks', keyStorePswd='Test1',
sigKeyAlias='mysigalias', sigKeyPswd='mysigpswd',encKeyAlias='myencalias',
encKeyPswd='myencpswd', recptAlias='myrcptalias')
```

This example removes all the security properties set on a secure `WSRP` producer:

```
wls:/weblogic/serverConfig>setWSRPProducer (appName='webcenter',
name='WSRPSamples2', tokenType='')
```

10.15.3 listWSRPProducers

Module: Oracle WebCenter Portal

Use with WLST: Online

10.15.3.1 Description

Lists WSRP producer registration details for a named application.

10.15.3.2 Syntax

```
listWSRPProducers(appName, [name, verbose, server, [applicationVersion]])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Optional. Name of an existing WSRP producer. If omitted, connection details for all WSRP producers configured for this application are listed.
<i>verbose</i>	Optional. Displays WSRP producer connection details in verbose mode. Valid options are 1 (true) and 0 (false). When set to 1, <code>listWSRPProducers</code> lists all connection properties. When set to 0, <code>listWSRPProducers</code> lists connection names only. This argument defaults to 1. If you set this argument to 0, do not specify the names argument.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.15.3.3 Example

The following example lists all the WSRP producers registered with a Portal Framework application named `myApp`:

```
wls:/weblogic/serverConfig> listWSRPProducers(appName='myApp', verbose=0)
```

```
-----  
WSRPSamples-connection  
-----
```

The following example lists detailed connection information for a WSRP producer registered as `WSRPSamples-connection` with a Portal Framework application named `myApp`:

```
wls:/weblogic/serverConfig> listWSRPProducers(appName='myApp',  
name='WSRPSamples-connection', verbose=1)
```

```
-----  
WSRPSamples-connection  
-----  
Connection Name: WSRPSamples-connection  
Web Service Connection Name: WSRPSamples-connection-wsconn  
Proxy Host: None  
Proxy Port: None  
Timeout: 0  
WSDL URL: http://example.com:7777/portletapp/portlets/wsrp2?WSDL
```

10.15.4 deregisterWSRPProducer

Module: Oracle WebCenter Portal

Use with WLST: Online

10.15.4.1 Description

Deregisters a WSRP producer, and deletes the associated WSRP and web service connections.

10.15.4.2 Syntax

```
deregisterWSRPProducer(appName, name, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing WSRP producer.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.15.4.3 Example

The following example deregisters the `WSRPSamples` producer in WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig> deregisterWSRPProducer (appName= 'webcenter',
name= 'WSRPSamples')
```

10.15.5 listWSRPProducerRegistrationProperties

Module: Oracle WebCenter Portal

Use with WLST: Online

10.15.5.1 Description

Lists registration properties supported by a WSRP portlet producer.

10.15.5.2 Syntax

```
listWSRPProducerRegistrationProperties(appName, url, [proxyHost, proxyPort,
server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>url</i>	WSRP producer URL. The syntax will vary according to your WSRP implementation, for example: <pre>http://host_name:port_number/context_root/portlets/wsrp2?WSDL</pre> <pre>http://host_name:port_number/context_root/portlets/wsrp1?WSDL</pre> <pre>http://host_name:port_number/context_root/portlets/?WSDL (WSRP 1.0 for backward compatibility)</pre> Where: <ul style="list-style-type: none"> ▪ <code>host_name</code> is the server where your producer is deployed ▪ <code>port_number</code> is the HTTP listener port number ▪ <code>context_root</code> is the Web application's context root ▪ <code>portlets[/wsrp(1 2)]?WSDL</code> is static text. The text entered here depends on how the producer is deployed. For example: <pre>http://myhost:7778/MyPortletApp/portlets/wsrp2?WSDL</pre>
<i>proxyHost</i>	Optional. Host name or IP address of the proxy server. A proxy is required when the application and the remote portlet producer are separated by a firewall and an HTTP proxy is needed to communicate with the producer.
<i>proxyPort</i>	Optional. Port number on which the proxy server listens.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.15.5.3 Example

The following example lists valid registration properties for the WSRP producer with the WSDL URL provided:

```
wls:/weblogic/serverConfig> listWSRPProducerRegistrationProperties
(appName='webcenter', url='http://myhost:9999/portletapp/portlets/wsrp2?WSDL')
```

```
Registration Property hint : hint text
Registration Property label : label text
Registration Property language : en
Registration Property name : {urn:xyz:wlp:prop:reg:registration}consumerRole
Registration Property value : None
```

10.15.6 listWSRPProducerUserCategories

Module: Oracle WebCenter Portal

Use with WLST: Online

10.15.6.1 Description

Lists any user categories that a WSRP producer might support. WebCenter Portal users can use the WLST command [mapWSRPProducerUserCategory](#) to map application roles to a producer's user category.

10.15.6.2 Syntax

```
listWSRPProducerUserCategories(appName, name, [server, [pplicationVersion]])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing WSRP producer.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.15.6.3 Example

The following example displays the categories associated with a WSRP producer named `WSRPSamples`:

```
wls:/weblogic/serverConfig> listWSRPProducerUserCategories (appName='webcenter',
name='WSRPSamples')
```

```
User Category Name : categoryTwo
User Category Description : Custom role two.
User Category Mapped Local Roles : None
```

```
User Category Name : categoryOne
User Category Description : Custom role one.
User Category Mapped Local Roles : None
```

10.15.7 mapWSRPProducerUserCategory

Module: Oracle WebCenter Portal

Use with WLST: Online

10.15.7.1 Description

Maps a role that is defined in the named application to a user category supported by a WSRP producer. The user categories may be found using [listWSRPProducerUserCategories](#).

10.15.7.2 Syntax

```
mapWSRPProducerUserCategory(appName, name, localRole, producerUserCategory,
[server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing WSRP producer.
<i>localRole</i>	Name of the application role to be mapped.
<i>producerUserCategory</i>	WSRP producer user category to which the WebCenter Portal or Portal Framework application role will be mapped.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.15.7.3 Example

The following example maps the application role `admin` to the WSRP user category `wrsp-admin`:

```
wls:/weblogic/serverConfig> mapWSRPProducerUserCategory(appName='webcenter',
name='WSRPProducer1', localRole='admin', producerUserCategory='wsrp-admin')
```

10.15.8 registerPDKJavaProducer

Module: Oracle WebCenter Portal

Use with WLST: Online

10.15.8.1 Description

Creates a connection to an Oracle PDK-Java portlet producer and registers the Oracle PDK-Java producer with a named application.

10.15.8.2 Syntax

```
registerPDKJavaProducer(appName, name, url, [serviceId, proxyHost, proxyPort,
subscriberId, sharedKey, timeout, establishSession, externalApp, mapUser, server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Connection name. The name must be unique (across all connection types) within the application.

Argument	Definition
<i>url</i>	<p>URL for the Oracle PDK-Java producer. Use the following syntax: <code>http://host_name:port_number/context_root/providers</code> Where:</p> <ul style="list-style-type: none"> ■ <code>host_name</code> is the server where the producer is deployed ■ <code>port_number</code> is the HTTP Listener port number ■ <code>context_root</code> is the web application's context root. ■ <code>providers</code> is static text. The text entered here depends on how the producer is deployed. <p>For example: <code>http://myHost:7778/myEnterprisePortlets/providers</code></p>
<i>serviceId</i>	<p>Optional. Service ID of the producer.</p> <p>PDK-Java enables you to deploy multiple producers under a single adapter servlet. Producers are identified by their unique service ID. A service ID is required only if the service ID is not appended to the URL end point.</p> <p>For example, the following URL endpoint requires <code>sample</code> as the service ID: <code>http://domain.example.com:7778/xyz/providers</code> However, the following URL endpoint, does not require a service ID: <code>http://domain.example.com:7778/xyz/providers/sample</code></p> <p>The service ID is used to look up a file called <code><service_id>.properties</code>, which defines the characteristics of the producer, such as whether to display its test page. Use any value to create the service ID.</p>
<i>proxyHost</i>	<p>Optional. Host name or IP address of the proxy server.</p> <p>A proxy is required if the application and the remote portlet producer are separated by a firewall and an HTTP proxy is needed for communication with the producer.</p>
<i>proxyPort</i>	<p>Optional. Port number on which the proxy server listens. This argument defaults to 80.</p>
<i>sharedKey</i>	<p>Optional. Shared key used for message authentication with the remote producer. Message authentication ensures that the incoming messages are sent from a host with a shared key. This argument defaults to null.</p> <p>The shared key can contain between 10 and 20 alphanumeric characters.</p>
<i>subscriberId</i>	<p>Optional. Consumer's identifier, if required.</p> <p>When a producer is registered with an application, a call is made to the producer. During the call, the consumer (WebCenter Portal or Portal Framework application in this instance) passes the value for <code>subscriberId</code> to the producer. The producer may be coded to use the subscriber ID.</p>
<i>timeout</i>	<p>Optional. Timeout setting for communications with the producer, in seconds. For example, the maximum time the producer may take to register, deregister, or display portlets on portal pages.</p> <p>This argument defaults to 30.</p> <p>Individual portlets may define their own timeout period, which takes precedence over the value expressed here.</p>

Argument	Definition
<i>establishSession</i>	Optional. Enable a user session when executing portlets from this producer. Valid values are 1 (true) and 0 (false). The default for this argument is 0. When sessions are enabled (1), the server maintains session-specific information, such as the user name. Message authentication uses sessions, so if a shared key is specified, this option should also be enabled. For sessionless communication between the producer and the server, specify 0.
<i>externalApp</i>	Optional. Name of the external application with which to associate the producer. Required if one of this producer's portlets requires authentication.
<i>mapUser</i>	Optional. Flag indicating whether the mapped user name from the external application should be passed to the producer. Valid values are 1 (true) and 0 (false). This argument defaults to 1.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <i>WC_Spaces</i> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.15.8.3 Example

The following example creates and registers an Oracle PDK-Java producer named `JPDKSamples` in WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig> registerPDKJavaProducer (appName='webcenter',
name='JPDKSamples', url='http://myhost:9999/jpdk/providers/sample')
```

10.15.9 setPDKJavaProducer

Module: Oracle WebCenter Portal

Use with WLST: Online

10.15.9.1 Description

Edits registration details for an existing PDK-Java producer.

10.15.9.2 Syntax

```
setPDKJavaProducer(appName, name, url, [serviceId, proxyHost, proxyPort,
subscriberId, sharedKey, timeout, establishSession, externalApp, mapUser, server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing PDK-Java producer.

Argument	Definition
<i>url</i>	<p>URL for the Oracle PDK-Java producer. Use the following syntax: <code>http://host_name:port_number/context_root/providers</code></p> <p>Where:</p> <ul style="list-style-type: none"> ■ <code>host_name</code> is the server where the producer is deployed ■ <code>port_number</code> is the HTTP Listener port number ■ <code>context_root</code> is the Web application's context root. ■ <code>providers</code> is static text. The text entered here depends on how the producer is deployed. <p>For example: <code>http://myHost:7778/myEnterprisePortlets/providers</code></p>
<i>serviceId</i>	<p>Optional. Service ID of the producer.</p> <p>PDK-Java enables you to deploy multiple producers under a single adapter servlet. Producers are identified by their unique service ID. A service ID is required only if the service ID is not appended to the URL end point.</p> <p>For example the following URL endpoint requires <code>sample</code> as the service ID: <code>http://domain.example.com:7778/xyz/providers</code></p> <p>However, the following URL endpoint, does not require a service ID: <code>http://domain.example.com:7778/xyz/providers/sample</code></p> <p>The service ID is used to look up a file called <code><service_id>.properties</code>, which defines the characteristics of the producer, such as whether to display its test page. Use any value to create the service ID.</p>
<i>proxyHost</i>	<p>Optional. Host name or IP address of the proxy server.</p> <p>A proxy is required if the application and the remote portlet producer are separated by a firewall and an HTTP proxy is needed for communication with the producer.</p>
<i>proxyPort</i>	Optional. Port number on which the proxy server listens.
<i>subscriberId</i>	<p>Optional. Consumer's identifier, if required.</p> <p>When a producer is registered with an application, a call is made to the producer. During the call, the consumer (WebCenter Portal or Portal Framework application in this instance) passes the value for Subscriber ID to the producer. If the producer does not see the expected value for Subscriber ID, it might reject the registration call.</p>
<i>sharedKey</i>	Optional. The shared key is used for message authentication with the remote producer. Message authentication ensures that the incoming messages are sent from a host with a shared key. You should enable sessions using the <code>sharedKey</code> argument, as well as the <code>establishSession</code> argument.
<i>timeout</i>	<p>Optional. Timeout setting for communications with the producer, in seconds. For example, the maximum time the producer may take to register, deregister, or display portlets on portal pages.</p> <p>Individual portlets may define their own timeout period, which takes precedence over the value expressed here.</p>

Argument	Definition
<i>establishSession</i>	Optional. Enable a user session when executing portlets from this producer. Valid values are 1 (true) and 0 (false). You should enable sessions using the <i>establishSession</i> argument, as well as the <i>sharedKey</i> argument. When sessions are enabled (1), the server maintains session-specific information, such as the user name. Message authentication uses sessions, so if a shared key is specified, this option should also be enabled. For sessionless communication between the producer and the server, set to 0.
<i>externalApp</i>	Optional. Name of the external application associated with this producer.
<i>mapUser</i>	Optional. Flag indicating whether the mapped user name from the external application should be passed to the producer. Valid values are 1 (true) and 0 (false).
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <i>WC_Spaces</i> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.15.9.3 Example

The following example changes a PDK-Java producer registered with *MyApp* to use a proxy server:

```
wls:/weblogic/serverConfig> setPDKJavaProducer(appName='MyApp', name='MyProducer',
url='http://myhost.com/jpdk/providers/sample', proxyHost='myproxy.com',
proxyPort=80)
```

10.15.10 deregisterPDKJavaProducer

Module: Oracle WebCenter Portal

Use with WLST: Online

10.15.10.1 Description

Deregisters an Oracle PDK-Java producer and deletes the associated connection, for a named application.

10.15.10.2 Syntax

```
deregisterPDKJavaProducer(appName, name, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <i>webcenter</i> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing PDK-Java producer.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <i>WC_Spaces</i> . Required when applications with the same name are deployed to different servers and also when you have a cluster.

Argument	Definition
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.15.10.3 Example

The following example deregisters the `wc-WebClipping` producer, and deletes the associated connection:

```
wls:/weblogic/serverConfig> deregisterPDKJavaProducer (appName='webcenter',
name='wc-WebClipping')
```

```
Already in Domain Runtime Tree
Producer wc-WebClipping has been deregistered.
Already in Domain Runtime Tree
"wc-WebClipping" successfully deleted
Already in Domain Runtime Tree
"wc-WebClipping-urlconn" successfully deleted
```

10.15.11 listPDKJavaProducers

Module: Oracle WebCenter Portal

Use with WLST: Online

10.15.11.1 Description

Lists details for one or more Oracle PDK-Java producers registered with a named application.

10.15.11.2 Syntax

```
listPDKJavaProducers (appName, [name, verbose, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Optional. Name of an existing PDK-Java portlet producer. If omitted, connection details for all PDK-Java producers configured for this application are listed.
<i>verbose</i>	Optional. Displays PDK-Java producer connection details in verbose mode. Valid options are 1 (true) and 0 (false). When set to 1, <code>listPDKJavaProducers</code> lists all connection properties. When set to 0, <code>listPDKJavaProducers</code> lists connection names only. This argument defaults to 1. If you set this argument to 0, do not specify the name argument.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.15.11.3 Example

The following example lists all the connection properties (verbose mode) for the JPDKSamples producer:

```
wls:/weblogic/serverConfig> listPDKJavaProducers (appName='webcenter',
name='JPDKSamples', verbose=1)

-----
wc-WebClipping
-----
Service Id: None
Shared Key: None
External Application Id: None
Subscriber Id: None
URL: http://myhost.com:9999/portalTools/webClipping/providers/webClipping
-----
wc-OmniPortlet
-----
Service Id: None
Shared Key: None
External Application Id: None
Subscriber Id: None
URL: http://myhost:9999/portalTools/omniPortlet/providers/omniPortlet
```

10.15.12 registerPageletProducer

Module: Oracle WebCenter Portal

Use with WLST: Online

10.15.12.1 Description

Registers a pagelet producer with a named application.

10.15.12.2 Syntax

```
registerPageletProducer(appName, name, url, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Connection name. The name must be unique (across all connection types) within the application. The name you specify here appears in Composer under the <i>Mash-ups > Pagelet Producers</i> folder (by default).

Argument	Definition
<i>url</i>	<p>URL required to access the server where the Pagelet Producer is deployed. Use the syntax:</p> <pre>protocol://host.domain:port_number/pagelets</pre> <p>The URL must include a fully-qualified domain name. For example:</p> <pre>http://myhost.example.com:7778/pagelets</pre> <p>If pagelets carry secure data, the URL registered must use the https protocol. For example:</p> <pre>https://myhost.com:7779/pagelets</pre> <p>Note: In WebCenter Portal, if the Pagelet Producer URL is protected by Oracle Access Manager (OAM), the URL to the pagelet catalog must be excluded (mapped directly without access control), or the catalog will appear to be empty when using REST. The pagelet catalog URL is:</p> <pre>http://proxy_host:proxy_port/api/v2/ensemble/pagelets</pre>
<i>server</i>	<p>Optional. Name of the managed server where the application is deployed. For example, <i>WC_Spaces</i>.</p> <p>Required when applications with the same name are deployed to different servers and also when you have a cluster.</p>
<i>applicationVersion</i>	<p>Optional. Version number of the deployed application. Required if more than one version of the application is deployed.</p>

10.15.12.3 Example

The following example registers a pagelet producer with WebCenter Portal (*webcenter*):

```
wls:/weblogic/serverConfig> registerPageletProducer(appName='webcenter',
name='MyPageletProducer', url='http://myhost.com:7001/pagelets')
```

10.15.13 setPageletProducer

Module: Oracle WebCenter Portal

Use with WLST: Online

10.15.13.1 Description

Edits connection details for an existing pagelet producer.

10.15.13.2 Syntax

```
setPageletProducer(appName, name, [url, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	<p>Name of the application in which to perform this operation.</p> <p>For WebCenter Portal, the application name is always <i>webcenter</i>.</p> <p>For Portal Framework applications, specify the appropriate name.</p>
<i>name</i>	<p>Name of an existing pagelet producer connection.</p>

Argument	Definition
<i>url</i>	<p>Optional. URL required to access the server where the Pagelet Producer is deployed. Use the syntax:</p> <p><i>protocol://host.domain:port_number/pagelets</i></p> <p>The URL must include a fully-qualified domain name. For example:</p> <p><code>http://myhost.example.com:7778/pagelets</code></p> <p>Note: In WebCenter Portal, if the Pagelet Producer URL is protected by Oracle Access Manager (OAM), the URL to the pagelet catalog must be excluded (mapped directly without access control), or the catalog will appear to be empty when using REST. The pagelet catalog URL is:</p> <p><code>http://proxy_host:proxy_port/api/v2/ensemble/pagelets</code></p>
<i>server</i>	<p>Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code>.</p> <p>Required when applications with the same name are deployed to different servers and also when you have a cluster.</p>
<i>applicationVersion</i>	<p>Optional. Version number of the deployed application. Required if more than one version of the application is deployed.</p>

10.15.13.3 Example

The following example updates administrator user name and password details for an existing pagelet producer connection named `MyPageletProducer`:

```
wls:/weblogic/serverConfig> setPageletProducer(appName='webcenter',
name='MyPageletProducer', url='http://mypagelethost.com:7778/pagelets')
```

10.15.14 listPageletProducers

Module: Oracle WebCenter Portal

Use with WLST: Online

10.15.14.1 Description

Lists connection details for one or all pagelet producers registered with a named application.

10.15.14.2 Syntax

```
listPageletProducers(appName, [name, verbose, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	<p>Name of the application in which to perform this operation.</p> <p>For WebCenter Portal, the application name is always <code>webcenter</code>.</p> <p>For Portal Framework applications, specify the appropriate name.</p>
<i>name</i>	<p>Optional. Name of an existing pagelet producer connection. Use this argument to view connection details for a specific pagelet producer.</p> <p>If omitted, connection details for all pagelet producers configured for this application are listed.</p>

Argument	Definition
<i>verbose</i>	Optional. Displays pagelet producer connection details in verbose mode. Valid options are 1 (true) and 0 (false). When set to 1, <code>listPageletProducers</code> lists all connection properties. When set to 0, <code>listPageletProducers</code> lists connection names only. This argument defaults to 1. If you set this argument to 0, do not specify the name argument.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.15.14.3 Example

The following example lists connection names and details for all pagelet producers currently registered for a Portal Framework application named `MyWebCenterApp`:

```
wls:/weblogic/serverConfig> listPageletProducers (appName='MyWebCenterApp',
verbose=1)
```

```
-----
MyPageletProducer
-----
URL: http://myhost.com:7001/pagelets
-----
TestPageletProducer
-----
URL: http://testhost.com:7002/pagelets
-----
```

The following example displays details for a single pagelet producer connection named `MyPageletProducer`:

```
wls:/weblogic/serverConfig> listPageletProducers (appName='webcenter',
name='MyPageletProducer', verbose=1)
```

```
-----
MyPageletProducer
-----
URL: http://myhost.com:7001/pagelets
```

10.15.15 deregisterPageletProducer

Module: Oracle WebCenter Portal

Use with WLST: Online

10.15.15.1 Description

Deregisters a pagelet producer currently registered with a named application.

10.15.15.2 Syntax

```
deregisterPageletProducer (appName, name, [server, applicationVersion])
```


Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing pagelet producer connection.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.15.15.3 Example

The following example deregisters a pagelet producer connection named `MyPageletProducer` currently configured for a Portal Framework application named `MyWebCenterApp`:

```
wls:/weblogic/serverConfig> deregisterPageletProducer (appName='MyWebCenterApp',
name='MyPageletProducer')
```

10.15.16 refreshProducer

Module: Oracle WebCenter Portal

Use with WLST: Online

10.15.16.1 Description

Refreshes the metadata stored for a named producer to reflect the portlets that are currently offered by that producer.

10.15.16.2 Syntax

```
refreshProducer (appName, producerName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>producerName</i>	Name of an existing producer.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.15.16.3 Example

The following example refreshes the `WSRPSamples` producer in WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig> refreshProducer (appName='webcenter',
```

```
producerName='WSRPSamples')
```

Producer WSRPSamples has been refreshed.

10.15.17 listPortletClientConfig

Module: Oracle WebCenter Portal

Use with WLST: Online

10.15.17.1 Description

Lists portlet client's configuration for a named application.

10.15.17.2 Syntax

```
listPortletClientConfig(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.15.17.3 Examples

The following example lists portlet client configuration for a Portal Framework application named `myPortalApp`.

```
wls:/weblogic/serverConfig> listPortletClientConfig(appName='myPortalApp')
```

```
-----
Portlet Client Configuration Settings
-----
Application Striping: 0
Content Cache Enabled: 0
Maximum Content Cache Objects: 2000
Maximum Content Cache Size: 10000000
Default Timeout: 30
Maximum IFrame Querystring Length: 0
Maximum Resource URL Length: 1500
Maximum Timeout: 60
Minimum Timeout: 2
Parallel Pool Size: 20
Parallel Queue Size: 40
Maximum Rendition Cache Objects: 1000
Resource Proxy Path: /resource-proxy
Supported Locales: en, de, fr
```

10.15.18 setPortletClientConfig

Module: Oracle WebCenter Portal

Use with WLST: Online

10.15.18.1 Description

Edits the portlet client's configuration, for a named application. If you omit a parameter, the corresponding configuration setting remains unchanged.

Note: Configuration changes made using this WLST command are only effective after you restart the Managed Server on which the application is deployed. For details, see *Oracle Fusion Middleware Administering Oracle WebCenter Portal*.

10.15.18.2 Syntax

```
setPortletClientConfig(appName, [applicationStriping, contentCacheEnabled,
contentCacheMaxObjects, contentCacheMaxSize, defaultTimeout,
maximumIframeQueryStringLength, maximumResourceUrlLength, maximumTimeout,
minimumTimeout, parallelPoolSize, parallelQueueSize,
renditionCacheMaxObjects, resourceProxyPath, supportedLocales, server,
applicationVersion])
```

Argument	Definition
<code>appName</code>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<code>applicationStriping</code>	Optional. Specifies whether to enable application striping. Valid values are 1 (true) and 0 (false). The default value is 0 (false).
<code>contentCacheEnabled</code>	Optional. Specifies whether to enable the portlet client's content cache. Valid values are 1 (true) and 0 (false). The default value is 1 (true).
<code>contentCacheMaxObjects</code>	Optional. Maximum number of objects to be stored in the portlet client's content cache. The default value is 0 (unlimited).
<code>contentCacheMaxSize</code>	Optional. Maximum size of the portlet client's content cache in bytes. The default value is 0 (unlimited).
<code>defaultTimeout</code>	Optional. Default timeout period in seconds for requests made to producers. The default value is 10 seconds.
<code>maximumIframeQueryStringLength</code>	Optional. Maximum length of portlet inline frame URLs before URL shortening is applied. The default value is 0 (always shorten URLs).
<code>maximumResourceUrlLength</code>	Optional. Maximum length of portlet resource URLs. The default value is 1500.
<code>maximumTimeout</code>	Optional. Maximum timeout period in seconds for requests made to producers. The default value is 300 seconds.

Argument	Definition
<i>minimumTimeout</i>	Optional. Minimum timeout period in seconds for requests made to producers. The default value is 1.
<i>parallelPoolSize</i>	Optional. Number of threads used for parallel execution of tasks. The default value is 10.
<i>parallelQueueSize</i>	Optional. Number of tasks to allow in queue for parallel execution. The default value is 20.
<i>renditionCacheMaxObjects</i>	Optional. Maximum number of objects in the cache used by the portlet client to store portlet renditions for use when rendering portlets in inline frames. The default value is 25.
<i>resourceProxyPath</i>	Optional. The base path of the portlet resource proxy servlet, relative to the context root of the application. The default value is <code>/resourceproxy</code> .
<i>supportedLocales</i>	Optional. Specifies one or more locales supported by the portlet client. The default value is <code>en</code> (English). Separate multiple locales with a comma. For example: <code>supportedLocales='en, fr, de'</code>
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.15.18.3 Examples

The following example sets new values for the `ContentCacheEnabled`, `MinimumTimeout`, `MaximumTimeout`, and `ParallelQueueSize` configuration settings. All other settings remain unchanged:

```
wls:/weblogic/serverConfig> setPortletClientConfig(appName='myPortalApp',
contentCacheEnabled=0, minimumTimeout=10, maximumTimeout=120,
parallelQueueSize=25)
```

The following example sets the value of the `SupportedLocales` configuration setting to English, French, and Spanish. All other settings remain unchanged:

```
wls:/weblogic/serverConfig> setPortletClientConfig(appName='myPortalApp',
supportedLocales='en, fr, es')
```

10.15.19 getPortletClientConfig

Module: Oracle WebCenter Portal

Use with WLST: Online

10.15.19.1 Description

Returns the value of a specific portlet client configuration setting or values of all settings for a named application.

10.15.19.2 Syntax

```
getPortletClientConfig(appName, [configSetting, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>configSetting</i>	Optional. Name of the portlet client configuration setting to return. One of the following values: <code>ApplicationStriping</code> <code>ContentCacheEnabled</code> <code>ContentCacheMaxObjects</code> <code>ContentCacheMaxSize</code> <code>DefaultTimeout</code> <code>MaximumIframeQueryStringLength</code> <code>MaximumResourceUrlLength</code> <code>MaximumTimeout</code> <code>MinimumTimeout</code> <code>ParallelPoolSize</code> <code>ParallelQueueSize</code> <code>RenditionCacheMaxObjects</code> <code>ResourceProxyPath</code> <code>SupportedLocales</code> Note: The values are case-sensitive. Omit this parameter to return the names and values of all settings.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.15.19.3 Examples

The following example returns the value of the `DefaultTimeout` configuration setting for a Portal Framework application named `myPortalApp`:

```
wls:/weblogic/serverConfig> defaultTimeout =
getPortletClientConfig(appName='myPortalApp', configSetting='DefaultTimeout')
```

The following example returns the names and values of all portlet client configuration settings for a Portal Framework application named `myPortalApp` in a dict:

```
wls:/weblogic/serverConfig> settingsDict =
getPortletClientConfig(appName='myPortalApp')
```

10.15.20 registerOOTBProducers

Module: Oracle WebCenter Portal

Use with WLST: Online

10.15.20.1 Description

Registers several out-of-the-box producers with WebCenter Portal or a Portal Framework application: OmniPortlet, Web Clipping, and WSRP Tools

10.15.20.2 Syntax

```
registerOOTBProducers(producerHost, producerPort, appName, [server,
applicationVersion])
```

Argument	Definition
<i>producerHost</i>	Host name or IP address of the server hosting out-of-the-box producers. In a cluster fronted by a load balancer, enter the host name of the load balancer.
<i>producerPort</i>	Port number for the server hosting out-of-the-box producers. In a cluster, fronted by a load balancer, enter the port number of the load balancer.
<i>appName</i>	Name of the application in which the out-of-the-box producers are to be registered. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.15.20.3 Example

The following example registers out-of-the-box producers in a Portal Framework application named `myApp`.

```
wls:/weblogic/serverConfig> registerOOTBProducers(producerHost='myhost.com',
producerPort=9999, appName='myApp')
```

```
Registering Out-of-the-Box Producers
Registering producers at http://myhost.com:9999
```

```
Registering Omniportlet
Created connection wc-OmniPortlet-urlconn
Created connection wc-OmniPortlet
Producer connection wc-OmniPortlet has been registered.
```

```
Registering WebClipping
Created connection wc-WebClipping-urlconn
Created connection wc-WebClipping
Producer connection wc-WebClipping has been registered.
```

```
Registering WSRP Tools
Created connection wc-WSRPTools-wsconn
Created connection wc-WSRPTools
Producer connection wc-WSRPTools has been registered.
```

10.15.21 deregisterOOTBProducers

Module: Oracle WebCenter Portal

Use with WLST: Online

10.15.21.1 Description

Deregisters out-of-the-box producers with WebCenter Portal or a Portal Framework application: OmniPortlet, Web Clipping, and WSRP Tools

10.15.21.2 Syntax

```
deregisterOOTBProducers(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which the out-of-the-box producers are currently registered. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.15.21.3 Example

The following example deregisters out-of-the-box producers, and deletes their associated connections, in a Portal Framework application named `myApp`.

```
wls:/weblogic/serverConfig> deregisterOOTBProducers (appName='myApp')
```

```
Deregistering Out-of-the-Box Producers
```

```
Deregistering Omniportlet
```

```
Producer wc-OmniPortlet has been deregistered.
```

```
wc-OmniPortlet successfully deleted
```

```
wc-OmniPortlet-urlconn successfully deleted
```

```
Deregistering WebClipping
```

```
Producer wc-WebClipping has been deregistered.
```

```
wc-WebClipping successfully deleted
```

```
wc-WebClipping-urlconn successfully deleted
```

```
Deregistering WSRP Tools
```

```
Producer wc-WSRPTools has been deregistered.
```

```
wc-WSRPTools successfully deleted
```

```
wc-WSRPTools-wsconn successfully deleted
```

10.15.22 registerSampleProducers

Module: Oracle WebCenter Portal

Use with WLST: Online

10.15.22.1 Description

Registers the sample producers provided with Oracle WebCenter Portal with a named application. There are two sample producers— WSRP Samples and JPDK Samples.

10.15.22.2 Syntax

```
registerSampleProducers(producerHost, producerPort, appName, [server,
applicationVersion])
```

Argument	Definition
<i>producerHost</i>	Host name or IP address of the server hosting the sample producers.
<i>producerPort</i>	Port number for the server hosting the sample producers.
<i>appName</i>	Name of the application in which the sample producers are to be registered. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.15.22.3 Example

The following example registers Oracle WebCenter Portal's sample producers in a Portal Framework application named `myApp`:

```
wls:/weblogic/serverConfig> registerSampleProducers(producerHost='myhost.com',
producerPort=9999, appName='myApp')
```

10.15.23 deregisterSampleProducers

Module: Oracle WebCenter Portal

Use with WLST: Online

10.15.23.1 Description

Deregisters Oracle WebCenter Portal's sample producers (WSRP Samples and JPDK Samples) from a named application.

10.15.23.2 Syntax

```
deregisterSampleProducers(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which the sample producers are currently registered. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name. If a value is not specified, this argument defaults to <code>webcenter</code> .

Argument	Definition
<code>server</code>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<code>applicationVersion</code>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.15.23.3 Example

The following example deregisters sample producers from a Portal Framework application named `myApp`.

```
wls:/weblogic/serverConfig> deregisterSampleProducers(appName='myApp')
```

10.16 Proxy Server

Use the commands listed in [Table 10–24](#) to manage proxy server settings used by tools and services, in a named application.

Configuration changes made using these WLST commands are only effective after your restart the Managed Server on which the application is deployed. For details, see *Oracle Fusion Middleware Administering Oracle WebCenter Portal*.

Table 10–24 RSS WLST Commands

Use this command...	To...	Use with WLST...
getWebCenterProxyConfig	Return the proxy host and proxy port used by the tools and services.	Online
setWebCenterProxyConfig	Specify the proxy host and proxy port used by tools and services.	Online
unsetWebCenterProxyConfig	Delete proxy host and proxy port settings.	Online
getRssProxyConfig	Deprecated.	Online
setRssProxyConfig	Deprecated.	Online
unsetRssProxyConfig	Deprecated.	Online

10.16.1 getWebCenterProxyConfig

Module: Oracle WebCenter Portal

Use with WLST: Online

10.16.1.1 Description

Returns the proxy host and proxy port used by RSS news feeds and activity streams in a named application. Depending on your network configuration, proxy details may be required to display external RSS news feeds and external links in activity streams in your application.

10.16.1.2 Syntax

```
getWebCenterProxyConfig(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.16.1.3 Example

The following example returns the proxy host and proxy port used by tools and services in WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig> getWebCenterProxyConfig (appName='webcenter')
```

10.16.2 setWebCenterProxyConfig

Module: Oracle WebCenter Portal

Use with WLST: Online

10.16.2.1 Description

Specifies the proxy host and proxy port used by RSS news feeds and activity streams, in a named application. Depending on your network configuration, proxy details may be required to display external RSS news feeds and external links in activity streams in your application.

10.16.2.2 Syntax

```
setWebCenterProxyConfig(appName, proxyHost, proxyPort, [server,  
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>proxyHost</i>	Host name of the proxy server.
<i>proxyPort</i>	Port on which the proxy server is running.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.16.2.3 Example

The following example sets the proxy host and proxy port used by tools and services in WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig> setWebCenterProxyConfig(appName='webcenter',
proxyHost='www-proxy.example.com', proxyPort='80')
```

10.16.3 unsetWebCenterProxyConfig

Module: Oracle WebCenter Portal

Use with WLST: Online

10.16.3.1 Description

Deletes the current proxy host and proxy port settings configured for a named application.

10.16.3.2 Syntax

```
unsetWebCenterProxyConfig(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.16.3.3 Example

The following example deletes the proxy host and proxy port settings configured for WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig> unsetWebCenterProxyConfig(appName='webcenter')
```

10.16.4 getRssProxyConfig

Module: Oracle WebCenter Portal

Use with WLST: Online

10.16.4.1 Description

(Deprecated from 11.1.1.8.0. Use [getWebCenterProxyConfig](#) instead.)

Returns the proxy host and proxy port used by tools and services. Depending on your network configuration, proxy details may be required to display external RSS news feeds and external links in activity streams in your application.

10.16.4.2 Syntax

```
getRssProxyConfig(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.16.4.3 Example

The following example returns the proxy host and proxy port used by tools and services in WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig> getRssProxyConfig (appName= 'webcenter')
```

10.16.5 setRssProxyConfig

Module: Oracle WebCenter Portal

Use with WLST: Online

10.16.5.1 Description

(Deprecated from 11.1.1.8.0. Use [setWebCenterProxyConfig](#) instead.)

Specifies the proxy host and proxy port used by tools and services, such as RSS news feeds and activity streams. Depending on your network configuration, proxy details may be required to display external RSS news feeds and external links in activity streams in your application.

10.16.5.2 Syntax

```
setRssProxyConfig(appName, proxyHost, proxyPort, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>proxyHost</i>	Host name of the proxy server.
<i>proxyPort</i>	Port on which the proxy server is running.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.16.5.3 Example

The following example sets the proxy host and proxy port used by tools and services in WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig> setRssProxyConfig(appName='webcenter',
proxyHost='www-proxy.example.com', proxyPort='80')
```

10.16.6 unsetRssProxyConfig

Module: Oracle WebCenter Portal

Use with WLST: Online

10.16.6.1 Description

(Deprecated from 11.1.1.8.0. Use [unsetWebCenterProxyConfig](#) instead.)

Deletes the current proxy host and proxy port settings used by tools and services.

10.16.6.2 Syntax

```
unsetRssProxyConfig(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.16.6.3 Example

The following example deletes the proxy host and proxy port settings used by tools and services in WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig> unsetRssProxyConfig(appName='webcenter')
```

10.17 Search - Oracle SES Search

Use the commands listed in [Table 10–25](#) to manage Oracle Secure Enterprise Search (SES) connections and other Oracle SES search related properties for WebCenter Portal and Portal Framework applications.

Configuration changes made using these WLST commands are only effective after your restart the Managed Server on which the application is deployed. For details, see *Oracle Fusion Middleware Administering Oracle WebCenter Portal*.

Table 10–25 Search - Oracle SES WLST Commands

Use this command...	To...	Use with WLST...
createSESConnection	Create a connection to an Oracle SES instance for a named application.	Online
setSESConnection	Edit an existing Oracle SES search connection.	Online
listSESConnections	List individual or all Oracle SES search connections that are configured for a named application.	Online

Table 10–25 (Cont.) Search - Oracle SES WLST Commands

Use this command...	To...	Use with WLST...
setSearchSESConfig	Configure search settings for an existing Oracle SES search connection.	Online
listSearchSESConfig	List Oracle SES properties for a named application.	Online
createFederationTrustedEntity	Create a federation trusted entity on an Oracle (SES) instance.	Online
setSESVersion	Obtains and stores version information for the Oracle SES instance that is currently configured for a named application.	Online
listSESVersion	Returns version information for the Oracle SES instance configured for a named application.	Online
createDefaultSourceGroup	Creates a source group in Oracle SES instance with default document, discussion, and announcement sources.	Online

10.17.1 createSESConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.17.1.1 Description

Creates a connection to an Oracle Secure Enterprise Search (SES) instance for a named application.

10.17.1.2 Syntax

```
createSESConnection(appName, name, url, appUser, appPassword, [default, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Connection name. The name must be unique (across all connection types) within the application.
<i>url</i>	Web services URL that Oracle Secure Enterprise Search exposes to enable Search requests. Use the format: <code>http://host:port/search/query/OracleSearch</code>
<i>appUser</i>	User name that the application uses to authenticate itself as a trusted application to Oracle Secure Enterprise Search so that it may perform searches on behalf of WebCenter Portal users. The specified user must be present in both the Oracle Identity Management server configured for the application and the Oracle Identity Management server configured for Oracle SES.
<i>appPassword</i>	Password for the user name specified.

Argument	Definition
<i>default</i>	Optional. Configures search to actively use the search connection. Valid options are 1 (true) and 0 (false). Setting to 1 replaces any other search connection that is being used. Setting to 0 does not change the current search configuration. This argument defaults to 0.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.17.1.3 Example

The following example creates a new search connection that points to the Oracle SES instance `http://myhost.com:7777/search/query/OracleSearch` and makes this connection the active SES search connection for a Portal Framework application named `myApp`.

```
wls:/weblogic/serverConfig>createSESConnection(appName='myApp', name='SESConn1',
url='http://myhost.com:7777/search/query/OracleSearch', appUser='wpadmin',
appPassword='password', default=1)
```

10.17.2 setSESConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.17.2.1 Description

Edits an existing Oracle Secure Enterprise Search (SES) search connection for a named application.

10.17.2.2 Syntax

```
setSESConnection(appName, name, [url, appUser, appPassword, default, server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing search connection.
<i>url</i>	Optional. Web services URL that Oracle Secure Enterprise Search exposes to enable Search requests. Use the format: <code>http://host:port/search/query/OracleSearch</code>
<i>appUser</i>	Optional. User name that the application uses to log in to Oracle Secure Enterprise Search so that it may perform searches on behalf of portal users.

Argument	Definition
<i>appPassword</i>	Optional. Password that the application uses to log in to Oracle Secure Enterprise Search so that it may perform searches on behalf of portal users.
<i>default</i>	Optional. Configures search to actively use the search connection. Valid options are 1 (true) and 0 (false). Setting to 1 replaces any other search connection that is being used. Setting to 0 does not change the current search configuration. This argument defaults to 0.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.17.2.3 Example

The following example modifies the URL of a search connection named `SESConn1` and makes the connection the active Oracle SES search connection for a Portal Framework application named `myApp`.

```
wls:/weblogic/serverConfig> etSESSConnection(appName='myApp', name='SESConn1',
url='http://myhost.com:7777/search/query/OracleSearch', appUser='wpadmin',
appPassword='password', default=1)
```

10.17.3 listSESSConnections

Module: Oracle WebCenter Portal

Use with WLST: Online

10.17.3.1 Description

Lists the names of all Oracle Secure Enterprise Search (SES) search connections configured for a named application.

10.17.3.2 Syntax

```
listSESSConnections(appName, [verbose, name, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>verbose</i>	Optional. Displays search connection details in verbose mode. Valid options are 1 (true) and 0 (false). When set to 1, <code>listSESSConnections</code> lists all of the SES search connections that are configured for an application, along with their details. When set to 0, <code>listSESSConnections</code> lists connection names only. This argument defaults to 0. If you set this argument to 0, do not specify the name argument.

Argument	Definition
<i>name</i>	Optional. Name of an existing search connection. You can use this argument to view details about a specific connection.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.17.3.3 Examples

The following example displays connection details for all Oracle SES search connections configured for a Portal Framework application named `myApp`.

```
wls:/weblogic/serverConfig>listSESConnections (appName='myApp', verbose=1)
```

The following example displays connection details for an Oracle SES search connection named `SESConn1`.

```
wls:/weblogic/serverConfig>listSESConnections (appName='myApp', verbose=1,
name='SESConn1')
```

10.17.4 setSearchSESConfig

Module: Oracle WebCenter Portal

Use with WLST: Online

10.17.4.1 Description

Configures search settings for an existing Oracle Secure Enterprise Search (SES) search connection. If a parameter is not specified it is not modified.

10.17.4.2 Syntax

```
setSearchSESConfig(appName,[connectionName, dataGroup, topNRows, server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>connectionName</i>	Optional. Names the connection used for search.
<i>dataGroup</i>	Optional. Names the Secure Enterprise Search data group in which to search. If a value is not provided, everything in the Oracle Secure Enterprise Search instance will be searched.
<i>topNRows</i>	Optional. Number of top N rows of search results for gathering refinement data.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.

Argument	Definition
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.17.4.3 Example

The following example specifies that search must use the SES search connection named `SESConn1`, and to search the data group named `group2`:

```
wls:/weblogic/serverConfig>setSearchSESConfig(appName='webcenter',connectionName='SESConn1',dataGroup='group2',topNRows=200);
```

The following example changes the maximum number of results that search returns. No connection name is specified in this example, so this configuration change is applied to the current default (or active) search connection:

```
wls:/weblogic/serverConfig>setSearchSESConfig(appName='webcenter',topNRows=500);
Already in Domain Runtime Tree
Restart is needed for the service connection changes to take effect.
```

10.17.5 listSearchSESConfig

Module: Oracle WebCenter Portal

Use with WLST: Online

10.17.5.1 Description

Lists Oracle SES search settings for a named application.

10.17.5.2 Syntax

```
listSearchSESConfig(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.17.5.3 Example

The following example displays Oracle SES search configuration information for WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig>listSearchSESConfig(appName='webcenter')
Already in Domain Runtime Tree
-----
Search SES Config
-----
connectionName:  SESConn1
dataGroup:      group2
```

topNRows: 200

10.17.6 createFederationTrustedEntity

Module: Oracle WebCenter Portal

Use with WLST: Online

10.17.6.1 Description

Creates a federation trusted entity on an Oracle Secure Enterprise Search (SES) instance for a given entity name and password.

10.17.6.2 Syntax

```
createFederationTrustedEntity(appName, sesUrl, sesPassword, entityName,
entityPassword, desc, [sesSchema, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>sesUrl</i>	Web service URL for the Oracle SES Administration API. Use the format: <code>http://host:port/search/api/admin/AdminService</code>
<i>sesPassword</i>	Password for the Oracle SES administrative user (<code>eqsys</code>).
<i>entityName</i>	Entity name.
<i>entityPassword</i>	Entity password.
<i>desc</i>	Short description of the entity. Alternatively, specify an empty string ' '.
<i>sesSchema</i>	Username for the Oracle SES administrative user. The default value is <code>eqsys</code> .
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.17.6.3 Example

The following example creates a federation trusted entity named `myEntity` on the Oracle SES instance

```
http://myseshost.com:7777/search/query/OracleSearch:
```

```
wls:/weblogic/serverConfig>
createFederationTrustedEntity(appName='webcenter',
sesUrl='http://myseshost.com:7777/search/api/admin/AdminService',
sesSchema='eqsys', sesPassword='password', entityName='myEntity',
entityPassword='password', desc='This is a my sample entity')
```

10.17.7 setSESVersion

Module: Oracle WebCenter Portal

Use with WLST: Online

10.17.7.1 Description

Obtains version information for the Oracle Secure Enterprise Search (SES) instance that is configured for a named application, and stores the version for use by search queries later on.

Version information is used when the Oracle SES connection is set as the default connection for search queries.

10.17.7.2 Syntax

```
setSESVersion(appName, sesUrl, sesSchema, sesPassword, [server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>sesUrl</i>	Web service URL for the Oracle SES Administration API. Use the format: <code>http://host:port/search/api/admin/AdminService</code>
<i>sesSchema</i>	Username for the Oracle SES administrative user. For example, <code>searchsys</code> .
<i>sesPassword</i>	Password for the Oracle SES administrative user.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.17.7.3 Example

The following example obtains version information for the Oracle SES instance `http://myhost.com:7777/search/query/OracleSearch` and makes this information available to a Portal Framework application named `MyApp`:

```
wls:/weblogic/serverConfig>setSESVersion(appName='myApp',
sesUrl='http://myseshost.com:7777/search/api/admin/AdminService',
sesSchema='searchsys', sesPassword='password')
```

10.17.8 listSESVersion

Module: Oracle WebCenter Portal

Use with WLST: Online

10.17.8.1 Description

Returns the version number of the Oracle Secure Enterprise Search (SES) instance that is being used by a named application.

10.17.8.2 Syntax

```
listSESVersion(appName, sesUrl, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>sesUrl</i>	Web service URL for the Oracle SES Administration API. Use the format: <code>http://host:port/search/api/admin/AdminService</code>
<i>sesUrl</i>	Web service URL for the Oracle SES Administration API. Use the format: <code>http://host:port/search/api/admin/AdminService</code>
<i>sesSchema</i>	Username for the Oracle SES administrative user. For example, <code>searchsys</code> .
<i>sesPassword</i>	Password for the Oracle SES administrative user.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.17.8.3 Example

The following example returns version information for the Oracle SES instance `http://myhost.com:7777/search/query/OracleSearch` and confirms that the version information is saved in the Portal Framework application named `MyApp`:

```
wls:/weblogic/serverConfig>listSESVersion(appName='myApp',
sesUrl='http://myseshost.com:7777/search/api/admin/AdminService')
```

```
-----
SES Version Config
-----
url: http://myhost.com:7777/search/api/admin/AdminService
version: 11.1.2.2.0
```

10.17.9 createDefaultSourceGroup

Module: Oracle WebCenter Portal

Use with WLST: Online

10.17.9.1 Description

Creates a source group in an Oracle Secure Enterprise Search (SES) instance with a default name, for a given host, port and application name, as well as the shared documents and discussions/announcement sources.

10.17.9.2 Syntax

```
createDefaultSourceGroup(appName, sesUrl, sesPassword, host, port, defaultHost,
defaultPort, [sesSchema, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>sesUrl</i>	Web service URL for the Oracle SES Administration API. Use the format: <code>http://host:port/search/api/admin/AdminService</code>
<i>sesPassword</i>	Password for the Oracle SES administrative user.
<i>host</i>	Host name of the machine where the application is running.
<i>port</i>	Port number used to access the application.
<i>defaultHost</i>	Host name of the machine where the default sources are configured.
<i>defaultPort</i>	Port number used where the default sources are configured.
<i>sesSchema</i>	Optional. Username for the Oracle SES administrative user. Default value is <code>eqsys</code> .
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.17.9.3 Example

The following example creates a default source group in the Oracle SES instance `http://myhost.com:7777/search/query/OracleSearch` for the Portal Framework application named `myApp` at: `http://webhost:8888/webcenter`

The default source group also includes documents and discussions sources at: `http://mydefaultHost:8989`

```
wls:/weblogic/serverConfig>createDefaultSourceGroup(appName='myApp',
sesUrl='http://myseshost.com:7777/search/api/admin/AdminService',
sesSchema='eqsys', sesPassword='password', host='webhost', port='8888',
defaultHost='mydefaultHost', defaultPort='8989')
```

10.18 Search - Oracle SES Search Crawlers

Use the commands listed in [Table 10-26](#) to manage Oracle Secure Enterprise Search (SES) crawlers for WebCenter Portal and Portal Framework applications.

There is no need to restart your application after running Oracle SES crawler WLST commands.

Table 10–26 Search - Oracle SES Crawler WLST Commands

Use this command...	To...	Use with WLST...
createSpacesCrawler	Create a crawler for WebCenter Portal objects on an Oracle SES instance.	Online
createDocumentsCrawler	Create a documents crawler for a named application, on an Oracle SES instance.	Online
createDiscussionsCrawler	Create a discussions crawlers and an announcement crawler for a named application, on an Oracle SES instance.	Online
listSpacesCrawler	Return the Spaces crawler configured for WebCenter Portal, on an Oracle SES instance.	Online
listDocumentsCrawler	Return the documents crawler configured for a named application, on an Oracle SES instance.	Online
listDiscussionsCrawler	Return the discussion and announcement crawlers configured for a named application, on an Oracle SES instance.	Online
startSpacesCrawler	Start the Spaces crawler configured for WebCenter Portal, on an Oracle SES instance.	Online
startDocumentsCrawler	Start the documents crawler configured for a named application, on an Oracle SES instance.	Online
startDiscussionsCrawler	Start the discussion and announcement crawlers configured for a named application, on an Oracle SES instance.	Online
stopSpacesCrawler	Stop the Spaces crawler configured for WebCenter Portal, on an Oracle SES instance.	Online
stopDocumentsCrawler	Stop the documents crawler configured for a named application, on an Oracle SES instance.	Online
stopDiscussionsCrawler	Stop discussion and announcement crawlers configured for a named application, on an Oracle SES instance.	Online
deleteSpacesCrawler	Delete the Spaces crawler configured for WebCenter Portal, on an Oracle SES instance.	Online
deleteDocumentsCrawler	Delete the documents crawler configured for a named application, on an Oracle SES instance.	Online
deleteDiscussionsCrawler	Delete discussion and announcement crawlers configured for a named application, on an Oracle SES instance.	Online

10.18.1 createSpacesCrawler

Module: Oracle WebCenter Portal

Use with WLST: Online

10.18.1.1 Description

Creates a crawler for WebCenter Portal objects on an Oracle SES instance. The command creates a WebCenter Portal datasource and specifies a schedule for crawling WebCenter Portal objects (such as portals, lists, pages, and people).

10.18.1.2 Syntax

```
createSpacesCrawler(appName, host, port, sesUrl, sesPassword, crawlUser,
crawlPassword, scratchDir, authUserIdFormat, crawlingMode, recrawlPolicy,
freqType, startHour, hoursBetweenLaunches, startDayOfWeek, startDayOfMonth,
daysBetweenLaunches, weeksBetweenLaunches, monthsBetweenLaunches, [server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> .
<i>host</i>	Host name of the machine where WebCenter Portal is running.
<i>port</i>	Port number used to access WebCenter Portal.
<i>sesUrl</i>	Web service URL for the Oracle SES Administration API. Use the format: <code>http://host:port/search/api/admin/AdminService</code>
<i>sesPassword</i>	Password for the Oracle SES administrative user (<code>eqsys</code>).
<i>crawlUser</i>	Crawl administration user in WebCenter Portal. This user must exist in WebCenter Portal and in your back-end identity management server with appropriate permissions and roles. For example: <code>mycrawladmin</code>)
<i>crawlPassword</i>	Password for the WebCenter Portal user that is specified in the <code>crawlUser</code> argument.
<i>scratchDir</i>	Local directory where Oracle SES can write temporary status logs. The directory must be on the system where Oracle SES is installed.
<i>authUserIdFormat</i>	Format of the user ID in the active identity plug-in. For example, <code>username, email, nickname, user_name</code> .
<i>crawlingMode</i>	Mode for crawling URLs in the source. The default mode is <code>ACCEPT_ALL</code> . Valid values are: <code>ACCEPT_ALL</code> , <code>INDEX_ONLY</code> , <code>EXAMINE_URL</code> : ACCEPT_ALL —Automatically Accept All URLs for Indexing: Crawls and indexes all URLs in the source. It also extracts and indexes any links found in those URLs. Previously crawled URLs are only reindexed if they have changed. EXAMINE_URL —Examine URLs Before Indexing: Crawls but does not index any URLs in the source. It also crawls any links found in those URLs. INDEX_ONLY —Index Only: Crawls and indexes all URLs in the source. It does not extract any links found in those URLs. Select this option for a source previously crawled using EXAMINE_URL .
<i>recrawlPolicy</i>	Specifies whether to crawl all documents or only documents that have changed. Valid values are <code>PROCESS_ALL</code> and <code>PROCESS_CHANGED</code> : PROCESS_ALL —All documents are crawled. Use this option to force a full crawl. PROCESS_CHANGED —Only crawl documents that have changed since the previous crawl. This setting can significantly speed up the crawling process.

Argument	Definition
<i>freqType</i>	<p>Frequency of scheduled crawls. Valid values are: MANUAL, MONTHLY, WEEKLY, DAILY, HOURLY.</p> <p>To schedule crawls MONTHLY, WEEKLY, DAILY, or HOURLY, specify additional arguments as follows:</p> <p>MONTHLY: startHour, startDayOfTheMonth, monthsBetweenLaunches</p> <p>WEEKLY: startHour, startDayOfTheWeek, weeksBetweenLaunches</p> <p>DAILY: startHour, daysBetweenLaunches</p> <p>HOURLY: hoursBetweenLaunches</p> <p>If regular crawls are not required, choose MANUAL and then use the startSpacesCrawler command to initiate a crawl manually.</p>
<i>startHour</i>	<p>Time to start the crawl. Any number between 1 and 24.</p> <p>For example, enter 2 for 2:00am, 14 for 2:00pm, and so on.</p>
<i>hoursBetweenLaunches</i>	<p>Number of hours between crawls.</p> <p>Only valid when <i>freqType</i>= 'HOURLY'.</p>
<i>startDayOfWeek</i>	<p>Day on which to start a weekly crawl. For example, MONDAY, TUESDAY, and so on.</p> <p>Only valid when <i>freqType</i>= 'WEEKLY'.</p>
<i>startDayOfMonth</i>	<p>Day of the month on which to start a monthly crawl. For example, enter 1 for 1st day of the month, 2 for 2nd day of the month, and so on.</p> <p>Only valid when <i>freqType</i>= 'MONTHLY'.</p>
<i>daysBetweenLaunches</i>	<p>Number of days between crawls.</p> <p>Only valid when <i>freqType</i>= 'DAILY'.</p>
<i>weeksBetweenLaunches</i>	<p>Number of weeks between crawls.</p> <p>Only valid when <i>freqType</i>= 'WEEKLY'.</p>
<i>monthsBetweenLaunches</i>	<p>Number of months between crawls.</p> <p>Only valid when <i>freqType</i>= 'MONTHLY'.</p>
<i>server</i>	<p>Optional. Name of the managed server where the application is deployed. For example, WC_Spaces.</p> <p>Required when applications with the same name are deployed to different servers and also when you have a cluster.</p>
<i>applicationVersion</i>	<p>Optional. Version number of the deployed application. Required if more than one version of the application is deployed.</p>

10.18.1.3 Example

The following example creates a Spaces crawler on the Oracle SES instance <http://myseshost.com:7777> for WebCenter Portal (webcenter) located at <http://myhost.com:8888/webcenter/portal>:

```
createSpacesCrawler(appName='webcenter', host='myhost.com', port='8888',
sesUrl='http://myseshost.com:7777/search/api/admin/AdminService',
sesPassword='sespassword', crawlUser='mycrawladmin', crawlPassword='password',
scratchDir='/tmp', authUserIdFormat='username', crawlingMode='ACCEPT_ALL',
recrawlPolicy='PROCESS_ALL', freqType='MANUAL', startHour=1,
hoursBetweenLaunches=1, startDayOfWeek='MONDAY', startDayOfMonth=1,
daysBetweenLaunches=1, weeksBetweenLaunches=1, monthsBetweenLaunches=1)
```

10.18.2 createDocumentsCrawler

Module: Oracle WebCenter Portal

Use with WLST: Online

10.18.2.1 Description

Creates a documents crawler for a named application, on an Oracle SES instance.

The command creates an Oracle WebCenter Content repository datasource and specifies a schedule for crawling documents in the Oracle WebCenter Content repository.

10.18.2.2 Syntax

```
createDocumentsCrawler(appName, host, port, sesUrl, sesPassword, configUrl,
user, password, scratchDir, httpEndpoint, displayUrl, realm, authUserIdFormat,
pipelineName, crawlingMode, recrawlPolicy, freqType, startHour,
hoursBetweenLaunches, startDayOfWeek, startDayOfMonth,
daysBetweenLaunches, weeksBetweenLaunches, monthsBetweenLaunches,
[server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>host</i>	Host name of the machine where the application is running.
<i>port</i>	Port number used to access the application.
<i>sesUrl</i>	Web service URL for the Oracle SES Administration API. Use the format: <code>http://host:port/search/api/admin/AdminService</code>
<i>sesPassword</i>	Password for the Oracle SES administrative user (<code>eqsys</code>).
<i>configUrl</i>	URL of the XML configuration file providing details of the source, such as the data feed type, location, security attributes, and so on. Use the URL format: <code>http://host:port/cs/idcplg?IdcService=SES_CRAWLER_DOWNLOAD_CONFIG&source=sourcename</code>
<i>user</i>	Administrative user for Oracle WebCenter Content's Content Server. For example, <code>sysadmin</code> . If the authentication type is Oracle SSO, then enter a user ID (and password) of a user in the identity management server fronted by Oracle SSO. This user must be granted the same permissions as <code>sysadmin</code> . If it is not possible to grant those permissions, then delete the "remote" user corresponding to this user in Content Server, and create a "local" version of the user (same name) in Content Server.
<i>password</i>	Password for the administrative user specified.
<i>scratchDir</i>	Local directory where Oracle SES can write temporary status logs. The directory must be on the system where Oracle SES is installed.
<i>httpEndpoint</i>	HTTP endpoint for Content Server authorization. For example: <code>http://host:port/idc/idcplg</code>

Argument	Definition
<i>displayUrl</i>	HTTP host information string to prefix the relative access URL to form the complete display URL. For example: <code>http://host:port/idc</code>
<i>realm</i>	Realm of the application serving the control and data feed. This parameter is relevant when the feeds are accessed over HTTP and is mandatory when the authentication type is BASIC. For example, <code>jazn.com</code>
<i>authUserIdFormat</i>	Format of the user ID (in active identity plug-in) that is used by Content Server authorization API. For example, username, email, nickname, user_name.
<i>pipelineName</i>	Document service pipeline created for this source in Oracle SES.
<i>crawlingMode</i>	Mode for crawling URLs in the source. The default mode is ACCEPT_ALL. Valid values are: ACCEPT_ALL, INDEX_ONLY, EXAMINE_URL: ACCEPT_ALL —Automatically Accept All URLs for Indexing: Crawls and indexes all URLs in the source. It also extracts and indexes any links found in those URLs. Previously crawled URLs are only reindexed if they have changed. EXAMINE_URL —Examine URLs Before Indexing: Crawls but does not index any URLs in the source. It also crawls any links found in those URLs. INDEX_ONLY —Index Only: Crawls and indexes all URLs in the source. It does not extract any links found in those URLs. Select this option for a source previously crawled using EXAMINE_URL
<i>recrawlPolicy</i>	Specifies whether to crawl all documents or only documents that have changed. Valid values are PROCESS_ALL and PROCESS_CHANGED: PROCESS_ALL —All documents are crawled. Use this option to force a full crawl. PROCESS_CHANGED —Only crawl documents that have changed since the previous crawl. This setting can significantly speed up the crawling process.
<i>freqType</i>	Frequency of scheduled crawls. Valid values are: MANUAL, MONTHLY, WEEKLY, DAILY, HOURLY. To schedule crawls MONTHLY, WEEKLY, DAILY, or HOURLY, specify additional arguments as follows: MONTHLY : startHour, startDayOfTheMonth, monthsBetweenLaunches WEEKLY : startHour, startDayOfTheWeek, weeksBetweenLaunches DAILY : startHour, daysBetweenLaunches HOURLY : hoursBetweenLaunches If regular crawls are not required, choose MANUAL and then use the startDocumentsCrawler command to initiate a crawl manually.
<i>startHour</i>	Time to start the crawl. Any number between 1 and 24. For example, enter 2 for 2:00am, 14 for 2:00pm, and so on.
<i>hoursBetweenLaunches</i>	Number of hours between crawls. Only valid when <code>freqType= 'HOURLY'</code> .
<i>startDayOfWeek</i>	Day on which to start a weekly crawl. For example, MONDAY, TUESDAY, and so on. Only valid when <code>freqType= 'WEEKLY'</code> .

Argument	Definition
<i>startDayOfMonth</i>	Day of the month on which to start a monthly crawl. For example, enter 1 for 1st day of the month, 2 for 2nd day of the month, and so on. Only valid when <code>freqType= 'MONTHLY'</code> .
<i>daysBetweenLaunches</i>	Number of days between crawls. Only valid when <code>freqType= 'DAILY'</code> .
<i>weeksBetweenLaunches</i>	Number of weeks between crawls. Only valid when <code>freqType= 'WEEKLY'</code> .
<i>monthsBetweenLaunches</i>	Number of months between crawls. Only valid when <code>freqType= 'MONTHLY'</code> .
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.18.2.3 Example

The following example creates a documents crawler on the Oracle SES instance `http://myseshost.com:7777` for WebCenter Portal (webcenter) located at `http://myhost.com:8888/webcenter/portal`:

```
createDocumentsCrawler(appName='webcenter', host='myhost.com', port='8888',
sesUrl='http://myseshost.com:7777/search/api/admin/AdminService',
sesPassword='password',
configUrl='http://myucmhost.com:9044/cs/idcplg?IdcService=SES_CRAWLER_DOWNLOAD_
CONFIG&source=mysource',
user='adminuser', password='password', scratchDir='/scratch',
httpEndpoint='http://myucmhost.com:9044/cs/idcplg',
displayUrl='http://myucmhost:9044/cs', realm='jajn.com',
authUserIdFormat='username',
pipelineName='My UCM Pipeline', crawlingMode='ACCEPT_ALL',
recrawlPolicy='PROCESS_ALL', freqType='MANUAL', startHour=1,
hoursBetweenLaunches=1, startDayOfWeek='MONDAY', startDayOfMonth=1,
daysBetweenLaunches=1, weeksBetweenLaunches=1, monthsBetweenLaunches=1)
```

10.18.3 createDiscussionsCrawler

Module: Oracle WebCenter Portal

Use with WLST: Online

10.18.3.1 Description

Creates a discussion forum crawler and an announcements crawler for a named application, on an Oracle Secure Enterprise Search (SES) instance.

The command creates two Oracle SES database sources (one for discussion forums and one for announcements) and specifies a crawl schedule. The discussion forums source is named `<appname_host_port>_forums` with a view of `FORUMCRAWLER_VW`, and the announcements source is named `<appname_host_port>_announcements` with a view of `ANNOUNCEMENTS_VW`.

10.18.3.2 Syntax

```
createDiscussionsCrawler(appName, host, port, sesUrl, sesPassword,
dbConnString, user, password, authUserIdFormat, crawlingMode,
recrawlPolicy, freqType, startHour, hoursBetweenLaunches, startDayOfWeek,
startDayOfMonth, daysBetweenLaunches, weeksBetweenLaunches,
monthsBetweenLaunches, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>host</i>	Host name of the machine where the application is running.
<i>port</i>	Port number used to access the application.
<i>sesUrl</i>	Web service URL for the Oracle SES Administration API. Use the format: <code>http://host:port/search/api/admin/AdminService</code>
<i>sesPassword</i>	Password for the Oracle SES administrative user (egsys).
<i>dbConnString</i>	Connection URL for the database on which the discussions server is installed. Use the format: Oracle: <code>jdbc:oracle:thin:@<host>:<port>/<oracle-sid></code> IBM DB2: <code>jdbc:db2://<host>:<port>/<database_name></code> Microsoft SQL Server: <code>jdbc:sqlserver://<host_or_IP_address>:<port>/<database_name></code>
<i>user</i>	Administrative user for the database on which the discussions server is installed. Oracle: The user <code>MyPrefix_DISCUSSIONS_CRAWLER</code> is created during installation. IBM DB2: The user <code>MyPrefix_DC</code> is created during installation (where <code>MyPrefix</code> is five characters) Microsoft SQL Server: The user <code>MyPrefix_DISCUSSIONS_CRAWLER</code> is created during installation.
<i>password</i>	Password for the administrative discussions server user specified.
<i>authUserIdFormat</i>	Format of the user ID (in active identity plug-in), that is used by the discussions server authorization API. For example, <code>username</code> , <code>email</code> , <code>nickname</code> , <code>user_name</code> .
<i>crawlingMode</i>	Mode for crawling URLs in the source. The default mode is <code>ACCEPT_ALL</code> . Valid values are: <code>ACCEPT_ALL</code> , <code>INDEX_ONLY</code> , <code>EXAMINE_URL</code> : ACCEPT_ALL —Automatically Accept All URLs for Indexing: Crawls and indexes all URLs in the source. It also extracts and indexes any links found in those URLs. Previously crawled URLs are only reindexed if they have changed. EXAMINE_URL —Examine URLs Before Indexing: Crawls but does not index any URLs in the source. It also crawls any links found in those URLs. INDEX_ONLY —Index Only: Crawls and indexes all URLs in the source. It does not extract any links found in those URLs. Select this option for a source previously crawled using <code>EXAMINE_URL</code> .

Argument	Definition
<i>recrawlPolicy</i>	<p>Specifies whether to crawl all documents or only documents that have changed. Valid values are <code>PROCESS_ALL</code> and <code>PROCESS_CHANGED</code>:</p> <p>PROCESS_ALL—All documents are crawled. Use this option to force a full crawl.</p> <p>PROCESS_CHANGED—Only crawl documents that have changed since the previous crawl. This setting can significantly speed up the crawling process.</p>
<i>freqType</i>	<p>Frequency of scheduled crawls. Valid values are: <code>MANUAL</code>, <code>MONTHLY</code>, <code>WEEKLY</code>, <code>DAILY</code>, <code>HOURLY</code>.</p> <p>To schedule crawls <code>MONTHLY</code>, <code>WEEKLY</code>, <code>DAILY</code>, or <code>HOURLY</code>, specify additional arguments as follows:</p> <p>MONTHLY: <code>startHour</code>, <code>startDayOfMonth</code>, <code>monthsBetweenLaunches</code></p> <p>WEEKLY: <code>startHour</code>, <code>startDayOfWeek</code>, <code>weeksBetweenLaunches</code></p> <p>DAILY: <code>startHour</code>, <code>daysBetweenLaunches</code></p> <p>HOURLY: <code>hoursBetweenLaunches</code></p> <p>If regular crawls are not required, choose <code>MANUAL</code> and then use the startDiscussionsCrawler command to initiate a crawl manually.</p>
<i>startHour</i>	<p>Time to start the crawl. Any number between 1 and 24.</p> <p>For example, enter 2 for 2:00am, 14 for 2:00pm, and so on.</p>
<i>hoursBetweenLaunches</i>	<p>Number of hours between crawls.</p> <p>Only valid when <code>freqType= 'HOURLY'</code>.</p>
<i>startDayOfWeek</i>	<p>Day on which to start a weekly crawl. For example, <code>MONDAY</code>, <code>TUESDAY</code>, and so on.</p> <p>Only valid when <code>freqType= 'WEEKLY'</code>.</p>
<i>startDayOfMonth</i>	<p>Day of the month on which to start a monthly crawl. For example, enter 1 for 1st day of the month, 2 for 2nd day of the month, and so on.</p> <p>Only valid when <code>freqType= 'MONTHLY'</code>.</p>
<i>daysBetweenLaunches</i>	<p>Number of days between crawls.</p> <p>Only valid when <code>freqType= 'DAILY'</code>.</p>
<i>weeksBetweenLaunches</i>	<p>Number of weeks between crawls.</p> <p>Only valid when <code>freqType= 'WEEKLY'</code>.</p>
<i>monthsBetweenLaunches</i>	<p>Number of months between crawls.</p> <p>Only valid when <code>freqType= 'MONTHLY'</code>.</p>
<i>server</i>	<p>Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code>.</p> <p>Required when applications with the same name are deployed to different servers and also when you have a cluster.</p>
<i>applicationVersion</i>	<p>Optional. Version number of the deployed application. Required if more than one version of the application is deployed.</p>

10.18.3.3 Example

The following example creates a discussion forum crawler and an announcements crawler on the Oracle SES instance `http://myseshost.com:7777` for WebCenter Portal (`webcenter`) located at `http://myhost.com:8888/webcenter/portal`:

```
createDiscussionsCrawler(appName='webcenter', host='myhost.com', port='8888',
```

```

sesUrl='http://myseshost.com:7777/search/api/admin/AdminService',
sesPassword='password',
dbConnString='jdbc:oracle:thin:@myjivedbhost.com:1521/mysid',
user='app_discussions_crawler', password='password',
  authUserIdFormat='nickname', crawlingMode='ACCEPT_ALL',
recrawlPolicy='PROCESS_ALL', freqType='MANUAL', startHour=1,
  hoursBetweenLaunches=1, startDayOfWeek='MONDAY',
startDayOfMonth=1, daysBetweenLaunches=1,
weeksBetweenLaunches=1, monthsBetweenLaunches=1)

```

10.18.4 listSpacesCrawler

Module: Oracle WebCenter Portal

Use with WLST: Online

10.18.4.1 Description

Returns the Spaces crawler configured on an Oracle SES instance for WebCenter Portal.

10.18.4.2 Syntax

```
listSpacesCrawler(appName, sesUrl, sesPassword, host, port, [sesSchema, verbose,
server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> .
<i>sesUrl</i>	Web service URL for the Oracle SES Administration API. Use the format: <code>http://host:port/search/api/admin/AdminService</code>
<i>sesPassword</i>	Password for the Oracle SES administrative user (<code>eqsys</code>).
<i>host</i>	Host name of the machine where WebCenter Portal is running.
<i>port</i>	Port number used to access WebCenter Portal.
<i>sesSchema</i>	Optional. Username for the Oracle SES administrative user. Default value is <code>eqsys</code> .
<i>verbose</i>	Optional. Valid options are 1 (true) and 0 (false). When set to 1, <code>listSpacesCrawler</code> returns the Spaces crawler configured for WebCenter Portal in Oracle SES, along with details. When set to 0, only source names are listed. This argument defaults to 0.
<i>server</i>	Optional. Name of the managed server where WebCenter Portal is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.18.4.3 Example

The following example returns the Spaces crawler configured in the Oracle SES instance `http://myseshost.com:7777` for WebCenter Portal located at `http://myhost.com:8888/webcenter/portal`:

```
listSpacesCrawler(appName='webcenter',
sesUrl='http://myseshost.com:7777/search/api/admin/AdminService',
sesSchema='egsys', sesPassword'password', host='myhost.com', port='8888')
```

```
Already in Domain Runtime Tree
-----
Spaces Crawlers
-----
webcenter_myhost.com_8888_portal
```

10.18.5 listDocumentsCrawler

Module: Oracle WebCenter Portal

Use with WLST: Online

10.18.5.1 Description

Returns the document crawler configured for a named application, on an Oracle SES instance.

10.18.5.2 Syntax

```
listDocumentsCrawler(appName, sesUrl, sesPassword, host, port, [sesSchema,
verbose, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>sesUrl</i>	Web service URL for the Oracle SES Administration API. Use the format: <code>http://host:port/search/api/admin/AdminService</code>
<i>sesPassword</i>	Password for the Oracle SES administrative user (<code>egsys</code>).
<i>host</i>	Host name of the machine where the application is running.
<i>port</i>	Port number used to access the application.
<i>sesSchema</i>	Optional. Username for the Oracle SES administrative user. Default value is <code>egsys</code> .
<i>verbose</i>	Optional. Valid options are 1 (true) and 0 (false). When set to 1, <code>listDocumentsCrawler</code> returns the documents crawler that is configured for the application in Oracle SES, along with details. When set to 0, only source names are listed. This argument defaults to 0.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.

Argument	Definition
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.18.5.3 Example

The following example returns the documents crawler configured in the Oracle SES instance `http://myseshost.com:7777` for WebCenter Portal (`webcenter`) located at `http://myhost.com:8888/webcenter/portal`:

```
listDocumentsCrawler(appName='webcenter',
sesUrl='http://myseshost.com:7777/search/api/admin/AdminService',
sesSchema='eqsys', sesPassword'password', host='myhost.com', port='8888')
```

Already in Domain Runtime Tree

Documents Crawlers

webcenter_myhost.com_8888_documents

10.18.6 listDiscussionsCrawler

Module: Oracle WebCenter Portal

Use with WLST: Online

10.18.6.1 Description

Returns the discussion and announcement crawlers configured for a named application on an Oracle SES instance.

10.18.6.2 Syntax

```
listDiscussionsCrawler(appName, sesUrl, sesPassword, host, port, [sesSchema,
verbose, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>sesUrl</i>	Web service URL for the Oracle SES Administration API. Use the format: <code>http://host:port/search/api/admin/AdminService</code>
<i>sesPassword</i>	Password for the Oracle SES administrative user (<code>eqsys</code>).
<i>host</i>	Host name of the machine where the application is running.
<i>port</i>	Port number used to access the application.
<i>sesSchema</i>	Optional. Username for the Oracle SES administrative user. Default value is <code>eqsys</code> .
<i>verbose</i>	Optional. Valid options are 1 (<code>true</code>) and 0 (<code>false</code>). When set to 1, <code>listDiscussionsCrawler</code> returns discussion and announcement crawlers that are configured in Oracle SES for an application, along with details. When set to 0, only source names are listed. This argument defaults to 0.

Argument	Definition
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.18.6.3 Example

The following example returns discussion and announcement crawlers configured in the Oracle SES instance `http://myseshost.com:7777` for WebCenter Portal located at `http://myhost.com:8888/webcenter/portal`:

```
listDiscussionsCrawler(appName='webcenter',
sesUrl='http://myseshost.com:7777/search/api/admin/AdminService',
sesSchema='eqsys', sesPassword='password', host='myhost.com', port='8888')
```

Already in Domain Runtime Tree

Discussions Crawler

webcenter_myhost.com_8888_forums

webcenter_myhost.com_8888_announcements

10.18.7 startSpacesCrawler

Module: Oracle WebCenter Portal

Use with WLST: Online

10.18.7.1 Description

Starts the Spaces crawler configured for WebCenter Portal, on an Oracle SES instance.

10.18.7.2 Syntax

```
startSpacesCrawler(appName, sesUrl, sesPassword, host, port, [sesSchema, server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> .
<i>sesUrl</i>	Web service URL for the Oracle SES Administration API. Use the format: <code>http://host:port/search/api/admin/AdminService</code>
<i>sesPassword</i>	Password for the Oracle SES administrative user (<code>eqsys</code>).
<i>host</i>	Host name of the machine where WebCenter Portal is running.
<i>port</i>	Port number used to access WebCenter Portal.
<i>sesSchema</i>	Optional. Username for the Oracle SES administrative user. Default value is <code>eqsys</code> .

Argument	Definition
<i>server</i>	Optional. Name of the managed server where WebCenter Portal is deployed. For example, <i>WC_Spaces</i> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of WebCenter Portal is deployed.

10.18.7.3 Example

The following example starts the Spaces crawler configured on the Oracle SES instance `http://myseshost.com:7777` for WebCenter Portal (*webcenter*) located at `http://myhost.com:8888/webcenter/portal`:

```
startSpacesCrawler(appName='webcenter',
sesUrl'http://myseshost.com:7777/search/api/admin/AdminService',
sesSchema='eqsys', sesPassword='password', host='myhost.com', port='8888')
```

10.18.8 startDocumentsCrawler

Module: Oracle WebCenter Portal

Use with WLST: Online

10.18.8.1 Description

Starts the documents crawler configured for a named application, on an Oracle SES instance.

10.18.8.2 Syntax

```
startDocumentsCrawler(appName, sesUrl, sesPassword, host, port, [sesSchema,
server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <i>webcenter</i> . For Portal Framework applications, specify the appropriate name.
<i>sesUrl</i>	Web service URL for the Oracle SES Administration API. Use the format: <code>http://host:port/search/api/admin/AdminService</code>
<i>sesPassword</i>	Password for the Oracle SES administrative user (<i>eqsys</i>).
<i>host</i>	Host name of the machine where the application is running.
<i>port</i>	Port number used to access the application.
<i>sesSchema</i>	Optional. Username for the Oracle SES administrative user. Default value is <i>eqsys</i> .
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <i>WC_Spaces</i> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.18.8.3 Example

The following example starts the document crawler configured on the Oracle SES instance `http://myseshost.com:7777` for WebCenter Portal (`webcenter`) located at `http://myhost.com:8888/webcenter/portal`:

```
startDocumentsCrawler (appName='webcenter',
sesUrl'http://myseshost.com:7777/search/api/admin/AdminService',
sesSchema='eqsys', sesPassword='password', host='myhost.com', port='8888')
```

10.18.9 startDiscussionsCrawler

Module: Oracle WebCenter Portal

Use with WLST: Online

10.18.9.1 Description

Starts the discussion and announcement crawlers configured for a named application, on an Oracle Secure Enterprise Search (SES) instance.

10.18.9.2 Syntax

```
startDiscussionsCrawler(appName, sesUrl, sesPassword, host, port, [sesSchema,
server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>sesUrl</i>	Web service URL for the Oracle SES Administration API. Use the format: <code>http://host:port/search/api/admin/AdminService</code>
<i>sesPassword</i>	Password for the Oracle SES administrative user (<code>eqsys</code>).
<i>host</i>	Host name of the machine where the application is running.
<i>port</i>	Port number used to access the application.
<i>sesSchema</i>	Optional. Username for the Oracle SES administrative user. Default value is <code>eqsys</code> .
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.18.9.3 Example

The following example starts the discussion and announcement crawlers configured on the Oracle SES instance `http://myseshost.com:7777` for WebCenter Portal (`webcenter`) located at `http://myhost.com:8888/webcenter/portal`:

```
startDiscussionsCrawler (appName='webcenter',
sesUrl'http://myseshost.com:7777/search/api/admin/AdminService',
sesSchema='eqsys', sesPassword='password', host='myhost.com', port='8888')
```

10.18.10 stopSpacesCrawler

Module: Oracle WebCenter Portal

Use with WLST: Online

10.18.10.1 Description

Stops the Spaces crawler configured for WebCenter Portal, on an Oracle SES instance.

10.18.10.2 Syntax

```
stopSpacesCrawler(appName, sesUrl, sesPassword, host, port, [sesSchema, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> .
<i>sesUrl</i>	Web service URL for the Oracle SES Administration API. Use the format: <code>http://host:port/search/api/admin/AdminService</code>
<i>sesPassword</i>	Password for the Oracle SES administrative user (<code>eqsys</code>).
<i>host</i>	Host name of the machine where WebCenter Portal is running.
<i>port</i>	Port number used to access WebCenter Portal.
<i>sesSchema</i>	Optional. Username for the Oracle SES administrative user. Default value is <code>eqsys</code> .
<i>server</i>	Optional. Name of the managed server where WebCenter Portal is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of WebCenter Portal is deployed.

10.18.10.3 Example

The following example stops the Spaces crawler configured on the Oracle SES instance `http://myseshost.com:7777` for WebCenter Portal located at `http://myhost.com:8888/webcenter/portal`:

```
stopSpacesCrawler(appName='webcenter',
sesUrl'http://myseshost.com:7777/search/api/admin/AdminService',
sesSchema='eqsys', sesPassword='password', host='myhost.com', port='8888')
```

10.18.11 stopDocumentsCrawler

Module: Oracle WebCenter Portal

Use with WLST: Online

10.18.11.1 Description

Stops the documents crawler configured for a named application, on an Oracle SES instance.

10.18.11.2 Syntax

```
stopDocumentsCrawler(appName, sesUrl, sesPassword, host, port, [sesSchema, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>sesUrl</i>	Web service URL for the Oracle SES Administration API. Use the format: <code>http://host:port/search/api/admin/AdminService</code>
<i>sesPassword</i>	Password for the Oracle SES administrative user (<code>eqsys</code>).
<i>host</i>	Host name of the machine where the application is running.
<i>port</i>	Port number used to access the application.
<i>sesSchema</i>	Optional. Username for the Oracle SES administrative user. Default value is <code>eqsys</code> .
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.18.11.3 Example

The following example stops the document crawler configured on the Oracle SES instance `http://myseshost.com:7777` for WebCenter Portal located at `http://myhost.com:8888/webcenter/portal`:

```
stopDocumentsCrawler(appName='webcenter',
sesUrl'http://myseshost.com:7777/search/api/admin/AdminService',
sesSchema='eqsys', sesPassword='password', host='myhost.com', port='8888')
```

10.18.12 stopDiscussionsCrawler

Module: Oracle WebCenter Portal

Use with WLST: Online

10.18.12.1 Description

Stops the discussion and announcement crawlers configured for a named application, on an Oracle SES instance.

10.18.12.2 Syntax

```
stopDiscussionsCrawler(appName, sesUrl, sesPassword, host, port, [sesSchema, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>sesUrl</i>	Web service URL for the Oracle SES Administration API. Use the format: <code>http://host:port/search/api/admin/AdminService</code>
<i>sesPassword</i>	Password for the Oracle SES administrative user (<code>eqsys</code>).
<i>host</i>	Host name of the machine where the application is running.
<i>port</i>	Port number used to access the application.
<i>sesSchema</i>	Optional. Username for the Oracle SES administrative user. Default value is <code>eqsys</code> .
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.18.12.3 Example

The following example stops the discussion and announcement crawlers configured on the Oracle SES instance `http://myseshost.com:7777` for WebCenter Portal located at `http://myhost.com:8888/webcenter/portal`:

```
stopDiscussionsCrawler(appName='webcenter',
sesUrl'http://myseshost.com:7777/search/api/admin/AdminService',
sesSchema='eqsys', sesPassword='password', host='myhost.com', port='8888')
```

10.18.13 deleteSpacesCrawler

Module: Oracle WebCenter Portal

Use with WLST: Online

10.18.13.1 Description

Deletes the Spaces crawler configured for WebCenter Portal, on an Oracle SES instance.

10.18.13.2 Syntax

```
deleteSpacesCrawler(appName, sesUrl, sesPassword, host, port,[sesSchema, server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> .
<i>sesUrl</i>	Web service URL for the Oracle SES Administration API. Use the format: <code>http://host:port/search/api/admin/AdminService</code>

Argument	Definition
<i>sesPassword</i>	Password for the Oracle SES administrative user (eqsys).
<i>host</i>	Host name of the machine where WebCenter Portal is running.
<i>port</i>	Port number used to access WebCenter Portal.
<i>sesSchema</i>	Optional. Username for the Oracle SES administrative user. Default value is eqsys.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, WC_Spaces. Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.18.13.3 Example

The following example deletes the Spaces crawler configured on the Oracle SES instance `http://myseshost.com:7777` for WebCenter Portal named `webcenter` located at `http://myhost.com:8888/webcenter/portal`:

```
deleteSpacesCrawler(appName='webcenter',
sesUrl'http://myseshost.com:7777/search/api/admin/AdminService',
sesSchema='eqsys', sesPassword='password', host='myhost.com', port='8888')
```

10.18.14 deleteDocumentsCrawler

Module: Oracle WebCenter Portal

Use with WLST: Online

10.18.14.1 Description

Deletes the documents crawler configured for a named application, on an Oracle SES instance.

10.18.14.2 Syntax

```
deleteDocumentsCrawler(appName, sesUrl, sesPassword, host, port, [sesSchema,
server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>sesUrl</i>	Web service URL for the Oracle SES Administration API. Use the format: <code>http://host:port/search/api/admin/AdminService</code>
<i>sesPassword</i>	Password for the Oracle SES administrative user (eqsys).
<i>host</i>	Host name of the machine where the application is running.
<i>port</i>	Port number used to access the application.
<i>sesSchema</i>	Optional. Username for the Oracle SES administrative user. Default value is eqsys.

Argument	Definition
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <i>WC_Spaces</i> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.18.14.3 Example

The following example deletes the document crawler configured on the Oracle SES instance `http://myseshost.com:7777` for WebCenter Portal located at `http://myhost.com:8888/webcenter/portal`:

```
deleteDocumentsCrawler(appName='webcenter',
sesUrl'http://myseshost.com:7777/search/api/admin/AdminService',
sesSchema='eqsys', sesPassword='password', host='myhost.com', port='8888')
```

10.18.15 deleteDiscussionsCrawler

Module: Oracle WebCenter Portal

Use with WLST: Online

10.18.15.1 Description

Deletes the discussion and announcement crawlers configured for a named application, on an Oracle SES instance.

10.18.15.2 Syntax

```
deleteDiscussionsCrawler(appName, sesUrl, sesPassword, host, port, [server],
[applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <i>webcenter</i> . For Portal Framework applications, specify the appropriate name.
<i>sesUrl</i>	Web service URL for the Oracle SES Administration API. Use the format: <code>http://host:port/search/api/admin/AdminService</code>
<i>sesPassword</i>	Password for the Oracle SES administrative user (<i>eqsys</i>).
<i>host</i>	Host name of the machine where the application is running.
<i>port</i>	Port number used to access the application.
<i>sesSchema</i>	Optional. Username for the Oracle SES administrative user. Default value is <i>eqsys</i> .
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <i>WC_Spaces</i> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.18.15.3 Example

The following example deletes the discussion and announcement crawlers configured on the Oracle SES instance `http://myseshost.com:7777` for WebCenter Portal located at `http://myhost.com:8888/webcenter/portal`:

```
deleteDiscussionsCrawler(appName='webcenter',
sesUrl'http://myseshost.com:7777/search/api/admin/AdminService',
sesSchema='egsys', sesPassword='password', host='myhost.com', port='8888')
```

10.19 Search - WebCenter Portal Search

Use the commands listed in [Table 10–27](#) to manage search settings and crawl options for WebCenter Portal and Portal Framework applications.

Configuration changes made using these WLST commands are effective immediately; no restart is required.

Table 10–27 WebCenter Portal Search WLST Commands

Use This Command...	To...	Use with WLST...
setSearchConfig	Modify search settings for a named application.	Online
listSearchConfig	List search properties for a named application.	Online
setSpacesCrawlProperties	Specify crawl properties for a named application.	Online
getSpacesCrawlProperties	Return the current crawl settings for a named application.	Online

10.19.1 setSearchConfig

Module: Oracle WebCenter Portal

Use with WLST: Online

10.19.1.1 Description

Modifies search settings for a named application. If a parameter is not specified, it is not modified.

10.19.1.2 Syntax

```
setSearchConfig(appName,[numSavedSearches, numResultsRegion, numResultsMain,
executionTimeout, prepareTimeout, showAllExecutionTimeout, server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>numSavedSearches</i>	Optional. The number of saved searches to display in the Saved Searches drop down (on main search page).
<i>numResultsRegion</i>	Optional. The number of saved searches displayed in a Saved Search task flow.

Argument	Definition
<i>numResultsMain</i>	Optional. The number of search results displayed, per tool or service, for searches submitted from the main search page.
<i>executionTimeout</i>	Optional. The maximum time that a tool or service is allowed to execute a search (in ms). The value for this argument must be a valid number.
<i>prepareTimeout</i>	Optional. The maximum time that a tool or service is allowed to initialize a search (in ms). The value for this argument must be a valid number.
<i>showAllExecutionTime out</i>	Optional. The maximum time that a tool or service is allowed to display search all results (in ms). The value for this argument must be a valid number.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <i>WC_Spaces</i> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.19.1.3 Examples

The following example specifies that saved searches display five search results per tool or service. Additionally, that a seven second search execution timeout is required:

```
wls:/weblogic/serverConfig>setSearchConfig(appName='webcenter',
numResultsRegion=5, executionTimeout=7000);
```

The following example increases the number of saved searches in the Saved Searches drop down list to eight:

```
wls:/weblogic/serverConfig>setSearchConfig(appName='webcenter',
numSavedSearches=8);
```

The following example sets the search execution timeout to five seconds and allows each tool or service fifteen seconds to display search results before timing out:

```
wls:/weblogic/serverConfig>setSearchConfig(appName='webcenter',
executionTimeout=5000, showAllExecutionTimeout=15000);
```

10.19.2 listSearchConfig

Module: Oracle WebCenter Portal

Use with WLST: Online

10.19.2.1 Description

Lists search settings for a named application.

10.19.2.2 Syntax

```
listSearchConfig(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.19.2.3 Example

The following example displays search configuration information for WebCenter Portal:

```
wls:/weblogic/serverConfig>listSearchConfig(appName='webcenter')
```

10.19.3 setSpacesCrawlProperties

Module: Oracle WebCenter Portal

Use with WLST: Online

10.19.3.1 Description

Specifies Oracle SES crawl properties for WebCenter Portal or Portal Framework applications.

WebCenter Portal and Portal Framework applications can be crawled by Oracle SES to provide a faster, more unified search experience across WebCenter Portal objects, specifically: portals, lists, pages, people (profiles), wikis, blogs, documents, discussions, and announcements. Three distinct crawlers make this possible:

- Spaces Crawler (for portals, lists, pages, and people)
- Documents Crawler (for documents, wikis, blogs)
- Discussions Crawler (for discussions and announcements).

Use this command to enable or disable Oracle SES crawlers in the following applications:

- **WebCenter Portal**—To use Oracle SES crawlers in WebCenter Portal, you *must* enable all three crawlers.
- **Portal Framework applications**—To use Oracle SES crawlers in Portal Framework applications, you *must* enable both the documents and discussions crawlers. The Spaces crawler is not applicable.

(WebCenter Portal only) You can also use this command to specify an interval between full crawls for the Spaces crawler. During a full crawl, all of the Spaces crawler content is re-read. Out-of-the-box, full crawls for the Spaces crawler occur every seven days but you can specify a different frequency to suit your installation.

Note that incremental crawls, for all three crawlers, are initiated by a scheduler running from Oracle SES. During these incremental crawls, only content added or updated since the previous crawl is processed.

10.19.3.2 Syntax

```
setSpacesCrawlProperties(appName, [fullCrawlIntervalInHours, spacesCrawlEnabled,
documentCrawlEnabled, discussionsCrawlEnabled, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>fullCrawlIntervalInHours</i>	Optional. (WebCenter Portal only) Number of hours between full crawls. The default is 168 hours or 7 days.
<i>spacesCrawlEnabled</i>	Optional. Specifies whether the Spaces crawler is enabled in Oracle SES. Valid values are 1 (true) and 0 (false). This argument defaults to 0. When set to 0, Oracle WebCenter Portal's internal search adapters return search results.
<i>documentCrawlEnabled</i>	Optional. Specifies whether the Documents crawler is enabled in Oracle SES. Valid values are 1 (true) and 0 (false). This argument defaults to 0. When set to 0, Oracle WebCenter Portal's internal search adapters return search results.
<i>discussionsCrawlEnabled</i>	Optional. Specifies whether the Discussions and Announcement crawlers are enabled in Oracle SES. Valid values are 1 (true) and 0 (false). This argument defaults to 0. When set to 0, Oracle WebCenter Portal's internal search adapters return search results.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.19.3.3 Example

The following example enables Oracle SES crawlers in WebCenter Portal and specifies that WebCenter Portal runs a full crawl through the Spaces crawler every 8 days:

```
wls:/weblogic/serverConfig>setSpacesCrawlProperties(appName='webcenter',
fullCrawlIntervalInHours=192, spacesCrawlEnabled=1, documentCrawlEnabled=1,
discussionsCrawlEnabled=1)
```

10.19.4 getSpacesCrawlProperties

Module: Oracle WebCenter Portal

Use with WLST: Online

10.19.4.1 Description

Returns the current crawl settings for a named application, such as the number of hours between full crawls (Spaces crawler), and whether Oracle SES crawlers are enabled.

10.19.4.2 Syntax

```
getSpacesCrawlProperties(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.19.4.3 Example

The following example returns the current crawl settings for WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig>getSpacesCrawlProperties (appName='webcenter')

Spaces Crawl Properties:
-----
fullCrawlIntervalInHours: 124
spacesCrawlEnabled:      1
documentCrawlEnabled:   1
discussionsCrawlEnabled: 1
```

10.20 Worklists

Use the commands listed in [Table 10–28](#) to manage BPEL server connections for applications.

Configuration changes made using these WLST commands are only effective after you restart the Managed Server on which the application is deployed. For details, see *Oracle Fusion Middleware Administering Oracle WebCenter Portal*.

Table 10–28 Worklist Commands

Use this command...	To...	Use with WLST...
createBPELConnection	Create a connection to a BPEL server for a named application.	Online
setBPELConnection	Edit an existing BPEL server connection.	Online
listBPELConnections	List all of the BPEL server connections that are configured for a named application.	Online
addWorklistConnection	Enable an existing BPEL server connection for worklists.	Online
removeWorklistConnection	Disable a BPEL server connection currently used by worklists.	Online
listWorklistConnections	List individual or all BPEL server connections configured for worklists.	Online

10.20.1 createBPELConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.20.1.1 Description

Creates a connection to a BPEL server for a named application. BPEL server connections can be used by worklists and also by WebCenter Portal's internal portal workflows.

To configure worklists to actively use a new BPEL server connection, use the `addWorklistConnection` command. See [Section 10.20.4, "addWorklistConnection"](#).

To specify the BPEL server connection that WebCenter Portal uses for its internal workflows, use the `setSpacesWorkflowConnectionName` command. See [Section 10.21.2, "setSpacesWorkflowConnectionName"](#).

10.20.1.2 Syntax

```
createBPELConnection(appName, name, url, [policy, recipientKeyAlias, linkUrl,
server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Connection name. The name must be unique (across all connection types) within the application.
<i>url</i>	URL required to access the BPEL server. Use the format: <code>protocol://host:port</code> The BPEL server URL must be unique within the application.
<i>policy</i>	Optional. SAML token policy this connection uses for authentication. Enter any valid policy. Valid values include: <ul style="list-style-type: none"> ■ <code>oracle/wss10_saml_token_client_policy</code>—use to access the BPEL server with the default, non message protected policy. ■ <code>oracle/wss10_saml_token_with_message_protection_client_policy</code>—use to access the BPEL server with a message protected policy. If selected, you must configure keys stores both in your application and in the BPEL application. ■ <code>GPA</code>—use if your environment supports Global Policy Attachments (GPA). If you omit this argument, the connection defaults to <code>oracle/wss10_saml_token_client_policy</code> .
<i>recipientKeyAlias</i>	Optional. Recipient key alias to be used for message protected SAML policy authentication. Only required when the BPEL server connection is using a SAML token policy for authentication and the application's worklist is using multiple BPEL server connections. The default is null. See also "Configuring WS-Security" in <i>Oracle Fusion Middleware Administering Oracle WebCenter Portal</i> .

Argument	Definition
<code>linkUrl</code>	<p>Optional. URL used to link to the BPEL server. Only required if it is different to the <code>url</code> argument. For example, when SSO or HTTPS is configured.</p> <p>Use the format: <code>protocol://host:port</code></p> <p>The default is null.</p> <p>For performance reasons, in an HTTPS or SSO environment, <code>linkUrl</code> specifies user access to BPEL worklist items, through HTTPS or SSO web servers, whereas <code>url</code> specifies direct access to BPEL web services, without redirection through HTTPS or SSO Web servers.</p>
<code>server</code>	<p>Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code>.</p> <p>Required when applications with the same name are deployed to different servers and also when you have a cluster.</p>
<code>applicationVersion</code>	<p>Optional. Version number of the deployed application. Required if more than one version of the application is deployed.</p>

10.20.1.3 Examples

The following example creates a connection named `WebCenter Worklist` with the default security policy:

```
wls:/weblogic/serverConfig> createBPELConnection(appName='webcenter',
name='WebCenter Worklist', url='http://myhost.com:8001',
policy='oracle/wss10_saml_token_client_policy')
```

The following example creates a connection that uses a message protected security policy, and defines a specific link URL:

```
wls:/weblogic/serverConfig> createBPELConnection(appName='webcenter',
name='WebCenter Worklist', url='http://myhost.com:8001', policy='oracle/wss10_
saml_token_with_message_protection_client_policy', recipientKeyAlias='myalias',
linkUrl='http://mySSO.com:7777')
```

The following example creates a connection to be used in an environment that supports Global Policy Attachments (GPA):

```
wls:/weblogic/serverConfig> createBPELConnection(appName='webcenter',
name='WebCenter Worklist', url='http://myhost.com:8001', policy='GPA')
```

10.20.2 setBPELConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.20.2.1 Description

Edits an existing BPEL server connection.

To configure the worklists to actively use an existing BPEL server connection, use the `addWorklistConnection` command. See [Section 10.20.4, "addWorklistConnection"](#).

To specify the BPEL server connection used for WebCenter Portal's internal workflows, use the `setSpacesWorkflowConnectionName` command. See [Section 10.21.2, "setSpacesWorkflowConnectionName"](#).

10.20.2.2 Syntax

```
setBPELConnection(appName, name, [url, policy, recipientKeyAlias, linkUrl, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Existing BPEL server connection name.
<i>url</i>	Optional. URL required to access the BPEL server. Use the format: <code><protocol>://<host>:<port></code> The BPEL server URL must be unique within the application.
<i>policy</i>	Optional. SAML token policy this connection uses for authentication. Enter any valid policy. Valid values include: <ul style="list-style-type: none"> ■ <code>oracle/wss10_saml_token_client_policy</code>—use to access the BPEL server with the default, non message protected policy. ■ <code>oracle/wss10_saml_token_with_message_protection_client_policy</code>—use to access the BPEL server with a message protected policy. If selected, you must configure keys stores both in your application and in the BPEL application. ■ <code>GPA</code>—use if your environment supports Global Policy Attachments (GPA). If you omit this argument, the connection defaults to <code>oracle/wss10_saml_token_client_policy</code> .
<i>recipientKeyAlias</i>	Optional. Recipient key alias to be used for message protected SAML policy authentication. Only required when the BPEL server connection is using a SAML token policy for authentication and the application's worklist is using multiple BPEL server connections. The default is null. See also "Configuring WS-Security" in <i>Oracle Fusion Middleware Administering Oracle WebCenter Portal</i> .
<i>linkUrl</i>	Optional. URL used to link to the BPEL server. Only required if it is different to the <code>url</code> argument. For example, when SSO or https is configured. Use the format: <code>protocol://host:port</code> For example, <code>http://mySSO.host.com:7777</code> The default is null. For performance reasons, in an HTTPS or SSO environment, the Link URL specifies user access to BPEL worklist items, through HTTPS or SSO web servers, whereas the BPEL SOAP URL specifies direct access to BPEL web services, without redirection through HTTPS or SSO web servers.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.20.2.3 Examples

The following example updates the BPEL server URL, security policy, recipient key alias, and link url for a connection named `WebCenter Worklist`.

```
wls:/weblogic/serverConfig> setBPELConnection(appName='webcenter',
name='WebCenter Worklist',url='http://myhost.com:6666', policy='oracle/wss10_
saml_token_with_message_protection_client_policy', recipientKeyAlias='myalias',
linkUrl='http://mySSO.com:7777')
```

The following example changes the security policy to use Global Policy Attachments (GPA):

```
wls:/weblogic/serverConfig> setBPELConnection(appName='webcenter',
name='WebCenter Worklist', policy='GPA')
```

10.20.3 listBPELConnections

Module: Oracle WebCenter Portal

Use with WLST: Online

10.20.3.1 Description

Without any arguments, this command lists all the BPEL connections that are configured for a named application. All BPEL connections are listed, even connections not currently used.

10.20.3.2 Syntax

```
listBPELConnections(appName, [verbose, name, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>verbose</i>	Optional. Displays BPEL server connection details in verbose mode. Valid options are 1 (true) and 0 (false). When set to 1, <code>listBPELConnections</code> lists all of the BPEL server connections that are configured, along with their details. When set to 0, <code>listBPELConnections</code> lists connection names only. This argument defaults to 0. If you set this argument to 0, do not specify the <code>name</code> argument.
<i>name</i>	Optional. Name of an existing BPEL server connection. You can use this argument to view details about a specific connection. To list all the connections, omit the <code>name</code> argument.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.20.3.3 Examples

The following example lists the names of all the BPEL server connections that are configured for WebCenter Portal:

```
wls:/weblogic/serverConfig> listBPELConnections(appName='webcenter')
-----
WebCenter Worklist
-----
-----
Human Resources Worklist
-----
```

The following example lists the names and details of all of the BPEL server connections that are configured for WebCenter Portal:

```
wls:/weblogic/serverConfig> listBPELConnections(appName='webcenter', verbose=1)
-----
WebCenter Worklist
-----
Connection Name: WebCenter Worklist
PolicyURI:oracle/wss10_saml_token_client_policy
URL:http://myhost.com:8001
-----
Human Resources Worklist
-----
Connection Name: Human Resources Worklist
PolicyURI:oracle/wss10_saml_token_client_policy
URL:http://myhost.com:8888
-----
```

10.20.4 addWorklistConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.20.4.1 Description

Enables an existing BPEL server connection for worklists. Worklists supports multiple connections so that users can monitor and manage assignments and notifications from a range of BPEL servers.

The name must specify an existing BPEL server connection.

10.20.4.2 Syntax

```
addWorklistConnection(appName, name, [verbose, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing BPEL server connection.

Argument	Definition
<i>verbose</i>	Optional. Displays output indicating whether a matching BPEL server connection exists and provides connection details. 1 turns verbose mode on 0 turns verbose mode off This argument defaults to 0.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <i>WC_Spaces</i> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.20.4.3 Examples

The following example enables the Human Resources Worklist connection for the worklists in WebCenter Portal:

```
wls:/weblogic/serverConfig>addWorklistConnection(appName='webcenter',
name='Human Resources Worklist', verbose=1)
Human Resources Worklist successfully added to WorkList
-----
Human Resources Worklist
-----
Connection Name: Human Resources Worklist
PolicyURI:oracle/wss10_saml_token_client_policy
URL:http://myhost.com:8888
```

The following example also enables the Human Resources Worklist connection for worklists in WebCenter Portal:

```
wls:/weblogic/serverConfig> addWorklistConnection(appName='webcenter',
name='Human Resources Worklist', verbose=1)
Human Resources Worklist successfully added to WorkList
-----
Human Resources Worklist
-----
Connection Name: Human Resources Worklist
PolicyURI:oracle/oracle/wss10_saml_token_client_policy
URL:http://myhost.com:8888
```

10.20.5 removeWorklistConnection

Module: Oracle WebCenter Portal

Use with WLST: Online

10.20.5.1 Description

Disables a BPEL server connection that is currently used by worklists. Connection details are retained but worklists no longer use the connection specified.

10.20.5.2 Syntax

```
removeWorklistConnection(appName, name, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>name</i>	Name of an existing BPEL server connection.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.20.5.3 Example

The following example disables the BPEL server connection named `WebCenter Worklist` for worklists in WebCenter Portal:

```
wls:/weblogic/serverConfig> removeWorklistConnection(appName='webcenter',
name='WebCenter Worklist')
WebCenter Worklist successfully removed from WorkList
```

10.20.6 listWorklistConnections

Module: Oracle WebCenter Portal

Use with WLST: Online

10.20.6.1 Description

Without any arguments, this command lists all of the BPEL server connections that are configured for the worklists, in a named application.

10.20.6.2 Syntax

```
listWorklistConnections(appName, [verbose, name, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>verbose</i>	Optional. Displays BPEL server connection details in verbose mode. Valid options are 1 (true) and 0 (false). When set to 1, <code>listWorklistConnections</code> lists all of the BPEL server connections that are configured for worklists, along with their details. When set to 0, <code>listWorklistConnections</code> lists connection names only. This argument defaults to 0. If you set this argument to 0, do not specify the name argument.
<i>name</i>	Optional. Name of an existing BPEL server connection. You can use this argument to view details about a specific connection. To list all connections, omit the name argument.

Argument	Definition
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <i>WC_Spaces</i> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.20.6.3 Examples

The following example lists the names of all of the BPEL server connections that are configured for worklists in WebCenter Portal:

```
wls:/weblogic/serverConfig>listWorklistConnections (appName='webcenter')
-----
WebCenter Worklist
-----
```

The following example lists both the names and connection details of all of the BPEL server connections that are configured for worklists in WebCenter Portal:

```
wls:/weblogic/serverConfig>listWorklistConnections (appName='webcenter', verbose=1)
-----
WebCenter Worklist
-----
Connection Name: WebCenter Worklist
PolicyURI:oracle/wss10_saml_token_client_policy
URL:http://myhost.com:8001
```

The following example lists connection details of a named BPEL server connection—*MyWorklist*. As worklists is not currently configured to use *MyWorklist*, an appropriate message displays.

```
wls:/weblogic/serverConfig> listWorklistConnections (appName='webcenter',
verbose=1, name='MyWorklist')
-----
The following connection is not in the ADF Worklist:MyWorklist
```

10.21 WebCenter Portal Application

Use the commands listed in [Table 10–29](#) to manage workflow settings and metadata for the "out-of-the-box" WebCenter Portal application.

Table 10–29 WebCenter Portal Application WLST Commands

Use This Command...	To...	Use with WLST...
getSpacesWorkflowConnectionName	Return the name of the BPEL server connection that WebCenter Portal is using for internal workflows.	Online
setSpacesWorkflowConnectionName	Specify the BPEL server connection used for WebCenter Portal workflows.	Online
refreshGroupSpaceCache	Migrate metadata for individual portals (in MDS) and portal security data to the 'WebCenter Portal Cache'.	Online
refreshSpaceTemplateCache	Migrate metadata for individual portal templates (in MDS) and portal template security data to the 'WebCenter Portal Templates Cache'.	Online

10.21.1 getSpacesWorkflowConnectionName

Module: Oracle WebCenter Portal

Use with WLST: Online

10.21.1.1 Description

Returns the name of the BPEL server connection that WebCenter Portal is currently using for internal workflows (portal membership notifications, portal subscription requests, and so on).

10.21.1.2 Syntax

```
getSpacesWorkflowConnectionName(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> .
<i>server</i>	Optional. Name of the managed server where WebCenter Portal is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of WebCenter Portal is deployed.

10.21.1.3 Example

The following example names the BPEL server connection that WebCenter Portal is currently using for internal workflows:

```
wls:/weblogic/serverConfig> getSpacesWorkflowConnectionName (appName='webcenter')
WorkflowConfigConnectionName: WebCenter-Worklist
```

10.21.2 setSpacesWorkflowConnectionName

Module: Oracle WebCenter Portal

Use with WLST: Online

10.21.2.1 Description

Specifies the BPEL server connection that WebCenter Portal uses for internal workflows. WebCenter Portal uses a BPEL server included with the Oracle SOA Suite to host internal workflows, such as portal membership notifications, portal subscription requests, and so on. The connection name specified here must be a valid BPEL server connection.

Note: Configuration changes made using this WLST command are only effective after you restart the Managed Server on which WebCenter Portal is deployed. For details, see *Oracle Fusion Middleware Administering Oracle WebCenter Portal*.

10.21.2.2 Syntax

```
setSpacesWorkflowConnectionName(appName, name, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> .
<i>name</i>	Name of an existing BPEL server connection.
<i>server</i>	Optional. Name of the managed server where WebCenter Portal is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of WebCenter Portal is deployed.

10.21.2.3 Example

The following example specifies that WebCenter Portal uses the BPEL server connection named `WebCenter-Worklist` for its internal workflows.

```
wls:/weblogic/serverConfig>setSpacesWorkflowConnectionName (appName='webcenter',
name='WebCenter-Worklist')
```

10.21.3 refreshGroupSpaceCache

Module: Oracle WebCenter Portal

Use with WLST: Online

10.21.3.1 Description

(Used when patching WebCenter Spaces 11.1.1.1.0 to 11.1.1.2.0).

Migrates metadata for individual spaces (in MDS) and space security data (in a policy store) to the *Spaces Cache*.

WebCenter Spaces 11.1.1.2.0 and later uses tables (referred to as the Spaces Cache) to store space metadata and security-related data. When you patch from WebCenter Spaces 11.1.1.1.0 to 11.1.1.2.0, you must manually run the `refreshGroupSpaceCache` command to migrate your existing space data to the new 'Spaces Cache'.

10.21.3.2 Syntax

```
refreshGroupSpaceCache(appName, [spaceNames, syncMode, updateType, cleanCache,
server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal (previously known as Spaces), the application name is always <code>webcenter</code> .
<i>spaceNames</i>	Optional. Names of one or more spaces (group spaces) that you want to refresh. To refresh all the spaces in MDS, enter <code>spaceNames= ''</code> To refresh selective spaces, enter one or more space names separated with a comma, for example: <code>spaceNames='MyGroupSpace1, MyGroupSpace'</code>

Argument	Definition
<i>updateType</i>	<p>Optional. Indicates the type of data to refresh. Valid values are: <i>security</i>, <i>metadata</i>, <i>all</i>. The default value is <i>security</i>.</p> <ul style="list-style-type: none"> ■ <i>security</i> - Refreshes the cache with security data stored in the policy store. The security data that is stored includes member data for the space, whether or not a space is public, and whether or not a space is accessible to users assigned the <i>Authenticated-User</i> role (in earlier releases this role was named <i>Spaces-User</i>). ■ <i>metadata</i> - Refreshes the cache with space-related metadata stored in MDS. The data that is stored includes metadata information such as the display name, keywords, icon, logo, and so on. ■ <i>all</i> - Refreshes the cache with data stored in MDS and the policy store.
<i>syncMode</i>	<p>Optional. Indicates whether to refresh the cache in synchronous or asynchronous mode.</p> <p>Valid values are 1 and 0. The default value is 1.</p> <p>When set to 1, the refresh process runs in synchronous mode.</p> <p>When set to 0, the refresh is asynchronous, that is, a new thread is spawned for the refresh process.</p> <p>Synchronous mode is recommended.</p>
<i>cleanCache</i>	<p>Optional. Indicates whether to remove data that no longer exists in MDS from the WebCenter Portal Cache during the refresh operation. Valid values are 1 and 0. The default value is 0.</p> <ul style="list-style-type: none"> ■ 0 - No content in the WebCenter Portal Cache is cleared during the refresh operation. ■ 1 - Clears space data from the WebCenter Portal Cache if the space does not exist in MDS: <ul style="list-style-type: none"> ■ If <i>spaceNames</i>= ' ', data in the Cache is refreshed for all the spaces in MDS and data for any other space (not in MDS) is removed from the Cache. ■ If <i>spaceNames</i> specifies the names of one or more spaces, only data for the named spaces is refreshed in the Cache. If you name a space that does not exist in MDS, data for that space is removed from the Cache. <p>Only set <i>cleanCache</i> to 1 if you are refreshing all the spaces. Do not set <i>cleanCache</i> to 1 if you are refreshing one or two individual spaces as this setting will unnecessarily remove all the spaces that are not refreshed.</p>
<i>server</i>	<p>Optional. Name of the managed server where WebCenter Portal is deployed. For example, <i>WC_Spaces</i>.</p> <p>Required when applications with the same name are deployed to different servers and also when you have a cluster.</p>
<i>applicationVersion</i>	<p>Optional. Version number of the deployed application. Required if more than one version of WebCenter Portal is deployed.</p>

10.21.3.3 Example

The following examples update the cache to include all space-related metadata (in MDS) and security data (in the policy store) in synchronous mode:

```
wls:/weblogic/serverConfig>refreshGroupSpaceCache (appName='webcenter',
spaceNames='', syncMode=1, updateType='all', cleanCache=0)
```

```
wls:/weblogic/serverConfig>refreshGroupSpaceCache (appName='webcenter')
```

The following example updates the Spaces Cache to include space-related metadata (in MDS) and security data (in the policy store) for two group spaces named MyGroupSpace1 and MyGroupSpace2. The cache refreshes in synchronous mode.

```
wls:/weblogic/serverConfig>refreshGroupSpaceCache (appName='webcenter',
spaceNames='MyGroupSpace1,MyGroupSpace2')
```

10.21.4 refreshSpaceTemplateCache

Module: Oracle WebCenter Portal

Use with WLST: Online

10.21.4.1 Description

Migrates metadata for individual space templates (in MDS) and template security data (in a policy store) to the *Space Template Cache*.

WebCenter Spaces 11.1.1.2.0 (and later) uses tables (referred to as the Space Template Cache) to store space template metadata and security-related data. When you patch from WebCenter Spaces 11.1.1.1.0 to 11.1.1.2.0, you must run the `refreshSpaceTemplateCache` command so that all your existing template data is migrated to the new Space Templates Cache.

10.21.4.2 Syntax

```
refreshSpaceTemplateCache (appName, [spaceTemplateName, syncMode, updateType,
cleanCache, server, applicationVersion])
```

Argument	Definition
<code>appName</code>	Name of the application in which to perform this operation. For WebCenter Portal (previously known as Spaces), the application name is always <code>webcenter</code> .
<code>spaceNames</code>	Optional. Names of one or more space templates that you want to refresh. To refresh all the space templates in MDS, enter <code>spaceTemplateName= ''</code> To refresh selective space templates, enter one or more template names separated with a comma, for example: <code>spaceNames='MySpaceTemplate1, MySpaceTemplate'</code>

Argument	Definition
<i>updateType</i>	<p>Optional. Indicates the type of data to refresh. Valid values are: <i>security</i>, <i>metadata</i>, <i>all</i>. The default value is <i>security</i>.</p> <ul style="list-style-type: none"> ▪ <i>security</i> - Refreshes the cache with security data stored in the policy store. The security data that is stored includes member data for the space template, whether or not a space template is public, and whether or not a space template is accessible to users assigned the <i>Authenticated-User</i> role (in earlier releases this role was named <i>Spaces-User</i>). ▪ <i>metadata</i> - Refreshes the cache with space template-related metadata stored in MDS. The data that is stored includes metadata information such as the display name, keywords, icon, logo, and so on. ▪ <i>all</i> - Refreshes the space template cache with data stored in MDS and the policy store.
<i>syncMode</i>	<p>Optional. Indicates whether to refresh the cache in synchronous or asynchronous mode.</p> <p>Valid values are 1 and 0. The default value is 1.</p> <p>When set to 1, the refresh process runs in synchronous mode.</p> <p>When set to 0, the refresh is asynchronous, that is, a new thread is spawned for the refresh process.</p> <p>Synchronous mode is recommended.</p>
<i>cleanCache</i>	<p>Optional. Indicates whether to remove data that no longer exists in MDS from the WebCenter Portal Cache during the refresh operation. Valid values are 1 and 0. The default value is 0.</p> <p>0 - No content in the WebCenter Portal Cache is cleared during the refresh operation.</p> <p>Always set this value to 0 when patching from 11.1.1.1.0 to 11.1.1.2.0.</p> <p>1 - Clears space template data from the WebCenter Portal Cache if the space template does not exist in MDS:</p> <ul style="list-style-type: none"> - If <i>spaceTemplateName</i>='' , data in the Cache is refreshed for all the templates in MDS and data for any other space template (not in MDS) is removed from the Cache. - If <i>spaceTemplateName</i> specifies the names of one or more templates, only data for the named templates is refreshed in the Cache. If you name a space template that does not exist in MDS, data for that space template is removed from the Cache. <p>Only set <i>cleanCache</i> to 1 if you imported an entire WebCenter Spaces application from an archive and you want to overwrite or clear the existing WebCenter Portal Cache.</p>
<i>server</i>	<p>Optional. Name of the managed server where WebCenter Portal is deployed. For example, <i>WC_Spaces</i>.</p> <p>Required when applications with the same name are deployed to different servers and also when you have a cluster.</p>
<i>applicationVersion</i>	<p>Optional. Version number of the deployed application. Required if more than one version of WebCenter Portal is deployed.</p>

10.21.4.3 Example

The following examples update the cache to include all space template-related metadata (in MDS) and security data (in the policy store) in synchronous mode:

```
wls:/weblogic/serverConfig>refreshSpaceTemplateCache(appName='webcenter',
spaceTemplateName='', syncMode=1, updateType='all', cleanCache=0)
```

```
wls:/weblogic/serverConfig>refreshSpaceTemplateCache (appName='webcenter')
```

The following example updates the Space Templates Cache to include space template related metadata (in MDS) and security data (in the policy store) for two space templates named `MySpaceTemplate1` and `MySpaceTemplate2`. The cache refreshes in synchronous mode.

```
wls:/weblogic/serverConfig>refreshSpaceTemplateCache (appName='webcenter',
spaceNames='MySpaceTemplate1,MySpaceTemplate2')
```

10.22 Identity Store

Use the commands listed in [Table 10–30](#) to configure options for searching an application's identity store.

Table 10–30 WebCenter Portal Identity Store WLST Commands

Use this command...	To...	Use with WLST...
setWebCenterIdStoreSearchConfig	Modify configuration options for searching a named applications's identity store.	Online
listWebCenterIdStoreSearchConfig	List current configuration options for searching a named application's identity store.	Online

10.22.1 setWebCenterIdStoreSearchConfig

Module: Oracle WebCenter Portal

Use with WLST: Online

10.22.1.1 Description

Modifies configuration options for searching a named application's identity store. Use these settings to optimize identity store searches (for users and roles) in WebCenter Portal or a Portal Framework application.

Identity store search parameters are stored in `adf-config.xml`. If a search parameter is not specified, it is not modified.

10.22.1.2 Syntax

```
setWebCenterIdStoreSearchConfig(appName, [narrowSearchTimeout, broadSearchTimeout,
maxSearchFilters, maxFetchRecords, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>narrowSearchTimeout</i>	Optional. Maximum time allowed (in ms) for small, simple searches, such as fetching a single user from the identity store. Out-of-the-box, the default is 30000ms.
<i>broadSearchTimeout</i>	Optional. Maximum time allowed (in ms) to return large result sets, such as returning users and roles that match a name pattern. Out-of-the-box, the default is 60000.

Argument	Definition
<i>maxSearchFilters</i>	Optional. Number of search filters allowed for the application's identity store. The maximum allowed, out-of-the-box, is 100. Some identity store searches are executed using search filters which are converted into LDAP search calls. If your associated LDAP server limits the search condition, you can set the <i>maxSearchFilters</i> property to match your LDAP server setting.
<i>maxFetchRecords</i>	Optional. Maximum number of records to be returned from each search query. Out-of-the-box, the default is 100. The value of this setting will impact the performance of your LDAP server so take this into consideration when increasing the search result limit. Note that the LDAP server imposes its own search result limit, so the actual limit that is used will be the lesser of these two values.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <i>WC_Spaces</i> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.22.1.3 Example

The following example increases both identity store search timeouts.

```
wls:/weblogic/serverConfig>setWebCenterIdStoreSearchConfig(appName='webcenter',
narrowSearchTimeout=60000, broadSearchTimeout=100000);
```

The following example limits the maximum number of records returned to 100.

```
wls:/weblogic/serverConfig>setWebCenterIdStoreSearchConfig(appName='webcenter',
maxFetchRecords=100);
```

10.22.2 listWebCenterIdStoreSearchConfig

Module: Oracle WebCenter Portal

Use with WLST: Online

10.22.2.1 Description

Lists current configuration options for searching the identity store for a named application (WebCenter Portal or a Portal Framework application).

Identity store search parameters are stored in *adf-config.xml*.

10.22.2.2 Syntax

```
listWebCenterIdStoreSearchConfig(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <i>webcenter</i> . For Portal Framework applications, specify the appropriate name.

Argument	Definition
<code>server</code>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<code>applicationVersion</code>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.22.2.3 Example

The following example displays identity store search configuration information for WebCenter Portal (`webcenter`).

```
wls:/weblogic/serverConfig>listWebCenterIdStoreSearchConfig (appName='webcenter');
```

```
-----
User role search configuration parameters
-----
Narrow search timeout      : 30000
Broad search timeout      : 60000
Maximum search filters    : 100
Maximum records to fetch  : 200
```

10.23 Lifecycle

Use the commands listed in [Table 10-31](#) to perform lifecycle operations for WebCenter Portal and Portal Framework applications.

Table 10-31 Lifecycle WLST Commands

Use this command...	To...	Use with WLST...
<code>deployWebCenterPortal</code>	(WebCenter Portal only) Deploy a portal from a stage environment to a production environment.	Online
<code>propagateWebCenterPortal</code>	(WebCenter Portal only) Propagate metadata for a named portal, from a stage environment to a production environment.	Online
<code>exportWebCenterPortals</code>	(WebCenter Portal only) Export one or more named portals to a portal archive (<code>.par</code> file).	Online
<code>exportWebCenterPortalTemplates</code>	(WebCenter Portal only) Export one or more named portal templates to a portal archive (<code>.par</code> file).	Online
<code>importWebCenterPortals</code>	(WebCenter Portal only) Import one or more portals or portal templates from a portal archive (<code>.par</code> file).	Online
<code>listWebCenterPortalArchive</code>	(WebCenter Portal only) List the content of a portal archive and extract the portal archive to a specified location	Online or Offline

Table 10–31 (Cont.) Lifecycle WLST Commands

Use this command...	To...	Use with WLST...
exportWebCenterPortalChanges	(WebCenter Portal only) Export metadata changes for a portal to a portal archive (.par file).	Online
importWebCenterPortalChanges	(WebCenter Portal only) Import metadata changes for a portal from a portal archive (.par file).	Online
exportWebCenterPortalConnections	(WebCenter Portal only) Export connection configuration information from a source WebCenter Portal environment to a named file.	Online
importWebCenterPortalConnections	(WebCenter Portal only) Import new WebCenter Portal connections from a named connection properties file.	Online
setSpaceState	(WebCenter Portal only) Take a portal offline or bring a portal online.	Online
exportWebCenterResource	Export a portal resource to an export archive (.ear file).	Online
importWebCenterResource	Import a portal resource from an export archive (.ear file)	Online
importWebCenterTranslations	Import translations for WebCenter Portal.	Online
exportWebCenterApplication	Export the WebCenter Portal application to an export archive (.ear file).	Online
importWebCenterApplication	Import the WebCenter Portal application from an export archive (.ear file).	Online
exportPortletClientMetadata	Export portlet client metadata and producer customizations and personalizations to an export archive.	Online
importPortletClientMetadata	Import portlet client metadata and producer customizations and personalizations from an export archive.	Online
showProducerImportFailures	Display names of producers where metadata imports have failed and reasons for those failures.	Online
retryAllFailedProducerImports	Attempt to import outstanding producer metadata	Online
cloneWebCenterManagedServer	Clone a Managed Server used by WebCenter Portal or a Portal Framework application.	Online

Table 10–32 Life Cycle WLST Commands Deprecated in 11.1.1.8.0

Use this command...	To...	Use with WLST...
exportGroupSpaces (Deprecated)	Export one or more spaces to an export archive.	Online
exportGroupSpaceTemplates (Deprecated)	Export one or more space templates to an export archive.	Online

Table 10–32 (Cont.) Life Cycle WLST Commands Deprecated in 11.1.1.8.0

Use this command...	To...	Use with WLST...
importGroupSpaces (Deprecated)	Import one or more spaces or space templates from an export archive.	Online

10.23.1 deployWebCenterPortal

Module: Oracle WebCenter Portal

Use with WLST: Online

10.23.1.1 Description

(WebCenter Portal only) Deploys a portal from a stage environment to a production environment.

Notes:

- The name of the managed server must be the same in both the stage and production environments.
 - A connection to the production environment must be defined on the stage instance.
 - You must have at least the `WebLogicMonitor` role and the `WebCenter Portal` permission `Portals - Manage All`.
-

10.23.1.2 Syntax

```
deployWebCenterPortal(appName, portalName, targetConnectionName,
deployCustomizations, deployPortalContent, deploySecurity, deployData,
deployActivities, overwrite, savePortal, deployLog, server, applicationVersion)
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> .
<i>portalName</i>	Name of the portal that you want to deploy. For example, <code>portalName='myPortal'</code> . Note: Do not enter the portal's display name here. You must enter the portal name that appears in the portal URL. If you are not sure, obtain the portal name from the <i>About Portal</i> dialog.
<i>targetConnectionName</i>	Name of a connection on the source stage instance that specifies how to connect to the target production instance. Note: Use Enterprise Manager or the WLST command adf_createHttpUrlConnection to configure the connection if it does not exist.

Argument	Definition
<i>deployCustomizations</i>	<p data-bbox="708 228 1446 281">Optional. Indicates whether to deploy customizations associated with the portal on the target. Valid values are 1 and 0.</p> <ul data-bbox="708 296 1446 695" style="list-style-type: none"> <li data-bbox="708 296 1446 569"> ■ 1 - Deploy portal customizations. This includes: <ul data-bbox="753 331 1446 569" style="list-style-type: none"> <li data-bbox="753 331 1446 384">Portal-level customizations (to system pages, assets, task flows, and so on) <li data-bbox="753 399 1446 451">User-level customizations (sometimes referred to as user personalizations) <p data-bbox="753 466 1446 569">deployCustomizations does not completely overwrite existing portal customizations on the target (if any). Only customizations included in the source portal are overwritten on deployment, leaving any other customizations on the target unchanged.</p> <li data-bbox="708 583 1446 695"> ■ 0 - Exclude portal customizations, for example, deploy default task flows without any customizations and the default portal settings. If you are redeploying a portal, all existing customizations on the target are preserved. <p data-bbox="708 709 1003 730">This argument defaults to 1.</p>
<i>deployPortalContent</i>	<p data-bbox="708 751 1446 804">Optional. Specifies whether to deploy the portal's content folder on the target. Valid values are 1 and 0.</p> <ul data-bbox="708 819 1446 884" style="list-style-type: none"> <li data-bbox="708 819 1446 846">■ 1 - Deploys the portal's content folder. <li data-bbox="708 856 1446 884">■ 0 - Excludes portal content. <p data-bbox="708 898 1003 919">This argument defaults to 0.</p>
<i>deploySecurity</i>	<p data-bbox="708 940 1446 993">Optional. Indicates whether to import portal member details on the target. Valid values are 1 and 0.</p> <ul data-bbox="708 1008 1446 1178" style="list-style-type: none"> <li data-bbox="708 1008 1446 1060">■ 1 - Roles and permissions for the portal, as well as member details and their role assignments, are deployed on the target. <li data-bbox="708 1075 1446 1178">■ 0 - Only portal roles and permissions are deployed. This option is useful when migrating between stage and production environments and where member details, added during the testing phase, are no longer required. <p data-bbox="708 1192 1003 1213">This argument defaults to 1.</p> <p data-bbox="708 1228 1446 1283">Note: Always set <code>deploySecurity=1</code> when importing a brand new portal as you cannot import a new portal without a security policy.</p>
<i>deployData</i>	<p data-bbox="708 1304 1446 1356">Optional. Indicates whether to deploy portal data on the target. Valid values are 1 and 0.</p> <ul data-bbox="708 1371 1446 1591" style="list-style-type: none"> <li data-bbox="708 1371 1446 1476">■ 1 - Portal-related data stored in the WebCenter Portal database for activity streams, events, feedback, lists, links, message boards, people connections, polls, profiles, polls, and surveys is deployed. <li data-bbox="708 1491 1446 1591">■ 0 - Portal data is not deployed and data on the target (if any) is preserved. This option is useful when migrating between stage and production environments and where test data is no longer required. <p data-bbox="708 1606 1003 1627">This argument defaults to 1.</p>

Argument	Definition
<i>deployActivities</i>	<p>Optional. Indicates whether to deploy activity stream messages on the target. This option is only applicable when <code>deployData=1</code>.</p> <p>Valid values are 1 and 0.</p> <ul style="list-style-type: none"> 1 - Activity stream messages from the source portal are deployed on the target. 0 - Activity stream messages from the source portal are not deployed to the target. Activity on the target (if any) is preserved. This option is useful when migrating between stage and production environments and where test activity data is not required. <p>This argument defaults to 1.</p>
<i>overwrite</i>	<p>Optional. Specifies whether to redeploy the portal if the portal already exists in the target. Valid values are 1 and 0.</p> <ul style="list-style-type: none"> 1 - Redeploys the portal. 0 - Prevents redeployment if the portal exists. <p>This argument defaults to 0.</p>
<i>savePortal</i>	<p>Optional. Specifies whether to back up the portal on the target instance before the portal is redeployed.</p> <p>Valid values are 1 and 0.</p> <ul style="list-style-type: none"> 1 - Backs up the portal before deployment. The backup archive is saved to the temporary directory on the target machine. 0 - Does not perform a portal back up before deployment. <p>The default value is 0.</p>
<i>deployLog</i>	<p>Optional. Name and location of a local log file containing detailed information about the deploy operation.</p> <p>If not specified, a deploy log file named <code>PortalDeploy_<timestamp>.log</code> is generated in the temporary directory.</p>
<i>server</i>	<p>Optional. Name of the managed server where WebCenter Portal is deployed. For example, <code>WC_Spaces</code>.</p> <p>Required when applications with the same name are deployed to different servers and also when you have a cluster.</p>
<i>applicationVersion</i>	<p>Optional. Version number of the deployed application. Required if more than one version of the WebCenter Portal application is deployed.</p>

10.23.1.3 Examples

The following example deploys a portal named `myPortal` without its content folder but includes the portal's customizations, security, and data:

```
wls:/weblogic/serverConfig> deployWebCenterPortal (appName='webcenter',
portalName='myPortal', targetConnectionName='MyProductionConnection')
```

Note: You can use the [adf_createHttpURLConnection](#) WLST command to create `MyProductionConnection`. For example:

```
adf_createHttpURLConnection (appName='webcenter',
name='MyProductionConnection',
url='http://example.com:7777', user='myuser',
password='mypassword', realm='ProductionRealm')
```

The following example deploys a portal named `myPortal` with all its associated content, customizations, security, and data, and also specifies a name and location for the deploy log file:

```
wls:/weblogic/serverConfig> deployWebCenterPortal (appName='webcenter',
portalName='myPortal', targetConnectionName='MyProductionConnection',
deployPortalContent=1, deployLog='/mydeploylogs/myPortal_deploy.log')
```

The following example backs up `myPortal` on the target before redeploying "myPortal" and all its associated content, customizations, security, and data on the source:

```
wls:/weblogic/serverConfig> deployWebCenterPortal (appName='webcenter',
portalName='myPortal', targetConnectionName='MyProductionConnection',
deployPortalContent=1, savePortal=1, overwrite=1)
```

10.23.2 propagateWebCenterPortal

Module: Oracle WebCenter Portal

Use with WLST: Online

10.23.2.1 Description

(WebCenter Portal only) Propagates metadata changes for a named portal, from a stage environment to a production environment. Metadata changes propagated:

- **Includes:**
 - Portal-level customizations (metadata changes) for portal pages, system pages, portlets, assets, task flows
 - User-level customizations (metadata changes) for portal pages, portlets, task flow instances
- **Excludes:** subportals, security, any changes to content and data, portal state (online/offline)

Important: You can only propagate portals that were previously deployed (from stage to production) using the [deployWebCenterPortal](#) command.

To migrate other changes, consider using [exportWebCenterPortals](#) and [importWebCenterPortals](#) or [deployWebCenterPortal](#).

Notes:

- The name of the managed server must be the same in both the stage and production environments.
 - A connection to the production environment must be defined on the stage instance.
 - You must have at least the `WebLogicMonitor` role and the `WebCenter Portal permission Portals - Manage All`.
-

10.23.2.2 Syntax

```
propagateWebCenterPortal (appName, portalName, targetConnectionName, [savePortal,
propagateLog, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> .
<i>portalName</i>	Name of the portal that you want to deploy. For example, <code>portalName='myPortal'</code> . Note: Do not enter the portal's display name here. You must enter the portal name that appears in the portal URL. If you are not sure, obtain the portal name from the <i>About Portal</i> dialog.
<i>targetConnectionName</i>	Name of a connection on the source stage instance that specifies how to connect to the target production instance. Note: Use Enterprise Manager or the WLST command <code>adf_createHttpURLConnection</code> to configure the connection if it does not exist.
<i>savePortal</i>	Optional. Specifies whether to back up the portal on the target instance to an archive before propagating changes. Valid values are 1 and 0: <ul style="list-style-type: none"> ▪ 1 - Backs up the target portal to an archive before propagation. If created, the backup archive is saved to the <code>/tmp</code> directory on the target machine. ▪ 0 - Do not back up the target portal before propagating changes. The default value is 0.
<i>propagateLog</i>	Optional. Name and location of a local log file containing detailed information about the propagation operation. If not specified, a propagation log file named <code>PortalPropagation_<timestamp>.log</code> is generated in the temporary directory.
<i>server</i>	Optional. Name of the managed server where WebCenter Portal is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the WebCenter Portal application is deployed.

10.23.2.3 Example

The following example propagates metadata changes for a portal named `myPortal`:

```
wls:/weblogic/serverConfig> propagateWebCenterPortal (appName='webcenter',
portalName='myPortal', targetConnectionName='MyProductionConnection')
```

Note: You can use the `adf_createHttpURLConnection` WLST command to create `MyProductionConnection`. For example:

```
adf_createHttpURLConnection (appName='webcenter',
name='MyProductionConnection',
url='http://example.com:7777', user='myuser',
password='mypassword', realm='ProductionRealm')
```

The following example backs up a portal named `myPortal` and then propagates metadata changes for the portal:

```
wls:/weblogic/serverConfig> propagateWebCenterPortal (appName='webcenter',
```

```
portalName='myPortal', targetConnectionName='MyProductionConnection',
savePortal=1)
```

The following example propagates metadata changes for a portal named `myPortal`, and also specifies a name and location for the propagation log file:

```
wls:/weblogic/serverConfig> propagateWebCenterPortal(appName='webcenter',
portalName='myPortal', targetConnectionName='MyProductionConnection',
propagateLog='/mypropagationlogs/myPortal_propagation.log')
```

10.23.3 exportWebCenterPortals

Module: Oracle WebCenter Portal

Use with WLST: Online

10.23.3.1 Description

(WebCenter Portal only) Exports one or more named portals to a portal archive (`.par` file), using the filename specified.

The portal archive file contains one or more portal data archives (`.pdr` files) -- one for each portal (or portal hierarchy) that you export. Each portal data archive includes portal-specific data, portal-level customizations, user-level customizations, security information, and optionally, the portal content folder.

The export operation continues if one of the portals fail to export properly. Status messages are shown in the WLST console indicating the success or failure of the export operation for each specified portal. Portals that could not be exported are excluded from the `.par` file.

Note: To run this command you must have at least the WebLogic Monitor role and the WebCenter Portal permission `Portals - Manage All`.

10.23.3.2 Syntax

```
exportWebCenterPortals(appName, fileName, [names, offlineDuringExport,
exportPortalContent, exportConnections, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> .
<i>fileName</i>	Name and location of the export archive (<code>.par</code> file). For example, <code>/myExports/myPortalExport.par</code> . If you do not specify a location, the archive is created in the same directory that you run the WLST command.

Argument	Definition
<i>names</i>	<p>Optional. Name of one or more portals that you want to export. Separate multiple portal names with a comma. For example: names= ' sales , finance '</p> <p>Note: Do not enter the portal's display names here. You must enter the name that is specified in the portal URL. The portal name is available from the <i>About Portal</i> dialog.</p> <p>If you leave the names argument blank, all the portals are exported (up to a maximum of ten portals). If your instance contains more than ten portals you must name each portal individually, using the names argument.</p>
<i>offlineDuringExport</i>	<p>Optional. Indicates whether the portals you want to export must be offline before starting the export process. If users are allowed to access the portal, any changes made to the portal once the export starts are not exported.</p> <p>Valid values are 1 and 0.</p> <ul style="list-style-type: none"> ■ 1 - Takes online portals (if any) offline before starting the export process and at the end of the export process, returns those portals back to their original online state. To prevent data loss during the export process, Oracle recommends that you set <code>offlineDuringExport=1</code>. ■ 0 - Exports the portals in their current state. <p>The default value is 0.</p>
<i>exportPortalContent</i>	<p>Optional. Specifies whether to export each portal's content folder on WebCenter Content Server.</p> <p>A content folder is automatically created on Content Server for any portal using document services to create, manage, and store portal documents (files, folders, wikis, blogs). Only content that is stored in this folder can be exported with the portal. The export does not, for example, include web content or pages displayed through Content Presenter since this information is not stored in the portal's content folder.</p> <p>Valid values are 1 and 0.</p> <ul style="list-style-type: none"> ■ 1 - Exports the portal's content folder. ■ 0 - Excludes portal content. <p>The default value is 0.</p>
<i>exportConnections</i>	<p>Optional. Specifies whether to export WebCenter Portal connections into a file named <code>connection.properties</code> and include it in the portal archive (<code>.par</code> file).</p> <p>In addition, a copy of <code>connection.properties</code> is included outside the archive at the same location, that is, the location specified using the <code>fileName</code> option.</p> <p>Valid values are 1 and 0.</p> <ul style="list-style-type: none"> ■ 1 - Export WebCenter Portal connections ■ 0 - Do not export WebCenter Portal connections. <p>The default value is 0.</p> <p>See also, "Understanding Connection Property Files" in <i>Oracle Fusion Middleware Administering Oracle WebCenter Portal</i>.</p>
<i>server</i>	<p>Optional. Name of the managed server where WebCenter Portal is deployed. For example, <code>WC_Spaces</code>.</p> <p>Required when applications with the same name are deployed to different servers and also when you have a cluster.</p>

Argument	Definition
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the WebCenter Portal application is deployed.

10.23.3.3 Examples

The following example exports `myPortal1` and `myPortal2` to `myPortalExport.par`:

```
wls:/weblogic/serverConfig> exportWebCenterPortals (appName='webcenter',
fileName='myPortalExport.par', names='myPortal1, myPortal2')
```

The following example exports `myPortal1` to `myPortalExport.par`. To ensure that `myPortal1` is offline while the export operation takes place, `offlineDuringExport` is set to 1:

```
wls:/weblogic/serverConfig> exportWebCenterPortals (appName='webcenter',
fileName='myPortalExport.par', names='myPortal1', offlineDuringExport=1)
```

The following example exports all the portals, including portal content folders, to `exportAllMyPortals.par`:

```
wls:/weblogic/serverConfig> exportWebCenterPortals (appName='webcenter',
fileName='exportAllMyPortals.par', exportPortalContent=1)
```

10.23.4 exportWebCenterPortalTemplates

Module: Oracle WebCenter Portal

Use with WLST: Online

10.23.4.1 Description

(WebCenter Portal only) Exports one or more named portal templates to a portal archive (`.par` file), using the filename specified. The portal archive file contains a portal data archive (`.pdr` file) for each portal template you export.

Each portal data archive includes template-specific data (pages, discussions, and lists), customizations, security information, and optionally, portal template content.

The export operation continues if one of the portal templates fails to export properly. Status messages are shown in the WLST console indicating the success or failure of the export operation for each specified portal. Portal templates that could not be exported are excluded from the `.par` file.

Note: To run this command you must have at least the WebLogic Monitor role and the WebCenter Portal permission `Portal Templates - Manage All`.

10.23.4.2 Syntax

```
exportWebCenterPortalTemplates (appName, fileName, [names,
exportPortalTemplateContent, server, applicationVersion])
```

Argument	Definition
<code>appName</code>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> .
<code>fileName</code>	Name and location of the export archive (.par file). For example, <code>/myExports/myPortalTemplateExport.par</code> . If you do not specify a location, the archive is created in the same directory that you run the WLST command.
<code>names</code>	Optional. Name of one or more portals templates that you want to export. Separate multiple template names with a comma. For example: <code>names='mySalesTemplate,myHRTemplate'</code> Note: Do not enter portal template display names here. You must enter the name that is specified in the portal template URL. The portal name is available from the <i>About Portal Template</i> dialog. If you leave the <code>names</code> argument blank, all the templates are exported (up to a maximum of ten templates). If your instance contains more than ten portal templates you must name each template individually, using the <code>names</code> argument.
<code>exportPortalTemplateContent</code>	Optional. Specifies whether to export each template's content folder on WebCenter Content Server. A content folder is automatically created on Content Server for any template using document services to create, manage, and store template documents (files, folders, wikis, blogs). Only content that is stored in this folder can be exported with the portal template. The export does not, for example, include web content or pages displayed through Content Presenter since this information is not stored in the portal template's content folder. Valid values are 1 and 0. <ul style="list-style-type: none"> ■ 1 - Exports the portal template's content folder. ■ 0 - Excludes portal template content. The default value is 0.
<code>server</code>	Optional. Name of the managed server where WebCenter Portal is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<code>applicationVersion</code>	Optional. Version number of the deployed application. Required if more than one version of the WebCenter Portal application is deployed.

10.23.4.3 Examples

The following example exports `myPortalTemplate1` and `myPortalTemplate2` to `myPortalTemplateExport.par`:

```
wls:/weblogic/serverConfig> exportWebCenterPortalTemplates(appName='webcenter',
fileName='myPortalTemplateExport.par', names='myPortalTemplate1,
myPortalTemplate2')
```

The following example exports all the portal templates, including portal template content, to `exportAllMyPortalTemplates.par`:

```
wls:/weblogic/serverConfig> exportWebCenterPortalTemplates(appName='webcenter',
fileName='exportAllMyPortalTemplates.par', exportPortalTemplateContent=1)
```


10.23.5 importWebCenterPortals

Module: Oracle WebCenter Portal

Use with WLST: Online

10.23.5.1 Description

(WebCenter Portal only) Imports one or more portals or portal templates from a portal archive (.par file).

Note: To run this command you must have at least the WebLogic Monitor role and either the WebCenter Portal permission `Portals - Manage All` or `Portal Templates - Manage All`.

10.23.5.2 Syntax

```
importWebCenterPortals(appName, fileName, names, [parentPortal,
importCustomizations, importPortalContent, importSecurity, importData,
importActivities, overwrite, savePortals, forceOffline, importLog, server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> .
<i>fileName</i>	Name of the portal archive (.par file) containing the portals or portal templates you want to import. For example, <code>mySalesPortal.par</code> . Note: If you want to import a <i>space archive</i> (.ear file) that was generated from a previous WebCenter Portal release, specify the name of the .ear file. For example, <code>myOldFinanceSpace.ear</code> .
<i>names</i>	Name of one or more portals or portal templates that you want to import. For example: <code>names='sales'</code> . Separate multiple names with a comma. For example: <code>names='sales,finance'</code> Note: Do not enter display names here. You must enter the name that is specified in the portal or portal template URL: <ul style="list-style-type: none"> ■ Portal names are available from the <i>About Portal</i> dialog. ■ Portal template names are available from the <i>About Portal Template</i> dialog. Note: The <code>names</code> argument is ignored if the archive that you want to import was generated to an .ear file from an earlier WebCenter Portal version, that is, version 11.1.1.7.0 or earlier.
<i>parentPortal</i>	Optional. Name of the parent portal under which to place portals in the archive. If specified, imported portals become subportals of the parent portal. This argument defaults to null. When no parent is specified, archived portals are imported as root portals. Note: If the archive contains portal templates, this argument is ignored.

Argument	Definition
<i>importCustomizations</i>	<p data-bbox="621 222 1369 279">Optional. Indicates whether to import customizations from the portal archive. Valid values are 1 and 0.</p> <ul data-bbox="621 289 1369 735" style="list-style-type: none"> <li data-bbox="621 289 1369 573"> <p data-bbox="670 289 1369 321">1 - Imports the portal's customizations. This includes:</p> <p data-bbox="670 331 1369 388">Portal-level customizations (to system pages, assets, task flows, and so on)</p> <p data-bbox="670 399 1369 455">User-level customizations (sometimes referred to as user personalizations)</p> <p data-bbox="670 466 1369 573">Import does not completely overwrite existing portal customizations on the target (if any). Only customizations included in the portal archive are overwritten on import, leaving any other customizations on the target unchanged.</p> <li data-bbox="621 583 1369 735"> <p data-bbox="670 583 1369 667">0 - New portals are imported without customizations, for example, default task flows and default portal settings are imported.</p> <p data-bbox="670 678 1369 735">If you are importing a portal that already exists on the target, existing customizations on the target are preserved.</p> <p data-bbox="621 745 1369 772">This argument defaults to 1.</p> <p data-bbox="621 783 1369 810">Note: Portlet and page customizations are always imported.</p> <p data-bbox="621 821 1369 884">Note: If the archive contains portal templates, this argument is ignored.</p>
<i>importPortalContent</i>	<p data-bbox="621 894 1369 978">Optional. Specifies whether to import content associated with the portal or portal template, that is, import documents in the archive (if any) to the target content repository.</p> <p data-bbox="621 989 1369 1016">Valid values are 1 and 0.</p> <ul data-bbox="621 1026 1369 1178" style="list-style-type: none"> <li data-bbox="621 1026 1369 1083"> <p data-bbox="670 1026 1369 1083">1 - Imports content into the target portal or portal template's content folder. Existing folders are overwritten.</p> <li data-bbox="621 1094 1369 1178"> <p data-bbox="670 1094 1369 1178">0 - Excludes portal (or portal template) content. This option is useful when migrating between stage and production environments where test content is no longer required.</p> <p data-bbox="621 1188 1369 1215">This argument defaults to 0.</p> <p data-bbox="621 1226 1369 1367">Note: Portal archives that contain large content folders may exceed the maximum upload size for files (2 GB by default). If necessary, you can increase this setting. For details, see "Changing the Maximum File Upload Size" in <i>Oracle Fusion Middleware Administering Oracle WebCenter Portal</i>.</p>
<i>importSecurity</i>	<p data-bbox="621 1377 1369 1434">Optional. Indicates whether or not to import portal member details from the export archive. Valid values are 1 and 0.</p> <ul data-bbox="621 1444 1369 1617" style="list-style-type: none"> <li data-bbox="621 1444 1369 1501"> <p data-bbox="670 1444 1369 1501">1 - Imports roles and permissions for the portal, as well as member details and their role assignments</p> <li data-bbox="621 1512 1369 1617"> <p data-bbox="670 1512 1369 1617">0 - Imports only portal roles and permissions. This option is useful when migrating between stage and production environments and where member details, added during the testing phase, are no longer required.</p> <p data-bbox="621 1627 1369 1654">This argument defaults to 1.</p> <p data-bbox="621 1665 1369 1728">Note: If the archive contains portal templates, this argument is ignored.</p>

Argument	Definition
<i>importData</i>	<p>Optional. Indicates whether to import data from the export archive. Valid values are 1 and 0.</p> <ul style="list-style-type: none"> ■ 1 - Portal-related data stored in the WebCenter Portal database for activity streams, events, feedback, lists, links, message boards, people connections, polls, profiles, and surveys is imported. ■ 0 - Portal data is not imported and data on the target (if any) is preserved. This option is useful when migrating between stage and production environments and where test data is no longer required. <p>This argument defaults to 1.</p> <p>Note: If the archive contains portal templates, this argument is ignored.</p>
<i>importActivities</i>	<p>Optional. Indicates whether to import activity messages from the export archive. Valid values are 1 and 0.</p> <ul style="list-style-type: none"> ■ 1 - Activity messages stored in the portal archive are imported. ■ 0 - Activity messages are not imported. <p>This argument defaults to 1.</p> <p>Note: If the archive contains portal templates, this argument is ignored.</p>
<i>overwrite</i>	<p>Optional. Specifies whether to overwrite portals or portal templates that exist in the target.</p> <p>Valid values are 1 and 0.</p> <ul style="list-style-type: none"> ■ 1 - Overwrites existing portals (or portal templates). ■ 0 - Only imports new portals (or portal templates). Do not import portals or portal templates that exist on the target. <p>The default is 0.</p>
<i>savePortals</i>	<p>Optional. Specifies whether to save existing portals or portal templates to an archive before starting the import operation.</p> <p>Valid values are 1 and 0:</p> <ul style="list-style-type: none"> ■ 1 - Before importing, back up existing portals or portal templates to an archive. If created, the archive is copied to the /tmp directory on the target machine. ■ 0 - Do not back up existing portals or portal templates. <p>The default value is 0.</p>
<i>forceOffline</i>	<p>Optional. Specifies whether to take existing portals offline before starting the import process.</p> <p>Valid values are 1 and 0.</p> <ul style="list-style-type: none"> ■ 1 - Takes the portals offline before starting the import process. ■ 0 - Attempts to import the portals. If one or more portals are currently online, you are prompted to take the portals offline. <p>The default value is 0.</p> <p>Note: If the archive contains portal templates, this argument is ignored.</p>
<i>importLog</i>	<p>Optional. Specifies the name of a local log file containing detailed information about the import operation.</p> <p>If not specified, a log file named <code>PortalImport_<timestamp>.log</code> is generated in the temporary directory.</p>

Argument	Definition
<i>server</i>	Optional. Name of the managed server where WebCenter Portal is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the WebCenter Portal application is deployed.

10.23.5.3 Example

The following example imports a new version of the sales portal archived in `myPortalExport.par` and specifies a name and location for the import log file. To ensure that the existing sales portal is offline while the import operation takes place, `forceOffline` is set to 1:

```
wls:/weblogic/serverConfig> importWebCenterPortals(appName='webcenter',
fileName='myPortalExport.par', names='sales', forceOffline=1, importLog='sales_
import.log')
```

The following example saves a copy of the sales portal before re-importing a new version of the sales portal from `myPortalExport.par`:

```
wls:/weblogic/serverConfig> importWebCenterPortals(appName='webcenter',
fileName='myPortalExport.par', names='sales', savePortals=1)
```

The following example imports the newHire portal template archived in `myPortalTemplateExport.par` and specifies a name and location for the import log file:

```
wls:/weblogic/serverConfig> importWebCenterPortals(appName='webcenter',
fileName='myPortalTemplateExport.par', names='newHire',
importLog='newHireTemplate_import.log')
```

10.23.6 listWebCenterPortalArchive

Module: Oracle WebCenter Portal

Use with WLST: Online or Offline

10.23.6.1 Description

(WebCenter Portal only) Lists the content of a portal archive and optionally, extracts the portal archive to a specified location.

10.23.6.2 Syntax

```
listWebCenterPortalArchive(appName, fileName, [extractDir, server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> .
<i>fileName</i>	Name and location of a portal archive.

Argument	Definition
<i>extractDir</i>	Optional. Destination directory in which to extract portal archive content. If a directory is specified, the portal archive is extracted to that location. If omitted, archive content is listed but not extracted.
<i>server</i>	Optional. Name of the managed server where WebCenter Portal is deployed. For example, <i>WC_Spaces</i> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the WebCenter Portal application is deployed.

10.23.6.3 Examples

The following example lists the content of `myPortal.par` and extracts archive content to the directory `/myPortalArchives/myPortalContent`:

```
wls:/weblogic/serverConfig> listWebCenterPortalArchive (appName='webcenter',
fileName='/myPortalArchives/myPortal.par',
extractDir='/myPortalArchives/myPortalContent')
```

10.23.7 exportWebCenterPortalChanges

Module: Oracle WebCenter Portal

Use: Online (IBM WebSphere only)

10.23.7.1 Description

(WebCenter Portal only) Exports portal metadata changes for a named portal to a portal archive (.par file), using the filename specified.

Portal metadata changes exported:

- **Includes:**
 - Portal-level customizations (metadata changes) for portal pages, system pages, portlets, assets, task flows
 - User-level customizations (metadata changes) for portal pages, portlets, task flow instances
- **Excludes:** subportals, security, any changes to content and data, portal state (online/offline)

Notes:

- You can only export changes for a portal that was previously exported using the [exportWebCenterPortals](#) WLST command.
 - You must have at least the `WebLogicMonitor` role and the `WebCenter Portal permission Portals - Manage All` to run this command.
-
-

10.23.7.2 Syntax

```
exportWebCenterPortalChanges (appName, fileName, portalName, [server,
```

```
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> .
<i>fileName</i>	Name and location of the export archive (.par file). For example, <code>/myExports/myPortalChangesExport.par</code> . If you do not specify a location, the archive is created in the same directory that you run the command.
<i>portalName</i>	Name of the portal for which you want to export changes. For example, <code>portalName='myPortal'</code> . Note: Do not enter the portal's display name here. You must enter the portal name that appears in the portal URL. If you are not sure, obtain the portal name from the <i>About Portal</i> dialog.
<i>server</i>	Optional. Name of the managed server where WebCenter Portal is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the WebCenter Portal application is deployed.

10.23.7.3 Example

The following example exports metadata changes for a portal named `myPortal` to `myPortalChangesExport.par`:

```
wsadmin> WebCenter.exportWebCenterPortalChanges(appName='webcenter',
fileName='myPortalChangesExport.par', portalName='myPortal')
```

10.23.8 importWebCenterPortalChanges

Module: Oracle WebCenter Portal

Use: Online (IBM WebSphere only)

10.23.8.1 Description

(WebCenter Portal only) Imports metadata changes from a portal archive (.par file), using the filename specified.

Notes:

- You can only import changes for a portal that was previously exported using the [importWebCenterPortals](#) WLST command.
 - You must have at least the WebLogic Monitor role and the WebCenter Portal permission `Portals - Manage All` to run this command.
-
-

10.23.8.2 Syntax

```
importWebCenterPortalChanges(appName, fileName, [importLog, server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> .
<i>fileName</i>	Name and location of the export archive (.par file). For example, <code>/myExports/myPortalChangesExport.par</code> .
<i>importLog</i>	Optional. Specifies a name of a local log file containing detailed information about the import operation. If not specified, a log file named <code>PortalChangesImport_<timestamp>.log</code> is generated in the temporary directory.
<i>server</i>	Optional. Name of the managed server where WebCenter Portal is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the WebCenter Portal application is deployed.

10.23.8.3 Example

The following example imports metadata changes for a portal from `myPortalChangesExport.par`:

```
wsadmin> WebCenter.importWebCenterPortalChanges(appName='webcenter',
fileName='myPortalChangesExport.par')
```

The following example imports metadata changes for a portal from `myPortalChangesExport.par` and specifies a name and location for the import log file:

```
wsadmin> WebCenter.importWebCenterPortalChanges(appName='webcenter',
fileName='myPortalChangesExport.par', importLog='myPortalImport.log')
```

10.23.9 exportWebCenterPortalConnections

Module: Oracle WebCenter Portal

Use with WLST: Online

10.23.9.1 Description

(WebCenter Portal only) Exports connection configuration information from the source WebCenter Portal environment to a named file.

The following connections are exported:

- Analytics collector connections
- Content repository connections (Oracle WebCenter Content, Oracle Portal, file system location)
- Discussions server connections
- Events server connections
- External application connections
- Mail server connections
- Oracle Secure Enterprise Search connections

- Portlet producer connections (WSRP and PDK-Java)
- Pagelet producer connections
- Presence server connections
- URL connections
- Web service connections (used by data controls)
- Worklist / BPEL server connections

Note:

- Personalization provider connections (for CMIS, Activity Graph, and People Connections) are not exported.
 - You must have at least the WebLogic Admin role to run the `exportWebCenterPortalConnections` command.
-
-

10.23.9.2 Syntax

```
exportWebCenterPortalConnections(appName, fileName, [connectionType,  
[connectionName,] logFile, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> .
<i>fileName</i>	Specifies a name and location for the connection properties file. If you do not specify a location, the file is saved in the current directory.

Argument	Definition
<i>connectionType</i>	<p>Optional. Specifies the type of connections you want to export. Separate multiple connection types with a comma. For example:</p> <pre>connectionType= 'wsrpProducerConnection, webServiceConnection'</pre> <p>If left blank, all connection types are exported.</p> <p>Valid connection types are:</p> <ul style="list-style-type: none"> ■ analyticsCollectorConnection (Analytics collector) ■ webcenterContentServerConnection (Oracle WebCenter Content) ■ oraclePortalConnection (Oracle Portal) ■ fileSystemConnection (File system) ■ discussionConnection (Discussions server) ■ personalEventConnection (Presence server) ■ externalAppConnection (External application) ■ mailConnection (Mail server) ■ sesConnection (Oracle Secure Enterprise Search) ■ wsrpProducerConnection (WSRP portlet producer) ■ jpdkProducerConnection (PDK-Java portlet producer) ■ pageletProducerConnection (Pagelet producer) ■ impConnection (Presence server) ■ urlConnection (URL) ■ webServiceConnection (Web service) ■ bpelConnection (Worklist / BPEL server) <p>Note: This argument is mandatory if you specify <i>connectionName</i>.</p>
<i>connectionName</i>	<p>Optional. Names specific connections you want to export for a single <i>connectionType</i>. Separate multiple connection names with a comma.</p> <p>For example, if <i>connectionType</i>= 'wsrpProducerConnection', you can specify to export one or more connections of this type:</p> <pre>connectionName= 'myWSRPProducer1, myWSRPProducer2'</pre> <p>When you specify a value for <i>connectionName</i>, you must specify the <i>connectionType</i> argument as well. For example:</p> <pre>exportWebCenterPortalConnections (appName= 'webcenter', fileName= '/scratch/conn.properties', connectionType= 'wsrpProducerConnection', connectionName= 'MyWSRPConn')</pre> <p>Note: If no names are specified, all connections are exported for the specified <i>connectionType</i>.</p>
<i>logFile</i>	<p>Specifies a name of a local log file containing detailed information about the export connection operation.</p> <p>If not specified, a log file named <code>ConnectionExport_<timestamp>.log</code> is generated in the temporary directory.</p>
<i>server</i>	<p>Optional. Name of the managed server where WebCenter Portal is deployed. For example, <code>WC_Spaces</code>.</p> <p>Required when applications with the same name are deployed to different servers and also when you have a cluster.</p>

Argument	Definition
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the WebCenter Portal application is deployed.

10.23.9.3 Examples

The following example exports connection configuration information for all WSRP producer and web service connections to a file named `connection.properties` located at `/myConnections`:

```
wls:/weblogic/serverConfig> exportWebCenterPortalConnections(appName='webcenter',
fileName='/myConnections/connection.properties',
connectionType='wsrpProducerConnection,webServiceConnection')
```

The following example exports connection configuration information for two WSRP producer connections named `myWSRP1` and `myWSRP2` to a file named `connection.properties` located at `/myConnections`:

```
wls:/weblogic/serverConfig> exportWebCenterPortalConnections(appName='webcenter',
fileName='/myConnections/connection.properties',
connectionType='wsrpProducerConnection', connectionName='myWSRP1,myWSRP2')
```

The following example exports all connection configuration information to a file named `connection.properties` located at `/myConnections`:

```
wls:/weblogic/serverConfig> exportWebCenterPortalConnections(appName='webcenter',
fileName='/myConnections/connection.properties')
```

The following example exports connection configuration information to a file named `connection.properties` located at `\myConnections`. Detailed information about the export operation is also logged to `exportConnections.log` located at `/myExportLogs`:

```
wls:/weblogic/serverConfig> exportWebCenterPortalConnections(appName='webcenter',
fileName='/myConnections/connection.properties',
logFile='/myExportLogs/exportConnections.log')
```

10.23.10 importWebCenterPortalConnections

Module: Oracle WebCenter Portal

Use with WLST: Online

10.23.10.1 Description

(WebCenter Portal only) Imports new WebCenter Portal connections from a named connection properties file. Connections that do not exist on the target are imported. Connections that exist on the target are ignored.

The following connections can be imported:

- Analytics collector connections
- Content repository connections (Oracle WebCenter Content, Oracle Portal, file system location)
- Discussions server connections
- Events server connections

- External application connections
- Mail server connections
- Oracle Secure Enterprise Search connections
- Portlet producer connections (WSRP and PDK-Java)
- Pagelet producer connections
- Presence server connections
- URL connections
- Web service connections (used by data controls)
- Worklist / BPEL server connections

Note:

- You must have at least the WebLogic Admin role to run the `importWebCenterPortalConnections` command.
 - You can only import connection information that was previously exported using the [exportWebCenterPortalConnections](#) command.
 - Newly imported portlet producer, external application, URL, and web service connections are immediately available in the target. For the other connection types, you are prompted to restart the managed server on which WebCenter Portal is deployed to make new connections available.
-
-

10.23.10.2 Syntax

```
importWebCenterPortalConnections(appName, fileName, [promptForPassword, logFile,
server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> .
<i>fileName</i>	Specifies the name and location of a connection properties file.
<i>promptForPassword</i>	Optional. Specifies whether to prompt the user for a password if credentials are required to create a new connection during the import operation. For example, you must enter a password to create a new Oracle-Secure Enterprise Search (SES) connection. Valid values are 1 and 0: <ul style="list-style-type: none"> ■ 1 - Prompts the user to enter credentials if a password is required. ■ 0 - Do not prompt the user to enter passwords if required to create a new connection. Always set this argument to 0 if you run this command within a script. The default is 1.
<i>logFile</i>	Optional. Specifies the name of a local log file in which to record detailed information about the import connection operation. If no value is specified, a log file named <code>ConnectionImport_<timestamp>.log</code> is generated in the temporary directory.

Argument	Definition
<i>server</i>	Optional. Name of the managed server where WebCenter Portal is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the WebCenter Portal application is deployed.

10.23.10.3 Examples

The following example imports connections defined in a file named `connection.properties`, located at `/myConnections`:

```
wls:/weblogic/serverConfig> importWebCenterPortalConnections(appName='webcenter',
fileName='/myConnections/connection.properties')
```

The following example imports connections defined in a file named `connection.properties`, located at `\myConnections`. Detailed information about the import operation is also logged to `importConnection.log`:

```
wls:/weblogic/serverConfig> importWebCenterPortalConnections(appName='webcenter',
fileName='/myConnections/connection.properties', logFile='importConnection.log')
```

The following example imports connections defined in a file named `connection.properties`, located at `\myConnections`. Do not prompt the user to enter credentials (if required):

```
wls:/weblogic/serverConfig> importWebCenterPortalConnections(appName='webcenter',
fileName='/myConnections/connection.properties', promptForPassword=0)
```

10.23.11 setSpaceState

Module: Oracle WebCenter Portal

Use with WLST: Online

10.23.11.1 Description

(WebCenter Portal only) Takes a portal offline or brings a portal online.

10.23.11.2 Syntax

```
setSpaceState(appName, spaceName, offline, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the name is always <code>webcenter</code> .
<i>spaceName</i>	Name of the portal you want to take offline or bring online.
<i>offline</i>	Specifies whether to take the portal offline or bring it back online. Valid values are 1 and 0: <ul style="list-style-type: none"> ■ 1 takes the portal offline ■ 0 brings the portal online

Argument	Definition
<i>server</i>	Optional. Name of the managed server where WebCenter Portal is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of tWebCenter Portal is deployed.

10.23.11.3 Example

The following example takes `MyPortal` offline:

```
wls:/weblogic/serverConfig> setSpaceState(appName='webcenter',
spaceName='MyPortal', offline=1)
```

10.23.12 exportWebCenterResource

Module: Oracle WebCenter Portal

Use with WLST: Online

10.23.12.1 Description

(WebCenter Portal and Portal Framework applications) Exports a single asset, device, or device group to an export archive (.ear file), using the filename specified.

When you export an asset, you can specify either `resourceGUID` or `resourceName`.

When you export a device or device group, you can only specify `resourceName`.

Notes:

- To run this command you must have at least the WebLogic Monitor role, as well as the appropriate Create/Edit/Delete permission for the type of asset, device or device group you want to export.

For more information, see "About Permissions Required to Import (or Export) Assets" in *Oracle Fusion Middleware Administering Oracle WebCenter Portal*.
 - You cannot export out-of-the-box assets, devices, or device groups.
-

10.23.12.2 Syntax

```
exportWebCenterResource(appName, fileName, resourceType, [resourceGUID,
resourceName, spaceName, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>fileName</i>	Name of the local file to which the export will be written.

Argument	Definition
<i>resourceType</i>	<p>Type of resource to export (an asset, device, or device group).</p> <p>Valid values include: <code>pageTemplate</code>, <code>contentPresenter</code>, <code>pageStyle</code>, <code>navigation</code>, <code>resourceCatalog</code>, <code>skin</code>, <code>taskFlow</code>, <code>mashupStyle</code>, <code>dataControl</code>, <code>device</code>, <code>deviceGroup</code></p> <p>Where:</p> <ul style="list-style-type: none"> ▪ <code>pageTemplate</code> - page template ▪ <code>contentPresenter</code> - Content presenter display template ▪ <code>pageStyle</code> - page style ▪ <code>navigation</code> - navigation models ▪ <code>resourceCatalog</code> - resource catalog ▪ <code>skin</code> - skin ▪ <code>taskFlow</code> - task flow ▪ <code>taskflowStyle</code> - task flow style ▪ <code>dataControl</code> - data control ▪ <code>device</code> - device ▪ <code>deviceGroup</code> - device group <p>You cannot export or import out-of-the-box assets, devices, or device groups.</p> <p>Note: In this release, <code>taskFlowStyle</code> replaces the asset type <code>mashupStyle</code>. The <code>mashupStyle</code> option is deprecated but continues to work in this release for backward compatibility.</p>
<i>resourceGUID</i>	<p>Optional. Unique ID (GUID) of an asset to export.</p> <p>Internal IDs are available from the <i>About</i> dialog for the asset.</p> <p>This argument is not used when <code>resourceType</code> is set to <code>device</code> or <code>deviceGroup</code>.</p>
<i>resourceName</i>	<p>Optional. Display name of an asset, device, or device group to export.</p> <p>Asset display names are available from the <i>About</i> dialog for the asset.</p> <p>Device and device group names are available from the <i>Edit</i> dialog for the device or device group.</p> <p>Note: You cannot export out-of-the-box assets, devices, or device groups.</p>
<i>spaceName</i>	<p>Optional. (WebCenter Portal only) Name of the portal containing the asset to export. Use this argument to export portal assets, that is, assets that are owned by a particular portal.</p> <p>Omit this argument if you want to export shared assets for WebCenter Portal. This argument defaults to null (shared assets are exported).</p> <p>This argument is not used when <code>resourceType</code> is set to <code>device</code> or <code>deviceGroup</code>.</p> <p>This argument is not required when exporting assets for a Portal Framework application.</p>
<i>exportContentDirectory</i>	<p>Deprecated.</p> <p>You can no longer include MDS content associated with assets in export archives. Use the standard MDS WLST command <code>exportMetadata</code> to migrate legacy MDS content, if required.</p> <p>Note: In 11.1.1.8.0 or later, Oracle recommends that you store asset-related content on your content server rather than MDS.</p>

Argument	Definition
<i>server</i>	Optional. Name of the managed server where the application is deployed. Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.23.12.3 Example

The following example exports a page template owned by a portal named `MyPortal` (in WebCenter Portal) to a local file named `myPageTemplateExport.ear`:

```
wls:/weblogic/serverConfig> exportWebCenterResource (appName='webcenter',
fileName='myPageTemplateExport.ear', resourceType='pageTemplate',
resourceGUID='gsr47d9a5ac_7398_439a_97d2_8b54ce905f7e, spaceName='MyPortal')
```

The following example exports the same page template owned by a portal named `MyPortal` but specifies the template's display name rather than the GUID:

```
wls:/weblogic/serverConfig> exportWebCenterResource (appName='webcenter',
fileName='myPageTemplateExport.ear', resourceType='pageTemplate',
resourceName='MyPageTemplate, spaceName='MyPortal')
```

The following example exports a device named `MyMobileDevice` from WebCenter Portal:

```
wls:/weblogic/serverConfig> exportWebCenterResource (appName='webcenter',
fileName='myDeviceExport.ear', resourceType='device',
resourceName='MyMobileDevice')
```

The following example exports a skin from a Portal Framework application named `myPortalApp` to a local file named `mySkinExport.ear`:

```
wls:/weblogic/serverConfig> exportWebCenterResource (appName='myPortalApp',
fileName='mySkinExport.ear', resourceType='skin',
resourceGUID='gsr47d9a5ac_7398_439a_97d2_8b54ce905f7e)
```

10.23.13 importWebCenterResource

Module: Oracle WebCenter Portal

Use with WLST: Online

10.23.13.1 Description

(WebCenter Portal and Portal Framework applications) Imports a single asset, device, or device group, from an export archive (.ear file).

Note:

- To run this command you must have at least the WebLogic Monitor role, as well as the appropriate Create/Edit/Delete permission for the type of asset, device or device group you want to import.

For more information, see "About Permissions Required to Import (or Export) Assets" in *Oracle Fusion Middleware Administering Oracle WebCenter Portal*.

- You cannot export or import out-of-the-box assets, devices, or device groups.

10.23.13.2 Syntax

```
importWebCenterResource(appName, fileName, [resourceType, spaceName, server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>fileName</i>	Name of the archive file that you want to import.
<i>resourceType</i>	Optional. Type of resource to import (an asset, device, or device group). Valid values include: <code>pageTemplate</code> , <code>contentPresenter</code> , <code>pageStyle</code> , <code>navigation</code> , <code>resourceCatalog</code> , <code>skin</code> , <code>taskFlow</code> , <code>mashupStyle</code> , <code>dataControl</code> , <code>device</code> , <code>deviceGroup</code> Where: <ul style="list-style-type: none"> ■ <code>pageTemplate</code> - page template ■ <code>contentPresenter</code> - Content presenter display template ■ <code>pageStyle</code> - page style ■ <code>navigation</code> - navigation models ■ <code>resourceCatalog</code> - resource catalog ■ <code>skin</code> - skin ■ <code>taskFlow</code> - task flow ■ <code>taskflowStyle</code> - task flow style ■ <code>dataControl</code> - data control ■ <code>device</code> - device ■ <code>deviceGroup</code> - device group If the archive (<code>.ear</code> file) contains one or more devices or device groups, then this argument is mandatory: <ul style="list-style-type: none"> ■ When <code>resourceType='device'</code>, all devices in the archive are imported. ■ When <code>resourceType='deviceGroup'</code>, all device groups in the archive and their associated devices are imported. Note: In this release, <code>taskFlowStyle</code> replaces the asset type <code>mashupStyle</code> . The <code>mashupStyle</code> option is deprecated but continues to work in this release for backward compatibility.

Argument	Definition
<i>spaceName</i>	Optional. (WebCenter Portal only) Name of the portal into which the asset is to be imported. Omit this argument if you want to import a shared asset to WebCenter Portal or to import an asset in to a Portal Framework application. This argument defaults to null (import shared asset). This argument is not used when <i>resourceType</i> is set to <i>device</i> or <i>deviceGroup</i> .
<i>overwriteContentDirectory</i>	Deprecated. You can no longer include MDS content associated with assets in export archives. Use the standard MDS WLST command <i>importMetadata</i> to migrate legacy MDS content, if required. Note: In 11.1.1.8.0 or later, Oracle recommends that you store asset-related content on your content server rather than MDS.
<i>server</i>	Optional. Name of the managed server where the application is deployed. Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.23.13.3 Example

The following example imports a page template from an archive named *myPageTemplateExport.ear* to *MyPortal* in WebCenter Portal:

```
wls:/weblogic/serverConfig> importWebCenterResource(appName='webcenter',
fileName='myPageTemplateExport.ear', spaceName='MyPortal',
resourceType='pageTemplate')
```

The following example imports a device from an archive named *myDeviceExport.ear* to WebCenter Portal:

```
wls:/weblogic/serverConfig> importWebCenterResource(appName='webcenter',
fileName='myDeviceExport.ear', resourceType='device')
```

The following example imports a skin from an archive named *mySkinExport.ear* to a Portal Framework application named *myPortalApp*:

```
wls:/weblogic/serverConfig> importWebCenterResource(appName='myPortalApp',
fileName='mySkinExport.ear', resourceType='skin')
```

10.23.14 importWebCenterTranslations

Module: Oracle WebCenter

Use with WLST: Online

10.23.14.1 Description

(WebCenter Portal and Portal Framework applications) Imports translated content (XLF files) to MDS and the WebCenter Portal repository for use in WebCenter Portal.

10.23.14.2 Syntax

```
importWebCenterTranslations(appName, server, mdsRootDir, [applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the name is always <code>webcenter</code> .
<i>server</i>	Name of the target managed server on which WebCenter Portal is deployed. For example, <code>WC_Spaces</code> .
<i>mdsRootDir</i>	MDS root directory on the file system that contains translated XLF files.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of WebCenter Portal is deployed.

10.23.14.3 Example

The following example imports translated content in the directory `/scratch/shared/newmd` to MDS and the WebCenter Portal repository:

```
wls:/weblogic/serverConfig> importWebCenterTranslations(appName='webcenter',
server='WC_Spaces', mdsRootDir='/scratch/shared/newmd')
```

10.23.15 exportWebCenterApplication

Module: Oracle WebCenter Portal

Use with WLST: Online

10.23.15.1 Description

(WebCenter Portal only) Exports an entire WebCenter Portal application to an export archive (`.ear` file) using the filename provided.

10.23.15.2 Syntax

```
exportWebCenterApplication(appName, fileName, [exportCustomizations, exportData,
server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the name is always <code>webcenter</code> .
<i>fileName</i>	Name of the export archive (<code>.ear</code> file) to which you want the export to be written.
<i>exportCustomizations</i>	Optional. Specifies whether to export global customizations and user customizations. Valid values are 1 and 0: <ul style="list-style-type: none"> ▪ 1 - Export global customizations and user customizations. ▪ 0 - Exclude customizations. On import, existing customizations on the target to system pages, task flows, assets, and so on, remain intact. This argument defaults to 1.

Argument	Definition
<i>exportData</i>	<p>Optional. Indicates whether to include data in the export archive. Valid values are 1 and 0.</p> <ul style="list-style-type: none"> ▪ 1 - All data stored in the WebCenter Portal database schema (WEBCENTER) is exported: activity streams, events, feedback, lists, links, message boards, people connections, polls, profiles, surveys, and tags. Notes data stored in the MDS repository is exported too. ▪ 0 - WebCenter Portal data is not exported. This option is useful when migrating from a test environment to a stage or production environment and where test data is no longer required. <p>This argument defaults to 0.</p>
<i>server</i>	<p>Optional. Name of the managed server where WebCenter Portal is deployed. For example, WC_Spaces.</p> <p>Required when applications with the same name are deployed to different servers and also when you have a cluster.</p>
<i>applicationVersion</i>	<p>Optional. Version number of the deployed application. Required if more than one version of WebCenter Portal is deployed.</p>

10.23.15.3 Examples

The following example exports WebCenter Portal with customizations and all possible data to a file named `myAppExport.ear`.

```
wls:/weblogic/serverConfig>exportWebCenterApplication(appName='webcenter',
fileName='myAppExport.ear', exportCustomizations=1, exportData=1)
```

The following example exports a test WebCenter Portal instance. In this case, data created during testing (such as lists, events, links, tags, and so on) is not required.

```
wls:/weblogic/serverConfig>exportWebCenterApplication(appName='webcenter',
fileName='myTestAppExport.ear', exportCustomizations=1, exportData=0)
```

10.23.16 importWebCenterApplication

Module: Oracle WebCenter Portal

Use with WLST: Online

10.23.16.1 Description

(WebCenter Portal only) Imports an entire WebCenter Portal application from an export archive file to a managed server.

After importing WebCenter Portal you must restart the managed server on which you deployed the application.

10.23.16.2 Syntax

```
importWebCenterApplication(appName, fileName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	<p>Name of the application in which to perform this operation.</p> <p>For WebCenter Portal, the name is always <code>webcenter</code>.</p>
<i>fileName</i>	<p>Name of the export archive that you want to import.</p>

Argument	Definition
<i>server</i>	Optional. Name of the managed server where WebCenter Portal is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of WebCenter Portal is deployed.

10.23.16.3 Example

The following example imports WebCenter Portal from the export archive `myAppExport.ear`.

```
wls:/weblogic/serverConfig> importWebCenterApplication(appName='webcenter',
fileName='myAppExport.ear')
```

10.23.17 exportPortletClientMetadata

Module: Oracle WebCenter Portal

Use with WLST: Online

10.23.17.1 Description

(WebCenter Portal and Portal Framework applications) Exports portlet client metadata and producer customizations and personalizations, for WebCenter Portal or a Portal Framework application. This command exports metadata for *all* the application's producers to a named export archive (`.ear` file). You cannot opt to export metadata for specific producers.

10.23.17.2 Syntax

```
exportPortletClientMetadata(appName, fileName, [exportPersonalizations, server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>fileName</i>	Name of the export archive (<code>.ear</code> file) to which you want the export to be written.
<i>exportPersonalizations</i>	Optional. Valid values are 1 (true) and 0 (false). <ul style="list-style-type: none"> ■ 1 - Personalizations for <i>all</i> producers are exported. ■ 0 - Personalizations are not exported. This argument defaults to 1.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.23.17.3 Example

The following example exports portlet client metadata and producer customizations to an export archive named `myExport.ear`. Personalizations are not exported.

```
wls:/weblogic/serverConfig> exportPortletClientMetadata (appName='myApp',
fileName='myExport.ear', exportPersonalizations=0)
```

The following example exports portlet client metadata for an application with the version number `V2.0` deployed on the server `WC_CustomPortal1`.

```
wls:/weblogic/serverConfig> exportPortletClientMetadata (appName='myApp',
fileName='myExport.ear', server='WC_CustomPortal1', applicationVersion='V2.0')
```

10.23.18 importPortletClientMetadata

Module: Oracle WebCenter Portal

Use with WLST: Online

10.23.18.1 Description

(WebCenter Portal and Portal Framework applications) Imports portlet client metadata and producer customizations and personalizations from a named export archive.

Producer personalizations are optional on export. Producer personalizations are imported if the export archive specified includes personalizations.

10.23.18.2 Syntax

```
importPortletClientMetadata(appName, fileName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>fileName</i>	Name of the export archive that you want to import.
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.23.18.3 Example

The following example imports portlet client metadata and producer customizations and personalizations from an export archive named `myExport.ear`.

```
wls:/weblogic/serverConfig> importPortletClientMetadata (appName='myApp',
fileName='myExport.ear')
```

10.23.19 showProducerImportFailures

Module: Oracle WebCenter Portal

Use with WLST: Online

10.23.19.1 Description

(WebCenter Portal and Portal Framework applications) Lists outstanding producer imports for a named application.

Producer import fails if a producer used by the application is not available when the application first starts after deployment or an import operation.

10.23.19.2 Syntax

```
showProducerImportFailures(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Name of the managed server on which the application is deployed.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.23.19.3 Example

The following example shows producer import failures for WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig> showProducerImportFailures (appName= 'webcenter')
```

10.23.20 retryAllFailedProducerImports

Module: Oracle WebCenter Portal

Use with WLST: Online

10.23.20.1 Description

(WebCenter Portal and Portal Framework applications) Imports outstanding producer metadata.

Producer import can fail if a producer used by the application is not available when the application first starts after deployment or an import operation. Use this command to import metadata for any producers for which metadata import previously failed.

10.23.20.2 Syntax

```
retryAllFailedProducerImports(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the name is always <code>webcenter</code> . For Portal Framework applications, specify the appropriate name.
<i>server</i>	Name of the managed server on which the application is deployed.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.23.20.3 Example

The following example imports missing producer metadata for WebCenter Portal (webcenter):

```
wls:/weblogic/serverConfig> retryAllFailedProducerImports (appName='webcenter')

Importing metadata from the following producers failed for application webcenter.
  Producer Description : Serialised stack trace:
  [[
    oracle.portlet.client.container.PortletHttpException: HTTP <unknown method>
    request to URL...
    ...
  Failure Id : /oracle/adf/portlet/producerImportFailures/producerImportFailure2
  Producer Id : /oracle/adf/portlet/JSR286FilePref
  Producer Name : JSR286FilePref

Tried to re-import producer metadata for application webcenter.
Attempt to re-import producer metadata succeeded.
```

Note: Errors and exceptions that occurred during a previous attempt to import producers display so you can see which failed producers the command is attempting to re-import.

10.23.21 cloneWebCenterManagedServer

Module: Oracle WebCenter Portal

Use with WLST: Online

10.23.21.1 Description

(WebCenter Portal and Portal Framework applications) Creates a new managed server with the same resources as a specified, base managed server.

10.23.21.2 Syntax

```
cloneWebCenterManagedServer (baseManagedServer, newManagedServer,
newManagedServerPort, [verbose])
```

Argument	Definition
<i>baseManagedServer</i>	Name of the base managed server.
<i>newManagedServer</i>	Name for the new, cloned managed server.
<i>newManagedServerPort</i>	Port number for the new managed server.
<i>verbose</i>	Optional. Creates the managed server in verbose mode. Valid values are 1 and 0. When set to 1, additional progress information displays during the creation process which is useful for diagnostic purposes. The default is 0.

10.23.21.3 Example

The following example creates a clone of the WC_CustomPortal managed server. The new managed server is named WC_CustomPortal2:

```
wls:/weblogic/serverConfig> cloneWebCenterManagedServer (baseManagedServer='WC_
```

```
CustomPortal', newManagedServer='WC_CustomPortal2', newManagedServerPort=1234)
```

10.23.22 exportGroupSpaces (Deprecated)

Module: Oracle WebCenter Portal

Use with WLST: Online

10.23.22.1 Description

(Deprecated from 11.1.1.8.0. Use [exportWebCenterPortals](#) instead.)

Exports one or more named portals (previously called *spaces*) to an export archive (.ear file), using the filename specified.

Space-related data*, application customizations, and security information is included in the export archive.

*Only internal space-related data stored in the Spaces database is exported. For example, data associated with tool or services such as activity streams, events, feedback, lists, links, message boards, people connections, profiles, polls, surveys, and tags.

You must take the spaces offline, even if only temporarily, to prevent data conflicts during the export process.

You must have at least the WebLogic `Monitor` role and the WebCenter Portal permission `Portals - Manage All` to run this command.

Note: You cannot use this command to export the Home space.

10.23.22.2 Syntax

```
exportGroupSpaces(appName, fileName, names, [forceOffline,server,
applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the Spaces application in which to perform this operation—always <code>webcenter</code> .
<i>fileName</i>	Name of the local file to which the export will be written.
<i>names</i>	Names of the spaces that you want to export. Separate multiple space names with a comma. For example: <code>names='sales, finance'</code> Note: Do not enter display names here. You must enter the space name that is specified in the space URL. The space name is available from the <i>About</i> dialog.
<i>forceOffline</i>	Optional. Specifies whether to take the spaces offline before starting export process. Valid values are 1 and 0. <ul style="list-style-type: none"> ■ 1 takes the spaces offline before starting the export process. ■ 0 attempts to export the spaces. If one or more spaces are currently online, an information message requests that you take the spaces offline. The default is 0.

Argument	Definition
<code>exportContentDirectory</code>	Deprecated. You can no longer include MDS content associated with assets in export archives. Use the standard MDS WLST command <code>exportMetadata</code> to migrate legacy MDS content, if required. Note: In 11.1.1.8.0 or later, Oracle recommends that you store asset-related content on your content server rather than MDS.
<code>server</code>	Optional. Name of the managed server where the Spaces application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<code>applicationVersion</code>	Optional. Version number of the deployed application. Required if more than one version of the Spaces application is deployed.

10.23.22.3 Example

The following example exports two spaces (`mySpace1` and `mySpace2`):

```
wls:/weblogic/serverConfig> exportGroupSpaces (appName='webcenter',
fileName='myExport.ear', names='mySpace1, mySpace2')
```

The following example takes `mySpace1` and `mySpace2` offline and then exports both spaces, to an archive named `myExport.ear`:

```
wls:/weblogic/serverConfig> exportGroupSpaces (appName='webcenter',
fileName='myExport.ear', names='mySpace1, mySpace2', forceOffline=1)
```

10.23.23 exportGroupSpaceTemplates (Deprecated)

Module: Oracle WebCenter Portal

Use with WLST: Online

10.23.23.1 Description

(Deprecated from 11.1.1.8.0. Use [exportWebCenterPortalTemplates](#) instead.)

Exports one or more portal templates (previously called *space templates*) to an export archive (`.ear` file), using the filename specified.

You must have at least the WebLogic Monitor role and the WebCenter Portal permission `Portal Templates - Manage All` to run this command.

10.23.23.2 Syntax

```
exportGroupSpaceTemplates(appName, fileName, names,
[exportContentDirectory, server, applicationVersion])
```

Argument	Definition
<code>appName</code>	Name of the Spaces application in which to perform this operation—always <code>webcenter</code> .
<code>fileName</code>	Name of the local file to which the export will be written.
<code>names</code>	Names of the space templates that you want to export. Separate multiple template names with a comma.

Argument	Definition
<code>exportContentDirectory</code>	Deprecated. You can no longer include MDS content associated with assets in export archives. Use the standard MDS WLST command <code>exportMetadata</code> to migrate legacy MDS content, if required. Note: In 11.1.1.8.0 or later, Oracle recommends that you store asset-related content on your content server rather than MDS.
<code>server</code>	Optional. Name of the managed server where the Spaces application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<code>applicationVersion</code>	Optional. Version number of the deployed application. Required if more than one version of the Spaces application is deployed.

10.23.23.3 Example

The following example exports two space templates (`mySpaceTemplate1` and `mySpaceTemplate2`):

```
wls:/weblogic/serverConfig> exportGroupSpaceTemplates(appName='webcenter',
fileName='myExport.ear', names='mySpaceTemplate1, mySpaceTemplate2')
```

10.23.24 importGroupSpaces (Deprecated)

Module: Oracle WebCenter Portal

Use with WLST: Online

10.23.24.1 Description

(Deprecated from 11.1.1.8.0. Use [importWebCenterPortals](#) instead.)

Imports one or more portals or portal templates (previously called *spaces* and *space templates*) from an export archive.

You must have at least the WebLogic Monitor role and either the WebCenter Portal permission `Portals - Manage All` or `Portal Templates - Manage All` to run this command.

Note: You must take existing spaces offline, even if only temporarily, to prevent data conflicts during the import process.

10.23.24.2 Syntax

```
importGroupSpaces(appName, fileName, [importCustomizations, importSecurity,
importData, parentSpace, forceOffline, server, applicationVersion])
```

Argument	Definition
<code>appName</code>	Name of the Spaces application in which to perform this operation—always <code>webcenter</code> .
<code>fileName</code>	Name of the archive file that you want to import.

Argument	Definition
<i>importCustomizations</i>	<p data-bbox="708 233 1435 285">Optional. Indicates whether to import space customizations from the export archive. Valid values are 1 and 0.</p> <ul data-bbox="708 296 1435 422" style="list-style-type: none"> <li data-bbox="708 296 1097 323">■ 1 - Import space customizations. <li data-bbox="708 333 1435 422">■ 0 - New spaces are imported without customizations (that is, default task flows are imported without any customizations and the default space settings are used). <p data-bbox="753 432 1395 485">If you are importing a space that already exists on the target, existing customizations on the target are preserved.</p> <p data-bbox="708 495 1005 522">This argument defaults to 1.</p> <p data-bbox="708 533 1341 560">Note: Portlet and page customizations are always imported.</p> <p data-bbox="708 571 1365 632">Note: If the archive contains portal templates, this argument is ignored.</p>
<i>importSecurity</i>	<p data-bbox="708 653 1435 705">Optional. Indicates whether to import space member details from the export archive. Valid values are 1 and 0.</p> <ul data-bbox="708 716 1435 894" style="list-style-type: none"> <li data-bbox="708 716 1435 768">■ 1 - Roles and permissions for the space, as well as member details and their role assignments are imported. <li data-bbox="708 779 1435 894">■ 0 - Only the roles and permissions are imported. This option is useful when migrating between stage and production environments and where member details, added during the testing phase, are no longer required. <p data-bbox="708 905 1005 932">This argument defaults to 1.</p> <p data-bbox="708 942 1365 999">Note: If the archive contains portal templates, this argument is ignored.</p>
<i>importData</i>	<p data-bbox="708 1020 1435 1073">Optional. Indicates whether to import data from the export archive. Valid values are 1 and 0.</p> <ul data-bbox="708 1083 1435 1251" style="list-style-type: none"> <li data-bbox="708 1083 1435 1157">■ 1 - Space-related data stored in the Spaces database for activity streams, events, feedback, lists, links, message boards, people connections, profiles, polls, surveys, and tags is imported. <li data-bbox="708 1167 1435 1251">■ 0 - Data is not imported. This option is useful when migrating between stage and production environments and where test data is no longer required. <p data-bbox="708 1262 1005 1289">This argument defaults to 1.</p> <p data-bbox="708 1299 1365 1356">Note: If the archive contains portal templates, this argument is ignored.</p>
<i>forceOffline</i>	<p data-bbox="708 1377 1435 1430">Optional. Takes the spaces offline before import. Valid values are 1 and 0.</p> <ul data-bbox="708 1440 1435 1535" style="list-style-type: none"> <li data-bbox="708 1440 1073 1472">■ 1 - All spaces are taken offline. <li data-bbox="708 1482 1435 1535">■ 0 - The current state of individual spaces (online or offline) is preserved. <p data-bbox="708 1545 1005 1572">This argument defaults to 0.</p>
<i>parentSpace</i>	<p data-bbox="708 1598 1435 1671">Optional. Name of the parent space under which to place spaces in the archive. If specified, imported spaces become children of the parent space.</p> <p data-bbox="708 1682 1435 1734">This argument defaults to null. When no parent is specified, archived spaces are imported as root spaces.</p> <p data-bbox="708 1745 1365 1797">Note: If the archive contains space templates, this argument is ignored.</p>

Argument	Definition
<code>overwriteContentDirectory</code>	<p>Deprecated.</p> <p>You can no longer include MDS content associated with assets in export archives. Use the standard MDS WLST command <code>exportMetadata</code> to migrate legacy MDS content, if required.</p> <p>Note: In 11.1.1.8.0 or later, Oracle recommends that you store asset-related content on your content server rather than MDS.</p> <p>Optional. Indicates whether to overwrite existing content directory files (used by portal resources) in the target with the files in the archive. Valid values are 1 and 0.</p> <ul style="list-style-type: none"> ▪ 1 Overwrites the content directory files in the target with the files in the archive ▪ 0 Only imports new files, that is, files that do not exist in the target content directory. <p>The default is 0.</p> <p>Note: The Spaces application stores portal resource content under a single 'shared' content directory (<code>oracle\webcenter\siteresources\scopedMD\shared</code>). The entire directory is imported; you cannot import content specific to selected space templates.</p>
<code>server</code>	<p>Optional. Name of the managed server where the Spaces application is deployed. For example, <code>WC_Spaces</code>.</p> <p>Required when applications with the same name are deployed to different servers and also when you have a cluster.</p>
<code>applicationVersion</code>	<p>Optional. Version number of the deployed application. Required if more than one version of the Spaces application is deployed.</p>

10.23.24.3 Example

The following example imports spaces or space templates from an archive named `myExport.ear`:

```
wls:/weblogic/serverConfig> importGroupSpaces (appName='webcenter',
fileName='myExport.ear')
```

The following example takes all existing spaces in the target in `myExport.ear` offline and then imports all the spaces in `myExport.ear` under the "Sales" space. Space customizations are imported too. Test data and security details are not imported:

```
wls:/weblogic/serverConfig> importGroupSpaces (appName='webcenter',
fileName='myExport.ear', importCustomizations=1, importSecurity=0, importData=0,
parentSpace="Sales", forceOffline=1)
```

10.24 Upgrade

Use the commands listed in [Table 10-33](#) when upgrading from a previous Oracle WebCenter Portal release.

See also, *Oracle Fusion Middleware Upgrade Guide for Oracle SOA Suite, WebCenter Portal, and ADF*.

Table 10–33 Oracle WebCenter Portal Upgrade WLST Commands

Use this command...	To...	Use with WLST...
<code>upgradeWebCenterDomain</code>	Upgrade a Oracle WebCenter Portal domain.	Offline
<code>upgradeWebCenterPermissions</code>	Upgrade WebCenter Portal permissions.	Online
<code>upgradeWebCenterApplication</code>	Upgrade WebCenter Portal or a Portal Framework application.	Online

10.24.1 upgradeWebCenterDomain

Module: Oracle WebCenter Portal

Use with WLST: Offline

10.24.1.1 Description

Upgrades a Oracle WebCenter Portal domain from 11.1.1.2.0 or 11.1.1.3.0 to 11.1.1.4.0

10.24.1.2 Syntax

```
upgradeWebCenterDomain(domainDirName, [oracleHome, upgradeCustomSpaces])
```

Argument	Definition
<code>domainDirName</code>	Full path to the domain's home directory. For example, <code>/home/Oracle/Domains/wc_domain</code> .
<code>oracleHome</code>	Optional. Path to Oracle WebCenter Portal's Oracle home directory. For example, <code>/home/Oracle/Middleware/Oracle_WC</code> .
<code>upgradeCustomSpaces</code>	Optional. Determines whether to upgrade the <code>custom.webcenter.spaces</code> shared library. Valid values are 1 (true) and 0 (false). Set to 1 if you customized the Spaces application (previous name for WebCenter Portal) and you want your customizations to be included when you upgrade. The default value is 0.

10.24.1.3 Example

The following example upgrades an Oracle WebCenter Portal domain named `base_domain`:

```
wls:/weblogic/serverConfig> upgradeWebCenterDomain(domainDirName='mw_home/user_project/domains/base_domain');
```

10.24.2 upgradeWebCenterPermissions

Module: Oracle WebCenter Portal

Use with WLST: Online

10.24.2.1 Description

Upgrades permissions for WebCenter Portal (previously known as *WebCenter Spaces*).

This command creates additional application roles and grants some additional permissions that are requirement for WebCenter Portal 11.1.1.4.0 and later.

10.24.2.2 Syntax

```
upgradeWebCenterPermissions()
```

10.24.2.3 Example

The following example upgrades permissions for WebCenter Portal:

```
wls:/weblogic/serverConfig> upgradeWebCenterPermissions();
```

10.24.3 upgradeWebCenterApplication

Module: Oracle WebCenter Portal

Use with WLST: Online

10.24.3.1 Description

Upgrades WebCenter Portal (previously known as *WebCenter Spaces*) from 11.1.1.2.0 or 11.1.1.3.0 to 11.1.1.4.0.

10.24.3.2 Syntax

```
upgradeWebCenterApplication(appName, [server, applicationVersion])
```

Argument	Definition
<i>appName</i>	Name of the application in which to perform this operation. For WebCenter Portal, the application name is always <code>webcenter</code> .
<i>server</i>	Optional. Name of the managed server where the application is deployed. For example, <code>WC_Spaces</code> . Required when applications with the same name are deployed to different servers and also when you have a cluster.
<i>applicationVersion</i>	Optional. Version number of the deployed application. Required if more than one version of the application is deployed.

10.24.3.3 Example

The following example upgrades WebCenter Portal (`webcenter`):

```
wls:/weblogic/serverConfig> upgradeWebCenterApplication(appName='webcenter');
```

Application Development Framework (ADF) Custom WLST Commands

This chapter provides detailed descriptions of custom WLST commands for ADF, including command syntax, arguments and command examples.

The following sections describe the WLST custom commands and variables in detail. Topics include:

- [Section 11.1, "Overview of WLST Command Categories"](#)
- [Section 11.2, "ADF-Specific WLST Commands"](#)

Note: To use these ADF custom WLST commands, you must invoke the WLST script from the Oracle Common home. See "Using Custom WLST Commands" in the *Oracle Fusion Middleware Administrator's Guide*.

11.1 Overview of WLST Command Categories

Use the ADF-based URL Connections WLST commands to navigate the hierarchy of configuration or runtime beans and control the prompt display. Use the `getADFMArchiveConfig` command to manage the `ADFMArchiveConfig` object.

11.2 ADF-Specific WLST Commands

Use the commands in [Table 11-1](#) for ADF-specific functions.

Table 11-1 Browse Commands for WLST Configuration

Use this command...	To...	Use with WLST...
<code>adf_createFileUrlConnection</code>	Create a new ADF File connection.	Online or Offline
<code>adf_createHttpUrlConnection</code>	Create a new ADF URL connection.	Online or Offline
<code>adf_setURLConnectionAttributes</code>	Set or edit the attributes of a newly created or existing ADF connection.	Online or Offline
<code>adf_listUrlConnection</code>	List a new URL connection.	Online or Offline
<code>getADFMArchiveConfig</code>	Return a handle to the <code>ADFMArchiveConfig</code> object for the specified archive.	Online or Offline

Table 11–1 (Cont.) Browse Commands for WLST Configuration

Use this command...	To...	Use with WLST...
exportJarVersions	Export CSV format of jars versions from current ORACLE_HOME at a specified location.	Offline
exportApplicationJarVersions	Export CSV format of runtime jars versions of a specified application at a specified location.	Online
exportApplicationSelectedJarVersions	Export CSV format of jars versions of selected jars at a specified location in coordination with the <code>Versions.xml</code> file.	Online
createWebServiceConnection	Create a Web service connection for an ADF application.	Online
listWebServiceConnection	List Web service connections for an ADF application.	Online
deleteWebServiceConnection	Delete a Web service connection for an ADF application.	Online

11.2.1 `adf_createFileURLConnection`

Use with WLST: Online or Offline

11.2.1.1 Description

Use this command to create a new connection based on the `oracle.adf.model.connection.url.FileURLConnection` connection class.

11.2.1.2 Syntax

```
adf_createFileURLConnection(appName, name, URL)
```

Argument	Definition
<i>appName</i>	Application name for which the connection that will be created.
<i>name</i>	The name of the new connection.
<i>URL</i>	The URL associated with this connection.

11.2.1.3 Example

```
adf_createFileURLConnection('myapp', 'tempDir', '/scratch/tmp')
```

11.2.2 `adf_createHttpURLConnection`

Use with WLST: Online or Offline

11.2.2.1 Description

Use this command to create a new connection based on the `oracle.adf.model.connection.url.HttpURLConnection` connection type class.

11.2.2.2 Syntax

```
adf.createHttpURLConnection (appName, name, [URL], [authenticationType], [realm], [user], [password])
```


Argument	Definition
<i>appName</i>	Application name for which the connection is to be created.
<i>name</i>	The name of the new connection.
<i>url</i>	(Optional) The URL associated with this connection.
<i>authenticationType</i>	(Optional) The default is basic.
<i>realm</i>	(Optional) If this connection deals with authentication, then this should be set. The default is basic.
<i>user</i>	(Optional)
<i>password</i>	(Optional)

11.2.2.3 Example

```
adf_createURLConnection('myapp', 'cnn', 'http://www.cnn.com')
```

11.2.3 adf_setURLConnectionAttributes

Use with WLST: Online or Offline

11.2.3.1 Description

Use this command to set or edit the attributes of a newly created or existing ADF connection.

11.2.3.2 Syntax

```
adf_setURLConnectionAttributes(appname, connectionname, attributes)
```

Argument	Definition
<i>appname</i>	Application name for which the connection that will be created.
<i>connectionname</i>	The name of the new connection.
<i>attributes</i>	The array containing attributes to set in key/value pairs.

11.2.3.3 Example

```
adf_setURLConnectionAttributes
('myapp', 'cnn', 'ChallengeAuthenticationType:digest',
'AuthenticationRealm:XMLRealm')
```

11.2.4 adf_listURLConnection

Use with WLST: Online or Offline

11.2.4.1 Description

Use this command to list the connections of the application.

11.2.4.2 Syntax

```
adf_listURLConnection(appname)
```

Argument	Definition
<i>appname</i>	Application name

11.2.4.3 Example

```
adf_listURLConnection ('myapp')
```

11.2.5 getADFMArchiveConfig

Use with WLST: Online or Offline.

11.2.5.1 Description

Returns a handle to the `ADFMArchiveConfig` object for the specified archive. The returned `ADFMArchiveConfig` object's methods can be used to change application configuration in an archive.

The `ADFMArchiveConfig` object provides the following methods:

- `setDatabaseJboSQLBuilder ([value])`—Sets the Database `jbo.SQLBuilder` attribute.
- `getDatabaseJboSQLBuilder ()`—Returns the current value of the `jbo.SQLBuilder` attribute.
- `setDatabaseJboSQLBuilderClass ([value])`—Sets the Database `jbo.SQLBuilderClass` attribute. Value is the full name of the custom builder class.
- `getDatabaseJboSQLBuilderClass ()`—Returns the current value of the `jbo.SQLBuilderClass` attribute.
- `setDefaultRowLimit ([value])`—Sets the defaults `rowLimit` attribute. Value is a long specifying the row limit (Default -1).
- `getDefaultRowLimit ()`—Returns the current value of the `rowLimit` attribute.
- `save ([toLocation])`—If you specify the `toLocation`, then the changes will be stored in the target archive file and the original file will remain unchanged. Otherwise, the changes will be saved in the original file itself.

11.2.5.2 Syntax

```
archiveConfigObject = ADFMAdmin.getADFMArchiveConfig(fromLocation)
```

Argument	Definition
<i>fromLocation</i>	The name of the ear file, including its complete path.

The syntax for `setDatabaseJboSQLBuilder ([value])` is:

```
archiveConfigObject.setDatabaseJboSQLBuilder([value])
```

Argument	Definition
<i>value</i>	The value of the <code>jbo.SQLBuilder</code> attribute. Valid values are: 'Oracle' (Default), 'OLite', 'DB2', 'SQL92', 'SQLServer', or 'Custom'. If 'Custom' is specified, then the <code>jbo.SQLBuilderClass</code> attribute should also be set.

The syntax for `getDatabaseJboSQLBuilder()` is:

```
archiveConfigObject.getDatabaseJboSQLBuilder()
```

The syntax for `setDatabaseJboSQLBuilderClass([value])` is:

```
archiveConfigObject.setDatabaseJboSQLBuilderClass([value])
```

Argument	Definition
<i>value</i>	The value of the <code>jbo.SQLBuilderClass</code> attribute.

The syntax for `getDatabaseJboSQLBuilderClass()` is:

```
archiveConfigObject.getDatabaseJboSQLBuilderClass()
```

The syntax for `setDefaultRowLimit([value])` is:

```
archiveConfigObject.setDefaultRowLimit([value])
```

Argument	Definition
<i>value</i>	The value of the <code>rowLimit</code> attribute.

The syntax for `getDefaultRowLimit()` is:

```
archiveConfigObject.getDefaultRowLimit([value])
```

The syntax for `save([toLocation])` is:

```
archiveConfigObject.save([toLocation])
```

Argument	Definition
<i>toLocation</i>	The file name along with the absolute path to store the changes.

11.2.5.3 Example

In the following example, the `jbo.SQLBuilder` attribute is set to 'DB2'.

```
wls:/offline> archive =
                ADFMAdmin.getADFMArchiveConfig(fromLocation='/tmp/testArchive.ear')
wls:/offline> archive.setDatabaseJboSQLBuilder(value='DB2')
wls:/offline> archive.save()
```

In the following example, the `jbo.SQLBuilder` attribute is removed so that application default is used.

```
wls:/offline> archive =
                ADFMAdmin.getADFMArchiveConfig(fromLocation='/tmp/testArchive.ear')
wls:/offline> archive.setDatabaseJboSQLBuilder()
wls:/offline> archive.save(toLocation='/tmp/targetArchive.ear')
```

In the following example, the `jbo.SQLBuilder` attribute is set to 'Custom', and the `jbo.SQLBuilderClass` attribute is set to the class 'com.example.CustomBuilder'.

```
wls:/offline> archive =
                ADFMAdmin.getADFMArchiveConfig(fromLocation='/tmp/testArchive.ear')
wls:/offline> archive.setDatabaseJboSQLBuilder('Custom')
wls:/offline> archive.setDatabaseJboSQLBuilderClass('com.example.CustomBuilder')
wls:/offline> archive.save(toLocation='/tmp/targetArchive.ear')
```

In the following example, the `rowLimit` attribute is set to 100.

```
wls:/offline> archive = getADFMArchiveConfig(fromLocation='/tmp/testArchive.ear')
wls:/offline> archive.setDefaultRowLimit(100)
wls:/offline> archive.save(toLocation='/tmp/targetArchive.ear')
```

11.2.6 exportJarVersions

Use with WLST: Offline.

11.2.6.1 Description

Use to export CSV format of jars versions from current `ORACLE_HOME` at a specified location. Exported jars versions information can be opened in Oracle OpenOffice or MS Excel.

11.2.6.2 Syntax

```
exportJarVersions(path)
```

Argument	Definition
path	Location to extract jars versions.

11.2.6.3 Example

This example shows how jars versions are exported to `/tmp/export-MyApp-Versions.csv`. R/W privileges for the CSV file need to be verified.

```
wls:/offline>exportJarVersions('/tmp/export-MyApp-Versions.csv')
```

11.2.7 exportApplicationJarVersions

Use with WLST: Online.

11.2.7.1 Description

Used to export CSV format of runtime jars versions of a specified application at a specified location.

11.2.7.2 Syntax

```
exportApplicationJarVersions(applicationName, path)
```

Argument	Definition
applicationName	Application name to export jars versions
path	Location to export jars versions.

11.2.7.3 Example

This example shows how `MyApp` runtime jars versions are exported to `/tmp/export-MyApp-Versions.csv`. R/W privileges for the CSV file need to be verified.

```
wls:/DefaultDomain/serverConfig>exportApplicationJarVersions('MyApp',
'/tmp/export-MyApp-Versions.csv')
```

11.2.8 exportApplicationSelectedJarVersions

Use with WLST: Online.

11.2.8.1 Description

Used to export CSV format of jars versions of selected jars at a specified location.

11.2.8.2 Syntax

```
exportApplicationSelectedJarVersions(applicationName, path, jarsLocation)
```

Argument	Definition
applicationName	Application name to export jars versions.
path	Location to extract jars versions.
jarsLocation	Optional list of selected jars. If not specified, default jars runtime version list from %WLSDOMAIN%/config/fmwconfig/Versions.xml will be exported. If the selectedJars property in Versions.xml is empty, version information of adfm.jar, adf-richclient-impl-11.jar, adf-controller.jar, adf-pageflow-impl.jar, adf-share-support.jar and mdsrt.jar will be exported.

11.2.8.3 Example

This example shows how jars versions are exported to /tmp/export-MyApp-Versions.csv using the selectedJars property of the Versions.xml file. In this case, since the jarsLocation parameter is not specified, the libraries listed in the selectedJars property of the Versions.xml file will be exported. R/W privileges for the CSV file need to be verified.

```
wls:/offline>exportApplicationSelectedJarVersions('MyApp',
'/tmp/export-MyApp-Versions.csv')
```

```
Versions.xml
<Diagnostics xmlns="xmlns.oracle.com/adf/diagnostics">
  <Versions xmlns="xmlns.oracle.com/adf/diagnostics/versions"
    exportVersionsOnApplicationStartup="true"
    selectedJars="$ORACLE_HOME$/modules/oracle.adf.model_11.1.1/adfm.jar;
$ORACLE_HOME$/modules/oracle.adf.view_11.1.1/adf-richclient-impl-11.jar;
$ORACLE_HOME$/modules/oracle.adf.controller_11.1.1/adf-controller.jar;
$ORACLE_HOME$/modules/oracle.adf.pageflow_11.1.1/adf-pageflow-impl.jar;
$ORACLE_HOME$/modules/oracle.adf.share_11.1.1/adf-share-support.jar;
$ORACLE_HOME$/modules/oracle.mds_11.1.1/mdsrt.jar" />
</Diagnostics>
```

This example shows how jars versions are exported to /tmp/export-MyApp-Versions.csv using the jarsLocation parameter. In this case, the libraries passed explicitly in the jarsLocation parameter will be exported. R/W privileges for the CSV file need to be verified.

```
wls:/offline>exportApplicationSelectedJarVersions('MyApp',
```

```
'/tmp/export-MyApp-Versions.csv',
'$ORACLE_HOME$/modules/oracle.adf.model_11.1.1/adfm.jar;$ORACLE_
HOME$/modules/oracle.adf.view_11.1.1/adf-richclient-impl-11.jar')
```

11.2.9 createWebServiceConnection

Use with WLST: Online.

11.2.9.1 Description

Used to create a Web Service connection for an ADF application.

Returns a set of service name and port names in the format {serviceName: List of portName}.

For example: {'PolicyReferenceEchoBeanService':
array(java.lang.String, ['PolicyReferenceEchoBeanPort'])}

11.2.9.2 Syntax

```
createWebServiceConnection(appName, wsConnName, wsdlUrlStr, readerProps)
```

Argument	Definition
appName	Name of the ADF application for which you want to create a Web service connection.
wsConnName	Name of the new Web service connection.
wsdlUrlStr	Name of the service WSDL URL string.
readerProps	The optional WSDL reader properties. For example: '["wsdl.reader.proxy.host=proxy.my.com", "wsdl.reader.proxy.port=80"]'

11.2.9.3 Example

This example shows how to create a Web service connection for an ADF application myapp, with a Web service connection mywsconn, and a WSDL URL string of http://myserver/myservice?WSDL.

```
createWebServiceConnection('myapp', 'mywsconn', 'http://myserver/myservice?WSDL')
```

11.2.10 listWebServiceConnection

Use with WLST: Online.

11.2.10.1 Description

Used to list the Web service connections associated with an ADF application.

11.2.10.2 Syntax

```
listWebServiceConnection(appName)
```

Argument	Definition
appName	Name of the ADF application for which you want to list its Web service connections.

11.2.10.3 Example

This example shows how to list the Web service connections for the application myapp.

```
listWebServiceConnection('myapp')
```

11.2.11 deleteWebServiceConnection

Use with WLST: Online.

11.2.11.1 Description

Used to delete a Web service connection associated with an ADF application.

11.2.11.2 Syntax

```
deleteWebServiceConnection(appName, wsConnName)
```

Argument	Definition
appName	Name of the ADF application for which you want to delete a Web service connection.
wsConnName	Name of the Web service connection you want to delete.

11.2.11.3 Example

This example shows how to delete the Web service connection mywsconn from the application myapp.

```
deleteWebServiceConnection('myapp', 'mywsconn')
```

Portal Custom WLST Commands

This chapter provides detailed descriptions of custom WLST commands for Oracle Portal, including command syntax, arguments and command examples.

Portal custom WLST commands are extensions to the WLST commands and are specific to Oracle Portal. [Table 12–1](#) lists the Portal custom WLST command categories.

For additional information about administration and configuration of Portal, see the *Oracle Fusion Middleware Administrator's Guide for Oracle Portal*.

Note: To use these commands, you must invoke WLST from the Oracle home in which the component has been installed. See "Using Custom WLST Commands" in the *Oracle Fusion Middleware Administrator's Guide*.

Table 12–1 Portal WLST Command Categories

Command category	Description
Database Access Descriptor Commands	Create, edit, or delete a general DAD or Portal DAD.
Configuration Commands	The Configuration commands: <ul style="list-style-type: none"> ▪ List and update the WebCache configuration and Oracle Internet Directory data ▪ Configure the Portal cache, Portal Page Engine, and Portal mid-tier ▪ List Portal site configuration.

12.1 Database Access Descriptor Commands

A Database Access Descriptor (DAD) is a set of values that specify how an application connects to an Oracle database to fulfill an HTTP request. The information in the DAD includes the user name (which also specifies the schema and the privileges), password, connect string, and globalization support language of the database.

There are two types of DADs: general DAD and portal DAD. An Oracle Portal middle tier uses a Portal DAD to access the Oracle Metadata Repository. For information about general DADs, refer to the *Oracle Fusion Middleware Administrator's Guide for Oracle HTTP Server*.

Use the Database Access Descriptor commands listed in [Table 12–2](#) to create, edit, or delete a Portal DAD from the WLST command-line scripting interface. Based on your actions, the `portal_dads.conf` file is updated.

Table 12–2 Database Access Descriptor Commands for Portal WLST Configuration

Use this command...	To...	Use with WLST...
<code>listDads</code>	List the parameters used by the Database Access Descriptors for configuration.	Online
<code>createPortalDad</code>	Create a Portal Database Access Descriptor.	Online
<code>updatePortalDad</code>	Update the attributes of a Portal Database Access Descriptor.	Online
<code>deletePortalDad</code>	Delete a Portal Database Access Descriptor.	Online

12.1.1 listDads

Command Category: Database Access Descriptor Commands

Use with WLST: Online

12.1.1.1 Description

Lists the parameters specified in all the Database Access Descriptors (both general DADs and Portal DADs).

12.1.1.2 Syntax

```
listDads ()
```

12.1.1.3 Example

The following example lists the various DADs in the domain.

```
listDads()
-----
/pls/portall
Schema: hluser
Connect String: foo.oracle.com:1521:orcl
NLS Language: "AMERICAN_AMERICA.AL32UTF8"
```

12.1.2 createPortalDad

Command Category: Database Access Descriptor Commands

Use with WLST: Online

12.1.2.1 Description

Creates a Portal Database Access Descriptor.

12.1.2.2 Syntax

```
createPortalDad (name, schema, password, [connect_string], nls_language)
```

Argument	Definition
<i>name</i>	Name of the Database Access Descriptor.
<i>schema</i>	The Portal database account user name.
<i>password</i>	The Portal database account password.

Argument	Definition
<i>connect_string</i>	Optional. The connection string used to connect to a remote database. Connect string may be host name: port number: connect string. The connect string format may be ServiceNameFormat (host:port:database_service_name), SIDFormat (host:port:database_sid), or TNSFormat (TNS alias or the whole TNS entry).
<i>nls_language</i>	The globalization support language of the Portal database that is represented by this DAD. This setting overrides the NLS_LANG environment variable for a database session and defines some important globalization support properties of the response, including the response character set. Make sure that this language setting matches the NLS_LANG of the back-end database.

12.1.2.3 Example

The following example creates the portal1 Portal DAD based on the specified arguments.

```
createPortalDad(name='portal1', schema='schema', password='welcome1', connect_string='foo.oracle.com:1521:orcl', nls_language='AMERICAN_AMERICA.AL32UTF8')
```

12.1.3 updatePortalDad

Command Category: Database Access Descriptor Commands

Use with WLST: Online

12.1.3.1 Description

Updates the attributes of the Portal Database Access Descriptor.

12.1.3.2 Syntax

```
updatePortalDad (name, [schema], [password], [connect_string], [nls_language])
```

Argument	Definition
<i>name</i>	Name of the Database Access Descriptor. This name cannot be changed during update.
<i>schema</i>	Optional. The Portal database account user name.
<i>password</i>	Optional. The Portal database account password.
<i>connect_string</i>	Optional. The connection string used to connect to a remote database. Connect string may be host name: port number: connect string. The connect string format may be ServiceNameFormat (host:port:database_service_name), SIDFormat (host:port:database_sid), or TNSFormat (TNS alias or the whole TNS entry).
<i>nls_language</i>	Optional. The globalization support language of the Portal database that is represented by this DAD. This setting overrides the NLS_LANG environment variable for a database session and defines some important Globalization Support properties of the response, including the response character set. Make sure that this language setting matches the NLS_LANG of the back-end database.

12.1.3.3 Example

The following example updates the portal1 Portal DAD based on the specified arguments.

```
updatePortalDad(name='portal1',schema='user1',password='welcome2',connect_
string='foo.oracle.com:1521:orcl',nls_language='AMERICAN_AMERICA.AL32UTF8')
```

12.1.4 deletePortalDad

Command Category: Database Access Descriptor Commands

Use with WLST: Online

12.1.4.1 Description

Deletes a Portal Database Access Descriptor.

12.1.4.2 Syntax

```
deletePortalDad(name)
```

Argument	Definition
<i>name</i>	Name of the Portal Database Access Descriptor.

12.1.4.3 Example

The following example deletes the portal1 Portal DAD entry from the portal_dads.conf file.

```
deletePortalDad(name='portal1')
```

12.2 Configuration Commands

Use the Configuration commands in [Table 12–3](#) to view and configure Portal cache, WebCache, Oracle Internet Directory data and so on.

Table 12–3 Configuration Commands for the Portal WLST Configuration

Use this command...	To...	Use with WLST...
configurePortalCache	Update the attributes of the Portal cache.	Online
configurePortalPageEngine	Update the attributes of the Portal mid-tier.	Online
listPortalWebcacheConfigAttributes	List the attributes of WebCache configuration.	Online
listPortalSiteConfigAttributes	List the attributes of Portal site configuration.	Online
listPortalOIDConfigAttributes	List the attributes of Oracle Internet Directory configuration.	Online
setPortalWebcacheConfig	Update the attributes of the WebCache configuration.	Online
setPortalOIDConfig	Update the attributes of the Oracle Internet Directory configuration.	Online
setPortalMidtierConfig	Update the attributes of the Portal mid-tier configuration.	Online

12.2.1 configurePortalCache

Command Category: Configuration Commands

Use with WLST: Online

12.2.1.1 Description

Portal cache is a file system-based cache for Oracle Portal pages and portlets. Portal cache supports validation-based caching and expiry-based caching. Portal cache consists of both Portal content cache and session cache.

This command updates the attributes of the Portal cache. These configuration details are maintained in the <Middleware Home>/user_projects/domains/<DOMAIN_HOME>/servers/WLS_PORTAL/stage/portal/portal/configuration/portal_cache.conf file.

12.2.1.2 Syntax

```
configurePortalCache([enable], [directory], [total_size], [max_size],
[cleanup_time], [max_age])
```

Argument	Definition
<i>enable</i>	Optional. Enables (On) or disables (Off) portal content and session caching.
<i>directory</i>	Optional. The directory where cached content is stored. Make sure that this directory exists and has read-write access.
<i>total_size</i>	Optional. The total amount of disk space (in megabytes) that the Portal cache may use. The maximum value allowed is 4 GB.
<i>max_size</i>	Optional. The maximum size (in bytes) for all cached files. The maximum value allowed is 4 GB. Any dynamically generated content that exceeds this limit is not cached.
<i>cleanup_time</i>	Optional. The time at which to start the cleanup of the cache storage. Use the [Sunday-Saturday, Everyday, Everymonth][hh:mm] format to define the exact day and time in which cleanup should occur.
<i>max_age</i>	Optional. Maximum age of a single cached document. This setting ensures the cache system does not contain any old content. Old cache files are removed to make space for new cache files. The default is 30 days.

12.2.1.3 Example

The following example configures the Portal cache.

```
configurePortalCache(enable=true,directory='/scratch/user/installs/Inst_1
/cache/PortalComponent/portal',total_size=10101010,max_size=12300033,cleanup_
time='Everyday 11:00',max_age=20)
```

12.2.2 configurePortalPageEngine

Command Category: Configuration Commands

Use with WLST: Online

12.2.2.1 Description

The Oracle Fusion Middleware Portal architecture is designed around a three-tier architecture that allows any browser to connect to it. This flexible architecture allows each component (browser, Oracle HTTP Server listener, Oracle Database 11g, and Oracle Portal) to be upgraded individually as required.

A part of the Oracle Portal middle tier, the Parallel Page Engine (PPE) is a servlet that runs under Oracle Containers for Java EE and services page requests. The PPE reads page metadata, calls providers for portlet content, accepts provider responses, and assembles the requested page in the specified page layout.

This command updates the properties in the `appConfig.xml` file, the configuration file that is used by the Portal mid-tier repository servlet. This configuration file is located in the `$MWHOME/user_projects/domains/AllClassicDomain/servers/WLS_PORTAL/stage/portal/portal/configuration/` directory.

12.2.2.2 Syntax

```
configurePortalPageEngine([encrypt_key], [resource_url_key], [use_port], [use_scheme], [x509certfile])
```

Argument	Definition
<i>encrypt_key</i>	Optional. Specifies the HMCA key to obscure the headers used for caching using WebCache. This allows for a more secure cache key, and makes retrieving a cached object by unwanted requests more difficult.
<i>resource_url_key</i>	Optional. This key, used by the PPE servlet, calculates checksums for URLs that are requested by WSRP and JPDK resource proxying. For WSRP resource proxying to work, the key must be set to an alpha-numeric value of 10 characters or more. In addition, for JPDK proxying, a JNDI environment variable, also called <code>resourceUriKey</code> , must be set for the provider.
<i>use_port</i>	Optional. Overrides the port used when the PPE makes requests to the portal. The default, if not specified, is to always use the page request port. Note that if you set <code>useScheme</code> , you must also set the <code>usePort</code> argument. This may be used for other reasons, but mostly it is used when SSL is running between the browser and the PPE but not between the PPE and Portal. In this case, the non-SSL port for loop back requests will be different from the SSL port used by the browser.
<i>use_scheme</i>	Optional. Overrides the scheme (HTTP or HTTPS) used when the PPE makes requests to the Portal. The default, if not specified, is to always use the page request scheme. Note that if you set <code>useScheme</code> , you must also set the <code>usePort</code> argument.
<i>x509certfile</i>	Optional. Specifies a file containing a list of certificates to be implicitly trusted by HTTPClient. These certificates are added as trust points to all connections made by HTTPClient using SSL.

12.2.2.3 Example

The following example updates the Portal page engine based on the specified arguments.

```
configurePortalPageEngine(encrypt_key='encryption key', resource_url_key='foo.oracle.com', use_port=9999, use_scheme='page_engine_1', x509certfile='file')
```

12.2.3 listPortalWebcacheConfigAttributes

Command Category: Configuration Commands

Use with WLST: Online

12.2.3.1 Description

Lists the attributes of WebCache configuration used by the Portal repository.

12.2.3.2 Syntax

```
listPortalWebcacheConfigAttributes ([dad_name])
```

Argument	Definition
<i>dad_name</i>	Optional. Name of the Database Access Descriptor. Default DAD name is 'portal'.

12.2.3.3 Example

The following example lists the WebCache configuration used by the Portal repository. The WebCache host name to which the invalidation messages are sent, the invalidation user name, password and the invalidation port to which the invalidation messages are sent are listed.

```
listPortalWebcacheConfigAttributes(dad_name='portal1')
listPortalWebcacheConfigAttributes('portal1')
-----
WebCacheConfig
-----
WebCache Host: foo.oracle.com
WebCache Invalidation Password: invalidator
WebCache Invalidation Port: 6523
WebCache Invalidation User: invalidator
```

12.2.4 listPortalSiteConfigAttributes

Command Category: Configuration Commands

Use with WLST: Online

12.2.4.1 Description

Lists the attributes of the Portal site configuration.

12.2.4.2 Syntax

```
listPortalSiteConfigAttributes ([dad_name])
```

Argument	Definition
<i>dad_name</i>	Optional. Name of the Database Access Descriptor. Default DAD name is 'portal'.

12.2.4.3 Example

The following example lists the Portal site configuration. Site protocol can be true or false. HTTP is the protocol when site protocol is false and HTTPS is the protocol when the site protocol is true. The site host name and port number are also listed.

```
listPortalSiteConfigAttributes(dad_name='portal1')
```

```
listPortalSiteConfigAttributes('portal1')
```

```
-----  
SiteConfig  
-----  
Site Protocol: false  
Site Host: foo.oracle.com  
Site Port: 8090
```

12.2.5 listPortalOIDConfigAttributes

Command Category: Configuration Commands

Use with WLST: Online

12.2.5.1 Description

Lists the attributes of the Oracle Internet Directory configuration.

12.2.5.2 Syntax

```
listPortalOIDConfigAttributes ([dad_name])
```

Argument	Definition
<i>dad_name</i>	Optional. Name of the Database Access Descriptor. Default DAD name is 'portal'.

12.2.5.3 Example

The following example lists the Oracle Internet Directory data, which includes the Oracle Internet Directory host name and port number.

```
listPortalOIDConfigAttributes(dad_name='portal1')  
listPortalOIDConfigAttributes('portal1')
```

```
-----  
OidConfig  
-----  
OID Port: 13060  
OID Host: foo.oracle.com
```

12.2.6 setPortalWebcacheConfig

Command Category: Configuration Commands

Use with WLST: Online

12.2.6.1 Description

WebCache offers caching, page assembly, and compression features. Oracle WebCache accelerates the delivery of both static and dynamic Web content, and provides load balancing and failover features for Oracle Fusion Middleware.

This command updates the WebCache configuration.

12.2.6.2 Syntax

```
setPortalWebcacheConfig([dad_name], [host], [inv_port], [inv_user],  
[inv_passwd])
```


Argument	Definition
<i>dad_name</i>	Optional. Name of the Database Access Descriptor. Default DAD name is 'portal'.
<i>host</i>	Optional. The name of the WebCache host to which invalidation messages are sent.
<i>inv_port</i>	Optional. The WebCache port number to which invalidation messages are sent.
<i>inv_user</i>	Optional. The user name used for sending the invalidation messages.
<i>inv_password</i>	Optional. WebCache invalidation password.

12.2.6.3 Example

The following example updates the WebCache configuration based on the specified values.

```
setPortalWebcacheConfig(dad_name='portal1',host='foo.oracle.com',
inv_port= '6523',inv_user= 'invalidator',inv_passwd=' invalidator')
```

12.2.7 setPortalOIDConfig

Command Category: Configuration Commands

Use with WLST: Online

12.2.7.1 Description

Updates the attributes of the Oracle Internet Directory configuration.

12.2.7.2 Syntax

```
setPortalOIDConfig ([dad_name], [host], [port], [protocol], [admin_user],
[admin_passwd])
```

Argument	Definition
<i>dad_name</i>	Optional. Name of the Database Access Descriptor. Default DAD name is 'portal'.
<i>host</i>	Optional. Oracle Internet Directory host name.
<i>port</i>	Optional. Oracle Internet Directory port number.
<i>protocol</i>	Optional. Oracle Internet Directory protocol.
<i>admin_user</i>	Optional. Oracle Internet Directory administrator's name.
<i>admin_passwd</i>	Optional. Oracle Internet Directory administrator's password.

12.2.7.3 Example

The following example updates the OID configuration based on the specified values.

```
setPortalOIDConfig(dad_name='portal1',
host='foo.oracle.com',port='13060',protocol=false,
admin_user='cn=orcladmin',admin_passwd='oracle1')
```

12.2.8 setPortalMidtierConfig

Command Category: Configuration Commands

Use with WLST: Online

12.2.8.1 Description

Updates the Portal repository with the latest Portal mid-tier configuration.

12.2.8.2 Syntax

```
setPortalMidtierConfig([dad_name], [ohs_host], [ohs_port], [ohs_protocol],
[webcache_host], [webcache_inv_user], [webcache_inv_port],
[webcache_inv_passwd])
```

Argument	Definition
<i>dad_name</i>	Optional. Name of the Database Access Descriptor. Default DAD name is 'portal'.
<i>ohs_host</i>	Optional. Oracle HTTP Server host name.
<i>ohs_port</i>	Optional. Oracle HTTP Server port number.
<i>ohs_protocol</i>	Optional. Oracle HTTP Server protocol.
<i>webcache_host</i>	Optional. The name of the WebCache host to which invalidation messages are sent.
<i>webcache_inv_user</i>	Optional. The WebCache user name used for sending the invalidation messages.
<i>webcache_inv_port</i>	Optional. The WebCache port number to which invalidation messages are sent.
<i>webcache_inv_passwd</i>	Optional. WebCache invalidation password.

12.2.8.3 Example

The following example updates the Portal mid-tier configuration based on the specified values.

```
setPortalMidtierConfig(dad_name='portal1',ohs_host='foo.oracle.com',
ohs_port='8090',ohs_protocol=false,webcache_host='foo.oracle.com',
webcache_inv_user= 'invalidator',webcache_inv_port='6523',
webcache_inv_passwd='invalidator')
```

Java Required Files Custom WLST Commands

Oracle JRF consists of those components not included in the WebLogic Server installation that provide common functionality for Oracle business applications and application frameworks. This chapter provides detailed descriptions of custom WLST commands for Java Required Files (JRF), including command syntax, arguments and command examples.

Oracle JRF consists of a number of independently developed libraries and applications that are deployed into a common location. The following components are considered part of Java Required Files: Oracle Application Development Framework, Oracle Fusion Middleware Audit Framework, Dynamic Monitoring Service, Fabric Common, HTTP Client, Infrastructure Security, Java Object Cache, JMX Framework, JPS, logging, MDS, OJSP.Next, Oracle Web Services, Oracle Web Services Manager, Oracle TopLink, UCP, XDK.

13.1 Java Required Files Commands

Use the commands in [Table 13–1](#) to configure a Managed Server or cluster with Java Required Files (JRF) applications and services or to copy the applications and services from one Managed Server or cluster and apply them to another Managed Server or cluster.

In the Use with WLST column, online means the command can only be used when connected to a running server. Offline means the command can only be used when not connected to a running server. Online or offline means the command can be used in both situations.

Note: To use these JRF custom WLST commands, you must invoke the WLST script from the Oracle Common home. See "Using Custom WLST Commands" in the *Oracle Fusion Middleware Administrator's Guide*.

Table 13–1 JRF Commands

Use this command...	To...	Use with WLST...
applyJRF	Configures a Managed Server or cluster with Java Required Files applications and services.	Online or Offline

Table 13–1 (Cont.) JRF Commands

Use this command...	To...	Use with WLST...
cloneDeployments	Copies the applications and services from Managed Server or cluster and applies them to another Managed Server or cluster.	Online or Offline

13.1.1 applyJRF

Use with WLST: Online or Offline

13.1.1.1 Description

Configures a Managed Server or cluster with Java Required Files (JRF). Managed Servers that are added by product templates during the template extension process do not need to be explicitly configured with JRF using this command.

Use the `applyJRF` command when additional Managed Servers or clusters are added to a domain after it is initially extended with a product template. The `applyJRF` command is required any time you add a Managed Server to a JRF-only domain, or if you add a Managed Server that has been configured for JRF to a domain that contains other Oracle products.

13.1.1.2 Syntax

```
applyJRF(target, [domainDir], [shouldUpdateDomain])
```

Argument	Definition
<i>target</i>	The name of the Managed Server or cluster to be configured with JRF applications and services. A value of an asterisk (*) for the target indicates that all clusters and standalone Managed Servers should be configured with JRF.
<i>domainDir</i>	The absolute path of the WebLogic Server domain.
<i>shouldUpdateDomain</i>	An optional boolean flag that controls how domain updates are carried out. When you set it to true (the default), the function implicitly invokes the following offline commands: <code>readDomain()</code> and <code>updateDomain()</code> , or the online commands: <code>edit()</code> , <code>startEdit()</code> , <code>save()</code> , and <code>activate()</code> . When you set it to false, you must call WLST commands to update the domain.

13.1.1.3 Example

The following example configures the Managed Server `server1` with JRF:

```
wls:/offline> applyJRF('server1', '/my_path/user_templates/domains/my_domain')
```

13.1.2 cloneDeployments

Use with WLST: Online or Offline

13.1.2.1 Description

Replicates all deployments targeted to a particular Managed Server or cluster on a second Managed Server or cluster. This command is provided as a convenience to configure a new Managed Server or cluster so that it has the same deployments as a pre-existing Managed Server or cluster.

The `cloneDeployments` command does not create new Managed Servers, and it does not copy properties other than deployment information to the target Managed Server.

13.1.2.2 Syntax

```
cloneDeployments(domain, source, target, [shouldUpdateDomain])
```

Argument	Definition
<i>domain</i>	The absolute path of the WebLogic Server domain. Ignored if the domain has been read, or if connected in online mode.
<i>source</i>	The name of the Managed Server or cluster from which you want to clone deployments. This must be the name of a valid Managed Server or cluster.
<i>target</i>	The target Managed Server or cluster that will receive the source server's applications and services. The target Managed Server must already exist.
<i>shouldUpdateDomain</i>	An optional boolean flag that controls how domain updates are carried out. When you set it to true (the default), the function implicitly invokes the following offline commands: <code>readDomain()</code> and <code>updateDomain()</code> , or online commands: <code>edit()</code> , <code>startEdit()</code> , <code>save()</code> , and <code>activate()</code> . When you set it to false, you must call WLST commands to update the domain.

13.1.2.3 Example

The following example replicates the deployments from `sourceServer` to `destinationServer`:

```
wls:/offline> cloneDeployments( '/my_path/user_templates/domains/my_domain',
  'sourceServer','destinationServer', 'false')
```

Web Services Custom WLST Commands

This chapter provides detailed descriptions of custom WLST commands for Web services, including command syntax, arguments and command examples.

The following sections describe the WebLogic Scripting Tool (WLST) commands for Oracle Infrastructure Web services (which includes SOA composites, ADF Business Components, and WebCenter services) and Java EE Web services. You can use these commands to manage Web services from the command line.

Topics in this chapter include:

- [Section 14.1, "Overview of Web Services WLST Commands"](#)
- [Section 14.2, "Web Service and Client Management Commands"](#)
- [Section 14.3, "Policy Management Commands"](#)
- [Section 14.4, "Policy Set Management Commands"](#)
- [Section 14.5, "Oracle WSM Repository Management Commands"](#)
- [Section 14.6, "Deployment Descriptor Migration Commands"](#)
- [Section 14.7, "Token Issuer Trust Configuration Commands"](#)
- [Section 14.8, "Diagnostic Commands"](#)

For additional details about using these WLST commands for Web services, see the *Oracle Fusion Middleware Security and Administrator's Guide for Web Services*.

Notes: To use the Web Services custom WLST commands, you must invoke WLST from the Oracle Common home directory. See "Using Custom WLST Commands" in the *Oracle Fusion Middleware Administrator's Guide*.

To display the help for the Web service and client management, policy management, and deployment descriptor migration commands, connect to a running instance of the server and enter `help('WebServices')`.

To display the help for the policy set management, Oracle WSM repository management, token issuer trust configuration, and diagnostic commands, connect to a running instance of the server and enter `help('wsmManage')`.

14.1 Overview of Web Services WLST Commands

You can use the Web services WLST commands, in online mode, to:

- Perform Web service configuration and Oracle WSM policy management tasks.
- Manage the Oracle WSM Repository
- Migrate post-deployment policy changes persisted in proprietary deployment descriptor (PDD) files for ADF Business Components and WebCenter services and propagate policy changes to all server instances in a domain.
- Check the status of OWSM components.
- View and define trusted issuers and DN lists for SAML signing certificates.

The Web services WLST commands manage deployed, active, and running Web services applications. They can be executed everywhere in WLST online mode, for example:

```
wls:/domain/serverConfig
wls:/domain/domainRuntime
```

The Web services WLST commands perform many of the same functions that you can complete using Fusion Middleware Control. When using the WLST commands to manage a Web service of an ADF or WebCenter application, you can apply the change only to a Web service deployed in an application on a specific server. If the application is deployed in a cluster or multi-server environment, you need to make the same change to each of the servers to which the application is deployed. Additionally, when you set or change an attached policy in ADF and WebCenter Web service and client applications, you must restart the application for the changes to take effect.

In contrast, if you are using the WLST commands to manage a SOA composite, you only need to issue the command once, and the change is propagated to all the server instances in the composite. When you set or change an attached policy in a SOA composite, you do not need to restart it. The SOA fabric runtime engine internally implements all of the policy management changes.

14.1.1 Specifying Application, Composite, and Service Names

The Web service WLST commands configure a Web service for a specific application. Therefore, the application path name has to uniquely identify the application and the server instance to which it is deployed.

Specifying a Web Service Application Name

To specify a Web service application in a WLST command, use the following format:

```
[/domain/server/]application[#version_number]
```

Parameters shown in brackets [] are optional. The following examples show the sample format for a Web service application name:

```
/soainfra/AdminServer/HelloWorld#1_0
/soainfra/server1/HelloWorld#1_0
```

If there is only one deployed instance of an application in a domain, you may omit the `domain/server` parameter, as shown in the following example:

```
HelloWorld#1_0
```

In all other instances, the `domain/server` parameter is required. If it is not specified and WLST finds more than one deployment of the same application on different servers in the domain, you are prompted to specify the domain and the server names.

Web Service client applications are deployed directly to WebLogic Server server instances. Each client application is managed separately. For example, if the application `myapp` is deployed to both the `AdminServer` and `server1` instances in the domain `mydomain`, then you need to issue configuration commands to each of the servers using the appropriate application path name:

```
/mydomain/AdminServer/myapp#1_0
/mydomain/server1/myapp#1_0
```

Specifying a SOA Composite Name

When there are multiple SOA partition folders in a domain, you must specify the partition name and the composite name using the following format:

```
partition/composite[version]
```

The following example shows the sample format for a SOA composite application name:

```
default/myComposite[1.0]
```

If there is a single SOA server (non-clustered) and only one SOA partition folder in a domain, you may omit the `partition` parameter, as shown in the following example:

```
myComposite[1.0]
```

Specifying a Service Name

When there are multiple versions (namespaces) of a Web service name for Web Service and Web Service clients, you must specify the namespace and the service name using the following format:

```
{http://namespace/}serviceName
```

Note the following:

- For Web service and client management commands, and policy management commands, you do not need to enter the namespace if there is only one service name qualified. If there are multiple versions of the service and you do not specify the namespace with the service name, an exception is thrown.
- The namespace (`{http://namespace/}`) should not be included for a SOA composite.
- For policy set management commands, both the namespace and service name are required for Web Service and Web Service Client (`ws-service` and `ws-client`) resource types.

For more information, see "Determining the Namespace for a Web Service" in *Oracle Fusion Middleware Security and Administrator's Guide for Web Services*.

14.1.2 Web Services WLST Command Categories

Web services WLST commands are divided into the categories described in [Table 14–1](#).

Table 14–1 Web Services WLST Command Categories

Command Category	Definition
Section 14.2, "Web Service and Client Management Commands"	View and manage Web services for the service and client.

Table 14–1 (Cont.) Web Services WLST Command Categories

Command Category	Definition
Section 14.3, "Policy Management Commands"	View and manage directly-attached policies for the service and client.
Section 14.4, "Policy Set Management Commands"	View and manage globally-available policy sets within repository sessions.
Section 14.5, "Oracle WSM Repository Management Commands"	Manage the Oracle WSM repository with new predefined policies provided in the latest installation of the software, as well as import and export documents into and from the repository.
Section 14.6, "Deployment Descriptor Migration Commands"	Migrate proprietary deployment descriptors for scaling post-deployment policy configuration changes in a cluster or propagating the changes to all server instances of the application in the domain.
Section 14–7, " Web Services Token Issuer Trust Commands"	View and define trusted issuers, trusted DN lists, and token attribute rule filters for SAML signing certificates.
Section 14.8, "Diagnostic Commands"	Check the status of the WSM components that are required for proper functioning of the product.

14.2 Web Service and Client Management Commands

Use the WLST commands listed in [Table 14–2](#) to view and manage Web services for deployed, active, and running Web service applications.

Table 14–2 Web Service and Client Management WLST Commands

Use this command...	To...	Use with WLST...
listWebServices	List the Web service information for an application, composite, or domain.	Online
listWebServicePorts	List the Web service ports for a Web service application or SOA composite.	Online
listWebServiceConfiguration	List Web services and port configuration for an application or SOA composite.	Online
setWebServiceConfiguration	Set or change the Web service port configuration for a Web service application or SOA composite.	Online
listWebServiceClients	List Web service client information for an application, SOA composite, or domain.	Online
listWebServiceClientPorts	List Web service client ports information for an application or SOA composite.	Online
listWebServiceClientStubProperties	List Web service client port stub properties for an application or SOA composite.	Online
setWebServiceClientStubProperty	Set, change, or delete a single stub property of a Web service client port for an application or SOA composite.	Online
setWebServiceClientStubProperties	Configure the set of stub properties of a Web service client port for an application or SOA composite.	Online

14.2.1 listWebServices

Command Category: Web Service and Client Management

Use with WLST: Online

14.2.1.1 Description

Lists the Web service information for an application, SOA composite, or domain. If you don't specify a Web service application or a SOA composite, the command lists all services in all applications and composites for every server instance in the domain.

You can specify the amount of information to be displayed in the output using the `detail` argument. When specified, the output provides endpoint (port) and policy details for all applications and composites in the domain, the secure status of the endpoints, any configuration overrides and constraints, and if the endpoints have a valid configuration. A subject is considered secure if the policies attached to it (either directly or globally) enforce authentication, authorization, or message protection behaviors. Because you can specify the priority of a global or directly attached policy (using the `reference.priority` configuration override), the `effective` field indicates if the directly attached policies are in effect for the endpoint.

Note that to simplify endpoint management, all directly attached policies are shown in the output regardless of whether they are in effect. In contrast, only globally attached policies that are in effect for the endpoint are displayed. For more information, see "How the Effective Set of Policies is Calculated" in *Oracle Fusion Middleware Security and Administrator's Guide for Web Services*.

The output is listed by each application deployed as shown in the following example:

```
/domain/server/application#version_number:
  moduleName=helloModule, moduleType=web,
  serviceName={http://namespace/}service
/soainfra/AdminServer/soa-infra:
  compositeName=default/HelloWorld[1.0], moduleType=soa, serviceName=service
```

Notes: The `listWebServices` command output does not include details on SOA components, including policy attachments.

For applications assembled prior to PS5, the namespace is not displayed with the `serviceName` in the output.

14.2.1.2 Syntax

```
listWebServices (application,composite,[detail])
```

Argument	Definition
<code>application</code>	Name and path of the application for which you want to list the Web services. For example, <code>/domain/server/application#version_number</code> If specified, all Web services in the application are listed.
<code>composite</code>	Name of the SOA composite for which you want to list the Web services. For example, <code>default/HelloWorld[1.0]</code> If specified, all Web services in the composite are listed.

Argument	Definition
<i>detail</i>	Optional. Specifies whether to list port and policy details for the Web service. Valid values are: <ul style="list-style-type: none"> ▪ <code>true</code>—Output includes details about the service, the port, and the policies. ▪ <code>false</code>—Output lists only the services. The default is <code>false</code>.

14.2.1.3 Examples

The following example for an Oracle Infrastructure Web service lists all the Web services in all applications and composites in the domain. Sample output is shown in this example.

```
wls:/soainfra/serverConfig> listWebServices()
/soainfra/AdminServer/soa-infra :
    compositeName=default/HelloWorld[1.0], moduleType=soa, serviceName=service
    compositeName=default/Project1[1.0], moduleType=soa,
serviceName=bpelprocess1_client_ep

/soainfra/AdminServer/HelloWorld#1_0 :
    moduleName=j2wbasicPolicy, moduleType=web, serviceName=WssUsernameService
```

The following example for an Oracle Infrastructure Web service sets the `detail` argument to `true`. Sample output is shown in this example. Note that the directly attached policy is not in effect for the endpoint `TestPort` in the application `jaxws-sut`.

```
wls:/jrfServer_domain/serverConfig> listWebServices(detail='true')

/jrfServer_domain/jrfServer_admin/jaxws-sut-no-policy :
    moduleName=jaxws-service, moduleType=web,
serviceName={http://namespace/}TestService
    enableTestPage: true
    enableWSDL: true

    TestPort
http://host.example.com:9315/jaxws-service/TestService
    enable: true
    enableREST: false
    enableSOAP: true
    maxRequestSize: -1
    loggingLevel: NULL
    wsat.flowOption: NEVER
    wsat.version: DEFAULT
    Constraint: No Constraint
    (global) security : oracle/wss_saml_or_username_token_
service_policy, enabled=true

/policysets/global/all-domains-default-web-service-policies : Domain("**")
    reference.priority=1
    Constraint: HTTPHeader('VIRTUAL_HOST_TYPE','external')
    (global) security : oracle/wss10_message_protection_
service_policy, enabled=true
    /policysets/global/domainExternal : Domain("**")
    Attached policy or policies are valid; endpoint is secure.

/jrfServer_domain/jrfServer_admin/jaxws-sut :
    moduleName=jaxws-sut-service, moduleType=web,
serviceName={http://namespace/}TestService
```

```

    enableTestPage: true
    enableWSDL: true

    TestPort
http://host.example.com:9315/jaxws-sut-service/TestService
    enable: true
    enableREST: false
    enableSOAP: true
    maxRequestSize: -1
    loggingLevel: NULL
    wsat.flowOption: NEVER
    wsat.version: DEFAULT
    management : oracle/log_policy, enabled=true
    security : oracle/wss_username_token_service_policy , enabled=true
, effective=false
    Constraint: No Constraint
                (global) security : oracle/wss_saml_or_username_token_
service_policy, enabled=true

/policysets/global/all-domains-default-web-service-policies : Domain("**")
                reference.priority=1
    Constraint: HTTPHeader('VIRTUAL_HOST_TYPE', 'external')
                (global) security : oracle/wss10_message_protection_
service_policy, enabled=true

                /policysets/global/domainExternal : Domain("**")
Attached policy or policies are valid; endpoint is secure.

```

The following example for a Java EE Web service sets the `detail` argument to `true`. Sample output is shown in this example. The output lists all the Web services in all applications and composites in the domain.

```

/wls-domain/AdminServer/hellows :
    moduleName=hellows#1!HelloWSService, moduleType=wls,
serviceName=HelloWSService
    HelloWSPort
    No policies attached; endpoint is not secure.

```

14.2.2 listWebServicePorts

Command Category: Web Service and Client Management

Use with WLST: Online

14.2.2.1 Description

List the Web service port names and the endpoint URLs for a Web service application or SOA composite.

The output will display the port name and endpoint URL of the Web service port. For example:

```
JRFWssUsernamePort      http://localhost:7001/j2wbasicPolicy/WssUsername
```

14.2.2.2 Syntax

```
listWebServicePorts (application, moduleOrCompName, moduleType, serviceName)
```

Argument	Definition
<i>application</i>	Name and path of the application for which you want to list the Web services port information. For example, <code>/domain/server/application#version_number</code> To list the port information for an application, this argument is required.
<i>moduleOrCompName</i>	Name of the Web module or SOA composite (for example <code>HelloWorld[1.0]</code>) for which you want to list the Web services port information. To list the port information for a SOA composite, the composite name is required (for example <code>default/HelloWorld[1.0]</code>), and the <code>moduleType</code> argument must be set to <code>soa</code> .
<i>moduleType</i>	Module type. Valid options are: <ul style="list-style-type: none"> ▪ <code>soa</code>—SOA composite. ▪ <code>web</code>—Oracle Infrastructure Web Services packaged as a Web module (including an EJB). ▪ <code>wls</code>—Java EE Web services.
<i>serviceName</i>	Name of the Web service in the application or SOA composite for which you want to list the port information. For example, <code>{http://namespace/}serviceName</code> . Note that the namespace (<code>{http://namespace/}</code>) should not be included for a SOA composite.

14.2.2.3 Example

The following example lists the Web service ports and endpoint URLs for the `j2wbasicPolicy` service in the `soainfra/AdminServer/HelloWorld#1_0` application. Note that the `WssUsernameService` module name is specified, and the `moduleType` is set to `web`.

```
wls:/soainfra/serverConfig> listWebServicePorts
( '/soainfra/AdminServer/HelloWorld#1_0',
  'WssUsernameService', 'web', '{http://namespace/}j2wbasicPolicy' )

JRFWssUsernamePort      http://localhost:7001/j2wbasicPolicy/WssUsername
```

The following example lists the Web service ports and endpoint URLs for the Java EE Web service `helloWorldJaxws` in the `wls-domain/AdminServer/helloWorldJaxws` application. Note that the `moduleType` is set to `wls`.

```
wls:/wls-domain/serverConfig> listWebServicePorts
( '/wls-domain/AdminServer/helloWorldJaxws', 'helloWorldJaxws#1!helloWorldJaxws',
  'wls', 'helloWorldJaxws' )

helloWorldJaxwsSoapHttpPort
```

14.2.3 listWebServiceConfiguration

Notes: This command applies to Oracle Infrastructure Web services only.

This command is deprecated and will be removed in a future release.

Command Category: Web Service and Client Management

Use with WLST: Online

14.2.3.1 Description

List the Web service port configuration for a Web service application or SOA composite.

The output will display the configuration information for the Web service port. For example:

```
enableREST: false
maxRequestSize: -1
```

14.2.3.2 Syntax

```
listWebServiceConfiguration(application,moduleOrCompName,moduleType,serviceName,
[subjectName])
```

Argument	Definition
<i>application</i>	Name and path of the application for which you want to list the Web services port configuration. For example, <code>/domain/server/application#version_number</code> To list the port configuration for a Web service application, this argument is required.
<i>moduleOrCompName</i>	Name of the Web module or SOA composite (for example <code>HelloWorld[1.0]</code>) for which you want to list the Web services port configuration. To list the port configuration for a SOA composite, the composite name is required (for example <code>default/HelloWorld[1.0]</code>), and the <code>moduleType</code> argument must be set to <code>soa</code> .
<i>moduleType</i>	Module type. Valid options are: <ul style="list-style-type: none"> ■ <code>soa</code>—SOA composite. ■ <code>web</code>—Oracle Infrastructure Web Services packaged as a Web module (including an EJB).
<i>serviceName</i>	Name of the Web service in the application or SOA composite for which you want to list the port configuration. For example, <code>{http://namespace/}serviceName</code> . Note that the namespace (<code>{http://namespace/}</code>) should not be included for a SOA composite.
<i>subjectName</i>	Optional. Policy subject, port, or operation for which you want to list configuration information.

14.2.3.3 Example

The following example lists the Web service and port configuration information for the application `HelloWorld#1_0` for the server `soa1` in the domain `soainfra`. In this example, the Web module name is `j2wbasicPolicy`, the service name is `WssUsernameService`, and the subject is a port named `JRFWssUsernamePort`.

```
wls:/wls-domain/serverConfig>listWebServiceConfiguration
('/soainfra/soa1/HelloWorld#1_0','j2wbasicPolicy','web',
'{http://namespace/}WssUsernameService','JRFWssUsernamePort')
```

14.2.4 setWebServiceConfiguration

Note: This command applies to Oracle Infrastructure Web services only.

This command is deprecated and will be removed in a future release.

Command Category: Web Service and Client Management

Use with WLST: Online

14.2.4.1 Description

Set or change the Web service port configuration for a Web service application or SOA composite.

Additional information about using this command is provided in "Configuring the Web Service Endpoint" in *Oracle Fusion Middleware Security and Administrator's Guide for Web Services*.

14.2.4.2 Syntax

```
setWebServiceConfiguration(application,moduleOrCompName,moduleType,serviceName,
subjectName,itemProperties)
```

Argument	Definition
<i>application</i>	Name and path of the application for which you want to set or change the Web services port configuration. For example, <code>/domain/server/application#version_number</code> To set or change the port configuration for a Web service application, this argument is required.
<i>moduleOrCompName</i>	Name of the Web module or SOA composite (for example <code>HelloWorld[1.0]</code>) for which you want to set or change the Web services port configuration. To set or change the port configuration for a SOA composite, the composite name is required (for example <code>default/HelloWorld[1.0]</code>), and the <code>moduleType</code> argument must be set to <code>soa</code> .
<i>moduleType</i>	Module type. Valid options are: <ul style="list-style-type: none"> ■ <code>soa</code>—SOA composite. ■ <code>web</code>—Oracle Infrastructure Web Services packaged as a Web module (including an EJB).
<i>serviceName</i>	Name of the Web service in the application or SOA composite for which you want to set or change the port configuration. For example, <code>{http://namespace/}serviceName</code> . Note that the namespace (<code>{http://namespace/}</code>) should not be included for a SOA composite.
<i>subjectName</i>	Policy subject, port or operation name for which you want to set or change the configuration information.

Argument	Definition
<i>itemProperties</i>	<p>Configurable properties that you can set or change. Specify the properties using the following format:</p> <pre>("name", "value")</pre> <p>Valid port configuration name and value pairs are as follows:</p> <ul style="list-style-type: none"> ■ <code>enable</code>—true or false. Default is true. ■ <code>enableTestPage</code>—true or false. Default is true. ■ <code>enableWSDL</code>—true or false. Default is true. ■ <code>enableREST</code>—true or false. Default is false. ■ <code>maxRequestSize</code>—long integer, -1 for values not set. The default is -1. ■ <code>loggingLevel</code>—NULL, FINEST . . . SEVERE (java.util.logging.Level). The default is NULL. ■ <code>wsat.flowOption</code>—Atomic transaction flow option. Valid values are: NEVER—Do not export transaction coordination context. (This is the default.), SUPPORTS—Export transaction coordination context if transaction is available, MANDATORY—Export transaction coordination context. An exception is thrown if there is no active transaction. This property is valid for SOA services only. ■ <code>wsat.version</code>—Atomic transaction version. Valid values are: WSAT10, WSAT11, WSAT12, and DEFAULT. This property is valid for SOA services only. <p>For additional information about the atomic transaction properties, see "Configuring Web Services Atomic Transactions" in <i>Oracle Fusion Middleware Security and Administrator's Guide for Web Services</i>.</p> <p>Note: If any configuration item contains an unrecognized property name or invalid value, this set command is rejected and an error message is displayed.</p>

14.2.4.3 Example

The following example enables the port `JRFWssUsernamePort` for the service `WssUsernameService` in the Web module `j2wbasicPolicy`. The service is in the application `HelloWorld#1_0` for the server `soa1` in the domain `soainfra`.

```
wls:/wls-domain/serverConfig>setWebServiceConfiguration
('/soainfra/soa1/HelloWorld#1_0','j2wbasicPolicy','web',
'{http://namespace/WssUsernameService','JRFWssUsernamePort', [{"enable", "true"}]})
```

14.2.5 listWebServiceClients

Command Category: Web Service and Client Management

Use with WLST: Online

14.2.5.1 Description

List Web service clients information for an application, SOA composite, or domain. If neither an application nor a composite is specified, the command lists information about all Web service clients in all applications and composites for every server instance in the domain.

You can specify the amount of information to be displayed in the output using the `detail` argument. When specified, the output provides endpoint (port) and policy details for clients in the domain, the secure status of the endpoints, any configuration

overrides and constraints, and if the endpoints have a valid configuration. A subject is considered secure if the policies attached to it (either directly or globally) enforce authentication, authorization, or message protection behaviors. Because you can specify the priority of a global or directly attached policy (using the `reference.priority` configuration override), the `effective` field indicates if the directly attached policies are in effect for the endpoint.

Note that to simplify endpoint management, all directly attached policies are shown in the output regardless of whether they are in effect. In contrast, only globally attached policies that are in effect for the endpoint are displayed. For more information, see "How the Effective Set of Policies is Calculated" in *Oracle Fusion Middleware Security and Administrator's Guide for Web Services*.

The output is listed by each application deployed as shown in the following examples:

This example shows the output of an *unsecured* endpoint:

```
/soa_domain/soa_server1/soa-infra :
    compositeName=default/Basic_SOA_Client[1.0], moduleType=soa,
serviceRefName=Service1
    Basic_soa_service_pt
serviceWSDLURI=http://host.example.com:38001/soa-infra/services/default/Basic_SOA_
service/Basic_soa_service.wsdl
    oracle.webservices.contentTransferEncoding=base64
    oracle.webservices.charsetEncoding=UTF-8
    oracle.webservices.operationStyleProperty=document
    wsat.flowOption=WSDLDriven
    oracle.webservices.soapVersion=soap1.1
    oracle.webservices.chunkSize=4096
    oracle.webservices.session.maintain=false
    oracle.webservices.preemptiveBasicAuth=false

oracle.webservices.encodingStyleProperty=http://schemas.xmlsoap.org/soap/encoding/
    oracle.webservices.donotChunk=true
    No attached policies found; endpoint is not secure.
```

This example shows the output for *secured* endpoints:

```
/soa_domain/soa_server1/AsynchronizedBC_asyncbc :
    moduleName=Asynchronized-AsynchronizedBC-context-root, moduleType=web,
serviceRefName=callback
    owsm.ga.server.serviceinterface.AppModule_asyncServiceImpl/_
oracleAsyncResponseClient
    Constraint: No Constraint
    (global) security : oracle/wss_username_token_client_policy,
enabled=true
    /policysets/global/web_callback_add_1 : Module("**")
    Attached policy or policies are valid; endpoint is secure.

/soa_domain/soa_server1/ADF_DC_4 :
    moduleName=wsdl, moduleType=wsconn, serviceRefName=TestService
    TestPort
serviceWSDLURI=http://host.example.com:12345/jaxws-sut-service/TestService?wsdl
    security : oracle/wss_username_token_client_policy, enabled=true,
effective=false
    Constraint: No Constraint
    (global) security : oracle/wss11_username_token_with_message_
protection_client_policy, enabled=true
    /policysets/global/PolicySet-Testport : port('TestPort')
    reference.priority=1
```

Attached policy or policies are valid; endpoint is secure.

```
/soa_domain/AdminServer/adf_dc_to_bc :
  moduleName=ADF_BC, moduleType=wsconn, serviceRefName=AppModuleService
  AppModuleServiceSoapHttpPort
serviceWSDLURI=http://host.example.com:12345/ADF_BC-ADF_
BC-context-root/AppModuleService?wsdl
  Constraint: No Constraint
  (global) security : oracle/wss11_username_token_with_message_
protection_client_policy, enabled=true
  /policysets/global/web_reference_add_1 : Domain("soa_
domain")
```

Attached policy or policies are valid; endpoint is secure.

14.2.5.2 Syntax

```
listWebServiceClients(application, composite, [detail])
```

Argument	Definition
<i>application</i>	Name and path of the application for which you want to list the Web service clients. For example, <code>/domain/server/application#version_number</code> If specified, all Web services clients in the application are listed.
<i>composite</i>	Name of the SOA composite for which you want to list the Web service clients. For example, <code>default/HelloWorld[1.0]</code> If specified, all Web service clients in the composite are listed.
<i>detail</i>	Optional. Specifies whether to list port and policy details for the Web service clients. Valid values are: <ul style="list-style-type: none"> ■ <code>true</code>—Output includes details about the clients, ports, policies, and whether the endpoint is secure or not. ■ <code>false</code>—Output lists only the clients. The default is false.

14.2.5.3 Examples

The following example lists information for all Web service clients in the domain.

```
wls:/wls-domain/serverConfig>listWebServiceClients()
```

The following example lists the Web service clients for the application `jwsclient_1#1.10` for the server `soa1` in the domain `soainfra`.

```
wls:/wls-domain/serverConfig>listWebServiceClients('soainfra/soa1/jwsclient_1#1.10')
```

The following example lists the Web service clients for the SOA composite `default/HelloWorld[1.0]`.

```
wls:/wls-domain/serverConfig>listWebServiceClients(None, 'default/HelloWorld[1.0]')
```

The following example lists details for all of the Web service clients in the domain.

```
wls:/wls-domain/serverConfig>listWebServiceClients(None, None, true)
```

14.2.6 listWebServiceClientPorts

Command Category: Web Service and Client Management

Use with WLST: Online

14.2.6.1 Description

List the Web service port names and the endpoint URLs for Web service clients in an application or SOA composite.

The output will display the name of the Web service client/reference port. For example:

```
AppModuleServiceSoapHttpPort
```

14.2.6.2 Syntax

```
listWebServiceClientPorts(application,moduleOrCompName,moduleType,serviceRefName)
```

Argument	Definition
<i>application</i>	Name and path of the application for which you want to list the Web services port information. For example, <code>/domain/server/application#version_number</code> To list the client port information for an application, this argument is required.
<i>moduleOrCompName</i>	Name of the Web module or SOA composite (for example <code>HelloWorld[1.0]</code>) for which you want to list the Web service client port information. To list the client port information for a SOA composite, the composite name is required (for example <code>default/HelloWorld[1.0]</code>), and the <code>moduleType</code> argument must be set to <code>soa</code> .
<i>moduleType</i>	Module type. Valid options are: <ul style="list-style-type: none"> ▪ <code>soa</code>—SOA composite. ▪ <code>web</code>—Oracle Infrastructure Web Services packaged as a Web module (including an EJB). ▪ <code>wls</code>—Java EE Web services. ▪ <code>wscconn</code>—Use with a connection-based Web service client such as an ADF DC Web service client, ADF JAX-WS Indirection Proxy, or WebCenter client.
<i>serviceRefName</i>	Service reference name of the application or SOA composite for which you want to list the Web service client port information. When the client is an asynchronous Web service callback client, the <code>serviceRefName</code> argument must be set to <code>callback</code> .

14.2.6.3 Examples

The following example lists the client ports for the `WssUsernameClient` Web module in the `/soainfra/soa1/jwsclient_1#1.1.0` application. Note that the `moduleType` is set to `wscconn`, and the `serviceRefName` is set to `WssUsernameClient`.

```
wls:/soainfra/serverConfig> listWebServiceClientPorts
('/soainfra/soa1/jwsclient_1#1.1.0','WssUsernameClient','wscconn',
'WssUsernameClient')
```

The following example lists the client ports in the `default/HelloWorld[1.0]` SOA composite. Note that the `moduleType` is set to `soa`, and the `serviceRefName` is set to `client`.

```
wls:/soainfra/serverConfig> listWebServiceClientPorts (None,
'default/HelloWorld[1.0]', 'soa', 'client')
```

14.2.7 listWebServiceClientStubProperties

Note: This command applies to Oracle Infrastructure Web service clients only.

Command Category: Web Service and Client Management

Use with WLST: Online

14.2.7.1 Description

List Web service client port stub properties for an application or SOA composite.

14.2.7.2 Syntax

```
listWebServiceClientStubProperties(application, moduleOrCompName, moduleType,
serviceRefName, portInfoName)
```

Argument	Definition
<i>application</i>	Name and path of the application for which you want to list the Web services client port stub properties. For example, <code>/domain/server/application#version_number</code> To list the client port stub properties information for an application, this argument is required.
<i>moduleOrCompName</i>	Name of the Web module or SOA composite (for example <code>HelloWorld[1.0]</code>) for which you want to list the Web services client port stub properties. To list the client port stub properties information for a SOA composite, the composite name is required (for example <code>default/HelloWorld[1.0]</code>), and the <code>moduleType</code> argument must be set to <code>soa</code> .
<i>moduleType</i>	Module type. Valid options are: <ul style="list-style-type: none"> ▪ <code>soa</code>—SOA composite. ▪ <code>web</code>—Oracle Infrastructure Web Services packaged as a Web module (including an EJB). ▪ <code>wconn</code>—Use with a connection-based Web service client such as an ADF DC Web service client, ADF JAX-WS Indirection Proxy, or WebCenter client.
<i>serviceRefName</i>	Service reference name of the application or SOA composite for which you want to list the Web service client port stub properties.
<i>portInfoName</i>	The name of the client port for which you want to list the stub properties.

14.2.7.3 Example

The following example lists the client port stub properties for the JRFWssUsernamePort port of the WssUsernameClient Web module in the /soainfra/soa1/jwsclient_1#1.1.0 application. Note that the moduleType is set to wsconn, and the serviceRefName is set to WssUsernameClient.

```
wls:/soainfra/serverConfig>listWebServiceClientStubProperties
('/soainfra/soa1/jwsclient_1#1.1.0','WssUsernameClient','wsconn',
'WssUsernameClient','JRFWssUsernamePort')
```

14.2.8 setWebServiceClientStubProperty

Note: This command applies to Oracle Infrastructure Web service clients only.

Command Category: Web Service and Client Management

Use with WLST: Online

14.2.8.1 Description

Set, change, or delete a single stub property of a Web service client port for an application or SOA composite.

14.2.8.2 Syntax

```
setWebServiceClientStubProperty(application, moduleOrCompName, moduleType,
serviceRefName, portInfoName, propName, [propValue])
```

Argument	Definition
<i>application</i>	Name and path of the application for which you want to set the Web services client port stub property. For example, /domain/server/application#version_number To set a client port stub property for an application, this argument is required.
<i>moduleOrCompName</i>	Name of the Web module or SOA composite (for example HelloWorld[1.0]) for which you want to set the Web services client port stub property. To set a client port stub property for a SOA composite, the composite name is required (for example default/HelloWorld[1.0]), and the moduleType argument must be set to soa.
<i>moduleType</i>	Module type. Valid options are: <ul style="list-style-type: none"> ▪ soa—SOA composite. ▪ web—Oracle Infrastructure Web Services packaged as a Web module (including an EJB). ▪ wsconn—Use with a connection-based Web service client such as an ADF DC Web service client, ADF JAX-WS Indirection Proxy, or WebCenter client.
<i>serviceRefName</i>	Service reference name of the application or SOA composite for which you want to set the Web service client port stub property.
<i>portInfoName</i>	The name of the client port for which you want to set the stub property.

Argument	Definition
<i>propName</i>	Stub property name that you want to set, change, or delete. For example, 'keystore.recipient.alias'.
<i>propValue</i>	Optional. The stub property value, for example 'orakey'. To remove the property, specify a blank " " value.

14.2.8.3 Example

The following example sets the client port stub property `keystore.recipient.alias` to the value `oracle` for the client port `JRFWssUsernamePort`. The port is a client port of the `WssUsernameClient` Web module in the `/soainfra/soa1/jwsclient_1#1.1.0` application. Note that the `moduleType` is set to `wsconn`, and the `serviceRefName` is set to `WssUsernameClient`.

```
wls:/soainfra/serverConfig>setWebServiceClientStubProperty
('/soainfra/soa1/jwsclient_1#1.1.0','WssUsernameClient','wsconn',
'WssUsernameClient','JRFWssUsernamePort','keystore.recipient.alias','oracle')
```

14.2.9 setWebServiceClientStubProperties

Note: This command applies to Oracle Infrastructure Web service clients only.

Command Category: Web Service and Client Management

Use with WLST: Online

14.2.9.1 Description

Configure the set of stub properties of a Web service client port for an application or SOA composite.

This command configures or resets all of the stub properties for the Oracle WSM client security policy attached to the client. Each property that you list in the command is set to the value you specify. If a property that was previously set is not explicitly specified in this command, it is reset to the default for the property. If no default exists, the property is removed.

14.2.9.2 Syntax

```
setWebServiceClientStubProperties(application, moduleOrCompName, moduleType,
serviceRefName, portInfoName, properties)
```

Argument	Definition
<i>application</i>	Name and path of the application for which you want to reset the Web services client port stub properties. For example, <code>/domain/server/application#version_number</code> To configure or reset the client port stub properties for an application, this argument is required.

Argument	Definition
<i>moduleOrCompName</i>	<p>Name of the Web module or SOA composite (for example <code>HelloWorld[1.0]</code>) for which you want to reset the Web services client port stub properties.</p> <p>To configure or reset client port stub properties for a SOA composite, the composite name is required (for example <code>default/HelloWorld[1.0]</code>), and the <code>moduleType</code> argument must be set to <code>soa</code>.</p>
<i>moduleType</i>	<p>Module type. Valid options are:</p> <ul style="list-style-type: none"> ▪ <code>soa</code>—SOA composite. ▪ <code>web</code>—Oracle Infrastructure Web Services packaged as a Web module (including an EJB). ▪ <code>wscnnc</code>—Use with a connection-based Web service client such as an ADF DC Web service client, ADF JAX-WS Indirection Proxy, or WebCenter client.
<i>serviceRefName</i>	Service reference name of the application or SOA composite for which you want to reset the Web service client port stub properties.
<i>portInfoName</i>	The name of the client port for which you want to reset the stub properties.
<i>properties</i>	<p>The list of properties to be set or changed. Properties must be specified using the following format:</p> <pre>("property", "value")</pre> <p>For example:</p> <pre>[("keystore.recipient.alias", "oracle"), ("csf-key", "oracle")]</pre> <p>To remove a property or clear the value assigned to it, specify a blank "" value. For example:</p> <pre>[("csf-key", "")]</pre> <p>To remove all the properties of the client port, set this argument to <code>None</code>.</p> <p>Sample client port stub properties are as follows:</p> <ul style="list-style-type: none"> ▪ <code>oracle.webservices.auth.username</code> ▪ <code>oracle.webservices.auth.password</code> ▪ <code>keystore.recipient.alias</code> ▪ <code>csf-key</code> ▪ <code>saml.issuer.name</code> ▪ <code>javax.xml.ws.session.maintain</code> ▪ <code>wsat.Version</code>—SOA references only ▪ <code>wsat.flowOption</code>—SOA references only <p>For a complete list of the configurable properties, see "Configuring the Web Service Client" in <i>Oracle Fusion Middleware Security and Administrator's Guide for Web Services</i>.</p>

14.2.9.3 Example

The following example resets the client port stub properties `wsat.flowOption` and `wsat.Version` to `SUPPORTS` and `DEFAULT`, respectively. Any other properties that were previously set for this client port are either reset to the default or removed. The client port is `JRFWssUsernamePort` of the `WssUsernameClient` Web module in the `/soainfra/soa1/jwsclient_1#1.1.0` application. Note that the `moduleType` is set to `wscnnc`, and the `serviceRefName` is set to `WssUsernameClient`.


```
wls:/soainfra/serverConfig>setWebServiceClientStubProperties('/soainfra/soa1/jwscli
ient_1#1.1.0',
'WssUsernameClient', 'wsconn', 'WssUsernameClient', 'JRFWssUsernamePort',
[("wsat.flowOption", "SUPPORTS"), ("wsat.Version", "DEFAULT")] )
```

14.3 Policy Management Commands

Use the WLST commands listed in [Table 14-3](#) to directly attach Oracle WSM Web service and client policies to application ports or SOA composites.

When you set or change an attached policy in ADF and WebCenter Web service and client applications, you must restart the application for the changes to take effect. After the policy change is completed, a reminder message is displayed prompting you to restart the application. You can stop and restart the application using the standard `stopApplication` and `startApplication` WLST commands. For more information about these commands, see ["Deployment Commands"](#) on page 3-19.

Table 14-3 Web Services WLST Directly-attached Policy Management Commands

Use this command...	To...	Use with WLST...
listAvailableWebServicePolicies	Display a list of all the available Oracle Web Services Manager (WSM) policies by category or subject type.	Online
listWebServicePolicies	List Web service port policy information for a Web service in an application or SOA composite.	Online
attachWebServicePolicy	Attach a policy to a Web service port of an application or SOA composite.	Online
attachWebServicePolicies	Attach multiple policies to a Web service port of an application or SOA composite.	Online
enableWebServicePolicy	Enable or disable a policy attached to a port of a Web service application or SOA composite.	Online
enableWebServicePolicies	Enable or disable multiple policies attached to a port of a Web service application or SOA composite.	Online
detachWebServicePolicy	Detach an Oracle WSM policy from a Web service port of an application or SOA composite.	Online
detachWebServicePolicies	Detach multiple Oracle WSM policies from a Web service port of an application or SOA composite.	Online
listWebServiceClientPolicies	List Web service client port policies information for an application or SOA composite.	Online
attachWebServiceClientPolicy	Attach an Oracle WSM policy to a Web service client port of an application or SOA composite.	Online
attachWebServiceClientPolicies	Attach multiple policies to a Web service client port of an application or SOA composite.	Online

Table 14–3 (Cont.) Web Services WLST Directly-attached Policy Management

Use this command...	To...	Use with WLST...
<code>enableWebServiceClientPolicy</code>	Enable or disable a policy of a Web service client port of an application or SOA composite.	Online
<code>enableWebServiceClientPolicies</code>	Enable or disable multiple policies of a Web service client port of an application or SOA composite.	Online
<code>detachWebServiceClientPolicy</code>	Detach a policy from a Web service client port of an application or SOA composite.	Online
<code>detachWebServiceClientPolicies</code>	Detach multiple policies from a Web service client port of an application or SOA composite.	Online
<code>setWebServicePolicyOverride</code>	Configure the Web service port policy override properties of an application or SOA composite.	Online

14.3.1 listAvailableWebServicePolicies

Command Category: Policy Management

Use with WLST: Online

14.3.1.1 Description

Display a list of all the available Oracle Web Services Manager (WSM) policies by category or subject type.

14.3.1.2 Syntax

```
listAvailableWebServicePolicies([category],[subject])
```

Argument	Definition
<i>category</i>	Optional. The policy category, for example: 'security', 'management'.
<i>subject</i>	Optional. The policy subject type, for example: 'server' or 'client'.

14.3.1.3 Example

The following example lists all the available Oracle WSM server security policies in the domain.

```
wls:/wls-domain/serverConfig>listAvailableWebServicePolicies('security','server')
```

14.3.2 listWebServicePolicies

Command Category: Policy Management

Use with WLST: Online

14.3.2.1 Description

List Web service port policy information for a Web service in an application or SOA composite.

The output will display the Web service port name, the OWSM policies it has attached to it, and if applicable, any policy override properties. For example:

```
HelloWorldPort:
security : oracle/wss_username_token_service_policy , enabled=true
```

14.3.2.2 Syntax

```
listWebServicePolicies(application,moduleOrCompName,moduleType,serviceName,subjectName)
```

Argument	Definition
<i>application</i>	Name and path of the application for which you want to list the Web services port policy information. For example, /domain/server/application#version_number To list the port policy information for a Web service application, this argument is required.
<i>moduleOrCompName</i>	Name of the Web module or SOA composite (for example HelloWorld[1.0]) for which you want to list the Web services port policy information. To list the port policy information for a SOA composite, the composite name is required (for example default/HelloWorld[1.0]), and the moduleType argument must be set to soa.
<i>moduleType</i>	Module type. Valid options are: <ul style="list-style-type: none"> ■ soa—SOA composite. ■ web—Oracle Infrastructure Web Services packaged as a Web module (including an EJB). ■ wls—Java EE Web services.
<i>serviceName</i>	Name of the Web service in the application or SOA composite for which you want to list the port policy information. For example, {http://namespace/}serviceName. Note that the namespace ({http://namespace/}) should not be included for a SOA composite.
<i>subjectName</i>	Policy subject, port, or operation name.

14.3.2.3 Examples

The following example lists the Web service port policy information for the application HelloWorld#1_0 for the server soa1 in the domain soainfra. In this example, the Web module name is j2wbasicPolicy, the service name is WssUsernameService, and the subject is a port named JRFWssUsernamePort.

```
wls:/wls-domain/serverConfig>listWebServicePolicies ('/soainfra/soa1/HelloWorld#1_0', 'j2wbasicPolicy', 'web', '{http://namespace/}WssUsernameService', 'JRFWssUsernamePort')
```

The following example lists the port policy information for the SOA composite default/HelloWorld[1.0]. Note that the moduleType is set to SOA, the service name is HelloService, and the subject is a port named HelloWorld_pt.

```
wls:/wls-domain/serverConfig>listWebServicePolicies (None, 'default/HelloWorld[1.0]', 'soa', 'HelloService', 'HelloWorld_pt')
```

14.3.3 attachWebServicePolicy

Command Category: Policy Management

Use with WLST: Online

14.3.3.1 Description

Attach a policy to a Web service port of an application or SOA composite.

The policyURI is validated through the Oracle WSM Policy Manager APIs if the wsm-pm application is installed on WebLogic Server and is available. If the PolicyURI that you specify in this command already is attached or exists, then this command enables the policy if it is disabled.

If the wsm-pm application is not installed or is not available, this command is not executed.

Note: Policy changes made using this WLST command are only effective after you restart your application. For ADF and WebCenter applications, a message is displayed to remind you to restart your application.

14.3.3.2 Syntax

```
attachWebServicePolicy(application, moduleOrCompName, moduleType, serviceName,
subjectName, policyURI, [subjectType=None])
```

Argument	Definition
<i>application</i>	Name and path of the application to which you want to attach a Web service policy. For example, <code>/domain/server/application#version_number</code> To attach a policy to a port of a Web service application, this argument is required.
<i>moduleOrCompName</i>	Name of the Web module or SOA composite (for example <code>HelloWorld[1.0]</code>) to which you want to attach a Web service policy. To attach a policy to a port of a SOA composite, the composite name is required (for example <code>default/HelloWorld[1.0]</code>), and the <code>moduleType</code> argument must be set to <code>soa</code> .
<i>moduleType</i>	Module type. Valid options are: <ul style="list-style-type: none"> ■ <code>soa</code>—SOA composite. ■ <code>web</code>—Oracle Infrastructure Web Services packaged as a Web module (including an EJB). ■ <code>wls</code>—Java EE Web services.
<i>serviceName</i>	Name of the Web service in the application or SOA composite. For example, <code>{http://namespace/}serviceName</code> . Note that the namespace (<code>{http://namespace/}</code>) should not be included for a SOA composite.
<i>subjectName</i>	Name of the policy subject, port, or operation.
<i>policyURI</i>	Oracle WSM policy name URI, for example <code>'oracle/log_policy'</code>
<i>subjectType</i>	Optional. Policy subject type. Valid options are: <ul style="list-style-type: none"> ■ <code>P</code>—Port. The default is <code>P</code>. ■ <code>O</code>—Not supported in this release.

14.3.3.3 Examples

The following example attaches the policy `oracle/wss_username_token_service_policy` to the port `JRFWssUsernamePort` of the Web module

WssUsernameService. The Web service is part of the application HelloWorld#1_0 for the server soa1 in the domain soainfra.

```
wls:/wls-domain/serverConfig>attachWebServicePolicy
('/soainfra/soa1/HelloWorld#1_0','j2wbasicPolicy','web',
'{http://namespace/}WssUsernameService','JRFWssUsernamePort','oracle/wss_username_
token_service_policy')
```

The following example attaches the policy oracle/log_policy to the port HelloWorld_pt of the service HelloService in the SOA composite default/HelloWorld[1.0]. Note that the namespace ({http://namespace/}) should not be included for a SOA composite.

```
wls:/wls-domain/serverConfig>attachWebServicePolicy(None,
'default/HelloWorld[1.0]', 'soa','HelloService','HelloWorld_pt','oracle/log_
policy')
```

The following example attaches the policy oracle/wss_username_token_service_policy to the port helloWorldJaxwsSoapHttpPort of the Java EE Web service helloWorldJaxws.

```
wls:wls-domain/serverConfig>attachWebServicePolicy
('/wls-domain/AdminServer/helloWorldJaxws','helloWorldJaxws#1!helloWorldJaxws',
'wls','helloWorldJaxws','helloWorldJaxwsSoapHttpPort','oracle/wss_username_
token_service_policy')
```

A Web service cannot contain both a WebLogic Web service policy and an Oracle Web service policy. If you have a Web service with a WebLogic Web service policy, you must first detach it before attaching the Oracle Web service policy. The following example detaches the WebLogic Web service policy Wssp1.2-2007-Saml2.0-SenderVouches-Wss1.1.xml from the port SimplePort in the Java EE Web service SimpleEjbService and attaches the Oracle Web service policy oracle/wss_username_token_service_policy.

```
wls:wls-domain/serverConfig>detachWebServicePolicy('/wls-domain/AdminServer/Simple
JAXWS','SimpleJAXWS#1!SimpleEjbService','wls','SimpleEjbService',
'SimplePort','policy:Wssp1.2-2007-Saml2.0-SenderVouches-Wss1.1.xml')
```

```
wls:wls-domain/serverConfig>attachWebServicePolicy('/wls-domain/AdminServer/Simple
JAXWS','SimpleJAXWS#1!SimpleEjbService','wls','SimpleEjbService','SimplePort',
'oracle/wss_username_token_service_policy')
```

Note: The detachWebServicePolicy WLST command allows you to detach WebLogic Web service policies from a Web service. However, you cannot use the attachWebServicePolicy WLST command to attach WebLogic Web service policies. To attach WebLogic Web service policies to a Web service, you must use the WebLogic Administration Console.

14.3.4 attachWebServicePolicies

Command Category: Policy Management

Use with WLST: Online

14.3.4.1 Description

Attach multiple policies to a Web service port of an application or SOA composite.

The policyURIs are validated through the Oracle WSM Policy Manager APIs if the wsm-pm application is installed on WebLogic Server and is available. If any of the policies that you specify in this command are already attached or exist, then this command enables the policies that are already attached (if they are disabled), and attaches the others.

If the wsm-pm application is not installed or is not available, this command is not executed.

Note: Policy changes made using this WLST command are only effective after you restart your application. For ADF and WebCenter applications, a message is displayed to remind you to restart your application.

14.3.4.2 Syntax

```
attachWebServicePolicies(application, moduleOrCompName, moduleType, serviceName,
subjectName, policyURIs, [subjectType=None])
```

Argument	Definition
<i>application</i>	Name and path of the application to which you want to attach the Web service policies. For example, <code>/domain/server/application#version_number</code> To attach the policies to a port of a Web service application, this argument is required.
<i>moduleOrCompName</i>	Name of the Web module or SOA composite (for example <code>HelloWorld[1.0]</code>) to which you want to attach Web service policies. To attach the policies to a port of a SOA composite, the composite name is required (for example <code>default/HelloWorld[1.0]</code>), and the <code>moduleType</code> argument must be set to <code>soa</code> .
<i>moduleType</i>	Module type. Valid options are: <ul style="list-style-type: none"> ■ <code>soa</code>—SOA composite. ■ <code>web</code>—Oracle Infrastructure Web Services packaged as a Web module (including an EJB). ■ <code>wls</code>—Java EE Web services.
<i>serviceName</i>	Name of the Web service in the application or SOA composite. For example, <code>{http://namespace/}serviceName</code> . Note that the namespace (<code>{http://namespace/}</code>) should not be included for a SOA composite.
<i>subjectName</i>	Name of the policy subject, port, or operation.
<i>policyURIs</i>	List of Oracle WSM policy name URIs, for example <code>["oracle/log_policy", "oracle/wss_username_token_service_policy"]</code> If any of the policies that you specify are already attached or exist, then this command enables the policies that are already attached (if they are disabled), and attaches the others.
<i>subjectType</i>	Optional. Policy subject type. Valid options are: <ul style="list-style-type: none"> ■ <code>P</code>—Port. The default is <code>P</code>. ■ <code>O</code>—Not supported in this release.

14.3.4.3 Example

The following example attaches the policies "oracle/log_policy", "oracle/wss_username_token_service_policy" to the port JRFWssUsernamePort of the Web module WssUsernameService. The Web service is part of the application HelloWorld#1_0 for the server soa1 in the domain soainfra.

```
wls:/wls-domain/serverConfig>attachWebServicePolicies
('/soainfra/soa1/HelloWorld#1_0','j2wbasicPolicy','web',
'{http://namespace/}WssUsernameService','JRFWssUsernamePort',
["oracle/log_policy", "oracle/wss_username_token_service_policy"])
```

The following example attaches the policies "oracle/binding_authorization_denyall_policy", "oracle/wss_username_token_service_policy" to the port helloWorldJaxwsSoapHttpPort of the Web module helloWorldJaxws. The Java EE Web service is part of the application helloWorldJaxws for the server AdminServer in the domain wls-domain.

```
wls:wls-domain/ServerConfig>attachWebServicePolicies
('/wls-domain/AdminServer/helloWorldJaxws','helloWorldJaxws#1!helloWorldJaxws',
'wls','helloWorldJaxws','helloWorldJaxwsSoapHttpPort', ["oracle/binding_
authorization_denyall_policy",
"oracle/wss_username_token_service_policy"])
```

14.3.5 enableWebServicePolicy

Command Category: Policy Management

Use with WLST: Online

14.3.5.1 Description

Enable or disable a policy attached to a port of a Web service application or SOA composite.

If the policy that you specify in this command is not attached to the port, an error message is displayed and/or an exception is thrown.

Note: Policy changes made using this WLST command are only effective after you restart your application. For ADF and WebCenter applications, a message is displayed to remind you to restart your application.

14.3.5.2 Syntax

```
enableWebServicePolicy(application, moduleOrCompName, moduleType, serviceName,
subjectName, policyURI, [enable], [subjectType=None] )
```

Argument	Definition
<i>application</i>	Name and path of the application for which you want to enable a Web service policy. For example, /domain/server/application#version_number To enable a policy that is attached to a port of a Web service application, this argument is required.

Argument	Definition
<i>moduleOrCompName</i>	Name of the Web module or SOA composite (for example HelloWorld[1.0]) for which you want to enable a Web service policy. To enable a policy that is attached to a port of a SOA composite, the composite name is required (for example default/HelloWorld[1.0]), and the <i>moduleType</i> argument must be set to <i>soa</i> .
<i>moduleType</i>	Module type. Valid options are: <ul style="list-style-type: none"> ■ <i>soa</i>—SOA composite. ■ <i>web</i>—Oracle Infrastructure Web Services packaged as a Web module (including an EJB). ■ <i>wls</i>—Java EE Web services.
<i>serviceName</i>	Name of the Web service in the application or SOA composite. For example, {http://namespace/}serviceName
<i>subjectName</i>	Name of the policy subject, port, or operation.
<i>policyURI</i>	Oracle WSM policy name URI, for example 'oracle/log_policy' If the policy that you specify is not attached, an error message is displayed and/or an exception is thrown.
<i>enable</i>	Optional. Specifies whether to enable or disable the policy. Valid options are: <ul style="list-style-type: none"> ■ <i>true</i>—Enables the policy. The default is <i>true</i>. ■ <i>false</i>—Disables the policy. If you omit this argument, the policy is enabled.
<i>subjectType</i>	Optional. Policy subject type. Valid options are: <ul style="list-style-type: none"> ■ <i>P</i>—Port. The default is <i>P</i>. ■ <i>O</i>—Not supported in this release.

14.3.5.3 Examples

The following example enables the policy `oracle/wss_username_token_service_policy` attached to the port `JRFWssUsernamePort` of the Web module `WssUsernameService`. The Web service is part of the application `HelloWorld#1_0` for the server `soa1` in the domain `soainfra`.

```
wls:/wls-domain/serverConfig>enableWebServicePolicy
('/soainfra/soa1/HelloWorld#1_0','j2wbasicPolicy','web',
'{http://namespace/}WssUsernameService','JRFWssUsernamePort','oracle/wss_username_
token_service_policy',true)
```

The following example enables the policy `oracle/log_policy` attached to the port `HelloWorld_pt` for the service `HelloService` in the SOA composite `default/HelloWorld[1.0]`. Note that the namespace (`{http://namespace/}`) should not be included for a SOA composite.

```
wls:/wls-domain/serverConfig>enableWebServicePolicy(None,
'default/HelloWorld[1.0]', 'soa','HelloService','HelloWorld_pt','oracle/log_
policy')
```

The following example disables the policy `oracle/log_policy` attached to the port `HelloWorld_pt` for the service `HelloService` in the SOA composite

default/HelloWorld[1.0]. Note that the namespace (`{http://namespace/}`) should not be included for a SOA composite.

```
wls:/wls-domain/serverConfig>enableWebServicePolicy(None,
'default/HelloWorld[1.0]', 'soa', 'HelloService', 'HelloWorld_pt', 'oracle/log_
policy', false)
```

The following example disables the policy `oracle/wss_username_token_service_policy` attached to the port `helloWorldJaxwsSoapHttpPort` for the service `helloWorldJaxws` in the Java EE Web service `wls-domain/AdminServer/helloWorldJaxws`

```
wls:/wls-domain/domainRuntime> enableWebServicePolicy
('/wls-domain/AdminServer/helloWorldJaxws', 'helloWorldJaxws#1!helloWorldJaxws',
'wls', 'helloWorldJaxws', 'helloWorldJaxwsSoapHttpPort', 'oracle/wss_username_
token_service_policy', false)
```

14.3.6 enableWebServicePolicies

Command Category: Policy Management

Use with WLST: Online

14.3.6.1 Description

Enable or disable multiple policies attached to a port of a Web service application or SOA composite.

If the policyURIs that you specify in this command are not attached to the port, an error message is displayed and/or an exception is thrown.

Note: Policy changes made using this WLST command are only effective after you restart your application. For ADF and WebCenter applications, a message is displayed to remind you to restart your application.

14.3.6.2 Syntax

```
enableWebServicePolicies(application, moduleOrCompName, moduleType, serviceName,
subjectName, policyURIs, [enable], [subjectType=None] )
```

Argument	Definition
<i>application</i>	Name and path of the application for which you want to enable the Web service policies. For example, <code>/domain/server/application#version_number</code> To enable policies that are attached to a port of a Web service application, this argument is required.
<i>moduleOrCompName</i>	Name of the Web module or SOA composite (for example <code>HelloWorld[1.0]</code>) for which you want to enable Web service policies. To enable policies that are attached to a port of a SOA composite, the composite name is required (for example <code>default/HelloWorld[1.0]</code>), and the <code>moduleType</code> argument must be set to <code>soa</code> .

Argument	Definition
<i>moduleType</i>	Module type. Valid options are: <ul style="list-style-type: none"> ■ <code>soa</code>—SOA composite. ■ <code>web</code>—Oracle Infrastructure Web Services packaged as a Web module (including an EJB). ■ <code>wls</code>—Java EE Web services.
<i>serviceName</i>	Name of the Web service in the application or SOA composite. For example, <code>{http://namespace/}serviceName</code> . Note that the namespace (<code>{http://namespace/}</code>) should not be included for a SOA composite.
<i>subjectName</i>	Name of the policy subject, port, or operation.
<i>policyURIs</i>	List of Oracle WSM policy name URIs, for example <code>["oracle/log_policy", "oracle/wss_username_token_service_policy"]</code> If the policyURIs that you specify are not attached, an error message is displayed and/or an exception is thrown.
<i>enable</i>	Optional. Specifies whether to enable or disable the policies. Valid options are: <ul style="list-style-type: none"> ■ <code>true</code>—Enables the policies. The default is <code>true</code>. ■ <code>false</code>—Disables the policies. If you omit this argument, the policies are enabled.
<i>subjectType</i>	Optional. Policy subject type. Valid options are: <ul style="list-style-type: none"> ■ <code>P</code>—Port. The default is <code>P</code>. ■ <code>O</code>—Not supported in this release.

14.3.6.3 Example

The following example enables the policies `["oracle/log_policy", "oracle/wss_username_token_service_policy"]` attached to the port `JRFWssUsernamePort` of the Web module `WssUsernameService`. The Web service is part of the application `HelloWorld#1_0` for the server `soa1` in the domain `soainfra`.

```
wls:/wls-domain/serverConfig>enableWebServicePolicies
('/soainfra/soa1/HelloWorld#1_0','j2wbasicPolicy','web',
'{http://namespace/}WssUsernameService','JRFWssUsernamePort',["oracle/log_policy",
"oracle/wss_username_token_service_policy"],true)
```

The following example disables the policies `["oracle/binding_authorization_denyall_policy", "oracle/wss_username_token_service_policy"]` attached to the port `helloWorldJaxwsSoapHttpPort` of the Web module `helloWorldJaxws#1!helloWorldJaxws`. The Web service is part of the application `helloWorldJaxws` for the server `AdminServer` in the domain `wls-domain`.

```
wls:/wls-domain/serverConfig>enableWebServicePolicies )
('/wls-domain/AdminServer/helloWorldJaxws','helloWorldJaxws#1!helloWorldJaxws',
'wls','helloWorldJaxws','helloWorldJaxwsSoapHttpPort', ["oracle/binding_
authorization_denyall_policy",
"oracle/wss_username_token_service_policy"], false)
```

14.3.7 detachWebServicePolicy

Command Category: Policy Management

Use with WLST: Online

14.3.7.1 Description

Detach an Oracle WSM policy from a Web service port of an application or SOA composite.

Note: Policy changes made using this WLST command are only effective after you restart your application. For ADF and WebCenter applications, a message is displayed to remind you to restart your application.

14.3.7.2 Syntax

```
detachWebServicePolicy(application, moduleOrCompName, moduleType, serviceName,
subjectName, policyURI, [subjectType=None])
```

Argument	Definition
<i>application</i>	Name and path of the application from which you want to detach a Web service policy. For example, <code>/domain/server/application#version_number</code> To detach a policy from a port of a Web service application, this argument is required.
<i>moduleOrCompName</i>	Name of the Web module or SOA composite (for example <code>HelloWorld[1.0]</code>) from which you want to detach a Web service policy. To detach a policy from a port of a SOA composite, the composite name is required (for example <code>default/HelloWorld[1.0]</code>), and the <code>moduleType</code> argument must be set to <code>soa</code> .
<i>moduleType</i>	Module type. Valid options are: <ul style="list-style-type: none"> ■ <code>soa</code>—SOA composite. ■ <code>web</code>—Oracle Infrastructure Web Services packaged as a Web module (including an EJB). ■ <code>wls</code>—Java EE Web services.
<i>serviceName</i>	Name of the Web service in the application or SOA composite. For example, <code>{http://namespace/}serviceName</code> . Note that the namespace (<code>{http://namespace/}</code>) should not be included for a SOA composite.
<i>subjectName</i>	Name of the policy subject, port, or operation.
<i>policyURI</i>	Oracle WSM policy name URI, for example <code>'oracle/log_policy'</code> If the policy specified is not attached, an error message is displayed and/or an exception is thrown.
<i>subjectType</i>	Optional. Policy subject type. Valid options are: <ul style="list-style-type: none"> ■ <code>P</code>—Port. The default is <code>P</code>. ■ <code>O</code>—Not supported in this release.

14.3.7.3 Examples

The following example detaches the policy oracle/wss_username_token_service_policy from the port JRFWssUsernamePort of the Web module WssUsernameService. The Web service is part of the application HelloWorld#1_0 for the server soa1 in the domain soainfra.

```
wls:/wls-domain/serverConfig>detachWebServicePolicy
('/soainfra/soa1/HelloWorld#1_0','j2wbasicPolicy','web',
'{http://namespace/}WssUsernameService','JRFWssUsernamePort','oracle/wss_username_
token_service_policy')
```

The following example detaches the policy oracle/log_policy from the port HelloWorld_pt of the service HelloService in the SOA composite default/HelloWorld[1.0]. Note that the namespace ({http://namespace/}) should not be included for a SOA composite.

```
wls:/wls-domain/serverConfig>detachWebServicePolicy(None,
'default/HelloWorld[1.0]','soa','HelloService','HelloWorld_pt','oracle/log_
policy')
```

The following example detaches the policy oracle/wss_username_token_service_policy from the port helloWorldJaxwsSoapHttpPort of the service helloWorldJaxws in the Java EE Web service

wls-domain/AdminServer/helloWorldJaxws.

```
wls:/wls-domain/serverConfig>detachWebServicePolicy
('/wls-domain/AdminServer/helloWorldJaxws','helloWorldJaxws#1!helloWorldJaxws',
'wls','helloWorldJaxws','helloWorldJaxwsSoapHttpPort','oracle/wss_username_
token_service_policy')
```

14.3.8 detachWebServicePolicies

Command Category: Policy Management

Use with WLST: Online

14.3.8.1 Description

Detach multiple Oracle WSM policies from a Web service port of an application or SOA composite.

If the wsm-pm application is not installed or is not available, this command is not executed.

Note: Policy changes made using this WLST command are only effective after you restart your application. For ADF and WebCenter applications, a message is displayed to remind you to restart your application.

14.3.8.2 Syntax

```
detachWebServicePolicies(application, moduleOrCompName, moduleType, serviceName,
subjectName, policyURIs, [subjectType=None])
```

Argument	Definition
<i>application</i>	Name and path of the application from which you want to detach the Web service policies. For example, <code>/domain/server/application#version_number</code> To detach policies from a port of a Web service application, this argument is required.
<i>moduleOrCompName</i>	Name of the Web module or SOA composite (for example <code>HelloWorld[1.0]</code>) from which you want to detach the Web service policies. To detach policies from a port of a SOA composite, the composite name is required (for example <code>default/HelloWorld[1.0]</code>), and the <code>moduleType</code> argument must be set to <code>soa</code> .
<i>moduleType</i>	Module type. Valid options are: <ul style="list-style-type: none"> ■ <code>soa</code>—SOA composite. ■ <code>web</code>—Oracle Infrastructure Web Services packaged as a Web module (including an EJB). ■ <code>wls</code>—Java EE Web services.
<i>serviceName</i>	Name of the Web service in the application or SOA composite. For example, <code>{http://namespace/}serviceName</code> . Note that the namespace (<code>{http://namespace/}</code>) should not be included for a SOA composite.
<i>subjectName</i>	Name of the policy subject, port, or operation.
<i>policyURIs</i>	List of Oracle WSM policy name URIs, for example <code>["oracle/log_policy", "oracle/wss_username_token_service_policy"]</code> If a policyURI specified is not attached, an error message is displayed and/or an exception is thrown.
<i>subjectType</i>	Optional. Policy subject type. Valid options are: <ul style="list-style-type: none"> ■ <code>P</code>—Port. The default is <code>P</code>. ■ <code>O</code>—Not supported in this release.

14.3.8.3 Example

The following example detaches the policies `"oracle/log_policy"`, `"oracle/wss_username_token_service_policy"` from the port `JRFWssUsernamePort` of the Web module `WssUsernameService`. The Web service is part of the application `HelloWorld#1_0` for the server `soa1` in the domain `soainfra`.

```
wls:/wls-domain/serverConfig>detachWebServicePolicies
('/soainfra/soa1/HelloWorld#1_0','j2wbasicPolicy','web',
'{http://namespace/}WssUsernameService','JRFWssUsernamePort',
["oracle/log_policy","oracle/wss_username_token_service_policy"])
```

The following example detaches the policies `"oracle/binding_authorization_denyall_policy"`, `"oracle/wss_username_token_service_policy"` from the port `helloWorldJaxwsSoapHttpPort` of the Java EE Web module `helloWorldJaxws`. The Web service is part of the application `helloWorldJaxws` for the server `AdminServer` in the domain `wls-domain`.

```
wls:/wls-domain/serverConfig>detachWebServicePolicies
('/wls-domain/AdminServer/helloWorldJaxws','helloWorldJaxws#1!helloWorldJaxws',
'wls','helloWorldJaxws','helloWorldJaxwsSoapHttpPort',["oracle/binding_
authorization_denyall_policy",
```

```
"oracle/wss_username_token_service_policy"])
```

14.3.9 listWebServiceClientPolicies

Command Category: Policy Management

Use with WLST: Online

14.3.9.1 Description

List Web service client port policies information for an application or SOA composite.

The output will display the Web service client/reference port name and the Oracle WSM policies it has attached to it. For example:

```
test-port:
security: oracle/wss_username_token_client_policy, enabled=true
```

14.3.9.2 Syntax

```
listWebServiceClientPolicies(application, moduleOrCompName, moduleType,
serviceRefName, portInfoName)
```

Argument	Definition
<i>application</i>	Name and path of the application for which you want to list the Web service client port policy information. For example, /domain/server/application#version_number To list the client port policy information for a Web services application, this argument is required.
<i>moduleOrCompName</i>	Name of the Web module or SOA composite (for example HelloWorld[1.0]) for which you want to list the Web services port policy information. To list the client port policy information for a SOA composite, the composite name is required (for example default/HelloWorld[1.0]), and the moduleType argument must be set to soa.
<i>moduleType</i>	Module type. Valid options are: <ul style="list-style-type: none"> ■ soa—SOA composite. ■ web—Oracle Infrastructure Web Services packaged as a Web module (including an EJB). ■ wls—Java EE Web services. ■ wsconn—Use with a connection-based Web service client such as an ADF DC Web service client, ADF JAX-WS Indirection Proxy, or WebCenter client.
<i>serviceRefName</i>	The service reference name of the application or composite.
<i>portInfoName</i>	The client port name.

14.3.9.3 Example

The following example lists the Web service client port policy information for the application jwsclient_1#1.1.0 for the server soa1 in the domain soainfra. In this example, the Web module name is WssUsernameClient, the module type is wsconn, the service reference name is WssUsernameClient, and the client port name is JRFWssUsernamePort.

```
wls:/wls-domain/serverConfig>listWebServiceClientPolicies
('/soainfra/soa1/jwsclient_1#1.1.0', 'WssUsernameClient', 'wsconn',
```

```
'WssUsernameClient', 'JRFWssUsernamePort')
```

14.3.10 attachWebServiceClientPolicy

Command Category: Policy Management

Use with WLST: Online

14.3.10.1 Description

Attach a Oracle WSM policy to a Web service client port of an application or SOA composite.

The policyURI is validated through the Oracle WSM Policy Manager APIs if the wsm-pm application is installed on WebLogic Server and is available. If the PolicyURI that you specify in this command already is attached or exists, then this command enables the policy if it is disabled.

If the wsm-pm application is not installed or is not available, this command is not executed.

Note: Policy changes made using this WLST command are only effective after you restart your application. For ADF and WebCenter applications, a message is displayed to remind you to restart your application.

14.3.10.2 Syntax

```
attachWebServiceClientPolicy(application,moduleOrCompName,moduleType,
serviceRefName, portInfoName, policyURI, [subjectType=None] )
```

Argument	Definition
<i>application</i>	Name and path of the application for which you want to attach a policy to the Web service client port. For example, <code>/domain/server/application#version_number</code> To attach a policy to a client port of a Web service application, this argument is required.
<i>moduleOrCompName</i>	Name of the Web module or SOA composite (for example <code>HelloWorld[1.0]</code>) for which you want to attach the policy to the client port. To attach a policy to a client port of a SOA composite, the composite name is required (for example <code>default/HelloWorld[1.0]</code>), and the <code>moduleType</code> argument must be set to <code>soa</code> .
<i>moduleType</i>	Module type. Valid options are: <ul style="list-style-type: none"> ■ <code>soa</code>—SOA composite. ■ <code>web</code>—Oracle Infrastructure Web Services packaged as a Web module (including an EJB). ■ <code>wls</code>—Java EE Web services. ■ <code>wscconn</code>—Use with a connection-based Web service client such as an ADF DC Web service client, ADF JAX-WS Indirection Proxy, or WebCenter client.
<i>serviceRefName</i>	The service reference name of the application or composite.
<i>portInfoName</i>	The client port to which you want to attach the Oracle WSM client policy.

Argument	Definition
<i>policyURI</i>	The Oracle WSM policy name URI, for example "oracle/wss_username_token_client_policy" If the policy that you specify is already attached or exists, then this command enables the policy if it is disabled.
<i>subjectType</i>	Optional. Policy subject type. Valid options are: <ul style="list-style-type: none"> ■ P—Port. The default is P. ■ O—Not supported in this release.

14.3.10.3 Examples

The following example attaches the client policy `oracle/wss_username_token_client_policy` to the port `JRFWssUsernamePort` of the Web module `WssUsernameClient`. The Web service is part of the application `jwsclient_1#1.1.0` for the server `soa1` in the domain `soainfra`.

```
wls:/wls-domain/serverConfig>attachWebServiceClientPolicy
('/soainfra/soa1/jwsclient_1#1.1.0','WssUsernameClient','wsconn',
'WssUsernameClient','JRFWssUsernamePort','oracle/wss_username_token_client_
policy')
```

The following example attaches the client policy `oracle/log_policy` to the client port `HelloWorld_pt` in the SOA composite `default/HelloWorld[1.0]`.

```
wls:/wls-domain/serverConfig>attachWebServiceClientPolicy
(None, 'default/HelloWorld[1.0]','soa','client','HelloWorld_pt','oracle/log_
policy')
```

The following example attaches the `oracle/wss_username_token_client_policy` client policy to the Java EE Web service client port `UpperCaseImplPort` of the Web module `owsm_mbean.resouce_pattern.web.ClientJWS/sei2`. The Web service is part of the application `ClientJWS`.

```
wls:/wls-domain/serverConfig> attachWebServiceClientPolicy
('/wls-domain/AdminServer/ClientJWS','owsm_mbean.resouce_
pattern.web.ClientJWS/sei2',
'wls','owsm_mbean.resouce_pattern.web.ClientJWS/sei2', 'UpperCaseImplPort',
'oracle/wss_username_token_client_policy')
```

14.3.11 attachWebServiceClientPolicies

Command Category: Policy Management

Use with WLST: Online

14.3.11.1 Description

Attach multiple policies to a Web service client port of an application or SOA composite.

The policyURIs are validated through the Oracle WSM Policy Manager APIs if the `wsm-pm` application is installed on WebLogic Server and is available. If the policies that you specify in this command are already attached or exist, then this command enables the policies that are already attached (if they are disabled), and attaches the others.

If the `wsm-pm` application is not installed or is not available, this command is not executed.

Note: Policy changes made using this WLST command are only effective after you restart your application. For ADF and WebCenter applications, a message is displayed to remind you to restart your application.

14.3.11.2 Syntax

```
attachWebServiceClientPolicies(application,moduleOrCompName,moduleType,
serviceRefName,portInfoName,policyURIs, [subjectType=None] )
```

Argument	Definition
<i>application</i>	Name and path of the application for which you want to attach Oracle WSM client policies to the Web service client port. For example, /domain/server/application#version_number To attach policies to a client port of a Web service application, this argument is required.
<i>moduleOrCompName</i>	Name of the Web module or SOA composite (for example HelloWorld[1.0]) for which you want to attach the policies to the client port. To attach policies to a client port of a SOA composite, the composite name is required (for example default/HelloWorld[1.0]), and the moduleType argument must be set to soa.
<i>moduleType</i>	Module type. Valid options are: <ul style="list-style-type: none"> ■ soa—SOA composite. ■ web—Oracle Infrastructure Web Services packaged as a Web module (including an EJB). ■ wls—Java EE Web services. ■ wsconn—Use with a connection-based Web service client such as an ADF DC Web service client, ADF JAX-WS Indirection Proxy, or WebCenter client.
<i>serviceRefName</i>	The service reference name of the application or composite.
<i>portInfoName</i>	The client port to which you want to attach the Oracle WSM client policy.
<i>policyURI</i>	The Oracle WSM policy name URIs, for example ["oracle/log_policy", "oracle/wss_username_token_client_policy"] If the policies that you specify in this command are already attached or exist, then this command enables the policies that are already attached (if they are disabled), and attaches the others.
<i>subjectType</i>	Optional. Policy subject type. Valid options are: <ul style="list-style-type: none"> ■ P—Port. The default is P. ■ O—Not supported in this release.

14.3.11.3 Examples

The following example attaches the policies oracle/wss_username_token_client_policy and oracle/log_policy to the port JRFWssUsernamePort of the Web module WssUsernameClient. The Web service is part of the application jwsclient_1#1.1.0 for the server soa1 in the domain soainfra.

```
wls:/wls-domain/serverConfig>attachWebServiceClientPolicies
('/soainfra/soa1/jwsclient_1#1.1.0','WssUsernameClient','wsconn',
'WssUsernameClient','JRFWssUsernamePort',['oracle/wss_username_token_client_
```

```
policy","oracle/log_policy"])
```

The following example attaches the policies `oracle/wss_username_token_client_policy` and `oracle/log_policy` to the client port `HelloWorld_pt` in the SOA composite `default/HelloWorld[1.0]`.

```
wls:/wls-domain/serverConfig>attachWebServiceClientPolicy
(None, 'default/HelloWorld[1.0]','soa','client','HelloWorld_pt',["oracle/wss_
username_token_client_policy","oracle/log_policy"])
```

The following example attaches the policies `oracle/wss10_saml20_token_client_policy` and `oracle/wss11_message_protection_client_policy` to the client port `UpperCaseImplPort` in the Java EE Web module `owsm_mbean.resouce_pattern.web.ClientJWS/sei2`.

```
wls:/wls-domain/serverConfig>attachWebServiceClientPolicies
('/wls-domain/AdminServer/ClientJWS','owsm_mbean.resouce_
pattern.web.ClientJWS/sei2',
'wls','owsm_mbean.resouce_pattern.web.ClientJWS/sei2','UpperCaseImplPort',\
["oracle/wss10_saml20_token_client_policy","oracle/wss11_message_protection_
client_policy"])
```

14.3.12 enableWebServiceClientPolicy

Command Category: Policy Management

Use with WLST: Online

14.3.12.1 Description

Enable or disable a policy of a Web service client port of an application or SOA composite.

Note: Policy changes made using this WLST command are only effective after you restart your application. For ADF and WebCenter applications, a message is displayed to remind you to restart your application.

14.3.12.2 Syntax

```
enableWebServiceClientPolicy(application,moduleOrCompName,moduleType,
serviceRefName,portInfoName,policyURI,[enable],[subjectType=None] )
```

Argument	Definition
<i>application</i>	Name and path of the application for which you want to enable or disable a policy of a Web service client port. For example, <code>/domain/server/application#version_number</code> To enable or disable a policy of a client port of a Web service application, this argument is required.
<i>moduleOrCompName</i>	Name of the Web module or SOA composite (for example <code>HelloWorld[1.0]</code>) for which you want to enable or disable a policy of a client port. To enable or disable a policy of a client port for a SOA composite, the composite name is required (for example <code>default/HelloWorld[1.0]</code>), and the <code>moduleType</code> argument must be set to <code>soa</code> .

Argument	Definition
<i>moduleType</i>	Module type. Valid options are: <ul style="list-style-type: none"> ■ soa—SOA composite. ■ web—Oracle Infrastructure Web Services packaged as a Web module (including an EJB). ■ wls—Java EE Web services. ■ wscconn—Use with a connection-based Web service client such as an ADF DC Web service client, ADF JAX-WS Indirection Proxy, or WebCenter client.
<i>serviceRefName</i>	The service reference name of the application or composite.
<i>portInfoName</i>	The name of the client port to which you want to attach the Oracle WSM client policy.
<i>policyURI</i>	The Oracle WSM policy name URI, for example "oracle/wss_username_token_client_policy"
<i>enable</i>	Optional. Specifies whether to enable or disable the policy. Valid options are: <ul style="list-style-type: none"> ■ true—Enables the policy. The default is true. ■ false—Disables the policy. If you omit this argument, the policy is enabled.
<i>subjectType</i>	Optional. Policy subject type. Valid options are: <ul style="list-style-type: none"> ■ P—Port. The default is P. ■ O—Not supported in this release.

14.3.12.3 Examples

The following example enables the client policy `oracle/wss_username_token_client_policy` of the port `JRFWssUsernamePort` of the Web module `WssUsernameClient`. The Web service is part of the application `jwsclient_1#1.1.0` for the server `soa1` in the domain `soainfra`.

```
wls:/wls-domain/serverConfig>enableWebServiceClientPolicy
('/soainfra/soa1/jwsclient_1#1.1.0','WssUsernameClient','wscconn',
'WssUsernameClient','JRFWssUsernamePort','oracle/wss_username_token_client_
policy',true)
```

The following example enables the client policy `oracle/log_policy` of the client port `HelloWorld_pt` in the SOA composite `default/HelloWorld[1.0]`.

```
wls:/wls-domain/serverConfig>enableWebServiceClientPolicy(None,
'default/HelloWorld[1.0]','soa','client','HelloWorld_pt','oracle/log_policy')
```

The following example disables the client policy `oracle/log_policy` of the client port `HelloWorld_pt` in the SOA composite `default/HelloWorld[1.0]`.

```
wls:/wls-domain/serverConfig>enableWebServiceClientPolicy(None,
'default/HelloWorld[1.0]','soa','client','HelloWorld_pt','oracle/log_policy',
false )
```

The following example disables the client policy `oracle/wss_username_token_client_policy` on the client port `UpperCaseImplPort` in the Java EE Web module `owsm_mbean.resouce_pattern.web.ClientJWS/sei2`.

```
wls:/wls-domain/serverConfig>enableWebServiceClientPolicy('/wls-domain/AdminServer
/ClientJWS',
```

```
'owsm_mbean.resouce_pattern.web.ClientJWS/sei2', 'wls', 'owsm_mbean.resouce_
pattern.web.ClientJWS/sei2',
'UpperCaseImplPort', "oracle/wss_username_token_client_policy", false)
```

14.3.13 enableWebServiceClientPolicies

Command Category: Policy Management

Use with WLST: Online

14.3.13.1 Description

Enable or disable multiple policies of a Web service client port of an application or SOA composite.

Note: Policy changes made using this WLST command are only effective after you restart your application. For ADF and WebCenter applications, a message is displayed to remind you to restart your application.

14.3.13.2 Syntax

```
enableWebServiceClientPolicies(application,moduleOrCompName,moduleType,
serviceRefName,portInfoName,policyURIs,[enable], [subjectType=None] )
```

Argument	Definition
<i>application</i>	Name and path of the application for which you want to enable or disable multiple policies of a Web service client port. For example, /domain/server/application#version_number To enable or disable multiple policies of a client port of a Web service application, this argument is required.
<i>moduleOrCompName</i>	Name of the Web module or SOA composite (for example HelloWorld[1.0]) for which you want to enable or disable multiple policies of a client port. To enable or disable multiple policies of a client port for a SOA composite, the composite name is required (for example default/HelloWorld[1.0]), and the <i>moduleType</i> argument must be set to <i>soa</i> .
<i>moduleType</i>	Module type. Valid options are: <ul style="list-style-type: none"> ■ <i>soa</i>—SOA composite. ■ <i>web</i>—Oracle Infrastructure Web Services packaged as a Web module (including an EJB). ■ <i>wls</i>—Java EE Web services. ■ <i>wscconn</i>—Use with a connection-based Web service client such as an ADF DC Web service client, ADF JAX-WS Indirection Proxy, or WebCenter client.
<i>serviceRefName</i>	The service reference name of the application or composite.
<i>portInfoName</i>	The name of the client port to which you want to attach the Oracle WSM client policies.
<i>policyURIs</i>	The list of Oracle WSM policy name URIs, for example ["oracle/log_policy", "oracle/wss_username_token_client_policy"].

Argument	Definition
<i>enable</i>	Optional. Specifies whether to enable or disable the policies. Valid options are: <ul style="list-style-type: none"> ■ <code>true</code>—Enables the policy. The default is <code>true</code>. ■ <code>false</code>—Disables the policy. If you omit this argument, the policies are enabled.
<i>subjectType</i>	Optional. Policy subject type. Valid options are: <ul style="list-style-type: none"> ■ <code>P</code>—Port. The default is <code>P</code>. ■ <code>O</code>—Not supported in this release.

14.3.13.3 Example

The following example enables the client policies `oracle/log_policy` and `oracle/wss_username_token_client_policy` of the port `JRFWssUsernamePort` of the Web module `WssUsernameClient`. The Web service is part of the application `jwsclient_1#1.1.0` for the server `soa1` in the domain `soainfra`.

```
wls:/wls-domain/serverConfig>enableWebServiceClientPolicies
('/soainfra/soa1/jwsclient_1#1.1.0','WssUsernameClient','wsconn',
'WssUsernameClient','JRFWssUsernamePort',
["oracle/log_policy", "oracle/wss_username_token_client_policy"], true )
```

The following example enables the client policies `oracle/wss10_saml20_token_client_policy` and `oracle/wss11_message_protection_client_policy` of the port `UpperCaseImplPort` of the Java EE Web service module `owsm_mbean.resouce_pattern.web.ClientJWS/sei2`.

```
wls:/wls-domain/serverConfig>enableWebServiceClientPolicies('/wls-domain/AdminServer/ClientJWS',
'owsm_mbean.resouce_pattern.web.ClientJWS/sei2','wls','owsm_mbean.resouce_
pattern.web.ClientJWS/sei2','
'UpperCaseImplPort',["oracle/wss10_saml20_token_client_policy","oracle/wss11_
message_protection_client_policy"], true)
```

14.3.14 detachWebServiceClientPolicy

Command Category: Policy Management

Use with WLST: Online

14.3.14.1 Description

Detach a policy from a Web service client port of an application or SOA composite.

Note: Policy changes made using this WLST command are only effective after you restart your application. For ADF and WebCenter applications, a message is displayed to remind you to restart your application.

14.3.14.2 Syntax

```
detachWebServiceClientPolicy(application,moduleOrCompName,moduleType,
serviceRefName, portInfoName, policyURI, [subjectType=None] )
```

Argument	Definition
<i>application</i>	Name and path of the application for which you want to detach a policy from a Web service client port. For example, <code>/domain/server/application#version_number</code> To detach a policy from a client port of a Web service application, this argument is required.
<i>moduleOrCompName</i>	Name of the Web module or SOA composite (for example <code>HelloWorld[1.0]</code>) for which you want to detach the policy from a client port. To detach a policy from a client port of a SOA composite, the composite name is required (for example <code>default/HelloWorld[1.0]</code>), and the <code>moduleType</code> argument must be set to <code>soa</code> .
<i>moduleType</i>	Module type. Valid options are: <ul style="list-style-type: none"> ■ <code>soa</code>—SOA composite. ■ <code>web</code>—Oracle Infrastructure Web Services packaged as a Web module (including an EJB). ■ <code>wls</code>—Java EE Web services. ■ <code>wscconn</code>—Use with a connection-based Web service client such as an ADF DC Web service client, ADF JAX-WS Indirection Proxy, or WebCenter client.
<i>serviceRefName</i>	The service reference name of the application or composite.
<i>portInfoName</i>	The client port from which you want to detach the Oracle WSM client policy.
<i>policyURI</i>	The Oracle WSM policy name URI, for example <code>"oracle/wss_username_token_client_policy"</code> If the policy specified is not attached, an error message is displayed and/or an exception is thrown.
<i>subjectType</i>	Optional. Policy subject type. Valid options are: <ul style="list-style-type: none"> ■ <code>P</code>—Port. The default is <code>P</code>. ■ <code>O</code>—Not supported in this release.

14.3.14.3 Examples

The following example detaches the client policy `oracle/wss_username_token_client_policy` from the port `JRFWssUsernamePort` of the Web module `WssUsernameClient`. The Web service is part of the application `jwsclient_1#1.1.0` for the server `soa1` in the domain `soainfra`.

```
wls:/wls-domain/serverConfig>detachWebServiceClientPolicy
('/soainfra/soa1/jwsclient_1#1.1.0','WssUsernameClient','wscconn',
'WssUsernameClient','JRFWssUsernamePort','oracle/wss_username_token_client_
policy')
```

The following example detaches the client policy `oracle/log_policy` from the client port `HelloWorld_pt` in the SOA composite `default/HelloWorld[1.0]`.

```
wls:/wls-domain/serverConfig>detachWebServiceClientPolicy(None,
'default/HelloWorld[1.0]','soa','client','HelloWorld_pt','oracle/log_policy' )
```

The following command detaches the client policy `oracle/wss_username_token_client_policy` from the client port `UpperCaseImplPort` in the Java EE client module `wsm_mbean.resouce_pattern.web.ClientJWS/sei2`.

```
wls:/wls-domain/serverConfig>
detachWebServiceClientPolicy('/wls-domain/AdminServer/ClientJWS', 'owsm_
mbean.resouce_pattern.web.ClientJWS/sei2', 'wls', 'owsm_mbean.resouce_
pattern.web.ClientJWS/sei2', 'UpperCaseImplPort', "oracle/wss_username_token_
client_policy")
```

14.3.15 detachWebServiceClientPolicies

Command Category: Policy Management

Use with WLST: Online

14.3.15.1 Description

Detach multiple policies from a Web service client port of an application or SOA composite.

Note: Policy changes made using this WLST command are only effective after you restart your application. For ADF and WebCenter applications, a message is displayed to remind you to restart your application.

14.3.15.2 Syntax

```
detachWebServiceClientPolicies(application,moduleOrCompName,moduleType,
serviceRefName,portInfoName,policyURIs, [subjectType=None] )
```

Argument	Definition
<i>application</i>	Name and path of the application for which you want to detach multiple policies from a Web service client port. For example, /domain/server/application#version_number To detach multiple policies from a client port of a Web service application, this argument is required.
<i>moduleOrCompName</i>	Name of the Web module or SOA composite (for example HelloWorld[1.0]) for which you want to detach multiple policies from a client port. To detach multiple policies from a client port for a SOA composite, the composite name is required (for example default/HelloWorld[1.0]), and the <i>moduleType</i> argument must be set to <i>soa</i> .
<i>moduleType</i>	Module type. Valid options are: <ul style="list-style-type: none"> ■ <i>soa</i>—SOA composite. ■ <i>web</i>—Oracle Infrastructure Web Services packaged as a Web module (including an EJB). ■ <i>wls</i>—Java EE Web services. ■ <i>wconn</i>—Use with a connection-based Web service client such as an ADF DC Web service client, ADF JAX-WS Indirection Proxy, or WebCenter client.
<i>serviceRefName</i>	The service reference name of the application or composite.
<i>portInfoName</i>	The client port from which you want to detach the Oracle WSM client policy.

Argument	Definition
<i>policyURI</i>	The Oracle WSM policy name URI, for example "oracle/wss_username_token_client_policy" If the policy specified is not attached, an error message is displayed and/or an exception is thrown.
<i>subjectType</i>	Optional. Policy subject type. Valid options are: <ul style="list-style-type: none"> ■ P—Port. The default is P. ■ O—Not supported in this release.

14.3.15.3 Example

The following example detaches the client policies `oracle/log_policy` and `oracle/wss_username_token_client_policy` from the port `JRFWssUsernamePort` of the Web module `WssUsernameClient`. The Web service is part of the application `jwsclient_1#1.1.0` for the server `soa1` in the domain `soainfra`.

```
wls:/wls-domain/serverConfig>detachWebServiceClientPolicies
('/soainfra/soa1/jwsclient_1#1.1.0','WssUsernameClient','wsconn',
'WssUsernameClient','JRFWssUsernamePort',
["oracle/log_policy","oracle/wss_username_token_client_policy"])
```

The following example detaches the client policies `oracle/wss10_saml20_token_client_policy` and `oracle/wss11_message_protection_client_policy` of the port `UpperCaseImplPort` of the Java EE Web service module `owsm_mbean.resouce_pattern.web.ClientJWS/sei2`.

```
wls:/wls-domain/serverConfig>detachWebServiceClientPolicies('/wls-domain/AdminServer/ClientJWS',
'owsm_mbean.resouce_pattern.web.ClientJWS/sei2','wls','owsm_mbean.resouce_
pattern.web.ClientJWS/sei2',
'UpperCaseImplPort',["oracle/wss10_saml20_token_client_policy","oracle/wss11_
message_protection_client_policy"])
```

14.3.16 setWebServicePolicyOverride

Command Category: Policy Management

Use with WLST: Online

14.3.16.1 Description

Configure the Web service port policy override properties of an application or SOA composite.

14.3.16.2 Syntax

```
setWebServicePolicyOverride(application,moduleOrCompName,moduleType, serviceName,
portName,policyURI,properties)
```

Argument	Definition
<i>application</i>	Name and path of the application for which you want to override the Web service port policy. For example, <code>/domain/server/application#version_number</code> To override properties on a policy attached to a port of a Web service application, this argument is required.

Argument	Definition
<i>moduleOrCompName</i>	Name of the Web module or SOA composite (for example HelloWorld[1.0]) for which you want to override a Web service port policy. To override properties on a policy attached to a SOA composite, the composite name is required (for example default/HelloWorld[1.0]), and the <i>moduleType</i> argument must be set to <i>soa</i> .
<i>moduleType</i>	Module type. Valid options are: <ul style="list-style-type: none"> ■ <i>soa</i>—SOA composite. ■ <i>web</i>—Oracle Infrastructure Web Services packaged as a Web module (including an EJB). ■ <i>wls</i>—Java EE Web services.
<i>serviceName</i>	Name of the Web service in the application or SOA composite. For example, {http://namespace/}serviceName. Note that the namespace ({http://namespace/}) should not be included for a SOA composite.
<i>subjectName</i>	Name of the policy subject, port, or operation.
<i>policyURI</i>	Oracle WSM policy name URI, for example 'oracle/log_policy' to which the override properties will be applied. If the policy specified is not attached, an error message is displayed and/or an exception is thrown.
<i>properties</i>	Policy override properties. Properties must be specified using the following format: [("name", "value")] For example: [("myprop", "myval")] If this argument is set to <i>None</i> , then all policy overrides are removed.

14.3.16.3 Examples

The following example configures the override properties for the policy `oracle/wss10_message_protection_service_policy` for the port `JRFWssUsernamePort` of the Web module `WssUsernameService`. The Web service is part of the application `HelloWorld#1_0` for the server `soa1` in the domain `soainfra`.

```
wls:/wls-domain/serverConfig>setWebServicePolicyOverride
('/soainfra/soa1/HelloWorld#1_0','j2wbasicPolicy',
'web',{http://namespace/}WssUsernameService','JRFWssUsernamePort',
"oracle/wss10_message_protection_service_policy",
[("keystore.sig.csf.key","sigkey")])
```

The following example configures the override properties for the policy `oracle/wss10_message_protection_service_policy` for the port `SimplePort` of the Java EE Web module `SimpleEjbService`. The Java EE Web service is part of the application `SimpleJAXWS` for the server `AdminServer` in the domain `wls-domain`.

```
wls:/wls-domain/serverConfig>setWebServicePolicyOverride('/wls-domain/AdminServer/
SimpleJAXWS',
'SimpleJAXWS#1!SimpleEjbService','wls','SimpleEjbService','SimplePort',
"oracle/wss10_message_protection_service_
policy",[("keystore.sig.csf.key","sigkey")])
```

14.4 Policy Set Management Commands

Policy sets enhance the security and manageability of an enterprise by providing a mechanism to globally attach one or more policies to a subject type. Using policy sets, an administrator can specify a default set of policies to be enforced even if none are directly attached. For detailed information about determining the type and scope of resources to which a policy set can be attached, see "Creating and Managing Policy Sets" in the *Oracle Fusion Middleware Security and Administrator's Guide for Web Services*.

All policy set creation, modification, or deletion commands must be performed in the context of a repository session. A repository session can only act on a single document.

Note: The commands in this section apply to Oracle Infrastructure Web Services only.

To view the help for the WLST commands described in this section, connect to a running instance of the server and enter `help('wsmManage')`.

Use the WLST commands listed in [Table 14-4](#) to manage Oracle WSM Web service policy sets for globally attached policies.

Table 14-4 Web Services WLST Policy Set Management Commands

Use this command...	To...	Use with WLST...
<code>abortRepositorySession</code>	Abort the current Oracle WSM Repository modification session, discarding any changes that were made to the repository during the session.	Online
<code>attachPolicySet</code>	Attach a policy set to the specified resource scope.	Online
<code>attachPolicySetPolicy</code>	Attach a policy to a policy set using the policy's URI.	Online
<code>beginRepositorySession</code>	Begin a session to modify the Oracle WSM Repository.	Online
<code>clonePolicySet</code>	Clone a new policy set from an existing policy set.	Online
<code>commitRepositorySession</code>	Write the contents of the current session to the Oracle WSM repository.	Online
<code>createPolicySet</code>	Create a new, empty policy set.	Online
<code>deleteAllPolicySets</code>	Delete all or selected policy sets from within the Oracle WSM repository.	Online
<code>deletePolicySet</code>	Delete a specified policy set.	Online
<code>describeRepositorySession</code>	Describe the contents of the current repository session.	Online
<code>detachPolicySetPolicy</code>	Detach a policy from a policy set using the policy's URI.	Online
<code>displayPolicySet</code>	Display the configuration of a specified policy set.	Online
<code>enablePolicySet</code>	Enable or disable a policy set.	Online

Table 14–4 (Cont.) Web Services WLST Policy Set Management Commands

Use this command...	To...	Use with WLST...
<code>enablePolicySetPolicy</code>	Enable or disable a policy attachment for a policy set using the policy's URI.	Online
<code>listPolicySets</code>	List the policy sets in the repository.	Online
<code>migrateAttachments</code>	Migrate direct policy attachments to global policy attachments if they are identical.	Online
<code>modifyPolicySet</code>	Specify an existing policy set for modification in the current session.	Online
<code>setPolicySetConstraint</code>	Specify a run-time constraint value for a policy set selected within a session.	Online
<code>setPolicySetPolicyOverride</code>	Add a configuration override to a policy reference in the current policy set.	Online
<code>setPolicySetDescription</code>	Specify a description for the policy set selected within a session.	Online
<code>validatePolicySet</code>	Validate an existing policy set in the repository or in a session.	Online

14.4.1 abortRepositorySession

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Policy Set Management

Use with WLST: Online

14.4.1.1 Description

Abort the current Oracle WSM Repository modification session, discarding any changes that were made to the repository during the session.

14.4.1.2 Syntax

```
abortRepositorySession()
```

14.4.1.3 Example

The following example aborts the current Oracle WSM Repository session.

```
wls:/wls-domain/serverConfig>abortRepositorySession()
```

14.4.2 attachPolicySet

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Policy Set Management

Use with WLST: Online

14.4.2.1 Description

Within a repository session, set an expression that attaches a policy set to the specified resource scope. The expression must define a valid resource scope in a supported format.

Issuing this command outside of a repository session containing a policy set that is being created or modified will result in an error.

14.4.2.2 Syntax

```
attachPolicySet (expression)
```

Argument	Definition
<i>expression</i>	Expression that attaches the policy set to the specified resource scope. For details about specifying the resource scope expression, see "Resource Scope" in <i>Oracle Fusion Middleware Security and Administrator's Guide for Web Services</i> .

14.4.2.3 Example

The following example attaches a policy set to the specified `base_domain` resource.

```
wls:/wls-domain/serverConfig>attachPolicySet('Domain("base_domain")')
```

This example attaches a policy set to the specified `base_domain` **and** `managed_server` resources.

```
wls:/wls-domain/serverConfig>attachPolicySet('Domain("base_domain") and Server("managed_server")')
```

14.4.3 attachPolicySetPolicy

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Policy Set Management

Use with WLST: Online

14.4.3.1 Description

Within a repository session, attach a policy, identified by a specified URI, to the current policy set.

Issuing this command outside of a repository session containing a policy set that is being created or modified will result in an error.

14.4.3.2 Syntax

```
attachPolicySetPolicy(uri)
```

Argument	Definition
<i>uri</i>	URI specifying the policy to attach to the current policy set. For example, 'oracle/log_policy'.

14.4.3.3 Example

The following example attaches the Oracle WSM logging policy to the current policy set.

```
wls:/wls-domain/serverConfig>attachPolicySetPolicy('oracle/log_policy')
```

14.4.4 beginRepositorySession

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Policy Set Management

Use with WLST: Online

14.4.4.1 Description

Begin a session to modify the Oracle WSM Repository. A repository session can only act on a single document. An error will be displayed if there is already a current session.

14.4.4.2 Syntax

```
beginRepositorySession()
```

14.4.4.3 Example

The following example begins an Oracle WSM Repository modification session.

```
wls:/wls-domain/serverConfig>beginRepositorySession()
```

14.4.5 clonePolicySet

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Policy Set Management

Use with WLST: Online

14.4.5.1 Description

Within a repository session, clone a new policy set from an existing policy set. When cloning an existing policy set, all values and attachments in the source policy set are copied into the new policy set, although you can supply a different expression identifying the resource scope. The expression must define a valid resource scope in a supported format.

Issuing this command outside of a repository session will result in an error.

14.4.5.2 Syntax

```
clonePolicySet(name, source, [attachTo=None], [description=None], [enable='true'])
```

Argument	Definition
<i>name</i>	Name of the new policy set clone.
<i>source</i>	Name of the source policy set that will be cloned.
<i>attachTo=None</i>	Optional. Expression that attaches the policy set to the specified resource scope. For details about specifying the resource scope expression, see "Resource Scope" in <i>Oracle Fusion Middleware Security and Administrator's Guide for Web Services</i> . If this argument is set to <i>None</i> , then the expression used in the source policy set to identify the scope of resources is retained.
<i>description=None</i>	Optional. Description for the new policy set. If this argument is set to <i>None</i> , then the description used in the source policy set is retained.
<i>enable='true'</i>	Optional. Specifies whether to enable or disable the policy set. Valid options are: <ul style="list-style-type: none"> ▪ <i>true</i>—Enables the policy set. The default is <i>true</i>. ▪ <i>false</i>—Disables the policy set. If you omit this argument, the policy set is enabled.

14.4.5.3 Example

The first example creates a policy set by cloning the existing *myPolicySet* policy set to create a new *mynewPolicySet*. The second example also creates a policy set, but narrows the resource scope to policy subjects in the specified *soa_server1* server in the domain.

```
wls:/wls-domain/serverConfig>clonePolicySet('myNewPolicySet','myPolicySet')
wls:/wls-domain/serverConfig>clonePolicySet('myNewPolicySet','myPolicySet','Server
("soa_server1")')
```

14.4.6 commitRepositorySession

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Policy Set Management

Use with WLST: Online

14.4.6.1 Description

Write the contents of the current session to the Oracle WSM Repository. Messages are displayed that describe what was committed. An error will be displayed if there is no current session.

14.4.6.2 Syntax

```
commitRepositorySession()
```

14.4.6.3 Example

The following example commits the current repository modification session.

```
wls:/wls-domain/serverConfig>commitRepositorySession()
```

14.4.7 createPolicySet

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Policy Set Management

Use with WLST: Online

14.4.7.1 Description

Create a new, empty policy set within a repository session. When creating a new policy set, you must specify the type of policy subject that the policy set will apply to, and a supported expression that defines a valid resource scope in a supported format.

Issuing this command outside of a repository session will result in an error.

14.4.7.2 Syntax

```
createPolicySet(name, type,attachTo,[description=None],[enable='true'])
```

Argument	Definition
<i>name</i>	Name of the new, empty policy set.
<i>type</i>	The type of policy subject to which the new policy set applies. The type of policy subject must be one of the following values: <ul style="list-style-type: none"> ▪ <code>rest-resource</code>—RESTful Resource ▪ <code>sca-component</code>—SOA Component ▪ <code>sca-reference</code>—SOA Reference ▪ <code>sca-service</code>—SOA Service ▪ <code>ws-service</code>—Web Service Endpoint ▪ <code>ws-client</code>—Web Service Client ▪ <code>ws-connection</code>—Web Service Connection ▪ <code>ws-callback</code>—Asynchronous Callback Client
<i>attachTo</i>	Expression that attaches the policy set to the specified resource scope. For details about specifying the resource scope expression, see "Resource Scope" in <i>Oracle Fusion Middleware Security and Administrator's Guide for Web Services</i> .
<i>description</i>	Optional. Description of the new policy set. If no description is specified, then the description for a new policy set will be "Global policy attachments for <type>", where <type> is the subject type.
<i>enable</i>	Optional. Specifies whether to enable or disable the new policy set. Valid options are: <ul style="list-style-type: none"> ▪ <code>true</code>—Enables the new policy set. The default is <code>true</code>. ▪ <code>false</code>—Disables the new policy set. If you omit this argument, the policy set is enabled.

14.4.7.3 Example

The first example creates a new policy set and specifies the resource scope to only `ws-service` types (Web Service Endpoint) in the `base_domain` domain. The second

example creates a new policy set, but also narrows the resource scope to only `sca-service` types (SOA Service) in the `soa_server1` server in the domain.

```
wls:/wls-domain/serverConfig>createPolicySet('myPolicySet','ws-service','Domain("base_domain")')
wls:/wls-domain/serverConfig>createPolicySet('myPolicySet','sca-service','Server("soa_server1")','My_policySet')
```

14.4.8 deleteAllPolicySets

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Policy Set Management

Use with WLST: Online

14.4.8.1 Description

Delete all or selected policy sets from within the Oracle WSM repository. You can specify whether to force deletion of all the policy sets, or prompt to select individual policy sets for deletion. If deletion of any policy set fails then this operation throws an exception and no policy sets are deleted.

14.4.8.2 Syntax

```
deleteAllPolicySets([mode])
```

Argument	Definition
<i>mode</i>	Optional. The action to be taken for performing policy set deletion. Valid options are: <ul style="list-style-type: none"> ▪ <code>force</code>—Automatically delete all policy sets without prompting. ▪ <code>prompt</code>—Request user confirmation for each policy set deletion. Available options are <code>yes</code>, <code>no</code>, and <code>cancel</code>. If you select <code>cancel</code> for any property set deletion, the operation is canceled and no policy sets are deleted. <p>If no mode is specified, this argument defaults to <code>prompt</code> mode.</p>

14.4.8.3 Examples

The following example automatically deletes all policy sets from the repository without prompting.

```
wls:/jrfServer_domain/serverConfig> deleteAllPolicySets("force")
```

```
Starting Operation deleteAllPolicySets ...
```

```
All policy sets were deleted successfully from repository.
```

```
deleteAllPolicySets Operation Completed.
```

The following examples delete selected policy sets from the repository.

```
wls:/jrfServer_domain/serverConfig> deleteAllPolicySets()
```

or


```
wls:/jrfServer_domain/serverConfig> deleteAllPolicySets('prompt')

Starting Operation deleteAllPolicySets ...

Policy Set Name: create_policyset_6
Select "create_policyset_6" for deletion (yes/no/cancel)? no
Policy Set Name: create_policyset_8
Select "create_policyset_8" for deletion (yes/no/cancel)? yes
Policy Set Name: create_policyset_21
Select "create_policyset_21" for deletion (yes/no/cancel)? no
Policy Set Name: create_policyset_10
Select "create_policyset_10" for deletion (yes/no/cancel)? yes

All the selected policy sets were deleted successfully from repository.

deleteAllPolicySets Operation Completed.
```

14.4.9 deletePolicySet

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Policy Set Management

Use with WLST: Online

14.4.9.1 Description

Delete a specified policy set within a repository session. If the session already contains a different policy set, an error will display. If the session already contains the named policy set, then a creation will be undone or a modification will be converted into a deletion.

Issuing this command outside of a repository session will result in an error.

14.4.9.2 Syntax

```
deletePolicySet (name)
```

Argument	Definition
<i>name</i>	Name of the policy set to be deleted.

14.4.9.3 Example

The following example deletes a specified *myPolicySet* policy set.

```
wls:/wls-domain/serverConfig> deletePolicySet('myPolicySet')
```

14.4.10 describeRepositorySession

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Policy Set Management

Use with WLST: Online

14.4.10.1 Description

Describe the contents of the current session. This will either indicate that the session is empty or list the name of the document that is being updated, along with the type of update (create, modify, or delete). An error will be displayed if there is no current session.

14.4.10.2 Syntax

```
describeRepositorySession()
```

14.4.10.3 Example

The following example describes the current repository modification session.

```
wls:/wls-domain/serverConfig>describeRepositorySession()
```

14.4.11 detachPolicySetPolicy

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Policy Set Management

Use with WLST: Online

14.4.11.1 Description

Within a repository session, detach a policy, identified by a specified URI, from the current policy set.

Issuing this command outside of a repository session containing a policy set that is being created or modified will result in an error.

14.4.11.2 Syntax

```
detachPolicySetPolicy(uri)
```

Argument	Definition
<i>uri</i>	URI specifying the policy to detach to the current policy set. For example, <code>oracle/log_policy</code> '.

14.4.11.3 Example

The following example detaches the Oracle WSM logging policy from the current policy set.

```
wls:/wls-domain/serverConfig>detachPolicySetPolicy('oracle/log_policy')
```

14.4.12 displayPolicySet

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Policy Set Management

Use with WLST: Online

14.4.12.1 Description

Display the configuration of a specified policy set. If the policy set is being modified in the current session, then that version will be displayed; otherwise, the latest version in the repository will be displayed. An error will display if the policy set does not exist.

This command can be issued outside of a repository session.

14.4.12.2 Syntax

```
displayPolicySet([name])
```

Argument	Definition
<i>name</i>	Optional. Name of the policy set to be displayed. If a name is not specified, the configuration of the policy set, if any, in the current session is displayed or an error message is displayed.

14.4.12.3 Example

The following example displays the configuration of the *myPolicySet* policy set.

```
wls:/wls-domain/serverConfig>displayPolicySet('myPolicySet')
```

14.4.13 enablePolicySet

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Policy Set Management

Use with WLST: Online

14.4.13.1 Description

Enable or disable the current policy set within a repository session. If not specified, this command enables the policy set.

Issuing this command outside of a repository session containing a policy set that is being created or modified will result in an error.

14.4.13.2 Syntax

```
enablePolicySet([enable=True])
```

Argument	Definition
<i>enable</i>	Optional. Specifies whether to enable or disable the policy set. Valid options are: <ul style="list-style-type: none"> ■ <code>true</code>—Enables the policy set. The default is <code>true</code>. ■ <code>false</code>—Disables the policy set. If you omit this argument, the policy set is enabled.

14.4.13.3 Example

The following example enables the current policy set.

```
wls:/wls-domain/serverConfig>enablePolicySet(true)
```

14.4.14 enablePolicySetPolicy

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Policy Set Management

Use with WLST: Online

14.4.14.1 Description

Within a repository session, enable or disable the policy attachment, which is identified by the provided URI in the current policy set. If not specified, this command enables the policy set. An error displays if the identified policy is not currently attached to the policy set.

Issuing this command outside of a repository session containing a policy set that is being created or modified will result in an error.

14.4.14.2 Syntax

```
enablePolicySetPolicy(uri, [enable=true])
```

Argument	Definition
<i>uri</i>	URI specifying the policy attachment within the policy set.
<i>enable</i>	Optional. Specifies whether to enable or disable the policy attachment specified by the URI in the policy set. Valid options are: <ul style="list-style-type: none"> ▪ <code>true</code>—Enables the specified policy attachment in the policy set. The default is <code>true</code>. ▪ <code>false</code>—Disables specified policy attachment in the policy set. If you omit this argument, the policy set attachment is enabled.

14.4.14.3 Example

The following example disables the specified logging policy attachment within the current policy set.

```
wls:/wls-domain/serverConfig>enablePolicySetPolicy('/oracle/log_policy', false)
```

14.4.15 listPolicySets

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Policy Set Management

Use with WLST: Online

14.4.15.1 Description

Lists the policy sets in the repository. This command will also display a policy set that is being created, modified, or deleted within the current session. You can list all the policy sets or limit the display to include only those that apply to specific policy subject resource types.

14.4.15.2 Syntax

```
listPolicySets([type=None])
```

Argument	Definition
<i>type=None</i>	<p>Optional. Specifies the type of policy sets to be displayed. The policy subject resource type must be one of the following values:</p> <ul style="list-style-type: none"> ▪ <i>sca-component</i>—SOA Component ▪ <i>sca-reference</i>—SOA Reference ▪ <i>sca-service</i>—SOA Service ▪ <i>ws-service</i>—Web Service Endpoint ▪ <i>ws-client</i>—Web Service Client ▪ <i>ws-connection</i>—Web Service Connection ▪ <i>ws-callback</i>—Asynchronous Callback Client <p>If this argument is set to <i>None</i>, then all the policy sets stored in the repository will be listed.</p>

14.4.15.3 Example

The first two examples list policy sets by either the *sca-reference* or *ws-client* resource types. Whereas, the third example lists all the policy sets stored in the repository.

```
wls:/wls-domain/serverConfig>listPolicySets('sca-reference')
wls:/wls-domain/serverConfig>listPolicySets('ws-client')
wls:/wls-domain/serverConfig>listPolicySets()
```

14.4.16 migrateAttachments

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Policy Set Management

Use with WLST: Online

14.4.16.1 Description

Migrates direct (local) policy attachments that are identical to the external global policy attachments that would otherwise be attached to each policy subject in the current domain. You can specify whether to force the migration, prompt for confirmation before each migration, or simply list the migrations that would occur. A direct policy attachment is identical if its URI is the same as one provided by a global policy attachment, and if it does not have any scoped configuration overrides.

Note: A direct attachment with an unscoped override will be migrated but an attachment with a scoped override will not. This is because after running the `migrateAttachments()` command, the enforcement of the policies on *all* subjects remains the same, even though some policies are globally attached.

Whether forced or prompted, the command lists each direct policy attachment that is migrated. This output will identify the policy subject that was modified, the URI of the identical policy reference, and the name of the global policy attachment document that duplicated the direct attachment.

14.4.16.2 Syntax

```
migrateAttachments([mode])
```

Argument	Definition
<i>mode</i>	<p>The action to be taken for each policy attachment that can be migrated. Valid options are:</p> <ul style="list-style-type: none"> ▪ <code>force</code>—Automatically migrate all identical policy attachments without prompting. ▪ <code>preview</code>—List all policy attachments that can be migrated, but does not perform any migration. ▪ <code>prompt</code>—Request user confirmation before migrating each policy attachment. <p>If no mode is specified, this argument defaults to <code>prompt</code> mode.</p>

14.4.16.3 Example

The following examples describe how to use the repository attachment migration modes.

```
wls:/wls-domain/serverConfig>migrateAttachments()
wls:/wls-domain/serverConfig>migrateAttachments('force')
wls:/wls-domain/serverConfig>migrateAttachments('preview')
wls:/wls-domain/serverConfig>migrateAttachments('prompt')
```

14.4.17 modifyPolicySet

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Policy Set Management

Use with WLST: Online

14.4.17.1 Description

Specify a policy set for modification in the current repository session. The latest version of the named policy set will be loaded into the current session. If the session already contains a different policy set, then an error will be displayed; if the session already contains the named policy set, then no action will be taken. Subsequent attempts to modify the named policy set will show the current version in the session.

Issuing this command outside of a repository session will result in an error.

14.4.17.2 Syntax

```
modifyPolicySet (name)
```

Argument	Definition
<i>name</i>	Name of the policy set to be modified in the current session.

14.4.17.3 Example

The following example opens the *myPolicySet* policy set for modification in the current session.

```
wls:/wls-domain/serverConfig>modifyPolicySet('myPolicySet')
```

14.4.18 setPolicySetConstraint

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Policy Set Management

Use with WLST: Online

14.4.18.1 Description

Specify a run-time constraint value for a policy set selected within a session. Issuing this command outside of a repository session containing a policy set that is being created or modified will result in an error.

For more information, see "Specifying Run-time Constraints in Policy Sets" in *Oracle Fusion Middleware Security and Administrator's Guide for Web Services*.

14.4.18.2 Syntax

```
setPolicySetConstraint (constraint)
```

Argument	Definition
<i>constraint</i>	Expression that specifies the run-time context to which the policy set applies. If not specified, the policy set applies to all run-time contexts.

14.4.18.3 Example

The following example specifies that the policy set apply only to requests from external clients.

```
setPolicySetConstraint('HTTPHeader("VIRTUAL_HOST_TYPE","external")')
```

The following example specifies that the policy set apply only to requests from non-external clients.

```
setPolicySetConstraint('!HTTPHeader("VIRTUAL_HOST_TYPE","external")')
```

14.4.19 setPolicySetDescription

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Policy Set Management

Use with WLST: Online

14.4.19.1 Description

Specify a description for a policy set selected within a session.

Issuing this command outside of a repository session containing a policy set that is being created or modified will result in an error.

14.4.19.2 Syntax

```
setPolicySetDescription(description)
```

Argument	Definition
<i>description</i>	Describes a policy set.

14.4.19.3 Example

The following example creates a description for a policy set.

```
wls:/wls-domain/serverConfig>setPolicySetDescription('PolicySetDescription')
```

14.4.20 setPolicySetPolicyOverride

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Policy Set Management

Use with WLST: Online

14.4.20.1 Description

Add a configuration override, described by a *name*, *value* pair, to an attached policy reference in the current policy set. The *value* argument is optional. If the *value* argument is omitted, the property specified by the *name* argument is removed from the policy reference in the policy set. If the property specified by the *name* argument already exists and a *value* argument is provided, the current value is overwritten by the new value specified with the *value* argument.

Issuing this command outside of a repository session containing a policy set that is being created or modified results in an error.

14.4.20.2 Syntax

```
setPolicySetPolicyOverride(uri,name,[value=None])
```


Argument	Definition
<i>URI</i>	String representing the Oracle WSM policy URI, for example 'oracle/wss10_saml_token_service_policy' to which the override properties will be applied.
<i>name</i>	String representing the name of the override property. For example: ['reference.priority']
<i>value</i>	Optional. String representing the value of the property. If this argument is not specified, the property specified by the name argument, if it exists, is removed.

14.4.20.3 Example

The following example specifies a configuration override for the `reference.priority` property for the `oracle/wss10_saml_token_service_policy` to a value of 1.

```
setPolicySetPolicyOverride('oracle/wss10_saml_token_service_policy',
'reference.priority', '1')
```

The following example removes the property `reference.priority` from the `oracle/wss10_saml_token_service_policy` in the policy set.

```
setPolicySetPolicyOverride('oracle/wss10_saml_token_service_policy',
'reference.priority')
```

14.4.21 validatePolicySet

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Policy Set Management

Use with WLST: Online

14.4.21.1 Description

Validates an existing policy set. If a policy set name is provided, the command will validate the specified policy set. If no policy set name is specified, the command will validate the policy set in the current repository session.

An error message displays if the policy set does not exist, or a name is not provided and the session is not active, or if the Oracle WSM Repository does not contain a suitable policy set.

14.4.21.2 Syntax

```
validatePolicySet([name=None])
```

Argument	Definition
<i>name</i>	Optional. Name of the policy set to validate. If a name is not provided then the command will validate the policy set being created or modified in the current session.

14.4.21.3 Example

The first example validates the policy set in the current session. The second example validates the specified *myPolicySet* policy set.

```
wls:/wls-domain/serverConfig>validatePolicySet ()
wls:/wls-domain/serverConfig>validatePolicySet ('myPolicySet')
```

14.5 Oracle WSM Repository Management Commands

Use the commands listed in [Table 14–5](#) to manage the WSM documents stored in the Oracle WSM Repository. For additional information about upgrading or migrating documents in an Oracle WSM Repository, see "Upgrading the Oracle WSM Policies in the Repository" in the *Oracle Fusion Middleware Security and Administrator's Guide for Web Services*.

Additional MDS WLST commands are described in [Chapter 8, "Metadata Services \(MDS\) Custom WLST Commands."](#)

Table 14–5 Policy Repository Management Commands

Use this command...	To...	Use with WLST...
upgradeWSMPolicyRepository	Upgrade the Oracle WSM predefined policies stored in the Oracle WSM Repository with any new predefined policies that are provided in the latest installation of the Oracle Fusion Middleware software.	Online
resetWSMPolicyRepository	Delete the existing policies stored in the Oracle WSM Repository and refresh it with the latest set of predefined policies that are provided in the new installation of the Oracle Fusion Middleware software.	Online
exportRepository	Export a set of documents from the repository into a supported ZIP archive. If the specified archive already exists, you can choose whether to overwrite the archive or merge the documents into the existing archive.	Online
importRepository	Import a set of documents from a supported ZIP archive into the repository. You can provide the location of a file that describes how to map a physical information from the source environment to the target environment.	Online

14.5.1 upgradeWSMPolicyRepository

Command Category: Policy Repository Management

Use with WLST: Online

Note: In PS6 and later, after you install the latest patch set, the repository is automatically upgraded as part of server startup. You no longer need to execute the `upgradeWSMPolicyRepository` command.

14.5.1.1 Description

Upgrade the Oracle WSM predefined policies stored in the Oracle WSM Repository with any new predefined policies that are provided in the latest installation of the Oracle Fusion Middleware software. If the repository is empty, all of the predefined policies included in the installation are loaded into the repository.

When you execute this command, a message is displayed indicating the policies that have been added to the repository. Any predefined policy that has not been customized for your environment will be replaced. Note, however, that predefined policies that have been customized and user-defined custom policies in the repository are not replaced. To replace these policies also, use the `resetWSMPolicyRepository(true)` command.

The output message also displays a list of any existing predefined policies that Oracle has changed or discontinued in the latest release. If a policy has been discontinued and is no longer supported, Oracle recommends that you remove all references to it and then delete it using Oracle Enterprise Manager.

14.5.1.2 Syntax

```
upgradeWSMPolicyRepository()
```

14.5.1.3 Example

The following example upgrades the existing installation with policies provided in the latest release:

```
wls:/wls-domain/serverConfig>upgradeWSMPolicyRepository()
```

14.5.2 resetWSMPolicyRepository

Command Category: Policy Repository Management

Use with WLST: Online

14.5.2.1 Description

Delete the existing policies stored in the Oracle WSM Repository and refresh it with the latest set of predefined policies that are provided in the new installation of the Oracle Fusion Middleware software. You can use the `clearStore` argument to specify whether to delete all policies, including custom user policies, from the Oracle WSM Repository before loading the new predefined policies.

14.5.2.2 Syntax

```
resetWSMPolicyRepository([clearStore='false'])
```

Argument	Definition
<code>clearStore='false'</code>	<p>Policies to be deleted. Valid values are:</p> <ul style="list-style-type: none"> ▪ <code>true</code>—All policies in the repository, including custom user policies, are deleted. ▪ <code>false</code>—Only the predefined policies supplied by Oracle are deleted. The default is <code>false</code>.

14.5.2.3 Example

The following example deletes all the policies in the repository, including user policies, and adds the predefined policies provided in the current product installation:

```
wls:/wls-domain/serverConfig>resetWSMPolicyRepository(true)
```

14.5.3 exportRepository

Command Category: Policy Repository Management

Use with WLST: Online

14.5.3.1 Description

Export a set of documents from the Oracle WSM Repository into a supported ZIP archive. If the specified archive already exists, the following options are presented:

The specified archive already exists. Update existing archive?
Enter "yes" to merge documents into existing archive, "no" to overwrite, or "cancel" to cancel the operation.

You can also specify a list of the documents to be exported, or use a search expression to find specific documents in the repository.

14.5.3.2 Syntax

```
exportRepository(archive, [documents=None], [expandReferences='false'])
```

Argument	Definition
<i>archive</i>	Name of the archive file. If the specified archive already exists, you can choose whether to overwrite the archive or merge the documents into the existing archive. During override, the original archive is backed up and a message describes the location of the backup archive.
<i>documents=None</i>	Optional. The documents to be exported to the archive. If no documents are specified, then all assertion templates, intents, policies, and policy sets will be exported. You can specify a list of the documents to be exported, or use a search expression to find specific documents in the repository.
<i>expandReferences='false'</i>	Optional. Specifies whether the policy references should be expanded during export.

14.5.3.3 Example

The following examples describe repository export sessions. The first example exports all Oracle WSM documents to the `policies.zip` file.

```
wls:/wls-domain/serverConfig>exportRepository("/tmp/policies.zip")
```

This example exports only the `sca-component`, `sca-reference`, and `sca-service` policy sets to the `policies.jar` file, and also expands the all policy references output during the export process.

```
wls:/wls-domain/serverConfig>exportRepository("/tmp/policies.jar",
["/policysets/sca_component,/policysets/sca_reference,/policysets/sca_service"],
true)
```

This example exports policy sets using wildcards to the `some_global_with_noreference_2` file.

```
wls:/wls-domain/serverConfig>exportRepository('./export/some_global_with_
noreference_2',
['policysets:global/web_%','policysets:global/web_ref%', 'policysets:global/web_
call%'], false)
```

14.5.4 importRepository

Command Category: Policy Repository Management

Use with WLST: Online

14.5.4.1 Description

Import a set of documents from a supported ZIP archive into the Oracle WSM Repository. You can use the `map` argument to provide the location of a file that describes how to map physical information from the source environment to the target environment. For example, you can use the map file to ensure that the attachment expression in a policy set document is updated to match the target environment, such as `Domain("foo")=Domain("bar")`

14.5.4.2 Syntax

```
importRepository(archive, [map=None], [generateMapFile='false'])
```

Argument	Definition
<i>archive</i>	Path to the archive file that contains the list of documents to be imported. If a document being imported is a duplicate of the current version that already exists in the repository, then it will not be imported and a new version of the document is not created
<i>map=None</i>	Optional. Location of a sample map file that describes how to map physical information from the source environment to the target environment. You can generate a new map file by setting the <code>generateMapFile</code> argument to <code>true</code> . If you specify a map file without setting the <code>generateMapFile</code> argument to <code>true</code> , and the file does not exist, the operation fails and an error is displayed.
<i>generateMapFile=false</i>	Optional. Specify whether to create a sample map file at the location specified by the <code>map</code> argument. No documents are imported when this argument is set to <code>true</code> . The default is <code>false</code> . After the map file is created you can edit it using any text editor. The map file contains the document names given in the archive file and their corresponding <code>attachTo</code> values. The <code>attachTo</code> value can be updated to correspond to the new environment. If a mapping update is not required for a document name, that entry may be either deleted or commented out using the <code>#</code> character. Note: When importing documents into the repository, OWSM validates the <code>attachTo</code> values only. If a value is invalid, then the policy set is disabled. Other text in the map file is not validated.

14.5.4.3 Example

The following examples describe repository import sessions.

The first example imports the contents of the `policies.zip` file into the repository.

```
wls:/wls-domain/serverConfig>importRepository("/tmp/policies.zip")
```

This example uses the `generateMapFile` argument to generate a map file.

```
wls:/wls-domain/serverConfig>importRepository("./export/some_global_with_noreference_2', map='./export/some_global_with_noreference_2_map', generateMapFile=true)
```

Here is an example of a generated map file:

This is an auto generated override file containing the document names given in the archive file and their corresponding attachTo values. The attachTo value can be updated according to the new environment details. If there is no update required for any document name, that entry may be either deleted or commented using the character ("#")

```
[Resource Scope Mappings
]
sca_component_add_1=Composite("Async")
sca_reference_add_1=Composite("Basic_SOA_Client")
sca_reference_no=Server("")
sca_service_add_1=Composite("Basic_SOA_service")
web_callback_add_1=Application("")
web_client_add_1=Module("")
web_reference_add_1=Domain("")
web_service_add_1=Domain("domain") and Server("soa") and Application("ADF")
ws_service_no_1=Server("Admin")
```

This example illustrates how to import documents using a generated map file: /some_global_with_noreference_2_map.

```
wls:/wls-domain/serverConfig>importRepository('../export/export_all', 'export_all_map')
```

14.6 Deployment Descriptor Migration Commands

Use the commands listed in [Table 14–6](#) to migrate the ADF Business Components and WebCenter services proprietary deployment descriptor (PDD) files between environments, such as from test to production.

For additional information about using these commands, see "Managing Application Migration Between Environments" in the *Oracle Fusion Middleware Security and Administrator's Guide for Web Services*.

Note: These commands are deprecated and will be removed in a future release.

Table 14–6 Deployment Descriptor Migration Commands

Use this command...	To...	Use with WLST...
exportJRFWSApplicationPDD	Export an ADF Business Control or WebCenter application deployment descriptor to a Java Archive (JAR) file.	Online
importJRFWSApplicationPDD	Import an ADF Business Control or WebCenter Web service application deployment descriptor from the exported JAR file into a new environment, for example, a production environment or a scaled server instance in a cluster.	Online
savePddToAllAppInstancesInDomain	Import and save the ADF BC or WebCenter Web service application deployment descriptor from the exported JAR file into all of the server instances in the connected domain.	Online

14.6.1 exportJRFWSApplicationPDD

Command Category: Deployment descriptor migration

Use with WLST: Online

14.6.1.1 Description

Export an ADF Business Control or WebCenter application deployment descriptor to a Java Archive (JAR) file. If you do not specify a name for the JAR file, the output displays the default name and path to the JAR file.

Note: This command is deprecated and will be removed in a future release.

14.6.1.2 Syntax

```
exportJRFWSApplicationPDD(application,pddJarFileName=None)
```

Argument	Definition
<i>application</i>	Name and path of the application for which you want to export the configuration information. For example, <code>/domain/server/application#version</code>
<i>pddJarFileName</i>	Optional. User-specified name for the JAR file. The default is None. For example, <code>/tmp/myPDD.jar</code> .

14.6.1.3 Example

The following example exports the Web service PDD for the application ADFBCHelloWorld into a JAR file named `exportPDD.jar`.

```
wls:/wls-domain/serverConfig>exportJRFWSApplicationPDD
('/wls-domain/ManagedServer/ADFBCHelloWorld','/tmp/exportPDD.jar')

/tmp/exportPDD.jar
```

14.6.2 importJRFWSApplicationPDD

Command Category: Deployment descriptor migration

Use with WLST: Online

14.6.2.1 Description

Import an ADF Business Control or WebCenter Web service application deployment descriptor from the exported JAR file into a new environment, for example, a production environment or a scaled server instance in a cluster.

Notes: Changes made using this WLST command are only effective after you restart your application. After importing the deployment descriptor, a message is displayed to remind you to restart your application.

This command is deprecated and will be removed in a future release.

14.6.2.2 Syntax

```
importJRFWSApplicationPDD(application,pddJarFileName)
```

Argument	Definition
<i>application</i>	Fully qualified path and name of the application to which you want to import the configuration information. For example, /domain/server/application#version
<i>pddJarFileName</i>	Name of the JAR file that contains the PDD file to be imported. For example, /tmp/myPDD.jar

14.6.2.3 Example

The following example imports the Web service application deployment descriptor for the ADFBCHelloWorld application that has been migrated to the server ManagedServer2. The command uses the name of the JAR file that was generated when the exportJRFWSApplicationPDD command was executed.

```
wls:/wls-domain/serverConfig>importJRFWSApplicationPDD
('/wls-domain/ManagedServer2/ADFBCHelloWorld', '/tmp/exportPDD.jar')
```

```
application /wls-domain/ManagedServer2/ADFBCHelloWorld PDD has been reset,
please restart application now to uptake changes!
```

14.6.3 savePddToAllAppInstancesInDomain

Command Category: Deployment descriptor migration

Use with WLST: Online

14.6.3.1 Description

Import and save the ADF BC or WebCenter Web service application deployment descriptor from the exported JAR file into all of the server instances in the connected domain. You can also use the optional `restartApp` argument to restart the application automatically.

Note: This command is deprecated and will be removed in a future release.

14.6.3.2 Syntax

```
savePddToAllAppInstancesInDomain(applicationName,pddJarFileName,restartApp=true)
```

Argument	Definition
<i>applicationName</i>	Name of the application to which you want to import the configuration information. For example, application#version
<i>pddJarFileName</i>	Name of the JAR file that contains the PDD file to be imported. For example, /tmp/myPDD.jar
<i>restartApp</i>	Optional. Restart the application. Valid values are: <ul style="list-style-type: none"> ■ <code>true</code>—Restart the application automatically. The default is <code>true</code>. ■ <code>false</code>—Do not restart the application automatically.

14.6.3.3 Example

The following example imports the Web service application deployment descriptor for the ADFBCHelloWorld application that was previously exported into all of the servers in the domain, and restarts the application.


```
wls:/wls-domain/serverConfig>savePddToAllAppInstancesInDomain
'ADFBCHelloWorld', '/tmp/exportPDD.jar' , true

saving pdd to com.bea:ServerRuntime=ManagedServer,Name=ADFBCHelloWorld,
Location=ManagedServer,Type=ApplicationRuntime
saving pdd to com.bea:ServerRuntime=ManagedServer2,Name=ADFBCHelloWorld,
Location=ManagedServer2,Type=ApplicationRuntime
restarting application ADFBCHelloWorld
Stopping application ADFBCHelloWorld.
<Mar 24, 2010 10:50:07 AM PDT> <Info> <J2EE Deployment SPI> <BEA-260121>
<Initiating stop operation for application, ADFBCHelloWorld
[archive: null], to Cluster-1 .>
.Completed the stop of Application with status completed
Current Status of your Deployment:
Deployment command type: stop
Deployment State      : completed
Deployment Message    : no message
Starting application ADFBCHelloWorld.
<Mar 24, 2010 10:50:11 AM PDT> <Info> <J2EE Deployment SPI> <BEA-260121>
<Initiating start operation for application, ADFBCHelloWorld
[archive: null], to Cluster-1 .>
.Completed the start of Application with status completed
Current Status of your Deployment:
Deployment command type: start
Deployment State      : completed
Deployment Message    : no message
```

The following example imports the Web service application deployment descriptor for the ADFBCHelloWorld application that was previously exported into all of the servers in the domain, but does not restart the application automatically. This example shows the commands you need to enter to restart the application manually.

```
wls:/wls-domain/serverConfig>savePddToAllAppInstancesInDomain
('ADFBCHelloWorld', '/tmp/exportPDD.jar', false)

saving pdd to com.bea:ServerRuntime=ManagedServer,Name=ADFBCHelloWorld,
Location=ManagedServer,Type=ApplicationRuntime
saving pdd to com.bea:ServerRuntime=ManagedServer2,Name=ADFBCHelloWorld,
Location=ManagedServer2,Type=ApplicationRuntime
application ADFBCHelloWorld PDD has been reset, please restart application now
to uptake changes!

wls:/wls-domain/serverConfig> stopApplication('ADFBCHelloWorld')
wls:/wls-domain/serverConfig> startApplication('ADFBCHelloWorld')
```

14.7 Token Issuer Trust Configuration Commands

Use the WLST commands listed in [Table 14-7](#) to view and define trusted issuers, trusted distinguished name (DN) lists, and token attribute rule filters for SAML signing certificates.

Note: The commands in this section apply to Oracle Infrastructure Web Services only.

To view the help for the WLST commands described in this section, connect to a running instance of the server and enter `help('wsmManage')`.

Table 14–7 Web Services Token Issuer Trust Commands

Use this command...	To...	Use with WLST...
<code>deleteWSMTokenIssuerTrust</code>	Delete the entry for the issuer, including the DN list in it.	Online
<code>deleteWSMTokenIssuerTrustAttributeRule</code>	Delete a token attribute rule associated with a trusted DN.	Online
<code>displayWSMTokenIssuerTrust</code>	Display the names of the DN lists associated with a specified issuer.	Online
<code>setWSMTokenIssuerTrust</code>	Specify a trusted SAML issuer with a DN list.	Online
<code>setWSMTokenIssuerTrustAttributeFilter</code>	Specify the DN of a token signing certificate and a list of trusted users.	Online

14.7.1 deleteWSMTokenIssuerTrust

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Token Issuer Trust Configuration

Use with WLST: Online

14.7.1.1 Description

Delete the trusted issuer, including the DN list in it.

14.7.1.2 Syntax

```
deleteWSMTokenIssuerTrust (type, issuer)
```

Arguments	Definition
<code>issuer</code>	The name of the issuer whose trusted DN list will be deleted. The issuer will also be deleted.
<code>type</code>	You can set either <code>dns . sv</code> for the trusted SAML sender vouches client list or <code>dns . hok</code> for the trusted STS security token service server list.

14.7.1.3 Examples

In the following example, the issuer `www.yourcompany.com` and the DN list in the `dns . sv` trusted SAML sender vouches client list for the issuer are deleted:

```
deleteWSMTokenIssuerTrust ('dns.sv', 'www.yourcompany.com')
```

14.7.2 deleteWSMTokenIssuerTrustAttributeRule

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Token Issuer Trust Configuration

Use with WLST: Online

14.7.2.1 Description

Delete the token attribute rule associated with a trusted DN.

14.7.2.2 Syntax

```
deleteWSMTokenIssuerTrustAttributeRule(dn)
```

Arguments	Description
dn	The DN of the token signing certificate used as the identifier for the token rule that is to be deleted.

14.7.2.3 Examples

In the following example, the token attribute rule associated with the CN=weblogic, OU=Orakey Test Encryption Purposes Only, O=Oracle, C=US' trusted DN is deleted.

```
deleteWSMTokenIssuerTrustAttributeRule('CN=weblogic, OU=Orakey Test Encryption Purposes Only, O=Oracle, C=US')
```

14.7.3 displayWSMTokenIssuerTrust

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Token Issuer Trust Configuration

Use with WLST: Online

14.7.3.1 Description

Display the names of the DN lists associated with a specified issuer for a given type. The `issuer` argument is optional. If `issuer` is not set, then the list of trusted issuers is displayed.

14.7.3.2 Syntax

```
displayWSMTokenIssuerTrust(type, issuer)
```

Arguments	Definition
type	Name of the DN list to display. You can set either <code>dns.sv</code> for the trusted SAML sender vouches client list or <code>dns.hok</code> for the trusted STS security token service server list.
issuer	Optional. The name of the issuer whose trusted DN list is displayed. If not set, the list of all the trusted issuers is displayed.

14.7.3.3 Examples

In the following example, the DN lists in the `dns.sv` trusted SAML sender vouches client list for the `www.oracle.com` trusted issuer are displayed:

```
displayWSMTokenIssuerTrust('dns.sv', 'www.oracle.com')
```

In the following example, the names of all trusted SAML issuers associated with the `dns.sv` trusted SAML sender vouches client list are displayed:

```
displayWSMTokenIssuerTrust('dns.sv', None)
```

14.7.4 setWSMTokenIssuerTrust

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Token Issuer Trust Configuration

Use with WLST: Online

14.7.4.1 Description

Specify a trusted SAML issuer with a DN list. The `trustedDNs` argument is optional. If you do not set this argument, only the trusted issuer will be set for the specified type.

This command can be used to specify the DN list associated with a trusted SAML issuer, update the list, or delete the list. See the following examples.

14.7.4.2 Syntax

```
setWSMTokenIssuerTrust(type, issuer, trustedDns)
```

Argument	Definition
<code>issuer</code>	The name of the trusted issuer, for example <code>www.oracle.com</code> .
<code>type</code>	The name of the DN list to set. You can set either <code>dns.sv</code> for the trusted SAML sender vouches client list or <code>dns.hok</code> for the trusted STS security token service server list.
<code>trustedDNs</code>	Optional. A list of DN values. This is a comma-separated list with the format <code>['CN=name1', 'CN=name2', 'CN=name3', ...]</code> . If you enter an empty set (<code>[]</code>) the list of DN values will be deleted for the issuer.

14.7.4.3 Examples

In the following example, `CN=weblogic, OU=Orakey Test Encryption Purposes Only, O=Oracle, C=US` is set as a DN in the `dns.sv` DN list for the `www.oracle.com` trusted issuer:

```
setWSMTokenIssuerTrust('dns.sv', 'www.oracle.com', ['CN=weblogic, OU=Orakey Test Encryption Purposes Only, O=Oracle, C=US'])
```

In the following example, the name `CN=orcladmin, OU=Doc, O=Oracle, C=US` is added to the `dns.sv` DN list for the `www.oracle.com` trusted issuer:

```
setWSMTokenIssuerTrust('dns.sv', 'www.oracle.com', ['CN=weblogic, OU=Orakey Test Encryption Purposes Only, O=Oracle, C=US', 'CN=orcladmin, OU=Doc, O=Oracle, C=US'])
```

In the following example, the list of DN values in the `dns.sv` DN list is removed from the `www.oracle.com` trusted issuer:

```
setWSMTokenIssuerTrust('dns.sv', 'www.oracle.com', [])
```

14.7.5 setWSMTokenIssuerTrustAttributeFilter

Note: This command applies to Oracle Infrastructure Web services only.

Command Category: Token Issuer Trust Configuration

Use with WLST: Online

14.7.5.1 Description

Specify token attribute rules for a trusted DN list. For each trusted DN configured for an issuer, a token attribute rule can be configured and applied.

Each rule has two parts: a name ID and an attributes part for user attributes that a DN for a signing certificate can assert. The name ID and the attribute can contain a filter with multiple value patterns.

To remove the list of filters for an attribute for the signing certificate, use an empty set ([]) for the value of `filters`.

Note: You must first use the `setWSMTokenIssuerTrust` command to configure a list of trusted DN names for an issuer.

14.7.5.2 Syntax

```
setWSMTokenIssuerTrustAttributeFilter(dn, attr-name, filters)
```

Argument	Definition
<code>dn</code>	The DN of a token signing certificate.
<code>attr-name</code>	The name of the attribute to assert. The value can be as follows: <ul style="list-style-type: none"> name-id—assert a subject name ID.
<code>filters</code>	List of filters for the attribute. The list has the format <code>['value1', 'value2', 'value3', ...]</code> . Each value can be an exact name or a name pattern with a wildcard character <code>"*"</code> . When <code>name-id</code> is selected for the <code>attr-name</code> argument, then the value of the subject name ID in the incoming SAML assertion must match one of the specified values to go through. If no values are specified, then any value for the subject name ID will go through.

14.7.5.3 Examples

In the following example, the name ID `yourTrustedUser` is set as a trusted user for the `weblogic` trusted DN:

```
setWSMTokenIssuerTrustAttributeFilter('CN=weblogic, OU=Orakey Test Encryption Purposes Only, O=Oracle, C=US', 'name-id', ['yourTrustedUser'])
```

In the following example, the name IDs `jdoe` is added to the list of trusted users for the `weblogic` trusted DN:

```
setWSMTokenIssuerTrustAttributeFilter('CN=weblogic, OU=Orakey Test Encryption Purposes Only, O=Oracle, C=US', 'name-id', ['yourTrustedUser', 'jdoe'])
```

In the following example, the list of trusted users for the `weblogic` trusted DN is removed:

```
setWSTokenIssuerTrustAttributeFilter('CN=weblogic, OU=Oracle Test Encryption Purposes Only, O=Oracle, C=US', 'name-id', [])
```

14.8 Diagnostic Commands

Use the WLST command in this section to check the status of the WSM components that are required for proper functioning of the product.

14.8.1 checkWSMStatus

Command Category: Diagnostic

Use with WLST: Online

14.8.1.1 Description

Check the status of the WSM components that are required for proper functioning of the product. The WSM components that are checked are the policy manager (`wsm-pm`), the agent (`agent`), and the credential store and keystore configuration. The status of the components can be checked together or individually.

Note: The Policy Manager (`wsm-pm`) application must be deployed and running for the check status tool to function correctly.

14.8.1.2 Syntax

```
checkWSMStatus([component=None], [address=None], [verbose=true])
```

Arguments	Description
<i>component</i>	Optional. All checks will be performed if no value is specified. Valid options are: <ul style="list-style-type: none"> ▪ <code>wsm-pm</code>—Policy Manager. Checks the configuration state of the policy manager component. ▪ <code>agent</code>—Enforcement Agent. Checks status of end-to-end service-side enforcement through the <code>wsm</code> agent component. The enforcement check is specific only to the environment from which the command is run. ▪ <code>credstore</code>—Credential Store. Checks whether the credentials are configured for the keystore password, signing, and encryption certificates in the keystore.
<i>address</i>	Optional. The HTTP URL of the host running the Policy Manager <code>wsm-pm</code> application. This value is required for checking enforcement through an agent component, for example, <pre>checkWSMStatus('agent', 'http://localhost:7001')</pre> The address is not required in the WebLogic Server domain where auto-discovery is present.
<i>verbose</i>	Optional. If the value of this flag is <code>true</code> , then the detailed messages (including stack trace, if any) are displayed. Default is <code>false</code> .

14.8.1.3 Examples

In the following example, the `checkWSMStatus` command is run without arguments. The status of the credential store, policy manager, and enforcement agent is returned.

```
wls:/base_domain/serverConfig> checkWSMStatus()
```

Credential Store Configuration:

PASSED.

Message(s):

keystore.pass.csf.key : Property is configured and its value is "keystore-csf-key".

Description: The "keystore.pass.csf.key" property points to the CSF alias that is mapped to the username and password of the keystore. Only the password is used; username is redundant in the case of the keystore.

keystore-csf-key : Credentials configured.

keystore.sig.csf.key : Property is configured and its value is "sign-csf-key".

Description: The "keystore.sig.csf.key" property points to the CSF alias that is mapped to the username and password of the private key that is used for signing.

sign-csf-key : Credentials configured.

Sign Key : Key configured.

Alias - orakey

Sign Certificate : Certificate configured.

Alias - CN=weblogic, OU=Orakey Test Encryption Purposes Only, O=Oracle, C=US

Expiry - June 28, 2020 11:17:12 AM PDT

keystore.enc.csf.key : Property is configured and its value is "enc-csf-key".

Description: The "keystore.enc.csf.key" property points to the CSF alias that is mapped to the username and password of the private key that is used for decryption.

enc-csf-key : Credentials configured.

Encrypt Key : Key configured.

Alias - orakey

Encrypt Certificate : Certificate configured.

Alias - CN=weblogic, OU=Orakey Test Encryption Purposes Only, O=Oracle, C=US

Expiry - June 28, 2020 11:17:12 AM PDT

Policy Manager:

PASSED.

Message(s):

OWSM Policy Manager connection state is OK.

OWSM Policy Manager connection URL is "host.example.com:1234".

Enforcement Agent:

PASSED.

Message(s):

Enforcement is successful.

Service URL:

<http://host.example.com:7001/Diagnostic/DiagnosticService?wsdl>

In the following example, the credential store key `keystore-csf-key` is deleted and the `checkWSMStatus` command is rerun for the credential store `credstore`. The

status check fails because the csf-key keystore-csf-key is not present in the credential store:

```
wls:/base_domain/serverConfig> deleteCred(map="oracle.wsm.security",
key="keystore-csf-key")
wls:/base_domain/serverConfig> checkWSMStatus('credstore')
```

Credential Store Configuration:

FAILED.

```
Message(s):
    keystore.pass.csf.key : Property is configured and its value is
"keystore-csf-key".
    Description: The "keystore.pass.csf.key" property points to the
CSF alias that is mapped to the username and password of the keystore. Only the
password is used; username is redundant in the case of the keystore.
    keystore-csf-key : Credentials not configured.
```

Credential Store Diagnostic Messages:

```
Message(s):
    The csf-key keystore-csf-key is not present in the credential
store.
```

Perform the following steps to update the credential store (using WLST commands):-

1. connect()
2. createCred(map="oracle.wsm.security", key="keystore-csf-key", user="keystore-csf-key", password="<keystore-password>", desc="Keystore Password CSF Key")

NOTE:- All the above commands are based on the Domain level configurations. The actual csf key may be overridden at runtime due to config override. See Documentation for more details.

In the following example, the csf-key keystore-csf-key is configured and the checkWSMStatus command is rerun. The configuration check passes.

```
wls:/base_domain/serverConfig> createCred(map="oracle.wsm.security",
key="keystore-csf-key", user="keystore-csf-key", password="welcome1",
desc="Keystore Password CSF Key")
Already in Domain Runtime Tree
```

```
wls:/base_domain/serverConfig> checkWSMStatus('credstore')
```

Credential Store Configuration:

PASSED.

```
Message(s):
    keystore.pass.csf.key : Property is configured and its value is
"keystore-csf-key".
    Description: The "keystore.pass.csf.key" property points to the
CSF alias that is mapped to the username and password of the keystore. Only the
password is used; username is redundant in the case of the keystore.
    keystore-csf-key : Credentials configured.
    keystore.sig.csf.key : Property is configured and its value is
"sign-csf-key".
    Description: The "keystore.sig.csf.key" property points to the
CSF alias that is mapped to the username and password of the private key that is
used for signing.
    sign-csf-key : Credentials configured.
    Sign Key : Key configured.
```



```

Alias - orakey
Sign Certificate : Certificate configured.
Alias - CN=weblogic, OU=Orakey Test Encryption Purposes Only,
O=Oracle, C=US
Expiry - June 28, 2020 11:17:12 AM PDT
keystore.enc.csf.key : Property is configured and its value is
"enc-csf-key".
Description: The "keystore.enc.csf.key" property points to the
CSF alias that is mapped to the username and password of the private key that is
used for decryption.
enc-csf-key : Credentials configured.
Encrypt Key : Key configured.
Alias - orakey
Encrypt Certificate : Certificate configured.
Alias - CN=weblogic, OU=Orakey Test Encryption Purposes Only,
O=Oracle, C=US
Expiry - June 28, 2020 11:17:12 AM PDT
true

```

The following example checks the enforcement status of the agent component at the URL <http://localhost:7001>.

```
wls:/test_domain1/serverConfig> checkWSMStatus('agent', 'http://localhost:7001')
```

Enforcement Agent:

Note: Enforcement might succeed if OWSM Policy Manager is down due to policy caching. For such scenarios wsm-pm test must be run prior to this test.

PASSED.

Message(s):

Enforcement is successful.

Service URL: <http://localhost:7001/Diagnostic/DiagnosticService?wsdl>

Diagnostic Framework Custom WLST Commands

The Diagnostic Framework aids in capturing relevant and timely diagnostics for critical errors. The diagnostics can be sent to Oracle Support for further analysis. Use the Diagnostic Framework commands to generate incidents, query existing incidents and execute individual diagnostics dumps to gather specific diagnostics data. This chapter provides detailed descriptions of WLST commands for the Diagnostic Framework, including command syntax, arguments and command examples.

For additional information about using the Diagnostic Framework, see "Diagnosing Problems" in the *Oracle Fusion Middleware Administrator's Guide*.

Note: To use the Diagnostic Framework custom WLST commands, you must invoke the WLST script from the Oracle Common home. See "Using Custom WLST Commands" in the *Oracle Fusion Middleware Administrator's Guide*.

Table 15–1 lists the different categories of Diagnostic Framework commands.

Table 15–1 Diagnostic Command Categories

Command Category	Description
Incident Commands	View problems and incidents and create incidents.
Diagnostic Dump Commands	Display information about dumps and execute dumps.
Dump Sampling Commands	Capture samples of diagnostic dumps at specified intervals.

15.1 Incident Commands

Use the commands in Table 15–2 to view problems and incidents and to create incidents.

Table 15–2 Incident Commands

Use this command...	To...	Use with WLST...
createIncident	Create a diagnostic incident.	Online
getIncidentFile	Retrieves the contents of the specified incident file.	Online
listADRHomes	List the set of ADR Home paths.	Online

Table 15–2 (Cont.) Incident Commands

Use this command...	To...	Use with WLST...
listIncidents	List a set of diagnostic incidents.	Online
listProblems	List a set of diagnostic problems.	Online
reloadCustomRules	Reloads all custom diagnostic rules or the specified rule.	Online, Offline
showIncident	Show the details of a specified incident.	Online

15.1.1 createIncident

Use with WLST: Online

15.1.1.1 Description

Creates a diagnostic incident, using the specified information to determine the set of diagnostic rules and actions to execute.

15.1.1.2 Syntax

```
createIncident([adrHome] [,incidentTime] [,messageId] [,ecid] [,appName]
               [,description] [,server])
```

Argument	Definition
<i>adrHome</i>	The path for the ADR Home in which to create the incident. The ADR Home must exist. If this argument is not specified, the default ADR Home is used. The default ADR Home is the following location: <i>ADR_BASE/diag/OFM/domain_name/server_name</i>
<i>incidentTime</i>	The timestamp at which the incident occurred. If this not specified, the current time is used. You can specify the following: <ul style="list-style-type: none"> ■ The time of the current day, in the format HH:MM. For example: 19:45 ■ The date and time, in the format MM/DD/YYYY HH:MM
<i>messageId</i>	The ID of the error message. For example, MDS-50400.
<i>ecid</i>	The Execution Context ID for the error message.
<i>appName</i>	The name of the deployed application for which the diagnostics are being gathered. For example, if you have multiple ADF applications deployed, each may register a dump called <i>adf.dump</i> . To execute this command for a specific application, you must specify the application name.
<i>description</i>	Descriptive text to associate with the incident. This is useful when reviewing the incident at a later time.
<i>server</i>	The name of the Managed Server from which to collect information. This argument is valid only when you are connected to the Administration Server.

15.1.1.3 Example

The following example creates an incident that is related to messages with the ID MDS-50400:

```
createIncident(messageId="MDS-50400", description="sample incident")
Incident Id: 55
Problem Id: 4
Problem Key: MDS-50400 [MANUAL]
Incident Time: 25th March 2010 11:55:45 GMT
Error Message Id: MDS-50400
Flood Controlled: false
```

15.1.2 getIncidentFile

Use with WLST: Online

15.1.2.1 Description

Retrieves the contents of the specified incident file.

15.1.2.2 Syntax

```
getIncidentFile(id, name [,outputFile] [,adrHome] [,server])
```

Argument	Definition
<i>id</i>	The ID of the incident that you want to retrieve.
<i>name</i>	The name of the file to retrieve. To find the name of the file, use the showIncident command.
<i>outputFile</i>	The name of the file to which to write the output.
<i>adrHome</i>	The path for the ADR Home from which to retrieve the information. If this argument is not specified, the default ADR Home will be queried. The default ADR Home is the following location: <i>ADR_BASE/diag/OFM/domain_name/server_name</i>
<i>server</i>	The name of the Managed Server from which to collect information. This argument is valid only when you are connected to the Administration Server.

15.1.2.3 Example

The following example writes the contents of the incident `dms_metrics3_i1.dmp` to the specified output file:

```
getIncidentFile(id='1', name='dms_metrics3_i1.dmp', outputFile='/tmp/incident1_
dms.txt')
```

The content of `'dms_metrics3_i1.dmp'` is written to `/tmp/incident1_dms.txt`

15.1.3 listADRHomes

Use with WLST: Online

15.1.3.1 Description

Lists the paths of all of the ADR Homes for the server.

15.1.3.2 Syntax

```
listADRHomes([server])
```

Argument	Definition
<i>server</i>	The name of the Managed Server from which to collect information. This argument is valid only when you are connected to the Administration Server.

15.1.3.3 Example

The following example lists the paths of the ADR homes:

```
listADRHomes()
diag/ofm/base_domain/WLS_Spaces

diag/ofm/fusionapps/GeneralLedger
```

15.1.4 listIncidents

Use with WLST: Online

15.1.4.1 Description

Lists the set of diagnostic incidents for the given problem ID, if specified, or all available incidents.

15.1.4.2 Syntax

```
listIncidents([id] [, adrHome] [,server])
```

Argument	Definition
<i>id</i>	The ID of the problem for which you want to list the set of diagnostic incidents.
<i>adrHome</i>	The path for the ADR Home from which to query incidents. If this argument is not specified, the default ADR Home will be queried. The default ADR Home is the following location: <i>ADR_BASE/diag/OFM/domain_name/server_name</i>
<i>server</i>	The name of the Managed Server from which to collect information. This argument is valid only when you are connected to the Administration Server.

15.1.4.3 Example

The following example lists the incidents associated with the problem with the ID 1:

```
listIncidents(id="1")
Incident Id      Problem Key      Incident Time
2010             10  MDS-50300 [WLS_Spaces] [oracle.mds.repos]  Mon Mar 15 11:22:12 PDT
2010             24  MDS-50300 [WLS_Spaces] [oracle.mds.repos]  Thu Mar 11 15:11:35 PDT
```

15.1.5 listProblems

Use with WLST: Online

15.1.5.1 Description

Lists the set of diagnostic problems associated with the specified ADR Home.

15.1.5.2 Syntax

```
listProblems([adrHome][, server])
```

Argument	Definition
<i>adrHome</i>	The path for the ADR Home from which to query problems. If this argument is not specified, the default ADR Home will be queried. The default ADR Home is the following location: <i>ADR_BASE</i> /diag/OFM/ <i>domain_name</i> / <i>server_name</i>
<i>server</i>	The name of the Managed Server from which to collect information. This argument is valid only when you are connected to the Administration Server.

15.1.5.3 Example

The following example lists the diagnostic problems in the default ADR home:

```
listProblems()
Problem Id      Problem Key
  1             MDS-50300 [WLS_Spaces] [oracle.mds.repos]
  2             JOC-38922 [AdminServer] [oracle.cache.network]
```

15.1.6 reloadCustomRules

Use with WLST: Online, Offline

15.1.6.1 Description

Reloads all custom diagnostic rules or the specified custom diagnostic rule.

15.1.6.2 Syntax

```
reloadCustomRules([name] [, server])
```

Argument	Definition
<i>name</i>	The name of a custom diagnostic rule. This argument is optional. If you specify it, only the named rule is reloaded. If you do not specify this argument, all custom diagnostic rules are reloaded. The file containing the custom diagnostic rule must be located in one of the following directories: <i>DOMAIN_HOME</i> /config/fmwconfig/dfw <i>DOMAIN_HOME</i> /config/fmwconfig/servers/ <i>server_name</i> /dfw
<i>server</i>	The name of the server to which to reload the rules. This argument is optional. If you do not specify it, the rules are reloaded to all servers. This option is only valid when you are connected to the Administration Server.

15.1.6.3 Example

The following example reloads the custom diagnostic rule myCustomRules.xml:

```
reloadCustomRules(name='myCustomRules.xml')
```

15.1.7 showIncident

Use with WLST: Online

15.1.7.1 Description

Shows the details of the specified incident.

15.1.7.2 Syntax

```
showIncident(id, [adrHome][, server])
```

Argument	Definition
<i>id</i>	The ID of the incident that you want to view.
<i>adrHome</i>	The path for the ADR Home from which to query the incident. If this argument is not specified, the default ADR Home will be queried. The default ADR Home is the following location: <i>ADR_BASE/diag/OFM/domain_name/server_name</i>
<i>server</i>	The name of the Managed Server from which to collect information. This argument is valid only when you are connected to the Administration Server.

15.1.7.3 Example

The following example displays information about the incident with the ID 10:

```
showIncident(id="10")
Incident Id: 10
Problem Id: 1
Problem Key: MDS-50300 [WLS_Spaces] [oracle.mds.repos]
Incident Time: 25th March 2010 10:12:15 GMT
Error Message Id: MDS-50300
Execution Context: 0000ICK4rbYC8xT6uBF9EH1AX1qF000000
Flood Controlled: false
Dump Files :
  dms_ecidctx1_i1.dmp
  jvm_threads2_i1.dmp
  dms_metrics3_i1.dmp
  odl_logs4_i1.dmp
  diagnostic_image_AdminServer_2010_03_25_11_12_15.zip
  readme.txt
```

15.2 Diagnostic Dump Commands

Use the commands in [Table 15–3](#) to display information about dumps and to execute dumps.

Table 15–3 Diagnostic Dump Commands

Use this command...	To...	Use with WLST...
describeDump	Display a description of the specified diagnostic dump.	Online
executeDump	Execute the specified diagnostic dump.	Online
listDumps	Display the set of diagnostic dumps that can be executed.	Online

15.2.1 describeDump

Use with WLST: Online

15.2.1.1 Description

Displays a description of the specified diagnostic dump.

15.2.1.2 Syntax

```
describeDump(name [, appName] [.server])
```

Argument	Definition
<i>name</i>	The name of the dump for which to display information.
<i>appName</i>	The name of the deployed application for which information is gathered. For example, if you have multiple ADF applications deployed, each may register a dump called <code>adf.dump</code> . To execute this command for a specific application, you must specify the application name.
<i>server</i>	The name of the Managed Server from which to collect information. This argument is valid only when you are connected to the Administration Server.

15.2.1.3 Example

The following example displays information about the dump with the name `odl.logs`. You use the [listDumps](#) command to retrieve the list of available dumps.

```
describeDump(name="odl.logs")
```

Name: `odl.logs`

Description: Dumps recent ODL logs, or logs correlated by ECID

Mandatory Arguments:

Optional Arguments:

Name	Type	Description
<code>ECID</code>	String	Execution Context Id to correlate log entries with
<code>timestamp</code>	String	Timestamp to query logs 5 minutes before/after

15.2.2 executeDump

Use with WLST: Online

15.2.2.1 Description

Executes the specified diagnostic dump.

15.2.2.2 Syntax

```
executeDump(name [, args] [, outputFile] [, id] [, adrHome] [, server])
```

Argument	Definition
<i>name</i>	The name of the diagnostic dump to execute.
<i>args</i>	Mandatory or optional arguments to pass to the dump.
<i>outputFile</i>	The name of the file to which to write the dump. If you do not specify this argument, the output is written to the console.
<i>id</i>	The ID of the incident to which to associate the dump. By default, the specified dump will not be associated with an incident.
<i>adrHome</i>	The ADR home that contains the incident. If you do not specify this argument, the default ADR home is used. The default ADR Home is the following location: <code>ADR_BASE/diag/OFM/domain_name/server_name</code>

Argument	Definition
<i>server</i>	The name of the Managed Server from which to collect information. This argument is valid only when you are connected to the Administration Server.

Arguments that are either required or are optional can be specified using the "args" keyword. For example:

```
executeDump("java.sysprops", args={"prop" : "os.name"})
```

15.2.2.3 Examples

The following example executes the dump with the name `jvm.threads` and writes it to the file `dumpout.txt`:

```
executeDump(name="jvm.threads", outputFile="/tmp/dumpout.txt")
Diagnostic dump jvm.threads output written to /tmp/dumpoutput.txt
```

The following example executes the dump with the name `jvm.threads` and the Incident ID for 33 and writes it to the file `dumpout.txt`:

```
executeDump(name="jvm.threads", outputFile="/tmp/dumpout.txt", id="33")
Diagnostic dump jvm.threads output associated with incident 33 in ADR Home
diag/ofm/base_domain/AdminServer
```

The following example executes a dump with the argument `prop` set to the value `os.name`:

```
executeDump(name="java.sysprops", args={"prop" : "os.name"})
```

15.2.3 listDumps

Use with WLST: Online

15.2.3.1 Description

Displays the set of diagnostic dumps that can be executed.

15.2.3.2 Syntax

```
listDumps([appName] [, server])
```

Argument	Definition
<i>appName</i>	<p>The name of a deployed application for which diagnostics are being gathered.</p> <p>For example, if you have multiple ADF applications deployed, each may register a dump called <code>adf.dump</code>. To execute this command for a specific application, you must specify the application name.</p> <p>If you specify this argument, the command returns the dumps for the specified application. If you do not specify this argument, the command returns the system dumps.</p>
<i>server</i>	The name of the Managed Server from which to collect information. This argument is valid only when you are connected to the Administration Server.

15.2.3.3 Example

The following example lists all of the available dumps.

```
listDumps()
dms.metrics
jvm.classhistogram
jvm.threads
odl.logs
```

Use the command `describeDump(name=<dumpName>)` for help on a specific dump.

15.3 Dump Sampling Commands

Use the commands in [Table 15–4](#) to capture samples of diagnostic dumps at specified intervals.

Table 15–4 Dump Sampling Commands

Use this command...	To...	Use with WLST...
<code>addDumpSample</code>	Creates samplings for Diagnostic Framework dumps.	Online
<code>enableDumpSampling</code>	Enables or disables all dump samplings.	Online
<code>getSamplingArchives</code>	Collects all dump samplings in a zip file containing the individual sampling files and a readme file.	Online
<code>isDumpSamplingEnabled</code>	Lists whether dump sampling is enabled or disabled.	Online
<code>listDumpSamples</code>	Lists all dump samplings, a specified dump sampling, or all dump samplings associated with a specified server.	Online
<code>removeDumpSample</code>	Removes the specified dump sampling.	Online
<code>updateDumpSample</code>	Updates the specified dump sampling, modifying the settings of the sampling.	Online

15.3.1 addDumpSample

Use with WLST: Online

15.3.1.1 Description

Creates dump samplings for Diagnostic Framework dumps.

15.3.1.2 Syntax

```
addDumpSample(sampleName, diagnosticDumpName [, appName], samplingInterval,
rotationCount [, dumpedImplicitly] [, toAppend] [, args] [, server=])
```

Argument	Definition
<code>sampleName</code>	The name of the sampling.
<code>diagnosticDumpName</code>	The name of the diagnostic dump to be sampled.
<code>appName</code>	Optional. The name of the application associated with the specified diagnostic dump. If you do not specify <code>appName</code> , the diagnostic dump has a scope of system.
<code>samplingInterval</code>	The sampling interval in seconds. If you specify zero or a negative value, sampling is suspended.

Argument	Definition
<i>rotationCount</i>	The maximum number of diagnostic dump samples to be kept in a rotation list. When this limit is reached, the oldest sample is deleted.
<i>dumpedImplicitly</i>	Optional. A Boolean value that specifies whether the diagnostic dump archive will be included in the <code>dfw.samplingArchive</code> . Valid values are <code>true</code> and <code>false</code> . The default is <code>true</code> . If the value is <code>false</code> , and you want to include the dump archive in the <code>dfw.samplingArchive</code> , you must pass the sampling name to the <code>executeDump</code> command using the <code>args</code> parameter.
<i>toAppend</i>	Optional. A Boolean value that specifies whether the diagnostic dump samples are appended to its predecessor, resulting in a single archive when you execute <code>dfw.samplingArchive</code> . Valid values are <code>true</code> and <code>false</code> . The default is <code>true</code> . If the value is <code>true</code> , the sample is appended to its predecessor. If the value is <code>false</code> , <code>dfw.sampleArchive</code> returns a zip file containing individual sample files. Specify <code>false</code> if the dump samples contain binary data.
<i>args</i>	Optional. Diagnostic dump arguments to be used by the diagnostic dump at each sampling time. The arguments are expressed as name/value pairs.
<i>server</i>	Optional. The name of the server from which to collect the information. If you do not specify this parameter, this command associates the dump sampling with the Administration Server.

15.3.1.3 Example

The following example adds a sampling for the dump `dms.metrics`:

```
addDumpSample(sampleName='dms_metrics', diagnosticDumpName='dms.metrics',
              samplingInterval=300, rotationCount=10)
```

`dms_metrics` is added

15.3.2 enableDumpSampling

Use with WLST: Online

15.3.2.1 Description

Enables or disables all dump samplings. This command affects all configured dump samplings.

15.3.2.2 Syntax

```
enableDumpSampling(enable [,server])
```

Argument	Definition
<i>enable</i>	A Boolean value that specifies whether to enable or disable dump samplings. Valid values are <code>true</code> and <code>false</code> .
<i>server</i>	Optional. The name of the server for which to enable or disable dump sampling. If you do not specify this parameter, this command enables or disables the dump sampling for the Administration Server.

15.3.2.3 Example

The following example disables all dump samplings:

```
enableDumpSampling(enable=false)
```

Dump sampling disabled

15.3.3 getSamplingArchives

Use with WLST: Online

15.3.3.1 Description

Collects all dump samplings in a zip file containing the individual sampling files and a readme file. This method is particularly useful in dealing with binary format dumps.

15.3.3.2 Syntax

```
getSamplingArchives([sampleName,] outputFile [,server])
```

Argument	Definition
<i>name</i>	Optional. The name of a particular dump sampling that you want to retrieve. If you do not specify this argument, the command returns all dump samplings.
<i>outputFile</i>	The absolute path of the file to which the dump samplings will be written.
<i>server</i>	Optional. The name of the server from which to collect the information. If you do not specify this parameter, this command collects the dump samples for the Administration Server.

15.3.3.3 Example

The following example retrieves the dump sampling for the dump JVMThreadDump:

```
getSamplingArchives(sampleName="JVMThreadDump", outputFile="/tmp/jvm_dump.zip")
wrote 63518 bytes to /tmp/jvm_dump.zip
```

The following shows the contents of the zip file:

```
unzip -l jvm_dump.zip
Archive:  jvm_dump.zip
  Length      Date    Time    Name
-----
  508780  08-21-12  07:25   dfw_
samplingArchive1065570966467923683.JVMThreadDump.dmp
   840  08-21-12  07:25   dfw_samplingArchive7749640004639161119.readme.txt
-----
  509620                                2 files
```

15.3.4 isDumpSamplingEnabled

Use with WLST: Online

15.3.4.1 Description

Lists whether dump sampling is enabled or disabled.

15.3.4.2 Syntax

```
isDumpSamplingEnabled([server])
```

Argument	Definition
<i>server</i>	Optional. The name of the server to determine if dump sampling is enabled or disabled. This argument is only valid when you are connected to the Administration Server.

15.3.4.3 Example

The following example lists the whether dump sampling is enabled or disabled for the server `soa_server1`:

```
isDumpSamplingEnabled(server="soa_server1")
Location changed to domainRuntime tree. This is a read-only tree with
DomainMBean as the root.
For more help, use help(domainRuntime)

true
```

15.3.5 listDumpSamples

Use with WLST: Online

15.3.5.1 Description

Lists all dump samplings, a specified dump sampling, or all dump samplings associated with a specified server.

15.3.5.2 Syntax

```
listDumpSamples([sampleName] [, server])
```

Argument	Definition
<i>sampleName</i>	Optional. The name of the sampling.
<i>server</i>	Optional. The name of the server for which to list the dump samplings. If you do not specify this parameter, this command lists the dump samplings for the Administration Server.

15.3.5.3 Example

The following example lists all dump samplings associated with the server `soa_server1`:

```
listDumpSamples(server="soa_server1")
Location changed to domainRuntime tree. This is a read-only tree with DomainMBean
as the root.
For more help, use help(domainRuntime)

Name           : JavaClassHistogram
Dump Name      : jvm.classshistogram
Application Name :
Sampling Interval : 1800
Rotation Count  : 5
Dump Implicitly : false
Append Samples  : true
Dump Arguments :

Name           : JVMThreadDump
Dump Name      : jvm.threads
Application Name :
```

```

Sampling Interval : 60
Rotation Count   : 10
Dump Implicitly  : true
Append Samples   : true
Dump Arguments   : context=true, timing=true

```

15.3.6 removeDumpSample

Use with WLST: Online

15.3.6.1 Description

Removes the dump sampling.

15.3.6.2 Syntax

```
removeDumpSample(sampleName [,server])
```

Argument	Definition
<i>sampleName</i>	The name of the sampling to be removed.
<i>server</i>	Optional. The name of the server from which to remove the sampling. If you do not specify this parameter, the dump sampling is removed from the Administration Server.

15.3.6.3 Example

The following example removes the dump sampling named HTTPSampling, associated with the server soa_server1:

```
removeDumpSample(sampleName="HTTPSampling", server="soa_server1")
```

Removed HTTPSampling

15.3.7 updateDumpSample

Use with WLST: Online

15.3.7.1 Description

Updates the specified dump sampling, modifying the settings of the sampling. You cannot change the name of the sampling. Modifications take affect at the next sampling interval.

15.3.7.2 Syntax

```
updateDumpSample(sampleName [, appName], samplingInterval,
rotationCount [,dumpedImplicitly] [, toAppend] [, arg,]
[, server])
```

Argument	Definition
<i>sampleName</i>	The name of the dump sampling.
<i>appName</i>	Optional. The name of the application associated with the specified diagnostic dump. If you do not specify appName, the diagnostic dump has a scope of system.
<i>samplingInterval</i>	Optional. The sampling interval in seconds. If you specify zero or a negative value, sampling is suspended.

Argument	Definition
<i>rotationCount</i>	Optional. The maximum number of diagnostic dump samplings to be kept in a rotation list. When this limit is reached, the oldest sampling is deleted
<i>dumpedImplicitly</i>	Optional. A Boolean value that specifies whether the diagnostic dump archive will be included in the <code>dfw.samplingArchive</code> . Valid values are <code>true</code> and <code>false</code> . The default is <code>true</code> . If the value is <code>false</code> , and you want to include the dump archive in the <code>dfw.samplingArchive</code> , you must pass the sampling name to the <code>executeDump</code> command using the <code>args</code> parameter.
<i>toAppend</i>	Optional. A Boolean value that specifies whether the diagnostic dump samples are appended to its predecessor, resulting in a single archive when you execute <code>dfw.samplingArchive</code> . Valid values are <code>true</code> and <code>false</code> . The default is <code>true</code> . If the value is <code>true</code> , the sample is appended to its predecessor. If the value is <code>false</code> , <code>dfw.sampleArchive</code> returns a zip file containing individual sampling files. Specify <code>false</code> if the dump samplings contain binary data.
<i>args</i>	Optional. Diagnostic dump arguments to be used by the diagnostic dump at each sampling time. The arguments are expressed as name/value pairs.
<i>server</i>	Optional. The name of the server from which to collect the information. If you do not specify this parameter, the dump sampling is updated for the Administration Server.

15.3.7.3 Example

The following example updates the dump sampling `HTTPSampling`, modifying the sampling interval, rotation count, and server.

```
updateDumpSample(sampleName="HTTPSampling", samplingInterval=200,  
                 rotationCount=5, server="soa_server1")
```

HTTPSampling is updated

Information Rights Management Custom WLST Commands

This chapter provides detailed descriptions of custom WLST commands for Oracle Fusion Middleware Information Rights Management, including command syntax, arguments and command examples.

The following sections describe the Oracle Fusion Middleware Information Rights Management custom WLST commands in detail. Topics include:

- [Section 16.1, "Overview of WLST IRM Commands"](#)
- [Section 16.2, "General Server Commands"](#)
- [Section 16.3, "Migration Commands"](#)
- [Section 16.4, "Test Content Commands"](#)
- [Section 16.5, "Languages Support Commands"](#)
- [Section 16.6, "Oracle IRM Desktop Installers Commands"](#)

For additional information about Oracle Information Rights Management, see *Oracle IRM Administrator's Guide*.

Note: To use these commands, you must invoke WLST from the Oracle home in which the component has been installed. See "Using Custom WLST Commands" in the *Oracle Fusion Middleware Administrator's Guide*.

16.1 Overview of WLST IRM Commands

WLST IRM commands are divided into the following categories:

Table 16-1 WLST IRM Command Categories

Command Category	Description
General Server Commands	Make general changes to Oracle IRM Server settings.
Migration Commands	Back up and migrate Oracle IRM Server user data.
Test Content Commands	Set up test content for users of Oracle IRM Desktop.
Languages Support Commands	Set up languages support for users of Oracle IRM Server.
Oracle IRM Desktop Installers Commands	Set up software installation support for Oracle IRM Desktop.

16.2 General Server Commands

Use the WLST commands listed in [Table 16–2](#) to make general changes to Oracle IRM Server settings.

Table 16–2 WLST General Server Commands

Use this command...	To...	Use with WLST...
addIRMRefreshPeriod	Create a new refresh period.	Online
getIRMRefreshPeriod	Display an existing refresh period.	Online
getIRMRefreshPeriods	Display all the refresh periods.	Online
removeIRMRefreshPeriod	Remove an existing refresh period.	Online
updateIRMRefreshPeriod	Update an existing refresh period.	Online
addIRMSyncWindow	Create a new sync window.	Online
getIRMSyncWindow	Display an existing sync window.	Online
getIRMSyncWindows	Display all the sync windows.	Online
removeIRMSyncWindow	Remove an existing sync window.	Online
updateIRMSyncWindow	Update an existing sync window.	Online
getIRMCryptoSchema	Display the cryptography algorithm.	Online
setIRMCryptoSchema	Set the cryptography algorithm.	Online
getIRMDeviceCount	Display the device count.	Online
setIRMDeviceCount	Set the device count.	Online
getIRMJournalCleanUp	Display the current report record clean-up values.	Online
setIRMJournalCleanUp	Set report record clean-up values.	Online
getIRMLicenseStateCleanUp	Display the license state clean-up frequency.	Online
setIRMLicenseStateCleanUp	Set the license state clean-up frequency.	Online
getIRMPrivacyURL	Display the URL of the privacy statement page.	Online
setIRMPrivacyURL	Set the URL of the privacy statement page.	Online
getIRMKeyStore	Display the type and location of the Oracle IRM keystore.	Online
setIRMKeyStore	Set the type and location of the Oracle IRM keystore.	Online

16.2.1 addIRMRefreshPeriod

Online command that creates a new refresh period.

16.2.1.1 Description

This command creates a refresh period. A refresh period is the maximum length of time that a user can use rights before the rights are refreshed from the server.

16.2.1.2 Syntax

```
addIRMRefreshPeriod(duration, dtype)
```

Argument	Definition
<i>duration</i>	Specifies the value of the refresh period. Integer.
<i>dtype</i>	Specifies the unit of the refresh period. 'MINUTES', 'HOURS', 'DAYS', 'MONTHS', 'YEARS'.

16.2.1.3 Examples

The following example creates a refresh period of 5 hours:

```
wls:/base_domain/serverConfig> addIRMRefreshPeriod(5,\"HOURS\")
```

The following example creates a refresh period of 50 minutes:

```
wls:/base_domain/serverConfig> addIRMRefreshPeriod(50,\"MINUTES\")
```

16.2.2 getIRMRefreshPeriod

Online command that displays an existing refresh period.

16.2.2.1 Description

This command displays the refresh period that is present at the specified index. A refresh period is the maximum length of time that a user can use rights before the rights are refreshed from the server.

16.2.2.2 Syntax

```
getIRMRefreshPeriod(pindex)
```

Argument	Definition
<i>pindex</i>	Specifies the index of the refresh period.

16.2.2.3 Examples

The following example displays the refresh period that is present at index zero:

```
wls:/base_domain/serverConfig> getIRMRefreshPeriod(0)
```

The following example displays the refresh period that is present at index one:

```
wls:/base_domain/serverConfig> getIRMRefreshPeriod(1)
```

16.2.3 getIRMRefreshPeriods

Online command that displays all existing refresh periods.

16.2.3.1 Description

This command displays all existing refresh periods. A refresh period is the maximum length of time that a user can use rights before the rights are refreshed from the server.

16.2.3.2 Syntax

```
getIRMRefreshPeriods()
```

16.2.3.3 Example

```
wls:/base_domain/serverConfig> getIRMRefreshPeriods()
```

16.2.4 removeIRMRefreshPeriod

Online command that removes an existing refresh period.

16.2.4.1 Description

This command removes a refresh period that is present at the specified index. A refresh period is the maximum length of time that a user can use rights before the rights are refreshed from the server.

16.2.4.2 Syntax

```
removeIRMRefreshPeriod(pindex)
```

Argument	Definition
<i>pindex</i>	Specifies the index of the refresh period.

16.2.4.3 Examples

The following example removes the refresh period that is present at index zero:

```
wls:/base_domain/serverConfig> removeIRMRefreshPeriod(0)
```

The following example removes the refresh period that is present at index one:

```
wls:/base_domain/serverConfig> removeIRMRefreshPeriod(1)
```

16.2.5 updateIRMRefreshPeriod

Online command that updates an existing refresh period.

16.2.5.1 Description

This command updates an existing refresh period. A refresh period is the maximum length of time that a user can use rights before the rights are refreshed from the server.

16.2.5.2 Syntax

```
updateIRMRefreshPeriod(pindex,duration,dtype)
```

Argument	Definition
<i>pindex</i>	Specifies the index of the refresh period.
<i>duration</i>	Specifies the value of the refresh period. Integer.
<i>dtype</i>	Specifies the unit of the refresh period. 'MINUTES', 'HOURS', 'DAYS', 'MONTHS' or 'YEARS'.

16.2.5.3 Examples

The following example updates the refresh period at index zero to have a duration of 5 hours:

```
wls:/base_domain/serverConfig> updateIRMRefreshPeriod(0,5,\"HOURS\")
```

The following example updates the refresh period at index zero to have a duration of 50 minutes:

```
wls:/base_domain/serverConfig> updateIRMRefreshPeriod(0,50,\"MINUTES\")
```

16.2.6 addIRMSyncWindow

Online command that creates a sync window.

16.2.6.1 Description

This command creates a sync window. A sync window is a period during which Oracle IRM Desktop will attempt to contact the server to synchronize rights.

16.2.6.2 Syntax

```
addIRMSyncWindow(day, stHrs, stMins, endHrs, endMins)
```

Argument	Definition
<i>day</i>	Specifies the weekday. 'MONDAY', 'TUESDAY', etc.
<i>stHrs</i>	Specifies the start hours. Integer.
<i>stMins</i>	Specifies the start minutes. Integer.
<i>endHrs</i>	Specifies the end hours. Integer.
<i>endMins</i>	Specifies the end minutes. Integer.

16.2.6.3 Example

The following example creates a sync window that will result in Oracle IRM Desktop attempting to contact the server between 9.30am and 6.30pm on Mondays:

```
wls:/base_domain/serverConfig> addIRMSyncWindow(\"MONDAY\", 9, 30, 6, 30)
```

16.2.7 getIRMSyncWindow

Online command that displays an existing sync window.

16.2.7.1 Description

This command displays a sync window that is present at the specified index. A sync window is a period during which Oracle IRM Desktop will attempt to contact the server to synchronize rights.

16.2.7.2 Syntax

```
getIRMSyncWindow(sindex)
```

Argument	Definition
<i>sindex</i>	Specifies the index of the sync window.

16.2.7.3 Examples

The following example displays the sync window at index zero:

```
wls:/base_domain/serverConfig> getIRMSyncWindow(0)
```

The following example displays the sync window at index one:

```
wls:/base_domain/serverConfig> getIRMSyncWindow(1)
```

16.2.8 getIRMSyncWindows

Online command that displays all existing sync windows.

16.2.8.1 Description

This command displays all existing sync windows. A sync window is a period during which Oracle IRM Desktop will attempt to contact the server to synchronize rights.

16.2.8.2 Syntax

```
getIRMSyncWindows()
```

16.2.8.3 Example

```
wls:/base_domain/serverConfig> getIRMSyncWindows()
```

16.2.9 removeIRMSyncWindow

Online command that removes an existing sync window.

16.2.9.1 Description

This command removes a sync window that is present at the specified index. A sync window is a period during which Oracle IRM Desktop will attempt to contact the server to synchronize rights.

16.2.9.2 Syntax

```
removeIRMSyncWindow(sindex)
```

Argument	Definition
<i>sindex</i>	Specifies the index of the sync window.

16.2.9.3 Examples

The following example removes the sync window at index zero:

```
wls:/base_domain/serverConfig> removeIRMSyncWindow(0)
```

The following example removes the sync window at index one:

```
wls:/base_domain/serverConfig> removeIRMSyncWindow(1)
```

16.2.10 updateIRMSyncWindow

Online command that updates an existing sync window.

16.2.10.1 Description

This command updates an existing sync window. A sync window is a period during which Oracle IRM Desktop will attempt to contact the server to synchronize rights.

16.2.10.2 Syntax

```
updateIRMSyncWindow(indexOfDay, day, stHrs, stMins, endHrs, endMins)
```

Argument	Definition
<i>indexOfDay</i>	Specifies the index of the sync window. Integer.
<i>day</i>	Specifies the weekday. 'MONDAY', 'TUESDAY', etc.
<i>stHrs</i>	Specifies the start hours. Integer.
<i>stMins</i>	Specifies the start minutes. Integer.

Argument	Definition
<i>endHrs</i>	Specifies the end hours. Integer.
<i>endMins</i>	Specifies the end minutes. Integer.

16.2.10.3 Example

The following example updates the sync window at index zero so that Oracle IRM Desktop will attempt to contact the server between 9.30am and 5.30pm on Mondays:

```
wls:/base_domain/serverConfig> updateIRMSyncWindow(0,\"MONDAY\",9,30,5,30)
```

16.2.11 getIRMCryptoSchema

Online command that displays the cryptography algorithm.

16.2.11.1 Description

This command displays the cryptography algorithm currently applied to files that are sealed using Oracle IRM.

16.2.11.2 Syntax

```
getIRMCryptoSchema()
```

16.2.11.3 Example

```
wls:/base_domain/serverConfig> getIRMCryptoSchema()
```

16.2.12 setIRMCryptoSchema

Online command that sets the cryptography algorithm.

16.2.12.1 Description

This command sets the cryptography algorithm that will be applied to files that are sealed using Oracle IRM. The default of AES128 is recommended.

16.2.12.2 Syntax

```
setIRMCryptoSchema(cryptID)
```

Argument	Definition
<i>cryptID</i>	Specifies the name of the cryptography algorithm. Possible algorithm names are AES128, AES256, AES128-FIPS, AES256-FIPS, DES3-FIPS.

16.2.12.3 Example

The following example sets the cryptography algorithm used for Oracle IRM communications to AES128:

```
wls:/base_domain/serverConfig> setIRMCryptoSchema(\"AES128\")
```

16.2.13 getIRMDeviceCount

Online command that displays the device count.

16.2.13.1 Description

This command displays the maximum number of devices on which a user can open a sealed document at one time. The value applies to all users, and does not differ for individual users.

16.2.13.2 Syntax

```
getIRMDeviceCount()
```

16.2.13.3 Example

```
wls:/base_domain/serverConfig> getIRMDeviceCount()
```

16.2.14 setIRMDeviceCount

Online command that sets the device count.

16.2.14.1 Description

This command sets the maximum number of devices on which a user can open a sealed document at one time. The value applies to all users. The device count is normally kept low (1 or 2) to make it difficult to circumvent document access restrictions by sharing passwords.

16.2.14.2 Syntax

```
setIRMDeviceCount(devCount)
```

Argument	Definition
<i>devCount</i>	Specifies the device count value (the number of devices). Integer.

16.2.14.3 Example

The following example sets the device count to 2:

```
wls:/base_domain/serverConfig> setIRMDeviceCount(2)
```

16.2.15 getIRMJournalCleanUp

Online command that displays the current report record clean-up values.

16.2.15.1 Description

This command displays the report record clean-up values. The values show how often report record clean-ups are performed, and the maximum age of the report records before they are deleted.

16.2.15.2 Syntax

```
getIRMJournalCleanUp()
```

16.2.15.3 Example

```
wls:/base_domain/serverConfig> getIRMJournalCleanUp()
```

16.2.16 setIRMJournalCleanUp

Online command that sets report record clean-up values.

16.2.16.1 Description

This command sets how often report record clean-ups are performed, and the maximum age of report records before they are deleted.

16.2.16.2 Syntax

```
setIRMJournalCleanUp(clDuration,clUnitType,retDuration,retUnitType)
```

Argument	Definition
<i>clDuration</i>	Specifies the value for how often report record clean-ups are performed. Integer.
<i>clUnitType</i>	Specifies the unit for how often report record clean-ups are performed. 'MINUTES', 'HOURS', 'DAYS', 'MONTHS', 'YEARS'.
<i>retDuration</i>	Specifies the value for the maximum age of report records before they are deleted. Integer.
<i>retUnitType</i>	Specifies the unit for the maximum age of report records before they are deleted. 'MINUTES', 'HOURS', 'DAYS', 'MONTHS', 'YEARS'.

16.2.16.3 Example

The following example runs report record clean-ups every 5 days, and deletes report records that are 6 months old:

```
wls:/base_domain/serverConfig> setIRMJournalCleanUp(5,\"DAYS\",6,\"MONTHS\")
```

16.2.17 getIRMLicenseStateCleanUp

Online command that displays the license state clean-up frequency.

16.2.17.1 Description

This command displays the license state clean-up frequency (the frequency at which license records will be deleted).

16.2.17.2 Syntax

```
getIRMLicenseStateCleanUp()
```

16.2.17.3 Example

```
wls:/base_domain/serverConfig> getIRMLicenseStateCleanUp()
```

16.2.18 setIRMLicenseStateCleanUp

Online command that sets the license state clean-up frequency.

16.2.18.1 Description

This command sets the license state clean-up frequency (the frequency at which license records will be deleted).

16.2.18.2 Syntax

```
setIRMLicenseStateCleanUp(duration,unitType)
```

Argument	Definition
<i>duration</i>	Specifies the value of the frequency at which license records will be deleted. Integer.
<i>unitType</i>	Specifies the unit for the frequency at which license records will be deleted. 'MINUTES', 'HOURS', 'DAYS', 'MONTHS', 'YEARS'.

16.2.18.3 Examples

The following example sets the frequency at which license records will be deleted to 10 hours:

```
wls:/base_domain/serverConfig> setIRMLicenseStateCleanup(10,\"HOURS\")
```

The following example sets the frequency at which license records will be deleted to 50 minutes:

```
wls:/base_domain/serverConfig> setIRMLicenseStateCleanup(50,\"MINUTES\")
```

16.2.19 getIRMPrivacyURL

Online command that displays the URL of the privacy statement page.

16.2.19.1 Description

This command displays the URL of the privacy statement page. The privacy statement page displays a statement that users must accept before viewing sealed content.

16.2.19.2 Syntax

```
getIRMPrivacyURL()
```

16.2.19.3 Examples

```
wls:/base_domain/serverConfig> getIRMPrivacyURL()
```

16.2.20 setIRMPrivacyURL

Online command that sets the URL of the privacy statement page.

16.2.20.1 Description

This command sets the URL of a privacy statement that users must accept before viewing sealed content.

16.2.20.2 Syntax

```
setIRMPrivacyURL(privacyURL)
```

Argument	Definition
<i>privacyURL</i>	Specifies the URL of the privacy statement page.

16.2.20.3 Example

The following example sets the URL of the privacy policy page to "http://irm.example.com/":

```
wls:/base_domain/serverConfig> setIRMPrivacyURL(\"http://irm.example.com/\")
```

16.2.21 getIRMKeyStore

Online command that displays the type and location of the Oracle IRM keystore.

16.2.21.1 Description

This command displays the type and location of the Oracle IRM keystore.

16.2.21.2 Syntax

```
getIRMKeyStore()
```

16.2.21.3 Examples

```
wls:/base_domain/serverConfig> getIRMKeyStore()
```

16.2.22 setIRMKeyStore

Online command that sets the type and location of the Oracle IRM keystore.

16.2.22.1 Description

This command sets the type and location of the Oracle IRM keystore. You should not normally need to change the keystore type and location from the default (type JKS at location \${domain.home}/config/fmwconfig/irm.jks).

16.2.22.2 Syntax

```
setIRMKeyStore()
```

You will be prompted to provide the following arguments:

Argument	Definition
KeyStore Type	Specifies the type of the keystore.
KeyStore Location	Specifies the location of the keystore.

16.2.22.3 Example

The following example sets the keystore type to JCEKS and the keystore location to D:/exampleDir/:

```
wls:/base_domain/serverConfig> setIRMKeyStore()  
Enter KeyStore Type: JCEKS  
Enter KeyStore Location: D:/exampleDir/
```

16.3 Migration Commands

Use the WLST commands listed in [Table 16-3](#) to set up import and export of user data between instances of Oracle IRM Server.

Table 16-3 WLST Commands for Import and Export of Oracle IRM user data

Use this command...	To...	Use with WLST...
setIRMExportFolder	Set or clear the data export folder location.	Online
getIRMExportFolder	Display the value for the data export folder.	Online
setIRMImportFolder	Set or clear the data import folder location.	Online

Table 16–3 (Cont.) WLST Commands for Import and Export of Oracle IRM user data

Use this command...	To...	Use with WLST...
<code>getIRMImportFolder</code>	Display the value for the data import folder.	Online

16.3.1 setIRMExportFolder

Online command that sets or clears the data export folder location.

16.3.1.1 Description

This command sets or clears the location of the folder used for data export.

16.3.1.2 Syntax

```
setIRMExportFolder(folder)
```

Argument	Definition
<i>folder</i>	Specifies the data export folder value.

16.3.1.3 Example

```
wls:/base_domain/serverConfig> setIRMExportFolder("export")
```

16.3.2 getIRMExportFolder

Online command that displays the value of the data export folder.

16.3.2.1 Description

This command displays the location of the folder used for data export.

16.3.2.2 Syntax

```
getIRMExportFolder()
```

16.3.2.3 Example

```
wls:/base_domain/serverConfig> getIRMExportFolder()
```

16.3.3 setIRMImportFolder

Online command that sets or clears the data import folder location.

16.3.3.1 Description

This command sets or clears the location of the folder used for data import.

16.3.3.2 Syntax

```
setIRMImportFolder(folder)
```

Argument	Definition
<i>folder</i>	Specifies the import folder value.

16.3.3.3 Example

```
wls:/base_domain/serverConfig> setIRMImportFolder("import")
```

16.3.4 getIRMImportFolder

Online command that displays the value of the data import folder.

16.3.4.1 Description

This command displays the location of the folder used for data import.

16.3.4.2 Syntax

```
getIRMImportFolder()
```

16.3.4.3 Example

```
wls:/base_domain/serverConfig> getIRMImportFolder()
```

16.4 Test Content Commands

Use the WLST commands listed in [Table 16-4](#) to set up test content for users of Oracle IRM Desktop.

Table 16-4 WLST Commands for Test Content

Use this command...	To...	Use with WLST...
addIRMTestContent	Create a new test content instance.	Online
getIRMTestContent	Display details for an existing test content instance.	Online
getIRMTestContents	Display details of all existing test content instances.	Online
removeIRMTestContent	Remove an existing test content instance.	Online
updateIRMTestContent	Update an existing text content instance.	Online

16.4.1 addIRMTestContent

Online command that creates a new test content instance.

16.4.1.1 Description

This command creates a test content instance. Test content instances identify an item of test content, usually an image file. Test content is shown in a sealed document when Oracle IRM Desktop successfully connects to Oracle IRM Server through the client test facility.

16.4.1.2 Syntax

```
addIRMTestContent(uri, localeKeys, testNames)
```

Argument	Definition
<i>uri</i>	Specifies the URI of the test content (for example, an image file).

Argument	Definition
<i>localeKeys</i>	Specifies the locale(s) associated with this test content instance. Must be from the list of two-letter language codes given in Table 16-5 (for example, 'fr' for French). If there is more than one supported locale for an instance, the two-letter codes must be listed as comma-separated values.
<i>testNames</i>	Specifies the name(s) associated with this test content instance. If there is more than one name for a URI, they must be specified as comma-separated values.

Table 16-5 Language codes (ISO 639-1 "two-letter codes")

Language/Code	Language/Code	Language/Code
Arabic: ar	Greek: el	Romanian: ro
Brazilian Portuguese: pt-BR	Hebrew: iw	Russian: ru
Czech: cs	Hungarian: hu	Simplified Chinese: zh-CN
Danish: da	Italian: it	Slovak: sk
Dutch: nl	Japanese: ja	Spanish: es
English: en	Korean: ko	Swedish: sv
Finnish: fi	Norwegian: no	Thai: th
French: fr	Polish: pl	Traditional Chinese: zh-TW
German: de	Portuguese: pt	Turkish: tr

16.4.1.3 Examples

The following example creates a test content instance comprising an image named `exampleImage.jpg` at `http://irm.example.com`, for use with English installations, and showing the name 'Test Content':

```
wls:/base_domain/serverConfig>
addIRMTestContent(\"http://irm.example.com/exampleImage.jpg\", \"en\", \"Test
Content\")
```

The following example creates a test content instance comprising an image named `exampleImage.jpg` at `http://irm.example.com`, for use with English and French installations, and showing the names 'Test Content (en)' and 'Test Content (fr)':

```
wls:/base_domain/serverConfig>
addIRMTestContent(\"http://irm.example.com/exampleImage.jpg\", \"en,fr\", \"Test
Content (en),Test Content (fr)\")
```

16.4.2 getIRMTestContent

Online command that displays the details of an existing test content instance.

16.4.2.1 Description

This command displays the details of the test content instance that is present at the specified index. Test content instances identify an item of test content, usually an image file. Test content is shown in a sealed document when Oracle IRM Desktop successfully connects to Oracle IRM Server through the client test facility.

16.4.2.2 Syntax

```
getIRMTTestContent(tindex)
```

Argument	Definition
<i>tindex</i>	Specifies the index of the test content instance.

16.4.2.3 Examples

The following example displays the details of the test content instance at index zero:

```
wls:/base_domain/serverConfig> getIRMTTestContent(0)
```

The following example displays the details of the test content instance at index one:

```
wls:/base_domain/serverConfig> getIRMTTestContent(1)
```

16.4.3 getIRMTTestContents

Online command that displays all the test content instances.

16.4.3.1 Description

This command displays all the test content instances. Test content instances identify an item of test content, usually an image file. Test content is shown in a sealed document when Oracle IRM Desktop successfully connects to Oracle IRM Server through the client test page.

16.4.3.2 Syntax

```
getIRMTTestContents()
```

16.4.3.3 Example

```
wls:/base_domain/serverConfig> getIRMTTestContents()
```

16.4.4 removeIRMTTestContent

Online command that removes an existing test content instance.

16.4.4.1 Description

This command removes the test content instance that is present at the specified index. Test content instances identify an item of test content, usually an image file.

16.4.4.2 Syntax

```
removeIRMTTestContent(tindex)
```

Argument	Definition
<i>tindex</i>	Specifies the index of test content.

16.4.4.3 Examples

The following example removes the test content instance at index zero:

```
wls:/base_domain/serverConfig> removeIRMTTestContent(0)
```

The following example removes the test content instance at index one:

```
wls:/base_domain/serverConfig> removeIRMTestContent(1)
```

16.4.5 updateIRMTestContent

Online command that updates an existing test content instance.

16.4.5.1 Description

This command updates an existing test content instance. Test content instances identify an item of test content, usually an image file. Test content is shown in a sealed document when Oracle IRM Desktop successfully connects to Oracle IRM Server through the client test facility.

16.4.5.2 Syntax

```
updateIRMTestContent(tindex,uri,localeKeys,testNames)
```

Argument	Definition
<i>tindex</i>	Specifies the index of the test content instance. Integer.
<i>uri</i>	Specifies the URI of the test content (for example, an image file).
<i>localeKeys</i>	Specifies the locale(s) associated with this test content instance. Must be from the list of two-letter language codes given in Table 16-5 (for example, 'fr' for French). If there is more than one supported locale for an instance, the two-letter codes must be listed as comma-separated values.
<i>testNames</i>	Specifies the name(s) associated with this test content instance. If there is more than one name for a URI, they must be specified as comma-separated values.

16.4.5.3 Examples

The following example updates a test content instance by changing the image to exampleImage.jpg at http://irm.example.com, for use with English installations, and showing the name 'Test Content':

```
wls:/base_domain/serverConfig>
updateIRMTestContent(0,\"http://irm.example.com/exampleImage.jpg\", \"en\", \"Test Content\")
```

The following example updates a test content instance by changing the image to exampleImage.jpg at http://irm.example.com, for use with English and French installations, and showing the names 'Test Content (English)' and 'Test Content (French)':

```
wls:/base_domain/serverConfig> updateIRMTestContent(0,
\"http://irm.example.com/exampleImage.jpg\", \"en,fr\", \"Test Content
(English),Test Content (French)\")
```

16.5 Languages Support Commands

Use the WLST commands listed in [Table 16-6](#) to set up languages support for users of Oracle IRM Server.

Table 16–6 WLST Commands for Oracle IRM Server languages support

Use this command...	To...	Use with WLST...
<code>addIRMTranslation</code>	Create a new language support instance.	Online
<code>getIRMDefaultTranslation</code>	Display the default language.	Online
<code>getIRMTranslations</code>	Display all the language support instances.	Online
<code>removeIRMTranslation</code>	Remove an existing language support instance.	Online
<code>setIRMTranslations</code>	Set the default language, and set a language support instance for one or more additional languages.	Online

16.5.1 addIRMTranslation

Online command that creates a new language support instance.

16.5.1.1 Description

This command creates a new language support instance. Each language support instance provides the facility in Oracle IRM Server to add names and descriptions in one or more languages (in addition to the default language).

16.5.1.2 Syntax

```
addIRMTranslation(transList)
```

Argument	Definition
<i>transList</i>	Specifies the supported language(s). Must be from the list of two-letter language codes given in Table 16–5 (for example, 'fr' for French). If there is more than one supported language for an instance, the two-letter codes must be listed as comma-separated values.

16.5.1.3 Examples

The following example creates a language support instance that will enable users of Oracle IRM Server to add names and descriptions in French (in addition to their default language):

```
wls:/base_domain/serverConfig> addIRMTranslation(\"fr\")
```

The following example creates a language support instance that will enable users of Oracle IRM Server to add names and descriptions in French and Arabic (in addition to their default language):

```
wls:/base_domain/serverConfig> addIRMTranslation(\"fr,ar\")
```

16.5.2 getIRMDefaultTranslation

Online command that displays the default language.

16.5.2.1 Description

This command displays the default language.

16.5.2.2 Syntax

```
getIRMDefaultTranslation()
```

16.5.2.3 Example

```
wls:/base_domain/serverConfig> getIRMDefaultTranslation()
```

16.5.3 getIRMTranslations

Online command that displays all the language support instances.

16.5.3.1 Description

This command displays all the language support instances. Each language support instance provides the facility in Oracle IRM Server to add names and descriptions in one or more languages (in addition to the default language).

16.5.3.2 Syntax

```
getIRMTranslations()
```

16.5.3.3 Example

```
wls:/base_domain/serverConfig> getIRMTranslations()
```

16.5.4 removeIRMTranslation

Online command that removes an existing language support instance.

16.5.4.1 Description

This command removes the language support instance that is present at the specified index. Each language support instance provides the facility in Oracle IRM Server to add names and descriptions in one or more languages (in addition to the default language).

16.5.4.2 Syntax

```
removeIRMTranslation(tindex)
```

Argument	Definition
<i>tindex</i>	Specifies the index of the language support instance.

16.5.4.3 Examples

The following example removes the language support instance at index zero:

```
wls:/base_domain/serverConfig> removeIRMTranslation(0)
```

The following example removes the language support instance at index one:

```
wls:/base_domain/serverConfig> removeIRMTranslation(1)
```

16.5.5 setIRMTranslations

Online command that sets the default language, and sets a language support instance for one or more languages in addition to the default language.

16.5.5.1 Description

This command sets the default language, and sets a language support instance for one or more languages in addition to the default language. Each language support instance provides the facility in Oracle IRM Server to add names and descriptions in one or more languages (in addition to the default language).

16.5.5.2 Syntax

```
setIRMTranslations(defaultTrans,transList)
```

Argument	Definition
<i>defaultTrans</i>	Specifies the default language. Language code (for example, 'en' for English).
<i>transList</i>	Specifies the supported language(s). Must be from the list of two-letter language codes given in Table 16-5 (for example, 'fr' for French). If there is more than one supported language for an instance, the two-letter codes must be listed as comma-separated values.

16.5.5.3 Examples

The following example enables users of Oracle IRM Server to enter names and descriptions in English as the default language, and additionally to enter names and descriptions in French:

```
wls:/base_domain/serverConfig> setIRMTranslations(\"en\",\"fr\")
```

The following example enables users of Oracle IRM Server to enter names and descriptions in English as the default language, and additionally to enter names and descriptions in French and Arabic:

```
wls:/base_domain/serverConfig> setIRMTranslations(\"en\",\"fr,ar\")
```

16.6 Oracle IRM Desktop Installers Commands

Use the WLST commands listed in [Table 16-7](#) to set up installation support for Oracle IRM Desktop software.

Table 16-7 WLST Oracle IRM Desktop Installers Commands

Use this command...	To...	Use with WLST...
addIRMDownload	Create a new installer.	Online
getIRMDownload	Display the details for an existing installer.	Online
getIRMDownloads	Display the details for all installers.	Online
removeIRMDownload	Remove an existing installer.	Online
updateIRMDownload	Update an existing installer.	Online

16.6.1 addIRMDownload

Online command that creates a new installer.

16.6.1.1 Description

This command creates a new installer. Each installer identifies the locale and URI of software for installing Oracle IRM Desktop, and displays a name and version number that enables users of Oracle IRM Server to select the installer.

16.6.1.2 Syntax

```
addIRMDownload(locale,name,version,uri)
```

Argument	Definition
<i>locale</i>	Specifies the locale of the installer. Must be from the list of two-letter language codes given in Table 16-5 (for example, 'en' for English).
<i>name</i>	Specifies the name for the installer.
<i>version</i>	Specifies the version of the installer. This is a label for the installer, and is not verified against the associated installation software.
<i>uri</i>	Specifies the URI of Oracle IRM Desktop installation software.

16.6.1.3 Example

The following example creates an installer for English language installation software at <http://irm.example.com/>, with the name 'Oracle IRM Desktop' and the version number 11.1.1.1.0.0 visible to users of Oracle IRM Server when they select this installer:

```
wls:/base_domain/serverConfig> addIRMDownload(\"en\", \"Oracle IRM
Desktop\", \"11.1.1.1.0.0\", \"http://irm.example.com/\")
```

16.6.2 getIRMDownload

Online command that displays the details for an existing installer.

16.6.2.1 Description

This command displays the details for an installer that is present at the specified index. Each installer identifies the locale and URI of software for installing Oracle IRM Desktop, and displays a name and version number that enables users of Oracle IRM Server to select the installer.

16.6.2.2 Syntax

```
getIRMDownload(dindex)
```

Argument	Definition
<i>dindex</i>	Specifies the index of the download.

16.6.2.3 Examples

The following example displays the details for the installer at index zero:

```
wls:/base_domain/serverConfig> getIRMDownload(0)
```

The following example displays the details for the installer at index one:

```
wls:/base_domain/serverConfig> getIRMDownload(1)
```

16.6.3 getIRMDownloads

Online command that displays the details of all installers.

16.6.3.1 Description

This command displays the details of all installers. Each installer identifies the locale and URI of software for installing Oracle IRM Desktop, and displays a name and version number that enables users of Oracle IRM Server to select the installer.

16.6.3.2 Syntax

```
getIRMDownloads()
```

16.6.3.3 Example

```
wls:/base_domain/serverConfig> getIRMDownloads()
```

16.6.4 removeIRMDownload

Online command that removes an existing installer.

16.6.4.1 Description

Removes the installer that is present at the specified index. Each installer identifies the locale and URI of software for installing Oracle IRM Desktop, and displays a name and version number that enables users of Oracle IRM Server to select the installer.

16.6.4.2 Syntax

```
removeIRMDownload(dindex)
```

Argument	Definition
<i>dindex</i>	Specifies the index of the download.

16.6.4.3 Examples

The following example removes the installer at index zero:

```
wls:/base_domain/serverConfig> removeIRMDownload(0)
```

The following example removes the installer at index one:

```
wls:/base_domain/serverConfig> removeIRMDownload(1)
```

16.6.5 updateIRMDownload

Online command that updates an existing installer.

16.6.5.1 Description

This command updates an existing installer. Each installer identifies the locale and URI of software for installing Oracle IRM Desktop, and displays a name and version number that enables users of Oracle IRM Server to select the installer.

16.6.5.2 Syntax

```
updateIRMDownload(dindex, locale, name, version, uri)
```

Argument	Definition
<i>dindex</i>	Specifies the index of the installer. Integer.

Argument	Definition
<i>locale</i>	Specifies the locale of the download. Must be from the list of two-letter language codes given in Table 16-5 (for example, 'en' for English).
<i>name</i>	Specifies the name for the installer.
<i>version</i>	Specifies the version of the installer. This is a label for the installer, and is not verified against the associated installation software.
<i>uri</i>	Specifies the URI for the Oracle IRM Desktop installation software.

16.6.5.3 Example

The following example updates the installer for index zero. After the update, the installation software is English language and is located at `http://irm.example.com/`. The name 'Oracle IRM Desktop (English)' and the version number 11.1.1.1.0.0 will be visible to users of Oracle IRM Server when they select this installer.

```
wls:/base_domain/serverConfig> updateIRMDownload(0,\"en\", \"Oracle IRM Desktop  
(English)\", \"11.1.1.1.0.0\", \"http://irm.example.com/\")
```

Oracle WebCenter: Imaging Custom WLST Commands

This chapter provides detailed descriptions of custom WLST commands for Oracle WebCenter: Imaging, including command syntax, arguments and command examples.

The following sections describe the WLST commands that are specific to Oracle WebCenter: Imaging. Topics include:

- [Section 17.1, "Overview of Imaging WLST Command Categories"](#)
- [Section 17.2, "Diagnostic Commands"](#)
- [Section 17.3, "Imaging Configuration Commands"](#)

17.1 Overview of Imaging WLST Command Categories

WLST commands specific to Imaging are divided into the following categories.

Table 17-1 *Imaging WLST Command Categories*

Command category	Description
Diagnostic Commands	Return workflow agent and other processing information.
Imaging Configuration Commands	Configure settings specific to Imaging and Process Management.

17.2 Diagnostic Commands

Use the Imaging WLST diagnostic commands, listed in [table Table 17-2](#), to list and organize processing failures during workflow processes.

Table 17-2 *Diagnostic Commands for Imaging*

Use this command...	To...	Use with WLST...
clearIPMWorkflowFaults	Clear processing failures that occurred during workflow agent processing.	Online
listIPMWorkflowFaults	Provide details of processing failures that occurred during workflow agent processing.	Online
repairIPMWorkflowFaults	Repair processing failures that occurred during workflow agent processing.	Online
sumIPMWorkflowFaults	Count processing failures during workflow agent processing, grouped by choice of date, application ID, or batch ID.	Online

Table 17-2 (Cont.) Diagnostic Commands for Imaging

Use this command...	To...	Use with WLST...
resetIpmDMSMetrics	Reset DMS metrics to zero.	Online

17.2.1 clearIPMWorkflowFaults

Command Category: Diagnostic Commands

Use with WLST: Online

17.2.1.1 Description

Clear processing failures that have occurred during workflow agent processing.

17.2.1.2 Syntax

```
clearIPMWorkflowFaults([startDate], [endDate], [appId], [batchId])
```

Argument	Definition
<i>startDate</i>	Optional. The start of the date range for which error details should be repaired, in yyyy-MM-dd format.
<i>endDate</i>	Optional. The end of the date range for which error details should be repaired, in yyyy-MM-dd format.
<i>appId</i>	Optional. The application ID for which error details should be repaired, in yyyy-MM-dd format.
<i>batchId</i>	Optional. The batch ID for which error details should be repaired.

17.2.1.3 Example

The following example clears the faults within the specified parameters.

```
clearIPMWorkflowFaults(startDate="2009-06-01", endDate="2009-06-02")
clearIPMWorkflowFaults(appId=3)
clearIPMWorkflowFaults(batchId=15)
clearIPMWorkflowFaults(startDate="2009-06-01", endDate="2009-06-02", appId=3)
```

17.2.2 listIPMWorkflowFaults

Command Category: Diagnostic Commands

Use with WLST: Online

17.2.2.1 Description

List details on processing failures that have occurred during workflow agent processing.

17.2.2.2 Syntax

```
listIPMWorkflowFaults([startDate], [endDate], [appId], [batchId])
```

Argument	Definition
<i>startDate</i>	Optional. The start of the date range for which error details should be repaired, in yyyy-MM-dd format.

Argument	Definition
<i>endDate</i>	Optional. The end of the date range for which error details should be repaired, in yyyy-MM-dd format.
<i>appId</i>	Optional. The application ID for which error details should be repaired.
<i>batchId</i>	Optional. The batch ID for which error details should be repaired.

17.2.2.3 Example

The following example lists the faults within the specified parameters.

```
listIPMWorkflowFaults(startDate="2009-06-01", endDate="2009-06-02")
listIPMWorkflowFaults(appId=3)
listIPMWorkflowFaults(batchId=15)
listIPMWorkflowFaults(startDate="2009-06-01", endDate="2009-06-02", appId=3)
```

17.2.3 repairIPMWorkflowFaults

Command Category: Diagnostic Commands

Use with WLST: Online

17.2.3.1 Description

Repair processing failures that have occurred during workflow agent processing.

17.2.3.2 Syntax

```
repairIPMWorkflowFaults([startDate], [endDate], [appId], [batchId])
```

Argument	Definition
<i>startDate</i>	Optional. The start of the date range for which error details should be repaired, in yyyy-MM-dd format.
<i>endDate</i>	Optional. The end of the date range for which error details should be repaired, in yyyy-MM-dd format.
<i>appId</i>	Optional. The application ID for which error details should be repaired.
<i>batchId</i>	Optional. The batch ID for which error details should be repaired.

17.2.3.3 Example

The following example repairs the faults within the specified parameters.

```
repairIPMWorkflowFaults(startDate="2009-06-01", endDate="2009-06-02")
repairIPMWorkflowFaults(appId=3)
repairIPMWorkflowFaults(batchId=15)
repairIPMWorkflowFaults(startDate="2009-06-01", endDate="2009-06-02", appId=3)
```

17.2.4 sumIPMWorkflowFaults

Command Category: Diagnostic Commands

Use with WLST: Online

17.2.4.1 Description

Provides a count of processing failures that have occurred during workflow agent processing. The results are grouped by date, application ID, or batch ID.

17.2.4.2 Syntax

```
sumIPMWorkflowFaults (group)
```

Argument	Definition
<i>groupOption</i>	Required. One of the following: <ul style="list-style-type: none"> ■ DATE: Returns fault counts grouped by date. ■ APPID: Returns fault counts grouped by application ID. ■ BATCHID: Returns fault counts grouped by batch ID.

17.2.4.3 Example

The following example returns all workflow faults grouped first by date, then by applications ID, then again grouped by batch ID.

```
sumIPMWorkflowFaults (group="DATE")
sumIPMWorkflowFaults (group="APPID")
sumIPMWorkflowFaults (group="BATCHID")
```

17.2.5 resetIpmDMSMetrics

Command Category: Diagnostic Commands

Use with WLST: Online

17.2.5.1 Description

Resets all Dynamic Monitoring Server (DMS) metrics associated with I/PM to zero. This is generally done if the administrator finds that historical performance data is skewing the current results.

17.2.5.2 Syntax

```
resetIpmDMSMetrics()
```

17.2.5.3 Example

The following example resets all DMS metrics to zero.

```
resetIpmDMSMetrics()
```

17.3 Imaging Configuration Commands

Use the Imaging configuration commands, listed in [Table 17-3](#), to list and set configuration values specific to Imaging.

Table 17-3 Configuration Commands for Imaging

Use this command...	To...	Use with WLST...
createIPMConnection	Creates a new Imaging connection from a connection definition file.	Online

Table 17-3 (Cont.) Configuration Commands for Imaging

Use this command...	To...	Use with WLST...
<code>getIPMConfig</code>	Get an Imaging configuration setting value, similar to navigating to the custom Imaging config mbean and using the standard WLST <i>set</i> command.	Online
<code>grantIPMCredAccess</code>	Grants CredentialAccessPermissions to Imaging when Imaging Managed Servers are in a separate domain home from the Administration Server.	Online
<code>importIPMApplication</code>	Imports an application definition from a previously exported definition file.	Online
<code>importIPMInput</code>	Imports an input definition from a previously exported definition file.	Online
<code>importIPMSearch</code>	Imports a search definition from a previously exported definition file.	Online
<code>listIPMConfig</code>	Lists Imaging configuration mbeans.	Online
<code>listIPMExportFile</code>	Lists the contents of an exported Imaging definitions file.	Online
<code>refreshIPMSecurity</code>	Refresh security items currently stored in the Imaging database.	Online
<code>setIPMConfig</code>	Sets an Imaging configuration value.	Online
<code>submitIPMToWorkflow</code>	Submits a document to the workflow agent.	Online

17.3.1 createIPMConnection

Command Category: Imaging Configuration Commands

Use with WLST: Online

17.3.1.1 Description

Creates a new Imaging connection from a connection definition file. The connection definition file is an XML file that describes a single Imaging connection definition using the Connection element type from the Imaging ConnectionService web services API schema definition. This schema is available from a running Imaging server using at the following URL:

`http://ipm_server_machine:ipm_server_port/imaging/ws/ConnectionService?xsd=1`

For more information about the connection definition file format, see the *Oracle Fusion Middleware Administering Oracle WebCenter Content: Imaging*.

17.3.1.2 Syntax

```
createIPMConnection(connectionFile)
```

Argument	Definition
<code>connectionFile</code>	Required. A full path to the connection definition file's location on the Imaging server Node. Must be enclosed in single or double quotes.

17.3.1.3 Example

The following example creates a connection based on the specified attribute.

```
createIPMConnection(connectionFile="/home/ipmuser/localCSConnection.xml")
```

17.3.2 getIPMConfig

Command Category: Imaging Configuration Commands

Use with WLST: Online

17.3.2.1 Description

Gets an Imaging configuration setting value. The command is equivalent to browsing the custom mbean hierarchy to the Imaging config mbean and using the standard WLST *set* command to set an mbean attribute.

17.3.2.2 Syntax

```
getIPMConfig(attrName)
```

Argument	Definition
<i>attrName</i>	Required. Name of the attribute to be read. Must be enclosed in single or double quotes.

17.3.2.3 Example

The following example returns the value for the specified attribute names.

```
getIPMConfig('AgentUser')
getIPMConfig('CheckInterval')
```

17.3.3 grantIPMCredAccess

Command Category: Imaging Configuration Commands

Use with WLST: Online

17.3.3.1 Description

Grants CredentialAccessPermissions to Imaging so that it can read credentials from the credential store. This command is required in configurations where Imaging managed servers are in a separate domain home from the Administration Server. When at least one Imaging managed server is in the same domain home as the Administration Server, this command is not required, as CredentialAccessPermissions are granted during Imaging startup.

When the Imaging Managed Server is not in the same domain home as the Administration Server, however, the Imaging startup grant only affects the local settings. Local settings get overwritten when the Administration Server synchronizes its copy as the domain wide configuration, so this command updates the Administration Server configuration such that permissions are distributed correctly to all domain nodes.

17.3.3.2 Syntax

```
grantIPMCredAccess()
```

17.3.3.3 Example

The following example returns a list of all Imaging configuration mbeans.

```
grantIPMCredAccess()
```

17.3.4 importIPMApplication

Command Category: Imaging Configuration Commands

Use with WLST: Online

17.3.4.1 Description

Imports an application definition from a previously exported definition file.

17.3.4.2 Syntax

```
importIPMApplication(exportFile, action, name, repository, securityOption,
securityMember, docSecurityOption, docSecurityGroup, storageOption, storageVolume)
```

Argument	Definition
<i>exportFile</i>	Required. A full path to the export definition file's location on the Imaging server node. Must be enclosed in single or double quotes.
<i>action</i>	Required. The action to be performed. Available actions are: <ul style="list-style-type: none"> ▪ Add: Creates a new input. Fails if an application with the same name already exists. ▪ Update: Modifies an existing input. Fails if an application with the same name does not exist. ▪ AddOrUpdate: Creates a new application if it does not already exist or updates one that does.
<i>name</i>	Required. The name of the application being imported from the exported definitions file.
<i>repository</i>	The name of the repository in which to create the application. Required when adding an application, ignored when updating or modifying an application.
<i>securityOption</i>	Optional. Specifies how to define security for the imported application as follows: <ul style="list-style-type: none"> ▪ Existing: Uses application security as defined in the existing definition. Valid only for an update action. ▪ Imported: Attempts to use application security as defined in the import file. Fails if any members defined in the import file are invalid. ▪ ValidOnly: Uses application security as defined in the import file and filters out any invalid members. ▪ CurrentUser: Sets full permissions to the user used to connect to the server. ▪ User: Sets full permissions to the user name provided in the securityMember parameter. ▪ Group: Sets full permissions to the group name provided in the securityMember parameter.
<i>securityMember</i>	Name of the user or group given full permissions to the application. Valid only when securityOption is set to either <i>User</i> or <i>Group</i> , otherwise it is ignored.

Argument	Definition
<i>docSecurityOption</i>	Optional. Specifies how to define document security for the imported application. <ul style="list-style-type: none"> ▪ Existing: Uses document security as defined in the existing application. Valid only for an update action. ▪ Imported: Attempts to use document security as defined in the import file. Fails if any members defined in the import file are invalid. ▪ ValidOnly: Uses document security as defined in the import file and filters out any invalid members. ▪ Group: Sets full permissions to the group name provided in the docSecurityGroup parameter.
<i>docSecurityGroup</i>	Name of group given full permissions to document security. Valid only when docSecurityOption is set to <i>Group</i> , otherwise it is ignored.
<i>storageOption</i>	Optional. Specifies how to define the storage policy for the imported application. <ul style="list-style-type: none"> ▪ Existing: Uses the document storage policy as defined in the existing application. Valid only for an update action. ▪ Imported: Attempts to use storage policy as defined in the import file. ▪ Volume: Uses the specific volume named in the storageVolume parameter. ▪ Default: Sets up the storage policy to use the system default volume.
<i>storageVolume</i>	Required. Volume for setting storage policy. Valid only when a storageOption of <i>Volume</i> is used. Ignored otherwise.

17.3.4.3 Example

The following example updates an existing application named *Invoices*. Note that the repository is listed as **None** because the update action uses the repository specified in the original application.

```
importIPMApplication(exportFile="/home/ipmuser/exportdefinitions.xml",
action="Update", name="Invoices", repository=None, securityOption="Existing")
```

17.3.4.4 Example

The following example creates a new application named *Receipts*. Note that the repository is explicitly named because the add action requires a valid repository be named.

```
importIPMApplication(exportFile="/home/ipmuser/exportdefinitions.xml",
action="Add", name="Receipts", repository="LocalCS", securityOption="ValidOnly")
```

17.3.5 importIPMInput

Command Category: Imaging Configuration Commands

Use with WLST: Online

17.3.5.1 Description

Imports an input definition from a previously exported definition file.

17.3.5.2 Syntax

```
importIPMInput(exportFile, action, name, securityOption, securityMember)
)
```

Argument	Definition
<i>exportFile</i>	Required. A full path to the export definition file's location on the Imaging server node. Must be enclosed in single or double quotes.
<i>action</i>	Required. The action to be performed. Available actions are: <ul style="list-style-type: none"> ▪ Add: Creates a new input. Fails if an input with the same name already exists. ▪ Update: Modifies an existing input. Fails if an input with the same name does not exist. ▪ AddOrUpdate: Creates a new application if it does not already exist or updates one that does.
<i>name</i>	Required. The name of the input being imported from the exported definitions file.
<i>repository</i>	The name of the repository in which to create the application. Required when adding an application, ignored when updating or modifying an application.
<i>securityOption</i>	Optional. Specifies how to define security for the imported application as follows: <ul style="list-style-type: none"> ▪ Existing: Uses input security as defined in the existing definition. Valid only for an update action. ▪ Imported: Attempts to use input security as defined in the import file. Fails if any members defined in the import file are invalid. ▪ ValidOnly: Uses input security as defined in the import file and filters out any invalid members. ▪ CurrentUser: Sets full permissions to the user used to connect to the server. ▪ User: Sets full permissions to the user name provided in the securityMember parameter. ▪ Group: Sets full permissions to the group name provided in the securityMember parameter.
<i>securityMember</i>	Name of the user or group given full permissions to the input. Valid only when securityOption is set to either <i>User</i> or <i>Group</i> , otherwise it is ignored.

17.3.5.3 Example

The following example updates an existing input named *Invoices*. Note that the repository is listed as **None** because the update action uses the repository specified in the original application.

```
importIPMInput(exportFile="/home/ipmuser/exportdefinitions.xml", action="Update",
name="Invoices", securityOption="Existing")
```

17.3.5.4 Example

The following example creates a new input named *Receipts*. Note that the repository is explicitly named because the add action requires a valid repository be named.

```
importIPMInput(exportFile="/home/ipmuser/exportdefinitions.xml", action="Add",
name="Receipts", securityOption="ValidOnly")
```

17.3.6 importIPMSearch

Command Category: Imaging Configuration Commands

Use with WLST: Online

17.3.6.1 Description

Import a search definition from a previously exported definition file.

17.3.6.2 Syntax

```
importIPMSearch(exportFile, action, name, securityOption, securityMember)
```

Argument	Definition
<i>exportFile</i>	Required. A full path to the export definition file's location on the Imaging server node. Must be enclosed in single or double quotes.
<i>action</i>	Required. The action to be performed. Available actions are: <ul style="list-style-type: none"> ▪ Add: Creates a new search. Fails if a search with the same name already exists. ▪ Update: Modifies an existing search. Fails if a search with the same name does not exist. ▪ AddOrUpdate: Creates a new search if it does not already exist or updates one that does.
<i>name</i>	Required. The name of the search being imported from the exported definitions file.
<i>repository</i>	The name of the repository in which to create the application. Required when adding an application, ignored when updating or modifying an application.
<i>securityOption</i>	Optional. Specifies how to define security for the imported application as follows: <ul style="list-style-type: none"> ▪ Existing: Uses search security as defined in the existing definition. Valid only for an update action. ▪ Imported: Attempts to use search security as defined in the import file. Fails if any members defined in the import file are invalid. ▪ ValidOnly: Uses search security as defined in the import file and filters out any invalid members. ▪ CurrentUser: Sets full permissions to the user used to connect to the server. ▪ User: Sets full permissions to the user name provided in the securityMember parameter. ▪ Group: Sets full permissions to the group name provided in the securityMember parameter.
<i>securityMember</i>	Name of the user or group given full permissions to the search. Valid only when securityOption is set to either <i>User</i> or <i>Group</i> , otherwise it is ignored.

17.3.6.3 Example

The following example updates an existing search named *Invoices*. Note that the repository is listed as **None** because the update action uses the repository specified in the original application.


```
importIPMSearch(exportFile="/home/ipmuser/exportdefinitions.xml", action="Update",
name="Invoices", securityOption="Existing")
```

17.3.6.4 Example

The following example creates a new search named *Receipts*. Note that the repository is explicitly named because the add action requires a valid repository be named.

```
importIPMSearch(exportFile="/home/ipmuser/exportdefinitions.xml", action="Add",
name="Receipts", securityOption="ValidOnly")
```

17.3.7 listIPMConfig

Command Category: Imaging Configuration Commands

Use with WLST: Online

17.3.7.1 Description

Provides a listing of Imaging configuration mbeans. The command is equivalent to browsing the custom mbean hierarchy and listing the Imaging mbean attributes.

17.3.7.2 Syntax

```
listIPMConfig()
```

17.3.7.3 Example

The following example returns a list of all Imaging configuration mbeans.

```
listIPMConfig()
```

17.3.8 listIPMExportFile

Command Category: Imaging Configuration Commands

Use with WLST: Online

17.3.8.1 Description

Lists the contents of an exported Imaging definitions file.

17.3.8.2 Syntax

```
listIPMExportFile(exportFile="<path to file>")
```

Argument	Definition
<i>exportFile</i>	Required. A full path to the export definition file's location on the Imaging server node. Must be enclosed in single or double quotes.

17.3.8.3 Example

The following example returns the contents of an Imaging definitions file.

```
listIPMExportFile(exportFile="/home/ipmuser/exportdefinitions.xml")
```

17.3.9 refreshIPMSecurity

Command Category: Imaging Configuration Commands

Use with WLST: Online

17.3.9.1 Description

Refreshes security items currently stored in the Imaging database. This is typically done when migrating security to a different policy store and only updates security items found in the new policy store.

17.3.9.2 Syntax

```
refreshIPMSecurity()
```

17.3.9.3 Example

The following example refreshes the security items stored in the Imaging database.

```
refreshIPMSecurity()
```

17.3.10 setIPMConfig

Command Category: Imaging Configuration Commands

Use with WLST: Online

17.3.10.1 Description

Sets an Imaging configuration setting value. The command is equivalent to browsing the custom mbean hierarchy to the Imaging config mbean and using the standard WLST 'set' command to set an mbean attribute.

17.3.10.2 Syntax

```
setIPMConfig(attrName, value)
```

Argument	Definition
<i>attrName</i>	Required. Name of the attribute to be set. Must be enclosed in single or double quotes.
<i>value</i>	Required. Value of the attribute to be set. Only enclosed in single or double quotes if value is a string literal.

17.3.10.3 Example

The following example sets the specified values for the specified attribute names.

```
setIPMConfig('AgentUser', 'agentadmin')  
setIPMConfig('CheckInterval', 30)
```

17.3.11 submitIPMToWorkflow

Command Category: Imaging Configuration Commands

Use with WLST: Online

17.3.11.1 Description

Submits a document to the workflow agent. Note that a confirmation message is displayed stating that the document has been submitted, however if the document is stored in an application that is not configured with a workflow, no action is taken.

17.3.11.2 Syntax

```
submitIPMToWorkflow(documentId)
```

Argument	Definition
<i>documentId</i>	Required. The unique document ID of the submitted document.

17.3.11.3 Example

The following example submits a document to a workflow.

```
submitIPMToWorkflow(documentId="2.IPM_12345")
```


Oracle Business Process Management Custom WLST Commands

This chapter provides detailed descriptions of custom WLST commands for Business Process Management (BPM), including command syntax, arguments and command examples.

This chapter lists and describes the custom WLST commands for Oracle Business Process Management.

18.1 BPMLifecycleAdmin Command Group

Table 18–1 lists and describes the BPMLifecycleAdmin commands for project lifecycle administration.

Table 18–1 *BPMLifecycleAdmin Commands for Project Lifecycle Administration*

Use this command...	To...	Use with WLST...
<code>create_public_share</code>	Create a public share.	Offline
<code>unlock_public_share</code>	Unlock a public share.	Offline
<code>export_public_share</code>	Export a public share to the file system.	Offline
<code>delete_public_share</code>	Delete a public share.	Offline
<code>publish_template</code>	Publish a template to MDS.	Offline
<code>export_template</code>	Export a template to the file system.	Offline
<code>delete_template</code>	Delete a template from MDS.	Offline
<code>connectProjectRepository</code>	Establish the connection to the MDS project repository.	Offline
<code>disconnectProjectRepository</code>	Close the connection from MDS project repository.	Offline
<code>importProject</code>	Import a project from disk into the project repository.	Offline
<code>createProject</code>	Create a public share project based on a Template project.	Offline
<code>deleteProject</code>	Delete a project from the project repository.	Offline
<code>exportProject</code>	Export a project stored in the repository to disk.	Offline
<code>unlockProject</code>	Unlock a project.	Offline

18.1.1 create_public_share

Command Category: BPMLifecycleAdmin Commands

Use with WLST: Offline

18.1.1.1 Description

Use this command to create a public share from a template. The template must exist in MDS.

18.1.1.2 Syntax

```
create_public_share(composerUser, composerPassword, connectionURL, templateName,
publicshareId, mdsconfigLocation, [Override], [oracleHome] )
```

Argument	Definition
<i>composerUser</i>	The Business Process Composer user who performs the current operation.
<i>composerPassword</i>	BPM Composer user's password
<i>connectionURL</i>	JNDI connection URL to the security server service in format <i>host:port</i>
<i>templateName</i>	Name of the template in MDS
<i>publicshareId</i>	Name of the public share to be created
<i>mdsconfigLocation</i>	Location of the <i>mds-config.xml</i> to be used to connect to MDS
<i>projectLocation</i>	The path where the public share will be created. If the path does not exist it will be created. The root is '/'.
<i>Override</i>	Enables you to override the public share if a public share exists in MDS with the same name. The template is not overwritten when you execute this command.
<i>oracleHome</i>	Optional. The Oracle home to be used.

18.1.1.3 Examples

The following example creates a public share named `Sample_PublicShare`. It is based on the template with name `Sample_Template`. The name of the public share is `Sample_PublicShare`, and the location of the `mds-config.xml` file is `/tmp/mds-config.xml`.

```
create_public_share('user_name', 'password', 'host:port', 'Sample_Template',
'Sample_PublicShare', '/tmp/mds-config.xml')
```

The following example creates a public share named `Sample_PublicShare`. It is based on the template named `Sample_Template` that exists in MDS. The public share, not the template, is overridden. The location of the `mds-config.xml` file is `/tmp/mds-config.xml`.

```
create_public_share('user_name', 'password', 'host:port', 'Sample_Template',
'Sample_PublicShare', '/tmp/mds-config.xml', 'true')
```

18.1.2 unlock_public_share

Command Category: BPMLifecycleAdmin Commands

Use with WLST: Offline

18.1.2.1 Description

Use this command to unlock a public share. For example, when you create a project by using the Ant task `create_public_share` command, the project is created as locked. You can then unlock it by using the `unlock_public_share` command.

A lock is also set by enabling or disabling the check box **enable sharing** in the project creation page in Oracle Business Process Composer.

It is also released when the user publishes a project from Business Process Composer.

The public share must exist in MDS.

18.1.2.2 Syntax

```
unlock_public_share(composerUser, composerPassword, connectionURL, publicshareId,
mdsconfigLocation, [oracleHome] )
```

Argument	Definition
<i>composerUser</i>	The Business Process Composer user who performs the current operation.
<i>composerPassword</i>	BPM Composer user's password
<i>connectionURL</i>	JNDI connection URL to the security server service in format <i>host:port</i>
<i>publicshareId</i>	Name of the public share to be unlocked
<i>mdsconfigLocation</i>	Location of the <code>mds-config.xml</code> to be used to connect to MDS
<i>oracleHome</i>	Optional. The Oracle home to be used

18.1.2.3 Example

The following example unlocks a public share named `Sample_PublicShare`. The location of the `mds-config.xml` file is `/tmp/mds-config.xml`.

```
unlock_public_share('user_name', 'password', 'host:port', 'Sample_PublicShare',
'/tmp/mds-config.xml')
```

18.1.3 export_public_share

Command Category: BPMLifecycleAdmin Commands

Use with WLST: Offline

18.1.3.1 Description

Use this command to export the public share from MDS to the file system.

18.1.3.2 Syntax

```
export_public_share(composerUser, composerPassword, connectionURL,
publicshareId, fsLocation, mdsconfigLocation, [oracleHome] )
```

Argument	Definition
<i>composerUser</i>	The Business Process Composer user who performs the current operation.
<i>composerPassword</i>	BPM Composer user's password
<i>connectionURL</i>	JNDI connection URL to the security server service in format <i>host:port</i>

Argument	Definition
<i>publicshareId</i>	Name of the public share to be exported
<i>fsLocation</i>	File system location where the project is to be downloaded
<i>mdsconfigLocation</i>	Location of the <code>mds-config.xml</code> to be used to connect to MDS
<i>oracleHome</i>	Optional. The Oracle home to be used

18.1.3.3 Example

The following example specifies the public share name as `Sample_PublicShare`, the file system location as `/tmp`, and the location of the `mds-config.xml` file as `/tmp/mds-config.xml`.

```
export_public_share('user_name', 'password', 'host:port', 'Sample_
PublicShare', '/tmp', '/tmp/mds-config.xml')
```

18.1.4 delete_public_share

Command Category: BPMLifecycleAdmin Commands

Use with WLST: Offline

18.1.4.1 Description

Use this command to delete a public share from MDS. Executing this command requires that the public share is not locked.

18.1.4.2 Syntax

```
delete_public_share(composerUser, composerPassword, connectionURL, publicshareId,
mdsconfigLocation, [releaseLock], [oracleHome] )
```

Argument	Definition
<i>composerUser</i>	The Business Process Composer user who performs the current operation.
<i>composerPassword</i>	BPM Composer user's password
<i>connectionURL</i>	JNDI connection URL to the security server service in format <code>host:port</code>
<i>publicshareId</i>	Name of the public share to be deleted
<i>mdsconfigLocation</i>	Location of the <code>mds-config.xml</code> to be used to connect to MDS
<i>releaseLock</i>	Optional. If the public share is locked, this lock can be released and the delete operation completed. You can set this attribute to either <code>true</code> or <code>false</code> . If not specified, default value is <code>false</code> .
<i>oracleHome</i>	Optional. The Oracle home to be used

18.1.4.3 Examples

The following example specifies the name and location of a public share to be deleted.

```
delete_public_share('Sample_PublicShare', '/tmp/mds-config.xml')
```

The following example specifies the name and location of a public share to be deleted, and that the public share should be deleted even if locked.

```
delete_public_share('user_name', 'password', 'host:port', 'Sample_
PublicShare', '/tmp/mds-config.xml', 'true')
```


18.1.5 publish_template

Command Category: BPMLifecycleAdmin Commands

Use with WLST: Offline

18.1.5.1 Description

Use this command to publish the template from the file system to MDS.

18.1.5.2 Syntax

```
publish_template(composerUser, composerPassword, connectionURL, templateName,
fsLocation, mdsconfigLocation, [Override], [oracleHome] )
```

Argument	Definition
<i>composerUser</i>	The Business Process Composer user who performs the current operation.
<i>composerPassword</i>	BPM Composer user's password
<i>connectionURL</i>	JNDI connection URL to the security server service in format <i>host:port</i>
<i>templateName</i>	Name of the template to be published
<i>fsLocation</i>	File system location of the template project
<i>mdsconfigLocation</i>	Location of the <i>mds-config.xml</i> to be used to connect to MDS
<i>projectLocation</i>	The path where the public share will be created. If the path does not exist it will be created. The root is '/'.
<i>Override</i>	When you publish a template in MDS, this attribute enables you to override an existing template with the same name. Can either be 'true' or 'false'. If not specified, default value is 'false'.
<i>oracleHome</i>	Optional. The Oracle home to be used

18.1.5.3 Example

The following example publishes a template named `Sample_Template_Name_MDS`. to the root folder.

```
f('user_name', 'password', 'host:port', 'Sample_Template', '/tmp/MyTemplate', '/',
'/tmp/mds-config.xml')
```

The following example publishes a template named `Sample_Template_Name_MDS`.to the `/WorkingOn/` folder.

```
publish_template('user_name', 'password', 'host:port', 'Sample_
Template', '/tmp/MyTemplate', '/WorkingOn', '/tmp/mds-config.xml')
```

18.1.6 export_template

Command Category: BPMLifecycleAdmin Commands

Use with WLST: Offline

18.1.6.1 Description

Use this command to export the template from MDS to the file system.

18.1.6.2 Syntax

```
export_template(composerUser, composerPassword, connectionURL, templateName,
fsLocation, mdsconfigLocation, [oracleHome] )
```

Argument	Definition
<i>composerUser</i>	The Business Process Composer user who performs the current operation.
<i>composerPassword</i>	BPM Composer user's password
<i>connectionURL</i>	JNDI connection URL to the security server service in format <i>host:port</i>
<i>templateName</i>	Name of the template to be exported
<i>fsLocation</i>	File system location where the project is to be downloaded
<i>mdsconfigLocation</i>	Location of the <i>mds-config.xml</i> to be used to connect to MDS
<i>oracleHome</i>	Optional. The Oracle home to be used

18.1.6.3 Example

The following example specifies the template name as *Sample_Template*, the file system location as */tmp*, and the location of the *mds-config.xml* file as */tmp/mds-config.xml*.

```
export_template('user_name', 'password', 'host:port', 'Sample_
Template', '/tmp', '/tmp/mds-config.xml')
```

18.1.7 delete_template

Command Category: BPMLifecycleAdmin Commands

Use with WLST: Offline

18.1.7.1 Description

Use this command to delete the template from MDS.

18.1.7.2 Syntax

```
delete_template(composerUser, composerPassword, connectionURL, templateName,
mdsconfigLocation, [oracleHome] )
```

Argument	Definition
<i>composerUser</i>	The Business Process Composer user who performs the current operation.
<i>composerPassword</i>	BPM Composer user's password
<i>connectionURL</i>	JNDI connection URL to the security server service in format <i>host:port</i>
<i>templateName</i>	Name of the template to be deleted
<i>fsLocation</i>	File system location of the template project
<i>mdsconfigLocation</i>	Location of the <i>mds-config.xml</i> to be used to connect to MDS

Argument	Definition
<code>projectLocation</code>	The path where the public share will be created. If the path does not exist it will be created. The root is '/'.
<code>oracleHome</code>	Optional. The Oracle home to be used

18.1.7.3 Example

The following example deletes the template named `Sample_template` from MDS.

```
delete_template('weblogic', 'welcome1', 'host:port',
'/Sample_template', '/tmp/mds-config.xml')
```

18.1.8 connectProjectRepository

Command Category: BPMLifecycleAdmin Commands

Use with WLST: Offline

18.1.8.1 Description

Use this command to establish the connection to the MDS project repository.

18.1.8.2 Syntax

```
connectProjectRepository(connectionURL, mdsConfigLocation, composerUser,
composerPassword, [mdsDbUser], [mdsDbPassword])
```

Argument	Definition
<code>connectionURL</code>	JNDI connection URL to the security server service in format: <code>host:port</code>
<code>mdsConfigLocation</code>	The location of the <code>mds-config.xml</code> to be used to connect to MDS
<code>composerUser</code>	BPM Composer user. This user will perform the current operation.
<code>composerPassword</code>	BPM Composer user's password.
<code>mdsDbUser</code>	Optional. Overrides the mds database username stored in the <code>mds-config.xml</code> file.
<code>mdsDbPassword</code>	Optional. Overrides the MDS database password stored in the <code>mds-config.xml</code> file.

18.1.8.3 Examples

```
connectProjectRepository(connectionURL='localhost:7001',
mdsConfigLocation='/home/user/mds-config.xml', composerUser='weblogic',
composerPassword='welcome1')
```

```
connectProjectRepository(connectionURL='localhost:7001',
mdsConfigLocation='/home/user/mds-config.xml', composerUser='weblogic',
composerPassword='welcome1', mdsDbUser='DEV_MDS', mdsDbPassword='dbPassword')
```

18.1.9 disconnectProjectRepository

Command Category: BPMLifecycleAdmin Commands

Use with WLST: Offline

18.1.9.1 Description

Use this command to close the connection from MDS project repository.

18.1.9.2 Syntax

```
disconnectProjectRepository()
```

18.1.9.3 Example

```
disconnectProjectRepository()
```

18.1.10 importProject

Command Category: BPMLifecycleAdmin Commands

Use with WLST: Offline

18.1.10.1 Description

Use this command to import a project from disk into the project repository. All projects will be imported as a template—that is, it does not matter if the imported project is a template or public shared.

18.1.10.2 Syntax

```
importProject(srcDir, toName, [toPath], [override])
```

Argument	Definition
<i>srcDir</i>	The file system location of the template project.
<i>toName</i>	The file system location of the template project.
<i>toPath</i>	[Optional] The path where the template will be imported. If the path does not exist it will be created. If not specified, the root '/' will be used.
<i>override</i>	[Optional] Specifies whether the import should override an existing template with the same name. If not specified, 'false' will be used.

18.1.10.3 Examples

```
importProject(srcDir='/home/user/myFolder/myTemplate', toName='NewTemplateName')
```

```
importProject(srcDir='/home/user/myFolder/myTemplate', toName='NewTemplateName',  
toPath='/NewFolder', override='true')
```

18.1.10.4 Security Constraints

None. All users are allowed to import a project template. These templates are imported by default with public permissions granted to all users.

18.1.11 createProject

Command Category: BPMLifecycleAdmin Commands

Use with WLST: Offline

18.1.11.1 Description

Use this command to create a public share project based on a template project.

18.1.11.2 Syntax

```
createProject(fromId, toName, [toPath])
```

Argument	Definition
<i>fromId</i>	The identifier of the template in MDS.
<i>toName</i>	The name of the public share to be created.
<i>toPath</i>	[Optional] The path where the public share will be created. If the path does not exist it will be created. If not specified, the root '/' will be used.

18.1.11.3 Example

```
createProject(fromId='/SampleTemplate', toName='SamplePublicShare')
```

```
createProject(fromId='/folder/SampleTemplate', toName='SamplePublicShare',
toPath='/newFolder')
```

18.1.11.4 Security Constraints

None. All the users are allowed to create public shares based on the templates. All the templates in MDS are public by default.

18.1.12 deleteProject

Command Category: BPMLifecycleAdmin Commands

Use with WLST: Offline

18.1.12.1 Description

Use this command to delete a project from the project repository.

18.1.12.2 Syntax

```
deleteProject(id, [type], [breakLinks])
```

Argument	Definition
<i>id</i>	The identifier of the project to be deleted.
<i>type</i>	[Optional] Specified if the project is a template or a public share. Valid values: 'TEMPLATE', 'PUBLIC_SHARED'. If not specified, 'TEMPLATE' is assumed.
<i>breakLinks</i>	[Optional] Only valid when deleting templates. If there are public shares linked to this template, specifies whether the links should be removed or not. Default: 'true'

18.1.12.3 Example

```
deleteProject(id='/SampleTemplate', type='TEMPLATE', breakLinks='true')
```

```
deleteProject(id='/folder/SamplePublicShare', type='PUBLIC_SHARED')
```

18.1.12.4 Security Constraints

ADMIN | OWNER

To perform a delete operation, the user must have the role of either ADMIN or OWNER of the project to delete.

18.1.13 exportProject

Command Category: BPMLifecycleAdmin Commands

Use with WLST: Offline

18.1.13.1 Description

Use this command to export a project stored in the repository to disk.

18.1.13.2 Syntax

```
exportProject(id, toDir, [type])
```

Argument	Definition
<i>id</i>	The identifier of the project to be exported.
<i>toDir</i>	The file system location where the project has to be downloaded. If the path does not exist it will be created.
<i>type</i>	[Optional] Specified if the project is a template or a public share. Valid values: 'TEMPLATE', 'PUBLIC_SHARED'. If not specified, 'TEMPLATE' is assumed.

18.1.13.3 Examples

```
exportProject(id='/SampleTemplate', toDir='/home/user/myFolder', type='TEMPLATE')
```

```
exportProject(id='/aFolder/SamplePublicShare', toDir='/home/user/myFolder', type='PUBLIC_SHARED')
```

18.1.13.4 Security Constraints

ADMIN | OWNER | EDITOR | VIEWER

The user needs at least VIEWER permission of the project to be exported.

18.1.14 unlockProject

Command Category: BPMLifecycleAdmin Commands

Use with WLST: Offline

18.1.14.1 Description

Unlock a project. Only public share projects can be unlocked.

18.1.14.2 Syntax

```
unlockProject(id)
```

Argument	Definition
<i>id</i>	The identifier of the project to be unlocked.

18.1.14.3 Example

```
unlockProject(id='SamplePublicShare')
```

18.1.14.4 Security Constraints

ADMIN | OWNER | EDITOR

A project can be unlocked only by the same user or application that locked it. The exception is the administrator user who can unlock a project regardless of the user or application that locked it.

An application can be Oracle Business Process Composer, Oracle Business Process Management Studio, or a generic application. WLST functions are considered generic applications.

Note: Because there is no WLST lock operation for projects, an owner or editor user cannot release a project by using the WLST `unlockProject` command if the project was locked by a different application. In this case, only an administrator user can unlock the project.

Oracle WebCenter Content Custom WLST Commands

This chapter provides detailed descriptions of custom WLST commands for Oracle WebCenter Content, including command syntax, arguments and command examples.

The following sections describe the custom WLST commands for Oracle WebCenter Content. These commands enable you to configure and monitor the Oracle WebCenter Content server and the Oracle WebCenter Content Server instance from the command line. Topics include:

- [Section 19.1, "Overview of WLST WebCenter Content Command Categories"](#)
- [Section 19.2, "WLST WebCenter Content Help"](#)
- [Section 19.3, "Getter and Setter Methods Implementation"](#)
- [Section 19.4, "Server Configuration Commands"](#)
- [Section 19.5, "Email Configuration Commands"](#)
- [Section 19.6, "System Status Commands"](#)
- [Section 19.7, "General Configuration Commands"](#)
- [Section 19.8, "Content Security Configuration Commands"](#)
- [Section 19.9, "Component Manager Configuration Commands"](#)
- [Section 19.10, "Records Management Configuration Commands"](#)
- [Section 19.11, "User Interface Commands"](#)
- [Section 19.12, "User Interface Connection Commands"](#)

For additional information about Oracle Webcenter Content and Content Server administration and configuration, see *Oracle Fusion Middleware Administrator's Guide*.

Note: To use the Oracle Webcenter Content custom commands, you must invoke the WLST script from the Oracle Common home in which the component has been installed. See "Using Custom WLST Commands" in the *Oracle Fusion Middleware Administrator's Guide*.

19.1 Overview of WLST WebCenter Content Command Categories

WLST WebCenter Content commands are divided into the following categories:

Table 19–1 WLST WebCenter Content Command Categories

Command Category	Description
Server Configuration Commands	View and manage server configuration options for the Content Server instance.
Email Configuration Commands	View and manage email configuration options for the Content Server instance.
System Status Commands	View system status information for the Content Server instance.
General Configuration Commands	View and manage general configuration options for the Content Server instance.
Content Security Configuration Commands	View and manage content security configuration options for the Content Server instance.
Component Manager Configuration Commands	View and manage Component Manager configuration options for the Content Server instance.
Records Management Configuration Commands	View and manage records management configuration options for the Content Server instance.
User Interface Commands	View and manage configuration for the optional Oracle WebCenter Content user interface.
User Interface Connection Commands	View and manage connections for the Oracle WebCenter Content user interface introduced in WebCenter Content 11g Release 1 (11.1.1.8)

19.2 WLST WebCenter Content Help

To view the WebCenter Content UCM commands that can be invoked from WLST, enter the following command at the WLST prompt:

```
help('UCM')
```

To view help for a specific Oracle Webcenter Content command, specify the name of the command; for example:

```
help('getUCMServerPort')
```

```
help('wccAdfConfig')
```

19.3 Getter and Setter Methods Implementation

The WLST component for Oracle Webcenter Content uses **getter** and **setter** methods to handle a situation where multiple applications register their corresponding MBeans on a managed server, but WLST can talk to only one application.

Getter Method

The **getter** method is designed to handle zero or one argument.

If you do not provide an argument to an WLST WebCenter Content command, then one of two things occurs:

- If only one application has registered its Mbean on the server, then the WLST WebCenter Content command should work successfully and display the output.
- If multiple applications have registered MBeans on the server, then an error message is displayed to prompt you to enter the specific application name in the argument.

If there is one argument to an WLST WebCenter Content command, then the following occurs:

- You must enter the correct application name when entering an argument. If the name is not entered properly, then an error message is displayed to prompt you to enter the valid application name in the argument.

Setter Method

The **setter** method is designed to handle one or two arguments.

- The first argument is the *value* to which you want to set the parameter.
- The second argument is the *application name*, which can be null or a string.

19.4 Server Configuration Commands

Use the commands in [Table 19–2](#) to configure the Oracle WebCenter Content Server instance.

Table 19–2 WLST Server Configuration Commands

Use this command...	To...	Use with WLST...
<code>getUCMHttpServerAddress</code>	Display the HTTP Server Address value.	Online
<code>getUCMServerPort</code>	Display the Intradoc Server Port configuration parameter.	Online
<code>setUCMServerPort</code>	Set the Intradoc Server Port configuration parameter.	Online
<code>getUCMIpAddressFilter</code>	Display the IP Address Filter value.	Online
<code>setUCMIpAddressFilter</code>	Set the IP Address Filter value.	Online
<code>getUCMUseSSL</code>	Display the Use SSL value.	Online

19.4.1 getUCMHttpServerAddress

Use with WLST: Online

19.4.1.1 Description

Gets the HTTP Server Address value from the `config.cfg` file and displays it.

19.4.1.2 Syntax

```
getUCMHttpServerAddress(['appName'])
```

Argument	Definition
<code>appName</code>	Optional. Name of the deployed application.

19.4.1.3 Example

The following command displays the Oracle Webcenter Content HTTP server address for the application "Oracle Universal Content Management - Content Server":

```
getUCMHttpServerAddress('Oracle Universal Content Management - Content Server')
server.example.com
```

19.4.2 getUCMServerPort

Use with WLST: Online

19.4.2.1 Description

Gets the Intradoc Server Port configuration parameter from the `config.cfg` file and displays it.

19.4.2.2 Syntax

```
getUCMServerPort(['appName'])
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.4.2.3 Example

The following command displays the Intradoc Server Port value for the application "Oracle Universal Content Management - Content Server":

```
getUCMServerPort('Oracle Universal Content Management - Content Server')
4442
```

19.4.3 setUCMServerPort

Use with WLST: Online

19.4.3.1 Description

Sets the Server Port configuration parameter.

19.4.3.2 Syntax

```
setUCMServerPort(value, ['appName'])
```

Argument	Definition
<i>value</i>	Server Port number. This number must be a positive integer between 0 and 65535.
<i>appName</i>	Optional. Name of the deployed application.

19.4.3.3 Example

The following command sets the Server Port configuration parameter for the application "Oracle Universal Content Management - Content Server":

```
setUCMServerPort(4442, 'Oracle Universal Content Management - Content Server')
```

19.4.4 getUCMIpAddressFilter

Use with WLST: Online

19.4.4.1 Description

Gets the IP Address Filter value from the `config.cfg` file and displays it.

19.4.4.2 Syntax

```
getUCMIpAddressFilter(['appName'])
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.4.4.3 Example

The following command displays the IP address filter value for the application "Oracle Universal Content Management - Content Server":

```
getUCMIpAddressFilter('Oracle Universal Content Management - Content Server')
10.131.123.*
```

19.4.5 setUCMIpAddressFilter

Use with WLST: Online

19.4.5.1 Description

Sets the Webcenter Content IP Address Filter value.

19.4.5.2 Syntax

```
setUCMIpAddressFilter(value, ['appName'])
```

Argument	Definition
<i>value</i>	WebCenter Content IP Address Filter number. This number must be of "*" format or IPV6 Format. The value must be taken from a list of IP Addresses allowed to communicate with the Content Server instance through the Intradoc Server Port.
<i>appName</i>	Optional. Name of the deployed application.

19.4.5.3 Example

The following command sets the value for the WebCenter Content IP address filter for the application "Oracle Universal Content Management - Content Server":

```
setUCMIpAddressFilter(10.131.123.*, 'Oracle Universal Content Management - Content Server')
```

19.4.6 getUCMUseSSL

Use with WLST: Online

19.4.6.1 Description

Gets the Use SSL value from the `config.cfg` file and displays it. The value can be True or False.

19.4.6.2 Syntax

```
getUCMUseSSL(['appName'])
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.4.6.3 Example

The following command displays the Use SSL value for the application "Oracle Universal Content Management - Content Server":

```
getUCMUseSSL('Oracle Universal Content Management - Content Server')
True
```

19.5 Email Configuration Commands

Use the commands in [Table 19–3](#) to configure email for the Oracle WebCenter Content Server instance.

Table 19–3 WLST E-Mail Configuration Commands

Use this command...	To...	Use with WLST...
getUCMMailServer	Display the Mail Server value.	Online
setUCMMailServer	Set the Mail Server value.	Online
getUCMSmtpPort	Display the SMTP Port value.	Online
getUCMSysAdminAddress	Display the Admin Address value.	Online
setUCMSysAdminAddress	Set the Admin Address value.	Online

19.5.1 getUCMMailServer

Use with WLST: Online

19.5.1.1 Description

Gets the Mail Server value from the `config.cfg` file and displays it.

19.5.1.2 Syntax

```
getUCMMailServer(['appName'])
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.5.1.3 Example

The following command displays the Mail Server value for the application "Oracle Universal Content Management - Content Server":

```
getUCMMailServer('Oracle Universal Content Management - Content Server')
mymailserver.example.com
```

19.5.2 setUCMMailServer

Use with WLST: Online

19.5.2.1 Description

Sets the Mail Server value in the `config.cfg` file.

19.5.2.2 Syntax

```
setUCMMailServer(value, ['appName'])
```

Argument	Definition
<i>value</i>	Value for the Mail Server. The value is the name of the mail server that the Content Server instance uses to send SMTP based email.
<i>appName</i>	Optional. Name of the deployed application.

19.5.2.3 Example

The following command sets the value for the Mail Server for the application "Oracle Universal Content Management - Content Server":

```
setUCMailServer(mymailserver.example.com,'Oracle Universal Content Management - Content Server')
```

19.5.3 getUCMSmtpPort

Use with WLST: Online

19.5.3.1 Description

Gets the SMTP Port value in the `config.cfg` file and displays it.

19.5.3.2 Syntax

```
getUCMSmtpPort(['appName'])
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.5.3.3 Example

The following command displays the SMTP port value for the application "Oracle Universal Content Management - Content Server":

```
getUCMSmtpPort('Oracle Universal Content Management - Content Server')
4055
```

19.5.4 getUCMSysAdminAddress

Use with WLST: Online

19.5.4.1 Description

Gets the Admin Address value from the `config.cfg` file and displays it. The value can be of the form `abc@xyz.def`.

19.5.4.2 Syntax

```
getUCMSysAdminAddress(['appName'])
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.5.4.3 Example

The following command displays the Admin Address value for the application "Oracle Universal Content Management - Content Server":

```
getUCMSysAdminAddress('Oracle Universal Content Management - Content Server')
```

mymail@example.com

19.5.5 setUCMSysAdminAddress

Use with WLST: Online

19.5.5.1 Description

Sets the Admin Address value in the `config.cfg` file.

19.5.5.2 Syntax

```
setUCMSysAdminAddress (value, ['AppName'])
```

Argument	Definition
<i>value</i>	Value for the Admin Address. The Admin Address can be of the form <i>abc@xyz.def</i> .
<i>appName</i>	Optional. Name of the deployed application.

19.5.5.3 Example

The following command sets the Admin Address value for the application "Oracle Universal Content Management - Content Server":

```
setUCMSysAdminAddress(mymail@example.com, 'Oracle Universal Content Management - Content Server')
```

19.6 System Status Commands

Use the commands in [Table 19–4](#) to configure additional settings to monitor the WebCenter Content Server instance.

Table 19–4 WLST Additional Configuration Commands

Use this command...	To...	Use with WLST...
getUCMCSVersion	Display the version number.	Online
getUCMServerUptime	Display the uptime value.	Online

19.6.1 getUCMCSVersion

Use with WLST: Online

19.6.1.1 Description

Gets the version number of the Content Server running instance.

19.6.1.2 Syntax

```
getUCMCSVersion(['appName'])
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.6.1.3 Example

The following command displays the version number of the active instance of the application "Oracle Universal Content Management - Content Server":

```
getUCMCSVersion('Oracle Universal Content Management - Content Server')
11g R1
```

19.6.2 getUCMServerUptime

Use with WLST: Online

19.6.2.1 Description

Gets the amount of time the Content Server instance has been up.

19.6.2.2 Syntax

```
getUCMServerUptime(['appName'])
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.6.2.3 Example

The following command displays the amount of time the application "Oracle Universal Content Management - Content Server" has been up:

```
getUCMServerUptime('Oracle Universal Content Management - Content Server')
00H:01 Min:12 Sec
```

19.7 General Configuration Commands

Use the commands in [Table 19–5](#) to configure general configuration options for the Oracle WebCenter Content Server instance.

Table 19–5 WLST General Configuration Options Commands

Use this command...	To...	Use with WLST...
getUCMOverrideFormat	Display the OverrideFormat value.	Online
setUCMOverrideFormat	Set the OverrideFormat value.	Online
getUCMDownloadApplet	Display the DownloadApplet value.	Online
setUCMDownloadApplet	Set the DownloadApplet value.	Online
getUCMMultiUpload	Display the MultiUpload value.	Online
setUCMMultiUpload	Set the MultiUpload value.	Online
getUCMUseAccounts	Display the UseAccount value.	Online
setUCMUseAccounts	Set the UseAccount value.	Online
getUCMIsAutoNumber	Display the AutoNumber value.	Online
setUCMIsAutoNumber	Set the AutoNumber value.	Online
getUCMAutoNumberPrefix	Display the AutoNumberPrefix value.	Online
setUCMAutoNumberPrefix	Set the AutoNumberPrefix value.	Online
getUCMMajorRevLabelSeq	Display the MajorRevLabelSeq value.	Online

Table 19–5 (Cont.) WLST General Configuration Options Commands

Use this command...	To...	Use with WLST...
setUCMMajorRevLabelSeq	Set the MajorRevLabelSeq value.	Online
getUCMMinorRevLabelSeq	Display the MinorRevLabelSeq value.	Online
setUCMMinorRevLabelSeq	Set the MinorRevLabelSeq value.	Online
getUCMJspServerEnabled	Display the JspServerEnabled value	Online
setUCMJspServerEnabled	Set the JspServerEnabled value.	Online
getUCMJspEnabledGroups	Display the JspEnabledGroups value.	Online
setUCMJspEnabledGroups	Set the JspEnabledGroups value.	Online

19.7.1 getUCMOverrideFormat

Use with WLST: Online

19.7.1.1 Description

Gets the value from the `config.cfg` file, indicating whether the `OverrideFormat` parameter is set. The `OverrideFormat` parameter enables users to choose the application format of their content items.

19.7.1.2 Syntax

```
getUCMOverrideFormat(['appName'])
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.7.1.3 Example

The following command displays the `OverrideFormat` parameter value:

```
getUCMOverrideFormat()
true
```

19.7.2 setUCMOverrideFormat

Use with WLST: Online

19.7.2.1 Description

Sets the `OverrideFormat` parameter to enable or disable the ability for users to choose the application format of their content items.

19.7.2.2 Syntax

```
getUCMOverrideFormat('value', ['appName'])
```

Argument	Definition
<i>value</i>	Specifies whether to enable or disable the <code>OverrideFormat</code> option. Values can be: Yes, No, True, False, 1, 0.
<i>appName</i>	Optional. Name of the deployed application.

19.7.2.3 Example

The following command enables the `OverRideFormat` parameter:

```
getUCMOverRideFormat('True')
```

19.7.3 getUCMDownloadApplet

Use with WLST: Online

19.7.3.1 Description

Gets the value from the `config.cfg` file indicating whether the `DownloadApplet` parameter is set. `DownloadApplet` enables users to download multiple files from a search results page.

19.7.3.2 Syntax

```
getUCMDownloadApplet(['appName'])
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.7.3.3 Example

The following command gets the value for the `DownloadApplet` parameter:

```
getUCMDownloadApplet()
true
```

19.7.4 setUCMDownloadApplet

Use with WLST: Online

19.7.4.1 Description

Sets the `DownloadApplet` parameter value to enable or disable the ability for users to download multiple files from a search results page.

19.7.4.2 Syntax

```
setUCMDownloadApplet('value', ['appName'])
```

Argument	Definition
<i>value</i>	Specifies whether to enable or disable the <code>DownloadApplet</code> option. Values can be: Yes, No, True, False, 1, 0.
<i>appName</i>	Optional. Name of the deployed application.

19.7.4.3 Example

The following command sets the value for the `DownloadApplet` to enable the functionality:

```
setUCMDownloadApplet('Yes')
```

19.7.5 getUCMMultiUpload

Use with WLST: Online

19.7.5.1 Description

Gets the value from the `config.cfg` file indicating whether the MultiUpload parameter is set. MultiUpload allows multiple files to be zipped and checked in as a single content item.

19.7.5.2 Syntax

```
getUCMMultiUpload(['appName'])
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.7.5.3 Example

The following command displays the value for the MultiUpload parameter:

```
getUCMMultiUpload()
true
```

19.7.6 setUCMMultiUpload

Use with WLST: Online

19.7.6.1 Description

Sets the MultiUpload parameter value to allow or disallow multiple files to be zipped and checked in as a single content item.

19.7.6.2 Syntax

```
setUCMMultiUpload('value', ['appName'])
```

Argument	Definition
<i>value</i>	Specifies whether to enable or disable the MultiUpload option. Values can be: Yes, No, True, False, 1, 0.
<i>appName</i>	Optional. Name of the deployed application.

19.7.6.3 Example

The following command sets MultiUpload to allow multiple files to be zipped and check in as a single content item:

```
setUCMMultiUpload('1')
```

19.7.7 getUCMUseAccounts

Use with WLST: Online

19.7.7.1 Description

Gets the value from the `config.cfg` file indicating whether the UseAccounts parameter is set. UseAccounts enables the use of accounts in Oracle WebCenter Content.

19.7.7.2 Syntax

```
getUCMUseAccounts(['appName'])
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.7.7.3 Example

The following command displays the value for the UseAccounts option:

```
getUCMUseAccounts()
True
```

19.7.8 setUCMUseAccounts

Use with WLST: Online

19.7.8.1 Description

Sets the UseAccounts parameter value to enable to disable the use of accounts in Oracle WebCenter Content.

19.7.8.2 Syntax

```
setUCMUseAccounts('value', ['appName'])
```

Argument	Definition
<i>value</i>	Specifies whether to enable or disable the UseAccounts option. Values can be: Yes, No, True, False, 1, 0.
<i>appName</i>	Optional. Name of the deployed application.

19.7.8.3 Example

The following command sets UseAccounts to enable accounts in Oracle WebCenter Content:

```
setUCMUseAccounts('True')
```

19.7.9 getUCMIsAutoNumber

Use with WLST: Online

19.7.9.1 Description

Gets the value from the `config.cfg` file indicating whether the IsAutoNumber parameter is set. The IsAutoNumber parameter enables automatic numbering of Content IDs.

19.7.9.2 Syntax

```
getUCMIsAutoNumber(['appName'])
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.7.9.3 Example

The following command displays the value for the IsAutoNumber parameter:

```
getUCMIsAutoNumber()
```

True

19.7.10 setUCMIsAutoNumber

Use with WLST: Online

19.7.10.1 Description

Sets the IsAutoNumber parameter value to enable or disable automatic numbering of Content IDs.

19.7.10.2 Syntax

```
setUCMIsAutoNumber('value', ['appName'])
```

Argument	Definition
<i>value</i>	Specifies whether to enable or disable the AutoNumber option. Values can be: Yes, No, True, False, 1, 0.
<i>appName</i>	Optional. Name of the deployed application.

19.7.10.3 Example

The following command sets IsAutoNumber to enable automatic numbering of Content IDs:

```
setUCMIsAutoNumber('True')
```

19.7.11 getUCMAutoNumberPrefix

Use with WLST: Online

19.7.11.1 Description

Gets the value from the `config.cfg` file for the AutoNumberPrefix parameter. The prefix is used in all automatically numbered content IDs for newly checked-in files, if the AutoNumber parameter is enabled.

19.7.11.2 Syntax

```
getUCMAutoNumberPrefix(['appName'])
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.7.11.3 Example

The following command displays the value for the AutoNumberPrefix parameter:

```
getUCMAutoNumberPrefix()  
dadvml0231usor
```

19.7.12 setUCMAutoNumberPrefix

Use with WLST: Online

19.7.12.1 Description

Sets the `AutoNumberPrefix` parameter value to a prefix used in all automatically numbered content IDs for newly checked-in files (if the `AutoNumber` parameter is enabled).

19.7.12.2 Syntax

```
setUCMUseAutoNumberPrefix('value', ['appName'])
```

Argument	Definition
<i>value</i>	The prefix used in all automatically numbered content IDs for newly checked-in files. Only applies if the <code>AutoNumber</code> parameter is enabled.
<i>appName</i>	Optional. Name of the deployed application.

19.7.12.3 Example

The following command sets the `AutoNumberPrefix`:

```
setUCMAutoNumberPrefix('dadvm10231usor')
```

19.7.13 getUCMMajorRevLabelSeq

Use with WLST: Online

19.7.13.1 Description

Gets the value from the `config.cfg` file for `MajorRevLabelSeq`, which defines the major sequence for revision numbers. `MajorRevLabelSeq` is the first part of the Revision Label.

19.7.13.2 Syntax

```
getUCMMajorRevLabelSeq(['appName'])
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.7.13.3 Example

The following command displays the value for the `MajorRevLabelSeq` parameter:

```
getUCMMajorRevLabelSeq()
A1
```

19.7.14 setUCMMajorRevLabelSeq

Use with WLST: Online

19.7.14.1 Description

Sets the value for the `MajorRevLabelSeq` parameter, which defines the major sequence for revision numbers. `MajorRevLabelSeq` is the first part of the Revision Label.

19.7.14.2 Syntax

```
setUCMMajorRevLabelSeq('value', ['appName'])
```

Argument	Definition
<i>value</i>	Value can be any of the following: A through D, 1 through 8.
<i>appName</i>	Optional. Name of the deployed application.

19.7.14.3 Example

The following command sets MajorRevLabelSeq to 'A1':

```
setUCMMajorRevLabelSeq('A1')
```

19.7.15 getUCMMinorRevLabelSeq

Use with WLST: Online

19.7.15.1 Description

Gets the value from the `config.cfg` file for MinorRevLabelSeq, which defines the minor sequence for revision numbers. MinorRevLabelSeq is the second part of the Revision Label.

19.7.15.2 Syntax

```
getUCMMinorRevLabelSeq(['appName'])
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.7.15.3 Example

The following command displays the value for the MinorRevLabelSeq parameter:

```
getUCMMinorRevLabelSeq()
b2
```

19.7.16 setUCMMinorRevLabelSeq

Use with WLST: Online

19.7.16.1 Description

Sets the value for the MinorRevLabelSeq parameter, which defines the minor sequence for revision numbers. MinorRevLabelSeq is the second part of the Revision Label.

19.7.16.2 Syntax

```
setUCMMinorRevLabelSeq('value', ['appName'])
```

Argument	Definition
<i>value</i>	Value can be any of the following: a through c, 1 through 7.
<i>appName</i>	Optional. Name of the deployed application.

19.7.16.3 Example

The following command sets MinorRevLabelSeq to 'b2':

```
setUCMMinorRevLabelSeq('b2')
```


19.7.17 getUCMJspServerEnabled

Use with WLST: Online

19.7.17.1 Description

Gets the value from the `config.cfg` file indicating whether the `JspServerEnabled` is set. If the parameter is turned on, Content Server can execute Java Server Pages. The Java Server Pages must be checked in to Content Server.

19.7.17.2 Syntax

```
getUCMJspServerEnabled(['appName'])
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.7.17.3 Example

The following command displays the value for the `JspServerEnabled` parameter:

```
getUCMJspServerEnabled()
true
```

19.7.18 setUCMJspServerEnabled

Use with WLST: Online

19.7.18.1 Description

Sets the value for the `JspServerEnabled` parameter. If the parameter is turned on, Content Server can execute Java Server Pages. The Java Server Pages must be checked in to Content Server.

19.7.18.2 Syntax

```
setUCMJspServerEnabled('value', ['appName'])
```

Argument	Definition
<i>value</i>	Specifies whether to enable or disable the parameter. Values can be: Yes, No, True, False, 1, 0.
<i>appName</i>	Optional. Name of the deployed application.

19.7.18.3 Example

The following command sets `JspServerEnabled` to 'true':

```
setUCMJspServerEnabled('true')
```

19.7.19 getUCMJspEnabledGroups

Use with WLST: Online

19.7.19.1 Description

Gets the value from the `config.cfg` file for the `JspEnabledGroups` parameter and lists is. `JspEnabledGroups` lists security groups enabled for Java Server Page

functionality. Security groups have certain permissions for contributors and administrators.

19.7.19.2 Syntax

```
getUCMJspEnabledGroups(['appName'])
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.7.19.3 Example

The following command displays the value for the JspEnabledGroups parameter:

```
getUCMJspEnabledGroups()
group1
Jsp
```

19.7.20 setUCMJspEnabledGroups

Use with WLST: Online

19.7.20.1 Description

Sets the value for the JspEnabledGroups parameter, which specifies security groups to be enabled for Java Server Page functionality.

19.7.20.2 Syntax

```
setUCMJspEnabledGroups('value', ['appName'])
```

Argument	Definition
<i>value</i>	Specifies the security groups to be enabled for Java Server Page functionality.
<i>appName</i>	Optional. Name of the deployed application.

19.7.20.3 Example

The following command sets JspEnabledGroups to 'group1':

```
setUCMJspEnabledGroups('group1')
```

19.8 Content Security Configuration Commands

Use the commands in [Table 19–6](#) to configure content security options for the Oracle WebCenter Content Server instance.

Table 19–6 WLST Content Security Configuration Commands

Use this command...	To...	Use with WLST...
getUCMCopyAccess	Display the CopyAccess parameter value.	Online
setUCMCopyAccess	Set the CopyAccess parameter value.	Online
getUCMExclusiveCheckout	Display the ExclusiveCheckout parameter value.	Online

Table 19–6 (Cont.) WLST Content Security Configuration Commands

Use this command...	To...	Use with WLST...
setUCMExclusiveCheckout	Set the ExclusiveCheckout parameter value.	Online
getUCMAuthorDelete	Display the AuthorDelete parameter value.	Online
setUCMAuthorDelete	Set the AuthorDelete parameter value.	Online
getUCMShowOnlyKnownAccounts	Display the ShowOnlyKnownAccounts parameter value.	Online
setUCMShowOnlyKnownAccounts	Set the ShowOnlyKnownAccounts parameter value.	Online

19.8.1 getUCMCopyAccess

Use with WLST: Online

19.8.1.1 Description

Gets the value from the `config.cfg` file and displays it. When CopyAccess is enabled, users with Read privilege on a content item can get a copy of the native file.

19.8.1.2 Syntax

```
getUCMCopyAccess(['appName'])
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.8.1.3 Example

The following command displays the CopyAccess value:

```
getUCMCopyAccess()
True
```

19.8.2 setUCMCopyAccess

Use with WLST: Online

19.8.2.1 Description

Sets the CopyAccess value in the `config.cfg` file. When CopyAccess is enabled, users with Read privilege on a content item can get a copy of the native file.

19.8.2.2 Syntax

```
setUCMCopyAccess('value', ['appName'])
```

Argument	Definition
<i>value</i>	Specifies whether to enable or disable the parameter. Values can be: Yes, No, True, False, 1, 0.
<i>appName</i>	Optional. Name of the deployed application.

19.8.2.3 Example

The following command sets the value to enable the CopyAccess parameter:

```
setUCMCopyAccess('True')
```

19.8.3 getUCMExclusiveCheckout

Use with WLST: Online

19.8.3.1 Description

Gets the value in the `config.cfg` file and displays it. When the ExclusiveCheckout parameter is enabled, Admin privilege is required to check out a content item checked in by another user.

19.8.3.2 Syntax

```
getUCMExclusiveCheckout(['appName'])
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.8.3.3 Example

The following command displays the value for the ExclusiveCheckout parameter:

```
getUCMExclusiveCheckout()
True
```

19.8.4 setUCMExclusiveCheckout

Use with WLST: Online

19.8.4.1 Description

Sets the value in the `config.cfg` file. When the ExclusiveCheckout parameter is enabled, Admin privilege is required to check out a content item checked in by another user.

19.8.4.2 Syntax

```
setUCMExclusiveCheckout('value', ['appName'])
```

Argument	Definition
<i>value</i>	Specifies whether to enable or disable the parameter. Values can be: Yes, No, True, False, 1, 0.
<i>appName</i>	Optional. Name of the deployed application.

19.8.4.3 Example

The following command sets the value to enable the ExclusiveCheckout parameter:

```
setUCMExclusiveCheckout('True')
```

19.8.5 getUCMAuthorDelete

Use with WLST: Online

19.8.5.1 Description

Gets the value from the `config.cfg` file and displays it. When the AuthorDelete parameter is enabled, authors are allowed to delete their revisions without having Delete privilege.

19.8.5.2 Syntax

```
getUCMAuthorDelete(['appName'])
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.8.5.3 Example

The following command displays the AuthorDelete parameter value:

```
getUCMAuthorDelete()
1
```

19.8.6 setUCMAuthorDelete

Use with WLST: Online

19.8.6.1 Description

Sets the AuthorDelete parameter value in the `config.cfg` file. When the AuthorDelete parameter is enabled, authors are allowed to delete their revisions without having Delete privilege.

19.8.6.2 Syntax

```
setUCMAuthorDelete('value', ['appName'])
```

Argument	Definition
<i>value</i>	Specifies whether to enable or disable the parameter. Values can be: Yes, No, True, False, 1, 0.
<i>appName</i>	Optional. Name of the deployed application.

19.8.6.3 Example

The following command enables the AuthorDelete parameter:

```
setUCMAuthorDelete('1')
```

19.8.7 getUCMShowOnlyKnownAccounts

Use with WLST: Online

19.8.7.1 Description

Gets the value from the `config.cfg` file and displays it. When the ShowOnlyKnownAccounts parameter is enabled, the list of Content Server accounts on a check-in page will contain only globally-predefined accounts.

19.8.7.2 Syntax

```
getUCMShowOnlyKnownAccounts(['appName'])
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.8.7.3 Example

The following command displays the ShowOnlyKnownAccounts parameter value as enabled:

```
getUCMShowOnlyKnownAccounts()
Yes
```

19.8.8 setUCMShowOnlyKnownAccounts

Use with WLST: Online

19.8.8.1 Description

Sets the ShowOnlyKnownAccount parameter value in the `config.cfg` file. When the ShowOnlyKnownAccounts parameter is enabled, the list of Content Server accounts on a check-in page will contain only globally-predefined accounts.

19.8.8.2 Syntax

```
setUCMShowOnlyKnownAccounts('value', ['appName'])
```

Argument	Definition
<i>value</i>	Specifies whether to enable or disable the parameter. Values can be: Yes, No, True, False, 1, 0.
<i>appName</i>	Optional. Name of the deployed application.

19.8.8.3 Example

The following command enables the ShowOnlyKnownAccounts parameter:

```
setUCMShowOnlyKnownAccounts('yes')
```

19.9 Component Manager Configuration Commands

Use the commands in [Table 19–7](#) to configure Component Manager options for the Oracle WebCenter Content Server instance.

Table 19–7 WLST Component Manager Configuration Commands

Use this command...	To...	Use with WLST...
getUCMComponentStatus	Display the status of a component.	Online
setUCMComponentStatus	Set the status of a component.	Online
installUCMComponent	Install a component.	Online
uninstallUCMComponent	Uninstall a component.	Online
getUCMComponentConfig	Display the configuration for a component.	Online
updateUCMComponentConfig	Set configuration parameters for a component.	Online

19.9.1 getUCMComponentStatus

Use with WLST: Online

19.9.1.1 Description

Gets the status of a component. The status can be enabled or disabled.

19.9.1.2 Syntax

```
getUCMComponentStatus('componentName', ['appName'])
```

Argument	Definition
<i>componentName</i>	Specifies a valid Content Server component name. For example, 'ContentFolios'.
<i>appName</i>	Optional. Name of the deployed application.

19.9.1.3 Example

The following command displays the status of the component "ContentFolios":

```
getUCMComponentStatus('ContentFolios')
Enabled
```

19.9.2 setUCMComponentStatus

Use with WLST: Online

19.9.2.1 Description

Sets the status of a component in the `config.cfg` file.

19.9.2.2 Syntax

```
setUCMComponentStatus('componentName', 'status', ['appName'])
```

Argument	Definition
<i>componentName</i>	Specifies a valid Content Server component name. For example, 'ContentFolios'.
<i>status</i>	Specifies whether the status of the component is enabled or disabled. Values can be: Enable, Disable.
<i>appName</i>	Optional. Name of the deployed application.

19.9.2.3 Example

The following command sets the status of 'ContentFolios' to 'Enable':

```
setUCMComponentStatus('ContentFolios', 'Enable')
```

19.9.3 installUCMComponent

Use with WLST: Online

19.9.3.1 Description

Installs the component present at the specified file location.

19.9.3.2 Syntax

```
installUCMComponent('filePath', ['appName'])
```

Argument	Definition
<i>filePath</i>	Specifies a valid file path to a component.
<i>appName</i>	Optional. Name of the deployed application.

19.9.3.3 Example

The following command installs the component at the location 'C:/manifest.zip':

```
installUCMComponent('C:/manifest.zip')
```

19.9.4 uninstallUCMComponent

Use with WLST: Online

19.9.4.1 Description

Uninstalls the specified component.

19.9.4.2 Syntax

```
uninstallUCMComponent('componentName', ['appName'])
```

Argument	Definition
<i>componentName</i>	Specifies a valid Content Server component name. For example, 'ContentFolios'.
<i>appName</i>	Optional. Name of the deployed application.

19.9.4.3 Example

The following command uninstalls the component named 'ContentFolios':

```
uninstallUCMComponent('ContentFolios')
```

19.9.5 downloadUCMComponent

Use with WLST: Online

19.9.5.1 Description

Downloads the specified component to the specified file location.

19.9.5.2 Syntax

```
downloadUCMComponent('componentName', 'filePath', ['appName'])
```

Argument	Definition
<i>componentName</i>	Specifies a valid Content Server component name. For example, 'ContentFolios'.
<i>filePath</i>	Specifies a valid file path to a component.
<i>appName</i>	Optional. Name of the deployed application.

19.9.5.3 Example

The following command downloads the component 'ContentFolios' to 'C:/manifest.zip':

```
downloadUCMComponet('ContentFolios', 'C:/manifest.zip')
```

19.9.6 getUCMComponentConfig

Use with WLST: Online

19.9.6.1 Description

Gets the configuration of the specified component and displays it.

19.9.6.2 Syntax

```
getUCMComponentConfig('componentName', ['appName'])
```

Argument	Definition
<i>componentName</i>	Specifies a valid component name. For example, 'ContentFolios'.
<i>appName</i>	Optional. Name of the deployed application.

19.9.6.3 Example

The following command displays the configuration for the component 'ContentFolios':

```
getUCMComponentConfig('ContentFolios')
```

19.9.7 updateUCMComponentConfig

Use with WLST: Online

19.9.7.1 Description

Sets the specified component with the configuration options provided.

19.9.7.2 Syntax

```
updateUCMComponentConfig('componentName', 'updateParams', ['appName'])
```

Argument	Definition
<i>componentName</i>	Specifies a valid component name. For example, 'Folders_g'.
<i>updateParams</i>	Specifies valid parameters for the component.
<i>appName</i>	Optional. Name of the deployed application.

19.9.7.3 Example

The following command sets configuration parameters for the component 'Folders_g':

```
updateUCMComponentConfig('Folders_g', 'GetCopyAccess:true,CollectionHiddenMeta:xHidden')
```

19.10 Records Management Configuration Commands

Use the commands in [Table 19–8](#) to configure records management options for the Oracle WebCenter Content Server instance.

Table 19–8 WLST Records Management Configuration Commands

Use this command...	To...	Use with WLST...
<code>getRMLevel</code>	Display the type of records management configuration.	Online
<code>getRMConfigurationLevel</code>	Display the records management configuration level.	Online
<code>getRMFeatures</code>	Display records management features.	Online
<code>getRMDispositionActions</code>	Display records management dispositions actions.	Online
<code>rmUpdate</code>	Update the records management configuration.	Online
<code>addOutgoingProvider</code>	Add an outgoing provider for the Adapter server used to store records management content.	Online
<code>registerSource</code>	Register the source for the Adapter server repository so records management can find it.	Online

19.10.1 getRMLevel

Use with WLST: Online

19.10.1.1 Description

Gets the type of records management configuration and displays it. The type can have the following values:

- none
- standalone
- adapter

19.10.1.2 Syntax

```
getRMLevel ( [ 'appName' ] )
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.10.1.3 Example

The following command displays the type of records management configuration:

```
getRMLevel ()
adapter
```

19.10.2 getRMConfigurationLevel

Use with WLST: Online

19.10.2.1 Description

Gets the records management configuration level and displays it. The configuration level can have the following values:

- **minimal:** Enables minimal amount of functionality and excludes some disposition actions and most of the application features. This is the default when the software is enabled.
- **typical:** Enables all disposition actions and all features except for DoD Configuration, Classified Topics, FOIA/PA tracking (Freedom of Information Act/Privacy Act), and E-mail.
- **dod2:** Enables the features from a Typical installation with the addition of DoD Configuration and E-mail.
- **dodclassified:** Enables all features except for FOIA/PA.
- **custom:** Enables the ability to choose a variety of features. Some disposition actions are dependent on other actions. If an action is selected, dependent actions are also automatically selected.

19.10.2.2 Syntax

```
getRMConfigurationLevel(['appName'])
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.10.2.3 Example

The following command displays the type of records management configuration:

```
getRMConfigurationLevel(['appName'])
minimal
```

19.10.3 getRMFeatures

Use with WLST: Online

19.10.3.1 Description

Gets a list of records management features and displays it. The list can have the following values:

- feature_related_content
- feature_audit_trigger
- feature_subject_to_review
- feature_revision_dates
- feature_security_markings
- feature_email_fields
- feature_dod_config
- feature_foia_privacyact

19.10.3.2 Syntax

```
getRMFeatures(['appName'])
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.10.3.3 Example

The following command displays the records management features:

```
getRMFeatures()  
feature_related_content  
feature_audit_trigger  
feature_subject_to_review
```

19.10.4 getRMDispositionActions

Use with WLST: Online

19.10.4.1 Description

Gets the values for records management disposition actions and displays them. The list can have the following values:

- actions_activate
- actions_obsolete
- actions_cancel
- actions_rescind
- actions_expire
- actions_cutoff
- actions_approve_deletion
- actions_destroy

19.10.4.2 Syntax

```
getRMDispositionActions(['appName'])
```

Argument	Definition
<i>appName</i>	Optional. Name of the deployed application.

19.10.4.3 Example

The following command displays a list of records management disposition actions:

```
getRMDispositionActions()  
actions_active  
actions_obsolete  
actions_cancel
```

19.10.5 rmUpdate

Use with WLST: Online

19.10.5.1 Description

Sets the records management configuration with feature and disposition actions and enables it.

19.10.5.2 Syntax

```
rmUpdate(urmLevel, level, featuresList, dispositionActionsList, enableRTMandURMAgent, ['appName'])
```

Argument	Definition
<i>urmLevel</i>	Specifies a valid records management configuration type.
<i>level</i>	Specifies a valid records management level.
<i>featuresList</i>	Specifies valid records management features.
<i>dispositionActionsList</i>	Specifies valid disposition actions.
<i>enableRTMandURMAgent</i>	Specifies whether to enable the RTM and URM Agent.'.
<i>appName</i>	Optional. Name of the deployed application.

19.10.5.3 Example

The following command sets the records management configuration and enables it:

```
rmUpdate(urmLevel='standalone',level='custom',featuresList='feature_related_content:feature_
revision_dates',dispositionActionsList='actions_
activate:actions:obsolete',enableRTMandURMAgent='1')
```

19.10.6 addOutgoingProvider

Use with WLST: Online

19.10.6.1 Description

Defines the outgoing provider that enables the Adapter server to connect to the Content Server instance with records management enabled.

19.10.6.2 Syntax

```
addOutgoingProvider(ProviderName, ProviderDescription, ServerHostName, HTTPServerAddress,
ServerPort, InstanceName, RelativeWebRoot, extraUpdateParams,['appName'])
```

Argument	Definition
<i>ProviderName</i>	Name of the outgoing provider.
<i>ProviderDescription</i>	Description of the outgoing provider.
<i>ServerHostname</i>	Name of the server host.
<i>HTTPServerAddress</i>	Address of the HTTP server.
<i>ServerPort</i>	Number of the server port.
<i>InstanceName</i>	Name of the instance for the Content Server with records management enabled.
<i>RelativeWebRoot</i>	Name of the relative web root.
<i>extraUpdateParams</i>	Extra parameters that can be used are: ClientHostIpFilter, ConnectionPassword, ConnectionPasswordName, IsRefinery, ProviderClass, ProviderConfig, ProviderConnection, RefineryMaxProJobs, RefineryReadOnly.
<i>appName</i>	Optional. Name of the deployed application.

19.10.6.3 Example

The following command defines an outgoing provider for the Adapter server to connect to the records management instance.:

```
addOutgoingProvider(ProviderName='x', ProviderDescription='y', ServerHostName='localhost', HTTPServerAddress='z', ServerPort='4444', InstanceName='w', RelativeWebRoot='cs', updateParams='RefineryMasJobs:100, IsRefinery:1')
```

19.10.7 registerSource

Use with WLST: Online

19.10.7.1 Description

Registration ensures that records management is aware of the Adapter and is ready to manage the stored content in the Adapter server's repository.

19.10.7.2 Syntax

```
registerSource(ProviderName, SourceName, SourceTableName, SourceDisplayName, ['appName'])
```

Argument	Definition
<i>ProviderName</i>	Name of the outgoing provider.
<i>SourceName</i>	Description of the source in the Adapter repository.
<i>SourceTableName</i>	Name of the source table in the Adapter repository.
<i>SourceDisplayName</i>	Display name for the source in the Adapter repository.
<i>appName</i>	Optional. Name of the deployed application.

19.10.7.3 Example

The following command registers the Adapter server's repository source for the records management stored content:

```
registerSource(ProviderName='x', SourceName='y', SourceTableName='z', SourceDisplayName='w')
```

19.11 User Interface Commands

Use the commands in [Table 19–9](#) to display and update the configuration of the Oracle WebCenter Content user interface introduced in Oracle WebCenter Content 11g Release 1 (11.1.1.8). For more information about this user interface, see "Getting Started with the WebCenter Content User Interface" in *Using Oracle WebCenter Content*.

These commands can be used only after the `WCCADFUI.zip` file has been installed and enabled on Oracle WebCenter Content.

To use these custom commands, you must invoke the WLST script from the appropriate Oracle home. Do not use the WLST script in the WebLogic Server home. For Oracle WebCenter Content user interface commands, the script is located at:

- UNIX: `wlstResources/common/bin/wlst.sh`
- Windows: `wlstResources\common\bin\wlst.cmd`

Before you run the WLST script, you must set the `WL_HOME` environment variable in the UNIX shell or Windows command prompt.

- UNIX: `export WL_HOME=/Oracle/WccUI/wlserver_10.3`
- Windows: `set WL_HOME=C:\Oracle\WccUI\wlserver_10.3`

Configuration changes made using these WLST commands are only effective after you restart the Managed Server on which the WebCenter Content - Web UI application is deployed.

Table 19–9 WLST WebCenter Content User Interface Commands

Use this command...	To...	Use with WLST...
<code>displayWccAdfConfig</code>	Display the configuration of the WebCenter Content user interface application.	Online
<code>updateWccAdfConfig</code>	Update the configuration of the WebCenter Content user interface application.	Online

19.11.1 displayWccAdfConfig

Use with WLST: Online

19.11.1.1 Description

Displays the configuration of the Oracle WebCenter Content user interface application.

19.11.1.2 Syntax

```
displayWccAdfConfig(appName='value', [attrName='value'])
```

Argument	Definition
<i>appName value</i>	Name of the deployed application.
<i>attrName value</i>	Optional. Name of the attribute to display. If omitted all attributes are displayed.

19.11.1.3 Examples

The following command displays all configuration attributes for the Oracle WebCenter Content user interface deployed with the application name "Oracle WebCenter Content - Web UI".

```
wls:/wccadf_domain/serverConfig> displayWccAdfConfig(appName='Oracle WebCenter
Content - Web UI')
WccInstanceName = Default
WccInstanceConnectionName = WccAdfDefaultConnection
ProxyContent = true
DocumentPreview = DOCUMENT_VIEWER
DefaultLocale = en_US
DefaultTimeZone = America/Los_Angeles
ApplicationUrl = null
ClusterCompatible = false
TemporaryDirectory = null
MaximumUploadedFileSize = 52428800
MaximumWindowsPerSession = 10
WccLoginPageEnabled = true
SkinFamily = wcc-skin
SkinVersion = null
CustomBrandingLogo = null
CustomBrandingTitle = null
```

The following command displays the value of the configuration attribute named "WccInstanceConnectionName".

```
wls:/wccadf_domain/serverConfig> displayWccAdfConfig(appName='Oracle WebCenter
Content - Web UI', attrName='WccInstanceConnectionName')
Attribute WccInstanceConnectionName value is: WccAdfDefaultConnection
```

19.11.2 updateWccAdfConfig

Use with WLST: Online

19.11.2.1 Description

Updates the configuration of the Oracle WebCenter Content user interface application. The command can be used to update a single attribute or multiple attributes.

19.11.2.2 Syntax

```
updateWccAdfConfig(appName, [wccInstanceName], [wccInstanceConnectionName],
[proxyContent], [documentPreview], [defaultLocale], [defaultTimeZone],
[applicationUrl], [clusterCompatible], [temporaryDirectory],
[maximumUploadedFileSize], [maximumWindowsPerSession],
[wccLoginPageEnabled], [skinFamily], [skinVersion], [customBrandingLogo],
[customBrandingTitle])
```

Argument	Definition
<i>appName</i>	Name of the deployed application.
<i>wccInstanceName</i>	Reserved for future use.
<i>wccInstanceConnectionName</i>	Name of the Content Server connection in Connection Architecture (<i>connections.xml</i>).
<i>proxyContent</i>	Controls how a browser retrieves document content, including the native file, the web-viewable rendition, thumbnails, and attachments. Must be "true" or "false". If "true" the browser requests this content from the Oracle WebCenter Content user interface, which in turn retrieves it from Content Server. If "false" the browser requests this content directly from Content Server.
<i>documentPreview</i>	Controls the preview displayed for a document. Must be one of the following case-sensitive values: <ul style="list-style-type: none"> DOCUMENT_VIEWER: Use the document viewer (if available) WEB_VIEWABLE: Display the web-viewable rendition (if available) NONE: No preview
<i>defaultLocale</i>	Locale to use if a user's locale cannot be otherwise determined. Must be in the format used by the Java class <code>java.util.Locale</code> (for example, "en_US").
<i>defaultTimeZone</i>	Time zone to use if the user's time zone cannot be otherwise determined. Must be in the format used by the Java method <code>java.util.TimeZone#getTimeZone</code> (for example, "America/Los_Angeles")
<i>applicationUrl</i>	Specifies the scheme, hostname, and port of URLs generated by the Oracle WebCenter Content user interface (for example, <code>https://wcc.example.com:16225</code>). Optional. If not set, the scheme, hostname, and port are determined from the HTTP request.

Argument	Definition
<i>clusterCompatible</i>	Specifies whether the Oracle WebCenter Content user interface supports session replication among nodes in a cluster. Either "true" or "false". Must be "true" if session replication is enabled on the Java EE Web Container.
<i>temporaryDirectory</i>	Base directory for temporary files created by the Oracle WebCenter Content user interface, such as in-progress uploads. This directory should be empty, on a fast file system with adequate free space, and readable and writable by only the owner of the process running the Oracle WebCenter Content user interface. The Oracle WebCenter Content user interface will create and manage a subdirectory structure. If <i>clusterCompatible</i> is "true" this directory must also be on a filesystem shared across all nodes in the cluster. Oracle recommends setting this attribute even if <i>clusterCompatible</i> is "false". If not set, the value of the Java system property <code>java.io.tmpdir</code> is used.
<i>maximumUploadedFileSize</i>	Maximum size of uploaded files (in bytes). If less than zero, there is no maximum size. If zero, file upload is disabled.
<i>maximumWindowsPerSession</i>	<p>Maximum number of active windows (or browser tabs, depending on browser configuration) per session. When this limit is reached, the least recently used window expires and subsequent interaction with that window displays an error message.</p> <p>The Oracle WebCenter Content user interface main page, <code>wccmain</code>, does not contribute to the session's window count and only expires when the session expires or is logged out. The document properties page, <code>wccdoc</code>, counts as two windows if <code>documentPreview</code> is "DOCUMENT_VIEWER", but counts as one window if <code>documentPreview</code> is "WEB_VIEWABLE" or "NONE".</p> <p>Use this attribute to control the maximum application server memory consumed by each session. Set to 0 to not limit the number of windows per session.</p>
<i>wccLoginPageEnabled</i>	Specifies whether the "wcclogin" page is enabled or disabled. Either "true" or "false". When Single Sign-On (SSO) authentication is enabled, the attribute value should be set to "false" to prevent users from using the "wcclogin" page instead of SSO.
<i>skinFamily</i>	Name of the skin family. The <code><skin-family></code> element in <code>trinidad-config.xml</code> is set to the value of this attribute.
<i>skinVersion</i>	Skin version. The <code><skin-version></code> element in <code>trinidad-config.xml</code> is set to the value of this attribute. Optional. If not set, no skin version is specified.
<i>customBrandingLogo</i>	HTTP URL of an image to display in the branding bar. Optional. If not set, a default image is displayed.
<i>customBrandingTitle</i>	The title to display in the branding bar. Optional. If not set, a default title is displayed.

19.11.2.3 Examples

The following command sets the `proxyContent` attribute to "true" for the Oracle WebCenter Content user interface deployed with the application name "Oracle WebCenter Content - Web UI". With this setting, browsers will retrieve document

content from the Oracle WebCenter Content user interface, rather than directly from Content Server.

```
updateWccAdfConfig(appName='Oracle WebCenter Content - Web UI', proxyContent=true)
```

The following command sets the defaultLocale attribute to "en_US" and the defaultTimeZone attribute to "America/Los_Angeles". If the Oracle WebCenter Content user interface cannot determine a user's preferred locale and time zone (for example, based on user preferences), it will default to the English language and display times using the America/Los_Angeles time zone.

```
updateWccAdfConfig(appName='Oracle WebCenter Content - Web UI', defaultLocale='en_US', defaultTimeZone='America/Los_Angeles')
```

The following command sets the temporaryDirectory attribute to "/tmp/wcc". The Oracle WebCenter Content user interface will store temporary files in this directory on the application server.

```
updateWccAdfConfig(appName='Oracle WebCenter Content - Web UI', temporaryDirectory='/tmp/wcc')
```

The following command sets the wccLoginPageEnabled property to "false". This prevents users from authenticating to the Oracle WebCenter Content user interface using its "wcclogin" page, requiring them to use Single Sign-On (SSO).

```
updateWccAdfConfig(appName='Oracle WebCenter Content - Web UI', wccLoginPageEnabled=false)
```

19.12 User Interface Connection Commands

Use the commands in [Table 19–10](#) to manage connections for the Oracle WebCenter Content user interface introduced in WebCenter Content 11g Release 1 (11.1.1.8). For more information about this user interface, see "Getting Started with the WebCenter Content User Interface" in *Using Oracle WebCenter Content*.

These commands can be used only after the `WCCADFUI.zip` file has been installed and enabled on Oracle WebCenter Content. To use these custom commands, you must invoke the WLST script from the appropriate Oracle home. Do not use the WLST script in the WebLogic Server home. For the Oracle WebCenter Content user interface commands, the script is located at:

- UNIX: `ConnArchWlstResources/common/bin/manageconnwlst.sh`
- Windows: `ConnArchWlstResources\common\bin\manageconnwlst.cmd`

Before you run the WLST script, you must set the `WL_HOME` environment variable in the UNIX shell or Windows command prompt.

- UNIX: `export WL_HOME=/Oracle/WccUI/wlserver_10.3`
- Windows: `set WL_HOME=C:\Oracle\WccUI\wlserver_10.3`

Configuration changes made using these WLST commands are only effective after you restart the Managed Server on which the WebCenter Content - Web UI application is deployed.

Table 19–10 WLST WebCenter Content User Interface Connection Commands

Use this command...	To...	Use with WLST...
createRIDCConnection	Create a new RIDC connection.	Online

Table 19–10 (Cont.) WLST WebCenter Content User Interface Connection Commands

Use this command...	To...	Use with WLST...
updateRIDCConnection	Update existing RIDC connection properties.	Online
listRIDCConnections	List all the RIDC connection Mbeans present in an application.	Online
deleteRIDCConnection	Remove an existing RIDC connection.	Online
displayRIDCConnection	Get all the attributes and their values associated with an RIDC connection Mbean with an option to get the value for a given attribute name.	Online

19.12.1 createRIDCConnection

Use with WLST: Online

19.12.1.1 Description

Creates a new RIDC connection reference and adds the connection name to the mds layer.

19.12.1.2 Syntax

```
createRIDCConnection('appName', 'conName')
```

Argument	Type	Description
<i>appName</i>	java.lang.String	Name of the application for which the connection will be created.
<i>connName</i>	java.lang.String	Name of the connection which is the placeholder for RIDC connection reference.

19.12.1.3 Example

The following command creates an RIDC connection 'WccAdfDefaultConnection' in the application 'Oracle WebCenter Content - Web UI':

```
createRIDCConnection('Oracle WebCenter Content - Web UI', 'WccAdfDefaultConnection')
```

19.12.2 updateRIDCConnection

Use with WLST: Online

19.12.2.1 Description

Updates the connection properties for an existing RIDC connection reference. These changes and additions are read as runtime data and saved in the mds layer.

19.12.2.2 Syntax

```
updateRIDCConnection(appName, connName, ['connUrl'], ['connSockettimeout'],
['connPoolMethod'], ['connPoolSize'], ['connWaitTime'], ['credUsername'],
['credPassword'], ['credAppidkey'], ['credImpersonationAllowed'], ['jaxwsStack'],
['jaxwsPolicy'], ['jaxwsJpsconfigfile'], ['jaxwsSkipstackoptimizations'],
['jaxwsServerInstancename'], ['jaxwsRegisteridentityswitchfilter'],
['httpLibrary'], ['idcsAlgorithm'], ['idcsKeystoreFile'],
['idcsKeystorePassword'], ['idcsKeystoreAlias'], ['idcsKeystoreAliasPassword'],
['idcsTrustmanagerFile'], ['idcsTrustmanagerPassword'])
```

Argument	Type	Definition
<i>appName</i>	java.lang.String	Name of the application for which the connection has to be updated.
<i>connName</i>	java.lang.String	Name of the connection which will be placeholder for RIDC connection properties.
<i>connURL</i>	java.lang.String	RIDC connection URL property.
<i>connSockettimeout</i>	java.lang.Integer	RIDC connection socket timeout property in seconds.
<i>connPoolMethod</i>	java.lang.String	RIDC connection pool method property.
<i>connPoolSize</i>	java.lang.Integer	RIDC connection pool size property.
<i>connWaitTime</i>	java.lang.Integer	RIDC connection wait time property.
<i>credUsername</i>	java.lang.String	RIDC authorization credential username property.
<i>credPassword</i>	java.lang.String	RIDC authorization credential password property.
<i>credAppidkey</i>	java.lang.String	RIDC authorization credential appid key property.
<i>credImpersonationAllowed</i>	java.lang.Boolean	Credential impersonation allowed property.
<i>jaxwsStack</i>	java.lang.String	JaxWs protocol stack property.
<i>jaxwsPolicy</i>	java.lang.String	JaxWs protocol policy property.
<i>jaxwsJpsconfigfile</i>	java.lang.String	JaxWs protocol Jps config file property.
<i>jaxwsSkipstackoptimizations</i>	java.lang.Boolean	JaxWs protocol skip stack optimizations property.
<i>jaxwsServerInstancename</i>	java.lang.String	JaxWs protocol server instance name property.
<i>jaxwsRegisteridentityswitchfilter</i>	java.lang.Boolean	JaxWs protocol register identity switch filter property.
<i>httpLibrary</i>	java.lang.String	Http protocol library property.
<i>idcsAlgorith</i>	java.lang.String	Secure Intradoc Protocol Algorithm property.
<i>idcsKeystoreFile</i>	java.lang.String	Secure Intradoc Protocol Keystore File property.
<i>idcsKeystorePassword</i>	java.lang.String	Secure Intradoc Protocol Keystore Password property.
<i>idcsKeystorealias</i>	java.lang.String	Secure Intradoc Protocol Keystore Alias property.
<i>idcsKeystoreAliasPassword</i>	java.lang.String	Secure Intradoc Protocol Keystore Alias password property.
<i>idcsTrustmanagerFile</i>	java.lang.String	Secure Intradoc Protocol TrustManager File property.
<i>idcsTrustmanagePassword</i>	java.lang.String	Secure Intradoc Protocol TrustManager Password property.

19.12.2.3 Example

The following command updates the Intradoc Protocol Connection with a 90 second socket timeout.

```
updateRIDCCConnection('Oracle WebCenter Content - Web UI', 'WccAdfDefaultConnection',
connUrl='idc://contentserver:4444', credUsername='weblogic', connSockettimeout=90)
```

19.12.3 listRIDCConnections

Use with WLST: Online

19.12.3.1 Description

Lists all the RIDC connection MBeans present in an ADF connection architecture based application.

19.12.3.2 Syntax

```
listRIDCConnections('appName')
```

Argument	Type	Description
<i>appName</i>	java.lang.String	Name of the application for which the connection mbeans has to be returned.

19.12.3.3 Example

The following command returns all the connection Mbeans with connection type 'RIDC' present in application 'Oracle WebCenter Content - Web UI'.

```
listRIDCConnections('Oracle WebCenter Content - Web UI')
```

19.12.4 deleteRIDCConnection

Use with WLST: Online

19.12.4.1 Description

Lists all the RIDC connection Mbeans present in an ADF connection architecture based application.

19.12.4.2 Syntax

```
deleteRIDCConnection('appName', 'connName')
```

Argument	Type	Description
<i>appName</i>	java.lang.String	Name of the application for which the connection will be removed.
<i>connName</i>	java.lang.String	Name of the connection to be removed for the given application.

19.12.4.3 Example

The following command removes the connection name 'WccAdfDefaultConnection' present in application 'Oracle WebCenter Content - Web UI'.

```
deleteRIDCConnection('Oracle WebCenter Content - Web UI', 'WccAdfDefaultConnection')
```

19.12.5 displayRIDCConnection

Use with WLST: Online

19.12.5.1 Description

Gets all the attribute name-value pairs present in a given connection Mbean of an application, with an option to get the value of an attribute present in a given connection Mbean of an application.

19.12.5.2 Syntax

```
displayRIDCConnection(appName, connName, ['attrName'] )
```

Argument	Type	Description
<i>appName</i>	java.lang.String	Name of the application for which the connection Mbean attribute value is desired.
<i>connName</i>	java.lang.String	Name of the connection that contains the mbean property.
<i>attrName</i>	java.lang.String	Optional. Attribute name in connection Mbean for which value is desired.

19.12.5.3 Examples

The following command retrieves the connection property value of 'PropConnectionUrl'.

```
displayRIDCConnection('Oracle WebCenter Content - Web UI',
'WccAdfDefaultConnection', 'PropConnectionUrl')
```

The following command retrieves all the connection properties present in connection 'WccAdfDefaultConnetion'.

```
ddisplayRIDCConnection('Oracle WebCenter Content - Web UI', 'WccAdfDefaultConnection')
```

Oracle WebCenter Capture Custom WLST Commands

This chapter provides detailed descriptions of custom WLST commands for Oracle WebCenter Capture, including command syntax, arguments and command examples.

The following sections describe the custom WLST commands for Oracle WebCenter Capture. These commands enable you to access and modify various configuration parameters for Oracle WebCenter Capture from the command line. Topics include:

- [Section 20.1, "Overview of WLST Oracle WebCenter Capture Command Categories"](#)
- [Section 20.2, "Configuration Commands"](#)

For information about Capture workspace console use, see *Oracle Fusion Middleware Managing Oracle WebCenter Capture*.

Note: To use the Oracle WebCenter Capture custom commands, you must invoke the WLST script from the Oracle Common home in which the component has been installed. Either connect to the Oracle WebLogic Server managed server (default port 16400) on which the Oracle WebCenter Capture application is deployed, or connect to the Oracle WebLogic Server administration server and change your location to domainRuntime by executing the command:

```
domainRuntime()
```

See "Using Custom WLST Commands" in *Oracle Fusion Middleware Administrator's Guide*.

20.1 Overview of WLST Oracle WebCenter Capture Command Categories

WLST Oracle WebCenter Capture commands are covered in the following category:

Table 20–1 WLST Oracle WebCenter Capture Command Categories

Command Category	Description
Configuration Commands	View and manage configuration for Oracle WebCenter Capture.

20.2 Configuration Commands

Use the commands in [Table 20–2](#) to configure Oracle WebCenter Capture.

Table 20–2 WLST Server Oracle WebCenter Capture Configuration Commands

Use this command...	To...	Use with WLST...
<code>listWorkspaces</code>	List all of the workspaces to which the administrator or workspace manager has access.	Online
<code>listBatches</code>	List all of the batches within a specified workspace.	Online
<code>exportBatch</code>	Export a batch including images and metadata to a specified file.	Online
<code>exportWorkspace</code>	Export an entire workspace including documents, metadata, scripts, profiles and jobs to an XML file.	Online
<code>importWorkspace</code>	Import a workspace from a XML file generated with the <code>exportWorkspace</code> command.	Online
<code>unlockBatch</code>	Delete the batch lock record for the specified batch.	Online
<code>listLockedBatches</code>	Display the list of locked batches.	Online
<code>listCaptureConfig</code>	Display the list of all Capture configuration attributes with their values.	Online
<code>getCaptureConfig</code>	Fetch the value of the attribute specified as an argument.	Online
<code>setCaptureConfig</code>	Set the value of the Capture attribute to the provided value.	Online
<code>scanForClientBundles</code>	Scan the client bundle directory for bundles.	Online
<code>deleteBundle</code>	Delete an existing bundle.	Online

20.2.1 listWorkspaces

Use with WLST: Online.

20.2.1.1 Description

Lists all workspaces to which the administrator or workspace manager has access.

20.2.1.2 Syntax

```
listWorkspaces()
```

20.2.1.3 Example

The following example lists all of the workspaces, preceded by their IDs.

```
listWorkspaces()
4 bills_workspace
2 certificates_workspace
5 receipts_workspace
```

20.2.2 listBatches

Use with WLST: Online.

20.2.2.1 Description

Lists all batches for the workspace specified by its ID. Each batch listed has five columns (displayed in this order): Batch ID, Batch Name, Created By (user), Last Updated By (user), and Last Modified (date).

20.2.2.2 Syntax

```
listBatches (WORKSPACE_ID)
```

Argument	Definition
<i>WORKSPACE_ID</i>	ID number for a workspace. Can be optionally specified within single quotes. For example, both 3 and '3' are valid arguments for a workspace with ID 3.

20.2.2.3 Example

The following example lists the batches for the workspace ID 3.

```
wls:/base_domain/domainRuntime> listBatches(1)
14 ABI1 <anonymous> <anonymous> 4/26/13
15 ABI2 <anonymous> <anonymous> 4/26/13
1 BCP11 captureuser <anonymous> 4/17/13
```

20.2.3 exportBatch

Use with WLST: Online.

20.2.3.1 Description

Exports a batch including images and metadata to a specified file.

20.2.3.2 Syntax

```
exportBatch(BATCH_ID, 'FILE_NAME')
```

Argument	Definition
<i>BATCH_ID</i>	ID number for a batch. Can be optionally specified within single quotes. For example, both 3 and '3' are valid arguments for a batch with ID 3.
<i>FILE_NAME</i>	Name of the file to which the batch will be exported. The file name must be specified along with its complete path.

20.2.3.3 Example

The following example exports a batch.

```
exportBatch(8, '/home/abc/batch8.xml')
Batch successfully exported
```

20.2.4 exportWorkspace

Use with WLST: Online.

20.2.4.1 Description

Exports an entire workspace including documents, metadata, scripts, profiles and jobs to an XML file.

20.2.4.2 Syntax

```
exportWorkspace(WORKSPACE_ID, 'FILE_NAME')
```

Argument	Definition
<i>WORKSPACE_ID</i>	ID number for a workspace. Can be optionally specified within single quotes. For example, both 3 and '3' are valid arguments for a workspace with ID 3.
<i>FILE_NAME</i>	Name of the file to which the workspace will be exported. The file name must be specified along with its complete path.

20.2.4.3 Example

The following example exports the workspace with the ID of workspace3.

```
exportWorkspace(3, '/home/abc/workspace3.xml')
```

Workspace successfully exported

20.2.5 importWorkspace

Use with WLST: Online.

20.2.5.1 Description

Imports a workspace from a XML file generated with the `exportWorkspace` command. The workspace being imported must not exist in the Oracle WebCenter Capture database.

20.2.5.2 Syntax

```
importWorkspace('FILE_NAME')
```

Argument	Definition
<i>FILE_NAME</i>	Name of the XML file from which a workspace is imported. The file name must be specified along with its complete path.

20.2.5.3 Examples

The following example imports a workspace with the file name of workspace3.

```
importWorkspace('/home/abc/workspace3.xml')
```

Workspace successfully imported

20.2.6 unlockBatch

Use with WLST: Online.

20.2.6.1 Description

Deletes the batch lock record for the specified batch. The batch will be put into a READY state so that it can be opened by the client.

20.2.6.2 Syntax

```
unlockBatch('BATCH_ID')
```

Argument	Definition
<i>BATCH_ID</i>	ID number for a batch. Can be optionally specified within single quotes. For example, both 3 and '3' are valid arguments for a batch with ID 3.

20.2.6.3 Example

The following example unlocks a batch ID 8.

```
unlockBatch('8')
Batch successfully unlocked
```

20.2.7 listLockedBatches

Use with WLST: Online.

20.2.7.1 Description

Displays the list of locked batches. Each batch listed has six columns (displayed in this order): Workspace ID, Batch ID, Batch Name, Created By (user), Workstation (name/IP address), Last Modified (date).

20.2.7.2 Syntax

```
listLockedBatches('WORKSPACE_ID')
```

Argument	Definition
<i>WORKSPACE_ID</i>	ID number for a workspace. Can be optionally specified within single quotes. For example, both 3 and '3' are valid arguments for a workspace with ID 3.

20.2.7.3 Example

The following example lists locked batches for the workspace ID 3.

```
wls:/base_domain/domainRuntime> listLockedBatches(1)
1 14 ABI1 <anonymous> sic01lzz.example.com 4/26/13
1 15 ABI2 <anonymous> slc01lzz.example.xom 4/26/13
1 17 BCP16 <captureuser> 10 159 104 189 4/30/13
```

20.2.8 listCaptureConfig

Use with WLST: Online.

20.2.8.1 Description

Displays the list of all Capture configuration attributes with their values. If a value cannot be fetched, it will be shown as "VALUE CANNOT BE DISPLAYED". The most likely cause of an unfetched value is insufficient privilege.

20.2.8.2 Syntax

```
listCaptureConfig()
```

20.2.8.3 Example

The following example lists Capture configuration attributes and values.

```
listCaptureConfig()
```

```
CaptureSystemID CAPTURE_01
BatchRefreshLimit 5
```

20.2.9 getCaptureConfig

Use with WLST: Online.

20.2.9.1 Description

Fetches the value of the attribute specified as an argument. The attribute name must be a string.

20.2.9.2 Syntax

```
getCaptureConfig(['NAME_OF_ATTRIBUTE'])
```

Argument	Definition
<i>NAME_OF_ATTRIBUTE</i>	Name of attribute (as a string) for Capture configuration.

20.2.9.3 Example

The following example fetches the value of the attribute for the Capture system ID.

```
getCaptureConfig('CaptureSYSTEMID')
CAPTURE_01
```

20.2.10 setCaptureConfig

Use with WLST: Online.

20.2.10.1 Description

Sets the value of the Capture attribute to the provided value.

20.2.10.2 Syntax

```
setCaptureConfig(['NAME_OF_ATTRIBUTE'], ['VALUE_OF_ATTRIBUTE'])
```

Argument	Definition
<i>NAME_OF_ATTRIBUTE</i>	Name of Capture configuration attribute to configure.
<i>VALUE_OF_ATTRIBUTE</i>	Value to set for the Capture configuration attribute.

20.2.10.3 Example

The following example sets the CaptureSystemID attribute to the value CAPTURE_02.

```
setCaptureConfig('CaptureSystemID', 'CAPTURE_02')
Attribute 'CaptureSystemID' changed to "CAPTURE_02"
```

20.2.11 scanForClientBundles

Use with WLST: Online.

20.2.11.1 Description

Scans the client bundle directory for bundles. Data for existing bundles will be updated and information for new bundles will be loaded and cached in the database.

20.2.11.2 Syntax

```
scanForClientBundles()
```

20.2.11.3 Example

The following example scans for bundles and lists processed bundles.

```
scanForClientBundles()  
Processed capture bundle.jar
```

20.2.12 deleteBundle

Use with WLST: Online.

20.2.12.1 Description

Deletes an existing bundle.

20.2.12.2 Syntax

```
deleteBundle('bundlename')
```

Argument	Definition
<i>bundlename</i>	Name of an existing bundle to delete.

20.2.12.3 Example

The following example deletes the specified bundle.

```
deleteBundle('Example')
```


Enterprise Scheduler Custom WLST Commands

This chapter describes Oracle Enterprise Scheduler custom WLST commands for getting job request content, managing requests, and managing server and configuration. It includes command syntax, arguments and examples.

Use the Oracle Enterprise Scheduler commands in the categories listed in [Table 21–1](#) to manage configuration, servers, logs, and job requests.

Note: To use these custom WLST commands, you must invoke the WLST script from the Oracle Common home. See "Using Custom WLST Commands" in the *Oracle Fusion Middleware Administrator's Guide*.

When running these WLST commands, you must have the following JARs on your classpath:

- `MW_HOME/oracle_common/modules/oracle.jmx_11.1.1/jmxframework.jar`
- `WL_HOME/server/lib/weblogic.jar`
- `MW_HOME/ORACLE_HOME/ess/lib/ess-admin.jar`

21.1 Enterprise Scheduler Custom Commands

Use the Enterprise Scheduler commands listed in [Table 21–1](#) to manage the Enterprise Scheduler server, configuration, job requests, and logs. In the **Use with WLST** column, "online" means the command can only be used when connected to a running administration server. "Offline" means the command can only be used when not connected to a running server.

Table 21–1 Oracle Enterprise Scheduler Management Commands

Use this command...	To...	Use with WLST...
essGetRequestContent	Get the log and output data files for a request after its execution is completed.	Online
essManageRequest	Cancel, recover, or complete request state manually.	Online
essManageRuntimeConfig	Add, modify, delete and display various configuration parameters.	Online

Table 21–1 (Cont.) Oracle Enterprise Scheduler Management Commands

Use this command...	To...	Use with WLST...
essManageServer	Start, stop or get status of the Enterprise Scheduler application running on the server.	Online
essQueryRequests	Search and list requests based upon hosting application name, state or elapsed time of execution.	Online

21.1.1 essGetRequestContent

Command Category: ESS

Use with WLST: Online

21.1.1.1 Description

Get the log and output data files for a request after its execution is completed.

21.1.1.2 Syntax

```
essGetOutputContent(requestId, contentType, logLines, outDir)
```

Argument	Definition
<i>requestId</i>	The request ID.
<i>contentType</i>	Type of the content to handle. Can be LOG, OUTPUT, BINARY_OUTPUT or TEXT_OUTPUT. By default, the OUTPUT contentType checks for both BINARY_OUTPUT and TEXT_OUTPUT contents.
<i>logLines</i>	Optional. The number of lines to be read from the request log. Default is 1000.
<i>outDir</i>	Optional. The absolute path of the output directory to dump the output files into. Default is the current directory.

21.1.1.3 Examples

To get the request log for request ID 123.

```
essGetOutputContent(123, "LOG")
```

To get all the output of request 123.

```
essGetOutputContent(123, "OUTPUT")
```

To get all the output of request 123 and save it in directory /tmp.

```
essGetOutputContent(123, "OUTPUT", outDir="/tmp")
```

To get all the text output of request 123 and save it in directory /tmp.

```
essGetOutputContent(123, "TEXT_OUTPUT", outDir="/tmp")
```

To get all the binary output of request 123 and save it in directory /tmp.

```
essGetOutputContent(123, "BINARY_OUTPUT", outDir="/tmp")
```

To get first 100 lines of the request log for request id 123.

```
essGetOutputContent(123, "LOG", logLines=100)
```


21.1.2 essManageRequest

Command Category: ESS

Use with WLST: Online

21.1.2.1 Description

Cancel, recover, or complete request state manually.

21.1.2.2 Syntax

```
essManageRequest(requestId, operation, asyncStatus, statusMessage)
```

Argument	Definition
<i>requestId</i>	The request ID.
<i>operation</i>	The operation to perform: CANCEL, RECOVER, or COMPLETE.
<i>asyncStatus</i>	Mandatory when the COMPLETE operation is specified. The status to set for the given request. Must be one of the following: <ul style="list-style-type: none"> ▪ BIZ_ERROR ▪ CANCEL ▪ ERROR ▪ ERROR_MANUAL_RECOVERY ▪ PAUSE ▪ SUCCESS ▪ UPDATE ▪ WARNING
<i>statusMessage</i>	Optional. The qualifying status message to describe the operation.

21.1.2.3 Examples

To cancel request 123.

```
essManageRequest(123, "CANCEL")
```

To recover request 123.

```
essManageRequest(123, "RECOVER")
```

To complete request 123.

```
essManageRequest(123, "COMPLETE", asyncStatus="ERROR", statusMessage="Completed by Admin")
```

21.1.3 essManageRuntimeConfig

Command Category: ESS

Use with WLST: Online

21.1.3.1 Description

Add, modify, delete and display various configuration parameters.

21.1.3.2 Syntax

```
essManageRuntimeConfig(app, type, operation, name, val)
```

Argument	Definition
<i>app</i>	The hosting application name for managing runtime configuration.
<i>type</i>	The type of configuration property. Can be either APP or ESS.
<i>operation</i>	Optional. The operation to perform. Value can be one of the following: add (add), mod (modify), del (delete), get (get), or getall (get all). The default is getall.
<i>name</i>	Optional when the getall value is used for operation. The name of the configuration parameter.
<i>val</i>	Optional when the del, get, or getall value is used for operation. The value to set for the parameter.

21.1.3.3 Examples

To add an ENV parameter "foo" with value "bar".

```
essManageRuntimeConfig("myapp", "APP", operation="add", name="foo", val="bar")
```

To get the value of the ENV parameter "foo".

```
essManageRuntimeConfig("myapp", "APP", operation="get", name="foo")
```

To get the list of all the ENV parameters.

```
essManageRuntimeConfig("myapp", "APP", operation="getall")
essManageRuntimeConfig("myapp", "APP")
```

To modify the value of the ENV parameter "foo" to "barone".

```
essManageRuntimeConfig("myapp", "APP", operation="mod", name="foo", val="barone")
```

To delete the ENV parameter "foo".

```
essManageRuntimeConfig("myapp", "APP", operation="del", name="foo")
```

To show all parameters of type ESS.

```
essManageRuntimeConfig("myapp", "ESS")
```

21.1.4 essManageServer

Command Category: ESS

Use with WLST: Online

21.1.4.1 Description

Start, stop or get status of the Enterprise Scheduler application running on the server. Starting the Enterprise Scheduler application means to start the Enterprise Scheduler processor thread so that request processing can start. Stopping Enterprise Scheduler means to stop or quiesce the Enterprise Scheduler processor so that no new requests are processed.

If connected to the WLS Administration Server in a cluster, this command would operate upon all nodes in the cluster.

21.1.4.2 Syntax

```
essManageServer(operation)
```

Argument	Definition
<i>operation</i>	The operation to perform. One of START, STOP, or STATUS.

21.1.4.3 Examples

To stop Enterprise Scheduler.

```
essManageServer ("STOP")
```

To get the current state of the Enterprise Scheduler processor.

```
essManageServer ("STATUS")
```

21.1.5 essQueryRequests

Command Category: ESS

Use with WLST: Online

21.1.5.1 Description

Search and list requests based on hosting application name, state or elapsed time of execution. This command can be used to find long running requests.

21.1.5.2 Syntax

```
essQueryRequests(app, state, days, hours, minutes)
```

Argument	Definition
<i>app</i>	Optional. The name of the hosting application.
<i>state</i>	Optional. The request state. Can be one of the following (default is RUNNING): <ul style="list-style-type: none"> ▪ BLOCKED ▪ CANCELLED ▪ CANCELLING ▪ COMPLETED ▪ ERROR ▪ ERROR_AUTO_RETRY ▪ ERROR_MANUAL_RECOVERY ▪ EXPIRED ▪ FINISHED ▪ HOLD ▪ PAUSED ▪ PENDING_VALIDATION ▪ READY ▪ RUNNING ▪ SCHEDULE_ENDED ▪ SUCCEEDED ▪ VALIDATION_FAILED ▪ WAIT ▪ WARNING

Argument	Definition
<i>days</i>	Optional. Specifies the time in days.
<i>hours</i>	Optional. Specifies the time in hours.
<i>minutes</i>	Optional. Specifies the time in minutes.

21.1.5.3 Examples

To get all the requests in RUNNING state.

```
essQueryRequests()  
essQueryRequests(state="RUNNING")
```

To get all CANCELLED requests.

```
essQueryRequests(state="CANCELLED")
```

To get all requests running for more than 2 days.

```
essQueryRequests(days=2)
```

To get all requests running for more than 10 hours.

```
essQueryRequests(hours=10)
```

To get all requests running for the application "myapp".

```
essQueryRequests(appName="myapp")
```