Gateway Documentation - Clearing Service

Oracle FLEXCUBE Universal Banking Release 11.3.83.02.0

Release FCUBS_11.3.2.0.0LA

[April] [2014]

ORACLE
FINANCIAL SERVICES

ORACLE

Table Of Contents

1. BACKGROUND **1**

2. FCUBSCGService **2**

2.1. AuthorizeChkProtContract **2**

2.1.1. CA-AuthorizeChkProtContract-Req-Full-MSG.xsd *2*

2.1.2. CA-AuthorizeChkProtContract-Req-IO-MSG.xsd *15*

2.1.3. CA-AuthorizeChkProtContract-Res-Full-MSG.xsd *21*

2.1.4. CA-AuthorizeChkProtContract-Res-PK-MSG.xsd *36*

2.2. CreateChkProtContract **45**

2.2.1. CA-CreateChkProtContract-Req-Full-MSG.xsd *45*

2.2.2. CA-CreateChkProtContract-Req-IO-MSG.xsd *58*

2.2.3. CA-CreateChkProtContract-Res-Full-MSG.xsd *69*

2.2.4. CA-CreateChkProtContract-Res-PK-MSG.xsd *84*

2.3. DeleteChkProtContract **97**

2.3.1. CA-DeleteChkProtContract-Req-Full-MSG.xsd *97*

2.3.2. CA-DeleteChkProtContract-Req-IO-MSG.xsd *110*

2.3.3. CA-DeleteChkProtContract-Res-Full-MSG.xsd *116*

2.3.4. CA-DeleteChkProtContract-Res-PK-MSG.xsd *131*

2.4. QueryChkProtContract **140**

2.4.1. CA-QueryChkProtContract-Req-IO-MSG.xsd *140*

2.4.2. CA-QueryChkProtContract-Res-Full-MSG.xsd *146*

2.5. ReverseChkProtContract **161**

2.5.1. CA-ReverseChkProtContract-Req-Full-MSG.xsd *161*

2.5.2. CA-ReverseChkProtContract-Req-IO-MSG.xsd *174*

2.5.3. CA-ReverseChkProtContract-Res-Full-MSG.xsd *180*

2.5.4. CA-ReverseChkProtContract-Res-PK-MSG.xsd *195*

2.6. AuthorizeCGProductMaint **204**

2.6.1. CG-AuthorizeCGProductMaint-Req-Full-MSG.xsd *204*

2.6.2. CG-AuthorizeCGProductMaint-Req-IO-MSG.xsd *216*

2.6.3. CG-AuthorizeCGProductMaint-Res-Full-MSG.xsd *223*

2.6.4. CG-AuthorizeCGProductMaint-Res-PK-MSG.xsd *237*

2.7. AuthorizeCollectionCheque **246**

2.7.1. CG-AuthorizeCollectionCheque-Req-Full-MSG.xsd *246*

2.7.2. CG-AuthorizeCollectionCheque-Req-IO-MSG.xsd *261*

2.7.3. CG-AuthorizeCollectionCheque-Res-Full-MSG.xsd *267*

2.7.4. CG-AuthorizeCollectionCheque-Res-PK-MSG.xsd *283*

2.8. AuthorizeDocType **292**

2.8.1. CG-AuthorizeDocType-Req-Full-MSG.xsd *292*

2.8.2. CG-AuthorizeDocType-Req-IO-MSG.xsd *301*

2.8.3. CG-AuthorizeDocType-Res-Full-MSG.xsd *308*

2.8.4. CG-AuthorizeDocType-Res-PK-MSG.xsd *318*

2.9. CloseCGProductMaint **327**

2.9.1. CG-CloseCGProductMaint-Req-Full-MSG.xsd *327*

2.9.2. CG-CloseCGProductMaint-Req-IO-MSG.xsd *339*

2.9.3. CG-CloseCGProductMaint-Res-Full-MSG.xsd *346*

2.9.4. CG-CloseCGProductMaint-Res-PK-MSG.xsd *360*

2.10. CloseCGRejErrCdMaint **369**

2.10.1. CG-CloseCGRejErrCdMaint-Req-Full-MSG.xsd *369*

2.10.2. CG-CloseCGRejErrCdMaint-Req-IO-MSG.xsd *378*

2.10.3. CG-CloseCGRejErrCdMaint-Res-Full-MSG.xsd *385*

2.10.4. CG-CloseCGRejErrCdMaint-Res-PK-MSG.xsd *395*

2.11. CloseClgServicePoint **405**

2.11.1. CG-CloseClgServicePoint-Req-Full-MSG.xsd *405*

2.11.2. CG-CloseClgServicePoint-Req-IO-MSG.xsd *414*

2.11.3. CG-CloseClgServicePoint-Res-Full-MSG.xsd *421*

ORACLE

2.11.4. CG-CloseClgServicePoint-Res-PK-MSG.xsd *431*
2.12. CloseDocException **441**
2.12.1. CG-CloseDocException-Req-Full-MSG.xsd *441*
2.12.2. CG-CloseDocException-Req-IO-MSG.xsd *451*
2.12.3. CG-CloseDocException-Res-Full-MSG.xsd *458*
2.12.4. CG-CloseDocException-Res-PK-MSG.xsd *469*
2.13. CloseDocType **479**
2.13.1. CG-CloseDocType-Req-Full-MSG.xsd *479*
2.13.2. CG-CloseDocType-Req-IO-MSG.xsd *488*
2.13.3. CG-CloseDocType-Res-Full-MSG.xsd *495*
2.13.4. CG-CloseDocType-Res-PK-MSG.xsd *505*
2.14. CloseSecCode **514**
2.14.1. CG-CloseSecCode-Req-Full-MSG.xsd *514*
2.14.2. CG-CloseSecCode-Req-IO-MSG.xsd *523*
2.14.3. CG-CloseSecCode-Res-Full-MSG.xsd *530*
2.14.4. CG-CloseSecCode-Res-PK-MSG.xsd *541*
2.15. CreateCGProductMaint **550**
2.15.1. CG-CreateCGProductMaint-Req-Full-MSG.xsd *550*
2.15.2. CG-CreateCGProductMaint-Req-IO-MSG.xsd *562*
2.15.3. CG-CreateCGProductMaint-Res-Full-MSG.xsd *572*
2.15.4. CG-CreateCGProductMaint-Res-PK-MSG.xsd *586*
2.16. CreateClgServicePoint **599**
2.16.1. CG-CreateClgServicePoint-Req-Full-MSG.xsd *599*
2.16.2. CG-CreateClgServicePoint-Req-IO-MSG.xsd *608*
2.16.3. CG-CreateClgServicePoint-Res-Full-MSG.xsd *615*
2.16.4. CG-CreateClgServicePoint-Res-PK-MSG.xsd *625*
2.17. CreateCollectionCheque **634**
2.17.1. CG-CreateCollectionCheque-Req-Full-MSG.xsd *634*
2.17.2. CG-CreateCollectionCheque-Req-IO-MSG.xsd *649*
2.17.3. CG-CreateCollectionCheque-Res-Full-MSG.xsd *662*
2.17.4. CG-CreateCollectionCheque-Res-PK-MSG.xsd *678*
2.18. CreateDocException **693**
2.18.1. CG-CreateDocException-Req-Full-MSG.xsd *693*
2.18.2. CG-CreateDocException-Req-IO-MSG.xsd *703*
2.18.3. CG-CreateDocException-Res-Full-MSG.xsd *711*
2.18.4. CG-CreateDocException-Res-PK-MSG.xsd *722*
2.19. CreateDocType **732**
2.19.1. CG-CreateDocType-Req-Full-MSG.xsd *732*
2.19.2. CG-CreateDocType-Req-IO-MSG.xsd *741*
2.19.3. CG-CreateDocType-Res-Full-MSG.xsd *748*
2.19.4. CG-CreateDocType-Res-PK-MSG.xsd *758*
2.20. CreateSecCode **767**
2.20.1. CG-CreateSecCode-Req-Full-MSG.xsd *767*
2.20.2. CG-CreateSecCode-Req-IO-MSG.xsd *776*
2.20.3. CG-CreateSecCode-Res-Full-MSG.xsd *783*
2.20.4. CG-CreateSecCode-Res-PK-MSG.xsd *794*
2.21. DeleteCGProductMaint **804**
2.21.1. CG-DeleteCGProductMaint-Req-Full-MSG.xsd *804*
2.21.2. CG-DeleteCGProductMaint-Req-IO-MSG.xsd *816*
2.21.3. CG-DeleteCGProductMaint-Res-Full-MSG.xsd *822*
2.21.4. CG-DeleteCGProductMaint-Res-PK-MSG.xsd *836*
2.22. DeleteCollectionCheque **845**
2.22.1. CG-DeleteCollectionCheque-Req-Full-MSG.xsd *845*
2.22.2. CG-DeleteCollectionCheque-Req-IO-MSG.xsd *860*
2.22.3. CG-DeleteCollectionCheque-Res-Full-MSG.xsd *866*
2.22.4. CG-DeleteCollectionCheque-Res-PK-MSG.xsd *882*
2.23. DeleteDocType **891**
2.23.1. CG-DeleteDocType-Req-Full-MSG.xsd *891*

2.23.2. CG-DeleteDocType-Req-IO-MSG.xsd 900
2.23.3. CG-DeleteDocType-Res-Full-MSG.xsd 906
2.23.4. CG-DeleteDocType-Res-PK-MSG.xsd 916
2.24. ModifyCGProductMaint 925
2.24.1. CG-ModifyCGProductMaint-Req-Full-MSG.xsd 925
2.24.2. CG-ModifyCGProductMaint-Req-IO-MSG.xsd 937
2.24.3. CG-ModifyCGProductMaint-Res-Full-MSG.xsd 946
2.24.4. CG-ModifyCGProductMaint-Res-PK-MSG.xsd 960
2.25. ModifyChequeCorrespondence 971
2.25.1. CG-ModifyChequeCorrespondence-Req-Full-MSG.xsd 971
2.25.2. CG-ModifyChequeCorrespondence-Req-IO-MSG.xsd 981
2.25.3. CG-ModifyChequeCorrespondence-Res-Full-MSG.xsd 987
2.25.4. CG-ModifyChequeCorrespondence-Res-PK-MSG.xsd 998
2.26. ModifyClgServicePoint 1007
2.26.1. CG-ModifyClgServicePoint-Req-Full-MSG.xsd 1007
2.26.2. CG-ModifyClgServicePoint-Req-IO-MSG.xsd 1016
2.26.3. CG-ModifyClgServicePoint-Res-Full-MSG.xsd 1023
2.26.4. CG-ModifyClgServicePoint-Res-PK-MSG.xsd 1033
2.27. ModifyDocException 1043
2.27.1. CG-ModifyDocException-Req-Full-MSG.xsd 1043
2.27.2. CG-ModifyDocException-Req-IO-MSG.xsd 1053
2.27.3. CG-ModifyDocException-Res-Full-MSG.xsd 1060
2.27.4. CG-ModifyDocException-Res-PK-MSG.xsd 1071
2.28. ModifyDocType 1081
2.28.1. CG-ModifyDocType-Req-Full-MSG.xsd 1081
2.28.2. CG-ModifyDocType-Req-IO-MSG.xsd 1090
2.28.3. CG-ModifyDocType-Res-Full-MSG.xsd 1097
2.28.4. CG-ModifyDocType-Res-PK-MSG.xsd 1107
2.29. ModifySecCode 1116
2.29.1. CG-ModifySecCode-Req-Full-MSG.xsd 1116
2.29.2. CG-ModifySecCode-Req-IO-MSG.xsd 1125
2.29.3. CG-ModifySecCode-Res-Full-MSG.xsd 1133
2.29.4. CG-ModifySecCode-Res-PK-MSG.xsd 1144
2.30. QueryCGProductMaint 1154
2.30.1. CG-QueryCGProductMaint-Req-IO-MSG.xsd 1154
2.30.2. CG-QueryCGProductMaint-Res-Full-MSG.xsd 1160
2.31. QueryCGRejErrCdMaint 1174
2.31.1. CG-QueryCGRejErrCdMaint-Req-IO-MSG.xsd 1174
2.31.2. CG-QueryCGRejErrCdMaint-Res-Full-MSG.xsd 1181
2.32. QueryChequeCorrespondence 1192
2.32.1. CG-QueryChequeCorrespondence-Req-IO-MSG.xsd 1192
2.32.2. CG-QueryChequeCorrespondence-Res-Full-MSG.xsd 1199
2.33. QueryClgHoliday 1211
2.33.1. CG-QueryClgHoliday-Req-IO-MSG.xsd 1211
2.33.2. CG-QueryClgHoliday-Res-Full-MSG.xsd 1218
2.34. QueryClgServicePoint 1232
2.34.1. CG-QueryClgServicePoint-Req-IO-MSG.xsd 1232
2.34.2. CG-QueryClgServicePoint-Res-Full-MSG.xsd 1239
2.35. QueryCollectionCheque 1250
2.35.1. CG-QueryCollectionCheque-Req-IO-MSG.xsd 1250
2.35.2. CG-QueryCollectionCheque-Res-Full-MSG.xsd 1256
2.36. QueryDocException 1273
2.36.1. CG-QueryDocException-Req-IO-MSG.xsd 1273
2.36.2. CG-QueryDocException-Res-Full-MSG.xsd 1280
2.37. QueryDocType 1292
2.37.1. CG-QueryDocType-Req-IO-MSG.xsd 1292

2.37.2. CG-QueryDocType-Res-Full-MSG.xsd *1298*
2.38. QueryLateClg **1309**
2.38.1. CG-QueryLateClg-Req-IO-MSG.xsd *1309*
2.38.2. CG-QueryLateClg-Res-Full-MSG.xsd *1316*
2.39. QueryQueryParityMismatch **1327**
2.39.1. CG-QueryQueryParityMismatch-Req-IO-MSG.xsd *1327*
2.39.2. CG-QueryQueryParityMismatch-Res-Full-MSG.xsd *1335*
2.40. QuerySecCode **1351**
2.40.1. CG-QuerySecCode-Req-IO-MSG.xsd *1351*
2.40.2. CG-QuerySecCode-Res-Full-MSG.xsd *1357*
2.41. ReopenCGProductMaint **1368**
2.41.1. CG-ReopenCGProductMaint-Req-Full-MSG.xsd *1368*
2.41.2. CG-ReopenCGProductMaint-Req-IO-MSG.xsd *1380*
2.41.3. CG-ReopenCGProductMaint-Res-Full-MSG.xsd *1387*
2.41.4. CG-ReopenCGProductMaint-Res-PK-MSG.xsd *1401*
2.42. ReopenCGRejErrCdMaint **1410**
2.42.1. CG-ReopenCGRejErrCdMaint-Req-Full-MSG.xsd *1410*
2.42.2. CG-ReopenCGRejErrCdMaint-Req-IO-MSG.xsd *1419*
2.42.3. CG-ReopenCGRejErrCdMaint-Res-Full-MSG.xsd *1426*
2.42.4. CG-ReopenCGRejErrCdMaint-Res-PK-MSG.xsd *1436*
2.43. ReopenClgServicePoint **1446**
2.43.1. CG-ReopenClgServicePoint-Req-Full-MSG.xsd *1446*
2.43.2. CG-ReopenClgServicePoint-Req-IO-MSG.xsd *1455*
2.43.3. CG-ReopenClgServicePoint-Res-Full-MSG.xsd *1462*
2.43.4. CG-ReopenClgServicePoint-Res-PK-MSG.xsd *1472*
2.44. ReopenDocException **1482**
2.44.1. CG-ReopenDocException-Req-Full-MSG.xsd *1482*
2.44.2. CG-ReopenDocException-Req-IO-MSG.xsd *1492*
2.44.3. CG-ReopenDocException-Res-Full-MSG.xsd *1499*
2.44.4. CG-ReopenDocException-Res-PK-MSG.xsd *1510*
2.45. ReopenDocType **1520**
2.45.1. CG-ReopenDocType-Req-Full-MSG.xsd *1520*
2.45.2. CG-ReopenDocType-Req-IO-MSG.xsd *1529*
2.45.3. CG-ReopenDocType-Res-Full-MSG.xsd *1536*
2.45.4. CG-ReopenDocType-Res-PK-MSG.xsd *1546*
2.46. ReopenSecCode **1555**
2.46.1. CG-ReopenSecCode-Req-Full-MSG.xsd *1555*
2.46.2. CG-ReopenSecCode-Req-IO-MSG.xsd *1564*
2.46.3. CG-ReopenSecCode-Res-Full-MSG.xsd *1571*
2.46.4. CG-ReopenSecCode-Res-PK-MSG.xsd *1582*
2.47. ReverseCollectionCheque **1591**
2.47.1. CG-ReverseCollectionCheque-Req-Full-MSG.xsd *1591*
2.47.2. CG-ReverseCollectionCheque-Req-IO-MSG.xsd *1606*
2.47.3. CG-ReverseCollectionCheque-Res-Full-MSG.xsd *1612*
2.47.4. CG-ReverseCollectionCheque-Res-PK-MSG.xsd *1628*
2.48. AuthorizeClearingReject **1637**
2.48.1. CGRejection-Auth-Req-Full-MSG.xsd *1637*
2.48.2. CGRejection-Auth-Req-IO-MSG.xsd *1650*
2.48.3. CGRejection-Auth-Res-Full-MSG.xsd *1657*
2.48.4. CGRejection-Auth-Res-PK-MSG.xsd *1671*
2.49. CreateClearingReject **1681**
2.49.1. CGRejection-Create-Req-Full-MSG.xsd *1681*
2.49.2. CGRejection-Create-Req-IO-MSG.xsd *1694*
2.49.3. CGRejection-Create-Res-Full-MSG.xsd *1702*
2.49.4. CGRejection-Create-Res-PK-MSG.xsd *1716*
2.50. QueryClearingReject **1726**
2.50.1. CGRejection-Query-Req-MSG.xsd *1726*

2.50.2. CGRejection-Query-Res-Full-MSG.xsd *1733*
2.51. AuthorizeStopPayment **1747**
2.51.1. CGStopPayment-Auth-Req-Full-MSG.xsd *1747*
2.51.2. CGStopPayment-Auth-Req-MSG.xsd *1759*
2.51.3. CGStopPayment-Auth-Res-Full-MSG.xsd *1766*
2.51.4. CGStopPayment-Auth-Res-PK-MSG.xsd *1779*
2.52. CreateStopPayment **1788**
2.52.1. CGStopPayment-Create-Req-Full-MSG.xsd *1788*
2.52.2. CGStopPayment-Create-Req-MSG.xsd *1800*
2.52.3. CGStopPayment-Create-Res-Full-MSG.xsd *1809*
2.52.4. CGStopPayment-Create-Res-PK-MSG.xsd *1822*
2.53. QueryStopPayment **1833**
2.53.1. CGStopPayment-Query-Req-MSG.xsd *1833*
2.53.2. CGStopPayment-Query-Res-Full-MSG.xsd *1840*
2.54. AuthorizeTransaction **1853**
2.54.1. CGTransaction-Auth-Req-Full-MSG.xsd *1853*
2.54.2. CGTransaction-Auth-Req-MSG.xsd *1915*
2.54.3. CGTransaction-Auth-Res-Full-MSG.xsd *1922*
2.54.4. CGTransaction-Auth-Res-PK-MSG.xsd *1986*
2.55. CreateTransaction **1995**
2.55.1. CGTransaction-Create-Req-Full-MSG.xsd *1995*
2.55.2. CGTransaction-Create-Req-MSG.xsd *2057*
2.55.3. CGTransaction-Create-Res-Full-MSG.xsd *2105*
2.55.4. CGTransaction-Create-Res-PK-MSG.xsd *2169*
2.56. QueryTransaction **2219**
2.56.1. CGTransaction-Query-Req-MSG.xsd *2219*
2.56.2. CGTransaction-Query-Res-Full-MSG.xsd *2226*
2.57. ReverseTransaction **2290**
2.57.1. CGTransaction-Reverse-Req-Full-MSG.xsd *2290*
2.57.2. CGTransaction-Reverse-Req-MSG.xsd *2352*
2.57.3. CGTransaction-Reverse-Res-Full-MSG.xsd *2359*
2.57.4. CGTransaction-Reverse-Res-PK-MSG.xsd *2423*
2.58. QueryCcyClgHoliday **2432**
2.58.1. ST-QueryCcyClgHoliday-Req-IO-MSG.xsd *2432*
2.58.2. ST-QueryCcyClgHoliday-Res-Full-MSG.xsd *2439*

1.BACKGROUND

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data.The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs.
The integration needs supported by the Gateway can be broadly categorized from the perspective of the Gateway as follows:

1. Inbound application integration – used when any external system needs to add, modify or query information within FLEXCUBE UBS
2. Outbound application integration– used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS
The following sections provide detailed XSD documentation of all operations available in FCUBSCGService of Branch-Module

2.FCUBSCGService

Clearing ServiceClearing Service

2.1.AuthorizeChkProtContract

AuthorizeChkProtContract

2.1.1.CA-AuthorizeChkProtContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Protest-Master-Full*
    - *PROTREFNO*
    - *BRANCH*
    - *MODULECODE*
    - *REFERENCE_NO*
    - *DTOFPROT*
    - *INST1*
    - *INST2*
    - *BANKCODE*
    - *SECTORCODE*
    - *TXN_AMOUNT1*
    - *TXNCCY*
    - *COLLECTTAX*

REMCIF

REMACCBRANCH

REMACCCCY

REMACC

REMDETAILS1

BENACCOUNT

REMARKS

MAKERID

MAKERSTAMP

CHECKERID

CHECKERSTAMP

AUTHSTAT

CONTSTAT

Protest-Reason

REASON_CODE

DESCRIPTION

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength 12; pattern [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Protest-Master-Full

Attribute	Description
Name	Protest-Master-Full
Datatype	
Description	

TOP

PROTREFNO

Attribute	Description	
Name	PROTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULECODE

Attribute	Description
Name	MODULECODE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

REFERENCE_NO

Attribute	Description	
Name	REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DTOFPROT

Attribute	Description	
Name	DTOFPROT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

INST1

Attribute	Description	
Name	INST1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INST2

Attribute	Description	
Name	INST2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BANKCODE

Attribute	Description
Name	BANKCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECTORCODE

Attribute	Description
Name	SECTORCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXN_AMOUNT1

Attribute	Description
Name	TXN_AMOUNT1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TXNCCY

Attribute	Description
Name	TXNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLECTTAX

Attribute	Description
Name	COLLECTTAX

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REMCIF

Attribute	**Description**
Name	REMCIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

REMACCBRANCH

Attribute	**Description**
Name	REMACCBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REMACCCCY

Attribute	**Description**
Name	REMACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REMACC

Attribute	**Description**
Name	REMACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

REMDETAILS1

Attribute	Description	
Name	REMDETAILS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENACCOUNT

Attribute	Description	
Name	BENACCOUNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	225

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Protest-Reason

Attribute	**Description**
Name	Protest-Reason
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

REASON_CODE

Attribute	**Description**
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

2.1.2.CA-AuthorizeChkProtContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Protest-Master-IO*
    - *PROTREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Protest-Master-IO

Attribute	Description
Name	Protest-Master-IO
Datatype	
Description	

TOP

PROTREFNO

Attribute	Description
Name	PROTREFNO
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

TOP

2.1.3.CA-AuthorizeChkProtContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Protest-Master-Full*
    - *PROTREFNO*
    - *BRANCH*
    - *MODULECODE*
    - *REFERENCE_NO*
    - *DTOFPROT*
    - *INST1*
    - *INST2*
    - *BANKCODE*
    - *SECTORCODE*
    - *TXN_AMOUNT1*
    - *TXNCCY*
    - *COLLECTTAX*
    - *REMCIF*
    - *REMACCBRANCH*
    - *REMACCCCY*
    - *REMACC*
    - *REMDETAILS1*
    - *BENACCOUNT*

REMARKS
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
CONTSTAT
Protest-Reason
REASON_CODE
DESCRIPTION
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Protest-Master-Full

Attribute	Description
Name	Protest-Master-Full
Datatype	
Description	

TOP

PROTREFNO

Attribute	Description	
Name	PROTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULECODE

Attribute	Description
Name	MODULECODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

REFERENCE_NO

Attribute	**Description**
Name	REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DTOFPROT

Attribute	**Description**
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INST1

Attribute	**Description**
Name	INST1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INST2

Attribute	**Description**
Name	INST2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BANKCODE

Attribute	**Description**
Name	BANKCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SECTORCODE

Attribute	**Description**
Name	SECTORCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXN_AMOUNT1

Attribute	**Description**
Name	TXN_AMOUNT1
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TXNCCY

Attribute	**Description**
Name	TXNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLECTTAX

Attribute	Description
Name	COLLECTTAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REMCIF

Attribute	Description
Name	REMCIF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

REMACCBRANCH

Attribute	Description
Name	REMACCBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REMACCCCY

Attribute	Description
Name	REMACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REMACC

Attribute	Description
Name	REMACC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REMDETAILS1

Attribute	**Description**
Name	REMDETAILS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENACCOUNT

Attribute	**Description**
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Protest-Reason

Attribute	Description
Name	Protest-Reason
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	

Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.1.4.CA-AuthorizeChkProtContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Protest-Master-PK*
      - *PROTREFNO*
    - *Protest-Master-IO*
      - *PROTREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Protest-Master-PK

Attribute	Description
Name	Protest-Master-PK
Datatype	
Description	

TOP

PROTREFNO

Attribute	Description	
Name	PROTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Protest-Master-IO

Attribute	Description
Name	Protest-Master-IO
Datatype	
Description	

TOP

PROTREFNO

Attribute	Description	
Name	PROTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.2.CreateChkProtContract

CreateChkProtContract

2.2.1.CA-CreateChkProtContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Protest-Master-Full*
    - *PROTREFNO*
    - *BRANCH*
    - *MODULECODE*
    - *REFERENCE_NO*
    - *DTOFPROT*
    - *INST1*
    - *INST2*
    - *BANKCODE*
    - *SECTORCODE*
    - *TXN_AMOUNT1*
    - *TXNCCY*
    - *COLLECTTAX*
    - *REMCIF*
    - *REMACCBRANCH*
    - *REMACCCCY*

REMACC

REMDETAILS1

BENACCOUNT

REMARKS

MAKERID

MAKERSTAMP

CHECKERID

CHECKERSTAMP

AUTHSTAT

CONTSTAT

Protest-Reason

REASON_CODE

DESCRIPTION

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Protest-Master-Full

Attribute	Description
Name	Protest-Master-Full
Datatype	
Description	

TOP

PROTREFNO

Attribute	Description	
Name	PROTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULECODE

Attribute	Description	
Name	MODULECODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INST1

Attribute	Description
Name	INST1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INST2

Attribute	Description
Name	INST2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BANKCODE

Attribute	Description
Name	BANKCODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECTORCODE

Attribute	**Description**
Name	SECTORCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXN_AMOUNT1

Attribute	**Description**
Name	TXN_AMOUNT1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TXNCCY

Attribute	**Description**
Name	TXNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLECTTAX

Attribute	**Description**
Name	COLLECTTAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REMCIF

Attribute	Description	
Name	REMCIF	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

REMACCBRANCH

Attribute	Description	
Name	REMACCBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

REMACCCCY

Attribute	Description	
Name	REMACCCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

REMACC

Attribute	Description	
Name	REMACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

TOP

REMDETAILS1

Attribute	Description
Name	REMDETAILS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENACCOUNT

Attribute	Description
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Protest-Reason

Attribute	Description	
Name	Protest-Reason	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

REASON_CODE

Attribute	Description	
Name	REASON_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

TOP

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

2.2.2.CA-CreateChkProtContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Protest-Master-IO*
    - *PROTREFNO*
    - *BRANCH*
    - *MODULECODE*
    - *REFERENCE_NO*
    - *DTOFPROT*
    - *INST1*
    - *INST2*
    - *BANKCODE*
    - *SECTORCODE*
    - *TXN_AMOUNT1*
    - *TXNCCY*
    - *REMACC*
    - *REMARKS*
    - *MAKERSTAMP*
    - *CHECKERSTAMP*
    - *AUTHSTAT*
    - *CONTSTAT*
    - *Protest-Reason*

REASON_CODE

DESCRIPTION

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**

Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Protest-Master-IO

Attribute	Description

Name	Protest-Master-IO
Datatype	
Description	

TOP

PROTREFNO

Attribute	Description
Name	PROTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULECODE

Attribute	Description
Name	MODULECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INST1

Attribute	Description
Name	INST1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INST2

Attribute	Description
Name	INST2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BANKCODE

Attribute	Description
Name	BANKCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECTORCODE

Attribute	Description
Name	SECTORCODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXN_AMOUNT1

Attribute	**Description**
Name	TXN_AMOUNT1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TXNCCY

Attribute	**Description**
Name	TXNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REMACC

Attribute	**Description**
Name	REMACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	225

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Protest-Reason

Attribute	Description
Name	Protest-Reason

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REASON_CODE

Attribute	**Description**
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

2.2.3.CA-CreateChkProtContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Protest-Master-Full*
    - *PROTREFNO*
    - *BRANCH*
    - *MODULECODE*
    - *REFERENCE_NO*
    - *DTOFPROT*
    - *INST1*
    - *INST2*
    - *BANKCODE*
    - *SECTORCODE*
    - *TXN_AMOUNT1*
    - *TXNCCY*
    - *COLLECTTAX*
    - *REMCIF*
    - *REMACCBRANCH*
    - *REMACCCCY*
    - *REMACC*
    - *REMDETAILS1*
    - *BENACCOUNT*

REMARKS
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
CONTSTAT
Protest-Reason
REASON_CODE
DESCRIPTION
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Protest-Master-Full

Attribute	Description
Name	Protest-Master-Full
Datatype	
Description	

TOP

PROTREFNO

Attribute	Description	
Name	PROTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULECODE

Attribute	Description
Name	MODULECODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

REFERENCE_NO

Attribute	**Description**
Name	REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DTOFPROT

Attribute	**Description**
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INST1

Attribute	**Description**
Name	INST1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INST2

Attribute	**Description**
Name	INST2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BANKCODE

Attribute	**Description**
Name	BANKCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SECTORCODE

Attribute	**Description**
Name	SECTORCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXN_AMOUNT1

Attribute	**Description**
Name	TXN_AMOUNT1
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TXNCCY

Attribute	**Description**
Name	TXNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLECTTAX

Attribute	Description
Name	COLLECTTAX
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

REMCIF

Attribute	Description
Name	REMCIF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

REMACCBRANCH

Attribute	Description
Name	REMACCBRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

REMACCCCY

Attribute	Description
Name	REMACCCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

REMACC

Attribute	Description
Name	REMACC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REMDETAILS1

Attribute	**Description**
Name	REMDETAILS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENACCOUNT

Attribute	**Description**
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Protest-Reason

Attribute	Description
Name	Protest-Reason
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	

Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.2.4.CA-CreateChkProtContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Protest-Master-PK*
      - *PROTREFNO*
    - *Protest-Master-IO*
      - *PROTREFNO*
      - *BRANCH*
      - *MODULECODE*
      - *REFERENCE_NO*
      - *DTOFPROT*
      - *INST1*
      - *INST2*
      - *BANKCODE*
      - *SECTORCODE*
      - *TXN_AMOUNT1*
      - *TXNCCY*
      - *REMACC*
      - *REMARKS*
      - *MAKERSTAMP*
      - *CHECKERSTAMP*

AUTHSTAT

CONTSTAT

Protest-Reason

REASON_CODE

DESCRIPTION

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Protest-Master-PK

Attribute	Description
Name	Protest-Master-PK
Datatype	
Description	

TOP

PROTREFNO

Attribute	Description	
Name	PROTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Protest-Master-IO

Attribute	Description
Name	Protest-Master-IO
Datatype	
Description	

TOP

PROTREFNO

Attribute	Description
Name	PROTREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULECODE

Attribute	Description	
Name	MODULECODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

REFERENCE_NO

Attribute	Description	
Name	REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DTOFPROT

Attribute	Description	
Name	DTOFPROT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

INST1

Attribute	Description
Name	INST1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INST2

Attribute	Description
Name	INST2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BANKCODE

Attribute	Description
Name	BANKCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECTORCODE

Attribute	Description
Name	SECTORCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXN_AMOUNT1

Attribute	Description

Name	TXN_AMOUNT1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TXNCCY

Attribute	**Description**
Name	TXNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REMACC

Attribute	**Description**
Name	REMACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Protest-Reason

Attribute	Description
Name	Protest-Reason
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC

Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.3.DeleteChkProtContract

DeleteChkProtContract

2.3.1.CA-DeleteChkProtContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Protest-Master-Full*
    - *PROTREFNO*
    - *BRANCH*
    - *MODULECODE*
    - *REFERENCE_NO*
    - *DTOFPROT*
    - *INST1*
    - *INST2*
    - *BANKCODE*
    - *SECTORCODE*
    - *TXN_AMOUNT1*
    - *TXNCCY*
    - *COLLECTTAX*
    - *REMCIF*
    - *REMACCBRANCH*
    - *REMACCCCY*

REMACC

REMDETAILS1

BENACCOUNT

REMARKS

MAKERID

MAKERSTAMP

CHECKERID

CHECKERSTAMP

AUTHSTAT

CONTSTAT

Protest-Reason

REASON_CODE

DESCRIPTION

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Protest-Master-Full

Attribute	Description
Name	Protest-Master-Full
Datatype	
Description	

TOP

PROTREFNO

Attribute	Description	
Name	PROTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULECODE

Attribute	Description	
Name	MODULECODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INST1

Attribute	Description
Name	INST1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INST2

Attribute	Description
Name	INST2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BANKCODE

Attribute	Description
Name	BANKCODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECTORCODE

Attribute	**Description**
Name	SECTORCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXN_AMOUNT1

Attribute	**Description**
Name	TXN_AMOUNT1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TXNCCY

Attribute	**Description**
Name	TXNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLECTTAX

Attribute	**Description**
Name	COLLECTTAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REMCIF

Attribute	Description	
Name	REMCIF	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

REMACCBRANCH

Attribute	Description	
Name	REMACCBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

REMACCCCY

Attribute	Description	
Name	REMACCCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

REMACC

Attribute	Description	
Name	REMACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	20

TOP

REMDETAILS1

Attribute	Description	
Name	REMDETAILS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENACCOUNT

Attribute	Description	
Name	BENACCOUNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	225

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Protest-Reason

Attribute	**Description**
Name	Protest-Reason
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REASON_CODE

Attribute	**Description**
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

2.3.2.CA-DeleteChkProtContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Protest-Master-IO*
    - *PROTREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Protest-Master-IO

Attribute	Description
Name	Protest-Master-IO
Datatype	
Description	

TOP

PROTREFNO

Attribute	Description	
Name	PROTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.3.3.CA-DeleteChkProtContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Protest-Master-Full*
    - *PROTREFNO*
    - *BRANCH*
    - *MODULECODE*
    - *REFERENCE_NO*
    - *DTOFPROT*
    - *INST1*
    - *INST2*
    - *BANKCODE*
    - *SECTORCODE*
    - *TXN_AMOUNT1*
    - *TXNCCY*
    - *COLLECTTAX*
    - *REMCIF*
    - *REMACCBRANCH*
    - *REMACCCCY*
    - *REMACC*
    - *REMDETAILS1*
    - *BENACCOUNT*

REMARKS
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
CONTSTAT
Protest-Reason
REASON_CODE
DESCRIPTION
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Protest-Master-Full

Attribute	Description
Name	Protest-Master-Full
Datatype	
Description	

TOP

PROTREFNO

Attribute	Description	
Name	PROTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULECODE

Attribute	Description
Name	MODULECODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

REFERENCE_NO

Attribute	**Description**
Name	REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DTOFPROT

Attribute	**Description**
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INST1

Attribute	**Description**
Name	INST1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INST2

Attribute	**Description**
Name	INST2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	16

TOP

BANKCODE

Attribute	Description	
Name	BANKCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOP

SECTORCODE

Attribute	Description	
Name	SECTORCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

TXN_AMOUNT1

Attribute	Description	
Name	TXN_AMOUNT1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

TOP

TXNCCY

Attribute	Description	
Name	TXNCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

COLLECTTAX

Attribute	Description
Name	COLLECTTAX
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

REMCIF

Attribute	Description
Name	REMCIF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

REMACCBRANCH

Attribute	Description
Name	REMACCBRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

REMACCCCY

Attribute	Description
Name	REMACCCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

REMACC

Attribute	Description
Name	REMACC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REMDETAILS1

Attribute	**Description**
Name	REMDETAILS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENACCOUNT

Attribute	**Description**
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Protest-Reason

Attribute	Description
Name	Protest-Reason
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	

Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.3.4.CA-DeleteChkProtContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Protest-Master-PK*
      - *PROTREFNO*
    - *Protest-Master-IO*
      - *PROTREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Protest-Master-PK

Attribute	Description
Name	Protest-Master-PK
Datatype	
Description	

TOP

PROTREFNO

Attribute	Description
Name	PROTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Protest-Master-IO

Attribute	Description
Name	Protest-Master-IO
Datatype	
Description	

TOP

PROTREFNO

Attribute	Description
Name	PROTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.4.QueryChkProtContract

QueryChkProtContract

2.4.1.CA-QueryChkProtContract-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Protest-Master-IO
PROTREFNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Protest-Master-IO

Attribute	Description
Name	Protest-Master-IO
Datatype	
Description	

TOP

PROTREFNO

Attribute	Description
Name	PROTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

2.4.2.CA-QueryChkProtContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Protest-Master-IO*
      - *PROTREFNO*
    - *Protest-Master-Full*
      - *PROTREFNO*
      - *BRANCH*
      - *MODULECODE*
      - *REFERENCE_NO*
      - *DTOFPROT*
      - *INST1*
      - *INST2*
      - *BANKCODE*
      - *SECTORCODE*
      - *TXN_AMOUNT1*
      - *TXNCCY*
      - *COLLECTTAX*
      - *REMCIF*
      - *REMACCBRANCH*
      - *REMACCCCY*

REMACC

REMDETAILS1

BENACCOUNT

REMARKS

MAKERID

MAKERSTAMP

CHECKERID

CHECKERSTAMP

AUTHSTAT

CONTSTAT

Protest-Reason

REASON_CODE

DESCRIPTION

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Protest-Master-IO

Attribute	Description
Name	Protest-Master-IO
Datatype	
Description	

TOP

PROTREFNO

Attribute	Description	
Name	PROTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Protest-Master-Full

Attribute	Description
Name	Protest-Master-Full
Datatype	
Description	

TOP

PROTREFNO

Attribute	Description
Name	PROTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULECODE

Attribute	Description
Name	MODULECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	16

TOP

DTOFPROT

Attribute	Description	
Name	DTOFPROT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

TOP

INST1

Attribute	Description	
Name	INST1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

TOP

INST2

Attribute	Description	
Name	INST2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

BANKCODE

Attribute	Description	
Name	BANKCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOP

SECTORCODE

Attribute	Description
Name	SECTORCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXN_AMOUNT1

Attribute	Description
Name	TXN_AMOUNT1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TXNCCY

Attribute	Description
Name	TXNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLECTTAX

Attribute	Description
Name	COLLECTTAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REMCIF

Attribute	Description
Name	REMCIF
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REMACCBRANCH

Attribute	Description
Name	REMACCBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REMACCCCY

Attribute	Description
Name	REMACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REMACC

Attribute	Description
Name	REMACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REMDETAILS1

Attribute	Description
Name	REMDETAILS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENACCOUNT

Attribute	Description
Name	BENACCOUNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 50

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Protest-Reason

Attribute	Description
Name	Protest-Reason
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 20

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.5.ReverseChkProtContract

ReverseChkProtContract

2.5.1.CA-ReverseChkProtContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Protest-Master-Full*
    - *PROTREFNO*
    - *BRANCH*
    - *MODULECODE*
    - *REFERENCE_NO*
    - *DTOFPROT*
    - *INST1*
    - *INST2*
    - *BANKCODE*
    - *SECTORCODE*
    - *TXN_AMOUNT1*
    - *TXNCCY*
    - *COLLECTTAX*
    - *REMCIF*
    - *REMACCBRANCH*
    - *REMACCCCY*

REMACC

REMDETAILS1

BENACCOUNT

REMARKS

MAKERID

MAKERSTAMP

CHECKERID

CHECKERSTAMP

AUTHSTAT

CONTSTAT

Protest-Reason

REASON_CODE

DESCRIPTION

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Protest-Master-Full

Attribute	Description
Name	Protest-Master-Full
Datatype	
Description	

TOP

PROTREFNO

Attribute	Description	
Name	PROTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULECODE

Attribute	Description	
Name	MODULECODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DTOFPROT

Attribute	Description
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INST1

Attribute	Description
Name	INST1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INST2

Attribute	Description
Name	INST2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BANKCODE

Attribute	Description
Name	BANKCODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECTORCODE

Attribute	**Description**
Name	SECTORCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXN_AMOUNT1

Attribute	**Description**
Name	TXN_AMOUNT1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TXNCCY

Attribute	**Description**
Name	TXNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLECTTAX

Attribute	**Description**
Name	COLLECTTAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REMCIF

Attribute	**Description**
Name	REMCIF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REMACCBRANCH

Attribute	**Description**
Name	REMACCBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REMACCCCY

Attribute	**Description**
Name	REMACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REMACC

Attribute	**Description**
Name	REMACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

REMDETAILS1

Attribute	Description
Name	REMDETAILS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENACCOUNT

Attribute	Description
Name	BENACCOUNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 50

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Protest-Reason

Attribute	**Description**
Name	Protest-Reason
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REASON_CODE

Attribute	**Description**
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

2.5.2.CA-ReverseChkProtContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Protest-Master-IO*
    - *PROTREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Protest-Master-IO

Attribute	Description
Name	Protest-Master-IO
Datatype	
Description	

TOP

PROTREFNO

Attribute	Description
Name	PROTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

2.5.3.CA-ReverseChkProtContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Protest-Master-Full*
    - *PROTREFNO*
    - *BRANCH*
    - *MODULECODE*
    - *REFERENCE_NO*
    - *DTOFPROT*
    - *INST1*
    - *INST2*
    - *BANKCODE*
    - *SECTORCODE*
    - *TXN_AMOUNT1*
    - *TXNCCY*
    - *COLLECTTAX*
    - *REMCIF*
    - *REMACCBRANCH*
    - *REMACCCCY*
    - *REMACC*
    - *REMDETAILS1*
    - *BENACCOUNT*

REMARKS
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
CONTSTAT
Protest-Reason
REASON_CODE
DESCRIPTION
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Protest-Master-Full

Attribute	Description
Name	Protest-Master-Full
Datatype	
Description	

TOP

PROTREFNO

Attribute	Description	
Name	PROTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULECODE

Attribute	Description
Name	MODULECODE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

REFERENCE_NO

Attribute	**Description**
Name	REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DTOFPROT

Attribute	**Description**
Name	DTOFPROT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INST1

Attribute	**Description**
Name	INST1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INST2

Attribute	**Description**
Name	INST2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BANKCODE

Attribute	Description
Name	BANKCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SECTORCODE

Attribute	Description
Name	SECTORCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXN_AMOUNT1

Attribute	Description
Name	TXN_AMOUNT1
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TXNCCY

Attribute	Description
Name	TXNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLECTTAX

Attribute	Description
Name	COLLECTTAX
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

REMCIF

Attribute	Description
Name	REMCIF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

REMACCBRANCH

Attribute	Description
Name	REMACCBRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

REMACCCCY

Attribute	Description
Name	REMACCCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

REMACC

Attribute	Description
Name	REMACC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REMDETAILS1

Attribute	**Description**
Name	REMDETAILS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENACCOUNT

Attribute	**Description**
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Protest-Reason

Attribute	Description
Name	Protest-Reason
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

REASON_CODE

Attribute	Description
Name	REASON_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	

Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.5.4.CA-ReverseChkProtContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Protest-Master-PK*
      - *PROTREFNO*
    - *Protest-Master-IO*
      - *PROTREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Protest-Master-PK

Attribute	Description
Name	Protest-Master-PK
Datatype	
Description	

TOP

PROTREFNO

Attribute	Description	
Name	PROTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Protest-Master-IO

Attribute	Description
Name	Protest-Master-IO
Datatype	
Description	

TOP

PROTREFNO

Attribute	Description	
Name	PROTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.6.AuthorizeCGProductMaint

AuthorizeCGProductMaint

2.6.1.CG-AuthorizeCGProductMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bank-Parameters-Full*
    - *BANK_CODE*
    - *INTERNAL_PRODUCT*
    - *PROT_INWARD_PROD*
    - *PROT_INTERNAL_PROD*
    - *NON_LOCAL_PROD*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Bank-Product-Det-A*
      - *PRODUCT_CODE*
      - *DOCUMENT_TYPE*

LOCAL_CLEARING

VARIOUS_PMNT_INDICATOR

OW_RET_PROD

CLG_SERVICE_PRODUCT

MEMO_PRODUCT

DRAWER_BANK_EXPENSE_ACC

Bank-Product-Det-B

PRODUCT_CODE

DOCUMENT_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Bank-Parameters-Full

Attribute	Description
Name	Bank-Parameters-Full
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

INTERNAL_PRODUCT

Attribute	Description	
Name	INTERNAL_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PROT_INWARD_PROD

Attribute	Description	
Name	PROT_INWARD_PROD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PROT_INTERNAL_PROD

Attribute	Description
Name	PROT_INTERNAL_PROD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

NON_LOCAL_PROD

Attribute	Description
Name	NON_LOCAL_PROD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Bank-Product-Det-A

Attribute	Description	
Name	Bank-Product-Det-A	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRODUCT_CODE

Attribute	Description	
Name	PRODUCT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LOCAL_CLEARING

Attribute	Description	
Name	LOCAL_CLEARING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VARIOUS_PMNT_INDICATOR

Attribute	Description
Name	VARIOUS_PMNT_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / V,N,G,A,O

TOP

OW_RET_PROD

Attribute	Description
Name	OW_RET_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLG_SERVICE_PRODUCT

Attribute	Description
Name	CLG_SERVICE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MEMO_PRODUCT

Attribute	Description
Name	MEMO_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DRAWER_BANK_EXPENSE_ACC

Attribute	Description
Name	DRAWER_BANK_EXPENSE_ACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Bank-Product-Det-B

Attribute	Description
Name	Bank-Product-Det-B
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRODUCT_CODE

Attribute	Description
Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

2.6.2.CG-AuthorizeCGProductMaint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bank-Parameters-IO*
    - *BANK_CODE*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Bank-Parameters-IO

Attribute	Description
Name	Bank-Parameters-IO
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description
Name	BANK_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.6.3.CG-AuthorizeCGProductMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bank-Parameters-Full*
    - *BANK_CODE*
    - *INTERNAL_PRODUCT*
    - *PROT_INWARD_PROD*
    - *PROT_INTERNAL_PROD*
    - *NON_LOCAL_PROD*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Bank-Product-Det-A*
      - *PRODUCT_CODE*
      - *DOCUMENT_TYPE*
      - *LOCAL_CLEARING*
      - *VARIOUS_PMNT_INDICATOR*
      - *OW_RET_PROD*

CLG_SERVICE_PRODUCT

MEMO_PRODUCT

DRAWER_BANK_EXPENSE_ACC

Bank-Product-Det-B

PRODUCT_CODE

DOCUMENT_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength 12; pattern [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Bank-Parameters-Full

Attribute	Description
Name	Bank-Parameters-Full
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

INTERNAL_PRODUCT

Attribute	Description	
Name	INTERNAL_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PROT_INWARD_PROD

Attribute	Description
Name	PROT_INWARD_PROD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PROT_INTERNAL_PROD

Attribute	**Description**
Name	PROT_INTERNAL_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

NON_LOCAL_PROD

Attribute	**Description**
Name	NON_LOCAL_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Bank-Product-Det-A

Attribute	Description
Name	Bank-Product-Det-A
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRODUCT_CODE

Attribute	Description
Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LOCAL_CLEARING

Attribute	Description

Name	LOCAL_CLEARING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VARIOUS_PMNT_INDICATOR

Attribute	**Description**
Name	VARIOUS_PMNT_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / V,N,G,A,O

TOP

OW_RET_PROD

Attribute	**Description**
Name	OW_RET_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLG_SERVICE_PRODUCT

Attribute	**Description**
Name	CLG_SERVICE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MEMO_PRODUCT

Attribute	**Description**
Name	MEMO_PRODUCT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DRAWER_BANK_EXPENSE_ACC

Attribute	Description	
Name	DRAWER_BANK_EXPENSE_ACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Bank-Product-Det-B

Attribute	Description	
Name	Bank-Product-Det-B	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRODUCT_CODE

Attribute	Description	
Name	PRODUCT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bank-Parameters-PK*
      - *BANK_CODE*
    - *Bank-Parameters-IO*
      - *BANK_CODE*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bank-Parameters-PK

Attribute	Description
Name	Bank-Parameters-PK
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Bank-Parameters-IO

Attribute	Description
Name	Bank-Parameters-IO
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

ORACLE

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.7.AuthorizeCollectionCheque

AuthorizeCollectionCheque

2.7.1.CG-AuthorizeCollectionCheque-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Master-Full*
    - *DEPOSITSLIP*
    - *TRN_BRANCH*
    - *REFERENCE_NO*
    - *BENE_DETAILS1*
    - *INSTRUMENT_CCY*
    - *INSTRUMENT_AMT*
    - *RECORD_STAT*
    - *AUTH_STAT*
    - *MAKER_ID*
    - *MAKER_DT_STAMP*
    - *CHECKER_ID*
    - *CHECKER_DT_STAMP*
    - *REMARKS*
    - *DEPOSITOR_NAME*
    - *BEN_ACCOUNT*

Coll-Dispatch-Details

INSTRUMENT_NO

INSTRUMENT_AMT

INSTRUMENT_DATE

DRAWEE_ACC_NO

DRAWEE_BANK

DRAWEE_BRANCH

DRAWEE_CITY

DEPOSIT_CITY

DOCUMENT_TYPE

COLLECTION_PRO_EXC

ROUTING_GL_EXC

CLEARING_CITY

CORRESPONDENT_BANK

CORRESPONDENT_BRANCH

COLLECTION_TYPE

TRN_REF_NO

DISPATCH_REF_NO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Clearing-Master-Full

Attribute	Description
Name	Clearing-Master-Full
Datatype	
Description	

TOP

DEPOSITSLIP

Attribute	Description	
Name	DEPOSITSLIP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TRN_BRANCH

Attribute	Description	
Name	TRN_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REFERENCE_NO

Attribute	Description

Name	REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BENE_DETAILS1

Attribute	**Description**
Name	BENE_DETAILS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRUMENT_CCY

Attribute	**Description**
Name	INSTRUMENT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTRUMENT_AMT

Attribute	**Description**
Name	INSTRUMENT_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

RECORD_STAT

Attribute	**Description**
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DEPOSITOR_NAME

Attribute	Description
Name	DEPOSITOR_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BEN_ACCOUNT

Attribute	Description
Name	BEN_ACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Coll-Dispatch-Details

Attribute	Description
Name	Coll-Dispatch-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSTRUMENT_NO

Attribute	Description
Name	INSTRUMENT_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRUMENT_AMT

Attribute	Description
Name	INSTRUMENT_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRAWEE_ACC_NO

Attribute	Description
Name	DRAWEE_ACC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	16

TOP

DRAWEE_BANK

Attribute	Description	
Name	DRAWEE_BANK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

DRAWEE_BRANCH

Attribute	Description	
Name	DRAWEE_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

DRAWEE_CITY

Attribute	Description	
Name	DRAWEE_CITY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

DEPOSIT_CITY

Attribute	Description	
Name	DEPOSIT_CITY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

COLLECTION_PRO_EXC

Attribute	Description
Name	COLLECTION_PRO_EXC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ROUTING_GL_EXC

Attribute	Description
Name	ROUTING_GL_EXC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CLEARING_CITY

Attribute	Description
Name	CLEARING_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

CORRESPONDENT_BANK

Attribute	Description
Name	CORRESPONDENT_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CORRESPONDENT_BRANCH

Attribute	Description
Name	CORRESPONDENT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COLLECTION_TYPE

Attribute	Description
Name	COLLECTION_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,O

TOP

TRN_REF_NO

Attribute	Description
Name	TRN_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DISPATCH_REF_NO

Attribute	Description
Name	DISPATCH_REF_NO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 21

TOP

2.7.2.CG-AuthorizeCollectionCheque-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Master-IO*
    - *REFERENCE_NO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Clearing-Master-IO

Attribute	Description
Name	Clearing-Master-IO
Datatype	
Description	

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

2.7.3.CG-AuthorizeCollectionCheque-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Master-Full*
    - *DEPOSITSLIP*
    - *TRN_BRANCH*
    - *REFERENCE_NO*
    - *BENE_DETAILS1*
    - *INSTRUMENT_CCY*
    - *INSTRUMENT_AMT*
    - *RECORD_STAT*
    - *AUTH_STAT*
    - *MAKER_ID*
    - *MAKER_DT_STAMP*
    - *CHECKER_ID*
    - *CHECKER_DT_STAMP*
    - *REMARKS*
    - *DEPOSITOR_NAME*
    - *BEN_ACCOUNT*
    - *Coll-Dispatch-Details*
      - *INSTRUMENT_NO*
      - *INSTRUMENT_AMT*

INSTRUMENT_DATE

DRAWEE_ACC_NO

DRAWEE_BANK

DRAWEE_BRANCH

DRAWEE_CITY

DEPOSIT_CITY

DOCUMENT_TYPE

COLLECTION_PRO_EXC

ROUTING_GL_EXC

CLEARING_CITY

CORRESPONDENT_BANK

CORRESPONDENT_BRANCH

COLLECTION_TYPE

TRN_REF_NO

DISPATCH_REF_NO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Clearing-Master-Full

Attribute	Description
Name	Clearing-Master-Full
Datatype	
Description	

TOP

DEPOSITSLIP

Attribute	Description	
Name	DEPOSITSLIP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TRN_BRANCH

Attribute	Description
Name	TRN_BRANCH
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REFERENCE_NO

Attribute	Description	
Name	REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BENE_DETAILS1

Attribute	Description	
Name	BENE_DETAILS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRUMENT_CCY

Attribute	Description	
Name	INSTRUMENT_CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INSTRUMENT_AMT

Attribute	Description	
Name	INSTRUMENT_AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

DEPOSITOR_NAME

Attribute	Description
Name	DEPOSITOR_NAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 35

TOP

BEN_ACCOUNT

Attribute	Description
Name	BEN_ACCOUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Coll-Dispatch-Details

Attribute	**Description**
Name	Coll-Dispatch-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSTRUMENT_NO

Attribute	**Description**
Name	INSTRUMENT_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRUMENT_AMT

Attribute	**Description**
Name	INSTRUMENT_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INSTRUMENT_DATE

Attribute	**Description**
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRAWEE_ACC_NO

Attribute	Description
Name	DRAWEE_ACC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DRAWEE_BANK

Attribute	Description
Name	DRAWEE_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DRAWEE_BRANCH

Attribute	Description
Name	DRAWEE_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DRAWEE_CITY

Attribute	Description
Name	DRAWEE_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

DEPOSIT_CITY

Attribute	Description

Name	DEPOSIT_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

DOCUMENT_TYPE

Attribute	**Description**
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

COLLECTION_PRO_EXC

Attribute	**Description**
Name	COLLECTION_PRO_EXC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ROUTING_GL_EXC

Attribute	**Description**
Name	ROUTING_GL_EXC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CLEARING_CITY

Attribute	**Description**
Name	CLEARING_CITY
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

CORRESPONDENT_BANK

Attribute	**Description**
Name	CORRESPONDENT_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CORRESPONDENT_BRANCH

Attribute	**Description**
Name	CORRESPONDENT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COLLECTION_TYPE

Attribute	**Description**
Name	COLLECTION_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,O

TOP

TRN_REF_NO

Attribute	**Description**
Name	TRN_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	16

TOP

DISPATCH_REF_NO

Attribute	Description	
Name	DISPATCH_REF_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	21

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Clearing-Master-PK*
      - *REFERENCE_NO*
    - *Clearing-Master-IO*
      - *REFERENCE_NO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Clearing-Master-PK

Attribute	Description
Name	Clearing-Master-PK
Datatype	
Description	

TOP

REFERENCE_NO

Attribute	Description	
Name	REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Clearing-Master-IO

Attribute	Description
Name	Clearing-Master-IO
Datatype	
Description	

TOP

REFERENCE_NO

Attribute	Description	
Name	REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.8.AuthorizeDocType

AuthorizeDocType

2.8.1.CG-AuthorizeDocType-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Document-Type-Full*
    - *INSTRUMENT_TYPE*
    - *DOCUMENT_TYPE*
    - *DESCRIPTION*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Document-Type-Full

Attribute	Description
Name	Document-Type-Full
Datatype	
Description	

TOP

INSTRUMENT_TYPE

Attribute	Description
Name	INSTRUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description

Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Document-Type-IO*
    - *DOCUMENT_TYPE*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Document-Type-IO

Attribute	Description
Name	Document-Type-IO
Datatype	
Description	

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.8.3.CG-AuthorizeDocType-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Document-Type-Full*
    - *INSTRUMENT_TYPE*
    - *DOCUMENT_TYPE*
    - *DESCRIPTION*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Document-Type-Full

Attribute	Description

Name	Document-Type-Full
Datatype	
Description	

TOP

INSTRUMENT_TYPE

Attribute	Description
Name	INSTRUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**

Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Document-Type-PK*
      - *DOCUMENT_TYPE*
    - *Document-Type-IO*
      - *DOCUMENT_TYPE*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Document-Type-PK

Attribute	Description
Name	Document-Type-PK
Datatype	
Description	

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Document-Type-IO

Attribute	Description
Name	Document-Type-IO
Datatype	
Description	

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.9.CloseCGProductMaint

CloseCGProductMaint

2.9.1.CG-CloseCGProductMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bank-Parameters-Full*
    - *BANK_CODE*
    - *INTERNAL_PRODUCT*
    - *PROT_INWARD_PROD*
    - *PROT_INTERNAL_PROD*
    - *NON_LOCAL_PROD*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Bank-Product-Det-A*
      - *PRODUCT_CODE*
      - *DOCUMENT_TYPE*

LOCAL_CLEARING

VARIOUS_PMNT_INDICATOR

OW_RET_PROD

CLG_SERVICE_PRODUCT

MEMO_PRODUCT

DRAWER_BANK_EXPENSE_ACC

Bank-Product-Det-B

PRODUCT_CODE

DOCUMENT_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Bank-Parameters-Full

Attribute	Description
Name	Bank-Parameters-Full
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

INTERNAL_PRODUCT

Attribute	Description	
Name	INTERNAL_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PROT_INWARD_PROD

Attribute	Description	
Name	PROT_INWARD_PROD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PROT_INTERNAL_PROD

Attribute	Description
Name	PROT_INTERNAL_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

NON_LOCAL_PROD

Attribute	Description
Name	NON_LOCAL_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Bank-Product-Det-A

Attribute	Description	
Name	Bank-Product-Det-A	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRODUCT_CODE

Attribute	Description	
Name	PRODUCT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LOCAL_CLEARING

Attribute	Description	
Name	LOCAL_CLEARING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VARIOUS_PMNT_INDICATOR

Attribute	Description
Name	VARIOUS_PMNT_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / V,N,G,A,O

TOP

OW_RET_PROD

Attribute	Description
Name	OW_RET_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLG_SERVICE_PRODUCT

Attribute	Description
Name	CLG_SERVICE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MEMO_PRODUCT

Attribute	Description
Name	MEMO_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DRAWER_BANK_EXPENSE_ACC

Attribute	Description
Name	DRAWER_BANK_EXPENSE_ACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Bank-Product-Det-B

Attribute	Description
Name	Bank-Product-Det-B
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRODUCT_CODE

Attribute	Description
Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bank-Parameters-IO*
    - *BANK_CODE*
    - *MAKER*
    - *MAKERSTAMP*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Bank-Parameters-IO

Attribute	Description
Name	Bank-Parameters-IO
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description
Name	BANK_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.9.3.CG-CloseCGProductMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bank-Parameters-Full*
    - *BANK_CODE*
    - *INTERNAL_PRODUCT*
    - *PROT_INWARD_PROD*
    - *PROT_INTERNAL_PROD*
    - *NON_LOCAL_PROD*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Bank-Product-Det-A*
      - *PRODUCT_CODE*
      - *DOCUMENT_TYPE*
      - *LOCAL_CLEARING*
      - *VARIOUS_PMNT_INDICATOR*
      - *OW_RET_PROD*

CLG_SERVICE_PRODUCT

MEMO_PRODUCT

DRAWER_BANK_EXPENSE_ACC

Bank-Product-Det-B

PRODUCT_CODE

DOCUMENT_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Bank-Parameters-Full

Attribute	Description
Name	Bank-Parameters-Full
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

INTERNAL_PRODUCT

Attribute	Description	
Name	INTERNAL_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PROT_INWARD_PROD

Attribute	Description
Name	PROT_INWARD_PROD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PROT_INTERNAL_PROD

Attribute	**Description**
Name	PROT_INTERNAL_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

NON_LOCAL_PROD

Attribute	**Description**
Name	NON_LOCAL_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Bank-Product-Det-A

Attribute	Description
Name	Bank-Product-Det-A
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRODUCT_CODE

Attribute	Description
Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LOCAL_CLEARING

Attribute	Description

Name	LOCAL_CLEARING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VARIOUS_PMNT_INDICATOR

Attribute	**Description**
Name	VARIOUS_PMNT_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / V,N,G,A,O

TOP

OW_RET_PROD

Attribute	**Description**
Name	OW_RET_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLG_SERVICE_PRODUCT

Attribute	**Description**
Name	CLG_SERVICE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MEMO_PRODUCT

Attribute	**Description**
Name	MEMO_PRODUCT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DRAWER_BANK_EXPENSE_ACC

Attribute	Description	
Name	DRAWER_BANK_EXPENSE_ACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Bank-Product-Det-B

Attribute	Description	
Name	Bank-Product-Det-B	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRODUCT_CODE

Attribute	Description	
Name	PRODUCT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bank-Parameters-PK*
      - *BANK_CODE*
    - *Bank-Parameters-IO*
      - *BANK_CODE*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bank-Parameters-PK

Attribute	Description
Name	Bank-Parameters-PK
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Bank-Parameters-IO

Attribute	Description
Name	Bank-Parameters-IO
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.10.CloseCGRejErrCdMaint

CloseCGRejErrCdMaint

2.10.1.CG-CloseCGRejErrCdMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Reject-Acc-Errcd-Full*
    - *CLEARING_TYPE*
    - *ERR_CODE*
    - *ERR_CODE_DESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Reject-Acc-Errcd-Full

Attribute	Description
Name	Reject-Acc-Errcd-Full
Datatype	
Description	

TOP

CLEARING_TYPE

Attribute	Description
Name	CLEARING_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / IW,IC,OC,

TOP

ERR_CODE

Attribute	Description
Name	ERR_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

ERR_CODE_DESC

Attribute	Description
Name	ERR_CODE_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description

Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Reject-Acc-Errcd-IO
CLEARING_TYPE
ERR_CODE
MAKER
MAKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Reject-Acc-Errcd-IO

Attribute	Description
Name	Reject-Acc-Errcd-IO
Datatype	
Description	

TOP

CLEARING_TYPE

Attribute	Description
Name	CLEARING_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / IW,IC,OC,

TOP

ERR_CODE

Attribute	Description
Name	ERR_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.10.3.CG-CloseCGRejErrCdMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Reject-Acc-Errcd-Full*
    - *CLEARING_TYPE*
    - *ERR_CODE*
    - *ERR_CODE_DESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Reject-Acc-Errcd-Full

Attribute	Description

Name	Reject-Acc-Errcd-Full
Datatype	
Description	

TOP

CLEARING_TYPE

Attribute	Description
Name	CLEARING_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / IW,IC,OC,

TOP

ERR_CODE

Attribute	Description
Name	ERR_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

ERR_CODE_DESC

Attribute	Description
Name	ERR_CODE_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description

Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Reject-Acc-Errcd-PK*
      - *CLEARING_TYPE*
      - *ERR_CODE*
    - *Reject-Acc-Errcd-IO*
      - *CLEARING_TYPE*
      - *ERR_CODE*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Reject-Acc-Errcd-PK

Attribute	Description
Name	Reject-Acc-Errcd-PK
Datatype	
Description	

TOP

CLEARING_TYPE

Attribute	Description	
Name	CLEARING_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

ERR_CODE

Attribute	Description	
Name	ERR_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

Reject-Acc-Errcd-IO

Attribute	Description
Name	Reject-Acc-Errcd-IO
Datatype	
Description	

TOP

CLEARING_TYPE

Attribute	Description	
Name	CLEARING_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

ORACLE

Restrictions	Restrictions	Description
	maxLength	2

TOP

ERR_CODE

Attribute	Description	
Name	ERR_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.11.CloseClgServicePoint

CloseClgServicePoint

2.11.1.CG-CloseClgServicePoint-Req-Full-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Clg-Service-Point-Full
DRAWEE_BANK
CITY
CLEARING_CITY
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Clg-Service-Point-Full

Attribute	Description
Name	Clg-Service-Point-Full
Datatype	
Description	

TOP

DRAWEE_BANK

Attribute	Description
Name	DRAWEE_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CITY

Attribute	Description
Name	CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

CLEARING_CITY

Attribute	Description
Name	CLEARING_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description

ORACLE

Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Clg-Service-Point-IO
DRAWEE_BANK
CITY
MAKER
MAKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Clg-Service-Point-IO

Attribute	Description
Name	Clg-Service-Point-IO
Datatype	
Description	

TOP

DRAWEE_BANK

Attribute	Description
Name	DRAWEE_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CITY

Attribute	Description
Name	CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.11.3.CG-CloseClgServicePoint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clg-Service-Point-Full*
    - *DRAWEE_BANK*
    - *CITY*
    - *CLEARING_CITY*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Clg-Service-Point-Full

Attribute	Description

Name	Clg-Service-Point-Full
Datatype	
Description	

TOP

DRAWEE_BANK

Attribute	Description
Name	DRAWEE_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CITY

Attribute	Description
Name	CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

CLEARING_CITY

Attribute	Description
Name	CLEARING_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**

Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Clg-Service-Point-PK*
      - *DRAWEE_BANK*
      - *CITY*
    - *Clg-Service-Point-IO*
      - *DRAWEE_BANK*
      - *CITY*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Clg-Service-Point-PK

Attribute	Description
Name	Clg-Service-Point-PK
Datatype	
Description	

TOP

DRAWEE_BANK

Attribute	Description	
Name	DRAWEE_BANK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CITY

Attribute	Description	
Name	CITY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

Clg-Service-Point-IO

Attribute	Description
Name	Clg-Service-Point-IO
Datatype	
Description	

TOP

DRAWEE_BANK

Attribute	Description	
Name	DRAWEE_BANK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	9

TOP

CITY

Attribute	Description	
Name	CITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	5

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.12.CloseDocException

CloseDocException

2.12.1.CG-CloseDocException-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Doc-Exception-Full*
    - *ACCOUNT_NO*
    - *EXECUTIVE*
    - *MODIFICATION_DATE*
    - *BRANCH_CODE*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Doc-Excep-Det*
      - *DOCUMENT_TYPE*
      - *EXCEPTION_ALLOWED*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

ORACLE

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Doc-Exception-Full

Attribute	Description

Name	Doc-Exception-Full
Datatype	
Description	

TOP

ACCOUNT_NO

Attribute	Description
Name	ACCOUNT_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EXECUTIVE

Attribute	Description
Name	EXECUTIVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MODIFICATION_DATE

Attribute	Description
Name	MODIFICATION_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description

Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Doc-Excep-Det

Attribute	**Description**
Name	Doc-Excep-Det
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOCUMENT_TYPE

Attribute	**Description**
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

ORACLE

TOP

EXCEPTION_ALLOWED

Attribute	Description
Name	EXCEPTION_ALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Doc-Exception-IO
ACCOUNT_NO
BRANCH_CODE
MAKER
MAKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Doc-Exception-IO

Attribute	Description
Name	Doc-Exception-IO
Datatype	
Description	

TOP

ACCOUNT_NO

Attribute	Description
Name	ACCOUNT_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.12.3.CG-CloseDocException-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Doc-Exception-Full*
    - *ACCOUNT_NO*
    - *EXECUTIVE*
    - *MODIFICATION_DATE*
    - *BRANCH_CODE*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Doc-Excep-Det*
      - *DOCUMENT_TYPE*
      - *EXCEPTION_ALLOWED*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Doc-Exception-Full

Attribute	Description
Name	Doc-Exception-Full
Datatype	
Description	

TOP

ACCOUNT_NO

Attribute	Description	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

EXECUTIVE

Attribute	Description	
Name	EXECUTIVE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MODIFICATION_DATE

Attribute	Description	
Name	MODIFICATION_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Doc-Excep-Det

Attribute	Description
Name	Doc-Excep-Det
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXCEPTION_ALLOWED

Attribute	**Description**
Name	EXCEPTION_ALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC

Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Doc-Exception-PK*
      - *ACCOUNT_NO*
      - *BRANCH_CODE*
    - *Doc-Exception-IO*
      - *ACCOUNT_NO*
      - *BRANCH_CODE*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Doc-Exception-PK

Attribute	Description
Name	Doc-Exception-PK
Datatype	
Description	

TOP

ACCOUNT_NO

Attribute	Description	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Doc-Exception-IO

Attribute	Description
Name	Doc-Exception-IO
Datatype	
Description	

TOP

ACCOUNT_NO

Attribute	Description	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

ORACLE

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.13.CloseDocType

CloseDocType

2.13.1.CG-CloseDocType-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Document-Type-Full*
    - *INSTRUMENT_TYPE*
    - *DOCUMENT_TYPE*
    - *DESCRIPTION*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Document-Type-Full

Attribute	Description
Name	Document-Type-Full
Datatype	
Description	

TOP

INSTRUMENT_TYPE

Attribute	Description
Name	INSTRUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description

Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

2.13.2.CG-CloseDocType-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Document-Type-IO*
    - *DOCUMENT_TYPE*
    - *MAKER*
    - *MAKERSTAMP*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Document-Type-IO

Attribute	Description
Name	Document-Type-IO
Datatype	
Description	

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.13.3.CG-CloseDocType-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Document-Type-Full*
    - *INSTRUMENT_TYPE*
    - *DOCUMENT_TYPE*
    - *DESCRIPTION*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Document-Type-Full

Attribute	Description

Name	Document-Type-Full
Datatype	
Description	

TOP

INSTRUMENT_TYPE

Attribute	Description
Name	INSTRUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT

ORACLE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**

Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Document-Type-PK*
      - *DOCUMENT_TYPE*
    - *Document-Type-IO*
      - *DOCUMENT_TYPE*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Document-Type-PK

Attribute	Description
Name	Document-Type-PK
Datatype	
Description	

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Document-Type-IO

Attribute	Description
Name	Document-Type-IO
Datatype	
Description	

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

ORACLE

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.14.CloseSecCode

CloseSecCode

2.14.1.CG-CloseSecCode-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Sectors-Full*
    - *SECTOR_CODE*
    - *SECTOR_DESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttms-Sectors-Full

Attribute	Description
Name	Sttms-Sectors-Full
Datatype	
Description	

TOP

SECTOR_CODE

Attribute	Description
Name	SECTOR_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECTOR_DESC

Attribute	Description
Name	SECTOR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs = unbounded; minOccurs = 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength = 105; minLength = 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: maxLength = 255; minLength = 0

TOP

2.14.2.CG-CloseSecCode-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Sectors-IO*
    - *SECTOR_CODE*
    - *MAKER*
    - *MAKERSTAMP*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttms-Sectors-IO

Attribute	Description
Name	Sttms-Sectors-IO
Datatype	
Description	

TOP

SECTOR_CODE

Attribute	Description
Name	SECTOR_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.14.3.CG-CloseSecCode-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Sectors-Full*
    - *SECTOR_CODE*
    - *SECTOR_DESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**

Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttms-Sectors-Full

Attribute	Description

Name	Sttms-Sectors-Full
Datatype	
Description	

TOP

SECTOR_CODE

Attribute	Description
Name	SECTOR_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECTOR_DESC

Attribute	Description
Name	SECTOR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttms-Sectors-PK*
      - *SECTOR_CODE*
    - *Sttms-Sectors-IO*
      - *SECTOR_CODE*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttms-Sectors-PK

Attribute	Description
Name	Sttms-Sectors-PK
Datatype	
Description	

TOP

SECTOR_CODE

Attribute	Description	
Name	SECTOR_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Sttms-Sectors-IO

Attribute	Description
Name	Sttms-Sectors-IO
Datatype	
Description	

TOP

SECTOR_CODE

Attribute	Description	
Name	SECTOR_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.15.CreateCGProductMaint

CreateCGProductMaint

2.15.1.CG-CreateCGProductMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bank-Parameters-Full*
    - *BANK_CODE*
    - *INTERNAL_PRODUCT*
    - *PROT_INWARD_PROD*
    - *PROT_INTERNAL_PROD*
    - *NON_LOCAL_PROD*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Bank-Product-Det-A*
      - *PRODUCT_CODE*
      - *DOCUMENT_TYPE*

LOCAL_CLEARING

VARIOUS_PMNT_INDICATOR

OW_RET_PROD

CLG_SERVICE_PRODUCT

MEMO_PRODUCT

DRAWER_BANK_EXPENSE_ACC

Bank-Product-Det-B

PRODUCT_CODE

DOCUMENT_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Bank-Parameters-Full

Attribute	Description
Name	Bank-Parameters-Full
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

INTERNAL_PRODUCT

Attribute	Description	
Name	INTERNAL_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PROT_INWARD_PROD

Attribute	Description	
Name	PROT_INWARD_PROD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PROT_INTERNAL_PROD

Attribute	Description
Name	PROT_INTERNAL_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

NON_LOCAL_PROD

Attribute	Description
Name	NON_LOCAL_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Bank-Product-Det-A

Attribute	Description	
Name	Bank-Product-Det-A	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRODUCT_CODE

Attribute	Description	
Name	PRODUCT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LOCAL_CLEARING

Attribute	Description	
Name	LOCAL_CLEARING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VARIOUS_PMNT_INDICATOR

Attribute	Description
Name	VARIOUS_PMNT_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / V,N,G,A,O

TOP

OW_RET_PROD

Attribute	Description
Name	OW_RET_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLG_SERVICE_PRODUCT

Attribute	Description
Name	CLG_SERVICE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MEMO_PRODUCT

Attribute	Description
Name	MEMO_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DRAWER_BANK_EXPENSE_ACC

Attribute	Description
Name	DRAWER_BANK_EXPENSE_ACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Bank-Product-Det-B

Attribute	Description
Name	Bank-Product-Det-B
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRODUCT_CODE

Attribute	Description
Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bank-Parameters-IO*
    - *BANK_CODE*
    - *INTERNAL_PRODUCT*
    - *PROT_INWARD_PROD*
    - *PROT_INTERNAL_PROD*
    - *NON_LOCAL_PROD*
    - *Bank-Product-Det-A*
      - *PRODUCT_CODE*
      - *DOCUMENT_TYPE*
      - *LOCAL_CLEARING*
      - *VARIOUS_PMNT_INDICATOR*
      - *OW_RET_PROD*
      - *CLG_SERVICE_PRODUCT*
      - *MEMO_PRODUCT*
      - *DRAWER_BANK_EXPENSE_ACC*
    - *Bank-Product-Det-B*
      - *PRODUCT_CODE*
      - *DOCUMENT_TYPE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Bank-Parameters-IO

Attribute	Description

Name	Bank-Parameters-IO
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description
Name	BANK_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

INTERNAL_PRODUCT

Attribute	Description
Name	INTERNAL_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PROT_INWARD_PROD

Attribute	Description
Name	PROT_INWARD_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PROT_INTERNAL_PROD

Attribute	Description
Name	PROT_INTERNAL_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

NON_LOCAL_PROD

Attribute	Description
Name	NON_LOCAL_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Bank-Product-Det-A

Attribute	Description
Name	Bank-Product-Det-A
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRODUCT_CODE

Attribute	Description
Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LOCAL_CLEARING

Attribute	Description

Name	LOCAL_CLEARING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VARIOUS_PMNT_INDICATOR

Attribute	**Description**
Name	VARIOUS_PMNT_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / V,N,G,A,O

TOP

OW_RET_PROD

Attribute	**Description**
Name	OW_RET_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLG_SERVICE_PRODUCT

Attribute	**Description**
Name	CLG_SERVICE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MEMO_PRODUCT

Attribute	**Description**
Name	MEMO_PRODUCT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DRAWER_BANK_EXPENSE_ACC

Attribute	Description
Name	DRAWER_BANK_EXPENSE_ACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Bank-Product-Det-B

Attribute	Description
Name	Bank-Product-Det-B
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRODUCT_CODE

Attribute	Description
Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ORACLE

2.15.3.CG-CreateCGProductMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bank-Parameters-Full*
    - *BANK_CODE*
    - *INTERNAL_PRODUCT*
    - *PROT_INWARD_PROD*
    - *PROT_INTERNAL_PROD*
    - *NON_LOCAL_PROD*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Bank-Product-Det-A*
      - *PRODUCT_CODE*
      - *DOCUMENT_TYPE*
      - *LOCAL_CLEARING*
      - *VARIOUS_PMNT_INDICATOR*
      - *OW_RET_PROD*

CLG_SERVICE_PRODUCT

MEMO_PRODUCT

DRAWER_BANK_EXPENSE_ACC

Bank-Product-Det-B

PRODUCT_CODE

DOCUMENT_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength 12; pattern [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Bank-Parameters-Full

Attribute	Description
Name	Bank-Parameters-Full
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

INTERNAL_PRODUCT

Attribute	Description	
Name	INTERNAL_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PROT_INWARD_PROD

Attribute	Description
Name	PROT_INWARD_PROD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PROT_INTERNAL_PROD

Attribute	**Description**
Name	PROT_INTERNAL_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

NON_LOCAL_PROD

Attribute	**Description**
Name	NON_LOCAL_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Bank-Product-Det-A

Attribute	Description
Name	Bank-Product-Det-A
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRODUCT_CODE

Attribute	Description
Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LOCAL_CLEARING

Attribute	Description

Name	LOCAL_CLEARING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VARIOUS_PMNT_INDICATOR

Attribute	**Description**
Name	VARIOUS_PMNT_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / V,N,G,A,O

TOP

OW_RET_PROD

Attribute	**Description**
Name	OW_RET_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLG_SERVICE_PRODUCT

Attribute	**Description**
Name	CLG_SERVICE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MEMO_PRODUCT

Attribute	**Description**
Name	MEMO_PRODUCT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DRAWER_BANK_EXPENSE_ACC

Attribute	Description	
Name	DRAWER_BANK_EXPENSE_ACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Bank-Product-Det-B

Attribute	Description	
Name	Bank-Product-Det-B	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRODUCT_CODE

Attribute	Description	
Name	PRODUCT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.15.4.CG-CreateCGProductMaint-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bank-Parameters-PK*
      - *BANK_CODE*
    - *Bank-Parameters-IO*
      - *BANK_CODE*
      - *INTERNAL_PRODUCT*
      - *PROT_INWARD_PROD*
      - *PROT_INTERNAL_PROD*
      - *NON_LOCAL_PROD*
      - *Bank-Product-Det-A*
        - *PRODUCT_CODE*
        - *DOCUMENT_TYPE*
        - *LOCAL_CLEARING*
        - *VARIOUS_PMNT_INDICATOR*
        - *OW_RET_PROD*
        - *CLG_SERVICE_PRODUCT*
        - *MEMO_PRODUCT*
        - *DRAWER_BANK_EXPENSE_ACC*
      - *Bank-Product-Det-B*

PRODUCT_CODE

DOCUMENT_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String

Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bank-Parameters-PK

Attribute	Description
Name	Bank-Parameters-PK
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Bank-Parameters-IO

Attribute	Description
Name	Bank-Parameters-IO
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	4

TOP

INTERNAL_PRODUCT

Attribute	Description	
Name	INTERNAL_PRODUCT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

PROT_INWARD_PROD

Attribute	Description	
Name	PROT_INWARD_PROD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

PROT_INTERNAL_PROD

Attribute	Description	
Name	PROT_INTERNAL_PROD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

NON_LOCAL_PROD

Attribute	Description	
Name	NON_LOCAL_PROD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

Bank-Product-Det-A

Attribute	Description
Name	Bank-Product-Det-A
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRODUCT_CODE

Attribute	Description
Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LOCAL_CLEARING

Attribute	Description
Name	LOCAL_CLEARING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VARIOUS_PMNT_INDICATOR

Attribute	Description

Name	VARIOUS_PMNT_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / V,N,G,A,O

TOP

OW_RET_PROD

Attribute	**Description**
Name	OW_RET_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLG_SERVICE_PRODUCT

Attribute	**Description**
Name	CLG_SERVICE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MEMO_PRODUCT

Attribute	**Description**
Name	MEMO_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DRAWER_BANK_EXPENSE_ACC

Attribute	**Description**
Name	DRAWER_BANK_EXPENSE_ACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Bank-Product-Det-B

Attribute	Description	
Name	Bank-Product-Det-B	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRODUCT_CODE

Attribute	Description	
Name	PRODUCT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.16.CreateClgServicePoint

CreateClgServicePoint

2.16.1.CG-CreateClgServicePoint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clg-Service-Point-Full*
    - *DRAWEE_BANK*
    - *CITY*
    - *CLEARING_CITY*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Clg-Service-Point-Full

Attribute	Description
Name	Clg-Service-Point-Full
Datatype	
Description	

TOP

DRAWEE_BANK

Attribute	Description
Name	DRAWEE_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CITY

Attribute	Description
Name	CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

CLEARING_CITY

Attribute	Description
Name	CLEARING_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description

ORACLE

Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

2.16.2.CG-CreateClgServicePoint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clg-Service-Point-IO*
    - *DRAWEE_BANK*
    - *CITY*
    - *CLEARING_CITY*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Clg-Service-Point-IO

Attribute	Description
Name	Clg-Service-Point-IO
Datatype	
Description	

TOP

DRAWEE_BANK

Attribute	Description
Name	DRAWEE_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CITY

Attribute	Description

Name	CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

CLEARING_CITY

Attribute	**Description**
Name	CLEARING_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

2.16.3.CG-CreateClgServicePoint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clg-Service-Point-Full*
    - *DRAWEE_BANK*
    - *CITY*
    - *CLEARING_CITY*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Clg-Service-Point-Full

Attribute	Description

Name	Clg-Service-Point-Full
Datatype	
Description	

TOP

DRAWEE_BANK

Attribute	Description
Name	DRAWEE_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CITY

Attribute	Description
Name	CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

CLEARING_CITY

Attribute	Description
Name	CLEARING_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**

Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Clg-Service-Point-PK*
      - *DRAWEE_BANK*
      - *CITY*
    - *Clg-Service-Point-IO*
      - *DRAWEE_BANK*
      - *CITY*
      - *CLEARING_CITY*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Clg-Service-Point-PK

Attribute	Description
Name	Clg-Service-Point-PK
Datatype	
Description	

TOP

DRAWEE_BANK

Attribute	Description	
Name	DRAWEE_BANK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CITY

Attribute	Description	
Name	CITY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

Clg-Service-Point-IO

Attribute	Description
Name	Clg-Service-Point-IO
Datatype	
Description	

TOP

DRAWEE_BANK

Attribute	Description	
Name	DRAWEE_BANK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CITY

Attribute	Description
Name	CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

CLEARING_CITY

Attribute	Description
Name	CLEARING_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String

Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.17.CreateCollectionCheque

CreateCollectionCheque

2.17.1.CG-CreateCollectionCheque-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Master-Full*
    - *DEPOSITSLIP*
    - *TRN_BRANCH*
    - *REFERENCE_NO*
    - *BENE_DETAILS1*
    - *INSTRUMENT_CCY*
    - *INSTRUMENT_AMT*
    - *RECORD_STAT*
    - *AUTH_STAT*
    - *MAKER_ID*
    - *MAKER_DT_STAMP*
    - *CHECKER_ID*
    - *CHECKER_DT_STAMP*
    - *REMARKS*
    - *DEPOSITOR_NAME*
    - *BEN_ACCOUNT*

Coll-Dispatch-Details

INSTRUMENT_NO

INSTRUMENT_AMT

INSTRUMENT_DATE

DRAWEE_ACC_NO

DRAWEE_BANK

DRAWEE_BRANCH

DRAWEE_CITY

DEPOSIT_CITY

DOCUMENT_TYPE

COLLECTION_PRO_EXC

ROUTING_GL_EXC

CLEARING_CITY

CORRESPONDENT_BANK

CORRESPONDENT_BRANCH

COLLECTION_TYPE

TRN_REF_NO

DISPATCH_REF_NO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Clearing-Master-Full

Attribute	Description
Name	Clearing-Master-Full
Datatype	
Description	

TOP

DEPOSITSLIP

Attribute	Description	
Name	DEPOSITSLIP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TRN_BRANCH

Attribute	Description	
Name	TRN_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REFERENCE_NO

Attribute	Description

Name	REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BENE_DETAILS1

Attribute	**Description**
Name	BENE_DETAILS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRUMENT_CCY

Attribute	**Description**
Name	INSTRUMENT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTRUMENT_AMT

Attribute	**Description**
Name	INSTRUMENT_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

RECORD_STAT

Attribute	**Description**
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

AUTH_STAT

Attribute	Description	
Name	AUTH_STAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,U

TOP

MAKER_ID

Attribute	Description	
Name	MAKER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKER_DT_STAMP

Attribute	Description	
Name	MAKER_DT_STAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER_ID

Attribute	Description	
Name	CHECKER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DEPOSITOR_NAME

Attribute	Description
Name	DEPOSITOR_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BEN_ACCOUNT

Attribute	Description
Name	BEN_ACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Coll-Dispatch-Details

Attribute	Description
Name	Coll-Dispatch-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSTRUMENT_NO

Attribute	Description
Name	INSTRUMENT_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRUMENT_AMT

Attribute	Description
Name	INSTRUMENT_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRAWEE_ACC_NO

Attribute	Description
Name	DRAWEE_ACC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	16

TOP

DRAWEE_BANK

Attribute	Description
Name	DRAWEE_BANK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

DRAWEE_BRANCH

Attribute	Description
Name	DRAWEE_BRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

DRAWEE_CITY

Attribute	Description
Name	DRAWEE_CITY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 5

TOP

DEPOSIT_CITY

Attribute	Description
Name	DEPOSIT_CITY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 5

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

COLLECTION_PRO_EXC

Attribute	Description
Name	COLLECTION_PRO_EXC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ROUTING_GL_EXC

Attribute	Description
Name	ROUTING_GL_EXC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CLEARING_CITY

Attribute	Description
Name	CLEARING_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

CORRESPONDENT_BANK

Attribute	Description
Name	CORRESPONDENT_BANK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CORRESPONDENT_BRANCH

Attribute	Description
Name	CORRESPONDENT_BRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COLLECTION_TYPE

Attribute	Description
Name	COLLECTION_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: E,O

TOP

TRN_REF_NO

Attribute	Description
Name	TRN_REF_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

DISPATCH_REF_NO

Attribute	Description
Name	DISPATCH_REF_NO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 21

TOP

2.17.2.CG-CreateCollectionCheque-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Master-IO*
    - *DEPOSITSLIP*
    - *REFERENCE_NO*
    - *BENE_DETAILS1*
    - *INSTRUMENT_CCY*
    - *INSTRUMENT_AMT*
    - *RECORD_STAT*
    - *AUTH_STAT*
    - *MAKER_DT_STAMP*
    - *CHECKER_ID*
    - *CHECKER_DT_STAMP*
    - *REMARKS*
    - *DEPOSITOR_NAME*
    - *BEN_ACCOUNT*
    - *Coll-Dispatch-Details*
      - *INSTRUMENT_NO*
      - *INSTRUMENT_AMT*
      - *INSTRUMENT_DATE*
      - *DRAWEE_ACC_NO*

DRAWEE_BANK

DRAWEE_BRANCH

DRAWEE_CITY

DEPOSIT_CITY

DOCUMENT_TYPE

COLLECTION_PRO_EXC

ROUTING_GL_EXC

CORRESPONDENT_BRANCH

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Clearing-Master-IO

Attribute	Description
Name	Clearing-Master-IO
Datatype	
Description	

TOP

DEPOSITSLIP

Attribute	Description	
Name	DEPOSITSLIP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

REFERENCE_NO

Attribute	Description	
Name	REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BENE_DETAILS1

Attribute	Description	
Name	BENE_DETAILS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRUMENT_CCY

Attribute	Description
Name	INSTRUMENT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTRUMENT_AMT

Attribute	Description
Name	INSTRUMENT_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	**Description**
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	**Description**
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DEPOSITOR_NAME

Attribute	**Description**
Name	DEPOSITOR_NAME
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BEN_ACCOUNT

Attribute	**Description**
Name	BEN_ACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Coll-Dispatch-Details

Attribute	**Description**
Name	Coll-Dispatch-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSTRUMENT_NO

Attribute	**Description**
Name	INSTRUMENT_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRUMENT_AMT

Attribute	**Description**
Name	INSTRUMENT_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRAWEE_ACC_NO

Attribute	Description
Name	DRAWEE_ACC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DRAWEE_BANK

Attribute	Description
Name	DRAWEE_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DRAWEE_BRANCH

Attribute	Description
Name	DRAWEE_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DRAWEE_CITY

Attribute	Description
Name	DRAWEE_CITY
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

DEPOSIT_CITY

Attribute	**Description**
Name	DEPOSIT_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

DOCUMENT_TYPE

Attribute	**Description**
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COLLECTION_PRO_EXC

Attribute	**Description**
Name	COLLECTION_PRO_EXC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROUTING_GL_EXC

Attribute	**Description**
Name	ROUTING_GL_EXC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CORRESPONDENT_BRANCH

Attribute	**Description**
Name	CORRESPONDENT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

2.17.3.CG-CreateCollectionCheque-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Master-Full*
    - *DEPOSITSLIP*
    - *TRN_BRANCH*
    - *REFERENCE_NO*
    - *BENE_DETAILS1*
    - *INSTRUMENT_CCY*
    - *INSTRUMENT_AMT*
    - *RECORD_STAT*
    - *AUTH_STAT*
    - *MAKER_ID*
    - *MAKER_DT_STAMP*
    - *CHECKER_ID*
    - *CHECKER_DT_STAMP*
    - *REMARKS*
    - *DEPOSITOR_NAME*
    - *BEN_ACCOUNT*
    - *Coll-Dispatch-Details*
      - *INSTRUMENT_NO*
      - *INSTRUMENT_AMT*

INSTRUMENT_DATE

DRAWEE_ACC_NO

DRAWEE_BANK

DRAWEE_BRANCH

DRAWEE_CITY

DEPOSIT_CITY

DOCUMENT_TYPE

COLLECTION_PRO_EXC

ROUTING_GL_EXC

CLEARING_CITY

CORRESPONDENT_BANK

CORRESPONDENT_BRANCH

COLLECTION_TYPE

TRN_REF_NO

DISPATCH_REF_NO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Clearing-Master-Full

Attribute	Description
Name	Clearing-Master-Full
Datatype	
Description	

TOP

DEPOSITSLIP

Attribute	Description	
Name	DEPOSITSLIP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TRN_BRANCH

Attribute	Description
Name	TRN_BRANCH
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REFERENCE_NO

Attribute	Description	
Name	REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BENE_DETAILS1

Attribute	Description	
Name	BENE_DETAILS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRUMENT_CCY

Attribute	Description	
Name	INSTRUMENT_CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INSTRUMENT_AMT

Attribute	Description	
Name	INSTRUMENT_AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

DEPOSITOR_NAME

Attribute	Description
Name	DEPOSITOR_NAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 35

TOP

BEN_ACCOUNT

Attribute	Description
Name	BEN_ACCOUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Coll-Dispatch-Details

Attribute	**Description**
Name	Coll-Dispatch-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSTRUMENT_NO

Attribute	**Description**
Name	INSTRUMENT_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRUMENT_AMT

Attribute	**Description**
Name	INSTRUMENT_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INSTRUMENT_DATE

Attribute	**Description**
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRAWEE_ACC_NO

Attribute	Description
Name	DRAWEE_ACC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DRAWEE_BANK

Attribute	Description
Name	DRAWEE_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DRAWEE_BRANCH

Attribute	Description
Name	DRAWEE_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DRAWEE_CITY

Attribute	Description
Name	DRAWEE_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

DEPOSIT_CITY

Attribute	Description

Name	DEPOSIT_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

DOCUMENT_TYPE

Attribute	**Description**
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

COLLECTION_PRO_EXC

Attribute	**Description**
Name	COLLECTION_PRO_EXC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ROUTING_GL_EXC

Attribute	**Description**
Name	ROUTING_GL_EXC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CLEARING_CITY

Attribute	**Description**
Name	CLEARING_CITY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

CORRESPONDENT_BANK

Attribute	Description	
Name	CORRESPONDENT_BANK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CORRESPONDENT_BRANCH

Attribute	Description	
Name	CORRESPONDENT_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COLLECTION_TYPE

Attribute	Description	
Name	COLLECTION_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,O

TOP

TRN_REF_NO

Attribute	Description	
Name	TRN_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DISPATCH_REF_NO

Attribute	**Description**
Name	DISPATCH_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 21

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.17.4.CG-CreateCollectionCheque-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Clearing-Master-PK*
      - *REFERENCE_NO*
    - *Clearing-Master-IO*
      - *DEPOSITSLIP*
      - *REFERENCE_NO*
      - *BENE_DETAILS1*
      - *INSTRUMENT_CCY*
      - *INSTRUMENT_AMT*
      - *RECORD_STAT*
      - *AUTH_STAT*
      - *MAKER_DT_STAMP*
      - *CHECKER_ID*
      - *CHECKER_DT_STAMP*
      - *REMARKS*
      - *DEPOSITOR_NAME*
      - *BEN_ACCOUNT*
      - *Coll-Dispatch-Details*
        - *INSTRUMENT_NO*

INSTRUMENT_AMT

INSTRUMENT_DATE

DRAWEE_ACC_NO

DRAWEE_BANK

DRAWEE_BRANCH

DRAWEE_CITY

DEPOSIT_CITY

DOCUMENT_TYPE

COLLECTION_PRO_EXC

ROUTING_GL_EXC

CORRESPONDENT_BRANCH

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Clearing-Master-PK

Attribute	Description
Name	Clearing-Master-PK
Datatype	
Description	

TOP

REFERENCE_NO

Attribute	Description	
Name	REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Clearing-Master-IO

Attribute	Description
Name	Clearing-Master-IO
Datatype	
Description	

TOP

DEPOSITSLIP

Attribute	Description
Name	DEPOSITSLIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BENE_DETAILS1

Attribute	Description
Name	BENE_DETAILS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRUMENT_CCY

Attribute	Description
Name	INSTRUMENT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTRUMENT_AMT

Attribute	Description
Name	INSTRUMENT_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKER_DT_STAMP

Attribute	Description	
Name	CHECKER_DT_STAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DEPOSITOR_NAME

Attribute	Description	
Name	DEPOSITOR_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BEN_ACCOUNT

Attribute	Description	
Name	BEN_ACCOUNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	20

TOP

Coll-Dispatch-Details

Attribute	Description	
Name	Coll-Dispatch-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INSTRUMENT_NO

Attribute	Description	
Name	INSTRUMENT_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

INSTRUMENT_AMT

Attribute	Description	
Name	INSTRUMENT_AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

INSTRUMENT_DATE

Attribute	Description	
Name	INSTRUMENT_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DRAWEE_ACC_NO

Attribute	Description
Name	DRAWEE_ACC_NO
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRAWEE_BANK

Attribute	**Description**
Name	DRAWEE_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DRAWEE_BRANCH

Attribute	**Description**
Name	DRAWEE_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DRAWEE_CITY

Attribute	**Description**
Name	DRAWEE_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

DEPOSIT_CITY

Attribute	**Description**
Name	DEPOSIT_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	5

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

COLLECTION_PRO_EXC

Attribute	Description
Name	COLLECTION_PRO_EXC
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: Y,N

TOP

ROUTING_GL_EXC

Attribute	Description
Name	ROUTING_GL_EXC
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 20

TOP

CORRESPONDENT_BRANCH

Attribute	Description
Name	CORRESPONDENT_BRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.18.CreateDocException

CreateDocException

2.18.1.CG-CreateDocException-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Doc-Exception-Full*
    - *ACCOUNT_NO*
    - *EXECUTIVE*
    - *MODIFICATION_DATE*
    - *BRANCH_CODE*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Doc-Excep-Det*
      - *DOCUMENT_TYPE*
      - *EXCEPTION_ALLOWED*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Doc-Exception-Full

Attribute	Description

Name	Doc-Exception-Full
Datatype	
Description	

TOP

ACCOUNT_NO

Attribute	Description
Name	ACCOUNT_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EXECUTIVE

Attribute	Description
Name	EXECUTIVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MODIFICATION_DATE

Attribute	Description
Name	MODIFICATION_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description

Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Doc-Excep-Det

Attribute	Description
Name	Doc-Excep-Det
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EXCEPTION_ALLOWED

Attribute	Description
Name	EXCEPTION_ALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Doc-Exception-IO
ACCOUNT_NO
EXECUTIVE
MODIFICATION_DATE
BRANCH_CODE
Doc-Excep-Det
DOCUMENT_TYPE
EXCEPTION_ALLOWED

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0

Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Doc-Exception-IO

Attribute	Description
Name	Doc-Exception-IO
Datatype	
Description	

TOP

ACCOUNT_NO

Attribute	Description
Name	ACCOUNT_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	20

TOP

EXECUTIVE

Attribute	Description
Name	EXECUTIVE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 20

TOP

MODIFICATION_DATE

Attribute	Description
Name	MODIFICATION_DATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

Doc-Excep-Det

Attribute	Description
Name	Doc-Excep-Det
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

DOCUMENT_TYPE

Attribute	Description

Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXCEPTION_ALLOWED

Attribute	**Description**
Name	EXCEPTION_ALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

2.18.3.CG-CreateDocException-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Doc-Exception-Full*
    - *ACCOUNT_NO*
    - *EXECUTIVE*
    - *MODIFICATION_DATE*
    - *BRANCH_CODE*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Doc-Excep-Det*
      - *DOCUMENT_TYPE*
      - *EXCEPTION_ALLOWED*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Doc-Exception-Full

Attribute	Description
Name	Doc-Exception-Full
Datatype	
Description	

TOP

ACCOUNT_NO

Attribute	Description	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

EXECUTIVE

Attribute	Description	
Name	EXECUTIVE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MODIFICATION_DATE

Attribute	Description	
Name	MODIFICATION_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	3

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Doc-Excep-Det

Attribute	Description
Name	Doc-Excep-Det
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXCEPTION_ALLOWED

Attribute	**Description**
Name	EXCEPTION_ALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC

Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.18.4.CG-CreateDocException-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Doc-Exception-PK*
      - *ACCOUNT_NO*
      - *BRANCH_CODE*
    - *Doc-Exception-IO*
      - *ACCOUNT_NO*
      - *EXECUTIVE*
      - *MODIFICATION_DATE*
      - *BRANCH_CODE*
      - *Doc-Excep-Det*
        - *DOCUMENT_TYPE*
        - *EXCEPTION_ALLOWED*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description

Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Doc-Exception-PK

Attribute	Description
Name	Doc-Exception-PK
Datatype	
Description	

TOP

ACCOUNT_NO

Attribute	Description	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Doc-Exception-IO

Attribute	Description
Name	Doc-Exception-IO
Datatype	
Description	

TOP

ACCOUNT_NO

Attribute	Description	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

ORACLE

Restrictions	Restrictions	Description
	maxLength	20

TOP

EXECUTIVE

Attribute	Description
Name	EXECUTIVE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 20

TOP

MODIFICATION_DATE

Attribute	Description
Name	MODIFICATION_DATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

Doc-Excep-Det

Attribute	Description
Name	Doc-Excep-Det
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

DOCUMENT_TYPE

Attribute	Description

Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EXCEPTION_ALLOWED

Attribute	**Description**
Name	EXCEPTION_ALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.19.CreateDocType

CreateDocType

2.19.1.CG-CreateDocType-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Document-Type-Full*
    - *INSTRUMENT_TYPE*
    - *DOCUMENT_TYPE*
    - *DESCRIPTION*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Document-Type-Full

Attribute	Description
Name	Document-Type-Full
Datatype	
Description	

TOP

INSTRUMENT_TYPE

Attribute	Description
Name	INSTRUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description

Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

2.19.2.CG-CreateDocType-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Document-Type-IO*
    - *INSTRUMENT_TYPE*
    - *DOCUMENT_TYPE*
    - *DESCRIPTION*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Document-Type-IO

Attribute	Description
Name	Document-Type-IO
Datatype	
Description	

TOP

INSTRUMENT_TYPE

Attribute	Description
Name	INSTRUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,D

TOP

DOCUMENT_TYPE

Attribute	Description

Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

2.19.3.CG-CreateDocType-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Document-Type-Full*
    - *INSTRUMENT_TYPE*
    - *DOCUMENT_TYPE*
    - *DESCRIPTION*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Document-Type-Full

Attribute	Description

Name	Document-Type-Full
Datatype	
Description	

TOP

INSTRUMENT_TYPE

Attribute	Description
Name	INSTRUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**

Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Document-Type-PK*
      - *DOCUMENT_TYPE*
    - *Document-Type-IO*
      - *INSTRUMENT_TYPE*
      - *DOCUMENT_TYPE*
      - *DESCRIPTION*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description

Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Document-Type-PK

Attribute	Description
Name	Document-Type-PK
Datatype	
Description	

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Document-Type-IO

Attribute	Description
Name	Document-Type-IO
Datatype	
Description	

TOP

INSTRUMENT_TYPE

Attribute	Description	
Name	INSTRUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.20.CreateSecCode

CreateSecCode

2.20.1.CG-CreateSecCode-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Sectors-Full*
    - *SECTOR_CODE*
    - *SECTOR_DESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 0 nillable: true
Restrictions	Restrictions: Description pattern: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 0 nillable: true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description pattern: [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description pattern: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttms-Sectors-Full

Attribute	Description
Name	Sttms-Sectors-Full
Datatype	
Description	

TOP

SECTOR_CODE

Attribute	Description
Name	SECTOR_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECTOR_DESC

Attribute	Description
Name	SECTOR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Sttms-Sectors-IO
SECTOR_CODE
SECTOR_DESC
UDFDETAILS
FLDNAM
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttms-Sectors-IO

Attribute	Description
Name	Sttms-Sectors-IO
Datatype	
Description	

TOP

SECTOR_CODE

Attribute	Description
Name	SECTOR_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SECTOR_DESC

Attribute	Description
Name	SECTOR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.20.3.CG-CreateSecCode-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Sectors-Full*
    - *SECTOR_CODE*
    - *SECTOR_DESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**

Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttms-Sectors-Full

Attribute	Description

Name	Sttms-Sectors-Full
Datatype	
Description	

TOP

SECTOR_CODE

Attribute	Description
Name	SECTOR_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECTOR_DESC

Attribute	Description
Name	SECTOR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttms-Sectors-PK*
      - *SECTOR_CODE*
    - *Sttms-Sectors-IO*
      - *SECTOR_CODE*
      - *SECTOR_DESC*
      - *UDFDETAILS*
        - *FLDNAM*
        - *FLDVAL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Sttms-Sectors-PK

Attribute	Description
Name	Sttms-Sectors-PK
Datatype	
Description	

TOP

SECTOR_CODE

Attribute	Description	
Name	SECTOR_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Sttms-Sectors-IO

Attribute	Description
Name	Sttms-Sectors-IO
Datatype	
Description	

TOP

SECTOR_CODE

Attribute	Description	
Name	SECTOR_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SECTOR_DESC

Attribute	Description	
Name	SECTOR_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	Restrictions: maxLength, Description: 105 Restrictions: minLength, Description: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 255 Restrictions: minLength, Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.21.DeleteCGProductMaint

DeleteCGProductMaint

2.21.1.CG-DeleteCGProductMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bank-Parameters-Full*
    - *BANK_CODE*
    - *INTERNAL_PRODUCT*
    - *PROT_INWARD_PROD*
    - *PROT_INTERNAL_PROD*
    - *NON_LOCAL_PROD*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Bank-Product-Det-A*
      - *PRODUCT_CODE*
      - *DOCUMENT_TYPE*

LOCAL_CLEARING

VARIOUS_PMNT_INDICATOR

OW_RET_PROD

CLG_SERVICE_PRODUCT

MEMO_PRODUCT

DRAWER_BANK_EXPENSE_ACC

Bank-Product-Det-B

PRODUCT_CODE

DOCUMENT_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Bank-Parameters-Full

Attribute	Description
Name	Bank-Parameters-Full
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

INTERNAL_PRODUCT

Attribute	Description	
Name	INTERNAL_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PROT_INWARD_PROD

Attribute	Description	
Name	PROT_INWARD_PROD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PROT_INTERNAL_PROD

Attribute	Description
Name	PROT_INTERNAL_PROD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

NON_LOCAL_PROD

Attribute	Description
Name	NON_LOCAL_PROD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Bank-Product-Det-A

Attribute	Description	
Name	Bank-Product-Det-A	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRODUCT_CODE

Attribute	Description	
Name	PRODUCT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LOCAL_CLEARING

Attribute	Description	
Name	LOCAL_CLEARING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

ORACLE

TOP

VARIOUS_PMNT_INDICATOR

Attribute	Description
Name	VARIOUS_PMNT_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / V,N,G,A,O

TOP

OW_RET_PROD

Attribute	Description
Name	OW_RET_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLG_SERVICE_PRODUCT

Attribute	Description
Name	CLG_SERVICE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MEMO_PRODUCT

Attribute	Description
Name	MEMO_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DRAWER_BANK_EXPENSE_ACC

Attribute	Description
Name	DRAWER_BANK_EXPENSE_ACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Bank-Product-Det-B

Attribute	Description
Name	Bank-Product-Det-B
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRODUCT_CODE

Attribute	Description
Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

2.21.2.CG-DeleteCGProductMaint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bank-Parameters-IO*
    - *BANK_CODE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration — Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 12 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Bank-Parameters-IO

Attribute	Description
Name	Bank-Parameters-IO
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

2.21.3.CG-DeleteCGProductMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bank-Parameters-Full*
    - *BANK_CODE*
    - *INTERNAL_PRODUCT*
    - *PROT_INWARD_PROD*
    - *PROT_INTERNAL_PROD*
    - *NON_LOCAL_PROD*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Bank-Product-Det-A*
      - *PRODUCT_CODE*
      - *DOCUMENT_TYPE*
      - *LOCAL_CLEARING*
      - *VARIOUS_PMNT_INDICATOR*
      - *OW_RET_PROD*

CLG_SERVICE_PRODUCT

MEMO_PRODUCT

DRAWER_BANK_EXPENSE_ACC

Bank-Product-Det-B

PRODUCT_CODE

DOCUMENT_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength 12; pattern [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Bank-Parameters-Full

Attribute	Description
Name	Bank-Parameters-Full
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

INTERNAL_PRODUCT

Attribute	Description	
Name	INTERNAL_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PROT_INWARD_PROD

Attribute	Description
Name	PROT_INWARD_PROD

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PROT_INTERNAL_PROD

Attribute	**Description**
Name	PROT_INTERNAL_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

NON_LOCAL_PROD

Attribute	**Description**
Name	NON_LOCAL_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Bank-Product-Det-A

Attribute	Description
Name	Bank-Product-Det-A
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRODUCT_CODE

Attribute	Description
Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LOCAL_CLEARING

Attribute	Description

Name	LOCAL_CLEARING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VARIOUS_PMNT_INDICATOR

Attribute	**Description**
Name	VARIOUS_PMNT_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / V,N,G,A,O

TOP

OW_RET_PROD

Attribute	**Description**
Name	OW_RET_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLG_SERVICE_PRODUCT

Attribute	**Description**
Name	CLG_SERVICE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MEMO_PRODUCT

Attribute	**Description**
Name	MEMO_PRODUCT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DRAWER_BANK_EXPENSE_ACC

Attribute	Description	
Name	DRAWER_BANK_EXPENSE_ACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Bank-Product-Det-B

Attribute	Description	
Name	Bank-Product-Det-B	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRODUCT_CODE

Attribute	Description	
Name	PRODUCT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bank-Parameters-PK*
      - *BANK_CODE*
    - *Bank-Parameters-IO*
      - *BANK_CODE*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bank-Parameters-PK

Attribute	Description
Name	Bank-Parameters-PK
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Bank-Parameters-IO

Attribute	Description
Name	Bank-Parameters-IO
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.22.DeleteCollectionCheque

DeleteCollectionCheque

2.22.1.CG-DeleteCollectionCheque-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Master-Full*
    - *DEPOSITSLIP*
    - *TRN_BRANCH*
    - *REFERENCE_NO*
    - *BENE_DETAILS1*
    - *INSTRUMENT_CCY*
    - *INSTRUMENT_AMT*
    - *RECORD_STAT*
    - *AUTH_STAT*
    - *MAKER_ID*
    - *MAKER_DT_STAMP*
    - *CHECKER_ID*
    - *CHECKER_DT_STAMP*
    - *REMARKS*
    - *DEPOSITOR_NAME*
    - *BEN_ACCOUNT*

Coll-Dispatch-Details

INSTRUMENT_NO

INSTRUMENT_AMT

INSTRUMENT_DATE

DRAWEE_ACC_NO

DRAWEE_BANK

DRAWEE_BRANCH

DRAWEE_CITY

DEPOSIT_CITY

DOCUMENT_TYPE

COLLECTION_PRO_EXC

ROUTING_GL_EXC

CLEARING_CITY

CORRESPONDENT_BANK

CORRESPONDENT_BRANCH

COLLECTION_TYPE

TRN_REF_NO

DISPATCH_REF_NO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Clearing-Master-Full

Attribute	Description
Name	Clearing-Master-Full
Datatype	
Description	

TOP

DEPOSITSLIP

Attribute	Description	
Name	DEPOSITSLIP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TRN_BRANCH

Attribute	Description	
Name	TRN_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REFERENCE_NO

Attribute	Description

Name	REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BENE_DETAILS1

Attribute	**Description**
Name	BENE_DETAILS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRUMENT_CCY

Attribute	**Description**
Name	INSTRUMENT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTRUMENT_AMT

Attribute	**Description**
Name	INSTRUMENT_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

RECORD_STAT

Attribute	**Description**
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DEPOSITOR_NAME

Attribute	Description
Name	DEPOSITOR_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BEN_ACCOUNT

Attribute	Description
Name	BEN_ACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Coll-Dispatch-Details

Attribute	Description
Name	Coll-Dispatch-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSTRUMENT_NO

Attribute	Description
Name	INSTRUMENT_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRUMENT_AMT

Attribute	Description
Name	INSTRUMENT_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRAWEE_ACC_NO

Attribute	Description
Name	DRAWEE_ACC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	16

TOP

DRAWEE_BANK

Attribute	Description
Name	DRAWEE_BANK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

DRAWEE_BRANCH

Attribute	Description
Name	DRAWEE_BRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

DRAWEE_CITY

Attribute	Description
Name	DRAWEE_CITY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 5

TOP

DEPOSIT_CITY

Attribute	Description
Name	DEPOSIT_CITY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 5

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

COLLECTION_PRO_EXC

Attribute	Description
Name	COLLECTION_PRO_EXC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ROUTING_GL_EXC

Attribute	Description
Name	ROUTING_GL_EXC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CLEARING_CITY

Attribute	Description
Name	CLEARING_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

CORRESPONDENT_BANK

Attribute	Description
Name	CORRESPONDENT_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CORRESPONDENT_BRANCH

Attribute	Description
Name	CORRESPONDENT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COLLECTION_TYPE

Attribute	Description
Name	COLLECTION_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,O

TOP

TRN_REF_NO

Attribute	Description
Name	TRN_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DISPATCH_REF_NO

Attribute	Description
Name	DISPATCH_REF_NO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 21

TOP

2.22.2.CG-DeleteCollectionCheque-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Master-IO*
    - *REFERENCE_NO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Clearing-Master-IO

Attribute	Description
Name	Clearing-Master-IO
Datatype	
Description	

TOP

REFERENCE_NO

Attribute	Description	
Name	REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.22.3.CG-DeleteCollectionCheque-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Master-Full*
    - *DEPOSITSLIP*
    - *TRN_BRANCH*
    - *REFERENCE_NO*
    - *BENE_DETAILS1*
    - *INSTRUMENT_CCY*
    - *INSTRUMENT_AMT*
    - *RECORD_STAT*
    - *AUTH_STAT*
    - *MAKER_ID*
    - *MAKER_DT_STAMP*
    - *CHECKER_ID*
    - *CHECKER_DT_STAMP*
    - *REMARKS*
    - *DEPOSITOR_NAME*
    - *BEN_ACCOUNT*
    - *Coll-Dispatch-Details*
      - *INSTRUMENT_NO*
      - *INSTRUMENT_AMT*

INSTRUMENT_DATE

DRAWEE_ACC_NO

DRAWEE_BANK

DRAWEE_BRANCH

DRAWEE_CITY

DEPOSIT_CITY

DOCUMENT_TYPE

COLLECTION_PRO_EXC

ROUTING_GL_EXC

CLEARING_CITY

CORRESPONDENT_BANK

CORRESPONDENT_BRANCH

COLLECTION_TYPE

TRN_REF_NO

DISPATCH_REF_NO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Clearing-Master-Full

Attribute	Description
Name	Clearing-Master-Full
Datatype	
Description	

TOP

DEPOSITSLIP

Attribute	Description	
Name	DEPOSITSLIP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TRN_BRANCH

Attribute	Description
Name	TRN_BRANCH
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REFERENCE_NO

Attribute	Description	
Name	REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BENE_DETAILS1

Attribute	Description	
Name	BENE_DETAILS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRUMENT_CCY

Attribute	Description	
Name	INSTRUMENT_CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INSTRUMENT_AMT

Attribute	Description	
Name	INSTRUMENT_AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

DEPOSITOR_NAME

Attribute	Description
Name	DEPOSITOR_NAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 35

TOP

BEN_ACCOUNT

Attribute	Description
Name	BEN_ACCOUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Coll-Dispatch-Details

Attribute	**Description**
Name	Coll-Dispatch-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSTRUMENT_NO

Attribute	**Description**
Name	INSTRUMENT_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRUMENT_AMT

Attribute	**Description**
Name	INSTRUMENT_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INSTRUMENT_DATE

Attribute	**Description**
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRAWEE_ACC_NO

Attribute	Description
Name	DRAWEE_ACC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DRAWEE_BANK

Attribute	Description
Name	DRAWEE_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DRAWEE_BRANCH

Attribute	Description
Name	DRAWEE_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DRAWEE_CITY

Attribute	Description
Name	DRAWEE_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

DEPOSIT_CITY

Attribute	Description

Name	DEPOSIT_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

DOCUMENT_TYPE

Attribute	**Description**
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

COLLECTION_PRO_EXC

Attribute	**Description**
Name	COLLECTION_PRO_EXC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ROUTING_GL_EXC

Attribute	**Description**
Name	ROUTING_GL_EXC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CLEARING_CITY

Attribute	**Description**
Name	CLEARING_CITY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

CORRESPONDENT_BANK

Attribute	Description	
Name	CORRESPONDENT_BANK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CORRESPONDENT_BRANCH

Attribute	Description	
Name	CORRESPONDENT_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COLLECTION_TYPE

Attribute	Description	
Name	COLLECTION_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,O

TOP

TRN_REF_NO

Attribute	Description	
Name	TRN_REF_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	16

TOP

DISPATCH_REF_NO

Attribute	Description	
Name	DISPATCH_REF_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	21

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.22.4.CG-DeleteCollectionCheque-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Clearing-Master-PK*
      - *REFERENCE_NO*
    - *Clearing-Master-IO*
      - *REFERENCE_NO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Clearing-Master-PK

Attribute	Description
Name	Clearing-Master-PK
Datatype	
Description	

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Clearing-Master-IO

Attribute	Description
Name	Clearing-Master-IO
Datatype	
Description	

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.23.DeleteDocType

DeleteDocType

2.23.1.CG-DeleteDocType-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Document-Type-Full*
    - *INSTRUMENT_TYPE*
    - *DOCUMENT_TYPE*
    - *DESCRIPTION*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Document-Type-Full

Attribute	Description
Name	Document-Type-Full
Datatype	
Description	

TOP

INSTRUMENT_TYPE

Attribute	Description
Name	INSTRUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description

Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

2.23.2.CG-DeleteDocType-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Document-Type-IO*
    - *DOCUMENT_TYPE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration — Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 12 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Document-Type-IO

Attribute	Description
Name	Document-Type-IO
Datatype	
Description	

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

2.23.3.CG-DeleteDocType-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Document-Type-Full*
    - *INSTRUMENT_TYPE*
    - *DOCUMENT_TYPE*
    - *DESCRIPTION*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Document-Type-Full

Attribute	Description

Name	Document-Type-Full
Datatype	
Description	

TOP

INSTRUMENT_TYPE

Attribute	Description
Name	INSTRUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description

Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Document-Type-PK*
      - *DOCUMENT_TYPE*
    - *Document-Type-IO*
      - *DOCUMENT_TYPE*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Document-Type-PK

Attribute	Description
Name	Document-Type-PK
Datatype	
Description	

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 1
Restrictions	Restrictions: maxLength, Description: 4

TOP

Document-Type-IO

Attribute	Description
Name	Document-Type-IO
Datatype	
Description	

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 1
Restrictions	Restrictions: maxLength, Description: 4

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.24.ModifyCGProductMaint

ModifyCGProductMaint

2.24.1.CG-ModifyCGProductMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bank-Parameters-Full*
    - *BANK_CODE*
    - *INTERNAL_PRODUCT*
    - *PROT_INWARD_PROD*
    - *PROT_INTERNAL_PROD*
    - *NON_LOCAL_PROD*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Bank-Product-Det-A*
      - *PRODUCT_CODE*
      - *DOCUMENT_TYPE*

LOCAL_CLEARING

VARIOUS_PMNT_INDICATOR

OW_RET_PROD

CLG_SERVICE_PRODUCT

MEMO_PRODUCT

DRAWER_BANK_EXPENSE_ACC

Bank-Product-Det-B

PRODUCT_CODE

DOCUMENT_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Bank-Parameters-Full

Attribute	Description
Name	Bank-Parameters-Full
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

INTERNAL_PRODUCT

Attribute	Description	
Name	INTERNAL_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PROT_INWARD_PROD

Attribute	Description	
Name	PROT_INWARD_PROD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PROT_INTERNAL_PROD

Attribute	Description
Name	PROT_INTERNAL_PROD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

NON_LOCAL_PROD

Attribute	Description
Name	NON_LOCAL_PROD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Bank-Product-Det-A

Attribute	Description	
Name	Bank-Product-Det-A	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRODUCT_CODE

Attribute	Description	
Name	PRODUCT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LOCAL_CLEARING

Attribute	Description	
Name	LOCAL_CLEARING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

ORACLE

TOP

VARIOUS_PMNT_INDICATOR

Attribute	Description
Name	VARIOUS_PMNT_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / V,N,G,A,O

TOP

OW_RET_PROD

Attribute	Description
Name	OW_RET_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLG_SERVICE_PRODUCT

Attribute	Description
Name	CLG_SERVICE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MEMO_PRODUCT

Attribute	Description
Name	MEMO_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DRAWER_BANK_EXPENSE_ACC

Attribute	Description
Name	DRAWER_BANK_EXPENSE_ACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Bank-Product-Det-B

Attribute	Description
Name	Bank-Product-Det-B
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRODUCT_CODE

Attribute	Description
Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bank-Parameters-IO*
    - *BANK_CODE*
    - *INTERNAL_PRODUCT*
    - *PROT_INWARD_PROD*
    - *PROT_INTERNAL_PROD*
    - *NON_LOCAL_PROD*
    - *MAKER*
    - *MAKERSTAMP*
    - *Bank-Product-Det-A*
      - *OW_RET_PROD*
      - *CLG_SERVICE_PRODUCT*
      - *MEMO_PRODUCT*
      - *DRAWER_BANK_EXPENSE_ACC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Bank-Parameters-IO

Attribute	Description
Name	Bank-Parameters-IO
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description
Name	BANK_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

INTERNAL_PRODUCT

Attribute	Description
Name	INTERNAL_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PROT_INWARD_PROD

Attribute	Description
Name	PROT_INWARD_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PROT_INTERNAL_PROD

Attribute	Description
Name	PROT_INTERNAL_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

NON_LOCAL_PROD

Attribute	Description

Name	NON_LOCAL_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Bank-Product-Det-A

Attribute	**Description**
Name	Bank-Product-Det-A
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OW_RET_PROD

Attribute	**Description**
Name	OW_RET_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	4

TOP

CLG_SERVICE_PRODUCT

Attribute	Description	
Name	CLG_SERVICE_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MEMO_PRODUCT

Attribute	Description	
Name	MEMO_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DRAWER_BANK_EXPENSE_ACC

Attribute	Description	
Name	DRAWER_BANK_EXPENSE_ACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

2.24.3.CG-ModifyCGProductMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bank-Parameters-Full*
    - *BANK_CODE*
    - *INTERNAL_PRODUCT*
    - *PROT_INWARD_PROD*
    - *PROT_INTERNAL_PROD*
    - *NON_LOCAL_PROD*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Bank-Product-Det-A*
      - *PRODUCT_CODE*
      - *DOCUMENT_TYPE*
      - *LOCAL_CLEARING*
      - *VARIOUS_PMNT_INDICATOR*
      - *OW_RET_PROD*

CLG_SERVICE_PRODUCT

MEMO_PRODUCT

DRAWER_BANK_EXPENSE_ACC

Bank-Product-Det-B

PRODUCT_CODE

DOCUMENT_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Bank-Parameters-Full

Attribute	Description
Name	Bank-Parameters-Full
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

INTERNAL_PRODUCT

Attribute	Description	
Name	INTERNAL_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PROT_INWARD_PROD

Attribute	Description
Name	PROT_INWARD_PROD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PROT_INTERNAL_PROD

Attribute	Description
Name	PROT_INTERNAL_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

NON_LOCAL_PROD

Attribute	Description
Name	NON_LOCAL_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Bank-Product-Det-A

Attribute	Description
Name	Bank-Product-Det-A
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRODUCT_CODE

Attribute	Description
Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LOCAL_CLEARING

Attribute	Description

Name	LOCAL_CLEARING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VARIOUS_PMNT_INDICATOR

Attribute	**Description**
Name	VARIOUS_PMNT_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / V,N,G,A,O

TOP

OW_RET_PROD

Attribute	**Description**
Name	OW_RET_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLG_SERVICE_PRODUCT

Attribute	**Description**
Name	CLG_SERVICE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MEMO_PRODUCT

Attribute	**Description**
Name	MEMO_PRODUCT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DRAWER_BANK_EXPENSE_ACC

Attribute	Description	
Name	DRAWER_BANK_EXPENSE_ACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Bank-Product-Det-B

Attribute	Description	
Name	Bank-Product-Det-B	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRODUCT_CODE

Attribute	Description	
Name	PRODUCT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.24.4.CG-ModifyCGProductMaint-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bank-Parameters-PK*
      - *BANK_CODE*
    - *Bank-Parameters-IO*
      - *BANK_CODE*
      - *INTERNAL_PRODUCT*
      - *PROT_INWARD_PROD*
      - *PROT_INTERNAL_PROD*
      - *NON_LOCAL_PROD*
      - *MAKER*
      - *MAKERSTAMP*
      - *Bank-Product-Det-A*
        - *OW_RET_PROD*
        - *CLG_SERVICE_PRODUCT*
        - *MEMO_PRODUCT*
        - *DRAWER_BANK_EXPENSE_ACC*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bank-Parameters-PK

Attribute	Description
Name	Bank-Parameters-PK
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Bank-Parameters-IO

Attribute	Description
Name	Bank-Parameters-IO
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

INTERNAL_PRODUCT

Attribute	Description

Name	INTERNAL_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PROT_INWARD_PROD

Attribute	**Description**
Name	PROT_INWARD_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PROT_INTERNAL_PROD

Attribute	**Description**
Name	PROT_INTERNAL_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

NON_LOCAL_PROD

Attribute	**Description**
Name	NON_LOCAL_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Bank-Product-Det-A

Attribute	Description	
Name	Bank-Product-Det-A	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

OW_RET_PROD

Attribute	Description	
Name	OW_RET_PROD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CLG_SERVICE_PRODUCT

Attribute	Description	
Name	CLG_SERVICE_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MEMO_PRODUCT

Attribute	Description
Name	MEMO_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DRAWER_BANK_EXPENSE_ACC

Attribute	Description
Name	DRAWER_BANK_EXPENSE_ACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String

Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.25.ModifyChequeCorrespondence

ModifyChequeCorrespondence

2.25.1.CG-ModifyChequeCorrespondence-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Coll-Dispatch-Master-Full*
    - *DEPOSIT_CITY*
    - *CLEARING_CITY*
    - *CORRESPONDENT_BANK*
    - *COLLECTION_TYPE*
    - *COL_CHRT*
    - *COLLECTION_STATUS*
    - *TRN_REF_NO1*
    - *Coll-Dispatch-Details*
      - *DEPOSITSLIP*
      - *REFERENCE_NO*
      - *INSTRUMENT_NO*
      - *INSTRUMENT_AMT*
      - *COLLSTAT*

FCUBS_HEADER

Attribute	Description

Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration — Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	minOccurs: 0 nillable: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	minOccurs: 0 nillable: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Coll-Dispatch-Master-Full

Attribute	Description

Name	Coll-Dispatch-Master-Full
Datatype	
Description	

TOP

DEPOSIT_CITY

Attribute	Description
Name	DEPOSIT_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

CLEARING_CITY

Attribute	Description
Name	CLEARING_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

CORRESPONDENT_BANK

Attribute	Description
Name	CORRESPONDENT_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COLLECTION_TYPE

Attribute	Description
Name	COLLECTION_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,O,

TOP

COL_CHRT

Attribute	Description
Name	COL_CHRT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / PL,CR,

TOP

COLLECTION_STATUS

Attribute	Description
Name	COLLECTION_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SEND,RTRN,CONF,QURY,

TOP

TRN_REF_NO1

Attribute	Description
Name	TRN_REF_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Coll-Dispatch-Details

Attribute	Description
Name	Coll-Dispatch-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DEPOSITSLIP

Attribute	Description

Name	DEPOSITSLIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REFERENCE_NO

Attribute	**Description**
Name	REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRUMENT_NO

Attribute	**Description**
Name	INSTRUMENT_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRUMENT_AMT

Attribute	**Description**
Name	INSTRUMENT_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLSTAT

Attribute	**Description**
Name	COLLSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	SENT,RTRN,CONF,

TOP

2.25.2.CG-ModifyChequeCorrespondence-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Coll-Dispatch-Master-IO*
    - *TRN_REF_NO1*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Coll-Dispatch-Master-IO

Attribute	Description
Name	Coll-Dispatch-Master-IO
Datatype	
Description	

TOP

TRN_REF_NO1

Attribute	Description	
Name	TRN_REF_NO1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.25.3.CG-ModifyChequeCorrespondence-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Coll-Dispatch-Master-Full*
    - *DEPOSIT_CITY*
    - *CLEARING_CITY*
    - *CORRESPONDENT_BANK*
    - *COLLECTION_TYPE*
    - *COL_CHRT*
    - *COLLECTION_STATUS*
    - *TRN_REF_NO1*
    - *Coll-Dispatch-Details*
      - *DEPOSITSLIP*
      - *REFERENCE_NO*
      - *INSTRUMENT_NO*
      - *INSTRUMENT_AMT*
      - *COLLSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Coll-Dispatch-Master-Full

Attribute	Description
Name	Coll-Dispatch-Master-Full
Datatype	
Description	

TOP

DEPOSIT_CITY

Attribute	Description	
Name	DEPOSIT_CITY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

CLEARING_CITY

Attribute	Description	
Name	CLEARING_CITY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

CORRESPONDENT_BANK

Attribute	Description	
Name	CORRESPONDENT_BANK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COLLECTION_TYPE

Attribute	Description
Name	COLLECTION_TYPE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,O,

TOP

COL_CHRT

Attribute	Description
Name	COL_CHRT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / PL,CR,

TOP

COLLECTION_STATUS

Attribute	Description
Name	COLLECTION_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SEND,RTRN,CONF,QURY,

TOP

TRN_REF_NO1

Attribute	Description
Name	TRN_REF_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Coll-Dispatch-Details

Attribute	Description
Name	Coll-Dispatch-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DEPOSITSLIP

Attribute	Description
Name	DEPOSITSLIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRUMENT_NO

Attribute	Description
Name	INSTRUMENT_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRUMENT_AMT

Attribute	Description
Name	INSTRUMENT_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLSTAT

Attribute	Description
Name	COLLSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SENT,RTRN,CONF,

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes		
	Attribute	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Coll-Dispatch-Master-PK*
      - *TRN_REF_NO1*
    - *Coll-Dispatch-Master-IO*
      - *TRN_REF_NO1*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Coll-Dispatch-Master-PK

Attribute	Description
Name	Coll-Dispatch-Master-PK
Datatype	
Description	

TOP

TRN_REF_NO1

Attribute	Description	
Name	TRN_REF_NO1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Coll-Dispatch-Master-IO

Attribute	Description
Name	Coll-Dispatch-Master-IO
Datatype	
Description	

TOP

TRN_REF_NO1

Attribute	Description	
Name	TRN_REF_NO1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.26.ModifyClgServicePoint

ModifyClgServicePoint

2.26.1.CG-ModifyClgServicePoint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clg-Service-Point-Full*
    - *DRAWEE_BANK*
    - *CITY*
    - *CLEARING_CITY*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Clg-Service-Point-Full

Attribute	Description
Name	Clg-Service-Point-Full
Datatype	
Description	

TOP

DRAWEE_BANK

Attribute	Description
Name	DRAWEE_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CITY

Attribute	Description
Name	CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

CLEARING_CITY

Attribute	Description
Name	CLEARING_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description

Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

2.26.2.CG-ModifyClgServicePoint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clg-Service-Point-IO*
    - *DRAWEE_BANK*
    - *CITY*
    - *MAKER*
    - *MAKERSTAMP*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Clg-Service-Point-IO

Attribute	Description
Name	Clg-Service-Point-IO
Datatype	
Description	

TOP

DRAWEE_BANK

Attribute	Description
Name	DRAWEE_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CITY

Attribute	Description
Name	CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

2.26.3.CG-ModifyClgServicePoint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clg-Service-Point-Full*
    - *DRAWEE_BANK*
    - *CITY*
    - *CLEARING_CITY*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Clg-Service-Point-Full

Attribute	Description

Name	Clg-Service-Point-Full
Datatype	
Description	

TOP

DRAWEE_BANK

Attribute	Description
Name	DRAWEE_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CITY

Attribute	Description
Name	CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

CLEARING_CITY

Attribute	Description
Name	CLEARING_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**

Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Clg-Service-Point-PK*
      - *DRAWEE_BANK*
      - *CITY*
    - *Clg-Service-Point-IO*
      - *DRAWEE_BANK*
      - *CITY*
      - *MAKER*
      - *MAKERSTAMP*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Clg-Service-Point-PK

Attribute	Description
Name	Clg-Service-Point-PK
Datatype	
Description	

TOP

DRAWEE_BANK

Attribute	Description	
Name	DRAWEE_BANK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CITY

Attribute	Description	
Name	CITY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

Clg-Service-Point-IO

Attribute	Description
Name	Clg-Service-Point-IO
Datatype	
Description	

TOP

DRAWEE_BANK

Attribute	Description	
Name	DRAWEE_BANK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	9

TOP

CITY

Attribute	Description	
Name	CITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	5

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.27.ModifyDocException

ModifyDocException

2.27.1.CG-ModifyDocException-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Doc-Exception-Full*
    - *ACCOUNT_NO*
    - *EXECUTIVE*
    - *MODIFICATION_DATE*
    - *BRANCH_CODE*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Doc-Excep-Det*
      - *DOCUMENT_TYPE*
      - *EXCEPTION_ALLOWED*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Doc-Exception-Full

Attribute	Description

Name	Doc-Exception-Full
Datatype	
Description	

TOP

ACCOUNT_NO

Attribute	Description
Name	ACCOUNT_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EXECUTIVE

Attribute	Description
Name	EXECUTIVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MODIFICATION_DATE

Attribute	Description
Name	MODIFICATION_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description

Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Doc-Excep-Det

Attribute	Description
Name	Doc-Excep-Det
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EXCEPTION_ALLOWED

Attribute	Description
Name	EXCEPTION_ALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

2.27.2.CG-ModifyDocException-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Doc-Exception-IO*
    - *ACCOUNT_NO*
    - *BRANCH_CODE*
    - *MAKER*
    - *MAKERSTAMP*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Doc-Exception-IO

Attribute	Description
Name	Doc-Exception-IO
Datatype	
Description	

TOP

ACCOUNT_NO

Attribute	Description
Name	ACCOUNT_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

2.27.3.CG-ModifyDocException-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Doc-Exception-Full*
    - *ACCOUNT_NO*
    - *EXECUTIVE*
    - *MODIFICATION_DATE*
    - *BRANCH_CODE*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Doc-Excep-Det*
      - *DOCUMENT_TYPE*
      - *EXCEPTION_ALLOWED*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Doc-Exception-Full

Attribute	Description
Name	Doc-Exception-Full
Datatype	
Description	

TOP

ACCOUNT_NO

Attribute	Description	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

EXECUTIVE

Attribute	Description	
Name	EXECUTIVE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MODIFICATION_DATE

Attribute	Description	
Name	MODIFICATION_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	3

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Doc-Excep-Det

Attribute	Description
Name	Doc-Excep-Det
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXCEPTION_ALLOWED

Attribute	**Description**
Name	EXCEPTION_ALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC

Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Doc-Exception-PK*
      - *ACCOUNT_NO*
      - *BRANCH_CODE*
    - *Doc-Exception-IO*
      - *ACCOUNT_NO*
      - *BRANCH_CODE*
      - *MAKER*
      - *MAKERSTAMP*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Doc-Exception-PK

Attribute	Description
Name	Doc-Exception-PK
Datatype	
Description	

TOP

ACCOUNT_NO

Attribute	Description	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Doc-Exception-IO

Attribute	Description
Name	Doc-Exception-IO
Datatype	
Description	

TOP

ACCOUNT_NO

Attribute	Description	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	20

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.28.ModifyDocType

ModifyDocType

2.28.1.CG-ModifyDocType-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Document-Type-Full*
    - *INSTRUMENT_TYPE*
    - *DOCUMENT_TYPE*
    - *DESCRIPTION*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Document-Type-Full

Attribute	Description
Name	Document-Type-Full
Datatype	
Description	

TOP

INSTRUMENT_TYPE

Attribute	Description
Name	INSTRUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description

Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

2.28.2.CG-ModifyDocType-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Document-Type-IO*
    - *DOCUMENT_TYPE*
    - *MAKER*
    - *MAKERSTAMP*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Document-Type-IO

Attribute	Description
Name	Document-Type-IO
Datatype	
Description	

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

MAKER

Attribute	Description

Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

2.28.3.CG-ModifyDocType-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Document-Type-Full*
    - *INSTRUMENT_TYPE*
    - *DOCUMENT_TYPE*
    - *DESCRIPTION*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Document-Type-Full

Attribute	Description

Name	Document-Type-Full
Datatype	
Description	

TOP

INSTRUMENT_TYPE

Attribute	Description
Name	INSTRUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**

Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Document-Type-PK*
      - *DOCUMENT_TYPE*
    - *Document-Type-IO*
      - *DOCUMENT_TYPE*
      - *MAKER*
      - *MAKERSTAMP*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description

Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Document-Type-PK

Attribute	Description
Name	Document-Type-PK
Datatype	
Description	

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 4

TOP

Document-Type-IO

Attribute	Description
Name	Document-Type-IO
Datatype	
Description	

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.29.ModifySecCode

ModifySecCode

2.29.1.CG-ModifySecCode-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Sectors-Full*
    - *SECTOR_CODE*
    - *SECTOR_DESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	Restrictions / Description maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions / Description length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute / Description minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute / Description nillable / true
Restrictions	Restrictions / Description pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute / Description nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttms-Sectors-Full

Attribute	Description
Name	Sttms-Sectors-Full
Datatype	
Description	

TOP

SECTOR_CODE

Attribute	Description
Name	SECTOR_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECTOR_DESC

Attribute	Description
Name	SECTOR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	255
minLength	0

TOP

2.29.2.CG-ModifySecCode-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Sectors-IO*
    - *SECTOR_CODE*
    - *MAKER*
    - *MAKERSTAMP*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0

Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttms-Sectors-IO

Attribute	Description
Name	Sttms-Sectors-IO
Datatype	
Description	

TOP

SECTOR_CODE

Attribute	Description
Name	SECTOR_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	Restrictions	Description
	maxLength	9

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

TOP

FLDVAL

<table>
<tr><th>Attribute</th><th>Description</th></tr>
<tr><td>Name</td><td>FLDVAL</td></tr>
<tr><td>Datatype</td><td>String</td></tr>
<tr><td>Description</td><td></td></tr>
<tr><td>Attributes</td><td>
<table>
<tr><th>Attribute</th><th>Description</th></tr>
<tr><td>minOccurs</td><td>0</td></tr>
</table>
</td></tr>
<tr><td>Restrictions</td><td>
<table>
<tr><th>Restrictions</th><th>Description</th></tr>
<tr><td>maxLength</td><td>255</td></tr>
<tr><td>minLength</td><td>0</td></tr>
</table>
</td></tr>
</table>

TOP

2.29.3.CG-ModifySecCode-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Sectors-Full*
    - *SECTOR_CODE*
    - *SECTOR_DESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description

Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttms-Sectors-Full

Attribute	Description

Name	Sttms-Sectors-Full
Datatype	
Description	

TOP

SECTOR_CODE

Attribute	Description
Name	SECTOR_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECTOR_DESC

Attribute	Description
Name	SECTOR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttms-Sectors-PK*
      - *SECTOR_CODE*
    - *Sttms-Sectors-IO*
      - *SECTOR_CODE*
      - *MAKER*
      - *MAKERSTAMP*
      - *UDFDETAILS*
        - *FLDNAM*
        - *FLDVAL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Sttms-Sectors-PK

Attribute	Description
Name	Sttms-Sectors-PK
Datatype	
Description	

TOP

SECTOR_CODE

Attribute	Description	
Name	SECTOR_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Sttms-Sectors-IO

Attribute	Description
Name	Sttms-Sectors-IO
Datatype	
Description	

TOP

SECTOR_CODE

Attribute	Description	
Name	SECTOR_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.30.QueryCGProductMaint

QueryCGProductMaint

2.30.1.CG-QueryCGProductMaint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bank-Parameters-IO*
    - *BANK_CODE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Bank-Parameters-IO

Attribute	Description
Name	Bank-Parameters-IO
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description
Name	BANK_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

2.30.2.CG-QueryCGProductMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bank-Parameters-IO*
      - *BANK_CODE*
    - *Bank-Parameters-Full*
      - *BANK_CODE*
      - *INTERNAL_PRODUCT*
      - *PROT_INWARD_PROD*
      - *PROT_INTERNAL_PROD*
      - *NON_LOCAL_PROD*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
      - *TXNSTAT*
      - *AUTHSTAT*
      - *Bank-Product-Det-A*
        - *PRODUCT_CODE*
        - *DOCUMENT_TYPE*

LOCAL_CLEARING

VARIOUS_PMNT_INDICATOR

OW_RET_PROD

CLG_SERVICE_PRODUCT

MEMO_PRODUCT

DRAWER_BANK_EXPENSE_ACC

Bank-Product-Det-B

PRODUCT_CODE

DOCUMENT_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bank-Parameters-IO

Attribute	Description
Name	Bank-Parameters-IO
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Bank-Parameters-Full

Attribute	Description
Name	Bank-Parameters-Full
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description
Name	BANK_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

INTERNAL_PRODUCT

Attribute	Description
Name	INTERNAL_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PROT_INWARD_PROD

Attribute	Description
Name	PROT_INWARD_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PROT_INTERNAL_PROD

Attribute	Description
Name	PROT_INTERNAL_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

NON_LOCAL_PROD

Attribute	Description
Name	NON_LOCAL_PROD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Bank-Product-Det-A

Attribute	**Description**
Name	Bank-Product-Det-A
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRODUCT_CODE

Attribute	Description
Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LOCAL_CLEARING

Attribute	Description
Name	LOCAL_CLEARING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VARIOUS_PMNT_INDICATOR

Attribute	Description
Name	VARIOUS_PMNT_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / V,N,G,A,O

TOP

OW_RET_PROD

Attribute	Description
Name	OW_RET_PROD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CLG_SERVICE_PRODUCT

Attribute	Description
Name	CLG_SERVICE_PRODUCT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

MEMO_PRODUCT

Attribute	Description
Name	MEMO_PRODUCT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

DRAWER_BANK_EXPENSE_ACC

Attribute	Description
Name	DRAWER_BANK_EXPENSE_ACC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

Bank-Product-Det-B

Attribute	Description
Name	Bank-Product-Det-B

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRODUCT_CODE

Attribute	Description
Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.31.QueryCGRejErrCdMaint

QueryCGRejErrCdMaint

2.31.1.CG-QueryCGRejErrCdMaint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Reject-Acc-Errcd-IO*
    - *CLEARING_TYPE*
    - *ERR_CODE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Reject-Acc-Errcd-IO

Attribute	Description
Name	Reject-Acc-Errcd-IO
Datatype	
Description	

TOP

CLEARING_TYPE

Attribute	Description
Name	CLEARING_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / IW,IC,OC,

TOP

ERR_CODE

Attribute	Description
Name	ERR_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

2.31.2.CG-QueryCGRejErrCdMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Reject-Acc-Errcd-IO*
      - *CLEARING_TYPE*
      - *ERR_CODE*
    - *Reject-Acc-Errcd-Full*
      - *CLEARING_TYPE*
      - *ERR_CODE*
      - *ERR_CODE_DESC*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
      - *TXNSTAT*
      - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Reject-Acc-Errcd-IO

Attribute	Description
Name	Reject-Acc-Errcd-IO
Datatype	
Description	

TOP

CLEARING_TYPE

Attribute	Description	
Name	CLEARING_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	IW,IC,OC,

TOP

ERR_CODE

Attribute	Description	
Name	ERR_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

Reject-Acc-Errcd-Full

Attribute	Description
Name	Reject-Acc-Errcd-Full
Datatype	
Description	

TOP

CLEARING_TYPE

Attribute	Description

Name	CLEARING_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / IW,IC,OC,

TOP

ERR_CODE

Attribute	**Description**
Name	ERR_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

ERR_CODE_DESC

Attribute	**Description**
Name	ERR_CODE_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.32.QueryChequeCorrespondence

QueryChequeCorrespondence

2.32.1.CG-QueryChequeCorrespondence-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Coll-Dispatch-Master-IO
COLLECTION_STATUS
TRN_REF_NO1

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Coll-Dispatch-Master-IO

Attribute	Description
Name	Coll-Dispatch-Master-IO
Datatype	
Description	

TOP

COLLECTION_STATUS

Attribute	Description
Name	COLLECTION_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SEND,RTRN,CONF,QURY,

TOP

TRN_REF_NO1

Attribute	Description
Name	TRN_REF_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

2.32.2.CG-QueryChequeCorrespondence-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Coll-Dispatch-Master-IO*
      - *COLLECTION_STATUS*
      - *TRN_REF_NO1*
    - *Coll-Dispatch-Master-Full*
      - *DEPOSIT_CITY*
      - *CLEARING_CITY*
      - *CORRESPONDENT_BANK*
      - *COLLECTION_TYPE*
      - *COL_CHRT*
      - *COLLECTION_STATUS*
      - *TRN_REF_NO1*
      - *Coll-Dispatch-Details*
        - *DEPOSITSLIP*
        - *REFERENCE_NO*
        - *INSTRUMENT_NO*
        - *INSTRUMENT_AMT*
        - *COLLSTAT*
  - *FCUBS_ERROR_RESP*

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Coll-Dispatch-Master-IO

Attribute	Description
Name	Coll-Dispatch-Master-IO
Datatype	
Description	

TOP

COLLECTION_STATUS

Attribute	Description	
Name	COLLECTION_STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SEND,RTRN,CONF,QURY,

TOP

TRN_REF_NO1

Attribute	Description	
Name	TRN_REF_NO1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Coll-Dispatch-Master-Full

Attribute	Description
Name	Coll-Dispatch-Master-Full

Datatype	
Description	

TOP

DEPOSIT_CITY

Attribute	Description
Name	DEPOSIT_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

CLEARING_CITY

Attribute	Description
Name	CLEARING_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

CORRESPONDENT_BANK

Attribute	Description
Name	CORRESPONDENT_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COLLECTION_TYPE

Attribute	Description
Name	COLLECTION_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,O,

TOP

COL_CHRT

Attribute	Description
Name	COL_CHRT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / PL,CR,

TOP

COLLECTION_STATUS

Attribute	Description
Name	COLLECTION_STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SEND,RTRN,CONF,QURY,

TOP

TRN_REF_NO1

Attribute	Description
Name	TRN_REF_NO1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Coll-Dispatch-Details

Attribute	Description
Name	Coll-Dispatch-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DEPOSITSLIP

Attribute	Description

Name	DEPOSITSLIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REFERENCE_NO

Attribute	**Description**
Name	REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRUMENT_NO

Attribute	**Description**
Name	INSTRUMENT_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRUMENT_AMT

Attribute	**Description**
Name	INSTRUMENT_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLSTAT

Attribute	**Description**
Name	COLLSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	SENT,RTRN,CONF,

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.33.QueryClgHoliday

Query Clearing Holiday

2.33.1.CG-QueryClgHoliday-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Holiday_Details-IO*
    - *YR*
    - *CLR_HOUS*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Holiday_Details-IO

Attribute	Description
Name	Holiday_Details-IO
Datatype	
Description	Query Of Clearing House Holiday Details IO Type

TOP

YR

Attribute	Description
Name	YR
Datatype	Number
Description	Indicates Year

TOP

CLR_HOUS

Attribute	Description
Name	CLR_HOUS
Datatype	String
Description	Indicaets Clearing House

Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	16

TOP

2.33.2.CG-QueryClgHoliday-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Holiday_Details-IO*
      - *YR*
      - *CLR_HOUS*
    - *Holiday_Details-Full*
      - *CLR_HOUS*
      - *YR*
      - *WEEKLY_HOL*
      - *UNEXPHOL*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *Holiday_list*
        - *CLEARINGHOUSE*

YEAR
MONTH
HOLIDAYLIST1
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Holiday_Details-IO

Attribute	Description
Name	Holiday_Details-IO
Datatype	
Description	Query Of Clearing House Holiday Details IO Type

TOP

YR

Attribute	Description
Name	YR
Datatype	Number
Description	Indicates Year

TOP

CLR_HOUS

Attribute	Description	
Name	CLR_HOUS	
Datatype	String	
Description	Indicaets Clearing House	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Holiday_Details-Full

Attribute	Description
Name	Holiday_Details-Full
Datatype	
Description	Query Of Clearing House Holiday Details Full Type

TOP

CLR_HOUS

Attribute	Description	
Name	CLR_HOUS	
Datatype	String	
Description	Indicaets Clearing House	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

YR

Attribute	Description
Name	YR
Datatype	Number
Description	Indicates Year

TOP

WEEKLY_HOL

Attribute	Description	
Name	WEEKLY_HOL	
Datatype	String	
Description	Indicates Weekly Holiday	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7

TOP

UNEXPHOL

Attribute	Description	
Name	UNEXPHOL	
Datatype	String	
Description	Indicates Unexpected Holiday	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether the record is Authorized atleast Once.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Holiday_list

Attribute	Description

Name	Holiday_list
Datatype	
Description	Clearing House Holiday List
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLEARINGHOUSE

Attribute	**Description**
Name	CLEARINGHOUSE
Datatype	String
Description	Indicates Clearing House
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

YEAR

Attribute	**Description**
Name	YEAR
Datatype	Number
Description	Indicates Year
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MONTH

Attribute	**Description**
Name	MONTH
Datatype	Number
Description	Indicaets Month
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOLIDAYLIST1

Attribute	**Description**
Name	HOLIDAYLIST1
Datatype	String
Description	Indicates Holiday List
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 31

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description

Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning Response Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.34.QueryClgServicePoint

QueryClgServicePoint

2.34.1.CG-QueryClgServicePoint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clg-Service-Point-IO*
    - *DRAWEE_BANK*
    - *CITY*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Clg-Service-Point-IO

Attribute	Description
Name	Clg-Service-Point-IO
Datatype	
Description	

TOP

DRAWEE_BANK

Attribute	Description
Name	DRAWEE_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CITY

Attribute	Description
Name	CITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

2.34.2.CG-QueryClgServicePoint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Clg-Service-Point-IO*
      - *DRAWEE_BANK*
      - *CITY*
    - *Clg-Service-Point-Full*
      - *DRAWEE_BANK*
      - *CITY*
      - *CLEARING_CITY*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
      - *TXNSTAT*
      - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Clg-Service-Point-IO

Attribute	Description
Name	Clg-Service-Point-IO
Datatype	
Description	

TOP

DRAWEE_BANK

Attribute	Description	
Name	DRAWEE_BANK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CITY

Attribute	Description	
Name	CITY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

Clg-Service-Point-Full

Attribute	Description
Name	Clg-Service-Point-Full
Datatype	
Description	

TOP

DRAWEE_BANK

Attribute	Description

Name	DRAWEE_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CITY

Attribute	Description
Name	CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

CLEARING_CITY

Attribute	Description
Name	CLEARING_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.35.QueryCollectionCheque

QueryCollectionCheque

2.35.1.CG-QueryCollectionCheque-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Master-IO*
    - *REFERENCE_NO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Clearing-Master-IO

Attribute	Description
Name	Clearing-Master-IO
Datatype	
Description	

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

2.35.2.CG-QueryCollectionCheque-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Clearing-Master-IO*
      - *REFERENCE_NO*
    - *Clearing-Master-Full*
      - *DEPOSITSLIP*
      - *TRN_BRANCH*
      - *REFERENCE_NO*
      - *BENE_DETAILS1*
      - *INSTRUMENT_CCY*
      - *INSTRUMENT_AMT*
      - *RECORD_STAT*
      - *AUTH_STAT*
      - *MAKER_ID*
      - *MAKER_DT_STAMP*
      - *CHECKER_ID*
      - *CHECKER_DT_STAMP*
      - *REMARKS*
      - *DEPOSITOR_NAME*
      - *BEN_ACCOUNT*

Coll-Dispatch-Details

INSTRUMENT_NO

INSTRUMENT_AMT

INSTRUMENT_DATE

DRAWEE_ACC_NO

DRAWEE_BANK

DRAWEE_BRANCH

DRAWEE_CITY

DEPOSIT_CITY

DOCUMENT_TYPE

COLLECTION_PRO_EXC

ROUTING_GL_EXC

CLEARING_CITY

CORRESPONDENT_BANK

CORRESPONDENT_BRANCH

COLLECTION_TYPE

TRN_REF_NO

DISPATCH_REF_NO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Clearing-Master-IO

Attribute	Description
Name	Clearing-Master-IO
Datatype	
Description	

TOP

REFERENCE_NO

Attribute	Description	
Name	REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Clearing-Master-Full

Attribute	Description
Name	Clearing-Master-Full
Datatype	
Description	

TOP

DEPOSITSLIP

Attribute	Description	
Name	DEPOSITSLIP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TRN_BRANCH

Attribute	Description	
Name	TRN_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REFERENCE_NO

Attribute	Description	
Name	REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BENE_DETAILS1

Attribute	Description
Name	BENE_DETAILS1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRUMENT_CCY

Attribute	Description	
Name	INSTRUMENT_CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INSTRUMENT_AMT

Attribute	Description	
Name	INSTRUMENT_AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

RECORD_STAT

Attribute	Description	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTH_STAT

Attribute	Description	
Name	AUTH_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U

TOP

MAKER_ID

Attribute	Description	
Name	MAKER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKER_DT_STAMP

Attribute	Description	
Name	MAKER_DT_STAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER_ID

Attribute	Description	
Name	CHECKER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKER_DT_STAMP

Attribute	Description	
Name	CHECKER_DT_STAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DEPOSITOR_NAME

Attribute	Description
Name	DEPOSITOR_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BEN_ACCOUNT

Attribute	Description
Name	BEN_ACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Coll-Dispatch-Details

Attribute	Description
Name	Coll-Dispatch-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSTRUMENT_NO

Attribute	Description
Name	INSTRUMENT_NO
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRUMENT_AMT

Attribute	**Description**
Name	INSTRUMENT_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INSTRUMENT_DATE

Attribute	**Description**
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRAWEE_ACC_NO

Attribute	**Description**
Name	DRAWEE_ACC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRAWEE_BANK

Attribute	**Description**
Name	DRAWEE_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DRAWEE_BRANCH

Attribute	Description
Name	DRAWEE_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DRAWEE_CITY

Attribute	Description
Name	DRAWEE_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

DEPOSIT_CITY

Attribute	Description
Name	DEPOSIT_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

COLLECTION_PRO_EXC

Attribute	Description

Name	COLLECTION_PRO_EXC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ROUTING_GL_EXC

Attribute	**Description**
Name	ROUTING_GL_EXC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CLEARING_CITY

Attribute	**Description**
Name	CLEARING_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

CORRESPONDENT_BANK

Attribute	**Description**
Name	CORRESPONDENT_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CORRESPONDENT_BRANCH

Attribute	**Description**
Name	CORRESPONDENT_BRANCH
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COLLECTION_TYPE

Attribute	Description
Name	COLLECTION_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,O

TOP

TRN_REF_NO

Attribute	Description
Name	TRN_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DISPATCH_REF_NO

Attribute	Description
Name	DISPATCH_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 21

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.36.QueryDocException

QueryDocException

2.36.1.CG-QueryDocException-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Doc-Exception-IO*
    - *ACCOUNT_NO*
    - *BRANCH_CODE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Doc-Exception-IO

Attribute	Description
Name	Doc-Exception-IO
Datatype	
Description	

TOP

ACCOUNT_NO

Attribute	Description
Name	ACCOUNT_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

2.36.2.CG-QueryDocException-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Doc-Exception-IO*
      - *ACCOUNT_NO*
      - *BRANCH_CODE*
    - *Doc-Exception-Full*
      - *ACCOUNT_NO*
      - *EXECUTIVE*
      - *MODIFICATION_DATE*
      - *BRANCH_CODE*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
      - *TXNSTAT*
      - *AUTHSTAT*
      - *Doc-Excep-Det*
        - *DOCUMENT_TYPE*
        - *EXCEPTION_ALLOWED*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>nillable</td><td>true</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Doc-Exception-IO

Attribute	Description
Name	Doc-Exception-IO
Datatype	
Description	

TOP

ACCOUNT_NO

Attribute	Description	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Doc-Exception-Full

Attribute	Description
Name	Doc-Exception-Full

Datatype	
Description	

TOP

ACCOUNT_NO

Attribute	Description
Name	ACCOUNT_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EXECUTIVE

Attribute	Description
Name	EXECUTIVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MODIFICATION_DATE

Attribute	Description
Name	MODIFICATION_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Doc-Excep-Det

Attribute	Description
Name	Doc-Excep-Det
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EXCEPTION_ALLOWED

Attribute	Description
Name	EXCEPTION_ALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.37.QueryDocType

QueryDocType

2.37.1.CG-QueryDocType-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Document-Type-IO*
    - *DOCUMENT_TYPE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Document-Type-IO

Attribute	Description
Name	Document-Type-IO
Datatype	
Description	

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

2.37.2.CG-QueryDocType-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Document-Type-IO*
      - *DOCUMENT_TYPE*
    - *Document-Type-Full*
      - *INSTRUMENT_TYPE*
      - *DOCUMENT_TYPE*
      - *DESCRIPTION*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
      - *TXNSTAT*
      - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Document-Type-IO

Attribute	Description
Name	Document-Type-IO
Datatype	
Description	

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Document-Type-Full

Attribute	Description
Name	Document-Type-Full
Datatype	
Description	

TOP

INSTRUMENT_TYPE

Attribute	Description	
Name	INSTRUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,D

TOP

DOCUMENT_TYPE

Attribute	Description

Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.38.QueryLateClg

Query Late Clearing

2.38.1.CG-QueryLateClg-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
CLEARING_MAIN-IO
BRN_COD
PRD_COD

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

CLEARING_MAIN-IO

Attribute	Description
Name	CLEARING_MAIN-IO
Datatype	
Description	Query Of Late Clearing Details Main IO Type

TOP

BRN_COD

Attribute	Description
Name	BRN_COD
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRD_COD

Attribute	Description
Name	PRD_COD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

2.38.2.CG-QueryLateClg-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *CLEARING_MAIN-IO*
      - *BRN_COD*
      - *PRD_COD*
    - *CLEARING_MAIN-Full*
      - *BRN_COD*
      - *PRD_COD*
      - *LATE_CLG*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*

EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

CLEARING_MAIN-IO

Attribute	Description
Name	CLEARING_MAIN-IO
Datatype	
Description	Query Of Late Clearing Details Main IO Type

TOP

BRN_COD

Attribute	Description	
Name	BRN_COD	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRD_COD

Attribute	Description	
Name	PRD_COD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CLEARING_MAIN-Full

Attribute	Description
Name	CLEARING_MAIN-Full
Datatype	
Description	Query Of Late Clearing Details Main Full Type

TOP

BRN_COD

Attribute	Description

Name	BRN_COD
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PRD_COD

Attribute	**Description**
Name	PRD_COD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LATE_CLG

Attribute	**Description**
Name	LATE_CLG
Datatype	String
Description	Indicates late Clearing allowed Yes/No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether the record is Authorized atleast Once.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description

Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Warning Response Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.39.QueryQueryParityMismatch

QueryQueryParityMismatch

2.39.1.CG-QueryQueryParityMismatch-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Ref-Match-IO*
    - *CLG_CCY*
    - *REFENTRY_CCY*
    - *REFENTRY_BOOKDT*
    - *CLG_REFNO*
    - *CLG_BOOKDT*
    - *PROCESS_DATE*
    - *INSTRUMENT_NO*
    - *REFENTRY_REFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description

Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Ref-Match-IO

Attribute	Description
Name	Ref-Match-IO
Datatype	
Description	

TOP

CLG_CCY

Attribute	Description
Name	CLG_CCY
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFENTRY_CCY

Attribute	**Description**
Name	REFENTRY_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REFENTRY_BOOKDT

Attribute	**Description**
Name	REFENTRY_BOOKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLG_REFNO

Attribute	**Description**
Name	CLG_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CLG_BOOKDT

Attribute	**Description**
Name	CLG_BOOKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PROCESS_DATE

Attribute	Description
Name	PROCESS_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRUMENT_NO

Attribute	Description
Name	INSTRUMENT_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REFENTRY_REFNO

Attribute	Description
Name	REFENTRY_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

2.39.2.CG-QueryQueryParityMismatch-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Ref-Match-IO*
      - *CLG_CCY*
      - *REFENTRY_CCY*
      - *REFENTRY_BOOKDT*
      - *CLG_REFNO*
      - *CLG_BOOKDT*
      - *PROCESS_DATE*
      - *INSTRUMENT_NO*
      - *REFENTRY_REFNO*
    - *Ref-Match-Full*
      - *CLG_CCY*
      - *CLG_AMOUNT*
      - *REFENTRY_CCY*
      - *REFENTRY_AMOUNT*
      - *REFENTRY_BOOKDT*
      - *CLG_REFNO*
      - *CLG_BOOKDT*
      - *PROCESS_DATE*

INSTRUMENT_NO

REFENTRY_REFNO

Ref-Match-Dtl

CLG_CCY

CLG_AMOUNT

CLG_ACCBRN

CLG_ACCNO

CLG_DEPOSIT_PLACE

ADJ_AMT

REFENTRY_CCY

REFENTRY_AMOUNT

REFENTRY_BOOKDT

CLG_REFNO

CLG_BOOKDT

PROCESS_DATE

INSTRUMENT_NO

REFENTRY_REFNO

REFENTRY_ACCNO

REFENTRY_ACCBRN

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Ref-Match-IO

Attribute	Description
Name	Ref-Match-IO
Datatype	
Description	

TOP

CLG_CCY

Attribute	Description
Name	CLG_CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	Restrictions	Description
	maxLength	3

TOP

REFENTRY_CCY

Attribute	Description	
Name	REFENTRY_CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

REFENTRY_BOOKDT

Attribute	Description	
Name	REFENTRY_BOOKDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CLG_REFNO

Attribute	Description	
Name	CLG_REFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

CLG_BOOKDT

Attribute	Description	
Name	CLG_BOOKDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PROCESS_DATE

Attribute	Description
Name	PROCESS_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRUMENT_NO

Attribute	Description
Name	INSTRUMENT_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REFENTRY_REFNO

Attribute	Description
Name	REFENTRY_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Ref-Match-Full

Attribute	Description
Name	Ref-Match-Full
Datatype	
Description	

TOP

CLG_CCY

Attribute	Description
Name	CLG_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CLG_AMOUNT

Attribute	Description
Name	CLG_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFENTRY_CCY

Attribute	Description
Name	REFENTRY_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REFENTRY_AMOUNT

Attribute	Description
Name	REFENTRY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFENTRY_BOOKDT

Attribute	Description
Name	REFENTRY_BOOKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLG_REFNO

Attribute	Description
Name	CLG_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CLG_BOOKDT

Attribute	Description
Name	CLG_BOOKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PROCESS_DATE

Attribute	Description
Name	PROCESS_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRUMENT_NO

Attribute	Description
Name	INSTRUMENT_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REFENTRY_REFNO

Attribute	Description
Name	REFENTRY_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Ref-Match-Dtl

Attribute	Description
Name	Ref-Match-Dtl
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CLG_CCY

Attribute	Description	
Name	CLG_CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

CLG_AMOUNT

Attribute	Description	
Name	CLG_AMOUNT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CLG_ACCBRN

Attribute	Description	
Name	CLG_ACCBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

CLG_ACCNO

Attribute	Description	
Name	CLG_ACCNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

CLG_DEPOSIT_PLACE

Attribute	Description
Name	CLG_DEPOSIT_PLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ADJ_AMT

Attribute	Description
Name	ADJ_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFENTRY_CCY

Attribute	Description
Name	REFENTRY_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REFENTRY_AMOUNT

Attribute	Description
Name	REFENTRY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFENTRY_BOOKDT

Attribute	Description
Name	REFENTRY_BOOKDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CLG_REFNO

Attribute	Description	
Name	CLG_REFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CLG_BOOKDT

Attribute	Description	
Name	CLG_BOOKDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PROCESS_DATE

Attribute	Description	
Name	PROCESS_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRUMENT_NO

Attribute	Description	
Name	INSTRUMENT_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

REFENTRY_REFNO

Attribute	Description
Name	REFENTRY_REFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

REFENTRY_ACCNO

Attribute	**Description**
Name	REFENTRY_ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

REFENTRY_ACCBRN

Attribute	**Description**
Name	REFENTRY_ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.40.QuerySecCode

QuerySecCode

2.40.1.CG-QuerySecCode-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Sectors-IO*
    - *SECTOR_CODE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttms-Sectors-IO

Attribute	Description
Name	Sttms-Sectors-IO
Datatype	
Description	

TOP

SECTOR_CODE

Attribute	Description
Name	SECTOR_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

2.40.2.CG-QuerySecCode-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttms-Sectors-IO*
      - *SECTOR_CODE*
    - *Sttms-Sectors-Full*
      - *SECTOR_CODE*
      - *SECTOR_DESC*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
      - *TXNSTAT*
      - *AUTHSTAT*
      - *UDFDETAILS*
        - *FLDNAM*
        - *FLDVAL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttms-Sectors-IO

Attribute	Description
Name	Sttms-Sectors-IO
Datatype	
Description	

TOP

SECTOR_CODE

Attribute	Description	
Name	SECTOR_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Sttms-Sectors-Full

Attribute	Description
Name	Sttms-Sectors-Full
Datatype	
Description	

TOP

SECTOR_CODE

Attribute	Description	
Name	SECTOR_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SECTOR_DESC

Attribute	Description

Name	SECTOR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.41.ReopenCGProductMaint

ReopenCGProductMaint

2.41.1.CG-ReopenCGProductMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bank-Parameters-Full*
    - *BANK_CODE*
    - *INTERNAL_PRODUCT*
    - *PROT_INWARD_PROD*
    - *PROT_INTERNAL_PROD*
    - *NON_LOCAL_PROD*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Bank-Product-Det-A*
      - *PRODUCT_CODE*
      - *DOCUMENT_TYPE*

LOCAL_CLEARING

VARIOUS_PMNT_INDICATOR

OW_RET_PROD

CLG_SERVICE_PRODUCT

MEMO_PRODUCT

DRAWER_BANK_EXPENSE_ACC

Bank-Product-Det-B

PRODUCT_CODE

DOCUMENT_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Bank-Parameters-Full

Attribute	Description
Name	Bank-Parameters-Full
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

INTERNAL_PRODUCT

Attribute	Description	
Name	INTERNAL_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PROT_INWARD_PROD

Attribute	Description	
Name	PROT_INWARD_PROD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PROT_INTERNAL_PROD

Attribute	Description
Name	PROT_INTERNAL_PROD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

NON_LOCAL_PROD

Attribute	Description
Name	NON_LOCAL_PROD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Bank-Product-Det-A

Attribute	Description	
Name	Bank-Product-Det-A	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRODUCT_CODE

Attribute	Description	
Name	PRODUCT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LOCAL_CLEARING

Attribute	Description	
Name	LOCAL_CLEARING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VARIOUS_PMNT_INDICATOR

Attribute	Description
Name	VARIOUS_PMNT_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / V,N,G,A,O

TOP

OW_RET_PROD

Attribute	Description
Name	OW_RET_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLG_SERVICE_PRODUCT

Attribute	Description
Name	CLG_SERVICE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MEMO_PRODUCT

Attribute	Description
Name	MEMO_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DRAWER_BANK_EXPENSE_ACC

Attribute	Description
Name	DRAWER_BANK_EXPENSE_ACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Bank-Product-Det-B

Attribute	Description
Name	Bank-Product-Det-B
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRODUCT_CODE

Attribute	Description
Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Bank-Parameters-IO
BANK_CODE
MAKER
MAKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Bank-Parameters-IO

Attribute	Description
Name	Bank-Parameters-IO
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description
Name	BANK_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.41.3.CG-ReopenCGProductMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Bank-Parameters-Full*
    - *BANK_CODE*
    - *INTERNAL_PRODUCT*
    - *PROT_INWARD_PROD*
    - *PROT_INTERNAL_PROD*
    - *NON_LOCAL_PROD*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Bank-Product-Det-A*
      - *PRODUCT_CODE*
      - *DOCUMENT_TYPE*
      - *LOCAL_CLEARING*
      - *VARIOUS_PMNT_INDICATOR*
      - *OW_RET_PROD*

CLG_SERVICE_PRODUCT

MEMO_PRODUCT

DRAWER_BANK_EXPENSE_ACC

Bank-Product-Det-B

PRODUCT_CODE

DOCUMENT_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength 12; pattern [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Bank-Parameters-Full

Attribute	Description
Name	Bank-Parameters-Full
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

INTERNAL_PRODUCT

Attribute	Description	
Name	INTERNAL_PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PROT_INWARD_PROD

Attribute	Description
Name	PROT_INWARD_PROD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PROT_INTERNAL_PROD

Attribute	**Description**
Name	PROT_INTERNAL_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

NON_LOCAL_PROD

Attribute	**Description**
Name	NON_LOCAL_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Bank-Product-Det-A

Attribute	Description
Name	Bank-Product-Det-A
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRODUCT_CODE

Attribute	Description
Name	PRODUCT_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LOCAL_CLEARING

Attribute	Description

Name	LOCAL_CLEARING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VARIOUS_PMNT_INDICATOR

Attribute	**Description**
Name	VARIOUS_PMNT_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / V,N,G,A,O

TOP

OW_RET_PROD

Attribute	**Description**
Name	OW_RET_PROD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLG_SERVICE_PRODUCT

Attribute	**Description**
Name	CLG_SERVICE_PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MEMO_PRODUCT

Attribute	**Description**
Name	MEMO_PRODUCT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DRAWER_BANK_EXPENSE_ACC

Attribute	Description	
Name	DRAWER_BANK_EXPENSE_ACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Bank-Product-Det-B

Attribute	Description	
Name	Bank-Product-Det-B	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRODUCT_CODE

Attribute	Description	
Name	PRODUCT_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Bank-Parameters-PK*
      - *BANK_CODE*
    - *Bank-Parameters-IO*
      - *BANK_CODE*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Bank-Parameters-PK

Attribute	Description
Name	Bank-Parameters-PK
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Bank-Parameters-IO

Attribute	Description
Name	Bank-Parameters-IO
Datatype	
Description	

TOP

BANK_CODE

Attribute	Description	
Name	BANK_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.42.ReopenCGRejErrCdMaint

ReopenCGRejErrCdMaint

2.42.1.CG-ReopenCGRejErrCdMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Reject-Acc-Errcd-Full*
    - *CLEARING_TYPE*
    - *ERR_CODE*
    - *ERR_CODE_DESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Reject-Acc-Errcd-Full

Attribute	Description
Name	Reject-Acc-Errcd-Full
Datatype	
Description	

TOP

CLEARING_TYPE

Attribute	Description
Name	CLEARING_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / IW,IC,OC,

TOP

ERR_CODE

Attribute	Description
Name	ERR_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

ERR_CODE_DESC

Attribute	Description
Name	ERR_CODE_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description

Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Reject-Acc-Errcd-IO
CLEARING_TYPE
ERR_CODE
MAKER
MAKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Reject-Acc-Errcd-IO

Attribute	Description
Name	Reject-Acc-Errcd-IO
Datatype	
Description	

TOP

CLEARING_TYPE

Attribute	Description
Name	CLEARING_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / IW,IC,OC,

TOP

ERR_CODE

Attribute	Description
Name	ERR_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.42.3.CG-ReopenCGRejErrCdMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Reject-Acc-Errcd-Full*
    - *CLEARING_TYPE*
    - *ERR_CODE*
    - *ERR_CODE_DESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Reject-Acc-Errcd-Full

Attribute	Description

Name	Reject-Acc-Errcd-Full
Datatype	
Description	

TOP

CLEARING_TYPE

Attribute	Description
Name	CLEARING_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / IW,IC,OC,

TOP

ERR_CODE

Attribute	Description
Name	ERR_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

ERR_CODE_DESC

Attribute	Description
Name	ERR_CODE_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**

Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Reject-Acc-Errcd-PK*
      - *CLEARING_TYPE*
      - *ERR_CODE*
    - *Reject-Acc-Errcd-IO*
      - *CLEARING_TYPE*
      - *ERR_CODE*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Reject-Acc-Errcd-PK

Attribute	Description
Name	Reject-Acc-Errcd-PK
Datatype	
Description	

TOP

CLEARING_TYPE

Attribute	Description	
Name	CLEARING_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

ERR_CODE

Attribute	Description	
Name	ERR_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

Reject-Acc-Errcd-IO

Attribute	Description
Name	Reject-Acc-Errcd-IO
Datatype	
Description	

TOP

CLEARING_TYPE

Attribute	Description	
Name	CLEARING_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	2

TOP

ERR_CODE

Attribute	Description	
Name	ERR_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.43.ReopenClgServicePoint

ReopenClgServicePoint

2.43.1.CG-ReopenClgServicePoint-Req-Full-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Clg-Service-Point-Full
DRAWEE_BANK
CITY
CLEARING_CITY
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Clg-Service-Point-Full

Attribute	Description
Name	Clg-Service-Point-Full
Datatype	
Description	

TOP

DRAWEE_BANK

Attribute	Description
Name	DRAWEE_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CITY

Attribute	Description
Name	CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

CLEARING_CITY

Attribute	Description
Name	CLEARING_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description

Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clg-Service-Point-IO*
    - *DRAWEE_BANK*
    - *CITY*
    - *MAKER*
    - *MAKERSTAMP*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Clg-Service-Point-IO

Attribute	Description
Name	Clg-Service-Point-IO
Datatype	
Description	

TOP

DRAWEE_BANK

Attribute	Description
Name	DRAWEE_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CITY

Attribute	Description
Name	CITY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 5

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

2.43.3.CG-ReopenClgServicePoint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clg-Service-Point-Full*
    - *DRAWEE_BANK*
    - *CITY*
    - *CLEARING_CITY*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Clg-Service-Point-Full

Attribute	Description

Name	Clg-Service-Point-Full
Datatype	
Description	

TOP

DRAWEE_BANK

Attribute	Description
Name	DRAWEE_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CITY

Attribute	Description
Name	CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

CLEARING_CITY

Attribute	Description
Name	CLEARING_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description

Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Clg-Service-Point-PK*
      - *DRAWEE_BANK*
      - *CITY*
    - *Clg-Service-Point-IO*
      - *DRAWEE_BANK*
      - *CITY*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Clg-Service-Point-PK

Attribute	Description
Name	Clg-Service-Point-PK
Datatype	
Description	

TOP

DRAWEE_BANK

Attribute	Description	
Name	DRAWEE_BANK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CITY

Attribute	Description	
Name	CITY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

Clg-Service-Point-IO

Attribute	Description
Name	Clg-Service-Point-IO
Datatype	
Description	

TOP

DRAWEE_BANK

Attribute	Description	
Name	DRAWEE_BANK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	9

TOP

CITY

Attribute	Description	
Name	CITY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	5

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.44.ReopenDocException

ReopenDocException

2.44.1.CG-ReopenDocException-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Doc-Exception-Full*
    - *ACCOUNT_NO*
    - *EXECUTIVE*
    - *MODIFICATION_DATE*
    - *BRANCH_CODE*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Doc-Excep-Det*
      - *DOCUMENT_TYPE*
      - *EXCEPTION_ALLOWED*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Doc-Exception-Full

Attribute	Description

Name	Doc-Exception-Full
Datatype	
Description	

TOP

ACCOUNT_NO

Attribute	Description
Name	ACCOUNT_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EXECUTIVE

Attribute	Description
Name	EXECUTIVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MODIFICATION_DATE

Attribute	Description
Name	MODIFICATION_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description

Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Doc-Excep-Det

Attribute	Description
Name	Doc-Excep-Det
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EXCEPTION_ALLOWED

Attribute	Description
Name	EXCEPTION_ALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Doc-Exception-IO
ACCOUNT_NO
BRANCH_CODE
MAKER
MAKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Doc-Exception-IO

Attribute	Description
Name	Doc-Exception-IO
Datatype	
Description	

TOP

ACCOUNT_NO

Attribute	Description
Name	ACCOUNT_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.44.3.CG-ReopenDocException-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Doc-Exception-Full*
    - *ACCOUNT_NO*
    - *EXECUTIVE*
    - *MODIFICATION_DATE*
    - *BRANCH_CODE*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Doc-Excep-Det*
      - *DOCUMENT_TYPE*
      - *EXCEPTION_ALLOWED*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Doc-Exception-Full

Attribute	Description
Name	Doc-Exception-Full
Datatype	
Description	

TOP

ACCOUNT_NO

Attribute	Description	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

EXECUTIVE

Attribute	Description	
Name	EXECUTIVE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MODIFICATION_DATE

Attribute	Description	
Name	MODIFICATION_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Doc-Excep-Det

Attribute	Description
Name	Doc-Excep-Det
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXCEPTION_ALLOWED

Attribute	**Description**
Name	EXCEPTION_ALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC

Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Doc-Exception-PK*
      - *ACCOUNT_NO*
      - *BRANCH_CODE*
    - *Doc-Exception-IO*
      - *ACCOUNT_NO*
      - *BRANCH_CODE*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Doc-Exception-PK

Attribute	Description
Name	Doc-Exception-PK
Datatype	
Description	

TOP

ACCOUNT_NO

Attribute	Description	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Doc-Exception-IO

Attribute	Description
Name	Doc-Exception-IO
Datatype	
Description	

TOP

ACCOUNT_NO

Attribute	Description	
Name	ACCOUNT_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	Restrictions	Description
	maxLength	20

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.45.ReopenDocType

ReopenDocType

2.45.1.CG-ReopenDocType-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Document-Type-Full*
    - *INSTRUMENT_TYPE*
    - *DOCUMENT_TYPE*
    - *DESCRIPTION*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Document-Type-Full

Attribute	Description
Name	Document-Type-Full
Datatype	
Description	

TOP

INSTRUMENT_TYPE

Attribute	Description
Name	INSTRUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description

Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Document-Type-IO
DOCUMENT_TYPE
MAKER
MAKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Document-Type-IO

Attribute	Description
Name	Document-Type-IO
Datatype	
Description	

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.45.3.CG-ReopenDocType-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Document-Type-Full*
    - *INSTRUMENT_TYPE*
    - *DOCUMENT_TYPE*
    - *DESCRIPTION*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Document-Type-Full

Attribute	Description

Name	Document-Type-Full
Datatype	
Description	

TOP

INSTRUMENT_TYPE

Attribute	Description
Name	INSTRUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,D

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**

Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Document-Type-PK*
      - *DOCUMENT_TYPE*
    - *Document-Type-IO*
      - *DOCUMENT_TYPE*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Document-Type-PK

Attribute	Description
Name	Document-Type-PK
Datatype	
Description	

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Document-Type-IO

Attribute	Description
Name	Document-Type-IO
Datatype	
Description	

TOP

DOCUMENT_TYPE

Attribute	Description	
Name	DOCUMENT_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.46.ReopenSecCode

ReopenSecCode

2.46.1.CG-ReopenSecCode-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Sectors-Full*
    - *SECTOR_CODE*
    - *SECTOR_DESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 0 nillable: true
Restrictions	Restrictions: Description pattern: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 0 nillable: true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description pattern: [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description pattern: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sttms-Sectors-Full

Attribute	Description
Name	Sttms-Sectors-Full
Datatype	
Description	

TOP

SECTOR_CODE

Attribute	Description
Name	SECTOR_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECTOR_DESC

Attribute	Description
Name	SECTOR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	255
minLength	0

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Sttms-Sectors-IO
SECTOR_CODE
MAKER
MAKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sttms-Sectors-IO

Attribute	Description
Name	Sttms-Sectors-IO
Datatype	
Description	

TOP

SECTOR_CODE

Attribute	Description
Name	SECTOR_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.46.3.CG-ReopenSecCode-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sttms-Sectors-Full*
    - *SECTOR_CODE*
    - *SECTOR_DESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**

Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sttms-Sectors-Full

Attribute	Description

Name	Sttms-Sectors-Full
Datatype	
Description	

TOP

SECTOR_CODE

Attribute	Description
Name	SECTOR_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECTOR_DESC

Attribute	Description
Name	SECTOR_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sttms-Sectors-PK*
      - *SECTOR_CODE*
    - *Sttms-Sectors-IO*
      - *SECTOR_CODE*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sttms-Sectors-PK

Attribute	Description
Name	Sttms-Sectors-PK
Datatype	
Description	

TOP

SECTOR_CODE

Attribute	Description	
Name	SECTOR_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Sttms-Sectors-IO

Attribute	Description
Name	Sttms-Sectors-IO
Datatype	
Description	

TOP

SECTOR_CODE

Attribute	Description	
Name	SECTOR_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.47.ReverseCollectionCheque

ReverseCollectionCheque

2.47.1.CG-ReverseCollectionCheque-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Master-Full*
    - *DEPOSITSLIP*
    - *TRN_BRANCH*
    - *REFERENCE_NO*
    - *BENE_DETAILS1*
    - *INSTRUMENT_CCY*
    - *INSTRUMENT_AMT*
    - *RECORD_STAT*
    - *AUTH_STAT*
    - *MAKER_ID*
    - *MAKER_DT_STAMP*
    - *CHECKER_ID*
    - *CHECKER_DT_STAMP*
    - *REMARKS*
    - *DEPOSITOR_NAME*
    - *BEN_ACCOUNT*

Coll-Dispatch-Details

INSTRUMENT_NO

INSTRUMENT_AMT

INSTRUMENT_DATE

DRAWEE_ACC_NO

DRAWEE_BANK

DRAWEE_BRANCH

DRAWEE_CITY

DEPOSIT_CITY

DOCUMENT_TYPE

COLLECTION_PRO_EXC

ROUTING_GL_EXC

CLEARING_CITY

CORRESPONDENT_BANK

CORRESPONDENT_BRANCH

COLLECTION_TYPE

TRN_REF_NO

DISPATCH_REF_NO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Clearing-Master-Full

Attribute	Description
Name	Clearing-Master-Full
Datatype	
Description	

TOP

DEPOSITSLIP

Attribute	Description	
Name	DEPOSITSLIP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TRN_BRANCH

Attribute	Description	
Name	TRN_BRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REFERENCE_NO

Attribute	Description

Name	REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BENE_DETAILS1

Attribute	**Description**
Name	BENE_DETAILS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRUMENT_CCY

Attribute	**Description**
Name	INSTRUMENT_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTRUMENT_AMT

Attribute	**Description**
Name	INSTRUMENT_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

RECORD_STAT

Attribute	**Description**
Name	RECORD_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

AUTH_STAT

Attribute	Description	
Name	AUTH_STAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,U

TOP

MAKER_ID

Attribute	Description	
Name	MAKER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKER_DT_STAMP

Attribute	Description	
Name	MAKER_DT_STAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER_ID

Attribute	Description	
Name	CHECKER_ID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DEPOSITOR_NAME

Attribute	Description
Name	DEPOSITOR_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BEN_ACCOUNT

Attribute	Description
Name	BEN_ACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Coll-Dispatch-Details

Attribute	Description
Name	Coll-Dispatch-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSTRUMENT_NO

Attribute	Description
Name	INSTRUMENT_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRUMENT_AMT

Attribute	Description
Name	INSTRUMENT_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INSTRUMENT_DATE

Attribute	Description
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRAWEE_ACC_NO

Attribute	Description
Name	DRAWEE_ACC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	16

TOP

DRAWEE_BANK

Attribute	Description
Name	DRAWEE_BANK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

DRAWEE_BRANCH

Attribute	Description
Name	DRAWEE_BRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

DRAWEE_CITY

Attribute	Description
Name	DRAWEE_CITY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 5

TOP

DEPOSIT_CITY

Attribute	Description
Name	DEPOSIT_CITY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 5

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

COLLECTION_PRO_EXC

Attribute	Description
Name	COLLECTION_PRO_EXC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ROUTING_GL_EXC

Attribute	Description
Name	ROUTING_GL_EXC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CLEARING_CITY

Attribute	Description
Name	CLEARING_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

CORRESPONDENT_BANK

Attribute	Description
Name	CORRESPONDENT_BANK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CORRESPONDENT_BRANCH

Attribute	Description
Name	CORRESPONDENT_BRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COLLECTION_TYPE

Attribute	Description
Name	COLLECTION_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: E,O

TOP

TRN_REF_NO

Attribute	Description
Name	TRN_REF_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

DISPATCH_REF_NO

Attribute	Description
Name	DISPATCH_REF_NO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 21

TOP

2.47.2.CG-ReverseCollectionCheque-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Master-IO*
    - *REFERENCE_NO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Clearing-Master-IO

Attribute	Description
Name	Clearing-Master-IO
Datatype	
Description	

TOP

REFERENCE_NO

Attribute	Description	
Name	REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.47.3.CG-ReverseCollectionCheque-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Master-Full*
    - *DEPOSITSLIP*
    - *TRN_BRANCH*
    - *REFERENCE_NO*
    - *BENE_DETAILS1*
    - *INSTRUMENT_CCY*
    - *INSTRUMENT_AMT*
    - *RECORD_STAT*
    - *AUTH_STAT*
    - *MAKER_ID*
    - *MAKER_DT_STAMP*
    - *CHECKER_ID*
    - *CHECKER_DT_STAMP*
    - *REMARKS*
    - *DEPOSITOR_NAME*
    - *BEN_ACCOUNT*
    - *Coll-Dispatch-Details*
      - *INSTRUMENT_NO*
      - *INSTRUMENT_AMT*

INSTRUMENT_DATE
DRAWEE_ACC_NO
DRAWEE_BANK
DRAWEE_BRANCH
DRAWEE_CITY
DEPOSIT_CITY
DOCUMENT_TYPE
COLLECTION_PRO_EXC
ROUTING_GL_EXC
CLEARING_CITY
CORRESPONDENT_BANK
CORRESPONDENT_BRANCH
COLLECTION_TYPE
TRN_REF_NO
DISPATCH_REF_NO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Clearing-Master-Full

Attribute	Description
Name	Clearing-Master-Full
Datatype	
Description	

TOP

DEPOSITSLIP

Attribute	Description	
Name	DEPOSITSLIP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TRN_BRANCH

Attribute	Description
Name	TRN_BRANCH
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REFERENCE_NO

Attribute	Description	
Name	REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BENE_DETAILS1

Attribute	Description	
Name	BENE_DETAILS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRUMENT_CCY

Attribute	Description	
Name	INSTRUMENT_CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INSTRUMENT_AMT

Attribute	Description	
Name	INSTRUMENT_AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

RECORD_STAT

Attribute	Description	
Name	RECORD_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTH_STAT

Attribute	Description	
Name	AUTH_STAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U

TOP

MAKER_ID

Attribute	Description	
Name	MAKER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKER_DT_STAMP

Attribute	Description	
Name	MAKER_DT_STAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

DEPOSITOR_NAME

Attribute	Description
Name	DEPOSITOR_NAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 35

TOP

BEN_ACCOUNT

Attribute	Description
Name	BEN_ACCOUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Coll-Dispatch-Details

Attribute	**Description**
Name	Coll-Dispatch-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSTRUMENT_NO

Attribute	**Description**
Name	INSTRUMENT_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRUMENT_AMT

Attribute	**Description**
Name	INSTRUMENT_AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INSTRUMENT_DATE

Attribute	**Description**
Name	INSTRUMENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRAWEE_ACC_NO

Attribute	Description
Name	DRAWEE_ACC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DRAWEE_BANK

Attribute	Description
Name	DRAWEE_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DRAWEE_BRANCH

Attribute	Description
Name	DRAWEE_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DRAWEE_CITY

Attribute	Description
Name	DRAWEE_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

DEPOSIT_CITY

Attribute	Description

Name	DEPOSIT_CITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

DOCUMENT_TYPE

Attribute	**Description**
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

COLLECTION_PRO_EXC

Attribute	**Description**
Name	COLLECTION_PRO_EXC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ROUTING_GL_EXC

Attribute	**Description**
Name	ROUTING_GL_EXC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CLEARING_CITY

Attribute	**Description**
Name	CLEARING_CITY
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

CORRESPONDENT_BANK

Attribute	**Description**
Name	CORRESPONDENT_BANK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CORRESPONDENT_BRANCH

Attribute	**Description**
Name	CORRESPONDENT_BRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COLLECTION_TYPE

Attribute	**Description**
Name	COLLECTION_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,O

TOP

TRN_REF_NO

Attribute	**Description**
Name	TRN_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	16

TOP

DISPATCH_REF_NO

Attribute	Description	
Name	DISPATCH_REF_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	21

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Clearing-Master-PK*
      - *REFERENCE_NO*
    - *Clearing-Master-IO*
      - *REFERENCE_NO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Clearing-Master-PK

Attribute	Description
Name	Clearing-Master-PK
Datatype	
Description	

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Clearing-Master-IO

Attribute	Description
Name	Clearing-Master-IO
Datatype	
Description	

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.48.AuthorizeClearingReject

Authorize Cleading Reject

2.48.1.CGRejection-Auth-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Reject-Details*
    - *SCODE*
    - *XREF*
    - *TXNBRN*
    - *REMACCOUNT*
    - *INSTRNO*
    - *ROUTINGNO*
    - *REASONCODE*
    - *REJECTREASON*
    - *FCCREF*
    - *STATUS*
    - *BENACCOUNT*
    - *INSTRCCY*
    - *INSTRAMT*
    - *INSTRDATE*
    - *CHEQUEISSUEDATE*

TXNDATE

VALDATE

LATECLG

ENDPOINT

MAKERID

MAKERSTAMP

CHECKERID

CHECKERSTAMP

MODNO

RECORDSTAT

AUTHSTAT

ONCEAUTH

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the request message format for authorisation of the rejected clearing contract

TOP

Clearing-Reject-Details

Attribute	Description
Name	Clearing-Reject-Details
Datatype	
Description	Clearing Reject Details

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

TXNBRN

Attribute	Description	
Name	TXNBRN	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

REASONCODE

Attribute	Description
Name	REASONCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 3 pattern / [a-zA-Z0-9]*

TOP

REJECTREASON

Attribute	Description
Name	REJECTREASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z0-9]{16}

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

BENACCOUNT

Attribute	Description
Name	BENACCOUNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20 Restrictions: pattern — Description: [a-zA-Z0-9]*

TOP

INSTRCCY

Attribute	Description
Name	INSTRCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [A-Z]{3}

TOP

INSTRAMT

Attribute	Description
Name	INSTRAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHEQUEISSUEDATE

Attribute	Description
Name	CHEQUEISSUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

LATECLG

Attribute	Description	
Name	LATECLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ENDPOINT

Attribute	Description	
Name	ENDPOINT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

2.48.2.CGRejection-Auth-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Reject-Details-IO*
    - *XREF*
    - *FCCREF*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the request message format for authorisation of the rejected clearing contract

TOP

Clearing-Reject-Details-IO

Attribute	Description
Name	Clearing-Reject-Details-IO
Datatype	
Description	Clearing Reject Details IO Type

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

2.48.3.CGRejection-Auth-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Reject-Details*
    - *SCODE*
    - *XREF*
    - *TXNBRN*
    - *REMACCOUNT*
    - *INSTRNO*
    - *ROUTINGNO*
    - *REASONCODE*
    - *REJECTREASON*
    - *FCCREF*
    - *STATUS*
    - *BENACCOUNT*
    - *INSTRCCY*
    - *INSTRAMT*
    - *INSTRDATE*
    - *CHEQUEISSUEDATE*
    - *TXNDATE*
    - *VALDATE*
    - *LATECLG*

ENDPOINT
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
MODNO
RECORDSTAT
AUTHSTAT
ONCEAUTH
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the response message format for authorisation of the rejected clearing contract

TOP

Clearing-Reject-Details

Attribute	Description
Name	Clearing-Reject-Details
Datatype	
Description	Clearing Reject Details

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

TXNBRN

Attribute	Description
Name	TXNBRN

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

REASONCODE

Attribute	Description
Name	REASONCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 3 pattern / [a-zA-Z0-9]*

TOP

REJECTREASON

Attribute	Description
Name	REJECTREASON

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

FCCREF

Attribute	**Description**
Name	FCCREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

STATUS

Attribute	**Description**
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BENACCOUNT

Attribute	**Description**
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

INSTRCCY

Attribute	**Description**
Name	INSTRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

INSTRAMT

Attribute	Description	
Name	INSTRAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

INSTRDATE

Attribute	Description	
Name	INSTRDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CHEQUEISSUEDATE

Attribute	Description	
Name	CHEQUEISSUEDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

TXNDATE

Attribute	Description	
Name	TXNDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

VALDATE

Attribute	Description
Name	VALDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATECLG

Attribute	Description
Name	LATECLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 0 Restrictions: totalDigits — Description: 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: O,C

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U

TOP

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Error Response Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Warning Response Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.48.4.CGRejection-Auth-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Clearing-Reject-Details-IO*
      - *SCODE*
      - *XREF*
      - *TXNBRN*
      - *REMACCOUNT*
      - *INSTRNO*
      - *ROUTINGNO*
      - *REASONCODE*
      - *REJECTREASON*
    - *Clearing-Reject-Details-PK*
      - *XREF*
      - *FCCREF*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**

Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the response message format for authorisation of the rejected clearing contract

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Clearing-Reject-Details-IO

Attribute	Description
Name	Clearing-Reject-Details-IO
Datatype	
Description	Clearing Reject Details IO Type

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

TXNBRN

Attribute	Description	
Name	TXNBRN	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

REASONCODE

Attribute	Description
Name	REASONCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 3 pattern / [a-zA-Z0-9]*

TOP

REJECTREASON

Attribute	Description
Name	REJECTREASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Clearing-Reject-Details-PK

Attribute	Description
Name	Clearing-Reject-Details-PK
Datatype	
Description	Clearing Reject Details PK Type

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

FCCREF

Attribute	Description	
Name	FCCREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Error Response Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Warning Response Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.49.CreateClearingReject

Create Clearing Reject

2.49.1.CGRejection-Create-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Reject-Details*
    - *SCODE*
    - *XREF*
    - *TXNBRN*
    - *REMACCOUNT*
    - *INSTRNO*
    - *ROUTINGNO*
    - *REASONCODE*
    - *REJECTREASON*
    - *FCCREF*
    - *STATUS*
    - *BENACCOUNT*
    - *INSTRCCY*
    - *INSTRAMT*
    - *INSTRDATE*
    - *CHEQUEISSUEDATE*

TXNDATE

VALDATE

LATECLG

ENDPOINT

MAKERID

MAKERSTAMP

CHECKERID

CHECKERSTAMP

MODNO

RECORDSTAT

AUTHSTAT

ONCEAUTH

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the request message format for rejection of the updated clearing contract

TOP

Clearing-Reject-Details

Attribute	Description
Name	Clearing-Reject-Details
Datatype	
Description	Creation Of Clearing Reject Details.

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

TXNBRN

Attribute	Description	
Name	TXNBRN	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

REASONCODE

Attribute	Description
Name	REASONCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 3 pattern / [a-zA-Z0-9]*

TOP

REJECTREASON

Attribute	Description
Name	REJECTREASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BENACCOUNT

Attribute	Description
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

INSTRCCY

Attribute	Description
Name	INSTRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

INSTRAMT

Attribute	Description
Name	INSTRAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHEQUEISSUEDATE

Attribute	Description
Name	CHEQUEISSUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

LATECLG

Attribute	Description	
Name	LATECLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ENDPOINT

Attribute	Description	
Name	ENDPOINT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Reject-Details-IO*
    - *SCODE*
    - *XREF*
    - *TXNBRN*
    - *REMACCOUNT*
    - *INSTRNO*
    - *ROUTINGNO*
    - *REASONCODE*
    - *REJECTREASON*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the request message format for rejection of the updated clearing contract

TOP

Clearing-Reject-Details-IO

Attribute	Description
Name	Clearing-Reject-Details-IO
Datatype	
Description	Creation Of Clearing Reject Details IO Type

TOP

SCODE

Attribute	Description
Name	SCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

TXNBRN

Attribute	Description
Name	TXNBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	27

TOP

REASONCODE

Attribute	Description	
Name	REASONCODE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	3
	pattern	[a-zA-Z0-9]*

TOP

REJECTREASON

Attribute	Description	
Name	REJECTREASON	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

2.49.3.CGRejection-Create-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Reject-Details*
    - *SCODE*
    - *XREF*
    - *TXNBRN*
    - *REMACCOUNT*
    - *INSTRNO*
    - *ROUTINGNO*
    - *REASONCODE*
    - *REJECTREASON*
    - *FCCREF*
    - *STATUS*
    - *BENACCOUNT*
    - *INSTRCCY*
    - *INSTRAMT*
    - *INSTRDATE*
    - *CHEQUEISSUEDATE*
    - *TXNDATE*
    - *VALDATE*
    - *LATECLG*

ENDPOINT
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
MODNO
RECORDSTAT
AUTHSTAT
ONCEAUTH
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the response message format for rejection of the updated clearing contract

TOP

Clearing-Reject-Details

Attribute	Description
Name	Clearing-Reject-Details
Datatype	
Description	Creation Of Clearing Reject Details

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

TXNBRN

Attribute	Description
Name	TXNBRN

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

REASONCODE

Attribute	Description
Name	REASONCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 3 pattern / [a-zA-Z0-9]*

TOP

REJECTREASON

Attribute	Description
Name	REJECTREASON

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

FCCREF

Attribute	**Description**
Name	FCCREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

STATUS

Attribute	**Description**
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BENACCOUNT

Attribute	**Description**
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

INSTRCCY

Attribute	**Description**
Name	INSTRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

INSTRAMT

Attribute	Description	
Name	INSTRAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

INSTRDATE

Attribute	Description	
Name	INSTRDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CHEQUEISSUEDATE

Attribute	Description	
Name	CHEQUEISSUEDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

TXNDATE

Attribute	Description	
Name	TXNDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

VALDATE

Attribute	Description
Name	VALDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATECLG

Attribute	Description
Name	LATECLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 0 Restrictions: totalDigits — Description: 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Warning Response Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.49.4.CGRejection-Create-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Clearing-Reject-Details-IO*
      - *SCODE*
      - *XREF*
      - *TXNBRN*
      - *REMACCOUNT*
      - *INSTRNO*
      - *ROUTINGNO*
      - *REASONCODE*
      - *REJECTREASON*
    - *Clearing-Reject-Details-PK*
      - *XREF*
      - *FCCREF*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**

Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the response message format for rejection of the updated clearing contract

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Clearing-Reject-Details-IO

Attribute	Description
Name	Clearing-Reject-Details-IO
Datatype	
Description	Creation Of Clearing Reject IO Type

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

TXNBRN

Attribute	Description	
Name	TXNBRN	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

REASONCODE

Attribute	Description
Name	REASONCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 3 pattern / [a-zA-Z0-9]*

TOP

REJECTREASON

Attribute	Description
Name	REJECTREASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Clearing-Reject-Details-PK

Attribute	Description
Name	Clearing-Reject-Details-PK
Datatype	
Description	Creation Of Clearing Reject PK Type

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z0-9]{16}

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Warning Response Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.50.QueryClearingReject

Query Clearing Reject

2.50.1.CGRejection-Query-Req-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Clearing-Reject-Details-IO
XREF
FCCREF

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Clearing-Reject-Details-IO

Attribute	Description
Name	Clearing-Reject-Details-IO
Datatype	
Description	

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

FCCREF

Attribute	Description
Name	FCCREF

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

2.50.2.CGRejection-Query-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Reject-Details*
    - *SCODE*
    - *XREF*
    - *TXNBRN*
    - *REMACCOUNT*
    - *INSTRNO*
    - *ROUTINGNO*
    - *REASONCODE*
    - *REJECTREASON*
    - *FCCREF*
    - *STATUS*
    - *BENACCOUNT*
    - *INSTRCCY*
    - *INSTRAMT*
    - *INSTRDATE*
    - *CHEQUEISSUEDATE*
    - *TXNDATE*
    - *VALDATE*
    - *LATECLG*

ENDPOINT
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
MODNO
RECORDSTAT
AUTHSTAT
ONCEAUTH
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	

Attributes		
	Attribute	**Description**
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the response message format for the Query of cheque rejection

TOP

Clearing-Reject-Details

Attribute	Description
Name	Clearing-Reject-Details
Datatype	
Description	Query Of Clearing Reject Details Type

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

TXNBRN

Attribute	Description
Name	TXNBRN

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

REASONCODE

Attribute	Description
Name	REASONCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 3 pattern / [a-zA-Z0-9]*

TOP

REJECTREASON

Attribute	Description
Name	REJECTREASON

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCCREF

Attribute	**Description**
Name	FCCREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

STATUS

Attribute	**Description**
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BENACCOUNT

Attribute	**Description**
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

INSTRCCY

Attribute	**Description**
Name	INSTRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

INSTRAMT

Attribute	Description	
Name	INSTRAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

INSTRDATE

Attribute	Description	
Name	INSTRDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CHEQUEISSUEDATE

Attribute	Description	
Name	CHEQUEISSUEDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

TXNDATE

Attribute	Description	
Name	TXNDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

VALDATE

Attribute	Description
Name	VALDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATECLG

Attribute	Description
Name	LATECLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: fractionDigits; Description: 0 Restrictions: totalDigits; Description: 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: O,C

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U

TOP

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Error Response Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Warning Response Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.51.AuthorizeStopPayment

Authorisation of Stop Payment

2.51.1.CGStopPayment-Auth-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stop-Payment-Details*
    - *SCODE*
    - *XREF*
    - *BRN*
    - *ACC*
    - *STOPPAYNO*
    - *STOPPAYTYPE*
    - *STARTCHKNO*
    - *ENDCHKNO*
    - *AMT*
    - *EFFDT*
    - *EXPDT*
    - *CONF*
    - *REM*
    - *CCY*
    - *ACCTITLE*

MAKERID

MAKERSTAMP

CHECKERID

CHECKERSTAMP

MODNO

RECORDSTAT

AUTHSTAT

ONCEAUTH

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the request message format for authorisation of the Stop Payment

TOP

Stop-Payment-Details

Attribute	Description
Name	Stop-Payment-Details
Datatype	
Description	Includes the Clearing Authorisation of Stop Payment Details.

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Restrictions	Restrictions: maxLength = 20; pattern = [a-zA-Z0-9]*

TOP

STOPPAYNO

Attribute	Description
Name	STOPPAYNO
Datatype	String
Description	
Restrictions	Restrictions: maxLength = 16; pattern = [a-zA-Z0-9]*

TOP

STOPPAYTYPE

Attribute	Description
Name	STOPPAYTYPE
Datatype	String
Description	
Restrictions	Restrictions: maxLength = 1

TOP

STARTCHKNO

Attribute	Description
Name	STARTCHKNO
Datatype	String
Description	
Restrictions	Restrictions: maxLength = 16

TOP

ENDCHKNO

Attribute	Description
Name	ENDCHKNO
Datatype	String
Description	
Restrictions	Restrictions: maxLength = 16

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	

TOP

CONF

Attribute	Description
Name	CONF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

ACCTITLE

Attribute	Description
Name	ACCTITLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

2.51.2.CGStopPayment-Auth-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stop-Payment-Details-IO*
    - *XREF*
    - *STOPPAYNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the request message format for authorisation of the Stop Payment

TOP

Stop-Payment-Details-IO

Attribute	Description
Name	Stop-Payment-Details-IO
Datatype	
Description	Includes the Clearing Authorisation of Stop Payment IO Details.

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

STOPPAYNO

Attribute	Description
Name	STOPPAYNO
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** maxLength / 16 pattern / [a-zA-Z0-9]*

TOP

2.51.3.CGStopPayment-Auth-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stop-Payment-Details*
    - *SCODE*
    - *XREF*
    - *BRN*
    - *ACC*
    - *STOPPAYNO*
    - *STOPPAYTYPE*
    - *STARTCHKNO*
    - *ENDCHKNO*
    - *AMT*
    - *EFFDT*
    - *EXPDT*
    - *CONF*
    - *REM*
    - *CCY*
    - *ACCTITLE*
    - *MAKERID*
    - *MAKERSTAMP*
    - *CHECKERID*

CHECKERSTAMP
MODNO
RECORDSTAT
AUTHSTAT
ONCEAUTH
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the response message format for authorisation of the Stop Payment

TOP

Stop-Payment-Details

Attribute	Description
Name	Stop-Payment-Details
Datatype	
Description	Includes the clearing Authorisation of Stop Payment Details.

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

STOPPAYNO

Attribute	Description
Name	STOPPAYNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16 pattern / [a-zA-Z0-9]*

TOP

STOPPAYTYPE

Attribute	Description
Name	STOPPAYTYPE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STARTCHKNO

Attribute	Description
Name	STARTCHKNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ENDCHKNO

Attribute	Description
Name	ENDCHKNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	

TOP

CONF

Attribute	Description
Name	CONF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

ACCTITLE

Attribute	Description	
Name	ACCTITLE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Stop-Payment-Details-IO*
      - *XREF*
      - *STOPPAYNO*
    - *Stop-Payment-Details-PK*
      - *XREF*
      - *STOPPAYNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description

Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the response message format for authorisation of the Stop Payment

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Stop-Payment-Details-IO

Attribute	Description
Name	Stop-Payment-Details-IO
Datatype	
Description	Includes the Authorisation of Stop Payment IO Details.

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

STOPPAYNO

Attribute	Description
Name	STOPPAYNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16; pattern / [a-zA-Z0-9]*

TOP

Stop-Payment-Details-PK

Attribute	Description
Name	Stop-Payment-Details-PK
Datatype	
Description	Includes the Authorisation of Stop Payment Primary Key Details.

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

STOPPAYNO

Attribute	Description
Name	STOPPAYNO

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16 pattern / [a-zA-Z0-9]*

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.52.CreateStopPayment

Input of Stop Payment

2.52.1.CGStopPayment-Create-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stop-Payment-Details*
    - *SCODE*
    - *XREF*
    - *BRN*
    - *ACC*
    - *STOPPAYNO*
    - *STOPPAYTYPE*
    - *STARTCHKNO*
    - *ENDCHKNO*
    - *AMT*
    - *EFFDT*
    - *EXPDT*
    - *CONF*
    - *REM*
    - *CCY*
    - *ACCTITLE*

MAKERID

MAKERSTAMP

CHECKERID

CHECKERSTAMP

MODNO

RECORDSTAT

AUTHSTAT

ONCEAUTH

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>nillable</td><td>true</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the request message format for Stop Payment

TOP

Stop-Payment-Details

Attribute	Description
Name	Stop-Payment-Details
Datatype	
Description	Includes the Clearing Input of Stop Payment Details.

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Restrictions	Restrictions: maxLength = 20; pattern = [a-zA-Z0-9]*

TOP

STOPPAYNO

Attribute	Description
Name	STOPPAYNO
Datatype	String
Description	
Restrictions	Restrictions: maxLength = 16; pattern = [a-zA-Z0-9]*

TOP

STOPPAYTYPE

Attribute	Description
Name	STOPPAYTYPE
Datatype	String
Description	
Restrictions	Restrictions: maxLength = 1

TOP

STARTCHKNO

Attribute	Description
Name	STARTCHKNO
Datatype	String
Description	
Restrictions	Restrictions: maxLength = 16

TOP

ENDCHKNO

Attribute	Description
Name	ENDCHKNO
Datatype	String
Description	
Restrictions	Restrictions: maxLength = 16

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	

TOP

CONF

Attribute	Description
Name	CONF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

ACCTITLE

Attribute	Description
Name	ACCTITLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stop-Payment-Details-IO*
    - *SCODE*
    - *XREF*
    - *BRN*
    - *ACC*
    - *STOPPAYTYPE*
    - *STARTCHKNO*
    - *ENDCHKNO*
    - *AMT*
    - *EFFDT*
    - *EXPDT*
    - *REM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description

Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the request message format for Stop Payment

TOP

Stop-Payment-Details-IO

Attribute	Description
Name	Stop-Payment-Details-IO
Datatype	
Description	Includes the clearing Input of Stop Payment Details.

TOP

SCODE

Attribute	Description
Name	SCODE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**
	maxLength / 20

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**
	length / 3
	pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**
	maxLength / 20
	pattern / [a-zA-Z0-9]*

TOP

STOPPAYTYPE

Attribute	Description
Name	STOPPAYTYPE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**
	maxLength / 1

TOP

STARTCHKNO

Attribute	Description

Name	STARTCHKNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ENDCHKNO

Attribute	Description
Name	ENDCHKNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	255

TOP

2.52.3.CGStopPayment-Create-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stop-Payment-Details*
    - *SCODE*
    - *XREF*
    - *BRN*
    - *ACC*
    - *STOPPAYNO*
    - *STOPPAYTYPE*
    - *STARTCHKNO*
    - *ENDCHKNO*
    - *AMT*
    - *EFFDT*
    - *EXPDT*
    - *CONF*
    - *REM*
    - *CCY*
    - *ACCTITLE*
    - *MAKERID*
    - *MAKERSTAMP*
    - *CHECKERID*

CHECKERSTAMP
MODNO
RECORDSTAT
AUTHSTAT
ONCEAUTH
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the response message format for Stop Payment clearing contract

TOP

Stop-Payment-Details

Attribute	Description
Name	Stop-Payment-Details
Datatype	
Description	Includes the clearing Input of Stop Payment Details.

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

STOPPAYNO

Attribute	Description
Name	STOPPAYNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16 pattern / [a-zA-Z0-9]*

TOP

STOPPAYTYPE

Attribute	Description
Name	STOPPAYTYPE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STARTCHKNO

Attribute	Description
Name	STARTCHKNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ENDCHKNO

Attribute	Description
Name	ENDCHKNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	

TOP

CONF

Attribute	Description
Name	CONF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

ACCTITLE

Attribute	Description	
Name	ACCTITLE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.52.4.CGStopPayment-Create-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Stop-Payment-Details-IO*
      - *SCODE*
      - *XREF*
      - *BRN*
      - *ACC*
      - *STOPPAYTYPE*
      - *STARTCHKNO*
      - *ENDCHKNO*
      - *AMT*
      - *EFFDT*
      - *EXPDT*
      - *REM*
    - *Stop-Payment-Details-PK*
      - *XREF*
      - *STOPPAYNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	

Description	This XSD gives the response message format for Stop Payment of the updated clearing contract

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Stop-Payment-Details-IO

Attribute	Description
Name	Stop-Payment-Details-IO
Datatype	
Description	Includes the Clearing Input of Stop Payment IO Details.

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

STOPPAYTYPE

Attribute	Description
Name	STOPPAYTYPE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STARTCHKNO

Attribute	Description
Name	STARTCHKNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ENDCHKNO

Attribute	Description
Name	ENDCHKNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Stop-Payment-Details-PK

Attribute	Description
Name	Stop-Payment-Details-PK
Datatype	
Description	Includes the Clearing Input of Stop Payment Primary Key Details.

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

STOPPAYNO

Attribute	Description
Name	STOPPAYNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16 pattern / [a-zA-Z0-9]*

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response.

Attributes	Attribute	Description
	minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.53.QueryStopPayment

Query of Stop Payment

2.53.1.CGStopPayment-Query-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stop-Payment-Details-IO*
    - *XREF*
    - *STOPPAYNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the request message format for the Query of Stop Payment

TOP

Stop-Payment-Details-IO

Attribute	Description
Name	Stop-Payment-Details-IO
Datatype	
Description	Includes the clearing Query of Stop Payment Details.

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

STOPPAYNO

Attribute	Description

Name	STOPPAYNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16 pattern / [a-zA-Z0-9]*

TOP

2.53.2.CGStopPayment-Query-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stop-Payment-Details*
    - *SCODE*
    - *XREF*
    - *BRN*
    - *ACC*
    - *STOPPAYNO*
    - *STOPPAYTYPE*
    - *STARTCHKNO*
    - *ENDCHKNO*
    - *AMT*
    - *EFFDT*
    - *EXPDT*
    - *CONF*
    - *REM*
    - *CCY*
    - *ACCTITLE*
    - *MAKERID*
    - *MAKERSTAMP*
    - *CHECKERID*

CHECKERSTAMP
MODNO
RECORDSTAT
AUTHSTAT
ONCEAUTH
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the response message format for the Query of Stop Payment

TOP

Stop-Payment-Details

Attribute	Description
Name	Stop-Payment-Details
Datatype	
Description	Includes the clearing Query of Stop Payment Details.

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

STOPPAYNO

Attribute	Description
Name	STOPPAYNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16 pattern / [a-zA-Z0-9]*

TOP

STOPPAYTYPE

Attribute	Description
Name	STOPPAYTYPE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STARTCHKNO

Attribute	Description
Name	STARTCHKNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ENDCHKNO

Attribute	Description
Name	ENDCHKNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	

TOP

CONF

Attribute	Description
Name	CONF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

ACCTITLE

Attribute	Description	
Name	ACCTITLE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Error Warning Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.54.AuthorizeTransaction

Authorisation of Clearing Transaction

2.54.1.CGTransaction-Auth-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transaction-Details*
    - *XREF*
    - *SCODE*
    - *STATUS*
    - *BATCHTOTAMT*
    - *CONSOLIDATED*
    - *DEPSLIP*
    - *BENACCOUNT1*
    - *Clearing-Details*
      - *PRODUCT*
      - *FCCREF*
      - *ESN*
      - *REMACCOUNT*
      - *INSTRNO*
      - *INSTRCCY*
      - *INSTRAMT*

INSTRDATE
CHEQUEISSUEDATE
TXNDATE
VALDATE
LATECLG
ROUTINGNO
SERIALNO
ENTRYNO
REGCC
SPLCHQ
TXNBRN
BENACCOUNT
TXNCCY
ENDPOINT
CHKBUKNUM
ACCCY
ACCCYAMT
ROUTBNKCOD
ROUTBRNCOD
ROUTSECTCOD
BENCUSTID
REMCUST
ACCBRN
INSTRNO2
ERRCODE
LCYCHGAMT
CHGCCYLCYXRT
LCYCHGAMT1
CHGCCYLCYXRT1
LCYCHGAMT2
CHGCCYLCYXRT2
LCYCHGAMT3
CHGCCYLCYXRT3
LCYCHGAMT4
CHGCCYLCYXRT4
ACYTOTCHGAMT
CR_CARD_NO
CC_HOLDER_NAME
REMBANK
REMBRANCH
BENBANK
BENBRANCH
BENCCY
ROUTBNKNAM

ROUTBRNNAM
ROUTSECTDISC
LCYTOTCHGAMT
TCYTOTCHGAMT
DENMCCY1
DENMAMT1
DENMCCY2
DENMAMT2
XRATE
DIRECTION
REMDET1
REMDET2
REMDET3
BENDET1
BENDET2
BENDET3
LOCLCLEARING
CHQVERDIGIT
TXNID
ORGTXNID
DIN
DINDATE
CUSTDATE
MODULE
MODREFNO
REJREASON
CUSTID
ACCTITLE
CUSTNAME
REMARKS
ACTAMT
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
MODNO
RECORDSTAT
AUTHSTAT
ONCEAUTH
STATUS
RECTYPE
TXNCD
DOCTYPE

Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG

TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE

FIELD_VALUE
VAL_TYPE
Charge-Details
CHGCOMP
WAIVER
CHGAMT
CHGCCY
MISHEAD
TXNCODE
NETTINGIND
CHGGL
TYPE
LCYCHG
XRATE
TCYCHG
TCYXRATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength 12; pattern [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for information relating to the Clearing Transaction that has to be Authorized

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the information related to Authorisation of Clearing Transaction.

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

STATUS

Attribute	Description
Name	STATUS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BATCHTOTAMT

Attribute	**Description**
Name	BATCHTOTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CONSOLIDATED

Attribute	**Description**
Name	CONSOLIDATED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEPSLIP

Attribute	**Description**
Name	DEPSLIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

BENACCOUNT1

Attribute	**Description**
Name	BENACCOUNT1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded

TOP

PRODUCT

Attribute	Description
Name	PRODUCT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**
	length / 4
	pattern / [a-zA-Z0-9]{4}

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	fractionDigits / 0
	totalDigits / 10

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRCCY

Attribute	Description
Name	INSTRCCY
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

INSTRAMT

Attribute	Description
Name	INSTRAMT
Datatype	Number
Description	
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	

TOP

CHEQUEISSUEDATE

Attribute	Description
Name	CHEQUEISSUEDATE
Datatype	Date
Description	

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	

TOP

VALDATE

Attribute	Description	
Name	VALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATECLG

Attribute	Description	
Name	LATECLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ROUTINGNO

Attribute	Description	
Name	ROUTINGNO	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	27

TOP

SERIALNO

Attribute	Description

Name	SERIALNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ENTRYNO

Attribute	**Description**
Name	ENTRYNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 9

TOP

REGCC

Attribute	**Description**
Name	REGCC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SPLCHQ

Attribute	**Description**
Name	SPLCHQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TXNBRN

Attribute	**Description**
Name	TXNBRN
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

BENACCOUNT

Attribute	Description	
Name	BENACCOUNT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

TXNCCY

Attribute	Description	
Name	TXNCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

ENDPOINT

Attribute	Description	
Name	ENDPOINT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

CHKBUKNUM

Attribute	Description	
Name	CHKBUKNUM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	2000

TOP

ACCCY

Attribute	Description	
Name	ACCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

ACCCYAMT

Attribute	Description	
Name	ACCCYAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

ROUTBNKCOD

Attribute	Description	
Name	ROUTBNKCOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

ROUTBRNCOD

Attribute	Description	
Name	ROUTBRNCOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

ROUTSECTCOD

Attribute	**Description**
Name	ROUTSECTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z_0-9]*

TOP

BENCUSTID

Attribute	**Description**
Name	BENCUSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

REMCUST

Attribute	**Description**
Name	REMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ACCBRN

Attribute	**Description**
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

INSTRNO2

Attribute	Description	
Name	INSTRNO2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

ERRCODE

Attribute	Description	
Name	ERRCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

TOP

LCYCHGAMT

Attribute	Description	
Name	LCYCHGAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT

Attribute	Description	
Name	CHGCCYLCYXRT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT1

Attribute	Description	
Name	LCYCHGAMT1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT1

Attribute	Description	
Name	CHGCCYLCYXRT1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT2

Attribute	Description	
Name	LCYCHGAMT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT2

Attribute	Description	
Name	CHGCCYLCYXRT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT3

Attribute	Description	
Name	LCYCHGAMT3	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT3

Attribute	Description	
Name	CHGCCYLCYXRT3	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT4

Attribute	Description	
Name	LCYCHGAMT4	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT4

Attribute	Description	
Name	CHGCCYLCYXRT4	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

ACYTOTCHGAMT

Attribute	Description	
Name	ACYTOTCHGAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CR_CARD_NO

Attribute	Description	
Name	CR_CARD_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

TOP

CC_HOLDER_NAME

Attribute	Description	
Name	CC_HOLDER_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

TOP

REMBANK

Attribute	Description	
Name	REMBANK	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

REMBRANCH

Attribute	Description
Name	REMBRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

BENBANK

Attribute	Description
Name	BENBANK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: pattern — Description: [a-zA-Z0-9]*

TOP

BENBRANCH

Attribute	Description
Name	BENBRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

BENCCY

Attribute	Description
Name	BENCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

ROUTBNKNAM

Attribute	Description	
Name	ROUTBNKNAM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ROUTBRNNAM

Attribute	Description	
Name	ROUTBRNNAM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ROUTSECTDISC

Attribute	Description	
Name	ROUTSECTDISC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

LCYTOTCHGAMT

Attribute	Description	
Name	LCYTOTCHGAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

TCYTOTCHGAMT

Attribute	Description
Name	TCYTOTCHGAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: fractionDigits, Description: 3 Restrictions: totalDigits, Description: 22

TOP

DENMCCY1

Attribute	Description
Name	DENMCCY1
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: length, Description: 3 Restrictions: pattern, Description: [A-Z]{3}

TOP

DENMAMT1

Attribute	Description
Name	DENMAMT1
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: fractionDigits, Description: 3 Restrictions: totalDigits, Description: 22

TOP

DENMCCY2

Attribute	Description
Name	DENMCCY2
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

DENMAMT2

Attribute	Description	
Name	DENMAMT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

DIRECTION

Attribute	Description	
Name	DIRECTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	I,O

TOP

REMDET1

Attribute	Description	
Name	REMDET1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

REMDET2

Attribute	Description	
Name	REMDET2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

REMDET3

Attribute	Description	
Name	REMDET3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

BENDET1

Attribute	Description	
Name	BENDET1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

BENDET2

Attribute	Description	
Name	BENDET2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

BENDET3

Attribute	Description
Name	BENDET3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LOCLCLEARING

Attribute	Description
Name	LOCLCLEARING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHQVERDIGIT

Attribute	Description
Name	CHQVERDIGIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0 totalDigits / 10

TOP

TXNID

Attribute	Description
Name	TXNID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ORGTXNID

Attribute	Description
Name	ORGTXNID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DIN

Attribute	Description
Name	DIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DINDATE

Attribute	Description
Name	DINDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTDATE

Attribute	Description
Name	CUSTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	pattern	[A-Z]*

TOP

MODREFNO

Attribute	Description
Name	MODREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REJREASON

Attribute	Description
Name	REJREASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z0-9]*

TOP

ACCTITLE

Attribute	Description
Name	ACCTITLE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACTAMT

Attribute	Description
Name	ACTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 0 Restrictions: totalDigits — Description: 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

RECTYPE

Attribute	Description
Name	RECTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TXNCD

Attribute	Description
Name	TXNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 9 Restrictions: minLength, Description: 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 12 Restrictions: minLength, Description: 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 16 Restrictions: minLength, Description: 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	Attribute: minOccurs, Description: 0

Restrictions	Restrictions	Description
	maxLength	16
	minLength	1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	Attribute: Description minOccurs: 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 9 minLength: 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description fractionDigits: 15 minInclusive: 0 totalDigits: 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	fractionDigits: 5; minInclusive: 0; totalDigits: 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	maxLength: 9; minLength: 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	maxLength: 9; minLength: 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS7

Attribute	Description

Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	**Description**
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	**Description**
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	**Description**
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	**Description**
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	**Description**
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	**Description**
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 minLength — 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 minLength — 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	**Description**
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	**Description**
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	**Description**
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	**Description**
Name	COMPMIS6LBL6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	**Description**
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	**Description**
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	**Description**
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	Indicated the Charge Component Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

CHGAMT

Attribute	Description	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHGCCY

Attribute	Description	
Name	CHGCCY	
Datatype	String	
Description	Indicates the currency of the charged amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description	Indicates the MIS head for charge.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNCODE

Attribute	Description	
Name	TXNCODE	
Datatype	String	
Description	Indicates the transacton code for charge	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

TOP

NETTINGIND

Attribute	Description
Name	NETTINGIND
Datatype	String
Description	Indicates whether charge need to be netted or not.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

CHGGL

Attribute	Description
Name	CHGGL
Datatype	String
Description	Indicates th GL associated with charge.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

TYPE

Attribute	Description
Name	TYPE
Datatype	String
Description	Indicates the type of charge. F - Fixed, P - Percentage, I - Interest
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LCYCHG

Attribute	Description
Name	LCYCHG
Datatype	Number
Description	Indicates the chage in local currency.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 3 Restrictions: totalDigits — Description: 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

TCYCHG

Attribute	Description
Name	TCYCHG
Datatype	Number
Description	Indicate the charge in transaction currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

TCYXRATE

Attribute	Description
Name	TCYXRATE
Datatype	Number
Description	Indicates the exchange rate for transaction currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Transaction-Details
XREF
Clearing-Details
FCCREF

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Input Only information relating to the Clearing Transaction that has to be Authorized

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the information related to Authorisation of Clearing Transaction.

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details

Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

2.54.3.CGTransaction-Auth-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transaction-Details*
    - *XREF*
    - *SCODE*
    - *STATUS*
    - *BATCHTOTAMT*
    - *CONSOLIDATED*
    - *DEPSLIP*
    - *BENACCOUNT1*
    - *Clearing-Details*
      - *PRODUCT*
      - *FCCREF*
      - *ESN*
      - *REMACCOUNT*
      - *INSTRNO*
      - *INSTRCCY*
      - *INSTRAMT*
      - *INSTRDATE*
      - *CHEQUEISSUEDATE*
      - *TXNDATE*

VALDATE
LATECLG
ROUTINGNO
SERIALNO
ENTRYNO
REGCC
SPLCHQ
TXNBRN
BENACCOUNT
TXNCCY
ENDPOINT
CHKBUKNUM
ACCCY
ACCCYAMT
ROUTBNKCOD
ROUTBRNCOD
ROUTSECTCOD
BENCUSTID
REMCUST
ACCBRN
INSTRNO2
ERRCODE
LCYCHGAMT
CHGCCYLCYXRT
LCYCHGAMT1
CHGCCYLCYXRT1
LCYCHGAMT2
CHGCCYLCYXRT2
LCYCHGAMT3
CHGCCYLCYXRT3
LCYCHGAMT4
CHGCCYLCYXRT4
ACYTOTCHGAMT
CR_CARD_NO
CC_HOLDER_NAME
REMBANK
REMBRANCH
BENBANK
BENBRANCH
BENCCY
ROUTBNKNAM
ROUTBRNNAM
ROUTSECTDISC
LCYTOTCHGAMT

TCYTOTCHGAMT
DENMCCY1
DENMAMT1
DENMCCY2
DENMAMT2
XRATE
DIRECTION
REMDET1
REMDET2
REMDET3
BENDET1
BENDET2
BENDET3
LOCLCLEARING
CHQVERDIGIT
TXNID
ORGTXNID
DIN
DINDATE
CUSTDATE
MODULE
MODREFNO
REJREASON
CUSTID
ACCTITLE
CUSTNAME
REMARKS
ACTAMT
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
MODNO
RECORDSTAT
AUTHSTAT
ONCEAUTH
STATUS
RECTYPE
TXNCD
DOCTYPE

Mis-Details

BRANCH
CUSTNO
MISGRP

REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3

- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *TXNMIS10*
- *FUNDMIS1LBL1*
- *FUNDMIS2LBL2*
- *FUNDMIS3LBL3*
- *FUNDMIS4LBL4*
- *FUNDMIS5LBL5*
- *FUNDMIS6LBL6*
- *FUNDMIS7LBL7*
- *FUNDMIS8LBL8*
- *FUNDMIS9LBL9*
- *FUNDMIS10LBL10*
- *COMPMIS1LBL1*
- *COMPMIS2LBL2*
- *COMPMIS3LBL3*
- *COMPMIS4LBL4*
- *COMPMIS5LBL5*
- *COMPMIS6LBL6*
- *COMPMIS7LBL7*
- *COMPMIS8LBL8*
- *COMPMIS9LBL9*
- *COMPMIS10LBL10*
- *TXNMIS1LBL1*
- *TXNMIS2LBL2*
- *TXNMIS3LBL3*
- *TXNMIS4LBL4*
- *TXNMIS5LBL5*
- *TXNMIS6LBL6*
- *TXNMIS7LBL7*
- *TXNMIS8LBL8*
- *TXNMIS9LBL9*
- *TXNMIS10LBL10*

Udf-Details

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Charge-Details

CHGCOMP

WAIVER

CHGAMT

CHGCCY

MISHEAD

TXNCODE

NETTINGIND

CHGGL

TYPE

LCYCHG

XRATE

TCYCHG

TCYXRATE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for information relating to the Clearing Transaction that has to be Authorized

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the information related to Authorisation of Clearing Transaction.

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SCODE

Attribute	Description
Name	SCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 4

TOP

BATCHTOTAMT

Attribute	Description
Name	BATCHTOTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: fractionDigits, Description: 3 Restrictions: totalDigits, Description: 22

TOP

CONSOLIDATED

Attribute	Description
Name	CONSOLIDATED
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

DEPSLIP

Attribute	Description
Name	DEPSLIP
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

BENACCOUNT1

Attribute	**Description**
Name	BENACCOUNT1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

Clearing-Details

Attribute	**Description**
Name	Clearing-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

PRODUCT

Attribute	**Description**
Name	PRODUCT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

FCCREF

Attribute	**Description**
Name	FCCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 0 totalDigits / 10

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRCCY

Attribute	Description
Name	INSTRCCY
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

INSTRAMT

Attribute	Description
Name	INSTRAMT
Datatype	Number
Description	

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	

TOP

CHEQUEISSUEDATE

Attribute	Description
Name	CHEQUEISSUEDATE
Datatype	Date
Description	

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	

TOP

VALDATE

Attribute	Description	
Name	VALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATECLG

Attribute	Description	
Name	LATECLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 27

TOP

SERIALNO

Attribute	Description
Name	SERIALNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ENTRYNO

Attribute	Description
Name	ENTRYNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 9

TOP

REGCC

Attribute	Description
Name	REGCC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SPLCHQ

Attribute	Description
Name	SPLCHQ
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TXNBRN

Attribute	Description
Name	TXNBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

BENACCOUNT

Attribute	Description
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

TXNCCY

Attribute	Description
Name	TXNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

CHKBUKNUM

Attribute	Description
Name	CHKBUKNUM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [A-Z]{3}

TOP

ACCCYAMT

Attribute	Description
Name	ACCCYAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 3 Restrictions: totalDigits — Description: 22

TOP

ROUTBNKCOD

Attribute	Description
Name	ROUTBNKCOD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

ROUTBRNCOD

Attribute	Description	
Name	ROUTBRNCOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

ROUTSECTCOD

Attribute	Description	
Name	ROUTSECTCOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

BENCUSTID

Attribute	Description	
Name	BENCUSTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

REMCUST

Attribute	Description	
Name	REMCUST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

INSTRNO2

Attribute	Description	
Name	INSTRNO2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ERRCODE

Attribute	Description	
Name	ERRCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LCYCHGAMT

Attribute	Description	
Name	LCYCHGAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT

Attribute	Description	
Name	CHGCCYLCYXRT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT1

Attribute	Description	
Name	LCYCHGAMT1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT1

Attribute	Description	
Name	CHGCCYLCYXRT1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT2

Attribute	Description	
Name	LCYCHGAMT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT2

Attribute	Description	
Name	CHGCCYLCYXRT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT3

Attribute	Description	
Name	LCYCHGAMT3	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT3

Attribute	Description	
Name	CHGCCYLCYXRT3	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT4

Attribute	Description	
Name	LCYCHGAMT4	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT4

Attribute	Description	
Name	CHGCCYLCYXRT4	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

ACYTOTCHGAMT

Attribute	Description	
Name	ACYTOTCHGAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CR_CARD_NO

Attribute	Description	
Name	CR_CARD_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

TOP

CC_HOLDER_NAME

Attribute	Description	
Name	CC_HOLDER_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

REMBANK

Attribute	**Description**
Name	REMBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

REMBRANCH

Attribute	**Description**
Name	REMBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

BENBANK

Attribute	**Description**
Name	BENBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

BENBRANCH

Attribute	**Description**
Name	BENBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

BENCCY

Attribute	Description
Name	BENCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [A-Z]{3}

TOP

ROUTBNKNAM

Attribute	Description
Name	ROUTBNKNAM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ROUTBRNNAM

Attribute	Description
Name	ROUTBRNNAM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ROUTSECTDISC

Attribute	Description
Name	ROUTSECTDISC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

LCYTOTCHGAMT

Attribute	Description
Name	LCYTOTCHGAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 3 Restrictions: totalDigits — Description: 22

TOP

TCYTOTCHGAMT

Attribute	Description
Name	TCYTOTCHGAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 3 Restrictions: totalDigits — Description: 22

TOP

DENMCCY1

Attribute	Description
Name	DENMCCY1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [A-Z]{3}

TOP

DENMAMT1

Attribute	Description
Name	DENMAMT1
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

DENMCCY2

Attribute	Description	
Name	DENMCCY2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

DENMAMT2

Attribute	Description	
Name	DENMAMT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

DIRECTION

Attribute	Description	
Name	DIRECTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

ORACLE

Restrictions	**Restrictions** / **Description** enumeration / I,O

TOP

REMDET1

Attribute	**Description**
Name	REMDET1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REMDET2

Attribute	**Description**
Name	REMDET2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REMDET3

Attribute	**Description**
Name	REMDET3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BENDET1

Attribute	**Description**
Name	BENDET1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BENDET2

Attribute	Description
Name	BENDET2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BENDET3

Attribute	Description
Name	BENDET3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LOCLCLEARING

Attribute	Description
Name	LOCLCLEARING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHQVERDIGIT

Attribute	Description
Name	CHQVERDIGIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

TXNID

Attribute	Description
Name	TXNID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ORGTXNID

Attribute	Description
Name	ORGTXNID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DIN

Attribute	Description
Name	DIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DINDATE

Attribute	Description
Name	DINDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTDATE

Attribute	Description
Name	CUSTDATE
Datatype	Date

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [A-Z]*

TOP

MODREFNO

Attribute	Description
Name	MODREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

REJREASON

Attribute	Description
Name	REJREASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

ACCTITLE

Attribute	Description	
Name	ACCTITLE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

ACTAMT

Attribute	Description	
Name	ACTAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

RECTYPE

Attribute	Description
Name	RECTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TXNCD

Attribute	Description
Name	TXNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Mis-Details

Attribute	Description

Name	Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	**Description**
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	**Description**
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	**Description**
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	**Description**

Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	**Description**
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	**Description**
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	**Description**
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	Attribute: minOccurs — Description: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

COSTCOD4

Attribute	Description	
Name	COSTCOD4	
Datatype	String	
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

COSTCOD5

Attribute	Description	
Name	COSTCOD5	
Datatype	String	
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

LINKGRP

Attribute	Description	
Name	LINKGRP	
Datatype	String	
Description	Indicates Link to Group	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12
	minLength	1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	**Description**
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	**Description**
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	**Description**
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	**Description**
Name	TXNMIS2LBL2
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	**Description**
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	**Description**
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	**Description**
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	Restrictions: maxLength — Description: 105 Restrictions: minLength — Description: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	Indicated the Charge Component Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	Indicates the MIS head for charge.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNCODE

Attribute	Description
Name	TXNCODE
Datatype	String
Description	Indicates the transacton code for charge
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETTINGIND

Attribute	Description
Name	NETTINGIND
Datatype	String
Description	Indicates whether charge need to be netted or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGGL

Attribute	Description
Name	CHGGL
Datatype	String
Description	Indicates th GL associated with charge.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

TYPE

Attribute	Description

Name	TYPE
Datatype	String
Description	Indicates the type of charge. F - Fixed, P - Percentage, I - Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LCYCHG

Attribute	Description
Name	LCYCHG
Datatype	Number
Description	Indicates the chage in local currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

TCYCHG

Attribute	Description
Name	TCYCHG
Datatype	Number
Description	Indicate the charge in transaction currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TCYXRATE

Attribute	Description
Name	TCYXRATE

Datatype	Number
Description	Indicates the exchange rate for transaction currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Transaction-Details*
      - *XREF*
      - *Clearing-Details*
        - *FCCREF*
    - *Transaction-Details-PK*
      - *XREF*
      - *Clearing-Details*
        - *FCCREF*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Input Only information relating to the Clearing Transaction that has to be Authorized

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the information regarding Authorisation of Clearing Transaction Details.

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	

TOP

FCCREF

Attribute	Description	
Name	FCCREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

Transaction-Details-PK

Attribute	Description
Name	Transaction-Details-PK
Datatype	
Description	Includes the information regarding Authorisation of Clearing Transaction primary key Details.

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description

Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.55.CreateTransaction

Input of Clearing Transaction

2.55.1.CGTransaction-Create-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transaction-Details*
    - *XREF*
    - *SCODE*
    - *STATUS*
    - *BATCHTOTAMT*
    - *CONSOLIDATED*
    - *DEPSLIP*
    - *BENACCOUNT1*
    - *Clearing-Details*
      - *PRODUCT*
      - *FCCREF*
      - *ESN*
      - *REMACCOUNT*
      - *INSTRNO*
      - *INSTRCCY*
      - *INSTRAMT*

INSTRDATE
CHEQUEISSUEDATE
TXNDATE
VALDATE
LATECLG
ROUTINGNO
SERIALNO
ENTRYNO
REGCC
SPLCHQ
TXNBRN
BENACCOUNT
TXNCCY
ENDPOINT
CHKBUKNUM
ACCCY
ACCCYAMT
ROUTBNKCOD
ROUTBRNCOD
ROUTSECTCOD
BENCUSTID
REMCUST
ACCBRN
INSTRNO2
ERRCODE
LCYCHGAMT
CHGCCYLCYXRT
LCYCHGAMT1
CHGCCYLCYXRT1
LCYCHGAMT2
CHGCCYLCYXRT2
LCYCHGAMT3
CHGCCYLCYXRT3
LCYCHGAMT4
CHGCCYLCYXRT4
ACYTOTCHGAMT
CR_CARD_NO
CC_HOLDER_NAME
REMBANK
REMBRANCH
BENBANK
BENBRANCH
BENCCY
ROUTBNKNAM

ROUTBRNNAM
ROUTSECTDISC
LCYTOTCHGAMT
TCYTOTCHGAMT
DENMCCY1
DENMAMT1
DENMCCY2
DENMAMT2
XRATE
DIRECTION
REMDET1
REMDET2
REMDET3
BENDET1
BENDET2
BENDET3
LOCLCLEARING
CHQVERDIGIT
TXNID
ORGTXNID
DIN
DINDATE
CUSTDATE
MODULE
MODREFNO
REJREASON
CUSTID
ACCTITLE
CUSTNAME
REMARKS
ACTAMT
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
MODNO
RECORDSTAT
AUTHSTAT
ONCEAUTH
STATUS
RECTYPE
TXNCD
DOCTYPE

Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG

TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE

FIELD_VALUE
VAL_TYPE
Charge-Details
CHGCOMP
WAIVER
CHGAMT
CHGCCY
MISHEAD
TXNCODE
NETTINGIND
CHGGL
TYPE
LCYCHG
XRATE
TCYCHG
TCYXRATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength 12; pattern [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Input Only information relating to the Clearing Transaction that has to be Created

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the information regarding Input of Clearing Transaction Details.

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

STATUS

Attribute	Description
Name	STATUS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BATCHTOTAMT

Attribute	**Description**
Name	BATCHTOTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CONSOLIDATED

Attribute	**Description**
Name	CONSOLIDATED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEPSLIP

Attribute	**Description**
Name	DEPSLIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

BENACCOUNT1

Attribute	**Description**
Name	BENACCOUNT1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

PRODUCT

Attribute	Description
Name	PRODUCT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 4; pattern / [a-zA-Z0-9]{4}

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

ORACLE

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRCCY

Attribute	Description
Name	INSTRCCY
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

INSTRAMT

Attribute	Description
Name	INSTRAMT
Datatype	Number
Description	
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	

TOP

CHEQUEISSUEDATE

Attribute	Description
Name	CHEQUEISSUEDATE
Datatype	Date
Description	

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	

TOP

VALDATE

Attribute	Description	
Name	VALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATECLG

Attribute	Description	
Name	LATECLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ROUTINGNO

Attribute	Description	
Name	ROUTINGNO	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	27

TOP

SERIALNO

Attribute	Description

Name	SERIALNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ENTRYNO

Attribute	**Description**
Name	ENTRYNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 9

TOP

REGCC

Attribute	**Description**
Name	REGCC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SPLCHQ

Attribute	**Description**
Name	SPLCHQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TXNBRN

Attribute	**Description**
Name	TXNBRN
Datatype	String
Description	

ORACLE

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

BENACCOUNT

Attribute	Description	
Name	BENACCOUNT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

TXNCCY

Attribute	Description	
Name	TXNCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

ENDPOINT

Attribute	Description	
Name	ENDPOINT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

CHKBUKNUM

Attribute	Description	
Name	CHKBUKNUM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	2000

TOP

ACCCY

Attribute	Description	
Name	ACCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

ACCCYAMT

Attribute	Description	
Name	ACCCYAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

ROUTBNKCOD

Attribute	Description	
Name	ROUTBNKCOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

ROUTBRNCOD

Attribute	Description	
Name	ROUTBRNCOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

ROUTSECTCOD

Attribute	Description	
Name	ROUTSECTCOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

BENCUSTID

Attribute	Description	
Name	BENCUSTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

REMCUST

Attribute	Description	
Name	REMCUST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

INSTRNO2

Attribute	Description	
Name	INSTRNO2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

ERRCODE

Attribute	Description	
Name	ERRCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

TOP

LCYCHGAMT

Attribute	Description	
Name	LCYCHGAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT

Attribute	Description	
Name	CHGCCYLCYXRT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT1

Attribute	Description	
Name	LCYCHGAMT1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT1

Attribute	Description	
Name	CHGCCYLCYXRT1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT2

Attribute	Description	
Name	LCYCHGAMT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT2

Attribute	Description	
Name	CHGCCYLCYXRT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT3

Attribute	Description	
Name	LCYCHGAMT3	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT3

Attribute	Description	
Name	CHGCCYLCYXRT3	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT4

Attribute	Description	
Name	LCYCHGAMT4	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT4

Attribute	Description	
Name	CHGCCYLCYXRT4	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

ORACLE

Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

ACYTOTCHGAMT

Attribute	Description	
Name	ACYTOTCHGAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CR_CARD_NO

Attribute	Description	
Name	CR_CARD_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

TOP

CC_HOLDER_NAME

Attribute	Description	
Name	CC_HOLDER_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

TOP

REMBANK

Attribute	Description	
Name	REMBANK	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

REMBRANCH

Attribute	Description
Name	REMBRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

BENBANK

Attribute	Description
Name	BENBANK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: pattern — Description: [a-zA-Z0-9]*

TOP

BENBRANCH

Attribute	Description
Name	BENBRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

BENCCY

Attribute	Description
Name	BENCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

ORACLE

Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

ROUTBNKNAM

Attribute	Description	
Name	ROUTBNKNAM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ROUTBRNNAM

Attribute	Description	
Name	ROUTBRNNAM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ROUTSECTDISC

Attribute	Description	
Name	ROUTSECTDISC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

LCYTOTCHGAMT

Attribute	Description	
Name	LCYTOTCHGAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

TCYTOTCHGAMT

Attribute	Description	
Name	TCYTOTCHGAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

DENMCCY1

Attribute	Description	
Name	DENMCCY1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

DENMAMT1

Attribute	Description	
Name	DENMAMT1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

DENMCCY2

Attribute	Description	
Name	DENMCCY2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

DENMAMT2

Attribute	Description	
Name	DENMAMT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

DIRECTION

Attribute	Description	
Name	DIRECTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	I,O

TOP

REMDET1

Attribute	Description	
Name	REMDET1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REMDET2

Attribute	**Description**
Name	REMDET2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REMDET3

Attribute	**Description**
Name	REMDET3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BENDET1

Attribute	**Description**
Name	BENDET1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BENDET2

Attribute	**Description**
Name	BENDET2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BENDET3

Attribute	Description
Name	BENDET3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LOCLCLEARING

Attribute	Description
Name	LOCLCLEARING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHQVERDIGIT

Attribute	Description
Name	CHQVERDIGIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0 totalDigits / 10

TOP

TXNID

Attribute	Description
Name	TXNID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ORGTXNID

Attribute	Description
Name	ORGTXNID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DIN

Attribute	Description
Name	DIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DINDATE

Attribute	Description
Name	DINDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTDATE

Attribute	Description
Name	CUSTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	pattern	[A-Z]*

TOP

MODREFNO

Attribute	Description
Name	MODREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REJREASON

Attribute	Description
Name	REJREASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z0-9]*

TOP

ACCTITLE

Attribute	Description
Name	ACCTITLE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACTAMT

Attribute	Description
Name	ACTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	0
	totalDigits	10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

RECTYPE

Attribute	Description
Name	RECTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

TXNCD

Attribute	Description
Name	TXNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 9 Restrictions: minLength, Description: 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 12 Restrictions: minLength, Description: 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 16 Restrictions: minLength, Description: 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	Attribute: minOccurs, Description: 0

Restrictions	Restrictions	Description
	maxLength	16
	minLength	1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	Attribute: minOccurs, Description: 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 9 Restrictions: minLength, Description: 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: fractionDigits, Description: 15 Restrictions: minInclusive, Description: 0 Restrictions: totalDigits, Description: 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 5 Restrictions: minInclusive — Description: 0 Restrictions: totalDigits — Description: 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS7

Attribute	Description

Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	**Description**
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	**Description**
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	**Description**
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	**Description**
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	**Description**
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	**Description**
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 minLength — 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 minLength — 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	**Description**
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	**Description**
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	**Description**
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	**Description**
Name	COMPMIS6LBL6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	**Description**
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	**Description**
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	**Description**
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	Indicated the Charge Component Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

CHGAMT

Attribute	Description	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCY

Attribute	Description	
Name	CHGCCY	
Datatype	String	
Description	Indicates the currency of the charged amount.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description	Indicates the MIS head for charge.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

TXNCODE

Attribute	Description	
Name	TXNCODE	
Datatype	String	
Description	Indicates the transacton code for charge	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

TOP

NETTINGIND

Attribute	Description
Name	NETTINGIND
Datatype	String
Description	Indicates whether charge need to be netted or not.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

CHGGL

Attribute	Description
Name	CHGGL
Datatype	String
Description	Indicates th GL associated with charge.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

TYPE

Attribute	Description
Name	TYPE
Datatype	String
Description	Indicates the type of charge. F - Fixed, P - Percentage, I - Interest
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LCYCHG

Attribute	Description
Name	LCYCHG
Datatype	Number
Description	Indicates the chage in local currency.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 3 Restrictions: totalDigits — Description: 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

TCYCHG

Attribute	Description
Name	TCYCHG
Datatype	Number
Description	Indicate the charge in transaction currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

TCYXRATE

Attribute	Description
Name	TCYXRATE
Datatype	Number
Description	Indicates the exchange rate for transaction currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

2.55.2.CGTransaction-Create-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transaction-Details*
    - *XREF*
    - *SCODE*
    - *CONSOLIDATED*
    - *DEPSLIP*
    - *Clearing-Details*
      - *PRODUCT*
      - *REMACCOUNT*
      - *INSTRNO*
      - *INSTRCCY*
      - *INSTRAMT*
      - *INSTRDATE*
      - *CHEQUEISSUEDATE*
      - *TXNDATE*
      - *VALDATE*
      - *LATECLG*
      - *ROUTINGNO*
      - *SERIALNO*
      - *ENTRYNO*

REGCC
SPLCHQ
TXNBRN
BENACCOUNT
TXNCCY
CR_CARD_NO
CC_HOLDER_NAME
ENDPOINT
CHKBUKNUM
ACCCY
ACCCYAMT
BENCUSTID
REMDET1
REMDET2
REMDET3
BENDET1
BENDET2
BENDET3
DIN
LOCLCLEARING
REMBANK
REMBRANCH
CHQVERDIGIT
DOCTYPE
TXNID
ORGTXNID
DINDATE
CUSTDATE
REMARKS
XRATE

Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD

REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3

- *FUNDMIS4LBL4*
- *FUNDMIS5LBL5*
- *FUNDMIS6LBL6*
- *FUNDMIS7LBL7*
- *FUNDMIS8LBL8*
- *FUNDMIS9LBL9*
- *FUNDMIS10LBL10*
- *COMPMIS1LBL1*
- *COMPMIS2LBL2*
- *COMPMIS3LBL3*
- *COMPMIS4LBL4*
- *COMPMIS5LBL5*
- *COMPMIS6LBL6*
- *COMPMIS7LBL7*
- *COMPMIS8LBL8*
- *COMPMIS9LBL9*
- *COMPMIS10LBL10*
- *TXNMIS1LBL1*
- *TXNMIS2LBL2*
- *TXNMIS3LBL3*
- *TXNMIS4LBL4*
- *TXNMIS5LBL5*
- *TXNMIS6LBL6*
- *TXNMIS7LBL7*
- *TXNMIS8LBL8*
- *TXNMIS9LBL9*
- *TXNMIS10LBL10*

Udf-Details

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Charge-Details

- *CHGCOMP*
- *WAIVER*
- *CHGAMT*
- *CHGCCY*
- *MISHEAD*
- *TXNCODE*
- *NETTINGIND*
- *CHGGL*
- *TYPE*
- *LCYCHG*

XRATE

TCYCHG

TCYXRATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	

Description	This XSD gives the message format for Input Only information relating to the Retail Teller Transaction that has to be Queried

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the information regarding Input of Clearing Transaction Details.

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

CONSOLIDATED

Attribute	Description	
Name	CONSOLIDATED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEPSLIP

Attribute	Description
Name	DEPSLIP
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

Clearing-Details

Attribute	**Description**
Name	Clearing-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

PRODUCT

Attribute	**Description**
Name	PRODUCT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

REMACCOUNT

Attribute	**Description**
Name	REMACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	**Description**
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRCCY

Attribute	Description
Name	INSTRCCY
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

INSTRAMT

Attribute	Description
Name	INSTRAMT
Datatype	Number
Description	
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	

TOP

CHEQUEISSUEDATE

Attribute	Description
Name	CHEQUEISSUEDATE
Datatype	Date
Description	

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

LATECLG

Attribute	Description	
Name	LATECLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ROUTINGNO

Attribute	Description	
Name	ROUTINGNO	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	27

TOP

SERIALNO

Attribute	Description	
Name	SERIALNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ENTRYNO

Attribute	Description	
Name	ENTRYNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	0
	totalDigits	9

TOP

REGCC

Attribute	Description
Name	REGCC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPLCHQ

Attribute	Description
Name	SPLCHQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TXNBRN

Attribute	Description
Name	TXNBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

BENACCOUNT

Attribute	Description
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

TXNCCY

Attribute	Description

Name	TXNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

CR_CARD_NO

Attribute	**Description**
Name	CR_CARD_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

CC_HOLDER_NAME

Attribute	**Description**
Name	CC_HOLDER_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

ENDPOINT

Attribute	**Description**
Name	ENDPOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CHKBUKNUM

Attribute	**Description**
Name	CHKBUKNUM
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ACCCY

Attribute	Description	
Name	ACCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ACCCYAMT

Attribute	Description	
Name	ACCCYAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BENCUSTID

Attribute	Description	
Name	BENCUSTID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

REMDET1

Attribute	Description
Name	REMDET1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REMDET2

Attribute	Description	
Name	REMDET2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REMDET3

Attribute	Description	
Name	REMDET3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BENDET1

Attribute	Description	
Name	BENDET1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BENDET2

Attribute	Description	
Name	BENDET2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

BENDET3

Attribute	Description	
Name	BENDET3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

DIN

Attribute	Description	
Name	DIN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

LOCLCLEARING

Attribute	Description	
Name	LOCLCLEARING	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REMBANK

Attribute	Description	
Name	REMBANK	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

REMBRANCH

Attribute	Description
Name	REMBRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

CHQVERDIGIT

Attribute	Description
Name	CHQVERDIGIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 0 Restrictions: totalDigits — Description: 10

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 0 Restrictions: totalDigits — Description: 10

TOP

TXNID

Attribute	Description
Name	TXNID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ORGTXNID

Attribute	Description
Name	ORGTXNID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DINDATE

Attribute	Description
Name	DINDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTDATE

Attribute	Description
Name	CUSTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	

Attributes		
	Attribute	**Description**
	minOccurs	0
Restrictions		
	Restrictions	**Description**
	fractionDigits	12
	totalDigits	24

TOP

Mis-Details

Attribute	**Description**	
Name	Mis-Details	
Datatype		
Description		
Attributes		
	Attribute	**Description**
	minOccurs	0

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions		
	Restrictions	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	**Description**	
Name	CUSTNO	
Datatype	String	
Description	Indicates The Customer Number.	
Attributes		
	Attribute	**Description**
	minOccurs	0
Restrictions		
	Restrictions	**Description**
	maxLength	9
	minLength	1

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description	Specifies The MIS Group.	
Attributes		
	Attribute	**Description**
	minOccurs	0
Restrictions		
	Restrictions	**Description**
	maxLength	12
	minLength	1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	**Description**
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	**Description**
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	**Description**
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	**Description**

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	**Description**
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	**Description**
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	Attribute: minOccurs — Description: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS5

Attribute	Description

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	**Description**
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	**Description**
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	**Description**
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	**Description**
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	**Description**
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	**Description**
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	**Description**
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	**Description**
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	**Description**
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	**Description**
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	Indicated the Charge Component Description.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true
Restrictions	Restrictions: fractionDigits — Description: 3 Restrictions: totalDigits — Description: 22

TOP

CHGCCY

Attribute	Description

Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MISHEAD

Attribute	**Description**
Name	MISHEAD
Datatype	String
Description	Indicates the MIS head for charge.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNCODE

Attribute	**Description**
Name	TXNCODE
Datatype	String
Description	Indicates the transacton code for charge
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETTINGIND

Attribute	**Description**
Name	NETTINGIND
Datatype	String
Description	Indicates whether charge need to be netted or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGGL

Attribute	**Description**
Name	CHGGL
Datatype	String
Description	Indicates th GL associated with charge.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

TYPE

Attribute	Description
Name	TYPE
Datatype	String
Description	Indicates the type of charge. F - Fixed, P - Percentage, I - Interest
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LCYCHG

Attribute	Description
Name	LCYCHG
Datatype	Number
Description	Indicates the chage in local currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

TCYCHG

Attribute	Description
Name	TCYCHG
Datatype	Number
Description	Indicate the charge in transaction currency

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

TCYXRATE

Attribute	Description
Name	TCYXRATE
Datatype	Number
Description	Indicates the exchange rate for transaction currency.
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	fractionDigits / 3
	totalDigits / 22

TOP

2.55.3.CGTransaction-Create-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transaction-Details*
    - *XREF*
    - *SCODE*
    - *STATUS*
    - *BATCHTOTAMT*
    - *CONSOLIDATED*
    - *DEPSLIP*
    - *BENACCOUNT1*
    - *Clearing-Details*
      - *PRODUCT*
      - *FCCREF*
      - *ESN*
      - *REMACCOUNT*
      - *INSTRNO*
      - *INSTRCCY*
      - *INSTRAMT*
      - *INSTRDATE*
      - *CHEQUEISSUEDATE*
      - *TXNDATE*

VALDATE
LATECLG
ROUTINGNO
SERIALNO
ENTRYNO
REGCC
SPLCHQ
TXNBRN
BENACCOUNT
TXNCCY
ENDPOINT
CHKBUKNUM
ACCCY
ACCCYAMT
ROUTBNKCOD
ROUTBRNCOD
ROUTSECTCOD
BENCUSTID
REMCUST
ACCBRN
INSTRNO2
ERRCODE
LCYCHGAMT
CHGCCYLCYXRT
LCYCHGAMT1
CHGCCYLCYXRT1
LCYCHGAMT2
CHGCCYLCYXRT2
LCYCHGAMT3
CHGCCYLCYXRT3
LCYCHGAMT4
CHGCCYLCYXRT4
ACYTOTCHGAMT
CR_CARD_NO
CC_HOLDER_NAME
REMBANK
REMBRANCH
BENBANK
BENBRANCH
BENCCY
ROUTBNKNAM
ROUTBRNNAM
ROUTSECTDISC
LCYTOTCHGAMT

TCYTOTCHGAMT
DENMCCY1
DENMAMT1
DENMCCY2
DENMAMT2
XRATE
DIRECTION
REMDET1
REMDET2
REMDET3
BENDET1
BENDET2
BENDET3
LOCLCLEARING
CHQVERDIGIT
TXNID
ORGTXNID
DIN
DINDATE
CUSTDATE
MODULE
MODREFNO
REJREASON
CUSTID
ACCTITLE
CUSTNAME
REMARKS
ACTAMT
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
MODNO
RECORDSTAT
AUTHSTAT
ONCEAUTH
STATUS
RECTYPE
TXNCD
DOCTYPE

Mis-Details

BRANCH
CUSTNO
MISGRP

REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3

- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *TXNMIS10*
- *FUNDMIS1LBL1*
- *FUNDMIS2LBL2*
- *FUNDMIS3LBL3*
- *FUNDMIS4LBL4*
- *FUNDMIS5LBL5*
- *FUNDMIS6LBL6*
- *FUNDMIS7LBL7*
- *FUNDMIS8LBL8*
- *FUNDMIS9LBL9*
- *FUNDMIS10LBL10*
- *COMPMIS1LBL1*
- *COMPMIS2LBL2*
- *COMPMIS3LBL3*
- *COMPMIS4LBL4*
- *COMPMIS5LBL5*
- *COMPMIS6LBL6*
- *COMPMIS7LBL7*
- *COMPMIS8LBL8*
- *COMPMIS9LBL9*
- *COMPMIS10LBL10*
- *TXNMIS1LBL1*
- *TXNMIS2LBL2*
- *TXNMIS3LBL3*
- *TXNMIS4LBL4*
- *TXNMIS5LBL5*
- *TXNMIS6LBL6*
- *TXNMIS7LBL7*
- *TXNMIS8LBL8*
- *TXNMIS9LBL9*
- *TXNMIS10LBL10*

Udf-Details

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Charge-Details

CHGCOMP

WAIVER

CHGAMT

CHGCCY

MISHEAD

TXNCODE

NETTINGIND

CHGGL

TYPE

LCYCHG

XRATE

TCYCHG

TCYXRATE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Input Only information relating to the Clearing Transaction that has to be Created

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the information Regarding Input of Clearing Transaction Details.

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SCODE

Attribute	Description
Name	SCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 4

TOP

BATCHTOTAMT

Attribute	Description
Name	BATCHTOTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: fractionDigits; Description: 3 Restrictions: totalDigits; Description: 22

TOP

CONSOLIDATED

Attribute	Description
Name	CONSOLIDATED
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: Y,N

TOP

DEPSLIP

Attribute	Description
Name	DEPSLIP
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

BENACCOUNT1

Attribute	**Description**
Name	BENACCOUNT1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

Clearing-Details

Attribute	**Description**
Name	Clearing-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

PRODUCT

Attribute	**Description**
Name	PRODUCT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

FCCREF

Attribute	**Description**
Name	FCCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRCCY

Attribute	Description
Name	INSTRCCY
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

INSTRAMT

Attribute	Description
Name	INSTRAMT
Datatype	Number
Description	

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	

TOP

CHEQUEISSUEDATE

Attribute	Description
Name	CHEQUEISSUEDATE
Datatype	Date
Description	

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	

TOP

VALDATE

Attribute	Description	
Name	VALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATECLG

Attribute	Description	
Name	LATECLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 27

TOP

SERIALNO

Attribute	Description
Name	SERIALNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ENTRYNO

Attribute	Description
Name	ENTRYNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 9

TOP

REGCC

Attribute	Description
Name	REGCC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SPLCHQ

Attribute	Description
Name	SPLCHQ
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TXNBRN

Attribute	Description
Name	TXNBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

BENACCOUNT

Attribute	Description
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

TXNCCY

Attribute	Description
Name	TXNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

ORACLE

Restrictions	Restrictions	Description
	maxLength	9

TOP

CHKBUKNUM

Attribute	Description
Name	CHKBUKNUM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [A-Z]{3}

TOP

ACCCYAMT

Attribute	Description
Name	ACCCYAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 3 Restrictions: totalDigits — Description: 22

TOP

ROUTBNKCOD

Attribute	Description
Name	ROUTBNKCOD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

ROUTBRNCOD

Attribute	Description
Name	ROUTBRNCOD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: pattern — Description: [a-zA-Z0-9]*

TOP

ROUTSECTCOD

Attribute	Description
Name	ROUTSECTCOD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

BENCUSTID

Attribute	Description
Name	BENCUSTID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: pattern — Description: [a-zA-Z0-9]*

TOP

REMCUST

Attribute	Description
Name	REMCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

INSTRNO2

Attribute	Description	
Name	INSTRNO2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ERRCODE

Attribute	Description	
Name	ERRCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LCYCHGAMT

Attribute	Description	
Name	LCYCHGAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT

Attribute	Description	
Name	CHGCCYLCYXRT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT1

Attribute	Description	
Name	LCYCHGAMT1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT1

Attribute	Description	
Name	CHGCCYLCYXRT1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT2

Attribute	Description	
Name	LCYCHGAMT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT2

Attribute	Description	
Name	CHGCCYLCYXRT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT3

Attribute	Description	
Name	LCYCHGAMT3	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT3

Attribute	Description	
Name	CHGCCYLCYXRT3	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT4

Attribute	Description	
Name	LCYCHGAMT4	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT4

Attribute	Description	
Name	CHGCCYLCYXRT4	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

ACYTOTCHGAMT

Attribute	Description	
Name	ACYTOTCHGAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CR_CARD_NO

Attribute	Description	
Name	CR_CARD_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

TOP

CC_HOLDER_NAME

Attribute	Description	
Name	CC_HOLDER_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

REMBANK

Attribute	Description	
Name	REMBANK	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

REMBRANCH

Attribute	Description	
Name	REMBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

BENBANK

Attribute	Description	
Name	BENBANK	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

BENBRANCH

Attribute	Description	
Name	BENBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

BENCCY

Attribute	Description
Name	BENCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: length, Description: 3 Restrictions: pattern, Description: [A-Z]{3}

TOP

ROUTBNKNAM

Attribute	Description
Name	ROUTBNKNAM
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 105

TOP

ROUTBRNNAM

Attribute	Description
Name	ROUTBRNNAM
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 105

TOP

ROUTSECTDISC

Attribute	Description
Name	ROUTSECTDISC
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

LCYTOTCHGAMT

Attribute	Description
Name	LCYTOTCHGAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 3 Restrictions: totalDigits — Description: 22

TOP

TCYTOTCHGAMT

Attribute	Description
Name	TCYTOTCHGAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 3 Restrictions: totalDigits — Description: 22

TOP

DENMCCY1

Attribute	Description
Name	DENMCCY1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [A-Z]{3}

TOP

DENMAMT1

Attribute	Description
Name	DENMAMT1
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

DENMCCY2

Attribute	Description	
Name	DENMCCY2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

DENMAMT2

Attribute	Description	
Name	DENMAMT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

DIRECTION

Attribute	Description	
Name	DIRECTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	I,O

TOP

REMDET1

Attribute	Description	
Name	REMDET1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

REMDET2

Attribute	Description	
Name	REMDET2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

REMDET3

Attribute	Description	
Name	REMDET3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

BENDET1

Attribute	Description	
Name	BENDET1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

BENDET2

Attribute	Description
Name	BENDET2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BENDET3

Attribute	Description
Name	BENDET3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LOCLCLEARING

Attribute	Description
Name	LOCLCLEARING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHQVERDIGIT

Attribute	Description
Name	CHQVERDIGIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

TXNID

Attribute	Description
Name	TXNID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ORGTXNID

Attribute	Description
Name	ORGTXNID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DIN

Attribute	Description
Name	DIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DINDATE

Attribute	Description
Name	DINDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTDATE

Attribute	Description
Name	CUSTDATE
Datatype	Date

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [A-Z]*

TOP

MODREFNO

Attribute	Description
Name	MODREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

REJREASON

Attribute	Description
Name	REJREASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

ACCTITLE

Attribute	Description
Name	ACCTITLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ACTAMT

Attribute	Description
Name	ACTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

ORACLE

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

RECTYPE

Attribute	Description
Name	RECTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TXNCD

Attribute	Description
Name	TXNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Mis-Details

Attribute	Description

Name	Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	**Description**
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	**Description**
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	Description	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

REFXRT

Attribute	Description	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	Description	
Name	CALCMETH	
Datatype	Number	
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6	
Attributes	Attribute	Description
	minOccurs	0

TOP

MISGRPTXN

Attribute	Description

Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	**Description**
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	**Description**
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	**Description**
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	**Description**
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	**Description**
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	**Description**
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	Attribute: minOccurs; Description: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

COSTCOD4

Attribute	Description	
Name	COSTCOD4	
Datatype	String	
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

COSTCOD5

Attribute	Description	
Name	COSTCOD5	
Datatype	String	
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

LINKGRP

Attribute	Description	
Name	LINKGRP	
Datatype	String	
Description	Indicates Link to Group	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12
	minLength	1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	**Description**
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	**Description**
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	**Description**
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	**Description**
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	**Description**
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	**Description**
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	**Description**
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	**Description**
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	**Description**
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	**Description**
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	Restrictions: maxLength — Description: 105 Restrictions: minLength — Description: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	Indicated the Charge Component Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	Indicates the MIS head for charge.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNCODE

Attribute	Description
Name	TXNCODE
Datatype	String
Description	Indicates the transacton code for charge
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETTINGIND

Attribute	Description
Name	NETTINGIND
Datatype	String
Description	Indicates whether charge need to be netted or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGGL

Attribute	Description
Name	CHGGL
Datatype	String
Description	Indicates th GL associated with charge.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

TYPE

Attribute	Description

Name	TYPE
Datatype	String
Description	Indicates the type of charge. F - Fixed, P - Percentage, I - Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LCYCHG

Attribute	Description
Name	LCYCHG
Datatype	Number
Description	Indicates the chage in local currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

TCYCHG

Attribute	Description
Name	TCYCHG
Datatype	Number
Description	Indicate the charge in transaction currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TCYXRATE

Attribute	Description
Name	TCYXRATE

Datatype	Number
Description	Indicates the exchange rate for transaction currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.55.4.CGTransaction-Create-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Transaction-Details*
      - *XREF*
      - *SCODE*
      - *CONSOLIDATED*
      - *DEPSLIP*
      - *Clearing-Details*
        - *PRODUCT*
        - *REMACCOUNT*
        - *INSTRNO*
        - *INSTRCCY*
        - *INSTRAMT*
        - *INSTRDATE*
        - *CHEQUEISSUEDATE*
        - *TXNDATE*
        - *VALDATE*
        - *LATECLG*
        - *ROUTINGNO*
        - *SERIALNO*

ENTRYNO

REGCC

SPLCHQ

TXNBRN

BENACCOUNT

TXNCCY

CR_CARD_NO

CC_HOLDER_NAME

ENDPOINT

CHKBUKNUM

ACCCY

ACCCYAMT

BENCUSTID

REMDET1

REMDET2

REMDET3

BENDET1

BENDET2

BENDET3

DIN

LOCLCLEARING

REMBANK

REMBRANCH

CHQVERDIGIT

DOCTYPE

TXNID

ORGTXNID

DINDATE

CUSTDATE

REMARKS

XRATE

Mis-Details

BRANCH

CUSTNO

MISGRP

REL_REF

REL_ACC

MISHD

POOLCD

REFRT

REFRTTYPE

REFXRT

CALCMETH

MISGRPTXN

REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2

- *FUNDMIS3LBL3*
- *FUNDMIS4LBL4*
- *FUNDMIS5LBL5*
- *FUNDMIS6LBL6*
- *FUNDMIS7LBL7*
- *FUNDMIS8LBL8*
- *FUNDMIS9LBL9*
- *FUNDMIS10LBL10*
- *COMPMIS1LBL1*
- *COMPMIS2LBL2*
- *COMPMIS3LBL3*
- *COMPMIS4LBL4*
- *COMPMIS5LBL5*
- *COMPMIS6LBL6*
- *COMPMIS7LBL7*
- *COMPMIS8LBL8*
- *COMPMIS9LBL9*
- *COMPMIS10LBL10*
- *TXNMIS1LBL1*
- *TXNMIS2LBL2*
- *TXNMIS3LBL3*
- *TXNMIS4LBL4*
- *TXNMIS5LBL5*
- *TXNMIS6LBL6*
- *TXNMIS7LBL7*
- *TXNMIS8LBL8*
- *TXNMIS9LBL9*
- *TXNMIS10LBL10*

Udf-Details

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Charge-Details

- *CHGCOMP*
- *WAIVER*
- *CHGAMT*
- *CHGCCY*
- *MISHEAD*
- *TXNCODE*
- *NETTINGIND*
- *CHGGL*
- *TYPE*

LCYCHG
XRATE
TCYCHG
TCYXRATE
Transaction-Details-PK
XREF
Clearing-Details
FCCREF
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength 12; pattern [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Input Only information relating to the Retail Teller Transaction that has to be Queried

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the information Regarding Input of Clearing Transaction IO Details.

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

CONSOLIDATED

Attribute	**Description**	
Name	CONSOLIDATED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEPSLIP

Attribute	**Description**	
Name	DEPSLIP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

Clearing-Details

Attribute	**Description**	
Name	Clearing-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

PRODUCT

Attribute	**Description**	
Name	PRODUCT	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	4
	pattern	[a-zA-Z0-9]{4}

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20 Restrictions: pattern — Description: [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 16

TOP

INSTRCCY

Attribute	Description
Name	INSTRCCY
Datatype	String
Description	
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [A-Z]{3}

TOP

INSTRAMT

Attribute	Description
Name	INSTRAMT
Datatype	Number
Description	
Restrictions	Restrictions: fractionDigits — Description: 3 Restrictions: totalDigits — Description: 22

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	

TOP

CHEQUEISSUEDATE

Attribute	Description
Name	CHEQUEISSUEDATE
Datatype	Date
Description	

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATECLG

Attribute	Description
Name	LATECLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

SERIALNO

Attribute	Description
Name	SERIALNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ENTRYNO

Attribute	**Description**
Name	ENTRYNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 9

TOP

REGCC

Attribute	**Description**
Name	REGCC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SPLCHQ

Attribute	**Description**
Name	SPLCHQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TXNBRN

Attribute	**Description**
Name	TXNBRN
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

BENACCOUNT

Attribute	Description
Name	BENACCOUNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20 Restrictions: pattern — Description: [a-zA-Z0-9]*

TOP

TXNCCY

Attribute	Description
Name	TXNCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [A-Z]{3}

TOP

CR_CARD_NO

Attribute	Description
Name	CR_CARD_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

CC_HOLDER_NAME

Attribute	Description
Name	CC_HOLDER_NAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

ENDPOINT

Attribute	Description	
Name	ENDPOINT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

CHKBUKNUM

Attribute	Description	
Name	CHKBUKNUM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

ACCCY

Attribute	Description	
Name	ACCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

ACCCYAMT

Attribute	Description	
Name	ACCCYAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

BENCUSTID

Attribute	Description
Name	BENCUSTID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: pattern; Description: [a-zA-Z0-9]*

TOP

REMDET1

Attribute	Description
Name	REMDET1
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

REMDET2

Attribute	Description
Name	REMDET2
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

REMDET3

Attribute	Description
Name	REMDET3
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BENDET1

Attribute	**Description**
Name	BENDET1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BENDET2

Attribute	**Description**
Name	BENDET2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BENDET3

Attribute	**Description**
Name	BENDET3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DIN

Attribute	**Description**
Name	DIN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LOCLCLEARING

Attribute	Description	
Name	LOCLCLEARING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REMBANK

Attribute	Description	
Name	REMBANK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

REMBRANCH

Attribute	Description	
Name	REMBRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CHQVERDIGIT

Attribute	Description	
Name	CHQVERDIGIT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	0
	totalDigits	10

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 0 Restrictions: totalDigits — Description: 10

TOP

TXNID

Attribute	Description
Name	TXNID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ORGTXNID

Attribute	Description
Name	ORGTXNID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

DINDATE

Attribute	Description
Name	DINDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CUSTDATE

Attribute	Description

Name	CUSTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

XRATE

Attribute	**Description**
Name	XRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

Mis-Details

Attribute	**Description**
Name	Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; minInclusive / 0; totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	**Description**
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	**Description**
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	**Description**
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 minLength — 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 minLength — 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	**Description**
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	**Description**
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	**Description**
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	**Description**
Name	COMPMIS6LBL6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions / Description: maxLength 9; minLength 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions / Description: maxLength 9; minLength 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions / Description: maxLength 9; minLength 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	**Description**
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	**Description**
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	**Description**
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	Indicated the Charge Component Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

CHGAMT

Attribute	Description	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCY

Attribute	Description	
Name	CHGCCY	
Datatype	String	
Description	Indicates the currency of the charged amount.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description	Indicates the MIS head for charge.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

TXNCODE

Attribute	Description	
Name	TXNCODE	
Datatype	String	
Description	Indicates the transacton code for charge	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

TOP

NETTINGIND

Attribute	Description
Name	NETTINGIND
Datatype	String
Description	Indicates whether charge need to be netted or not.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

CHGGL

Attribute	Description
Name	CHGGL
Datatype	String
Description	Indicates th GL associated with charge.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

TYPE

Attribute	Description
Name	TYPE
Datatype	String
Description	Indicates the type of charge. F - Fixed, P - Percentage, I - Interest
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LCYCHG

Attribute	Description
Name	LCYCHG
Datatype	Number
Description	Indicates the chage in local currency.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 3 Restrictions: totalDigits — Description: 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

TCYCHG

Attribute	Description
Name	TCYCHG
Datatype	Number
Description	Indicate the charge in transaction currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

TCYXRATE

Attribute	Description
Name	TCYXRATE
Datatype	Number
Description	Indicates the exchange rate for transaction currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

Transaction-Details-PK

Attribute	Description
Name	Transaction-Details-PK
Datatype	
Description	Includes the information Regarding Input of Clearing Transaction Primary Key Details.

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS error Response Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description

Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.56.QueryTransaction

Query of Clearing Transaction

2.56.1.CGTransaction-Query-Req-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Transaction-Details
XREF
Clearing-Details
FCCREF

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration — Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 12 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 128 Restrictions: pattern; Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Input Only information relating to the Clearing Transaction that has to be Queried

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes information relating to the Clearing Transaction that has to be Queried.

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

2.56.2.CGTransaction-Query-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transaction-Details*
    - *XREF*
    - *SCODE*
    - *STATUS*
    - *BATCHTOTAMT*
    - *CONSOLIDATED*
    - *DEPSLIP*
    - *BENACCOUNT1*
    - *Clearing-Details*
      - *PRODUCT*
      - *FCCREF*
      - *ESN*
      - *REMACCOUNT*
      - *INSTRNO*
      - *INSTRCCY*
      - *INSTRAMT*
      - *INSTRDATE*
      - *CHEQUEISSUEDATE*
      - *TXNDATE*

VALDATE
LATECLG
ROUTINGNO
SERIALNO
ENTRYNO
REGCC
SPLCHQ
TXNBRN
BENACCOUNT
TXNCCY
ENDPOINT
CHKBUKNUM
ACCCY
ACCCYAMT
ROUTBNKCOD
ROUTBRNCOD
ROUTSECTCOD
BENCUSTID
REMCUST
ACCBRN
INSTRNO2
ERRCODE
LCYCHGAMT
CHGCCYLCYXRT
LCYCHGAMT1
CHGCCYLCYXRT1
LCYCHGAMT2
CHGCCYLCYXRT2
LCYCHGAMT3
CHGCCYLCYXRT3
LCYCHGAMT4
CHGCCYLCYXRT4
ACYTOTCHGAMT
CR_CARD_NO
CC_HOLDER_NAME
REMBANK
REMBRANCH
BENBANK
BENBRANCH
BENCCY
ROUTBNKNAM
ROUTBRNNAM
ROUTSECTDISC
LCYTOTCHGAMT

TCYTOTCHGAMT
DENMCCY1
DENMAMT1
DENMCCY2
DENMAMT2
XRATE
DIRECTION
REMDET1
REMDET2
REMDET3
BENDET1
BENDET2
BENDET3
LOCLCLEARING
CHQVERDIGIT
TXNID
ORGTXNID
DIN
DINDATE
CUSTDATE
MODULE
MODREFNO
REJREASON
CUSTID
ACCTITLE
CUSTNAME
REMARKS
ACTAMT
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
MODNO
RECORDSTAT
AUTHSTAT
ONCEAUTH
STATUS
RECTYPE
TXNCD
DOCTYPE

Mis-Details

BRANCH
CUSTNO
MISGRP

REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3

TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Details

CHGCOMP

WAIVER

CHGAMT

CHGCCY

MISHEAD

TXNCODE

NETTINGIND

CHGGL

TYPE

LCYCHG

XRATE

TCYCHG

TCYXRATE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Full Response information relating to the Clearing Transaction that has been successfully Queried

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the Full Response information relating to the Clearing Transaction that has been successfully Queried.

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 20

TOP

SCODE

Attribute	Description
Name	SCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 4

TOP

BATCHTOTAMT

Attribute	Description
Name	BATCHTOTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: fractionDigits, Description: 3 Restrictions: totalDigits, Description: 22

TOP

CONSOLIDATED

Attribute	Description
Name	CONSOLIDATED
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

DEPSLIP

Attribute	Description
Name	DEPSLIP
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

BENACCOUNT1

Attribute	**Description**
Name	BENACCOUNT1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

Clearing-Details

Attribute	**Description**
Name	Clearing-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

PRODUCT

Attribute	**Description**
Name	PRODUCT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

FCCREF

Attribute	**Description**
Name	FCCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRCCY

Attribute	Description
Name	INSTRCCY
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

INSTRAMT

Attribute	Description
Name	INSTRAMT
Datatype	Number
Description	

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	

TOP

CHEQUEISSUEDATE

Attribute	Description
Name	CHEQUEISSUEDATE
Datatype	Date
Description	

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	

TOP

VALDATE

Attribute	Description	
Name	VALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATECLG

Attribute	Description	
Name	LATECLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 27

TOP

SERIALNO

Attribute	Description
Name	SERIALNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ENTRYNO

Attribute	Description
Name	ENTRYNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 9

TOP

REGCC

Attribute	Description
Name	REGCC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SPLCHQ

Attribute	Description
Name	SPLCHQ
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TXNBRN

Attribute	Description
Name	TXNBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

BENACCOUNT

Attribute	Description
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

TXNCCY

Attribute	Description
Name	TXNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

CHKBUKNUM

Attribute	Description	
Name	CHKBUKNUM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

ACCCY

Attribute	Description	
Name	ACCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

ACCCYAMT

Attribute	Description	
Name	ACCCYAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

ROUTBNKCOD

Attribute	Description	
Name	ROUTBNKCOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

ROUTBRNCOD

Attribute	Description	
Name	ROUTBRNCOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

ROUTSECTCOD

Attribute	Description	
Name	ROUTSECTCOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

BENCUSTID

Attribute	Description	
Name	BENCUSTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

REMCUST

Attribute	Description	
Name	REMCUST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

INSTRNO2

Attribute	Description	
Name	INSTRNO2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ERRCODE

Attribute	Description	
Name	ERRCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LCYCHGAMT

Attribute	Description	
Name	LCYCHGAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT

Attribute	Description	
Name	CHGCCYLCYXRT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT1

Attribute	Description	
Name	LCYCHGAMT1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT1

Attribute	Description	
Name	CHGCCYLCYXRT1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT2

Attribute	Description	
Name	LCYCHGAMT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT2

Attribute	Description	
Name	CHGCCYLCYXRT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT3

Attribute	Description	
Name	LCYCHGAMT3	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT3

Attribute	Description	
Name	CHGCCYLCYXRT3	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT4

Attribute	Description	
Name	LCYCHGAMT4	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT4

Attribute	Description	
Name	CHGCCYLCYXRT4	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

ACYTOTCHGAMT

Attribute	Description	
Name	ACYTOTCHGAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CR_CARD_NO

Attribute	Description	
Name	CR_CARD_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

TOP

CC_HOLDER_NAME

Attribute	Description	
Name	CC_HOLDER_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

REMBANK

Attribute	Description	
Name	REMBANK	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

REMBRANCH

Attribute	Description	
Name	REMBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

BENBANK

Attribute	Description	
Name	BENBANK	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

BENBRANCH

Attribute	Description	
Name	BENBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

BENCCY

Attribute	Description	
Name	BENCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

ROUTBNKNAM

Attribute	Description	
Name	ROUTBNKNAM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ROUTBRNNAM

Attribute	Description	
Name	ROUTBRNNAM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ROUTSECTDISC

Attribute	Description	
Name	ROUTSECTDISC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

LCYTOTCHGAMT

Attribute	Description
Name	LCYTOTCHGAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 3 Restrictions: totalDigits — Description: 22

TOP

TCYTOTCHGAMT

Attribute	Description
Name	TCYTOTCHGAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 3 Restrictions: totalDigits — Description: 22

TOP

DENMCCY1

Attribute	Description
Name	DENMCCY1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [A-Z]{3}

TOP

DENMAMT1

Attribute	Description
Name	DENMAMT1
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

DENMCCY2

Attribute	Description	
Name	DENMCCY2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

DENMAMT2

Attribute	Description	
Name	DENMAMT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

DIRECTION

Attribute	Description	
Name	DIRECTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	I,O

TOP

REMDET1

Attribute	Description
Name	REMDET1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REMDET2

Attribute	Description
Name	REMDET2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REMDET3

Attribute	Description
Name	REMDET3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

BENDET1

Attribute	Description
Name	BENDET1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

BENDET2

Attribute	Description
Name	BENDET2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BENDET3

Attribute	Description
Name	BENDET3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LOCLCLEARING

Attribute	Description
Name	LOCLCLEARING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHQVERDIGIT

Attribute	Description
Name	CHQVERDIGIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

TXNID

Attribute	Description
Name	TXNID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ORGTXNID

Attribute	Description
Name	ORGTXNID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

DIN

Attribute	Description
Name	DIN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

DINDATE

Attribute	Description
Name	DINDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CUSTDATE

Attribute	Description
Name	CUSTDATE
Datatype	Date

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [A-Z]*

TOP

MODREFNO

Attribute	Description
Name	MODREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

REJREASON

Attribute	Description
Name	REJREASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

ACCTITLE

Attribute	**Description**
Name	ACCTITLE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTNAME

Attribute	**Description**
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ACTAMT

Attribute	**Description**
Name	ACTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

RECTYPE

Attribute	Description
Name	RECTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TXNCD

Attribute	Description
Name	TXNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Mis-Details

Attribute	Description

Name	Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	**Description**
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	**Description**
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	**Description**
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	**Description**
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description

Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	**Description**
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	**Description**
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	**Description**
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	Attribute: minOccurs — Description: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	**Description**
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	**Description**
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	**Description**
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	**Description**
Name	COMPMIS6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

COSTCOD4

Attribute	Description	
Name	COSTCOD4	
Datatype	String	
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

COSTCOD5

Attribute	Description	
Name	COSTCOD5	
Datatype	String	
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

LINKGRP

Attribute	Description	
Name	LINKGRP	
Datatype	String	
Description	Indicates Link to Group	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12
	minLength	1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	**Description**
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	**Description**
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	**Description**
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	**Description**
Name	TXNMIS2LBL2
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	**Description**
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	**Description**
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	**Description**
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	Restrictions: maxLength — Description: 105 Restrictions: minLength — Description: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	Indicated the Charge Component Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	Indicates the MIS head for charge.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNCODE

Attribute	Description
Name	TXNCODE
Datatype	String
Description	Indicates the transacton code for charge
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETTINGIND

Attribute	Description
Name	NETTINGIND
Datatype	String
Description	Indicates whether charge need to be netted or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGGL

Attribute	Description
Name	CHGGL
Datatype	String
Description	Indicates th GL associated with charge.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

TYPE

Attribute	Description

Name	TYPE
Datatype	String
Description	Indicates the type of charge. F - Fixed, P - Percentage, I - Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LCYCHG

Attribute	**Description**
Name	LCYCHG
Datatype	Number
Description	Indicates the chage in local currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	**Description**
Name	XRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

TCYCHG

Attribute	**Description**
Name	TCYCHG
Datatype	Number
Description	Indicate the charge in transaction currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TCYXRATE

Attribute	**Description**
Name	TCYXRATE

Datatype	Number
Description	Indicates the exchange rate for transaction currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response Details.

Attributes		
	Attribute	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.57.ReverseTransaction

Reversal of Clearing Transaction

2.57.1.CGTransaction-Reverse-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transaction-Details*
    - *XREF*
    - *SCODE*
    - *STATUS*
    - *BATCHTOTAMT*
    - *CONSOLIDATED*
    - *DEPSLIP*
    - *BENACCOUNT1*
    - *Clearing-Details*
      - *PRODUCT*
      - *FCCREF*
      - *ESN*
      - *REMACCOUNT*
      - *INSTRNO*
      - *INSTRCCY*
      - *INSTRAMT*

INSTRDATE
CHEQUEISSUEDATE
TXNDATE
VALDATE
LATECLG
ROUTINGNO
SERIALNO
ENTRYNO
REGCC
SPLCHQ
TXNBRN
BENACCOUNT
TXNCCY
ENDPOINT
CHKBUKNUM
ACCCY
ACCCYAMT
ROUTBNKCOD
ROUTBRNCOD
ROUTSECTCOD
BENCUSTID
REMCUST
ACCBRN
INSTRNO2
ERRCODE
LCYCHGAMT
CHGCCYLCYXRT
LCYCHGAMT1
CHGCCYLCYXRT1
LCYCHGAMT2
CHGCCYLCYXRT2
LCYCHGAMT3
CHGCCYLCYXRT3
LCYCHGAMT4
CHGCCYLCYXRT4
ACYTOTCHGAMT
CR_CARD_NO
CC_HOLDER_NAME
REMBANK
REMBRANCH
BENBANK
BENBRANCH
BENCCY
ROUTBNKNAM

ROUTBRNNAM
ROUTSECTDISC
LCYTOTCHGAMT
TCYTOTCHGAMT
DENMCCY1
DENMAMT1
DENMCCY2
DENMAMT2
XRATE
DIRECTION
REMDET1
REMDET2
REMDET3
BENDET1
BENDET2
BENDET3
LOCLCLEARING
CHQVERDIGIT
TXNID
ORGTXNID
DIN
DINDATE
CUSTDATE
MODULE
MODREFNO
REJREASON
CUSTID
ACCTITLE
CUSTNAME
REMARKS
ACTAMT
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
MODNO
RECORDSTAT
AUTHSTAT
ONCEAUTH
STATUS
RECTYPE
TXNCD
DOCTYPE

Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG

TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE

FIELD_VALUE
VAL_TYPE
Charge-Details
CHGCOMP
WAIVER
CHGAMT
CHGCCY
MISHEAD
TXNCODE
NETTINGIND
CHGGL
TYPE
LCYCHG
XRATE
TCYCHG
TCYXRATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for information relating to the Clearing Transaction that has to be Reversed

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the information relating to the Clearing Transaction that has to be Reversed.

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SCODE

Attribute	Description
Name	SCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z_0-9]*

TOP

STATUS

Attribute	Description

Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BATCHTOTAMT

Attribute	**Description**
Name	BATCHTOTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CONSOLIDATED

Attribute	**Description**
Name	CONSOLIDATED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEPSLIP

Attribute	**Description**
Name	DEPSLIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

BENACCOUNT1

Attribute	**Description**
Name	BENACCOUNT1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded

TOP

PRODUCT

Attribute	Description
Name	PRODUCT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**
	length / 4
	pattern / [a-zA-Z0-9]{4}

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	fractionDigits / 0
	totalDigits / 10

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRCCY

Attribute	Description
Name	INSTRCCY
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

INSTRAMT

Attribute	Description
Name	INSTRAMT
Datatype	Number
Description	
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	

TOP

CHEQUEISSUEDATE

Attribute	Description
Name	CHEQUEISSUEDATE
Datatype	Date
Description	

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	

TOP

VALDATE

Attribute	Description	
Name	VALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATECLG

Attribute	Description	
Name	LATECLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ROUTINGNO

Attribute	Description	
Name	ROUTINGNO	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	27

TOP

SERIALNO

Attribute	Description

Name	SERIALNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ENTRYNO

Attribute	**Description**
Name	ENTRYNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 9

TOP

REGCC

Attribute	**Description**
Name	REGCC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SPLCHQ

Attribute	**Description**
Name	SPLCHQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TXNBRN

Attribute	**Description**
Name	TXNBRN
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

BENACCOUNT

Attribute	Description	
Name	BENACCOUNT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

TXNCCY

Attribute	Description	
Name	TXNCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

ENDPOINT

Attribute	Description	
Name	ENDPOINT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

CHKBUKNUM

Attribute	Description	
Name	CHKBUKNUM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	2000

TOP

ACCCY

Attribute	Description	
Name	ACCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

ACCCYAMT

Attribute	Description	
Name	ACCCYAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

ROUTBNKCOD

Attribute	Description	
Name	ROUTBNKCOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

ROUTBRNCOD

Attribute	Description	
Name	ROUTBRNCOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

ROUTSECTCOD

Attribute	**Description**
Name	ROUTSECTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z_0-9]*

TOP

BENCUSTID

Attribute	**Description**
Name	BENCUSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

REMCUST

Attribute	**Description**
Name	REMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ACCBRN

Attribute	**Description**
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

INSTRNO2

Attribute	Description	
Name	INSTRNO2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

ERRCODE

Attribute	Description	
Name	ERRCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

TOP

LCYCHGAMT

Attribute	Description	
Name	LCYCHGAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT

Attribute	Description	
Name	CHGCCYLCYXRT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT1

Attribute	Description	
Name	LCYCHGAMT1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT1

Attribute	Description	
Name	CHGCCYLCYXRT1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT2

Attribute	Description	
Name	LCYCHGAMT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT2

Attribute	Description	
Name	CHGCCYLCYXRT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT3

Attribute	Description	
Name	LCYCHGAMT3	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT3

Attribute	Description	
Name	CHGCCYLCYXRT3	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT4

Attribute	Description	
Name	LCYCHGAMT4	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT4

Attribute	Description	
Name	CHGCCYLCYXRT4	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

ACYTOTCHGAMT

Attribute	Description	
Name	ACYTOTCHGAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CR_CARD_NO

Attribute	Description	
Name	CR_CARD_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

TOP

CC_HOLDER_NAME

Attribute	Description	
Name	CC_HOLDER_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

TOP

REMBANK

Attribute	Description	
Name	REMBANK	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

REMBRANCH

Attribute	Description
Name	REMBRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

BENBANK

Attribute	Description
Name	BENBANK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: pattern — Description: [a-zA-Z0-9]*

TOP

BENBRANCH

Attribute	Description
Name	BENBRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

BENCCY

Attribute	Description
Name	BENCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

ROUTBNKNAM

Attribute	Description	
Name	ROUTBNKNAM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ROUTBRNNAM

Attribute	Description	
Name	ROUTBRNNAM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ROUTSECTDISC

Attribute	Description	
Name	ROUTSECTDISC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

LCYTOTCHGAMT

Attribute	Description	
Name	LCYTOTCHGAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

TCYTOTCHGAMT

Attribute	Description
Name	TCYTOTCHGAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: fractionDigits, Description: 3 Restrictions: totalDigits, Description: 22

TOP

DENMCCY1

Attribute	Description
Name	DENMCCY1
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: length, Description: 3 Restrictions: pattern, Description: [A-Z]{3}

TOP

DENMAMT1

Attribute	Description
Name	DENMAMT1
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: fractionDigits, Description: 3 Restrictions: totalDigits, Description: 22

TOP

DENMCCY2

Attribute	Description
Name	DENMCCY2
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

DENMAMT2

Attribute	Description	
Name	DENMAMT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

DIRECTION

Attribute	Description	
Name	DIRECTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	I,O

TOP

REMDET1

Attribute	Description	
Name	REMDET1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REMDET2

Attribute	**Description**
Name	REMDET2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REMDET3

Attribute	**Description**
Name	REMDET3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BENDET1

Attribute	**Description**
Name	BENDET1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BENDET2

Attribute	**Description**
Name	BENDET2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BENDET3

Attribute	Description
Name	BENDET3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LOCLCLEARING

Attribute	Description
Name	LOCLCLEARING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHQVERDIGIT

Attribute	Description
Name	CHQVERDIGIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0 totalDigits / 10

TOP

TXNID

Attribute	Description
Name	TXNID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ORGTXNID

Attribute	Description
Name	ORGTXNID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 255

TOP

DIN

Attribute	Description
Name	DIN
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 16

TOP

DINDATE

Attribute	Description
Name	DINDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CUSTDATE

Attribute	Description
Name	CUSTDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	pattern	[A-Z]*

TOP

MODREFNO

Attribute	Description
Name	MODREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REJREASON

Attribute	Description
Name	REJREASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z0-9]*

TOP

ACCTITLE

Attribute	Description
Name	ACCTITLE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACTAMT

Attribute	Description
Name	ACTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	0
	totalDigits	10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

RECTYPE

Attribute	Description
Name	RECTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

TXNCD

Attribute	Description
Name	TXNCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 9 Restrictions: minLength, Description: 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 12 Restrictions: minLength, Description: 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 16 Restrictions: minLength, Description: 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	Attribute: minOccurs, Description: 0

Restrictions	Restrictions	Description
	maxLength	16
	minLength	1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	Attribute: Description minOccurs: 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 9 minLength: 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description fractionDigits: 15 minInclusive: 0 totalDigits: 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	fractionDigits: 5; minInclusive: 0; totalDigits: 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	maxLength: 9; minLength: 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	maxLength: 9; minLength: 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS7

Attribute	Description

Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	**Description**
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	**Description**
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	**Description**
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	**Description**
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	**Description**
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	**Description**
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 minLength — 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 minLength — 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	**Description**
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	**Description**
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	**Description**
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	**Description**
Name	COMPMIS6LBL6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	Indicated the Charge Component Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

CHGAMT

Attribute	Description	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCY

Attribute	Description	
Name	CHGCCY	
Datatype	String	
Description	Indicates the currency of the charged amount.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description	Indicates the MIS head for charge.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

TXNCODE

Attribute	Description	
Name	TXNCODE	
Datatype	String	
Description	Indicates the transacton code for charge	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

TOP

NETTINGIND

Attribute	Description
Name	NETTINGIND
Datatype	String
Description	Indicates whether charge need to be netted or not.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

CHGGL

Attribute	Description
Name	CHGGL
Datatype	String
Description	Indicates th GL associated with charge.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

TYPE

Attribute	Description
Name	TYPE
Datatype	String
Description	Indicates the type of charge. F - Fixed, P - Percentage, I - Interest
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LCYCHG

Attribute	Description
Name	LCYCHG
Datatype	Number
Description	Indicates the chage in local currency.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 3 Restrictions: totalDigits — Description: 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

TCYCHG

Attribute	Description
Name	TCYCHG
Datatype	Number
Description	Indicate the charge in transaction currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

TCYXRATE

Attribute	Description
Name	TCYXRATE
Datatype	Number
Description	Indicates the exchange rate for transaction currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

2.57.2.CGTransaction-Reverse-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transaction-Details*
    - *XREF*
    - *Clearing-Details*
      - *FCCREF*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Input Only information relating to the Clearing Transaction that has to be Reversed

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the information relating to the Clearing Transaction that has to be Reversed.

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Clearing-Details

Attribute	Description

Name	Clearing-Details
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

2.57.3.CGTransaction-Reverse-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transaction-Details*
    - *XREF*
    - *SCODE*
    - *STATUS*
    - *BATCHTOTAMT*
    - *CONSOLIDATED*
    - *DEPSLIP*
    - *BENACCOUNT1*
    - *Clearing-Details*
      - *PRODUCT*
      - *FCCREF*
      - *ESN*
      - *REMACCOUNT*
      - *INSTRNO*
      - *INSTRCCY*
      - *INSTRAMT*
      - *INSTRDATE*
      - *CHEQUEISSUEDATE*
      - *TXNDATE*

VALDATE
LATECLG
ROUTINGNO
SERIALNO
ENTRYNO
REGCC
SPLCHQ
TXNBRN
BENACCOUNT
TXNCCY
ENDPOINT
CHKBUKNUM
ACCCY
ACCCYAMT
ROUTBNKCOD
ROUTBRNCOD
ROUTSECTCOD
BENCUSTID
REMCUST
ACCBRN
INSTRNO2
ERRCODE
LCYCHGAMT
CHGCCYLCYXRT
LCYCHGAMT1
CHGCCYLCYXRT1
LCYCHGAMT2
CHGCCYLCYXRT2
LCYCHGAMT3
CHGCCYLCYXRT3
LCYCHGAMT4
CHGCCYLCYXRT4
ACYTOTCHGAMT
CR_CARD_NO
CC_HOLDER_NAME
REMBANK
REMBRANCH
BENBANK
BENBRANCH
BENCCY
ROUTBNKNAM
ROUTBRNNAM
ROUTSECTDISC
LCYTOTCHGAMT

TCYTOTCHGAMT

DENMCCY1

DENMAMT1

DENMCCY2

DENMAMT2

XRATE

DIRECTION

REMDET1

REMDET2

REMDET3

BENDET1

BENDET2

BENDET3

LOCLCLEARING

CHQVERDIGIT

TXNID

ORGTXNID

DIN

DINDATE

CUSTDATE

MODULE

MODREFNO

REJREASON

CUSTID

ACCTITLE

CUSTNAME

REMARKS

ACTAMT

MAKERID

MAKERSTAMP

CHECKERID

CHECKERSTAMP

MODNO

RECORDSTAT

AUTHSTAT

ONCEAUTH

STATUS

RECTYPE

TXNCD

DOCTYPE

Mis-Details

BRANCH

CUSTNO

MISGRP

REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3

- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *TXNMIS10*
- *FUNDMIS1LBL1*
- *FUNDMIS2LBL2*
- *FUNDMIS3LBL3*
- *FUNDMIS4LBL4*
- *FUNDMIS5LBL5*
- *FUNDMIS6LBL6*
- *FUNDMIS7LBL7*
- *FUNDMIS8LBL8*
- *FUNDMIS9LBL9*
- *FUNDMIS10LBL10*
- *COMPMIS1LBL1*
- *COMPMIS2LBL2*
- *COMPMIS3LBL3*
- *COMPMIS4LBL4*
- *COMPMIS5LBL5*
- *COMPMIS6LBL6*
- *COMPMIS7LBL7*
- *COMPMIS8LBL8*
- *COMPMIS9LBL9*
- *COMPMIS10LBL10*
- *TXNMIS1LBL1*
- *TXNMIS2LBL2*
- *TXNMIS3LBL3*
- *TXNMIS4LBL4*
- *TXNMIS5LBL5*
- *TXNMIS6LBL6*
- *TXNMIS7LBL7*
- *TXNMIS8LBL8*
- *TXNMIS9LBL9*
- *TXNMIS10LBL10*

Udf-Details

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Charge-Details

CHGCOMP

WAIVER

CHGAMT

CHGCCY

MISHEAD

TXNCODE

NETTINGIND

CHGGL

TYPE

LCYCHG

XRATE

TCYCHG

TCYXRATE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for information relating to the Clearing Transaction that has to be Reversed

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the information relating to the Clearing Transaction that has to be Reversed.

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 20

TOP

SCODE

Attribute	Description
Name	SCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 4

TOP

BATCHTOTAMT

Attribute	Description
Name	BATCHTOTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: fractionDigits; Description: 3 Restrictions: totalDigits; Description: 22

TOP

CONSOLIDATED

Attribute	Description
Name	CONSOLIDATED
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: Y,N

TOP

DEPSLIP

Attribute	Description
Name	DEPSLIP
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

BENACCOUNT1

Attribute	**Description**
Name	BENACCOUNT1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

Clearing-Details

Attribute	**Description**
Name	Clearing-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

PRODUCT

Attribute	**Description**
Name	PRODUCT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

FCCREF

Attribute	**Description**
Name	FCCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRCCY

Attribute	Description
Name	INSTRCCY
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

INSTRAMT

Attribute	Description
Name	INSTRAMT
Datatype	Number
Description	

Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	

TOP

CHEQUEISSUEDATE

Attribute	Description
Name	CHEQUEISSUEDATE
Datatype	Date
Description	

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATECLG

Attribute	Description
Name	LATECLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 27

TOP

SERIALNO

Attribute	Description
Name	SERIALNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ENTRYNO

Attribute	Description
Name	ENTRYNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 9

TOP

REGCC

Attribute	Description
Name	REGCC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SPLCHQ

Attribute	Description
Name	SPLCHQ
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TXNBRN

Attribute	Description
Name	TXNBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

BENACCOUNT

Attribute	Description
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

TXNCCY

Attribute	Description
Name	TXNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

CHKBUKNUM

Attribute	Description
Name	CHKBUKNUM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [A-Z]{3}

TOP

ACCCYAMT

Attribute	Description
Name	ACCCYAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 3 Restrictions: totalDigits — Description: 22

TOP

ROUTBNKCOD

Attribute	Description
Name	ROUTBNKCOD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

ROUTBRNCOD

Attribute	Description	
Name	ROUTBRNCOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

ROUTSECTCOD

Attribute	Description	
Name	ROUTSECTCOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

BENCUSTID

Attribute	Description	
Name	BENCUSTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

REMCUST

Attribute	Description	
Name	REMCUST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

INSTRNO2

Attribute	Description	
Name	INSTRNO2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ERRCODE

Attribute	Description	
Name	ERRCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LCYCHGAMT

Attribute	Description	
Name	LCYCHGAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT

Attribute	Description	
Name	CHGCCYLCYXRT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT1

Attribute	Description	
Name	LCYCHGAMT1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT1

Attribute	Description	
Name	CHGCCYLCYXRT1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT2

Attribute	Description	
Name	LCYCHGAMT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT2

Attribute	Description	
Name	CHGCCYLCYXRT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT3

Attribute	Description	
Name	LCYCHGAMT3	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT3

Attribute	Description	
Name	CHGCCYLCYXRT3	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT4

Attribute	Description	
Name	LCYCHGAMT4	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT4

Attribute	Description	
Name	CHGCCYLCYXRT4	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

ACYTOTCHGAMT

Attribute	Description	
Name	ACYTOTCHGAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CR_CARD_NO

Attribute	Description	
Name	CR_CARD_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

TOP

CC_HOLDER_NAME

Attribute	Description	
Name	CC_HOLDER_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

REMBANK

Attribute	Description	
Name	REMBANK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

REMBRANCH

Attribute	Description	
Name	REMBRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

BENBANK

Attribute	Description	
Name	BENBANK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

BENBRANCH

Attribute	Description	
Name	BENBRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

BENCCY

Attribute	Description
Name	BENCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [A-Z]{3}

TOP

ROUTBNKNAM

Attribute	Description
Name	ROUTBNKNAM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ROUTBRNNAM

Attribute	Description
Name	ROUTBRNNAM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ROUTSECTDISC

Attribute	Description
Name	ROUTSECTDISC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

LCYTOTCHGAMT

Attribute	Description	
Name	LCYTOTCHGAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

TCYTOTCHGAMT

Attribute	Description	
Name	TCYTOTCHGAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

DENMCCY1

Attribute	Description	
Name	DENMCCY1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

DENMAMT1

Attribute	Description	
Name	DENMAMT1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

DENMCCY2

Attribute	Description	
Name	DENMCCY2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

DENMAMT2

Attribute	Description	
Name	DENMAMT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

DIRECTION

Attribute	Description	
Name	DIRECTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	I,O

TOP

REMDET1

Attribute	Description
Name	REMDET1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REMDET2

Attribute	Description
Name	REMDET2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REMDET3

Attribute	Description
Name	REMDET3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

BENDET1

Attribute	Description
Name	BENDET1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

BENDET2

Attribute	Description
Name	BENDET2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BENDET3

Attribute	Description
Name	BENDET3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LOCLCLEARING

Attribute	Description
Name	LOCLCLEARING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHQVERDIGIT

Attribute	Description
Name	CHQVERDIGIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

TXNID

Attribute	Description
Name	TXNID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ORGTXNID

Attribute	Description
Name	ORGTXNID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DIN

Attribute	Description
Name	DIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DINDATE

Attribute	Description
Name	DINDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTDATE

Attribute	Description
Name	CUSTDATE
Datatype	Date

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [A-Z]*

TOP

MODREFNO

Attribute	Description
Name	MODREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

REJREASON

Attribute	Description
Name	REJREASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

ACCTITLE

Attribute	Description
Name	ACCTITLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ACTAMT

Attribute	Description
Name	ACTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

RECTYPE

Attribute	Description
Name	RECTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TXNCD

Attribute	Description
Name	TXNCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOCTYPE

Attribute	Description
Name	DOCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Mis-Details

Attribute	Description

Name	Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	**Description**
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	**Description**
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	**Description**
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	**Description**
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	**Description**
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	**Description**
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	**Description**
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	**Description**

Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	**Description**
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	**Description**
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	**Description**
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	Attribute: minOccurs — Description: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

COSTCOD4

Attribute	Description	
Name	COSTCOD4	
Datatype	String	
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

COSTCOD5

Attribute	Description	
Name	COSTCOD5	
Datatype	String	
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

LINKGRP

Attribute	Description	
Name	LINKGRP	
Datatype	String	
Description	Indicates Link to Group	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12
	minLength	1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	**Description**
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	**Description**
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	**Description**
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	**Description**
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	**Description**
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	**Description**
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	**Description**
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	**Description**
Name	TXNMIS2LBL2
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	**Description**
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	**Description**
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	**Description**
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	**Description**
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Udf-Details

Attribute	**Description**
Name	Udf-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	Indicated the Charge Component Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	Indicates the MIS head for charge.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNCODE

Attribute	Description
Name	TXNCODE
Datatype	String
Description	Indicates the transacton code for charge
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETTINGIND

Attribute	Description
Name	NETTINGIND
Datatype	String
Description	Indicates whether charge need to be netted or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGGL

Attribute	Description
Name	CHGGL
Datatype	String
Description	Indicates th GL associated with charge.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

TYPE

Attribute	Description

Name	TYPE
Datatype	String
Description	Indicates the type of charge. F - Fixed, P - Percentage, I - Interest
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LCYCHG

Attribute	**Description**
Name	LCYCHG
Datatype	Number
Description	Indicates the chage in local currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

XRATE

Attribute	**Description**
Name	XRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

TCYCHG

Attribute	**Description**
Name	TCYCHG
Datatype	Number
Description	Indicate the charge in transaction currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TCYXRATE

Attribute	**Description**
Name	TCYXRATE

Datatype	Number
Description	Indicates the exchange rate for transaction currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Transaction-Details*
      - *XREF*
      - *Clearing-Details*
        - *FCCREF*
    - *Transaction-Details-PK*
      - *XREF*
      - *Clearing-Details*
        - *FCCREF*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Input Only information relating to the Clearing Transaction that has to be Reversed

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the information relating to the Clearing Transaction that has to be Reversed.

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	

TOP

FCCREF

Attribute	Description	
Name	FCCREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

Transaction-Details-PK

Attribute	Description
Name	Transaction-Details-PK
Datatype	
Description	Includes the information relating to the Clearing Transaction that has to be Reversed with the primary key details.

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description

Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.58.QueryCcyClgHoliday

Query Currency cleading Holing

2.58.1.ST-QueryCcyClgHoliday-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CCY_Holiday_Details-IO*
    - *CCCY*
    - *YR*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CCY_Holiday_Details-IO

Attribute	Description
Name	CCY_Holiday_Details-IO
Datatype	
Description	

TOP

CCCY

Attribute	Description
Name	CCCY
Datatype	String
Description	Indicates Clearing Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

YR

Attribute	Description
Name	YR
Datatype	Number
Description	Indicates Year

TOP

2.58.2.ST-QueryCcyClgHoliday-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *CCY_Holiday_Details*
      - *CCCY*
      - *YR*
    - *CCY_Holiday_Details-Full*
      - *YR*
      - *WKLY_HOL*
      - *CCCY*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *CCY_Holiday_List*
        - *ccy1*
        - *yer*

mont

hol_lst

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength 12; pattern [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

CCY_Holiday_Details

Attribute	Description
Name	CCY_Holiday_Details
Datatype	
Description	Query Of Clearing Currency Holiday Details

TOP

CCCY

Attribute	Description	
Name	CCCY	
Datatype	String	
Description	Indicates Clearing Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

YR

Attribute	Description
Name	YR
Datatype	Number
Description	Indicates Year

TOP

CCY_Holiday_Details-Full

Attribute	Description
Name	CCY_Holiday_Details-Full
Datatype	
Description	Query Of Clearing Currency Holiday Details Full Type

TOP

YR

Attribute	Description
Name	YR
Datatype	Number
Description	Indicates Year

TOP

WKLY_HOL

Attribute	Description	
Name	WKLY_HOL	
Datatype	String	
Description	Indicates Weekly Holiday	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7

TOP

CCCY

Attribute	Description	
Name	CCCY	
Datatype	String	
Description	Indicates Clearing Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Specifies the User Id who has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether the record is Authorized atleast Once.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CCY_Holiday_List

Attribute	Description
Name	CCY_Holiday_List
Datatype	
Description	Currency Holiday List
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ccy1

Attribute	Description
Name	ccy1

Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

yer

Attribute	**Description**
Name	yer
Datatype	Number
Description	Indicates Year
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

mont

Attribute	**Description**
Name	mont
Datatype	Number
Description	Indicates Month
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

hol_lst

Attribute	**Description**
Name	hol_lst
Datatype	String
Description	Indicates Holiday List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 31

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	Warning Response Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

Clearing Service
[April] [2014]

Oracle Financial Services software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax:+91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2013], [2014], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of
this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any

kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.