

Gateway Documentation - Collections Service
Oracle FLEXCUBE Universal Banking Release 11.3.83.02.0
Release FCUBS_11.3.2.0.0LA
[April] [2014]



Table Of Contents

1. BACKGROUND	1
2. FCUBSCNService	2
2.1. AuthorizeCollectionInteraction	2
2.1.1. CN-AuthorizeCollectionInteraction-Req-Full-MSG.xsd	2
2.1.2. CN-AuthorizeCollectionInteraction-Req-IO-MSG.xsd	21
2.1.3. CN-AuthorizeCollectionInteraction-Res-Full-MSG.xsd	27
2.1.4. CN-AuthorizeCollectionInteraction-Res-PK-MSG.xsd	48
2.2. CreateCollectionInteraction	57
2.2.1. CN-CreateCollectionInteraction-Req-Full-MSG.xsd	57
2.2.2. CN-CreateCollectionInteraction-Req-IO-MSG.xsd	76
2.2.3. CN-CreateCollectionInteraction-Res-Full-MSG.xsd	87
2.2.4. CN-CreateCollectionInteraction-Res-PK-MSG.xsd	108
2.3. DeleteCollectionInteraction	122
2.3.1. CN-DeleteCollectionInteraction-Req-Full-MSG.xsd	122
2.3.2. CN-DeleteCollectionInteraction-Req-IO-MSG.xsd	141
2.3.3. CN-DeleteCollectionInteraction-Res-Full-MSG.xsd	147
2.3.4. CN-DeleteCollectionInteraction-Res-PK-MSG.xsd	168

1.BACKGROUND

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data. The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs.

The integration needs supported by the Gateway can be broadly categorized from the perspective of the Gateway as follows:

- 1. Inbound application integration** – used when any external system needs to add, modify or query information within FLEXCUBE UBS
- 2. Outbound application integration** – used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS

The following sections provide detailed XSD documentation of all operations available in FCUBSCNService of CN-Module

2.FCUBSCNService

Collections ServiceCollections Service

2.1.AuthorizeCollectionInteraction

AuthorizeCollectionInteraction

2.1.1.CN-AuthorizeCollectionInteraction-Req-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Main-Full

CLCTAGENTID

COLLREF_2

SRCCD

RECORD_DATE

ISN

AGNCYNAME

CUSTOMER

CUSTOMER_NAME1

INTSUBSEQNO

CLCTNESN

EXTREF

RECORGN

PROCESS_STAGE
TOTPTPAMT
ACTION_CODE
RESLT
ACTINDT
DELREASON
NEXTACTION
RSLTDT
NXTACTIONDT
COMNTS
NLS_HR
OFSMINS
CUSTMAIL
MEDIA
INTRACTIONPLACE
CUSTMOB
Asset
LOANREFNO
ASSETQUTPRINCIPAL
ASSETCCY
ASSETBRN
ASSETTOTALOVD
ASSETSCHOVD
ASSETUDETSTAT
ASSETAMT
Ptp
PTPAMT
PTPDT
AMTPAID
PTPSTAT
PTPCHARGE
TAGCCY
Footer
CONREFNO
MAKER
MAKDTTIME
CHKR
CHKDTTIME
EVNTSEQNO
CONSTAT
AUTHSTATS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node. Entire processing in FLEXCUBE UBS Messaging Database Layer is based upon the information provided in this node.

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description							
Name	USERID							
Datatype	String							
Description								
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*	
Restrictions	Description							
maxLength	12							
pattern	[A-Z_0-9]*							

[TOP](#)

BRANCH

Attribute	Description							
Name	BRANCH							
Datatype	String							
Description								
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}	
Restrictions	Description							
length	3							
pattern	[a-zA-Z_0-9]{3}							

[TOP](#)

MODULEID

Attribute	Description							
Name	MODULEID							
Datatype	String							
Description								
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true	
Attribute	Description							
minOccurs	0							
nillable	true							

[TOP](#)

SERVICE

Attribute	Description					
Name	SERVICE					
Datatype	String					
Description						
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true	
Attribute	Description					
nillable	true					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*	
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Request	

[TOP](#)

Main-Full

Attribute	Description	

Name	Main-Full
Datatype	
Description	It indicates Collection Interaction Authorization Full Request details of Collections module

[TOP](#)

CLCTAGENTID

Attribute	Description	
Name	CLCTAGENTID	
Datatype	String	
Description	Collection Agent to whom this collection is assigned	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

COLLREF_2

Attribute	Description	
Name	COLLREF_2	
Datatype	String	
Description	This is the unique reference number assigned to the collection process	
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

SRCCD

Attribute	Description	
Name	SRCCD	
Datatype	String	
Description	This denotes Source Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

RECORD_DATE

Attribute	Description	
Name	RECORD_DATE	
Datatype	Date	
Description	The date on which the interaction was created in the system	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ISN

Attribute	Description	
Name	ISN	
Datatype	String	
Description	Interaction Sequence Number for every new interaction	
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

AGNCYNAME

Attribute	Description	
Name	AGNCYNAME	
Datatype	String	
Description	Name of the Collecting Agency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

CUSTOMER

Attribute	Description	
Name	CUSTOMER	
Datatype	String	
Description	Counterparty of the underlying Asset	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

CUSTOMER_NAME1

Attribute	Description	
Name	CUSTOMER_NAME1	
Datatype	String	
Description	Displays the name of the customer	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

INTSUBSEQNO

Attribute	Description	
Name	INTSUBSEQNO	
Datatype	Number	
Description	Further actions on a recorded interaction will increment this number	

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CLCTNESN

Attribute	Description	
Name	CLCTNESN	
Datatype	Number	
Description	Collection Event Sequence Number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXTREF

Attribute	Description	
Name	EXTREF	
Datatype	String	
Description	Reference supplied by the external system in case the Interaction was uploaded	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

RECORGN

Attribute	Description	
Name	RECORGN	
Datatype	String	
Description	The types of the interactions booked 1. Manual 2. System Generated 3. Upload	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	M,S,U

[TOP](#)

PROCESS_STAGE

Attribute	Description	
Name	PROCESS_STAGE	
Datatype	String	
Description	The current stage of the interaction Ex: Initiated or Approved or Rejected or Executed	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	I,R,E,A

[TOP](#)

TOTPTPAMT

Attribute	Description					
Name	TOTPTPAMT					
Datatype	Number					
Description	This is the total amount, the customer promises to pay. Applicable only if the result of action is a factory shipped result code for PTP					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

[TOP](#)

ACTION_CODE

Attribute	Description					
Name	ACTION_CODE					
Datatype	String					
Description	This is the action that is being executed as part of the interaction carried out					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20	
Restrictions	Description					
maxLength	20					

[TOP](#)

RESLT

Attribute	Description					
Name	RESLT					
Datatype	String					
Description	This is the result of the action during execution					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20	
Restrictions	Description					
maxLength	20					

[TOP](#)

ACTINDT

Attribute	Description					
Name	ACTINDT					
Datatype	Date					
Description	This is the date of execution of the aforesaid action					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

[TOP](#)

DELREASON

Attribute	Description	
Name	DELREASON	
Datatype	String	
Description	The reason for the Account going into overdue as given by the Customer	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

NEXTACTION

Attribute	Description	
Name	NEXTACTION	
Datatype	String	
Description	This field denotes the next action that can be executed by the person	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

RSLTDT

Attribute	Description	
Name	RSLTDT	
Datatype	Date	
Description	Typically a Action Date, in case of WAITING action, the next action date can be taken as Result Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NXTACTIONDT

Attribute	Description	
Name	NXTACTIONDT	
Datatype	Date	
Description	Next Action Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMNTS

Attribute	Description	
Name	COMNTS	
Datatype	String	
Description	The comments related to the interaction can be captured here	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

NLS_HR

Attribute	Description					
Name	NLS_HR					
Datatype	Number					
Description	Hour of the interaction can be recorded					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

[TOP](#)

OFSMINS

Attribute	Description					
Name	OFSMINS					
Datatype	Number					
Description	Minute of the interaction can be recorded					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

[TOP](#)

CUSTMAIL

Attribute	Description					
Name	CUSTMAIL					
Datatype	String					
Description	Customer E-mail Id					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>		Restrictions	Description	maxLength	35
Restrictions	Description					
maxLength	35					

[TOP](#)

MEDIA

Attribute	Description					
Name	MEDIA					
Datatype	String					
Description	Media, Mail, FAX, Phone etc..					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>		Restrictions	Description	maxLength	35
Restrictions	Description					
maxLength	35					

[TOP](#)

INTRACTIONPLACE

Attribute	Description	
Name	INTRACTIONPLACE	
Datatype	String	
Description	Interaction Place. This is applicable for some actions like personal visit	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

CUSTMOB

Attribute	Description	
Name	CUSTMOB	
Datatype	Number	
Description	Customer Mobile Number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

Asset

Attribute	Description	
Name	Asset	
Datatype		
Description	Collection Asset Details	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LOANREFNO

Attribute	Description	
Name	LOANREFNO	
Datatype	String	
Description	This is a Asset Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

ASSETQUTPRINCIPAL

Attribute	Description	
Name	ASSETQUTPRINCIPAL	
Datatype	Number	
Description	Principal Outstanding Amount as on Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ASSETCCY

Attribute	Description	
Name	ASSETCCY	

Datatype	String	
Description	Currency in which the transaction takes place	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

ASSETBRN

Attribute	Description	
Name	ASSETBRN	
Datatype	String	
Description	Asset Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

ASSETTOTALOVD

Attribute	Description	
Name	ASSETTOTALOVD	
Datatype	Number	
Description	Total Overdue Amount as on Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ASSETSCHOVD

Attribute	Description	
Name	ASSETSCHOVD	
Datatype	Number	
Description	Total No of Schedules Overdue	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ASSETUDETSTAT

Attribute	Description	
Name	ASSETUDETSTAT	
Datatype	String	
Description	User Defined Status for the Asset Reference	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

ASSETAMT

Attribute	Description	
Name	ASSETAMT	
Datatype	Number	
Description	Total Asset Amount	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

Ptp

Attribute	Description	
Name	Ptp	
Datatype		
Description	Promise To Pay Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

PTPAMT

Attribute	Description	
Name	PTPAMT	
Datatype	Number	
Description	The Amount which Customer Promise to pay	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PTPDT

Attribute	Description	
Name	PTPDT	
Datatype	Date	
Description	Date on which the Amount will be paid	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMTPAID

Attribute	Description	
Name	AMTPAID	
Datatype	Number	
Description	Actual Amount paid by the customer	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PTPSTAT

Attribute	Description	
Name	PTPSTAT	
Datatype	String	
Description	PTP Status as on Date: Pending(P), Honored(H), Broken(B), Partial (L), Cancelled (C)	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	P,H,B,L

[TOP](#)

PTPCARGE

Attribute	Description	
Name	PTPCARGE	
Datatype	Number	
Description	Promise to Pay Charge	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

Footer

Attribute	Description	
Name	Footer	
Datatype		
Description	This includes Audit Trail Details	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CONREFNO

Attribute	Description	
Name	CONREFNO	

Datatype	String	
Description	The reference number for the contract booked	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	The user who books the Contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKDTTIME

Attribute	Description	
Name	MAKDTTIME	
Datatype	String	
Description	The date and Time at which the contract is booked	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

CHKR

Attribute	Description	
Name	CHKR	
Datatype	String	
Description	The Approver of the Contract Booked	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHKDTTIME

Attribute	Description	
Name	CHKDTTIME	
Datatype	String	
Description	The time at which the contract booked got approved	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

EVNTSEQNO

Attribute	Description	
Name	EVNTSEQNO	
Datatype	Number	
Description	Event sequence number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CONSTAT

Attribute	Description	
Name	CONSTAT	
Datatype	String	
Description	Contract Status : "Active", "Hold", "Reversed" etc..	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,O,C

[TOP](#)

AUTHSTATS

Attribute	Description	
Name	AUTHSTATS	
Datatype	String	
Description	The Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,U,A

[TOP](#)

2.1.2.CN-AuthorizeCollectionInteraction-Req-IO-MSG.xsd

FCUBS_HEADER

SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
 PARAM
 NAME
 VALUE

FCUBS_BODY

Main-IO
ISN

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node. Entire processing in FLEXCUBE UBS Messaging Database Layer is based upon the information provided in this node.

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions enumeration	Description FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute minOccurs nillable	Description 0 true
Restrictions	Restrictions pattern	Description [a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute minOccurs nillable	Description 0 true
Restrictions	Restrictions pattern	Description [a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions maxLength pattern	Description 12 [A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	

Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	

Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	It indicates Collection Interaction Authorization IO Request details of Collections module

[TOP](#)

ISN

Attribute	Description	
Name	ISN	
Datatype	String	
Description	Interaction Sequence Number for every new interaction	
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

2.1.3.CN-AuthorizeCollectionInteraction-Res-Full-MSG.xsd

FCUBS_HEADER

SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
 PARAM
 NAME
 VALUE

FCUBS_BODY

Main-Full
 CLCTAGENTID
 COLLREF_2
 SRCCD
 RECORD_DATE
 ISN
 AGNCYNAME
 CUSTOMER
 CUSTOMER_NAME1
 INTSUBSEQNO
 CLCTNESN
 EXTREF
 RECORGN
 PROCESS_STAGE
 TOTPTPAMT
 ACTION_CODE
 RESLT
 ACTINDT
 DELREASON

NEXTACTION
RSLTDT
NXTACTIONDT
COMNTS
NLS_HR
OFSMINS
CUSTMAIL
MEDIA
INTRACTIONPLACE
CUSTMOB
Asset
 LOANREFNO
 ASSETQUTPRINCIPAL
 ASSETCCY
 ASSETBRN
 ASSETTOTALOVD
 ASSETSCHOVD
 ASSETUDETSTAT
 ASSETAMT
Ptp
 PTPAMT
 PTPDAT
 AMTPAID
 PTPSTAT
 PTPCHARGE
 TAGCCY
Footer
 CONREFNO
 MAKER
 MAKDTTIME
 CHKR
 CHKDTTIME
 EVNTSEQNO
 CONSTAT
 AUTHSTATS
FCUBS_ERROR_RESP
 ERROR
 E CODE
 E DESC
FCUBS_WARNING_RESP
 WARNING
 W CODE
 W DESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node. Entire processing in FLEXCUBE UBS Messaging Database Layer is based upon the information provided in this node.

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

MSGID

Attribute	Description						
Name	MSGID						
Datatype	String						
Description							
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

[TOP](#)

CORRELIID

Attribute	Description
Name	CORRELIID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

PASSWORD

Attribute	Description	

Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/-]*

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

[TOP](#)

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	It indicates Collection Interaction Authorization Full Response details of Collections module

[TOP](#)

CLCTAGENTID

Attribute	Description	
Name	CLCTAGENTID	
Datatype	String	
Description	Collection Agent to whom this collection is assigned	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

COLLREF_2

Attribute	Description	
Name	COLLREF_2	
Datatype	String	
Description	This is the unique reference number assigned to the collection process	
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

SRCCD

Attribute	Description	
Name	SRCCD	
Datatype	String	
Description	This denotes Source Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

RECORD_DATE

Attribute	Description	
Name	RECORD_DATE	
Datatype	Date	
Description	The date on which the interaction was created in the system	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**ISN**

Attribute	Description	
Name	ISN	
Datatype	String	
Description	Interaction Sequence Number for every new interaction	
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**AGNCYNAME**

Attribute	Description	
Name	AGNCYNAME	
Datatype	String	
Description	Name of the Collecting Agency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)**CUSTOMER**

Attribute	Description	
Name	CUSTOMER	
Datatype	String	
Description	Counterparty of the underlying Asset	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)**CUSTOMER_NAME1**

Attribute	Description	
Name	CUSTOMER_NAME1	
Datatype	String	
Description	Displays the name of the customer	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)**INTSUBSEQNO**

Attribute	Description	
Name	INTSUBSEQNO	

Datatype	Number					
Description	Further actions on a recorded interaction will increment this number					
Attributes	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

[TOP](#)

CLCTNESN

Attribute	Description					
Name	CLCTNESN					
Datatype	Number					
Description	Collection Event Sequence Number					
Attributes	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

[TOP](#)

EXTREF

Attribute	Description					
Name	EXTREF					
Datatype	String					
Description	Reference supplied by the external system in case the Interaction was uploaded					
Attributes	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>maxLength</td> <td>30</td> </tr> </table>	Restrictions	Description	maxLength	30	
Restrictions	Description					
maxLength	30					

[TOP](#)

RECORGN

Attribute	Description					
Name	RECORGN					
Datatype	String					
Description	The types of the interactions booked 1. Manual 2. System Generated 3. Upload					
Attributes	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>enumeration</td> <td>M,S,U</td> </tr> </table>	Restrictions	Description	enumeration	M,S,U	
Restrictions	Description					
enumeration	M,S,U					

[TOP](#)

PROCESS_STAGE

Attribute	Description					
Name	PROCESS_STAGE					
Datatype	String					
Description	The current stage of the interaction Ex: Initiated or Approved or Rejected or Executed					
Attributes	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

Restrictions	Restrictions	Description
	enumeration	I,R,E,A

[TOP](#)

TOTPTPAMT

Attribute	Description					
Name	TOTPTPAMT					
Datatype	Number					
Description	This is the total amount, the customer promises to pay. Applicable only if the result of action is a factory shipped result code for PTP					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

[TOP](#)

ACTION_CODE

Attribute	Description					
Name	ACTION_CODE					
Datatype	String					
Description	This is the action that is being executed as part of the interaction carried out					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>		Restrictions	Description	maxLength	20
Restrictions	Description					
maxLength	20					

[TOP](#)

RESLT

Attribute	Description					
Name	RESLT					
Datatype	String					
Description	This is the result of the action during execution					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>		Restrictions	Description	maxLength	20
Restrictions	Description					
maxLength	20					

[TOP](#)

ACTINDT

Attribute	Description					
Name	ACTINDT					
Datatype	Date					
Description	This is the date of execution of the aforesaid action					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

[TOP](#)

DELREASON

Attribute	Description	

Name	DELREASON	
Datatype	String	
Description	The reason for the Account going into overdue as given by the Customer	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

NEXTACTION

Attribute	Description	
Name	NEXTACTION	
Datatype	String	
Description	This field denotes the next action that can be executed by the person	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

RSLTDT

Attribute	Description	
Name	RSLTDT	
Datatype	Date	
Description	Typically a Action Date, in case of WAITING action, the next action date can be taken as Result Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NXTACTIONNDT

Attribute	Description	
Name	NXTACTIONNDT	
Datatype	Date	
Description	Next Action Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMNTS

Attribute	Description	
Name	COMNTS	
Datatype	String	
Description	The comments related to the interaction can be captured here	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

NLS_HR

Attribute	Description	
Name	NLS_HR	
Datatype	Number	
Description	Hour of the interaction can be recorded	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

OFSMINS

Attribute	Description	
Name	OFSMINS	
Datatype	Number	
Description	Minute of the interaction can be recorded	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CUSTMAIL

Attribute	Description	
Name	CUSTMAIL	
Datatype	String	
Description	Customer E-mail Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

MEDIA

Attribute	Description	
Name	MEDIA	
Datatype	String	
Description	Media, Mail, FAX, Phone etc..	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

INTRACTIONPLACE

Attribute	Description	
Name	INTRACTIONPLACE	
Datatype	String	
Description	Interaction Place. This is applicable for some actions like personal visit	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

CUSTMOB

Attribute	Description	
Name	CUSTMOB	
Datatype	Number	
Description	Customer Mobile Number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

Asset

Attribute	Description	
Name	Asset	
Datatype		
Description	Collection Asset Details	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LOANREFNO

Attribute	Description	
Name	LOANREFNO	
Datatype	String	
Description	This is a Asset Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

ASSETQUTPRINCIPAL

Attribute	Description	
Name	ASSETQUTPRINCIPAL	
Datatype	Number	
Description	Principal Outstanding Amount as on Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ASSETCCY

Attribute	Description	
Name	ASSETCCY	

Datatype	String	
Description	Currency in which the transaction takes place	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

ASSETBRN

Attribute	Description	
Name	ASSETBRN	
Datatype	String	
Description	Asset Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

ASSETTOTALOVD

Attribute	Description	
Name	ASSETTOTALOVD	
Datatype	Number	
Description	Total Overdue Amount as on Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ASSETSCHOVD

Attribute	Description	
Name	ASSETSCHOVD	
Datatype	Number	
Description	Total No of Schedules Overdue	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ASSETUDETSTAT

Attribute	Description	
Name	ASSETUDETSTAT	
Datatype	String	
Description	User Defined Status for the Asset Reference	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

ASSETAMT

Attribute	Description	
Name	ASSETAMT	
Datatype	Number	
Description	Total Asset Amount	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

Ptp

Attribute	Description	
Name	Ptp	
Datatype		
Description	Promise To Pay Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

PTPAMT

Attribute	Description	
Name	PTPAMT	
Datatype	Number	
Description	The Amount which Customer Promise to pay	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PTPDT

Attribute	Description	
Name	PTPDT	
Datatype	Date	
Description	Date on which the Amount will be paid	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMTPAID

Attribute	Description	
Name	AMTPAID	
Datatype	Number	
Description	Actual Amount paid by the customer	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PTPSTAT

Attribute	Description	
Name	PTPSTAT	
Datatype	String	
Description	PTP Status as on Date: Pending(P), Honored(H), Broken(B), Partial (L), Cancelled (C)	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	P,H,B,L

[TOP](#)

PTPCARGE

Attribute	Description	
Name	PTPCARGE	
Datatype	Number	
Description	Promise to Pay Charge	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

Footer

Attribute	Description	
Name	Footer	
Datatype		
Description	This includes Audit Trail Details	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CONREFNO

Attribute	Description	
Name	CONREFNO	

Datatype	String	
Description	The reference number for the contract booked	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	The user who books the Contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKDTTIME

Attribute	Description	
Name	MAKDTTIME	
Datatype	String	
Description	The date and Time at which the contract is booked	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

CHKR

Attribute	Description	
Name	CHKR	
Datatype	String	
Description	The Approver of the Contract Booked	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHKDTTIME

Attribute	Description	
Name	CHKDTTIME	
Datatype	String	
Description	The time at which the contract booked got approved	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

EVNTSEQNO

Attribute	Description	
Name	EVNTSEQNO	
Datatype	Number	
Description	Event sequence number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CONSTAT

Attribute	Description	
Name	CONSTAT	
Datatype	String	
Description	Contract Status : "Active", "Hold", "Reversed" etc..	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,O,C

[TOP](#)

AUTHSTATS

Attribute	Description	
Name	AUTHSTATS	
Datatype	String	
Description	The Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,U,A

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.1.4.CN-AuthorizeCollectionInteraction-Res-PK-MSG.xsd

FCUBS_HEADER

SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
 PARAM
 NAME
 VALUE

FCUBS_BODY

CHOICE

Main-PK

ISN

Main-IO

ISN

FCUBS_ERROR_RESP

ERROR

E CODE

E DESC

FCUBS_WARNING_RESP

WARNING

W CODE

W DESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node. Entire processing in FLEXCUBE UBS Messaging Database Layer is based upon the information provided in this node.
-------------	--

[TOP](#)

SOURCE

Attribute	Description					
Name	SOURCE					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*	
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

[TOP](#)

UBSCOMP

Attribute	Description					
Name	UBSCOMP					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS	
Restrictions	Description					
enumeration	FCUBS,FCIS					

[TOP](#)

MSGID

Attribute	Description							
Name	MSGID							
Datatype	String							
Description								
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true	
Attribute	Description							
minOccurs	0							
nillable	true							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*			
Restrictions	Description							
pattern	[a-zA-Z_0-9]*							

[TOP](#)

CORRELID

Attribute	Description							
Name	CORRELID							
Datatype	String							
Description								
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true	
Attribute	Description							
minOccurs	0							
nillable	true							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*			
Restrictions	Description							
pattern	[a-zA-Z_0-9]*							

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about PK Response	

[TOP](#)

CHOICE

Attribute	Description	

Name	CHOICE
Datatype	
Description	

[TOP](#)

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	It indicates Collection Interaction Authorization PK Response details of Collections module

[TOP](#)

ISN

Attribute	Description	
Name	ISN	
Datatype	String	
Description	Interaction Sequence Number for every new interaction	
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

Main-IO

Attribute	Description	
Name	Main-IO	
Datatype		
Description	It indicates Collection Interaction Authorization IO Response details of Collections module	

[TOP](#)

ISN

Attribute	Description	
Name	ISN	
Datatype	String	
Description	Interaction Sequence Number for every new interaction	
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description	
Name	WCODE	

Datatype	String
Description	

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

2.2.CreateCollectionInteraction

CreateCollectionInteraction

2.2.1.CN-CreateCollectionInteraction-Req-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Main-Full

CLCTAGENTID

COLLREF_2

SRCCD

RECORD_DATE

ISN

AGNCYNAME

CUSTOMER

CUSTOMER_NAME1

INTSUBSEQNO

CLCTNESN

EXTREF

RECORGN

PROCESS_STAGE

TOTPTPAMT

ACTION_CODE

RESLT
ACTINDT
DELREASON
NEXTACTION
RSLTDT
NXTACTIONDT
COMNTS
NLS_HR
OFSMINS
CUSTMAIL
MEDIA
INTRACTIONPLACE
CUSTMOB

Asset

LOANREFNO
ASSETQUTPRINCIPAL
ASSETCCY
ASSETBRN
ASSETTOTALOVD
ASSETSCHOVD
ASSETUDETSTAT
ASSETAMT

Ptp

PTPAMT
PTPDAT
AMTPAID
PTPSTAT
PTPCHARGE
TAGCCY

Footer

CONREFNO
MAKER
MAKDTTIME
CHKR
CHKDTTIME
EVNTSEQNO
CONSTAT
AUTHSTATS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node. Entire processing in FLEXCUBE UBS Messaging Database Layer is based upon the information provided in this node.
-------------	--

[TOP](#)

SOURCE

Attribute	Description					
Name	SOURCE					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

[TOP](#)

UBSCOMP

Attribute	Description					
Name	UBSCOMP					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

[TOP](#)

MSGID

Attribute	Description							
Name	MSGID							
Datatype	String							
Description								
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	nillable	true
Attribute	Description							
minOccurs	0							
nillable	true							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description							
pattern	[a-zA-Z_0-9]*							

[TOP](#)

CORRELID

Attribute	Description							
Name	CORRELID							
Datatype	String							
Description								
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	nillable	true
Attribute	Description							
minOccurs	0							
nillable	true							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description							
pattern	[a-zA-Z_0-9]*							

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Request	

[TOP](#)

Main-Full

Attribute	Description	

Name	Main-Full
Datatype	
Description	It indicates Collection Interaction Creation Full Request details of Collections module

[TOP](#)

CLCTAGENTID

Attribute	Description					
Name	CLCTAGENTID					
Datatype	String					
Description	Collection Agent to whom this collection is assigned					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20	
Restrictions	Description					
maxLength	20					

[TOP](#)

COLLREF_2

Attribute	Description					
Name	COLLREF_2					
Datatype	String					
Description	This is the unique reference number assigned to the collection process					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>	Restrictions	Description	maxLength	16	
Restrictions	Description					
maxLength	16					

[TOP](#)

SRCCD

Attribute	Description					
Name	SRCCD					
Datatype	String					
Description	This denotes Source Code					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>15</td></tr> </tbody> </table>	Restrictions	Description	maxLength	15	
Restrictions	Description					
maxLength	15					

[TOP](#)

RECORD_DATE

Attribute	Description					
Name	RECORD_DATE					
Datatype	Date					
Description	The date on which the interaction was created in the system					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

[TOP](#)

ISN

Attribute	Description	
Name	ISN	
Datatype	String	
Description	Interaction Sequence Number for every new interaction	
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

AGNCYNAME

Attribute	Description	
Name	AGNCYNAME	
Datatype	String	
Description	Name of the Collecting Agency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

CUSTOMER

Attribute	Description	
Name	CUSTOMER	
Datatype	String	
Description	Counterparty of the underlying Asset	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

CUSTOMER_NAME1

Attribute	Description	
Name	CUSTOMER_NAME1	
Datatype	String	
Description	Displays the name of the customer	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

INTSUBSEQNO

Attribute	Description	
Name	INTSUBSEQNO	
Datatype	Number	
Description	Further actions on a recorded interaction will increment this number	

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CLCTNESN

Attribute	Description	
Name	CLCTNESN	
Datatype	Number	
Description	Collection Event Sequence Number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXTREF

Attribute	Description	
Name	EXTREF	
Datatype	String	
Description	Reference supplied by the external system in case the Interaction was uploaded	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

RECORGN

Attribute	Description	
Name	RECORGN	
Datatype	String	
Description	The types of the interactions booked 1. Manual 2. System Generated 3. Upload	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	M,S,U

[TOP](#)

PROCESS_STAGE

Attribute	Description	
Name	PROCESS_STAGE	
Datatype	String	
Description	The current stage of the interaction Ex: Initiated or Approved or Rejected or Executed	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	I,R,E,A

[TOP](#)

TOTPTPAMT

Attribute	Description					
Name	TOTPTPAMT					
Datatype	Number					
Description	This is the total amount, the customer promises to pay. Applicable only if the result of action is a factory shipped result code for PTP					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

[TOP](#)

ACTION_CODE

Attribute	Description					
Name	ACTION_CODE					
Datatype	String					
Description	This is the action that is being executed as part of the interaction carried out					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20	
Restrictions	Description					
maxLength	20					

[TOP](#)

RESLT

Attribute	Description					
Name	RESLT					
Datatype	String					
Description	This is the result of the action during execution					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20	
Restrictions	Description					
maxLength	20					

[TOP](#)

ACTINDT

Attribute	Description					
Name	ACTINDT					
Datatype	Date					
Description	This is the date of execution of the aforesaid action					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

[TOP](#)

DELREASON

Attribute	Description	
Name	DELREASON	
Datatype	String	
Description	The reason for the Account going into overdue as given by the Customer	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

NEXTACTION

Attribute	Description	
Name	NEXTACTION	
Datatype	String	
Description	This field denotes the next action that can be executed by the person	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

RSLTDT

Attribute	Description	
Name	RSLTDT	
Datatype	Date	
Description	Typically a Action Date, in case of WAITING action, the next action date can be taken as Result Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NXTACTIONNDT

Attribute	Description	
Name	NXTACTIONNDT	
Datatype	Date	
Description	Next Action Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMNTS

Attribute	Description	
Name	COMNTS	
Datatype	String	
Description	The comments related to the interaction can be captured here	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

NLS_HR

Attribute	Description					
Name	NLS_HR					
Datatype	Number					
Description	Hour of the interaction can be recorded					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

[TOP](#)

OFSMINS

Attribute	Description					
Name	OFSMINS					
Datatype	Number					
Description	Minute of the interaction can be recorded					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

[TOP](#)

CUSTMAIL

Attribute	Description					
Name	CUSTMAIL					
Datatype	String					
Description	Customer E-mail Id					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>		Restrictions	Description	maxLength	35
Restrictions	Description					
maxLength	35					

[TOP](#)

MEDIA

Attribute	Description					
Name	MEDIA					
Datatype	String					
Description	Media, Mail, FAX, Phone etc..					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>		Restrictions	Description	maxLength	35
Restrictions	Description					
maxLength	35					

[TOP](#)

INTRACTIONPLACE

Attribute	Description	
Name	INTRACTIONPLACE	
Datatype	String	
Description	Interaction Place. This is applicable for some actions like personal visit	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

CUSTMOB

Attribute	Description	
Name	CUSTMOB	
Datatype	Number	
Description	Customer Mobile Number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

Asset

Attribute	Description	
Name	Asset	
Datatype		
Description	Collection Asset Details	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LOANREFNO

Attribute	Description	
Name	LOANREFNO	
Datatype	String	
Description	This is a Asset Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

ASSETQUTPRINCIPAL

Attribute	Description	
Name	ASSETQUTPRINCIPAL	
Datatype	Number	
Description	Principal Outstanding Amount as on Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ASSETCCY

Attribute	Description	
Name	ASSETCCY	

Datatype	String	
Description	Currency in which the transaction takes place	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

ASSETBRN

Attribute	Description	
Name	ASSETBRN	
Datatype	String	
Description	Asset Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

ASSETTOTALOVD

Attribute	Description	
Name	ASSETTOTALOVD	
Datatype	Number	
Description	Total Overdue Amount as on Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ASSETSCHOVD

Attribute	Description	
Name	ASSETSCHOVD	
Datatype	Number	
Description	Total No of Schedules Overdue	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ASSETUDETSTAT

Attribute	Description	
Name	ASSETUDETSTAT	
Datatype	String	
Description	User Defined Status for the Asset Reference	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

ASSETAMT

Attribute	Description	
Name	ASSETAMT	
Datatype	Number	
Description	Total Asset Amount	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

Ptp

Attribute	Description	
Name	Ptp	
Datatype		
Description	Promise To Pay Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

PTPAMT

Attribute	Description	
Name	PTPAMT	
Datatype	Number	
Description	The Amount which Customer Promise to pay	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PTPDT

Attribute	Description	
Name	PTPDT	
Datatype	Date	
Description	Date on which the Amount will be paid	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMTPAID

Attribute	Description	
Name	AMTPAID	
Datatype	Number	
Description	Actual Amount paid by the customer	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PTPSTAT

Attribute	Description	
Name	PTPSTAT	
Datatype	String	
Description	PTP Status as on Date: Pending(P), Honored(H), Broken(B), Partial (L), Cancelled (C)	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	P,H,B,L

[TOP](#)

PTPCARGE

Attribute	Description	
Name	PTPCARGE	
Datatype	Number	
Description	Promise to Pay Charge	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

Footer

Attribute	Description	
Name	Footer	
Datatype		
Description	This includes Audit Trail Details	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CONREFNO

Attribute	Description	
Name	CONREFNO	

Datatype	String	
Description	The reference number for the contract booked	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	The user who books the Contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKDTTIME

Attribute	Description	
Name	MAKDTTIME	
Datatype	String	
Description	The date and Time at which the contract is booked	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

CHKR

Attribute	Description	
Name	CHKR	
Datatype	String	
Description	The Approver of the Contract Booked	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHKDTTIME

Attribute	Description	
Name	CHKDTTIME	
Datatype	String	
Description	The time at which the contract booked got approved	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

EVNTSEQNO

Attribute	Description	
Name	EVNTSEQNO	
Datatype	Number	
Description	Event sequence number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CONSTAT

Attribute	Description	
Name	CONSTAT	
Datatype	String	
Description	Contract Status : "Active", "Hold" , "Reversed" etc..	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,O,C

[TOP](#)

AUTHSTATS

Attribute	Description	
Name	AUTHSTATS	
Datatype	String	
Description	The Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,U,A

[TOP](#)

2.2.2.CN>CreateCollectionInteraction-Req-IO-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Main-IO

COLLREF_2

SRCCD

ISN

CLCTNESN

ACTION_CODE

RESLT

ACTINDT

DELREASON

NEXTACTION

RSLTDT

NXTACTIONDT

COMNTS

NLS_HR

OFSMINS

CUSTMAIL

MEDIA

INTRACTIONPLACE

CUSTMOB

Ptp

PTPAMT

PTPDT

TAGCCY

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node. Entire processing in FLEXCUBE UBS Messaging Database Layer is based upon the information provided in this node.

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELIID

Attribute	Description	
Name	CORRELIID	

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

PASSWORD

Attribute	Description	

Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/-]*

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about IO Request	

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	It indicates Collection Interaction Creation IO Request details of Collections module

COLLREF_2

Attribute	Description				
Name	COLLREF_2				
Datatype	String				
Description	This is the unique reference number assigned to the collection process				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

SRCCD

Attribute	Description				
Name	SRCCD				
Datatype	String				
Description	This denotes Source Code				
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>15</td></tr> </tbody> </table>	Restrictions	Description	maxLength	15
Restrictions	Description				
maxLength	15				

ISN

Attribute	Description				
Name	ISN				
Datatype	String				
Description	Interaction Sequence Number for every new interaction				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

CLCTNESN

Attribute	Description				
Name	CLCTNESN				
Datatype	Number				
Description	Collection event Sequence number				
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

[TOP](#)

ACTION_CODE

Attribute	Description	
Name	ACTION_CODE	
Datatype	String	
Description	This is the action that is being executed as part of the interaction carried out	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

RESLT

Attribute	Description	
Name	RESLT	
Datatype	String	
Description	This is the result of the action during execution	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

ACTINDT

Attribute	Description	
Name	ACTINDT	
Datatype	Date	
Description	This is the date of execution of the aforesaid action	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DELREASON

Attribute	Description	
Name	DELREASON	
Datatype	String	
Description	The reason for the Account going into overdue as given by the Customer	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

NEXTACTION

Attribute	Description	
Name	NEXTACTION	

Datatype	String	
Description	This field denotes the next action that can be executed by the person	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

RSLTDT

Attribute	Description	
Name	RSLTDT	
Datatype	Date	
Description	Typically a Action Date, in case of WAITING action, the next action date can be taken as Result Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NXTACTIONNDT

Attribute	Description	
Name	NXTACTIONNDT	
Datatype	Date	
Description	Next Action Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMNTS

Attribute	Description	
Name	COMNTS	
Datatype	String	
Description	The comments related to the interaction can be captured here	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

NLS_HR

Attribute	Description	
Name	NLS_HR	
Datatype	Number	
Description	Hour of the interaction can be recorded	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

OFSMINS

Attribute	Description	
Name	OFSMINS	
Datatype	Number	
Description	Minute of the interaction can be recorded	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CUSTMAIL

Attribute	Description	
Name	CUSTMAIL	
Datatype	String	
Description	Customer E-mail Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

MEDIA

Attribute	Description	
Name	MEDIA	
Datatype	String	
Description	Media, Mail, FAX, Phone etc..	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

INTRACTIONPLACE

Attribute	Description	
Name	INTRACTIONPLACE	
Datatype	String	
Description	Interaction Place. This is applicable for some actions like personal visit	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

CUSTMOB

Attribute	Description	
Name	CUSTMOB	
Datatype	Number	

Description	Customer Mobile Number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

Ptp

Attribute	Description	
Name	Ptp	
Datatype		
Description	Promise To Pay Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

PTPAMT

Attribute	Description	
Name	PTPAMT	
Datatype	Number	
Description	The Amount which Customer Promise to pay	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PTPDT

Attribute	Description	
Name	PTPDT	
Datatype	Date	
Description	Date on which the Amount will be paid	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

2.2.3.CN>CreateCollectionInteraction-Res-Full-MSG.xsd

FCUBS_HEADER
 SOURCE
 UBSCOMP
 MSGID
 CORRELID
 USERID
 BRANCH
 MODULEID
 SERVICE
 OPERATION
 SOURCE_OPERATION
 SOURCE_USERID
 DESTINATION
 MULTITRIPID
 FUNCTIONID
 ACTION
 MSGSTAT
 PASSWORD
 ADDL
 PARAM
 NAME
 VALUE
FCUBS_BODY
 Main-Full
 CLCTAGENTID
 COLLREF_2
 SRCCD
 RECORD_DATE
 ISN
 AGNCYNAME
 CUSTOMER
 CUSTOMER_NAME1
 INTSUBSEQNO
 CLCTNESN
 EXTREF
 RECORGN
 PROCESS_STAGE
 TOTPTPAMT
 ACTION_CODE
 RESLT
 ACTINDT
 DELREASON

NEXTACTION
RSLTDT
NXTACTIONDT
COMNTS
NLS_HR
OFSMINS
CUSTMAIL
MEDIA
INTRACTIONPLACE
CUSTMOB
Asset
 LOANREFNO
 ASSETQUTPRINCIPAL
 ASSETCCY
 ASSETBRN
 ASSETTOTALOVD
 ASSETSCHOVD
 ASSETUDETSTAT
 ASSETAMT
Ptp
 PTPAMT
 PTPDT
 AMTPAID
 PTPSTAT
 PTPCHARGE
 TAGCCY
Footer
 CONREFNO
 MAKER
 MAKDTTIME
 CHKR
 CHKDTTIME
 EVNTSEQNO
 CONSTAT
 AUTHSTATS
FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node. Entire processing in FLEXCUBE UBS Messaging Database Layer is based upon the information provided in this node.

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

MSGID

Attribute	Description						
Name	MSGID						
Datatype	String						
Description							
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

[TOP](#)

CORRELIID

Attribute	Description
Name	CORRELIID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

PASSWORD

Attribute	Description	

Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/-]*

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

[TOP](#)

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	It indicates Collection Interaction Creation Full Response details of Collections module

[TOP](#)

CLCTAGENTID

Attribute	Description	
Name	CLCTAGENTID	
Datatype	String	
Description	Collection Agent to whom this collection is assigned	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

COLLREF_2

Attribute	Description	
Name	COLLREF_2	
Datatype	String	
Description	This is the unique reference number assigned to the collection process	
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

SRCCD

Attribute	Description	
Name	SRCCD	
Datatype	String	
Description	This denotes Source Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

RECORD_DATE

Attribute	Description	
Name	RECORD_DATE	
Datatype	Date	
Description	The date on which the interaction was created in the system	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**ISN**

Attribute	Description	
Name	ISN	
Datatype	String	
Description	Interaction Sequence Number for every new interaction	
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**AGNCYNAME**

Attribute	Description	
Name	AGNCYNAME	
Datatype	String	
Description	Name of the Collecting Agency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)**CUSTOMER**

Attribute	Description	
Name	CUSTOMER	
Datatype	String	
Description	Counterparty of the underlying Asset	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)**CUSTOMER_NAME1**

Attribute	Description	
Name	CUSTOMER_NAME1	
Datatype	String	
Description	Displays the name of the customer	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)**INTSUBSEQNO**

Attribute	Description	
Name	INTSUBSEQNO	

Datatype	Number					
Description	Further actions on a recorded interaction will increment this number					
Attributes	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

[TOP](#)

CLCTNESN

Attribute	Description					
Name	CLCTNESN					
Datatype	Number					
Description	Collection Event Sequence Number					
Attributes	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

[TOP](#)

EXTREF

Attribute	Description					
Name	EXTREF					
Datatype	String					
Description	Reference supplied by the external system in case the Interaction was uploaded					
Attributes	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>maxLength</td> <td>30</td> </tr> </table>	Restrictions	Description	maxLength	30	
Restrictions	Description					
maxLength	30					

[TOP](#)

RECORGN

Attribute	Description					
Name	RECORGN					
Datatype	String					
Description	The types of the interactions booked 1. Manual 2. System Generated 3. Upload					
Attributes	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>enumeration</td> <td>M,S,U</td> </tr> </table>	Restrictions	Description	enumeration	M,S,U	
Restrictions	Description					
enumeration	M,S,U					

[TOP](#)

PROCESS_STAGE

Attribute	Description					
Name	PROCESS_STAGE					
Datatype	String					
Description	The current stage of the interaction Ex: Initiated or Approved or Rejected or Executed					
Attributes	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

Restrictions	Restrictions	Description
	enumeration	I,R,E,A

[TOP](#)

TOTPTPAMT

Attribute	Description					
Name	TOTPTPAMT					
Datatype	Number					
Description	This is the total amount, the customer promises to pay. Applicable only if the result of action is a factory shipped result code for PTP					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

[TOP](#)

ACTION_CODE

Attribute	Description					
Name	ACTION_CODE					
Datatype	String					
Description	This is the action that is being executed as part of the interaction carried out					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>		Restrictions	Description	maxLength	20
Restrictions	Description					
maxLength	20					

[TOP](#)

RESLT

Attribute	Description					
Name	RESLT					
Datatype	String					
Description	This is the result of the action during execution					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>		Restrictions	Description	maxLength	20
Restrictions	Description					
maxLength	20					

[TOP](#)

ACTINDT

Attribute	Description					
Name	ACTINDT					
Datatype	Date					
Description	This is the date of execution of the aforesaid action					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

[TOP](#)

DELREASON

Attribute	Description	

Name	DELREASON	
Datatype	String	
Description	The reason for the Account going into overdue as given by the Customer	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

NEXTACTION

Attribute	Description	
Name	NEXTACTION	
Datatype	String	
Description	This field denotes the next action that can be executed by the person	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

RSLTDT

Attribute	Description	
Name	RSLTDT	
Datatype	Date	
Description	Typically a Action Date, in case of WAITING action, the next action date can be taken as Result Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NXTACTIONNDT

Attribute	Description	
Name	NXTACTIONNDT	
Datatype	Date	
Description	Next Action Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMNTS

Attribute	Description	
Name	COMNTS	
Datatype	String	
Description	The comments related to the interaction can be captured here	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

NLS_HR

Attribute	Description	
Name	NLS_HR	
Datatype	Number	
Description	Hour of the interaction can be recorded	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

OFSMINS

Attribute	Description	
Name	OFSMINS	
Datatype	Number	
Description	Minute of the interaction can be recorded	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CUSTMAIL

Attribute	Description	
Name	CUSTMAIL	
Datatype	String	
Description	Customer E-mail Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

MEDIA

Attribute	Description	
Name	MEDIA	
Datatype	String	
Description	Media, Mail, FAX, Phone etc..	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

INTRACTIONPLACE

Attribute	Description	
Name	INTRACTIONPLACE	
Datatype	String	
Description	Interaction Place. This is applicable for some actions like personal visit	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

CUSTMOB

Attribute	Description	
Name	CUSTMOB	
Datatype	Number	
Description	Customer Mobile Number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

Asset

Attribute	Description	
Name	Asset	
Datatype		
Description	Collection Asset Details	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LOANREFNO

Attribute	Description	
Name	LOANREFNO	
Datatype	String	
Description	This is a Asset Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

ASSETQUTPRINCIPAL

Attribute	Description	
Name	ASSETQUTPRINCIPAL	
Datatype	Number	
Description	Principal Outstanding Amount as on Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ASSETCCY

Attribute	Description	
Name	ASSETCCY	

Datatype	String	
Description	Currency in which the transaction takes place	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

ASSETBRN

Attribute	Description	
Name	ASSETBRN	
Datatype	String	
Description	Asset Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

ASSETTOTALOVD

Attribute	Description	
Name	ASSETTOTALOVD	
Datatype	Number	
Description	Total Overdue Amount as on Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ASSETSCHOVD

Attribute	Description	
Name	ASSETSCHOVD	
Datatype	Number	
Description	Total No of Schedules Overdue	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ASSETUDETSTAT

Attribute	Description	
Name	ASSETUDETSTAT	
Datatype	String	
Description	User Defined Status for the Asset Reference	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

ASSETAMT

Attribute	Description	
Name	ASSETAMT	
Datatype	Number	
Description	Total Asset Amount	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

Ptp

Attribute	Description	
Name	Ptp	
Datatype		
Description	Promise To Pay Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

PTPAMT

Attribute	Description	
Name	PTPAMT	
Datatype	Number	
Description	The Amount which Customer Promise to pay	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PTPDT

Attribute	Description	
Name	PTPDT	
Datatype	Date	
Description	Date on which the Amount will be paid	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMTPAID

Attribute	Description	
Name	AMTPAID	
Datatype	Number	
Description	Actual Amount paid by the customer	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PTPSTAT

Attribute	Description	
Name	PTPSTAT	
Datatype	String	
Description	PTP Status as on Date: Pending(P), Honored(H), Broken(B), Partial (L), Cancelled (C)	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	P,H,B,L

[TOP](#)

PTPCARGE

Attribute	Description	
Name	PTPCARGE	
Datatype	Number	
Description	Promise to Pay Charge	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

Footer

Attribute	Description	
Name	Footer	
Datatype		
Description	This includes Audit Trail Details	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CONREFNO

Attribute	Description	
Name	CONREFNO	

Datatype	String	
Description	The reference number for the contract booked	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	The user who books the Contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKDTTIME

Attribute	Description	
Name	MAKDTTIME	
Datatype	String	
Description	The date and Time at which the contract is booked	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

CHKR

Attribute	Description	
Name	CHKR	
Datatype	String	
Description	The Approver of the Contract Booked	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHKDTTIME

Attribute	Description	
Name	CHKDTTIME	
Datatype	String	
Description	The time at which the contract booked got approved	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

EVNTSEQNO

Attribute	Description	
Name	EVNTSEQNO	
Datatype	Number	
Description	Event sequence number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CONSTAT

Attribute	Description	
Name	CONSTAT	
Datatype	String	
Description	Contract Status : "Active", "Hold", "Reversed" etc..	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,O,C

[TOP](#)

AUTHSTATS

Attribute	Description	
Name	AUTHSTATS	
Datatype	String	
Description	The Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,U,A

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.2.4.CN>CreateCollectionInteraction-Res-PK-MSG.xsd

FCUBS_HEADER
 SOURCE
 UBSCOMP
 MSGID
 CORRELID
 USERID
 BRANCH
 MODULEID
 SERVICE
 OPERATION
 SOURCE_OPERATION
 SOURCE_USERID
 DESTINATION
 MULTITRIPID
 FUNCTIONID
 ACTION
 MSGSTAT
 PASSWORD
 ADDL
 PARAM
 NAME
 VALUE
FCUBS_BODY
 CHOICE
 Main-PK
 ISN
 Main-IO
 COLLREF_2
 SRCCD
 ISN
 CLCTNESN
 ACTION_CODE
 RESLT
 ACTINDT
 DELREASON
 NEXTACTION
 RSLTDT
 NXTACTIONDT
 COMNTS
 NLS_HR
 OFSMINS
 CUSTMAIL

MEDIA
INTRACTIONPLACE
CUSTMOB
Ptp
PTPAMT
PTPDT
TAGCCY
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node. Entire processing in FLEXCUBE UBS Messaging Database Layer is based upon the information provided in this node.

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description
Name	MSGID

Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRECID

Attribute	Description	
Name	CORRECID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		

Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	It indicates Collection Interaction Creation PK Response details of Collections module

[TOP](#)

ISN

Attribute	Description	
Name	ISN	
Datatype	String	
Description	Interaction Sequence Number for every new interaction	
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	It indicates Collection Interaction Creation IO Response details of Collections module

[TOP](#)

COLLREF_2

Attribute	Description	
Name	COLLREF_2	
Datatype	String	
Description	This is the unique reference number assigned to the collection process	
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

SRCCD

Attribute	Description	
Name	SRCCD	
Datatype	String	
Description	This denotes Source Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

ISN

Attribute	Description	
Name	ISN	
Datatype	String	
Description	Interaction Sequence Number for every new interaction	
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

CLCTNESN

Attribute	Description	
Name	CLCTNESN	
Datatype	Number	
Description	Collection event Sequence number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ACTION_CODE

Attribute	Description	
Name	ACTION_CODE	
Datatype	String	
Description	This is the action that is being executed as part of the interaction carried out	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

RESLT

Attribute	Description	
Name	RESLT	
Datatype	String	
Description	This is the result of the action during execution	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

ACTINDT

Attribute	Description	
Name	ACTINDT	
Datatype	Date	
Description	This is the date of execution of the aforesaid action	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

DELREASON

Attribute	Description	
Name	DELREASON	
Datatype	String	
Description	The reason for the Account going into overdue as given by the Customer	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

NEXTACTION

Attribute	Description	
Name	NEXTACTION	
Datatype	String	
Description	This field denotes the next action that can be executed by the person	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

RSLTDT

Attribute	Description					
Name	RSLTDT					
Datatype	Date					
Description	Typically a Action Date, in case of WAITING action, the next action date can be taken as Result Date					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

[TOP](#)

NXTACTIONDT

Attribute	Description					
Name	NXTACTIONDT					
Datatype	Date					
Description	Next Action Date					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

[TOP](#)

COMNTS

Attribute	Description					
Name	COMNTS					
Datatype	String					
Description	The comments related to the interaction can be captured here					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>35</td></tr> </tbody> </table>	Restrictions	Description	maxLength	35	
Restrictions	Description					
maxLength	35					

[TOP](#)

NLS_HR

Attribute	Description					
Name	NLS_HR					
Datatype	Number					
Description	Hour of the interaction can be recorded					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

[TOP](#)

OFSMINS

Attribute	Description					
Name	OFSMINS					
Datatype	Number					
Description	Minute of the interaction can be recorded					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

[TOP](#)

CUSTMAIL

Attribute	Description	
Name	CUSTMAIL	
Datatype	String	
Description	Customer E-mail Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

MEDIA

Attribute	Description	
Name	MEDIA	
Datatype	String	
Description	Media, Mail, FAX, Phone etc..	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

INTRACTIONPLACE

Attribute	Description	
Name	INTRACTIONPLACE	
Datatype	String	
Description	Interaction Place. This is applicable for some actions like personal visit	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

CUSTMOB

Attribute	Description	
Name	CUSTMOB	
Datatype	Number	
Description	Customer Mobile Number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

Ptp

Attribute	Description	
Name	Ptp	
Datatype		

Description	Promise To Pay Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

PTPAMT

Attribute	Description	
Name	PTPAMT	
Datatype	Number	
Description	The Amount which Customer Promise to pay	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PTPDT

Attribute	Description	
Name	PTPDT	
Datatype	Date	
Description	Date on which the Amount will be paid	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	

Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td><td>unbounded</td></tr> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
Attribute	Description						
maxOccurs	unbounded						
minOccurs	0						

[TOP](#)

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

[TOP](#)

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

2.3.DeleteCollectionInteraction

DeleteCollectionInteraction

2.3.1.CN-DeleteCollectionInteraction-Req-Full-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Main-Full

CLCTAGENTID

COLLREF_2

SRCCD

RECORD_DATE

ISN

AGNCYNAME

CUSTOMER

CUSTOMER_NAME1

INTSUBSEQNO

CLCTNESN

EXTREF

RECORGN

PROCESS_STAGE

TOTPTPAMT

ACTION_CODE

RESLT
ACTINDT
DELREASON
NEXTACTION
RSLTDT
NXTACTIONDT
COMNTS
NLS_HR
OFSMINS
CUSTMAIL
MEDIA
INTRACTIONPLACE
CUSTMOB

Asset

LOANREFNO
ASSETQUTPRINCIPAL
ASSETCCY
ASSETBRN
ASSETTOTALOVD
ASSETSCHOVD
ASSETUDETSTAT
ASSETAMT

Ptp

PTPAMT
PTPDAT
AMTPAID
PTPSTAT
PTPCHARGE
TAGCCY

Footer

CONREFNO
MAKER
MAKDTTIME
CHKR
CHKDTTIME
EVNTSEQNO
CONSTAT
AUTHSTATS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node. Entire processing in FLEXCUBE UBS Messaging Database Layer is based upon the information provided in this node.
-------------	--

[TOP](#)

SOURCE

Attribute	Description					
Name	SOURCE					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

[TOP](#)

UBSCOMP

Attribute	Description					
Name	UBSCOMP					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

[TOP](#)

MSGID

Attribute	Description							
Name	MSGID							
Datatype	String							
Description								
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	nillable	true
Attribute	Description							
minOccurs	0							
nillable	true							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description							
pattern	[a-zA-Z_0-9]*							

[TOP](#)

CORRELID

Attribute	Description							
Name	CORRELID							
Datatype	String							
Description								
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	nillable	true
Attribute	Description							
minOccurs	0							
nillable	true							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description							
pattern	[a-zA-Z_0-9]*							

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Request	

[TOP](#)

Main-Full

Attribute	Description	

Name	Main-Full
Datatype	
Description	It indicates Collection Interaction Deletion Full Request details of Collections module

[TOP](#)

CLCTAGENTID

Attribute	Description					
Name	CLCTAGENTID					
Datatype	String					
Description	Collection Agent to whom this collection is assigned					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20	
Restrictions	Description					
maxLength	20					

[TOP](#)

COLLREF_2

Attribute	Description					
Name	COLLREF_2					
Datatype	String					
Description	This is the unique reference number assigned to the collection process					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>	Restrictions	Description	maxLength	16	
Restrictions	Description					
maxLength	16					

[TOP](#)

SRCCD

Attribute	Description					
Name	SRCCD					
Datatype	String					
Description	This denotes Source Code					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>15</td></tr> </tbody> </table>	Restrictions	Description	maxLength	15	
Restrictions	Description					
maxLength	15					

[TOP](#)

RECORD_DATE

Attribute	Description					
Name	RECORD_DATE					
Datatype	Date					
Description	The date on which the interaction was created in the system					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

[TOP](#)

ISN

Attribute	Description	
Name	ISN	
Datatype	String	
Description	Interaction Sequence Number for every new interaction	
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

AGNCYNAME

Attribute	Description	
Name	AGNCYNAME	
Datatype	String	
Description	Name of the Collecting Agency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

CUSTOMER

Attribute	Description	
Name	CUSTOMER	
Datatype	String	
Description	Counterparty of the underlying Asset	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

CUSTOMER_NAME1

Attribute	Description	
Name	CUSTOMER_NAME1	
Datatype	String	
Description	Displays the name of the customer	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

INTSUBSEQNO

Attribute	Description	
Name	INTSUBSEQNO	
Datatype	Number	
Description	Further actions on a recorded interaction will increment this number	

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CLCTNESN

Attribute	Description	
Name	CLCTNESN	
Datatype	Number	
Description	Collection Event Sequence Number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

EXTREF

Attribute	Description	
Name	EXTREF	
Datatype	String	
Description	Reference supplied by the external system in case the Interaction was uploaded	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

[TOP](#)

RECORGN

Attribute	Description	
Name	RECORGN	
Datatype	String	
Description	The types of the interactions booked 1. Manual 2. System Generated 3. Upload	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	M,S,U

[TOP](#)

PROCESS_STAGE

Attribute	Description	
Name	PROCESS_STAGE	
Datatype	String	
Description	The current stage of the interaction Ex: Initiated or Approved or Rejected or Executed	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	I,R,E,A

[TOP](#)

TOTPTPAMT

Attribute	Description					
Name	TOTPTPAMT					
Datatype	Number					
Description	This is the total amount, the customer promises to pay. Applicable only if the result of action is a factory shipped result code for PTP					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

[TOP](#)

ACTION_CODE

Attribute	Description					
Name	ACTION_CODE					
Datatype	String					
Description	This is the action that is being executed as part of the interaction carried out					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20	
Restrictions	Description					
maxLength	20					

[TOP](#)

RESLT

Attribute	Description					
Name	RESLT					
Datatype	String					
Description	This is the result of the action during execution					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20	
Restrictions	Description					
maxLength	20					

[TOP](#)

ACTINDT

Attribute	Description					
Name	ACTINDT					
Datatype	Date					
Description	This is the date of execution of the aforesaid action					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

[TOP](#)

DELREASON

Attribute	Description	
Name	DELREASON	
Datatype	String	
Description	The reason for the Account going into overdue as given by the Customer	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

NEXTACTION

Attribute	Description	
Name	NEXTACTION	
Datatype	String	
Description	This field denotes the next action that can be executed by the person	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

RSLTDT

Attribute	Description	
Name	RSLTDT	
Datatype	Date	
Description	Typically a Action Date, in case of WAITING action, the next action date can be taken as Result Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NXTACTIONNDT

Attribute	Description	
Name	NXTACTIONNDT	
Datatype	Date	
Description	Next Action Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMNTS

Attribute	Description	
Name	COMNTS	
Datatype	String	
Description	The comments related to the interaction can be captured here	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

NLS_HR

Attribute	Description					
Name	NLS_HR					
Datatype	Number					
Description	Hour of the interaction can be recorded					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

[TOP](#)

OFSMINS

Attribute	Description					
Name	OFSMINS					
Datatype	Number					
Description	Minute of the interaction can be recorded					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

[TOP](#)

CUSTMAIL

Attribute	Description					
Name	CUSTMAIL					
Datatype	String					
Description	Customer E-mail Id					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>		Restrictions	Description	maxLength	35
Restrictions	Description					
maxLength	35					

[TOP](#)

MEDIA

Attribute	Description					
Name	MEDIA					
Datatype	String					
Description	Media, Mail, FAX, Phone etc..					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>		Restrictions	Description	maxLength	35
Restrictions	Description					
maxLength	35					

[TOP](#)

INTRACTIONPLACE

Attribute	Description	
Name	INTRACTIONPLACE	
Datatype	String	
Description	Interaction Place. This is applicable for some actions like personal visit	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

CUSTMOB

Attribute	Description	
Name	CUSTMOB	
Datatype	Number	
Description	Customer Mobile Number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

Asset

Attribute	Description	
Name	Asset	
Datatype		
Description	Collection Asset Details	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LOANREFNO

Attribute	Description	
Name	LOANREFNO	
Datatype	String	
Description	This is a Asset Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

ASSETQUTPRINCIPAL

Attribute	Description	
Name	ASSETQUTPRINCIPAL	
Datatype	Number	
Description	Principal Outstanding Amount as on Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ASSETCCY

Attribute	Description	
Name	ASSETCCY	

Datatype	String	
Description	Currency in which the transaction takes place	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

ASSETBRN

Attribute	Description	
Name	ASSETBRN	
Datatype	String	
Description	Asset Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

ASSETTOTALOVD

Attribute	Description	
Name	ASSETTOTALOVD	
Datatype	Number	
Description	Total Overdue Amount as on Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ASSETSCHOVD

Attribute	Description	
Name	ASSETSCHOVD	
Datatype	Number	
Description	Total No of Schedules Overdue	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ASSETUDETSTAT

Attribute	Description	
Name	ASSETUDETSTAT	
Datatype	String	
Description	User Defined Status for the Asset Reference	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

ASSETAMT

Attribute	Description	
Name	ASSETAMT	
Datatype	Number	
Description	Total Asset Amount	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

Ptp

Attribute	Description	
Name	Ptp	
Datatype		
Description	Promise To Pay Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

PTPAMT

Attribute	Description	
Name	PTPAMT	
Datatype	Number	
Description	The Amount which Customer Promise to pay	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PTPDT

Attribute	Description	
Name	PTPDT	
Datatype	Date	
Description	Date on which the Amount will be paid	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMTPAID

Attribute	Description	
Name	AMTPAID	
Datatype	Number	
Description	Actual Amount paid by the customer	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PTPSTAT

Attribute	Description	
Name	PTPSTAT	
Datatype	String	
Description	PTP Status as on Date: Pending(P), Honored(H), Broken(B), Partial (L), Cancelled (C)	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	P,H,B,L

[TOP](#)

PTPCARGE

Attribute	Description	
Name	PTPCARGE	
Datatype	Number	
Description	Promise to Pay Charge	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

Footer

Attribute	Description	
Name	Footer	
Datatype		
Description	This includes Audit Trail Details	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CONREFNO

Attribute	Description	
Name	CONREFNO	

Datatype	String	
Description	The reference number for the contract booked	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	The user who books the Contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKDTTIME

Attribute	Description	
Name	MAKDTTIME	
Datatype	String	
Description	The date and Time at which the contract is booked	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

CHKR

Attribute	Description	
Name	CHKR	
Datatype	String	
Description	The Approver of the Contract Booked	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHKDTTIME

Attribute	Description	
Name	CHKDTTIME	
Datatype	String	
Description	The time at which the contract booked got approved	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

EVNTSEQNO

Attribute	Description	
Name	EVNTSEQNO	
Datatype	Number	
Description	Event sequence number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CONSTAT

Attribute	Description	
Name	CONSTAT	
Datatype	String	
Description	Contract Status : "Active", "Hold", "Reversed" etc..	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,O,C

[TOP](#)

AUTHSTATS

Attribute	Description	
Name	AUTHSTATS	
Datatype	String	
Description	The Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,U,A

[TOP](#)

2.3.2.CN-DeleteCollectionInteraction-Req-IO-MSG.xsd

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Main-IO

ISN

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node. Entire processing in FLEXCUBE UBS Messaging Database Layer is based upon the information provided in this node.

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions enumeration	Description FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute minOccurs nillable	Description 0 true
Restrictions	Restrictions pattern	Description [a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute minOccurs nillable	Description 0 true
Restrictions	Restrictions pattern	Description [a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions maxLength pattern	Description 12 [A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	

Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	

Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

Main-IO

Attribute	Description
Name	Main-IO
Datatype	
Description	It indicates Collection Interaction Deletion IO Request details of Collections module

[TOP](#)

ISN

Attribute	Description	
Name	ISN	
Datatype	String	
Description	Interaction Sequence Number for every new interaction	
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

2.3.3.CN-DeleteCollectionInteraction-Res-Full-MSG.xsd

FCUBS_HEADER
 SOURCE
 UBSCOMP
 MSGID
 CORRELID
 USERID
 BRANCH
 MODULEID
 SERVICE
 OPERATION
 SOURCE_OPERATION
 SOURCE_USERID
 DESTINATION
 MULTITRIPID
 FUNCTIONID
 ACTION
 MSGSTAT
 PASSWORD
 ADDL
 PARAM
 NAME
 VALUE
FCUBS_BODY
 Main-Full
 CLCTAGENTID
 COLLREF_2
 SRCCD
 RECORD_DATE
 ISN
 AGNCYNAME
 CUSTOMER
 CUSTOMER_NAME1
 INTSUBSEQNO
 CLCTNESN
 EXTREF
 RECORGN
 PROCESS_STAGE
 TOTPTPAMT
 ACTION_CODE
 RESLT
 ACTINDT
 DELREASON

NEXTACTION
RSLTDT
NXTACTIONDT
COMNTS
NLS_HR
OFSMINS
CUSTMAIL
MEDIA
INTRACTIONPLACE
CUSTMOB
Asset
 LOANREFNO
 ASSETQUTPRINCIPAL
 ASSETCCY
 ASSETBRN
 ASSETTOTALOVD
 ASSETSCHOVD
 ASSETUDETSTAT
 ASSETAMT
Ptp
 PTPAMT
 PTPDT
 AMTPAID
 PTPSTAT
 PTPCHARGE
 TAGCCY
Footer
 CONREFNO
 MAKER
 MAKDTTIME
 CHKR
 CHKDTTIME
 EVNTSEQNO
 CONSTAT
 AUTHSTATS
FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node. Entire processing in FLEXCUBE UBS Messaging Database Layer is based upon the information provided in this node.

[TOP](#)

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

MSGID

Attribute	Description						
Name	MSGID						
Datatype	String						
Description							
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

[TOP](#)

CORRELIID

Attribute	Description
Name	CORRELIID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

PASSWORD

Attribute	Description	

Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/-]*

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

[TOP](#)

Main-Full

Attribute	Description
Name	Main-Full
Datatype	
Description	It indicates Collection Interaction Deletion Full Response details of Collections module

[TOP](#)

CLCTAGENTID

Attribute	Description	
Name	CLCTAGENTID	
Datatype	String	
Description	Collection Agent to whom this collection is assigned	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

COLLREF_2

Attribute	Description	
Name	COLLREF_2	
Datatype	String	
Description	This is the unique reference number assigned to the collection process	
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

SRCCD

Attribute	Description	
Name	SRCCD	
Datatype	String	
Description	This denotes Source Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

RECORD_DATE

Attribute	Description	
Name	RECORD_DATE	
Datatype	Date	
Description	The date on which the interaction was created in the system	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**ISN**

Attribute	Description					
Name	ISN					
Datatype	String					
Description	Interaction Sequence Number for every new interaction					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>	Restrictions	Description	maxLength	16	
Restrictions	Description					
maxLength	16					

[TOP](#)**AGNCYNAME**

Attribute	Description					
Name	AGNCYNAME					
Datatype	String					
Description	Name of the Collecting Agency					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>35</td></tr> </tbody> </table>	Restrictions	Description	maxLength	35	
Restrictions	Description					
maxLength	35					

[TOP](#)**CUSTOMER**

Attribute	Description					
Name	CUSTOMER					
Datatype	String					
Description	Counterparty of the underlying Asset					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20	
Restrictions	Description					
maxLength	20					

[TOP](#)**CUSTOMER_NAME1**

Attribute	Description					
Name	CUSTOMER_NAME1					
Datatype	String					
Description	Displays the name of the customer					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>35</td></tr> </tbody> </table>	Restrictions	Description	maxLength	35	
Restrictions	Description					
maxLength	35					

[TOP](#)**INTSUBSEQNO**

Attribute	Description	
Name	INTSUBSEQNO	

Datatype	Number					
Description	Further actions on a recorded interaction will increment this number					
Attributes	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

[TOP](#)

CLCTNESN

Attribute	Description					
Name	CLCTNESN					
Datatype	Number					
Description	Collection Event Sequence Number					
Attributes	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

[TOP](#)

EXTREF

Attribute	Description					
Name	EXTREF					
Datatype	String					
Description	Reference supplied by the external system in case the Interaction was uploaded					
Attributes	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>maxLength</td> <td>30</td> </tr> </table>	Restrictions	Description	maxLength	30	
Restrictions	Description					
maxLength	30					

[TOP](#)

RECORGN

Attribute	Description					
Name	RECORGN					
Datatype	String					
Description	The types of the interactions booked 1. Manual 2. System Generated 3. Upload					
Attributes	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>enumeration</td> <td>M,S,U</td> </tr> </table>	Restrictions	Description	enumeration	M,S,U	
Restrictions	Description					
enumeration	M,S,U					

[TOP](#)

PROCESS_STAGE

Attribute	Description					
Name	PROCESS_STAGE					
Datatype	String					
Description	The current stage of the interaction Ex: Initiated or Approved or Rejected or Executed					
Attributes	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

Restrictions	Restrictions	Description
	enumeration	I,R,E,A

[TOP](#)

TOTPTPAMT

Attribute	Description					
Name	TOTPTPAMT					
Datatype	Number					
Description	This is the total amount, the customer promises to pay. Applicable only if the result of action is a factory shipped result code for PTP					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

[TOP](#)

ACTION_CODE

Attribute	Description					
Name	ACTION_CODE					
Datatype	String					
Description	This is the action that is being executed as part of the interaction carried out					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>		Restrictions	Description	maxLength	20
Restrictions	Description					
maxLength	20					

[TOP](#)

RESLT

Attribute	Description					
Name	RESLT					
Datatype	String					
Description	This is the result of the action during execution					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>		Restrictions	Description	maxLength	20
Restrictions	Description					
maxLength	20					

[TOP](#)

ACTINDT

Attribute	Description					
Name	ACTINDT					
Datatype	Date					
Description	This is the date of execution of the aforesaid action					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

[TOP](#)

DELREASON

Attribute	Description	

Name	DELREASON	
Datatype	String	
Description	The reason for the Account going into overdue as given by the Customer	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

NEXTACTION

Attribute	Description	
Name	NEXTACTION	
Datatype	String	
Description	This field denotes the next action that can be executed by the person	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

[TOP](#)

RSLTDT

Attribute	Description	
Name	RSLTDT	
Datatype	Date	
Description	Typically a Action Date, in case of WAITING action, the next action date can be taken as Result Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

NXTACTIONNDT

Attribute	Description	
Name	NXTACTIONNDT	
Datatype	Date	
Description	Next Action Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

COMNTS

Attribute	Description	
Name	COMNTS	
Datatype	String	
Description	The comments related to the interaction can be captured here	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

NLS_HR

Attribute	Description	
Name	NLS_HR	
Datatype	Number	
Description	Hour of the interaction can be recorded	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

OFSMINS

Attribute	Description	
Name	OFSMINS	
Datatype	Number	
Description	Minute of the interaction can be recorded	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CUSTMAIL

Attribute	Description	
Name	CUSTMAIL	
Datatype	String	
Description	Customer E-mail Id	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

MEDIA

Attribute	Description	
Name	MEDIA	
Datatype	String	
Description	Media, Mail, FAX, Phone etc..	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

INTRACTIONPLACE

Attribute	Description	
Name	INTRACTIONPLACE	
Datatype	String	
Description	Interaction Place. This is applicable for some actions like personal visit	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

CUSTMOB

Attribute	Description	
Name	CUSTMOB	
Datatype	Number	
Description	Customer Mobile Number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

Asset

Attribute	Description	
Name	Asset	
Datatype		
Description	Collection Asset Details	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

LOANREFNO

Attribute	Description	
Name	LOANREFNO	
Datatype	String	
Description	This is a Asset Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

ASSETQUTPRINCIPAL

Attribute	Description	
Name	ASSETQUTPRINCIPAL	
Datatype	Number	
Description	Principal Outstanding Amount as on Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ASSETCCY

Attribute	Description	
Name	ASSETCCY	

Datatype	String	
Description	Currency in which the transaction takes place	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

ASSETBRN

Attribute	Description	
Name	ASSETBRN	
Datatype	String	
Description	Asset Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

ASSETTOTALOVD

Attribute	Description	
Name	ASSETTOTALOVD	
Datatype	Number	
Description	Total Overdue Amount as on Date	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ASSETSCHOVD

Attribute	Description	
Name	ASSETSCHOVD	
Datatype	Number	
Description	Total No of Schedules Overdue	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

ASSETUDETSTAT

Attribute	Description	
Name	ASSETUDETSTAT	
Datatype	String	
Description	User Defined Status for the Asset Reference	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

[TOP](#)

ASSETAMT

Attribute	Description	
Name	ASSETAMT	
Datatype	Number	
Description	Total Asset Amount	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

Ptp

Attribute	Description	
Name	Ptp	
Datatype		
Description	Promise To Pay Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

PTPAMT

Attribute	Description	
Name	PTPAMT	
Datatype	Number	
Description	The Amount which Customer Promise to pay	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PTPDT

Attribute	Description	
Name	PTPDT	
Datatype	Date	
Description	Date on which the Amount will be paid	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

AMTPAID

Attribute	Description	
Name	AMTPAID	
Datatype	Number	
Description	Actual Amount paid by the customer	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

PTPSTAT

Attribute	Description	
Name	PTPSTAT	
Datatype	String	
Description	PTP Status as on Date: Pending(P), Honored(H), Broken(B), Partial (L), Cancelled (C)	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	P,H,B,L

[TOP](#)

PTPCARGE

Attribute	Description	
Name	PTPCARGE	
Datatype	Number	
Description	Promise to Pay Charge	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

Footer

Attribute	Description	
Name	Footer	
Datatype		
Description	This includes Audit Trail Details	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CONREFNO

Attribute	Description	
Name	CONREFNO	

Datatype	String	
Description	The reference number for the contract booked	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	The user who books the Contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

MAKDTTIME

Attribute	Description	
Name	MAKDTTIME	
Datatype	String	
Description	The date and Time at which the contract is booked	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

CHKR

Attribute	Description	
Name	CHKR	
Datatype	String	
Description	The Approver of the Contract Booked	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

CHKDTTIME

Attribute	Description	
Name	CHKDTTIME	
Datatype	String	
Description	The time at which the contract booked got approved	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

[TOP](#)

EVNTSEQNO

Attribute	Description	
Name	EVNTSEQNO	
Datatype	Number	
Description	Event sequence number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

CONSTAT

Attribute	Description	
Name	CONSTAT	
Datatype	String	
Description	Contract Status : "Active", "Hold", "Reversed" etc..	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,O,C

[TOP](#)

AUTHSTATS

Attribute	Description	
Name	AUTHSTATS	
Datatype	String	
Description	The Authorization Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,U,A

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.3.4.CN-DeleteCollectionInteraction-Res-PK-MSG.xsd

FCUBS_HEADER

SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
 PARAM
 NAME
 VALUE

FCUBS_BODY

CHOICE
 Main-PK
 ISN
 Main-IO
 ISN

FCUBS_ERROR_RESP
 ERROR
 E CODE
 E DESC

FCUBS_WARNING_RESP
 WARNING
 W CODE
 W DESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	This is a standard node that would form the header for FLEXCUBE UBS Envelope. Information to identify the partner system, service, operation, user and branch etc., will form the tags in this node. Entire processing in FLEXCUBE UBS Messaging Database Layer is based upon the information provided in this node.
-------------	--

[TOP](#)

SOURCE

Attribute	Description					
Name	SOURCE					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

[TOP](#)

UBSCOMP

Attribute	Description					
Name	UBSCOMP					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

[TOP](#)

MSGID

Attribute	Description							
Name	MSGID							
Datatype	String							
Description								
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	nillable	true
Attribute	Description							
minOccurs	0							
nillable	true							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description							
pattern	[a-zA-Z_0-9]*							

[TOP](#)

CORRELID

Attribute	Description							
Name	CORRELID							
Datatype	String							
Description								
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	nillable	true
Attribute	Description							
minOccurs	0							
nillable	true							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description							
pattern	[a-zA-Z_0-9]*							

[TOP](#)

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		

Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	
	minOccurs	0

[TOP](#)

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about PK Response	

[TOP](#)

CHOICE

Attribute	Description	

Name	CHOICE
Datatype	
Description	

[TOP](#)

Main-PK

Attribute	Description
Name	Main-PK
Datatype	
Description	It indicates Collection Interaction Deletion PK Response details of Collections module

[TOP](#)

ISN

Attribute	Description	
Name	ISN	
Datatype	String	
Description	Interaction Sequence Number for every new interaction	
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

Main-IO

Attribute	Description	
Name	Main-IO	
Datatype		
Description	It indicates Collection Interaction Deletion IO Response details of Collections module	

[TOP](#)

ISN

Attribute	Description	
Name	ISN	
Datatype	String	
Description	Interaction Sequence Number for every new interaction	
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

WCODE

Attribute	Description	
Name	WCODE	

Datatype	String
Description	

[TOP](#)

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)



Collections Service

[April] [2014]

Oracle Financial Services software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:

Phone: +91 22 6718 3000

Fax:+91 22 6718 3001

www.oracle.com/financialservices/

Copyright © [2013], [2014], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any

kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.