Gateway Documentation - FCUBSCFService
Oracle FLEXCUBE Universal Banking
Release 12.87.02.0.0
[Febraury][2016]

Table Of Contents

1. Background **1**

2. FCUBSCFService **2**

2.1.AuthCFFloatRateMaint **2**

2.1.1.CF-AuthCFFloatRateMaint-Req-Full-MSG.xsd 2

2.1.2.CF-AuthCFFloatRateMaint-Req-IO-MSG.xsd 15

2.1.3.CF-AuthCFFloatRateMaint-Res-Full-MSG.xsd 23

2.1.4.CF-AuthCFFloatRateMaint-Res-PK-MSG.xsd 40

2.2.AuthCFRateCodeMaint **58**

2.2.1.CF-AuthCFRateCodeMaint-Req-Full-MSG.xsd 58

2.2.2.CF-AuthCFRateCodeMaint-Req-IO-MSG.xsd 70

2.2.3.CF-AuthCFRateCodeMaint-Res-Full-MSG.xsd 77

2.2.4.CF-AuthCFRateCodeMaint-Res-PK-MSG.xsd 92

2.3.AuthCFRateTypeDefn **107**

2.3.1.CF-AuthCFRateTypeDefn-Req-Full-MSG.xsd 107

2.3.2.CF-AuthCFRateTypeDefn-Req-IO-MSG.xsd 118

2.3.3.CF-AuthCFRateTypeDefn-Res-Full-MSG.xsd 125

2.3.4.CF-AuthCFRateTypeDefn-Res-PK-MSG.xsd 138

2.4.AuthorizeCFDFLTRI **152**

2.4.1.CF-AuthorizeCFDFLTRI-Req-Full-MSG.xsd 152

2.4.2.CF-AuthorizeCFDFLTRI-Req-IO-MSG.xsd 164

2.4.3.CF-AuthorizeCFDFLTRI-Res-Full-MSG.xsd 172

2.4.4.CF-AuthorizeCFDFLTRI-Res-PK-MSG.xsd 185

2.5.CloseCFDFLTRI **195**

2.5.1.CF-CloseCFDFLTRI-Req-Full-MSG.xsd 195

2.5.2.CF-CloseCFDFLTRI-Req-IO-MSG.xsd 207

2.5.3.CF-CloseCFDFLTRI-Res-Full-MSG.xsd 215

2.5.4.CF-CloseCFDFLTRI-Res-PK-MSG.xsd 228

2.6.CreateCFDFLTRI **238**

2.6.1.CF-CreateCFDFLTRI-Req-Full-MSG.xsd 238

2.6.2.CF-CreateCFDFLTRI-Req-IO-MSG.xsd 250

2.6.3.CF-CreateCFDFLTRI-Res-Full-MSG.xsd 260

2.6.4.CF-CreateCFDFLTRI-Res-PK-MSG.xsd 273

2.7.CreateCFFloatRateMaint **285**

2.7.1.CF-CreateCFFloatRateMaint-Req-Full-MSG.xsd 285

2.7.2.CF-CreateCFFloatRateMaint-Req-IO-MSG.xsd 299

2.7.3.CF-CreateCFFloatRateMaint-Res-Full-MSG.xsd 312

2.7.4.CF-CreateCFFloatRateMaint-Res-PK-MSG.xsd 333

2.8.CreateCFRateCodeMaint **356**

2.8.1.CF-CreateCFRateCodeMaint-Req-Full-MSG.xsd 356

2.8.2.CF-CreateCFRateCodeMaint-Req-IO-MSG.xsd 368

2.8.3.CF-CreateCFRateCodeMaint-Res-Full-MSG.xsd 380

2.8.4.CF-CreateCFRateCodeMaint-Res-PK-MSG.xsd 400

2.9.CreateCFRateTypeDefn **420**

2.9.1.CF-CreateCFRateTypeDefn-Req-Full-MSG.xsd 420

2.9.2.CF-CreateCFRateTypeDefn-Req-IO-MSG.xsd 431

2.9.3.CF-CreateCFRateTypeDefn-Res-Full-MSG.xsd 442

2.9.4.CF-CreateCFRateTypeDefn-Res-PK-MSG.xsd 459

2.10.DeleteCFDFLTRI **477**

2.10.1.CF-DeleteCFDFLTRI-Req-Full-MSG.xsd 477
2.10.2.CF-DeleteCFDFLTRI-Req-IO-MSG.xsd 489
2.10.3.CF-DeleteCFDFLTRI-Res-Full-MSG.xsd 496
2.10.4.CF-DeleteCFDFLTRI-Res-PK-MSG.xsd 509
2.11.DeleteCFFloatRateMaint 518
2.11.1.CF-DeleteCFFloatRateMaint-Req-Full-MSG.xsd 518
2.11.2.CF-DeleteCFFloatRateMaint-Req-IO-MSG.xsd 532
2.11.3.CF-DeleteCFFloatRateMaint-Res-Full-MSG.xsd 539
2.11.4.CF-DeleteCFFloatRateMaint-Res-PK-MSG.xsd 556
2.12.DeleteCFRateCodeMaint 574
2.12.1.CF-DeleteCFRateCodeMaint-Req-Full-MSG.xsd 574
2.12.2.CF-DeleteCFRateCodeMaint-Req-IO-MSG.xsd 586
2.12.3.CF-DeleteCFRateCodeMaint-Res-Full-MSG.xsd 593
2.12.4.CF-DeleteCFRateCodeMaint-Res-PK-MSG.xsd 607
2.13.DeleteCFRateTypeDefn 622
2.13.1.CF-DeleteCFRateTypeDefn-Req-Full-MSG.xsd 622
2.13.2.CF-DeleteCFRateTypeDefn-Req-IO-MSG.xsd 633
2.13.3.CF-DeleteCFRateTypeDefn-Res-Full-MSG.xsd 640
2.13.4.CF-DeleteCFRateTypeDefn-Res-PK-MSG.xsd 653
2.14.ModifyCFDFLTRI 666
2.14.1.CF-ModifyCFDFLTRI-Req-Full-MSG.xsd 666
2.14.2.CF-ModifyCFDFLTRI-Req-IO-MSG.xsd 678
2.14.3.CF-ModifyCFDFLTRI-Res-Full-MSG.xsd 688
2.14.4.CF-ModifyCFDFLTRI-Res-PK-MSG.xsd 701
2.15.ModifyCFFloatRateMaint 713
2.15.1.CF-ModifyCFFloatRateMaint-Req-Full-MSG.xsd 713
2.15.2.CF-ModifyCFFloatRateMaint-Req-IO-MSG.xsd 727
2.15.3.CF-ModifyCFFloatRateMaint-Res-Full-MSG.xsd 737
2.15.4.CF-ModifyCFFloatRateMaint-Res-PK-MSG.xsd 756
2.16.ModifyCFRateCodeMaint 777
2.16.1.CF-ModifyCFRateCodeMaint-Req-Full-MSG.xsd 777
2.16.2.CF-ModifyCFRateCodeMaint-Req-IO-MSG.xsd 789
2.16.3.CF-ModifyCFRateCodeMaint-Res-Full-MSG.xsd 799
2.16.4.CF-ModifyCFRateCodeMaint-Res-PK-MSG.xsd 817
2.17.ModifyCFRateTypeDefn 835
2.17.1.CF-ModifyCFRateTypeDefn-Req-Full-MSG.xsd 835
2.17.2.CF-ModifyCFRateTypeDefn-Req-IO-MSG.xsd 846
2.17.3.CF-ModifyCFRateTypeDefn-Res-Full-MSG.xsd 855
2.17.4.CF-ModifyCFRateTypeDefn-Res-PK-MSG.xsd 870
2.18.QueryCFDFLTRI 886
2.18.1.CF-QueryCFDFLTRI-Req-IO-MSG.xsd 886
2.18.2.CF-QueryCFDFLTRI-Res-Full-MSG.xsd 893
2.19.QueryCFFloatRateMaint 907
2.19.1.CF-QueryCFFloatRateMaint-Req-IO-MSG.xsd 907
2.19.2.CF-QueryCFFloatRateMaint-Res-Full-MSG.xsd 914
2.20.QueryCFRateCodeMaint 931
2.20.1.CF-QueryCFRateCodeMaint-Req-IO-MSG.xsd 931
2.20.2.CF-QueryCFRateCodeMaint-Res-Full-MSG.xsd 937
2.21.QueryCFRateTypeDefn 951
2.21.1.CF-QueryCFRateTypeDefn-Req-IO-MSG.xsd 951
2.21.2.CF-QueryCFRateTypeDefn-Res-Full-MSG.xsd 958
2.22.ReopenCFDFLTRI 971

2.22.1.CF-ReopenCFDFLTRI-Req-Full-MSG.xsd 971
2.22.2.CF-ReopenCFDFLTRI-Req-IO-MSG.xsd 983
2.22.3.CF-ReopenCFDFLTRI-Res-Full-MSG.xsd 991
2.22.4.CF-ReopenCFDFLTRI-Res-PK-MSG.xsd 1005

1. Background

Integration of different applications and solutions is a key area in today's systems.A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data.The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs.The integration needs supported by the Gateway can be broadly categorized from the perspective of Gateway as follows

1. Inbound application integration :

This is used when any external system needs to add, modify or query information within FLEXCUBE UBS

2. Outbound application integration :

This is used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS

The following sections provide detailed XSD documentation of all operations available in FCUBSCFService of Core Module

2. FCUBSCFService

2.1.AuthCFFloatRateMaint

2.1.1.CF-AuthCFFloatRateMaint-Req-Full-MSG.xsd

- *AUTHCFFLOATRATEMAINT_FSFS_REQ*
  - *FCUBS_HEADER*
    - *SOURCE*
    - *UBSCOMP*
    - *MSGID*
    - *CORRELID*
    - *USERID*
    - *BRANCH*
    - *MODULEID*
    - *SERVICE*
    - *OPERATION*
    - *SOURCE_OPERATION*
    - *SOURCE_USERID*
    - *DESTINATION*
    - *MULTITRIPID*
    - *FUNCTIONID*
    - *ACTION*
    - *MSGSTAT*
    - *PASSWORD*
    - *ADDL*
      - *PARAM*
        - *NAME*
        - *VALUE*
  - *FCUBS_BODY*
    - *Cftm-Rate-Master-Full*
      - *RATECODE*
      - *RATECODEDESCRIPTION*
      - *TENORCODE*
      - *TENORCODEDESCRIPTION*

CCYCODE

CCYNAME

EFFECTIVEDATE

RATESOURCE

RATESOURCEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Rate-Detail

- *RATETYPE*
- *RATETYPEDESCRIPTION*
- *INTERESTRATE*

UDFDETAILS

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

AUTHCFFLOATRATEMAINT_FSFS_REQ

Attribute	Description
Name	AUTHCFFLOATRATEMAINT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Master-Full

Attribute	Description
Name	Cftm-Rate-Master-Full
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 10

RATECODEDESCRIPTION

Attribute	Description
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates Rate Code Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code

Restrictions	

Restrictions	Description
maxLength	12

TENORCODEDESCRIPTION

Attribute	Description
Name	TENORCODEDESCRIPTION
Datatype	String
Description	Indicates Tenor Code Description
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	

Restrictions	Description
maxLength	3

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency Code Description
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

RATESOURCE

Attribute	Description

Name	RATESOURCE
Datatype	String
Description	Indicates Rate Source
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

RATESOURCEDESCRIPTION

Attribute	**Description**
Name	RATESOURCEDESCRIPTION
Datatype	String
Description	Indicates Rate Source Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	The User id who has booked the contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has booked the contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

CHECKERID

Attribute	**Description**

Name	CHECKERID
Datatype	String
Description	The User id who has authorized the booked contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

MODNO

Attribute	**Description**
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates Record Status

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorized
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

Cftm-Rate-Detail

Attribute	**Description**
Name	Cftm-Rate-Detail
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

RATETYPE

Attribute	**Description**
Name	RATETYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

RATETYPEDESCRIPTION

Attribute	**Description**
Name	RATETYPEDESCRIPTION
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

INTERESTRATE

Attribute	Description
Name	INTERESTRATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

2.1.2.CF-AuthCFFloatRateMaint-Req-IO-MSG.xsd

AUTHCFFLOATRATEMAINT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Master-IO

RATECODE

TENORCODE

CCYCODE

EFFECTIVEDATE

MODNO

AUTHCFFLOATRATEMAINT_IOPK_REQ

Attribute	Description
Name	AUTHCFFLOATRATEMAINT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Master-IO

Attribute	Description
Name	Cftm-Rate-Master-IO
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CCYCODE

Attribute	Description

Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

EFFECTIVEDATE

Attribute	**Description**
Name	EFFECTIVEDATE
Datatype	String
Description	

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Integer
Description	Specifies The Modification Number.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

2.1.3.CF-AuthCFFloatRateMaint-Res-Full-MSG.xsd

AUTHCFFLOATRATEMAINT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Master-IO

RATECODE

TENORCODE

CCYCODE

EFFECTIVEDATE

MODNO

Cftm-Rate-Master-Full

RATECODE

RATECODEDESCRIPTION

TENORCODE

TENORCODEDESCRIPTION

CCYCODE

CCYNAME

EFFECTIVEDATE

RATESOURCE

RATESOURCEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Rate-Detail

RATETYPE

RATETYPEDESCRIPTION

INTERESTRATE

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHCFFLOATRATEMAINT_FSFS_RES

Attribute	Description
Name	AUTHCFFLOATRATEMAINT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Master-IO

Attribute	Description
Name	Cftm-Rate-Master-IO
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CCYCODE

Attribute	Description

Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

EFFECTIVEDATE

Attribute	**Description**
Name	EFFECTIVEDATE
Datatype	String
Description	

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Integer
Description	Specifies The Modification Number.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Cftm-Rate-Master-Full

Attribute	**Description**
Name	Cftm-Rate-Master-Full
Datatype	
Description	

RATECODE

Attribute	**Description**
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 10

RATECODEDESCRIPTION

Attribute	**Description**
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates Rate Code Description

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TENORCODEDESCRIPTION

Attribute	Description
Name	TENORCODEDESCRIPTION
Datatype	String
Description	Indicates Tenor Code Description
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency Code Description
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

RATESOURCE

Attribute	Description
Name	RATESOURCE
Datatype	String
Description	Indicates Rate Source
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

RATESOURCEDESCRIPTION

Attribute	Description
Name	RATESOURCEDESCRIPTION
Datatype	String
Description	Indicates Rate Source Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	The User id who has booked the contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP

Datatype	String
Description	Indicates date and stamp when the user has booked the contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	The User id who has authorized the booked contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

MODNO

Attribute	**Description**
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorized
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Cftm-Rate-Detail

Attribute	Description
Name	Cftm-Rate-Detail
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

INTERESTRATE

Attribute	Description
Name	INTERESTRATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.1.4.CF-AuthCFFloatRateMaint-Res-PK-MSG.xsd

AUTHCFFLOATRATEMAINT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Master-PK

RATECODE

TENORCODE

CCYCODE

EFFECTIVEDATE

Cftm-Rate-Master-IO

RATECODE

TENORCODE

CCYCODE

EFFECTIVEDATE

MODNO

Cftm-Rate-Master-Full

RATECODE

RATECODEDESCRIPTION

TENORCODE

TENORCODEDESCRIPTION

CCYCODE

CCYNAME

EFFECTIVEDATE

RATESOURCE

RATESOURCEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Rate-Detail

RATETYPE

RATETYPEDESCRIPTION

INTERESTRATE

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHCFFLOATRATEMAINT_IOPK_RES

Attribute	Description
Name	AUTHCFFLOATRATEMAINT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Master-PK

Attribute	Description
Name	Cftm-Rate-Master-PK
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CCYCODE

Attribute	Description

Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

EFFECTIVEDATE

Attribute	**Description**
Name	EFFECTIVEDATE
Datatype	String
Description	

Cftm-Rate-Master-IO

Attribute	**Description**
Name	Cftm-Rate-Master-IO
Datatype	
Description	

RATECODE

Attribute	**Description**
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TENORCODE

Attribute	**Description**
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CCYCODE

Attribute	**Description**
Name	CCYCODE

Datatype	String
Description	Indicates Currency Code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	String
Description	

MODNO

Attribute	Description
Name	MODNO
Datatype	Integer
Description	Specifies The Modification Number.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

Cftm-Rate-Master-Full

Attribute	Description
Name	Cftm-Rate-Master-Full
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

RATECODEDESCRIPTION

Attribute	Description
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates Rate Code Description

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TENORCODE

Attribute	**Description**
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Restrictions	**Restrictions** / **Description** maxLength / 12

TENORCODEDESCRIPTION

Attribute	**Description**
Name	TENORCODEDESCRIPTION
Datatype	String
Description	Indicates Tenor Code Description
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

CCYCODE

Attribute	**Description**
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

CCYNAME

Attribute	**Description**
Name	CCYNAME
Datatype	String
Description	Indicates Currency Code Description
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

RATESOURCE

Attribute	Description
Name	RATESOURCE
Datatype	String
Description	Indicates Rate Source
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

RATESOURCEDESCRIPTION

Attribute	Description
Name	RATESOURCEDESCRIPTION
Datatype	String
Description	Indicates Rate Source Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	The User id who has booked the contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP

Datatype	String
Description	Indicates date and stamp when the user has booked the contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	The User id who has authorized the booked contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

MODNO

Attribute	**Description**
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 1

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorized
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

Cftm-Rate-Detail

Attribute	**Description**
Name	Cftm-Rate-Detail
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

RATETYPE

Attribute	**Description**
Name	RATETYPE
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

INTERESTRATE

Attribute	Description
Name	INTERESTRATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.2.AuthCFRateCodeMaint

2.2.1.CF-AuthCFRateCodeMaint-Req-Full-MSG.xsd

AUTHCFRATECODEMAINT_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Code-Defn-Full

RATECODE

RATECODEDESCRIPTION

HOLIDAYCCY

PROPAGATIONACROSSBRANCHES

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Tenor-Code-Defn

TENORCODE

TENORCODEDESCRIPTION

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

AUTHCFRATECODEMAINT_FSFS_REQ

Attribute	Description
Name	AUTHCFRATECODEMAINT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Code-Defn-Full

Attribute	Description
Name	Cftm-Rate-Code-Defn-Full
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

RATECODEDESCRIPTION

Attribute	Description
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates the description of rate code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

HOLIDAYCCY

Attribute	Description

Name	HOLIDAYCCY
Datatype	String
Description	Indicates Holiday Currency
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

PROPAGATIONACROSSBRANCHES

Attribute	**Description**
Name	PROPAGATIONACROSSBRANCHES
Datatype	String
Description	Propagate Across Branches
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	Specifies the User id who has saved the record.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the date and time when the user has saved the record.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

CHECKERID

Attribute	**Description**

Name	CHECKERID
Datatype	String
Description	Indicates the User id who has authorized the record.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

MODNO

Attribute	**Description**
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	It indicates the status of the record,whether open or Closed.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorized
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

Cftm-Tenor-Code-Defn

Attribute	**Description**
Name	Cftm-Tenor-Code-Defn
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

TENORCODE

Attribute	**Description**
Name	TENORCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TENORCODEDESCRIPTION

Attribute	**Description**
Name	TENORCODEDESCRIPTION
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

2.2.2.CF-AuthCFRateCodeMaint-Req-IO-MSG.xsd

AUTHCFRATECODEMAINT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Code-Defn-IO

RATECODE

MODNO

AUTHCFRATECODEMAINT_IOPK_REQ

Attribute	Description
Name	AUTHCFRATECODEMAINT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description

Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Code-Defn-IO

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Integer
Description	Specifies The Modification Number.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

2.2.3.CF-AuthCFRateCodeMaint-Res-Full-MSG.xsd

AUTHCFRATECODEMAINT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Code-Defn-IO

RATECODE

MODNO

Cftm-Rate-Code-Defn-Full

RATECODE

RATECODEDESCRIPTION

HOLIDAYCCY

PROPAGATIONACROSSBRANCHES

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Tenor-Code-Defn

TENORCODE

TENORCODEDESCRIPTION

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHCFRATECODEMAINT_FSFS_RES

Attribute	Description
Name	AUTHCFRATECODEMAINT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Code-Defn-IO

Attribute	**Description**

Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Integer
Description	Specifies The Modification Number.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

Cftm-Rate-Code-Defn-Full

Attribute	Description
Name	Cftm-Rate-Code-Defn-Full
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

RATECODEDESCRIPTION

Attribute	Description
Name	RATECODEDESCRIPTION

Datatype	String
Description	Indicates the description of rate code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

HOLIDAYCCY

Attribute	**Description**
Name	HOLIDAYCCY
Datatype	String
Description	Indicates Holiday Currency
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

PROPAGATIONACROSSBRANCHES

Attribute	**Description**
Name	PROPAGATIONACROSSBRANCHES
Datatype	String
Description	Propagate Across Branches
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	Specifies the User id who has saved the record.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP

Datatype	String
Description	Indicates the date and time when the user has saved the record.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User id who has authorized the record.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	It indicates the status of the record,whether open or Closed.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorized
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Cftm-Tenor-Code-Defn

Attribute	Description
Name	Cftm-Tenor-Code-Defn
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TENORCODEDESCRIPTION

Attribute	Description
Name	TENORCODEDESCRIPTION
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name

Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.2.4.CF-AuthCFRateCodeMaint-Res-PK-MSG.xsd

AUTHCFRATECODEMAINT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Code-Defn-PK

RATECODE

Cftm-Rate-Code-Defn-IO

RATECODE

MODNO

Cftm-Rate-Code-Defn-Full

RATECODE

RATECODEDESCRIPTION

HOLIDAYCCY

PROPAGATIONACROSSBRANCHES

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Tenor-Code-Defn

TENORCODE

TENORCODEDESCRIPTION

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

Attribute	Description
Name	AUTHCFRATECODEMAINT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Code-Defn-PK

Attribute	Description
Name	Cftm-Rate-Code-Defn-PK
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

Cftm-Rate-Code-Defn-IO

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Integer
Description	Specifies The Modification Number.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

Cftm-Rate-Code-Defn-Full

Attribute	Description
Name	Cftm-Rate-Code-Defn-Full
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

RATECODEDESCRIPTION

Attribute	Description
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates the description of rate code

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

HOLIDAYCCY

Attribute	**Description**
Name	HOLIDAYCCY
Datatype	String
Description	Indicates Holiday Currency
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

PROPAGATIONACROSSBRANCHES

Attribute	**Description**
Name	PROPAGATIONACROSSBRANCHES
Datatype	String
Description	Propagate Across Branches
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	Specifies the User id who has saved the record.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the date and time when the user has saved the record.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	Indicates the User id who has authorized the record.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

MODNO

Attribute	**Description**
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 1

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	It indicates the status of the record,whether open or Closed.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorized
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

Cftm-Tenor-Code-Defn

Attribute	**Description**
Name	Cftm-Tenor-Code-Defn
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

TENORCODE

Attribute	**Description**
Name	TENORCODE
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TENORCODEDESCRIPTION

Attribute	**Description**
Name	TENORCODEDESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name

Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.3.AuthCFRateTypeDefn

2.3.1.CF-AuthCFRateTypeDefn-Req-Full-MSG.xsd

AUTHCFRATETYPEDEFN_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Type-Defn-Full

RATETYPE

RATETYPEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

AUTHCFRATETYPEDEFN_FSFS_REQ

Attribute	Description
Name	AUTHCFRATETYPEDEFN_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Type-Defn-Full

Attribute	Description
Name	Cftm-Rate-Type-Defn-Full
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	Indicates Rate Type Description
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	The User Id who has created\last modified the Rate Type Definition details.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user hascreated\last modified the Rate Type Definition details.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	The User Id who has Authorized the creation\modification of Rate Type Definition details.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user has Authorized the creation\ modification of Rate Type Definition details.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

MODNO

Attribute	**Description**
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A - Authorized U - Un Authorized

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status O - Open C - Close
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Rate Type Definition detail has been Authorized atleast Once.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.3.2.CF-AuthCFRateTypeDefn-Req-IO-MSG.xsd

AUTHCFRATETYPEDEFN_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Type-Defn-IO

RATETYPE

MODNO

AUTHCFRATETYPEDEFN_IOPK_REQ

Attribute	Description
Name	AUTHCFRATETYPEDEFN_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Type-Defn-IO

Attribute	Description
Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Integer
Description	Indicates Modification Number i.e. the number of times Rate Type Definition has been modified.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

2.3.3.CF-AuthCFRateTypeDefn-Res-Full-MSG.xsd

AUTHCFRATETYPEDEFN_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Type-Defn-IO

RATETYPE

MODNO

Cftm-Rate-Type-Defn-Full

RATETYPE

RATETYPEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

Attribute	Description
Name	AUTHCFRATETYPEDEFN_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Type-Defn-IO

Attribute	Description
Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Integer
Description	Indicates Modification Number i.e. the number of times Rate Type Definition has been modified.

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22

Cftm-Rate-Type-Defn-Full

Attribute	**Description**
Name	Cftm-Rate-Type-Defn-Full
Datatype	
Description	

RATETYPE

Attribute	**Description**
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

RATETYPEDESCRIPTION

Attribute	**Description**
Name	RATETYPEDESCRIPTION
Datatype	String
Description	Indicates Rate Type Description
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	The User Id who has created\last modified the Rate Type Definition details.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	12

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user hascreated\last modified the Rate Type Definition details.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	25

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	The User Id who has Authorized the creation\modification of Rate Type Definition details.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user has Authorized the creation\ modification of Rate Type Definition details.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	25

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A - Authorized U - Un Authorized
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status O - Open C - Close
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Rate Type Definition detail has been Authorized atleast Once.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.3.4.CF-AuthCFRateTypeDefn-Res-PK-MSG.xsd

AUTHCFRATETYPEDEFN_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Type-Defn-PK

RATETYPE

Cftm-Rate-Type-Defn-IO

RATETYPE

MODNO

Cftm-Rate-Type-Defn-Full

RATETYPE

RATETYPEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHCFRATETYPEDEFN_IOPK_RES

Attribute	Description
Name	AUTHCFRATETYPEDEFN_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String

Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Type-Defn-PK

Attribute	Description
Name	Cftm-Rate-Type-Defn-PK
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

Cftm-Rate-Type-Defn-IO

Attribute	Description
Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Integer
Description	Indicates Modification Number i.e. the number of times Rate Type Definition has been modified.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

Cftm-Rate-Type-Defn-Full

Attribute	Description
Name	Cftm-Rate-Type-Defn-Full
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	Indicates Rate Type Description
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	The User Id who has created\last modified the Rate Type Definition details.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user hascreated\last modified the Rate Type Definition details.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	The User Id who has Authorized the creation\modification of Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user has Authorized the creation\ modification of Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A - Authorized U - Un Authorized
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status O - Open C - Close
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Rate Type Definition detail has been Authorized atleast Once.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description

Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.4.AuthorizeCFDFLTRI

2.4.1.CF-AuthorizeCFDFLTRI-Req-Full-MSG.xsd

AUTHORIZECFDFLTRI_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-Full

RATE_CODE

DESC

BRANCH_CODE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Rate-Ccy

CCY_CODE

Fload-Rate

AMOUNT_SLAB1

EFFECTIVE_DATE

BORROW_LEND_IND

Fltrate-Detail

TENOR_TO1

INTEREST_RATE

UDFDETAILS

FLDNAM

FLDVAL

AUTHORIZECFDFLTRI_FSFS_REQ

Attribute	Description
Name	AUTHORIZECFDFLTRI_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-Full

Attribute	Description
Name	Rate-Code-Full
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 10

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	

Restrictions	
	Restrictions / **Description**: maxLength / 3

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

Rate-Ccy

Attribute	**Description**
Name	Rate-Ccy
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

CCY_CODE

Attribute	Description
Name	CCY_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

Fload-Rate

Attribute	Description
Name	Fload-Rate
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

AMOUNT_SLAB1

Attribute	Description
Name	AMOUNT_SLAB1
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 9999999999999999999.99

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M

Fltrate-Detail

Attribute	Description
Name	Fltrate-Detail
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

TENOR_TO1

Attribute	Description
Name	TENOR_TO1
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	5
minInclusive	0
maxInclusive	99999

INTEREST_RATE

Attribute	Description
Name	INTEREST_RATE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
maxInclusive	100

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.4.2.CF-AuthorizeCFDFLTRI-Req-IO-MSG.xsd

AUTHORIZECFDFLTRI_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-IO

RATE_CODE

BRANCH_CODE

CHECKER

CHECKERSTAMP

MODNO

AUTHORIZECFDFLTRI_IOPK_REQ

Attribute	Description
Name	AUTHORIZECFDFLTRI_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.

Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-IO

Attribute	Description
Name	Rate-Code-IO
Datatype	
Description	

RATE_CODE

Attribute	Description

Name	RATE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 10

BRANCH_CODE

Attribute	**Description**
Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	4

2.4.3.CF-AuthorizeCFDFLTRI-Res-Full-MSG.xsd

AUTHORIZECFDFLTRI_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-Full

RATE_CODE

DESC

BRANCH_CODE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Rate-Ccy

CCY_CODE

Fload-Rate

AMOUNT_SLAB1

EFFECTIVE_DATE

BORROW_LEND_IND

Fltrate-Detail

TENOR_TO1

INTEREST_RATE

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZECFDFLTRI_FSFS_RES

Attribute	Description
Name	AUTHORIZECFDFLTRI_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-Full

Attribute	Description
Name	Rate-Code-Full
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 10

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	

Restrictions	
	Restrictions / **Description**: maxLength / 3

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: maxLength / 35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

Rate-Ccy

Attribute	Description
Name	Rate-Ccy
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

CCY_CODE

Attribute	Description
Name	CCY_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

Fload-Rate

Attribute	Description
Name	Fload-Rate
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

AMOUNT_SLAB1

Attribute	Description
Name	AMOUNT_SLAB1
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 9999999999999999999.99

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M

Fltrate-Detail

Attribute	Description
Name	Fltrate-Detail
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

TENOR_TO1

Attribute	Description
Name	TENOR_TO1
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	5
minInclusive	0
maxInclusive	99999

INTEREST_RATE

Attribute	Description
Name	INTEREST_RATE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
maxInclusive	100

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.4.4.CF-AuthorizeCFDFLTRI-Res-PK-MSG.xsd

AUTHORIZECFDFLTRI_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-PK

RATE_CODE

BRANCH_CODE

Rate-Code-IO

RATE_CODE

BRANCH_CODE

CHECKER

CHECKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZECFDFLTRI_IOPK_RES

Attribute	Description
Name	AUTHORIZECFDFLTRI_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-PK

Attribute	Description
Name	Rate-Code-PK
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

Rate-Code-IO

Attribute	Description
Name	Rate-Code-IO
Datatype	
Description	

RATE_CODE

Attribute	Description

Name	RATE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 10

BRANCH_CODE

Attribute	**Description**
Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.5.CloseCFDFLTRI

2.5.1.CF-CloseCFDFLTRI-Req-Full-MSG.xsd

CLOSECFDFLTRI_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-Full

RATE_CODE

DESC

BRANCH_CODE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Rate-Ccy

CCY_CODE

Fload-Rate

AMOUNT_SLAB1

EFFECTIVE_DATE

BORROW_LEND_IND

Fltrate-Detail

TENOR_TO1

INTEREST_RATE

UDFDETAILS

FLDNAM

FLDVAL

CLOSECFDFLTRI_FSFS_REQ

Attribute	Description
Name	CLOSECFDFLTRI_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-Full

Attribute	Description
Name	Rate-Code-Full
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 10

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	3

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

Rate-Ccy

Attribute	Description
Name	Rate-Ccy
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

CCY_CODE

Attribute	Description
Name	CCY_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

Fload-Rate

Attribute	Description
Name	Fload-Rate
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

AMOUNT_SLAB1

Attribute	Description
Name	AMOUNT_SLAB1
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 9999999999999999999.99

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M

Fltrate-Detail

Attribute	Description
Name	Fltrate-Detail
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

TENOR_TO1

Attribute	Description
Name	TENOR_TO1
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	5
minInclusive	0
maxInclusive	99999

INTEREST_RATE

Attribute	Description
Name	INTEREST_RATE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
maxInclusive	100

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.5.2.CF-CloseCFDFLTRI-Req-IO-MSG.xsd

CLOSECFDFLTRI_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-IO

RATE_CODE

BRANCH_CODE

MAKER

MAKERSTAMP

MODNO

CLOSECFDFLTRI_IOPK_REQ

Attribute	Description
Name	CLOSECFDFLTRI_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.

Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-IO

Attribute	Description
Name	Rate-Code-IO
Datatype	
Description	

RATE_CODE

Attribute	Description

Name	RATE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 10

BRANCH_CODE

Attribute	**Description**
Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	4

2.5.3.CF-CloseCFDFLTRI-Res-Full-MSG.xsd

CLOSECFDFLTRI_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-Full

RATE_CODE

DESC

BRANCH_CODE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Rate-Ccy

CCY_CODE

Fload-Rate

AMOUNT_SLAB1

EFFECTIVE_DATE

BORROW_LEND_IND

Fltrate-Detail

TENOR_TO1

INTEREST_RATE

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CLOSECFDFLTRI_FSFS_RES

Attribute	Description
Name	CLOSECFDFLTRI_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-Full

Attribute	Description
Name	Rate-Code-Full
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 10

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	3

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

Rate-Ccy

Attribute	**Description**
Name	Rate-Ccy
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

CCY_CODE

Attribute	Description
Name	CCY_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

Fload-Rate

Attribute	Description
Name	Fload-Rate
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

AMOUNT_SLAB1

Attribute	Description
Name	AMOUNT_SLAB1
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 9999999999999999999.99

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M

Fltrate-Detail

Attribute	Description
Name	Fltrate-Detail
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

TENOR_TO1

Attribute	Description
Name	TENOR_TO1
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	5
minInclusive	0
maxInclusive	99999

INTEREST_RATE

Attribute	Description
Name	INTEREST_RATE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
maxInclusive	100

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.5.4.CF-CloseCFDFLTRI-Res-PK-MSG.xsd

CLOSECFDFLTRI_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-PK

RATE_CODE

BRANCH_CODE

Rate-Code-IO

RATE_CODE

BRANCH_CODE

MAKER

MAKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CLOSECFDFLTRI_IOPK_RES

Attribute	Description
Name	CLOSECFDFLTRI_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-PK

Attribute	Description
Name	Rate-Code-PK
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

Rate-Code-IO

Attribute	Description
Name	Rate-Code-IO
Datatype	
Description	

RATE_CODE

Attribute	Description

Name	RATE_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	10

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.6.CreateCFDFLTRI

2.6.1.CF-CreateCFDFLTRI-Req-Full-MSG.xsd

CREATECFDFLTRI_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-Full

RATE_CODE

DESC

BRANCH_CODE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Rate-Ccy

CCY_CODE

Fload-Rate

AMOUNT_SLAB1

EFFECTIVE_DATE

BORROW_LEND_IND

Fltrate-Detail

TENOR_TO1

INTEREST_RATE

UDFDETAILS

FLDNAM

FLDVAL

CREATECFDFLTRI_FSFS_REQ

Attribute	Description
Name	CREATECFDFLTRI_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-Full

Attribute	Description
Name	Rate-Code-Full
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 10

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	

Restrictions	
	Restrictions / **Description**: maxLength / 3

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: maxLength / 35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

Rate-Ccy

Attribute	Description
Name	Rate-Ccy
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

CCY_CODE

Attribute	Description
Name	CCY_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

Fload-Rate

Attribute	Description
Name	Fload-Rate
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

AMOUNT_SLAB1

Attribute	Description
Name	AMOUNT_SLAB1
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 9999999999999999999.99

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M

Fltrate-Detail

Attribute	Description
Name	Fltrate-Detail
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

TENOR_TO1

Attribute	Description
Name	TENOR_TO1
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	5
minInclusive	0
maxInclusive	99999

INTEREST_RATE

Attribute	Description
Name	INTEREST_RATE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
maxInclusive	100

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.6.2.CF-CreateCFDFLTRI-Req-IO-MSG.xsd

CREATECFDFLTRI_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-IO

RATE_CODE

DESC

BRANCH_CODE

Rate-Ccy

CCY_CODE

Fload-Rate

AMOUNT_SLAB1

EFFECTIVE_DATE

BORROW_LEND_IND

Fltrate-Detail

TENOR_TO1

INTEREST_RATE

UDFDETAILS

FLDNAM

FLDVAL

CREATECFDFLTRI_IOPK_REQ

Attribute	Description
Name	CREATECFDFLTRI_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String

Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-IO

Attribute	Description
Name	Rate-Code-IO
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 10

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

Rate-Ccy

Attribute	Description
Name	Rate-Ccy
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

CCY_CODE

Attribute	Description
Name	CCY_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

Fload-Rate

Attribute	Description
Name	Fload-Rate
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

AMOUNT_SLAB1

Attribute	Description
Name	AMOUNT_SLAB1
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	9999999999999999999.99

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Restrictions	

Restrictions	Description
enumeration	B,L,M

Fltrate-Detail

Attribute	Description
Name	Fltrate-Detail
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TENOR_TO1

Attribute	Description
Name	TENOR_TO1
Datatype	Decimal
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>99999</td></tr></table>

INTEREST_RATE

Attribute	Description
Name	INTEREST_RATE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>maxInclusive</td><td>100</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.6.3.CF-CreateCFDFLTRI-Res-Full-MSG.xsd

CREATECFDFLTRI_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-Full

RATE_CODE

DESC

BRANCH_CODE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Rate-Ccy

CCY_CODE

Fload-Rate

AMOUNT_SLAB1

EFFECTIVE_DATE

BORROW_LEND_IND

Fltrate-Detail

TENOR_TO1

INTEREST_RATE

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATECFDFLTRI_FSFS_RES

Attribute	Description
Name	CREATECFDFLTRI_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-Full

Attribute	Description
Name	Rate-Code-Full
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Rate-Ccy

Attribute	Description
Name	Rate-Ccy
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

CCY_CODE

Attribute	Description
Name	CCY_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

Fload-Rate

Attribute	Description
Name	Fload-Rate
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

AMOUNT_SLAB1

Attribute	Description
Name	AMOUNT_SLAB1
Datatype	Decimal
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>9999999999999999999.99</td></tr></table>

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration — B,L,M

FItrate-Detail

Attribute	Description
Name	FItrate-Detail
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs — 0; maxOccurs — unbounded

TENOR_TO1

Attribute	Description
Name	TENOR_TO1
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits — 5; minInclusive — 0; maxInclusive — 99999

INTEREST_RATE

Attribute	Description
Name	INTEREST_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs — 0
Restrictions	**Restrictions** / **Description**: totalDigits — 22; maxInclusive — 100

UDFDETAILS

Attribute	Description

Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	150
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.6.4.CF-CreateCFDFLTRI-Res-PK-MSG.xsd

CREATECFDFLTRI_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-PK

RATE_CODE

BRANCH_CODE

Rate-Code-IO

RATE_CODE

DESC

BRANCH_CODE

Rate-Ccy

CCY_CODE

Fload-Rate

AMOUNT_SLAB1

EFFECTIVE_DATE

BORROW_LEND_IND

Fltrate-Detail

TENOR_TO1

INTEREST_RATE

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATECFDFLTRI_IOPK_RES

Attribute	Description
Name	CREATECFDFLTRI_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	
	Restrictions / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description**: minOccurs / 0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-PK

Attribute	Description
Name	Rate-Code-PK
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

Rate-Code-IO

Attribute	Description
Name	Rate-Code-IO
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

Rate-Ccy

Attribute	Description
Name	Rate-Ccy
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

CCY_CODE

Attribute	Description
Name	CCY_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

Fload-Rate

Attribute	Description
Name	Fload-Rate
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

AMOUNT_SLAB1

Attribute	Description
Name	AMOUNT_SLAB1
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 9999999999999999999.99

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>B,L,M</td></tr></table>

Fltrate-Detail

Attribute	Description
Name	Fltrate-Detail
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TENOR_TO1

Attribute	Description
Name	TENOR_TO1
Datatype	Decimal
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>99999</td></tr></table>

INTEREST_RATE

Attribute	Description
Name	INTEREST_RATE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>maxInclusive</td><td>100</td></tr></table>

UDFDETAILS

Attribute	Description

Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions

Restrictions	Description
maxLength	150
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.7.CreateCFFloatRateMaint

2.7.1.CF-CreateCFFloatRateMaint-Req-Full-MSG.xsd

CREATECFFLOATRATEMAINT_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Master-Full

RATECODE

RATECODEDESCRIPTION

TENORCODE

TENORCODEDESCRIPTION

CCYCODE

CCYNAME

EFFECTIVEDATE

RATESOURCE

RATESOURCEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Rate-Detail

RATETYPE

RATETYPEDESCRIPTION

INTERESTRATE

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

CREATECFFLOATRATEMAINT_FSFS_REQ

Attribute	Description
Name	CREATECFFLOATRATEMAINT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String

Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Master-Full

Attribute	Description
Name	Cftm-Rate-Master-Full
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 10

RATECODEDESCRIPTION

Attribute	Description
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates Rate Code Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TENORCODEDESCRIPTION

Attribute	Description
Name	TENORCODEDESCRIPTION
Datatype	String
Description	Indicates Tenor Code Description

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

CCYCODE

Attribute	**Description**
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

CCYNAME

Attribute	**Description**
Name	CCYNAME
Datatype	String
Description	Indicates Currency Code Description
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

EFFECTIVEDATE

Attribute	**Description**
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

RATESOURCE

Attribute	**Description**
Name	RATESOURCE
Datatype	String
Description	Indicates Rate Source
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

RATESOURCEDESCRIPTION

Attribute	Description
Name	RATESOURCEDESCRIPTION
Datatype	String
Description	Indicates Rate Source Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	The User id who has booked the contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has booked the contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	The User id who has authorized the booked contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

ONCEAUTH

Attribute	Description
Name	ONCEAUTH

Datatype	String
Description	Indicates Once Authorized
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Cftm-Rate-Detail

Attribute	Description
Name	Cftm-Rate-Detail
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

INTERESTRATE

Attribute	Description
Name	INTERESTRATE
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.7.2.CF-CreateCFFloatRateMaint-Req-IO-MSG.xsd

CREATECFFLOATRATEMAINT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Master-IO

RATECODE

TENORCODE

CCYCODE

EFFECTIVEDATE

RATESOURCE

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Rate-Detail

RATETYPE

RATETYPEDESCRIPTION

INTERESTRATE

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

CREATECFFLOATRATEMAINT_IOPK_REQ

Attribute	Description
Name	CREATECFFLOATRATEMAINT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Master-IO

Attribute	Description
Name	Cftm-Rate-Master-IO
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TENORCODE

Attribute	Description

Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

CCYCODE

Attribute	**Description**
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description**: maxLength / 3

EFFECTIVEDATE

Attribute	**Description**
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

RATESOURCE

Attribute	**Description**
Name	RATESOURCE
Datatype	String
Description	Indicates Rate Source
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	Indicates Maker Identification
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Stamp
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker Identification
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Stamp
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String

Description	Indicates Authorization Status
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates Whether The Floating Rate Maintenance Record is Authorized Atleast Once.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

Cftm-Rate-Detail

Attribute	**Description**
Name	Cftm-Rate-Detail
Datatype	
Description	
Attribute	**Attribute** / **Description**: maxOccurs / unbounded

RATETYPE

Attribute	**Description**
Name	RATETYPE
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

INTERESTRATE

Attribute	Description
Name	INTERESTRATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.7.3.CF-CreateCFFloatRateMaint-Res-Full-MSG.xsd

CREATECFFLOATRATEMAINT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Master-IO

RATECODE

TENORCODE

CCYCODE

EFFECTIVEDATE

RATESOURCE

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Rate-Detail

RATETYPE

RATETYPEDESCRIPTION

INTERESTRATE

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Cftm-Rate-Master-Full

RATECODE

RATECODEDESCRIPTION

TENORCODE

TENORCODEDESCRIPTION

CCYCODE

CCYNAME

EFFECTIVEDATE

RATESOURCE

RATESOURCEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Rate-Detail

RATETYPE

RATETYPEDESCRIPTION

INTERESTRATE

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATECFFLOATRATEMAINT_FSFS_RES

Attribute	Description
Name	CREATECFFLOATRATEMAINT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Master-IO

Attribute	Description
Name	Cftm-Rate-Master-IO
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 10

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description**: maxLength / 3

EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

RATESOURCE

Attribute	Description
Name	RATESOURCE
Datatype	String
Description	Indicates Rate Source
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker Identification
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Stamp
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

CHECKERID

Attribute	Description
Name	CHECKERID

Datatype	String
Description	Indicates Checker Identification
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Stamp
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

MODNO

Attribute	**Description**
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates Record Status

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates Whether The Floating Rate Maintenance Record is Authorized Atleast Once.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

Cftm-Rate-Detail

Attribute	**Description**
Name	Cftm-Rate-Detail
Datatype	
Description	
Attribute	**Attribute** / **Description** maxOccurs / unbounded

RATETYPE

Attribute	**Description**
Name	RATETYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

RATETYPEDESCRIPTION

Attribute	**Description**
Name	RATETYPEDESCRIPTION
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

INTERESTRATE

Attribute	Description
Name	INTERESTRATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

Cftm-Rate-Master-Full

Attribute	Description
Name	Cftm-Rate-Master-Full
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code

Restrictions	

Restrictions	Description
maxLength	10

RATECODEDESCRIPTION

Attribute	Description
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates Rate Code Description
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Restrictions	

Restrictions	Description
maxLength	12

TENORCODEDESCRIPTION

Attribute	Description
Name	TENORCODEDESCRIPTION
Datatype	String
Description	Indicates Tenor Code Description
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	

Restrictions	Description
maxLength	3

CCYNAME

Attribute	Description

Name	CCYNAME
Datatype	String
Description	Indicates Currency Code Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

EFFECTIVEDATE

Attribute	**Description**
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

RATESOURCE

Attribute	**Description**
Name	RATESOURCE
Datatype	String
Description	Indicates Rate Source
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

RATESOURCEDESCRIPTION

Attribute	**Description**
Name	RATESOURCEDESCRIPTION
Datatype	String
Description	Indicates Rate Source Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	The User id who has booked the contract

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has booked the contract
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	The User id who has authorized the booked contract
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

MODNO

Attribute	**Description**
Name	MODNO
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorized
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Cftm-Rate-Detail

Attribute	Description
Name	Cftm-Rate-Detail
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

INTERESTRATE

Attribute	Description
Name	INTERESTRATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.7.4.CF-CreateCFFloatRateMaint-Res-PK-MSG.xsd

CREATECFFLOATRATEMAINT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Master-PK

RATECODE

TENORCODE

CCYCODE

EFFECTIVEDATE

Cftm-Rate-Master-IO

RATECODE

TENORCODE

CCYCODE

EFFECTIVEDATE

RATESOURCE

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Rate-Detail

RATETYPE

RATETYPEDESCRIPTION

INTERESTRATE

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Cftm-Rate-Master-Full

RATECODE

RATECODEDESCRIPTION

TENORCODE

TENORCODEDESCRIPTION

CCYCODE

CCYNAME

EFFECTIVEDATE

RATESOURCE

RATESOURCEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Rate-Detail

RATETYPE

RATETYPEDESCRIPTION

INTERESTRATE

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATECFFLOATRATEMAINT_IOPK_RES

Attribute	Description
Name	CREATECFFLOATRATEMAINT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Master-PK

Attribute	**Description**

Name	Cftm-Rate-Master-PK
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	String
Description	

Cftm-Rate-Master-IO

Attribute	Description
Name	Cftm-Rate-Master-IO

Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 10

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description**: maxLength / 3

EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

RATESOURCE

Attribute	Description
Name	RATESOURCE
Datatype	String
Description	Indicates Rate Source
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	10

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker Identification
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Stamp
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	25

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker Identification
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Stamp
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	25

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Whether The Floating Rate Maintenance Record is Authorized Atleast Once.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 1

Cftm-Rate-Detail

Attribute	Description
Name	Cftm-Rate-Detail
Datatype	
Description	
Attribute	**Attribute** / **Description**: maxOccurs / unbounded

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

INTERESTRATE

Attribute	Description
Name	INTERESTRATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

UDFDETAILS

Attribute	Description

Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

VAL_TYPE

Attribute	**Description**
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

Cftm-Rate-Master-Full

Attribute	**Description**
Name	Cftm-Rate-Master-Full
Datatype	
Description	

RATECODE

Attribute	**Description**
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 10

RATECODEDESCRIPTION

Attribute	**Description**
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates Rate Code Description
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TENORCODEDESCRIPTION

Attribute	Description
Name	TENORCODEDESCRIPTION
Datatype	String
Description	Indicates Tenor Code Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description**: maxLength / 3

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency Code Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

RATESOURCE

Attribute	Description
Name	RATESOURCE
Datatype	String
Description	Indicates Rate Source
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

RATESOURCEDESCRIPTION

Attribute	Description
Name	RATESOURCEDESCRIPTION
Datatype	String
Description	Indicates Rate Source Description
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	The User id who has booked the contract
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has booked the contract
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	The User id who has authorized the booked contract
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

RECSTAT

Attribute	Description
Name	RECSTAT

Datatype	String
Description	Indicates Record Status
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorized
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

Cftm-Rate-Detail

Attribute	**Description**
Name	Cftm-Rate-Detail
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

RATETYPE

Attribute	**Description**
Name	RATETYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

RATETYPEDESCRIPTION

Attribute	**Description**
Name	RATETYPEDESCRIPTION
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 105

INTERESTRATE

Attribute	**Description**
Name	INTERESTRATE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.8.CreateCFRateCodeMaint

2.8.1.CF-CreateCFRateCodeMaint-Req-Full-MSG.xsd

- *CREATECFRATECODEMAINT_FSFS_REQ*
  - *FCUBS_HEADER*
    - *SOURCE*
    - *UBSCOMP*
    - *MSGID*
    - *CORRELID*
    - *USERID*
    - *BRANCH*
    - *MODULEID*
    - *SERVICE*
    - *OPERATION*
    - *SOURCE_OPERATION*
    - *SOURCE_USERID*
    - *DESTINATION*
    - *MULTITRIPID*
    - *FUNCTIONID*
    - *ACTION*
    - *MSGSTAT*
    - *PASSWORD*
    - *ADDL*
      - *PARAM*
        - *NAME*
        - *VALUE*
  - *FCUBS_BODY*
    - *Cftm-Rate-Code-Defn-Full*
      - *RATECODE*
      - *RATECODEDESCRIPTION*
      - *HOLIDAYCCY*
      - *PROPAGATIONACROSSBRANCHES*
      - *MAKERID*

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Tenor-Code-Defn

TENORCODE

TENORCODEDESCRIPTION

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

CREATECFRATECODEMAINT_FSFS_REQ

Attribute	Description
Name	CREATECFRATECODEMAINT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID

Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String

Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Code-Defn-Full

Attribute	Description
Name	Cftm-Rate-Code-Defn-Full
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

RATECODEDESCRIPTION

Attribute	Description
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates the description of rate code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

HOLIDAYCCY

Attribute	Description
Name	HOLIDAYCCY
Datatype	String
Description	Indicates Holiday Currency
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

PROPAGATIONACROSSBRANCHES

Attribute	Description
Name	PROPAGATIONACROSSBRANCHES
Datatype	String
Description	Propagate Across Branches
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User id who has saved the record.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the date and time when the user has saved the record.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User id who has authorized the record.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	It indicates the status of the record,whether open or Closed.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

ONCEAUTH

Attribute	Description
Name	ONCEAUTH

Datatype	String
Description	Indicates Once Authorized
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Cftm-Tenor-Code-Defn

Attribute	Description
Name	Cftm-Tenor-Code-Defn
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TENORCODEDESCRIPTION

Attribute	Description
Name	TENORCODEDESCRIPTION
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.8.2.CF-CreateCFRateCodeMaint-Req-IO-MSG.xsd

CREATECFRATECODEMAINT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Code-Defn-IO

RATECODE

RATECODEDESCRIPTION

HOLIDAYCCY

PROPAGATIONACROSSBRANCHES

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Tenor-Code-Defn

TENORCODE

TENORCODEDESCRIPTION

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

CREATECFRATECODEMAINT_IOPK_REQ

Attribute	Description
Name	CREATECFRATECODEMAINT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Code-Defn-IO

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

RATECODEDESCRIPTION

Attribute	Description
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates the description of rate code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

HOLIDAYCCY

Attribute	Description

Name	HOLIDAYCCY
Datatype	String
Description	Indicates Holiday Currency
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

PROPAGATIONACROSSBRANCHES

Attribute	**Description**
Name	PROPAGATIONACROSSBRANCHES
Datatype	String
Description	Propagate Across Branches
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	Specifies the User id who has saved the record.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the date and time when the user has saved the record.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

CHECKERID

Attribute	**Description**

Name	CHECKERID
Datatype	String
Description	Indicates the User id who has authorized the record.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

MODNO

Attribute	**Description**
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	It indicates the status of the record,whether open or Closed.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorized
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

Cftm-Tenor-Code-Defn

Attribute	**Description**
Name	Cftm-Tenor-Code-Defn
Datatype	
Description	
Attribute	**Attribute** / **Description** maxOccurs / unbounded

TENORCODE

Attribute	**Description**
Name	TENORCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TENORCODEDESCRIPTION

Attribute	**Description**
Name	TENORCODEDESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	105

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.8.3.CF-CreateCFRateCodeMaint-Res-Full-MSG.xsd

CREATECFRATECODEMAINT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Code-Defn-IO

RATECODE

RATECODEDESCRIPTION

HOLIDAYCCY

PROPAGATIONACROSSBRANCHES

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Tenor-Code-Defn

TENORCODE

TENORCODEDESCRIPTION

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Cftm-Rate-Code-Defn-Full

RATECODE

RATECODEDESCRIPTION

HOLIDAYCCY

PROPAGATIONACROSSBRANCHES

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Tenor-Code-Defn

TENORCODE

TENORCODEDESCRIPTION

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATECFRATECODEMAINT_FSFS_RES

Attribute	Description
Name	CREATECFRATECODEMAINT_FSFS_RES

Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	
	Attribute / **Description**: minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Code-Defn-IO

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

RATECODEDESCRIPTION

Attribute	Description
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates the description of rate code

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

HOLIDAYCCY

Attribute	**Description**
Name	HOLIDAYCCY
Datatype	String
Description	Indicates Holiday Currency
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

PROPAGATIONACROSSBRANCHES

Attribute	**Description**
Name	PROPAGATIONACROSSBRANCHES
Datatype	String
Description	Propagate Across Branches
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	Specifies the User id who has saved the record.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the date and time when the user has saved the record.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User id who has authorized the record.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	It indicates the status of the record,whether open or Closed.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorized
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

Cftm-Tenor-Code-Defn

Attribute	**Description**
Name	Cftm-Tenor-Code-Defn
Datatype	
Description	
Attribute	**Attribute** / **Description** maxOccurs / unbounded

TENORCODE

Attribute	**Description**
Name	TENORCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	10

TENORCODEDESCRIPTION

Attribute	Description
Name	TENORCODEDESCRIPTION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

Cftm-Rate-Code-Defn-Full

Attribute	Description
Name	Cftm-Rate-Code-Defn-Full
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

RATECODEDESCRIPTION

Attribute	**Description**
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates the description of rate code
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

HOLIDAYCCY

Attribute	**Description**
Name	HOLIDAYCCY
Datatype	String
Description	Indicates Holiday Currency
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

PROPAGATIONACROSSBRANCHES

Attribute	**Description**
Name	PROPAGATIONACROSSBRANCHES
Datatype	String
Description	Propagate Across Branches
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	Specifies the User id who has saved the record.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the date and time when the user has saved the record.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	Indicates the User id who has authorized the record.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

MODNO

Attribute	**Description**
Name	MODNO
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	It indicates the status of the record,whether open or Closed.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorized
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Cftm-Tenor-Code-Defn

Attribute	Description
Name	Cftm-Tenor-Code-Defn
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	10

TENORCODEDESCRIPTION

Attribute	Description
Name	TENORCODEDESCRIPTION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.8.4.CF-CreateCFRateCodeMaint-Res-PK-MSG.xsd

CREATECFRATECODEMAINT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Code-Defn-PK

RATECODE

Cftm-Rate-Code-Defn-IO

RATECODE

RATECODEDESCRIPTION

HOLIDAYCCY

PROPAGATIONACROSSBRANCHES

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Tenor-Code-Defn

TENORCODE

TENORCODEDESCRIPTION

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Cftm-Rate-Code-Defn-Full

RATECODE

RATECODEDESCRIPTION

HOLIDAYCCY

PROPAGATIONACROSSBRANCHES

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Tenor-Code-Defn

TENORCODE

TENORCODEDESCRIPTION

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATECFRATECODEMAINT_IOPK_RES

Attribute	Description
Name	CREATECFRATECODEMAINT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Code-Defn-PK

Attribute	Description
Name	Cftm-Rate-Code-Defn-PK
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

Cftm-Rate-Code-Defn-IO

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	10

RATECODEDESCRIPTION

Attribute	Description
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates the description of rate code
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

HOLIDAYCCY

Attribute	Description
Name	HOLIDAYCCY
Datatype	String
Description	Indicates Holiday Currency
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

PROPAGATIONACROSSBRANCHES

Attribute	Description
Name	PROPAGATIONACROSSBRANCHES
Datatype	String
Description	Propagate Across Branches
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User id who has saved the record.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the date and time when the user has saved the record.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	25

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User id who has authorized the record.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	25

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	It indicates the status of the record,whether open or Closed.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorized
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

Cftm-Tenor-Code-Defn

Attribute	Description
Name	Cftm-Tenor-Code-Defn
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TENORCODEDESCRIPTION

Attribute	Description
Name	TENORCODEDESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	**Restrictions** / **Description**: maxLength 105; minLength 1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 255; minLength 0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 2; minLength 0

Cftm-Rate-Code-Defn-Full

Attribute	Description

Name	Cftm-Rate-Code-Defn-Full
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

RATECODEDESCRIPTION

Attribute	Description
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates the description of rate code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

HOLIDAYCCY

Attribute	Description
Name	HOLIDAYCCY
Datatype	String
Description	Indicates Holiday Currency
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

PROPAGATIONACROSSBRANCHES

Attribute	Description
Name	PROPAGATIONACROSSBRANCHES
Datatype	String
Description	Propagate Across Branches
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	Specifies the User id who has saved the record.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the date and time when the user has saved the record.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	Indicates the User id who has authorized the record.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

MODNO

Attribute	**Description**
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	It indicates the status of the record,whether open or Closed.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorized
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	1

Cftm-Tenor-Code-Defn

Attribute	Description
Name	Cftm-Tenor-Code-Defn
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	10

TENORCODEDESCRIPTION

Attribute	Description
Name	TENORCODEDESCRIPTION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.9.CreateCFRateTypeDefn

2.9.1.CF-CreateCFRateTypeDefn-Req-Full-MSG.xsd

CREATECFRATETYPEDEFN_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Type-Defn-Full

RATETYPE

RATETYPEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

CREATECFRATETYPEDEFN_FSFS_REQ

Attribute	Description
Name	CREATECFRATETYPEDEFN_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Type-Defn-Full

Attribute	Description
Name	Cftm-Rate-Type-Defn-Full
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	Indicates Rate Type Description
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

MAKERID

Attribute	Description

Name	MAKERID
Datatype	String
Description	The User Id who has created\last modified the Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user hascreated\last modified the Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	The User Id who has Authorized the creation\modification of Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user has Authorized the creation\ modification of Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A - Authorized U - Un Authorized
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status O - Open C - Close
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Rate Type Definition detail has been Authorized atleast Once.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

UDFDETAILS

Attribute	Description

Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.9.2.CF-CreateCFRateTypeDefn-Req-IO-MSG.xsd

CREATECFRATETYPEDEFN_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Type-Defn-IO

RATETYPE

RATETYPEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

CREATECFRATETYPEDEFN_IOPK_REQ

Attribute	Description
Name	CREATECFRATETYPEDEFN_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Type-Defn-IO

Attribute	Description
Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	Indicates Rate Type Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

MAKERID

Attribute	Description

Name	MAKERID
Datatype	String
Description	The User Id who has created\last modified the Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user hascreated\last modified the Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	The User Id who has Authorized the creation\modification of Rate Type Definiton details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user has Authorized the creation\modification of Rate Type Defintion details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A - Authorized U - Un Authorized
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status O - Open C - Close
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether the Rate Type Definition detail has been Authorized atleast Once.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

UDFDETAILS

Attribute	Description

Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions

Restrictions	Description
maxLength	8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.9.3.CF-CreateCFRateTypeDefn-Res-Full-MSG.xsd

CREATECFRATETYPEDEFN_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Type-Defn-IO

RATETYPE

RATETYPEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Cftm-Rate-Type-Defn-Full

RATETYPE

RATETYPEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATECFRATETYPEDEFN_FSFS_RES

Attribute	Description
Name	CREATECFRATETYPEDEFN_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String

Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Type-Defn-IO

Attribute	Description
Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	Indicates Rate Type Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	The User Id who has created\last modified the Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: maxLength / 12

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user hascreated\last modified the Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	The User Id who has Authorized the creation\modification of Rate Type Definiton details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user has Authorized the creation\modification of Rate Type Defintion details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A - Authorized U - Un Authorized
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status O - Open C - Close
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether the Rate Type Definition detail has been Authorized atleast Once.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

Cftm-Rate-Type-Defn-Full

Attribute	Description
Name	Cftm-Rate-Type-Defn-Full
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	Indicates Rate Type Description
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	The User Id who has created\last modified the Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user hascreated\last modified the Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	The User Id who has Authorized the creation\modification of Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user has Authorized the creation\ modification of Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	25

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A - Authorized U - Un Authorized
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status O - Open C - Close
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Rate Type Definition detail has been Authorized atleast Once.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	**Attribute** / **Description**: maxOccurs / unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String

Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.9.4.CF-CreateCFRateTypeDefn-Res-PK-MSG.xsd

CREATECFRATETYPEDEFN_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Type-Defn-PK

RATETYPE

Cftm-Rate-Type-Defn-IO

RATETYPE

RATETYPEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Cftm-Rate-Type-Defn-Full

RATETYPE

RATETYPEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATECFRATETYPEDEFN_IOPK_RES

Attribute	Description
Name	CREATECFRATETYPEDEFN_IOPK_RES

Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	
	Attribute / **Description**: minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Type-Defn-PK

Attribute	Description
Name	Cftm-Rate-Type-Defn-PK
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

Cftm-Rate-Type-Defn-IO

Attribute	Description
Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	Indicates Rate Type Description
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	The User Id who has created\last modified the Rate Type Definition details.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user hascreated\last modified the Rate Type Definition details.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 25

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	The User Id who has Authorized the creation\modification of Rate Type Definiton details.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user has Authorized the creation\modification of Rate Type Defintion details.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A - Authorized U - Un Authorized
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	1

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status O - Open C - Close
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether the Rate Type Definition detail has been Authorized atleast Once.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

Cftm-Rate-Type-Defn-Full

Attribute	Description
Name	Cftm-Rate-Type-Defn-Full
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	Indicates Rate Type Description
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	The User Id who has created\last modified the Rate Type Definition details.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user hascreated\last modified the Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	The User Id who has Authorized the creation\modification of Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user has Authorized the creation\ modification of Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AUTHSTAT

Attribute	Description

Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A - Authorized U - Un Authorized
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates Record Status O - Open C - Close
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Rate Type Definition detail has been Authorized atleast Once.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String

Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

DATATYPE

Attribute	**Description**
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

FIELD_VALUE

Attribute	**Description**
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

VAL_TYPE

Attribute	**Description**
Name	VAL_TYPE
Datatype	String

Description	Indicates Value Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.10.DeleteCFDFLTRI

2.10.1.CF-DeleteCFDFLTRI-Req-Full-MSG.xsd

DELETECFDFLTRI_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-Full

RATE_CODE

DESC

BRANCH_CODE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Rate-Ccy

CCY_CODE

Fload-Rate

AMOUNT_SLAB1

EFFECTIVE_DATE

BORROW_LEND_IND

Fltrate-Detail

TENOR_TO1

INTEREST_RATE

UDFDETAILS

FLDNAM

FLDVAL

DELETECFDFLTRI_FSFS_REQ

Attribute	Description
Name	DELETECFDFLTRI_FSFS_REQ

Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-Full

Attribute	Description
Name	Rate-Code-Full
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	105

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

Rate-Ccy

Attribute	Description
Name	Rate-Ccy
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

CCY_CODE

Attribute	Description
Name	CCY_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

Fload-Rate

Attribute	Description
Name	Fload-Rate
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

AMOUNT_SLAB1

Attribute	Description
Name	AMOUNT_SLAB1
Datatype	Decimal
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>9999999999999999999.99</td></tr></table>

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	

Restrictions	

Restrictions	Description
enumeration	B,L,M

Fltrate-Detail

Attribute	Description
Name	Fltrate-Detail
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

TENOR_TO1

Attribute	Description
Name	TENOR_TO1
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	5
minInclusive	0
maxInclusive	99999

INTEREST_RATE

Attribute	Description
Name	INTEREST_RATE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
maxInclusive	100

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAM

Attribute	Description

Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.10.2.CF-DeleteCFDFLTRI-Req-IO-MSG.xsd

DELETECFDFLTRI_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-IO

RATE_CODE

BRANCH_CODE

DELETECFDFLTRI_IOPK_REQ

Attribute	Description
Name	DELETECFDFLTRI_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String

Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-IO

Attribute	Description
Name	Rate-Code-IO
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

2.10.3.CF-DeleteCFDFLTRI-Res-Full-MSG.xsd

DELETECFDFLTRI_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-Full

RATE_CODE

DESC

BRANCH_CODE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Rate-Ccy

CCY_CODE

Fload-Rate

AMOUNT_SLAB1

EFFECTIVE_DATE

BORROW_LEND_IND

Fltrate-Detail

TENOR_TO1

INTEREST_RATE

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETECFDFLTRI_FSFS_RES

Attribute	Description
Name	DELETECFDFLTRI_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-Full

Attribute	Description
Name	Rate-Code-Full
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Rate-Ccy

Attribute	Description
Name	Rate-Ccy
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

CCY_CODE

Attribute	Description
Name	CCY_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

Fload-Rate

Attribute	Description
Name	Fload-Rate
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

AMOUNT_SLAB1

Attribute	Description
Name	AMOUNT_SLAB1
Datatype	Decimal
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>9999999999999999999.99</td></tr></table>

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>B,L,M</td></tr></table>

Fltrate-Detail

Attribute	Description
Name	Fltrate-Detail
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TENOR_TO1

Attribute	Description
Name	TENOR_TO1
Datatype	Decimal
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>99999</td></tr></table>

INTEREST_RATE

Attribute	Description
Name	INTEREST_RATE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>maxInclusive</td><td>100</td></tr></table>

UDFDETAILS

Attribute	Description

Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	150
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.10.4.CF-DeleteCFDFLTRI-Res-PK-MSG.xsd

DELETECFDFLTRI_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-PK

RATE_CODE

BRANCH_CODE

Rate-Code-IO

RATE_CODE

BRANCH_CODE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETECFDFLTRI_IOPK_RES

Attribute	Description
Name	DELETECFDFLTRI_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-PK

Attribute	Description
Name	Rate-Code-PK
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

BRANCH_CODE

Attribute	Description

Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

Rate-Code-IO

Attribute	**Description**
Name	Rate-Code-IO
Datatype	
Description	

RATE_CODE

Attribute	**Description**
Name	RATE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 10

BRANCH_CODE

Attribute	**Description**
Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attribute	**Attribute** / **Description**: maxOccurs / unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.11.DeleteCFFloatRateMaint

2.11.1.CF-DeleteCFFloatRateMaint-Req-Full-MSG.xsd

DELETECFFLOATRATEMAINT_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Master-Full

RATECODE

RATECODEDESCRIPTION

TENORCODE

TENORCODEDESCRIPTION

CCYCODE

CCYNAME

EFFECTIVEDATE

RATESOURCE

RATESOURCEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Rate-Detail

RATETYPE

RATETYPEDESCRIPTION

INTERESTRATE

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

DELETECFFLOATRATEMAINT_FSFS_REQ

Attribute	Description
Name	DELETECFFLOATRATEMAINT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String

Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Master-Full

Attribute	Description
Name	Cftm-Rate-Master-Full
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 10

RATECODEDESCRIPTION

Attribute	Description
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates Rate Code Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TENORCODEDESCRIPTION

Attribute	Description
Name	TENORCODEDESCRIPTION
Datatype	String
Description	Indicates Tenor Code Description

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

CCYCODE

Attribute	**Description**
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

CCYNAME

Attribute	**Description**
Name	CCYNAME
Datatype	String
Description	Indicates Currency Code Description
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

EFFECTIVEDATE

Attribute	**Description**
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

RATESOURCE

Attribute	**Description**
Name	RATESOURCE
Datatype	String
Description	Indicates Rate Source
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

RATESOURCEDESCRIPTION

Attribute	Description
Name	RATESOURCEDESCRIPTION
Datatype	String
Description	Indicates Rate Source Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	The User id who has booked the contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has booked the contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	The User id who has authorized the booked contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

ONCEAUTH

Attribute	Description
Name	ONCEAUTH

Datatype	String
Description	Indicates Once Authorized
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Cftm-Rate-Detail

Attribute	Description
Name	Cftm-Rate-Detail
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

INTERESTRATE

Attribute	Description
Name	INTERESTRATE
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.11.2.CF-DeleteCFFloatRateMaint-Req-IO-MSG.xsd

DELETECFFLOATRATEMAINT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Master-IO

RATECODE

TENORCODE

CCYCODE

EFFECTIVEDATE

DELETECFFLOATRATEMAINT_IOPK_REQ

Attribute	Description
Name	DELETECFFLOATRATEMAINT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Master-IO

Attribute	Description
Name	Cftm-Rate-Master-IO
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	String
Description	

2.11.3.CF-DeleteCFFloatRateMaint-Res-Full-MSG.xsd

DELETECFFLOATRATEMAINT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Master-IO

RATECODE

TENORCODE

CCYCODE

EFFECTIVEDATE

Cftm-Rate-Master-Full

RATECODE

RATECODEDESCRIPTION

TENORCODE

TENORCODEDESCRIPTION

CCYCODE

CCYNAME

EFFECTIVEDATE

RATESOURCE

RATESOURCEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Rate-Detail

RATETYPE

RATETYPEDESCRIPTION

INTERESTRATE

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETECFFLOATRATEMAINT_FSFS_RES

Attribute	Description
Name	DELETECFFLOATRATEMAINT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Master-IO

Attribute	Description
Name	Cftm-Rate-Master-IO
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description**: maxLength / 10

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	String
Description	

Cftm-Rate-Master-Full

Attribute	Description
Name	Cftm-Rate-Master-Full
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 10

RATECODEDESCRIPTION

Attribute	Description
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates Rate Code Description
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TENORCODEDESCRIPTION

Attribute	Description
Name	TENORCODEDESCRIPTION
Datatype	String
Description	Indicates Tenor Code Description
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency Code Description

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

RATESOURCE

Attribute	Description
Name	RATESOURCE
Datatype	String
Description	Indicates Rate Source
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

RATESOURCEDESCRIPTION

Attribute	Description
Name	RATESOURCEDESCRIPTION
Datatype	String
Description	Indicates Rate Source Description
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	The User id who has booked the contract
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	
	Restrictions / **Description**: maxLength / 12

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has booked the contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	The User id who has authorized the booked contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorized
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

Cftm-Rate-Detail

Attribute	Description
Name	Cftm-Rate-Detail
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

INTERESTRATE

Attribute	Description
Name	INTERESTRATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.11.4.CF-DeleteCFFloatRateMaint-Res-PK-MSG.xsd

DELETECFFLOATRATEMAINT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Master-IO

RATECODE

TENORCODE

CCYCODE

EFFECTIVEDATE

Cftm-Rate-Master-PK

RATECODE

TENORCODE

CCYCODE

EFFECTIVEDATE

Cftm-Rate-Master-Full

RATECODE

RATECODEDESCRIPTION

TENORCODE

TENORCODEDESCRIPTION

CCYCODE

CCYNAME

EFFECTIVEDATE

RATESOURCE

RATESOURCEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Rate-Detail

RATETYPE

RATETYPEDESCRIPTION

INTERESTRATE

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETECFFLOATRATEMAINT_IOPK_RES

Attribute	Description
Name	DELETECFFLOATRATEMAINT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Master-IO

Attribute	Description
Name	Cftm-Rate-Master-IO
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CCYCODE

Attribute	Description

Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

EFFECTIVEDATE

Attribute	**Description**
Name	EFFECTIVEDATE
Datatype	String
Description	

Cftm-Rate-Master-PK

Attribute	**Description**
Name	Cftm-Rate-Master-PK
Datatype	
Description	

RATECODE

Attribute	**Description**
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TENORCODE

Attribute	**Description**
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CCYCODE

Attribute	**Description**
Name	CCYCODE

Datatype	String
Description	Indicates Currency Code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	String
Description	

Cftm-Rate-Master-Full

Attribute	Description
Name	Cftm-Rate-Master-Full
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

RATECODEDESCRIPTION

Attribute	Description
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates Rate Code Description
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code

Restrictions	
	Restrictions / **Description**: maxLength / 12

TENORCODEDESCRIPTION

Attribute	Description
Name	TENORCODEDESCRIPTION
Datatype	String
Description	Indicates Tenor Code Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description**: maxLength / 3

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency Code Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

RATESOURCE

Attribute	Description

Name	RATESOURCE
Datatype	String
Description	Indicates Rate Source
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

RATESOURCEDESCRIPTION

Attribute	**Description**
Name	RATESOURCEDESCRIPTION
Datatype	String
Description	Indicates Rate Source Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	The User id who has booked the contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has booked the contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

CHECKERID

Attribute	**Description**

Name	CHECKERID
Datatype	String
Description	The User id who has authorized the booked contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

MODNO

Attribute	**Description**
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates Record Status

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorized
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Cftm-Rate-Detail

Attribute	Description
Name	Cftm-Rate-Detail
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

INTERESTRATE

Attribute	**Description**
Name	INTERESTRATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.12.DeleteCFRateCodeMaint

2.12.1.CF-DeleteCFRateCodeMaint-Req-Full-MSG.xsd

- *DELETECFRATECODEMAINT_FSFS_REQ*
  - *FCUBS_HEADER*
    - *SOURCE*
    - *UBSCOMP*
    - *MSGID*
    - *CORRELID*
    - *USERID*
    - *BRANCH*
    - *MODULEID*
    - *SERVICE*
    - *OPERATION*
    - *SOURCE_OPERATION*
    - *SOURCE_USERID*
    - *DESTINATION*
    - *MULTITRIPID*
    - *FUNCTIONID*
    - *ACTION*
    - *MSGSTAT*
    - *PASSWORD*
    - *ADDL*
      - *PARAM*
        - *NAME*
        - *VALUE*
  - *FCUBS_BODY*
    - *Cftm-Rate-Code-Defn-Full*
      - *RATECODE*
      - *RATECODEDESCRIPTION*
      - *HOLIDAYCCY*
      - *PROPAGATIONACROSSBRANCHES*
      - *MAKERID*

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Tenor-Code-Defn

TENORCODE

TENORCODEDESCRIPTION

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

DELETECFRATECODEMAINT_FSFS_REQ

Attribute	Description
Name	DELETECFRATECODEMAINT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String

Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Code-Defn-Full

Attribute	Description
Name	Cftm-Rate-Code-Defn-Full
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

RATECODEDESCRIPTION

Attribute	Description
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates the description of rate code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

HOLIDAYCCY

Attribute	Description
Name	HOLIDAYCCY
Datatype	String
Description	Indicates Holiday Currency
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

PROPAGATIONACROSSBRANCHES

Attribute	Description
Name	PROPAGATIONACROSSBRANCHES
Datatype	String
Description	Propagate Across Branches
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User id who has saved the record.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the date and time when the user has saved the record.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User id who has authorized the record.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	It indicates the status of the record,whether open or Closed.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

ONCEAUTH

Attribute	Description
Name	ONCEAUTH

Datatype	String
Description	Indicates Once Authorized
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Cftm-Tenor-Code-Defn

Attribute	Description
Name	Cftm-Tenor-Code-Defn
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TENORCODEDESCRIPTION

Attribute	Description
Name	TENORCODEDESCRIPTION
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.12.2.CF-DeleteCFRateCodeMaint-Req-IO-MSG.xsd

DELETECFRATECODEMAINT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Code-Defn-IO

RATECODE

DELETECFRATECODEMAINT_IOPK_REQ

Attribute	Description
Name	DELETECFRATECODEMAINT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.

Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Code-Defn-IO

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	

RATECODE

Attribute	Description

Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

2.12.3.CF-DeleteCFRateCodeMaint-Res-Full-MSG.xsd

DELETECFRATECODEMAINT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Code-Defn-IO

RATECODE

Cftm-Rate-Code-Defn-Full

RATECODE

RATECODEDESCRIPTION

HOLIDAYCCY

PROPAGATIONACROSSBRANCHES

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Tenor-Code-Defn

TENORCODE

TENORCODEDESCRIPTION

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

Attribute	Description
Name	DELETECFRATECODEMAINT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Code-Defn-IO

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

Cftm-Rate-Code-Defn-Full

Attribute	Description
Name	Cftm-Rate-Code-Defn-Full
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

RATECODEDESCRIPTION

Attribute	Description
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates the description of rate code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

HOLIDAYCCY

Attribute	Description
Name	HOLIDAYCCY
Datatype	String
Description	Indicates Holiday Currency
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

PROPAGATIONACROSSBRANCHES

Attribute	Description
Name	PROPAGATIONACROSSBRANCHES
Datatype	String
Description	Propagate Across Branches
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User id who has saved the record.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the date and time when the user has saved the record.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User id who has authorized the record.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	It indicates the status of the record,whether open or Closed.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorized
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Cftm-Tenor-Code-Defn

Attribute	Description
Name	Cftm-Tenor-Code-Defn
Datatype	

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TENORCODEDESCRIPTION

Attribute	Description
Name	TENORCODEDESCRIPTION
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.12.4.CF-DeleteCFRateCodeMaint-Res-PK-MSG.xsd

DELETECFRATECODEMAINT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Code-Defn-IO

RATECODE

Cftm-Rate-Code-Defn-PK

RATECODE

Cftm-Rate-Code-Defn-Full

RATECODE

RATECODEDESCRIPTION

HOLIDAYCCY

PROPAGATIONACROSSBRANCHES

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Tenor-Code-Defn

TENORCODE

TENORCODEDESCRIPTION

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETECFRATECODEMAINT_IOPK_RES

Attribute	Description
Name	DELETECFRATECODEMAINT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.

Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Code-Defn-IO

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	

RATECODE

Attribute	Description

Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

Cftm-Rate-Code-Defn-PK

Attribute	**Description**
Name	Cftm-Rate-Code-Defn-PK
Datatype	
Description	

RATECODE

Attribute	**Description**
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

Cftm-Rate-Code-Defn-Full

Attribute	**Description**
Name	Cftm-Rate-Code-Defn-Full
Datatype	
Description	

RATECODE

Attribute	**Description**
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

RATECODEDESCRIPTION

Attribute	**Description**
Name	RATECODEDESCRIPTION

Datatype	String
Description	Indicates the description of rate code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

HOLIDAYCCY

Attribute	**Description**
Name	HOLIDAYCCY
Datatype	String
Description	Indicates Holiday Currency
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

PROPAGATIONACROSSBRANCHES

Attribute	**Description**
Name	PROPAGATIONACROSSBRANCHES
Datatype	String
Description	Propagate Across Branches
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	Specifies the User id who has saved the record.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP

Datatype	String
Description	Indicates the date and time when the user has saved the record.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User id who has authorized the record.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 1

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	It indicates the status of the record,whether open or Closed.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorized
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

Cftm-Tenor-Code-Defn

Attribute	**Description**
Name	Cftm-Tenor-Code-Defn
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

TENORCODE

Attribute	**Description**
Name	TENORCODE
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TENORCODEDESCRIPTION

Attribute	**Description**
Name	TENORCODEDESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name

Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.13.DeleteCFRateTypeDefn

2.13.1.CF-DeleteCFRateTypeDefn-Req-Full-MSG.xsd

DELETECFRATETYPEDEFN_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Type-Defn-Full

RATETYPE

RATETYPEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

DELETECFRATETYPEDEFN_FSFS_REQ

Attribute	Description
Name	DELETECFRATETYPEDEFN_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Type-Defn-Full

Attribute	Description
Name	Cftm-Rate-Type-Defn-Full
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	Indicates Rate Type Description
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	The User Id who has created\last modified the Rate Type Definition details.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user hascreated\last modified the Rate Type Definition details.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	The User Id who has Authorized the creation\modification of Rate Type Definition details.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user has Authorized the creation\ modification of Rate Type Definition details.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

MODNO

Attribute	**Description**
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A - Authorized U - Un Authorized

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status O - Open C - Close
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Rate Type Definition detail has been Authorized atleast Once.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

2.13.2.CF-DeleteCFRateTypeDefn-Req-IO-MSG.xsd

DELETECFRATETYPEDEFN_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Type-Defn-IO

RATETYPE

DELETECFRATETYPEDEFN_IOPK_REQ

Attribute	Description
Name	DELETECFRATETYPEDEFN_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Type-Defn-IO

Attribute	Description
Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	12

2.13.3.CF-DeleteCFRateTypeDefn-Res-Full-MSG.xsd

DELETECFRATETYPEDEFN_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Type-Defn-IO

RATETYPE

Cftm-Rate-Type-Defn-Full

RATETYPE

RATETYPEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETECFRATETYPEDEFN_FSFS_RES

Attribute	Description
Name	DELETECFRATETYPEDEFN_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Type-Defn-IO

Attribute	Description
Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

Cftm-Rate-Type-Defn-Full

Attribute	Description
Name	Cftm-Rate-Type-Defn-Full
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 12

RATETYPEDESCRIPTION

Attribute	**Description**
Name	RATETYPEDESCRIPTION
Datatype	String
Description	Indicates Rate Type Description
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	The User Id who has created\last modified the Rate Type Definition details.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user hascreated\last modified the Rate Type Definition details.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	The User Id who has Authorized the creation\modification of Rate Type Definition details.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user has Authorized the creation\ modification of Rate Type Definition details.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

MODNO

Attribute	**Description**
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A - Authorized U - Un Authorized
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates Record Status O - Open C - Close

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Rate Type Definition detail has been Authorized atleast Once.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name

Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.13.4.CF-DeleteCFRateTypeDefn-Res-PK-MSG.xsd

DELETECFRATETYPEDEFN_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Type-Defn-IO

RATETYPE

Cftm-Rate-Type-Defn-PK

RATETYPE

Cftm-Rate-Type-Defn-Full

RATETYPE

RATETYPEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETECFRATETYPEDEFN_IOPK_RES

Attribute	Description
Name	DELETECFRATETYPEDEFN_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Type-Defn-IO

Attribute	Description
Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

Cftm-Rate-Type-Defn-PK

Attribute	Description
Name	Cftm-Rate-Type-Defn-PK
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	12

Cftm-Rate-Type-Defn-Full

Attribute	Description
Name	Cftm-Rate-Type-Defn-Full
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	Indicates Rate Type Description
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	The User Id who has created\last modified the Rate Type Definition details.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

MAKERDTSTAMP

Attribute	Description

Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user hascreated\last modified the Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	The User Id who has Authorized the creation\modification of Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user has Authorized the creation\ modification of Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

MODNO

Attribute	**Description**
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT

Datatype	String
Description	Indicates Authorization Status A - Authorized U - Un Authorized
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates Record Status O - Open C - Close
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Rate Type Definition detail has been Authorized atleast Once.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.14.ModifyCFDFLTRI

2.14.1.CF-ModifyCFDFLTRI-Req-Full-MSG.xsd

MODIFYCFDFLTRI_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-Full

RATE_CODE

DESC

BRANCH_CODE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Rate-Ccy

CCY_CODE

Fload-Rate

AMOUNT_SLAB1

EFFECTIVE_DATE

BORROW_LEND_IND

Fltrate-Detail

TENOR_TO1

INTEREST_RATE

UDFDETAILS

FLDNAM

FLDVAL

MODIFYCFDFLTRI_FSFS_REQ

Attribute	Description
Name	MODIFYCFDFLTRI_FSFS_REQ

Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-Full

Attribute	Description
Name	Rate-Code-Full
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	105

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

Rate-Ccy

Attribute	Description
Name	Rate-Ccy
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

CCY_CODE

Attribute	Description
Name	CCY_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

Fload-Rate

Attribute	Description
Name	Fload-Rate
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

AMOUNT_SLAB1

Attribute	Description
Name	AMOUNT_SLAB1
Datatype	Decimal
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>9999999999999999999.99</td></tr></table>

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	

Restrictions	

Restrictions	Description
enumeration	B,L,M

Fltrate-Detail

Attribute	Description
Name	Fltrate-Detail
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

TENOR_TO1

Attribute	Description
Name	TENOR_TO1
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	5
minInclusive	0
maxInclusive	99999

INTEREST_RATE

Attribute	Description
Name	INTEREST_RATE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
maxInclusive	100

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAM

Attribute	Description

Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.14.2.CF-ModifyCFDFLTRI-Req-IO-MSG.xsd

MODIFYCFDFLTRI_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-IO

RATE_CODE

DESC

BRANCH_CODE

MAKER

MAKERSTAMP

Rate-Ccy

Fload-Rate

BORROW_LEND_IND

Fltrate-Detail

INTEREST_RATE

UDFDETAILS

FLDNAM

FLDVAL

MODIFYCFDFLTRI_IOPK_REQ

Attribute	Description
Name	MODIFYCFDFLTRI_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-IO

Attribute	Description
Name	Rate-Code-IO
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 10

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	3

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

Rate-Ccy

Attribute	Description
Name	Rate-Ccy
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

Fload-Rate

Attribute	Description
Name	Fload-Rate
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

BORROW_LEND_IND

Attribute	Description

Name	BORROW_LEND_IND
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M

Fltrate-Detail

Attribute	**Description**
Name	Fltrate-Detail
Datatype	
Description	
Attribute	**Attribute** / **Description**: maxOccurs / unbounded

INTEREST_RATE

Attribute	**Description**
Name	INTEREST_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; maxInclusive / 100

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.14.3.CF-ModifyCFDFLTRI-Res-Full-MSG.xsd

MODIFYCFDFLTRI_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-Full

RATE_CODE

DESC

BRANCH_CODE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Rate-Ccy

CCY_CODE

Fload-Rate

AMOUNT_SLAB1

EFFECTIVE_DATE

BORROW_LEND_IND

Fltrate-Detail

TENOR_TO1

INTEREST_RATE

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

Attribute	Description
Name	MODIFYCFDFLTRI_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-Full

Attribute	Description
Name	Rate-Code-Full
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	105

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

Rate-Ccy

Attribute	Description
Name	Rate-Ccy
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

CCY_CODE

Attribute	Description
Name	CCY_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

Fload-Rate

Attribute	Description
Name	Fload-Rate
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

AMOUNT_SLAB1

Attribute	Description
Name	AMOUNT_SLAB1
Datatype	Decimal
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>9999999999999999999.99</td></tr></table>

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	

Restrictions	

Restrictions	Description
enumeration	B,L,M

Fltrate-Detail

Attribute	Description
Name	Fltrate-Detail
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

TENOR_TO1

Attribute	Description
Name	TENOR_TO1
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	5
minInclusive	0
maxInclusive	99999

INTEREST_RATE

Attribute	Description
Name	INTEREST_RATE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
maxInclusive	100

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAM

Attribute	Description

Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	150
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.14.4.CF-ModifyCFDFLTRI-Res-PK-MSG.xsd

MODIFYCFDFLTRI_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-PK

RATE_CODE

BRANCH_CODE

Rate-Code-IO

RATE_CODE

DESC

BRANCH_CODE

MAKER

MAKERSTAMP

Rate-Ccy

Fload-Rate

BORROW_LEND_IND

Fltrate-Detail

INTEREST_RATE

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYCFDFLTRI_IOPK_RES

Attribute	Description
Name	MODIFYCFDFLTRI_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.

Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-PK

Attribute	Description
Name	Rate-Code-PK
Datatype	
Description	

RATE_CODE

Attribute	Description

Name	RATE_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	10

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

Rate-Code-IO

Attribute	Description
Name	Rate-Code-IO
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	10

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 3

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

Rate-Ccy

Attribute	**Description**
Name	Rate-Ccy
Datatype	
Description	
Attribute	**Attribute** / **Description** maxOccurs / unbounded

Fload-Rate

Attribute	**Description**
Name	Fload-Rate
Datatype	
Description	
Attribute	**Attribute** / **Description** maxOccurs / unbounded

BORROW_LEND_IND

Attribute	**Description**

Name	BORROW_LEND_IND
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / B,L,M

Fltrate-Detail

Attribute	**Description**
Name	Fltrate-Detail
Datatype	
Description	
Attribute	**Attribute** / **Description**: maxOccurs / unbounded

INTEREST_RATE

Attribute	**Description**
Name	INTEREST_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; maxInclusive / 100

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.15.ModifyCFFloatRateMaint

2.15.1.CF-ModifyCFFloatRateMaint-Req-Full-MSG.xsd

MODIFYCFFLOATRATEMAINT_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Master-Full

RATECODE

RATECODEDESCRIPTION

TENORCODE

TENORCODEDESCRIPTION

CCYCODE

CCYNAME

EFFECTIVEDATE

RATESOURCE

RATESOURCEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Rate-Detail

RATETYPE

RATETYPEDESCRIPTION

INTERESTRATE

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

MODIFYCFFLOATRATEMAINT_FSFS_REQ

Attribute	Description
Name	MODIFYCFFLOATRATEMAINT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.

Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Master-Full

Attribute	Description
Name	Cftm-Rate-Master-Full
Datatype	
Description	

RATECODE

Attribute	Description

Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 10

RATECODEDESCRIPTION

Attribute	**Description**
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates Rate Code Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TENORCODE

Attribute	**Description**
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TENORCODEDESCRIPTION

Attribute	**Description**
Name	TENORCODEDESCRIPTION
Datatype	String
Description	Indicates Tenor Code Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

CCYCODE

Attribute	**Description**
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description**: maxLength / 3

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency Code Description
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

RATESOURCE

Attribute	Description
Name	RATESOURCE
Datatype	String
Description	Indicates Rate Source
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

RATESOURCEDESCRIPTION

Attribute	Description
Name	RATESOURCEDESCRIPTION
Datatype	String
Description	Indicates Rate Source Description
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String

Description	The User id who has booked the contract
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has booked the contract
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	The User id who has authorized the booked contract
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

MODNO

Attribute	Description
Name	MODNO

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorized
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Cftm-Rate-Detail

Attribute	Description
Name	Cftm-Rate-Detail
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

INTERESTRATE

Attribute	Description
Name	INTERESTRATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.15.2.CF-ModifyCFFloatRateMaint-Req-IO-MSG.xsd

MODIFYCFFLOATRATEMAINT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Master-IO

RATECODE

TENORCODE

CCYCODE

EFFECTIVEDATE

MODNO

Cftm-Rate-Detail

RATETYPE

RATETYPEDESCRIPTION

INTERESTRATE

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

MODIFYCFFLOATRATEMAINT_IOPK_REQ

Attribute	Description
Name	MODIFYCFFLOATRATEMAINT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String

Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Master-IO

Attribute	Description
Name	Cftm-Rate-Master-IO
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 10

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description**: maxLength / 3

EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

MODNO

Attribute	Description
Name	MODNO
Datatype	Integer
Description	Specifies The Modification Number.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

Cftm-Rate-Detail

Attribute	Description
Name	Cftm-Rate-Detail
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

INTERESTRATE

Attribute	Description
Name	INTERESTRATE
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

2.15.3.CF-ModifyCFFloatRateMaint-Res-Full-MSG.xsd

MODIFYCFFLOATRATEMAINT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Master-IO

RATECODE

TENORCODE

CCYCODE

EFFECTIVEDATE

MODNO

Cftm-Rate-Detail

RATETYPE

RATETYPEDESCRIPTION

INTERESTRATE

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Cftm-Rate-Master-Full

RATECODE

RATECODEDESCRIPTION

TENORCODE

TENORCODEDESCRIPTION

CCYCODE

CCYNAME

EFFECTIVEDATE

RATESOURCE

RATESOURCEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Rate-Detail

RATETYPE

RATETYPEDESCRIPTION

INTERESTRATE

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYCFFLOATRATEMAINT_FSFS_RES

Attribute	Description
Name	MODIFYCFFLOATRATEMAINT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Master-IO

Attribute	Description
Name	Cftm-Rate-Master-IO
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TENORCODE

Attribute	Description

Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

CCYCODE

Attribute	**Description**
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description**: maxLength / 3

EFFECTIVEDATE

Attribute	**Description**
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Integer
Description	Specifies The Modification Number.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Cftm-Rate-Detail

Attribute	**Description**
Name	Cftm-Rate-Detail
Datatype	
Description	
Attribute	**Attribute** / **Description**: maxOccurs / unbounded

RATETYPE

Attribute	**Description**
Name	RATETYPE

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

INTERESTRATE

Attribute	Description
Name	INTERESTRATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 8

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

DATATYPE

Attribute	**Description**
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

FIELD_VALUE

Attribute	**Description**
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

VAL_TYPE

Attribute	**Description**
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

Cftm-Rate-Master-Full

Attribute	Description
Name	Cftm-Rate-Master-Full
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

RATECODEDESCRIPTION

Attribute	Description
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates Rate Code Description
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TENORCODEDESCRIPTION

Attribute	Description
Name	TENORCODEDESCRIPTION
Datatype	String
Description	Indicates Tenor Code Description

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

CCYCODE

Attribute	**Description**
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description** maxLength / 3

CCYNAME

Attribute	**Description**
Name	CCYNAME
Datatype	String
Description	Indicates Currency Code Description
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

EFFECTIVEDATE

Attribute	**Description**
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

RATESOURCE

Attribute	**Description**
Name	RATESOURCE
Datatype	String
Description	Indicates Rate Source
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

RATESOURCEDESCRIPTION

Attribute	Description
Name	RATESOURCEDESCRIPTION
Datatype	String
Description	Indicates Rate Source Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	The User id who has booked the contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has booked the contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	The User id who has authorized the booked contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

ONCEAUTH

Attribute	Description
Name	ONCEAUTH

Datatype	String
Description	Indicates Once Authorized
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Cftm-Rate-Detail

Attribute	Description
Name	Cftm-Rate-Detail
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

INTERESTRATE

Attribute	Description
Name	INTERESTRATE
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	**Attribute** / **Description** maxOccurs / unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String

Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.15.4.CF-ModifyCFFloatRateMaint-Res-PK-MSG.xsd

MODIFYCFFLOATRATEMAINT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Master-PK

RATECODE

TENORCODE

CCYCODE

EFFECTIVEDATE

Cftm-Rate-Master-IO

RATECODE

TENORCODE

CCYCODE

EFFECTIVEDATE

MODNO

Cftm-Rate-Detail

RATETYPE

RATETYPEDESCRIPTION

INTERESTRATE

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Cftm-Rate-Master-Full

RATECODE

RATECODEDESCRIPTION

TENORCODE

TENORCODEDESCRIPTION

CCYCODE

CCYNAME

EFFECTIVEDATE

RATESOURCE

RATESOURCEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Rate-Detail

RATETYPE

RATETYPEDESCRIPTION

INTERESTRATE

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYCFFLOATRATEMAINT_IOPK_RES

Attribute	Description
Name	MODIFYCFFLOATRATEMAINT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Master-PK

Attribute	**Description**

Name	Cftm-Rate-Master-PK
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	String
Description	

Cftm-Rate-Master-IO

Attribute	Description
Name	Cftm-Rate-Master-IO

Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 10

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description**: maxLength / 3

EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

MODNO

Attribute	Description
Name	MODNO
Datatype	Integer
Description	Specifies The Modification Number.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: totalDigits / 22

Cftm-Rate-Detail

Attribute	Description
Name	Cftm-Rate-Detail
Datatype	
Description	
Attribute	**Attribute** / **Description**: maxOccurs / unbounded

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

INTERESTRATE

Attribute	Description
Name	INTERESTRATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

UDFDETAILS

Attribute	Description

Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

VAL_TYPE

Attribute	**Description**
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

Cftm-Rate-Master-Full

Attribute	**Description**
Name	Cftm-Rate-Master-Full
Datatype	
Description	

RATECODE

Attribute	**Description**
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description** maxLength / 10

RATECODEDESCRIPTION

Attribute	**Description**
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates Rate Code Description
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Restrictions	**Restrictions** / **Description**: maxLength / 12

TENORCODEDESCRIPTION

Attribute	Description
Name	TENORCODEDESCRIPTION
Datatype	String
Description	Indicates Tenor Code Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	**Restrictions** / **Description**: maxLength / 3

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency Code Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

RATESOURCE

Attribute	Description
Name	RATESOURCE
Datatype	String
Description	Indicates Rate Source
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

RATESOURCEDESCRIPTION

Attribute	Description
Name	RATESOURCEDESCRIPTION
Datatype	String
Description	Indicates Rate Source Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	The User id who has booked the contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has booked the contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	The User id who has authorized the booked contract
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

RECSTAT

Attribute	Description
Name	RECSTAT

Datatype	String
Description	Indicates Record Status
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorized
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

Cftm-Rate-Detail

Attribute	**Description**
Name	Cftm-Rate-Detail
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

RATETYPE

Attribute	**Description**
Name	RATETYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

RATETYPEDESCRIPTION

Attribute	**Description**
Name	RATETYPEDESCRIPTION
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

INTERESTRATE

Attribute	Description
Name	INTERESTRATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.16.ModifyCFRateCodeMaint

2.16.1.CF-ModifyCFRateCodeMaint-Req-Full-MSG.xsd

- *MODIFYCFRATECODEMAINT_FSFS_REQ*
  - *FCUBS_HEADER*
    - *SOURCE*
    - *UBSCOMP*
    - *MSGID*
    - *CORRELID*
    - *USERID*
    - *BRANCH*
    - *MODULEID*
    - *SERVICE*
    - *OPERATION*
    - *SOURCE_OPERATION*
    - *SOURCE_USERID*
    - *DESTINATION*
    - *MULTITRIPID*
    - *FUNCTIONID*
    - *ACTION*
    - *MSGSTAT*
    - *PASSWORD*
    - *ADDL*
      - *PARAM*
        - *NAME*
        - *VALUE*
  - *FCUBS_BODY*
    - *Cftm-Rate-Code-Defn-Full*
      - *RATECODE*
      - *RATECODEDESCRIPTION*
      - *HOLIDAYCCY*
      - *PROPAGATIONACROSSBRANCHES*
      - *MAKERID*

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Tenor-Code-Defn

TENORCODE

TENORCODEDESCRIPTION

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

MODIFYCFRATECODEMAINT_FSFS_REQ

Attribute	Description
Name	MODIFYCFRATECODEMAINT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID

Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String

Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Code-Defn-Full

Attribute	Description
Name	Cftm-Rate-Code-Defn-Full
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

RATECODEDESCRIPTION

Attribute	Description
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates the description of rate code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

HOLIDAYCCY

Attribute	Description
Name	HOLIDAYCCY
Datatype	String
Description	Indicates Holiday Currency
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

PROPAGATIONACROSSBRANCHES

Attribute	Description
Name	PROPAGATIONACROSSBRANCHES
Datatype	String
Description	Propagate Across Branches
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User id who has saved the record.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the date and time when the user has saved the record.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User id who has authorized the record.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	It indicates the status of the record,whether open or Closed.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

ONCEAUTH

Attribute	Description
Name	ONCEAUTH

Datatype	String
Description	Indicates Once Authorized
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Cftm-Tenor-Code-Defn

Attribute	Description
Name	Cftm-Tenor-Code-Defn
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TENORCODEDESCRIPTION

Attribute	Description
Name	TENORCODEDESCRIPTION
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.16.2.CF-ModifyCFRateCodeMaint-Req-IO-MSG.xsd

MODIFYCFRATECODEMAINT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Code-Defn-IO

RATECODE

RATECODEDESCRIPTION

HOLIDAYCCY

MODNO

Cftm-Tenor-Code-Defn

TENORCODE

TENORCODEDESCRIPTION

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

MODIFYCFRATECODEMAINT_IOPK_REQ

Attribute	Description
Name	MODIFYCFRATECODEMAINT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Code-Defn-IO

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

RATECODEDESCRIPTION

Attribute	Description
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates the description of rate code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

HOLIDAYCCY

Attribute	Description

Name	HOLIDAYCCY
Datatype	String
Description	Indicates Holiday Currency
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Integer
Description	Specifies The Modification Number.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Cftm-Tenor-Code-Defn

Attribute	**Description**
Name	Cftm-Tenor-Code-Defn
Datatype	
Description	
Attribute	**Attribute** / **Description**: maxOccurs / unbounded

TENORCODE

Attribute	**Description**
Name	TENORCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TENORCODEDESCRIPTION

Attribute	**Description**
Name	TENORCODEDESCRIPTION
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

2.16.3.CF-ModifyCFRateCodeMaint-Res-Full-MSG.xsd

MODIFYCFRATECODEMAINT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Code-Defn-IO

RATECODE

RATECODEDESCRIPTION

HOLIDAYCCY

MODNO

Cftm-Tenor-Code-Defn

TENORCODE

TENORCODEDESCRIPTION

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Cftm-Rate-Code-Defn-Full

RATECODE

RATECODEDESCRIPTION

HOLIDAYCCY

PROPAGATIONACROSSBRANCHES

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Tenor-Code-Defn

TENORCODE

TENORCODEDESCRIPTION

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYCFRATECODEMAINT_FSFS_RES

Attribute	Description
Name	MODIFYCFRATECODEMAINT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Code-Defn-IO

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

RATECODEDESCRIPTION

Attribute	Description
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates the description of rate code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

HOLIDAYCCY

Attribute	Description

Name	HOLIDAYCCY
Datatype	String
Description	Indicates Holiday Currency
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Integer
Description	Specifies The Modification Number.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Cftm-Tenor-Code-Defn

Attribute	**Description**
Name	Cftm-Tenor-Code-Defn
Datatype	
Description	
Attribute	**Attribute** / **Description**: maxOccurs / unbounded

TENORCODE

Attribute	**Description**
Name	TENORCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TENORCODEDESCRIPTION

Attribute	**Description**
Name	TENORCODEDESCRIPTION
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

Cftm-Rate-Code-Defn-Full

Attribute	Description
Name	Cftm-Rate-Code-Defn-Full
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	10

RATECODEDESCRIPTION

Attribute	Description
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates the description of rate code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

HOLIDAYCCY

Attribute	Description
Name	HOLIDAYCCY
Datatype	String
Description	Indicates Holiday Currency
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

PROPAGATIONACROSSBRANCHES

Attribute	Description
Name	PROPAGATIONACROSSBRANCHES
Datatype	String
Description	Propagate Across Branches
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User id who has saved the record.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the date and time when the user has saved the record.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User id who has authorized the record.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String

Description	Indicates Authorization Status
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	It indicates the status of the record,whether open or Closed.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorized
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

Cftm-Tenor-Code-Defn

Attribute	Description
Name	Cftm-Tenor-Code-Defn
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	10

TENORCODEDESCRIPTION

Attribute	Description
Name	TENORCODEDESCRIPTION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name

Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.16.4.CF-ModifyCFRateCodeMaint-Res-PK-MSG.xsd

MODIFYCFRATECODEMAINT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Code-Defn-PK

RATECODE

Cftm-Rate-Code-Defn-IO

RATECODE

RATECODEDESCRIPTION

HOLIDAYCCY

MODNO

Cftm-Tenor-Code-Defn

TENORCODE

TENORCODEDESCRIPTION

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Cftm-Rate-Code-Defn-Full

RATECODE

RATECODEDESCRIPTION

HOLIDAYCCY

PROPAGATIONACROSSBRANCHES

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Tenor-Code-Defn

TENORCODE

TENORCODEDESCRIPTION

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYCFRATECODEMAINT_IOPK_RES

Attribute	Description
Name	MODIFYCFRATECODEMAINT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: maxLength = 128; pattern = [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0; maxOccurs = unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Code-Defn-PK

Attribute	**Description**

Name	Cftm-Rate-Code-Defn-PK
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

Cftm-Rate-Code-Defn-IO

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

RATECODEDESCRIPTION

Attribute	Description
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates the description of rate code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

HOLIDAYCCY

Attribute	Description
Name	HOLIDAYCCY

Datatype	String
Description	Indicates Holiday Currency
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Integer
Description	Specifies The Modification Number.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Cftm-Tenor-Code-Defn

Attribute	**Description**
Name	Cftm-Tenor-Code-Defn
Datatype	
Description	
Attribute	**Attribute** / **Description**: maxOccurs / unbounded

TENORCODE

Attribute	**Description**
Name	TENORCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TENORCODEDESCRIPTION

Attribute	**Description**
Name	TENORCODEDESCRIPTION
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

Cftm-Rate-Code-Defn-Full

Attribute	Description
Name	Cftm-Rate-Code-Defn-Full
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	10

RATECODEDESCRIPTION

Attribute	Description
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates the description of rate code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

HOLIDAYCCY

Attribute	Description
Name	HOLIDAYCCY
Datatype	String
Description	Indicates Holiday Currency
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

PROPAGATIONACROSSBRANCHES

Attribute	Description
Name	PROPAGATIONACROSSBRANCHES
Datatype	String
Description	Propagate Across Branches
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Specifies the User id who has saved the record.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the date and time when the user has saved the record.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User id who has authorized the record.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String

Description	Indicates Authorization Status
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	It indicates the status of the record,whether open or Closed.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorized
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

Cftm-Tenor-Code-Defn

Attribute	Description
Name	Cftm-Tenor-Code-Defn
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TENORCODEDESCRIPTION

Attribute	Description
Name	TENORCODEDESCRIPTION
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name

Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.17.ModifyCFRateTypeDefn

2.17.1.CF-ModifyCFRateTypeDefn-Req-Full-MSG.xsd

MODIFYCFRATETYPEDEFN_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Type-Defn-Full

RATETYPE

RATETYPEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

MODIFYCFRATETYPEDEFN_FSFS_REQ

Attribute	Description
Name	MODIFYCFRATETYPEDEFN_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Type-Defn-Full

Attribute	Description
Name	Cftm-Rate-Type-Defn-Full
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	Indicates Rate Type Description
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	The User Id who has created\last modified the Rate Type Definition details.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user hascreated\last modified the Rate Type Definition details.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	The User Id who has Authorized the creation\modification of Rate Type Definition details.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user has Authorized the creation\ modification of Rate Type Definition details.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

MODNO

Attribute	**Description**
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A - Authorized U - Un Authorized

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status O - Open C - Close
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Rate Type Definition detail has been Authorized atleast Once.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.17.2.CF-ModifyCFRateTypeDefn-Req-IO-MSG.xsd

MODIFYCFRATETYPEDEFN_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Type-Defn-IO

RATETYPE

RATETYPEDESCRIPTION

MODNO

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

MODIFYCFRATETYPEDEFN_IOPK_REQ

Attribute	Description
Name	MODIFYCFRATETYPEDEFN_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Type-Defn-IO

Attribute	Description
Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	

RATETYPE

Attribute	Description

Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

RATETYPEDESCRIPTION

Attribute	**Description**
Name	RATETYPEDESCRIPTION
Datatype	String
Description	Indicates Rate Type Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Integer
Description	Indicates Modification Number i.e the number of times the Rate Type Definition detail has been modified.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String

Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String

Description	Indicates Value Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.17.3.CF-ModifyCFRateTypeDefn-Res-Full-MSG.xsd

MODIFYCFRATETYPEDEFN_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Type-Defn-IO

RATETYPE

RATETYPEDESCRIPTION

MODNO

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Cftm-Rate-Type-Defn-Full

RATETYPE

RATETYPEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYCFRATETYPEDEFN_FSFS_RES

Attribute	Description
Name	MODIFYCFRATETYPEDEFN_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Type-Defn-IO

Attribute	Description
Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	12

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	Indicates Rate Type Description
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

MODNO

Attribute	Description
Name	MODNO
Datatype	Integer
Description	Indicates Modification Number i.e the number of times the Rate Type Definition detail has been modified.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

Cftm-Rate-Type-Defn-Full

Attribute	Description
Name	Cftm-Rate-Type-Defn-Full
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	12

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	Indicates Rate Type Description
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	105

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	The User Id who has created\last modified the Rate Type Definition details.
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	12

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user hascreated\last modified the Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	The User Id who has Authorized the creation\modification of Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user has Authorized the creation\ modification of Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AUTHSTAT

Attribute	Description

Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A - Authorized U - Un Authorized
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates Record Status O - Open C - Close
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Rate Type Definition detail has been Authorized atleast Once.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String

Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String

Description	Indicates Value Type
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	**Attribute** / **Description**: maxOccurs / unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.17.4.CF-ModifyCFRateTypeDefn-Res-PK-MSG.xsd

MODIFYCFRATETYPEDEFN_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Type-Defn-PK

RATETYPE

Cftm-Rate-Type-Defn-IO

RATETYPE

RATETYPEDESCRIPTION

MODNO

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Cftm-Rate-Type-Defn-Full

RATETYPE

RATETYPEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYCFRATETYPEDEFN_IOPK_RES

Attribute	Description
Name	MODIFYCFRATETYPEDEFN_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Type-Defn-PK

Attribute	**Description**

Name	Cftm-Rate-Type-Defn-PK
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

Cftm-Rate-Type-Defn-IO

Attribute	Description
Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	Indicates Rate Type Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

MODNO

Attribute	Description
Name	MODNO

Datatype	Integer
Description	Indicates Modification Number i.e the number of times the Rate Type Definition detail has been modified.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

FIELD_VALUE

Attribute	**Description**
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

VAL_TYPE

Attribute	**Description**
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

Cftm-Rate-Type-Defn-Full

Attribute	**Description**
Name	Cftm-Rate-Type-Defn-Full
Datatype	
Description	

RATETYPE

Attribute	**Description**
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

RATETYPEDESCRIPTION

Attribute	**Description**
Name	RATETYPEDESCRIPTION
Datatype	String
Description	Indicates Rate Type Description
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	The User Id who has created\last modified the Rate Type Definition details.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user hascreated\last modified the Rate Type Definition details.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	The User Id who has Authorized the creation\modification of Rate Type Definition details.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user has Authorized the creation\ modification of Rate Type Definition details.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

MODNO

Attribute	**Description**
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A - Authorized U - Un Authorized
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates Record Status O - Open C - Close

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 1

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Rate Type Definition detail has been Authorized atleast Once.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name

Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.18.QueryCFDFLTRI

2.18.1.CF-QueryCFDFLTRI-Req-IO-MSG.xsd

QUERYCFDFLTRI_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-IO

RATE_CODE

BRANCH_CODE

QUERYCFDFLTRI_IOFS_REQ

Attribute	Description
Name	QUERYCFDFLTRI_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-IO

Attribute	Description
Name	Rate-Code-IO
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

BRANCH_CODE

Attribute	Description

Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

2.18.2.CF-QueryCFDFLTRI-Res-Full-MSG.xsd

QUERYCFDFLTRI_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-IO

RATE_CODE

BRANCH_CODE

Rate-Code-Full

RATE_CODE

DESC

BRANCH_CODE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Rate-Ccy

CCY_CODE

Fload-Rate

AMOUNT_SLAB1

EFFECTIVE_DATE

BORROW_LEND_IND

Fltrate-Detail

TENOR_TO1

INTEREST_RATE

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

Attribute	Description
Name	QUERYCFDFLTRI_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-IO

Attribute	Description
Name	Rate-Code-IO
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

Rate-Code-Full

Attribute	Description
Name	Rate-Code-Full
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 10

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Rate-Ccy

Attribute	Description
Name	Rate-Ccy
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

CCY_CODE

Attribute	Description
Name	CCY_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

Fload-Rate

Attribute	Description
Name	Fload-Rate
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

AMOUNT_SLAB1

Attribute	Description
Name	AMOUNT_SLAB1
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	9999999999999999999.99

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Restrictions	

Restrictions	Description
enumeration	B,L,M

Fltrate-Detail

Attribute	Description
Name	Fltrate-Detail
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

TENOR_TO1

Attribute	Description
Name	TENOR_TO1
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	5
minInclusive	0
maxInclusive	99999

INTEREST_RATE

Attribute	Description
Name	INTEREST_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; maxInclusive / 100

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150; minLength / 0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.19.QueryCFFloatRateMaint

2.19.1.CF-QueryCFFloatRateMaint-Req-IO-MSG.xsd

QUERYCFFLOATRATEMAINT_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Master-IO

RATECODE

TENORCODE

CCYCODE

EFFECTIVEDATE

QUERYCFFLOATRATEMAINT_IOFS_REQ

Attribute	Description
Name	QUERYCFFLOATRATEMAINT_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Master-IO

Attribute	Description
Name	Cftm-Rate-Master-IO
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	10

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	String
Description	

2.19.2.CF-QueryCFFloatRateMaint-Res-Full-MSG.xsd

QUERYCFFLOATRATEMAINT_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Master-IO

RATECODE

TENORCODE

CCYCODE

EFFECTIVEDATE

Cftm-Rate-Master-Full

RATECODE

RATECODEDESCRIPTION

TENORCODE

TENORCODEDESCRIPTION

CCYCODE

CCYNAME

EFFECTIVEDATE

RATESOURCE

RATESOURCEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Rate-Detail

RATETYPE

RATETYPEDESCRIPTION

INTERESTRATE

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYCFFLOATRATEMAINT_IOFS_RES

Attribute	Description
Name	QUERYCFFLOATRATEMAINT_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Master-IO

Attribute	Description
Name	Cftm-Rate-Master-IO
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CCYCODE

Attribute	Description

Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

EFFECTIVEDATE

Attribute	**Description**
Name	EFFECTIVEDATE
Datatype	String
Description	

Cftm-Rate-Master-Full

Attribute	**Description**
Name	Cftm-Rate-Master-Full
Datatype	
Description	

RATECODE

Attribute	**Description**
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Restrictions	**Restrictions** / **Description**: maxLength / 10

RATECODEDESCRIPTION

Attribute	**Description**
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates Rate Code Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TENORCODE

Attribute	**Description**
Name	TENORCODE
Datatype	String
Description	Indicates Tenor Code

Restrictions	

Restrictions	Description
maxLength	12

TENORCODEDESCRIPTION

Attribute	Description
Name	TENORCODEDESCRIPTION
Datatype	String
Description	Indicates Tenor Code Description
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	Indicates Currency Code
Restrictions	

Restrictions	Description
maxLength	3

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency Code Description
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

RATESOURCE

Attribute	Description

Name	RATESOURCE
Datatype	String
Description	Indicates Rate Source
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

RATESOURCEDESCRIPTION

Attribute	**Description**
Name	RATESOURCEDESCRIPTION
Datatype	String
Description	Indicates Rate Source Description
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	The User id who has booked the contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has booked the contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

CHECKERID

Attribute	**Description**

Name	CHECKERID
Datatype	String
Description	The User id who has authorized the booked contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

MODNO

Attribute	**Description**
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates Record Status

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorized
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Cftm-Rate-Detail

Attribute	Description
Name	Cftm-Rate-Detail
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 105

INTERESTRATE

Attribute	**Description**
Name	INTERESTRATE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.20.QueryCFRateCodeMaint

2.20.1.CF-QueryCFRateCodeMaint-Req-IO-MSG.xsd

- *QUERYCFRATECODEMAINT_IOFS_REQ*
  - *FCUBS_HEADER*
    - *SOURCE*
    - *UBSCOMP*
    - *MSGID*
    - *CORRELID*
    - *USERID*
    - *BRANCH*
    - *MODULEID*
    - *SERVICE*
    - *OPERATION*
    - *SOURCE_OPERATION*
    - *SOURCE_USERID*
    - *DESTINATION*
    - *MULTITRIPID*
    - *FUNCTIONID*
    - *ACTION*
    - *MSGSTAT*
    - *PASSWORD*
    - *ADDL*
      - *PARAM*
        - *NAME*
        - *VALUE*
  - *FCUBS_BODY*
    - *Cftm-Rate-Code-Defn-IO*
      - *RATECODE*

QUERYCFRATECODEMAINT_IOFS_REQ

Attribute	Description
Name	QUERYCFRATECODEMAINT_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Code-Defn-IO

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

2.20.2.CF-QueryCFRateCodeMaint-Res-Full-MSG.xsd

QUERYCFRATECODEMAINT_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Code-Defn-IO

RATECODE

Cftm-Rate-Code-Defn-Full

RATECODE

RATECODEDESCRIPTION

HOLIDAYCCY

PROPAGATIONACROSSBRANCHES

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Cftm-Tenor-Code-Defn

TENORCODE

TENORCODEDESCRIPTION

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYCFRATECODEMAINT_IOFS_RES

Attribute	Description
Name	QUERYCFRATECODEMAINT_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description

Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	
	Restrictions / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description**: minOccurs / 0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Code-Defn-IO

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

Cftm-Rate-Code-Defn-Full

Attribute	Description
Name	Cftm-Rate-Code-Defn-Full
Datatype	
Description	

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

RATECODEDESCRIPTION

Attribute	Description
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates the description of rate code
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

HOLIDAYCCY

Attribute	Description

Name	HOLIDAYCCY
Datatype	String
Description	Indicates Holiday Currency
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

PROPAGATIONACROSSBRANCHES

Attribute	**Description**
Name	PROPAGATIONACROSSBRANCHES
Datatype	String
Description	Propagate Across Branches
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	Specifies the User id who has saved the record.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the date and time when the user has saved the record.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

CHECKERID

Attribute	**Description**

Name	CHECKERID
Datatype	String
Description	Indicates the User id who has authorized the record.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and stamp when the user has authorized the booked contract
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

MODNO

Attribute	**Description**
Name	MODNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	It indicates the status of the record,whether open or Closed.

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorized
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

Cftm-Tenor-Code-Defn

Attribute	Description
Name	Cftm-Tenor-Code-Defn
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

TENORCODE

Attribute	Description
Name	TENORCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	10

TENORCODEDESCRIPTION

Attribute	Description
Name	TENORCODEDESCRIPTION
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.21.QueryCFRateTypeDefn

2.21.1.CF-QueryCFRateTypeDefn-Req-IO-MSG.xsd

QUERYCFRATETYPEDEFN_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Type-Defn-IO

RATETYPE

QUERYCFRATETYPEDEFN_IOFS_REQ

Attribute	Description
Name	QUERYCFRATETYPEDEFN_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Type-Defn-IO

Attribute	Description
Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

2.21.2.CF-QueryCFRateTypeDefn-Res-Full-MSG.xsd

QUERYCFRATETYPEDEFN_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cftm-Rate-Type-Defn-IO

RATETYPE

Cftm-Rate-Type-Defn-Full

RATETYPE

RATETYPEDESCRIPTION

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYCFRATETYPEDEFN_IOFS_RES

Attribute	Description
Name	QUERYCFRATETYPEDEFN_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	

Cftm-Rate-Type-Defn-IO

Attribute	**Description**

Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

Cftm-Rate-Type-Defn-Full

Attribute	Description
Name	Cftm-Rate-Type-Defn-Full
Datatype	
Description	

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates Rate Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	Indicates Rate Type Description
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String
Description	The User Id who has created\last modified the Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERDTSTAMP

Attribute	**Description**
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user hascreated\last modified the Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	The User Id who has Authorized the creation\modification of Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user has Authorized the creation\ modification of Rate Type Definition details.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

MODNO

Attribute	Description
Name	MODNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A - Authorized U - Un Authorized
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status O - Open C - Close
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates whether Rate Type Definition detail has been Authorized atleast Once.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value Type
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC

Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.22.ReopenCFDFLTRI

2.22.1.CF-ReopenCFDFLTRI-Req-Full-MSG.xsd

REOPENCFDFLTRI_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-Full

RATE_CODE

DESC

BRANCH_CODE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Rate-Ccy

CCY_CODE

Fload-Rate

AMOUNT_SLAB1

EFFECTIVE_DATE

BORROW_LEND_IND

Fltrate-Detail

TENOR_TO1

INTEREST_RATE

UDFDETAILS

FLDNAM

FLDVAL

REOPENCFDFLTRI_FSFS_REQ

Attribute	Description
Name	REOPENCFDFLTRI_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-Full

Attribute	Description
Name	Rate-Code-Full
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Rate-Ccy

Attribute	Description
Name	Rate-Ccy
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

CCY_CODE

Attribute	Description
Name	CCY_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

Fload-Rate

Attribute	Description
Name	Fload-Rate
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

AMOUNT_SLAB1

Attribute	Description
Name	AMOUNT_SLAB1
Datatype	Decimal
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>9999999999999999999.99</td></tr></table>

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / B,L,M

FItrate-Detail

Attribute	Description
Name	FItrate-Detail
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

TENOR_TO1

Attribute	Description
Name	TENOR_TO1
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description** totalDigits / 5 minInclusive / 0 maxInclusive / 99999

INTEREST_RATE

Attribute	Description
Name	INTEREST_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 maxInclusive / 100

UDFDETAILS

Attribute	Description

Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.22.2.CF-ReopenCFDFLTRI-Req-IO-MSG.xsd

REOPENCFDFLTRI_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-IO

RATE_CODE

BRANCH_CODE

MAKER

MAKERSTAMP

MODNO

REOPENCFDFLTRI_IOPK_REQ

Attribute	Description
Name	REOPENCFDFLTRI_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-IO

Attribute	Description
Name	Rate-Code-IO
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	4

2.22.3.CF-ReopenCFDFLTRI-Res-Full-MSG.xsd

REOPENCFDFLTRI_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-Full

RATE_CODE

DESC

BRANCH_CODE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Rate-Ccy

CCY_CODE

Fload-Rate

AMOUNT_SLAB1

EFFECTIVE_DATE

BORROW_LEND_IND

Fltrate-Detail

TENOR_TO1

INTEREST_RATE

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

REOPENCFDFLTRI_FSFS_RES

Attribute	Description
Name	REOPENCFDFLTRI_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-Full

Attribute	Description

Name	Rate-Code-Full
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 10

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Rate-Ccy

Attribute	Description
Name	Rate-Ccy
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

CCY_CODE

Attribute	Description
Name	CCY_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

Fload-Rate

Attribute	Description
Name	Fload-Rate
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

AMOUNT_SLAB1

Attribute	Description
Name	AMOUNT_SLAB1
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	9999999999999999999.99

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

BORROW_LEND_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	
Restrictions	

Restrictions	Description
enumeration	B,L,M

Fltrate-Detail

Attribute	Description
Name	Fltrate-Detail
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

TENOR_TO1

Attribute	Description
Name	TENOR_TO1
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	5
minInclusive	0
maxInclusive	99999

INTEREST_RATE

Attribute	Description
Name	INTEREST_RATE

Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; maxInclusive / 100

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150; minLength / 0

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.22.4.CF-ReopenCFDFLTRI-Res-PK-MSG.xsd

REOPENCFDFLTRI_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Rate-Code-PK

RATE_CODE

BRANCH_CODE

Rate-Code-IO

RATE_CODE

BRANCH_CODE

MAKER

MAKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

REOPENCFDFLTRI_IOPK_RES

Attribute	Description
Name	REOPENCFDFLTRI_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**

Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Rate-Code-PK

Attribute	Description

Name	Rate-Code-PK
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	10

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

Rate-Code-IO

Attribute	Description
Name	Rate-Code-IO
Datatype	
Description	

RATE_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	10

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

MAKER

Attribute	Description
Name	MAKER
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

Gateway Documentation - FCUBSCFService
[Febraury] [2016]

Oracle Financial services Software Limited
Oracle Park
Off western Express Highway
Goregaon(East)
Mumbai,Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax:+91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2013], [2016], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.