

Gateway Documentation - FCUBSCoreService
Oracle FLEXCUBE Universal Banking
Release 12.87.02.0.0
[Febraury][2016]



Table Of Contents

1. Background	1
2. FCUBSCoreService	2
2.1. AuthorizeCSMBPLinkage	2
2.1.1. CO-AuthorizeCSMBPLinkage-Req-Full-MSG.xsd	2
2.1.2. CO-AuthorizeCSMBPLinkage-Req-IO-MSG.xsd	13
2.1.3. CO-AuthorizeCSMBPLinkage-Res-Full-MSG.xsd	21
2.1.4. CO-AuthorizeCSMBPLinkage-Res-PK-MSG.xsd	34
2.2. AuthorizeRPBenfPlan	43
2.2.1. CO-AuthorizeRPBenfPlan-Req-Full-MSG.xsd	43
2.2.2. CO-AuthorizeRPBenfPlan-Req-IO-MSG.xsd	57
2.2.3. CO-AuthorizeRPBenfPlan-Res-Full-MSG.xsd	65
2.2.4. CO-AuthorizeRPBenfPlan-Res-PK-MSG.xsd	80
2.3. AuthorizeRPEIgPlan	89
2.3.1. CO-AuthorizeRPEIgPlan-Req-Full-MSG.xsd	89
2.3.2. CO-AuthorizeRPEIgPlan-Req-IO-MSG.xsd	100
2.3.3. CO-AuthorizeRPEIgPlan-Res-Full-MSG.xsd	108
2.3.4. CO-AuthorizeRPEIgPlan-Res-PK-MSG.xsd	120
2.4. AuthorizeRPErBenPlan	129
2.4.1. CO-AuthorizeRPErBenPlan-Req-Full-MSG.xsd	129
2.4.2. CO-AuthorizeRPErBenPlan-Req-IO-MSG.xsd	141
2.4.3. CO-AuthorizeRPErBenPlan-Res-Full-MSG.xsd	149
2.4.4. CO-AuthorizeRPErBenPlan-Res-PK-MSG.xsd	162
2.5. AuthorizeRPSchMntc	172
2.5.1. CO-AuthorizeRPSchMntc-Req-Full-MSG.xsd	172
2.5.2. CO-AuthorizeRPSchMntc-Req-IO-MSG.xsd	186
2.5.3. CO-AuthorizeRPSchMntc-Res-Full-MSG.xsd	194
2.5.4. CO-AuthorizeRPSchMntc-Res-PK-MSG.xsd	209
2.6. CreateCSMBPLinkage	219
2.6.1. CO-CreateCSMBPLinkage-Req-Full-MSG.xsd	219
2.6.2. CO-CreateCSMBPLinkage-Req-IO-MSG.xsd	230
2.6.3. CO-CreateCSMBPLinkage-Res-Full-MSG.xsd	238
2.6.4. CO-CreateCSMBPLinkage-Res-PK-MSG.xsd	251
2.7. CreateRPBenfPlan	261
2.7.1. CO-CreateRPBenfPlan-Req-Full-MSG.xsd	261
2.7.2. CO-CreateRPBenfPlan-Req-IO-MSG.xsd	274
2.7.3. CO-CreateRPBenfPlan-Res-Full-MSG.xsd	286
2.7.4. CO-CreateRPBenfPlan-Res-PK-MSG.xsd	301
2.8. CreateRPEIgPlan	314
2.8.1. CO-CreateRPEIgPlan-Req-Full-MSG.xsd	314
2.8.2. CO-CreateRPEIgPlan-Req-IO-MSG.xsd	325
2.8.3. CO-CreateRPEIgPlan-Res-Full-MSG.xsd	333
2.8.4. CO-CreateRPEIgPlan-Res-PK-MSG.xsd	346
2.9. CreateRPErBenPlan	356
2.9.1. CO-CreateRPErBenPlan-Req-Full-MSG.xsd	356
2.9.2. CO-CreateRPErBenPlan-Req-IO-MSG.xsd	368
2.9.3. CO-CreateRPErBenPlan-Res-Full-MSG.xsd	378
2.9.4. CO-CreateRPErBenPlan-Res-PK-MSG.xsd	392
2.10. CreateRPSchMntc	403

2.10.1.CO-CreateRPSchMntc-Req-Full-MSG.xsd	403
2.10.2.CO-CreateRPSchMntc-Req-IO-MSG.xsd	418
2.10.3.CO-CreateRPSchMntc-Res-Full-MSG.xsd	429
2.10.4.CO-CreateRPSchMntc-Res-PK-MSG.xsd	445
2.11.DeleteCSMBPLinkage	459
2.11.1.CO-DeleteCSMBPLinkage-Req-Full-MSG.xsd	459
2.11.2.CO-DeleteCSMBPLinkage-Req-IO-MSG.xsd	470
2.11.3.CO-DeleteCSMBPLinkage-Res-Full-MSG.xsd	477
2.11.4.CO-DeleteCSMBPLinkage-Res-PK-MSG.xsd	490
2.12.DeleteRPBenfPlan	499
2.12.1.CO-DeleteRPBenfPlan-Req-Full-MSG.xsd	499
2.12.2.CO-DeleteRPBenfPlan-Req-IO-MSG.xsd	513
2.12.3.CO-DeleteRPBenfPlan-Res-Full-MSG.xsd	519
2.12.4.CO-DeleteRPBenfPlan-Res-PK-MSG.xsd	534
2.13.DeleteRPEIgPlan	543
2.13.1.CO-DeleteRPEIgPlan-Req-Full-MSG.xsd	543
2.13.2.CO-DeleteRPEIgPlan-Req-IO-MSG.xsd	554
2.13.3.CO-DeleteRPEIgPlan-Res-Full-MSG.xsd	561
2.13.4.CO-DeleteRPEIgPlan-Res-PK-MSG.xsd	573
2.14.DeleteRPErBenPlan	581
2.14.1.CO-DeleteRPErBenPlan-Req-Full-MSG.xsd	582
2.14.2.CO-DeleteRPErBenPlan-Req-IO-MSG.xsd	593
2.14.3.CO-DeleteRPErBenPlan-Res-Full-MSG.xsd	600
2.14.4.CO-DeleteRPErBenPlan-Res-PK-MSG.xsd	614
2.15.DeleteRPSchMntc	622
2.15.1.CO-DeleteRPSchMntc-Req-Full-MSG.xsd	622
2.15.2.CO-DeleteRPSchMntc-Req-IO-MSG.xsd	636
2.15.3.CO-DeleteRPSchMntc-Res-Full-MSG.xsd	643
2.15.4.CO-DeleteRPSchMntc-Res-PK-MSG.xsd	659
2.16.ModifyCSMBPLinkage	668
2.16.1.CO-ModifyCSMBPLinkage-Req-Full-MSG.xsd	668
2.16.2.CO-ModifyCSMBPLinkage-Req-IO-MSG.xsd	679
2.16.3.CO-ModifyCSMBPLinkage-Res-Full-MSG.xsd	688
2.16.4.CO-ModifyCSMBPLinkage-Res-PK-MSG.xsd	701
2.17.ModifyRPBenfPlan	711
2.17.1.CO-ModifyRPBenfPlan-Req-Full-MSG.xsd	711
2.17.2.CO-ModifyRPBenfPlan-Req-IO-MSG.xsd	724
2.17.3.CO-ModifyRPBenfPlan-Res-Full-MSG.xsd	735
2.17.4.CO-ModifyRPBenfPlan-Res-PK-MSG.xsd	750
2.18.ModifyRPEIgPlan	763
2.18.1.CO-ModifyRPEIgPlan-Req-Full-MSG.xsd	763
2.18.2.CO-ModifyRPEIgPlan-Req-IO-MSG.xsd	774
2.18.3.CO-ModifyRPEIgPlan-Res-Full-MSG.xsd	783
2.18.4.CO-ModifyRPEIgPlan-Res-PK-MSG.xsd	795
2.19.ModifyRPErBenPlan	806
2.19.1.CO-ModifyRPErBenPlan-Req-Full-MSG.xsd	806
2.19.2.CO-ModifyRPErBenPlan-Req-IO-MSG.xsd	818
2.19.3.CO-ModifyRPErBenPlan-Res-Full-MSG.xsd	828
2.19.4.CO-ModifyRPErBenPlan-Res-PK-MSG.xsd	841
2.20.ModifyRPSchMntc	853
2.20.1.CO-ModifyRPSchMntc-Req-Full-MSG.xsd	853
2.20.2.CO-ModifyRPSchMntc-Req-IO-MSG.xsd	867

2.20.3.CO-ModifyRPSchMntc-Res-Full-MSG.xsd	879
2.20.4.CO-ModifyRPSchMntc-Res-PK-MSG.xsd	894
2.21.QueryCSMBPLinkage	908
2.21.1.CO-QueryCSMBPLinkage-Req-IO-MSG.xsd	908
2.21.2.CO-QueryCSMBPLinkage-Res-Full-MSG.xsd	915
2.22.QueryRPBenfPlan	928
2.22.1.CO-QueryRPBenfPlan-Req-IO-MSG.xsd	928
2.22.2.CO-QueryRPBenfPlan-Res-Full-MSG.xsd	935
2.23.QueryRPEIgPlan	951
2.23.1.CO-QueryRPEIgPlan-Req-IO-MSG.xsd	951
2.23.2.CO-QueryRPEIgPlan-Res-Full-MSG.xsd	958
2.24.QueryRPErBenPlan	970
2.24.1.CO-QueryRPErBenPlan-Req-IO-MSG.xsd	970
2.24.2.CO-QueryRPErBenPlan-Res-Full-MSG.xsd	977
2.25.QueryRPSchMntc	991
2.25.1.CO-QueryRPSchMntc-Req-IO-MSG.xsd	991
2.25.2.CO-QueryRPSchMntc-Res-Full-MSG.xsd	998
2.26.AuthorizeAcctr	1014
2.26.1.CS-AuthorizeAcctr-Req-Full-MSG.xsd	1014
2.26.2.CS-AuthorizeAcctr-Req-IO-MSG.xsd	1026
2.26.3.CS-AuthorizeAcctr-Res-Full-MSG.xsd	1033
2.26.4.CS-AuthorizeAcctr-Res-PK-MSG.xsd	1047
2.27.AuthorizeAcltr	1056
2.27.1.CS-AuthorizeAcltr-Req-Full-MSG.xsd	1056
2.27.2.CS-AuthorizeAcltr-Req-IO-MSG.xsd	1068
2.27.3.CS-AuthorizeAcltr-Res-Full-MSG.xsd	1075
2.27.4.CS-AuthorizeAcltr-Res-PK-MSG.xsd	1088
2.28.AuthorizeActrp	1097
2.28.1.CS-AuthorizeActrp-Req-Full-MSG.xsd	1097
2.28.2.CS-AuthorizeActrp-Req-IO-MSG.xsd	1107
2.28.3.CS-AuthorizeActrp-Res-Full-MSG.xsd	1115
2.28.4.CS-AuthorizeActrp-Res-PK-MSG.xsd	1126
2.29.AuthorizeDeveloper	1136
2.29.1.CS-AuthorizeDeveloper-Req-Full-MSG.xsd	1136
2.29.2.CS-AuthorizeDeveloper-Req-IO-MSG.xsd	1149
2.29.3.CS-AuthorizeDeveloper-Res-Full-MSG.xsd	1157
2.29.4.CS-AuthorizeDeveloper-Res-PK-MSG.xsd	1171
2.30.AuthorizeProject	1180
2.30.1.CS-AuthorizeProject-Req-Full-MSG.xsd	1180
2.30.2.CS-AuthorizeProject-Req-IO-MSG.xsd	1192
2.30.3.CS-AuthorizeProject-Res-Full-MSG.xsd	1200
2.30.4.CS-AuthorizeProject-Res-PK-MSG.xsd	1213
2.31.CloseAcctr	1223
2.31.1.CS-CloseAcctr-Req-Full-MSG.xsd	1223
2.31.2.CS-CloseAcctr-Req-IO-MSG.xsd	1235
2.31.3.CS-CloseAcctr-Res-Full-MSG.xsd	1243
2.31.4.CS-CloseAcctr-Res-PK-MSG.xsd	1256
2.32.CloseAcltr	1266
2.32.1.CS-CloseAcltr-Req-Full-MSG.xsd	1266
2.32.2.CS-CloseAcltr-Req-IO-MSG.xsd	1277
2.32.3.CS-CloseAcltr-Res-Full-MSG.xsd	1285
2.32.4.CS-CloseAcltr-Res-PK-MSG.xsd	1297

2.33.CloseActrp	1307
2.33.1.CS-CloseActrp-Req-Full-MSG.xsd	1307
2.33.2.CS-CloseActrp-Req-IO-MSG.xsd	1317
2.33.3.CS-CloseActrp-Res-Full-MSG.xsd	1324
2.33.4.CS-CloseActrp-Res-PK-MSG.xsd	1336
2.34.CreateAcctr	1345
2.34.1.CS-CreateAcctr-Req-Full-MSG.xsd	1345
2.34.2.CS-CreateAcctr-Req-IO-MSG.xsd	1357
2.34.3.CS-CreateAcctr-Res-Full-MSG.xsd	1365
2.34.4.CS-CreateAcctr-Res-PK-MSG.xsd	1379
2.35.CreateAcctr	1389
2.35.1.CS-CreateAcctr-Req-Full-MSG.xsd	1389
2.35.2.CS-CreateAcctr-Req-IO-MSG.xsd	1400
2.35.3.CS-CreateAcctr-Res-Full-MSG.xsd	1408
2.35.4.CS-CreateAcctr-Res-PK-MSG.xsd	1421
2.36.CreateActrp	1430
2.36.1.CS-CreateActrp-Req-Full-MSG.xsd	1430
2.36.2.CS-CreateActrp-Req-IO-MSG.xsd	1440
2.36.3.CS-CreateActrp-Res-Full-MSG.xsd	1448
2.36.4.CS-CreateActrp-Res-PK-MSG.xsd	1460
2.37.CreateDeveloper	1470
2.37.1.CS-CreateDeveloper-Req-Full-MSG.xsd	1470
2.37.2.CS-CreateDeveloper-Req-IO-MSG.xsd	1483
2.37.3.CS-CreateDeveloper-Res-Full-MSG.xsd	1494
2.37.4.CS-CreateDeveloper-Res-PK-MSG.xsd	1509
2.38.CreateProject	1522
2.38.1.CS-CreateProject-Req-Full-MSG.xsd	1522
2.38.2.CS-CreateProject-Req-IO-MSG.xsd	1534
2.38.3.CS-CreateProject-Res-Full-MSG.xsd	1544
2.38.4.CS-CreateProject-Res-PK-MSG.xsd	1557
2.39.DeleteAcctr	1569
2.39.1.CS-DeleteAcctr-Req-Full-MSG.xsd	1569
2.39.2.CS-DeleteAcctr-Req-IO-MSG.xsd	1581
2.39.3.CS-DeleteAcctr-Res-Full-MSG.xsd	1588
2.39.4.CS-DeleteAcctr-Res-PK-MSG.xsd	1601
2.40.DeleteAcctr	1610
2.40.1.CS-DeleteAcctr-Req-Full-MSG.xsd	1610
2.40.2.CS-DeleteAcctr-Req-IO-MSG.xsd	1621
2.40.3.CS-DeleteAcctr-Res-Full-MSG.xsd	1628
2.40.4.CS-DeleteAcctr-Res-PK-MSG.xsd	1640
2.41.DeleteActrp	1649
2.41.1.CS-DeleteActrp-Req-Full-MSG.xsd	1649
2.41.2.CS-DeleteActrp-Req-IO-MSG.xsd	1659
2.41.3.CS-DeleteActrp-Res-Full-MSG.xsd	1665
2.41.4.CS-DeleteActrp-Res-PK-MSG.xsd	1677
2.42.DeleteDeveloper	1685
2.42.1.CS-DeleteDeveloper-Req-Full-MSG.xsd	1685
2.42.2.CS-DeleteDeveloper-Req-IO-MSG.xsd	1698
2.42.3.CS-DeleteDeveloper-Res-Full-MSG.xsd	1705
2.42.4.CS-DeleteDeveloper-Res-PK-MSG.xsd	1720
2.43.DeleteProject	1728
2.43.1.CS-DeleteProject-Req-Full-MSG.xsd	1728

2.43.2.CS-DeleteProject-Req-IO-MSG.xsd	1740
2.43.3.CS-DeleteProject-Res-Full-MSG.xsd	1747
2.43.4.CS-DeleteProject-Res-PK-MSG.xsd	1761
2.44.ModifyAcctr	1770
2.44.1.CS-ModifyAcctr-Req-Full-MSG.xsd	1770
2.44.2.CS-ModifyAcctr-Req-IO-MSG.xsd	1782
2.44.3.CS-ModifyAcctr-Res-Full-MSG.xsd	1791
2.44.4.CS-ModifyAcctr-Res-PK-MSG.xsd	1804
2.45.ModifyAcltr	1815
2.45.1.CS-ModifyAcltr-Req-Full-MSG.xsd	1815
2.45.2.CS-ModifyAcltr-Req-IO-MSG.xsd	1826
2.45.3.CS-ModifyAcltr-Res-Full-MSG.xsd	1835
2.45.4.CS-ModifyAcltr-Res-PK-MSG.xsd	1848
2.46.ModifyActrp	1859
2.46.1.CS-ModifyActrp-Req-Full-MSG.xsd	1859
2.46.2.CS-ModifyActrp-Req-IO-MSG.xsd	1869
2.46.3.CS-ModifyActrp-Res-Full-MSG.xsd	1878
2.46.4.CS-ModifyActrp-Res-PK-MSG.xsd	1889
2.47.ModifyDeveloper	1900
2.47.1.CS-ModifyDeveloper-Req-Full-MSG.xsd	1900
2.47.2.CS-ModifyDeveloper-Req-IO-MSG.xsd	1913
2.47.3.CS-ModifyDeveloper-Res-Full-MSG.xsd	1924
2.47.4.CS-ModifyDeveloper-Res-PK-MSG.xsd	1939
2.48.ModifyProject	1951
2.48.1.CS-ModifyProject-Req-Full-MSG.xsd	1951
2.48.2.CS-ModifyProject-Req-IO-MSG.xsd	1963
2.48.3.CS-ModifyProject-Res-Full-MSG.xsd	1974
2.48.4.CS-ModifyProject-Res-PK-MSG.xsd	1987
2.49.QueryAcctr	2000
2.49.1.CS-QueryAcctr-Req-IO-MSG.xsd	2000
2.49.2.CS-QueryAcctr-Res-Full-MSG.xsd	2007
2.50.QueryAcltr	2020
2.50.1.CS-QueryAcltr-Req-IO-MSG.xsd	2020
2.50.2.CS-QueryAcltr-Res-Full-MSG.xsd	2027
2.51.QueryActrp	2040
2.51.1.CS-QueryActrp-Req-IO-MSG.xsd	2040
2.51.2.CS-QueryActrp-Res-Full-MSG.xsd	2047
2.52.QueryDeveloper	2059
2.52.1.CS-QueryDeveloper-Req-IO-MSG.xsd	2059
2.52.2.CS-QueryDeveloper-Res-Full-MSG.xsd	2065
2.53.QueryProject	2080
2.53.1.CS-QueryProject-Req-IO-MSG.xsd	2080
2.53.2.CS-QueryProject-Res-Full-MSG.xsd	2087
2.54.ReopenAcctr	2101
2.54.1.CS-ReopenAcctr-Req-Full-MSG.xsd	2102
2.54.2.CS-ReopenAcctr-Req-IO-MSG.xsd	2113
2.54.3.CS-ReopenAcctr-Res-Full-MSG.xsd	2121
2.54.4.CS-ReopenAcctr-Res-PK-MSG.xsd	2134
2.55.ReopenAcltr	2144
2.55.1.CS-ReopenAcltr-Req-Full-MSG.xsd	2144
2.55.2.CS-ReopenAcltr-Req-IO-MSG.xsd	2155
2.55.3.CS-ReopenAcltr-Res-Full-MSG.xsd	2163

2.55.4.CS-ReopenActr-Res-PK-MSG.xsd	2175
2.56.ReopenActrp	2185
2.56.1.CS-ReopenActrp-Req-Full-MSG.xsd	2185
2.56.2.CS-ReopenActrp-Req-IO-MSG.xsd	2195
2.56.3.CS-ReopenActrp-Res-Full-MSG.xsd	2202
2.56.4.CS-ReopenActrp-Res-PK-MSG.xsd	2214
2.57.AuthorizeUserHoliday	2223
2.57.1.SM-AuthorizeUserHoliday-Req-Full-MSG.xsd	2223
2.57.2.SM-AuthorizeUserHoliday-Req-IO-MSG.xsd	2233
2.57.3.SM-AuthorizeUserHoliday-Res-Full-MSG.xsd	2240
2.57.4.SM-AuthorizeUserHoliday-Res-PK-MSG.xsd	2251
2.58.CreateUserHoliday	2261
2.58.1.SM-CreateUserHoliday-Req-Full-MSG.xsd	2261
2.58.2.SM-CreateUserHoliday-Req-IO-MSG.xsd	2271
2.58.3.SM-CreateUserHoliday-Res-Full-MSG.xsd	2278
2.58.4.SM-CreateUserHoliday-Res-PK-MSG.xsd	2289
2.59.DeleteUserHoliday	2299
2.59.1.SM-DeleteUserHoliday-Req-Full-MSG.xsd	2299
2.59.2.SM-DeleteUserHoliday-Req-IO-MSG.xsd	2308
2.59.3.SM-DeleteUserHoliday-Res-Full-MSG.xsd	2315
2.59.4.SM-DeleteUserHoliday-Res-PK-MSG.xsd	2326
2.60.QueryUserHoliday	2336
2.60.1.SM-QueryUserHoliday-Req-IO-MSG.xsd	2336
2.60.2.SM-QueryUserHoliday-Res-Full-MSG.xsd	2343
2.61.AuthorizeAddressCode	2354
2.61.1.ST-AuthorizeAddressCode-Req-Full-MSG.xsd	2354
2.61.2.ST-AuthorizeAddressCode-Req-IO-MSG.xsd	2366
2.61.3.ST-AuthorizeAddressCode-Res-Full-MSG.xsd	2374
2.61.4.ST-AuthorizeAddressCode-Res-PK-MSG.xsd	2387
2.62.AuthorizeCustChange	2397
2.62.1.ST-AuthorizeCustChange-Req-Full-MSG.xsd	2397
2.62.2.ST-AuthorizeCustChange-Req-IO-MSG.xsd	2415
2.62.3.ST-AuthorizeCustChange-Res-Full-MSG.xsd	2423
2.62.4.ST-AuthorizeCustChange-Res-PK-MSG.xsd	2443
2.63.CloseAddressCode	2452
2.63.1.ST-CloseAddressCode-Req-Full-MSG.xsd	2452
2.63.2.ST-CloseAddressCode-Req-IO-MSG.xsd	2464
2.63.3.ST-CloseAddressCode-Res-Full-MSG.xsd	2472
2.63.4.ST-CloseAddressCode-Res-PK-MSG.xsd	2485
2.64.CloseCustChange	2495
2.64.1.ST-CloseCustChange-Req-Full-MSG.xsd	2495
2.64.2.ST-CloseCustChange-Req-IO-MSG.xsd	2513
2.64.3.ST-CloseCustChange-Res-Full-MSG.xsd	2521
2.64.4.ST-CloseCustChange-Res-PK-MSG.xsd	2541
2.65.CreateAddressCode	2550
2.65.1.ST-CreateAddressCode-Req-Full-MSG.xsd	2550
2.65.2.ST-CreateAddressCode-Req-IO-MSG.xsd	2562
2.65.3.ST-CreateAddressCode-Res-Full-MSG.xsd	2572
2.65.4.ST-CreateAddressCode-Res-PK-MSG.xsd	2586
2.66.CreateCustChange	2597
2.66.1.ST-CreateCustChange-Req-Full-MSG.xsd	2597
2.66.2.ST-CreateCustChange-Req-IO-MSG.xsd	2616

2.66.3.ST-CreateCustChange-Res-Full-MSG.xsd	2627
2.66.4.ST-CreateCustChange-Res-PK-MSG.xsd	2647
2.67.DeleteAddressCode	2660
2.67.1.ST-DeleteAddressCode-Req-Full-MSG.xsd	2660
2.67.2.ST-DeleteAddressCode-Req-IO-MSG.xsd	2672
2.67.3.ST-DeleteAddressCode-Res-Full-MSG.xsd	2679
2.67.4.ST-DeleteAddressCode-Res-PK-MSG.xsd	2692
2.68.DeleteCustChange	2701
2.68.1.ST-DeleteCustChange-Req-Full-MSG.xsd	2701
2.68.2.ST-DeleteCustChange-Req-IO-MSG.xsd	2719
2.68.3.ST-DeleteCustChange-Res-Full-MSG.xsd	2726
2.68.4.ST-DeleteCustChange-Res-PK-MSG.xsd	2746
2.69.ModifyAddressCode	2754
2.69.1.ST-ModifyAddressCode-Req-Full-MSG.xsd	2754
2.69.2.ST-ModifyAddressCode-Req-IO-MSG.xsd	2766
2.69.3.ST-ModifyAddressCode-Res-Full-MSG.xsd	2777
2.69.4.ST-ModifyAddressCode-Res-PK-MSG.xsd	2791
2.70.QueryAddressCode	2804
2.70.1.ST-QueryAddressCode-Req-IO-MSG.xsd	2804
2.70.2.ST-QueryAddressCode-Res-Full-MSG.xsd	2811
2.71.QueryCntryCodes	2825
2.71.1.ST-QueryCntryCodes-Req-IO-MSG.xsd	2825
2.71.2.ST-QueryCntryCodes-Res-Full-MSG.xsd	2831
2.72.QueryCustChange	2846
2.72.1.ST-QueryCustChange-Req-IO-MSG.xsd	2846
2.72.2.ST-QueryCustChange-Res-Full-MSG.xsd	2853
2.73.QueryLCHoliday	2873
2.73.1.ST-QueryLCHoliday-Req-IO-MSG.xsd	2873
2.73.2.ST-QueryLCHoliday-Res-Full-MSG.xsd	2880
2.74.QueryLOCHL	2895
2.74.1.ST-QueryLOCHL-Req-IO-MSG.xsd	2895
2.74.2.ST-QueryLOCHL-Res-Full-MSG.xsd	2902
2.75.ReopenAddressCode	2915
2.75.1.ST-ReopenAddressCode-Req-Full-MSG.xsd	2915
2.75.2.ST-ReopenAddressCode-Req-IO-MSG.xsd	2927
2.75.3.ST-ReopenAddressCode-Res-Full-MSG.xsd	2934
2.75.4.ST-ReopenAddressCode-Res-PK-MSG.xsd	2948

1. Background

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data. The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs. The integration needs supported by the Gateway can be broadly categorized from the perspective of Gateway as follows

1. Inbound application integration :

This is used when any external system needs to add, modify or query information within FLEXCUBE UBS

2. Outbound application integration :

This is used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS

The following sections provide detailed XSD documentation of all operations available in FCUBSCoreService of Core Module

2. FCUBSCoreService

2.1.AuthorizeCSMBPLinkage

2.1.1.CO-AuthorizeCSMBPLinkage-Req-Full-MSG.xsd

AUTHORIZECSMBPLINKAGE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Csm-Ben-Master-C-Full

CSM

CUSTOMER_NO

CSM_DESC

CUSTOMER_NAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Cotm-Csm-Ben-Detail-C

BEN_START_DT

MODULE

BEN_PLAN_TYPE

BEN_PLAN_ID

BEN_PLAN_DESC

PRIORITYNO

BEN_END_DT

AUTHORIZECSMBPLINKAGE_FSFS_REQ

Attribute	Description
Name	AUTHORIZECSMBPLINKAGE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
------------------	--------------------

Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE. ⁴	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Cotm-Csm-Ben-Master-C-Full
Datatype	
Description	

CSM

Attribute	Description				
Name	CSM				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

CUSTOMER_NO

Attribute	Description				
Name	CUSTOMER_NO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

CSM_DESC

Attribute	Description				
Name	CSM_DESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>255</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

CUSTOMER_NAME

Attribute	Description				
Name	CUSTOMER_NAME				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>255</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

MAKER

Attribute	Description
-----------	-------------

Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description
------------------	--------------------

Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	totalDigits	4
	Description	

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	1
	Description	

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	1
	Description	

Cotm-Csm-Ben-Detail-C

Attribute	Description	
Name	Cotm-Csm-Ben-Detail-C	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

BEN_START_DT

Attribute	Description	
Name	BEN_START_DT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

BEN_PLAN_TYPE

Attribute	Description	
Name	BEN_PLAN_TYPE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

PRIORITYNO

Attribute	Description	
Name	PRIORITYNO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

BEN_END_DT

Attribute	Description	
Name	BEN_END_DT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

2.1.2.CO-AuthorizeCSMBPLinkage-Req-IO-MSG.xsd

AUTHORIZECSMBPLINKAGE_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Csm-Ben-Master-C-IO

CSM

CUSTOMER_NO

CHECKER

CHECKERSTAMP

MODNO

AUTHORIZECSMBPLINKAGE_IOPK_REQ

Attribute	Description
Name	AUTHORIZECSMBPLINKAGE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Cotm-Csm-Ben-Master-C-IO

Attribute	Description	
------------------	--------------------	--

Name	Cotm-Csm-Ben-Master-C-IO
Datatype	
Description	

CSM

Attribute	Description	
Name	CSM	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description
Name	MODNO

Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

2.1.3.CO-AuthorizeCSMBPLinkage-Res-Full-MSG.xsd

AUTHORIZECSMBPLINKAGE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Csm-Ben-Master-C-Full

CSM

CUSTOMER_NO

CSM_DESC

CUSTOMER_NAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Cotm-Csm-Ben-Detail-C

BEN_START_DT

MODULE

BEN_PLAN_TYPE

BEN_PLAN_ID

BEN_PLAN_DESC

PRIORITYNO

BEN_END_DT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZECSMBPLINKAGE_FSFS_RES

Attribute	Description
Name	AUTHORIZECSMBPLINKAGE_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
------------------	--------------------

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotm-Csm-Ben-Master-C-Full

Attribute	Description
Name	Cotm-Csm-Ben-Master-C-Full
Datatype	
Description	

CSM

Attribute	Description				
Name	CSM				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

CUSTOMER_NO

Attribute	Description				
Name	CUSTOMER_NO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

CSM_DESC

Attribute	Description				
Name	CSM_DESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	255

CUSTOMER_NAME

Attribute	Description	
Name	CUSTOMER_NAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

Cotm-Csm-Ben-Detail-C

Attribute	Description	
Name	Cotm-Csm-Ben-Detail-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BEN_START_DT

Attribute	Description	
Name	BEN_START_DT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	2

BEN_PLAN_TYPE

Attribute	Description	
Name	BEN_PLAN_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_ID

Attribute	Description
------------------	--------------------

Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

PRIORITYNO

Attribute	Description	
Name	PRIORITYNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

BEN_END_DT

Attribute	Description	
Name	BEN_END_DT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String

Description	
-------------	--

2.1.4.CO-AuthorizeCSMBPLinkage-Res-PK-MSG.xsd

AUTHORIZECSMBPLINKAGE_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Csm-Ben-Master-C-PK

CUSTOMER_NO

CSM

Cotm-Csm-Ben-Master-C-IO

CSM

CUSTOMER_NO

CHECKER

CHECKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZECSMBPLINKAGE_IOPK_RES

Attribute	Description
Name	AUTHORIZECSMBPLINKAGE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Cotm-Csm-Ben-Master-C-PK

Attribute	Description
------------------	--------------------

Name	Cotm-Csm-Ben-Master-C-PK
Datatype	
Description	

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

CSM

Attribute	Description	
Name	CSM	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

Cotm-Csm-Ben-Master-C-IO

Attribute	Description
Name	Cotm-Csm-Ben-Master-C-IO
Datatype	
Description	

CSM

Attribute	Description	
Name	CSM	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.2.AuthorizeRPBenfPlan

2.2.1.CO-AuthorizeRPBenfPlan-Req-Full-MSG.xsd

AUTHORIZERP BENFPLAN_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Benefit-Master-Full

BEN_PLAN_ID

BEN_PLAN_DESC

MODULE

PRIORITY_NO

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Cotms-Benefit-Details

PRODUCT

PRICE_COMP_TYPE

PRICE_COMP

BEN_TYPE

VAR_TYPE

VAR_CCY

VAR_VALUE

VAR_RULE

MAX_VALUE

MIN_VALUE

CCY_CODE

UDFDETAILS

FLDNAM

FLDVAL

AUTHORIZERP BENFPLAN_FSFS_REQ

Attribute	Description
Name	AUTHORIZERP BENFPLAN_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Benefit-Master-Full

Attribute	Description
Name	Cotms-Benefit-Master-Full
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description				
Name	BEN_PLAN_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

BEN_PLAN_DESC

Attribute	Description				
Name	BEN_PLAN_DESC				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

MODULE

Attribute	Description				
Name	MODULE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>2</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	2
Restrictions	Description				
maxLength	2				

PRIORITY_NO

Attribute	Description	
Name	PRIORITY_NO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	5

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute		Description	
Name	CHECKERSTAMP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

MODNO

Attribute		Description	
Name	MODNO		
Datatype	Decimal		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	totalDigits	4	

TXNSTAT

Attribute		Description	
Name	TXNSTAT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1	

AUTHSTAT

Attribute		Description	
Name	AUTHSTAT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1	

Attribute	Description	
Name	Cotms-Benefit-Details	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

PRODUCT

Attribute	Description	
Name	PRODUCT	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	4

PRICE_COMP_TYPE

Attribute	Description	
Name	PRICE_COMP_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	I,C,F,M

PRICE_COMP

Attribute	Description	
Name	PRICE_COMP	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_TYPE

Attribute	Description	
Name	BEN_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	V,W,

VAR_TYPE

Attribute	Description	
Name	VAR_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	F,A,P,V,T,N,

VAR_CCY

Attribute	Description	
Name	VAR_CCY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

VAR_VALUE

Attribute	Description	
Name	VAR_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

VAR_RULE

Attribute	Description	
Name	VAR_RULE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

MAX_VALUE

Attribute	Description	
Name	MAX_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

MIN_VALUE

Attribute	Description	
Name	MIN_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

CCY_CODE

Attribute	Description	
Name	CCY_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.2.2.CO-AuthorizeRPBenfPlan-Req-IO-MSG.xsd

AUTHORIZERP BENFPLAN_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Benefit-Master-IO

BEN_PLAN_ID

MODULE

CHECKER

CHECKERSTAMP

MODNO

AUTHORIZERP BENFPLAN_IOPK_REQ

Attribute	Description
Name	AUTHORIZERP BENFPLAN_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Cotms-Benefit-Master-IO

Attribute		Description
------------------	--	--------------------

Name	Cotms-Benefit-Master-IO
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	2

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description
Name	MODNO

Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

2.2.3.CO-AuthorizeRPBenfPlan-Res-Full-MSG.xsd

AUTHORIZERP BENFPLAN_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Benefit-Master-Full

BEN_PLAN_ID

BEN_PLAN_DESC

MODULE

PRIORITY_NO

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Cotms-Benefit-Details

PRODUCT

PRICE_COMP_TYPE

PRICE_COMP

BEN_TYPE

VAR_TYPE

VAR_CCY

VAR_VALUE

VAR_RULE

MAX_VALUE

MIN_VALUE

CCY_CODE

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

AUTHORIZERPBFPLAN_FSFS_RES

Attribute	Description
Name	AUTHORIZERPBFPLAN_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute		Description	
Name	SOURCE_USERID		
Datatype	String		
Description	This is the user id in the Source system who is performing the action.		
Attribute	Attribute		Description
	minOccurs	0	

DESTINATION

Attribute		Description	
Name	DESTINATION		
Datatype	String		
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute		Description	
Name	MULTITRIPID		
Datatype	String		
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute		Description	
Name	FUNCTIONID		
Datatype	String		
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.		
Attribute	Attribute		Description
	minOccurs	0	

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Benefit-Master-Full

Attribute	Description
Name	Cotms-Benefit-Master-Full
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description				
Name	BEN_PLAN_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

BEN_PLAN_DESC

Attribute	Description
-----------	-------------

Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	2

PRIORITY_NO

Attribute	Description	
Name	PRIORITY_NO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	5

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Cotms-Benefit-Details

Attribute	Description	
Name	Cotms-Benefit-Details	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

PRODUCT

Attribute	Description	
Name	PRODUCT	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	4

PRICE_COMP_TYPE

Attribute	Description	
Name	PRICE_COMP_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	I,C,F,M

PRICE_COMP

Attribute	Description
------------------	--------------------

Name	PRICE_COMP	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_TYPE

Attribute	Description	
Name	BEN_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	V,W,

VAR_TYPE

Attribute	Description	
Name	VAR_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	F,A,P,V,T,N,

VAR_CCY

Attribute	Description	
Name	VAR_CCY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

VAR_VALUE

Attribute	Description	
Name	VAR_VALUE	
Datatype	Decimal	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

VAR_RULE

Attribute	Description	
Name	VAR_RULE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MAX_VALUE

Attribute	Description	
Name	MAX_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

MIN_VALUE

Attribute	Description	
Name	MIN_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

CCY_CODE

Attribute	Description	
Name	CCY_CODE	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxOccurs	unbounded

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String

Description	
-------------	--

2.2.4.CO-AuthorizeRPBenfPlan-Res-PK-MSG.xsd

AUTHORIZERP BENFPLAN_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Benefit-Master-PK

BEN_PLAN_ID

MODULE

Cotms-Benefit-Master-IO

BEN_PLAN_ID

MODULE

CHECKER

CHECKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZERPBFPLAN_IOPK_RES

Attribute	Description
Name	AUTHORIZERPBFPLAN_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Cotms-Benefit-Master-PK

Attribute	Description
------------------	--------------------

Name	Cotms-Benefit-Master-PK
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	2

Cotms-Benefit-Master-IO

Attribute	Description
Name	Cotms-Benefit-Master-IO
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	2

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String

Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.3.AuthorizeRPElgPlan

2.3.1.CO-AuthorizeRPElgPlan-Req-Full-MSG.xsd

[AUTHORIZERPELGPLAN_FSFS_REQ](#)

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Elplan-Master-Full

EL_PLAN_CODE

EL_PLAN_DESC

EL_CONDITION

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Cotms-Elplan-Rde

RDE_CODE

RDE_PARAM_VAL

UDFDETAILS

FLDNAM

FLDVAL

AUTHORIZERPELGPLAN_FSFS_REQ

Attribute	Description
Name	AUTHORIZERPELGPLAN_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

ORACLE®

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Elplan-Master-Full

Attribute	Description
Name	Cotms-Elplan-Master-Full
Datatype	
Description	

EL_PLAN_CODE

Attribute	Description
------------------	--------------------

Name	EL_PLAN_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

EL_PLAN_DESC

Attribute	Description	
Name	EL_PLAN_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

EL_CONDITION

Attribute	Description	
Name	EL_CONDITION	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	4000

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Cotms-Elplan-Rde

Attribute	Description	
Name	Cotms-Elplan-Rde	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

RDE_CODE

Attribute	Description	
Name	RDE_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

RDE_PARAM_VAL

Attribute	Description	
Name	RDE_PARAM_VAL	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.3.2.CO-AuthorizeRPElgPlan-Req-IO-MSG.xsd

AUTHORIZERPELGPLAN_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Elplan-Master-IO

EL_PLAN_CODE

CHECKER

CHECKERSTAMP

MODNO

AUTHORIZERPELGPLAN_IOPK_REQ

Attribute	Description
Name	AUTHORIZERPELGPLAN_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within EL EXCLUDE LIBS. In

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Elplan-Master-IO

Attribute	Description
Name	Cotms-Elplan-Master-IO
Datatype	
Description	

EL_PLAN_CODE

Attribute	Description				
Name	EL_PLAN_CODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

2.3.3.CO-AuthorizeRPElgPlan-Res-Full-MSG.xsd

AUTHORIZERPELGPLAN_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Elplan-Master-Full

EL_PLAN_CODE

EL_PLAN_DESC

EL_CONDITION

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Cotms-Elplan-Rde

RDE_CODE

RDE_PARAM_VAL

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZERPELGPLAN_FSFS_RES

Attribute	Description
-----------	-------------

Name	AUTHORIZERPELGPLAN_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	
	Description	
	maxLength	12
pattern	[A-Z_0-9]*	

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	
	Description	
	length	3
pattern	[a-zA-Z_0-9]{3}	

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	

Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	

Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Cotms-Elplan-Master-Full

Attribute	Description	
Name	Cotms-Elplan-Master-Full	
Datatype		
Description		

EL_PLAN_CODE

Attribute	Description	
Name	EL_PLAN_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

EL_PLAN_DESC

Attribute	Description	
Name	EL_PLAN_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

EL_CONDITION

Attribute	Description	
Name	EL_CONDITION	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4000

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute		Description	
Name	CHECKERSTAMP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

MODNO

Attribute		Description	
Name	MODNO		
Datatype	Decimal		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	totalDigits	4	

TXNSTAT

Attribute		Description	
Name	TXNSTAT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1	

AUTHSTAT

Attribute		Description	
Name	AUTHSTAT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1	

Attribute	Description	
Name	Cotms-Elplan-Rde	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

RDE_CODE

Attribute	Description	
Name	RDE_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

RDE_PARAM_VAL

Attribute	Description	
Name	RDE_PARAM_VAL	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.3.4.CO-AuthorizeRPElgPlan-Res-PK-MSG.xsd

AUTHORIZERPELGPLAN_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTIRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Elplan-Master-PK

EL_PLAN_CODE

Cotms-Elplan-Master-IO

EL_PLAN_CODE

CHECKER

CHECKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZERPELGPLAN_IOPK_RES

Attribute	Description
Name	AUTHORIZERPELGPLAN_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
------------------	--------------------

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Elplan-Master-PK

Attribute	Description
Name	Cotms-Elplan-Master-PK
Datatype	
Description	

EL_PLAN_CODE

Attribute	Description				
Name	EL_PLAN_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

Cotms-Elplan-Master-IO

Attribute	Description
Name	Cotms-Elplan-Master-IO
Datatype	
Description	

EL_PLAN_CODE

Attribute	Description				
Name	EL_PLAN_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

CHECKER

Attribute	Description
-----------	-------------

Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.4.AuthorizeRPErBenPlan

2.4.1.CO-AuthorizeRPErBenPlan-Req-Full-MSG.xsd

[AUTHORIZERPERBENPLAN_FSFS_REQ](#)

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Ben-Exch-Master-C-Full

BEN_PLAN_ID

BEN_PLAN_DESC

PRIORITY_NO

APPLY_SPREAD_AS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Cotm-Ben-Exch-Detail-C

BUY_SPREAD

SALESPRD

BEN_PLAN_ID

RATTYP

VAR_CCY1

VAR_CCY2

UDFDETAILS

FLDNAM

FLDVAL

AUTHORIZERPERBENPLAN_FSFS_REQ

Attribute	Description
Name	AUTHORIZERPERBENPLAN_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Cotm-Ben-Exch-Master-C-Full

Attribute		Description
------------------	--	--------------------

Name	Cotm-Ben-Exch-Master-C-Full
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions	Restrictions	
	Description	
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Restrictions	Restrictions	
	Description	
	maxLength	105

PRIORITY_NO

Attribute	Description	
Name	PRIORITY_NO	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	5

APPLY_SPREAD_AS

Attribute	Description	
Name	APPLY_SPREAD_AS	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	enumeration	D,V

MAKER

Attribute	Description
Name	MAKER

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description
Name	MODNO

Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Cotm-Ben-Exch-Detail-C

Attribute	Description	
Name	Cotm-Ben-Exch-Detail-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BUY_SPREAD

Attribute	Description	
Name	BUY_SPREAD	
Datatype	Decimal	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

SALESPRD

Attribute	Description	
Name	SALESPRD	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

RATTYP

Attribute	Description	
Name	RATTYP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	8

VAR_CCY1

Attribute	Description	
Name	VAR_CCY1	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	3

VAR_CCY2

Attribute	Description				
Name	VAR_CCY2				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

FLDNAM

Attribute	Description						
Name	FLDNAM						
Datatype	String						
Description	Indicates Field Name						
Restrictions							
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	105	minLength	1
Restrictions	Description						
maxLength	105						
minLength	1						

FLDVAL

Attribute	Description						
Name	FLDVAL						
Datatype	String						
Description	Indicates Field Value						
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions							
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></tbody></table>	Restrictions	Description	maxLength	150	minLength	0
Restrictions	Description						
maxLength	150						
minLength	0						

2.4.2.CO-AuthorizeRPERBenPlan-Req-IO-MSG.xsd

AUTHORIZERPERBENPLAN_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cotm-Ben-Exch-Master-C-IO
BEN_PLAN_ID
CHECKER
CHECKERSTAMP
MODNO

AUTHORIZERPERBENPLAN_IOPK_REQ

Attribute	Description
Name	AUTHORIZERPERBENPLAN_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotm-Ben-Exch-Master-C-IO

Attribute	Description
Name	Cotm-Ben-Exch-Master-C-IO
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description				
Name	BEN_PLAN_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

2.4.3.CO-AuthorizeRPErBenPlan-Res-Full-MSG.xsd

AUTHORIZERPERBENPLAN_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Ben-Exch-Master-C-Full

BEN_PLAN_ID

BEN_PLAN_DESC

PRIORITY_NO

APPLY_SPREAD_AS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Cotm-Ben-Exch-Detail-C

BUY_SPREAD

SALESPRD

BEN_PLAN_ID

RATTYP

VAR_CCY1

VAR_CCY2

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZERPERBENPLAN_FSFS_RES

Attribute	Description
Name	AUTHORIZERPERBENPLAN_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0
	maxOccurs		unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Cotm-Ben-Exch-Master-C-Full

Attribute		Description	
Name		Cotm-Ben-Exch-Master-C-Full	
Datatype			
Description			

BEN_PLAN_ID

Attribute		Description	
Name		BEN_PLAN_ID	
Datatype		String	
Description			
Restrictions	Restrictions		Description
	maxLength		35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

PRIORITY_NO

Attribute	Description	
Name	PRIORITY_NO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	5

APPLY_SPREAD_AS

Attribute	Description	
Name	APPLY_SPREAD_AS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	D,V

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Cotm-Ben-Exch-Detail-C

Attribute	Description	
Name	Cotm-Ben-Exch-Detail-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BUY_SPREAD

Attribute	Description	
Name	BUY_SPREAD	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

SALESPRD

Attribute	Description	
Name	SALESPRD	
Datatype	Decimal	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

RATTYP

Attribute	Description	
Name	RATTYP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	8

VAR_CCY1

Attribute	Description	
Name	VAR_CCY1	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	3

VAR_CCY2

Attribute	Description	
Name	VAR_CCY2	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	3

UDFDETAILS

Attribute	Description
------------------	--------------------

Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	
		Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	
		Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	
		Description
	minOccurs	0
Restrictions	Restrictions	
		Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	
		Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	
		Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.4.4.CO-AuthorizeRPERBenPlan-Res-PK-MSG.xsd

AUTHORIZERPERBENPLAN_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cotm-Ben-Exch-Master-C-PK
BEN_PLAN_ID
Cotm-Ben-Exch-Master-C-IO
BEN_PLAN_ID
CHECKER
CHECKERSTAMP
MODNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING

WCODE

WDESC

AUTHORIZERPERBENPLAN_IOPK_RES

Attribute	Description
Name	AUTHORIZERPERBENPLAN_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

FCUBS_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description			

Cotm-Ben-Exch-Master-C-PK

Attribute		Description	
Name	Cotm-Ben-Exch-Master-C-PK		
Datatype			
Description			

BEN_PLAN_ID

Attribute		Description	
Name	BEN_PLAN_ID		
Datatype	String		
Description			
Restrictions	Restrictions		Description
	maxLength	35	

Cotm-Ben-Exch-Master-C-IO

Attribute	Description
Name	Cotm-Ben-Exch-Master-C-IO
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description				
Name	BEN_PLAN_ID				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

CHECKERSTAMP

Attribute	Description				
Name	CHECKERSTAMP				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

MODNO

Attribute	Description				
Name	MODNO				
Datatype	Decimal				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		

Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.5.AuthorizeRPSchMntc

2.5.1.CO-AuthorizeRPSchMntc-Req-Full-MSG.xsd

AUTHORIZERPSCHMNTC_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Scheme-Master-Full

SCHEME_ID1

SCHEME_DESC

SC_START_DT

SC_END_DT

BEN_VALID_PERIOD

BEN_VALID_BASIS

VALID_TYPE

APPLY_FOR

EXECUTABLE_TYPE

RENEW_TYPE

SCHEME_RP_DESC

BEN_EXPIRY

SCHEME_STATUS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Elig

EL_PLAN_CODE

EL_REV_FREQ

FIRST_REV_DT

LAST_REV_DT

NEXT_REV_DT

Cotms-Scheme-Detail

BEN_PLAN_ID

BEN_PLAN_DESC

UDFDETAILS

FLDNAM

FLDVAL

AUTHORIZERPSCHMNTC_FSFS_REQ

Attribute	Description
Name	AUTHORIZERPSCHMNTC_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute			
		Attribute	Description
		minOccurs	0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute			
		Attribute	Description
		minOccurs	0
		maxOccurs	unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Cotms-Scheme-Master-Full

Attribute		Description	
Name		Cotms-Scheme-Master-Full	
Datatype			
Description			

SCHEME_ID1

Attribute		Description	
Name		SCHEME_ID1	
Datatype		String	
Description			
Restrictions			
		Restrictions	Description
		maxLength	35

SCHEME_DESC

Attribute	Description	
Name	SCHEME_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

SC_START_DT

Attribute	Description	
Name	SC_START_DT	
Datatype	String	
Description		

SC_END_DT

Attribute	Description	
Name	SC_END_DT	
Datatype	String	
Description		

BEN_VALID_PERIOD

Attribute	Description	
Name	BEN_VALID_PERIOD	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

BEN_VALID_BASIS

Attribute	Description	
Name	BEN_VALID_BASIS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	D,M,Y,

VALID_TYPE

Attribute	Description	
Name	VALID_TYPE	
Datatype	String	

Description					
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>enumeration</td> <td>O,R,P,</td> </tr> </table>	Restrictions	Description	enumeration	O,R,P,
Restrictions	Description				
enumeration	O,R,P,				

APPLY_FOR

Attribute	Description				
Name	APPLY_FOR				
Datatype	String				
Description					
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>enumeration</td> <td>N,A,E,</td> </tr> </table>	Restrictions	Description	enumeration	N,A,E,
Restrictions	Description				
enumeration	N,A,E,				

EXECUTABLE_TYPE

Attribute	Description				
Name	EXECUTABLE_TYPE				
Datatype	String				
Description					
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>enumeration</td> <td>M,A,</td> </tr> </table>	Restrictions	Description	enumeration	M,A,
Restrictions	Description				
enumeration	M,A,				

RENEW_TYPE

Attribute	Description				
Name	RENEW_TYPE				
Datatype	String				
Description					
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>enumeration</td> <td>B,S,</td> </tr> </table>	Restrictions	Description	enumeration	B,S,
Restrictions	Description				
enumeration	B,S,				

SCHEME_RP_DESC

Attribute	Description				
Name	SCHEME_RP_DESC				
Datatype	String				
Description					
Attribute	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>maxLength</td> <td>1000</td> </tr> </table>	Restrictions	Description	maxLength	1000
Restrictions	Description				
maxLength	1000				

BEN_EXPIRY

Attribute	Description
Name	BEN_EXPIRY
Datatype	String
Description	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

SCHEME_STATUS

Attribute	Description	
Name	SCHEME_STATUS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	A,E

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

Elig

Attribute	Description	
Name	Elig	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

EL_PLAN_CODE

Attribute	Description	
Name	EL_PLAN_CODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	35

EL_REV_FREQ

Attribute	Description	
Name	EL_REV_FREQ	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	D,W,F,M,Q,H,Y

FIRST_REV_DT

Attribute	Description
Name	FIRST_REV_DT
Datatype	String
Description	

LAST_REV_DT

Attribute	Description	
Name	LAST_REV_DT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

NEXT_REV_DT

Attribute	Description	
Name	NEXT_REV_DT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Cotms-Scheme-Detail

Attribute	Description	
Name	Cotms-Scheme-Detail	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.5.2.CO-AuthorizeRPSchMntc-Req-IO-MSG.xsd

AUTHORIZERPSCHMNTC_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Scheme-Master-IO

SCHEME_ID1

CHECKER

CHECKERSTAMP

MODNO

AUTHORIZERPSCHMNTC_IOPK_REQ

Attribute	Description
Name	AUTHORIZERPSCHMNTC_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Cotms-Scheme-Master-IO

Attribute		Description
------------------	--	--------------------

Name	Cotms-Scheme-Master-IO
Datatype	
Description	

SCHEME_ID1

Attribute	Description	
Name	SCHEME_ID1	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

AUTHORIZERPSCHMNTC_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Scheme-Master-Full

SCHEME_ID1

SCHEME_DESC

SC_START_DT

SC_END_DT

BEN_VALID_PERIOD

BEN_VALID_BASIS

VALID_TYPE

APPLY_FOR
EXECUTABLE_TYPE
RENEW_TYPE
SCHEME_RP_DESC
BEN_EXPIRY
SCHEME_STATUS
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Elig
EL_PLAN_CODE
EL_REV_FREQ
FIRST_REV_DT
LAST_REV_DT
NEXT_REV_DT
Cotms-Scheme-Detail
BEN_PLAN_ID
BEN_PLAN_DESC
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE

AUTHORIZERPSCHMNTC_FSFS_RES

Attribute	Description
Name	AUTHORIZERPSCHMNTC_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute		Description	
Name	SOURCE_USERID		
Datatype	String		
Description	This is the user id in the Source system who is performing the action.		
Attribute	Attribute		Description
	minOccurs	0	

DESTINATION

Attribute		Description	
Name	DESTINATION		
Datatype	String		
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute		Description	
Name	MULTITRIPID		
Datatype	String		
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute		Description	
Name	FUNCTIONID		
Datatype	String		
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.		
Attribute	Attribute		Description
	minOccurs	0	

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Scheme-Master-Full

Attribute	Description
Name	Cotms-Scheme-Master-Full
Datatype	
Description	

SCHEME_ID1

Attribute	Description				
Name	SCHEME_ID1				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

SCHEME_DESC

Attribute	Description
-----------	-------------

Name	SCHEME_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

SC_START_DT

Attribute	Description	
Name	SC_START_DT	
Datatype	String	
Description		

SC_END_DT

Attribute	Description	
Name	SC_END_DT	
Datatype	String	
Description		

BEN_VALID_PERIOD

Attribute	Description	
Name	BEN_VALID_PERIOD	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

BEN_VALID_BASIS

Attribute	Description	
Name	BEN_VALID_BASIS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	D,M,Y,

VALID_TYPE

Attribute	Description	
Name	VALID_TYPE	
Datatype	String	
Description		

Restrictions		
	Restrictions	Description
	enumeration	O,R,P,

APPLY_FOR

Attribute	Description	
Name	APPLY_FOR	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	N,A,E,

EXECUTABLE_TYPE

Attribute	Description	
Name	EXECUTABLE_TYPE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	M,A,

RENEW_TYPE

Attribute	Description	
Name	RENEW_TYPE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	B,S,

SCHEME_RP_DESC

Attribute	Description	
Name	SCHEME_RP_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

BEN_EXPIRY

Attribute	Description	
Name	BEN_EXPIRY	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

SCHEME_STATUS

Attribute	Description	
Name	SCHEME_STATUS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	A,E

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

Elig

Attribute	Description	
Name	Elig	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

EL_PLAN_CODE

Attribute	Description	
Name	EL_PLAN_CODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	35

EL_REV_FREQ

Attribute	Description	
Name	EL_REV_FREQ	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	D,W,F,M,Q,H,Y

FIRST_REV_DT

Attribute	Description
Name	FIRST_REV_DT
Datatype	String
Description	

LAST_REV_DT

Attribute	Description	
Name	LAST_REV_DT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

NEXT_REV_DT

Attribute	Description	
Name	NEXT_REV_DT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Cotms-Scheme-Detail

Attribute	Description	
Name	Cotms-Scheme-Detail	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	

Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.5.4.CO-AuthorizeRPSchMntc-Res-PK-MSG.xsd

AUTHORIZERPSCHMNTC_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
 PARAM
 NAME
 VALUE
FCUBS_BODY
 Cotms-Scheme-Master-PK
 SCHEME_ID1
 Cotms-Scheme-Master-IO
 SCHEME_ID1
 CHECKER
 CHECKERSTAMP
 MODNO
FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

AUTHORIZERPSCHMNTC_IOPK_RES

Attribute	Description
Name	AUTHORIZERPSCHMNTC_IOPK_RES

Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	

Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	

Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Cotms-Scheme-Master-PK

Attribute	Description	
Name	Cotms-Scheme-Master-PK	
Datatype		
Description		

SCHEME_ID1

Attribute	Description	
Name	SCHEME_ID1	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	35

Cotms-Scheme-Master-IO

Attribute	Description	
Name	Cotms-Scheme-Master-IO	
Datatype		
Description		

SCHEME_ID1

Attribute	Description	

Name	SCHEME_ID1	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		

Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.6.CreateCSMBPLinkage

2.6.1.CO-CreateCSMBPLinkage-Req-Full-MSG.xsd

CREATECSMBPLINKAGE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Csm-Ben-Master-C-Full

CSM

CUSTOMER_NO

CSM_DESC

CUSTOMER_NAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Cotm-Csm-Ben-Detail-C

BEN_START_DT

MODULE

BEN_PLAN_TYPE

BEN_PLAN_ID

BEN_PLAN_DESC

PRIORITYNO

BEN_END_DT

CREATECSMBPLINKAGE_FSFS_REQ

Attribute	Description
Name	CREATECSMBPLINKAGE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description

Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nullable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotm-Csm-Ben-Master-C-Full

Attribute	Description
Name	Cotm-Csm-Ben-Master-C-Full
Datatype	
Description	

CSM

Attribute	Description				
Name	CSM				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

CUSTOMER_NO

Attribute	Description				
Name	CUSTOMER_NO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

CSM_DESC

Attribute	Description				
Name	CSM_DESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>255</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

CUSTOMER_NAME

Attribute	Description
Name	CUSTOMER_NAME
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Cotm-Csm-Ben-Detail-C

Attribute	Description	
Name	Cotm-Csm-Ben-Detail-C	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BEN_START_DT

Attribute	Description	
Name	BEN_START_DT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

BEN_PLAN_TYPE

Attribute	Description	
Name	BEN_PLAN_TYPE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description
------------------	--------------------

Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

PRIORITYNO

Attribute	Description	
Name	PRIORITYNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

BEN_END_DT

Attribute	Description	
Name	BEN_END_DT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

2.6.2.CO-CreateCSMBPLinkage-Req-IO-MSG.xsd

CREATECSMBPLINKAGE_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Csm-Ben-Master-C-IO

CSM

CUSTOMER_NO

Cotm-Csm-Ben-Detail-C

BEN_START_DT

BEN_PLAN_ID

BEN_END_DT

CREATECSMBPLINKAGE_IOPK_REQ

Attribute	Description
Name	CREATECSMBPLINKAGE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotm-Csm-Ben-Master-C-IO

Attribute	Description
Name	Cotm-Csm-Ben-Master-C-IO
Datatype	
Description	

CSM

Attribute	Description				
Name	CSM				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

CUSTOMER_NO

Attribute	Description				
Name	CUSTOMER_NO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

Cotm-Csm-Ben-Detail-C

Attribute	Description						
Name	Cotm-Csm-Ben-Detail-C						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

BEN_START_DT

Attribute	Description				
Name	BEN_START_DT				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

BEN_PLAN_ID

Attribute	Description				
Name	BEN_PLAN_ID				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

BEN_END_DT

Attribute	Description				
Name	BEN_END_DT				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

2.6.3.CO-CreateCSMBPLinkage-Res-Full-MSG.xsd

CREATECSMBPLINKAGE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Csm-Ben-Master-C-Full

CSM

CUSTOMER_NO

CSM_DESC

CUSTOMER_NAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Cotm-Csm-Ben-Detail-C

BEN_START_DT

MODULE

BEN_PLAN_TYPE

BEN_PLAN_ID

BEN_PLAN_DESC

PRIORITYNO

BEN_END_DT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATECSMBPLINKAGE_FSFS_RES

Attribute	Description
Name	CREATECSMBPLINKAGE_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotm-Csm-Ben-Master-C-Full

Attribute	Description
Name	Cotm-Csm-Ben-Master-C-Full
Datatype	
Description	

CSM

Attribute	Description
------------------	--------------------

Name	CSM	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

CSM_DESC

Attribute	Description	
Name	CSM_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

CUSTOMER_NAME

Attribute	Description	
Name	CUSTOMER_NAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Cotm-Csm-Ben-Detail-C

Attribute	Description	
Name	Cotm-Csm-Ben-Detail-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BEN_START_DT

Attribute	Description	
Name	BEN_START_DT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

MODULE

Attribute	Description
------------------	--------------------

Name	MODULE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

BEN_PLAN_TYPE

Attribute	Description	
Name	BEN_PLAN_TYPE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

PRIORITYNO

Attribute	Description	
Name	PRIORITYNO	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

BEN_END_DT

Attribute	Description	
Name	BEN_END_DT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description
------------------	--------------------

Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.6.4.CO-CreateCSMBPLinkage-Res-PK-MSG.xsd

CREATECSMBPLINKAGE_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Csm-Ben-Master-C-PK

CUSTOMER_NO

CSM

Cotm-Csm-Ben-Master-C-IO

CSM

CUSTOMER_NO

Cotm-Csm-Ben-Detail-C

BEN_START_DT

BEN_PLAN_ID

BEN_END_DT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATECSMBPLINKAGE_IOPK_RES

Attribute	Description
Name	CREATECSMBPLINKAGE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotm-Csm-Ben-Master-C-PK

Attribute	Description
Name	Cotm-Csm-Ben-Master-C-PK
Datatype	
Description	

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description		
Restrictions	Restrictions	
	Description	
	maxLength	9

CSM

Attribute	Description	
Name	CSM	
Datatype	String	
Description		
Restrictions	Restrictions	
	Description	
	maxLength	35

Cotm-Csm-Ben-Master-C-IO

Attribute	Description
Name	Cotm-Csm-Ben-Master-C-IO

Datatype	
Description	

CSM

Attribute	Description	
Name	CSM	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

Cotm-Csm-Ben-Detail-C

Attribute	Description	
Name	Cotm-Csm-Ben-Detail-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BEN_START_DT

Attribute	Description	
Name	BEN_START_DT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_END_DT

Attribute	Description	
Name	BEN_END_DT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.7.CreateRPBenfPlan

2.7.1.CO-CreateRPBenfPlan-Req-Full-MSG.xsd

CREATERPBENFPLAN_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Benefit-Master-Full

BEN_PLAN_ID

BEN_PLAN_DESC

MODULE

PRIORITY_NO

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Cotms-Benefit-Details

PRODUCT

PRICE_COMP_TYPE

PRICE_COMP

BEN_TYPE

VAR_TYPE

VAR_CCY

VAR_VALUE

VAR_RULE

MAX_VALUE

MIN_VALUE

CCY_CODE

UDFDETAILS

FLDNAM

CREATERPBENFPLAN_FSFS_REQ

Attribute	Description
Name	CREATERPBENFPLAN_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute		Description	
Name	SOURCE_USERID		
Datatype	String		
Description	This is the user id in the Source system who is performing the action.		
Attribute	Attribute		Description
	minOccurs	0	

DESTINATION

Attribute		Description	
Name	DESTINATION		
Datatype	String		
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute		Description	
Name	MULTITRIPID		
Datatype	String		
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute		Description	
Name	FUNCTIONID		
Datatype	String		
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.		
Attribute	Attribute		Description
	minOccurs	0	

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Benefit-Master-Full

Attribute	Description
Name	Cotms-Benefit-Master-Full
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description				
Name	BEN_PLAN_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

BEN_PLAN_DESC

Attribute	Description
-----------	-------------

Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	2

PRIORITY_NO

Attribute	Description	
Name	PRIORITY_NO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	5

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Cotms-Benefit-Details

Attribute	Description	
Name	Cotms-Benefit-Details	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

PRODUCT

Attribute	Description	
Name	PRODUCT	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	4

PRICE_COMP_TYPE

Attribute	Description	
Name	PRICE_COMP_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	I,C,F,M

PRICE_COMP

Attribute	Description
------------------	--------------------

Name	PRICE_COMP	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_TYPE

Attribute	Description	
Name	BEN_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	V,W,

VAR_TYPE

Attribute	Description	
Name	VAR_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	F,A,P,V,T,N,

VAR_CCY

Attribute	Description	
Name	VAR_CCY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

VAR_VALUE

Attribute	Description	
Name	VAR_VALUE	
Datatype	Decimal	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

VAR_RULE

Attribute	Description	
Name	VAR_RULE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MAX_VALUE

Attribute	Description	
Name	MAX_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

MIN_VALUE

Attribute	Description	
Name	MIN_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

CCY_CODE

Attribute	Description	
Name	CCY_CODE	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.7.2.CO-CreateRPBenfPlan-Req-IO-MSG.xsd

CREATERPBENFPLAN_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cotms-Benefit-Master-IO
BEN_PLAN_ID
BEN_PLAN_DESC
MODULE
PRIORITY_NO
Cotms-Benefit-Details
PRODUCT
PRICE_COMP_TYPE
PRICE_COMP
BEN_TYPE
VAR_TYPE
VAR_CCY
VAR_VALUE
VAR_RULE

MAX_VALUE

MIN_VALUE

CCY_CODE

UDFDETAILS

FLDNAM

FLDVAL

CREATERPBENFPLAN_IOPK_REQ

Attribute	Description
Name	CREATERPBENFPLAN_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Benefit-Master-IO

Attribute	Description
Name	Cotms-Benefit-Master-IO
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description
------------------	--------------------

Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	2

PRIORITY_NO

Attribute	Description	
Name	PRIORITY_NO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	5

Cotms-Benefit-Details

Attribute	Description	
Name	Cotms-Benefit-Details	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

PRODUCT

Attribute	Description
------------------	--------------------

Name	PRODUCT	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	4

PRICE_COMP_TYPE

Attribute	Description	
Name	PRICE_COMP_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	I,C,F,M

PRICE_COMP

Attribute	Description	
Name	PRICE_COMP	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_TYPE

Attribute	Description	
Name	BEN_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	V,W,

VAR_TYPE

Attribute	Description	
Name	VAR_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	F,A,P,V,T,N,

VAR_CCY

Attribute	Description	
Name	VAR_CCY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

VAR_VALUE

Attribute	Description	
Name	VAR_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

VAR_RULE

Attribute	Description	
Name	VAR_RULE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MAX_VALUE

Attribute	Description	
Name	MAX_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	22

MIN_VALUE

Attribute	Description	
Name	MIN_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

CCY_CODE

Attribute	Description	
Name	CCY_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.7.3.CO-CreateRPBenfPlan-Res-Full-MSG.xsd

CREATERPBENFPLAN_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Benefit-Master-Full

BEN_PLAN_ID

BEN_PLAN_DESC

MODULE

PRIORITY_NO

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Cotms-Benefit-Details

PRODUCT

PRICE_COMP_TYPE

PRICE_COMP

BEN_TYPE

VAR_TYPE

VAR_CCY

VAR_VALUE

VAR_RULE

MAX_VALUE

MIN_VALUE

CCY_CODE

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATERPBENFPLAN_FSFS_RES

Attribute	Description
Name	CREATERPBENFPLAN_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute			
		Attribute	Description
		minOccurs	0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute			
		Attribute	Description
		minOccurs	0
		maxOccurs	unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Cotms-Benefit-Master-Full

Attribute		Description	
Name		Cotms-Benefit-Master-Full	
Datatype			
Description			

BEN_PLAN_ID

Attribute		Description	
Name		BEN_PLAN_ID	
Datatype		String	
Description			
Restrictions			
		Restrictions	Description
		maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	2

PRIORITY_NO

Attribute	Description	
Name	PRIORITY_NO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	5

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Cotms-Benefit-Details

Attribute	Description	
Name	Cotms-Benefit-Details	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

PRODUCT

Attribute	Description	
Name	PRODUCT	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	4

PRICE_COMP_TYPE

Attribute	Description	
Name	PRICE_COMP_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	I,C,F,M

PRICE_COMP

Attribute	Description	
Name	PRICE_COMP	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_TYPE

Attribute	Description	
Name	BEN_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	V,W,

VAR_TYPE

Attribute	Description	
Name	VAR_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	F,A,P,V,T,N,

VAR_CCY

Attribute	Description	
Name	VAR_CCY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

VAR_VALUE

Attribute	Description				
Name	VAR_VALUE				
Datatype	Decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
	Restrictions	Description			
totalDigits	22				

VAR_RULE

Attribute	Description				
Name	VAR_RULE				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
	Restrictions	Description			
maxLength	35				

MAX_VALUE

Attribute	Description				
Name	MAX_VALUE				
Datatype	Decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
	Restrictions	Description			
totalDigits	22				

MIN_VALUE

Attribute	Description				
Name	MIN_VALUE				
Datatype	Decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
	Restrictions	Description			
totalDigits	22				

CCY_CODE

Attribute		Description	
Name	CCY_CODE		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	255	

UDFDETAILS

Attribute		Description	
Name	UDFDETAILS		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

FLDNAM

Attribute		Description	
Name	FLDNAM		
Datatype	String		
Description	Indicates Field Name		
Restrictions	Restrictions		Description
	maxLength	105	
	minLength	1	

FLDVAL

Attribute		Description	
Name	FLDVAL		
Datatype	String		
Description	Indicates Field Value		
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	150	
	minLength	0	

FCUBS_ERROR_RESP

Attribute		Description	
Name	FCUBS_ERROR_RESP		
Datatype			
Description			

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.7.4.CO-CreateRPBenfPlan-Res-PK-MSG.xsd

CREATERPBENFPLAN_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Benefit-Master-PK

BEN_PLAN_ID

MODULE

Cotms-Benefit-Master-IO

BEN_PLAN_ID

BEN_PLAN_DESC

MODULE

PRIORITY_NO

Cotms-Benefit-Details

PRODUCT

PRICE_COMP_TYPE

PRICE_COMP

BEN_TYPE

VAR_TYPE

VAR_CCY

VAR_VALUE

VAR_RULE

MAX_VALUE

MIN_VALUE

CCY_CODE

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATERPBENFPLAN_IOPK_RES

Attribute	Description
Name	CREATERPBENFPLAN_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Benefit-Master-PK

Attribute	Description
Name	Cotms-Benefit-Master-PK
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description				
Name	BEN_PLAN_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

MODULE

Attribute	Description				
Name	MODULE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>2</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	2
Restrictions	Description				
maxLength	2				

Cotms-Benefit-Master-IO

Attribute	Description
Name	Cotms-Benefit-Master-IO
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description

Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	2

PRIORITY_NO

Attribute	Description	
Name	PRIORITY_NO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	5

Cotms-Benefit-Details

Attribute	Description	
Name	Cotms-Benefit-Details	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

PRODUCT

Attribute	Description
------------------	--------------------

Name	PRODUCT	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	4

PRICE_COMP_TYPE

Attribute	Description	
Name	PRICE_COMP_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	I,C,F,M

PRICE_COMP

Attribute	Description	
Name	PRICE_COMP	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_TYPE

Attribute	Description	
Name	BEN_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	V,W,

VAR_TYPE

Attribute	Description	
Name	VAR_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	F,A,P,V,T,N,

VAR_CCY

Attribute	Description	
Name	VAR_CCY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

VAR_VALUE

Attribute	Description	
Name	VAR_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

VAR_RULE

Attribute	Description	
Name	VAR_RULE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MAX_VALUE

Attribute	Description	
Name	MAX_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	22

MIN_VALUE

Attribute	Description	
Name	MIN_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

CCY_CODE

Attribute	Description	
Name	CCY_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.8.CreateRPElgPlan

2.8.1.CO-CreateRPElgPlan-Req-Full-MSG.xsd

CREATERPELGPLAN_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Elplan-Master-Full

EL_PLAN_CODE

EL_PLAN_DESC

EL_CONDITION

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Cotms-Elplan-Rde

RDE_CODE

RDE_PARAM_VAL

UDFDETAILS

FLDNAM

FLDVAL

CREATERPELGPLAN_FSFS_REQ

Attribute	Description
Name	CREATERPELGPLAN_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Elplan-Master-Full

Attribute	Description
Name	Cotms-Elplan-Master-Full
Datatype	
Description	

EL_PLAN_CODE

Attribute	Description				
Name	EL_PLAN_CODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

EL_PLAN_DESC

Attribute	Description				
Name	EL_PLAN_DESC				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

EL_CONDITION

Attribute	Description				
Name	EL_CONDITION				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	4000

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Cotms-Elplan-Rde

Attribute	Description	
Name	Cotms-Elplan-Rde	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

RDE_CODE

Attribute	Description				
Name	RDE_CODE				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

RDE_PARAM_VAL

Attribute	Description				
Name	RDE_PARAM_VAL				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

FLDNAM

Attribute	Description						
Name	FLDNAM						
Datatype	String						
Description	Indicates Field Name						
Restrictions							
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	105	minLength	1
Restrictions	Description						
maxLength	105						
minLength	1						

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.8.2.CO-CreateRPElgPlan-Req-IO-MSG.xsd

CREATERPELGPLAN_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Elplan-Master-IO

EL_PLAN_CODE

EL_PLAN_DESC

EL_CONDITION

Cotms-Elplan-Rde

RDE_CODE

RDE_PARAM_VAL

UDFDETAILS

FLDNAM

FLDVAL

CREATERPELGPLAN_IOPK_REQ

Attribute	Description
Name	CREATERPELGPLAN_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Cotms-Elplan-Master-IO

Attribute	Description	
Name	Cotms-Elplan-Master-IO	
Datatype		
Description		

EL_PLAN_CODE

Attribute	Description	
------------------	--------------------	--

Name	EL_PLAN_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

EL_PLAN_DESC

Attribute	Description	
Name	EL_PLAN_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

EL_CONDITION

Attribute	Description	
Name	EL_CONDITION	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	4000

Cotms-Elplan-Rde

Attribute	Description	
Name	Cotms-Elplan-Rde	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

RDE_CODE

Attribute	Description	
Name	RDE_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

RDE_PARAM_VAL

Attribute	Description	
Name	RDE_PARAM_VAL	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.8.3.CO-CreateRPElgPlan-Res-Full-MSG.xsd

CREATERPELGPLAN_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cotms-Elplan-Master-Full
EL_PLAN_CODE
EL_PLAN_DESC
EL_CONDITION
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT

Cotms-Elplan-Rde

RDE_CODE

RDE_PARAM_VAL

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATERPELGPLAN_FSFS_RES

Attribute	Description
Name	CREATERPELGPLAN_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

MSGID

Attribute	Description					
Name	MSGID					
Datatype	String					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	String					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Cotms-Elplan-Master-Full
Datatype	
Description	

EL_PLAN_CODE

Attribute	Description				
Name	EL_PLAN_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

EL_PLAN_DESC

Attribute	Description				
Name	EL_PLAN_DESC				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

EL_CONDITION

Attribute	Description				
Name	EL_CONDITION				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>4000</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	4000
Restrictions	Description				
maxLength	4000				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute	Description
-----------	-------------

Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description
------------------	--------------------

Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

Cotms-Elplan-Rde

Attribute	Description	
Name	Cotms-Elplan-Rde	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

RDE_CODE

Attribute	Description	
Name	RDE_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

RDE_PARAM_VAL

Attribute	Description	
Name	RDE_PARAM_VAL	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxOccurs	unbounded

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String

Description	
-------------	--

2.8.4.CO-CreateRPElgPlan-Res-PK-MSG.xsd

CREATERPELGPLAN_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Elplan-Master-PK

EL_PLAN_CODE

Cotms-Elplan-Master-IO

EL_PLAN_CODE

EL_PLAN_DESC

EL_CONDITION

Cotms-Elplan-Rde

RDE_CODE

RDE_PARAM_VAL

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATERPELGPLAN_IOPK_RES

Attribute	Description
Name	CREATERPELGPLAN_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Cotms-Elplan-Master-PK

Attribute	Description
------------------	--------------------

Name	Cotms-Elplan-Master-PK
Datatype	
Description	

EL_PLAN_CODE

Attribute	Description	
Name	EL_PLAN_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

Cotms-Elplan-Master-IO

Attribute	Description
Name	Cotms-Elplan-Master-IO
Datatype	
Description	

EL_PLAN_CODE

Attribute	Description	
Name	EL_PLAN_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

EL_PLAN_DESC

Attribute	Description	
Name	EL_PLAN_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

EL_CONDITION

Attribute	Description	
Name	EL_CONDITION	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	4000

Cotms-Elplan-Rde

Attribute	Description	
Name	Cotms-Elplan-Rde	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

RDE_CODE

Attribute	Description	
Name	RDE_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

RDE_PARAM_VAL

Attribute	Description	
Name	RDE_PARAM_VAL	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.9.CreateRPErBenPlan

2.9.1.CO-CreateRPErBenPlan-Req-Full-MSG.xsd

CREATERPERBENPLAN_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Ben-Exch-Master-C-Full

BEN_PLAN_ID

BEN_PLAN_DESC

PRIORITY_NO

APPLY_SPREAD_AS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Cotm-Ben-Exch-Detail-C

BUY_SPREAD

SALESPRD

BEN_PLAN_ID

RATTYP

VAR_CCY1

VAR_CCY2

UDFDETAILS

FLDNAM

FLDVAL

CREATERPERBENPLAN_FSFS_REQ

Attribute	Description
Name	CREATERPERBENPLAN_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0
	maxOccurs		unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Cotm-Ben-Exch-Master-C-Full

Attribute		Description	
Name		Cotm-Ben-Exch-Master-C-Full	
Datatype			
Description			

BEN_PLAN_ID

Attribute		Description	
Name		BEN_PLAN_ID	
Datatype		String	
Description			
Restrictions	Restrictions		Description
	maxLength		35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

PRIORITY_NO

Attribute	Description	
Name	PRIORITY_NO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	5

APPLY_SPREAD_AS

Attribute	Description	
Name	APPLY_SPREAD_AS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	D,V

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Cotm-Ben-Exch-Detail-C

Attribute	Description	
Name	Cotm-Ben-Exch-Detail-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BUY_SPREAD

Attribute	Description	
Name	BUY_SPREAD	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

SALESPRD

Attribute	Description	
Name	SALESPRD	
Datatype	Decimal	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

RATTYP

Attribute	Description	
Name	RATTYP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	8

VAR_CCY1

Attribute	Description	
Name	VAR_CCY1	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	3

VAR_CCY2

Attribute	Description	
Name	VAR_CCY2	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	3

UDFDETAILS

Attribute	Description
------------------	--------------------

Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.9.2.CO-CreateRPERBenPlan-Req-IO-MSG.xsd

CREATERPERBENPLAN_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Ben-Exch-Master-C-IO

BEN_PLAN_ID

BEN_PLAN_DESC

PRIORITY_NO

APPLY_SPREAD_AS

Cotm-Ben-Exch-Detail-C

BUY_SPREAD

SALESPRD

BEN_PLAN_ID

RATTYP

VAR_CCY1

VAR_CCY2

UDFDETAILS

FLDNAM

FLDVAL

CREATERPERBENPLAN_IOPK_REQ

Attribute	Description
Name	CREATERPERBENPLAN_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotm-Ben-Exch-Master-C-IO

Attribute	Description
Name	Cotm-Ben-Exch-Master-C-IO
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description				
Name	BEN_PLAN_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

BEN_PLAN_DESC

Attribute	Description				
Name	BEN_PLAN_DESC				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

PRIORITY_NO

Attribute	Description				
Name	PRIORITY_NO				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	5

APPLY_SPREAD_AS

Attribute	Description	
Name	APPLY_SPREAD_AS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	D,V

Cotm-Ben-Exch-Detail-C

Attribute	Description	
Name	Cotm-Ben-Exch-Detail-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BUY_SPREAD

Attribute	Description	
Name	BUY_SPREAD	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

SALESPRD

Attribute	Description	
Name	SALESPRD	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	22

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

RATTYP

Attribute	Description	
Name	RATTYP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	8

VAR_CCY1

Attribute	Description	
Name	VAR_CCY1	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	3

VAR_CCY2

Attribute	Description	
Name	VAR_CCY2	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	3

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.9.3.CO-CreateRPERBenPlan-Res-Full-MSG.xsd

CREATERPERBENPLAN_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Ben-Exch-Master-C-Full

BEN_PLAN_ID

BEN_PLAN_DESC

PRIORITY_NO

APPLY_SPREAD_AS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Cotm-Ben-Exch-Detail-C

BUY_SPREAD

SALESPRD

BEN_PLAN_ID

RATTYP

VAR_CCY1

VAR_CCY2

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATERPERBENPLAN_FSFS_RES

Attribute	Description
Name	CREATERPERBENPLAN_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

Attribute	Description					
Name	MSGID					
Datatype	String					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	String					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description							
Name	USERID							
Datatype	String							
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description							
maxLength	12							
pattern	[A-Z_0-9]*							

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Cotm-Ben-Exch-Master-C-Full

Attribute	Description	
Name	Cotm-Ben-Exch-Master-C-Full	
Datatype		
Description		

BEN_PLAN_ID

Attribute	Description	
------------------	--------------------	--

Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

PRIORITY_NO

Attribute	Description	
Name	PRIORITY_NO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	5

APPLY_SPREAD_AS

Attribute	Description	
Name	APPLY_SPREAD_AS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	D,V

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Cotm-Ben-Exch-Detail-C

Attribute	Description	
Name	Cotm-Ben-Exch-Detail-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BUY_SPREAD

Attribute	Description	
Name	BUY_SPREAD	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	22

SALESPRD

Attribute	Description	
Name	SALESPRD	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

RATTYP

Attribute	Description	
Name	RATTYP	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	8

VAR_CCY1

Attribute	Description	
Name	VAR_CCY1	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

VAR_CCY2

Attribute	Description
------------------	--------------------

Name	VAR_CCY2	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

Attribute		Description	
Name	ERROR		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

ECODE

Attribute		Description	
Name	ECODE		
Datatype	String		
Description			

EDESC

Attribute		Description	
Name	EDESC		
Datatype	String		
Description			

FCUBS_WARNING_RESP

Attribute		Description	
Name	FCUBS_WARNING_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

WARNING

Attribute		Description	
Name	WARNING		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

WCODE

Attribute		Description	
Name	WCODE		
Datatype	String		
Description			

WDESC

Attribute		Description	
Name	WDESC		
Datatype	String		
Description			

CREATERPERBENPLAN_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Ben-Exch-Master-C-PK

BEN_PLAN_ID

Cotm-Ben-Exch-Master-C-IO

BEN_PLAN_ID

BEN_PLAN_DESC

PRIORITY_NO

APPLY_SPREAD_AS

Cotm-Ben-Exch-Detail-C

BUY_SPREAD

SALESPRD

BEN_PLAN_ID

RATTYP

VAR_CCY1

VAR_CCY2

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATERPERBENPLAN_IOPK_RES

Attribute	Description
Name	CREATERPERBENPLAN_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description

Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nullable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotm-Ben-Exch-Master-C-PK

Attribute	Description
Name	Cotm-Ben-Exch-Master-C-PK
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description				
Name	BEN_PLAN_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

Cotm-Ben-Exch-Master-C-IO

Attribute	Description
Name	Cotm-Ben-Exch-Master-C-IO
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description				
Name	BEN_PLAN_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

BEN_PLAN_DESC

Attribute	Description				
Name	BEN_PLAN_DESC				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

PRIORITY_NO

Attribute	Description
Name	PRIORITY_NO

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	5

APPLY_SPREAD_AS

Attribute	Description	
Name	APPLY_SPREAD_AS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	D,V

Cotm-Ben-Exch-Detail-C

Attribute	Description	
Name	Cotm-Ben-Exch-Detail-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BUY_SPREAD

Attribute	Description	
Name	BUY_SPREAD	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

SALESPRD

Attribute	Description	
Name	SALESPRD	
Datatype	Decimal	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

RATTYP

Attribute	Description	
Name	RATTYP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	8

VAR_CCY1

Attribute	Description	
Name	VAR_CCY1	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	3

VAR_CCY2

Attribute	Description	
Name	VAR_CCY2	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	3

UDFDETAILS

Attribute	Description
------------------	--------------------

Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	
		Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	
		Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	
		Description
	minOccurs	0
Restrictions	Restrictions	
		Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	
		Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	
		Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.10.CreateRPSchMntc

2.10.1.CO-CreateRPSchMntc-Req-Full-MSG.xsd

CREATERPSCHMNTC_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cotms-Scheme-Master-Full
SCHEME_ID1
SCHEME_DESC
SC_START_DT
SC_END_DT
BEN_VALID_PERIOD
BEN_VALID_BASIS
VALID_TYPE
APPLY_FOR
EXECUTABLE_TYPE
RENEW_TYPE
SCHEME_RP_DESC

BEN_EXPIRY

SCHEME_STATUS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Elig

EL_PLAN_CODE

EL_REV_FREQ

FIRST_REV_DT

LAST_REV_DT

NEXT_REV_DT

Cotms-Scheme-Detail

BEN_PLAN_ID

BEN_PLAN_DESC

UDFDETAILS

FLDNAM

FLDVAL

CREATERPSCHMNTC_FSFS_REQ

Attribute	Description
Name	CREATERPSCHMNTC_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within EL EXCLUDE UBS. In

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Scheme-Master-Full

Attribute	Description
Name	Cotms-Scheme-Master-Full
Datatype	
Description	

SCHEME_ID1

Attribute	Description				
Name	SCHEME_ID1				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

SCHEME_DESC

Attribute	Description				
Name	SCHEME_DESC				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

SC_START_DT

Attribute	Description
Name	SC_START_DT
Datatype	String
Description	

SC_END_DT

Attribute	Description

Name	SC_END_DT
Datatype	String
Description	

BEN_VALID_PERIOD

Attribute	Description	
Name	BEN_VALID_PERIOD	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

BEN_VALID_BASIS

Attribute	Description	
Name	BEN_VALID_BASIS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	D,M,Y,

VALID_TYPE

Attribute	Description	
Name	VALID_TYPE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	O,R,P,

APPLY_FOR

Attribute	Description	
Name	APPLY_FOR	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	N,A,E,

EXECUTABLE_TYPE

Attribute	Description
Name	EXECUTABLE_TYPE

Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	M,A,

RENEW_TYPE

Attribute	Description	
Name	RENEW_TYPE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	B,S,

SCHEME_RP_DESC

Attribute	Description	
Name	SCHEME_RP_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

BEN_EXPIRY

Attribute	Description	
Name	BEN_EXPIRY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

SCHEME_STATUS

Attribute	Description	
Name	SCHEME_STATUS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	A,E

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Elig

Attribute	Description	
Name	Elig	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

EL_PLAN_CODE

Attribute	Description				
Name	EL_PLAN_CODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

EL_REV_FREQ

Attribute	Description				
Name	EL_REV_FREQ				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>D,W,F,M,Q,H,Y</td></tr></tbody></table>	Restrictions	Description	enumeration	D,W,F,M,Q,H,Y
Restrictions	Description				
enumeration	D,W,F,M,Q,H,Y				

FIRST_REV_DT

Attribute	Description
Name	FIRST_REV_DT
Datatype	String
Description	

LAST_REV_DT

Attribute	Description				
Name	LAST_REV_DT				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

NEXT_REV_DT

Attribute	Description				
Name	NEXT_REV_DT				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Cotms-Scheme-Detail

Attribute	Description
Name	Cotms-Scheme-Detail
Datatype	
Description	

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL

Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.10.2.CO-CreateRPSchMntc-Req-IO-MSG.xsd

CREATERPSCHMNTC_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Scheme-Master-IO

SCHEME_ID1
SCHEME_DESC
SC_START_DT
SC_END_DT
BEN_VALID_PERIOD
BEN_VALID_BASIS
VALID_TYPE
APPLY_FOR
EXECUTABLE_TYPE
RENEW_TYPE
SCHEME_RP_DESC
BEN_EXPIRY
Elig
 EL_PLAN_CODE
 EL_REV_FREQ
 FIRST_REV_DT
 NEXT_REV_DT
Cotms-Scheme-Detail
 BEN_PLAN_ID
 BEN_PLAN_DESC
UDFDETAILS
 FLDNAM
 FLDVAL

CREATERPSCHMNTC_IOPK_REQ

Attribute	Description
Name	CREATERPSCHMNTC_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Scheme-Master-IO

Attribute	Description
Name	Cotms-Scheme-Master-IO
Datatype	
Description	

SCHEME_ID1

Attribute	Description				
Name	SCHEME_ID1				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

SCHEME_DESC

Attribute	Description				
Name	SCHEME_DESC				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

SC_START_DT

Attribute	Description
Name	SC_START_DT
Datatype	String
Description	

SC_END_DT

Attribute	Description

Name	SC_END_DT
Datatype	String
Description	

BEN_VALID_PERIOD

Attribute	Description	
Name	BEN_VALID_PERIOD	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

BEN_VALID_BASIS

Attribute	Description	
Name	BEN_VALID_BASIS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	D,M,Y,

VALID_TYPE

Attribute	Description	
Name	VALID_TYPE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	O,R,P,

APPLY_FOR

Attribute	Description	
Name	APPLY_FOR	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	N,A,E,

EXECUTABLE_TYPE

Attribute	Description
Name	EXECUTABLE_TYPE

Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	M,A,

RENEW_TYPE

Attribute	Description	
Name	RENEW_TYPE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	B,S,

SCHEME_RP_DESC

Attribute	Description	
Name	SCHEME_RP_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

BEN_EXPIRY

Attribute	Description	
Name	BEN_EXPIRY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

Elig

Attribute	Description	
Name	Elig	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

EL_PLAN_CODE

Attribute	Description	
Name	EL_PLAN_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

EL_REV_FREQ

Attribute	Description	
Name	EL_REV_FREQ	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	D,W,F,M,Q,H,Y

FIRST_REV_DT

Attribute	Description	
Name	FIRST_REV_DT	
Datatype	String	
Description		

NEXT_REV_DT

Attribute	Description	
Name	NEXT_REV_DT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Cotms-Scheme-Detail

Attribute	Description	
Name	Cotms-Scheme-Detail	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.10.3.CO-CreateRPSchMntc-Res-Full-MSG.xsd

[CREATERPSCHMNTC_FSFS_RES](#)

[FCUBS_HEADER](#)

[SOURCE](#)

UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cotms-Scheme-Master-Full
SCHEME_ID1
SCHEME_DESC
SC_START_DT
SC_END_DT
BEN_VALID_PERIOD
BEN_VALID_BASIS
VALID_TYPE
APPLY_FOR
EXECUTABLE_TYPE
RENEW_TYPE

SCHEME_RP_DESC

BEN_EXPIRY

SCHEME_STATUS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Elig

EL_PLAN_CODE

EL_REV_FREQ

FIRST_REV_DT

LAST_REV_DT

NEXT_REV_DT

Cotms-Scheme-Detail

BEN_PLAN_ID

BEN_PLAN_DESC

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATERPSCHMNTC_FSFS_RES

Attribute	Description
-----------	-------------

Name	CREATERPSCHMNTC_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	
	Description	
	maxLength	12
pattern	[A-Z_0-9]*	

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	
	Description	
	length	3
pattern	[a-zA-Z_0-9]{3}	

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	

Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	

Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Cotms-Scheme-Master-Full

Attribute	Description	
Name	Cotms-Scheme-Master-Full	
Datatype		
Description		

SCHEME_ID1

Attribute	Description	
Name	SCHEME_ID1	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	35

SCHEME_DESC

Attribute	Description	
Name	SCHEME_DESC	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105

SC_START_DT

Attribute	Description
Name	SC_START_DT
Datatype	String
Description	

SC_END_DT

Attribute	Description
Name	SC_END_DT
Datatype	String
Description	

BEN_VALID_PERIOD

Attribute	Description				
Name	BEN_VALID_PERIOD				
Datatype	Decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
	Restrictions	Description			
totalDigits	22				

BEN_VALID_BASIS

Attribute	Description				
Name	BEN_VALID_BASIS				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>D,M,Y,</td></tr></tbody></table>	Restrictions	Description	enumeration	D,M,Y,
	Restrictions	Description			
enumeration	D,M,Y,				

VALID_TYPE

Attribute	Description				
Name	VALID_TYPE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>O,R,P,</td></tr></tbody></table>	Restrictions	Description	enumeration	O,R,P,
	Restrictions	Description			
enumeration	O,R,P,				

APPLY_FOR

Attribute	Description
Name	APPLY_FOR
Datatype	String

Description					
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>enumeration</td> <td>N,A,E,</td> </tr> </table>	Restrictions	Description	enumeration	N,A,E,
Restrictions	Description				
enumeration	N,A,E,				

EXECUTABLE_TYPE

Attribute	Description				
Name	EXECUTABLE_TYPE				
Datatype	String				
Description					
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>enumeration</td> <td>M,A,</td> </tr> </table>	Restrictions	Description	enumeration	M,A,
Restrictions	Description				
enumeration	M,A,				

RENEW_TYPE

Attribute	Description				
Name	RENEW_TYPE				
Datatype	String				
Description					
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>enumeration</td> <td>B,S,</td> </tr> </table>	Restrictions	Description	enumeration	B,S,
Restrictions	Description				
enumeration	B,S,				

SCHEME_RP_DESC

Attribute	Description				
Name	SCHEME_RP_DESC				
Datatype	String				
Description					
Attribute	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>maxLength</td> <td>1000</td> </tr> </table>	Restrictions	Description	maxLength	1000
Restrictions	Description				
maxLength	1000				

BEN_EXPIRY

Attribute	Description				
Name	BEN_EXPIRY				
Datatype	String				
Description					
Attribute	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>enumeration</td> <td>Y,N</td> </tr> </table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

SCHEME_STATUS

Attribute	Description
-----------	-------------

Name	SCHEME_STATUS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,E

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description
------------------	--------------------

Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

Elig

Attribute	Description
------------------	--------------------

Name	Elig	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

EL_PLAN_CODE

Attribute	Description	
Name	EL_PLAN_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

EL_REV_FREQ

Attribute	Description	
Name	EL_REV_FREQ	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	D,W,F,M,Q,H,Y

FIRST_REV_DT

Attribute	Description	
Name	FIRST_REV_DT	
Datatype	String	
Description		

LAST_REV_DT

Attribute	Description	
Name	LAST_REV_DT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

NEXT_REV_DT

Attribute	Description	
Name	NEXT_REV_DT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Attribute	Description	
Name	Cotms-Scheme-Detail	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute		Description	
Name	FLDVAL		
Datatype	String		
Description	Indicates Field Value		
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	150	
	minLength	0	

FCUBS_ERROR_RESP

Attribute		Description	
Name	FCUBS_ERROR_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

ERROR

Attribute		Description	
Name	ERROR		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

ECODE

Attribute		Description	
Name	ECODE		
Datatype	String		
Description			

EDESC

Attribute		Description	
Name	EDESC		
Datatype	String		
Description			

FCUBS_WARNING_RESP

Attribute		Description	
Name	FCUBS_WARNING_RESP		
Datatype			
Description			

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.10.4.CO-CreateRPSchMntc-Res-PK-MSG.xsd

CREATERPSCHMNTC_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Scheme-Master-PK

SCHEME_ID1

Cotms-Scheme-Master-IO

SCHEME_ID1

SCHEME_DESC

SC_START_DT

SC_END_DT

BEN_VALID_PERIOD

BEN_VALID_BASIS

VALID_TYPE

APPLY_FOR

EXECUTABLE_TYPE

RENEW_TYPE

SCHEME_RP_DESC

BEN_EXPIRY

Elig

EL_PLAN_CODE

EL_REV_FREQ

FIRST_REV_DT

NEXT_REV_DT

Cotms-Scheme-Detail

BEN_PLAN_ID

BEN_PLAN_DESC

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATERPSCHMNTC_IOPK_RES

Attribute	Description
Name	CREATERPSCHMNTC_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Cotms-Scheme-Master-PK

Attribute		Description
------------------	--	--------------------

Name	Cotms-Scheme-Master-PK
Datatype	
Description	

SCHEME_ID1

Attribute	Description	
Name	SCHEME_ID1	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

Cotms-Scheme-Master-IO

Attribute	Description
Name	Cotms-Scheme-Master-IO
Datatype	
Description	

SCHEME_ID1

Attribute	Description	
Name	SCHEME_ID1	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

SCHEME_DESC

Attribute	Description	
Name	SCHEME_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

SC_START_DT

Attribute	Description
Name	SC_START_DT
Datatype	String
Description	

SC_END_DT

Attribute	Description
Name	SC_END_DT
Datatype	String
Description	

BEN_VALID_PERIOD

Attribute	Description
-----------	-------------

Name	BEN_VALID_PERIOD	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

BEN_VALID_BASIS

Attribute	Description	
Name	BEN_VALID_BASIS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Y,

VALID_TYPE

Attribute	Description	
Name	VALID_TYPE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	O,R,P,

APPLY_FOR

Attribute	Description	
Name	APPLY_FOR	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	N,A,E,

EXECUTABLE_TYPE

Attribute	Description	
Name	EXECUTABLE_TYPE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	M,A,

RENEW_TYPE

Attribute		Description	
Name	RENEW_TYPE		
Datatype	String		
Description			
Restrictions	Restrictions		Description
	enumeration	B,S,	

SCHEME_RP_DESC

Attribute		Description	
Name	SCHEME_RP_DESC		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1000	

BEN_EXPIRY

Attribute		Description	
Name	BEN_EXPIRY		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	Y,N	

Elig

Attribute		Description	
Name	Elig		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

EL_PLAN_CODE

Attribute		Description	
Name	EL_PLAN_CODE		
Datatype	String		
Description			

Restrictions		
	Restrictions	Description
	maxLength	35

EL_REV_FREQ

Attribute	Description	
Name	EL_REV_FREQ	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	D,W,F,M,Q,H,Y

FIRST_REV_DT

Attribute	Description	
Name	FIRST_REV_DT	
Datatype	String	
Description		

NEXT_REV_DT

Attribute	Description	
Name	NEXT_REV_DT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Cotms-Scheme-Detail

Attribute	Description	
Name	Cotms-Scheme-Detail	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description
------------------	--------------------

Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
Restrictions	Restrictions	Description
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
Restrictions	Restrictions	Description
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.11.DeleteCSMBPLinkage

2.11.1.CO-DeleteCSMBPLinkage-Req-Full-MSG.xsd

DELETECSMBPLINKAGE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Csm-Ben-Master-C-Full

CSM

CUSTOMER_NO

CSM_DESC

CUSTOMER_NAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Cotm-Csm-Ben-Detail-C

BEN_START_DT

MODULE

BEN_PLAN_TYPE

BEN_PLAN_ID

BEN_PLAN_DESC

PRIORITYNO

BEN_END_DT

DELETECSMBPLINKAGE_FSFS_REQ

Attribute	Description
Name	DELETECSMBPLINKAGE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description

Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nullable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotm-Csm-Ben-Master-C-Full

Attribute	Description
Name	Cotm-Csm-Ben-Master-C-Full
Datatype	
Description	

CSM

Attribute	Description				
Name	CSM				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

CUSTOMER_NO

Attribute	Description				
Name	CUSTOMER_NO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

CSM_DESC

Attribute	Description				
Name	CSM_DESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>255</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

CUSTOMER_NAME

Attribute	Description
Name	CUSTOMER_NAME
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

Cotm-Csm-Ben-Detail-C

Attribute	Description	
Name	Cotm-Csm-Ben-Detail-C	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BEN_START_DT

Attribute	Description	
Name	BEN_START_DT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

BEN_PLAN_TYPE

Attribute	Description	
Name	BEN_PLAN_TYPE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description
------------------	--------------------

Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

PRIORITYNO

Attribute	Description	
Name	PRIORITYNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

BEN_END_DT

Attribute	Description	
Name	BEN_END_DT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

2.11.2.CO-DeleteCSMBPLinkage-Req-IO-MSG.xsd

DELETECSMBPLINKAGE_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Csm-Ben-Master-C-IO

CSM

CUSTOMER_NO

DELETECSMBPLINKAGE_IOPK_REQ

Attribute	Description
Name	DELETECSMBPLINKAGE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
-----------	-------------

Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE. ⁴⁷²	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Cotm-Csm-Ben-Master-C-IO
Datatype	
Description	

CSM

Attribute	Description				
Name	CSM				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

CUSTOMER_NO

Attribute	Description				
Name	CUSTOMER_NO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

2.11.3.CO-DeleteCSMBPLinkage-Res-Full-MSG.xsd

DELETECSMBPLINKAGE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Csm-Ben-Master-C-Full

CSM

CUSTOMER_NO

CSM_DESC

CUSTOMER_NAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Cotm-Csm-Ben-Detail-C

BEN_START_DT

MODULE

BEN_PLAN_TYPE

BEN_PLAN_ID

BEN_PLAN_DESC

PRIORITYNO

BEN_END_DT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETECSMBPLINKAGE_FSFS_RES

Attribute	Description
Name	DELETECSMBPLINKAGE_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*
	Description	

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*
	Description	

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	enumeration	SUCCESS,WARNING,FAILURE
	Description	

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*
	Description	

ADDL

Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

FCUBS_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description			

Cotm-Csm-Ben-Master-C-Full

Attribute		Description	
Name	Cotm-Csm-Ben-Master-C-Full		
Datatype			
Description			

CSM

Attribute		Description	
Name	CSM		
Datatype	String		
Description			
Restrictions	Restrictions		Description
	maxLength	35	

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

CSM_DESC

Attribute	Description	
Name	CSM_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

CUSTOMER_NAME

Attribute	Description	
Name	CUSTOMER_NAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Cotm-Csm-Ben-Detail-C

Attribute	Description	
Name	Cotm-Csm-Ben-Detail-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BEN_START_DT

Attribute	Description	
Name	BEN_START_DT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	2

BEN_PLAN_TYPE

Attribute	Description	
Name	BEN_PLAN_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

PRIORITYNO

Attribute	Description	
Name	PRIORITYNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

BEN_END_DT

Attribute	Description				
Name	BEN_END_DT				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

FCUBS_ERROR_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.11.4.CO-DeleteCSMBPLinkage-Res-PK-MSG.xsd

DELETECSMBPLINKAGE_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Csm-Ben-Master-C-PK

CUSTOMER_NO

CSM

Cotm-Csm-Ben-Master-C-IO

CSM

CUSTOMER_NO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETECSMBPLINKAGE_IOPK_RES

Attribute	Description
Name	DELETECSMBPLINKAGE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
pattern	[A-Z_0-9]*	

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotm-Csm-Ben-Master-C-PK

Attribute	Description
Name	Cotm-Csm-Ben-Master-C-PK
Datatype	
Description	

CUSTOMER_NO

Attribute	Description				
Name	CUSTOMER_NO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

CSM

Attribute	Description				
Name	CSM				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

Cotm-Csm-Ben-Master-C-IO

Attribute	Description
Name	Cotm-Csm-Ben-Master-C-IO
Datatype	
Description	

CSM

Attribute	Description

Name	CSM	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	

Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.12.DeleteRPBenfPlan

2.12.1.CO-DeleteRPBenfPlan-Req-Full-MSG.xsd

DELETERPBENFPLAN_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Benefit-Master-Full

BEN_PLAN_ID

BEN_PLAN_DESC

MODULE

PRIORITY_NO

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Cotms-Benefit-Details

PRODUCT

PRICE_COMP_TYPE

PRICE_COMP

BEN_TYPE

VAR_TYPE

VAR_CCY

VAR_VALUE

VAR_RULE

MAX_VALUE

MIN_VALUE

CCY_CODE

UDFDETAILS

FLDNAM

FLDVAL

DELETERPBENFPLAN_FSFS_REQ

Attribute	Description
Name	DELETERPBENFPLAN_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Benefit-Master-Full

Attribute	Description
Name	Cotms-Benefit-Master-Full
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description
------------------	--------------------

Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	2

PRIORITY_NO

Attribute	Description	
Name	PRIORITY_NO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	5

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute		Description	
Name	MAKERSTAMP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

CHECKER

Attribute		Description	
Name	CHECKER		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	12	

CHECKERSTAMP

Attribute		Description	
Name	CHECKERSTAMP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

MODNO

Attribute		Description	
Name	MODNO		
Datatype	Decimal		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	totalDigits	4	

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	1
	Description	

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	1
	Description	

Cotms-Benefit-Details

Attribute	Description	
Name	Cotms-Benefit-Details	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

PRODUCT

Attribute	Description	
Name	PRODUCT	
Datatype	String	
Description		
Restrictions	Restrictions	
	maxLength	4
	Description	

PRICE_COMP_TYPE

Attribute	Description	
Name	PRICE_COMP_TYPE	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	I,C,F,M

PRICE_COMP

Attribute	Description	
Name	PRICE_COMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	35

BEN_TYPE

Attribute	Description	
Name	BEN_TYPE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	V,W,

VAR_TYPE

Attribute	Description	
Name	VAR_TYPE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	F,A,P,V,T,N,

VAR_CCY

Attribute	Description	
Name	VAR_CCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	3

VAR_VALUE

Attribute	Description	
Name	VAR_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

VAR_RULE

Attribute	Description	
Name	VAR_RULE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MAX_VALUE

Attribute	Description	
Name	MAX_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

MIN_VALUE

Attribute	Description	
Name	MIN_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	22

CCY_CODE

Attribute	Description	
Name	CCY_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

DELETERPBENFPLAN_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Benefit-Master-IO

BEN_PLAN_ID

MODULE

DELETERPBENFPLAN_IOPK_REQ

Attribute	Description
Name	DELETERPBENFPLAN_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Benefit-Master-IO

Attribute	Description
Name	Cotms-Benefit-Master-IO
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description				
Name	BEN_PLAN_ID				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

MODULE

Attribute	Description				
Name	MODULE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>2</td></tr></tbody></table>	Restrictions	Description	maxLength	2
Restrictions	Description				
maxLength	2				

2.12.3.CO-DeleteRPBenfPlan-Res-Full-MSG.xsd

DELETERPBENFPLAN_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cotms-Benefit-Master-Full
BEN_PLAN_ID
BEN_PLAN_DESC
MODULE
PRIORITY_NO
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Cotms-Benefit-Details

PRODUCT

PRICE_COMP_TYPE

PRICE_COMP

BEN_TYPE

VAR_TYPE

VAR_CCY

VAR_VALUE

VAR_RULE

MAX_VALUE

MIN_VALUE

CCY_CODE

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETERPBENFPLAN_FSFS_RES

Attribute	Description
Name	DELETERPBENFPLAN_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Benefit-Master-Full

Attribute	Description
Name	Cotms-Benefit-Master-Full
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description				
Name	BEN_PLAN_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

BEN_PLAN_DESC

Attribute	Description				
Name	BEN_PLAN_DESC				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

MODULE

Attribute	Description				
Name	MODULE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>2</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	2
Restrictions	Description				
maxLength	2				

PRIORITY_NO

Attribute	Description	
Name	PRIORITY_NO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	5

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute		Description	
Name	CHECKERSTAMP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

MODNO

Attribute		Description	
Name	MODNO		
Datatype	Decimal		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	totalDigits	4	

TXNSTAT

Attribute		Description	
Name	TXNSTAT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1	

AUTHSTAT

Attribute		Description	
Name	AUTHSTAT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1	

Attribute	Description	
Name	Cotms-Benefit-Details	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

PRODUCT

Attribute	Description	
Name	PRODUCT	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	4

PRICE_COMP_TYPE

Attribute	Description	
Name	PRICE_COMP_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	I,C,F,M

PRICE_COMP

Attribute	Description	
Name	PRICE_COMP	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_TYPE

Attribute	Description	
Name	BEN_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	V,W,

VAR_TYPE

Attribute	Description	
Name	VAR_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	F,A,P,V,T,N,

VAR_CCY

Attribute	Description	
Name	VAR_CCY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

VAR_VALUE

Attribute	Description	
Name	VAR_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

VAR_RULE

Attribute	Description	
Name	VAR_RULE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

MAX_VALUE

Attribute	Description	
Name	MAX_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

MIN_VALUE

Attribute	Description	
Name	MIN_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

CCY_CODE

Attribute	Description	
Name	CCY_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.12.4.CO-DeleteRPBenfPlan-Res-PK-MSG.xsd

DELETERPBENFPLAN_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
 PARAM
 NAME
 VALUE
FCUBS_BODY
 Cotms-Benefit-Master-PK
 BEN_PLAN_ID
 MODULE
 Cotms-Benefit-Master-IO
 BEN_PLAN_ID
 MODULE
FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

DELETERPBENFPLAN_IOPK_RES

Attribute	Description
Name	DELETERPBENFPLAN_IOPK_RES

Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	

Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	

Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Cotms-Benefit-Master-PK

Attribute	Description	
Name	Cotms-Benefit-Master-PK	
Datatype		
Description		

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	2

Cotms-Benefit-Master-IO

Attribute	Description
Name	Cotms-Benefit-Master-IO
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description				
Name	BEN_PLAN_ID				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

MODULE

Attribute	Description				
Name	MODULE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>2</td></tr></tbody></table>	Restrictions	Description	maxLength	2
Restrictions	Description				
maxLength	2				

FCUBS_ERROR_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.13.DeleteRPElgPlan

2.13.1.CO-DeleteRPElgPlan-Req-Full-MSG.xsd

DELETERPELGPLAN_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cotms-Elplan-Master-Full
EL_PLAN_CODE
EL_PLAN_DESC
EL_CONDITION
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Cotms-Elplan-Rde
RDE_CODE
RDE_PARAM_VAL
UDFDETAILS
FLDNAM

DELETERPELGPLAN_FSFS_REQ

Attribute	Description
Name	DELETERPELGPLAN_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute		Description	
Name	SOURCE_USERID		
Datatype	String		
Description	This is the user id in the Source system who is performing the action.		
Attribute	Attribute		Description
	minOccurs	0	

DESTINATION

Attribute		Description	
Name	DESTINATION		
Datatype	String		
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute		Description	
Name	MULTITRIPID		
Datatype	String		
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute		Description	
Name	FUNCTIONID		
Datatype	String		
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.		
Attribute	Attribute		Description
	minOccurs	0	

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Elplan-Master-Full

Attribute	Description
Name	Cotms-Elplan-Master-Full
Datatype	
Description	

EL_PLAN_CODE

Attribute	Description				
Name	EL_PLAN_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

EL_PLAN_DESC

Attribute	Description
-----------	-------------

Name	EL_PLAN_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

EL_CONDITION

Attribute	Description	
Name	EL_CONDITION	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	4000

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

Cotms-Elplan-Rde

Attribute	Description	
Name	Cotms-Elplan-Rde	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxOccurs	unbounded

RDE_CODE

Attribute	Description	
Name	RDE_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

RDE_PARAM_VAL

Attribute	Description	
Name	RDE_PARAM_VAL	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.13.2.CO-DeleteRPElgPlan-Req-IO-MSG.xsd

DELETERPELGPLAN_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Elplan-Master-IO

EL_PLAN_CODE

DELETERPELGPLAN_IOPK_REQ

Attribute	Description
Name	DELETERPELGPLAN_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Cotms-Elplan-Master-IO

Attribute		Description
------------------	--	--------------------

Name	Cotms-Elplan-Master-IO
Datatype	
Description	

EL_PLAN_CODE

Attribute	Description	
Name	EL_PLAN_CODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	35

2.13.3.CO-DeleteRPElgPlan-Res-Full-MSG.xsd

DELETERPELGPLAN_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Elplan-Master-Full

EL_PLAN_CODE

EL_PLAN_DESC

EL_CONDITION

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Cotms-Elplan-Rde

RDE_CODE

RDE_PARAM_VAL

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETERPELGPLAN_FSFS_RES

Attribute	Description
Name	DELETERPELGPLAN_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	
-------------	--

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Elplan-Master-Full

Attribute	Description
Name	Cotms-Elplan-Master-Full
Datatype	
Description	

EL_PLAN_CODE

Attribute	Description				
Name	EL_PLAN_CODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

EL_PLAN_DESC

Attribute	Description				
Name	EL_PLAN_DESC				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

EL_CONDITION

Attribute	Description				
Name	EL_CONDITION				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	4000

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Cotms-Elplan-Rde

Attribute	Description	
Name	Cotms-Elplan-Rde	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

RDE_CODE

Attribute	Description	
Name	RDE_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

RDE_PARAM_VAL

Attribute	Description	
Name	RDE_PARAM_VAL	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.13.4. CO-DeleteRPElgPlan-Res-PK-MSG.xsd

DELETERPELGPLAN_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Elplan-Master-PK

EL_PLAN_CODE

Cotms-Elplan-Master-IO

EL_PLAN_CODE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETERPELGPLAN_IOPK_RES

Attribute	Description
Name	DELETERPELGPLAN_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description

Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nullable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Elplan-Master-PK

Attribute	Description
Name	Cotms-Elplan-Master-PK
Datatype	
Description	

EL_PLAN_CODE

Attribute	Description				
Name	EL_PLAN_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

Cotms-Elplan-Master-IO

Attribute	Description
Name	Cotms-Elplan-Master-IO
Datatype	
Description	

EL_PLAN_CODE

Attribute	Description				
Name	EL_PLAN_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

FCUBS_ERROR_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

ERROR

Attribute	Description
-----------	-------------

Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

DELETERPERBENPLAN_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Ben-Exch-Master-C-Full

BEN_PLAN_ID

BEN_PLAN_DESC

PRIORITY_NO

APPLY_SPREAD_AS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Cotm-Ben-Exch-Detail-C

BUY_SPREAD

SALESPRD

BEN_PLAN_ID

RATTYP

VAR_CCY1

VAR_CCY2

UDFDETAILS

FLDNAM

FLDVAL

DELETERPERBENPLAN_FSFS_REQ

Attribute	Description
Name	DELETERPERBENPLAN_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

MSGID

Attribute	Description					
Name	MSGID					
Datatype	String					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	String					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Cotm-Ben-Exch-Master-C-Full
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description				
Name	BEN_PLAN_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

BEN_PLAN_DESC

Attribute	Description				
Name	BEN_PLAN_DESC				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

PRIORITY_NO

Attribute	Description				
Name	PRIORITY_NO				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>5</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	5
Restrictions	Description				
maxLength	5				

APPLY_SPREAD_AS

Attribute	Description				
Name	APPLY_SPREAD_AS				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>D,V</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	D,V
Restrictions	Description				
enumeration	D,V				

MAKER

Attribute	Description
-----------	-------------

Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description
------------------	--------------------

Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Cotm-Ben-Exch-Detail-C

Attribute	Description	
Name	Cotm-Ben-Exch-Detail-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BUY_SPREAD

Attribute	Description	
Name	BUY_SPREAD	
Datatype	Decimal	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

SALESPRD

Attribute	Description	
Name	SALESPRD	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

RATTYP

Attribute	Description	
Name	RATTYP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	8

VAR_CCY1

Attribute	Description	
Name	VAR_CCY1	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	3

VAR_CCY2

Attribute	Description				
Name	VAR_CCY2				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

FLDNAM

Attribute	Description						
Name	FLDNAM						
Datatype	String						
Description	Indicates Field Name						
Restrictions							
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	105	minLength	1
Restrictions	Description						
maxLength	105						
minLength	1						

FLDVAL

Attribute	Description						
Name	FLDVAL						
Datatype	String						
Description	Indicates Field Value						
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions							
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></tbody></table>	Restrictions	Description	maxLength	150	minLength	0
Restrictions	Description						
maxLength	150						
minLength	0						

2.14.2.CO-DeleteRPErBenPlan-Req-IO-MSG.xsd

DELETERPERBENPLAN_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cotm-Ben-Exch-Master-C-IO
BEN_PLAN_ID

DELETERPERBENPLAN_IOPK_REQ

Attribute	Description
Name	DELETERPERBENPLAN_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within EL EXCLUDE UBS. In

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotm-Ben-Exch-Master-C-IO

Attribute	Description
Name	Cotm-Ben-Exch-Master-C-IO
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description				
Name	BEN_PLAN_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

*2.14.3.CO-DeleteRPErBenPlan-Res-Full-MSG.xsd**DELETERPERBENPLAN_FSFS_RES**FCUBS_HEADER**SOURCE**UBSCOMP**MSGID**CORRELID**USERID**BRANCH**MODULEID**SERVICE**OPERATION*

SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTIRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cotm-Ben-Exch-Master-C-Full
BEN_PLAN_ID
BEN_PLAN_DESC
PRIORITY_NO
APPLY_SPREAD_AS
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Cotm-Ben-Exch-Detail-C
BUY_SPREAD
SALESPRD
BEN_PLAN_ID
RATTYP
VAR_CCY1
VAR_CCY2

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETERPERBENPLAN_FSFS_RES

Attribute	Description
Name	DELETERPERBENPLAN_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Cotm-Ben-Exch-Master-C-Full

Attribute	Description
------------------	--------------------

Name	Cotm-Ben-Exch-Master-C-Full
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

PRIORITY_NO

Attribute	Description	
Name	PRIORITY_NO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	5

APPLY_SPREAD_AS

Attribute	Description	
Name	APPLY_SPREAD_AS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	D,V

MAKER

Attribute	Description
Name	MAKER

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description
Name	MODNO

Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Cotm-Ben-Exch-Detail-C

Attribute	Description	
Name	Cotm-Ben-Exch-Detail-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BUY_SPREAD

Attribute	Description	
Name	BUY_SPREAD	
Datatype	Decimal	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

SALESPRD

Attribute	Description	
Name	SALESPRD	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

RATTYP

Attribute	Description	
Name	RATTYP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	8

VAR_CCY1

Attribute	Description	
Name	VAR_CCY1	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	3

VAR_CCY2

Attribute	Description				
Name	VAR_CCY2				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

FLDNAM

Attribute	Description						
Name	FLDNAM						
Datatype	String						
Description	Indicates Field Name						
Restrictions							
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	105	minLength	1
Restrictions	Description						
maxLength	105						
minLength	1						

FLDVAL

Attribute	Description						
Name	FLDVAL						
Datatype	String						
Description	Indicates Field Value						
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions							
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></tbody></table>	Restrictions	Description	maxLength	150	minLength	0
Restrictions	Description						
maxLength	150						
minLength	0						

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.14.4.CO-DeleteRPErBenPlan-Res-PK-MSG.xsd

DELETERPERBENPLAN_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Ben-Exch-Master-C-PK

BEN_PLAN_ID

Cotm-Ben-Exch-Master-C-IO

BEN_PLAN_ID

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETERPERBENPLAN_IOPK_RES

Attribute	Description
Name	DELETERPERBENPLAN_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

ORACLE®

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
Restrictions	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
Restrictions	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotm-Ben-Exch-Master-C-PK

Attribute	Description
Name	Cotm-Ben-Exch-Master-C-PK
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description
------------------	--------------------

Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

Cotm-Ben-Exch-Master-C-IO

Attribute	Description	
Name	Cotm-Ben-Exch-Master-C-IO	
Datatype		
Description		

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	

Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.15.DeleteRPSchMntc

2.15.1.CO-DeleteRPSchMntc-Req-Full-MSG.xsd

DELETERPSCHMNTC_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cotms-Scheme-Master-Full
SCHEME_ID1
SCHEME_DESC
SC_START_DT
SC_END_DT
BEN_VALID_PERIOD
BEN_VALID_BASIS
VALID_TYPE
APPLY_FOR
EXECUTABLE_TYPE
RENEW_TYPE
SCHEME_RP_DESC
BEN_EXPIRY
SCHEME_STATUS
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Elig

EL_PLAN_CODE

EL_REV_FREQ

FIRST_REV_DT

LAST_REV_DT

NEXT_REV_DT

Cotms-Scheme-Detail

BEN_PLAN_ID

BEN_PLAN_DESC

UDFDETAILS

FLDNAM

FLDVAL

DELETERPSCHMNTC_FSFS_REQ

Attribute	Description
Name	DELETERPSCHMNTC_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
-----------	-------------

Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Cotms-Scheme-Master-Full
Datatype	
Description	

SCHEME_ID1

Attribute	Description				
Name	SCHEME_ID1				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

SCHEME_DESC

Attribute	Description				
Name	SCHEME_DESC				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

SC_START_DT

Attribute	Description
Name	SC_START_DT
Datatype	String
Description	

SC_END_DT

Attribute	Description
Name	SC_END_DT
Datatype	String
Description	

BEN_VALID_PERIOD

Attribute	Description				
Name	BEN_VALID_PERIOD				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

BEN_VALID_BASIS

Attribute	Description
-----------	-------------

Name	BEN_VALID_BASIS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Y,

VALID_TYPE

Attribute	Description	
Name	VALID_TYPE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	O,R,P,

APPLY_FOR

Attribute	Description	
Name	APPLY_FOR	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	N,A,E,

EXECUTABLE_TYPE

Attribute	Description	
Name	EXECUTABLE_TYPE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	M,A,

RENEW_TYPE

Attribute	Description	
Name	RENEW_TYPE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	B,S,

SCHEME_RP_DESC

Attribute	Description	
Name	SCHEME_RP_DESC	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

BEN_EXPIRY

Attribute	Description	
Name	BEN_EXPIRY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

SCHEME_STATUS

Attribute	Description	
Name	SCHEME_STATUS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	A,E

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description
Name	TXNSTAT

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Elig

Attribute	Description	
Name	Elig	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

EL_PLAN_CODE

Attribute	Description	
Name	EL_PLAN_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

EL_REV_FREQ

Attribute	Description	
Name	EL_REV_FREQ	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	D,W,F,M,Q,H,Y

FIRST_REV_DT

Attribute	Description
Name	FIRST_REV_DT
Datatype	String
Description	

LAST_REV_DT

Attribute	Description				
Name	LAST_REV_DT				
Datatype	String				
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

NEXT_REV_DT

Attribute	Description				
Name	NEXT_REV_DT				
Datatype	String				
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Cotms-Scheme-Detail

Attribute	Description						
Name	Cotms-Scheme-Detail						
Datatype							
Description							
Attribute							
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

BEN_PLAN_ID

Attribute	Description				
Name	BEN_PLAN_ID				
Datatype	String				
Description					
Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

BEN_PLAN_DESC

Attribute	Description				
Name	BEN_PLAN_DESC				
Datatype	String				
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.15.2.CO-DeleteRPSchMntc-Req-IO-MSG.xsd

DELETERPSCHMNTC_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cotms-Scheme-Master-IO
SCHEME_ID1

DELETERPSCHMNTC_IOPK_REQ

Attribute	Description
Name	DELETERPSCHMNTC_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Scheme-Master-IO

Attribute	Description
Name	Cotms-Scheme-Master-IO
Datatype	
Description	

SCHEME_ID1

Attribute	Description				
Name	SCHEME_ID1				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

*2.15.3.CO-DeleteRPSchMntc-Res-Full-MSG.xsd**DELETERPSCHMNTC_FSFS_RES**FCUBS_HEADER**SOURCE**UBSCOMP**MSGID**CORRELID**USERID**BRANCH**MODULEID**SERVICE**OPERATION*

SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cotms-Scheme-Master-Full
SCHEME_ID1
SCHEME_DESC
SC_START_DT
SC_END_DT
BEN_VALID_PERIOD
BEN_VALID_BASIS
VALID_TYPE
APPLY_FOR
EXECUTABLE_TYPE
RENEW_TYPE
SCHEME_RP_DESC
BEN_EXPIRY
SCHEME_STATUS
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO

TXNSTAT

AUTHSTAT

Elig

EL_PLAN_CODE

EL_REV_FREQ

FIRST_REV_DT

LAST_REV_DT

NEXT_REV_DT

Cotms-Scheme-Detail

BEN_PLAN_ID

BEN_PLAN_DESC

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETERPSCHMNTC_FSFS_RES

Attribute	Description
Name	DELETERPSCHMNTC_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Scheme-Master-Full

Attribute	Description
Name	Cotms-Scheme-Master-Full
Datatype	
Description	

SCHEME_ID1

Attribute	Description				
Name	SCHEME_ID1				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

SCHEME_DESC

Attribute	Description				
Name	SCHEME_DESC				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

SC_START_DT

Attribute	Description
Name	SC_START_DT
Datatype	String
Description	

SC_END_DT

Attribute	Description

Name	SC_END_DT
Datatype	String
Description	

BEN_VALID_PERIOD

Attribute	Description	
Name	BEN_VALID_PERIOD	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

BEN_VALID_BASIS

Attribute	Description	
Name	BEN_VALID_BASIS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	D,M,Y,

VALID_TYPE

Attribute	Description	
Name	VALID_TYPE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	O,R,P,

APPLY_FOR

Attribute	Description	
Name	APPLY_FOR	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	N,A,E,

EXECUTABLE_TYPE

Attribute	Description
Name	EXECUTABLE_TYPE

Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	M,A,

RENEW_TYPE

Attribute	Description	
Name	RENEW_TYPE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	B,S,

SCHEME_RP_DESC

Attribute	Description	
Name	SCHEME_RP_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

BEN_EXPIRY

Attribute	Description	
Name	BEN_EXPIRY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

SCHEME_STATUS

Attribute	Description	
Name	SCHEME_STATUS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	A,E

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Elig

Attribute	Description	
Name	Elig	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

EL_PLAN_CODE

Attribute	Description	
Name	EL_PLAN_CODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	35

EL_REV_FREQ

Attribute	Description	
Name	EL_REV_FREQ	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	D,W,F,M,Q,H,Y

FIRST_REV_DT

Attribute	Description	
Name	FIRST_REV_DT	
Datatype	String	
Description		

LAST_REV_DT

Attribute	Description	
Name	LAST_REV_DT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

NEXT_REV_DT

Attribute	Description	
Name	NEXT_REV_DT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

Cotms-Scheme-Detail

Attribute	Description	
Name	Cotms-Scheme-Detail	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL

Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	150
	minLength	0
	Description	

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	
	maxOccurs	unbounded
	Description	

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.15.4.CO-DeleteRPSchMntc-Res-PK-MSG.xsd

DELETERPSCHMNTC_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Scheme-Master-PK

SCHEME_ID1

Cotms-Scheme-Master-IO

SCHEME_ID1

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETERPSCHMNTC_IOPK_RES

Attribute	Description
Name	DELETERPSCHMNTC_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
pattern	[A-Z_0-9]*	

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Scheme-Master-PK

Attribute	Description
Name	Cotms-Scheme-Master-PK
Datatype	
Description	

SCHEME_ID1

Attribute	Description				
Name	SCHEME_ID1				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

Cotms-Scheme-Master-IO

Attribute	Description
Name	Cotms-Scheme-Master-IO
Datatype	
Description	

SCHEME_ID1

Attribute	Description				
Name	SCHEME_ID1				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

FCUBS_ERROR_RESP

Attribute	Description
-----------	-------------

Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	
	Description	
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	
	Description	
	maxOccurs	unbounded

WCODE

Attribute	Description
------------------	--------------------

Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.16.ModifyCSMBPLinkage

2.16.1.CO-ModifyCSMBPLinkage-Req-Full-MSG.xsd

MODIFYCSMBPLINKAGE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Csm-Ben-Master-C-Full

CSM
CUSTOMER_NO
CSM_DESC
CUSTOMER_NAME
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Cotm-Csm-Ben-Detail-C
BEN_START_DT
MODULE
BEN_PLAN_TYPE
BEN_PLAN_ID
BEN_PLAN_DESC
PRIORITYNO
BEN_END_DT

MODIFYCSMBPLINKAGE_FSFS_REQ

Attribute	Description
Name	MODIFYCSMBPLINKAGE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotm-Csm-Ben-Master-C-Full

Attribute	Description
Name	Cotm-Csm-Ben-Master-C-Full
Datatype	
Description	

CSM

Attribute	Description				
Name	CSM				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

CUSTOMER_NO

Attribute	Description				
Name	CUSTOMER_NO				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

CSM_DESC

Attribute	Description				
Name	CSM_DESC				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	255

CUSTOMER_NAME

Attribute	Description	
Name	CUSTOMER_NAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

Cotm-Csm-Ben-Detail-C

Attribute	Description	
Name	Cotm-Csm-Ben-Detail-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BEN_START_DT

Attribute	Description	
Name	BEN_START_DT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	2

BEN_PLAN_TYPE

Attribute	Description	
Name	BEN_PLAN_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_ID

Attribute	Description
------------------	--------------------

Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

PRIORITYNO

Attribute	Description	
Name	PRIORITYNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

BEN_END_DT

Attribute	Description	
Name	BEN_END_DT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

2.16.2.CO-ModifyCSMBPLinkage-Req-IO-MSG.xsd

MODIFYCSMBPLINKAGE_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
 PARAM
 NAME
 VALUE
FCUBS_BODY
 Cotm-Csm-Ben-Master-C-IO
 CSM
 CUSTOMER_NO
 MAKER
 MAKERSTAMP
 Cotm-Csm-Ben-Detail-C
 BEN_START_DT
 BEN_PLAN_ID
 BEN_END_DT

MODIFYCSMBPLINKAGE_IOPK_REQ

Attribute	Description
Name	MODIFYCSMBPLINKAGE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotm-Csm-Ben-Master-C-IO

Attribute	Description
Name	Cotm-Csm-Ben-Master-C-IO
Datatype	
Description	

CSM

Attribute	Description				
Name	CSM				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

CUSTOMER_NO

Attribute	Description				
Name	CUSTOMER_NO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

Cotm-Csm-Ben-Detail-C

Attribute	Description	
Name	Cotm-Csm-Ben-Detail-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

BEN_START_DT

Attribute	Description	
Name	BEN_START_DT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_END_DT

Attribute	Description	
Name	BEN_END_DT	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0

2.16.3.CO-ModifyCSMBPLinkage-Res-Full-MSG.xsd

MODIFYCSMBPLINKAGE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Csm-Ben-Master-C-Full

CSM

CUSTOMER_NO

CSM_DESC

CUSTOMER_NAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Cotm-Csm-Ben-Detail-C

BEN_START_DT

MODULE

BEN_PLAN_TYPE

BEN_PLAN_ID

BEN_PLAN_DESC

PRIORITYNO

BEN_END_DT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYCSMBPLINKAGE_FSFS_RES

Attribute	Description
Name	MODIFYCSMBPLINKAGE_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
pattern	[A-Z_0-9]*	

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotm-Csm-Ben-Master-C-Full

Attribute	Description
Name	Cotm-Csm-Ben-Master-C-Full
Datatype	
Description	

CSM

Attribute	Description				
Name	CSM				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

CUSTOMER_NO

Attribute	Description				
Name	CUSTOMER_NO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

CSM_DESC

Attribute	Description				
Name	CSM_DESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	255

CUSTOMER_NAME

Attribute	Description	
Name	CUSTOMER_NAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

Cotm-Csm-Ben-Detail-C

Attribute	Description	
Name	Cotm-Csm-Ben-Detail-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BEN_START_DT

Attribute	Description	
Name	BEN_START_DT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	2

BEN_PLAN_TYPE

Attribute	Description	
Name	BEN_PLAN_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_ID

Attribute	Description
------------------	--------------------

Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

PRIORITYNO

Attribute	Description	
Name	PRIORITYNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

BEN_END_DT

Attribute	Description	
Name	BEN_END_DT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String

Description	
-------------	--

2.16.4. CO-ModifyCSMBPLinkage-Res-PK-MSG.xsd

MODIFYCSMBPLINKAGE_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Csm-Ben-Master-C-PK

CUSTOMER_NO

CSM

Cotm-Csm-Ben-Master-C-IO

CSM

CUSTOMER_NO

MAKER

MAKERSTAMP

Cotm-Csm-Ben-Detail-C

BEN_START_DT

BEN_PLAN_ID

BEN_END_DT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYCSMBPLINKAGE_IOPK_RES

Attribute	Description
Name	MODIFYCSMBPLINKAGE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Cotm-Csm-Ben-Master-C-PK

Attribute	Description
------------------	--------------------

Name	Cotm-Csm-Ben-Master-C-PK
Datatype	
Description	

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

CSM

Attribute	Description	
Name	CSM	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

Cotm-Csm-Ben-Master-C-IO

Attribute	Description
Name	Cotm-Csm-Ben-Master-C-IO
Datatype	
Description	

CSM

Attribute	Description	
Name	CSM	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

MAKER

Attribute	Description
Name	MAKER
Datatype	String

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

Cotm-Csm-Ben-Detail-C

Attribute	Description	
Name	Cotm-Csm-Ben-Detail-C	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

BEN_START_DT

Attribute	Description	
Name	BEN_START_DT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	35

BEN_END_DT

Attribute	Description
------------------	--------------------

Name	BEN_END_DT	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	
	Description	
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description
------------------	--------------------

Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.17.ModifyRPBenfPlan

2.17.1.CO-ModifyRPBenfPlan-Req-Full-MSG.xsd

MODIFYRPBENFPLAN_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Benefit-Master-Full

BEN_PLAN_ID

BEN_PLAN_DESC

MODULE

PRIORITY_NO

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Cotms-Benefit-Details

PRODUCT

PRICE_COMP_TYPE

PRICE_COMP

BEN_TYPE

VAR_TYPE

VAR_CCY

VAR_VALUE

VAR_RULE

MAX_VALUE

MIN_VALUE

CCY_CODE

UDFDETAILS

FLDNAM

FLDVAL

MODIFYRPBENFPLAN_FSFS_REQ

Attribute	Description
Name	MODIFYRPBENFPLAN_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute		Description	
Name	SOURCE_USERID		
Datatype	String		
Description	This is the user id in the Source system who is performing the action.		
Attribute	Attribute		Description
	minOccurs	0	

DESTINATION

Attribute		Description	
Name	DESTINATION		
Datatype	String		
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute		Description	
Name	MULTITRIPID		
Datatype	String		
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute		Description	
Name	FUNCTIONID		
Datatype	String		
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.		
Attribute	Attribute		Description
	minOccurs	0	

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Benefit-Master-Full

Attribute	Description
Name	Cotms-Benefit-Master-Full
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description				
Name	BEN_PLAN_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

BEN_PLAN_DESC

Attribute	Description
-----------	-------------

Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	2

PRIORITY_NO

Attribute	Description	
Name	PRIORITY_NO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	5

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Cotms-Benefit-Details

Attribute	Description	
Name	Cotms-Benefit-Details	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

PRODUCT

Attribute	Description	
Name	PRODUCT	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	4

PRICE_COMP_TYPE

Attribute	Description	
Name	PRICE_COMP_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	I,C,F,M

PRICE_COMP

Attribute	Description
------------------	--------------------

Name	PRICE_COMP	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_TYPE

Attribute	Description	
Name	BEN_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	V,W,

VAR_TYPE

Attribute	Description	
Name	VAR_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	F,A,P,V,T,N,

VAR_CCY

Attribute	Description	
Name	VAR_CCY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

VAR_VALUE

Attribute	Description	
Name	VAR_VALUE	
Datatype	Decimal	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

VAR_RULE

Attribute	Description	
Name	VAR_RULE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MAX_VALUE

Attribute	Description	
Name	MAX_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

MIN_VALUE

Attribute	Description	
Name	MIN_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

CCY_CODE

Attribute	Description	
Name	CCY_CODE	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.17.2.CO-ModifyRPBenfPlan-Req-IO-MSG.xsd

MODIFYRPBENFPLAN_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cotms-Benefit-Master-IO
BEN_PLAN_ID
BEN_PLAN_DESC
MODULE
PRIORITY_NO
MAKER
MAKERSTAMP
Cotms-Benefit-Details
PRICE_COMP_TYPE
BEN_TYPE
VAR_TYPE
VAR_CCY
VAR_CCY2
MAX_VALUE

MIN_VALUE

UDFDETAILS

FLDNAM

FLDVAL

MODIFYRPBENFPLAN_IOPK_REQ

Attribute	Description
Name	MODIFYRPBENFPLAN_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field. 726

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*
	Description	

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*
	Description	

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	enumeration	SUCCESS,WARNING,FAILURE
	Description	

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*
	Description	

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0
	maxOccurs		unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Cotms-Benefit-Master-IO

Attribute		Description	
Name		Cotms-Benefit-Master-IO	
Datatype			
Description			

BEN_PLAN_ID

Attribute		Description	
Name		BEN_PLAN_ID	
Datatype		String	
Description			
Restrictions	Restrictions		Description
	maxLength		35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	2

PRIORITY_NO

Attribute	Description	
Name	PRIORITY_NO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	5

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

Cotms-Benefit-Details

Attribute	Description	
Name	Cotms-Benefit-Details	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

PRICE_COMP_TYPE

Attribute	Description	
Name	PRICE_COMP_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	I,C,F,M

BEN_TYPE

Attribute	Description	
Name	BEN_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	V,W,

VAR_TYPE

Attribute	Description	
Name	VAR_TYPE	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	F,A,P,V,T,N,

VAR_CCY

Attribute	Description	
Name	VAR_CCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

VAR_CCY2

Attribute	Description	
Name	VAR_CCY2	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

MAX_VALUE

Attribute	Description	
Name	MAX_VALUE	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MIN_VALUE

Attribute	Description	
Name	MIN_VALUE	
Datatype	Decimal	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
Restrictions	Restrictions	Description
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
Restrictions	Restrictions	Description
	minLength	0

2.17.3.CO-ModifyRPBenfPlan-Res-Full-MSG.xsd

MODIFYRPBENFPLAN_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cotms-Benefit-Master-Full
BEN_PLAN_ID
BEN_PLAN_DESC
MODULE
PRIORITY_NO
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Cotms-Benefit-Details
PRODUCT

PRICE_COMP_TYPE

PRICE_COMP

BEN_TYPE

VAR_TYPE

VAR_CCY

VAR_VALUE

VAR_RULE

MAX_VALUE

MIN_VALUE

CCY_CODE

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYRPBENFPLAN_FSFS_RES

Attribute	Description
Name	MODIFYRPBENFPLAN_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within EL EXCLUDE UBS. In

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Benefit-Master-Full

Attribute	Description
Name	Cotms-Benefit-Master-Full
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description				
Name	BEN_PLAN_ID				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

BEN_PLAN_DESC

Attribute	Description				
Name	BEN_PLAN_DESC				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

MODULE

Attribute	Description				
Name	MODULE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>2</td></tr></tbody></table>	Restrictions	Description	maxLength	2
Restrictions	Description				
maxLength	2				

PRIORITY_NO

Attribute	Description	
Name	PRIORITY_NO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	5

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute		Description	
Name	CHECKERSTAMP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

MODNO

Attribute		Description	
Name	MODNO		
Datatype	Decimal		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	totalDigits	4	

TXNSTAT

Attribute		Description	
Name	TXNSTAT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1	

AUTHSTAT

Attribute		Description	
Name	AUTHSTAT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1	

Attribute	Description	
Name	Cotms-Benefit-Details	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

PRODUCT

Attribute	Description	
Name	PRODUCT	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	4

PRICE_COMP_TYPE

Attribute	Description	
Name	PRICE_COMP_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	I,C,F,M

PRICE_COMP

Attribute	Description	
Name	PRICE_COMP	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_TYPE

Attribute	Description	
Name	BEN_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	V,W,

VAR_TYPE

Attribute	Description	
Name	VAR_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	F,A,P,V,T,N,

VAR_CCY

Attribute	Description	
Name	VAR_CCY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

VAR_VALUE

Attribute	Description	
Name	VAR_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

VAR_RULE

Attribute	Description	
Name	VAR_RULE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

MAX_VALUE

Attribute	Description	
Name	MAX_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

MIN_VALUE

Attribute	Description	
Name	MIN_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

CCY_CODE

Attribute	Description	
Name	CCY_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.17.4.CO-ModifyRPBenfPlan-Res-PK-MSG.xsd

MODIFYRPBENFPLAN_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cotms-Benefit-Master-PK
BEN_PLAN_ID
MODULE
Cotms-Benefit-Master-IO
BEN_PLAN_ID
BEN_PLAN_DESC
MODULE
PRIORITY_NO
MAKER
MAKERSTAMP
Cotms-Benefit-Details
PRICE_COMP_TYPE
BEN_TYPE
VAR_TYPE
VAR_CCY
VAR_CCY2
MAX_VALUE

MIN_VALUE

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYRPBENFPLAN_IOPK_RES

Attribute	Description
Name	MODIFYRPBENFPLAN_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Cotms-Benefit-Master-PK

Attribute	Description
------------------	--------------------

Name	Cotms-Benefit-Master-PK
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	2

Cotms-Benefit-Master-IO

Attribute	Description	
Name	Cotms-Benefit-Master-IO	
Datatype		
Description		

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	2

PRIORITY_NO

Attribute	Description	
Name	PRIORITY_NO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	5

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

Cotms-Benefit-Details

Attribute	Description	
Name	Cotms-Benefit-Details	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

PRICE_COMP_TYPE

Attribute	Description	
Name	PRICE_COMP_TYPE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	I,C,F,M

BEN_TYPE

Attribute	Description	
Name	BEN_TYPE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	V,W,

VAR_TYPE

Attribute	Description	
Name	VAR_TYPE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	F,A,P,V,T,N,

VAR_CCY

Attribute	Description	
Name	VAR_CCY	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

VAR_CCY2

Attribute	Description	
Name	VAR_CCY2	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

MAX_VALUE

Attribute	Description	
Name	MAX_VALUE	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MIN_VALUE

Attribute	Description	
Name	MIN_VALUE	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
------------------	--------------------

Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.18.ModifyRPEIPlan

2.18.1.CO-ModifyRPEIPlan-Req-Full-MSG.xsd

MODIFYRPELGPLAN_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cotms-Elplan-Master-Full
EL_PLAN_CODE
EL_PLAN_DESC
EL_CONDITION
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Cotms-Elplan-Rde
RDE_CODE

RDE_PARAM_VAL

UDFDETAILS

FLDNAM

FLDVAL

MODIFYRPELGPLAN_FSFS_REQ

Attribute	Description
Name	MODIFYRPELGPLAN_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field. 765

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*
	Description	

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*
	Description	

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	enumeration	SUCCESS,WARNING,FAILURE
	Description	

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*
	Description	

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0
	maxOccurs		unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Cotms-Elplan-Master-Full

Attribute		Description	
Name		Cotms-Elplan-Master-Full	
Datatype			
Description			

EL_PLAN_CODE

Attribute		Description	
Name		EL_PLAN_CODE	
Datatype		String	
Description			
Restrictions	Restrictions		Description
	maxLength		35

EL_PLAN_DESC

Attribute	Description				
Name	EL_PLAN_DESC				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
	Restrictions	Description			
maxLength	105				

EL_CONDITION

Attribute	Description				
Name	EL_CONDITION				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>4000</td></tr></tbody></table>	Restrictions	Description	maxLength	4000
	Restrictions	Description			
maxLength	4000				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
	Restrictions	Description			
maxLength	35				

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Cotms-Elplan-Rde

Attribute	Description	
Name	Cotms-Elplan-Rde	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

RDE_CODE

Attribute	Description	
Name	RDE_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

RDE_PARAM_VAL

Attribute	Description	
Name	RDE_PARAM_VAL	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.18.2.CO-ModifyRPElgPlan-Req-IO-MSG.xsd

MODIFYRPELGPLAN_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Elplan-Master-IO

EL_PLAN_CODE

EL_PLAN_DESC

EL_CONDITION

MAKER

MAKERSTAMP

UDFDETAILS

FLDNAM

FLDVAL

MODIFYRPELGPLAN_IOPK_REQ

Attribute	Description
Name	MODIFYRPELGPLAN_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Elplan-Master-IO

Attribute	Description
Name	Cotms-Elplan-Master-IO
Datatype	
Description	

EL_PLAN_CODE

Attribute	Description				
Name	EL_PLAN_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

EL_PLAN_DESC

Attribute	Description				
Name	EL_PLAN_DESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

EL_CONDITION

Attribute	Description
Name	EL_CONDITION
Datatype	String
Description	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	4000

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.18.3.CO-ModifyRPElgPlan-Res-Full-MSG.xsd

MODIFYRPELGPLAN_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM
NAME
VALUE
FCUBS_BODY
Cotms-Elplan-Master-Full
EL_PLAN_CODE
EL_PLAN_DESC
EL_CONDITION
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Cotms-Elplan-Rde
RDE_CODE
RDE_PARAM_VAL
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

MODIFYRPELGPLAN_FSFS_RES

Attribute	Description
Name	MODIFYRPELGPLAN_FSFS_RES

Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	

Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	

Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Cotms-Elplan-Master-Full

Attribute	Description	
Name	Cotms-Elplan-Master-Full	
Datatype		
Description		

EL_PLAN_CODE

Attribute	Description	
Name	EL_PLAN_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

EL_PLAN_DESC

Attribute	Description	
Name	EL_PLAN_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

EL_CONDITION

Attribute	Description	
Name	EL_CONDITION	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4000

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute		Description	
Name	CHECKERSTAMP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

MODNO

Attribute		Description	
Name	MODNO		
Datatype	Decimal		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	totalDigits	4	

TXNSTAT

Attribute		Description	
Name	TXNSTAT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1	

AUTHSTAT

Attribute		Description	
Name	AUTHSTAT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1	

Attribute	Description	
Name	Cotms-Elplan-Rde	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

RDE_CODE

Attribute	Description	
Name	RDE_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

RDE_PARAM_VAL

Attribute	Description	
Name	RDE_PARAM_VAL	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.18.4.CO-ModifyRPElgPlan-Res-PK-MSG.xsd

MODIFYRPELGPLAN_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Elplan-Master-PK

EL_PLAN_CODE

Cotms-Elplan-Master-IO

EL_PLAN_CODE

EL_PLAN_DESC

EL_CONDITION

MAKER

MAKERSTAMP

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYRPELGPLAN_IOPK_RES

Attribute	Description
-----------	-------------

Name	MODIFYRPELGPLAN_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	
	Description	
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	
	Description	
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	

Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	

Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Cotms-Elplan-Master-PK

Attribute	Description	
Name	Cotms-Elplan-Master-PK	
Datatype		
Description		

EL_PLAN_CODE

Attribute	Description	
Name	EL_PLAN_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

Cotms-Elplan-Master-IO

Attribute	Description	
Name	Cotms-Elplan-Master-IO	
Datatype		
Description		

EL_PLAN_CODE

Attribute	Description	
-----------	-------------	--

Name	EL_PLAN_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

EL_PLAN_DESC

Attribute	Description	
Name	EL_PLAN_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

EL_CONDITION

Attribute	Description	
Name	EL_CONDITION	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	4000

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String

2.19.ModifyRPErBenPlan

2.19.1.CO-ModifyRPErBenPlan-Req-Full-MSG.xsd

MODIFYRPERBENPLAN_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Ben-Exch-Master-C-Full

BEN_PLAN_ID

BEN_PLAN_DESC

PRIORITY_NO

APPLY_SPREAD_AS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Cotm-Ben-Exch-Detail-C

BUY_SPREAD

SALESPRD

BEN_PLAN_ID

RATTYP

VAR_CCY1

VAR_CCY2

UDFDETAILS

FLDNAM

FLDVAL

MODIFYRPERBENPLAN_FSFS_REQ

Attribute	Description
Name	MODIFYRPERBENPLAN_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description
Name	USERID

Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotm-Ben-Exch-Master-C-Full

Attribute	Description
Name	Cotm-Ben-Exch-Master-C-Full
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description				
Name	BEN_PLAN_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

BEN_PLAN_DESC

Attribute	Description				
Name	BEN_PLAN_DESC				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

PRIORITY_NO

Attribute	Description				
Name	PRIORITY_NO				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>5</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	5
Restrictions	Description				
maxLength	5				

APPLY_SPREAD_AS

Attribute	Description
Name	APPLY_SPREAD_AS
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,V

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

Cotm-Ben-Exch-Detail-C

Attribute	Description	
Name	Cotm-Ben-Exch-Detail-C	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BUY_SPREAD

Attribute	Description	
Name	BUY_SPREAD	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

SALESPRD

Attribute	Description	
Name	SALESPRD	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

RATTYP

Attribute	Description	
Name	RATTYP	
Datatype	String	
Description		

Restrictions		
	Restrictions	Description
	maxLength	8

VAR_CCY1

Attribute	Description	
Name	VAR_CCY1	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

VAR_CCY2

Attribute	Description	
Name	VAR_CCY2	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.19.2.CO-ModifyRPErBenPlan-Req-IO-MSG.xsd

MODIFYRPERBENPLAN_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Ben-Exch-Master-C-IO

BEN_PLAN_ID

PRIORITY_NO

APPLY_SPREAD_AS

MAKER

MAKERSTAMP

Cotm-Ben-Exch-Detail-C

BUY_SPREAD

SALESPRD

RATTYP

VAR_CCY1

VAR_CCY2

UDFDETAILS

FLDNAM

FLDVAL

MODIFYRPERBENPLAN_IOPK_REQ

Attribute	Description
Name	MODIFYRPERBENPLAN_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Cotm-Ben-Exch-Master-C-IO

Attribute		Description
------------------	--	--------------------

Name	Cotm-Ben-Exch-Master-C-IO
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	35

PRIORITY_NO

Attribute	Description	
Name	PRIORITY_NO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	5

APPLY_SPREAD_AS

Attribute	Description	
Name	APPLY_SPREAD_AS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,V

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

Cotm-Ben-Exch-Detail-C

Attribute	Description	
Name	Cotm-Ben-Exch-Detail-C	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BUY_SPREAD

Attribute	Description	
Name	BUY_SPREAD	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

SALESPRD

Attribute	Description	
Name	SALESPRD	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

RATTYP

Attribute	Description
Name	RATTYP

Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	8

VAR_CCY1

Attribute	Description	
Name	VAR_CCY1	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

VAR_CCY2

Attribute	Description	
Name	VAR_CCY2	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.19.3.CO-ModifyRPErBenPlan-Res-Full-MSG.xsd

MODIFYRPERBENPLAN_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Ben-Exch-Master-C-Full

BEN_PLAN_ID

BEN_PLAN_DESC
PRIORITY_NO
APPLY_SPREAD_AS
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Cotm-Ben-Exch-Detail-C
BUY_SPREAD
SALESPRD
BEN_PLAN_ID
RATTYP
VAR_CCY1
VAR_CCY2
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

MODIFYRPERBENPLAN_FSFS_RES

Attribute	Description
Name	MODIFYRPERBENPLAN_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotm-Ben-Exch-Master-C-Full

Attribute	Description
Name	Cotm-Ben-Exch-Master-C-Full
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions	Restrictions	
	Description	
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Restrictions	Restrictions	
	Description	
	maxLength	105

PRIORITY_NO

Attribute	Description
Name	PRIORITY_NO

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	5

APPLY_SPREAD_AS

Attribute	Description	
Name	APPLY_SPREAD_AS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	D,V

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	

Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	1
	Description	

Cotm-Ben-Exch-Detail-C

Attribute	Description	
Name	Cotm-Ben-Exch-Detail-C	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

BUY_SPREAD

Attribute	Description	
Name	BUY_SPREAD	
Datatype	Decimal	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	totalDigits	22
	Description	

SALESPRD

Attribute	Description	
Name	SALESPRD	
Datatype	Decimal	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	totalDigits	22
	Description	

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

RATTYP

Attribute	Description	
Name	RATTYP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	8

VAR_CCY1

Attribute	Description	
Name	VAR_CCY1	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	3

VAR_CCY2

Attribute	Description	
Name	VAR_CCY2	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	3

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.19.4.CO-ModifyRPErBenPlan-Res-PK-MSG.xsd

MODIFYRPERBENPLAN_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Ben-Exch-Master-C-PK

BEN_PLAN_ID

Cotm-Ben-Exch-Master-C-IO

BEN_PLAN_ID

PRIORITY_NO

APPLY_SPREAD_AS

MAKER

MAKERSTAMP

Cotm-Ben-Exch-Detail-C

BUY_SPREAD

SALESPRD

RATTYP

VAR_CCY1

VAR_CCY2

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYRPERBENPLAN_IOPK_RES

Attribute	Description
Name	MODIFYRPERBENPLAN_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field. 843

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0
	maxOccurs		unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Cotm-Ben-Exch-Master-C-PK

Attribute		Description	
Name		Cotm-Ben-Exch-Master-C-PK	
Datatype			
Description			

BEN_PLAN_ID

Attribute		Description	
Name		BEN_PLAN_ID	
Datatype		String	
Description			
Restrictions	Restrictions		Description
	maxLength		35

Cotm-Ben-Exch-Master-C-IO

Attribute	Description
Name	Cotm-Ben-Exch-Master-C-IO
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description				
Name	BEN_PLAN_ID				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

PRIORITY_NO

Attribute	Description				
Name	PRIORITY_NO				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>5</td></tr></tbody></table>	Restrictions	Description	maxLength	5
Restrictions	Description				
maxLength	5				

APPLY_SPREAD_AS

Attribute	Description				
Name	APPLY_SPREAD_AS				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>D,V</td></tr></tbody></table>	Restrictions	Description	enumeration	D,V
Restrictions	Description				
enumeration	D,V				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

Cotm-Ben-Exch-Detail-C

Attribute	Description	
Name	Cotm-Ben-Exch-Detail-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BUY_SPREAD

Attribute	Description	
Name	BUY_SPREAD	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

SALESPRD

Attribute	Description	
Name	SALESPRD	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	22

RATTYP

Attribute	Description	
Name	RATTYP	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	8

VAR_CCY1

Attribute	Description	
Name	VAR_CCY1	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

VAR_CCY2

Attribute	Description	
Name	VAR_CCY2	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description						
Name	FLDVAL						
Datatype	String						
Description	Indicates Field Value						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></tbody></table>	Restrictions	Description	maxLength	150	minLength	0
	Restrictions	Description					
	maxLength	150					
minLength	0						

FCUBS_ERROR_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
	Attribute	Description					
	minOccurs	0					
maxOccurs	unbounded						

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.20.ModifyRPSchMntc

2.20.1.CO-ModifyRPSchMntc-Req-Full-MSG.xsd

MODIFYRPSCHMNTC_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cotms-Scheme-Master-Full
SCHEME_ID1
SCHEME_DESC
SC_START_DT
SC_END_DT
BEN_VALID_PERIOD
BEN_VALID_BASIS
VALID_TYPE
APPLY_FOR
EXECUTABLE_TYPE
RENEW_TYPE
SCHEME_RP_DESC
BEN_EXPIRY
SCHEME_STATUS
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Elig

EL_PLAN_CODE

EL_REV_FREQ

FIRST_REV_DT

LAST_REV_DT

NEXT_REV_DT

Cotms-Scheme-Detail

BEN_PLAN_ID

BEN_PLAN_DESC

UDFDETAILS

FLDNAM

FLDVAL

MODIFYRPSCHMNTC_FSFS_REQ

Attribute	Description
Name	MODIFYRPSCHMNTC_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Cotms-Scheme-Master-Full

Attribute	Description
------------------	--------------------

Name	Cotms-Scheme-Master-Full
Datatype	
Description	

SCHEME_ID1

Attribute	Description	
Name	SCHEME_ID1	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

SCHEME_DESC

Attribute	Description	
Name	SCHEME_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

SC_START_DT

Attribute	Description	
Name	SC_START_DT	
Datatype	String	
Description		

SC_END_DT

Attribute	Description	
Name	SC_END_DT	
Datatype	String	
Description		

BEN_VALID_PERIOD

Attribute	Description	
Name	BEN_VALID_PERIOD	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

BEN_VALID_BASIS

Attribute	Description	
Name	BEN_VALID_BASIS	
Datatype	String	

Description	
Attribute	Attribute
	minOccurs
Restrictions	Description
	0
Restrictions	Restrictions
	enumeration
	Description
	D,M,Y,

VALID_TYPE

Attribute	Description
Name	VALID_TYPE
Datatype	String
Description	
Restrictions	Restrictions
	enumeration
	Description
	O,R,P,

APPLY_FOR

Attribute	Description
Name	APPLY_FOR
Datatype	String
Description	
Restrictions	Restrictions
	enumeration
	Description
	N,A,E,

EXECUTABLE_TYPE

Attribute	Description
Name	EXECUTABLE_TYPE
Datatype	String
Description	
Restrictions	Restrictions
	enumeration
	Description
	M,A,

RENEW_TYPE

Attribute	Description
Name	RENEW_TYPE
Datatype	String
Description	
Restrictions	Restrictions
	enumeration
	Description
	B,S,

SCHEME_RP_DESC

Attribute	Description
Name	SCHEME_RP_DESC
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

BEN_EXPIRY

Attribute	Description	
Name	BEN_EXPIRY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

SCHEME_STATUS

Attribute	Description	
Name	SCHEME_STATUS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,E

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

Elig

Attribute	Description	
Name	Elig	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

EL_PLAN_CODE

Attribute	Description	
Name	EL_PLAN_CODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	35

EL_REV_FREQ

Attribute	Description	
Name	EL_REV_FREQ	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	D,W,F,M,Q,H,Y

FIRST_REV_DT

Attribute	Description
------------------	--------------------

Name	FIRST_REV_DT
Datatype	String
Description	

LAST_REV_DT

Attribute	Description	
Name	LAST_REV_DT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

NEXT_REV_DT

Attribute	Description	
Name	NEXT_REV_DT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Cotms-Scheme-Detail

Attribute	Description	
Name	Cotms-Scheme-Detail	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.20.2.CO-ModifyRPSchMntc-Req-IO-MSG.xsd

MODIFYRPSCHMNTC_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cotms-Scheme-Master-IO
SCHEME_ID1
BEN_VALID_PERIOD
BEN_VALID_BASIS
EXECUTABLE_TYPE
SCHEME_RP_DESC
BEN_EXPIRY
MAKER
MAKERSTAMP
Elig
EL_REV_FREQ
NEXT_REV_DT
Cotms-Scheme-Detail
BEN_PLAN_ID
SCHEME_ID
BEN_PLAN_DESC

MODULE
UDFDETAILS
FLDNAM
FLDVAL

MODIFYRPSCHMNTC_IOPK_REQ

Attribute	Description
Name	MODIFYRPSCHMNTC_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field. 869

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

ADDL

Attribute		Description			
Name		ADDL			
Datatype					
Description					
Attribute					
		Attribute		Description	
		minOccurs		0	

PARAM

Attribute		Description			
Name		PARAM			
Datatype					
Description					
Attribute					
		Attribute		Description	
		minOccurs		0	
		maxOccurs		unbounded	

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Cotms-Scheme-Master-IO

Attribute		Description	
Name		Cotms-Scheme-Master-IO	
Datatype			
Description			

SCHEME_ID1

Attribute		Description			
Name		SCHEME_ID1			
Datatype		String			
Description					
Restrictions					
		Restrictions		Description	
		maxLength		35	

BEN_VALID_PERIOD

Attribute	Description				
Name	BEN_VALID_PERIOD				
Datatype	Decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
	Restrictions	Description			
totalDigits	22				

BEN_VALID_BASIS

Attribute	Description				
Name	BEN_VALID_BASIS				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>D,M,Y,</td></tr></tbody></table>	Restrictions	Description	enumeration	D,M,Y,
	Restrictions	Description			
enumeration	D,M,Y,				

EXECUTABLE_TYPE

Attribute	Description				
Name	EXECUTABLE_TYPE				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>M,A,</td></tr></tbody></table>	Restrictions	Description	enumeration	M,A,
	Restrictions	Description			
enumeration	M,A,				

SCHEME_RP_DESC

Attribute	Description				
Name	SCHEME_RP_DESC				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1000</td></tr></tbody></table>	Restrictions	Description	maxLength	1000
	Restrictions	Description			
maxLength	1000				

BEN_EXPIRY

Attribute		Description	
Name	BEN_EXPIRY		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	Y,N	

MAKER

Attribute		Description	
Name	MAKER		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	12	

MAKERSTAMP

Attribute		Description	
Name	MAKERSTAMP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

Elig

Attribute		Description	
Name	Elig		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

EL_REV_FREQ

Attribute		Description	
Name	EL_REV_FREQ		
Datatype	String		

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,W,F,M,Q,H,Y

NEXT_REV_DT

Attribute	Description	
Name	NEXT_REV_DT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

Cotms-Scheme-Detail

Attribute	Description	
Name	Cotms-Scheme-Detail	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	35

SCHEME_ID

Attribute	Description	
Name	SCHEME_ID	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	35
	Description	

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	2
	Description	

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	
	maxLength	105
	minLength	1
	Description	

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.20.3.CO-ModifyRPSchMntc-Res-Full-MSG.xsd

MODIFYRPSCHMNTC_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Scheme-Master-Full

SCHEME_ID1

SCHEME_DESC
SC_START_DT
SC_END_DT
BEN_VALID_PERIOD
BEN_VALID_BASIS
VALID_TYPE
APPLY_FOR
EXECUTABLE_TYPE
RENEW_TYPE
SCHEME_RP_DESC
BEN_EXPIRY
SCHEME_STATUS
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Elig
EL_PLAN_CODE
EL_REV_FREQ
FIRST_REV_DT
LAST_REV_DT
NEXT_REV_DT
Cotms-Scheme-Detail
BEN_PLAN_ID
BEN_PLAN_DESC
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYRPSCHMNTC_FSFS_RES

Attribute	Description
Name	MODIFYRPSCHMNTC_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
-----------	-------------

Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Scheme-Master-Full

Attribute	Description
Name	Cotms-Scheme-Master-Full
Datatype	
Description	

SCHEME_ID1

Attribute	Description
------------------	--------------------

Name	SCHEME_ID1	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

SCHEME_DESC

Attribute	Description	
Name	SCHEME_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

SC_START_DT

Attribute	Description	
Name	SC_START_DT	
Datatype	String	
Description		

SC_END_DT

Attribute	Description	
Name	SC_END_DT	
Datatype	String	
Description		

BEN_VALID_PERIOD

Attribute	Description	
Name	BEN_VALID_PERIOD	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

BEN_VALID_BASIS

Attribute	Description	
Name	BEN_VALID_BASIS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	D,M,Y,

VALID_TYPE

Attribute	Description	
Name	VALID_TYPE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	O,R,P,

APPLY_FOR

Attribute	Description	
Name	APPLY_FOR	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	N,A,E,

EXECUTABLE_TYPE

Attribute	Description	
Name	EXECUTABLE_TYPE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	M,A,

RENEW_TYPE

Attribute	Description	
Name	RENEW_TYPE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	B,S,

SCHEME_RP_DESC

Attribute	Description	
Name	SCHEME_RP_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1000

BEN_EXPIRY

Attribute	Description	
Name	BEN_EXPIRY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

SCHEME_STATUS

Attribute	Description	
Name	SCHEME_STATUS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	A,E

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Elig

Attribute	Description	
Name	Elig	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

EL_PLAN_CODE

Attribute	Description	
Name	EL_PLAN_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

EL_REV_FREQ

Attribute	Description	
Name	EL_REV_FREQ	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	D,W,F,M,Q,H,Y

FIRST_REV_DT

Attribute	Description	
Name	FIRST_REV_DT	
Datatype	String	
Description		

LAST_REV_DT

Attribute		Description	
Name	LAST_REV_DT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	

NEXT_REV_DT

Attribute		Description	
Name	NEXT_REV_DT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	

Cotms-Scheme-Detail

Attribute		Description	
Name	Cotms-Scheme-Detail		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

BEN_PLAN_ID

Attribute		Description	
Name	BEN_PLAN_ID		
Datatype	String		
Description			
Restrictions	Restrictions		Description
	maxLength	35	

BEN_PLAN_DESC

Attribute		Description	
Name	BEN_PLAN_DESC		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions	Restrictions	
maxLength		35	

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.20.4.CO-ModifyRPSchMntc-Res-PK-MSG.xsd

MODIFYRPSCHMNTC_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cotms-Scheme-Master-PK
SCHEME_ID1
Cotms-Scheme-Master-IO
SCHEME_ID1
BEN_VALID_PERIOD
BEN_VALID_BASIS
EXECUTABLE_TYPE
SCHEME_RP_DESC
BEN_EXPIRY
MAKER
MAKERSTAMP
Elig
EL_REV_FREQ

NEXT_REV_DT

Cotms-Scheme-Detail

BEN_PLAN_ID

SCHEME_ID

BEN_PLAN_DESC

MODULE

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYRPSCHMNTC_IOPK_RES

Attribute	Description
Name	MODIFYRPSCHMNTC_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description
-----------	-------------

Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nullable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Scheme-Master-PK

Attribute	Description
Name	Cotms-Scheme-Master-PK
Datatype	
Description	

SCHEME_ID1

Attribute	Description				
Name	SCHEME_ID1				
Datatype	String				
Description					
Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

Cotms-Scheme-Master-IO

Attribute	Description
Name	Cotms-Scheme-Master-IO
Datatype	
Description	

SCHEME_ID1

Attribute	Description				
Name	SCHEME_ID1				
Datatype	String				
Description					
Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

BEN_VALID_PERIOD

Attribute	Description				
Name	BEN_VALID_PERIOD				
Datatype	Decimal				
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

BEN_VALID_BASIS

Attribute		Description	
Name	BEN_VALID_BASIS		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	D,M,Y,	

EXECUTABLE_TYPE

Attribute		Description	
Name	EXECUTABLE_TYPE		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	M,A,	

SCHEME_RP_DESC

Attribute		Description	
Name	SCHEME_RP_DESC		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1000	

BEN_EXPIRY

Attribute		Description	
Name	BEN_EXPIRY		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	Y,N	

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

Elig

Attribute	Description	
Name	Elig	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

EL_REV_FREQ

Attribute	Description	
Name	EL_REV_FREQ	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	D,W,F,M,Q,H,Y

NEXT_REV_DT

Attribute	Description	
Name	NEXT_REV_DT	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0

Cotms-Scheme-Detail

Attribute	Description	
Name	Cotms-Scheme-Detail	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

SCHEME_ID

Attribute	Description	
Name	SCHEME_ID	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODULE

Attribute	Description
------------------	--------------------

Name	MODULE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.21.QueryCSMBPLinkage

2.21.1.CO-QueryCSMBPLinkage-Req-IO-MSG.xsd

QUERYCSMBPLINKAGE_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Csm-Ben-Master-C-IO

CSM

CUSTOMER_NO

QUERYCSMBPLINKAGE_IOFS_REQ

Attribute	Description
Name	QUERYCSMBPLINKAGE_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotm-Csm-Ben-Master-C-IO

Attribute	Description
Name	Cotm-Csm-Ben-Master-C-IO
Datatype	
Description	

CSM

Attribute	Description				
Name	CSM				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

CUSTOMER_NO

Attribute	Description
-----------	-------------

Name	CUSTOMER_NO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

2.21.2.CO-QueryCSMBPLinkage-Res-Full-MSG.xsd

QUERYCSMBPLINKAGE_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotm-Csm-Ben-Master-C-IO

CSM

CUSTOMER_NO

Cotm-Csm-Ben-Master-C-Full

CSM

CUSTOMER_NO

CSM_DESC

CUSTOMER_NAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Cotm-Csm-Ben-Detail-C

BEN_START_DT

MODULE

BEN_PLAN_TYPE

BEN_PLAN_ID

BEN_PLAN_DESC

PRIORITYNO

BEN_END_DT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYCSMBPLINKAGE_IOFS_RES

Attribute	Description
Name	QUERYCSMBPLINKAGE_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		

Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotm-Csm-Ben-Master-C-IO

Attribute	Description
Name	Cotm-Csm-Ben-Master-C-IO
Datatype	
Description	

CSM

Attribute	Description	
Name	CSM	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

Cotm-Csm-Ben-Master-C-Full

Attribute	Description
Name	Cotm-Csm-Ben-Master-C-Full

Datatype	
Description	

CSM

Attribute	Description	
Name	CSM	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

CSM_DESC

Attribute	Description	
Name	CSM_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

CUSTOMER_NAME

Attribute	Description	
Name	CUSTOMER_NAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	

Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Cotm-Csm-Ben-Detail-C

Attribute	Description	
Name	Cotm-Csm-Ben-Detail-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BEN_START_DT

Attribute	Description	
Name	BEN_START_DT	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	2

BEN_PLAN_TYPE

Attribute	Description	
Name	BEN_PLAN_TYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

PRIORITYNO

Attribute	Description	
Name	PRIORITYNO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

BEN_END_DT

Attribute	Description	
Name	BEN_END_DT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	

Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.22.QueryRPBenfPlan

2.22.1.CO-QueryRPBenfPlan-Req-IO-MSG.xsd

QUERYRPBENFPLAN_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Benefit-Master-IO

BEN_PLAN_ID

MODULE

QUERYRPBENFPLAN_IOFS_REQ

Attribute	Description
Name	QUERYRPBENFPLAN_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Benefit-Master-IO

Attribute	Description
Name	Cotms-Benefit-Master-IO
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description				
Name	BEN_PLAN_ID				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

MODULE

Attribute	Description				
Name	MODULE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>2</td></tr></tbody></table>	Restrictions	Description	maxLength	2
Restrictions	Description				
maxLength	2				

2.22.2.CO-QueryRPBenfPlan-Res-Full-MSG.xsd

QUERYRPBENFPLAN_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cotms-Benefit-Master-IO
BEN_PLAN_ID
MODULE
Cotms-Benefit-Master-Full
BEN_PLAN_ID
BEN_PLAN_DESC
MODULE
PRIORITY_NO
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO

TXNSTAT

AUTHSTAT

Cotms-Benefit-Details

PRODUCT

PRICE_COMP_TYPE

PRICE_COMP

BEN_TYPE

VAR_TYPE

VAR_CCY

VAR_VALUE

VAR_RULE

MAX_VALUE

MIN_VALUE

CCY_CODE

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYRPBENFPLAN_IOFS_RES

Attribute	Description
Name	QUERYRPBENFPLAN_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	
-------------	--

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
pattern	[A-Z_0-9]*	

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Benefit-Master-IO

Attribute	Description
Name	Cotms-Benefit-Master-IO
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description				
Name	BEN_PLAN_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

MODULE

Attribute	Description				
Name	MODULE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>2</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	2
Restrictions	Description				
maxLength	2				

Cotms-Benefit-Master-Full

Attribute	Description
Name	Cotms-Benefit-Master-Full
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description

Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

MODULE

Attribute	Description	
Name	MODULE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	2

PRIORITY_NO

Attribute	Description	
Name	PRIORITY_NO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	5

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	1
	Description	

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	1
	Description	

Cotms-Benefit-Details

Attribute	Description	
Name	Cotms-Benefit-Details	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

PRODUCT

Attribute	Description	
Name	PRODUCT	
Datatype	String	
Description		
Restrictions	Restrictions	
	maxLength	4
	Description	

PRICE_COMP_TYPE

Attribute	Description	
Name	PRICE_COMP_TYPE	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	I,C,F,M

PRICE_COMP

Attribute	Description	
Name	PRICE_COMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	35

BEN_TYPE

Attribute	Description	
Name	BEN_TYPE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	V,W,

VAR_TYPE

Attribute	Description	
Name	VAR_TYPE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	F,A,P,V,T,N,

VAR_CCY

Attribute	Description	
Name	VAR_CCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	3

VAR_VALUE

Attribute	Description	
Name	VAR_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

VAR_RULE

Attribute	Description	
Name	VAR_RULE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MAX_VALUE

Attribute	Description	
Name	MAX_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

MIN_VALUE

Attribute	Description	
Name	MIN_VALUE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	22

CCY_CODE

Attribute	Description	
Name	CCY_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute		Description	
Name	FCUBS_ERROR_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

ERROR

Attribute		Description	
Name	ERROR		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

ECODE

Attribute		Description	
Name	ECODE		
Datatype	String		
Description			

EDESC

Attribute		Description	
Name	EDESC		
Datatype	String		
Description			

FCUBS_WARNING_RESP

Attribute		Description	
Name	FCUBS_WARNING_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

WARNING

Attribute		Description	
Name	WARNING		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.23.QueryRPEIlgPlan

2.23.1.CO-QueryRPEIlgPlan-Req-IO-MSG.xsd

QUERYRPELGPLAN_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

EL_PLAN_CODE

QUERYRPELGPLAN_IOFS_REQ

Attribute	Description
Name	QUERYRPELGPLAN_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0
	maxOccurs		unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Cotms-Elplan-Master-IO

Attribute		Description	
Name		Cotms-Elplan-Master-IO	
Datatype			
Description			

EL_PLAN_CODE

Attribute		Description	
Name		EL_PLAN_CODE	
Datatype		String	
Description			
Restrictions	Restrictions		Description
	maxLength		35

QUERYRPELGPLAN_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Elplan-Master-IO

EL_PLAN_CODE

Cotms-Elplan-Master-Full

EL_PLAN_CODE

EL_PLAN_DESC

EL_CONDITION

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Cotms-Elplan-Rde

RDE_CODE

RDE_PARAM_VAL

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYRPELGPLAN_IOFS_RES

Attribute	Description
Name	QUERYRPELGPLAN_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotms-Elplan-Master-IO

Attribute	Description
Name	Cotms-Elplan-Master-IO
Datatype	
Description	

EL_PLAN_CODE

Attribute	Description				
Name	EL_PLAN_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

Cotms-Elplan-Master-Full

Attribute	Description
Name	Cotms-Elplan-Master-Full
Datatype	
Description	

EL_PLAN_CODE

Attribute	Description				
Name	EL_PLAN_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

EL_PLAN_DESC

Attribute	Description
-----------	-------------

Name	EL_PLAN_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

EL_CONDITION

Attribute	Description	
Name	EL_CONDITION	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	4000

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

Cotms-Elplan-Rde

Attribute	Description	
Name	Cotms-Elplan-Rde	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxOccurs	unbounded

RDE_CODE

Attribute	Description	
Name	RDE_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

RDE_PARAM_VAL

Attribute	Description	
Name	RDE_PARAM_VAL	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
------------------	--------------------

Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.24.QueryRPErBenPlan

2.24.1.CO-QueryRPErBenPlan-Req-IO-MSG.xsd

QUERYRPERBENPLAN_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cotm-Ben-Exch-Master-C-IO
BEN_PLAN_ID

QUERYRPERBENPLAN_IOFS_REQ

Attribute	Description
Name	QUERYRPERBENPLAN_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within EL EXCLUDE UBS. In

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cotm-Ben-Exch-Master-C-IO

Attribute	Description
Name	Cotm-Ben-Exch-Master-C-IO
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description				
Name	BEN_PLAN_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

*2.24.2.CO-QueryRPERBenPlan-Res-Full-MSG.xsd**QUERYRPERBENPLAN_IOFS_RES**FCUBS_HEADER**SOURCE**UBSCOMP**MSGID**CORRELID**USERID**BRANCH**MODULEID**SERVICE**OPERATION*

SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cotm-Ben-Exch-Master-C-IO
BEN_PLAN_ID
Cotm-Ben-Exch-Master-C-Full
BEN_PLAN_ID
BEN_PLAN_DESC
PRIORITY_NO
APPLY_SPREAD_AS
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Cotm-Ben-Exch-Detail-C
BUY_SPREAD
SALESPRD
BEN_PLAN_ID
RATTYP

VAR_CCY1

VAR_CCY2

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYRPERBENPLAN_IOFS_RES

Attribute	Description
Name	QUERYRPERBENPLAN_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description					
Name	SOURCE_OPERATION					
Datatype	String					
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

SOURCE_USERID

Attribute	Description					
Name	SOURCE_USERID					
Datatype	String					
Description	This is the user id in the Source system who is performing the action.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

DESTINATION

Attribute	Description					
Name	DESTINATION					
Datatype	String					
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

MULTITRIPID

Attribute	Description					
Name	MULTITRIPID					
Datatype	String					
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Cotm-Ben-Exch-Master-C-IO

Attribute	Description
------------------	--------------------

Name	Cotm-Ben-Exch-Master-C-IO
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

Cotm-Ben-Exch-Master-C-Full

Attribute	Description
Name	Cotm-Ben-Exch-Master-C-Full
Datatype	
Description	

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

PRIORITY_NO

Attribute	Description	
Name	PRIORITY_NO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	5

APPLY_SPREAD_AS

Attribute	Description	
Name	APPLY_SPREAD_AS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	D,V

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Attribute	Description	
Name	Cotm-Ben-Exch-Detail-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BUY_SPREAD

Attribute	Description	
Name	BUY_SPREAD	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

SALESPRD

Attribute	Description	
Name	SALESPRD	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

BEN_PLAN_ID

Attribute	Description	
Name	BEN_PLAN_ID	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

RATTYP

Attribute	Description	
Name	RATTYP	
Datatype	String	

Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>8</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	8
Restrictions	Description				
maxLength	8				

VAR_CCY1

Attribute	Description				
Name	VAR_CCY1				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

VAR_CCY2

Attribute	Description				
Name	VAR_CCY2				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

FLDNAM

Attribute	Description						
Name	FLDNAM						
Datatype	String						
Description	Indicates Field Name						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	105	minLength	1
Restrictions	Description						
maxLength	105						
minLength	1						

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.25.QueryRPSchMntc

2.25.1.CO-QueryRPSchMntc-Req-IO-MSG.xsd

QUERYRPSCHMNTC_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Scheme-Master-IO

SCHEME_ID1

QUERYRPSCHMNTC_IOFS_REQ

Attribute	Description
Name	QUERYRPSCHMNTC_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

ORACLE®

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
Restrictions	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
Restrictions	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Cotms-Scheme-Master-IO

Attribute	Description	
Name	Cotms-Scheme-Master-IO	
Datatype		
Description		

SCHEME_ID1

Attribute	Description	
------------------	--------------------	--

Name	SCHEME_ID1	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

2.25.2.CO-QueryRPSchMntc-Res-Full-MSG.xsd

QUERYRPSCHMNTC_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cotms-Scheme-Master-IO

SCHEME_ID1

Cotms-Scheme-Master-Full

SCHEME_ID1
SCHEME_DESC
SC_START_DT
SC_END_DT
BEN_VALID_PERIOD
BEN_VALID_BASIS
VALID_TYPE
APPLY_FOR
EXECUTABLE_TYPE
RENEW_TYPE
SCHEME_RP_DESC
BEN_EXPIRY
SCHEME_STATUS
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Elig
EL_PLAN_CODE
EL_REV_FREQ
FIRST_REV_DT
LAST_REV_DT
NEXT_REV_DT
Cotms-Scheme-Detail
BEN_PLAN_ID
BEN_PLAN_DESC
UDFDETAILS
FLDNAM
FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYRPSCHMNTC_IOFS_RES

Attribute	Description
Name	QUERYRPSCHMNTC_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Cotms-Scheme-Master-IO

Attribute	Description	
Name	Cotms-Scheme-Master-IO	
Datatype		
Description		

SCHEME_ID1

Attribute	Description	

Name	SCHEME_ID1	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

Cotms-Scheme-Master-Full

Attribute	Description
Name	Cotms-Scheme-Master-Full
Datatype	
Description	

SCHEME_ID1

Attribute	Description	
Name	SCHEME_ID1	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

SCHEME_DESC

Attribute	Description	
Name	SCHEME_DESC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	105

SC_START_DT

Attribute	Description
Name	SC_START_DT
Datatype	String
Description	

SC_END_DT

Attribute	Description
Name	SC_END_DT
Datatype	String
Description	

BEN_VALID_PERIOD

Attribute	Description
Name	BEN_VALID_PERIOD
Datatype	Decimal
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

BEN_VALID_BASIS

Attribute	Description	
Name	BEN_VALID_BASIS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,M,Y,

VALID_TYPE

Attribute	Description	
Name	VALID_TYPE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	O,R,P,

APPLY_FOR

Attribute	Description	
Name	APPLY_FOR	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	N,A,E,

EXECUTABLE_TYPE

Attribute	Description	
Name	EXECUTABLE_TYPE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	M,A,

RENEW_TYPE

Attribute	Description
------------------	--------------------

Name	RENEW_TYPE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	B,S,

SCHEME_RP_DESC

Attribute	Description	
Name	SCHEME_RP_DESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

BEN_EXPIRY

Attribute	Description	
Name	BEN_EXPIRY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

SCHEME_STATUS

Attribute	Description	
Name	SCHEME_STATUS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	A,E

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Elig

Attribute	Description	
Name	Elig	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

EL_PLAN_CODE

Attribute	Description	
Name	EL_PLAN_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

EL_REV_FREQ

Attribute	Description				
Name	EL_REV_FREQ				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>D,W,F,M,Q,H,Y</td></tr></tbody></table>	Restrictions	Description	enumeration	D,W,F,M,Q,H,Y
Restrictions	Description				
enumeration	D,W,F,M,Q,H,Y				

FIRST_REV_DT

Attribute	Description
Name	FIRST_REV_DT
Datatype	String
Description	

LAST_REV_DT

Attribute	Description				
Name	LAST_REV_DT				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

NEXT_REV_DT

Attribute	Description				
Name	NEXT_REV_DT				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Cotms-Scheme-Detail

Attribute	Description						
Name	Cotms-Scheme-Detail						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

BEN_PLAN_ID

Attribute	Description
Name	BEN_PLAN_ID
Datatype	String
Description	

Restrictions		
	Restrictions	Description
	maxLength	35

BEN_PLAN_DESC

Attribute	Description	
Name	BEN_PLAN_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute		Description	
Name	FCUBS_ERROR_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

ERROR

Attribute		Description	
Name	ERROR		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

ECODE

Attribute		Description	
Name	ECODE		
Datatype	String		
Description			

EDESC

Attribute		Description	
Name	EDESC		
Datatype	String		
Description			

FCUBS_WARNING_RESP

Attribute		Description	
Name	FCUBS_WARNING_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

WARNING

Attribute		Description	
Name	WARNING		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.26.AuthorizeAcctr

2.26.1.CS-AuthorizeAcctr-Req-Full-MSG.xsd

AUTHORIZEACCTR_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-Full

TRANSFER_ID

CURRENT_BRANCH

TARGET_BRANCH_CODE

TRANSDT

TARGET_BRANCH_NAME

CURRENT_BRANCH_NAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Child

ACCOUNTNUMBER

AC_DESC

CUSTOMER_NUMBER

TXT_CUSTNAME

UDFDETAILS

FLDNAM

FLDVAL

AUTHORIZEACCTR_FSFS_REQ

Attribute	Description
Name	AUTHORIZEACCTR_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

CURRENT_BRANCH

Attribute	Description				
Name	CURRENT_BRANCH				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TARGET_BRANCH_CODE

Attribute	Description				
Name	TARGET_BRANCH_CODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	String
Description	

TARGET_BRANCH_NAME

Attribute	Description				
Name	TARGET_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
	Restrictions	Description			
maxLength	255				

CURRENT_BRANCH_NAME

Attribute	Description				
Name	CURRENT_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
	Restrictions	Description			
maxLength	255				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Child

Attribute	Description	
Name	Child	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCOUNTNUMBER

Attribute	Description	
Name	ACCOUNTNUMBER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	20

AC_DESC

Attribute	Description	
Name	AC_DESC	
Datatype	String	
Description		

Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	255
	Description	

CUSTOMER_NUMBER

Attribute	Description	
Name	CUSTOMER_NUMBER	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	255
	Description	

TXT_CUSTNAME

Attribute	Description	
Name	TXT_CUSTNAME	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	255
	Description	

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.26.2.CS-AuthorizeAcctr-Req-IO-MSG.xsd

AUTHORIZEACCTR_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM
NAME
VALUE
FCUBS_BODY
Master-IO
TRANSFER_ID
CHECKER
CHECKERSTAMP
MODNO

AUTHORIZEACCTR_IOPK_REQ

Attribute	Description
Name	AUTHORIZEACCTR_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	

Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Master-IO

Attribute	Description	
Name	Master-IO	
Datatype		
Description		

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
	Restrictions	Description			
maxLength	16				

CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

CHECKERSTAMP

Attribute	Description				
Name	CHECKERSTAMP				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
	Restrictions	Description			
maxLength	35				

MODNO

Attribute	Description				
Name	MODNO				
Datatype	Decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>4</td></tr></tbody></table>	Restrictions	Description	totalDigits	4
	Restrictions	Description			
totalDigits	4				

2.26.3.CS-AuthorizeAcctr-Res-Full-MSG.xsd

[AUTHORIZEACCTR_FSFS_RES](#)

[FCUBS_HEADER](#)

SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Master-Full
TRANSFER_ID
CURRENT_BRANCH
TARGET_BRANCH_CODE
TRANSDT
TARGET_BRANCH_NAME
CURRENT_BRANCH_NAME
MAKER
MAKERSTAMP
CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Child

ACCOUNTNUMBER

AC_DESC

CUSTOMER_NUMBER

TXT_CUSTNAME

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEACCTR_FSFS_RES

Attribute	Description
Name	AUTHORIZEACCTR_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

CURRENT_BRANCH

Attribute	Description				
Name	CURRENT_BRANCH				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TARGET_BRANCH_CODE

Attribute	Description				
Name	TARGET_BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	String
Description	

TARGET_BRANCH_NAME

Attribute	Description				
Name	TARGET_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

CURRENT_BRANCH_NAME

Attribute	Description				
Name	CURRENT_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Child

Attribute	Description	
Name	Child	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCOUNTNUMBER

Attribute	Description	
Name	ACCOUNTNUMBER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	20

AC_DESC

Attribute	Description	
Name	AC_DESC	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

CUSTOMER_NUMBER

Attribute	Description	
Name	CUSTOMER_NUMBER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TXT_CUSTNAME

Attribute	Description	
Name	TXT_CUSTNAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.26.4.CS-AuthorizeAcctr-Res-PK-MSG.xsd

AUTHORIZEACCTR_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTIRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-PK

TRANSFER_ID

Master-IO

TRANSFER_ID

CHECKER

CHECKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEACCTR_IOPK_RES

Attribute	Description
Name	AUTHORIZEACCTR_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
------------------	--------------------

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-PK

Attribute	Description
Name	Master-PK
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

CHECKER

Attribute	Description
-----------	-------------

Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.27.AuthorizeAcltr

2.27.1.CS-AuthorizeAcltr-Req-Full-MSG.xsd

[AUTHORIZEACLTR_FSFS_REQ](#)

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-Full

TRANSFER_ID

ACCOUNT_CLASS

CURRENT_BRANCH_CODE

TARGET_BRANCH_CODE

TRANSFER_DATE

CURRENT_BRANCH_NAME

TARGET_BRANCH_NAME

ACCOUNT_CLASS_DESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

AUTHORIZEACLTR_FSFS_REQ

Attribute	Description
Name	AUTHORIZEACLTR_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Master-Full

Attribute		Description
------------------	--	--------------------

Name	Master-Full
Datatype	
Description	

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	64

ACCOUNT_CLASS

Attribute	Description	
Name	ACCOUNT_CLASS	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	24

CURRENT_BRANCH_CODE

Attribute	Description	
Name	CURRENT_BRANCH_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	12

TARGET_BRANCH_CODE

Attribute	Description	
Name	TARGET_BRANCH_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	12

TRANSFER_DATE

Attribute	Description	
Name	TRANSFER_DATE	
Datatype	String	
Description		

CURRENT_BRANCH_NAME

Attribute	Description	
Name	CURRENT_BRANCH_NAME	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TARGET_BRANCH_NAME

Attribute	Description	
Name	TARGET_BRANCH_NAME	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

ACCOUNT_CLASS_DESC

Attribute	Description	
Name	ACCOUNT_CLASS_DESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.27.2. CS-AuthorizeAcltr-Req-IO-MSG.xsd

AUTHORIZEACLTR_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-IO

TRANSFER_ID

CHECKER

CHECKERSTAMP

AUTHORIZEACLTR_IOPK_REQ

Attribute	Description
Name	AUTHORIZEACLTR_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute		Description	
Name	SOURCE_USERID		
Datatype	String		
Description	This is the user id in the Source system who is performing the action.		
Attribute	Attribute		Description
	minOccurs	0	

DESTINATION

Attribute		Description	
Name	DESTINATION		
Datatype	String		
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute		Description	
Name	MULTITRIPID		
Datatype	String		
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute		Description	
Name	FUNCTIONID		
Datatype	String		
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.		
Attribute	Attribute		Description
	minOccurs	0	

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>64</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	64
Restrictions	Description				
maxLength	64				

CHECKER

Attribute	Description
-----------	-------------

Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

2.27.3.CS-AuthorizeAcltr-Res-Full-MSG.xsd

AUTHORIZEACLTR_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Master-Full
TRANSFER_ID
ACCOUNT_CLASS
CURRENT_BRANCH_CODE
TARGET_BRANCH_CODE
TRANSFER_DATE
CURRENT_BRANCH_NAME
TARGET_BRANCH_NAME
ACCOUNT_CLASS_DESC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEACLTR_FSFS_RES

Attribute	Description
Name	AUTHORIZEACLTR_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	

Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Master-Full

Attribute	Description	
Name	Master-Full	
Datatype		
Description		

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>64</td></tr></tbody></table>	Restrictions	Description	maxLength	64
Restrictions	Description				
maxLength	64				

ACCOUNT_CLASS

Attribute	Description				
Name	ACCOUNT_CLASS				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>24</td></tr></tbody></table>	Restrictions	Description	maxLength	24
Restrictions	Description				
maxLength	24				

CURRENT_BRANCH_CODE

Attribute	Description				
Name	CURRENT_BRANCH_CODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

TARGET_BRANCH_CODE

Attribute	Description				
Name	TARGET_BRANCH_CODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	String
Description	

CURRENT_BRANCH_NAME

Attribute	Description
Name	CURRENT_BRANCH_NAME
Datatype	String
Description	

Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	255

TARGET_BRANCH_NAME

Attribute	Description	
Name	TARGET_BRANCH_NAME	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	255

ACCOUNT_CLASS_DESC

Attribute	Description	
Name	ACCOUNT_CLASS_DESC	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.27.4.CS-AuthorizeAcltr-Res-PK-MSG.xsd

AUTHORIZEACLTR_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-PK

TRANSFER_ID

Master-IO

TRANSFER_ID

CHECKER

CHECKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEACLTR_IOPK_RES

Attribute	Description
Name	AUTHORIZEACLTR_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-PK

Attribute	Description
Name	Master-PK
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>64</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	64
Restrictions	Description				
maxLength	64				

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>64</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	64
Restrictions	Description				
maxLength	64				

CHECKER

Attribute	Description
-----------	-------------

Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.28.AuthorizeActrp

2.28.1.CS-AuthorizeActrp-Req-Full-MSG.xsd

[AUTHORIZEACTRP_FSFS_REQ](#)

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cstm-Branch-Trfr-Param-Full

BRANCH_CODE

TRN_CODE

TRANSFER_GL

PROCESS_MODE

MAX_NO_OF_PROCESS

COMMIT_FREQUENCY

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

AUTHORIZEACTRP_FSFS_REQ

Attribute	Description
Name	AUTHORIZEACTRP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute			
		Attribute	Description
		minOccurs	0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute			
		Attribute	Description
		minOccurs	0
		maxOccurs	unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Cstm-Branch-Trfr-Param-Full

Attribute		Description	
Name		Cstm-Branch-Trfr-Param-Full	
Datatype			
Description			

BRANCH_CODE

Attribute		Description	
Name		BRANCH_CODE	
Datatype		String	
Description			
Restrictions			
		Restrictions	Description
		maxLength	3

TRN_CODE

Attribute	Description				
Name	TRN_CODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TRANSFER_GL

Attribute	Description				
Name	TRANSFER_GL				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

PROCESS_MODE

Attribute	Description				
Name	PROCESS_MODE				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>S,J</td></tr></tbody></table>	Restrictions	Description	enumeration	S,J
Restrictions	Description				
enumeration	S,J				

MAX_NO_OF_PROCESS

Attribute	Description				
Name	MAX_NO_OF_PROCESS				
Datatype	Decimal				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

COMMIT_FREQUENCY

Attribute	Description
Name	COMMIT_FREQUENCY
Datatype	Decimal
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

2.28.2.CS-AuthorizeActrp-Req-IO-MSG.xsd

[AUTHORIZEACTRP_IOPK_REQ](#)

[FCUBS_HEADER](#)

[SOURCE](#)

UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
 PARAM
 NAME
 VALUE
FCUBS_BODY
 Cstm-Branch-Trfr-Param-IO
 BRANCH_CODE
 CHECKER
 CHECKERSTAMP
 MODNO

AUTHORIZEACTRP_IOPK_REQ

Attribute	Description
Name	AUTHORIZEACTRP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
-----------	-------------

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cstm-Branch-Trfr-Param-IO

Attribute	Description
Name	Cstm-Branch-Trfr-Param-IO
Datatype	
Description	

BRANCH_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

2.28.3.CS-AuthorizeActrp-Res-Full-MSG.xsd

AUTHORIZEACTRP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cstm-Branch-Trfr-Param-Full

BRANCH_CODE

TRN_CODE

TRANSFER_GL

PROCESS_MODE

MAX_NO_OF_PROCESS

COMMIT_FREQUENCY

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEACTRP_FSFS_RES

Attribute	Description
Name	AUTHORIZEACTRP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cstm-Branch-Trfr-Param-Full

Attribute	Description
Name	Cstm-Branch-Trfr-Param-Full
Datatype	
Description	

BRANCH_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TRN_CODE

Attribute	Description				
Name	TRN_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TRANSFER_GL

Attribute	Description				
Name	TRANSFER_GL				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

PROCESS_MODE

Attribute	Description	
Name	PROCESS_MODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	S,J

MAX_NO_OF_PROCESS

Attribute	Description	
Name	MAX_NO_OF_PROCESS	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

COMMIT_FREQUENCY

Attribute	Description	
Name	COMMIT_FREQUENCY	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute		Description	
Name	MAKERSTAMP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

CHECKER

Attribute		Description	
Name	CHECKER		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	12	

CHECKERSTAMP

Attribute		Description	
Name	CHECKERSTAMP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

MODNO

Attribute		Description	
Name	MODNO		
Datatype	Decimal		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	totalDigits	4	

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.28.4.CS-AuthorizeActrp-Res-PK-MSG.xsd

AUTHORIZEACTRP_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cstm-Branch-Trfr-Param-PK

BRANCH_CODE

Cstm-Branch-Trfr-Param-IO

BRANCH_CODE

CHECKER

CHECKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEACTRP_IOPK_RES

Attribute	Description
-----------	-------------

Name	AUTHORIZEACTRP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	
	Description	
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	
	Description	
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	

Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	

Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Cstm-Branch-Trfr-Param-PK

Attribute	Description	
Name	Cstm-Branch-Trfr-Param-PK	
Datatype		
Description		

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	3

Cstm-Branch-Trfr-Param-IO

Attribute	Description	
Name	Cstm-Branch-Trfr-Param-IO	
Datatype		
Description		

BRANCH_CODE

Attribute	Description	

Name	BRANCH_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		

Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.29.AuthorizeDeveloper

2.29.1.CS-AuthorizeDeveloper-Req-Full-MSG.xsd

AUTHORIZEDDEVELOPER_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Developer-Full

WEBSITE

DEVELOPCODE

ADDRESS

DEVELOPERNAME

ADDRESS4

COUNTRY

EMAILID

ZIP

ADDRESS2

ADDRESS3

COUNTRY_NAME

TELEPHONE

FAX

MOBILE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Developer-Projects

PROJECTNAME

PROJECTDESC

AUTHORIZEDDEVELOPER_FSFS_REQ

Attribute	Description
Name	AUTHORIZEDDEVELOPER_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Developer-Full

Attribute	Description
Name	Developer-Full
Datatype	
Description	

WEBSITE

Attribute	Description				
Name	WEBSITE				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

DEVELOPCODE

Attribute	Description				
Name	DEVELOPCODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

ADDRESS

Attribute	Description
Name	ADDRESS
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

DEVELOPERNAME

Attribute	Description	
Name	DEVELOPERNAME	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

ADDRESS4

Attribute	Description	
Name	ADDRESS4	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

COUNTRY

Attribute	Description	
Name	COUNTRY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

EMAILID

Attribute	Description	
Name	EMAILID	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

ZIP

Attribute	Description	
Name	ZIP	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

ADDRESS2

Attribute	Description	
Name	ADDRESS2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

ADDRESS3

Attribute	Description	
Name	ADDRESS3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

COUNTRY_NAME

Attribute	Description	
Name	COUNTRY_NAME	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TELEPHONE

Attribute	Description	
Name	TELEPHONE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

FAX

Attribute	Description	
Name	FAX	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

MOBILE

Attribute	Description	
Name	MOBILE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Developer-Projects

Attribute	Description	
Name	Developer-Projects	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

PROJECTNAME

Attribute	Description	
Name	PROJECTNAME	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

PROJECTDESC

Attribute	Description	
Name	PROJECTDESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

2.29.2.CS-AuthorizeDeveloper-Req-IO-MSG.xsd

AUTHORIZEDDEVELOPER_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Developer-IO

DEVELOPCODE

CHECKER

CHECKERSTAMP

MODNO

AUTHORIZEDEVELOPER_IOPK_REQ

Attribute	Description
Name	AUTHORIZEDEVELOPER_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Developer-IO

Attribute		Description
------------------	--	--------------------

Name	Developer-IO
Datatype	
Description	

DEVELOPCODE

Attribute	Description	
Name	DEVELOPCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	9

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

AUTHORIZEDDEVELOPER_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Developer-Full

WEBSITE

DEVELOPCODE

ADDRESS

DEVELOPERNAME

ADDRESS4

COUNTRY

EMAILID

ZIP

ADDRESS2

ADDRESS3

COUNTRY_NAME

TELEPHONE

FAX

MOBILE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Developer-Projects

PROJECTNAME

PROJECTDESC

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEDEVELOPER_FSFS_RES

Attribute	Description
Name	AUTHORIZEDEVELOPER_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	
-------------	--

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Developer-Full

Attribute	Description
Name	Developer-Full
Datatype	
Description	

WEBSITE

Attribute	Description	
Name	WEBSITE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

DEVELOPCODE

Attribute	Description	
Name	DEVELOPCODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

ADDRESS

Attribute	Description
Name	ADDRESS
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

DEVELOPERNAME

Attribute	Description	
Name	DEVELOPERNAME	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

ADDRESS4

Attribute	Description	
Name	ADDRESS4	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

COUNTRY

Attribute	Description	
Name	COUNTRY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

EMAILID

Attribute	Description	
Name	EMAILID	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

ZIP

Attribute	Description	
Name	ZIP	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

ADDRESS2

Attribute	Description	
Name	ADDRESS2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

ADDRESS3

Attribute	Description	
Name	ADDRESS3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

COUNTRY_NAME

Attribute	Description	
Name	COUNTRY_NAME	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TELEPHONE

Attribute	Description	
Name	TELEPHONE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

FAX

Attribute	Description	
Name	FAX	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

MOBILE

Attribute	Description	
Name	MOBILE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Developer-Projects

Attribute	Description	
Name	Developer-Projects	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

PROJECTNAME

Attribute	Description	
Name	PROJECTNAME	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

PROJECTDESC

Attribute	Description	
Name	PROJECTDESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.29.4. CS-AuthorizeDeveloper-Res-PK-MSG.xsd

AUTHORIZEDDEVELOPER_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
 NAME
 VALUE
FCUBS_BODY
 Developer-PK
 DEVELOPCODE
 Developer-IO
 DEVELOPCODE
 CHECKER
 CHECKERSTAMP
 MODNO
FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

AUTHORIZEDDEVELOPER_IOPK_RES

Attribute	Description
Name	AUTHORIZEDDEVELOPER_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Developer-PK

Attribute	Description
Name	Developer-PK
Datatype	
Description	

DEVELOPCODE

Attribute	Description				
Name	DEVELOPCODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

Developer-IO

Attribute	Description
Name	Developer-IO
Datatype	
Description	

DEVELOPCODE

Attribute	Description				
Name	DEVELOPCODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

CHECKER

Attribute	Description
-----------	-------------

Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.30.AuthorizeProject

2.30.1.CS-AuthorizeProject-Req-Full-MSG.xsd

AUTHORIZEPROJECT_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Developer-Projects-Full

DEVELOPCODE

PROJECTNAME

PROJECTDESC

ADDRESS

PRJADDR2

PRJADDR3

STATUS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Dev-Prj-Dtls

UNITID

UNITHOLDERNAME

UDFDETAILS

FLDNAM

FLDVAL

AUTHORIZEPROJECT_FSFS_REQ

Attribute	Description
Name	AUTHORIZEPROJECT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Developer-Projects-Full

Attribute		Description
------------------	--	--------------------

Name	Developer-Projects-Full
Datatype	
Description	

DEVELOPCODE

Attribute	Description	
Name	DEVELOPCODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

PROJECTNAME

Attribute	Description	
Name	PROJECTNAME	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

PROJECTDESC

Attribute	Description	
Name	PROJECTDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

ADDRESS

Attribute	Description	
Name	ADDRESS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

PRJADDR2

Attribute	Description
Name	PRJADDR2

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

PRJADDR3

Attribute	Description	
Name	PRJADDR3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Dev-Prj-Dtls

Attribute	Description	
Name	Dev-Prj-Dtls	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

UNITID

Attribute	Description	
Name	UNITID	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9

UNITHOLDERNAME

Attribute	Description	
Name	UNITHOLDERNAME	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
Restrictions	Restrictions	Description
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
Restrictions	Restrictions	Description
	minLength	0

2.30.2.CS-AuthorizeProject-Req-IO-MSG.xsd

AUTHORIZEPROJECT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
 PARAM
 NAME
 VALUE
FCUBS_BODY
 Developer-Projects-IO
 DEVELOPCODE
 PROJECTNAME
 CHECKER
 CHECKERSTAMP
 MODNO

AUTHORIZEPROJECT_IOPK_REQ

Attribute	Description
Name	AUTHORIZEPROJECT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Developer-Projects-IO

Attribute	Description
Name	Developer-Projects-IO
Datatype	
Description	

DEVELOPCODE

Attribute	Description				
Name	DEVELOPCODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

PROJECTNAME

Attribute	Description				
Name	PROJECTNAME				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

2.30.3. CS-AuthorizeProject-Res-Full-MSG.xsd

AUTHORIZEPROJECT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Developer-Projects-Full

DEVELOPCODE

PROJECTNAME

PROJECTDESC

ADDRESS

PRJADDR2

PRJADDR3

STATUS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Dev-Prj-Dtls

UNITID

UNITHOLDERNAME

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEPROJECT_FSFS_RES

Attribute	Description
Name	AUTHORIZEPROJECT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Developer-Projects-Full

Attribute	Description	
Name	Developer-Projects-Full	
Datatype		
Description		

DEVELOPCODE

Attribute	Description	
------------------	--------------------	--

Name	DEVELOPCODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

PROJECTNAME

Attribute	Description	
Name	PROJECTNAME	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

PROJECTDESC

Attribute	Description	
Name	PROJECTDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

ADDRESS

Attribute	Description	
Name	ADDRESS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

PRJADDR2

Attribute	Description	
Name	PRJADDR2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	100

PRJADDR3

Attribute	Description	
Name	PRJADDR3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Dev-Prj-Dtls

Attribute	Description	
Name	Dev-Prj-Dtls	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

UNITID

Attribute	Description	
Name	UNITID	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9

UNITHOLDERNAME

Attribute	Description	
Name	UNITHOLDERNAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	105

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description
------------------	--------------------

Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

AUTHORIZEPROJECT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Developer-Projects-PK

DEVELOPCODE

PROJECTNAME

Developer-Projects-IO

DEVELOPCODE

PROJECTNAME

CHECKER

CHECKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEPROJECT_IOPK_RES

Attribute	Description
Name	AUTHORIZEPROJECT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Developer-Projects-PK

Attribute	Description	
Name	Developer-Projects-PK	
Datatype		
Description		

DEVELOPCODE

Attribute	Description	

Name	DEVELOPCODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

PROJECTNAME

Attribute	Description	
Name	PROJECTNAME	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

Developer-Projects-IO

Attribute	Description	
Name	Developer-Projects-IO	
Datatype		
Description		

DEVELOPCODE

Attribute	Description	
Name	DEVELOPCODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

PROJECTNAME

Attribute	Description	
Name	PROJECTNAME	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
------------------	--------------------

Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.31.CloseAcctr

2.31.1.CS-CloseAcctr-Req-Full-MSG.xsd

CLOSEACCTR_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Master-Full
TRANSFER_ID
CURRENT_BRANCH
TARGET_BRANCH_CODE
TRANSDT
TARGET_BRANCH_NAME
CURRENT_BRANCH_NAME
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT

AUTHSTAT

Child

ACCOUNTNUMBER

AC_DESC

CUSTOMER_NUMBER

TXT_CUSTNAME

UDFDETAILS

FLDNAM

FLDVAL

CLOSEACCTR_FSFS_REQ

Attribute	Description
Name	CLOSEACCTR_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Master-Full

Attribute	Description	
Name	Master-Full	
Datatype		
Description		

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

CURRENT_BRANCH

Attribute	Description				
Name	CURRENT_BRANCH				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TARGET_BRANCH_CODE

Attribute	Description				
Name	TARGET_BRANCH_CODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	String
Description	

TARGET_BRANCH_NAME

Attribute	Description				
Name	TARGET_BRANCH_NAME				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

CURRENT_BRANCH_NAME

Attribute	Description
Name	CURRENT_BRANCH_NAME
Datatype	String

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

Child

Attribute	Description	
Name	Child	
Datatype		

Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

ACCOUNTNUMBER

Attribute	Description				
Name	ACCOUNTNUMBER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

AC_DESC

Attribute	Description				
Name	AC_DESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>255</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

CUSTOMER_NUMBER

Attribute	Description				
Name	CUSTOMER_NUMBER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>255</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

TXT_CUSTNAME

Attribute	Description
Name	TXT_CUSTNAME
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
Restrictions	Restrictions	Description
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
Restrictions	Restrictions	Description
	minLength	0

2.31.2.CS-CloseAcctr-Req-IO-MSG.xsd

CLOSEACCTR_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
 PARAM
 NAME
 VALUE
FCUBS_BODY
 Master-IO
 TRANSFER_ID
 MAKER
 MAKERSTAMP
 MODNO

CLOSEACCTR_IOPK_REQ

Attribute	Description
Name	CLOSEACCTR_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

2.31.3.CS-CloseAcctr-Res-Full-MSG.xsd

CLOSEACCTR_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-Full

TRANSFER_ID

CURRENT_BRANCH

TARGET_BRANCH_CODE

TRANSDT

TARGET_BRANCH_NAME

CURRENT_BRANCH_NAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Child

ACCOUNTNUMBER

AC_DESC

CUSTOMER_NUMBER

TXT_CUSTNAME

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CLOSEACCTR_FSFS_RES

Attribute	Description
Name	CLOSEACCTR_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*
	Description	

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*
	Description	

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	enumeration	SUCCESS,WARNING,FAILURE
	Description	

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*
	Description	

ADDL

Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

FCUBS_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description			

Master-Full

Attribute		Description	
Name	Master-Full		
Datatype			
Description			

TRANSFER_ID

Attribute		Description	
Name	TRANSFER_ID		
Datatype	String		
Description			
Restrictions	Restrictions		Description
	maxLength	16	

CURRENT_BRANCH

Attribute	Description	
Name	CURRENT_BRANCH	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

TARGET_BRANCH_CODE

Attribute	Description	
Name	TARGET_BRANCH_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

TRANSDT

Attribute	Description	
Name	TRANSDT	
Datatype	String	
Description		

TARGET_BRANCH_NAME

Attribute	Description	
Name	TARGET_BRANCH_NAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

CURRENT_BRANCH_NAME

Attribute	Description	
Name	CURRENT_BRANCH_NAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Child

Attribute	Description	
Name	Child	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCOUNTNUMBER

Attribute	Description	
Name	ACCOUNTNUMBER	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

AC_DESC

Attribute	Description	
Name	AC_DESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

CUSTOMER_NUMBER

Attribute	Description	
Name	CUSTOMER_NUMBER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TXT_CUSTNAME

Attribute	Description	
Name	TXT_CUSTNAME	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		

Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
------------------	--------------------

Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.31.4.CS-CloseAcctr-Res-PK-MSG.xsd

CLOSEACCTR_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Master-PK
TRANSFER_ID
Master-IO
TRANSFER_ID
MAKER
MAKERSTAMP
MODNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE

CLOSEACCTR_IOPK_RES

Attribute	Description
Name	CLOSEACCTR_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute		Description	
Name	SOURCE_USERID		
Datatype	String		
Description	This is the user id in the Source system who is performing the action.		
Attribute	Attribute		Description
	minOccurs	0	

DESTINATION

Attribute		Description	
Name	DESTINATION		
Datatype	String		
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute		Description	
Name	MULTITRIPID		
Datatype	String		
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute		Description	
Name	FUNCTIONID		
Datatype	String		
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.		
Attribute	Attribute		Description
	minOccurs	0	

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-PK

Attribute	Description
Name	Master-PK
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

Master-IO

Attribute	Description
-----------	-------------

Name	Master-IO
Datatype	
Description	

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	16

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute		Description	
Name	FCUBS_ERROR_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

ERROR

Attribute		Description	
Name	ERROR		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

ECODE

Attribute		Description	
Name	ECODE		
Datatype	String		
Description			

EDESC

Attribute		Description	
Name	EDESC		
Datatype	String		
Description			

FCUBS_WARNING_RESP

Attribute		Description	
Name	FCUBS_WARNING_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

WARNING

Attribute		Description	
Name	WARNING		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.32.CloseAcltr

2.32.1.CS-CloseAcltr-Req-Full-MSG.xsd

CLOSEACLTR_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-Full

TRANSFER_ID

ACCOUNT_CLASS

CURRENT_BRANCH_CODE

TARGET_BRANCH_CODE

TRANSFER_DATE

CURRENT_BRANCH_NAME

TARGET_BRANCH_NAME

ACCOUNT_CLASS_DESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

CLOSEACLTR_FSFS_REQ

Attribute	Description
Name	CLOSEACLTR_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>64</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	64
Restrictions	Description				
maxLength	64				

ACCOUNT_CLASS

Attribute	Description				
Name	ACCOUNT_CLASS				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>24</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	24
Restrictions	Description				
maxLength	24				

CURRENT_BRANCH_CODE

Attribute	Description				
Name	CURRENT_BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

TARGET_BRANCH_CODE

Attribute	Description				
Name	TARGET_BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	String
Description	

CURRENT_BRANCH_NAME

Attribute	Description				
Name	CURRENT_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
	Restrictions	Description			
maxLength	255				

TARGET_BRANCH_NAME

Attribute	Description				
Name	TARGET_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
	Restrictions	Description			
maxLength	255				

ACCOUNT_CLASS_DESC

Attribute	Description				
Name	ACCOUNT_CLASS_DESC				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.32.2. CS-CloseAcltr-Req-IO-MSG.xsd

CLOSEACLTR_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-IO

TRANSFER_ID

MAKER

MAKERSTAMP

MODNO

CLOSEACLTR_IOPK_REQ

Attribute	Description
Name	CLOSEACLTR_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Master-IO

Attribute		Description
------------------	--	--------------------

Name	Master-IO
Datatype	
Description	

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	64

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

CLOSEACLTR_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-Full

TRANSFER_ID

ACCOUNT_CLASS

CURRENT_BRANCH_CODE

TARGET_BRANCH_CODE

TRANSFER_DATE

CURRENT_BRANCH_NAME

TARGET_BRANCH_NAME

ACCOUNT_CLASS_DESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CLOSEACLTR_FSFS_RES

Attribute	Description
Name	CLOSEACLTR_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>64</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	64
Restrictions	Description				
maxLength	64				

ACCOUNT_CLASS

Attribute	Description				
Name	ACCOUNT_CLASS				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>24</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	24
Restrictions	Description				
maxLength	24				

CURRENT_BRANCH_CODE

Attribute	Description				
Name	CURRENT_BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

TARGET_BRANCH_CODE

Attribute	Description				
Name	TARGET_BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	String
Description	

CURRENT_BRANCH_NAME

Attribute	Description				
Name	CURRENT_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
	Restrictions	Description			
maxLength	255				

TARGET_BRANCH_NAME

Attribute	Description				
Name	TARGET_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
	Restrictions	Description			
maxLength	255				

ACCOUNT_CLASS_DESC

Attribute	Description				
Name	ACCOUNT_CLASS_DESC				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.32.4.CS-CloseAcltr-Res-PK-MSG.xsd

CLOSEACLTR_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
 PARAM
 NAME
 VALUE
FCUBS_BODY
 Master-PK
 TRANSFER_ID
 Master-IO
 TRANSFER_ID
 MAKER
 MAKERSTAMP
 MODNO
FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

CLOSEACLTR_IOPK_RES

Attribute	Description
-----------	-------------

Name	CLOSEACLTR_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	
	Description	
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	
	Description	
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	

Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	

Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Master-PK

Attribute	Description	
Name	Master-PK	
Datatype		
Description		

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	64

Master-IO

Attribute	Description	
Name	Master-IO	
Datatype		
Description		

TRANSFER_ID

Attribute	Description	

Name	TRANSFER_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	64

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		

Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.33.CloseActrp

2.33.1.CS-CloseActrp-Req-Full-MSG.xsd

CLOSEACTRP_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cstm-Branch-Trfr-Param-Full

BRANCH_CODE

TRN_CODE

TRANSFER_GL

PROCESS_MODE

MAX_NO_OF_PROCESS

COMMIT_FREQUENCY

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

CLOSEACTRP_FSFS_REQ

Attribute	Description
Name	CLOSEACTRP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Cstm-Branch-Trfr-Param-Full

Attribute		Description
------------------	--	--------------------

Name	Cstm-Branch-Trfr-Param-Full
Datatype	
Description	

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

TRN_CODE

Attribute	Description	
Name	TRN_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

TRANSFER_GL

Attribute	Description	
Name	TRANSFER_GL	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

PROCESS_MODE

Attribute	Description	
Name	PROCESS_MODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	S,J

MAX_NO_OF_PROCESS

Attribute	Description
Name	MAX_NO_OF_PROCESS
Datatype	Decimal
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

COMMIT_FREQUENCY

Attribute	Description	
Name	COMMIT_FREQUENCY	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

2.33.2.CS-CloseActrp-Req-IO-MSG.xsd

CLOSEACTRP_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cstm-Branch-Trfr-Param-IO

BRANCH_CODE

MAKER

MAKERSTAMP

MODNO

CLOSEACTRP_IOPK_REQ

Attribute	Description
Name	CLOSEACTRP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute			
		Attribute	Description
		minOccurs	0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute			
		Attribute	Description
		minOccurs	0
		maxOccurs	unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Cstm-Branch-Trfr-Param-IO

Attribute		Description	
Name		Cstm-Branch-Trfr-Param-IO	
Datatype			
Description			

BRANCH_CODE

Attribute		Description	
Name		BRANCH_CODE	
Datatype		String	
Description			
Restrictions			
		Restrictions	Description
		maxLength	3

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

2.33.3.CS-CloseActrp-Res-Full-MSG.xsd

CLOSEACTRP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cstm-Branch-Trfr-Param-Full
BRANCH_CODE
TRN_CODE
TRANSFER_GL
PROCESS_MODE
MAX_NO_OF_PROCESS
COMMIT_FREQUENCY
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
FCUBS_ERROR_RESP
ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CLOSEACTRP_FSFS_RES

Attribute	Description
Name	CLOSEACTRP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cstm-Branch-Trfr-Param-Full

Attribute	Description
Name	Cstm-Branch-Trfr-Param-Full
Datatype	
Description	

BRANCH_CODE

Attribute	Description
------------------	--------------------

Name	BRANCH_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

TRN_CODE

Attribute	Description	
Name	TRN_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

TRANSFER_GL

Attribute	Description	
Name	TRANSFER_GL	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

PROCESS_MODE

Attribute	Description	
Name	PROCESS_MODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	S,J

MAX_NO_OF_PROCESS

Attribute	Description	
Name	MAX_NO_OF_PROCESS	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

COMMIT_FREQUENCY

Attribute		Description	
Name	COMMIT_FREQUENCY		
Datatype	Decimal		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	totalDigits	22	

MAKER

Attribute		Description	
Name	MAKER		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	12	

MAKERSTAMP

Attribute		Description	
Name	MAKERSTAMP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

CHECKER

Attribute		Description	
Name	CHECKER		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	12	

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

FCUBS_ERROR_RESP

Attribute		Description	
Name	FCUBS_ERROR_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

ERROR

Attribute		Description	
Name	ERROR		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

ECODE

Attribute		Description	
Name	ECODE		
Datatype	String		
Description			

EDESC

Attribute		Description	
Name	EDESC		
Datatype	String		
Description			

FCUBS_WARNING_RESP

Attribute		Description	
Name	FCUBS_WARNING_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

WARNING

Attribute		Description	
Name	WARNING		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.33.4.CS-CloseActrp-Res-PK-MSG.xsd

CLOSEACTRP_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cstm-Branch-Trfr-Param-PK

BRANCH_CODE

Cstm-Branch-Trfr-Param-IO

BRANCH_CODE

MAKER

MAKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CLOSEACTRP_IOPK_RES

Attribute	Description
Name	CLOSEACTRP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

MSGID

Attribute	Description					
Name	MSGID					
Datatype	String					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	String					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Cstm-Branch-Trfr-Param-PK
Datatype	
Description	

BRANCH_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

Cstm-Branch-Trfr-Param-IO

Attribute	Description
Name	Cstm-Branch-Trfr-Param-IO
Datatype	
Description	

BRANCH_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description
------------------	--------------------

Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.34.CreateAcctr

2.34.1.CS-CreateAcctr-Req-Full-MSG.xsd

CREATEACCTR_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION
MULTIRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Master-Full
TRANSFER_ID
CURRENT_BRANCH
TARGET_BRANCH_CODE
TRANSDT
TARGET_BRANCH_NAME
CURRENT_BRANCH_NAME
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Child
ACCOUNTNUMBER
AC_DESC
CUSTOMER_NUMBER
TXT_CUSTNAME
UDFDETAILS
FLDNAM

CREATEACCTR_FSFS_REQ

Attribute	Description
Name	CREATEACCTR_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute		Description	
Name	SOURCE_USERID		
Datatype	String		
Description	This is the user id in the Source system who is performing the action.		
Attribute	Attribute		Description
	minOccurs	0	

DESTINATION

Attribute		Description	
Name	DESTINATION		
Datatype	String		
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute		Description	
Name	MULTITRIPID		
Datatype	String		
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute		Description	
Name	FUNCTIONID		
Datatype	String		
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.		
Attribute	Attribute		Description
	minOccurs	0	

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

CURRENT_BRANCH

Attribute	Description
-----------	-------------

Name	CURENT_BRANCH	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

TARGET_BRANCH_CODE

Attribute	Description	
Name	TARGET_BRANCH_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

TRANSDT

Attribute	Description	
Name	TRANSDT	
Datatype	String	
Description		

TARGET_BRANCH_NAME

Attribute	Description	
Name	TARGET_BRANCH_NAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

CURRENT_BRANCH_NAME

Attribute	Description	
Name	CURRENT_BRANCH_NAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description
Name	MODNO

Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Child

Attribute	Description	
Name	Child	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCOUNTNUMBER

Attribute	Description	
Name	ACCOUNTNUMBER	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	20

AC_DESC

Attribute	Description	
Name	AC_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

CUSTOMER_NUMBER

Attribute	Description	
Name	CUSTOMER_NUMBER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TXT_CUSTNAME

Attribute	Description	
Name	TXT_CUSTNAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.34.2. CS-CreateAcctr-Req-IO-MSG.xsd

CREATEACCTR_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-IO

TRANSFER_ID

TARGET_BRANCH_CODE

TRANSDT

Child

UDFDETAILS

FLDNAM

FLDVAL

CREATEACCTR_IOPK_REQ

Attribute	Description
Name	CREATEACCTR_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

TARGET_BRANCH_CODE

Attribute	Description				
Name	TARGET_BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	String
Description	

Child

Attribute	Description

Name	Child	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.34.3.CS-CreateAcctr-Res-Full-MSG.xsd

CREATEACCTR_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Master-Full
TRANSFER_ID
CURRENT_BRANCH
TARGET_BRANCH_CODE
TRANSDT
TARGET_BRANCH_NAME
CURRENT_BRANCH_NAME
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT

Child

ACCOUNTNUMBER

AC_DESC

CUSTOMER_NUMBER

TXT_CUSTNAME

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEACCTR_FSFS_RES

Attribute	Description
Name	CREATEACCTR_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description
Name	USERID

Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
	Attribute	Description			
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

CURRENT_BRANCH

Attribute	Description				
Name	CURRENT_BRANCH				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TARGET_BRANCH_CODE

Attribute	Description				
Name	TARGET_BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	String
Description	

TARGET_BRANCH_NAME

Attribute	Description
Name	TARGET_BRANCH_NAME

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

CURRENT_BRANCH_NAME

Attribute	Description	
Name	CURRENT_BRANCH_NAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	

Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Child

Attribute	Description	
Name	Child	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCOUNTNUMBER

Attribute	Description	
Name	ACCOUNTNUMBER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	20

AC_DESC

Attribute	Description	
Name	AC_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

CUSTOMER_NUMBER

Attribute	Description	
Name	CUSTOMER_NUMBER	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TXT_CUSTNAME

Attribute	Description	
Name	TXT_CUSTNAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.34.4.CS-CreateAcctr-Res-PK-MSG.xsd

CREATEACCTR_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-PK

TRANSFER_ID

Master-IO

TRANSFER_ID

TARGET_BRANCH_CODE

TRANSDT

Child

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEACCTR_IOPK_RES

Attribute	Description
Name	CREATEACCTR_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within EL EXCLUDE UBS. In

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-PK

Attribute	Description
Name	Master-PK
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

TARGET_BRANCH_CODE

Attribute	Description

Name	TARGET_BRANCH_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	String
Description	

Child

Attribute	Description	
Name	Child	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.35.CreateAcltr

2.35.1.CS-CreateAcltr-Req-Full-MSG.xsd

CREATEACLTR_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-Full

TRANSFER_ID

ACCOUNT_CLASS

CURRENT_BRANCH_CODE

TARGET_BRANCH_CODE

TRANSFER_DATE

CURRENT_BRANCH_NAME

TARGET_BRANCH_NAME

ACCOUNT_CLASS_DESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

CREATEACLTR_FSFS_REQ

Attribute	Description
Name	CREATEACLTR_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	
-------------	--

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
pattern	[A-Z_0-9]*	

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>64</td></tr></tbody></table>	Restrictions	Description	maxLength	64
Restrictions	Description				
maxLength	64				

ACCOUNT_CLASS

Attribute	Description				
Name	ACCOUNT_CLASS				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>24</td></tr></tbody></table>	Restrictions	Description	maxLength	24
Restrictions	Description				
maxLength	24				

CURRENT_BRANCH_CODE

Attribute	Description				
Name	CURRENT_BRANCH_CODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

TARGET_BRANCH_CODE

Attribute	Description				
Name	TARGET_BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	String
Description	

CURRENT_BRANCH_NAME

Attribute	Description				
Name	CURRENT_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
	Restrictions	Description			
maxLength	255				

TARGET_BRANCH_NAME

Attribute	Description				
Name	TARGET_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
	Restrictions	Description			
maxLength	255				

ACCOUNT_CLASS_DESC

Attribute	Description				
Name	ACCOUNT_CLASS_DESC				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.35.2. CS-CreateAcltr-Req-IO-MSG.xsd

CREATEACLTR_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-IO

TRANSFER_ID

ACCOUNT_CLASS

TARGET_BRANCH_CODE

TRANSFER_DATE

UDFDETAILS

FLDNAM

FLDVAL

CREATEACLTR_IOPK_REQ

Attribute	Description
Name	CREATEACLTR_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
-----------	-------------

Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE. ¹⁴⁰²	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Master-IO
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>64</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	64
Restrictions	Description				
maxLength	64				

ACCOUNT_CLASS

Attribute	Description				
Name	ACCOUNT_CLASS				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>24</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	24
Restrictions	Description				
maxLength	24				

TARGET_BRANCH_CODE

Attribute	Description				
Name	TARGET_BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	String
Description	

UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

FLDNAM

Attribute	Description
-----------	-------------

Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.35.3.CS-CreateAcItr-Res-Full-MSG.xsd

CREATEACLTR_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTIRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-Full

TRANSFER_ID

ACCOUNT_CLASS

CURRENT_BRANCH_CODE

TARGET_BRANCH_CODE

TRANSFER_DATE

CURRENT_BRANCH_NAME

TARGET_BRANCH_NAME

ACCOUNT_CLASS_DESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

CREATEACLTR_FSFS_RES

Attribute	Description
Name	CREATEACLTR_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute		Description	
Name	SOURCE_USERID		
Datatype	String		
Description	This is the user id in the Source system who is performing the action.		
Attribute	Attribute		Description
	minOccurs	0	

DESTINATION

Attribute		Description	
Name	DESTINATION		
Datatype	String		
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute		Description	
Name	MULTITRIPID		
Datatype	String		
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute		Description	
Name	FUNCTIONID		
Datatype	String		
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.		
Attribute	Attribute		Description
	minOccurs	0	

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>64</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	64
Restrictions	Description				
maxLength	64				

ACCOUNT_CLASS

Attribute	Description
-----------	-------------

Name	ACCOUNT_CLASS	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	24

CURRENT_BRANCH_CODE

Attribute	Description	
Name	CURRENT_BRANCH_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	12

TARGET_BRANCH_CODE

Attribute	Description	
Name	TARGET_BRANCH_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	12

TRANSFER_DATE

Attribute	Description	
Name	TRANSFER_DATE	
Datatype	String	
Description		

CURRENT_BRANCH_NAME

Attribute	Description	
Name	CURRENT_BRANCH_NAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TARGET_BRANCH_NAME

Attribute	Description	
Name	TARGET_BRANCH_NAME	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

ACCOUNT_CLASS_DESC

Attribute	Description	
Name	ACCOUNT_CLASS_DESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxOccurs	unbounded

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String

2.35.4. CS-CreateAcltr-Res-PK-MSG.xsd

*CREATEACLTR_IOPK_RES**FCUBS_HEADER**SOURCE**UBSCOMP**MSGID**CORRELID**USERID**BRANCH**MODULEID**SERVICE**OPERATION**SOURCE_OPERATION**SOURCE_USERID**DESTINATION**MULTITRIPID**FUNCTIONID**ACTION**MSGSTAT**PASSWORD**ADDL**PARAM**NAME**VALUE**FCUBS_BODY**Master-PK**TRANSFER_ID**Master-IO**TRANSFER_ID**ACCOUNT_CLASS**TARGET_BRANCH_CODE**TRANSFER_DATE*

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEACLTR_IOPK_RES

Attribute	Description
Name	CREATEACLTR_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Master-PK

Attribute	Description
------------------	--------------------

Name	Master-PK
Datatype	
Description	

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	64

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	64

ACCOUNT_CLASS

Attribute	Description	
Name	ACCOUNT_CLASS	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	24

TARGET_BRANCH_CODE

Attribute	Description	
Name	TARGET_BRANCH_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	12

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	String

Description	
-------------	--

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.36.CreateActrp

2.36.1.CS-CreateActrp-Req-Full-MSG.xsd

[CREATEACTRP_FSFS_REQ](#)

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cstm-Branch-Trfr-Param-Full

BRANCH_CODE

TRN_CODE

TRANSFER_GL

PROCESS_MODE

MAX_NO_OF_PROCESS

COMMIT_FREQUENCY

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

CREATEACTRP_FSFS_REQ

Attribute	Description
Name	CREATEACTRP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0
	maxOccurs		unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Cstm-Branch-Trfr-Param-Full

Attribute		Description	
Name		Cstm-Branch-Trfr-Param-Full	
Datatype			
Description			

BRANCH_CODE

Attribute		Description	
Name		BRANCH_CODE	
Datatype		String	
Description			
Restrictions	Restrictions		Description
	maxLength		3

TRN_CODE

Attribute	Description				
Name	TRN_CODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TRANSFER_GL

Attribute	Description				
Name	TRANSFER_GL				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

PROCESS_MODE

Attribute	Description				
Name	PROCESS_MODE				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>S,J</td></tr></tbody></table>	Restrictions	Description	enumeration	S,J
Restrictions	Description				
enumeration	S,J				

MAX_NO_OF_PROCESS

Attribute	Description				
Name	MAX_NO_OF_PROCESS				
Datatype	Decimal				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

COMMIT_FREQUENCY

Attribute	Description
Name	COMMIT_FREQUENCY
Datatype	Decimal
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

2.36.2.CS-CreateActrp-Req-IO-MSG.xsd

[CREATEACTRP_IOPK_REQ](#)

[FCUBS_HEADER](#)

[SOURCE](#)

UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
 PARAM
 NAME
 VALUE
FCUBS_BODY
 Cstm-Branch-Trfr-Param-IO
 BRANCH_CODE
 TRN_CODE
 TRANSFER_GL
 PROCESS_MODE
 MAX_NO_OF_PROCESS
 COMMIT_FREQUENCY

CREATEACTRP_IOPK_REQ

Attribute	Description
Name	CREATEACTRP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cstm-Branch-Trfr-Param-IO

Attribute	Description
Name	Cstm-Branch-Trfr-Param-IO
Datatype	
Description	

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	3

TRN_CODE

Attribute	Description	
Name	TRN_CODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	3

TRANSFER_GL

Attribute	Description
Name	TRANSFER_GL

Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

PROCESS_MODE

Attribute	Description	
Name	PROCESS_MODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	S,J

MAX_NO_OF_PROCESS

Attribute	Description	
Name	MAX_NO_OF_PROCESS	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

COMMIT_FREQUENCY

Attribute	Description	
Name	COMMIT_FREQUENCY	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

2.36.3.CS-CreateActrp-Res-Full-MSG.xsd

CREATEACTRP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cstm-Branch-Trfr-Param-Full
BRANCH_CODE
TRN_CODE
TRANSFER_GL
PROCESS_MODE
MAX_NO_OF_PROCESS
COMMIT_FREQUENCY
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEACTRP_FSFS_RES

Attribute	Description
Name	CREATEACTRP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Cstm-Branch-Trfr-Param-Full

Attribute		Description
------------------	--	--------------------

Name	Cstm-Branch-Trfr-Param-Full
Datatype	
Description	

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

TRN_CODE

Attribute	Description	
Name	TRN_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

TRANSFER_GL

Attribute	Description	
Name	TRANSFER_GL	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

PROCESS_MODE

Attribute	Description	
Name	PROCESS_MODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	S,J

MAX_NO_OF_PROCESS

Attribute	Description
Name	MAX_NO_OF_PROCESS
Datatype	Decimal
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

COMMIT_FREQUENCY

Attribute	Description	
Name	COMMIT_FREQUENCY	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description
------------------	--------------------

Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.36.4.CS-CreateActrp-Res-PK-MSG.xsd

CREATEACTRP_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cstm-Branch-Trfr-Param-PK

BRANCH_CODE

Cstm-Branch-Trfr-Param-IO

BRANCH_CODE

TRN_CODE

TRANSFER_GL

PROCESS_MODE

MAX_NO_OF_PROCESS

COMMIT_FREQUENCY

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEACTRP_IOPK_RES

Attribute	Description
Name	CREATEACTRP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within EL EXCLUDE UBS. In

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
pattern	[A-Z_0-9]*	

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cstm-Branch-Trfr-Param-PK

Attribute	Description
Name	Cstm-Branch-Trfr-Param-PK
Datatype	
Description	

BRANCH_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

Cstm-Branch-Trfr-Param-IO

Attribute	Description
Name	Cstm-Branch-Trfr-Param-IO
Datatype	
Description	

BRANCH_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TRN_CODE

Attribute	Description

Name	TRN_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

TRANSFER_GL

Attribute	Description	
Name	TRANSFER_GL	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

PROCESS_MODE

Attribute	Description	
Name	PROCESS_MODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	S,J

MAX_NO_OF_PROCESS

Attribute	Description	
Name	MAX_NO_OF_PROCESS	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

COMMIT_FREQUENCY

Attribute	Description	
Name	COMMIT_FREQUENCY	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	22

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		

Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.37.CreateDeveloper

2.37.1.CS-CreateDeveloper-Req-Full-MSG.xsd

CREATEDVELOPER_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Developer-Full

WEBSITE

DEVELOPCODE

ADDRESS

DEVELOPERNAME

ADDRESS4

COUNTRY

EMAILID

ZIP

ADDRESS2

ADDRESS3

COUNTRY_NAME

TELEPHONE

FAX

MOBILE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Developer-Projects

PROJECTNAME

PROJECTDESC

CREATEDVELOPER_FSFS_REQ

Attribute	Description
Name	CREATEDVELOPER_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		

Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Developer-Full

Attribute	Description
Name	Developer-Full
Datatype	
Description	

WEBSITE

Attribute	Description	
Name	WEBSITE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

DEVELOPCODE

Attribute	Description	
Name	DEVELOPCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	9

ADDRESS

Attribute	Description	
Name	ADDRESS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

DEVELOPERNAME

Attribute	Description	
Name	DEVELOPERNAME	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

ADDRESS4

Attribute	Description	
Name	ADDRESS4	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

COUNTRY

Attribute	Description	
Name	COUNTRY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

EMAILID

Attribute	Description	
Name	EMAILID	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

ZIP

Attribute	Description	
Name	ZIP	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

ADDRESS2

Attribute	Description	
Name	ADDRESS2	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

ADDRESS3

Attribute	Description	
Name	ADDRESS3	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

COUNTRY_NAME

Attribute	Description	
Name	COUNTRY_NAME	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TELEPHONE

Attribute	Description	
Name	TELEPHONE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

FAX

Attribute	Description	
Name	FAX	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

MOBILE

Attribute	Description	
Name	MOBILE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Developer-Projects

Attribute	Description	
Name	Developer-Projects	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

PROJECTNAME

Attribute	Description	
Name	PROJECTNAME	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

PROJECTDESC

Attribute	Description	
Name	PROJECTDESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

2.37.2.CS-CreateDeveloper-Req-IO-MSG.xsd

CREATEDVELOPER_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Developer-IO

WEBSITE

DEVELOPCODE

ADDRESS

DEVELOPERNAME

ADDRESS4

COUNTRY

EMAILID

ZIP

ADDRESS2

ADDRESS3

COUNTRY_NAME

TELEPHONE

FAX

MOBILE

Developer-Projects

PROJECTNAME

PROJECTDESC

CREATEDDEVELOPER_IOPK_REQ

Attribute	Description
Name	CREATEDDEVELOPER_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Developer-IO

Attribute	Description
Name	Developer-IO
Datatype	
Description	

WEBSITE

Attribute	Description	
Name	WEBSITE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

DEVELOPCODE

Attribute	Description	
Name	DEVELOPCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	9

ADDRESS

Attribute	Description
Name	ADDRESS
Datatype	String
Description	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

DEVELOPERNAME

Attribute	Description	
Name	DEVELOPERNAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

ADDRESS4

Attribute	Description	
Name	ADDRESS4	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

COUNTRY

Attribute	Description	
Name	COUNTRY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

EMAILID

Attribute	Description	
Name	EMAILID	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

ZIP

Attribute	Description	
Name	ZIP	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

ADDRESS2

Attribute	Description	
Name	ADDRESS2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

ADDRESS3

Attribute	Description	
Name	ADDRESS3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

COUNTRY_NAME

Attribute	Description	
Name	COUNTRY_NAME	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TELEPHONE

Attribute	Description	
Name	TELEPHONE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

FAX

Attribute	Description	
Name	FAX	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

MOBILE

Attribute	Description	
Name	MOBILE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

Developer-Projects

Attribute	Description	
Name	Developer-Projects	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

PROJECTNAME

Attribute	Description	
Name	PROJECTNAME	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

PROJECTDESC

Attribute	Description	
Name	PROJECTDESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

2.37.3. CS-CreateDeveloper-Res-Full-MSG.xsd

CREATEDVELOPER_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Developer-Full
WEBSITE
DEVELOPCODE
ADDRESS
DEVELOPERNAME
ADDRESS4
COUNTRY
EMAILID
ZIP
ADDRESS2
ADDRESS3
COUNTRY_NAME
TELEPHONE
FAX
MOBILE
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT

AUTHSTAT

Developer-Projects

PROJECTNAME

PROJECTDESC

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEDVELOPER_FSFS_RES

Attribute	Description
Name	CREATEDVELOPER_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Developer-Full

Attribute	Description
------------------	--------------------

Name	Developer-Full
Datatype	
Description	

WEBSITE

Attribute	Description	
Name	WEBSITE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

DEVELOPCODE

Attribute	Description	
Name	DEVELOPCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	9

ADDRESS

Attribute	Description	
Name	ADDRESS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

DEVELOPERNAME

Attribute	Description	
Name	DEVELOPERNAME	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

ADDRESS4

Attribute		Description	
Name	ADDRESS4		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	100	

COUNTRY

Attribute		Description	
Name	COUNTRY		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	3	

EMAILID

Attribute		Description	
Name	EMAILID		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	30	

ZIP

Attribute		Description	
Name	ZIP		
Datatype	Decimal		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	totalDigits	22	

ADDRESS2

Attribute	Description	
Name	ADDRESS2	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

ADDRESS3

Attribute	Description	
Name	ADDRESS3	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

COUNTRY_NAME

Attribute	Description	
Name	COUNTRY_NAME	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TELEPHONE

Attribute	Description	
Name	TELEPHONE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

FAX

Attribute	Description	
Name	FAX	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

MOBILE

Attribute	Description	
Name	MOBILE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Developer-Projects

Attribute	Description	
Name	Developer-Projects	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

PROJECTNAME

Attribute	Description	
Name	PROJECTNAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

PROJECTDESC

Attribute	Description	
Name	PROJECTDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		

Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String

Description	
-------------	--

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.37.4.CS-CreateDeveloper-Res-PK-MSG.xsd

CREATEDEVELOPER_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Developer-PK

DEVELOPCODE

Developer-IO

WEBSITE

DEVELOPCODE

ADDRESS

DEVELOPERNAME

ADDRESS4

COUNTRY

EMAILID

ZIP

ADDRESS2

ADDRESS3

COUNTRY_NAME

TELEPHONE

FAX

MOBILE

Developer-Projects

PROJECTNAME

PROJECTDESC

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEDEVELOPER_IOPK_RES

Attribute	Description
Name	CREATEDEVELOPER_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	
-------------	--

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Developer-PK

Attribute	Description
Name	Developer-PK
Datatype	
Description	

DEVELOPCODE

Attribute	Description				
Name	DEVELOPCODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

Developer-IO

Attribute	Description
Name	Developer-IO
Datatype	
Description	

WEBSITE

Attribute	Description				
Name	WEBSITE				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

DEVELOPCODE

Attribute	Description	
Name	DEVELOPCODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

ADDRESS

Attribute	Description	
Name	ADDRESS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

DEVELOPERNAME

Attribute	Description	
Name	DEVELOPERNAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

ADDRESS4

Attribute	Description	
Name	ADDRESS4	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

COUNTRY

Attribute	Description	
Name	COUNTRY	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

EMAILID

Attribute	Description	
Name	EMAILID	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

ZIP

Attribute	Description	
Name	ZIP	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

ADDRESS2

Attribute	Description	
Name	ADDRESS2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

ADDRESS3

Attribute	Description	
Name	ADDRESS3	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

COUNTRY_NAME

Attribute	Description	
Name	COUNTRY_NAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TELEPHONE

Attribute	Description	
Name	TELEPHONE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

FAX

Attribute	Description	
Name	FAX	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

MOBILE

Attribute	Description	
Name	MOBILE	

Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	30
	Description	

Developer-Projects

Attribute	Description	
Name	Developer-Projects	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

PROJECTNAME

Attribute	Description	
Name	PROJECTNAME	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	35
	Description	

PROJECTDESC

Attribute	Description	
Name	PROJECTDESC	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	105
	Description	

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.38.CreateProject

2.38.1.CS-CreateProject-Req-Full-MSG.xsd

CREATEPROJECT_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Developer-Projects-Full

DEVELOPCODE

PROJECTNAME

PROJECTDESC

ADDRESS

PRJADDR2

PRJADDR3

STATUS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Dev-Prj-Dtls

UNITID

UNITHOLDERNAME

UDFDETAILS

FLDNAM

FLDVAL

CREATEPROJECT_FSFS_REQ

Attribute	Description
Name	CREATEPROJECT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Developer-Projects-Full

Attribute	Description
Name	Developer-Projects-Full
Datatype	
Description	

DEVELOPCODE

Attribute	Description				
Name	DEVELOPCODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

PROJECTNAME

Attribute	Description				
Name	PROJECTNAME				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

PROJECTDESC

Attribute	Description				
Name	PROJECTDESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	105

ADDRESS

Attribute	Description	
Name	ADDRESS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

PRJADDR2

Attribute	Description	
Name	PRJADDR2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

PRJADDR3

Attribute	Description	
Name	PRJADDR3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Dev-Prj-Dtls

Attribute	Description	
Name	Dev-Prj-Dtls	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

UNITID

Attribute	Description	
Name	UNITID	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

UNITHOLDERNAME

Attribute	Description	
Name	UNITHOLDERNAME	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.38.2.CS-CreateProject-Req-IO-MSG.xsd

CREATEPROJECT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Developer-Projects-IO

DEVELOPCODE

PROJECTNAME

PROJECTDESC

ADDRESS

PRJADDR2

PRJADDR3

STATUS

Dev-Prj-Dtls

UNITID

UNITHOLDERNAME

UDFDETAILS

FLDNAM

FLDVAL

CREATEPROJECT_IOPK_REQ

Attribute	Description
Name	CREATEPROJECT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Developer-Projects-IO

Attribute		Description
------------------	--	--------------------

Name	Developer-Projects-IO
Datatype	
Description	

DEVELOPCODE

Attribute	Description	
Name	DEVELOPCODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

PROJECTNAME

Attribute	Description	
Name	PROJECTNAME	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

PROJECTDESC

Attribute	Description	
Name	PROJECTDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

ADDRESS

Attribute	Description	
Name	ADDRESS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

PRJADDR2

Attribute	Description
Name	PRJADDR2

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

PRJADDR3

Attribute	Description	
Name	PRJADDR3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

Dev-Prj-Dtls

Attribute	Description	
Name	Dev-Prj-Dtls	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

UNITID

Attribute	Description	
Name	UNITID	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9

UNITHOLDERNAME

Attribute	Description	
Name	UNITHOLDERNAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.38.3. CS-CreateProject-Res-Full-MSG.xsd

CREATEPROJECT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Developer-Projects-Full

DEVELOPCODE

PROJECTNAME

PROJECTDESC

ADDRESS

PRJADDR2

PRJADDR3

STATUS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Dev-Prj-Dtls

UNITID

UNITHOLDERNAME

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEPROJECT_FSFS_RES

Attribute	Description
Name	CREATEPROJECT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Developer-Projects-Full

Attribute	Description
Name	Developer-Projects-Full
Datatype	
Description	

DEVELOPCODE

Attribute	Description				
Name	DEVELOPCODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

PROJECTNAME

Attribute	Description				
Name	PROJECTNAME				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

PROJECTDESC

Attribute	Description				
Name	PROJECTDESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	105

ADDRESS

Attribute	Description	
Name	ADDRESS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

PRJADDR2

Attribute	Description	
Name	PRJADDR2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

PRJADDR3

Attribute	Description	
Name	PRJADDR3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Dev-Prj-Dtls

Attribute	Description	
Name	Dev-Prj-Dtls	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

UNITID

Attribute	Description	
Name	UNITID	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

UNITHOLDERNAME

Attribute	Description	
Name	UNITHOLDERNAME	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.38.4. CS-CreateProject-Res-PK-MSG.xsd

CREATEPROJECT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Developer-Projects-PK

DEVELOPCODE

PROJECTNAME

Developer-Projects-IO

DEVELOPCODE

PROJECTNAME

PROJECTDESC

ADDRESS

PRJADDR2

PRJADDR3

STATUS

Dev-Prj-Dtls

UNITID

UNITHOLDERNAME

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEPROJECT_IOPK_RES

Attribute	Description
-----------	-------------

Name	CREATEPROJECT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	
	Description	
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	
	Description	
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	

Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	

Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Developer-Projects-PK

Attribute	Description	
Name	Developer-Projects-PK	
Datatype		
Description		

DEVELOPCODE

Attribute	Description	
Name	DEVELOPCODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

PROJECTNAME

Attribute	Description	
Name	PROJECTNAME	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

Developer-Projects-IO

Attribute	Description
Name	Developer-Projects-IO
Datatype	
Description	

DEVELOPCODE

Attribute	Description				
Name	DEVELOPCODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

PROJECTNAME

Attribute	Description				
Name	PROJECTNAME				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

PROJECTDESC

Attribute	Description				
Name	PROJECTDESC				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

ADDRESS

Attribute	Description				
Name	ADDRESS				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>100</td></tr></tbody></table>	Restrictions	Description	maxLength	100
Restrictions	Description				
maxLength	100				

PRJADDR2

Attribute	Description	
Name	PRJADDR2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

PRJADDR3

Attribute	Description	
Name	PRJADDR3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

Dev-Prj-Dtls

Attribute	Description	
Name	Dev-Prj-Dtls	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

UNITID

Attribute	Description	
Name	UNITID	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

UNITHOLDERNAME

Attribute	Description	
Name	UNITHOLDERNAME	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.39.DeleteAcctr

2.39.1.CS-DeleteAcctr-Req-Full-MSG.xsd

DELETEACCTR_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM
 NAME
 VALUE
FCUBS_BODY
 Master-Full
 TRANSFER_ID
 CURRENT_BRANCH
 TARGET_BRANCH_CODE
 TRANSDT
 TARGET_BRANCH_NAME
 CURRENT_BRANCH_NAME
 MAKER
 MAKERSTAMP
 CHECKER
 CHECKERSTAMP
 MODNO
 TXNSTAT
 AUTHSTAT
 Child
 ACCOUNTNUMBER
 AC_DESC
 CUSTOMER_NUMBER
 TXT_CUSTNAME
 UDFDETAILS
 FLDNAM
 FLDVAL

DELETEACCTR_FSFS_REQ

Attribute	Description
Name	DELETEACCTR_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
-----------	-------------

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

CURRENT_BRANCH

Attribute	Description				
Name	CURRENT_BRANCH				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TARGET_BRANCH_CODE

Attribute	Description				
Name	TARGET_BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	String
Description	

TARGET_BRANCH_NAME

Attribute	Description				
Name	TARGET_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

CURRENT_BRANCH_NAME

Attribute	Description				
Name	CURRENT_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Child

Attribute	Description	
Name	Child	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCOUNTNUMBER

Attribute	Description	
Name	ACCOUNTNUMBER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	20

AC_DESC

Attribute	Description	
Name	AC_DESC	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

CUSTOMER_NUMBER

Attribute	Description	
Name	CUSTOMER_NUMBER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TXT_CUSTNAME

Attribute	Description	
Name	TXT_CUSTNAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.39.2.CS-DeleteAcctr-Req-IO-MSG.xsd

DELETEACCTR_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-IO

TRANSFER_ID

DELETEACCTR_IOPK_REQ

Attribute	Description
Name	DELETEACCTR_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TRANSFER_ID

Attribute	Description
------------------	--------------------

Name	TRANSFER_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	16

2.39.3.CS-DeleteAcctr-Res-Full-MSG.xsd

DELETEACCTR_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-Full

TRANSFER_ID

CURRENT_BRANCH

TARGET_BRANCH_CODE
TRANSDT
TARGET_BRANCH_NAME
CURRENT_BRANCH_NAME
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Child
 ACCOUNTNUMBER
 AC_DESC
 CUSTOMER_NUMBER
 TXT_CUSTNAME
 UDFDETAILS
 FLDNAM
 FLDVAL
FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

DELETEACCTR_FSFS_RES

Attribute	Description
Name	DELETEACCTR_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

CURRENT_BRANCH

Attribute	Description				
Name	CURRENT_BRANCH				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TARGET_BRANCH_CODE

Attribute	Description				
Name	TARGET_BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	String
Description	

TARGET_BRANCH_NAME

Attribute	Description				
Name	TARGET_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

CURRENT_BRANCH_NAME

Attribute	Description				
Name	CURRENT_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Child

Attribute	Description	
Name	Child	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCOUNTNUMBER

Attribute	Description	
Name	ACCOUNTNUMBER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	20

AC_DESC

Attribute	Description	
Name	AC_DESC	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

CUSTOMER_NUMBER

Attribute	Description	
Name	CUSTOMER_NUMBER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TXT_CUSTNAME

Attribute	Description	
Name	TXT_CUSTNAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.39.4.CS-DeleteAcctr-Res-PK-MSG.xsd

DELETEACCTR_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-PK

TRANSFER_ID

Master-IO

TRANSFER_ID

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEACCTR_IOPK_RES

Attribute	Description
Name	DELETEACCTR_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-PK

Attribute	Description
Name	Master-PK
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

FCUBS_ERROR_RESP

Attribute	Description
-----------	-------------

Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	
	Description	
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	
	Description	
	maxOccurs	unbounded

WCODE

Attribute	Description
------------------	--------------------

Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.40.DeleteAcltr

2.40.1.CS-DeleteAcltr-Req-Full-MSG.xsd

DELETEACLTR_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-Full

TRANSFER_ID
ACCOUNT_CLASS
CURRENT_BRANCH_CODE
TARGET_BRANCH_CODE
TRANSFER_DATE
CURRENT_BRANCH_NAME
TARGET_BRANCH_NAME
ACCOUNT_CLASS_DESC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM
FLDVAL

DELETEACLTR_FSFS_REQ

Attribute	Description
Name	DELETEACLTR_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>64</td></tr></tbody></table>	Restrictions	Description	maxLength	64
Restrictions	Description				
maxLength	64				

ACCOUNT_CLASS

Attribute	Description				
Name	ACCOUNT_CLASS				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>24</td></tr></tbody></table>	Restrictions	Description	maxLength	24
Restrictions	Description				
maxLength	24				

CURRENT_BRANCH_CODE

Attribute	Description				
Name	CURRENT_BRANCH_CODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

TARGET_BRANCH_CODE

Attribute	Description				
Name	TARGET_BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	String
Description	

CURRENT_BRANCH_NAME

Attribute	Description				
Name	CURRENT_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
	Restrictions	Description			
maxLength	255				

TARGET_BRANCH_NAME

Attribute	Description				
Name	TARGET_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
	Restrictions	Description			
maxLength	255				

ACCOUNT_CLASS_DESC

Attribute	Description				
Name	ACCOUNT_CLASS_DESC				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.40.2. CS-DeleteAcctr-Req-IO-MSG.xsd

DELETEACLTR_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-IO

TRANSFER_ID

DELETEACLTR_IOPK_REQ

Attribute	Description
Name	DELETEACLTR_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Master-IO

Attribute	Description	
Name	Master-IO	
Datatype		
Description		

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>64</td></tr></tbody></table>	Restrictions	Description	maxLength	64
Restrictions	Description				
maxLength	64				

2.40.3.CS-DeleteAcctr-Res-Full-MSG.xsd

DELETEACLTR_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-Full

TRANSFER_ID

ACCOUNT_CLASS
CURRENT_BRANCH_CODE
TARGET_BRANCH_CODE
TRANSFER_DATE
CURRENT_BRANCH_NAME
TARGET_BRANCH_NAME
ACCOUNT_CLASS_DESC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
 FLDNAM
 FLDVAL
FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

DELETEACLTR_FSFS_RES

Attribute	Description
Name	DELETEACLTR_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	
-------------	--

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>64</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	64
Restrictions	Description				
maxLength	64				

ACCOUNT_CLASS

Attribute	Description				
Name	ACCOUNT_CLASS				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>24</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	24
Restrictions	Description				
maxLength	24				

CURRENT_BRANCH_CODE

Attribute	Description				
Name	CURRENT_BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

TARGET_BRANCH_CODE

Attribute	Description	
Name	TARGET_BRANCH_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	12

TRANSFER_DATE

Attribute	Description	
Name	TRANSFER_DATE	
Datatype	String	
Description		

CURRENT_BRANCH_NAME

Attribute	Description	
Name	CURRENT_BRANCH_NAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TARGET_BRANCH_NAME

Attribute	Description	
Name	TARGET_BRANCH_NAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

ACCOUNT_CLASS_DESC

Attribute	Description	
Name	ACCOUNT_CLASS_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.40.4.CS-DeleteAcctr-Res-PK-MSG.xsd

DELETEACLTR_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-PK

TRANSFER_ID

Master-IO

TRANSFER_ID

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEACLTR_IOPK_RES

Attribute	Description
Name	DELETEACLTR_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-PK

Attribute	Description
Name	Master-PK
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>64</td></tr></tbody></table>	Restrictions	Description	maxLength	64
Restrictions	Description				
maxLength	64				

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>64</td></tr></tbody></table>	Restrictions	Description	maxLength	64
Restrictions	Description				
maxLength	64				

FCUBS_ERROR_RESP

Attribute	Description
-----------	-------------

Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	
	Description	
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	
	Description	
	maxOccurs	unbounded

WCODE

Attribute	Description
------------------	--------------------

Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.41.DeleteActrp

2.41.1.CS-DeleteActrp-Req-Full-MSG.xsd

DELETEACTRP_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cstm-Branch-Trfr-Param-Full

BRANCH_CODE

TRN_CODE

TRANSFER_GL

PROCESS_MODE

MAX_NO_OF_PROCESS

COMMIT_FREQUENCY

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

DELETEACTRP_FSFS_REQ

Attribute	Description
Name	DELETEACTRP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Cstm-Branch-Trfr-Param-Full

Attribute		Description
------------------	--	--------------------

Name	Cstm-Branch-Trfr-Param-Full
Datatype	
Description	

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

TRN_CODE

Attribute	Description	
Name	TRN_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

TRANSFER_GL

Attribute	Description	
Name	TRANSFER_GL	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

PROCESS_MODE

Attribute	Description	
Name	PROCESS_MODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	S,J

MAX_NO_OF_PROCESS

Attribute	Description
Name	MAX_NO_OF_PROCESS
Datatype	Decimal
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

COMMIT_FREQUENCY

Attribute	Description	
Name	COMMIT_FREQUENCY	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

2.41.2.CS-DeleteActrp-Req-IO-MSG.xsd

DELETEACTRP_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cstm-Branch-Trfr-Param-IO

BRANCH_CODE

Attribute	Description
Name	DELETEACTRP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nilable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nilable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	

Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Cstm-Branch-Trfr-Param-IO

Attribute	Description	
Name	Cstm-Branch-Trfr-Param-IO	
Datatype		
Description		

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

2.41.3.CS-DeleteActrp-Res-Full-MSG.xsd

DELETEACTRP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cstm-Branch-Trfr-Param-Full
BRANCH_CODE
TRN_CODE
TRANSFER_GL
PROCESS_MODE
MAX_NO_OF_PROCESS
COMMIT_FREQUENCY
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEACTRP_FSFS_RES

Attribute	Description
Name	DELETEACTRP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	

Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Cstm-Branch-Trfr-Param-Full

Attribute	Description	
Name	Cstm-Branch-Trfr-Param-Full	
Datatype		
Description		

BRANCH_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

TRN_CODE

Attribute	Description				
Name	TRN_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

TRANSFER_GL

Attribute	Description				
Name	TRANSFER_GL				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
	Restrictions	Description			
maxLength	20				

PROCESS_MODE

Attribute	Description				
Name	PROCESS_MODE				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>S,J</td></tr></tbody></table>	Restrictions	Description	enumeration	S,J
	Restrictions	Description			
enumeration	S,J				

MAX_NO_OF_PROCESS

Attribute	Description				
Name	MAX_NO_OF_PROCESS				
Datatype	Decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions		
	Restrictions	Description
	totalDigits	22

COMMIT_FREQUENCY

Attribute	Description	
Name	COMMIT_FREQUENCY	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		

Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.41.4.CS-DeleteActrp-Res-PK-MSG.xsd

DELETEACTRP_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cstm-Branch-Trfr-Param-PK

BRANCH_CODE

Cstm-Branch-Trfr-Param-IO

BRANCH_CODE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEACTRP_IOPK_RES

Attribute	Description
Name	DELETEACTRP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

MSGID

Attribute	Description					
Name	MSGID					
Datatype	String					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	String					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Cstm-Branch-Trfr-Param-PK
Datatype	
Description	

BRANCH_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

Cstm-Branch-Trfr-Param-IO

Attribute	Description
Name	Cstm-Branch-Trfr-Param-IO
Datatype	
Description	

BRANCH_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

FCUBS_ERROR_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

ECODE

Attribute	Description
-----------	-------------

Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.42.DeleteDeveloper

2.42.1.CS-DeleteDeveloper-Req-Full-MSG.xsd

DELETEDEVELOPER_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Developer-Full
WEBSITE
DEVELOPCODE
ADDRESS
DEVELOPERNAME
ADDRESS4
COUNTRY
EMAILID
ZIP
ADDRESS2
ADDRESS3
COUNTRY_NAME
TELEPHONE

FAX

MOBILE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Developer-Projects

PROJECTNAME

PROJECTDESC

DELETEDEVELOPER_FSFS_REQ

Attribute	Description
Name	DELETEDEVELOPER_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Developer-Full

Attribute	Description
------------------	--------------------

Name	Developer-Full
Datatype	
Description	

WEBSITE

Attribute	Description	
Name	WEBSITE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

DEVELOPCODE

Attribute	Description	
Name	DEVELOPCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	9

ADDRESS

Attribute	Description	
Name	ADDRESS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

DEVELOPERNAME

Attribute	Description	
Name	DEVELOPERNAME	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

ADDRESS4

Attribute		Description	
Name	ADDRESS4		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	100	

COUNTRY

Attribute		Description	
Name	COUNTRY		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	3	

EMAILID

Attribute		Description	
Name	EMAILID		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	30	

ZIP

Attribute		Description	
Name	ZIP		
Datatype	Decimal		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	totalDigits	22	

ADDRESS2

Attribute	Description	
Name	ADDRESS2	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

ADDRESS3

Attribute	Description	
Name	ADDRESS3	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

COUNTRY_NAME

Attribute	Description	
Name	COUNTRY_NAME	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TELEPHONE

Attribute	Description	
Name	TELEPHONE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

FAX

Attribute	Description	
Name	FAX	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

MOBILE

Attribute	Description	
Name	MOBILE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	1
	Description	

Developer-Projects

Attribute	Description	
Name	Developer-Projects	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

PROJECTNAME

Attribute	Description	
Name	PROJECTNAME	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	35
	Description	

PROJECTDESC

Attribute	Description	
Name	PROJECTDESC	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	105
	Description	

2.42.2.CS-DeleteDeveloper-Req-IO-MSG.xsd

DELETEDEVELOPER_IOPK_REQ

FCUBS_HEADER

SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Developer-IO
DEVELOPCODE

DELETEDEVELOPER_IOPK_REQ

Attribute	Description
Name	DELETEDEVELOPER_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Developer-IO

Attribute	Description
Name	Developer-IO
Datatype	
Description	

DEVELOPCODE

Attribute	Description				
Name	DEVELOPCODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

2.42.3.CS-DeleteDeveloper-Res-Full-MSG.xsd

DELETEDEVELOPER_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Developer-Full
WEBSITE
DEVELOPCODE
ADDRESS
DEVELOPERNAME
ADDRESS4
COUNTRY
EMAILID
ZIP
ADDRESS2
ADDRESS3
COUNTRY_NAME
TELEPHONE
FAX
MOBILE
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Developer-Projects

PROJECTNAME

PROJECTDESC

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEDEVELOPER_FSFS_RES

Attribute	Description
Name	DELETEDEVELOPER_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

MSGID

Attribute	Description					
Name	MSGID					
Datatype	String					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	String					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Developer-Full
Datatype	
Description	

WEBSITE

Attribute	Description				
Name	WEBSITE				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

DEVELOPCODE

Attribute	Description				
Name	DEVELOPCODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

ADDRESS

Attribute	Description				
Name	ADDRESS				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>100</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	100
Restrictions	Description				
maxLength	100				

DEVELOPERNAME

Attribute	Description				
Name	DEVELOPERNAME				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	35

ADDRESS4

Attribute	Description	
Name	ADDRESS4	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

COUNTRY

Attribute	Description	
Name	COUNTRY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

EMAILID

Attribute	Description	
Name	EMAILID	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

ZIP

Attribute	Description	
Name	ZIP	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	22

ADDRESS2

Attribute	Description	
Name	ADDRESS2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

ADDRESS3

Attribute	Description	
Name	ADDRESS3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

COUNTRY_NAME

Attribute	Description	
Name	COUNTRY_NAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TELEPHONE

Attribute	Description	
Name	TELEPHONE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	30

FAX

Attribute	Description	
Name	FAX	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

MOBILE

Attribute	Description	
Name	MOBILE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Developer-Projects

Attribute	Description	
Name	Developer-Projects	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

PROJECTNAME

Attribute	Description	
Name	PROJECTNAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

PROJECTDESC

Attribute	Description	
Name	PROJECTDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	105

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		

Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.42.4.CS-DeleteDeveloper-Res-PK-MSG.xsd

DELETEDEVELOPER_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Developer-PK

DEVELOPCODE

Developer-IO

DEVELOPCODE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEDEVELOPER_IOPK_RES

Attribute	Description
Name	DELETEDEVELOPER_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

MSGID

Attribute	Description					
Name	MSGID					
Datatype	String					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	String					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Developer-PK
Datatype	
Description	

DEVELOPCODE

Attribute	Description				
Name	DEVELOPCODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

Developer-IO

Attribute	Description
Name	Developer-IO
Datatype	
Description	

DEVELOPCODE

Attribute	Description				
Name	DEVELOPCODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

FCUBS_ERROR_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

ECODE

Attribute	Description
-----------	-------------

Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.43.DeleteProject

2.43.1.CS-DeleteProject-Req-Full-MSG.xsd

DELETEPROJECT_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Developer-Projects-Full
DEVELOPCODE
PROJECTNAME
PROJECTDESC
ADDRESS
PRJADDR2
PRJADDR3
STATUS
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO

TXNSTAT

AUTHSTAT

Dev-Prj-Dtls

UNITID

UNITHOLDERNAME

UDFDETAILS

FLDNAM

FLDVAL

DELETEPROJECT_FSFS_REQ

Attribute	Description
Name	DELETEPROJECT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

ORACLE®

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Developer-Projects-Full

Attribute	Description	
Name	Developer-Projects-Full	
Datatype		
Description		

DEVELOPCODE

Attribute	Description	
------------------	--------------------	--

Name	DEVELOPCODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

PROJECTNAME

Attribute	Description	
Name	PROJECTNAME	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

PROJECTDESC

Attribute	Description	
Name	PROJECTDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

ADDRESS

Attribute	Description	
Name	ADDRESS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

PRJADDR2

Attribute	Description	
Name	PRJADDR2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	100

PRJADDR3

Attribute	Description	
Name	PRJADDR3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Dev-Prj-Dtls

Attribute	Description	
Name	Dev-Prj-Dtls	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

UNITID

Attribute	Description	
Name	UNITID	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9

UNITHOLDERNAME

Attribute	Description	
Name	UNITHOLDERNAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	105

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.43.2.CS-DeleteProject-Req-IO-MSG.xsd

DELETEPROJECT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Developer-Projects-IO

DEVELOPCODE

PROJECTNAME

DELETEPROJECT_IOPK_REQ

Attribute	Description
Name	DELETEPROJECT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Developer-Projects-IO

Attribute	Description
Name	Developer-Projects-IO
Datatype	
Description	

DEVELOPCODE

Attribute	Description				
Name	DEVELOPCODE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

PROJECTNAME

Attribute	Description				
Name	PROJECTNAME				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

2.43.3.CS-DeleteProject-Res-Full-MSG.xsd

DELETEPROJECT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Developer-Projects-Full
DEVELOPCODE
PROJECTNAME
PROJECTDESC
ADDRESS
PRJADDR2
PRJADDR3
STATUS
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO

TXNSTAT

AUTHSTAT

Dev-Prj-Dtls

UNITID

UNITHOLDERNAME

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEPROJECT_FSFS_RES

Attribute	Description
Name	DELETEPROJECT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description
Name	USERID

Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nullable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Developer-Projects-Full

Attribute	Description
Name	Developer-Projects-Full
Datatype	
Description	

DEVELOPCODE

Attribute	Description				
Name	DEVELOPCODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

PROJECTNAME

Attribute	Description				
Name	PROJECTNAME				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

PROJECTDESC

Attribute	Description				
Name	PROJECTDESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

ADDRESS

Attribute	Description
Name	ADDRESS
Datatype	String
Description	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

PRJADDR2

Attribute	Description	
Name	PRJADDR2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

PRJADDR3

Attribute	Description	
Name	PRJADDR3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

Dev-Prj-Dtls

Attribute	Description	
Name	Dev-Prj-Dtls	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

UNITID

Attribute	Description	
Name	UNITID	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9

UNITHOLDERNAME

Attribute	Description	
Name	UNITHOLDERNAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.43.4.CS-DeleteProject-Res-PK-MSG.xsd

DELETEPROJECT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Developer-Projects-PK

DEVELOPCODE

PROJECTNAME

Developer-Projects-IO

DEVELOPCODE

PROJECTNAME

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEPROJECT_IOPK_RES

Attribute	Description
Name	DELETEPROJECT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
-----------	-------------

Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nullable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Developer-Projects-PK

Attribute	Description
Name	Developer-Projects-PK
Datatype	
Description	

DEVELOPCODE

Attribute	Description				
Name	DEVELOPCODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

PROJECTNAME

Attribute	Description				
Name	PROJECTNAME				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

Developer-Projects-IO

Attribute	Description
Name	Developer-Projects-IO
Datatype	
Description	

DEVELOPCODE

Attribute	Description				
Name	DEVELOPCODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

PROJECTNAME

Attribute	Description
Name	PROJECTNAME

Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	

Datatype				
Description				
Attribute				
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs
Attribute	Description			
maxOccurs	unbounded			

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.44.ModifyAcctr

2.44.1.CS-ModifyAcctr-Req-Full-MSG.xsd

MODIFYACCTR_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-Full

TRANSFER_ID

CURRENT_BRANCH

TARGET_BRANCH_CODE

TRANSDT

TARGET_BRANCH_NAME

CURRENT_BRANCH_NAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Child

ACCOUNTNUMBER

AC_DESC

CUSTOMER_NUMBER

TXT_CUSTNAME

UDFDETAILS

FLDNAM

FLDVAL

MODIFYACCTR_FSFS_REQ

Attribute	Description
Name	MODIFYACCTR_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

CURRENT_BRANCH

Attribute	Description				
Name	CURRENT_BRANCH				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TARGET_BRANCH_CODE

Attribute	Description				
Name	TARGET_BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	String
Description	

TARGET_BRANCH_NAME

Attribute	Description				
Name	TARGET_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

CURRENT_BRANCH_NAME

Attribute	Description				
Name	CURRENT_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Child

Attribute	Description	
Name	Child	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCOUNTNUMBER

Attribute	Description	
Name	ACCOUNTNUMBER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	20

AC_DESC

Attribute	Description	
Name	AC_DESC	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

CUSTOMER_NUMBER

Attribute	Description	
Name	CUSTOMER_NUMBER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TXT_CUSTNAME

Attribute	Description	
Name	TXT_CUSTNAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.44.2.CS-ModifyAcctr-Req-IO-MSG.xsd

MODIFYACCTR_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM
NAME
VALUE
FCUBS_BODY
Master-IO
TRANSFER_ID
TARGET_BRANCH_CODE
TRANSDT
MAKER
MAKERSTAMP
Child
UDFDETAILS
FLDNAM
FLDVAL

MODIFYACCTR_IOPK_REQ

Attribute	Description
Name	MODIFYACCTR_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

MSGID

Attribute	Description					
Name	MSGID					
Datatype	String					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	String					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Master-IO
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

TARGET_BRANCH_CODE

Attribute	Description				
Name	TARGET_BRANCH_CODE				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TRANSDT

Attribute	Description				
Name	TRANSDT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute	Description
-----------	-------------

Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	35
	Description	

Child

Attribute	Description	
Name	Child	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	
	maxLength	105
	minLength	1
	Description	

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.44.3. CS-ModifyAcctr-Res-Full-MSG.xsd

MODIFYACCTR_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-Full

TRANSFER_ID

CURRENT_BRANCH

TARGET_BRANCH_CODE

TRANSDT

TARGET_BRANCH_NAME

CURRENT_BRANCH_NAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Child

ACCOUNTNUMBER

AC_DESC

CUSTOMER_NUMBER

TXT_CUSTNAME

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYACCTR_FSFS_RES

Attribute	Description
Name	MODIFYACCTR_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

CURRENT_BRANCH

Attribute	Description				
Name	CURRENT_BRANCH				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TARGET_BRANCH_CODE

Attribute	Description				
Name	TARGET_BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	String
Description	

TARGET_BRANCH_NAME

Attribute	Description				
Name	TARGET_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

CURRENT_BRANCH_NAME

Attribute	Description				
Name	CURRENT_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Child

Attribute	Description	
Name	Child	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCOUNTNUMBER

Attribute	Description	
Name	ACCOUNTNUMBER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	20

AC_DESC

Attribute	Description	
Name	AC_DESC	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

CUSTOMER_NUMBER

Attribute	Description	
Name	CUSTOMER_NUMBER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TXT_CUSTNAME

Attribute	Description	
Name	TXT_CUSTNAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.44.4.CS-ModifyAcctr-Res-PK-MSG.xsd

MODIFYACCTR_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION
MULTIRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Master-PK
TRANSFER_ID
Master-IO
TRANSFER_ID
TARGET_BRANCH_CODE
TRANSDT
MAKER
MAKERSTAMP
Child
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

Attribute	Description
Name	MODIFYACCTR_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	

Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Master-PK

Attribute	Description	
Name	Master-PK	
Datatype		
Description		

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	16

Master-IO

Attribute	Description	
Name	Master-IO	
Datatype		
Description		

TRANSFER_ID

Attribute	Description	

Name	TRANSFER_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	16

TARGET_BRANCH_CODE

Attribute	Description	
Name	TARGET_BRANCH_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

TRANSDT

Attribute	Description	
Name	TRANSDT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

Child

Attribute	Description	
Name	Child	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description
------------------	--------------------

Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	
	Description	
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	
	Description	
	maxOccurs	unbounded

WCODE

Attribute	Description
------------------	--------------------

Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.45.ModifyAcltr

2.45.1.CS-ModifyAcltr-Req-Full-MSG.xsd

MODIFYACLTR_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-Full

TRANSFER_ID
ACCOUNT_CLASS
CURRENT_BRANCH_CODE
TARGET_BRANCH_CODE
TRANSFER_DATE
CURRENT_BRANCH_NAME
TARGET_BRANCH_NAME
ACCOUNT_CLASS_DESC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM
FLDVAL

MODIFYACLTR_FSFS_REQ

Attribute	Description
Name	MODIFYACLTR_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>64</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	64
Restrictions	Description				
maxLength	64				

ACCOUNT_CLASS

Attribute	Description				
Name	ACCOUNT_CLASS				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>24</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	24
Restrictions	Description				
maxLength	24				

CURRENT_BRANCH_CODE

Attribute	Description				
Name	CURRENT_BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

TARGET_BRANCH_CODE

Attribute	Description				
Name	TARGET_BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	String
Description	

CURRENT_BRANCH_NAME

Attribute	Description				
Name	CURRENT_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
	Restrictions	Description			
maxLength	255				

TARGET_BRANCH_NAME

Attribute	Description				
Name	TARGET_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
	Restrictions	Description			
maxLength	255				

ACCOUNT_CLASS_DESC

Attribute	Description				
Name	ACCOUNT_CLASS_DESC				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.45.2. CS-ModifyAcltr-Req-IO-MSG.xsd

MODIFYACLTR_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-IO

TRANSFER_ID

ACCOUNT_CLASS

TARGET_BRANCH_CODE

TRANSFER_DATE

ACCOUNT_CLASS_DESC

MAKER

MAKERSTAMP

UDFDETAILS

FLDNAM

FLDVAL

MODIFYACLTR_IOPK_REQ

Attribute	Description
Name	MODIFYACLTR_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>64</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	64
Restrictions	Description				
maxLength	64				

ACCOUNT_CLASS

Attribute	Description				
Name	ACCOUNT_CLASS				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>24</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	24
Restrictions	Description				
maxLength	24				

TARGET_BRANCH_CODE

Attribute	Description
Name	TARGET_BRANCH_CODE
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TRANSFER_DATE

Attribute	Description	
Name	TRANSFER_DATE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

ACCOUNT_CLASS_DESC

Attribute	Description	
Name	ACCOUNT_CLASS_DESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.45.3.CS-ModifyAcltr-Res-Full-MSG.xsd

MODIFYACLTR_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Master-Full
TRANSFER_ID
ACCOUNT_CLASS
CURRENT_BRANCH_CODE
TARGET_BRANCH_CODE
TRANSFER_DATE
CURRENT_BRANCH_NAME
TARGET_BRANCH_NAME
ACCOUNT_CLASS_DESC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYACLTR_FSFS_RES

Attribute	Description
Name	MODIFYACLTR_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Master-Full

Attribute		Description
------------------	--	--------------------

Name	Master-Full
Datatype	
Description	

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	64

ACCOUNT_CLASS

Attribute	Description	
Name	ACCOUNT_CLASS	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	24

CURRENT_BRANCH_CODE

Attribute	Description	
Name	CURRENT_BRANCH_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	12

TARGET_BRANCH_CODE

Attribute	Description	
Name	TARGET_BRANCH_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	12

TRANSFER_DATE

Attribute	Description	
Name	TRANSFER_DATE	
Datatype	String	
Description		

CURRENT_BRANCH_NAME

Attribute	Description	
Name	CURRENT_BRANCH_NAME	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TARGET_BRANCH_NAME

Attribute	Description	
Name	TARGET_BRANCH_NAME	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

ACCOUNT_CLASS_DESC

Attribute	Description	
Name	ACCOUNT_CLASS_DESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		

Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.45.4.CS-ModifyAcltr-Res-PK-MSG.xsd

MODIFYACLTR_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-PK

TRANSFER_ID

Master-IO

TRANSFER_ID

ACCOUNT_CLASS

TARGET_BRANCH_CODE

TRANSFER_DATE

ACCOUNT_CLASS_DESC

MAKER

MAKERSTAMP

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYACLTR_IOPK_RES

Attribute	Description
Name	MODIFYACLTR_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-PK

Attribute	Description
Name	Master-PK
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>64</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	64
Restrictions	Description				
maxLength	64				

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>64</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	64
Restrictions	Description				
maxLength	64				

ACCOUNT_CLASS

Attribute	Description
-----------	-------------

Name	ACCOUNT_CLASS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	24

TARGET_BRANCH_CODE

Attribute	Description	
Name	TARGET_BRANCH_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

TRANSFER_DATE

Attribute	Description	
Name	TRANSFER_DATE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

ACCOUNT_CLASS_DESC

Attribute	Description	
Name	ACCOUNT_CLASS_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.46.ModifyActrp

2.46.1.CS-ModifyActrp-Req-Full-MSG.xsd

MODIFYACTRP_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM
NAME
VALUE
FCUBS_BODY
Cstm-Branch-Trfr-Param-Full
BRANCH_CODE
TRN_CODE
TRANSFER_GL
PROCESS_MODE
MAX_NO_OF_PROCESS
COMMIT_FREQUENCY
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT

MODIFYACTRP_FSFS_REQ

Attribute	Description
Name	MODIFYACTRP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cstm-Branch-Trfr-Param-Full

Attribute	Description
Name	Cstm-Branch-Trfr-Param-Full
Datatype	
Description	

BRANCH_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TRN_CODE

Attribute	Description				
Name	TRN_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TRANSFER_GL

Attribute	Description				
Name	TRANSFER_GL				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

PROCESS_MODE

Attribute	Description	
Name	PROCESS_MODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	S,J

MAX_NO_OF_PROCESS

Attribute	Description	
Name	MAX_NO_OF_PROCESS	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

COMMIT_FREQUENCY

Attribute	Description	
Name	COMMIT_FREQUENCY	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute		Description	
Name	MAKERSTAMP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

CHECKER

Attribute		Description	
Name	CHECKER		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	12	

CHECKERSTAMP

Attribute		Description	
Name	CHECKERSTAMP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

MODNO

Attribute		Description	
Name	MODNO		
Datatype	Decimal		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	totalDigits	4	

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

2.46.2. CS-ModifyActrp-Req-IO-MSG.xsd

MODIFYACTRP_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cstm-Branch-Trfr-Param-IO

BRANCH_CODE

TRN_CODE

TRANSFER_GL

PROCESS_MODE

MAX_NO_OF_PROCESS

COMMIT_FREQUENCY

MAKER

MAKERSTAMP

MODIFYACTRP_IOPK_REQ

Attribute	Description
Name	MODIFYACTRP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description
Name	USERID

Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cstm-Branch-Trfr-Param-IO

Attribute	Description
Name	Cstm-Branch-Trfr-Param-IO
Datatype	
Description	

BRANCH_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TRN_CODE

Attribute	Description				
Name	TRN_CODE				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TRANSFER_GL

Attribute	Description				
Name	TRANSFER_GL				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

PROCESS_MODE

Attribute	Description
-----------	-------------

Name	PROCESS_MODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	S,J

MAX_NO_OF_PROCESS

Attribute	Description	
Name	MAX_NO_OF_PROCESS	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

COMMIT_FREQUENCY

Attribute	Description	
Name	COMMIT_FREQUENCY	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description
------------------	--------------------

Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

2.46.3.CS-ModifyActrp-Res-Full-MSG.xsd

MODIFYACTRP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cstm-Branch-Trfr-Param-Full

BRANCH_CODE

TRN_CODE

TRANSFER_GL

PROCESS_MODE

MAX_NO_OF_PROCESS

COMMIT_FREQUENCY

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYACTRP_FSFS_RES

Attribute	Description
Name	MODIFYACTRP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within EL EXCLUDE UBS. In

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cstm-Branch-Trfr-Param-Full

Attribute	Description
Name	Cstm-Branch-Trfr-Param-Full
Datatype	
Description	

BRANCH_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TRN_CODE

Attribute	Description				
Name	TRN_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TRANSFER_GL

Attribute	Description				
Name	TRANSFER_GL				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

PROCESS_MODE

Attribute	Description	
Name	PROCESS_MODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	S,J

MAX_NO_OF_PROCESS

Attribute	Description	
Name	MAX_NO_OF_PROCESS	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

COMMIT_FREQUENCY

Attribute	Description	
Name	COMMIT_FREQUENCY	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute		Description	
Name	MAKERSTAMP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

CHECKER

Attribute		Description	
Name	CHECKER		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	12	

CHECKERSTAMP

Attribute		Description	
Name	CHECKERSTAMP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

MODNO

Attribute		Description	
Name	MODNO		
Datatype	Decimal		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	totalDigits	4	

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.46.4.CS-ModifyActrp-Res-PK-MSG.xsd

MODIFYACTRP_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cstm-Branch-Trfr-Param-PK
BRANCH_CODE
Cstm-Branch-Trfr-Param-IO
BRANCH_CODE
TRN_CODE
TRANSFER_GL
PROCESS_MODE
MAX_NO_OF_PROCESS
COMMIT_FREQUENCY
MAKER
MAKERSTAMP
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING

WCODE

WDESC

MODIFYACTRP_IOPK_RES

Attribute	Description
Name	MODIFYACTRP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute			
		Attribute	Description
		minOccurs	0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute			
		Attribute	Description
		minOccurs	0
		maxOccurs	unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Cstm-Branch-Trfr-Param-PK

Attribute		Description	
Name		Cstm-Branch-Trfr-Param-PK	
Datatype			
Description			

BRANCH_CODE

Attribute		Description	
Name		BRANCH_CODE	
Datatype		String	
Description			
Restrictions			
		Restrictions	Description
		maxLength	3

Cstm-Branch-Trfr-Param-IO

Attribute	Description
Name	Cstm-Branch-Trfr-Param-IO
Datatype	
Description	

BRANCH_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TRN_CODE

Attribute	Description				
Name	TRN_CODE				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TRANSFER_GL

Attribute	Description				
Name	TRANSFER_GL				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

PROCESS_MODE

Attribute	Description				
Name	PROCESS_MODE				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	enumeration	S,J

MAX_NO_OF_PROCESS

Attribute	Description	
Name	MAX_NO_OF_PROCESS	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

COMMIT_FREQUENCY

Attribute	Description	
Name	COMMIT_FREQUENCY	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		

Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.47.ModifyDeveloper

2.47.1.CS-ModifyDeveloper-Req-Full-MSG.xsd

MODIFYDEVELOPER_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME
VALUE
FCUBS_BODY
Developer-Full
WEBSITE
DEVELOPCODE
ADDRESS
DEVELOPERNAME
ADDRESS4
COUNTRY
EMAILID
ZIP
ADDRESS2
ADDRESS3
COUNTRY_NAME
TELEPHONE
FAX
MOBILE
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Developer-Projects
PROJECTNAME
PROJECTDESC

MODIFYDEVELOPER_FSFS_REQ

Attribute	Description
Name	MODIFYDEVELOPER_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Developer-Full

Attribute	Description
Name	Developer-Full
Datatype	
Description	

WEBSITE

Attribute	Description	
Name	WEBSITE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

DEVELOPCODE

Attribute	Description	
Name	DEVELOPCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	9

ADDRESS

Attribute	Description	
Name	ADDRESS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

DEVELOPERNAME

Attribute	Description	
Name	DEVELOPERNAME	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

ADDRESS4

Attribute	Description	
Name	ADDRESS4	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

COUNTRY

Attribute	Description	
Name	COUNTRY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

EMAILID

Attribute	Description	
Name	EMAILID	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

ZIP

Attribute	Description	
Name	ZIP	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

ADDRESS2

Attribute	Description	
Name	ADDRESS2	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

ADDRESS3

Attribute	Description	
Name	ADDRESS3	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

COUNTRY_NAME

Attribute	Description	
Name	COUNTRY_NAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TELEPHONE

Attribute	Description	
Name	TELEPHONE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

FAX

Attribute	Description	
Name	FAX	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

MOBILE

Attribute	Description	
Name	MOBILE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Developer-Projects

Attribute	Description	
Name	Developer-Projects	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

PROJECTNAME

Attribute	Description	
Name	PROJECTNAME	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

PROJECTDESC

Attribute	Description	
Name	PROJECTDESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

2.47.2.CS-ModifyDeveloper-Req-IO-MSG.xsd

MODIFYDEVELOPER_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Developer-IO

WEBSITE

DEVELOPCODE

ADDRESS

DEVELOPERNAME

ADDRESS4

COUNTRY

EMAILID

ZIP

ADDRESS2

ADDRESS3

COUNTRY_NAME

TELEPHONE

FAX

MOBILE

MAKER

MAKERSTAMP

MODIFYDEVELOPER_IOPK_REQ

Attribute	Description
Name	MODIFYDEVELOPER_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
------------------	--------------------

Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Developer-IO

Attribute	Description
Name	Developer-IO
Datatype	
Description	

WEBSITE

Attribute	Description				
Name	WEBSITE				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

DEVELOPCODE

Attribute	Description				
Name	DEVELOPCODE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

ADDRESS

Attribute	Description
Name	ADDRESS
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

DEVELOPERNAME

Attribute	Description	
Name	DEVELOPERNAME	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

ADDRESS4

Attribute	Description	
Name	ADDRESS4	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

COUNTRY

Attribute	Description	
Name	COUNTRY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

EMAILID

Attribute	Description	
Name	EMAILID	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

ZIP

Attribute	Description	
Name	ZIP	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

ADDRESS2

Attribute	Description	
Name	ADDRESS2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

ADDRESS3

Attribute	Description	
Name	ADDRESS3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

COUNTRY_NAME

Attribute	Description	
Name	COUNTRY_NAME	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TELEPHONE

Attribute	Description	
Name	TELEPHONE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

FAX

Attribute	Description	
Name	FAX	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

MOBILE

Attribute	Description	
Name	MOBILE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

2.47.3.CS-ModifyDeveloper-Res-Full-MSG.xsd

MODIFYDEVELOPER_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Developer-Full

WEBSITE

DEVELOPCODE

ADDRESS

DEVELOPERNAME

ADDRESS4

COUNTRY

EMAILID

ZIP

ADDRESS2

ADDRESS3

COUNTRY_NAME

TELEPHONE

FAX

MOBILE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Developer-Projects

PROJECTNAME

PROJECTDESC

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYDEVELOPER_FSFS_RES

Attribute	Description
Name	MODIFYDEVELOPER_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Developer-Full

Attribute	Description
Name	Developer-Full
Datatype	
Description	

WEBSITE

Attribute	Description
------------------	--------------------

Name	WEBSITE	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	35
	Description	

DEVELOPCODE

Attribute	Description	
Name	DEVELOPCODE	
Datatype	String	
Description		
Restrictions	Restrictions	
	maxLength	9
	Description	

ADDRESS

Attribute	Description	
Name	ADDRESS	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	100
	Description	

DEVELOPERNAME

Attribute	Description	
Name	DEVELOPERNAME	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	35
	Description	

ADDRESS4

Attribute	Description	
Name	ADDRESS4	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

COUNTRY

Attribute	Description	
Name	COUNTRY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

EMAILID

Attribute	Description	
Name	EMAILID	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

ZIP

Attribute	Description	
Name	ZIP	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

ADDRESS2

Attribute	Description	
Name	ADDRESS2	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

ADDRESS3

Attribute	Description	
Name	ADDRESS3	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

COUNTRY_NAME

Attribute	Description	
Name	COUNTRY_NAME	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TELEPHONE

Attribute	Description	
Name	TELEPHONE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

FAX

Attribute	Description	
Name	FAX	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

MOBILE

Attribute	Description	
Name	MOBILE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Developer-Projects

Attribute	Description	
Name	Developer-Projects	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

PROJECTNAME

Attribute	Description	
Name	PROJECTNAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

PROJECTDESC

Attribute	Description	
Name	PROJECTDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.47.4.CS-ModifyDeveloper-Res-PK-MSG.xsd

MODIFYDEVELOPER_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Developer-PK

DEVELOPCODE

Developer-IO

WEBSITE

DEVELOPCODE

ADDRESS

DEVELOPERNAME

ADDRESS4

COUNTRY

EMAILID

ZIP

ADDRESS2

ADDRESS3

COUNTRY_NAME

TELEPHONE

FAX

MOBILE

MAKER

MAKERSTAMP

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYDEVELOPER_IOPK_RES

Attribute	Description
Name	MODIFYDEVELOPER_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Developer-PK

Attribute	Description
Name	Developer-PK
Datatype	
Description	

DEVELOPCODE

Attribute	Description				
Name	DEVELOPCODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

Developer-IO

Attribute	Description
Name	Developer-IO
Datatype	
Description	

WEBSITE

Attribute	Description				
Name	WEBSITE				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

DEVELOPCODE

Attribute	Description				
Name	DEVELOPCODE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

ADDRESS

Attribute	Description				
Name	ADDRESS				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>100</td></tr></tbody></table>	Restrictions	Description	maxLength	100
	Restrictions	Description			
maxLength	100				

DEVELOPERNAME

Attribute	Description				
Name	DEVELOPERNAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
	Restrictions	Description			
maxLength	35				

ADDRESS4

Attribute	Description				
Name	ADDRESS4				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>100</td></tr></tbody></table>	Restrictions	Description	maxLength	100
	Restrictions	Description			
maxLength	100				

COUNTRY

Attribute	Description
Name	COUNTRY

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

EMAILID

Attribute	Description	
Name	EMAILID	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

ZIP

Attribute	Description	
Name	ZIP	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

ADDRESS2

Attribute	Description	
Name	ADDRESS2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

ADDRESS3

Attribute	Description	
Name	ADDRESS3	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

COUNTRY_NAME

Attribute	Description	
Name	COUNTRY_NAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TELEPHONE

Attribute	Description	
Name	TELEPHONE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

FAX

Attribute	Description	
Name	FAX	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

MOBILE

Attribute	Description	
Name	MOBILE	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.48.ModifyProject

2.48.1.CS-ModifyProject-Req-Full-MSG.xsd

[MODIFYPROJECT_FSFS_REQ](#)

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Developer-Projects-Full

DEVELOPCODE

PROJECTNAME

PROJECTDESC

ADDRESS

PRJADDR2

PRJADDR3

STATUS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Dev-Prj-Dtls

UNITID

UNITHOLDERNAME

UDFDETAILS

FLDNAM

FLDVAL

MODIFYPROJECT_FSFS_REQ

Attribute	Description
Name	MODIFYPROJECT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Developer-Projects-Full

Attribute		Description
------------------	--	--------------------

Name	Developer-Projects-Full
Datatype	
Description	

DEVELOPCODE

Attribute	Description	
Name	DEVELOPCODE	
Datatype	String	
Description		
Restrictions	Restrictions	
	Description	
	maxLength	9

PROJECTNAME

Attribute	Description	
Name	PROJECTNAME	
Datatype	String	
Description		
Restrictions	Restrictions	
	Description	
	maxLength	35

PROJECTDESC

Attribute	Description	
Name	PROJECTDESC	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	105

ADDRESS

Attribute	Description	
Name	ADDRESS	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	100

PRJADDR2

Attribute	Description	
Name	PRJADDR2	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

PRJADDR3

Attribute	Description	
Name	PRJADDR3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Dev-Prj-Dtls

Attribute	Description	
Name	Dev-Prj-Dtls	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

UNITID

Attribute	Description	
Name	UNITID	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9

UNITHOLDERNAME

Attribute	Description	
Name	UNITHOLDERNAME	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
Restrictions	Restrictions	Description
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
Restrictions	Restrictions	Description
	minLength	0

2.48.2.CS-ModifyProject-Req-IO-MSG.xsd

MODIFYPROJECT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Developer-Projects-IO
DEVELOPCODE
PROJECTNAME
PROJECTDESC
ADDRESS
PRJADDR2
PRJADDR3
STATUS
MAKER
MAKERSTAMP
Dev-Prj-Dtls
UNITID
UNITHOLDERNAME
UDFDETAILS

FLDNAM

FLDVAL

MODIFYPROJECT_IOPK_REQ

Attribute	Description
Name	MODIFYPROJECT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*
	Description	

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*
	Description	

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	enumeration	SUCCESS,WARNING,FAILURE
	Description	

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*
	Description	

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0
	maxOccurs		unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Developer-Projects-IO

Attribute		Description	
Name		Developer-Projects-IO	
Datatype			
Description			

DEVELOPCODE

Attribute		Description	
Name		DEVELOPCODE	
Datatype		String	
Description			
Restrictions	Restrictions		Description
	maxLength		9

PROJECTNAME

Attribute	Description	
Name	PROJECTNAME	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

PROJECTDESC

Attribute	Description	
Name	PROJECTDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

ADDRESS

Attribute	Description	
Name	ADDRESS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

PRJADDR2

Attribute	Description	
Name	PRJADDR2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

PRJADDR3

Attribute	Description	
Name	PRJADDR3	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

Dev-Prj-Dtls

Attribute	Description
Name	Dev-Prj-Dtls

Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

UNITID

Attribute	Description				
Name	UNITID				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

UNITHOLDERNAME

Attribute	Description				
Name	UNITHOLDERNAME				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

FLDNAM

Attribute	Description						
Name	FLDNAM						
Datatype	String						
Description	Indicates Field Name						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	105	minLength	1
Restrictions	Description						
maxLength	105						
minLength	1						

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.48.3.CS-ModifyProject-Res-Full-MSG.xsd

MODIFYPROJECT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Developer-Projects-Full

DEVELOPCODE

PROJECTNAME

PROJECTDESC

ADDRESS

PRJADDR2

PRJADDR3

STATUS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Dev-Prj-Dtls

UNITID

UNITHOLDERNAME

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYPROJECT_FSFS_RES

Attribute	Description
-----------	-------------

Name	MODIFYPROJECT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	
	Description	
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	
	Description	
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	

Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	

Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Developer-Projects-Full

Attribute	Description	
Name	Developer-Projects-Full	
Datatype		
Description		

DEVELOPCODE

Attribute	Description	
Name	DEVELOPCODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

PROJECTNAME

Attribute	Description	
Name	PROJECTNAME	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

PROJECTDESC

Attribute	Description	
Name	PROJECTDESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

ADDRESS

Attribute	Description	
Name	ADDRESS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

PRJADDR2

Attribute	Description	
Name	PRJADDR2	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

PRJADDR3

Attribute	Description	
Name	PRJADDR3	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	100

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Attribute	Description	
Name	Dev-Prj-Dtls	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

UNITID

Attribute	Description	
Name	UNITID	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9

UNITHOLDERNAME

Attribute	Description	
Name	UNITHOLDERNAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.48.4.CS-ModifyProject-Res-PK-MSG.xsd

MODIFYPROJECT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Developer-Projects-PK

DEVELOPCODE

PROJECTNAME

Developer-Projects-IO

DEVELOPCODE

PROJECTNAME

PROJECTDESC

ADDRESS

PRJADDR2

PRJADDR3

STATUS

MAKER

MAKERSTAMP

Dev-Prj-Dtls

UNITID

UNITHOLDERNAME

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYPROJECT_IOPK_RES

Attribute	Description
Name	MODIFYPROJECT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Developer-Projects-PK

Attribute	Description
Name	Developer-Projects-PK
Datatype	
Description	

DEVELOPCODE

Attribute	Description
------------------	--------------------

Name	DEVELOPCODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

PROJECTNAME

Attribute	Description	
Name	PROJECTNAME	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

Developer-Projects-IO

Attribute	Description	
Name	Developer-Projects-IO	
Datatype		
Description		

DEVELOPCODE

Attribute	Description	
Name	DEVELOPCODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

PROJECTNAME

Attribute	Description	
Name	PROJECTNAME	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

PROJECTDESC

Attribute	Description	
Name	PROJECTDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	105

ADDRESS

Attribute	Description	
Name	ADDRESS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

PRJADDR2

Attribute	Description	
Name	PRJADDR2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

PRJADDR3

Attribute	Description	
Name	PRJADDR3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

Dev-Prj-Dtls

Attribute	Description	
Name	Dev-Prj-Dtls	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

UNITID

Attribute	Description	
Name	UNITID	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	9

UNITHOLDERNAME

Attribute	Description	
Name	UNITHOLDERNAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

Attribute		Description	
Name	FCUBS_ERROR_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

ERROR

Attribute		Description	
Name	ERROR		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

ECODE

Attribute		Description	
Name	ECODE		
Datatype	String		
Description			

EDESC

Attribute		Description	
Name	EDESC		
Datatype	String		
Description			

FCUBS_WARNING_RESP

Attribute		Description	
Name	FCUBS_WARNING_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

WARNING

Attribute		Description	
Name	WARNING		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.49.QueryAcctr

2.49.1.CS-QueryAcctr-Req-IO-MSG.xsd

QUERYACCTR_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

QUERYACCTR_IOFS_REQ

Attribute	Description
Name	QUERYACCTR_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

FCUBS_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description			

Master-IO

Attribute		Description	
Name	Master-IO		
Datatype			
Description			

TRANSFER_ID

Attribute		Description	
Name	TRANSFER_ID		
Datatype	String		
Description			
Restrictions	Restrictions		Description
	maxLength	16	

QUERYACCTR_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-IO

TRANSFER_ID

Master-Full

TRANSFER_ID

CURRENT_BRANCH

TARGET_BRANCH_CODE

TRANSDT

TARGET_BRANCH_NAME

CURRENT_BRANCH_NAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Child

ACCOUNTNUMBER

AC_DESC

CUSTOMER_NUMBER

TXT_CUSTNAME

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYACCTR_IOFS_RES

Attribute	Description
Name	QUERYACCTR_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

CURRENT_BRANCH

Attribute	Description
-----------	-------------

Name	CURENT_BRANCH	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

TARGET_BRANCH_CODE

Attribute	Description	
Name	TARGET_BRANCH_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

TRANSDT

Attribute	Description	
Name	TRANSDT	
Datatype	String	
Description		

TARGET_BRANCH_NAME

Attribute	Description	
Name	TARGET_BRANCH_NAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

CURRENT_BRANCH_NAME

Attribute	Description	
Name	CURRENT_BRANCH_NAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description
Name	MODNO

Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Child

Attribute	Description	
Name	Child	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCOUNTNUMBER

Attribute	Description	
Name	ACCOUNTNUMBER	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	20

AC_DESC

Attribute	Description	
Name	AC_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

CUSTOMER_NUMBER

Attribute	Description	
Name	CUSTOMER_NUMBER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TXT_CUSTNAME

Attribute	Description	
Name	TXT_CUSTNAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
------------------	--------------------

Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.50.QueryAcltr

2.50.1.CS-QueryAcltr-Req-IO-MSG.xsd

QUERYACLTR_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Master-IO
TRANSFER_ID

QUERYACLTR_IOFS_REQ

Attribute	Description
Name	QUERYACLTR_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within EL EXCLUDE UBS. In

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>64</td></tr></tbody></table>	Restrictions	Description	maxLength	64
Restrictions	Description				
maxLength	64				

2.50.2.CS-QueryAcltr-Res-Full-MSG.xsd

QUERYACLTR_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Master-IO
TRANSFER_ID
Master-Full
TRANSFER_ID
ACCOUNT_CLASS
CURRENT_BRANCH_CODE
TARGET_BRANCH_CODE
TRANSFER_DATE
CURRENT_BRANCH_NAME
TARGET_BRANCH_NAME
ACCOUNT_CLASS_DESC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYACLTR_IOFS_RES

Attribute	Description
Name	QUERYACLTR_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Master-IO

Attribute		Description
------------------	--	--------------------

Name	Master-IO
Datatype	
Description	

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	64

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	64

ACCOUNT_CLASS

Attribute	Description	
Name	ACCOUNT_CLASS	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	24

CURRENT_BRANCH_CODE

Attribute	Description	
Name	CURRENT_BRANCH_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	12

TARGET_BRANCH_CODE

Attribute	Description
Name	TARGET_BRANCH_CODE
Datatype	String

Description		
Restrictions		
	Restrictions	Description
	maxLength	12

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	String
Description	

CURRENT_BRANCH_NAME

Attribute	Description	
Name	CURRENT_BRANCH_NAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TARGET_BRANCH_NAME

Attribute	Description	
Name	TARGET_BRANCH_NAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

ACCOUNT_CLASS_DESC

Attribute	Description	
Name	ACCOUNT_CLASS_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description
------------------	--------------------

Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description
------------------	--------------------

Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.51.QueryActrp

2.51.1.CS-QueryActrp-Req-IO-MSG.xsd

QUERYACTRP_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cstm-Branch-Trfr-Param-IO

BRANCH_CODE

QUERYACTRP_IOFS_REQ

Attribute	Description
Name	QUERYACTRP_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

MSGID

Attribute	Description					
Name	MSGID					
Datatype	String					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	String					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Cstm-Branch-Trfr-Param-IO
Datatype	
Description	

BRANCH_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

2.51.2.CS-QueryActrp-Res-Full-MSG.xsd

QUERYACTRP_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cstm-Branch-Trfr-Param-IO

BRANCH_CODE

Cstm-Branch-Trfr-Param-Full

BRANCH_CODE

TRN_CODE

TRANSFER_GL

PROCESS_MODE

MAX_NO_OF_PROCESS

COMMIT_FREQUENCY

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYACTRP_IOFS_RES

Attribute	Description
Name	QUERYACTRP_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	
-------------	--

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Cstm-Branch-Trfr-Param-IO

Attribute	Description
Name	Cstm-Branch-Trfr-Param-IO
Datatype	
Description	

BRANCH_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

Cstm-Branch-Trfr-Param-Full

Attribute	Description
Name	Cstm-Branch-Trfr-Param-Full
Datatype	
Description	

BRANCH_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TRN_CODE

Attribute	Description

Name	TRN_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

TRANSFER_GL

Attribute	Description	
Name	TRANSFER_GL	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

PROCESS_MODE

Attribute	Description	
Name	PROCESS_MODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	S,J

MAX_NO_OF_PROCESS

Attribute	Description	
Name	MAX_NO_OF_PROCESS	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

COMMIT_FREQUENCY

Attribute	Description	
Name	COMMIT_FREQUENCY	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String

Description	
-------------	--

2.52.QueryDeveloper

2.52.1.CS-QueryDeveloper-Req-IO-MSG.xsd

QUERYDEVELOPER_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Developer-IO

DEVELOPCODE

QUERYDEVELOPER_IOFS_REQ

Attribute	Description
Name	QUERYDEVELOPER_IOFS_REQ
Datatype	

Description	
-------------	--

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
-----------	-------------

Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	
	Description	
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	
	Description	
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	
	Description	
	minOccurs	0

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

SOURCE_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description	This is the user id in the Source system who is performing the action.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Developer-IO

Attribute	Description
Name	Developer-IO
Datatype	
Description	

DEVELOPCODE

Attribute	Description	
Name	DEVELOPCODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	9

2.52.2.CS-QueryDeveloper-Res-Full-MSG.xsd

QUERYDEVELOPER_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Developer-IO
DEVELOPCODE
Developer-Full
WEBSITE
DEVELOPCODE
ADDRESS
DEVELOPERNAME
ADDRESS4
COUNTRY
EMAILID
ZIP
ADDRESS2
ADDRESS3
COUNTRY_NAME
TELEPHONE
FAX

MOBILE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Developer-Projects

PROJECTNAME

PROJECTDESC

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYDEVELOPER_IOFS_RES

Attribute	Description
Name	QUERYDEVELOPER_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Developer-IO

Attribute	Description
Name	Developer-IO
Datatype	
Description	

DEVELOPCODE

Attribute	Description				
Name	DEVELOPCODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

Developer-Full

Attribute	Description
Name	Developer-Full
Datatype	
Description	

WEBSITE

Attribute	Description				
Name	WEBSITE				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

DEVELOPCODE

Attribute	Description	
Name	DEVELOPCODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

ADDRESS

Attribute	Description	
Name	ADDRESS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

DEVELOPERNAME

Attribute	Description	
Name	DEVELOPERNAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

ADDRESS4

Attribute	Description	
Name	ADDRESS4	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

COUNTRY

Attribute	Description	
Name	COUNTRY	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

EMAILID

Attribute	Description	
Name	EMAILID	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

ZIP

Attribute	Description	
Name	ZIP	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

ADDRESS2

Attribute	Description	
Name	ADDRESS2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

ADDRESS3

Attribute	Description	
Name	ADDRESS3	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

COUNTRY_NAME

Attribute	Description	
Name	COUNTRY_NAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TELEPHONE

Attribute	Description	
Name	TELEPHONE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

FAX

Attribute	Description	
Name	FAX	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

MOBILE

Attribute	Description	
Name	MOBILE	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	30

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Developer-Projects

Attribute	Description	
Name	Developer-Projects	

Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

PROJECTNAME

Attribute	Description				
Name	PROJECTNAME				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

PROJECTDESC

Attribute	Description				
Name	PROJECTDESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

FCUBS_ERROR_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.53.QueryProject

2.53.1.CS-QueryProject-Req-IO-MSG.xsd

QUERYPROJECT_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Developer-Projects-IO
DEVELOPCODE
PROJECTNAME

QUERYPROJECT_IOFS_REQ

Attribute	Description
Name	QUERYPROJECT_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Developer-Projects-IO

Attribute	Description
Name	Developer-Projects-IO
Datatype	
Description	

DEVELOPCODE

Attribute	Description				
Name	DEVELOPCODE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

PROJECTNAME

Attribute	Description				
Name	PROJECTNAME				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

2.53.2.CS-QueryProject-Res-Full-MSG.xsd

QUERYPROJECT_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Developer-Projects-IO
DEVELOPCODE
PROJECTNAME
Developer-Projects-Full
DEVELOPCODE
PROJECTNAME
PROJECTDESC
ADDRESS
PRJADDR2
PRJADDR3
STATUS
MAKER
MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Dev-Prj-Dtls

UNITID

UNITHOLDERNAME

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYPROJECT_IOFS_RES

Attribute	Description
Name	QUERYPROJECT_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Developer-Projects-IO

Attribute	Description
Name	Developer-Projects-IO
Datatype	
Description	

DEVELOPCODE

Attribute	Description				
Name	DEVELOPCODE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

PROJECTNAME

Attribute	Description				
Name	PROJECTNAME				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

Developer-Projects-Full

Attribute	Description
Name	Developer-Projects-Full
Datatype	
Description	

DEVELOPCODE

Attribute	Description
-----------	-------------

Name	DEVELOPCODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

PROJECTNAME

Attribute	Description	
Name	PROJECTNAME	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	35

PROJECTDESC

Attribute	Description	
Name	PROJECTDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

ADDRESS

Attribute	Description	
Name	ADDRESS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

PRJADDR2

Attribute	Description	
Name	PRJADDR2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	100

PRJADDR3

Attribute	Description	
Name	PRJADDR3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	100

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Dev-Prj-Dtls

Attribute	Description	
Name	Dev-Prj-Dtls	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

UNITID

Attribute	Description	
Name	UNITID	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9

UNITHOLDERNAME

Attribute	Description	
Name	UNITHOLDERNAME	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	105

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description
------------------	--------------------

Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

REOPENACCTR_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-Full

TRANSFER_ID

CURRENT_BRANCH

TARGET_BRANCH_CODE

TRANSDT

TARGET_BRANCH_NAME

CURRENT_BRANCH_NAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Child

ACCOUNTNUMBER

AC_DESC

CUSTOMER_NUMBER

TXT_CUSTNAME

UDFDETAILS

FLDNAM

FLDVAL

REOPENACCTR_FSFS_REQ

Attribute	Description
Name	REOPENACCTR_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

MSGID

Attribute	Description					
Name	MSGID					
Datatype	String					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	String					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
Restrictions	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Master-Full
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

CURRENT_BRANCH

Attribute	Description				
Name	CURRENT_BRANCH				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TARGET_BRANCH_CODE

Attribute	Description				
Name	TARGET_BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	String
Description	

TARGET_BRANCH_NAME

Attribute	Description				
Name	TARGET_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>255</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

CURRENT_BRANCH_NAME

Attribute	Description	
Name	CURRENT_BRANCH_NAME	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute		Description	
Name	CHECKERSTAMP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

MODNO

Attribute		Description	
Name	MODNO		
Datatype	Decimal		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	totalDigits	4	

TXNSTAT

Attribute		Description	
Name	TXNSTAT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1	

AUTHSTAT

Attribute		Description	
Name	AUTHSTAT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1	

Child

Attribute	Description	
Name	Child	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCOUNTNUMBER

Attribute	Description	
Name	ACCOUNTNUMBER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	20

AC_DESC

Attribute	Description	
Name	AC_DESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

CUSTOMER_NUMBER

Attribute	Description	
Name	CUSTOMER_NUMBER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TXT_CUSTNAME

Attribute	Description	
Name	TXT_CUSTNAME	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.54.2.CS-ReopenAcctr-Req-IO-MSG.xsd

REOPENACCTR_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Master-IO
TRANSFER_ID
MAKER
MAKERSTAMP
MODNO

REOPENACCTR_IOPK_REQ

Attribute	Description
Name	REOPENACCTR_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-IO

Attribute	Description
Name	Master-IO
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

2.54.3.CS-ReopenAcctr-Res-Full-MSG.xsd

REOPENACCTR_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-Full

TRANSFER_ID

CURRENT_BRANCH

TARGET_BRANCH_CODE

TRANSDT

TARGET_BRANCH_NAME

CURRENT_BRANCH_NAME

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Child

ACCOUNTNUMBER

AC_DESC

CUSTOMER_NUMBER

TXT_CUSTNAME

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

REOPENACCTR_FSFS_RES

Attribute	Description
Name	REOPENACCTR_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*
	Description	

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*
	Description	

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	enumeration	SUCCESS,WARNING,FAILURE
	Description	

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*
	Description	

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0
	maxOccurs		unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Master-Full

Attribute		Description	
Name		Master-Full	
Datatype			
Description			

TRANSFER_ID

Attribute		Description	
Name		TRANSFER_ID	
Datatype		String	
Description			
Restrictions	Restrictions		Description
	maxLength		16

CURRENT_BRANCH

Attribute	Description				
Name	CURRENT_BRANCH				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

TARGET_BRANCH_CODE

Attribute	Description				
Name	TARGET_BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	String
Description	

TARGET_BRANCH_NAME

Attribute	Description				
Name	TARGET_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
	Restrictions	Description			
maxLength	255				

CURRENT_BRANCH_NAME

Attribute	Description				
Name	CURRENT_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
	Restrictions	Description			
maxLength	255				

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Child

Attribute	Description	
Name	Child	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCOUNTNUMBER

Attribute	Description	
Name	ACCOUNTNUMBER	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

AC_DESC

Attribute	Description	
Name	AC_DESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

CUSTOMER_NUMBER

Attribute	Description	
Name	CUSTOMER_NUMBER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TXT_CUSTNAME

Attribute	Description	
Name	TXT_CUSTNAME	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		

Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
------------------	--------------------

Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.54.4.CS-ReopenAcctr-Res-PK-MSG.xsd

REOPENACCTR_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Master-PK
TRANSFER_ID
Master-IO
TRANSFER_ID
MAKER
MAKERSTAMP
MODNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE

REOPENACCTR_IOPK_RES

Attribute	Description
Name	REOPENACCTR_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute		Description	
Name	SOURCE_USERID		
Datatype	String		
Description	This is the user id in the Source system who is performing the action.		
Attribute	Attribute		Description
	minOccurs	0	

DESTINATION

Attribute		Description	
Name	DESTINATION		
Datatype	String		
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute		Description	
Name	MULTITRIPID		
Datatype	String		
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute		Description	
Name	FUNCTIONID		
Datatype	String		
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.		
Attribute	Attribute		Description
	minOccurs	0	

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-PK

Attribute	Description
Name	Master-PK
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

Master-IO

Attribute	Description
-----------	-------------

Name	Master-IO
Datatype	
Description	

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	16

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute		Description	
Name	FCUBS_ERROR_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

ERROR

Attribute		Description	
Name	ERROR		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

ECODE

Attribute		Description	
Name	ECODE		
Datatype	String		
Description			

EDESC

Attribute		Description	
Name	EDESC		
Datatype	String		
Description			

FCUBS_WARNING_RESP

Attribute		Description	
Name	FCUBS_WARNING_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

WARNING

Attribute		Description	
Name	WARNING		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.55.ReopenAcltr

2.55.1.CS-ReopenAcltr-Req-Full-MSG.xsd

REOPENACLTR_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-Full

TRANSFER_ID

ACCOUNT_CLASS

CURRENT_BRANCH_CODE

TARGET_BRANCH_CODE

TRANSFER_DATE

CURRENT_BRANCH_NAME

TARGET_BRANCH_NAME

ACCOUNT_CLASS_DESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

REOPENACLTR_FSFS_REQ

Attribute	Description
Name	REOPENACLTR_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
pattern	[A-Z_0-9]*	

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>64</td></tr></tbody></table>	Restrictions	Description	maxLength	64
Restrictions	Description				
maxLength	64				

ACCOUNT_CLASS

Attribute	Description				
Name	ACCOUNT_CLASS				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>24</td></tr></tbody></table>	Restrictions	Description	maxLength	24
Restrictions	Description				
maxLength	24				

CURRENT_BRANCH_CODE

Attribute	Description				
Name	CURRENT_BRANCH_CODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

TARGET_BRANCH_CODE

Attribute	Description				
Name	TARGET_BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	String
Description	

CURRENT_BRANCH_NAME

Attribute	Description				
Name	CURRENT_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
	Restrictions	Description			
maxLength	255				

TARGET_BRANCH_NAME

Attribute	Description				
Name	TARGET_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
	Restrictions	Description			
maxLength	255				

ACCOUNT_CLASS_DESC

Attribute	Description				
Name	ACCOUNT_CLASS_DESC				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.55.2. CS-ReopenAcltr-Req-IO-MSG.xsd

REOPENACLTR_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-IO

TRANSFER_ID

MAKER

MAKERSTAMP

MODNO

REOPENACLTR_IOPK_REQ

Attribute	Description
Name	REOPENACLTR_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Master-IO

Attribute	Description
------------------	--------------------

Name	Master-IO
Datatype	
Description	

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	64

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

REOPENACLTR_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-Full

TRANSFER_ID

ACCOUNT_CLASS

CURRENT_BRANCH_CODE

TARGET_BRANCH_CODE

TRANSFER_DATE

CURRENT_BRANCH_NAME

TARGET_BRANCH_NAME

ACCOUNT_CLASS_DESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

REOPENACLTR_FSFS_RES

Attribute	Description
Name	REOPENACLTR_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Master-Full

Attribute	Description
Name	Master-Full
Datatype	
Description	

TRANSFER_ID

Attribute	Description				
Name	TRANSFER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>64</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	64
Restrictions	Description				
maxLength	64				

ACCOUNT_CLASS

Attribute	Description				
Name	ACCOUNT_CLASS				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>24</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	24
Restrictions	Description				
maxLength	24				

CURRENT_BRANCH_CODE

Attribute	Description				
Name	CURRENT_BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

TARGET_BRANCH_CODE

Attribute	Description				
Name	TARGET_BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

TRANSFER_DATE

Attribute	Description
Name	TRANSFER_DATE
Datatype	String
Description	

CURRENT_BRANCH_NAME

Attribute	Description				
Name	CURRENT_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
	Restrictions	Description			
maxLength	255				

TARGET_BRANCH_NAME

Attribute	Description				
Name	TARGET_BRANCH_NAME				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
	Restrictions	Description			
maxLength	255				

ACCOUNT_CLASS_DESC

Attribute	Description				
Name	ACCOUNT_CLASS_DESC				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	255

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.55.4.CS-ReopenAcltr-Res-PK-MSG.xsd

REOPENACLTR_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Master-PK

TRANSFER_ID

Master-IO

TRANSFER_ID

MAKER

MAKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

REOPENACLTR_IOPK_RES

Attribute	Description
-----------	-------------

Name	REOPENACLTR_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	
	Description	
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	
	Description	
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	

Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	

Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Master-PK

Attribute	Description	
Name	Master-PK	
Datatype		
Description		

TRANSFER_ID

Attribute	Description	
Name	TRANSFER_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	64

Master-IO

Attribute	Description	
Name	Master-IO	
Datatype		
Description		

TRANSFER_ID

Attribute	Description	

Name	TRANSFER_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	64

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		

Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.56.ReopenActrp

2.56.1.CS-ReopenActrp-Req-Full-MSG.xsd

REOPENACTRP_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cstm-Branch-Trfr-Param-Full

BRANCH_CODE

TRN_CODE

TRANSFER_GL

PROCESS_MODE

MAX_NO_OF_PROCESS

COMMIT_FREQUENCY

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

REOPENACTRP_FSFS_REQ

Attribute	Description
Name	REOPENACTRP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Cstm-Branch-Trfr-Param-Full

Attribute		Description
------------------	--	--------------------

Name	Cstm-Branch-Trfr-Param-Full
Datatype	
Description	

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

TRN_CODE

Attribute	Description	
Name	TRN_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

TRANSFER_GL

Attribute	Description	
Name	TRANSFER_GL	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

PROCESS_MODE

Attribute	Description	
Name	PROCESS_MODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	S,J

MAX_NO_OF_PROCESS

Attribute	Description
Name	MAX_NO_OF_PROCESS
Datatype	Decimal
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

COMMIT_FREQUENCY

Attribute	Description	
Name	COMMIT_FREQUENCY	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

2.56.2.CS-ReopenActrp-Req-IO-MSG.xsd

REOPENACTRP_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cstm-Branch-Trfr-Param-IO

BRANCH_CODE

MAKER

MAKERSTAMP

MODNO

REOPENACTRP_IOPK_REQ

Attribute	Description
Name	REOPENACTRP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

FCUBS_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description			

Cstm-Branch-Trfr-Param-IO

Attribute		Description	
Name	Cstm-Branch-Trfr-Param-IO		
Datatype			
Description			

BRANCH_CODE

Attribute		Description	
Name	BRANCH_CODE		
Datatype	String		
Description			
Restrictions	Restrictions		Description
	maxLength	3	

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

2.56.3.CS-ReopenActrp-Res-Full-MSG.xsd

REOPENACTRP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Cstm-Branch-Trfr-Param-Full
BRANCH_CODE
TRN_CODE
TRANSFER_GL
PROCESS_MODE
MAX_NO_OF_PROCESS
COMMIT_FREQUENCY
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
FCUBS_ERROR_RESP
ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

REOPENACTRP_FSFS_RES

Attribute	Description
Name	REOPENACTRP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Cstm-Branch-Trfr-Param-Full

Attribute	Description	
Name	Cstm-Branch-Trfr-Param-Full	
Datatype		
Description		

BRANCH_CODE

Attribute	Description	
------------------	--------------------	--

Name	BRANCH_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

TRN_CODE

Attribute	Description	
Name	TRN_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

TRANSFER_GL

Attribute	Description	
Name	TRANSFER_GL	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

PROCESS_MODE

Attribute	Description	
Name	PROCESS_MODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	S,J

MAX_NO_OF_PROCESS

Attribute	Description	
Name	MAX_NO_OF_PROCESS	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

COMMIT_FREQUENCY

Attribute	Description	
Name	COMMIT_FREQUENCY	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

FCUBS_ERROR_RESP

Attribute		Description	
Name	FCUBS_ERROR_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

ERROR

Attribute		Description	
Name	ERROR		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

ECODE

Attribute		Description	
Name	ECODE		
Datatype	String		
Description			

EDESC

Attribute		Description	
Name	EDESC		
Datatype	String		
Description			

FCUBS_WARNING_RESP

Attribute		Description	
Name	FCUBS_WARNING_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

WARNING

Attribute		Description	
Name	WARNING		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.56.4.CS-ReopenActrp-Res-PK-MSG.xsd

REOPENACTRP_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Cstm-Branch-Trfr-Param-PK

BRANCH_CODE

Cstm-Branch-Trfr-Param-IO

BRANCH_CODE

MAKER

MAKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

REOPENACTRP_IOPK_RES

Attribute	Description
Name	REOPENACTRP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

MSGID

Attribute	Description					
Name	MSGID					
Datatype	String					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	String					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Cstm-Branch-Trfr-Param-PK
Datatype	
Description	

BRANCH_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

Cstm-Branch-Trfr-Param-IO

Attribute	Description
Name	Cstm-Branch-Trfr-Param-IO
Datatype	
Description	

BRANCH_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description
------------------	--------------------

Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	
	Description	
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.57.AuthorizeUserHoliday

2.57.1.SM-AuthorizeUserHoliday-Req-Full-MSG.xsd

AUTHORIZEUSERHOLIDAY_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTIRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-User-Holiday-Full

BRANCH_CODE

USER_ID

LEAVE_FROM

LEAVE_TO

REMARKS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

AUTHORIZEUSERHOLIDAY_FSFS_REQ

Attribute	Description
Name	AUTHORIZEUSERHOLIDAY_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-User-Holiday-Full

Attribute	Description
Name	Smtbs-User-Holiday-Full
Datatype	
Description	

BRANCH_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

USER_ID

Attribute	Description				
Name	USER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

LEAVE_FROM

Attribute	Description
Name	LEAVE_FROM
Datatype	String
Description	

LEAVE_TO

Attribute	Description
Name	LEAVE_TO
Datatype	String
Description	

REMARKS

Attribute	Description				
Name	REMARKS				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>2000</td></tr></tbody></table>	Restrictions	Description	maxLength	2000
	Restrictions	Description			
maxLength	2000				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
	Restrictions	Description			
maxLength	35				

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

2.57.2.SM-AuthorizeUserHoliday-Req-IO-MSG.xsd

AUTHORIZEUSERHOLIDAY_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-User-Holiday-IO

USER_ID

LEAVE_FROM

LEAVE_TO

CHECKER

CHECKERSTAMP

MODNO

AUTHORIZEUSERHOLIDAY_IOPK_REQ

Attribute	Description
Name	AUTHORIZEUSERHOLIDAY_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field. 2234

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0
	maxOccurs		unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Smtbs-User-Holiday-IO

Attribute		Description	
Name		Smtbs-User-Holiday-IO	
Datatype			
Description			

USER_ID

Attribute		Description	
Name		USER_ID	
Datatype		String	
Description			
Restrictions	Restrictions		Description
	maxLength		12

LEAVE_FROM

Attribute	Description
Name	LEAVE_FROM
Datatype	String
Description	

LEAVE_TO

Attribute	Description
Name	LEAVE_TO
Datatype	String
Description	

CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

CHECKERSTAMP

Attribute	Description				
Name	CHECKERSTAMP				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
	Restrictions	Description			
maxLength	35				

MODNO

Attribute	Description				
Name	MODNO				
Datatype	Decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>4</td></tr></tbody></table>	Restrictions	Description	totalDigits	4
	Restrictions	Description			
totalDigits	4				

AUTHORIZEUSERHOLIDAY_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-User-Holiday-Full

BRANCH_CODE

USER_ID

LEAVE_FROM

LEAVE_TO

REMARKS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEUSERHOLIDAY_FSFS_RES

Attribute	Description
Name	AUTHORIZEUSERHOLIDAY_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Smtbs-User-Holiday-Full

Attribute		Description
------------------	--	--------------------

Name	Smtbs-User-Holiday-Full
Datatype	
Description	

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

USER_ID

Attribute	Description	
Name	USER_ID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12

LEAVE_FROM

Attribute	Description	
Name	LEAVE_FROM	
Datatype	String	
Description		

LEAVE_TO

Attribute	Description	
Name	LEAVE_TO	
Datatype	String	
Description		

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		

Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.57.4.SM-AuthorizeUserHoliday-Res-PK-MSG.xsd

AUTHORIZEUSERHOLIDAY_IOPK_RES

FCUBS_HEADER

SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Smtbs-User-Holiday-PK
USER_ID
LEAVE_FROM
LEAVE_TO
Smtbs-User-Holiday-IO
USER_ID
LEAVE_FROM
LEAVE_TO
CHECKER
CHECKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEUSERHOLIDAY_IOPK_RES

Attribute	Description
Name	AUTHORIZEUSERHOLIDAY_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Smtbs-User-Holiday-PK

Attribute	Description	
Name	Smtbs-User-Holiday-PK	
Datatype		
Description		

USER_ID

Attribute	Description				
Name	USER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

LEAVE_FROM

Attribute	Description
Name	LEAVE_FROM
Datatype	String
Description	

LEAVE_TO

Attribute	Description
Name	LEAVE_TO
Datatype	String
Description	

Smtbs-User-Holiday-IO

Attribute	Description
Name	Smtbs-User-Holiday-IO
Datatype	
Description	

USER_ID

Attribute	Description				
Name	USER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

LEAVE_FROM

Attribute	Description
Name	LEAVE_FROM
Datatype	String
Description	

LEAVE_TO

Attribute	Description
Name	LEAVE_TO
Datatype	String
Description	

CHECKER

Attribute	Description
-----------	-------------

Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.58.CreateUserHoliday

2.58.1.SM-CreateUserHoliday-Req-Full-MSG.xsd

CREATEUSERHOLIDAY_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-User-Holiday-Full

BRANCH_CODE

USER_ID

LEAVE_FROM

LEAVE_TO

REMARKS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

CREATEUSERHOLIDAY_FSFS_REQ

Attribute	Description
Name	CREATEUSERHOLIDAY_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field. 2263

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

ADDL

Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

FCUBS_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description			

Smtbs-User-Holiday-Full

Attribute		Description	
Name	Smtbs-User-Holiday-Full		
Datatype			
Description			

BRANCH_CODE

Attribute		Description	
Name	BRANCH_CODE		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	

Restrictions		
	Restrictions	Description
	maxLength	3

USER_ID

Attribute	Description	
Name	USER_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	12

LEAVE_FROM

Attribute	Description	
Name	LEAVE_FROM	
Datatype	String	
Description		

LEAVE_TO

Attribute	Description	
Name	LEAVE_TO	
Datatype	String	
Description		

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	2000

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute		Description	
Name	MAKERSTAMP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

CHECKER

Attribute		Description	
Name	CHECKER		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	12	

CHECKERSTAMP

Attribute		Description	
Name	CHECKERSTAMP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

MODNO

Attribute		Description	
Name	MODNO		
Datatype	Decimal		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	totalDigits	4	

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

2.58.2.SM-CreateUserHoliday-Req-IO-MSG.xsd

CREATEUSERHOLIDAY_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-User-Holiday-IO

USER_ID

LEAVE_FROM

LEAVE_TO

REMARKS

CREATEUSERHOLIDAY_IOPK_REQ

Attribute	Description
Name	CREATEUSERHOLIDAY_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description					
Name	SOURCE_OPERATION					
Datatype	String					
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

SOURCE_USERID

Attribute	Description					
Name	SOURCE_USERID					
Datatype	String					
Description	This is the user id in the Source system who is performing the action.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

DESTINATION

Attribute	Description					
Name	DESTINATION					
Datatype	String					
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

MULTITRIPID

Attribute	Description					
Name	MULTITRIPID					
Datatype	String					
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Smtbs-User-Holiday-IO

Attribute		Description
------------------	--	--------------------

Name	Smtbs-User-Holiday-IO
Datatype	
Description	

USER_ID

Attribute	Description	
Name	USER_ID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12

LEAVE_FROM

Attribute	Description
Name	LEAVE_FROM
Datatype	String
Description	

LEAVE_TO

Attribute	Description
Name	LEAVE_TO
Datatype	String
Description	

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

2.58.3.SM-CreateUserHoliday-Res-Full-MSG.xsd

CREATEUSERHOLIDAY_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Smtbs-User-Holiday-Full
BRANCH_CODE
USER_ID
LEAVE_FROM
LEAVE_TO
REMARKS
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
FCUBS_ERROR_RESP
ERROR
ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEUSERHOLIDAY_FSFS_RES

Attribute	Description
Name	CREATEUSERHOLIDAY_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*
	Description	

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*
	Description	

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	enumeration	SUCCESS,WARNING,FAILURE
	Description	

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*
	Description	

ADDL

Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

FCUBS_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description			

Smtbs-User-Holiday-Full

Attribute		Description	
Name	Smtbs-User-Holiday-Full		
Datatype			
Description			

BRANCH_CODE

Attribute		Description	
Name	BRANCH_CODE		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	

Restrictions		
	Restrictions	Description
	maxLength	3

USER_ID

Attribute	Description	
Name	USER_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	12

LEAVE_FROM

Attribute	Description	
Name	LEAVE_FROM	
Datatype	String	
Description		

LEAVE_TO

Attribute	Description	
Name	LEAVE_TO	
Datatype	String	
Description		

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	2000

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute		Description	
Name	MAKERSTAMP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

CHECKER

Attribute		Description	
Name	CHECKER		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	12	

CHECKERSTAMP

Attribute		Description	
Name	CHECKERSTAMP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

MODNO

Attribute		Description	
Name	MODNO		
Datatype	Decimal		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	totalDigits	4	

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.58.4.SM-CreateUserHoliday-Res-PK-MSG.xsd

CREATEUSERHOLIDAY_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Smtbs-User-Holiday-PK
USER_ID
LEAVE_FROM
LEAVE_TO
Smtbs-User-Holiday-IO
USER_ID
LEAVE_FROM
LEAVE_TO
REMARKS
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

CREATEUSERHOLIDAY_IOPK_RES

Attribute	Description
Name	CREATEUSERHOLIDAY_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute		Description	
Name	SOURCE_USERID		
Datatype	String		
Description	This is the user id in the Source system who is performing the action.		
Attribute	Attribute		Description
	minOccurs	0	

DESTINATION

Attribute		Description	
Name	DESTINATION		
Datatype	String		
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute		Description	
Name	MULTITRIPID		
Datatype	String		
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute		Description	
Name	FUNCTIONID		
Datatype	String		
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.		
Attribute	Attribute		Description
	minOccurs	0	

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-User-Holiday-PK

Attribute	Description
Name	Smtbs-User-Holiday-PK
Datatype	
Description	

USER_ID

Attribute	Description				
Name	USER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

LEAVE_FROM

Attribute	Description
-----------	-------------

Name	LEAVE_FROM
Datatype	String
Description	

LEAVE_TO

Attribute	Description
Name	LEAVE_TO
Datatype	String
Description	

Smtbs-User-Holiday-IO

Attribute	Description
Name	Smtbs-User-Holiday-IO
Datatype	
Description	

USER_ID

Attribute	Description				
Name	USER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

LEAVE_FROM

Attribute	Description
Name	LEAVE_FROM
Datatype	String
Description	

LEAVE_TO

Attribute	Description
Name	LEAVE_TO
Datatype	String
Description	

REMARKS

Attribute	Description				
Name	REMARKS				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>2000</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	2000
Restrictions	Description				
maxLength	2000				

FCUBS_ERROR_RESP

Attribute	Description
-----------	-------------

Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	
	Description	
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	
	Description	
	maxOccurs	unbounded

WCODE

Attribute	Description
------------------	--------------------

Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.59.DeleteUserHoliday

2.59.1.SM-DeleteUserHoliday-Req-Full-MSG.xsd

DELETEUSERHOLIDAY_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-User-Holiday-Full

BRANCH_CODE

USER_ID

LEAVE_FROM

LEAVE_TO

REMARKS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

DELETEUSERHOLIDAY_FSFS_REQ

Attribute	Description
Name	DELETEUSERHOLIDAY_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Smtbs-User-Holiday-Full

Attribute		Description
------------------	--	--------------------

Name	Smtbs-User-Holiday-Full
Datatype	
Description	

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

USER_ID

Attribute	Description	
Name	USER_ID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12

LEAVE_FROM

Attribute	Description	
Name	LEAVE_FROM	
Datatype	String	
Description		

LEAVE_TO

Attribute	Description	
Name	LEAVE_TO	
Datatype	String	
Description		

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

2.59.2.SM-DeleteUserHoliday-Req-IO-MSG.xsd

DELETEUSERHOLIDAY_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-User-Holiday-IO

USER_ID

LEAVE_FROM

LEAVE_TO

DELETEUSERHOLIDAY_IOPK_REQ

Attribute	Description
Name	DELETEUSERHOLIDAY_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-User-Holiday-IO

Attribute	Description
Name	Smtbs-User-Holiday-IO
Datatype	
Description	

USER_ID

Attribute	Description				
Name	USER_ID				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

LEAVE_FROM

Attribute	Description
Name	LEAVE_FROM
Datatype	String
Description	

LEAVE_TO

Attribute	Description
Name	LEAVE_TO
Datatype	String
Description	

2.59.3.SM-DeleteUserHoliday-Res-Full-MSG.xsd

DELETEUSERHOLIDAY_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Smtbs-User-Holiday-Full
BRANCH_CODE
USER_ID
LEAVE_FROM
LEAVE_TO
REMARKS
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEUSERHOLIDAY_FSFS_RES

Attribute	Description
Name	DELETEUSERHOLIDAY_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Smtbs-User-Holiday-Full

Attribute	Description	
Name	Smtbs-User-Holiday-Full	
Datatype		
Description		

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

USER_ID

Attribute	Description	
Name	USER_ID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12

LEAVE_FROM

Attribute	Description	
Name	LEAVE_FROM	
Datatype	String	
Description		

LEAVE_TO

Attribute	Description	
Name	LEAVE_TO	
Datatype	String	
Description		

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	

Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.59.4.SM-DeleteUserHoliday-Res-PK-MSG.xsd

DELETEUSERHOLIDAY_IOPK_RES

FCUBS_HEADER

SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Smtbs-User-Holiday-PK
USER_ID
LEAVE_FROM
LEAVE_TO
Smtbs-User-Holiday-IO
USER_ID
LEAVE_FROM
LEAVE_TO
FCUBS_ERROR_RESP
ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEUSERHOLIDAY_IOPK_RES

Attribute	Description
Name	DELETEUSERHOLIDAY_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-User-Holiday-PK

Attribute	Description
Name	Smtbs-User-Holiday-PK
Datatype	
Description	

USER_ID

Attribute	Description
------------------	--------------------

Name	USER_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	12

LEAVE_FROM

Attribute	Description
Name	LEAVE_FROM
Datatype	String
Description	

LEAVE_TO

Attribute	Description
Name	LEAVE_TO
Datatype	String
Description	

Smtbs-User-Holiday-IO

Attribute	Description
Name	Smtbs-User-Holiday-IO
Datatype	
Description	

USER_ID

Attribute	Description	
Name	USER_ID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	12

LEAVE_FROM

Attribute	Description
Name	LEAVE_FROM
Datatype	String
Description	

LEAVE_TO

Attribute	Description
Name	LEAVE_TO
Datatype	String
Description	

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.60.QueryUserHoliday

2.60.1.SM-QueryUserHoliday-Req-IO-MSG.xsd

QUERYUSERHOLIDAY_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-User-Holiday-IO

USER_ID

LEAVE_FROM

LEAVE_TO

QUERYUSERHOLIDAY_IOFS_REQ

Attribute	Description
Name	QUERYUSERHOLIDAY_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute		Description	
Name	SOURCE_USERID		
Datatype	String		
Description	This is the user id in the Source system who is performing the action.		
Attribute	Attribute		Description
	minOccurs	0	

DESTINATION

Attribute		Description	
Name	DESTINATION		
Datatype	String		
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute		Description	
Name	MULTITRIPID		
Datatype	String		
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute		Description	
Name	FUNCTIONID		
Datatype	String		
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.		
Attribute	Attribute		Description
	minOccurs	0	

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-User-Holiday-IO

Attribute	Description
Name	Smtbs-User-Holiday-IO
Datatype	
Description	

USER_ID

Attribute	Description				
Name	USER_ID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

LEAVE_FROM

Attribute	Description
-----------	-------------

Name	LEAVE_FROM
Datatype	String
Description	

LEAVE_TO

Attribute	Description
Name	LEAVE_TO
Datatype	String
Description	

2.60.2.SM-QueryUserHoliday-Res-Full-MSG.xsd

QUERYUSERHOLIDAY_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-User-Holiday-IO

USER_ID

LEAVE_FROM

LEAVE_TO

Smtbs-User-Holiday-Full

BRANCH_CODE

USER_ID

LEAVE_FROM

LEAVE_TO

REMARKS

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYUSERHOLIDAY_IOFS_RES

Attribute	Description
Name	QUERYUSERHOLIDAY_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-User-Holiday-IO

Attribute	Description
Name	Smtbs-User-Holiday-IO
Datatype	
Description	

USER_ID

Attribute	Description				
Name	USER_ID				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

LEAVE_FROM

Attribute	Description
Name	LEAVE_FROM
Datatype	String
Description	

LEAVE_TO

Attribute	Description
Name	LEAVE_TO
Datatype	String
Description	

Smtbs-User-Holiday-Full

Attribute	Description
Name	Smtbs-User-Holiday-Full
Datatype	
Description	

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

USER_ID

Attribute	Description	
Name	USER_ID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12

LEAVE_FROM

Attribute	Description	
Name	LEAVE_FROM	
Datatype	String	
Description		

LEAVE_TO

Attribute	Description	
Name	LEAVE_TO	
Datatype	String	
Description		

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.61.AuthorizeAddressCode

2.61.1.ST-AuthorizeAddressCode-Req-Full-MSG.xsd

AUTHORIZEADDRESSCODE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Address-Details-Full

ADDRESS_CODE

MARK_FOR_EXPIRY

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Kanji

English

PIN_CODE

Katakana

Script-Add-Detail

SCRIPT_CODE

ADDR1

ADDR2

ADDR3

PIN_CODE

ADDRESS_CODE

PREFECTURE

AUTHORIZEADDRESSCODE_FSFS_REQ

Attribute	Description
Name	AUTHORIZEADDRESSCODE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Address-Details-Full

Attribute	Description	
------------------	--------------------	--

Name	Address-Details-Full
Datatype	
Description	

ADDRESS_CODE

Attribute	Description	
Name	ADDRESS_CODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12

MARK_FOR_EXPIRY

Attribute	Description	
Name	MARK_FOR_EXPIRY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute		Description	
Name	CHECKER		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	12	

CHECKERSTAMP

Attribute		Description	
Name	CHECKERSTAMP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

MODNO

Attribute		Description	
Name	MODNO		
Datatype	Decimal		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	totalDigits	4	

TXNSTAT

Attribute		Description	
Name	TXNSTAT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1	

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Kanji

Attribute	Description	
Name	Kanji	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

English

Attribute	Description	
Name	English	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	6

Katakana

Attribute	Description	
Name	Katakana	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Scrt-Add-Detail

Attribute	Description						
Name	Scrt-Add-Detail						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

SCRIPT_CODE

Attribute	Description				
Name	SCRIPT_CODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr></tbody></table>	Restrictions	Description	maxLength	8
Restrictions	Description				
maxLength	8				

ADDR1

Attribute	Description				
Name	ADDR1				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

ADDR2

Attribute	Description				
Name	ADDR2				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

ADDRESS_CODE

Attribute	Description	
Name	ADDRESS_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

PREFECTURE

Attribute	Description	
Name	PREFECTURE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

2.61.2.ST-AuthorizeAddressCode-Req-IO-MSG.xsd

[AUTHORIZEADDRESSCODE_IOPK_REQ](#)

[FCUBS_HEADER](#)

[SOURCE](#)

UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Address-Details-IO
ADDRESS_CODE
CHECKER
CHECKERSTAMP
MODNO

AUTHORIZEADDRESSCODE_IOPK_REQ

Attribute	Description
Name	AUTHORIZEADDRESSCODE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
-----------	-------------

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Address-Details-IO

Attribute	Description
Name	Address-Details-IO
Datatype	
Description	

ADDRESS_CODE

Attribute	Description				
Name	ADDRESS_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

2.61.3.ST-AuthorizeAddressCode-Res-Full-MSG.xsd

AUTHORIZEADDRESSCODE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Address-Details-Full

ADDRESS_CODE

MARK_FOR_EXPIRY

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Kanji

English

PIN_CODE

Katakana

Script-Add-Detail

SCRIPT_CODE

ADDR1

ADDR2

ADDR3

PIN_CODE

ADDRESS_CODE

PREFECTURE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEADDRESSCODE_FSFS_RES

Attribute	Description
Name	AUTHORIZEADDRESSCODE_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

FCUBS_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description			

Address-Details-Full

Attribute		Description	
Name	Address-Details-Full		
Datatype			
Description			

ADDRESS_CODE

Attribute		Description	
Name	ADDRESS_CODE		
Datatype	String		
Description			
Restrictions	Restrictions		Description
	maxLength	12	

MARK_FOR_EXPIRY

Attribute	Description	
Name	MARK_FOR_EXPIRY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute		Description	
Name	CHECKERSTAMP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

MODNO

Attribute		Description	
Name	MODNO		
Datatype	Decimal		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	totalDigits	4	

TXNSTAT

Attribute		Description	
Name	TXNSTAT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1	

AUTHSTAT

Attribute		Description	
Name	AUTHSTAT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1	

Attribute	Description	
Name	Kanji	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

English

Attribute	Description	
Name	English	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	6

Katakana

Attribute	Description	
Name	Katakana	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Scrp-Add-Detail

Attribute	Description	
Name	Scrp-Add-Detail	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

SCRIPT_CODE

Attribute	Description	
Name	SCRIPT_CODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	8

ADDR1

Attribute	Description	
Name	ADDR1	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

ADDR2

Attribute	Description	
Name	ADDR2	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

ADDR3

Attribute	Description	
Name	ADDR3	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	15

ADDRESS_CODE

Attribute	Description	
Name	ADDRESS_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

PREFECTURE

Attribute	Description	
Name	PREFECTURE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.61.4.ST-AuthorizeAddressCode-Res-PK-MSG.xsd

[AUTHORIZEADDRESSCODE_IOPK_RES](#)

[FCUBS_HEADER](#)

SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Address-Details-PK
ADDRESS_CODE
Address-Details-IO
ADDRESS_CODE
CHECKER
CHECKERSTAMP
MODNO
FCUBS_ERROR_RESP
ERROR
ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEADDRESSCODE_IOPK_RES

Attribute	Description
Name	AUTHORIZEADDRESSCODE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0
	maxOccurs		unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Address-Details-PK

Attribute		Description	
Name		Address-Details-PK	
Datatype			
Description			

ADDRESS_CODE

Attribute		Description	
Name		ADDRESS_CODE	
Datatype		String	
Description			
Restrictions	Restrictions		Description
	maxLength		12

Address-Details-IO

Attribute	Description
Name	Address-Details-IO
Datatype	
Description	

ADDRESS_CODE

Attribute	Description				
Name	ADDRESS_CODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

CHECKERSTAMP

Attribute	Description				
Name	CHECKERSTAMP				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

MODNO

Attribute	Description				
Name	MODNO				
Datatype	Decimal				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		

Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.62.AuthorizeCustChange

2.62.1.ST-AuthorizeCustChange-Req-Full-MSG.xsd

AUTHORIZECUSTCHANGE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Addtl-Det-C-Full

TRNSFRREFNO

TRNSFRDT

TRNSFRDESC

TRNSFRSTAT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Src-Cust-C

SRCCUSTNO

Trgt-Cust-C

TRGTCUSTNO

BRN_TRFR

Acc-Det

ACCTYPE

BRNCD

ACTNO

CNTNUEACCTDESC

CNTNUEACCNTADDR

NCDTRNSFRPRICE

ACCOUNTCCY

LINKEDACNO

SDREFRNO

CACCBRNCH

LIQ_INT

Acct-Lmt-Linkage

LNKTYP

CURRLINKREFNO

NEWLNKREFNO

AVAILABLE_AMT

Acct-Comm-Linkage

CMCURRCOMMREFNO

CMNEWCOMMREFNO

AVAILABLE_AMT

Validatn-Msgs

ACCTYPE

ACCCUSTNO

ERRCODE

ERRPARAMS

MSGTYPE

MESSAGE

AUTHORIZECUSTCHANGE_FSFS_REQ

Attribute	Description
Name	AUTHORIZECUSTCHANGE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description
Name	USERID

Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Addtnl-Det-C-Full

Attribute	Description
Name	Addtnl-Det-C-Full
Datatype	
Description	

TRNSFRREFNO

Attribute	Description				
Name	TRNSFRREFNO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

TRNSFRDT

Attribute	Description				
Name	TRNSFRDT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

TRNSFRDESC

Attribute	Description				
Name	TRNSFRDESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>255</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

TRNSFRSTAT

Attribute	Description
Name	TRNSFRSTAT
Datatype	String
Description	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	U,P,S,F,C

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Src-Cust-C

Attribute	Description	
Name	Src-Cust-C	
Datatype		
Description		

Attribute		
	Attribute	Description
	minOccurs	0

SRCCUSTNO

Attribute	Description	
Name	SRCCUSTNO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

Trgt-Cust-C

Attribute	Description	
Name	Trgt-Cust-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

TRGTCUSTNO

Attribute	Description	
Name	TRGTCUSTNO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

BRN_TRFR

Attribute	Description	
Name	BRN_TRFR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

Acc-Det

Attribute	Description	
Name	Acc-Det	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCTYPE

Attribute	Description	
Name	ACCTYPE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

ACTNO

Attribute	Description	
Name	ACTNO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

CNTNUEACCTDESC

Attribute	Description	
Name	CNTNUEACCTDESC	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

CNTNUEACCNTADDR

Attribute	Description	
Name	CNTNUEACCNTADDR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

NCDTRNSFRPRICE

Attribute	Description	
Name	NCDTRNSFRPRICE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

ACCOUNTCCY

Attribute	Description	
Name	ACCOUNTCCY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	20

LINKEDACNO

Attribute	Description	
Name	LINKEDACNO	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	25

SDREFRNO

Attribute	Description	
Name	SDREFRNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	25

CACCBRNCH

Attribute	Description	
Name	CACCBRNCH	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

LIQ_INT

Attribute	Description	
Name	LIQ_INT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

Acct-Lmt-Linkage

Attribute	Description	
Name	Acct-Lmt-Linkage	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

LNKTYP

Attribute	Description	
Name	LNKTYP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	T,C,U,F,P,

CURRLINKREFNO

Attribute	Description	
Name	CURRLINKREFNO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

NEWLNKREFNO

Attribute	Description	
Name	NEWLNKREFNO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

AVAILABLE_AMT

Attribute	Description	
Name	AVAILABLE_AMT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

Acct-Comm-Linkage

Attribute	Description	
Name	Acct-Comm-Linkage	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxOccurs	unbounded

CMCURRCOMMREFNO

Attribute	Description	
Name	CMCURRCOMMREFNO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CMNEWCOMMREFNO

Attribute	Description	
Name	CMNEWCOMMREFNO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

AVAILABLE_AMT

Attribute	Description	
Name	AVAILABLE_AMT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

Validatn-Msgs

Attribute	Description	
Name	Validatn-Msgs	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCTYPE

Attribute	Description	
Name	ACCTYPE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

ACCCUSTNO

Attribute	Description	
Name	ACCCUSTNO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

ERRCODE

Attribute	Description	
Name	ERRCODE	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

ERRPARAMS

Attribute	Description	
Name	ERRPARAMS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MSGTYPE

Attribute	Description	
Name	MSGTYPE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	E,I,O

MESSAGE

Attribute	Description	
Name	MESSAGE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

2.62.2.ST-AuthorizeCustChange-Req-IO-MSG.xsd

[AUTHORIZECUSTCHANGE_IOPK_REQ](#)

[FCUBS_HEADER](#)

[SOURCE](#)

UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
 PARAM
 NAME
 VALUE
FCUBS_BODY
 Addnl-Det-C-IO
 TRNSFRREFNO
 CHECKER
 CHECKERSTAMP
 MODNO

AUTHORIZECUSTCHANGE_IOPK_REQ

Attribute	Description
Name	AUTHORIZECUSTCHANGE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
-----------	-------------

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Addnl-Det-C-IO

Attribute	Description
Name	Addnl-Det-C-IO
Datatype	
Description	

TRNSFRREFNO

Attribute	Description				
Name	TRNSFRREFNO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

2.62.3.ST-AuthorizeCustChange-Res-Full-MSG.xsd

AUTHORIZECUSTCHANGE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Addtl-Det-C-Full

TRNSFRREFNO

TRNSFRDT

TRNSFRDESC

TRNSFRSTAT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Src-Cust-C

SRCCUSTNO

Trgt-Cust-C

TRGTCUSTNO

BRN_TRFR

Acc-Det

ACCTYPE

BRNCD

ACTNO

CNTNUEACCTDESC

CNTNUEACCNTADDR

NCDTRNSFRPRICE

ACCOUNTCCY

LINKEDACNO

SDREFRNO

CACCBRNCH

LIQ_INT

Acct-Lmt-Linkage

LNKTYP

CURRLINKREFNO

NEWLNKREFNO

AVAILABLE_AMT

Acct-Comm-Linkage

CMCURRCOMMREFNO

CMNEWCOMMREFNO

AVAILABLE_AMT

Validatn-Msgs

ACCTYPE

ACCCUSTNO

ERRCODE

ERRPARAMS

MSGTYPE

MESSAGE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZECUSTCHANGE_FSFS_RES

Attribute	Description
Name	AUTHORIZECUSTCHANGE_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
------------------	--------------------

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Addtnl-Det-C-Full

Attribute	Description
Name	Addtnl-Det-C-Full
Datatype	
Description	

TRNSFRREFNO

Attribute	Description				
Name	TRNSFRREFNO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

TRNSFRDT

Attribute	Description				
Name	TRNSFRDT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

TRNSFRDESC

Attribute	Description				
Name	TRNSFRDESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	255

TRNSFRSTAT

Attribute	Description	
Name	TRNSFRSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	U,P,S,F,C

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

Src-Cust-C

Attribute	Description	
Name	Src-Cust-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

SRCCUSTNO

Attribute	Description	
Name	SRCCUSTNO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

Trgt-Cust-C

Attribute	Description	
Name	Trgt-Cust-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

TRGTCUSTNO

Attribute	Description	
Name	TRGTCUSTNO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

BRN_TRFR

Attribute	Description	
Name	BRN_TRFR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	Y,N

Acc-Det

Attribute	Description	
Name	Acc-Det	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCTYPE

Attribute	Description	
Name	ACCTYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	2

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

ACTNO

Attribute	Description	
Name	ACTNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	50

CNTNUEACCTDESC

Attribute	Description	
Name	CNTNUEACCTDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

CNTNUEACCNTADDR

Attribute	Description	
Name	CNTNUEACCNTADDR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

NCDTRNSFRPRICE

Attribute	Description	
Name	NCDTRNSFRPRICE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

ACCOUNTCCY

Attribute	Description	
Name	ACCOUNTCCY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	20

LINKEDACNO

Attribute	Description	
Name	LINKEDACNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	25

SDREFRNO

Attribute	Description	
Name	SDREFRNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	25

CACCBRNCH

Attribute	Description	
Name	CACCBRNCH	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

LIQ_INT

Attribute	Description	
Name	LIQ_INT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	Y,N

Acct-Lmt-Linkage

Attribute	Description	
Name	Acct-Lmt-Linkage	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

LNKTYP

Attribute	Description	
Name	LNKTYP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	T,C,U,F,P,

CURRLINKREFNO

Attribute	Description	
Name	CURRLINKREFNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

NEWLNKREFNO

Attribute	Description	
Name	NEWLNKREFNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

AVAILABLE_AMT

Attribute	Description	
Name	AVAILABLE_AMT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

Acct-Comm-Linkage

Attribute	Description	
Name	Acct-Comm-Linkage	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

CMCURRCOMMREFNO

Attribute	Description	
Name	CMCURRCOMMREFNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CMNEWCOMMREFNO

Attribute	Description	
Name	CMNEWCOMMREFNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

AVAILABLE_AMT

Attribute	Description	
Name	AVAILABLE_AMT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

Validatn-Msgs

Attribute	Description	
Name	Validatn-Msgs	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCTYPE

Attribute	Description	
Name	ACCTYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	2

ACCCUSTNO

Attribute	Description	
Name	ACCCUSTNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	50

ERRCODE

Attribute	Description	
Name	ERRCODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	11

ERRPARAMS

Attribute	Description	
Name	ERRPARAMS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

MSGTYPE

Attribute	Description	
Name	MSGTYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	E,I,O

MESSAGE

Attribute	Description	
Name	MESSAGE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1000

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		

Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.62.4.ST-AuthorizeCustChange-Res-PK-MSG.xsd

AUTHORIZECUSTCHANGE_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Addtl-Det-C-PK

TRNSFRREFNO

Addtl-Det-C-IO

TRNSFRREFNO

CHECKER

CHECKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZECUSTCHANGE_IOPK_RES

Attribute	Description
Name	AUTHORIZECUSTCHANGE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description

Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nullable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Addtnl-Det-C-PK

Attribute	Description
Name	Addtnl-Det-C-PK
Datatype	
Description	

TRNSFRREFNO

Attribute	Description				
Name	TRNSFRREFNO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

Addtnl-Det-C-IO

Attribute	Description
Name	Addtnl-Det-C-IO
Datatype	
Description	

TRNSFRREFNO

Attribute	Description				
Name	TRNSFRREFNO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.63.CloseAddressCode

2.63.1.ST-CloseAddressCode-Req-Full-MSG.xsd

CLOSEADDRESSCODE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Address-Details-Full
ADDRESS_CODE
MARK_FOR_EXPIRY
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Kanji
English
PIN_CODE
Katakana
Scrp-Add-Detail
SCRIPT_CODE

ADDR1

ADDR2

ADDR3

PIN_CODE

ADDRESS_CODE

PREFECTURE

CLOSEADDRESSCODE_FSFS_REQ

Attribute	Description
Name	CLOSEADDRESSCODE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Address-Details-Full

Attribute	Description
Name	Address-Details-Full
Datatype	
Description	

ADDRESS_CODE

Attribute	Description
------------------	--------------------

Name	ADDRESS_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	12

MARK_FOR_EXPIRY

Attribute	Description	
Name	MARK_FOR_EXPIRY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

Kanji

Attribute	Description	
Name	Kanji	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

English

Attribute	Description	
Name	English	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

Katakana

Attribute	Description	
Name	Katakana	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

Scrt-Add-Detail

Attribute	Description
------------------	--------------------

Name	Scrt-Add-Detail	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

SCRIPT_CODE

Attribute	Description	
Name	SCRIPT_CODE	
Datatype	String	
Description		
Restrictions	Restrictions	
	Description	
	maxLength	8

ADDR1

Attribute	Description	
Name	ADDR1	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	35

ADDR2

Attribute	Description	
Name	ADDR2	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	35

ADDR3

Attribute	Description	
Name	ADDR3	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	15

ADDRESS_CODE

Attribute	Description	
Name	ADDRESS_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

PREFECTURE

Attribute	Description	
Name	PREFECTURE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

2.63.2.ST-CloseAddressCode-Req-IO-MSG.xsd

CLOSEADDRESSCODE_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Address-Details-IO
ADDRESS_CODE
MAKER
MAKERSTAMP
MODNO

CLOSEADDRESSCODE_IOPK_REQ

Attribute	Description
Name	CLOSEADDRESSCODE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Address-Details-IO

Attribute	Description
Name	Address-Details-IO
Datatype	
Description	

ADDRESS_CODE

Attribute	Description				
Name	ADDRESS_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

2.63.3.ST-CloseAddressCode-Res-Full-MSG.xsd

CLOSEADDRESSCODE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Address-Details-Full

ADDRESS_CODE

MARK_FOR_EXPIRY

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Kanji

English

PIN_CODE

Katakana

Script-Add-Detail

SCRIPT_CODE

ADDR1

ADDR2

ADDR3

PIN_CODE

ADDRESS_CODE

PREFECTURE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CLOSEADDRESSCODE_FSFS_RES

Attribute	Description
Name	CLOSEADDRESSCODE_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

FCUBS_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description			

Address-Details-Full

Attribute		Description	
Name	Address-Details-Full		
Datatype			
Description			

ADDRESS_CODE

Attribute		Description	
Name	ADDRESS_CODE		
Datatype	String		
Description			
Restrictions	Restrictions		Description
	maxLength	12	

MARK_FOR_EXPIRY

Attribute	Description	
Name	MARK_FOR_EXPIRY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute		Description	
Name	CHECKERSTAMP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

MODNO

Attribute		Description	
Name	MODNO		
Datatype	Decimal		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	totalDigits	4	

TXNSTAT

Attribute		Description	
Name	TXNSTAT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1	

AUTHSTAT

Attribute		Description	
Name	AUTHSTAT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1	

Attribute	Description	
Name	Kanji	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

English

Attribute	Description	
Name	English	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	6

Katakana

Attribute	Description	
Name	Katakana	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Scrp-Add-Detail

Attribute	Description	
Name	Scrp-Add-Detail	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

SCRIPT_CODE

Attribute	Description	
Name	SCRIPT_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	8

ADDR1

Attribute	Description	
Name	ADDR1	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

ADDR2

Attribute	Description	
Name	ADDR2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

ADDR3

Attribute	Description	
Name	ADDR3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	15

ADDRESS_CODE

Attribute	Description	
Name	ADDRESS_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

PREFECTURE

Attribute	Description	
Name	PREFECTURE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.63.4.ST-CloseAddressCode-Res-PK-MSG.xsd

CLOSEADDRESSCODE_IOPK_RES

FCUBS_HEADER

SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Address-Details-PK
ADDRESS_CODE
Address-Details-IO
ADDRESS_CODE
MAKER
MAKERSTAMP
MODNO
FCUBS_ERROR_RESP
ERROR
ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CLOSEADDRESSCODE_IOPK_RES

Attribute	Description
Name	CLOSEADDRESSCODE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0
	maxOccurs		unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Address-Details-PK

Attribute		Description	
Name		Address-Details-PK	
Datatype			
Description			

ADDRESS_CODE

Attribute		Description	
Name		ADDRESS_CODE	
Datatype		String	
Description			
Restrictions	Restrictions		Description
	maxLength		12

Address-Details-IO

Attribute	Description
Name	Address-Details-IO
Datatype	
Description	

ADDRESS_CODE

Attribute	Description				
Name	ADDRESS_CODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

MODNO

Attribute	Description				
Name	MODNO				
Datatype	Decimal				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.64.CloseCustChange

2.64.1.ST-CloseCustChange-Req-Full-MSG.xsd

CLOSECUSTCHANGE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Addtl-Det-C-Full

TRNSFRREFNO

TRNSFRDT

TRNSFRDESC

TRNSFRSTAT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Src-Cust-C

SRCCUSTNO

Trgt-Cust-C

TRGTCUSTNO

BRN_TRFR

Acc-Det

ACCTYPE

BRNCD

ACTNO

CNTNUEACCTDESC

CNTNUEACCNTADDR

NCDTRNSFRPRICE

ACCOUNTCCY

LINKEDACNO

SDREFRNO

CACCBRNCH

LIQ_INT

Acct-Lmt-Linkage

LNKTYP

CURRLINKREFNO

NEWLNKREFNO

AVAILABLE_AMT

Acct-Comm-Linkage

CMCURRCOMMREFNO

CMNEWCOMMREFNO

AVAILABLE_AMT

Validatn-Msgs

ACCTYPE

ACCCUSTNO

ERRCODE

ERRPARAMS

MSGTYPE

MESSAGE

CLOSECUSTCHANGE_FSFS_REQ

Attribute	Description
Name	CLOSECUSTCHANGE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description
Name	USERID

Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Addtnl-Det-C-Full

Attribute	Description
Name	Addtnl-Det-C-Full
Datatype	
Description	

TRNSFRREFNO

Attribute	Description				
Name	TRNSFRREFNO				
Datatype	String				
Description					
Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

TRNSFRDT

Attribute	Description				
Name	TRNSFRDT				
Datatype	String				
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

TRNSFRDESC

Attribute	Description				
Name	TRNSFRDESC				
Datatype	String				
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>255</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

TRNSFRSTAT

Attribute	Description
Name	TRNSFRSTAT
Datatype	String
Description	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	U,P,S,F,C

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Src-Cust-C

Attribute	Description	
Name	Src-Cust-C	
Datatype		
Description		

Attribute		
	Attribute	Description
	minOccurs	0

SRCCUSTNO

Attribute	Description	
Name	SRCCUSTNO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

Trgt-Cust-C

Attribute	Description	
Name	Trgt-Cust-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

TRGTCUSTNO

Attribute	Description	
Name	TRGTCUSTNO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

BRN_TRFR

Attribute	Description	
Name	BRN_TRFR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

Acc-Det

Attribute	Description	
Name	Acc-Det	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCTYPE

Attribute	Description	
Name	ACCTYPE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

ACTNO

Attribute	Description	
Name	ACTNO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

CNTNUEACCTDESC

Attribute	Description	
Name	CNTNUEACCTDESC	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

CNTNUEACCNTADDR

Attribute	Description	
Name	CNTNUEACCNTADDR	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

NCDTRNSFRPRICE

Attribute	Description	
Name	NCDTRNSFRPRICE	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

ACCOUNTCCY

Attribute	Description	
Name	ACCOUNTCCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

LINKEDACNO

Attribute	Description	
Name	LINKEDACNO	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	25

SDREFRNO

Attribute	Description	
Name	SDREFRNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	25

CACCBRNCH

Attribute	Description	
Name	CACCBRNCH	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

LIQ_INT

Attribute	Description	
Name	LIQ_INT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

Acct-Lmt-Linkage

Attribute	Description	
Name	Acct-Lmt-Linkage	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

LNKTYP

Attribute	Description	
Name	LNKTYP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	T,C,U,F,P,

CURRLINKREFNO

Attribute	Description	
Name	CURRLINKREFNO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

NEWLNKREFNO

Attribute	Description	
Name	NEWLNKREFNO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

AVAILABLE_AMT

Attribute	Description	
Name	AVAILABLE_AMT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

Acct-Comm-Linkage

Attribute	Description	
Name	Acct-Comm-Linkage	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxOccurs	unbounded

CMCURRCOMMREFNO

Attribute	Description	
Name	CMCURRCOMMREFNO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CMNEWCOMMREFNO

Attribute	Description	
Name	CMNEWCOMMREFNO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

AVAILABLE_AMT

Attribute	Description	
Name	AVAILABLE_AMT	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

Validatn-Msgs

Attribute	Description	
Name	Validatn-Msgs	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCTYPE

Attribute	Description	
Name	ACCTYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

ACCCUSTNO

Attribute	Description	
Name	ACCCUSTNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

ERRCODE

Attribute	Description	
Name	ERRCODE	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

ERRPARAMS

Attribute	Description	
Name	ERRPARAMS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MSGTYPE

Attribute	Description	
Name	MSGTYPE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	E,I,O

MESSAGE

Attribute	Description	
Name	MESSAGE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

2.64.2.ST-CloseCustChange-Req-IO-MSG.xsd

CLOSECUSTCHANGE_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
 PARAM
 NAME
 VALUE
FCUBS_BODY
 Addnl-Det-C-IO
 TRNSFRREFNO
 MAKER
 MAKERSTAMP
 MODNO

CLOSECUSTCHANGE_IOPK_REQ

Attribute	Description
Name	CLOSECUSTCHANGE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
------------------	--------------------

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Addnl-Det-C-IO

Attribute	Description
Name	Addnl-Det-C-IO
Datatype	
Description	

TRNSFRREFNO

Attribute	Description				
Name	TRNSFRREFNO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

2.64.3.ST-CloseCustChange-Res-Full-MSG.xsd

CLOSECUSTCHANGE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Addtl-Det-C-Full

TRNSFRREFNO

TRNSFRDT

TRNSFRDESC

TRNSFRSTAT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Src-Cust-C

SRCCUSTNO

Trgt-Cust-C

TRGTCUSTNO

BRN_TRFR

Acc-Det

ACCTYPE

BRNCD

ACTNO

CNTNUEACCTDESC

CNTNUEACCNTADDR

NCOTRNSFRPRICE

ACCOUNTCCY

LINKEDACNO

SDREFRNO

CACCBRNCH

LIQ_INT

Acct-Lmt-Linkage

LNKTYP

CURRLINKREFNO

NEWLNKREFNO

AVAILABLE_AMT

Acct-Comm-Linkage

CMCURRCOMMREFNO

CMNEWCOMMREFNO

AVAILABLE_AMT

Validatn-Msgs

ACCTYPE

ACCCUSTNO

ERRCODE

ERRPARAMS

MSGTYPE

MESSAGE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CLOSECUSTCHANGE_FSFS_RES

Attribute	Description
Name	CLOSECUSTCHANGE_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
------------------	--------------------

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Addtnl-Det-C-Full

Attribute	Description
Name	Addtnl-Det-C-Full
Datatype	
Description	

TRNSFRREFNO

Attribute	Description				
Name	TRNSFRREFNO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

TRNSFRDT

Attribute	Description				
Name	TRNSFRDT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

TRNSFRDESC

Attribute	Description				
Name	TRNSFRDESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	255

TRNSFRSTAT

Attribute	Description	
Name	TRNSFRSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	U,P,S,F,C

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

Src-Cust-C

Attribute	Description	
Name	Src-Cust-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

SRCCUSTNO

Attribute	Description	
Name	SRCCUSTNO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

Trgt-Cust-C

Attribute	Description	
Name	Trgt-Cust-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

TRGTCUSTNO

Attribute	Description	
Name	TRGTCUSTNO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

BRN_TRFR

Attribute	Description	
Name	BRN_TRFR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	Y,N

Acc-Det

Attribute	Description	
Name	Acc-Det	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCTYPE

Attribute	Description	
Name	ACCTYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	2

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

ACTNO

Attribute	Description	
Name	ACTNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	50

CNTNUEACCTDESC

Attribute	Description	
Name	CNTNUEACCTDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

CNTNUEACCNTADDR

Attribute	Description	
Name	CNTNUEACCNTADDR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

NCDTRNSFRPRICE

Attribute	Description	
Name	NCDTRNSFRPRICE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

ACCOUNTCCY

Attribute	Description	
Name	ACCOUNTCCY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	20

LINKEDACNO

Attribute	Description	
Name	LINKEDACNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	25

SDREFRNO

Attribute	Description	
Name	SDREFRNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	25

CACCBRNCH

Attribute	Description	
Name	CACCBRNCH	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

LIQ_INT

Attribute	Description	
Name	LIQ_INT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	Y,N

Acct-Lmt-Linkage

Attribute	Description	
Name	Acct-Lmt-Linkage	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

LNKTYP

Attribute	Description	
Name	LNKTYP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	T,C,U,F,P,

CURRLINKREFNO

Attribute	Description	
Name	CURRLINKREFNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

NEWLNKREFNO

Attribute	Description	
Name	NEWLNKREFNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

AVAILABLE_AMT

Attribute	Description	
Name	AVAILABLE_AMT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

Acct-Comm-Linkage

Attribute	Description	
Name	Acct-Comm-Linkage	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

CMCURRCOMMREFNO

Attribute	Description	
Name	CMCURRCOMMREFNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CMNEWCOMMREFNO

Attribute	Description	
Name	CMNEWCOMMREFNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

AVAILABLE_AMT

Attribute	Description	
Name	AVAILABLE_AMT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

Validatn-Msgs

Attribute	Description	
Name	Validatn-Msgs	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCTYPE

Attribute	Description	
Name	ACCTYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	2

ACCCUSTNO

Attribute	Description	
Name	ACCCUSTNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	50

ERRCODE

Attribute	Description	
Name	ERRCODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	11

ERRPARAMS

Attribute	Description	
Name	ERRPARAMS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

MSGTYPE

Attribute	Description	
Name	MSGTYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	E,I,O

MESSAGE

Attribute	Description	
Name	MESSAGE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1000

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.64.4.ST-CloseCustChange-Res-PK-MSG.xsd

CLOSECUSTCHANGE_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Addtl-Det-C-PK

TRNSFRREFNO

Addtl-Det-C-IO

TRNSFRREFNO

MAKER

MAKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CLOSECUSTCHANGE_IOPK_RES

Attribute	Description
Name	CLOSECUSTCHANGE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description

Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Addtnl-Det-C-PK

Attribute	Description
Name	Addtnl-Det-C-PK
Datatype	
Description	

TRNSFRREFNO

Attribute	Description				
Name	TRNSFRREFNO				
Datatype	String				
Description					
Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

Addtnl-Det-C-IO

Attribute	Description
Name	Addtnl-Det-C-IO
Datatype	
Description	

TRNSFRREFNO

Attribute	Description				
Name	TRNSFRREFNO				
Datatype	String				
Description					
Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute		Description	
Name	MAKERSTAMP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

MODNO

Attribute		Description	
Name	MODNO		
Datatype	Decimal		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	totalDigits	4	

FCUBS_ERROR_RESP

Attribute		Description	
Name	FCUBS_ERROR_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

ERROR

Attribute		Description	
Name	ERROR		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

ECODE

Attribute		Description	
Name	ECODE		
Datatype	String		
Description			

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.65.CreateAddressCode

2.65.1.ST-CreateAddressCode-Req-Full-MSG.xsd

CREATEADDRESSCODE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Address-Details-Full
ADDRESS_CODE
MARK_FOR_EXPIRY
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Kanji
English
PIN_CODE
Katakana
Scrp-Add-Detail
SCRIPT_CODE

ADDR1

ADDR2

ADDR3

PIN_CODE

ADDRESS_CODE

PREFECTURE

CREATEADDRESSCODE_FSFS_REQ

Attribute	Description
Name	CREATEADDRESSCODE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Address-Details-Full

Attribute	Description
Name	Address-Details-Full
Datatype	
Description	

ADDRESS_CODE

Attribute	Description
------------------	--------------------

Name	ADDRESS_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	12

MARK_FOR_EXPIRY

Attribute	Description	
Name	MARK_FOR_EXPIRY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Kanji

Attribute	Description	
Name	Kanji	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

English

Attribute	Description	
Name	English	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	6

Katakana

Attribute	Description	
Name	Katakana	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Scrt-Add-Detail

Attribute	Description
------------------	--------------------

Name	Scrp-Add-Detail	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

SCRIPT_CODE

Attribute	Description	
Name	SCRIPT_CODE	
Datatype	String	
Description		
Restrictions	Restrictions	
	Description	
	maxLength	8

ADDR1

Attribute	Description	
Name	ADDR1	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	35

ADDR2

Attribute	Description	
Name	ADDR2	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	35

ADDR3

Attribute	Description	
Name	ADDR3	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	15

ADDRESS_CODE

Attribute	Description	
Name	ADDRESS_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

PREFECTURE

Attribute	Description	
Name	PREFECTURE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

2.65.2.ST-CreateAddressCode-Req-IO-MSG.xsd

CREATEADDRESSCODE_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Address-Details-IO
ADDRESS_CODE
MARK_FOR_EXPIRY
English
PIN_CODE
Script-Add-Detail
SCRIPT_CODE
ADDR1
ADDR2
ADDR3
PIN_CODE
ADDRESS_CODE
PREFECTURE

CREATEADDRESSCODE_IOPK_REQ

Attribute	Description
Name	CREATEADDRESSCODE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute		Description	
Name	SOURCE_USERID		
Datatype	String		
Description	This is the user id in the Source system who is performing the action.		
Attribute	Attribute		Description
	minOccurs	0	

DESTINATION

Attribute		Description	
Name	DESTINATION		
Datatype	String		
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute		Description	
Name	MULTITRIPID		
Datatype	String		
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute		Description	
Name	FUNCTIONID		
Datatype	String		
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.		
Attribute	Attribute		Description
	minOccurs	0	

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Address-Details-IO

Attribute	Description
Name	Address-Details-IO
Datatype	
Description	

ADDRESS_CODE

Attribute	Description				
Name	ADDRESS_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MARK_FOR_EXPIRY

Attribute	Description
-----------	-------------

Name	MARK_FOR_EXPIRY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

English

Attribute	Description	
Name	English	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	6

Scpt-Add-Detail

Attribute	Description	
Name	Scpt-Add-Detail	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

SCRIPT_CODE

Attribute	Description	
Name	SCRIPT_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	8

ADDR1

Attribute	Description	
Name	ADDR1	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

ADDR2

Attribute	Description	
Name	ADDR2	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

ADDR3

Attribute	Description	
Name	ADDR3	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

ADDRESS_CODE

Attribute	Description	
Name	ADDRESS_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

PREFECTURE

Attribute	Description	
Name	PREFECTURE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

2.65.3.ST-CreateAddressCode-Res-Full-MSG.xsd

CREATEADDRESSCODE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Address-Details-Full

ADDRESS_CODE

MARK_FOR_EXPIRY

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Kanji

English

PIN_CODE

Katakana

Scrp-Add-Detail

SCRIPT_CODE

ADDR1

ADDR2

ADDR3

PIN_CODE

ADDRESS_CODE

PREFECTURE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEADDRESSCODE_FSFS_RES

Attribute	Description
Name	CREATEADDRESSCODE_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Address-Details-Full

Attribute	Description	
Name	Address-Details-Full	
Datatype		
Description		

ADDRESS_CODE

Attribute	Description	
------------------	--------------------	--

Name	ADDRESS_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	12

MARK_FOR_EXPIRY

Attribute	Description	
Name	MARK_FOR_EXPIRY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

Kanji

Attribute	Description	
Name	Kanji	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

English

Attribute	Description	
Name	English	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

Katakana

Attribute	Description	
Name	Katakana	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

Scrt-Add-Detail

Attribute	Description
------------------	--------------------

Name	Scrp-Add-Detail	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

SCRIPT_CODE

Attribute	Description	
Name	SCRIPT_CODE	
Datatype	String	
Description		
Restrictions	Restrictions	
	Description	
	maxLength	8

ADDR1

Attribute	Description	
Name	ADDR1	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	35

ADDR2

Attribute	Description	
Name	ADDR2	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	35

ADDR3

Attribute	Description	
Name	ADDR3	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	15

ADDRESS_CODE

Attribute	Description	
Name	ADDRESS_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

PREFECTURE

Attribute	Description	
Name	PREFECTURE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String

*2.65.4.ST-CreateAddressCode-Res-PK-MSG.xsd**CREATEADDRESSCODE_IOPK_RES**FCUBS_HEADER**SOURCE**UBSCOMP**MSGID**CORRELID**USERID**BRANCH**MODULEID**SERVICE**OPERATION**SOURCE_OPERATION**SOURCE_USERID**DESTINATION**MULTITRIPID**FUNCTIONID**ACTION**MSGSTAT**PASSWORD**ADDL**PARAM**NAME**VALUE**FCUBS_BODY**Address-Details-PK**ADDRESS_CODE**Address-Details-IO**ADDRESS_CODE**MARK_FOR_EXPIRY**English**PIN_CODE*

Script-Add-Detail

SCRIPT_CODE

ADDR1

ADDR2

ADDR3

PIN_CODE

ADDRESS_CODE

PREFECTURE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEADDRESSCODE_IOPK_RES

Attribute	Description
Name	CREATEADDRESSCODE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description
Name	USERID

Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nullable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Address-Details-PK

Attribute	Description
Name	Address-Details-PK
Datatype	
Description	

ADDRESS_CODE

Attribute	Description				
Name	ADDRESS_CODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

Address-Details-IO

Attribute	Description
Name	Address-Details-IO
Datatype	
Description	

ADDRESS_CODE

Attribute	Description				
Name	ADDRESS_CODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MARK_FOR_EXPIRY

Attribute	Description				
Name	MARK_FOR_EXPIRY				
Datatype	String				
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Y,N</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

Attribute		Description	
Name	English		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

PIN_CODE

Attribute		Description	
Name	PIN_CODE		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	6	

Scpt-Add-Detail

Attribute		Description	
Name	Scpt-Add-Detail		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

SCRIPT_CODE

Attribute		Description	
Name	SCRIPT_CODE		
Datatype	String		
Description			
Restrictions	Restrictions		Description
	maxLength	8	

ADDR1

Attribute		Description	
Name	ADDR1		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	

Restrictions		
	Restrictions	Description
	maxLength	35

ADDR2

Attribute	Description	
Name	ADDR2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

ADDR3

Attribute	Description	
Name	ADDR3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	15

ADDRESS_CODE

Attribute	Description	
Name	ADDRESS_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	12

PREFECTURE

Attribute	Description	
Name	PREFECTURE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description
------------------	--------------------

Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.66.CreateCustChange

2.66.1.ST-CreateCustChange-Req-Full-MSG.xsd

CREATECUSTCHANGE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION
MULTIRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Addnl-Det-C-Full
TRNSFRREFNO
TRNSFRDT
TRNSFRDESC
TRNSFRSTAT
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Src-Cust-C
SRCCUSTNO
Trgt-Cust-C
TRGTCUSTNO
BRN_TRFR
Acc-Det
ACCTYPE
BRNCD
ACTNO

CNTNUEACCTDESC

CNTNUEACCNTADDR

NCDTRNSFRPRICE

ACCOUNTCCY

LINKEDACNO

SDREFRNO

CACCBRNCH

LIQ_INT

Acct-Lmt-Linkage

LNKTYP

CURRLINKREFNO

NEWLNKREFNO

AVAILABLE_AMT

Acct-Comm-Linkage

CMCURRCOMMREFNO

CMNEWCOMMREFNO

AVAILABLE_AMT

Validatn-Msgs

ACCTYPE

ACCCUSTNO

ERRCODE

ERRPARAMS

MSGTYPE

MESSAGE

CREATECUSTCHANGE_FSFS_REQ

Attribute	Description
Name	CREATECUSTCHANGE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Addtnl-Det-C-Full

Attribute	Description
Name	Addtnl-Det-C-Full
Datatype	
Description	

TRNSFRREFNO

Attribute	Description				
Name	TRNSFRREFNO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

TRNSFRDT

Attribute	Description				
Name	TRNSFRDT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

TRNSFRDESC

Attribute	Description				
Name	TRNSFRDESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	255

TRNSFRSTAT

Attribute	Description	
Name	TRNSFRSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	U,P,S,F,C

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

Src-Cust-C

Attribute	Description	
Name	Src-Cust-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

SRCCUSTNO

Attribute	Description	
Name	SRCCUSTNO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

Trgt-Cust-C

Attribute	Description	
Name	Trgt-Cust-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

TRGTCUSTNO

Attribute	Description	
Name	TRGTCUSTNO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

BRN_TRFR

Attribute	Description	
Name	BRN_TRFR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	Y,N

Acc-Det

Attribute	Description	
Name	Acc-Det	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCTYPE

Attribute	Description	
Name	ACCTYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	2

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

ACTNO

Attribute	Description	
Name	ACTNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	50

CNTNUEACCTDESC

Attribute	Description	
Name	CNTNUEACCTDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

CNTNUEACCNTADDR

Attribute	Description	
Name	CNTNUEACCNTADDR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

NCDTRNSFRPRICE

Attribute	Description	
Name	NCDTRNSFRPRICE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

ACCOUNTCCY

Attribute	Description	
Name	ACCOUNTCCY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	20

LINKEDACNO

Attribute	Description	
Name	LINKEDACNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	25

SDREFRNO

Attribute	Description	
Name	SDREFRNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	25

CACCBRNCH

Attribute	Description	
Name	CACCBRNCH	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

LIQ_INT

Attribute	Description	
Name	LIQ_INT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	Y,N

Acct-Lmt-Linkage

Attribute	Description	
Name	Acct-Lmt-Linkage	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

LNKTYP

Attribute	Description	
Name	LNKTYP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	T,C,U,F,P,

CURRLINKREFNO

Attribute	Description	
Name	CURRLINKREFNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

NEWLNKREFNO

Attribute	Description	
Name	NEWLNKREFNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

AVAILABLE_AMT

Attribute	Description	
Name	AVAILABLE_AMT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

Acct-Comm-Linkage

Attribute	Description	
Name	Acct-Comm-Linkage	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

CMCURRCOMMREFNO

Attribute	Description	
Name	CMCURRCOMMREFNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CMNEWCOMMREFNO

Attribute	Description	
Name	CMNEWCOMMREFNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

AVAILABLE_AMT

Attribute	Description	
Name	AVAILABLE_AMT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

Validatn-Msgs

Attribute	Description	
Name	Validatn-Msgs	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCTYPE

Attribute	Description	
Name	ACCTYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	2

ACCCUSTNO

Attribute	Description	
Name	ACCCUSTNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	50

ERRCODE

Attribute	Description	
Name	ERRCODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	11

ERRPARAMS

Attribute	Description	
Name	ERRPARAMS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

MSGTYPE

Attribute	Description	
Name	MSGTYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	E,I,O

MESSAGE

Attribute	Description	
Name	MESSAGE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1000

2.66.2.ST-CreateCustChange-Req-IO-MSG.xsd

CREATECUSTCHANGE_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Addtnl-Det-C-IO

TRNSFRREFNO

TRNSFRDT

TRNSFRDESC

Src-Cust-C

SRCCUSTNO

Trgt-Cust-C

TRGTCUSTNO

BRN_TRFR

Acc-Det

CNTNUEACCTDESC

CNTNUEACCNTADDR

NCDTRNSFRPRICE

CACCBRNCH

LIQ_INT

Acct-Lmt-Linkage

NEWLNKREFNO

Acct-Comm-Linkage

CMNEWCOMMREFNO

Validatn-Msgs

CREATECUSTCHANGE_IOPK_REQ

Attribute	Description
Name	CREATECUSTCHANGE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
-----------	-------------

Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Addnl-Det-C-IO
Datatype	
Description	

TRNSFRREFNO

Attribute	Description				
Name	TRNSFRREFNO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

TRNSFRDT

Attribute	Description				
Name	TRNSFRDT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

TRNSFRDESC

Attribute	Description				
Name	TRNSFRDESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>255</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

Src-Cust-C

Attribute	Description				
Name	Src-Cust-C				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SRCCUSTNO

Attribute	Description
Name	SRCCUSTNO
Datatype	String
Description	

Restrictions		
	Restrictions	Description
	maxLength	9

Trgt-Cust-C

Attribute	Description	
Name	Trgt-Cust-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

TRGTCUSTNO

Attribute	Description	
Name	TRGTCUSTNO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

BRN_TRFR

Attribute	Description	
Name	BRN_TRFR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

Acc-Det

Attribute	Description	
Name	Acc-Det	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

CNTNUEACCTDESC

Attribute	Description	
Name	CNTNUEACCTDESC	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

CNTNUEACCNTADDR

Attribute	Description	
Name	CNTNUEACCNTADDR	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

NCDTRNSFRPRICE

Attribute	Description	
Name	NCDTRNSFRPRICE	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

CACCBRNCH

Attribute	Description	
Name	CACCBRNCH	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

LIQ_INT

Attribute	Description	
Name	LIQ_INT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

Acct-Lmt-Linkage

Attribute	Description	
Name	Acct-Lmt-Linkage	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NEWLNKREFNO

Attribute	Description	
Name	NEWLNKREFNO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

Acct-Comm-Linkage

Attribute	Description	
Name	Acct-Comm-Linkage	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

CMNEWCOMMREFNO

Attribute	Description	
Name	CMNEWCOMMREFNO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

Validatn-Msgs

Attribute	Description						
Name	Validatn-Msgs						
Datatype							
Description							
Attribute							
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

2.66.3.ST-CreateCustChange-Res-Full-MSG.xsd

CREATECUSTCHANGE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Addnl-Det-C-Full

TRNSFRREFNO

TRNSFRDT

TRNSFRDESC

TRNSFRSTAT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Src-Cust-C

SRCCUSTNO

Trgt-Cust-C

TRGTCUSTNO

BRN_TRFR

Acc-Det

ACCTYPE

BRNCD

ACTNO

CNTNUEACCTDESC

CNTNUEACCNTADDR

NCDTRNSFRPRICE

ACCOUNTCCY

LINKEDACNO

SDREFRNO

CACCBRNCH

LIQ_INT

Acct-Lmt-Linkage

LNKTYP

CURRLINKREFNO

NEWLNKREFNO

AVAILABLE_AMT

Acct-Comm-Linkage

CMCURRCOMMREFNO

CMNEWCOMMREFNO

AVAILABLE_AMT

Validatn-Msgs

ACCTYPE

ACCCUSTNO

ERRCODE

ERRPARAMS

MSGTYPE

MESSAGE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATECUSTCHANGE_FSFS_RES

Attribute	Description
Name	CREATECUSTCHANGE_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Addtnl-Det-C-Full

Attribute	Description
Name	Addtnl-Det-C-Full
Datatype	
Description	

TRNSFRREFNO

Attribute	Description				
Name	TRNSFRREFNO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

TRNSFRDT

Attribute	Description				
Name	TRNSFRDT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

TRNSFRDESC

Attribute	Description				
Name	TRNSFRDESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	255

TRNSFRSTAT

Attribute	Description	
Name	TRNSFRSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	U,P,S,F,C

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

Src-Cust-C

Attribute	Description	
Name	Src-Cust-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

SRCCUSTNO

Attribute	Description	
Name	SRCCUSTNO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

Trgt-Cust-C

Attribute	Description	
Name	Trgt-Cust-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

TRGTCUSTNO

Attribute	Description	
Name	TRGTCUSTNO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

BRN_TRFR

Attribute	Description	
Name	BRN_TRFR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	Y,N

Acc-Det

Attribute	Description	
Name	Acc-Det	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCTYPE

Attribute	Description	
Name	ACCTYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	2

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

ACTNO

Attribute	Description	
Name	ACTNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	50

CNTNUEACCTDESC

Attribute	Description	
Name	CNTNUEACCTDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

CNTNUEACCNTADDR

Attribute	Description	
Name	CNTNUEACCNTADDR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

NCDTRNSFRPRICE

Attribute	Description	
Name	NCDTRNSFRPRICE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

ACCOUNTCCY

Attribute	Description	
Name	ACCOUNTCCY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	20

LINKEDACNO

Attribute	Description	
Name	LINKEDACNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	25

SDREFRNO

Attribute	Description	
Name	SDREFRNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	25

CACCBRNCH

Attribute	Description	
Name	CACCBRNCH	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

LIQ_INT

Attribute	Description	
Name	LIQ_INT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	Y,N

Acct-Lmt-Linkage

Attribute	Description	
Name	Acct-Lmt-Linkage	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

LNKTYP

Attribute	Description	
Name	LNKTYP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	T,C,U,F,P,

CURRLINKREFNO

Attribute	Description	
Name	CURRLINKREFNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

NEWLNKREFNO

Attribute	Description	
Name	NEWLNKREFNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

AVAILABLE_AMT

Attribute	Description	
Name	AVAILABLE_AMT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

Acct-Comm-Linkage

Attribute	Description	
Name	Acct-Comm-Linkage	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

CMCURRCOMMREFNO

Attribute	Description	
Name	CMCURRCOMMREFNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CMNEWCOMMREFNO

Attribute	Description	
Name	CMNEWCOMMREFNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

AVAILABLE_AMT

Attribute	Description	
Name	AVAILABLE_AMT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

Validatn-Msgs

Attribute	Description	
Name	Validatn-Msgs	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCTYPE

Attribute	Description	
Name	ACCTYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	2

ACCCUSTNO

Attribute	Description	
Name	ACCCUSTNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	50

ERRCODE

Attribute	Description	
Name	ERRCODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	11

ERRPARAMS

Attribute	Description	
Name	ERRPARAMS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

MSGTYPE

Attribute	Description	
Name	MSGTYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	E,I,O

MESSAGE

Attribute	Description	
Name	MESSAGE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1000

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.66.4.ST-CreateCustChange-Res-PK-MSG.xsd

CREATECUSTCHANGE_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Addtnl-Det-C-PK

TRNSFRREFNO

Addtnl-Det-C-IO

TRNSFRREFNO

TRNSFRDT

TRNSFRDESC

Src-Cust-C

SRCCUSTNO

Trgt-Cust-C

TRGTCUSTNO

BRN_TRFR

Acc-Det

CNTNUEACCTDESC

CNTNUEACCNTADDR

NCDTRNSFRPRICE

CACCBRNCH

LIQ_INT

Acct-Lmt-Linkage

NEWLNKREFNO

Acct-Comm-Linkage

CMNEWCOMMREFNO

Validatn-Msgs

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATECUSTCHANGE_IOPK_RES

Attribute	Description
Name	CREATECUSTCHANGE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute		Description	
Name	SOURCE_USERID		
Datatype	String		
Description	This is the user id in the Source system who is performing the action.		
Attribute	Attribute		Description
	minOccurs	0	

DESTINATION

Attribute		Description	
Name	DESTINATION		
Datatype	String		
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute		Description	
Name	MULTITRIPID		
Datatype	String		
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute		Description	
Name	FUNCTIONID		
Datatype	String		
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.		
Attribute	Attribute		Description
	minOccurs	0	

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Addtl-Det-C-PK

Attribute	Description
Name	Addtl-Det-C-PK
Datatype	
Description	

TRNSFRREFNO

Attribute	Description				
Name	TRNSFRREFNO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

Addtl-Det-C-IO

Attribute	Description
-----------	-------------

Name	Addtnl-Det-C-IO
Datatype	
Description	

TRNSFRREFNO

Attribute	Description	
Name	TRNSFRREFNO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

TRNSFRDT

Attribute	Description	
Name	TRNSFRDT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

TRNSFRDESC

Attribute	Description	
Name	TRNSFRDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

Src-Cust-C

Attribute	Description	
Name	Src-Cust-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

SRCCUSTNO

Attribute	Description	
Name	SRCCUSTNO	
Datatype	String	
Description		

Restrictions		
	Restrictions	Description
	maxLength	9

Trgt-Cust-C

Attribute	Description	
Name	Trgt-Cust-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

TRGTCUSTNO

Attribute	Description	
Name	TRGTCUSTNO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

BRN_TRFR

Attribute	Description	
Name	BRN_TRFR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

Acc-Det

Attribute	Description	
Name	Acc-Det	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

CNTNUEACCTDESC

Attribute	Description	
Name	CNTNUEACCTDESC	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

CNTNUEACCNTADDR

Attribute	Description	
Name	CNTNUEACCNTADDR	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

NCDTRNSFRPRICE

Attribute	Description	
Name	NCDTRNSFRPRICE	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

CACCBRNCH

Attribute	Description	
Name	CACCBRNCH	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

LIQ_INT

Attribute	Description	
Name	LIQ_INT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

Acct-Lmt-Linkage

Attribute	Description	
Name	Acct-Lmt-Linkage	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NEWLNKREFNO

Attribute	Description	
Name	NEWLNKREFNO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

Acct-Comm-Linkage

Attribute	Description	
Name	Acct-Comm-Linkage	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

CMNEWCOMMREFNO

Attribute	Description	
Name	CMNEWCOMMREFNO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

Validatn-Msgs

Attribute	Description	
Name	Validatn-Msgs	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.67.DeleteAddressCode

2.67.1.ST-DeleteAddressCode-Req-Full-MSG.xsd

DELETEADDRESSCODE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Address-Details-Full

ADDRESS_CODE

MARK_FOR_EXPIRY

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Kanji

English

PIN_CODE

Katakana

Script-Add-Detail

SCRIPT_CODE

ADDR1

ADDR2

ADDR3

PIN_CODE

ADDRESS_CODE

PREFECTURE

DELETEADDRESSCODE_FSFS_REQ

Attribute	Description
Name	DELETEADDRESSCODE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute		Description	
Name	SOURCE_USERID		
Datatype	String		
Description	This is the user id in the Source system who is performing the action.		
Attribute	Attribute		Description
	minOccurs	0	

DESTINATION

Attribute		Description	
Name	DESTINATION		
Datatype	String		
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute		Description	
Name	MULTITRIPID		
Datatype	String		
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute		Description	
Name	FUNCTIONID		
Datatype	String		
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.		
Attribute	Attribute		Description
	minOccurs	0	

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Address-Details-Full

Attribute	Description
Name	Address-Details-Full
Datatype	
Description	

ADDRESS_CODE

Attribute	Description				
Name	ADDRESS_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MARK_FOR_EXPIRY

Attribute	Description
-----------	-------------

Name	MARK_FOR_EXPIRY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description
------------------	--------------------

Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

Kanji

Attribute	Description
------------------	--------------------

Name	Kanji	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

English

Attribute	Description	
Name	English	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	6

Katakana

Attribute	Description	
Name	Katakana	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Scpt-Add-Detail

Attribute	Description	
Name	Scpt-Add-Detail	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

SCRIPT_CODE

Attribute	Description
------------------	--------------------

Name	SCRIPT_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	8

ADDR1

Attribute	Description	
Name	ADDR1	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

ADDR2

Attribute	Description	
Name	ADDR2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

ADDR3

Attribute	Description	
Name	ADDR3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

ADDRESS_CODE

Attribute	Description	
Name	ADDRESS_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

PREFECTURE

Attribute	Description	
Name	PREFECTURE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

2.67.2.ST-DeleteAddressCode-Req-IO-MSG.xsd

DELETEADDRESSCODE_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Address-Details-IO

ADDRESS_CODE

DELETEADDRESSCODE_IOPK_REQ

Attribute	Description
Name	DELETEADDRESSCODE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
-----------	-------------

Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Address-Details-IO
Datatype	
Description	

ADDRESS_CODE

Attribute	Description				
Name	ADDRESS_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

2.67.3.ST-DeleteAddressCode-Res-Full-MSG.xsd

DELETEADDRESSCODE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Address-Details-Full

ADDRESS_CODE

MARK_FOR_EXPIRY

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Kanji

English

PIN_CODE

Katakana

Scrp-Add-Detail

SCRIPT_CODE

ADDR1

ADDR2

ADDR3

PIN_CODE

ADDRESS_CODE

PREFECTURE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

Attribute	Description
Name	DELETEADDRESSCODE_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	

Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

FCUBS_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description			

Address-Details-Full

Attribute		Description	
Name	Address-Details-Full		
Datatype			
Description			

ADDRESS_CODE

Attribute		Description	
Name	ADDRESS_CODE		
Datatype	String		
Description			
Restrictions	Restrictions		Description
	maxLength	12	

MARK_FOR_EXPIRY

Attribute		Description	
Name	MARK_FOR_EXPIRY		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	

Restrictions		
	Restrictions	Description
	enumeration	Y,N

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Kanji

Attribute	Description	
Name	Kanji	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

English

Attribute	Description				
Name	English				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PIN_CODE

Attribute	Description				
Name	PIN_CODE				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>6</td></tr></tbody></table>	Restrictions	Description	maxLength	6
Restrictions	Description				
maxLength	6				

Katakana

Attribute	Description				
Name	Katakana				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Scpt-Add-Detail

Attribute	Description						
Name	Scpt-Add-Detail						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

SCRIPT_CODE

Attribute	Description				
Name	SCRIPT_CODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr></tbody></table>	Restrictions	Description	maxLength	8
Restrictions	Description				
maxLength	8				

Attribute		Description	
Name	ADDR1		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

ADDR2

Attribute		Description	
Name	ADDR2		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

ADDR3

Attribute		Description	
Name	ADDR3		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

PIN_CODE

Attribute		Description	
Name	PIN_CODE		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	15	

ADDRESS_CODE

Attribute	Description	
Name	ADDRESS_CODE	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	12
	Description	

PREFECTURE

Attribute	Description	
Name	PREFECTURE	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	105
	Description	

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	
	maxOccurs	unbounded
	Description	

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.67.4.ST-DeleteAddressCode-Res-PK-MSG.xsd

DELETEADDRESSCODE_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Address-Details-PK

ADDRESS_CODE

Address-Details-IO

ADDRESS_CODE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEADDRESSCODE_IOPK_RES

Attribute	Description
Name	DELETEADDRESSCODE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Address-Details-PK

Attribute	Description
Name	Address-Details-PK
Datatype	
Description	

ADDRESS_CODE

Attribute	Description				
Name	ADDRESS_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

Address-Details-IO

Attribute	Description
Name	Address-Details-IO
Datatype	
Description	

ADDRESS_CODE

Attribute	Description				
Name	ADDRESS_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

FCUBS_ERROR_RESP

Attribute	Description
-----------	-------------

Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	
	Description	
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	
	Description	
	maxOccurs	unbounded

WCODE

Attribute	Description
------------------	--------------------

Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.68.DeleteCustChange

2.68.1.ST-DeleteCustChange-Req-Full-MSG.xsd

DELETECUSTCHANGE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Addtnl-Det-C-Full

TRNSFRREFNO
TRNSFRDRT
TRNSFRDESC
TRNSFRSTAT
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Src-Cust-C
SRCCUSTNO
Trgt-Cust-C
TRGTCUSTNO
BRN_TRFR
Acc-Det
ACCTYPE
BRNCD
ACTNO
CNTNUEACCTDESC
CNTNUEACCNTADDR
NCDTRNSFRPRICE
ACCOUNTCCY
LINKEDACNO
SDREFRNO
CACCBRNCH
LIQ_INT
Acct-Lmt-Linkage
LNKTYP
CURRLINKREFNO
NEWLNKREFNO

AVAILABLE_AMT

Acct-Comm-Linkage

CMCURRCOMMREFNO

CMNEWCOMMREFNO

AVAILABLE_AMT

Validatn-Msgs

ACCTYPE

ACCCUSTNO

ERRCODE

ERRPARAMS

MSGTYPE

MESSAGE

DELETECUSTCHANGE_FSFS_REQ

Attribute	Description
Name	DELETECUSTCHANGE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Addnl-Det-C-Full

Attribute		Description
------------------	--	--------------------

Name	Addtnl-Det-C-Full
Datatype	
Description	

TRNSFRREFNO

Attribute	Description	
Name	TRNSFRREFNO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

TRNSFRDT

Attribute	Description	
Name	TRNSFRDT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

TRNSFRDESC

Attribute	Description	
Name	TRNSFRDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TRNSFRSTAT

Attribute	Description	
Name	TRNSFRSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	U,P,S,F,C

MAKER

Attribute	Description
Name	MAKER

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description
Name	MODNO

Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Src-Cust-C

Attribute	Description	
Name	Src-Cust-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

SRCCUSTNO

Attribute	Description	
Name	SRCCUSTNO	
Datatype	String	
Description		

Restrictions		
	Restrictions	Description
	maxLength	9

Trgt-Cust-C

Attribute	Description	
Name	Trgt-Cust-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

TRGTCUSTNO

Attribute	Description	
Name	TRGTCUSTNO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

BRN_TRFR

Attribute	Description	
Name	BRN_TRFR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

Acc-Det

Attribute	Description	
Name	Acc-Det	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCTYPE

Attribute	Description	
Name	ACCTYPE	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	2

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

ACTNO

Attribute	Description	
Name	ACTNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	50

CNTNUEACCTDESC

Attribute	Description	
Name	CNTNUEACCTDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

CNTNUEACCNTADDR

Attribute	Description	
Name	CNTNUEACCNTADDR	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

NCDTRNSFRPRICE

Attribute	Description	
Name	NCDTRNSFRPRICE	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

ACCOUNTCCY

Attribute	Description	
Name	ACCOUNTCCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

LINKEDACNO

Attribute	Description	
Name	LINKEDACNO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

SDREFRNO

Attribute	Description	
Name	SDREFRNO	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	25

CACCBRNCH

Attribute	Description	
Name	CACCBRNCH	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

LIQ_INT

Attribute	Description	
Name	LIQ_INT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

Acct-Lmt-Linkage

Attribute	Description	
Name	Acct-Lmt-Linkage	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

LNKTYP

Attribute	Description	
Name	LNKTYP	
Datatype	String	
Description		

Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	enumeration	T,C,U,F,P,
	Description	

CURRLINKREFNO

Attribute		Description
Name	CURRLINKREFNO	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	35
	Description	

NEWLNKREFNO

Attribute		Description
Name	NEWLNKREFNO	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	35
	Description	

AVAILABLE_AMT

Attribute		Description
Name	AVAILABLE_AMT	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	1000
	Description	

Acct-Comm-Linkage

Attribute		Description
Name	Acct-Comm-Linkage	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

CMCURRCOMMREFNO

Attribute	Description	
Name	CMCURRCOMMREFNO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CMNEWCOMMREFNO

Attribute	Description	
Name	CMNEWCOMMREFNO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

AVAILABLE_AMT

Attribute	Description	
Name	AVAILABLE_AMT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

Validatn-Msgs

Attribute	Description	
Name	Validatn-Msgs	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCTYPE

Attribute	Description	
Name	ACCTYPE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2

ACCCUSTNO

Attribute	Description	
Name	ACCCUSTNO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

ERRCODE

Attribute	Description	
Name	ERRCODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

ERRPARAMS

Attribute	Description	
Name	ERRPARAMS	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

MSGTYPE

Attribute	Description	
Name	MSGTYPE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	E,I,O

MESSAGE

Attribute	Description	
Name	MESSAGE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

2.68.2.ST-DeleteCustChange-Req-IO-MSG.xsd

DELETECUSTCHANGE_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Addnl-Det-C-IO

TRNSFRREFNO

DELETECUSTCHANGE_IOPK_REQ

Attribute	Description
Name	DELETECUSTCHANGE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
-----------	-------------

Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Addtnl-Det-C-IO
Datatype	
Description	

TRNSFRREFNO

Attribute	Description				
Name	TRNSFRREFNO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

2.68.3.ST-DeleteCustChange-Res-Full-MSG.xsd

DELETECUSTCHANGE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Addnl-Det-C-Full

TRNSFRREFNO

TRNSFRDT

TRNSFRDESC

TRNSFRSTAT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Src-Cust-C

SRCCUSTNO

Trgt-Cust-C

TRGTCUSTNO

BRN_TRFR

Acc-Det

ACCTYPE

BRNCD

ACTNO

CNTNUEACCTDESC

CNTNUEACCNTADDR

NCDTRNSFRPRICE

ACCOUNTCCY

LINKEDACNO

SDREFRNO

CACCBRNCH

LIQ_INT

Acct-Lmt-Linkage

LNKTYP

CURRLINKREFNO

NEWLNKREFNO

AVAILABLE_AMT

Acct-Comm-Linkage

CMCURRCOMMREFNO

CMNEWCOMMREFNO

AVAILABLE_AMT

Validatn-Msgs

ACCTYPE

ACCCUSTNO

ERRCODE

ERRPARAMS

MSGTYPE

MESSAGE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETECUSTCHANGE_FSFS_RES

Attribute	Description
Name	DELETECUSTCHANGE_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Addtnl-Det-C-Full

Attribute	Description
Name	Addtnl-Det-C-Full
Datatype	
Description	

TRNSFRREFNO

Attribute	Description				
Name	TRNSFRREFNO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

TRNSFRDT

Attribute	Description				
Name	TRNSFRDT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

TRNSFRDESC

Attribute	Description				
Name	TRNSFRDESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	255

TRNSFRSTAT

Attribute	Description	
Name	TRNSFRSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	U,P,S,F,C

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

Src-Cust-C

Attribute	Description	
Name	Src-Cust-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

SRCCUSTNO

Attribute	Description	
Name	SRCCUSTNO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

Trgt-Cust-C

Attribute	Description	
Name	Trgt-Cust-C	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

TRGTCUSTNO

Attribute	Description	
Name	TRGTCUSTNO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

BRN_TRFR

Attribute	Description	
Name	BRN_TRFR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	Y,N

Acc-Det

Attribute	Description	
Name	Acc-Det	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCTYPE

Attribute	Description	
Name	ACCTYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	2

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

ACTNO

Attribute	Description	
Name	ACTNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	50

CNTNUEACCTDESC

Attribute	Description	
Name	CNTNUEACCTDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

CNTNUEACCNTADDR

Attribute	Description	
Name	CNTNUEACCNTADDR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

NCDTRNSFRPRICE

Attribute	Description	
Name	NCDTRNSFRPRICE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

ACCOUNTCCY

Attribute	Description	
Name	ACCOUNTCCY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	20

LINKEDACNO

Attribute	Description	
Name	LINKEDACNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	25

SDREFRNO

Attribute	Description	
Name	SDREFRNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	25

CACCBRNCH

Attribute	Description	
Name	CACCBRNCH	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

LIQ_INT

Attribute	Description	
Name	LIQ_INT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	Y,N

Acct-Lmt-Linkage

Attribute	Description	
Name	Acct-Lmt-Linkage	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

LNKTYP

Attribute	Description	
Name	LNKTYP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	T,C,U,F,P,

CURRLINKREFNO

Attribute	Description	
Name	CURRLINKREFNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

NEWLNKREFNO

Attribute	Description	
Name	NEWLNKREFNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

AVAILABLE_AMT

Attribute	Description	
Name	AVAILABLE_AMT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

Acct-Comm-Linkage

Attribute	Description	
Name	Acct-Comm-Linkage	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

CMCURRCOMMREFNO

Attribute	Description	
Name	CMCURRCOMMREFNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CMNEWCOMMREFNO

Attribute	Description	
Name	CMNEWCOMMREFNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

AVAILABLE_AMT

Attribute	Description	
Name	AVAILABLE_AMT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

Validatn-Msgs

Attribute	Description	
Name	Validatn-Msgs	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCTYPE

Attribute	Description	
Name	ACCTYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	2

ACCCUSTNO

Attribute	Description	
Name	ACCCUSTNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	50

ERRCODE

Attribute	Description	
Name	ERRCODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	11

ERRPARAMS

Attribute	Description	
Name	ERRPARAMS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

MSGTYPE

Attribute	Description	
Name	MSGTYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	E,I,O

MESSAGE

Attribute	Description	
Name	MESSAGE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1000

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		

Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.68.4.ST-DeleteCustChange-Res-PK-MSG.xsd

DELETECUSTCHANGE_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Addtl-Det-C-PK

TRNSFRREFNO

Addtl-Det-C-IO

TRNSFRREFNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETECUSTCHANGE_IOPK_RES

Attribute	Description
Name	DELETECUSTCHANGE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Addnl-Det-C-PK
Datatype	
Description	

TRNSFRREFNO

Attribute	Description				
Name	TRNSFRREFNO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

Addnl-Det-C-IO

Attribute	Description
Name	Addnl-Det-C-IO
Datatype	
Description	

TRNSFRREFNO

Attribute	Description				
Name	TRNSFRREFNO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

FCUBS_ERROR_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

ECODE

Attribute	Description
-----------	-------------

Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.69.ModifyAddressCode

2.69.1.ST-ModifyAddressCode-Req-Full-MSG.xsd

MODIFYADDRESSCODE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Address-Details-Full
ADDRESS_CODE
MARK_FOR_EXPIRY
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Kanji
English
PIN_CODE

Katakana

Script-Add-Detail

SCRIPT_CODE

ADDR1

ADDR2

ADDR3

PIN_CODE

ADDRESS_CODE

PREFECTURE

MODIFYADDRESSCODE_FSFS_REQ

Attribute	Description
Name	MODIFYADDRESSCODE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Address-Details-Full

Attribute	Description	
Name	Address-Details-Full	
Datatype		
Description		

ADDRESS_CODE

Attribute	Description				
Name	ADDRESS_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

MARK_FOR_EXPIRY

Attribute	Description				
Name	MARK_FOR_EXPIRY				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>	Restrictions	Description	enumeration	Y,N
	Restrictions	Description			
enumeration	Y,N				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
	Restrictions	Description			
maxLength	35				

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Kanji

Attribute	Description	
Name	Kanji	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

English

Attribute	Description	
Name	English	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	6

Katakana

Attribute	Description	
Name	Katakana	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Scrt-Add-Detail

Attribute	Description	
Name	Scrp-Add-Detail	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

SCRIPT_CODE

Attribute	Description	
Name	SCRIPT_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	8

ADDR1

Attribute	Description	
Name	ADDR1	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

ADDR2

Attribute	Description	
Name	ADDR2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

ADDR3

Attribute	Description	
Name	ADDR3	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

ADDRESS_CODE

Attribute	Description	
Name	ADDRESS_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

PREFECTURE

Attribute	Description	
Name	PREFECTURE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

2.69.2.ST-ModifyAddressCode-Req-IO-MSG.xsd

[MODIFYADDRESSCODE_IOPK_REQ](#)

[FCUBS_HEADER](#)

[SOURCE](#)

UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Address-Details-IO
ADDRESS_CODE
MARK_FOR_EXPIRY
MAKER
MAKERSTAMP
English
ADDR2
ADDRESS_LINE3
ADDRESS_LINE4
PIN_CODE
Scrp-Add-Detail

SCRIPT_CODE

ADDR1

ADDR2

ADDR3

PIN_CODE

ADDRESS_CODE

PREFECTURE

MODIFYADDRESSCODE_IOPK_REQ

Attribute	Description
Name	MODIFYADDRESSCODE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
-----------	-------------

Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Address-Details-IO

Attribute	Description
Name	Address-Details-IO
Datatype	
Description	

ADDRESS_CODE

Attribute	Description
------------------	--------------------

Name	ADDRESS_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	12

MARK_FOR_EXPIRY

Attribute	Description	
Name	MARK_FOR_EXPIRY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

English

Attribute	Description	
Name	English	
Datatype		
Description		

Attribute		
	Attribute	Description
	minOccurs	0

ADDR2

Attribute	Description	
Name	ADDR2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

ADDRESS_LINE3

Attribute	Description	
Name	ADDRESS_LINE3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

ADDRESS_LINE4

Attribute	Description	
Name	ADDRESS_LINE4	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	6

Scpt-Add-Detail

Attribute	Description	
Name	Scpt-Add-Detail	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

SCRIPT_CODE

Attribute	Description	
Name	SCRIPT_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	8

ADDR1

Attribute	Description	
Name	ADDR1	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

ADDR2

Attribute	Description	
Name	ADDR2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

ADDR3

Attribute	Description
------------------	--------------------

Name	ADDR3	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

ADDRESS_CODE

Attribute	Description	
Name	ADDRESS_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

PREFECTURE

Attribute	Description	
Name	PREFECTURE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

2.69.3.ST-ModifyAddressCode-Res-Full-MSG.xsd

MODIFYADDRESSCODE_FSFS_RES

FCUBS_HEADER

SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Address-Details-Full
ADDRESS_CODE
MARK_FOR_EXPIRY
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT

Kanji

English

PIN_CODE

Katakana

Scrp-Add-Detail

SCRIPT_CODE

ADDR1

ADDR2

ADDR3

PIN_CODE

ADDRESS_CODE

PREFECTURE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYADDRESSCODE_FSFS_RES

Attribute	Description
Name	MODIFYADDRESSCODE_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Address-Details-Full

Attribute	Description
Name	Address-Details-Full
Datatype	
Description	

ADDRESS_CODE

Attribute	Description				
Name	ADDRESS_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MARK_FOR_EXPIRY

Attribute	Description				
Name	MARK_FOR_EXPIRY				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Y,N</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Kanji

Attribute	Description	
Name	Kanji	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

English

Attribute	Description	
Name	English	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

Katakana

Attribute	Description	
Name	Katakana	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

Scpt-Add-Detail

Attribute	Description	
Name	Scpt-Add-Detail	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

SCRIPT_CODE

Attribute	Description	
Name	SCRIPT_CODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	8

ADDR1

Attribute	Description	
Name	ADDR1	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

ADDR2

Attribute	Description	
Name	ADDR2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

ADDR3

Attribute	Description	
Name	ADDR3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	15

ADDRESS_CODE

Attribute	Description	
Name	ADDRESS_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	12

PREFECTURE

Attribute	Description	
Name	PREFECTURE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description
------------------	--------------------

Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.69.4.ST-ModifyAddressCode-Res-PK-MSG.xsd

MODIFYADDRESSCODE_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Address-Details-PK

ADDRESS_CODE

Address-Details-IO

ADDRESS_CODE

MARK_FOR_EXPIRY

MAKER

MAKERSTAMP

English

ADDR2

ADDRESS_LINE3

ADDRESS_LINE4

PIN_CODE

Script-Add-Detail

SCRIPT_CODE

ADDR1

ADDR2

ADDR3

PIN_CODE

ADDRESS_CODE

PREFECTURE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYADDRESSCODE_IOPK_RES

Attribute	Description
Name	MODIFYADDRESSCODE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Address-Details-PK

Attribute	Description
Name	Address-Details-PK
Datatype	
Description	

ADDRESS_CODE

Attribute	Description
------------------	--------------------

Name	ADDRESS_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	12

Address-Details-IO

Attribute	Description	
Name	Address-Details-IO	
Datatype		
Description		

ADDRESS_CODE

Attribute	Description	
Name	ADDRESS_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	12

MARK_FOR_EXPIRY

Attribute	Description	
Name	MARK_FOR_EXPIRY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

English

Attribute	Description	
Name	English	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

ADDR2

Attribute	Description	
Name	ADDR2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

ADDRESS_LINE3

Attribute	Description	
Name	ADDRESS_LINE3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

ADDRESS_LINE4

Attribute	Description	
Name	ADDRESS_LINE4	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

Scpt-Add-Detail

Attribute	Description	
Name	Scpt-Add-Detail	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

SCRIPT_CODE

Attribute	Description	
Name	SCRIPT_CODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	8

ADDR1

Attribute	Description	
Name	ADDR1	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

ADDR2

Attribute	Description	
Name	ADDR2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

ADDR3

Attribute	Description	
Name	ADDR3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	15

ADDRESS_CODE

Attribute	Description	
Name	ADDRESS_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	12

PREFECTURE

Attribute	Description	
Name	PREFECTURE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description
------------------	--------------------

Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.70.QueryAddressCode

2.70.1.ST-QueryAddressCode-Req-IO-MSG.xsd

[*QUERYADDRESSCODE_IOFS_REQ*](#)

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Address-Details-IO

ADDRESS_CODE

QUERYADDRESSCODE_IOFS_REQ

Attribute	Description
Name	QUERYADDRESSCODE_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Address-Details-IO

Attribute	Description
------------------	--------------------

Name	Address-Details-IO
Datatype	
Description	

ADDRESS_CODE

Attribute	Description	
Name	ADDRESS_CODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12

2.70.2.ST-QueryAddressCode-Res-Full-MSG.xsd

QUERYADDRESSCODE_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Address-Details-IO

ADDRESS_CODE

Address-Details-Full

ADDRESS_CODE

MARK_FOR_EXPIRY

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Kanji

English

PIN_CODE

Katakana

Scrp-Add-Detail

SCRIPT_CODE

ADDR1

ADDR2

ADDR3

PIN_CODE

ADDRESS_CODE

PREFECTURE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYADDRESSCODE_IOFS_RES

Attribute	Description
Name	QUERYADDRESSCODE_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute		Description	
Name	SOURCE_USERID		
Datatype	String		
Description	This is the user id in the Source system who is performing the action.		
Attribute	Attribute		Description
	minOccurs	0	

DESTINATION

Attribute		Description	
Name	DESTINATION		
Datatype	String		
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute		Description	
Name	MULTITRIPID		
Datatype	String		
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute		Description	
Name	FUNCTIONID		
Datatype	String		
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.		
Attribute	Attribute		Description
	minOccurs	0	

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Address-Details-IO

Attribute	Description
Name	Address-Details-IO
Datatype	
Description	

ADDRESS_CODE

Attribute	Description				
Name	ADDRESS_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

Address-Details-Full

Attribute	Description
-----------	-------------

Name	Address-Details-Full
Datatype	
Description	

ADDRESS_CODE

Attribute	Description	
Name	ADDRESS_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	12

MARK_FOR_EXPIRY

Attribute	Description	
Name	MARK_FOR_EXPIRY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Kanji

Attribute	Description	
Name	Kanji	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

English

Attribute	Description	
Name	English	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	6

Katakana

Attribute	Description	
Name	Katakana	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Scrt-Add-Detail

Attribute	Description						
Name	Scrt-Add-Detail						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

SCRIPT_CODE

Attribute	Description				
Name	SCRIPT_CODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr></tbody></table>	Restrictions	Description	maxLength	8
Restrictions	Description				
maxLength	8				

ADDR1

Attribute	Description				
Name	ADDR1				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

ADDR2

Attribute	Description				
Name	ADDR2				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	15

ADDRESS_CODE

Attribute	Description	
Name	ADDRESS_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

PREFECTURE

Attribute	Description	
Name	PREFECTURE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.71.QueryCntryCodes

2.71.1.ST-QueryCntryCodes-Req-IO-MSG.xsd

QUERYCNTRYCODES_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Stcntry-IO

CNTRYCD

Attribute	Description
Name	QUERYCNTRYCODES_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	

Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Stcntry-IO

Attribute	Description	
Name	Stcntry-IO	
Datatype		
Description		

CNTRYCD

Attribute	Description	
Name	CNTRYCD	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	3

2.71.2.ST-QueryCntryCodes-Res-Full-MSG.xsd

[*QUERYCNTRYCODES_IOFS_RES*](#)

[*FCUBS_HEADER*](#)

[*SOURCE*](#)

[*UBSCOMP*](#)

[*MSGID*](#)

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Stentry-IO
CNTRYCD
Stentry-Full
CNTRYCD
COUNTRY_NAME
ALT_COUNTRY_CODE
BLACKLISTED
LIMIT_CCY
OVERALL_LIMIT
IBAN_CHECK_REQD
INTRA_EUROPEAN
CLR_CODE_BIC
CLEAR_NETWORK

ISO_COUNTRY_CODE

GEN_MT205

ISD_CODE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYCNTRYCODES_IOFS_RES

Attribute	Description
Name	QUERYCNTRYCODES_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages this field has to contain the source code for the partner system as maintained within EL EXCLUDE UBS. In

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Stcntry-IO

Attribute	Description
Name	Stcntry-IO
Datatype	
Description	

CNTRYCD

Attribute	Description				
Name	CNTRYCD				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

Stcntry-Full

Attribute	Description
Name	Stcntry-Full
Datatype	
Description	

CNTRYCD

Attribute	Description				
Name	CNTRYCD				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

COUNTRY_NAME

Attribute	Description
-----------	-------------

Name	COUNTRY_NAME	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

ALT_COUNTRY_CODE

Attribute	Description	
Name	ALT_COUNTRY_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

BLACKLISTED

Attribute	Description	
Name	BLACKLISTED	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

LIMIT_CCY

Attribute	Description	
Name	LIMIT_CCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

OVERALL_LIMIT

Attribute	Description
------------------	--------------------

Name	OVERALL_LIMIT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22
	minInclusive	0.000

IBAN_CHECK_REQD

Attribute	Description	
Name	IBAN_CHECK_REQD	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	Y,N

INTRA_EUROPEAN

Attribute	Description	
Name	INTRA_EUROPEAN	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

CLR_CODE_BIC

Attribute	Description	
Name	CLR_CODE_BIC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

CLEAR_NETWORK

Attribute	Description	
Name	CLEAR_NETWORK	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	6

ISO_COUNTRY_CODE

Attribute	Description	
Name	ISO_COUNTRY_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

GEN_MT205

Attribute	Description	
Name	GEN_MT205	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

ISD_CODE

Attribute	Description	
Name	ISD_CODE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	10

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.72.QueryCustChange

2.72.1.ST-QueryCustChange-Req-IO-MSG.xsd

QUERYCUSTCHANGE_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Addtl-Det-C-IO

TRNSFRREFNO

QUERYCUSTCHANGE_IOFS_REQ

Attribute	Description
Name	QUERYCUSTCHANGE_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

MSGID

Attribute	Description					
Name	MSGID					
Datatype	String					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	String					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Addtnl-Det-C-IO
Datatype	
Description	

TRNSFRREFNO

Attribute	Description				
Name	TRNSFRREFNO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

2.72.2.ST-QueryCustChange-Res-Full-MSG.xsd

QUERYCUSTCHANGE_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Addtl-Det-C-IO

TRNSFRREFNO

Addtl-Det-C-Full

TRNSFRREFNO

TRNSFRDT

TRNSFRDESC

TRNSFRSTAT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Src-Cust-C

SRCCUSTNO

Trgt-Cust-C

TRGTCUSTNO

BRN_TRFR

Acc-Det

ACCTYPE

BRNCD

ACTNO

CNTNUEACCTDESC

CNTNUEACCNTADDR

NCDTRNSFRPRICE

ACCOUNTCCY

LINKEDACNO

SDREFRNO

CACCBRNCH

LIQ_INT

Acct-Lmt-Linkage

LNKTYP

CURRLINKREFNO

NEWLNKREFNO

AVAILABLE_AMT

Acct-Comm-Linkage

CMCURRCOMMREFNO

CMNEWCOMMREFNO

AVAILABLE_AMT

Validatn-Msgs

ACCTYPE

ACCCUSTNO

ERRCODE

ERRPARAMS

MSGTYPE

MESSAGE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYCUSTCHANGE_IOFS_RES

Attribute	Description
Name	QUERYCUSTCHANGE_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Addtnl-Det-C-IO

Attribute	Description
Name	Addtnl-Det-C-IO
Datatype	
Description	

TRNSFRREFNO

Attribute	Description				
Name	TRNSFRREFNO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

Addtnl-Det-C-Full

Attribute	Description
Name	Addtnl-Det-C-Full
Datatype	
Description	

TRNSFRREFNO

Attribute	Description				
Name	TRNSFRREFNO				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

TRNSFRDT

Attribute	Description
-----------	-------------

Name	TRNSFRDT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

TRNSFRDESC

Attribute	Description	
Name	TRNSFRDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

TRNSFRSTAT

Attribute	Description	
Name	TRNSFRSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	U,P,S,F,C

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

Src-Cust-C

Attribute	Description	
Name	Src-Cust-C	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

SRCCUSTNO

Attribute	Description	
Name	SRCCUSTNO	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	9

Trgt-Cust-C

Attribute	Description	
Name	Trgt-Cust-C	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

TRGTCUSTNO

Attribute	Description
------------------	--------------------

Name	TRGTCUSTNO	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

BRN_TRFR

Attribute	Description	
Name	BRN_TRFR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

Acc-Det

Attribute	Description	
Name	Acc-Det	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCTYPE

Attribute	Description	
Name	ACCTYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	2

BRNCD

Attribute	Description	
Name	BRNCD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	3

ACTNO

Attribute	Description	
Name	ACTNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	50

CNTNUEACCTDESC

Attribute	Description	
Name	CNTNUEACCTDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

CNTNUEACCNTADDR

Attribute	Description	
Name	CNTNUEACCNTADDR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

NCDTRNSFRPRICE

Attribute	Description	
Name	NCDTRNSFRPRICE	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	22

ACCOUNTCCY

Attribute	Description	
Name	ACCOUNTCCY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	20

LINKEDACNO

Attribute	Description	
Name	LINKEDACNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	25

SDREFRNO

Attribute	Description	
Name	SDREFRNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	25

CACCBRNCH

Attribute	Description	
Name	CACCBRNCH	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1000

LIQ_INT

Attribute	Description	
Name	LIQ_INT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

Acct-Lmt-Linkage

Attribute	Description	
Name	Acct-Lmt-Linkage	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

LNKTYP

Attribute	Description	
Name	LNKTYP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	T,C,U,F,P,

CURRLINKREFNO

Attribute	Description	
Name	CURRLINKREFNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

NEWLNKREFNO

Attribute	Description	
Name	NEWLNKREFNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

AVAILABLE_AMT

Attribute	Description	
Name	AVAILABLE_AMT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

Acct-Comm-Linkage

Attribute	Description	
Name	Acct-Comm-Linkage	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

CMCURRCOMMREFNO

Attribute	Description	
Name	CMCURRCOMMREFNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

CMNEWCOMMREFNO

Attribute	Description	
Name	CMNEWCOMMREFNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

AVAILABLE_AMT

Attribute	Description	
Name	AVAILABLE_AMT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

Validatn-Msgs

Attribute	Description	
Name	Validatn-Msgs	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ACCTYPE

Attribute	Description	
Name	ACCTYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	2

ACCCUSTNO

Attribute	Description	
Name	ACCCUSTNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	50

ERRCODE

Attribute	Description	
Name	ERRCODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	11

ERRPARAMS

Attribute	Description	
Name	ERRPARAMS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255

MSGTYPE

Attribute	Description	
Name	MSGTYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	E,I,O

MESSAGE

Attribute	Description	
Name	MESSAGE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1000

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description
------------------	--------------------

Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.73.QueryLCHoliday

2.73.1.ST-QueryLCHoliday-Req-IO-MSG.xsd

[*QUERYLCHOLIDAY_IOFS_REQ*](#)

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Lcl-Hol-Master-IO

BRNCODE

YEAR

QUERYLCHOLIDAY_IOFS_REQ

Attribute	Description
Name	QUERYLCHOLIDAY_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

Attribute	Description
Name	Lcl-Hol-Master-IO
Datatype	
Description	Includes the Letter of Credit Holiday Primary Key Type details.

BRNCODE

Attribute	Description				
Name	BRNCODE				
Datatype	String				
Description	Indicates Branch Code				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

YEAR

Attribute	Description
Name	YEAR
Datatype	String
Description	Indicates the Year.

2.73.2.ST-QueryLCHoliday-Res-Full-MSG.xsd

QUERYLCHOLIDAY_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Lcl-Hol-Master-IO

BRNCODE

YEAR

Lcl-Hol-Master-Full

BRNCODE

YEAR

WEEKLYHOLIDAYS

UNEXPHOL

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

Lcl-Holiday

BRNCODE

YEAR

MONTH

HOLIDAYLIST

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYLCHOLIDAY_IOFS_RES

Attribute	Description
Name	QUERYLCHOLIDAY_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullResponse	

Lcl-Hol-Master-IO

Attribute	Description
------------------	--------------------

Name	Lcl-Hol-Master-IO
Datatype	
Description	Includes the Letter of Credit Holiday Primary Key Type details.

BRNCODE

Attribute	Description	
Name	BRNCODE	
Datatype	String	
Description	Indicates Branch Code	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

YEAR

Attribute	Description
Name	YEAR
Datatype	String
Description	Indicates the Year.

Lcl-Hol-Master-Full

Attribute	Description
Name	Lcl-Hol-Master-Full
Datatype	
Description	Includes the Holiday Full Type details.

BRNCODE

Attribute	Description	
Name	BRNCODE	
Datatype	String	
Description	Indicates Branch Code	
Restrictions	Restrictions	Description
	maxLength	3

YEAR

Attribute	Description	
Name	YEAR	
Datatype	String	
Description	Indicates the Year.	
Attribute	Attribute	Description
	minOccurs	0

WEEKLYHOLIDAYS

Attribute	Description
Name	WEEKLYHOLIDAYS
Datatype	String

Description	Indicates the weekly holidays.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	7

UNEXPHOL

Attribute	Description	
Name	UNEXPHOL	
Datatype	String	
Description	Indicates the unexpected Holidays.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Stamp	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	

Description	Indicates Checker ID	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Stamp	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

MODNO

Attribute	Description	
Name	MODNO	
Datatype	String	
Description	Indicates the Modification Number.	
Attribute	Attribute	Description
	minOccurs	0

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	It indicates the Authorisation status	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Auth	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

Lcl-Holiday

Attribute	Description	
Name	Lcl-Holiday	
Datatype		
Description	Includes the Local Holiday.	
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BRNCODE

Attribute	Description	
Name	BRNCODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

YEAR

Attribute	Description	
Name	YEAR	
Datatype	String	
Description	Indicates the Year.	

Attribute		
	Attribute	Description
	minOccurs	0

MONTH

Attribute	Description	
Name	MONTH	
Datatype	String	
Description	Indicates the Month.	
Attribute		
	Attribute	Description
	minOccurs	0

HOLIDAYLIST

Attribute	Description	
Name	HOLIDAYLIST	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	31

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes the UDF Details.	
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	15

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255
	minLength	0

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value Type	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	2
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	
	Description	
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	
	Description	
	maxOccurs	unbounded

WCODE

Attribute	Description
------------------	--------------------

Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.74.QueryLOCHL

2.74.1.ST-QueryLOCHL-Req-IO-MSG.xsd

QUERYLOCHL_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Local-Holiday-Master-IO

BRANCH

YEAR

QUERYLOCHL_IOFS_REQ

Attribute	Description
Name	QUERYLOCHL_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0
	maxOccurs		unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Local-Holiday-Master-IO

Attribute		Description	
Name		Local-Holiday-Master-IO	
Datatype			
Description			

BRANCH

Attribute		Description	
Name		BRANCH	
Datatype		String	
Description			
Restrictions	Restrictions		Description
	maxLength		3

YEAR

Attribute	Description				
Name	YEAR				
Datatype	Decimal				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>4</td></tr></tbody></table>	Restrictions	Description	totalDigits	4
Restrictions	Description				
totalDigits	4				

2.74.2.ST-QueryLOCHL-Res-Full-MSG.xsd

QUERYLOCHL_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Local-Holiday-Master-IO

BRANCH

YEAR

Local-Holiday-Master-Full

BRANCH

YEAR

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Local-Holiday

BRANCH_CODE

YEAR

MONTH

HOLIDAY_LIST

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYLOCHL_IOFS_RES

Attribute	Description
Name	QUERYLOCHL_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Local-Holiday-Master-IO

Attribute	Description
Name	Local-Holiday-Master-IO
Datatype	
Description	

BRANCH

Attribute	Description				
Name	BRANCH				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

YEAR

Attribute	Description				
Name	YEAR				
Datatype	Decimal				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>4</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	4
Restrictions	Description				
totalDigits	4				

Local-Holiday-Master-Full

Attribute	Description
Name	Local-Holiday-Master-Full
Datatype	
Description	

BRANCH

Attribute	Description

Name	BRANCH	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

YEAR

Attribute	Description	
Name	YEAR	
Datatype	Decimal	
Description		
Restrictions		
	Restrictions	Description
	totalDigits	4

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

Local-Holiday

Attribute	Description	
Name	Local-Holiday	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

YEAR

Attribute	Description	
Name	YEAR	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

MONTH

Attribute	Description	
Name	MONTH	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	2

HOLIDAY_LIST

Attribute	Description	
Name	HOLIDAY_LIST	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	31

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute		Description	
Name	FCUBS_ERROR_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

ERROR

Attribute		Description	
Name	ERROR		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

ECODE

Attribute		Description	
Name	ECODE		
Datatype	String		
Description			

EDESC

Attribute		Description	
Name	EDESC		
Datatype	String		
Description			

FCUBS_WARNING_RESP

Attribute		Description	
Name	FCUBS_WARNING_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

WARNING

Attribute		Description	
Name	WARNING		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.75.ReopenAddressCode

2.75.1.ST-ReopenAddressCode-Req-Full-MSG.xsd

REOPENADDRESSCODE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Address-Details-Full

ADDRESS_CODE

MARK_FOR_EXPIRY

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Kanji

English

PIN_CODE

Katakana

Scrp-Add-Detail

SCRIPT_CODE

ADDR1

ADDR2

ADDR3

PIN_CODE

ADDRESS_CODE

PREFECTURE

REOPENADDRESSCODE_FSFS_REQ

Attribute	Description
Name	REOPENADDRESSCODE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Address-Details-Full

Attribute	Description
Name	Address-Details-Full
Datatype	
Description	

ADDRESS_CODE

Attribute	Description				
Name	ADDRESS_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MARK_FOR_EXPIRY

Attribute	Description				
Name	MARK_FOR_EXPIRY				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Y,N</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Kanji

Attribute	Description	
Name	Kanji	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

English

Attribute	Description	
Name	English	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	6

Katakana

Attribute	Description	
Name	Katakana	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0

Scpt-Add-Detail

Attribute	Description	
Name	Scpt-Add-Detail	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

SCRIPT_CODE

Attribute	Description	
Name	SCRIPT_CODE	
Datatype	String	
Description		
Restrictions	Restrictions	
	Description	
	maxLength	8

ADDR1

Attribute	Description	
Name	ADDR1	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

ADDR2

Attribute	Description	
Name	ADDR2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

ADDR3

Attribute	Description	
Name	ADDR3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	15

ADDRESS_CODE

Attribute	Description	
Name	ADDRESS_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	12

PREFECTURE

Attribute	Description	
Name	PREFECTURE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

2.75.2.ST-ReopenAddressCode-Req-IO-MSG.xsd

REOPENADDRESSCODE_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Address-Details-IO

ADDRESS_CODE

MAKER

MAKERSTAMP

MODNO

REOPENADDRESSCODE_IOPK_REQ

Attribute	Description
Name	REOPENADDRESSCODE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
Restrictions	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
Restrictions	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Address-Details-IO

Attribute	Description
Name	Address-Details-IO
Datatype	
Description	

ADDRESS_CODE

Attribute	Description
------------------	--------------------

Name	ADDRESS_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	12

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

2.75.3.ST-ReopenAddressCode-Res-Full-MSG.xsd

REOPENADDRESSCODE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL

PARAM
NAME
VALUE

FCUBS_BODY

Address-Details-Full

ADDRESS_CODE
MARK_FOR_EXPIRY
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT

Kanji
English

PIN_CODE

Katakana

Scrp-Add-Detail

SCRIPT_CODE

ADDR1

ADDR2

ADDR3

PIN_CODE

ADDRESS_CODE

PREFECTURE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

REOPENADDRESSCODE_FSFS_RES

Attribute	Description
Name	REOPENADDRESSCODE_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Address-Details-Full

Attribute	Description
Name	Address-Details-Full
Datatype	
Description	

ADDRESS_CODE

Attribute	Description				
Name	ADDRESS_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

MARK_FOR_EXPIRY

Attribute	Description				
Name	MARK_FOR_EXPIRY				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>	Restrictions	Description	enumeration	Y,N
	Restrictions	Description			
enumeration	Y,N				

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

Kanji

Attribute	Description	
Name	Kanji	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

English

Attribute	Description	
Name	English	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

Katakana

Attribute	Description	
Name	Katakana	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

Scpt-Add-Detail

Attribute	Description	
Name	Scpt-Add-Detail	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

SCRIPT_CODE

Attribute	Description	
Name	SCRIPT_CODE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	8

ADDR1

Attribute	Description	
Name	ADDR1	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	35

ADDR2

Attribute	Description	
Name	ADDR2	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

ADDR3

Attribute	Description	
Name	ADDR3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

PIN_CODE

Attribute	Description	
Name	PIN_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	15

ADDRESS_CODE

Attribute	Description	
Name	ADDRESS_CODE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	12

PREFECTURE

Attribute	Description	
Name	PREFECTURE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description
------------------	--------------------

Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.75.4.ST-ReopenAddressCode-Res-PK-MSG.xsd

REOPENADDRESSCODE_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Address-Details-PK

ADDRESS_CODE

Address-Details-IO

ADDRESS_CODE

MAKER

MAKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

REOPENADDRESSCODE_IOPK_RES

Attribute	Description
Name	REOPENADDRESSCODE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	
-------------	--

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
pattern	[A-Z_0-9]*	

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Address-Details-PK

Attribute	Description
Name	Address-Details-PK
Datatype	
Description	

ADDRESS_CODE

Attribute	Description				
Name	ADDRESS_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

Address-Details-IO

Attribute	Description
Name	Address-Details-IO
Datatype	
Description	

ADDRESS_CODE

Attribute	Description				
Name	ADDRESS_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKER

Attribute	Description
-----------	-------------

Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	



FINANCIAL SERVICES

Gateway Documentation - FCUBSCoreService
[Febraury] [2016]

Oracle Financial services Software Limited
Oracle Park
Off western Express Highway
Goregaon(East)
Mumbai,Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax:+91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2013], [2016], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.